

KATALYST.

Full-Stack Learning & Mentorship Platform

Complete Source Code, System Architecture & File Documentation

PROJECT SUMMARY METRICS

Platform Version:	2.0.0 (Production Architecture)	Backend Framework:	Node.js 20+ / Express.js 5
Frontend Stack:	React 19, Vite, Tailwind CSS	Database:	MongoDB Atlas (Mongoose ORM)
Total Source Files:	99 files included	Security:	JWT Authentication & RBAC
Frontend Files:	52 modules & views	Backend Files:	45 controllers, routes, models

1. Executive Summary

Katalyst is a full-stack educational and mentorship platform engineered to connect students with professional mentors while facilitating structured technical training and career acceleration. The application features three distinct role-based portals (Student, Mentor, Admin), comprehensive training tracks with video lessons and quizzes, 1-on-1 meeting scheduling with Google Meet links, real-time notification drawers, AI-assisted career roadmaps, and resume evaluation.

2. Document Table of Contents

Section	Topic	Coverage
Section 1	Executive Summary & System Architecture	High-level overview & system design
Section 2	Technology Stack & Layer Mapping	Frontend, backend, database, and auth stack
Section 3	Complete File Directory Inventory	All project files categorized with paths & sizes
Section 4	Backend Architecture & Data Models	Mongoose schemas, controllers, and REST routes
Section 5	Frontend Architecture & Portal Pages	React components, state contexts, and routes
Section 6	API Reference & Access Control Matrix	All REST endpoints, request/response models
Section 7	Complete Source Code Listings	Full file contents and implementations

3. Architecture & Technology Stack

Layer	Technology	Role & Purpose
Frontend Core	React 19.0.0 + Vite 8.2.0	Fast modular SPA client with lightning HMR
Styling Framework	Tailwind CSS 3.4 + PostCSS	Custom theme tokens, glassmorphism UI, Dark mode
Routing & Nav	React Router v7	Declarative browser routing & protected role routes
State Management	React Context (Auth & Theme)	Global authentication persistence & theme switches
Data Visualization	Recharts 2.15	Interactive progress rings & readiness index charts
Icons & UI	Lucide React 1.31	Feather-style SVG icon system across all portals
Backend Runtime	Node.js 20+ / Express 5.2	Non-blocking RESTful API & middleware pipeline
Database Store	MongoDB Atlas / Mongoose 9.9	Schema validation, indexing, and object relations
Authentication	JWT (jsonwebtoken 9.0) + bcryptjs	Stateless bearer token authorization & password hashing
AI Services	Google Generative AI (Gemini 1.5)	Resume analysis, personalized roadmaps & chat
File Handling	Multer Middleware	Local disk storage for student PDF resumes
Containerization	Docker & Docker Compose	Multi-stage build Dockerfiles for full-stack isolation

4. Complete File Inventory List

Total registered source and configuration files in this build: 99

Category	Relative File Path	Size
Backend	backend/.env	0.3 KB
Backend	backend/.env.example	0.3 KB
Backend	backend/config/db.js	0.3 KB
Backend	backend/controllers/adminController.js	7.3 KB
Backend	backend/controllers/aiController.js	10.5 KB
Backend	backend/controllers/authController.js	9.1 KB
Backend	backend/controllers/createMentor.js	1.3 KB
Backend	backend/controllers/meetingController.js	6.6 KB
Backend	backend/controllers/mentorController.js	7.2 KB
Backend	backend/controllers/notificationController.js	1.8 KB
Backend	backend/controllers/progressController.js	3.0 KB
Backend	backend/controllers/studentController.js	5.1 KB
Backend	backend/controllers/trainingController.js	7.5 KB
Backend	backend/createMentor.js	0.0 KB
Backend	backend/Dockerfile	0.1 KB
Backend	backend/generate_all_files_pdf.js	22.3 KB
Backend	backend/generate_pdf.js	0.1 KB
Backend	backend/middleware/auth.js	0.6 KB

Category	Relative File Path	Size
Backend	backend/middleware/roleCheck.js	0.3 KB
Backend	backend/models/Admin.js	1.1 KB
Backend	backend/models/Certificate.js	0.7 KB
Backend	backend/models/Feedback.js	0.8 KB
Backend	backend/models/Meeting.js	1.1 KB
Backend	backend/models/Mentor.js	1.7 KB
Backend	backend/models/Notification.js	0.7 KB
Backend	backend/models/Progress.js	1.2 KB
Backend	backend/models/Student.js	1.6 KB
Backend	backend/models/Training.js	1.6 KB
Backend	backend/models/user.js	0.4 KB
Backend	backend/package.json	0.9 KB
Backend	backend/routes/admin.js	0.9 KB
Backend	backend/routes/ai.js	0.6 KB
Backend	backend/routes/auth.js	0.4 KB
Backend	backend/routes/meeting.js	0.9 KB
Backend	backend/routes/mentor.js	0.6 KB
Backend	backend/routes/notification.js	0.4 KB
Backend	backend/routes/progress.js	0.6 KB
Backend	backend/routes/student.js	1.3 KB
Backend	backend/routes/training.js	0.9 KB
Backend	backend/seed.js	3.9 KB
Backend	backend/server.js	2.7 KB
Backend	backend/utlis/generateToken.js	0.2 KB
Backend	backend/utlis/progressCalculator.js	1.5 KB
Backend	backend/utlis/progressService.js	1.7 KB
Backend	backend/utlis/sendEmail.js	2.5 KB
Root Config	docker-compose.yml	0.6 KB
Frontend	frontend/.env.example	0.0 KB
Frontend	frontend/capacitor.config.json	0.1 KB
Frontend	frontend/Dockerfile	0.2 KB
Frontend	frontend/eslint.config.js	0.6 KB
Frontend	frontend/index.html	0.4 KB
Frontend	frontend/package.json	0.5 KB
Frontend	frontend/postcss.config.js	0.1 KB
Frontend	frontend/public/Login.css	2.2 KB
Frontend	frontend/README.md	1.0 KB
Frontend	frontend/src/api.js	0.7 KB
Frontend	frontend/src/App.css	5.6 KB
Frontend	frontend/src/App.jsx	4.4 KB
Frontend	frontend/src/components/CalendarView.jsx	5.0 KB

Category	Relative File Path	Size
Frontend	frontend/src/components/ChatBot.jsx	3.1 KB
Frontend	frontend/src/components/layout/DashboardLayout.jsx	2.5 KB
Frontend	frontend/src/components/layout/Sidebar.jsx	5.6 KB
Frontend	frontend/src/components/NotificationPanel.jsx	2.6 KB
Frontend	frontend/src/components/NotificationsPage.jsx	4.4 KB
Frontend	frontend/src/components/ProtectedRoute.jsx	0.6 KB
Frontend	frontend/src/components/ThemeToggle.jsx	0.4 KB
Frontend	frontend/src/components/ui/StatCard.jsx	0.7 KB
Frontend	frontend/src/context/AuthContext.jsx	1.1 KB
Frontend	frontend/src/context/ThemeContext.jsx	0.7 KB
Frontend	frontend/src/index.css	3.8 KB
Frontend	frontend/src/Login.css	2.2 KB
Frontend	frontend/src/Login.jsx	2.4 KB
Frontend	frontend/src/main.jsx	0.2 KB
Frontend	frontend/src/NotificationDrawer.jsx	0.0 KB
Frontend	frontend/src/pages/admin/Dashboard.jsx	3.6 KB
Frontend	frontend/src/pages/admin/Meetings.jsx	5.3 KB
Frontend	frontend/src/pages/admin/Mentors.jsx	4.1 KB
Frontend	frontend/src/pages/admin/Notifications.jsx	0.2 KB
Frontend	frontend/src/pages/admin/Reports.jsx	3.5 KB
Frontend	frontend/src/pages/admin/Students.jsx	3.7 KB
Frontend	frontend/src/pages/admin/Trainings.jsx	6.5 KB
Frontend	frontend/src/pages/Home.jsx	4.7 KB
Frontend	frontend/src/pages/Login.jsx	9.1 KB
Frontend	frontend/src/pages/mentor/Dashboard.jsx	5.0 KB
Frontend	frontend/src/pages/mentor/Meetings.jsx	6.3 KB
Frontend	frontend/src/pages/mentor/Notifications.jsx	0.2 KB
Frontend	frontend/src/pages/mentor/Students.jsx	4.2 KB
Frontend	frontend/src/pages/Register.jsx	5.4 KB
Frontend	frontend/src/pages/student/AIHub.jsx	8.0 KB
Frontend	frontend/src/pages/student/Certificates.jsx	2.8 KB
Frontend	frontend/src/pages/student/Dashboard.jsx	6.9 KB
Frontend	frontend/src/pages/student/Meetings.jsx	8.9 KB
Frontend	frontend/src/pages/student/Notifications.jsx	0.2 KB
Frontend	frontend/src/pages/student/Profile.jsx	4.6 KB
Frontend	frontend/src/pages/student/TrainingDetail.jsx	7.0 KB
Frontend	frontend/src/pages/student/Trainings.jsx	3.1 KB
Frontend	frontend/tailwind.config.js	0.8 KB
Frontend	frontend/vite.config.js	0.2 KB
Root Config	README.md	2.6 KB

6. API Endpoints Reference

Method	Endpoint Route	Role	Description
POST	/api/auth/register	Public	Student registration with bcrypt hashing
POST	/api/auth/login	Public	Unified login for student, mentor, admin (JWT)
GET	/api/auth/me	Auth	Get active profile based on JWT token
GET	/api/students/profile	Student	Get current student profile & mentor details
PUT	/api/students/profile	Student	Update student bio, skills, and target role
POST	/api/students/resume	Student	Upload student resume PDF via Multer
GET	/api/trainings	Public/Auth	List all available trainings and courses
GET	/api/trainings/:id	Auth	Get course modules, lessons, and student progress
POST	/api/trainings/:id/enroll	Student	Enroll in a training track
POST	/api/trainings/:id/complete-video	Student	Mark video lesson completed & update progress
POST	/api/trainings/:id/submit-quiz	Student	Submit quiz responses & calculate score
GET	/api/meetings/student	Student	Get all meetings booked by student
POST	/api/meetings	Student	Book a new meeting with assigned mentor
GET	/api/meetings/mentor	Mentor	Get all meeting requests assigned to mentor
PUT	/api/meetings/:id/status	Mentor	Approve/Reject meeting and supply Meet link
GET	/api/notifications	Auth	Fetch user notifications list
PUT	/api/notifications/:id/read	Auth	Mark notification as read
POST	/api/ai/resume-analyze	Student	AI resume strength & improvement analysis
POST	/api/ai/career-roadmap	Student	AI personalized milestone career roadmap
POST	/api/ai/chatbot	Auth	AI chatbot assistant for student guidance
GET	/api/admin/stats	Admin	Fetch system-wide metrics, counts & analytics
GET	/api/admin/users	Admin	List and manage all registered users

KATALYST.

Complete Source Code Listings

Generated: 22/8/2026 | Full Project Files

7. Complete Project Source Code

The following sections contain the complete, verbatim source code for each file in the project organized by subsystem.

```
1 | PORT=5000
2 | MONGO_URI=mongodb://127.0.0.1:27017/katalyst
3 | JWT_SECRET=katalyst_super_secret_jwt_key_2026_change_in_production
4 | JWT_EXPIRES_IN=7d
5 | NODE_ENV=development
6 | CLIENT_URL=http://localhost:5173
7 | # Email (Optional - for notifications)
8 | EMAIL_USER=your_email@gmail.com
9 | EMAIL_PASS=your_app_password_here (0.3 KB)
10 | MONGO_URI=mongodb+srv://<username>:<password>@<cluster>.mongodb.net/katalyst?retryWrites=true&w=majority
11 | JWT_SECRET=supersecretkey
12 | JWT_EXPIRES_IN=7d
13 | CLIENT_URL=http://localhost:4173
14 | EMAIL_USER=youremail@example.com
15 | EMAIL_PASS=your-email-password
16 | NODE_ENV=development
17 | PORT=5000 (0.3 KB)
18 |
19 | const mongoose = require("mongoose");
20 | const connectDB = async () => {
21 |   try {
22 |     const conn = await mongoose.connect(process.env.MONGO_URI);
23 |     console.log(` MongoDB Connected: ${conn.connection.host}`);
24 |   } catch (error) {
25 |     console.error(` MongoDB Connection Error: ${error.message}`);
26 |     process.exit(1);
27 |   }
28 | };
29 | module.exports = connectDB; (7.3 KB)
30 |
31 | const Student = require("../models/Student");
32 | const Mentor = require("../models/Mentor");
33 | const Training = require("../models/Training");
34 | const Meeting = require("../models/Meeting");
35 | const Progress = require("../models/Progress");
36 | const Certificate = require("../models/Certificate");
37 | const Notification = require("../models/Notification");
38 | // @desc Admin dashboard analytics
39 | // @route GET /api/admin/dashboard
40 | const getDashboard = async (req, res) => {
41 |   try {
42 |     const [
43 |       totalStudents,
44 |       totalMentors,
45 |       totalTrainings,
46 |       totalMeetings,
47 |       completedMeetings,
48 |       pendingMeetings,
49 |       totalCertificates,
50 |     ] = await Promise.all([
51 |       Student.countDocuments(),
52 |       Mentor.countDocuments(),
53 |       Training.countDocuments(),
54 |       Meeting.countDocuments(),
55 |       Meeting.countDocuments({ status: "completed" }),
56 |       Meeting.countDocuments({ status: "pending" }),
57 |       Certificate.countDocuments(),
58 |     ]);
59 |
60 |     // Monthly student registrations (last 6 months)
61 |     const sixMonthsAgo = new Date();
62 |     sixMonthsAgo.setMonth(sixMonthsAgo.getMonth() - 6);
63 |     const monthlyStudents = await Student.aggregate([
64 |       { $match: { createdAt: { $gte: sixMonthsAgo } } },
65 |       {
66 |         $group: {
```



```
38 |         _id: { $month: "$createdAt" },
39 |         count: { $sum: 1 },
40 |     },
41 | },
42 | { $sort: { _id: 1 } },
43 | ]);
44 |
45 | // Training enrollment stats
46 | const trainingStats = await Training.aggregate([
47 |     {
48 |         $project: {
49 |             title: 1,
50 |             category: 1,
51 |             enrollments: { $size: "$enrolledStudents" },
52 |         },
53 |     },
54 |     { $sort: { enrollments: -1 } },
55 |     { $limit: 5 },
56 | ]);
57 |
58 | res.json({
59 |     stats: {
60 |         totalStudents,
61 |         totalMentors,
62 |         totalTrainings,
63 |         totalMeetings,
64 |         completedMeetings,
65 |         pendingMeetings,
66 |         totalCertificates,
67 |     },
68 |     monthlyStudents,
69 |     topTrainings: trainingStats,
70 | });
71 | } catch (error) {
72 |     res.status(500).json({ message: "Server error", error: error.message });
73 | }
74 | };
75 |
76 | // @desc Get all students
77 | // @route GET /api/admin/students
78 | const getAllStudents = async (req, res) => {
79 |     try {
80 |         const students = await Student.find()
81 |             .select("-password")
82 |             .populate("assignedMentor", "name email")
83 |             .sort({ createdAt: -1 });
84 |         res.json({ students });
85 |     } catch (error) {
86 |         res.status(500).json({ message: "Server error", error: error.message });
87 |     }
88 | };
89 |
90 | // @desc Toggle student active status
91 | // @route PUT /api/admin/students/:id
92 | const updateStudent = async (req, res) => {
93 |     try {
94 |         const { isActive } = req.body;
95 |         const student = await Student.findByIdAndUpdate(
96 |             req.params.id,
97 |             { isActive },
98 |             { new: true }
99 |         ).select("-password");
100 |         res.json({ message: "Student updated", student });
101 |     } catch (error) {
102 |         res.status(500).json({ message: "Server error", error: error.message });
103 |     }
104 | };
105 |
106 | // @desc Delete student
107 | // @route DELETE /api/admin/students/:id
108 | const deleteStudent = async (req, res) => {
109 |     try {
110 |         await Student.findByIdAndDelete(req.params.id);
111 |         await Progress.deleteOne({ studentId: req.params.id });
112 |         res.json({ message: "Student deleted" });
113 |     } catch (error) {
114 |         res.status(500).json({ message: "Server error", error: error.message });
```

```
115 |   }
116 | };
117 |
118 | // @desc Get all mentors
119 | // @route GET /api/admin/mentors
120 | const getAllMentors = async (req, res) => {
121 |   try {
122 |     const mentors = await Mentor.find().select("-password").sort({ createdAt: -1 });
123 |     res.json({ mentors });
124 |   } catch (error) {
125 |     res.status(500).json({ message: "Server error", error: error.message });
126 |   }
127 | };
128 |
129 | // @desc Create mentor (admin only)
130 | // @route POST /api/admin/mentors
131 | const createMentor = async (req, res) => {
132 |   try {
133 |     const { name, email, password, expertise, designation, company, bio } = req.body;
134 |     const exists = await Mentor.findOne({ email });
135 |     if (exists) return res.status(400).json({ message: "Email already registered" });
136 |     const mentor = await Mentor.create({
137 |       name, email, password,
138 |       expertise: expertise ? expertise.split(",").map((s) => s.trim()) : [],
139 |       designation, company, bio,
140 |     });
141 |     res.status(201).json({ message: "Mentor created", mentor: { ...mentor.toObject(), password: undefined } });
142 |   } catch (error) {
143 |     res.status(500).json({ message: "Server error", error: error.message });
144 |   }
145 | };
146 |
147 | // @desc Delete mentor
148 | // @route DELETE /api/admin/mentors/:id
149 | const deleteMentor = async (req, res) => {
150 |   try {
151 |     await Mentor.findByIdAndDelete(req.params.id);
152 |     res.json({ message: "Mentor deleted" });
153 |   } catch (error) {
154 |     res.status(500).json({ message: "Server error", error: error.message });
155 |   }
156 | };
157 |
158 | // @desc Assign mentor to student
159 | // @route POST /api/admin/assign-mentor
160 | const assignMentor = async (req, res) => {
161 |   try {
162 |     const { studentId, mentorId } = req.body;
163 |     const student = await Student.findByIdAndUpdate(
164 |       studentId,
165 |       { assignedMentor: mentorId },
166 |       { new: true }
167 |     ).select("-password");
168 |     await Mentor.findByIdAndUpdate(mentorId, {
169 |       $addToSet: { assignedStudents: studentId },
170 |     });
171 |     const mentor = await Mentor.findById(mentorId);
172 |     // Notify student
173 |     await Notification.create({
174 |       userId: studentId,
175 |       userRole: "student",
176 |       title: "Mentor Assigned! 🎉",
177 |       message: `${mentor.name} has been assigned as your mentor. Say hello!`,
178 |       type: "system",
179 |     });
180 |     res.json({ message: "Mentor assigned successfully", student });
181 |   } catch (error) {
182 |     res.status(500).json({ message: "Server error", error: error.message });
183 |   }
184 | };
185 |
186 | // @desc Get reports
187 | // @route GET /api/admin/reports
188 | const getReports = async (req, res) => {
189 |   try {
190 |     const progressData = await Progress.find()
```

```
197 |     .populate("studentId", "name email")
198 |     .sort({ overallScore: -1 });
200 |     const meetingReport = await Meeting.aggregate([
201 |       { $group: { _id: "$status", count: { $sum: 1 } } },
202 |     ]);
204 |     const categoryEnrollment = await Training.aggregate([
205 |       {
206 |         $group: {
207 |           _id: "$category",
208 |           totalEnrollments: { $sum: { $size: "$enrolledStudents" } },
209 |         },
210 |       },
211 |     ]);
213 |     res.json({ progressData, meetingReport, categoryEnrollment });
214 |   } catch (error) {
215 |     res.status(500).json({ message: "Server error", error: error.message });
216 |   }
217 | };
219 | // @desc Send notification to all users of a role
220 | // @route POST /api/admin/notify
221 | const sendBulkNotification = async (req, res) => {
222 |   try {
223 |     const { title, message, userRole } = req.body;
224 |     let users = [];
225 |     if (userRole === "student") users = await Student.find().select("_id");
226 |     else if (userRole === "mentor") users = await Mentor.find().select("_id");
227 |     else {
228 |       const students = await Student.find().select("_id");
229 |       const mentors = await Mentor.find().select("_id");
230 |       users = [...students, ...mentors];
231 |     }
233 |     const notifications = users.map((u) => ({
234 |       userId: u._id,
235 |       userRole: userRole === "all" ? "student" : userRole,
236 |       title,
237 |       message,
238 |       type: "system",
239 |     }));
241 |     await Notification.insertMany(notifications);
242 |     res.json({ message: `Notification sent to ${users.length} users` });
243 |   } catch (error) {
244 |     res.status(500).json({ message: "Server error", error: error.message });
245 |   }
246 | };
248 | module.exports = {
249 |   getDashboard,
250 |   getAllStudents,
251 |   updateStudent,
252 |   deleteStudent,
253 |   getAllMentors,
254 |   createMentor,
255 |   deleteMentor,
256 |   assignMentor,
257 |   getReports,
258 |   sendBulkNotification,
259 | };
260 |
```

KATALYST

Source Code: backend/controllers/aiController.js

Generated: 22/8/2026 | Backend

(10.5 KB)

```
1 | const Student = require("../models/Student");
2 | const Training = require("../models/Training");
3 | const Progress = require("../models/Progress");
4 | const { GoogleGenerativeAI } = require("@google/generative-ai");
5 |
6 | // Helper to initialize Gemini model
7 | const getGeminiModel = () => {
8 |   const apiKey = process.env.GEMINI_API_KEY;
9 |   if (!apiKey || apiKey.startsWith("your_") || apiKey.includes("change_in_production")) {
10 |     return null;
11 |   }
12 |   try {
13 |     const genAI = new GoogleGenerativeAI(apiKey);
14 |     return genAI.getGenerativeModel({ model: "gemini-1.5-flash" });
15 |   } catch (error) {
16 |     console.error("& p Failed to initialize Google Generative AI:", error.message);
17 |     return null;
18 |   }
19 | };
20 |
21 | // Helper to clean JSON response from Gemini
22 | const cleanJSONResponse = (text) => {
23 |   // Remove markdown block tags if present
24 |   let cleaned = text.trim();
25 |   if (cleaned.startsWith("```")) {
26 |     cleaned = cleaned.replace(/^```json\s*/i, "").replace(/```$/, "").trim();
27 |   }
28 |   return JSON.parse(cleaned);
29 | };
30 |
31 | // @desc Analyze student resume
32 | // @route POST /api/ai/resume-analyze
33 | const analyzeResume = async (req, res) => {
34 |   try {
35 |     const { content } = req.body;
36 |     if (!content) return res.status(400).json({ message: "Resume content is required" });
37 |
38 |     // Try Gemini first
39 |     const model = getGeminiModel();
40 |     if (model) {
41 |       try {
42 |         const prompt = `Analyze the following resume content and output a valid JSON object.
43 | Do NOT wrap the response in markdown blocks (e.g. do not use \`\`\`json). The JSON object must contain exactly
44 | 1. "strengths": An array of strings highlighting the key technical and soft skill strengths.
45 | 2. "improvementAreas": An array of strings listing gaps or areas where the resume or experience can be enhance
46 | 3. "actionItems": An array of actionable steps for the student to improve their placement readiness.
47 | Resume Content:
48 | ${content}`;
49 |
50 |         const result = await model.generateContent(prompt);
51 |         const parsed = cleanJSONResponse(result.response.text());
52 |         return res.json({
53 |           strengths: parsed.strengths || [],
54 |           improvementAreas: parsed.improvementAreas || [],
55 |           actionItems: parsed.actionItems || [],
56 |         });
57 |       } catch (err) {
58 |         console.error("& p Gemini resume analysis failed, falling back to rule-based:", err.message);
59 |       }
60 |     }
61 |
62 |     // Fallback rule-based analysis
63 |     const strengths = [];
64 |     const areas = [];
65 |     const recommendations = [];
66 |
67 |     if (/react|javascript|frontend|html|css/i.test(content)) strengths.push("Frontend development expertise");
68 |     if (/node|express|backend|api/i.test(content)) strengths.push("Backend and API development experience");
69 |     if (/data|sql|mongodb|database/i.test(content)) strengths.push("Data management and database skills");
70 |     if (/design|ui|ux/i.test(content)) strengths.push("UI/UX and product design awareness");
71 |     if (/project/i.test(content)) areas.push("Add project work or portfolio examples");
72 |     if (/github|github\.com/i.test(content)) areas.push("Include GitHub or code repository links");
73 |     if (/lead|team|mentor/i.test(content)) areas.push("Mention collaboration, leadership, or mentorship activ
74 |
75 |     if (/intern|junior|entry/i.test(content)) recommendations.push("Apply to junior and internship roles for f
76 |
77 |     if (!strengths.length) strengths.push("Strong foundational skills are visible.");
78 |     if (!areas.length) areas.push("Highlight measurable impact and completed projects.");
79 |
80 |     res.json({
81 |       strengths,
```

```
82 |     improvementAreas: areas,
83 |     actionItems: [
84 |       "Update resume with specific project accomplishments.",
85 |       "Add portfolio or GitHub links.",
86 |       "Share results and metrics for each learning milestone.",
87 |     ].concat(recommendations),
88 |   });
89 | } catch (error) {
90 |   res.status(500).json({ message: "Server error", error: error.message });
91 | }
92 | };
93 |
94 | // @desc Generate career roadmap
95 | // @route POST /api/ai/career-roadmap
96 | const careerRoadmap = async (req, res) => {
97 |   try {
98 |     const student = await Student.findById(req.user.id).select("name skills assignedMentor");
99 |     const progress = await Progress.findOne({ studentId: req.user.id });
100 |     const enrolledTrainings = await Training.find({ "enrolledStudents.studentId": req.user.id }).select("title
101 |
102 |     // Try Gemini first
103 |     const model = getGeminiModel();
104 |     if (model) {
105 |       try {
106 |         const prompt = `Generate a customized career roadmap for student "${student.name}".
107 | Skills: ${JSON.stringify(student.skills || [])}
108 | Enrolled Courses: ${JSON.stringify(enrolledTrainings.map(t => t.title))}
109 | Placement Readiness: ${progress?.placementReadiness || 0}%
110 |
111 | Output a valid JSON array of objects representing roadmap milestones.
112 | Do NOT wrap the response in markdown blocks (e.g. do not use ```json). Each object must have exactly these
113 | 1. "title": A short title for the milestone.
114 | 2. "description": A brief actionable description of what the student needs to do.
115 | 3. "daysFromNow": An integer representing how many days from today this milestone should ideally be completed.
116 |
117 | Return at least 3 milestones.`;
118 |
119 |         const result = await model.generateContent(prompt);
120 |         const parsed = cleanJSONResponse(result.response.text());
121 |         const roadmap = parsed.map(step => ({
122 |           title: step.title,
123 |           description: step.description,
124 |           dueDate: new Date(Date.now() + (step.daysFromNow || 14) * 24 * 60 * 60 * 1000),
125 |         }));
126 |
127 |         return res.json({
128 |           student: student.name,
129 |           skills: student.skills,
130 |           currentMentor: student.assignedMentor || null,
131 |           trainings: enrolledTrainings,
132 |           roadmap,
133 |         });
134 |       } catch (err) {
135 |         console.error("& p Gemini roadmap generation failed, falling back:", err.message);
136 |       }
137 |     }
138 |
139 |     // Fallback roadmap
140 |     const roadmap = [
141 |       {
142 |         title: "Strengthen foundational skills",
143 |         description: "Complete active trainings and finish remaining video modules.",
144 |         dueDate: new Date(Date.now() + 14 * 24 * 60 * 60 * 1000),
145 |       },
146 |       {
147 |         title: "Book mentor reviews",
148 |         description: "Schedule at least two mentoring sessions focused on projects and resume readiness.",
149 |         dueDate: new Date(Date.now() + 21 * 24 * 60 * 60 * 1000),
150 |       },
151 |       {
152 |         title: "Build a portfolio project",
153 |         description: "Create one end-to-end project using current learning topics and publish it on GitHub.",
154 |         dueDate: new Date(Date.now() + 35 * 24 * 60 * 60 * 1000),
155 |       },
156 |     ];
157 |
158 |     if (progress && progress.placementReadiness < 60) {
159 |       roadmap.push({
160 |         title: "Raise placement readiness",
```

```
161 |         description: "Focus on quizzes, mentor feedback, and resume improvements to reach 70+ readiness.",
162 |         dueDate: new Date(Date.now() + 45 * 24 * 60 * 60 * 1000),
163 |     });
164 | }
165 |
166 | res.json({
167 |     student: student.name,
168 |     skills: student.skills,
169 |     currentMentor: student.assignedMentor || null,
170 |     trainings: enrolledTrainings,
171 |     roadmap,
172 | });
173 | } catch (error) {
174 |     res.status(500).json({ message: "Server error", error: error.message });
175 | }
176 | };
177 |
178 | // @desc Scholarship recommendations
179 | // @route POST /api/ai/scholarships
180 | const scholarshipRecommendations = async (req, res) => {
181 |     try {
182 |         const { interests = [] } = req.body;
183 |         // Try Gemini first
184 |         const model = getGeminiModel();
185 |         if (model) {
186 |             try {
187 |                 const prompt = `Recommend targeted scholarships for a student with interests: ${JSON.stringify(interests)}
188 | Output a valid JSON array of objects representing recommended scholarships.
189 | Do NOT wrap the response in markdown blocks (e.g. do not use \`\`\`json). Each object must have exactly these
190 | 1. "name": The name of the scholarship.
191 | 2. "description": A description of the scholarship, eligibility requirements, and value.
192 | 3. "category": The scholarship category (e.g. Technology, Diversity, AI/ML, General).
193 | Return at least 3 recommendations.`;
194 |
195 |                 const result = await model.generateContent(prompt);
196 |                 const parsed = cleanJSONResponse(result.response.text());
197 |                 return res.json({ recommendations: parsed });
198 |             } catch (err) {
199 |                 console.error("& p Gemini scholarship search failed, falling back:", err.message);
200 |             }
201 |         }
202 |         // Fallback scholarship logic
203 |         const recommendations = [
204 |             {
205 |                 name: "Future Leaders Scholarship",
206 |                 description: "Designed for students building strong full-stack portfolios.",
207 |                 category: "Technology",
208 |             },
209 |             {
210 |                 name: "Women in Tech Assistance",
211 |                 description: "Support for female learners focusing on coding and mentorship.",
212 |                 category: "Diversity",
213 |             },
214 |             {
215 |                 name: "AI Learning Grant",
216 |                 description: "For students preparing for machine learning or data science pathways.",
217 |                 category: "AI/ML",
218 |             },
219 |         ];
220 |         const filtered = interests.length
221 |             ? recommendations.filter((r) =>
222 |                 interests.some((interest) => r.category.toLowerCase().includes(interest.toLowerCase()))
223 |             )
224 |             : recommendations;
225 |         res.json({ recommendations: filtered.length ? filtered : recommendations });
226 |     } catch (error) {
227 |         res.status(500).json({ message: "Server error", error: error.message });
228 |     }
229 | };
230 |
231 | // @desc AI Assistant Chatbot
232 | // @route POST /api/ai/chatbot
233 | const assistantChat = async (req, res) => {
234 |     try {
235 |         const { question } = req.body;
```

```
241 |     if (!question) return res.status(400).json({ message: "Question is required" });
243 |     // Try Gemini first
244 |     const model = getGeminiModel();
245 |     if (model) {
246 |       try {
247 |         const prompt = `You are "Katalyst AI", a helpful, friendly, and smart career and learning assistant on
248 | Provide a concise, encouraging, and actionable answer to the student's question under 120 words.
250 | Student Question: "${question}"`;
252 |         const result = await model.generateContent(prompt);
253 |         return res.json({ answer: result.response.text().trim() });
254 |       } catch (err) {
255 |         console.error("& p Gemini chatbot failed, falling back:", err.message);
256 |       }
257 |     }
259 |     // Fallback chatbot answer
260 |     const answer = `Hi there! I am Katalyst AI (fallback mode).
261 | To help with your query: "${question}" – we recommend scheduling a session with your assigned mentor, finishin
262 | res.json({ answer });
263 |   } catch (error) {
264 |     res.status(500).json({ message: "Server error", error: error.message });
265 |   }
266 | };
268 | module.exports = { analyzeResume, careerRoadmap, scholarshipRecommendations, assistantChat };
269 |
1 | const Student = require("../models/Student");
2 | const Mentor = require("../models/Mentor");
3 | const Admin = require("../models/Admin");
4 | const Progress = require("../models/Progress");
5 | const Notification = require("../models/Notification");
6 | const generateToken = require("../utils/generateToken");
8 | // =====
9 | // REGISTER STUDENT
10 | // POST /api/auth/register
11 | // =====
12 | // =====
13 | // REGISTER USER (Student, Mentor, or Admin)
14 | // POST /api/auth/register
15 | // =====
16 | const registerStudent = async (req, res) => {
17 |   try {
18 |     console.log("REGISTER REQUEST:", req.body);
20 |     const { name, email, password, phone, role = "student" } = req.body;
22 |     // Validate required fields
23 |     if (!name || !email || !password) {
24 |       return res.status(400).json({
25 |         message: "Name, email and password are required",
26 |       });
27 |     }
29 |     // Clean email
30 |     const cleanEmail = email.trim().toLowerCase();
31 |     const targetRole = ["student", "mentor", "admin"].includes(role) ? role : "student";
33 |     // Check existing across all collections
34 |     const [existingStudent, existingMentor, existingAdmin] = await Promise.all([
35 |       Student.findOne({ email: cleanEmail }),
36 |       Mentor.findOne({ email: cleanEmail }),
37 |       Admin.findOne({ email: cleanEmail }),
38 |     ]);
40 |     if (existingStudent || existingMentor || existingAdmin) {
41 |       return res.status(400).json({
42 |         message: "Email already registered",
43 |       });
44 |     }
46 |     let newUser;
48 |     if (targetRole === "admin") {
49 |       newUser = await Admin.create({
50 |         name: name.trim(),
51 |         email: cleanEmail,
52 |         password,
53 |       });
54 |     } else if (targetRole === "mentor") {
```

```
55 |         newUser = await Mentor.create({
56 |             name: name.trim(),
57 |             email: cleanEmail,
58 |             password,
59 |             phone: phone || "",
60 |             expertise: ["Web Development", "Mentorship"],
61 |             designation: "Senior Mentor",
62 |             company: "Katalyst",
63 |         });
64 |     } else {
65 |         newUser = await Student.create({
66 |             name: name.trim(),
67 |             email: cleanEmail,
68 |             password,
69 |             phone: phone || "",
70 |         });
71 |         // Create progress & welcome notification for student
72 |         try {
73 |             await Progress.create({ studentId: newUser._id });
74 |         } catch (err) {}
75 |         try {
76 |             await Notification.create({
77 |                 userId: newUser._id,
78 |                 userRole: "student",
79 |                 title: "Welcome to Katalyst! 🎉",
80 |                 message: "Your account is ready. Start exploring trainings and book your first mentorship session!",
81 |                 type: "system",
82 |             });
83 |         } catch (err) {}
84 |     }
85 |     console.log("USER CREATED:", newUser._id, targetRole);
86 |     return res.status(201).json({
87 |         message: "Registration successful",
88 |         token: generateToken(newUser._id, targetRole),
89 |         user: {
90 |             id: newUser._id,
91 |             name: newUser.name,
92 |             email: newUser.email,
93 |             role: targetRole,
94 |             profilePic: newUser.profilePic || "",
95 |         },
96 |     });
97 | } catch (error) {
98 |     console.error("REGISTER ERROR:", error);
99 |     return res.status(500).json({
100 |         message: "Registration failed",
101 |         error: error.message,
102 |     });
103 | }
104 | };
105 |
106 | // =====
107 | // LOGIN (With Multi-Role Auto-Provisioning on Valid Password)
108 | // POST /api/auth/login
109 | // =====
110 | const login = async (req, res) => {
111 |     try {
112 |         console.log("LOGIN REQUEST:", req.body);
113 |         const { email, password, role } = req.body;
114 |         if (!email || !password) {
115 |             return res.status(400).json({
116 |                 message: "Email and password are required",
117 |             });
118 |         }
119 |         const cleanEmail = email.trim().toLowerCase();
120 |         const cleanPass = password.trim();
121 |         const targetRole = role || "student";
122 |         // 1. Search across all collections for existing account
123 |         let student = await Student.findOne({ email: cleanEmail });
124 |         let mentor = await Mentor.findOne({ email: cleanEmail });
125 |         let admin = await Admin.findOne({ email: cleanEmail });
126 |         let existingUser = student || mentor || admin;
```



```
137 | // Not found anywhere
138 | if (!existingUser) {
139 |   return res.status(401).json({
140 |     message: `No account registered with ${cleanEmail}. Please create an account first.`,
141 |   });
142 | }
143 |
144 | // 2. Check password against existing user
145 | if (!existingUser.matchPassword) {
146 |   return res.status(500).json({
147 |     message: "Password authentication misconfigured in user model",
148 |   });
149 | }
150 |
151 | const passwordCorrect = await existingUser.matchPassword(cleanPass);
152 |
153 | if (!passwordCorrect) {
154 |   return res.status(401).json({
155 |     message: "Incorrect password. Please try again or click Forgot Password.",
156 |   });
157 | }
158 |
159 | // 3. Password is valid! Provision/Resolve target role profile if needed
160 | let userToLogin = null;
161 | let actualRole = targetRole;
162 |
163 | if (targetRole === "admin") {
164 |   if (!admin) {
165 |     admin = await Admin.create({
166 |       name: existingUser.name,
167 |       email: cleanEmail,
168 |       password: cleanPass,
169 |     });
170 |   }
171 |   userToLogin = admin;
172 |   actualRole = "admin";
173 | } else if (targetRole === "mentor") {
174 |   if (!mentor) {
175 |     mentor = await Mentor.create({
176 |       name: existingUser.name,
177 |       email: cleanEmail,
178 |       password: cleanPass,
179 |       phone: existingUser.phone || "",
180 |       expertise: ["Web Development", "Mentorship"],
181 |       designation: "Senior Mentor",
182 |       company: "Katalyst",
183 |     });
184 |   }
185 |   userToLogin = mentor;
186 |   actualRole = "mentor";
187 | } else {
188 |   if (!student) {
189 |     student = await Student.create({
190 |       name: existingUser.name,
191 |       email: cleanEmail,
192 |       password: cleanPass,
193 |       phone: existingUser.phone || "",
194 |     });
195 |     try { await Progress.create({ studentId: student._id }); } catch (err) {}
196 |   }
197 |   userToLogin = student;
198 |   actualRole = "student";
199 | }
200 |
201 | // Check active state
202 | if (!userToLogin.isActive && actualRole !== "admin") {
203 |   return res.status(403).json({
204 |     message: "Account is deactivated",
205 |   });
206 | }
207 |
208 | // Update student last login
209 | if (actualRole === "student") {
210 |   userToLogin.lastLogin = new Date();
211 |   await userToLogin.save();
212 | }
213 |
214 | // Generate JWT with actualRole
215 | const token = generateToken(userToLogin._id, actualRole);
```

```
217 |     console.log("LOGIN SUCCESS:", userToLogin.email, actualRole);
219 |     return res.status(200).json({
220 |       message: "Login successful",
221 |       token,
222 |       user: {
223 |         id: userToLogin._id,
224 |         name: userToLogin.name,
225 |         email: userToLogin.email,
226 |         role: actualRole,
227 |         profilePic: userToLogin.profilePic || "",
228 |       },
229 |     });
230 |   } catch (error) {
231 |     console.error("LOGIN ERROR:", error);
232 |     return res.status(500).json({
233 |       message: "Login failed",
234 |       error: error.message,
235 |     });
236 |   }
237 | };
239 | // =====
240 | // GET CURRENT USER
241 | // GET /api/auth/me
242 | // =====
243 | const getMe = async (req, res) => {
244 |   try {
245 |     const { id, role } = req.user;
247 |     let user;
249 |     if (role === "student") {
250 |       user = await Student.findById(id)
251 |         .select("-password")
252 |         .populate(
253 |           "assignedMentor",
254 |           "name email expertise profilePic"
255 |         );
256 |     } else if (role === "mentor") {
257 |       user = await Mentor.findById(id).select("-password");
258 |     } else if (role === "admin") {
259 |       user = await Admin.findById(id).select("-password");
260 |     } else {
261 |       return res.status(400).json({
262 |         message: "Invalid user role",
263 |       });
264 |     }
266 |     if (!user) {
267 |       return res.status(404).json({
268 |         message: "User not found",
269 |       });
270 |     }
272 |     return res.status(200).json({
273 |       user: {
274 |         ...user.toObject(),
275 |         role,
276 |       },
277 |     });
278 |   } catch (error) {
279 |     console.error("GET ME ERROR:", error);
281 |     return res.status(500).json({
282 |       message: "Server error",
283 |       error: error.message,
284 |     });
285 |   }
286 | };
288 | // =====
289 | // RESET PASSWORD
290 | // POST /api/auth/reset-password
291 | // =====
292 | const resetPassword = async (req, res) => {
293 |   try {
294 |     const { email, newPassword } = req.body;
295 |     if (!email || !newPassword) {
```

```
296 |     return res.status(400).json({ message: "Email and new password are required" });
297 |   }
299 |   const cleanEmail = email.trim().toLowerCase();
301 |   const [student, mentor, admin] = await Promise.all([
302 |     Student.findOne({ email: cleanEmail }),
303 |     Mentor.findOne({ email: cleanEmail }),
304 |     Admin.findOne({ email: cleanEmail }),
305 |   ]);
307 |   const targetUser = student || mentor || admin;
309 |   if (!targetUser) {
310 |     return res.status(404).json({ message: "No account found with this email" });
311 |   }
313 |   targetUser.password = newPassword;
314 |   await targetUser.save();
316 |   return res.json({ message: "Password reset successful! You can now log in." });
317 | } catch (error) {
318 |   return res.status(500).json({ message: "Server error", error: error.message });
319 | }
320 | };
322 | module.exports = {
323 |   registerStudent,
324 |   login,
325 |   getMe,
326 |   resetPassword,
327 | }; (1.3 KB)

1 | const mongoose = require("mongoose");
2 | const Mentor = require("../models/Mentor");
3 | require("dotenv").config();
5 | async function createMentor() {
6 |   try {
7 |     await mongoose.connect(process.env.MONGO_URI);
9 |     console.log("MongoDB connected");
11 |     const email = "sarah@katalyst.io";
13 |     const existing = await Mentor.findOne({ email });
15 |     if (existing) {
16 |       console.log("Mentor already exists:", existing.email);
17 |       await mongoose.disconnect();
18 |       return;
19 |     }
21 |     const mentor = await Mentor.create({
22 |       name: "Sarah Mentor",
23 |       email: "sarah@katalyst.io",
24 |       password: "Mentor@123",
25 |       phone: "9876543210",
26 |       bio: "Experienced Katalyst mentor",
27 |       profilePic: "",
28 |       expertise: ["Web Development", "JavaScript", "React"],
29 |       designation: "Senior Mentor",
30 |       company: "Katalyst",
31 |       role: "mentor",
32 |       isActive: true,
33 |       assignedStudents: [],
34 |       rating: 0,
35 |       totalRatings: 0,
36 |       availability: [],
37 |     });
39 |     console.log("MENTOR CREATED");
40 |     console.log("Email:", mentor.email);
41 |     console.log("Password: Mentor@123");
43 |     await mongoose.disconnect();
44 |   } catch (error) {
45 |     console.error("L ERROR:", error.message);
46 |     process.exit(1);
47 |   }
48 | }
50 | createMentor();
```

(6.6 KB)

```
1 | const Meeting = require("../models/Meeting");
2 | const Mentor = require("../models/Mentor");
3 | const Student = require("../models/Student");
4 | const Notification = require("../models/Notification");
5 |
6 | // @desc Book a meeting
7 | // @route POST /api/meetings
8 | const bookMeeting = async (req, res) => {
9 |   try {
10 |     const { mentorId, topic, agenda, scheduledDate, scheduledTime, duration, meetLink } = req.body;
11 |     let resolvedMentorId = mentorId;
12 |     if (!resolvedMentorId) {
13 |       const student = await Student.findById(req.user.id);
14 |       resolvedMentorId = student?.assignedMentor;
15 |     }
16 |     if (!resolvedMentorId) {
17 |       // Fallback: pick the first available mentor in the DB
18 |       const fallbackMentor = await Mentor.findOne();
19 |       if (fallbackMentor) {
20 |         resolvedMentorId = fallbackMentor._id;
21 |       }
22 |     }
23 |   }
24 |   if (!resolvedMentorId) {
25 |     return res.status(400).json({ message: "No mentor available in platform. Please contact admin." });
26 |   }
27 |   const mentor = await Mentor.findById(resolvedMentorId);
28 |   if (!mentor) return res.status(404).json({ message: "Mentor not found" });
29 |   // Auto-generate Google Meet link if not provided
30 |   const randomCode = Math.random().toString(36).substring(2, 5) + "-" + Math.random().toString(36).substring(2, 5);
31 |   const generatedMeetLink = meetLink || `https://meet.google.com/${randomCode}`;
32 |   const meeting = await Meeting.create({
33 |     studentId: req.user.id,
34 |     mentorId: resolvedMentorId,
35 |     topic,
36 |     agenda,
37 |     scheduledDate,
38 |     scheduledTime,
39 |     duration: duration || 60,
40 |     meetLink: generatedMeetLink,
41 |     status: "accepted", // Auto-confirm with meet link
42 |   });
43 |   // Notify mentor with Google Meet link
44 |   await Notification.create({
45 |     userId: resolvedMentorId,
46 |     userRole: "mentor",
47 |     title: "New Meeting Scheduled ðŸ“œ",
48 |     message: `Meeting on "${topic}" scheduled. Google Meet: ${generatedMeetLink}`,
49 |     type: "meeting",
50 |   });
51 |   // Notify student with Google Meet link
52 |   await Notification.create({
53 |     userId: req.user.id,
54 |     userRole: "student",
55 |     title: "Meeting Confirmed & Google Meet Ready! ðŸ“œ",
56 |     message: `Your meeting on "${topic}" is set for ${scheduledDate} at ${scheduledTime}. Google Meet Link: ${generatedMeetLink}`,
57 |     type: "meeting",
58 |   });
59 |   res.status(201).json({ message: "Meeting scheduled with Google Meet link!", meeting });
60 | } catch (error) {
61 |   res.status(500).json({ message: "Server error", error: error.message });
62 | }
63 | };
64 |
65 | // @desc Get student meetings
66 | // @route GET /api/meetings/student
67 | const getStudentMeetings = async (req, res) => {
68 |   try {
69 |     const { status } = req.query;
70 |     const filter = { studentId: req.user.id };
71 |     if (status) filter.status = status;
72 |     const meetings = await Meeting.find(filter)
73 |       .populate("mentorId", "name email profilePic designation company")
74 |       .sort({ scheduledDate: -1 });
75 |   } catch (error) {
76 |     res.status(500).json({ message: "Server error", error: error.message });
77 |   }
78 | };
```

```
83 |     res.json({ meetings });
84 |   } catch (error) {
85 |     res.status(500).json({ message: "Server error", error: error.message });
86 |   }
87 | };
88 |
89 | // @desc Get mentor meetings
90 | // @route GET /api/meetings/mentor
91 | const getMentorMeetings = async (req, res) => {
92 |   try {
93 |     const { status } = req.query;
94 |     const filter = { mentorId: req.user.id };
95 |     if (status) filter.status = status;
96 |
97 |     const meetings = await Meeting.find(filter)
98 |       .populate("studentId", "name email profilePic phone")
99 |       .sort({ scheduledDate: -1 });
100 |
101 |     res.json({ meetings });
102 |   } catch (error) {
103 |     res.status(500).json({ message: "Server error", error: error.message });
104 |   }
105 | };
106 |
107 | // @desc Update meeting status
108 | // @route PUT /api/meetings/:id/status
109 | const updateMeetingStatus = async (req, res) => {
110 |   try {
111 |     const { status, rejectionReason, meetLink } = req.body;
112 |     const defaultMeetLink = meetLink || "https://meet.google.com/katalyst-session";
113 |
114 |     const updateObj = { status, rejectionReason: rejectionReason || "" };
115 |     if (status === "accepted") {
116 |       updateObj.meetLink = defaultMeetLink;
117 |     }
118 |
119 |     const meeting = await Meeting.findByIdAndUpdate(
120 |       req.params.id,
121 |       updateObj,
122 |       { new: true }
123 |     ).populate("mentorId", "name");
124 |
125 |     if (meeting) {
126 |       await Notification.create({
127 |         userId: meeting.studentId,
128 |         userRole: "student",
129 |         title: `Meeting ${status === "accepted" ? "Accepted" : status === "rejected" ? "Declined" : "Updated"}`,
130 |         message: `Your meeting "${meeting.topic}" has been ${status}${status === "accepted" ? ". Link: ${defaultMeetLink}" : ""}`,
131 |         type: "meeting",
132 |       });
133 |     }
134 |
135 |     res.json({ message: "Meeting updated", meeting });
136 |   } catch (error) {
137 |     res.status(500).json({ message: "Server error", error: error.message });
138 |   }
139 | };
140 |
141 | // @desc Submit student feedback for meeting
142 | // @route POST /api/meetings/:id/feedback
143 | const submitStudentFeedback = async (req, res) => {
144 |   try {
145 |     const { rating, comment } = req.body;
146 |     const meeting = await Meeting.findByIdAndUpdate(
147 |       req.params.id,
148 |       {
149 |         "studentFeedback.rating": rating,
150 |         "studentFeedback.comment": comment,
151 |         "studentFeedback.givenAt": new Date(),
152 |       },
153 |       { new: true }
154 |     );
155 |
156 |     // Update mentor rating
157 |     const mentor = await Mentor.findById(meeting.mentorId);
158 |     const newTotal = mentor.totalRatings + 1;
159 |     const newRating = ((mentor.rating * mentor.totalRatings) + rating) / newTotal;
160 |     await Mentor.findByIdAndUpdate(meeting.mentorId, {
161 |       rating: Math.round(newRating * 10) / 10,
162 |       totalRatings: newTotal,
163 |     });
164 |   }
165 | }
```

```
165 |     res.json({ message: "Feedback submitted", meeting });
166 |   } catch (error) {
167 |     res.status(500).json({ message: "Server error", error: error.message });
168 |   }
169 | };
171 | // @desc Cancel meeting
172 | // @route DELETE /api/meetings/:id
173 | const cancelMeeting = async (req, res) => {
174 |   try {
175 |     const meeting = await Meeting.findById(req.params.id);
176 |     if (!meeting) return res.status(404).json({ message: "Meeting not found" });
177 |     meeting.status = "cancelled";
178 |     await meeting.save();
179 |     res.json({ message: "Meeting cancelled" });
180 |   } catch (error) {
181 |     res.status(500).json({ message: "Server error", error: error.message });
182 |   }
183 | };
185 | // @desc Get all meetings (admin)
186 | // @route GET /api/meetings/admin
187 | const getAllMeetingsAdmin = async (req, res) => {
188 |   try {
189 |     const meetings = await Meeting.find({})
190 |       .populate("studentId", "name email profilePic")
191 |       .populate("mentorId", "name email profilePic designation")
192 |       .sort({ scheduledDate: -1 });
194 |     res.json({ meetings });
195 |   } catch (error) {
196 |     res.status(500).json({ message: "Server error", error: error.message });
197 |   }
198 | };
200 | module.exports = {
201 |   bookMeeting,
202 |   getStudentMeetings,
203 |   getMentorMeetings,
204 |   getAllMeetingsAdmin,
205 |   updateMeetingStatus,
206 |   submitStudentFeedback,
207 |   cancelMeeting,
208 | };
209 |
210 | const Mentor = require("../models/Mentor");
211 | const Student = require("../models/Student");
212 | const Meeting = require("../models/Meeting");
213 | const Progress = require("../models/Progress");
214 | const Feedback = require("../models/Feedback");
215 | const Notification = require("../models/Notification");
216 | const { sendEmail, meetingAcceptedEmail, meetingRejectedEmail } = require("../utils/sendEmail");
217 |
218 | // @desc Get mentor dashboard
219 | // @route GET /api/mentors/dashboard
220 | const getDashboard = async (req, res) => {
221 |   try {
222 |     const mentor = await Mentor.findById(req.user.id)
223 |       .select("-password")
224 |       .populate("assignedStudents", "name email profilePic lastLogin");
225 |     const pendingMeetings = await Meeting.find({
226 |       mentorId: req.user.id,
227 |       status: "pending",
228 |     })
229 |       .populate("studentId", "name email profilePic")
230 |       .sort({ createdAt: -1 });
231 |     const upcomingMeetings = await Meeting.find({
232 |       mentorId: req.user.id,
233 |       status: "accepted",
234 |       scheduledDate: { $gte: new Date() },
235 |     })
236 |       .populate("studentId", "name email profilePic")
237 |       .sort({ scheduledDate: 1 })
238 |       .limit(5);
239 |     const completedMeetings = await Meeting.countDocuments({
240 |       mentorId: req.user.id,
```

```
35 |         status: "completed",
36 |     });
37 |
38 |     res.json({
39 |         mentor,
40 |         pendingMeetings,
41 |         upcomingMeetings,
42 |         stats: {
43 |             totalStudents: mentor.assignedStudents.length,
44 |             pendingRequests: pendingMeetings.length,
45 |             completedMeetings,
46 |             rating: mentor.rating,
47 |         },
48 |     });
49 | } catch (error) {
50 |     res.status(500).json({ message: "Server error", error: error.message });
51 | }
52 | };
53 |
54 | // @desc Get assigned students with progress
55 | // @route GET /api/mentors/students
56 | const getStudents = async (req, res) => {
57 |     try {
58 |         const mentor = await Mentor.findById(req.user.id).populate(
59 |             "assignedStudents",
60 |             "name email profilePic phone skills bio lastLogin"
61 |         );
62 |         const studentsWithProgress = await Promise.all(
63 |             mentor.assignedStudents.map(async (student) => {
64 |                 const progress = await Progress.findOne({ studentId: student._id });
65 |                 return { ...student.toObject(), progress };
66 |             })
67 |         );
68 |         res.json({ students: studentsWithProgress });
69 |     } catch (error) {
70 |         res.status(500).json({ message: "Server error", error: error.message });
71 |     }
72 | };
73 |
74 | // @desc Accept or reject meeting
75 | // @route PUT /api/mentors/meeting/:id
76 | const respondToMeeting = async (req, res) => {
77 |     try {
78 |         const { status, rejectionReason } = req.body;
79 |         const meeting = await Meeting.findById(req.params.id).populate(
80 |             "studentId",
81 |             "name email"
82 |         );
83 |         if (!meeting) {
84 |             return res.status(404).json({ message: "Meeting not found" });
85 |         }
86 |         if (meeting.mentorId.toString() !== req.user.id) {
87 |             return res.status(403).json({ message: "Not authorized" });
88 |         }
89 |         meeting.status = status;
90 |         if (status === "rejected") meeting.rejectionReason = rejectionReason || "";
91 |         if (status === "accepted") {
92 |             meeting.meetLink = `https://meet.google.com/${Math.random().toString(36).substr(2, 10)}`;
93 |             await meeting.save();
94 |             if (status === "accepted") {
95 |                 await Progress.findOneAndUpdate(
96 |                     { studentId: meeting.studentId._id },
97 |                     { $inc: { totalMeetingsScheduled: 1 } },
98 |                     { upsert: true, new: true }
99 |                 );
100 |                 const { syncStudentProgress } = require("../utils/progressService");
101 |                 await syncStudentProgress(meeting.studentId._id);
102 |             }
103 |             const mentor = await Mentor.findById(req.user.id).select("name");
104 |             // Notify student
105 |             await Notification.create({
106 |                 userId: meeting.studentId._id,
107 |                 userRole: "student",
108 |                 title: status === "accepted" ? "Meeting Accepted! " : "Meeting Update",
109 |                 message:
```

KATALYST

Source Code: backend/controllers/mentorController.js (Cont.)

Generated: 22/8/2026 | Backend

```
117 |         status === "accepted"
118 |         ? `${mentor.name} accepted your meeting request. Check your schedule!`
119 |         : `Your meeting request was not accepted. Reason: ${rejectionReason || "Not specified"}`,
120 |         type: "meeting",
121 |     });
122 |     // Send email
123 |     if (status === "accepted") {
124 |         await sendEmail({
125 |             to: meeting.studentId.email,
126 |             subject: "Katalyst - Meeting Confirmed!",
127 |             html: meetingAcceptedEmail(
128 |                 meeting.studentId.name,
129 |                 mentor.name,
130 |                 new Date(meeting.scheduledDate).toDateString(),
131 |                 meeting.scheduledTime,
132 |                 meeting.meetLink
133 |             ),
134 |         });
135 |     } else if (status === "rejected") {
136 |         await sendEmail({
137 |             to: meeting.studentId.email,
138 |             subject: "Katalyst - Meeting Update",
139 |             html: meetingRejectedEmail(meeting.studentId.name, mentor.name, rejectionReason),
140 |         });
141 |     }
142 |     res.json({ message: `Meeting ${status}`, meeting });
143 | } catch (error) {
144 |     res.status(500).json({ message: "Server error", error: error.message });
145 | }
146 | };
147 |
148 | // @desc Add meeting notes
149 | // @route POST /api/mentors/meeting/:id/notes
150 | const addMeetingNotes = async (req, res) => {
151 |     try {
152 |         const { notes } = req.body;
153 |         const meeting = await Meeting.findById(req.params.id);
154 |         if (!meeting) return res.status(404).json({ message: "Meeting not found" });
155 |         meeting.notes = notes;
156 |         meeting.status = "completed";
157 |         await meeting.save();
158 |         // Update attendance
159 |         await Progress.findOneAndUpdate(
160 |             { studentId: meeting.studentId },
161 |             { $inc: { meetingsAttended: 1 } }
162 |         );
163 |         const { syncStudentProgress } = require("../utils/progressService");
164 |         await syncStudentProgress(meeting.studentId);
165 |         res.json({ message: "Notes added and meeting marked complete", meeting });
166 |     } catch (error) {
167 |         res.status(500).json({ message: "Server error", error: error.message });
168 |     }
169 | };
170 |
171 | // @desc Give feedback/rating to student
172 | // @route POST /api/mentors/feedback
173 | const giveFeedback = async (req, res) => {
174 |     try {
175 |         const { studentId, meetingId, rating, comment } = req.body;
176 |         const feedback = await Feedback.create({
177 |             fromId: req.user.id,
178 |             fromRole: "mentor",
179 |             toId: studentId,
180 |             toRole: "student",
181 |             meetingId,
182 |             rating,
183 |             comment,
184 |             type: "meeting",
185 |         });
186 |         // Save mentor feedback on meeting
187 |         await Meeting.findByIdAndUpdate(meetingId, {
188 |             "mentorFeedback.rating": rating,
189 |             "mentorFeedback.comment": comment,
```



```
198 |     "mentorFeedback.givenAt": new Date(),
199 |   });
200 |
201 |   await Notification.create({
202 |     userId: studentId,
203 |     userRole: "student",
204 |     title: "New Feedback Received +P",
205 |     message: `Your mentor has given you a ${rating}/5 rating. Check your feedback section.`,
206 |     type: "feedback",
207 |   });
208 |
209 |   const { syncStudentProgress } = require("../utils/progressService");
210 |   await syncStudentProgress(studentId);
211 |
212 |   res.json({ message: "Feedback submitted", feedback });
213 | } catch (error) {
214 |   res.status(500).json({ message: "Server error", error: error.message });
215 | }
216 | };
217 |
218 | // @desc Get all meetings for mentor
219 | // @route GET /api/mentors/meetings
220 | const getMeetings = async (req, res) => {
221 |   try {
222 |     const meetings = await Meeting.find({ mentorId: req.user.id })
223 |       .populate("studentId", "name email profilePic")
224 |       .sort({ scheduledDate: -1 });
225 |     res.json({ meetings });
226 |   } catch (error) {
227 |     res.status(500).json({ message: "Server error", error: error.message });
228 |   }
229 | };
230 |
231 | module.exports = {
232 |   getDashboard,
233 |   getStudents,
234 |   respondToMeeting,
235 |   addMeetingNotes,
236 |   giveFeedback,
237 |   getMeetings,
238 | };
239 |
240 | const Notification = require("../models/Notification");
241 |
242 | // @desc Get notifications for current user
243 | // @route GET /api/notifications
244 | const getNotifications = async (req, res) => {
245 |   try {
246 |     const { page = 1, limit = 20 } = req.query;
247 |     const notifications = await Notification.find({ userId: req.user.id })
248 |       .sort({ createdAt: -1 })
249 |       .skip((page - 1) * limit)
250 |       .limit(Number(limit));
251 |
252 |     const unreadCount = await Notification.countDocuments({
253 |       userId: req.user.id,
254 |       isRead: false,
255 |     });
256 |     res.json({ notifications, unreadCount });
257 |   } catch (error) {
258 |     res.status(500).json({ message: "Server error", error: error.message });
259 |   }
260 | };
261 |
262 | // @desc Mark single notification as read
263 | // @route PUT /api/notifications/:id/read
264 | const markAsRead = async (req, res) => {
265 |   try {
266 |     await Notification.findByIdAndUpdate(req.params.id, { isRead: true });
267 |     res.json({ message: "Marked as read" });
268 |   } catch (error) {
269 |     res.status(500).json({ message: "Server error", error: error.message });
270 |   }
271 | };
272 |
273 | // @desc Mark all as read
274 | // @route PUT /api/notifications/read-all
275 | const markAllAsRead = async (req, res) => {
276 |   try {
277 |     await Notification.updateMany({ userId: req.user.id, isRead: false }, { isRead: true });
278 |   }
279 | }
```

```
40 |     res.json({ message: "All notifications marked as read" });
41 |   } catch (error) {
42 |     res.status(500).json({ message: "Server error", error: error.message });
43 |   }
44 | });
45 |
46 | // @desc Delete a notification
47 | // @route DELETE /api/notifications/:id
48 | const deleteNotification = async (req, res) => {
49 |   try {
50 |     await Notification.findByIdAndDelete(req.params.id);
51 |     res.json({ message: "Notification deleted" });
52 |   } catch (error) {
53 |     res.status(500).json({ message: "Server error", error: error.message });
54 |   }
55 | };
56 |
57 | module.exports = { getNotifications, markAsRead, markAllAsRead, deleteNotification };
58 |
59 | const Progress = require("../models/Progress");
60 | const Training = require("../models/Training");
61 | const { calculateOverallProgress, calculatePlacementReadiness } = require("../utils/progressCalculator");
62 |
63 | const getStudentProgress = async (req, res) => {
64 |   try {
65 |     const progress = await Progress.findOne({ studentId: req.user.id });
66 |     if (!progress) return res.status(404).json({ message: "Progress record not found" });
67 |     res.json({ progress });
68 |   } catch (error) {
69 |     res.status(500).json({ message: "Server error", error: error.message });
70 |   }
71 | };
72 |
73 | const getDetailedStudentReport = async (req, res) => {
74 |   try {
75 |     const targetStudentId = req.params.studentId || req.user.id;
76 |     const student = await Student.findById(targetStudentId)
77 |       .select("-password")
78 |       .populate("assignedMentor", "name email designation company")
79 |       .populate("enrolledTrainings", "title category level duration lessons");
80 |     if (!student) return res.status(404).json({ message: "Student not found" });
81 |     let progress = await Progress.findOne({ studentId: targetStudentId });
82 |     if (!progress) {
83 |       progress = await Progress.create({ studentId: targetStudentId });
84 |     }
85 |     res.json({
86 |       student,
87 |       progress,
88 |     });
89 |   } catch (error) {
90 |     res.status(500).json({ message: "Server error", error: error.message });
91 |   }
92 | };
93 |
94 | const getPlacementReadiness = async (req, res) => {
95 |   try {
96 |     const progress = await Progress.findOne({ studentId: req.user.id });
97 |     if (!progress) return res.status(404).json({ message: "Progress record not found" });
98 |     const placementScore = calculatePlacementReadiness({
99 |       overallScore: progress.overallScore,
100 |       quizScores: progress.quizScores,
101 |       assignmentsSubmitted: progress.assignmentsSubmitted,
102 |       meetingsAttended: progress.meetingsAttended,
103 |       hasResume: progress.hasResume,
104 |     });
105 |     res.json({ placementReadiness: placementScore });
106 |   } catch (error) {
107 |     res.status(500).json({ message: "Server error", error: error.message });
108 |   }
109 | };
110 |
111 | const getAdminProgressReport = async (req, res) => {
112 |   try {
113 |     const progressData = await Progress.find()
114 |       .populate("studentId", "name email assignedMentor")
115 |       .sort({ overallScore: -1 });
116 |     const averageOverall =
```

```
65 |     progressData.length > 0
66 |     ?
67 |     progressData.reduce((sum, p) => sum + p.overallScore, 0) / progressData.length
68 |     : 0;
69 |
70 |     const averagePlacement =
71 |     progressData.length > 0
72 |     ?
73 |     progressData.reduce((sum, p) => sum + p.placementReadiness, 0) / progressData.length
74 |     : 0;
75 |
76 |     res.json({
77 |       progressData,
78 |       metrics: {
79 |         averageOverall: Math.round(averageOverall),
80 |         averagePlacement: Math.round(averagePlacement),
81 |         totalStudents: progressData.length,
82 |       },
83 |     });
84 |   } catch (error) {
85 |     res.status(500).json({ message: "Server error", error: error.message });
86 |   }
87 | };
88 |
89 | module.exports = {
90 |   getStudentProgress,
91 |   getDetailedStudentReport,
92 |   getPlacementReadiness,
93 |   getAdminProgressReport,
94 | }; View Source Code for backend/controllers/progressController.js \(5.1 KB\)
95 |
96 | 1 | const Student = require("../models/Student");
97 | 2 | const Meeting = require("../models/Meeting");
98 | 3 | const Progress = require("../models/Progress");
99 | 4 | const Certificate = require("../models/Certificate");
100 | 5 | const Notification = require("../models/Notification");
101 | 6 | const Training = require("../models/Training");
102 | 7 | const path = require("path");
103 | 8 |
104 | 9 | // @desc Get student dashboard data
105 | 10 | // @route GET /api/students/dashboard
106 | 11 | const getDashboard = async (req, res) => {
107 | 12 |   try {
108 | 13 |     const student = await Student.findById(req.user.id)
109 | 14 |       .select("-password")
110 | 15 |       .populate("assignedMentor", "name email expertise profilePic designation company");
111 | 16 |
112 | 17 |     const progress = await Progress.findOne({ studentId: req.user.id });
113 | 18 |
114 | 19 |     const upcomingMeetings = await Meeting.find({
115 | 20 |       studentId: req.user.id,
116 | 21 |       status: "accepted",
117 | 22 |       scheduledDate: { $gte: new Date() },
118 | 23 |     })
119 | 24 |       .populate("mentorId", "name profilePic designation")
120 | 25 |       .sort({ scheduledDate: 1 })
121 | 26 |       .limit(3);
122 | 27 |
123 | 28 |     const enrolledTrainings = await Training.find({
124 | 29 |       "enrolledStudents.studentId": req.user.id,
125 | 30 |     }).select("title category thumbnail enrolledStudents");
126 | 31 |
127 | 32 |     const notifications = await Notification.find({
128 | 33 |       userId: req.user.id,
129 | 34 |       isRead: false,
130 | 35 |     })
131 | 36 |       .sort({ createdAt: -1 })
132 | 37 |       .limit(5);
133 | 38 |
134 | 39 |     const certificates = await Certificate.find({ studentId: req.user.id });
135 | 40 |
136 | 41 |     res.json({
137 | 42 |       student,
138 | 43 |       progress,
139 | 44 |       upcomingMeetings,
140 | 45 |       enrolledTrainings: enrolledTrainings.map((t) => {
141 | 46 |         const enrollment = t.enrolledStudents.find(
142 | 47 |           (e) => e.studentId.toString() === req.user.id
143 | 48 |         );
144 | 49 |         return {
145 | 50 |           _id: t._id,
```

```
51 |         title: t.title,
52 |         category: t.category,
53 |         thumbnail: t.thumbnail,
54 |         isCompleted: enrollment?.isCompleted || false,
55 |         completedVideos: enrollment?.completedVideos?.length || 0,
56 |         quizScore: enrollment?.quizScore || 0,
57 |     });
58 | },
59 |     unreadNotifications: notifications.length,
60 |     certificates: certificates.length,
61 | });
62 | } catch (error) {
63 |     res.status(500).json({ message: "Server error", error: error.message });
64 | }
65 | };
66 |
67 | // @desc Get/Update student profile
68 | // @route GET|PUT /api/students/profile
69 | const getProfile = async (req, res) => {
70 |     try {
71 |         const student = await Student.findById(req.user.id)
72 |             .select("-password")
73 |             .populate("assignedMentor", "name email profilePic designation company");
74 |         res.json({ student });
75 |     } catch (error) {
76 |         res.status(500).json({ message: "Server error", error: error.message });
77 |     }
78 | };
79 |
80 | const updateProfile = async (req, res) => {
81 |     try {
82 |         const { name, phone, bio, skills } = req.body;
83 |         const updated = await Student.findByIdAndUpdate(
84 |             req.user.id,
85 |             {
86 |                 name,
87 |                 phone,
88 |                 bio,
89 |                 skills: Array.isArray(skills)
90 |                     ? skills
91 |                     : skills
92 |                     ? skills.split(",").map((s) => s.trim()).filter(Boolean)
93 |                     : [],
94 |             },
95 |             { new: true }
96 |         ).select("-password");
97 |         res.json({ message: "Profile updated", student: updated });
98 |     } catch (error) {
99 |         res.status(500).json({ message: "Server error", error: error.message });
100 |     }
101 | };
102 |
103 | // @desc Upload resume
104 | // @route POST /api/students/resume
105 | const uploadResume = async (req, res) => {
106 |     try {
107 |         if (!req.file) return res.status(400).json({ message: "No file uploaded" });
108 |         const resumeUrl = `/uploads/resumes/${req.file.filename}`;
109 |         await Student.findByIdAndUpdate(req.user.id, { resumeUrl });
110 |         // Mark as having resume in Progress and sync
111 |         await Progress.findOneAndUpdate(
112 |             { studentId: req.user.id },
113 |             { hasResume: true }
114 |         );
115 |         const { syncStudentProgress } = require("../utils/progressService");
116 |         await syncStudentProgress(req.user.id);
117 |         res.json({ message: "Resume uploaded", resumeUrl });
118 |     } catch (error) {
119 |         res.status(500).json({ message: "Server error", error: error.message });
120 |     }
121 | };
122 |
123 | // @desc Get student certificates
124 | // @route GET /api/students/certificates
125 | const getCertificates = async (req, res) => {
126 |     try {
```

```
129 |     const certs = await Certificate.find({ studentId: req.user.id }).populate(
130 |       "trainingId",
131 |       "title category"
132 |     );
133 |     res.json({ certificates: certs });
134 |   } catch (error) {
135 |     res.status(500).json({ message: "Server error", error: error.message });
136 |   }
137 | };
138 |
139 | // @desc Get student progress
140 | // @route GET /api/students/progress
141 | const getProgress = async (req, res) => {
142 |   try {
143 |     const progress = await Progress.findOne({ studentId: req.user.id }).populate(
144 |       "quizScores.trainingId",
145 |       "title"
146 |     );
147 |     res.json({ progress });
148 |   } catch (error) {
149 |     res.status(500).json({ message: "Server error", error: error.message });
150 |   }
151 | };
152 |
153 | // @desc Get all meetings for student
154 | // @route GET /api/students/meetings
155 | const getMeetings = async (req, res) => {
156 |   try {
157 |     const meetings = await Meeting.find({ studentId: req.user.id })
158 |       .populate("mentorId", "name profilePic email designation")
159 |       .sort({ scheduledDate: -1 });
160 |     res.json({ meetings });
161 |   } catch (error) {
162 |     res.status(500).json({ message: "Server error", error: error.message });
163 |   }
164 | };
165 |
166 | module.exports = {
167 |   getDashboard,
168 |   getProfile,
169 |   updateProfile,
170 |   uploadResume,
171 |   getCertificates,
172 |   getProgress,
173 |   getMeetings,
174 | };
175 |
176 | const Training = require("../models/Training");
177 | const Certificate = require("../models/Certificate");
178 | const Progress = require("../models/Progress");
179 | const Notification = require("../models/Notification");
180 | const { calculateOverallProgress } = require("../utils/progressCalculator");
181 |
182 | // @desc Get all trainings
183 | // @route GET /api/trainings
184 | const getAllTrainings = async (req, res) => {
185 |   try {
186 |     const { category, level } = req.query;
187 |     const filter = { isPublished: true };
188 |     if (category) filter.category = category;
189 |     if (level) filter.level = level;
190 |
191 |     const trainings = await Training.find(filter).select(
192 |       "title description category thumbnail level duration instructor tags enrolledStudents createdAt"
193 |     );
194 |
195 |     const trainingsWithCount = trainings.map((t) => ({
196 |       ...t.toObject(),
197 |       enrollmentCount: t.enrolledStudents.length,
198 |       enrolledStudents: undefined,
199 |     }));
200 |     res.json({ trainings: trainingsWithCount });
201 |   } catch (error) {
202 |     res.status(500).json({ message: "Server error", error: error.message });
203 |   }
204 | };
205 |
206 | // @desc Get training details
```

```
33 | // @route GET /api/trainings/:id
34 | const getTrainingById = async (req, res) => {
35 |   try {
36 |     const training = await Training.findById(req.params.id);
37 |     if (!training) return res.status(404).json({ message: "Training not found" });
38 |     let userEnrollment = null;
39 |     if (req.user) {
40 |       userEnrollment = training.enrolledStudents.find(
41 |         (e) => e.studentId.toString() === req.user.id
42 |       );
43 |     }
44 |     res.json({
45 |       training: {
46 |         ...training.toObject(),
47 |         enrollmentCount: training.enrolledStudents.length,
48 |       },
49 |       userEnrollment,
50 |     });
51 |   } catch (error) {
52 |     res.status(500).json({ message: "Server error", error: error.message });
53 |   }
54 | };
55 |
56 | // @desc Enroll in training
57 | // @route POST /api/trainings/:id/enroll
58 | const enrollTraining = async (req, res) => {
59 |   try {
60 |     const training = await Training.findById(req.params.id);
61 |     if (!training) return res.status(404).json({ message: "Training not found" });
62 |     const alreadyEnrolled = training.enrolledStudents.find(
63 |       (e) => e.studentId.toString() === req.user.id
64 |     );
65 |     if (alreadyEnrolled)
66 |       return res.status(400).json({ message: "Already enrolled" });
67 |     training.enrolledStudents.push({ studentId: req.user.id });
68 |     await training.save();
69 |     await Notification.create({
70 |       userId: req.user.id,
71 |       userRole: "student",
72 |       title: `Enrolled in ${training.title} ðŸŽŽ`,
73 |       message: `You're now enrolled. Start learning and track your progress!`,
74 |       type: "training",
75 |     });
76 |     res.json({ message: "Enrolled successfully" });
77 |   } catch (error) {
78 |     res.status(500).json({ message: "Server error", error: error.message });
79 |   }
80 | };
81 |
82 | // @desc Mark video as completed
83 | // @route POST /api/trainings/:id/complete-video
84 | const completeVideo = async (req, res) => {
85 |   try {
86 |     const { videoIndex } = req.body;
87 |     const training = await Training.findById(req.params.id);
88 |     if (!training) return res.status(404).json({ message: "Training not found" });
89 |     const enrollment = training.enrolledStudents.find(
90 |       (e) => e.studentId.toString() === req.user.id
91 |     );
92 |     if (!enrollment) return res.status(400).json({ message: "Not enrolled" });
93 |     if (!enrollment.completedVideos.includes(videoIndex)) {
94 |       enrollment.completedVideos.push(videoIndex);
95 |     }
96 |     // Check if all videos completed
97 |     const allCompleted =
98 |       training.videos.length > 0 &&
99 |       enrollment.completedVideos.length === training.videos.length;
100 |     if (allCompleted) {
101 |       enrollment.isCompleted = true;
102 |       enrollment.completedAt = new Date();
103 |       // Issue certificate
104 |       const cert = await Certificate.create({
```

```
116 |         studentId: req.user.id,
117 |         trainingId: training._id,
118 |         trainingTitle: training.title,
119 |     });
120 |
121 |     await Notification.create({
122 |         userId: req.user.id,
123 |         userRole: "student",
124 |         title: "Certificate Earned! 🎉",
125 |         message: `Congratulations! You completed "${training.title}" and earned a certificate.`,
126 |         type: "certificate",
127 |     });
128 | }
129 |
130 | await training.save();
131 |
132 | // Update progress
133 | const allTrainings = await Training.find({
134 |     "enrolledStudents.studentId": req.user.id,
135 | });
136 | const completedCount = allTrainings.filter((t) =>
137 |     t.enrolledStudents.find(
138 |         (e) => e.studentId.toString() === req.user.id && e.isCompleted
139 |     )
140 | ).length;
141 | const trainingCompletion =
142 |     allTrainings.length > 0
143 |     ? Math.round((completedCount / allTrainings.length) * 100)
144 |     : 0;
145 |
146 | await Progress.findOneAndUpdate(
147 |     { studentId: req.user.id },
148 |     { trainingCompletion }
149 | );
150 |
151 | const { syncStudentProgress } = require("../utils/progressService");
152 | await syncStudentProgress(req.user.id);
153 |
154 | res.json({
155 |     message: allCompleted
156 |     ? "Training completed! Certificate issued."
157 |     : "Video marked complete",
158 |     isCompleted: allCompleted,
159 | });
160 | } catch (error) {
161 |     res.status(500).json({ message: "Server error", error: error.message });
162 | }
163 | });
164 |
165 | // @desc Submit quiz
166 | // @route POST /api/trainings/:id/submit-quiz
167 | const submitQuiz = async (req, res) => {
168 |     try {
169 |         const { answers } = req.body; // [{ questionIndex, selectedOption }]
170 |         const training = await Training.findById(req.params.id);
171 |         if (!training) return res.status(404).json({ message: "Training not found" });
172 |
173 |         let score = 0;
174 |         const maxScore = training.quizzes.reduce((s, q) => s + (q.points || 10), 0);
175 |         answers.forEach(({ questionIndex, selectedOption }) => {
176 |             const quiz = training.quizzes[questionIndex];
177 |             if (quiz && quiz.correctAnswer === selectedOption) {
178 |                 score += quiz.points || 10;
179 |             }
180 |         });
181 |     } catch (error) {
182 |         // Handle error
183 |     }
184 |
185 |     const enrollment = training.enrolledStudents.find(
186 |         (e) => e.studentId.toString() === req.user.id
187 |     );
188 |     if (enrollment) enrollment.quizScore = score;
189 |     await training.save();
190 |
191 |     await Progress.findOneAndUpdate(
192 |         { studentId: req.user.id },
193 |         {
194 |             $push: {
195 |                 quizScores: {
196 |                     trainingId: training._id,
197 |                     score,
```

```
198 |     },
199 |   }
200 | );
202 | const { syncStudentProgress } = require("../utils/progressService");
203 | await syncStudentProgress(req.user.id);
205 | res.json({ score, maxScore, percentage: Math.round((score / maxScore) * 100) });
206 | } catch (error) {
207 |   res.status(500).json({ message: "Server error", error: error.message });
208 | }
209 | };
211 | // @desc Create training (admin)
212 | // @route POST /api/trainings
213 | const createTraining = async (req, res) => {
214 |   try {
215 |     const training = await Training.create(req.body);
216 |     res.status(201).json({ message: "Training created", training });
217 |   } catch (error) {
218 |     res.status(500).json({ message: "Server error", error: error.message });
219 |   }
220 | };
222 | // @desc Update training (admin)
223 | // @route PUT /api/trainings/:id
224 | const updateTraining = async (req, res) => {
225 |   try {
226 |     const training = await Training.findByIdAndUpdate(req.params.id, req.body, { new: true });
227 |     res.json({ message: "Training updated", training });
228 |   } catch (error) {
229 |     res.status(500).json({ message: "Server error", error: error.message });
230 |   }
231 | };
233 | // @desc Delete training (admin)
234 | // @route DELETE /api/trainings/:id
235 | const deleteTraining = async (req, res) => {
236 |   try {
237 |     await Training.findByIdAndDelete(req.params.id);
238 |     res.json({ message: "Training deleted" });
239 |   } catch (error) {
240 |     res.status(500).json({ message: "Server error", error: error.message });
241 |   }
242 | };
244 | module.exports = {
245 |   getAllTrainings,
246 |   getTrainingById,
247 |   enrollTraining,
248 |   completeVideo,
249 |   submitQuiz,
250 |   createTraining,
251 |   updateTraining,
252 |   deleteTraining,
253 | };
254 | View Backend/controllers/trainingController.js \(0.0 KB\)
254 | View Backend/controllers/trainingController.js \(0.1 KB\)
1 |
1 | FROM node:20-alpine
3 | WORKDIR /usr/src/app
5 | COPY package*.json ./
6 | RUN npm install --production
8 | COPY . .
10 | EXPOSE 5000
12 | CMD ["npm", "start"]
13 |
```


KATALYST

Source Code: backend/generate_all_files_pdf.js

Generated: 22/8/2026 | Backend

(22.3 KB)

```
1 | const PDFDocument = require("pdfkit");
2 | const fs = require("fs");
3 | const path = require("path");
4 |
5 | const rootDir = path.resolve(__dirname, "..");
6 | const frontendDir = path.join(rootDir, "frontend");
7 | const backendDir = path.join(rootDir, "backend");
8 |
9 | // Folders to ignore
10 | const IGNORE_DIRS = new Set([
11 |   "node_modules",
12 |   ".git",
13 |   "dist",
14 |   "build",
15 |   ".vscode",
16 |   "android",
17 |   "uploads",
18 |   "StudentLearningApp_CURRENT_BACKUP",
19 |   "assets"
20 | ]);
21 |
22 | const ALLOWED_EXTS = new Set([
23 |   ".js",
24 |   ".jsx",
25 |   ".json",
26 |   ".css",
27 |   ".html",
28 |   ".md",
29 |   ".yaml",
30 |   ".yml",
31 |   ".example"
32 | ]);
33 |
34 | function getFilesRecursively(dir, baseDir = dir) {
35 |   let results = [];
36 |   try {
37 |     const list = fs.readdirSync(dir);
38 |     for (const file of list) {
39 |       const fullPath = path.join(dir, file);
40 |       const relPath = path.relative(baseDir, fullPath).replace(/\\/g, "/");
41 |       const stat = fs.statSync(fullPath);
42 |
43 |       if (stat.isDirectory()) {
44 |         if (!IGNORE_DIRS.has(file)) {
45 |           results = results.concat(getFilesRecursively(fullPath, baseDir));
46 |         }
47 |       } else {
48 |         const ext = path.extname(file);
49 |         const isEnv = file.startsWith(".env");
50 |         const isDockerfile = file === "Dockerfile";
51 |
52 |         if (ALLOWED_EXTS.has(ext) || isEnv || isDockerfile) {
53 |           if (!file.endsWith("package-lock.json") && !file.endsWith(".log") && !file.endsWith(".exe") && file
54 |             results.push({
55 |               fullPath,
56 |               relPath,
57 |               size: stat.size,
58 |               name: file,
59 |               category: relPath.startsWith("backend") ? "Backend" : relPath.startsWith("frontend") ? "Frontend
60 |             });
61 |         }
62 |       }
63 |     }
64 |   } catch (err) {
65 |     console.error("Error reading dir:", err.message);
66 |   }
67 |   return results;
68 | }
69 |
70 |
71 | function generateCompletePDF(outputPath) {
72 |   console.log(`Starting PDF compilation to: ${outputPath}...`);
73 |
74 |   const doc = new PDFDocument({
75 |     margin: 40,
76 |     size: "A4",
77 |     bufferPages: true,
78 |   });
79 |
80 |   const stream = fs.createWriteStream(outputPath);
```

KATALYST

Source Code: backend/generate_all_files_pdf.js (Cont.)

Generated: 22/8/2026 | Backend

```
81 | doc.pipe(stream);
83 | // Styling Palette
84 | const primaryColor = "#db2777"; // Tailwind pink-600
85 | const secondaryColor = "#4f46e5"; // Tailwind indigo-600
86 | const darkBg = "#0f172a"; // Slate 900
87 | const textColor = "#1e293b"; // Slate 800
88 | const mutedText = "#64748b"; // Slate 500
89 | const borderLight = "#e2e8f0"; // Slate 200
91 | function drawHeaderBanner(title, subtitle) {
92 |   doc.rect(0, 0, 595, 110).fill(darkBg);
93 |   doc
94 |     .fillColor("#ffffff")
95 |     .fontSize(22)
96 |     .font("Helvetica-Bold")
97 |     .text("KATALYST", 40, 28, { continued: true })
98 |     .fillColor(primaryColor)
99 |     .text(".", { continued: false });
101 |   doc
102 |     .fillColor("#e2e8f0")
103 |     .fontSize(11)
104 |     .font("Helvetica")
105 |     .text(title, 40, 58);
107 |   doc
108 |     .fillColor("#94a3b8")
109 |     .fontSize(8.5)
110 |     .text(`Generated: ${new Date().toLocaleDateString()} | ${subtitle}`, 40, 78);
112 |   doc.y = 130;
113 | }
115 | function addSectionHeading(title) {
116 |   if (doc.y > 680) doc.addPage();
117 |   doc.moveDown(0.5);
118 |   doc
119 |     .fillColor(primaryColor)
120 |     .fontSize(14)
121 |     .font("Helvetica-Bold")
122 |     .text(title)
123 |     .moveDown(0.2);
125 |   doc
126 |     .strokeColor(primaryColor)
127 |     .lineWidth(1.5)
128 |     .moveTo(40, doc.y)
129 |     .lineTo(555, doc.y)
130 |     .stroke()
131 |     .moveDown(0.5);
132 | }
134 | function addSubHeading(title) {
135 |   if (doc.y > 700) doc.addPage();
136 |   doc
137 |     .fillColor(secondaryColor)
138 |     .fontSize(11)
139 |     .font("Helvetica-Bold")
140 |     .text(title)
141 |     .moveDown(0.3);
142 | }
144 | // --- COVER / TITLE PAGE ---
145 | doc.rect(0, 0, 595, 842).fill(darkBg);
147 | doc
148 |   .fillColor("#ffffff")
149 |   .fontSize(36)
150 |   .font("Helvetica-Bold")
151 |   .text("KATALYST", 50, 180, { continued: true })
152 |   .fillColor(primaryColor)
153 |   .text(".", { continued: false });
155 | doc
156 |   .fillColor("#f472b6")
157 |   .fontSize(18)
158 |   .font("Helvetica-Bold")
159 |   .text("Full-Stack Learning & Mentorship Platform", 50, 235);
161 | doc
162 |   .fillColor("#cbd5e1")
163 |   .fontSize(12)
```

```
164 |     .font("Helvetica")
165 |     .text("Complete Source Code, System Architecture & File Documentation", 50, 265, { width: 495 });
167 | doc
168 |     .strokeColor(primaryColor)
169 |     .lineWidth(2)
170 |     .moveTo(50, 310)
171 |     .lineTo(545, 310)
172 |     .stroke();
174 | // Cover stats box
175 | const allFiles = getFilesRecursively(rootDir, rootDir);
176 | const backendFiles = allFiles.filter(f => f.category === "Backend");
177 | const frontendFiles = allFiles.filter(f => f.category === "Frontend");
179 | doc
180 |     .rect(50, 340, 495, 140)
181 |     .fillAndStroke("#1e293b", "#334155");
183 | doc
184 |     .fillColor("#ffffff")
185 |     .fontSize(11)
186 |     .font("Helvetica-Bold")
187 |     .text("PROJECT SUMMARY METRICS", 70, 360);
189 | const metrics = [
190 |     ["Platform Version:", "2.0.0 (Production Architecture)", "Backend Framework:", "Node.js 20+ / Express.js 5",
191 |     ["Frontend Stack:", "React 19, Vite, Tailwind CSS", "Database:", "MongoDB Atlas (Mongoose ORM)"],
192 |     ["Total Source Files:", `${allFiles.length} files included`, "Security:", "JWT Authentication & RBAC"],
193 |     ["Frontend Files:", `${frontendFiles.length} modules & views`, "Backend Files:", `${backendFiles.length} c
194 | ];
196 | let mY = 385;
197 | metrics.forEach(m => {
198 |     doc.font("Helvetica-Bold").fontSize(9).fillColor("#94a3b8").text(m[0], 70, mY, { width: 110 });
199 |     doc.font("Helvetica").fontSize(9).fillColor("#f8fafc").text(m[1], 180, mY, { width: 140 });
200 |     doc.font("Helvetica-Bold").fontSize(9).fillColor("#94a3b8").text(m[2], 330, mY, { width: 100 });
201 |     doc.font("Helvetica").fontSize(9).fillColor("#f8fafc").text(m[3], 430, mY, { width: 110 });
202 |     mY += 20;
203 | });
205 | doc
206 |     .fillColor("#94a3b8")
207 |     .fontSize(9.5)
208 |     .font("Helvetica")
209 |     .text(`Compiled on: ${new Date().toLocaleDateString('en-US', { weekday: 'long', year: 'numeric', month: 'l
210 |     .text("Confidential & Proprietary - Katalyst Development Team", 50, 735);
212 | // --- PAGE 2: TABLE OF CONTENTS & EXECUTIVE SUMMARY ---
213 | doc.addPage();
214 | drawHeaderBanner("Executive Summary & Table of Contents", "System Overview");
216 | addSectionHeading("1. Executive Summary");
217 | doc
218 |     .fillColor(textColor)
219 |     .fontSize(9.5)
220 |     .font("Helvetica")
221 |     .text(
222 |         "Katalyst is a full-stack educational and mentorship platform engineered to connect students with profes
223 |         { align: "justify", lineGap: 3 }
224 |     )
225 |     .moveDown(1);
227 | addSectionHeading("2. Document Table of Contents");
229 | const tocItems = [
230 |     ["Section 1", "Executive Summary & System Architecture", "High-level overview & system design"],
231 |     ["Section 2", "Technology Stack & Layer Mapping", "Frontend, backend, database, and auth stack"],
232 |     ["Section 3", "Complete File Directory Inventory", "All project files categorized with paths & sizes"],
233 |     ["Section 4", "Backend Architecture & Data Models", "Mongoose schemas, controllers, and REST routes"],
234 |     ["Section 5", "Frontend Architecture & Portal Pages", "React components, state contexts, and routes"],
235 |     ["Section 6", "API Reference & Access Control Matrix", "All REST endpoints, request/response models"],
236 |     ["Section 7", "Complete Source Code Listings", "Full file contents and implementations"]
237 | ];
239 | let tocY = doc.y;
240 | doc.rect(40, tocY, 515, 20).fill("#f1f5f9");
241 | doc.font("Helvetica-Bold").fontSize(9).fillColor(darkBg);
242 | doc.text("Section", 50, tocY + 5, { width: 80 });
243 | doc.text("Topic", 130, tocY + 5, { width: 200 });
244 | doc.text("Coverage", 330, tocY + 5, { width: 215 });
246 | tocY += 20;
```

```
247 | doc.font("Helvetica").fontSize(8.5);
248 | tocItems.forEach((item, idx) => {
249 |   const bg = idx % 2 === 0 ? "#ffffff" : "#f8fafc";
250 |   doc.rect(40, tocY, 515, 18).fill(bg);
251 |   doc.fillColor(primaryColor).font("Helvetica-Bold").text(item[0], 50, tocY + 4, { width: 80 });
252 |   doc.fillColor(darkBg).font("Helvetica-Bold").text(item[1], 130, tocY + 4, { width: 200 });
253 |   doc.fillColor(mutedText).font("Helvetica").text(item[2], 330, tocY + 4, { width: 215 });
254 |   tocY += 18;
255 | });
256 |
257 | doc.y = tocY + 15;
258 |
259 | // --- PAGE 3: TECH STACK ARCHITECTURE ---
260 | doc.addPage();
261 | drawHeaderBanner("Technology Stack & Architecture", "Architecture Blueprint");
262 |
263 | addSectionHeading("3. Architecture & Technology Stack");
264 |
265 | const techStackDetails = [
266 |   ["Frontend Core", "React 19.0.0 + Vite 8.2.0", "Fast modular SPA client with lightning HMR"],
267 |   ["Styling Framework", "Tailwind CSS 3.4 + PostCSS", "Custom theme tokens, glassmorphism UI, Dark mode"],
268 |   ["Routing & Nav", "React Router v7", "Declarative browser routing & protected role routes"],
269 |   ["State Management", "React Context (Auth & Theme)", "Global authentication persistence & theme switches"],
270 |   ["Data Visualization", "Recharts 2.15", "Interactive progress rings & readiness index charts"],
271 |   ["Icons & UI", "Lucide React 1.31", "Feather-style SVG icon system across all portals"],
272 |   ["Backend Runtime", "Node.js 20+ / Express 5.2", "Non-blocking RESTful API & middleware pipeline"],
273 |   ["Database Store", "MongoDB Atlas / Mongoose 9.9", "Schema validation, indexing, and object relations"],
274 |   ["Authentication", "JWT (jsonwebtoken 9.0) + bcryptjs", "Stateless bearer token authorization & password h"],
275 |   ["AI Services", "Google Generative AI (Gemini 1.5)", "Resume analysis, personalized roadmaps & chat"],
276 |   ["File Handling", "Multer Middleware", "Local disk storage for student PDF resumes"],
277 |   ["Containerization", "Docker & Docker Compose", "Multi-stage build Dockerfiles for full-stack isolation"]
278 | ];
279 |
280 | let tsY = doc.y;
281 | doc.rect(40, tsY, 515, 20).fill("#fce7f3");
282 | doc.font("Helvetica-Bold").fontSize(9).fillColor(darkBg);
283 | doc.text("Layer", 50, tsY + 5, { width: 110 });
284 | doc.text("Technology", 160, tsY + 5, { width: 170 });
285 | doc.text("Role & Purpose", 330, tsY + 5, { width: 215 });
286 |
287 | tsY += 20;
288 | doc.font("Helvetica").fontSize(8);
289 | techStackDetails.forEach((row, idx) => {
290 |   const bg = idx % 2 === 0 ? "#ffffff" : "#fdf2f8";
291 |   doc.rect(40, tsY, 515, 17).fill(bg);
292 |   doc.fillColor(primaryColor).font("Helvetica-Bold").text(row[0], 50, tsY + 4, { width: 110 });
293 |   doc.fillColor(darkBg).font("Helvetica").text(row[1], 160, tsY + 4, { width: 170 });
294 |   doc.fillColor(mutedText).font("Helvetica").text(row[2], 330, tsY + 4, { width: 215 });
295 |   tsY += 17;
296 | });
297 |
298 | doc.y = tsY + 20;
299 |
300 | // --- COMPLETE DIRECTORY INVENTORY TABLE ---
301 | addSectionHeading("4. Complete File Inventory List");
302 | doc
303 |   .fillColor(mutedText)
304 |   .fontSize(8.5)
305 |   .font("Helvetica")
306 |   .text(`Total registered source and configuration files in this build: ${allFiles.length}`)
307 |   .moveDown(0.5);
308 |
309 | let fileTableY = doc.y;
310 | doc.rect(40, fileTableY, 515, 18).fill("#f1f5f9");
311 | doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
312 | doc.text("Category", 48, fileTableY + 4, { width: 75 });
313 | doc.text("Relative File Path", 125, fileTableY + 4, { width: 310 });
314 | doc.text("Size", 445, fileTableY + 4, { width: 100, align: "right" });
315 |
316 | fileTableY += 18;
317 | doc.font("Helvetica").fontSize(7.5);
318 |
319 | allFiles.forEach((f, idx) => {
320 |   if (fileTableY > 750) {
321 |     doc.addPage();
322 |     drawHeaderBanner("Complete File Inventory List (Cont.)", "File Inventory");
323 |     fileTableY = doc.y;
324 |     doc.rect(40, fileTableY, 515, 18).fill("#f1f5f9");
325 |     doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
326 |     doc.text("Category", 48, fileTableY + 4, { width: 75 });
327 |     doc.text("Relative File Path", 125, fileTableY + 4, { width: 310 });
328 |     doc.text("Size", 445, fileTableY + 4, { width: 100, align: "right" });
```

```
329 |         fileTableY += 18;
330 |         doc.font("Helvetica").fontSize(7.5);
331 |     }
332 |     const bg = idx % 2 === 0 ? "ffffff" : "#f8fafc";
333 |     doc.rect(40, fileTableY, 515, 15).fill(bg);
334 |     const catColor = f.category === "Backend" ? secondaryColor : f.category === "Frontend" ? primaryColor : "#
335 |     doc.fillColor(catColor).font("Helvetica-Bold").text(f.category, 48, fileTableY + 3, { width: 75 });
336 |     doc.fillColor(darkBg).font("Helvetica").text(f.relPath, 125, fileTableY + 3, { width: 310 });
337 |     doc.fillColor(mutedText).text(`${(f.size / 1024).toFixed(1)} KB`, 445, fileTableY + 3, { width: 100, align
338 |     fileTableY += 15;
339 | });
340 | doc.y = fileTableY + 20;
341 | // --- SECTION 5: BACKEND DATA MODELS & SCHEMAS ---
342 | doc.addPage();
343 | drawHeaderBanner("Backend Data Models & Architecture", "Database Design");
344 | addSectionHeading("5. Database Models & Schema Specifications");
345 | const modelsSummary = [
346 |     {
347 |         name: "Student (models/Student.js)",
348 |         fields: "name, email, password, role ('student'), bio, skills (Array), resumeUrl, assignedMentor (Object
349 |         desc: "Stores learner profiles, credentials, skills matrix, resume links, and assigned mentor associatio
350 |     },
351 |     {
352 |         name: "Mentor (models/Mentor.js)",
353 |         fields: "name, email, password, role ('mentor'), company, designation, expertise (Array), bio, assignedS
354 |         desc: "Maintains industry professional mentor records, company background, mentee limits, and assigned l
355 |     },
356 |     {
357 |         name: "Admin (models/Admin.js)",
358 |         fields: "name, email, password, role ('admin'), permissions (Array), department, activeStatus",
359 |         desc: "Superuser entity with full platform permissions to manage courses, assign mentors, and generate a
360 |     },
361 |     {
362 |         name: "Training (models/Training.js)",
363 |         fields: "title, description, category, level, duration, thumbnail, modules (Array of {title, videos: [{t
364 |         desc: "Course catalog containing structured learning modules, video lessons, quiz assessments, and compl
365 |     },
366 |     {
367 |         name: "Meeting (models/Meeting.js)",
368 |         fields: "studentId, mentorId, title, agenda, scheduledDate, startTime, endTime, status ('pending'|'appro
369 |         desc: "1-on-1 mentor meeting requests, schedule slots, Google Meet links, mentor acceptance status, and
370 |     },
371 |     {
372 |         name: "Progress (models/Progress.js)",
373 |         fields: "studentId, trainingId, completedVideos (Array), quizScores (Array), placementReadiness (0-100),
374 |         desc: "Tracks video lesson completions, quiz results, placement readiness formula index, and certificate
375 |     },
376 |     {
377 |         name: "Notification (models/Notification.js)",
378 |         fields: "recipientId, senderId, title, message, type ('meeting'|'course'|'system'), isRead, actionUrl, c
379 |         desc: "In-app notifications delivering meeting approvals, course updates, feedback, and reminders to use
380 |     }
381 | ];
382 | modelsSummary.forEach(m => {
383 |     if (doc.y > 660) {
384 |         doc.addPage();
385 |         drawHeaderBanner("Backend Data Models & Architecture (Cont.)", "Database Design");
386 |     }
387 |     addSubHeading(m.name);
388 |     doc
389 |         .rect(40, doc.y, 515, 45)
390 |         .fillAndStroke("#f8fafc", borderLight);
391 |     doc
392 |         .fillColor(darkBg)
393 |         .fontSize(8)
394 |         .font("Helvetica-Bold")
395 |         .text("Schema Fields:", 48, doc.y - 40)
396 |         .font("Helvetica")
397 |         .text(m.fields, 125, doc.y - 40, { width: 420 });
398 |     doc
399 |         .font("Helvetica-Bold")
```

```
410 |     .text("Description:", 48, doc.y - 20)
411 |     .font("Helvetica")
412 |     .fillColor(mutedText)
413 |     .text(m.desc, 125, doc.y - 20, { width: 420 });
415 |     doc.y += 10;
416 | });
418 | // --- SECTION 6: API REFERENCE & ACCESS MATRIX ---
419 | doc.addPage();
420 | drawHeaderBanner("RESTful API Routes & Access Matrix", "API Endpoints");
422 | addSectionHeading("6. API Endpoints Reference");
424 | const fullApiList = [
425 |   ["POST", "/api/auth/register", "Public", "Student registration with bcrypt hashing"],
426 |   ["POST", "/api/auth/login", "Public", "Unified login for student, mentor, admin (JWT)"],
427 |   ["GET", "/api/auth/me", "Auth", "Get active profile based on JWT token"],
428 |   ["GET", "/api/students/profile", "Student", "Get current student profile & mentor details"],
429 |   ["PUT", "/api/students/profile", "Student", "Update student bio, skills, and target role"],
430 |   ["POST", "/api/students/resume", "Student", "Upload student resume PDF via Multer"],
431 |   ["GET", "/api/trainings", "Public/Auth", "List all available trainings and courses"],
432 |   ["GET", "/api/trainings/:id", "Auth", "Get course modules, lessons, and student progress"],
433 |   ["POST", "/api/trainings/:id/enroll", "Student", "Enroll in a training track"],
434 |   ["POST", "/api/trainings/:id/complete-video", "Student", "Mark video lesson completed & update progress"],
435 |   ["POST", "/api/trainings/:id/submit-quiz", "Student", "Submit quiz responses & calculate score"],
436 |   ["GET", "/api/meetings/student", "Student", "Get all meetings booked by student"],
437 |   ["POST", "/api/meetings", "Student", "Book a new meeting with assigned mentor"],
438 |   ["GET", "/api/meetings/mentor", "Mentor", "Get all meeting requests assigned to mentor"],
439 |   ["PUT", "/api/meetings/:id/status", "Mentor", "Approve/Reject meeting and supply Meet link"],
440 |   ["GET", "/api/notifications", "Auth", "Fetch user notifications list"],
441 |   ["PUT", "/api/notifications/:id/read", "Auth", "Mark notification as read"],
442 |   ["POST", "/api/ai/resume-analyze", "Student", "AI resume strength & improvement analysis"],
443 |   ["POST", "/api/ai/career-roadmap", "Student", "AI personalized milestone career roadmap"],
444 |   ["POST", "/api/ai/chatbot", "Auth", "AI chatbot assistant for student guidance"],
445 |   ["GET", "/api/admin/stats", "Admin", "Fetch system-wide metrics, counts & analytics"],
446 |   ["GET", "/api/admin/users", "Admin", "List and manage all registered users"]
447 | ];
449 | let apiY = doc.y;
450 | doc.rect(40, apiY, 515, 18).fill("#fce7f3");
451 | doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
452 | doc.text("Method", 48, apiY + 4, { width: 50 });
453 | doc.text("Endpoint Route", 100, apiY + 4, { width: 175 });
454 | doc.text("Role", 280, apiY + 4, { width: 70 });
455 | doc.text("Description", 355, apiY + 4, { width: 195 });
457 | apiY += 18;
458 | doc.font("Helvetica").fontSize(7.5);
460 | fullApiList.forEach((row, idx) => {
461 |   if (apiY > 760) {
462 |     doc.addPage();
463 |     drawHeaderBanner("RESTful API Routes & Access Matrix (Cont.)", "API Endpoints");
464 |     apiY = doc.y;
465 |     doc.rect(40, apiY, 515, 18).fill("#fce7f3");
466 |     doc.font("Helvetica-Bold").fontSize(8.5).fillColor(darkBg);
467 |     doc.text("Method", 48, apiY + 4, { width: 50 });
468 |     doc.text("Endpoint Route", 100, apiY + 4, { width: 175 });
469 |     doc.text("Role", 280, apiY + 4, { width: 70 });
470 |     doc.text("Description", 355, apiY + 4, { width: 195 });
471 |     apiY += 18;
472 |     doc.font("Helvetica").fontSize(7.5);
473 |   }
475 |   const bg = idx % 2 === 0 ? "#ffffff" : "#fdf2f8";
476 |   doc.rect(40, apiY, 515, 15).fill(bg);
478 |   const mColor = row[0] === "POST" ? "#0284c7" : row[0] === "GET" ? "#16a34a" : "#d97706";
479 |   doc.fillColor(mColor).font("Helvetica-Bold").text(row[0], 48, apiY + 3, { width: 50 });
480 |   doc.fillColor(darkBg).font("Helvetica").text(row[1], 100, apiY + 3, { width: 175 });
481 |   doc.fillColor(primaryColor).font("Helvetica-Bold").text(row[2], 280, apiY + 3, { width: 70 });
482 |   doc.fillColor(mutedText).font("Helvetica").text(row[3], 355, apiY + 3, { width: 195 });
483 |   apiY += 15;
484 | });
486 | doc.y = apiY + 20;
488 | // --- SECTION 7: SOURCE CODE OF ALL FILES ---
489 | doc.addPage();
490 | drawHeaderBanner("Complete Source Code Listings", "Full Project Files");
492 | addSectionHeading("7. Complete Project Source Code");
```

```
493 | doc
494 |   .fillColor(mutedText)
495 |   .fontSize(8.5)
496 |   .font("Helvetica")
497 |   .text("The following sections contain the complete, verbatim source code for each file in the project orga
498 |   .moveDown(1);
500 | // Print all files with code
501 | allFiles.forEach((fileObj, fIdx) => {
502 |   let content = "";
503 |   try {
504 |     content = fs.readFileSync(fileObj.fullPath, "utf-8");
505 |   } catch (e) {
506 |     content = `// Error reading file: ${e.message}`;
507 |   }
509 |   // New file header
510 |   if (doc.y > 640) {
511 |     doc.addPage();
512 |     drawHeaderBanner("Source Code: " + fileObj.relPath, fileObj.category);
513 |   }
515 |   doc.moveDown(0.5);
516 |   doc
517 |     .rect(40, doc.y, 515, 24)
518 |     .fill(darkBg);
520 |   doc
521 |     .fillColor("#ffffff")
522 |     .fontSize(9.5)
523 |     .font("Helvetica-Bold")
524 |     .text(`File ${fIdx + 1} of ${allFiles.length}: ${fileObj.relPath}`, 50, doc.y - 18, { continued: true }
525 |     .fillColor("#94a3b8")
526 |     .fontSize(8)
527 |     .text(` ${fileObj.size / 1024}.toFixed(1)} KB`, { continued: false });
529 |   doc.moveDown(0.6);
531 |   // Print file lines
532 |   const lines = content.split(/\r?\n/);
533 |   doc.font("Courier").fontSize(7).fillColor("#1e293b");
535 |   for (let i = 0; i < lines.length; i++) {
536 |     if (doc.y > 770) {
537 |       doc.addPage();
538 |       drawHeaderBanner("Source Code: " + fileObj.relPath + " (Cont.)", fileObj.category);
539 |       doc.font("Courier").fontSize(7).fillColor("#1e293b");
540 |     }
542 |     const lineNum = String(i + 1).padStart(4, " ");
543 |     const lineText = lines[i];
544 |     // Draw background for code line
545 |     const lineBg = i % 2 === 0 ? "ffffff" : "f8f9fa";
546 |     doc.rect(40, doc.y, 515, 9.5).fill(lineBg);
548 |     doc
549 |       .fillColor("#94a3b8")
550 |       .text(lineNum + " | ", 42, doc.y + 1, { continued: true })
551 |       .fillColor("#0f172a")
552 |       .text(lineText.substring(0, 110), { continued: false });
554 |     doc.y += 0.5;
555 |   }
557 |   doc.moveDown(0.8);
558 | });
560 | // --- FOOTERS & NUMBERING ON ALL PAGES ---
561 | const range = doc.bufferedPageRange();
562 | for (let i = 0; i < range.start + range.count; i++) {
563 |   doc.switchToPage(i);
565 |   // Skip cover page footer
566 |   if (i === 0) continue;
568 |   doc
569 |     .strokeColor(borderLight)
570 |     .lineWidth(0.5)
571 |     .moveTo(40, 805)
572 |     .lineTo(555, 805)
573 |     .stroke();
575 |   doc
576 |     .fillColor("#94a3b8")
577 |     .fontSize(8)
```



```
578 |     .font("Helvetica")
579 |     .text("KATALYST - Full-Stack Student Learning & Mentorship Platform", 40, 812, { continued: true })
580 |     .text(`Page ${i + 1} of ${range.count}`, { align: "right" });
581 | }
583 | doc.end();
585 | stream.on("finish", () => {
586 |     console.log(` Complete PDF compiled successfully: ${outputPath} (${range.count} pages)`);
587 | });
588 | }
590 | // Target Paths
591 | const projectPdfPath = path.join(rootDir, "Student_Learning_App_Complete_Documentation.pdf");
592 | const standardPdfPath = path.join(rootDir, "Student_Learning_App_Documentation.pdf");
594 | generateCompletePDF(projectPdfPath);
595 | generateCompletePDF(standardPdfPath); (0.1 KB)
596 |
1 | // Forwarding to generate_all_files_pdf.js
2 | require("./generate_all_files_pdf.js"); (0.6 KB)
3 |
1 | const jwt = require("jsonwebtoken");
3 | const protect = (req, res, next) => {
4 |     let token;
5 |     if (
6 |         req.headers.authorization &&
7 |         req.headers.authorization.startsWith("Bearer")
8 |     ) {
9 |         try {
10 |             token = req.headers.authorization.split(" ")[1];
11 |             const decoded = jwt.verify(token, process.env.JWT_SECRET);
12 |             req.user = decoded; // { id, role }
13 |             next();
14 |         } catch (err) {
15 |             return res.status(401).json({ message: "Not authorized, token failed" });
16 |         }
17 |     }
18 |     if (!token) {
19 |         return res.status(401).json({ message: "Not authorized, no token" });
20 |     }
21 | };
23 | module.exports = { protect }; (0.3 KB)
24 |
1 | const allowRoles = (...roles) => {
2 |     return (req, res, next) => {
3 |         if (!req.user || !roles.includes(req.user.role)) {
4 |             return res.status(403).json({
5 |                 message: `Access denied. Required role: ${roles.join(" or ")}`,
6 |             });
7 |         }
8 |         next();
9 |     };
10 | };
12 | module.exports = { allowRoles }; (1.1 KB)
13 |
1 | const mongoose = require("mongoose");
2 | const bcrypt = require("bcryptjs");
4 | const adminSchema = new mongoose.Schema(
5 |     {
6 |         name: {
7 |             type: String,
8 |             required: true,
9 |             trim: true,
10 |         },
12 |         email: {
13 |             type: String,
14 |             required: true,
15 |             unique: true,
16 |             lowercase: true,
17 |             trim: true,
18 |         },
20 |         password: {
21 |             type: String,
22 |             required: true,
```



```
23 |     minlength: 6,
24 |   },
25 |   profilePic: {
26 |     type: String,
27 |     default: "",
28 |   },
29 |   role: {
30 |     type: String,
31 |     default: "admin",
32 |   },
33 |   isActive: {
34 |     type: Boolean,
35 |     default: true,
36 |   },
37 | },
38 | {
39 |   timestamps: true,
40 | }
41 | );
42 |
43 | // Hash password before saving
44 | adminSchema.pre("save", async function () {
45 |   if (!this.isModified("password")) {
46 |     return;
47 |   }
48 |   const salt = await bcrypt.genSalt(10);
49 |   this.password = await bcrypt.hash(this.password, salt);
50 | });
51 |
52 | // Check password
53 | adminSchema.methods.matchPassword = async function (enteredPassword) {
54 |   return await bcrypt.compare(enteredPassword, this.password);
55 | };
56 |
57 | module.exports = mongoose.model("Admin", adminSchema);
58 |
59 | const mongoose = require("mongoose");
60 | const { v4: uuidv4 } = require("uuid");
61 | const certificateSchema = new mongoose.Schema(
62 |   {
63 |     studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student", required: true },
64 |     trainingId: { type: mongoose.Schema.Types.ObjectId, ref: "Training", required: true },
65 |     studentName: String,
66 |     trainingTitle: String,
67 |     issuedDate: { type: Date, default: Date.now },
68 |     certificateUrl: { type: String, default: "" },
69 |     uniqueId: { type: String, default: () => uuidv4().slice(0, 12).toUpperCase() },
70 |     isValid: { type: Boolean, default: true },
71 |   },
72 |   { timestamps: true }
73 | );
74 |
75 | module.exports = mongoose.model("Certificate", certificateSchema);
76 |
77 | const mongoose = require("mongoose");
78 | const feedbackSchema = new mongoose.Schema(
79 |   {
80 |     fromId: { type: mongoose.Schema.Types.ObjectId, required: true, refPath: "fromRole" },
81 |     fromRole: { type: String, enum: ["student", "mentor"], required: true },
82 |     toId: { type: mongoose.Schema.Types.ObjectId, required: true, refPath: "toRole" },
83 |     toRole: { type: String, enum: ["student", "mentor"], required: true },
84 |     meetingId: { type: mongoose.Schema.Types.ObjectId, ref: "Meeting" },
85 |     trainingId: { type: mongoose.Schema.Types.ObjectId, ref: "Training" },
86 |     rating: { type: Number, min: 1, max: 5, required: true },
87 |     comment: { type: String, default: "" },
88 |     type: { type: String, enum: ["meeting", "training", "general"], default: "meeting" },
89 |   },
90 |   { timestamps: true }
91 | );
92 |
93 | module.exports = mongoose.model("Feedback", feedbackSchema);
```

(1.1 KB)

```
1 | const mongoose = require("mongoose");
3 | const meetingSchema = new mongoose.Schema(
4 |   {
5 |     studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student", required: true },
6 |     mentorId: { type: mongoose.Schema.Types.ObjectId, ref: "Mentor", required: true },
7 |     topic: { type: String, required: true },
8 |     agenda: { type: String, default: "" },
9 |     scheduledDate: { type: Date, required: true },
10 |     scheduledTime: { type: String, required: true },
11 |     duration: { type: Number, default: 60 }, // minutes
12 |     status: {
13 |       type: String,
14 |       enum: ["pending", "accepted", "rejected", "completed", "cancelled"],
15 |       default: "pending",
16 |     },
17 |     meetLink: { type: String, default: "" },
18 |     notes: { type: String, default: "" },
19 |     studentFeedback: {
20 |       rating: { type: Number, min: 1, max: 5 },
21 |       comment: String,
22 |       givenAt: Date,
23 |     },
24 |     mentorFeedback: {
25 |       rating: { type: Number, min: 1, max: 5 },
26 |       comment: String,
27 |       givenAt: Date,
28 |     },
29 |     rejectionReason: { type: String, default: "" },
30 |   },
31 |   { timestamps: true }
32 | );
34 | module.exports = mongoose.model("Meeting", meetingSchema);
```

(1.7 KB)

```
1 | const mongoose = require("mongoose");
2 | const bcrypt = require("bcryptjs");
4 | const mentorSchema = new mongoose.Schema(
5 |   {
6 |     name: {
7 |       type: String,
8 |       required: true,
9 |       trim: true,
10 |     },
12 |     email: {
13 |       type: String,
14 |       required: true,
15 |       unique: true,
16 |       lowercase: true,
17 |       trim: true,
18 |     },
20 |     password: {
21 |       type: String,
22 |       required: true,
23 |       minlength: 6,
24 |     },
26 |     phone: {
27 |       type: String,
28 |       default: "",
29 |     },
31 |     bio: {
32 |       type: String,
33 |       default: "",
34 |     },
36 |     profilePic: {
37 |       type: String,
38 |       default: "",
39 |     },
41 |     expertise: [
42 |       {
43 |         type: String,
44 |       },
45 |     ],

```

```
47 |     designation: {
48 |       type: String,
49 |       default: "",
50 |     },
52 |     company: {
53 |       type: String,
54 |       default: "",
55 |     },
57 |     assignedStudents: [
58 |       {
59 |         type: mongoose.Schema.Types.ObjectId,
60 |         ref: "Student",
61 |       },
62 |     ],
64 |     rating: {
65 |       type: Number,
66 |       default: 0,
67 |       min: 0,
68 |       max: 5,
69 |     },
71 |     totalRatings: {
72 |       type: Number,
73 |       default: 0,
74 |     },
76 |     role: {
77 |       type: String,
78 |       default: "mentor",
79 |     },
81 |     isActive: {
82 |       type: Boolean,
83 |       default: true,
84 |     },
86 |     availability: [
87 |       {
88 |         day: String,
89 |         slots: [String],
90 |       },
91 |     ],
92 |   },
93 |   {
94 |     timestamps: true,
95 |   }
96 | );
98 | // Hash password before saving
99 | mentorSchema.pre("save", async function () {
100 |   if (!this.isModified("password")) {
101 |     return;
102 |   }
104 |   const salt = await bcrypt.genSalt(10);
105 |   this.password = await bcrypt.hash(this.password, salt);
106 | });
108 | // Check password
109 | mentorSchema.methods.matchPassword = async function (enteredPassword) {
110 |   return await bcrypt.compare(enteredPassword, this.password);
111 | };
113 | module.exports = mongoose.model("Mentor", mentorSchema);
```

(0.7 KB)

```
1 | const mongoose = require("mongoose");
3 | const notificationSchema = new mongoose.Schema(
4 |   {
5 |     userId: { type: mongoose.Schema.Types.ObjectId, required: true },
6 |     userRole: { type: String, enum: ["student", "mentor", "admin"], required: true },
7 |     title: { type: String, required: true },
8 |     message: { type: String, required: true },
9 |     type: {
10 |       type: String,
11 |       enum: ["meeting", "training", "feedback", "system", "certificate", "general"],
12 |       default: "general",
13 |     },
14 |     isRead: { type: Boolean, default: false },
15 |     link: { type: String, default: "" },
16 |     icon: { type: String, default: "bell" },
17 |   },
18 |   { timestamps: true }
19 | );
```

```
23 | module.exports = mongoose.model("Notification", notificationSchema);
```

(1.2 KB)

```
1 | const mongoose = require("mongoose");
3 | const progressSchema = new mongoose.Schema(
4 |   {
5 |     studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student", required: true, unique: true },
6 |     trainingCompletion: { type: Number, default: 0, min: 0, max: 100 }, // %
7 |     meetingsAttended: { type: Number, default: 0 },
8 |     totalMeetingsScheduled: { type: Number, default: 0 },
9 |     quizScores: [
10 |       {
11 |         trainingId: { type: mongoose.Schema.Types.ObjectId, ref: "Training" },
12 |         score: Number,
13 |         maxScore: Number,
14 |         attemptedAt: { type: Date, default: Date.now },
15 |       },
16 |     ],
17 |     assignmentsSubmitted: { type: Number, default: 0 },
18 |     attendanceRate: { type: Number, default: 0, min: 0, max: 100 }, // %
19 |     overallScore: { type: Number, default: 0, min: 0, max: 100 }, // weighted composite
20 |     placementReadiness: { type: Number, default: 0, min: 0, max: 100 },
21 |     lastUpdated: { type: Date, default: Date.now },
22 |     milestones: [
23 |       {
24 |         title: String,
25 |         achievedAt: Date,
26 |         type: { type: String, enum: ["training", "meeting", "quiz", "certificate"] },
27 |       },
28 |     ],
29 |   },
30 |   { timestamps: true }
31 | );
```

```
33 | module.exports = mongoose.model("Progress", progressSchema);
```

(1.6 KB)

```
1 | const mongoose = require("mongoose");
2 | const bcrypt = require("bcryptjs");
4 | const studentSchema = new mongoose.Schema(
5 |   {
6 |     name: {
7 |       type: String,
8 |       required: true,
9 |       trim: true,
10 |     },
12 |     email: {
13 |       type: String,
14 |       required: true,
15 |       unique: true,
16 |       lowercase: true,
17 |       trim: true,
18 |     },
20 |     password: {
21 |       type: String,
22 |       required: true,
```

```
23 |     minlength: 6,
24 |   },
25 |   phone: {
26 |     type: String,
27 |     default: "",
28 |   },
29 |   bio: {
30 |     type: String,
31 |     default: "",
32 |   },
33 |   profilePic: {
34 |     type: String,
35 |     default: "",
36 |   },
37 |   resumeUrl: {
38 |     type: String,
39 |     default: "",
40 |   },
41 |   skills: [
42 |     {
43 |       type: String,
44 |     },
45 |   ],
46 |   assignedMentor: {
47 |     type: mongoose.Schema.Types.ObjectId,
48 |     ref: "Mentor",
49 |     default: null,
50 |   },
51 |   enrolledTrainings: [
52 |     {
53 |       type: mongoose.Schema.Types.ObjectId,
54 |       ref: "Training",
55 |     },
56 |   ],
57 |   role: {
58 |     type: String,
59 |     default: "student",
60 |   },
61 |   isActive: {
62 |     type: Boolean,
63 |     default: true,
64 |   },
65 |   lastLogin: {
66 |     type: Date,
67 |   },
68 | },
69 | {
70 |   timestamps: true,
71 | }
72 | );
73 | // Hash password before saving
74 | studentSchema.pre("save", async function () {
75 |   if (!this.isModified("password")) {
76 |     return;
77 |   }
78 |   const salt = await bcrypt.genSalt(10);
79 |   this.password = await bcrypt.hash(this.password, salt);
80 | });
81 | // Check password
82 | studentSchema.methods.matchPassword = async function (enteredPassword) {
83 |   return await bcrypt.compare(enteredPassword, this.password);
84 | };
85 | module.exports = mongoose.model("Student", studentSchema);
```

(1.6 KB)

```
1 | const mongoose = require("mongoose");
3 | const videoSchema = new mongoose.Schema({
4 |   title: String,
5 |   url: String,
6 |   duration: String,
7 |   order: Number,
8 | });
10 | const quizSchema = new mongoose.Schema({
11 |   question: String,
12 |   options: [String],
13 |   correctAnswer: Number,
14 |   points: { type: Number, default: 10 },
15 | });
17 | const assignmentSchema = new mongoose.Schema({
18 |   title: String,
19 |   description: String,
20 |   dueDate: Date,
21 |   maxScore: { type: Number, default: 100 },
22 | });
24 | const trainingSchema = new mongoose.Schema(
25 |   {
26 |     title: { type: String, required: true, trim: true },
27 |     description: { type: String, required: true },
28 |     category: {
29 |       type: String,
30 |       enum: ["Web Development", "Data Science", "DSA", "Cloud", "AI/ML", "Soft Skills", "Other"],
31 |       default: "Other",
32 |     },
33 |     thumbnail: { type: String, default: "" },
34 |     level: { type: String, enum: ["Beginner", "Intermediate", "Advanced"], default: "Beginner" },
35 |     duration: { type: String, default: "" },
36 |     videos: [videoSchema],
37 |     quizzes: [quizSchema],
38 |     assignments: [assignmentSchema],
39 |     enrolledStudents: [
40 |       {
41 |         studentId: { type: mongoose.Schema.Types.ObjectId, ref: "Student" },
42 |         enrolledAt: { type: Date, default: Date.now },
43 |         completedVideos: [Number],
44 |         quizScore: { type: Number, default: 0 },
45 |         isCompleted: { type: Boolean, default: false },
46 |         completedAt: Date,
47 |       },
48 |     ],
49 |     certificateTemplate: { type: String, default: "default" },
50 |     isPublished: { type: Boolean, default: true },
51 |     instructor: { type: String, default: "" },
52 |     tags: [String],
53 |   },
54 |   { timestamps: true }
55 | );
57 | module.exports = mongoose.model("Training", trainingSchema);
58 |
1 | const mongoose = require("mongoose");
3 | const userSchema = new mongoose.Schema(
4 |   {
5 |     name: {
6 |       type: String,
7 |       required: true,
8 |     },
10 |     email: {
11 |       type: String,
12 |       required: true,
13 |       unique: true,
14 |     },
16 |     password: {
17 |       type: String,
18 |       required: true,
19 |     },
20 |   },
21 |   {
```

KATALYST

Source Code: backend/models/user.js (Cont.)

Generated: 22/8/2026 | Backend

```
22 |     timestamps: true,
23 |   }
24 | });
25 | module.exports = mongoose.model("User", UserSchema);
26 |
1 | {
2 |   "name": "katalyst-backend",
3 |   "version": "2.0.0",
4 |   "description": "Katalyst Student-Mentor Learning Platform - Backend API",
5 |   "main": "server.js",
6 |   "scripts": {
7 |     "start": "node server.js",
8 |     "dev": "nodemon server.js",
9 |     "seed": "node seed.js",
10 |    "generate-pdf": "node generate_all_files_pdf.js"
11 |  },
12 |  "keywords": [
13 |    "katalyst",
14 |    "learning",
15 |    "mentorship",
16 |    "education"
17 |  ],
18 |  "author": "Katalyst Team",
19 |  "license": "MIT",
20 |  "type": "commonjs",
21 |  "dependencies": {
22 |    "@google/generative-ai": "^0.24.1",
23 |    "bcryptjs": "^2.4.3",
24 |    "cors": "^2.8.6",
25 |    "dotenv": "^17.4.2",
26 |    "express": "^5.2.1",
27 |    "express-rate-limit": "^7.5.0",
28 |    "express-validator": "^7.2.1",
29 |    "helmet": "^8.0.0",
30 |    "jsonwebtoken": "^9.0.2",
31 |    "mongoose": "^9.9.1",
32 |    "multer": "^1.4.5-lts.1",
33 |    "nodemailer": "^6.10.1",
34 |    "pdfkit": "^0.19.1",
35 |    "uuid": "^11.1.0"
36 |  },
37 |  "devDependencies": {
38 |    "nodemon": "^3.1.14"
39 |  }
40 | }
41 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getDashboard,
7 |   getAllStudents,
8 |   updateStudent,
9 |   deleteStudent,
10 |   getAllMentors,
11 |   createMentor,
12 |   deleteMentor,
13 |   assignMentor,
14 |   getReports,
15 |   sendBulkNotification,
16 | } = require("../controllers/adminController");
17 | router.use(protect, allowRoles("admin"));
18 | router.get("/dashboard", getDashboard);
19 | router.get("/students", getAllStudents);
20 | router.put("/students/:id", updateStudent);
21 | router.delete("/students/:id", deleteStudent);
22 | router.get("/mentors", getAllMentors);
23 | router.post("/mentors", createMentor);
24 | router.delete("/mentors/:id", deleteMentor);
25 | router.post("/assign-mentor", assignMentor);
26 | router.get("/reports", getReports);
```

```
29 | router.post("/notify", sendBulkNotification);
30 | module.exports = router; (0.6 KB)
31 |
32 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   analyzeResume,
7 |   careerRoadmap,
8 |   scholarshipRecommendations,
9 |   assistantChat,
10 | } = require("../controllers/aiController");
11 | router.use(protect);
12 | router.post("/chatbot", assistantChat);
13 | router.use(allowRoles("student"));
14 | router.post("/resume-analyze", analyzeResume);
15 | router.post("/career-roadmap", careerRoadmap);
16 | router.post("/scholarships", scholarshipRecommendations);
17 | module.exports = router; (0.4 KB)
18 |
19 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { registerStudent, login, getMe, resetPassword } = require("../controllers/authController");
4 | const { protect } = require("../middleware/auth");
5 |
6 | router.post("/register", registerStudent);
7 | router.post("/login", login);
8 | router.post("/reset-password", resetPassword);
9 | router.get("/me", protect, getMe);
10 | module.exports = router; (0.9 KB)
11 |
12 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   bookMeeting,
7 |   getStudentMeetings,
8 |   getMentorMeetings,
9 |   getAllMeetingsAdmin,
10 |   updateMeetingStatus,
11 |   submitStudentFeedback,
12 |   cancelMeeting,
13 | } = require("../controllers/meetingController");
14 | router.use(protect);
15 | router.post("/", allowRoles("student"), bookMeeting);
16 | router.get("/student", allowRoles("student"), getStudentMeetings);
17 | router.get("/mentor", allowRoles("mentor"), getMentorMeetings);
18 | router.get("/admin", allowRoles("admin"), getAllMeetingsAdmin);
19 | router.put("/:id/status", allowRoles("mentor", "admin"), updateMeetingStatus);
20 | router.post("/:id/feedback", allowRoles("student"), submitStudentFeedback);
21 | router.delete("/:id", allowRoles("student", "admin"), cancelMeeting);
22 | module.exports = router; (0.6 KB)
23 |
24 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getDashboard,
7 |   getStudents,
8 |   respondToMeeting,
9 |   addMeetingNotes,
10 |   giveFeedback,
11 |   getMeetings,
12 | } = require("../controllers/mentorController");
13 | router.use(protect, allowRoles("mentor"));
14 | router.get("/dashboard", getDashboard);
15 | router.get("/students", getStudents);
16 | router.get("/meetings", getMeetings);
17 | router.put("/meeting/:id", respondToMeeting);
```



```
20 | router.post("/meeting/:id/notes", addMeetingNotes);
21 | router.post("/feedback", giveFeedback);
22 | module.exports = router; (0.4 KB)
23 |
24 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const {
5 |   getNotifications,
6 |   markAsRead,
7 |   markAllAsRead,
8 |   deleteNotification,
9 | } = require("../controllers/notificationController");
11 | router.use(protect);
13 | router.get("/", getNotifications);
14 | router.put("/read-all", markAllAsRead);
15 | router.put("/:id/read", markAsRead);
16 | router.delete("/:id", deleteNotification);
17 | module.exports = router; (0.6 KB)
18 |
19 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getStudentProgress,
7 |   getPlacementReadiness,
8 |   getAdminProgressReport,
9 | } = require("../controllers/progressController");
11 | router.use(protect);
13 | router.get("/", allowRoles("student"), getStudentProgress);
14 | router.get("/placement", allowRoles("student"), getPlacementReadiness);
15 | router.get("/admin", allowRoles("admin"), getAdminProgressReport);
17 | module.exports = router; (1.3 KB)
18 |
19 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const multer = require("multer");
4 | const path = require("path");
5 | const { protect } = require("../middleware/auth");
6 | const { allowRoles } = require("../middleware/roleCheck");
7 | const {
8 |   getDashboard,
9 |   getProfile,
10 |   updateProfile,
11 |   uploadResume,
12 |   getCertificates,
13 |   getProgress,
14 |   getMeetings,
15 | } = require("../controllers/studentController");
17 | // Multer setup for resume upload
18 | const storage = multer.diskStorage({
19 |   destination: (req, file, cb) => cb(null, "uploads/resumes/"),
20 |   filename: (req, file, cb) =>
21 |     cb(null, `${req.user.id}-${Date.now()}${path.extname(file.originalname)}`),
22 | });
23 | const upload = multer({
24 |   storage,
25 |   limits: { fileSize: 5 * 1024 * 1024 }, // 5MB
26 |   fileFilter: (req, file, cb) => {
27 |     const allowed = [".pdf", ".doc", ".docx"];
28 |     if (!allowed.includes(path.extname(file.originalname).toLowerCase()))
29 |       return cb(new Error("Only PDF/DOC files allowed"));
30 |     cb(null, true);
31 |   },
32 | });
34 | router.use(protect, allowRoles("student"));
36 | router.get("/dashboard", getDashboard);
37 | router.get("/profile", getProfile);
38 | router.put("/profile", updateProfile);
39 | router.post("/resume", upload.single("resume"), uploadResume);
```

KATALYST.

Source Code: backend/routes/student.js (Cont.)

Generated: 22/8/2026 | Backend

```
40 | router.get("/certificates", getCertificates);
41 | router.get("/progress", getProgress);
42 | router.get("/meetings", getMeetings);
43 | module.exports = router; (0.9 KB)
45 |
1 | const express = require("express");
2 | const router = express.Router();
3 | const { protect } = require("../middleware/auth");
4 | const { allowRoles } = require("../middleware/roleCheck");
5 | const {
6 |   getAllTrainings,
7 |   getTrainingById,
8 |   enrollTraining,
9 |   completeVideo,
10 | submitQuiz,
11 | createTraining,
12 | updateTraining,
13 | deleteTraining,
14 | } = require("../controllers/trainingController");
16 | // Public
17 | router.get("/", getAllTrainings);
18 | router.get("/:id", protect, getTrainingById);
20 | // Student
21 | router.post("/:id/enroll", protect, allowRoles("student"), enrollTraining);
22 | router.post("/:id/complete-video", protect, allowRoles("student"), completeVideo);
23 | router.post("/:id/submit-quiz", protect, allowRoles("student"), submitQuiz);
25 | // Admin
26 | router.post("/", protect, allowRoles("admin"), createTraining);
27 | router.put("/:id", protect, allowRoles("admin"), updateTraining);
28 | router.delete("/:id", protect, allowRoles("admin"), deleteTraining);
29 | module.exports = router; (3.9 KB)
31 |
1 | const mongoose = require("mongoose");
2 | const dotenv = require("dotenv");
3 | const bcrypt = require("bcryptjs");
4 | const connectDB = require("../config/db");
5 | const Student = require("../models/Student");
6 | const Mentor = require("../models/Mentor");
7 | const Admin = require("../models/Admin");
8 | const Training = require("../models/Training");
9 | const Progress = require("../models/Progress");
10 | const Notification = require("../models/Notification");
11 | const Certificate = require("../models/Certificate");
13 | dotenv.config();
15 | const seed = async () => {
16 |   try {
17 |     await connectDB();
18 |     await Promise.all([
19 |       Student.deleteMany(),
20 |       Mentor.deleteMany(),
21 |       Admin.deleteMany(),
22 |       Training.deleteMany(),
23 |       Progress.deleteMany(),
24 |       Notification.deleteMany(),
25 |       Certificate.deleteMany(),
26 |     ]);
28 |     const admin = await Admin.create({
29 |       name: "System Admin",
30 |       email: "admin@katalyst.io",
31 |       password: "Admin@123",
32 |     });
34 |     const mentor1 = await Mentor.create({
35 |       name: "Dr. Sarah Jenkins",
36 |       email: "sarah@katalyst.io",
37 |       password: "Mentor@123",
38 |       expertise: ["Web Development", "React", "Career Coaching"],
39 |       designation: "Senior Mentor",
40 |       company: "Katalyst Labs",
41 |       bio: "Guiding students to build scalable web apps and strong career roadmaps.",
42 |     });
44 |     const student1 = await Student.create({
```

```
45 |     name: "Diksha Sharma",
46 |     email: "diksha@katalyst.io",
47 |     password: "Student@123",
48 |     phone: "1234567890",
49 |     bio: "Full Stack student learning modern web development.",
50 |     skills: ["HTML", "CSS", "JavaScript"],
51 |     assignedMentor: mentor1._id,
52 |   });
53 |
54 |   const training1 = await Training.create({
55 |     title: "Web Development Masterclass",
56 |     description: "Learn HTML, CSS, JavaScript and React in a project-based path.",
57 |     category: "Web Development",
58 |     level: "Beginner",
59 |     duration: "6 weeks",
60 |     thumbnail: "https://i.imgur.com/Ua7I9qH.png",
61 |     instructor: "Katalyst Mentors",
62 |     tags: ["web", "frontend", "react"],
63 |     videos: [
64 |       { title: "HTML Basics", url: "https://youtu.be/example", duration: "12m", order: 1 },
65 |       { title: "CSS Essentials", url: "https://youtu.be/example", duration: "20m", order: 2 },
66 |       { title: "JavaScript Fundamentals", url: "https://youtu.be/example", duration: "25m", order: 3 },
67 |       { title: "React UI Components", url: "https://youtu.be/example", duration: "30m", order: 4 },
68 |     ],
69 |     quizzes: [
70 |       { question: "What does HTML stand for?", options: ["Hypertext Markup Language", "Hyperlinks and Text M
71 |     ],
72 |     assignments: [
73 |       { title: "Build Portfolio Homepage", description: "Create a responsive portfolio landing page.", dueDa
74 |     ],
75 |     enrolledStudents: [{ studentId: student1._id },
76 |   });
77 |
78 |   await Progress.create({
79 |     studentId: student1._id,
80 |     trainingCompletion: 25,
81 |     meetingsAttended: 1,
82 |     totalMeetingsScheduled: 2,
83 |     quizScores: [{ trainingId: training1._id, score: 8, maxScore: 10 }],
84 |     assignmentsSubmitted: 1,
85 |     attendanceRate: 80,
86 |     overallScore: 66,
87 |     placementReadiness: 60,
88 |     hasResume: false,
89 |   });
90 |
91 |   await Notification.create({
92 |     userId: student1._id,
93 |     userRole: "student",
94 |     title: "Welcome to Katalyst!",
95 |     message: "Your student dashboard is ready. Start your first training now.",
96 |     type: "system",
97 |   });
98 |
99 |   await Certificate.create({
100 |     studentId: student1._id,
101 |     trainingId: training1._id,
102 |     studentName: student1.name,
103 |     trainingTitle: training1.title,
104 |   });
105 |
106 |   console.log("Seed data created successfully");
107 |   process.exit();
108 | } catch (error) {
109 |   console.error("Seed error:", error.message);
110 |   process.exit(1);
111 | }
112 | };
113 |
114 | seed();
115 |
```

KATALYST

Source Code: backend/server.js

Generated: 22/8/2026 | Backend

(2.7 KB)

```
1 | const express = require("express");
2 | const cors = require("cors");
3 | const helmet = require("helmet");
4 | const rateLimit = require("express-rate-limit");
5 | const path = require("path");
6 | require("dotenv").config();
7 |
8 | const connectDB = require("../config/db");
9 |
10 | // Routes
11 | const authRoutes = require("../routes/auth");
12 | const studentRoutes = require("../routes/student");
13 | const mentorRoutes = require("../routes/mentor");
14 | const adminRoutes = require("../routes/admin");
15 | const trainingRoutes = require("../routes/training");
16 | const meetingRoutes = require("../routes/meeting");
17 | const notificationRoutes = require("../routes/notification");
18 | const progressRoutes = require("../routes/progress");
19 | const aiRoutes = require("../routes/ai");
20 |
21 | const app = express();
22 |
23 | // Connect to MongoDB
24 | connectDB();
25 |
26 | // Security middleware
27 | app.use(helmet());
28 | app.use(
29 |   cors({
30 |     origin: [
31 |       "http://localhost:5173",
32 |     ],
33 |     credentials: true,
34 |   })
35 | );
36 |
37 | // Rate limiting
38 | const limiter = rateLimit({
39 |   windowMs: 15 * 60 * 1000, // 15 min
40 |   max: 100,
41 |   message: { message: "Too many requests, please try again later." },
42 | });
43 | app.use("/api/", limiter);
44 |
45 | // Auth rate limit (stricter)
46 | const authLimiter = rateLimit({
47 |   windowMs: 15 * 60 * 1000,
48 |   max: 20,
49 |   message: { message: "Too many login attempts, please try again later." },
50 | });
51 | app.use("/api/auth/", authLimiter);
52 |
53 | // Body parsing
54 | app.use(express.json({ limit: "10mb" }));
55 | app.use(express.urlencoded({ extended: true, limit: "10mb" }));
56 |
57 | // Static files (uploaded resumes)
58 | app.use("/uploads", express.static(path.join(__dirname, "uploads")));
59 |
60 | // Health check
61 | app.get("/", (req, res) => {
62 |   res.json({
63 |     message: "ðŸš€ Katalyst API is running!",
64 |     version: "1.0.0",
65 |     timestamp: new Date().toISOString(),
66 |   });
67 | });
68 |
69 | // API Routes
70 | app.use("/api/auth", authRoutes);
71 | app.use("/api/students", studentRoutes);
72 | app.use("/api/mentors", mentorRoutes);
73 | app.use("/api/admin", adminRoutes);
74 | app.use("/api/trainings", trainingRoutes);
75 | app.use("/api/meetings", meetingRoutes);
76 | app.use("/api/notifications", notificationRoutes);
77 | app.use("/api/progress", progressRoutes);
78 | app.use("/api/ai", aiRoutes);
79 |
80 | // 404 handler
81 | app.use((req, res) => {
```

KATALYST

Source Code: backend/server.js (Cont.)

Generated: 22/8/2026 | Backend

```
83 |   res.status(404).json({ message: "Route not found" });
84 | });
85 | // Global error handler
86 | app.use((err, req, res, next) => {
87 |   console.error("ðŸ’¥ Error:", err.stack);
88 |   res.status(err.status || 500).json({
89 |     message: err.message || "Internal Server Error",
90 |     ...(process.env.NODE_ENV === "development" && { stack: err.stack }),
91 |   });
92 | });
93 | });
94 | const PORT = process.env.PORT || 5000;
95 | app.listen(PORT, () => {
96 |   console.log(`ðŸš€ Katalyst server running on port ${PORT}`);
97 |   console.log(`ðŸš€ Environment: ${process.env.NODE_ENV || "development"}`);
98 | });
99 | });
```

100 | module.exports = app; (0.2 KB)

```
1 | const jwt = require("jsonwebtoken");
2 | const generateToken = (id, role) => {
3 |   return jwt.sign({ id, role }, process.env.JWT_SECRET, {
4 |     expiresIn: process.env.JWT_EXPIRES_IN || "7d",
5 |   });
6 | };
7 | 
```

8 | module.exports = generateToken; (1.5 KB)

```
10 | /**
11 |  * Calculate overall progress score (weighted composite)
12 |  * Weights: Training 40%, Meetings 30%, Quiz 20%, Attendance 10%
13 |  */
14 | const calculateOverallProgress = ({
15 |   trainingCompletion = 0,
16 |   meetingsAttended = 0,
17 |   totalMeetingsScheduled = 0,
18 |   quizScores = [],
19 |   attendanceRate = 0,
20 | }) => {
21 |   const meetingRate =
22 |     totalMeetingsScheduled > 0
23 |       ? (meetingsAttended / totalMeetingsScheduled) * 100
24 |       : 0;
25 |   const avgQuizScore =
26 |     quizScores.length > 0
27 |       ? quizScores.reduce((sum, q) => sum + (q.score / q.maxScore) * 100, 0) /
28 |         quizScores.length
29 |       : 0;
30 |   const overall =
31 |     trainingCompletion * 0.4 +
32 |     meetingRate * 0.3 +
33 |     avgQuizScore * 0.2 +
34 |     attendanceRate * 0.1;
35 |   return Math.round(Math.min(overall, 100));
36 | };
37 | /**
38 |  * Calculate placement readiness score
39 |  */
40 | const calculatePlacementReadiness = ({
41 |   overallScore = 0,
42 |   quizScores = [],
43 |   assignmentsSubmitted = 0,
44 |   meetingsAttended = 0,
45 |   hasResume = false,
46 | }) => {
47 |   const quizAvg =
48 |     quizScores.length > 0
49 |       ? quizScores.reduce((s, q) => s + (q.score / q.maxScore) * 100, 0) /
50 |         quizScores.length
51 |       : 0;
52 |   const resumeBonus = hasResume ? 10 : 0;
53 |   const meetingBonus = Math.min(meetingsAttended * 5, 20);
54 |   const assignmentBonus = Math.min(assignmentsSubmitted * 5, 15);
55 |   const score =
```

```
53 |     overallScore * 0.4 + quizAvg * 0.3 + resumeBonus + meetingBonus + assignmentBonus;
55 |     return Math.round(Math.min(score, 100));
56 | };
58 | module.exports = { calculateOverallProgress, calculatePlacementReadiness };
59 |
1 | const Progress = require("../models/Progress");
2 | const Training = require("../models/Training");
3 | const { calculateOverallProgress, calculatePlacementReadiness } = require("./progressCalculator");
5 | const syncStudentProgress = async (studentId) => {
6 |     const progress =
7 |         (await Progress.findOne({ studentId })) ||
8 |         new Progress({ studentId, trainingCompletion: 0, meetingsAttended: 0, totalMeetingsScheduled: 0, attendanc
10 |     const trainings = await Training.find({ "enrolledStudents.studentId": studentId });
11 |     const completedCount = trainings.filter((training) => {
12 |         const enrollment = training.enrolledStudents.find(
13 |             (item) => item.studentId.toString() === studentId.toString()
14 |         );
15 |         return enrollment?.isCompleted;
16 |     }).length;
18 |     progress.trainingCompletion = trainings.length
19 |         ? Math.round((completedCount / trainings.length) * 100)
20 |         : 0;
22 |     // Calculate attendanceRate based on meetings
23 |     const meetingRate = progress.totalMeetingsScheduled > 0
24 |         ? Math.round((progress.meetingsAttended / progress.totalMeetingsScheduled) * 100)
25 |         : 100; // default to 100 if no meetings are scheduled yet
26 |     progress.attendanceRate = Math.min(meetingRate, 100);
28 |     progress.overallScore = calculateOverallProgress(progress.toObject());
29 |     progress.placementReadiness = calculatePlacementReadiness({
30 |         overallScore: progress.overallScore,
31 |         quizScores: progress.quizScores,
32 |         assignmentsSubmitted: progress.assignmentsSubmitted,
33 |         meetingsAttended: progress.meetingsAttended,
34 |         hasResume: progress.hasResume,
35 |     });
36 |     progress.lastUpdated = new Date();
38 |     return progress.save();
39 | };
41 | module.exports = { syncStudentProgress };
42 |
1 | const nodemailer = require("nodemailer");
3 | const transporter = nodemailer.createTransport({
4 |     service: "gmail",
5 |     auth: {
6 |         user: process.env.EMAIL_USER,
7 |         pass: process.env.EMAIL_PASS, // App password
8 |     },
9 | });
11 | const sendEmail = async ({ to, subject, html }) => {
12 |     try {
13 |         const info = await transporter.sendMail({
14 |             from: `Katalyst Platform <${process.env.EMAIL_USER}>`,
15 |             to,
16 |             subject,
17 |             html,
18 |         });
19 |         console.log(`Email sent:`, info.messageId);
20 |         return { success: true };
21 |     } catch (error) {
22 |         console.error("Email failed:", error.message);
23 |         return { success: false, error: error.message };
24 |     }
25 | };
27 | // Email templates
28 | const meetingAcceptedEmail = (studentName, mentorName, date, time, meetLink) => `
29 | <div style="font-family: Arial, sans-serif; max-width: 600px; margin: 0 auto;">
30 |   <div style="background: linear-gradient(135deg, #1e3a8a, #3b82f6); padding: 30px; border-radius: 12px 12px
31 |     <h1 style="color: white; margin: 0;">Katalyst</h1>
32 |   </div>
33 |   <div style="background: #f8fafc; padding: 30px; border-radius: 0 0 12px 12px;">
34 |     <h2>Meeting Confirmed! <B%</h2>
```

```
35 |         <p>Hi <strong>${studentName}</strong>, </p>
36 |         <p>Your meeting with <strong>${mentorName}</strong> has been accepted.</p>
37 |         <div style="background: white; padding: 20px; border-radius: 8px; border-left: 4px solid #3b82f6;">
38 |             <p><strong>🕒 Date:</strong> ${date}</p>
39 |             <p><strong>🕒 Time:</strong> ${time}</p>
40 |             <p><strong>🔗 Meet Link:</strong> <a href="${meetLink}">${meetLink}</a></p>
41 |         </div>
42 |         <p style="color: #6b7280; font-size: 14px;">Best of luck with your mentorship session!</p>
43 |     </div>
44 | </div>
45 | `;
46 |
47 | const meetingRejectedEmail = (studentName, mentorName, reason) => `
48 |     <div style="font-family: Arial, sans-serif; max-width: 600px; margin: 0 auto;">
49 |         <div style="background: linear-gradient(135deg, #1e3a8a, #3b82f6); padding: 30px; border-radius: 12px 12px
50 |             <h1 style="color: white; margin: 0;">Katalyst</h1>
51 |         </div>
52 |         <div style="background: #f8fafc; padding: 30px; border-radius: 0 0 12px 12px;">
53 |             <h2>Meeting Update</h2>
54 |             <p>Hi <strong>${studentName}</strong>, </p>
55 |             <p>Your meeting request with <strong>${mentorName}</strong> was not accepted at this time.</p>
56 |             ${reason ? `<p><strong>Reason:</strong> ${reason}</p>` : ""}
57 |             <p>Please book another slot or contact the admin for assistance.</p>
58 |         </div>
59 |     </div>
60 | `;
61 |
62 | module.exports = { sendEmail, meetingAcceptedEmail, meetingRejectedEmail };
63 |
64 | {
65 |   version: "3.9"
66 | }
67 |
68 | {
69 |   services:
70 |     backend:
71 |       build:
72 |         context: ./backend
73 |         dockerfile: Dockerfile
74 |         env_file:
75 |           - ./backend/.env.example
76 |         ports:
77 |           - "5000:5000"
78 |         volumes:
79 |           - ./backend/uploads:/usr/src/app/uploads
80 |         depends_on:
81 |           - mongo
82 |       frontend:
83 |         build:
84 |           context: ./frontend
85 |           dockerfile: Dockerfile
86 |           env_file:
87 |             - ./frontend/.env.example
88 |         ports:
89 |           - "4173:4173"
90 |         depends_on:
91 |           - backend
92 |       mongo:
93 |         image: mongo:7.0
94 |         restart: unless-stopped
95 |         ports:
96 |           - "27017:27017"
97 |         volumes:
98 |           - mongo-data:/data/db
99 |       volumes:
100 |         mongo-data:
```

(0.0 KB)

```
1 | VITE_API_URL=http://localhost:5000/api (0.1 KB)
```

(0.2 KB)

```
1 | {
2 |   "appId": "com.katalyst.student",
3 |   "appName": "Katalyst 2.0",
4 |   "webDir": "dist"
5 | }
6 |
7 | FROM node:20-alpine
8 | WORKDIR /usr/src/app
9 | COPY package*.json ./
10 | RUN npm install
11 | COPY . .
12 | RUN npm run build
13 | EXPOSE 4173
14 | CMD ["npm", "run", "preview", "--", "0.0.0.0", "0.0.0.0"]
15 |
16 | import js from '@eslint/js'
17 | import globals from 'globals'
18 | import reactHooks from 'eslint-plugin-react-hooks'
19 | import reactRefresh from 'eslint-plugin-react-refresh'
20 | import { defineConfig, globalIgnores } from 'eslint/config'
21 | export default defineConfig([
22 |   globalIgnores(['dist']),
23 |   {
24 |     files: ['**/*.js', '*.jsx'],
25 |     extends: [
26 |       js.configs.recommended,
27 |       reactHooks.configs.flat.recommended,
28 |       reactRefresh.configs.vite,
29 |     ],
30 |     languageOptions: {
31 |       globals: globals.browser,
32 |       parserOptions: { ecmaFeatures: { jsx: true } },
33 |     },
34 |   },
35 | ],)
36 |
37 | <!doctype html>
38 | <html lang="en">
39 |   <head>
40 |     <meta charset="UTF-8" />
41 |     <link rel="icon" type="image/svg+xml" href="/favicon.svg" />
42 |     <meta name="viewport" content="width=device-width, initial-scale=1.0" />
43 |     <title>frontend</title>
44 |   </head>
45 |   <body>
46 |     <div id="root"></div>
47 |     <script type="module" src="/src/main.jsx"></script>
48 |   </body>
49 | </html>
50 |
51 | (0.4 KB)
```

(0.5 KB)

```
1 | {
2 |   "name": "katalyst-frontend",
3 |   "private": true,
4 |   "version": "2.0.0",
5 |   "type": "module",
6 |   "scripts": {
7 |     "dev": "vite",
8 |     "build": "vite build",
9 |     "preview": "vite preview"
10 |  },
11 |   "dependencies": {
12 |     "@vitejs/plugin-react": "^5.0.0",
13 |     "axios": "^1.19.0",
14 |     "lucide-react": "^1.31.0",
15 |     "react": "^19.0.0",
16 |     "react-dom": "^19.0.0",
17 |     "react-router-dom": "^7.18.2",
18 |     "recharts": "^2.15.4",
19 |     "vite": "^8.2.0"
20 |  },
21 | }
```



```
21 |   "devDependencies": {
22 |     "autoprefixer": "^10.4.21",
23 |     "postcss": "^8.5.3",
24 |     "tailwindcss": "3.4.17"
25 |   }
26 | } // frontend/public/css/normalize (0.1 KB)
27 |
1 | export default {
2 |   plugins: {
3 |     tailwindcss: {},
4 |     autoprefixer: {},
5 |   },
6 | }, // frontend/public/Login.css (2.2 KB)
7 |
1 | .login-page {
2 |   min-height: 100vh;
3 |   background: #09090b;
4 |   display: flex;
5 |   justify-content: center;
6 |   align-items: center;
7 |   padding: 30px;
8 |   position: relative;
9 | }
10 |
11 | .back-button {
12 |   position: absolute;
13 |   top: 30px;
14 |   left: 5%;
15 |   background: transparent;
16 |   border: none;
17 |   color: #a1a1aa;
18 |   font-size: 15px;
19 |   cursor: pointer;
20 | }
21 |
22 | .back-button:hover {
23 |   color: white;
24 | }
25 |
26 | .login-card {
27 |   width: 100%;
28 |   max-width: 480px;
29 |   padding: 45px;
30 |   background: #111114;
31 |   border: 1px solid #27272a;
32 |   border-radius: 20px;
33 |   box-shadow: 0 30px 80px rgba(0, 0, 0, 0.5);
34 | }
35 |
36 | .login-logo {
37 |   font-size: 22px;
38 |   font-weight: 800;
39 |   letter-spacing: 2px;
40 |   margin-bottom: 35px;
41 | }
42 |
43 | .login-logo span {
44 |   color: #8b5cf6;
45 | }
46 |
47 | .login-card h1 {
48 |   font-size: 38px;
49 |   margin-bottom: 10px;
50 | }
51 |
52 | .login-subtitle {
53 |   color: #71717a;
54 |   margin-bottom: 30px;
55 | }
56 |
57 | .role-options {
58 |   display: flex;
59 |   flex-direction: column;
60 |   gap: 12px;
61 | }
62 |
63 | .role-card {
64 |   width: 100%;
65 |   padding: 17px;
66 |   background: #18181b;
```

```
67 | border: 1px solid #27272a;
68 | border-radius: 12px;
69 | color: white;
70 | display: flex;
71 | align-items: center;
72 | gap: 15px;
73 | text-align: left;
74 | cursor: pointer;
75 | }
77 | .role-card:hover {
78 |   border-color: #7c3aed;
79 | }
81 | .role-card.selected {
82 |   border-color: #8b5cf6;
83 |   background: #1c1729;
84 | }
86 | .role-icon {
87 |   width: 42px;
88 |   height: 42px;
89 |   display: flex;
90 |   align-items: center;
91 |   justify-content: center;
92 |   background: #27272a;
93 |   border-radius: 10px;
94 |   font-size: 20px;
95 | }
97 | .role-card h3 {
98 |   margin-bottom: 4px;
99 | }
101 | .role-card p {
102 |   color: #71717a;
103 |   font-size: 12px;
104 | }
106 | .continue-button {
107 |   width: 100%;
108 |   padding: 14px;
109 |   margin-top: 25px;
110 |   border: none;
111 |   border-radius: 8px;
112 |   background: #7c3aed;
113 |   color: white;
114 |   font-size: 15px;
115 |   cursor: pointer;
116 | }
118 | .continue-button:hover {
119 |   background: #8b5cf6;
120 | }
122 | .demo-button {
123 |   width: 100%;
124 |   padding: 13px;
125 |   margin-top: 10px;
126 |   border: 1px solid #3f3f46;
127 |   border-radius: 8px;
128 |   background: transparent;
129 |   color: white;
130 |   cursor: pointer;
131 | }
133 | .login-footer {
134 |   text-align: center;
135 |   color: #52525b;
136 |   font-size: 11px;
137 |   line-height: 1.6;
138 |   margin-top: 30px;
139 | }
140 |
```

(1.0 KB)

```
1 | # React + Vite
3 | This template provides a minimal setup to get React working in Vite with HMR and some ESLint rules.
5 | Currently, two official plugins are available:
7 | - [@vitejs/plugin-react](https://github.com/vitejs/vite-plugin-react/blob/main/packages/plugin-react) uses [Ox
8 | - [@vitejs/plugin-react-swc](https://github.com/vitejs/vite-plugin-react/blob/main/packages/plugin-react-swc)
10 | ## React Compiler
12 | The React Compiler is not enabled on this template because of its impact on dev & build performances. To add i
14 | ## Expanding the ESLint configuration
16 | If you are developing a production application, we recommend using TypeScript with type-aware lint rules enabl
17 |
1 | import axios from "axios";
3 | const API = axios.create({
4 |   baseURL: import.meta.env.VITE_API_URL || "http://localhost:5000/api",
5 | });
7 | API.interceptors.request.use((config) => {
8 |   const token = localStorage.getItem("token");
9 |   if (token) config.headers.Authorization = `Bearer ${token}`;
10 |   return config;
11 | });
13 | API.interceptors.response.use(
14 |   (res) => res,
15 |   (err) => {
16 |     if (err.response?.status === 401) {
17 |       localStorage.removeItem("token");
18 |       localStorage.removeItem("user");
19 |       if (!window.location.pathname.includes("/login")) {
20 |         window.location.href = "/login";
21 |       }
22 |     }
23 |     return Promise.reject(err);
24 |   }
25 | );
27 | export default API;
```

(5.6 KB)

```
1 | * {
2 |   margin: 0;
3 |   padding: 0;
4 |   box-sizing: border-box;
5 | }
7 | html {
8 |   scroll-behavior: smooth;
9 | }
11 | body {
12 |   font-family: Arial, Helvetica, sans-serif;
13 |   background: #09090b;
14 |   color: #ffffff;
15 | }
17 | button {
18 |   font-family: inherit;
19 |   cursor: pointer;
20 | }
22 | .app {
23 |   min-height: 100vh;
24 |   background: transparent;
25 |   position: relative;
26 | }
28 | /* NAVBAR */
30 | .navbar {
31 |   height: 80px;
32 |   padding: 0 7%;
33 |   display: flex;
34 |   align-items: center;
35 |   justify-content: space-between;
36 |   border-bottom: 1px solid #202024;
37 | }
39 | .logo {
40 |   font-size: 22px;
41 |   font-weight: 800;
42 |   letter-spacing: 2px;
```

```
43 | }
45 | .logo span {
46 |   color: #8b5cf6;
47 | }
49 | .nav-links {
50 |   display: flex;
51 |   gap: 35px;
52 | }
54 | .nav-links a {
55 |   color: #a1a1aa;
56 |   text-decoration: none;
57 |   font-size: 14px;
58 | }
60 | .nav-links a:hover {
61 |   color: white;
62 | }
64 | .nav-buttons {
65 |   display: flex;
66 |   gap: 12px;
67 | }
69 | .login-btn,
70 | .signup-btn {
71 |   padding: 10px 18px;
72 |   border-radius: 8px;
73 |   font-size: 14px;
74 | }
76 | .login-btn {
77 |   background: transparent;
78 |   color: white;
79 |   border: 1px solid #333338;
80 | }
82 | .signup-btn {
83 |   background: #7c3aed;
84 |   color: white;
85 |   border: none;
86 | }
88 | /* HERO */
90 | .hero {
91 |   min-height: 700px;
92 |   padding: 90px 7%;
93 |   display: grid;
94 |   grid-template-columns: 1fr 1fr;
95 |   gap: 80px;
96 |   align-items: center;
97 | }
99 | .badge {
100 |   display: inline-block;
101 |   padding: 8px 13px;
102 |   border: 1px solid #302456;
103 |   border-radius: 50px;
104 |   color: #a78bfa;
105 |   font-size: 11px;
106 |   letter-spacing: 1px;
107 |   margin-bottom: 25px;
108 | }
110 | .hero h1 {
111 |   font-size: clamp(60px, 7vw, 100px);
112 |   line-height: 0.9;
113 |   letter-spacing: -5px;
114 |   margin-bottom: 30px;
115 | }
117 | .hero h1 span {
118 |   color: #8b5cf6;
119 | }
121 | .hero-content > p {
122 |   max-width: 520px;
123 |   color: #a1a1aa;
124 |   font-size: 17px;
125 |   line-height: 1.7;
126 | }
```

```
128 | .hero-buttons {
129 |   margin-top: 35px;
130 |   display: flex;
131 |   gap: 15px;
132 | }
133 |
134 | .primary-btn,
135 | .secondary-btn {
136 |   padding: 14px 24px;
137 |   border-radius: 8px;
138 |   font-size: 15px;
139 | }
140 |
141 | .primary-btn {
142 |   border: none;
143 |   background: #7c3aed;
144 |   color: white;
145 | }
146 |
147 | .secondary-btn {
148 |   background: transparent;
149 |   border: 1px solid #3f3f46;
150 |   color: white;
151 | }
152 |
153 | /* DASHBOARD PREVIEW */
154 |
155 | .dashboard-preview {
156 |   padding: 25px;
157 |   border: 1px solid #27272a;
158 |   border-radius: 20px;
159 |   background: #111114;
160 |   box-shadow: 0 30px 80px rgba(0, 0, 0, 0.5);
161 | }
162 |
163 | .preview-header {
164 |   display: flex;
165 |   justify-content: space-between;
166 |   align-items: center;
167 |   margin-bottom: 25px;
168 | }
169 |
170 | .preview-header small,
171 | .progress-card small,
172 | .meeting-card small {
173 |   color: #71717a;
174 |   font-size: 10px;
175 |   letter-spacing: 1px;
176 | }
177 |
178 | .preview-header h3 {
179 |   margin-top: 6px;
180 | }
181 |
182 | .profile-circle {
183 |   width: 40px;
184 |   height: 40px;
185 |   border-radius: 50%;
186 |   background: #7c3aed;
187 |   display: flex;
188 |   justify-content: center;
189 |   align-items: center;
190 |   font-weight: bold;
191 | }
192 |
193 | .progress-card {
194 |   padding: 22px;
195 |   border: 1px solid #27272a;
196 |   border-radius: 14px;
197 |   background: #18181b;
198 | }
199 |
200 | .progress-top {
201 |   display: flex;
202 |   justify-content: space-between;
203 |   align-items: center;
204 | }
205 |
206 | .progress-top h2 {
207 |   font-size: 38px;
208 |   margin-top: 5px;
209 | }
```

```
211 | .progress-ring {
212 |   width: 65px;
213 |   height: 65px;
214 |   border: 5px solid #7c3aed;
215 |   border-radius: 50%;
216 |   display: flex;
217 |   align-items: center;
218 |   justify-content: center;
219 |   font-size: 13px;
220 | }
221 |
222 | .progress-bar {
223 |   height: 6px;
224 |   background: #27272a;
225 |   border-radius: 10px;
226 |   margin-top: 20px;
227 |   overflow: hidden;
228 | }
229 |
230 | .progress-fill {
231 |   width: 75%;
232 |   height: 100%;
233 |   background: #8b5cf6;
234 | }
235 |
236 | /* STATS */
237 |
238 | .stats {
239 |   display: grid;
240 |   grid-template-columns: 1fr 1fr;
241 |   gap: 12px;
242 |   margin-top: 12px;
243 | }
244 |
245 | .stat-card {
246 |   padding: 18px;
247 |   border-radius: 14px;
248 |   background: #18181b;
249 |   border: 1px solid #27272a;
250 | }
251 |
252 | .stat-card span {
253 |   display: block;
254 |   font-size: 10px;
255 |   color: #71717a;
256 | }
257 |
258 | .stat-card strong {
259 |   display: block;
260 |   font-size: 25px;
261 |   margin: 8px 0;
262 | }
263 |
264 | .stat-card small {
265 |   color: #a1a1aa;
266 | }
267 |
268 | /* MEETING */
269 |
270 | .meeting-card {
271 |   margin-top: 12px;
272 |   padding: 18px;
273 |   border-radius: 14px;
274 |   background: #18181b;
275 |   border: 1px solid #27272a;
276 |   display: flex;
277 |   justify-content: space-between;
278 |   align-items: center;
279 | }
280 |
281 | .meeting-card h4 {
282 |   margin: 7px 0;
283 | }
284 |
285 | .meeting-card p {
286 |   color: #71717a;
287 |   font-size: 13px;
288 | }
289 |
290 | .meeting-card button {
291 |   border: none;
292 |   background: transparent;
293 |   color: #a78bfa;
```

```
294 | }
295 | /* ABOUT */
296 | .about-section {
297 |   padding: 120px 7%;
298 |   border-top: 1px solid #202024;
299 | }
300 | .section-label {
301 |   color: #8b5cf6;
302 |   font-size: 11px;
303 |   letter-spacing: 2px;
304 |   margin-bottom: 20px;
305 | }
306 | .about-section h2 {
307 |   font-size: 60px;
308 |   line-height: 1;
309 |   letter-spacing: -3px;
310 | }
311 | .about-section h2 span {
312 |   color: #71717a;
313 | }
314 | .section-description {
315 |   max-width: 600px;
316 |   color: #a1a1aa;
317 |   line-height: 1.7;
318 |   margin-top: 25px;
319 | }
320 | /* FEATURES */
321 | .features-section {
322 |   padding: 0 7% 120px;
323 |   display: grid;
324 |   grid-template-columns: repeat(3, 1fr);
325 |   gap: 20px;
326 | }
327 | .feature-card {
328 |   padding: 35px;
329 |   border: 1px solid #27272a;
330 |   border-radius: 16px;
331 |   background: #111114;
332 | }
333 | .feature-number {
334 |   color: #8b5cf6;
335 |   font-size: 13px;
336 |   margin-bottom: 45px;
337 | }
338 | .feature-card h3 {
339 |   margin-bottom: 15px;
340 | }
341 | .feature-card p {
342 |   color: #71717a;
343 |   line-height: 1.6;
344 |   font-size: 14px;
345 | }
346 | /* FOOTER */
347 | footer {
348 |   padding: 50px 7%;
349 |   border-top: 1px solid #202024;
350 | }
351 | footer p {
352 |   color: #71717a;
353 |   margin: 12px 0 25px;
354 | }
355 | footer small {
356 |   color: #52525b;
357 | }
358 | /* RESPONSIVE */
359 | @media (max-width: 900px) {
360 |   .nav-links {
361 |     display: none;
362 |   }
363 | }
```

```
382 | .hero {
383 |   grid-template-columns: 1fr;
384 |   padding-top: 60px;
385 | }
387 | .features-section {
388 |   grid-template-columns: 1fr;
389 | }
390 | }
392 | @media (max-width: 500px) {
393 |   .navbar {
394 |     padding: 0 5%;
395 |   }
397 |   .signup-btn {
398 |     display: none;
399 |   }
401 |   .hero {
402 |     padding: 50px 5%;
403 |   }
405 |   .hero h1 {
406 |     font-size: 65px;
407 |   }
409 |   .about-section {
410 |     padding: 80px 5%;
411 |   }
413 |   .about-section h2 {
414 |     font-size: 45px;
415 |   }
417 |   .features-section {
418 |     padding: 0 5% 80px;
419 |   }
420 | }
421 | }
422 | }
423 | }
424 | }
425 | }
426 | }
427 | }
428 | }
429 | }
430 | }
431 | }
432 | }
433 | }
434 | }
435 | }
436 | }
437 | }
438 | }
439 | }
440 | }
441 | }
442 | }
443 | }
444 | }
445 | }
446 | }
447 | }
448 | }
449 | }
450 | }
451 | }
452 | }
453 | }
454 | }
455 | }
456 | }
457 | }
458 | }
459 | }
460 | }
461 | }
462 | }
463 | }
464 | }
465 | }
466 | }
467 | }
468 | }
469 | }
470 | }
471 | }
472 | }
473 | }
474 | }
475 | }
476 | }
477 | }
478 | }
479 | }
480 | }
481 | }
482 | }
483 | }
484 | }
485 | }
486 | }
487 | }
488 | }
489 | }
490 | }
491 | }
492 | }
493 | }
494 | }
495 | }
496 | }
497 | }
498 | }
499 | }
500 | }
501 | }
502 | }
503 | }
504 | }
505 | }
506 | }
507 | }
508 | }
509 | }
510 | }
511 | }
512 | }
513 | }
514 | }
515 | }
516 | }
517 | }
518 | }
519 | }
520 | }
521 | }
522 | }
523 | }
524 | }
525 | }
526 | }
527 | }
528 | }
529 | }
530 | }
531 | }
532 | }
533 | }
534 | }
535 | }
536 | }
537 | }
538 | }
539 | }
540 | }
541 | }
542 | }
543 | }
544 | }
545 | }
546 | }
547 | }
548 | }
549 | }
550 | }
551 | }
552 | }
553 | }
554 | }
555 | }
556 | }
557 | }
558 | }
559 | }
560 | }
561 | }
562 | }
563 | }
564 | }
565 | }
566 | }
567 | }
568 | }
569 | }
570 | }
571 | }
572 | }
573 | }
574 | }
575 | }
576 | }
577 | }
578 | }
579 | }
580 | }
581 | }
582 | }
583 | }
584 | }
585 | }
586 | }
587 | }
588 | }
589 | }
590 | }
591 | }
592 | }
593 | }
594 | }
595 | }
596 | }
597 | }
598 | }
599 | }
600 | }
```

4.4 KB

```
1 | import { BrowserRouter, Routes, Route, Navigate } from "react-router-dom";
2 | import { AuthProvider } from "../context/AuthContext";
3 | import { ThemeProvider } from "../context/ThemeContext";
4 | import ProtectedRoute from "../components/ProtectedRoute";
5 |
6 | import Home from "../pages/Home";
7 | import Login from "../pages/Login";
8 | import Register from "../pages/Register";
9 |
10 | import StudentDashboard from "../pages/student/Dashboard";
11 | import StudentTrainings from "../pages/student/Trainings";
12 | import TrainingDetail from "../pages/student/TrainingDetail";
13 | import StudentMeetings from "../pages/student/Meetings";
14 | import StudentProfile from "../pages/student/Profile";
15 | import StudentCertificates from "../pages/student/Certificates";
16 | import StudentAIHub from "../pages/student/AIHub";
17 | import StudentNotifications from "../pages/student/Notifications";
18 |
19 | import MentorDashboard from "../pages/mentor/Dashboard";
20 | import MentorStudents from "../pages/mentor/Students";
21 | import MentorMeetings from "../pages/mentor/Meetings";
22 | import MentorNotifications from "../pages/mentor/Notifications";
23 |
24 | import AdminDashboard from "../pages/admin/Dashboard";
25 | import AdminStudents from "../pages/admin/Students";
26 | import AdminMentors from "../pages/admin/Mentors";
27 | import AdminTrainings from "../pages/admin/Trainings";
28 | import AdminMeetings from "../pages/admin/Meetings";
29 | import AdminNotifications from "../pages/admin/Notifications";
30 | import AdminReports from "../pages/admin/Reports";
31 |
32 | function App() {
33 |   return (
34 |     <ThemeProvider>
35 |       <AuthProvider>
36 |         <BrowserRouter>
37 |           <Routes>
38 |             <Route path="/" element={<Home />} />
39 |             <Route path="/login" element={<Login />} />
40 |             <Route path="/register" element={<Register />} />
41 |             <Route path="/student" element={<ProtectedRoute roles={["student"]}><StudentDashboard /></ProtectedRoute /> />
42 |             <Route path="/student/trainings" element={<ProtectedRoute roles={["student"]}><StudentTrainings /></ProtectedRoute /> />
43 |             <Route path="/student/profile" element={<ProtectedRoute roles={["student"]}><StudentProfile /></ProtectedRoute /> />
44 |             <Route path="/student/certificates" element={<ProtectedRoute roles={["student"]}><StudentCertificates /></ProtectedRoute /> />
45 |             <Route path="/student/aihub" element={<ProtectedRoute roles={["student"]}><StudentAIHub /></ProtectedRoute /> />
46 |             <Route path="/student/notifications" element={<ProtectedRoute roles={["student"]}><StudentNotifications /></ProtectedRoute /> />
47 |             <Route path="/mentor" element={<ProtectedRoute roles={["mentor"]}><MentorDashboard /></ProtectedRoute /> />
48 |             <Route path="/mentor/students" element={<ProtectedRoute roles={["mentor"]}><MentorStudents /></ProtectedRoute /> />
49 |             <Route path="/mentor/meetings" element={<ProtectedRoute roles={["mentor"]}><MentorMeetings /></ProtectedRoute /> />
50 |             <Route path="/mentor/notifications" element={<ProtectedRoute roles={["mentor"]}><MentorNotifications /></ProtectedRoute /> />
51 |             <Route path="/admin" element={<ProtectedRoute roles={["admin"]}><AdminDashboard /></ProtectedRoute /> />
52 |             <Route path="/admin/students" element={<ProtectedRoute roles={["admin"]}><AdminStudents /></ProtectedRoute /> />
53 |             <Route path="/admin/mentors" element={<ProtectedRoute roles={["admin"]}><AdminMentors /></ProtectedRoute /> />
54 |             <Route path="/admin/trainings" element={<ProtectedRoute roles={["admin"]}><AdminTrainings /></ProtectedRoute /> />
55 |             <Route path="/admin/meetings" element={<ProtectedRoute roles={["admin"]}><AdminMeetings /></ProtectedRoute /> />
56 |             <Route path="/admin/notifications" element={<ProtectedRoute roles={["admin"]}><AdminNotifications /></ProtectedRoute /> />
57 |             <Route path="/admin/reports" element={<ProtectedRoute roles={["admin"]}><AdminReports /></ProtectedRoute /> />
58 |           </Routes>
59 |         </BrowserRouter>
60 |       </AuthProvider>
61 |     </ThemeProvider>
62 |   );
63 | }
64 |
65 | export default App;
```



```
45 |         <Route path="/student/trainings/:id" element={<ProtectedRoute roles={["student"]} ><TrainingDetail
46 |         <Route path="/student/meetings" element={<ProtectedRoute roles={["student"]} ><StudentMeetings /></
47 |         <Route path="/student/notifications" element={<ProtectedRoute roles={["student"]} ><StudentNotifica
48 |         <Route path="/student/certificates" element={<ProtectedRoute roles={["student"]} ><StudentCertifica
49 |         <Route path="/student/ai" element={<ProtectedRoute roles={["student"]} ><StudentAIHub /></Protected
50 |         <Route path="/student/profile" element={<ProtectedRoute roles={["student"]} ><StudentProfile /></Pr
52 |         { /* Mentor Routes */ }
53 |         <Route path="/mentor" element={<ProtectedRoute roles={["mentor"]} ><MentorDashboard /></ProtectedRo
54 |         <Route path="/mentor/students" element={<ProtectedRoute roles={["mentor"]} ><MentorStudents /></Pro
55 |         <Route path="/mentor/meetings" element={<ProtectedRoute roles={["mentor"]} ><MentorMeetings /></Pro
56 |         <Route path="/mentor/notifications" element={<ProtectedRoute roles={["mentor"]} ><MentorNotificatio
57 |         <Route path="/mentor/profile" element={<ProtectedRoute roles={["mentor"]} ><StudentProfile /></Prot
59 |         { /* Admin Routes */ }
60 |         <Route path="/admin" element={<ProtectedRoute roles={["admin"]} ><AdminDashboard /></ProtectedRoute
61 |         <Route path="/admin/students" element={<ProtectedRoute roles={["admin"]} ><AdminStudents /></Prot
62 |         <Route path="/admin/mentors" element={<ProtectedRoute roles={["admin"]} ><AdminMentors /></Protecte
63 |         <Route path="/admin/trainings" element={<ProtectedRoute roles={["admin"]} ><AdminTrainings /></Prot
64 |         <Route path="/admin/meetings" element={<ProtectedRoute roles={["admin"]} ><AdminMeetings /></Prot
65 |         <Route path="/admin/notifications" element={<ProtectedRoute roles={["admin"]} ><AdminNotifications
66 |         <Route path="/admin/reports" element={<ProtectedRoute roles={["admin"]} ><AdminReports /></Protecte
68 |         <Route path="" element={<Navigate to="/" replace /> } />
69 |     </Routes>
70 |     </BrowserRouter>
71 |     </AuthProvider>
72 |     </ThemeProvider>
73 |   );
74 | }
76 | export default App; src/components/CalendarViews \(5.0 KB\)
77 |
78 | import { useState } from "react";
79 | import { ChevronLeft, ChevronRight, Calendar as CalendarIcon, Clock, Video, User } from "lucide-react";
80 |
81 | export default function CalendarView({ events = [], onSelectDate, userRole = "student" }) {
82 |   const [currentDate, setCurrentDate] = useState(new Date());
83 |
84 |   const year = currentDate.getFullYear();
85 |   const month = currentDate.getMonth();
86 |
87 |   const monthNames = [
88 |     "January", "February", "March", "April", "May", "June",
89 |     "July", "August", "September", "October", "November", "December"
90 |   ];
91 |
92 |   const firstDayOfMonth = new Date(year, month, 1).getDay();
93 |   const daysInMonth = new Date(year, month + 1, 0).getDate();
94 |
95 |   const prevMonth = () => setCurrentDate(new Date(year, month - 1, 1));
96 |   const nextMonth = () => setCurrentDate(new Date(year, month + 1, 1));
97 |
98 |   // Match events to days
99 |   const getEventsForDay = (day) => {
100 |     return events.filter((e) => {
101 |       const eDate = new Date(e.scheduledDate || e.date || e.createdAt);
102 |       return (
103 |         eDate.getDate() === day &&
104 |         eDate.getMonth() === month &&
105 |         eDate.getFullYear() === year
106 |       );
107 |     });
108 |   };
109 |
110 |   const statusColors = {
111 |     accepted: "bg-green-500 text-white",
112 |     pending: "bg-amber-500 text-white",
113 |     rejected: "bg-red-500 text-white",
114 |     completed: "bg-purple-600 text-white",
115 |   };
116 |
117 |   return (
118 |     <div className="glass-card p-6">
119 |       { /* Calendar Header */ }
120 |       <div className="flex items-center justify-between mb-6">
121 |         <div className="flex h-10 w-10 items-center justify-center rounded-xl bg-katalyst-500 text-white">
122 |           <CalendarIcon className="h-5 w-5" />
123 |         </div>
124 |         <div>
125 |           <h2 className="text-xl font-bold">
126 |             {monthNames[month]} {year}
127 |           </h2>
128 |         </div>
129 |       </div>
130 |     </div>
131 |   );
132 | }
```

```
51 |         </h2>
52 |         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
53 |             Interactive Schedule & Meeting Calendar ({userRole.toUpperCase()})
54 |         </p>
55 |     </div>
56 | </div>
57 |
58 |     <div className="flex items-center gap-2">
59 |         <button onClick={prevMonth} className="btn-secondary !p-2">
60 |             <ChevronLeft className="h-4 w-4" />
61 |         </button>
62 |         <button onClick={() => setCurrentDate(new Date())} className="btn-secondary !py-1.5 text-xs font-sem
63 |             Today
64 |         </button>
65 |         <button onClick={nextMonth} className="btn-secondary !p-2">
66 |             <ChevronRight className="h-4 w-4" />
67 |         </button>
68 |     </div>
69 | </div>
70 |
71 |     {/* Weekday headers */}
72 |     <div className="grid grid-cols-7 gap-1 text-center font-bold text-xs mb-2 text-gray-500 uppercase tracki
73 |         <span>Sun</span>
74 |         <span>Mon</span>
75 |         <span>Tue</span>
76 |         <span>Wed</span>
77 |         <span>Thu</span>
78 |         <span>Fri</span>
79 |         <span>Sat</span>
80 |     </div>
81 |
82 |     {/* Days Grid */}
83 |     <div className="grid grid-cols-7 gap-2">
84 |         {/* Empty padding days for previous month */}
85 |         {Array.from({ length: firstDayOfMonth }).map((_, i) => (
86 |             <div key={`empty-${i}`} className="h-24 rounded-xl bg-gray-50/30 dark:bg-gray-800/10 opacity-30" />
87 |         ))}
88 |
89 |         {/* Month Days */}
90 |         {Array.from({ length: daysInMonth }).map((_, i) => {
91 |             const day = i + 1;
92 |             const dayEvents = getEventsForDay(day);
93 |             const isToday =
94 |                 day === new Date().getDate() &&
95 |                 month === new Date().getMonth() &&
96 |                 year === new Date().getFullYear();
97 |
98 |             return (
99 |                 <div
100 |                     key={day}
101 |                     onClick={() => onSelectDate && onSelectDate(new Date(year, month, day))}
102 |                     className={`h-24 rounded-xl border p-2 flex flex-col justify-between transition-all cursor-point
103 |                         isToday ? "border-katalyst-500 bg-katalyst-500/10 font-bold" : "border-gray-200 dark:border-gr
104 |                     `}
105 |                 >
106 |                     <div className="flex justify-between items-center">
107 |                         <span className={`text-xs ${isToday ? "text-katalyst-500 font-bold" : ""}`}>
108 |                             {day}
109 |                         </span>
110 |                         {dayEvents.length > 0 && (
111 |                             <span className="h-2 w-2 rounded-full bg-katalyst-500 animate-pulse" />
112 |                         )}
113 |                     </div>
114 |
115 |                     {/* Day Events Badge List */}
116 |                     <div className="space-y-1 overflow-y-auto max-h-14">
117 |                         {dayEvents.map((ev, idx) => (
118 |                             <div
119 |                                 key={idx}
120 |                                 className={`truncate rounded px-1.5 py-0.5 text-[10px] font-semibold ${
121 |                                     statusColors[ev.status] || "bg-katalyst-500 text-white"
122 |                                 `}
123 |                                 title={`${ev.topic || ev.title} - ${ev.scheduledTime || ""}`}
124 |                             >
125 |                                 {ev.scheduledTime ? `${ev.scheduledTime}` : ""}
126 |                                 {ev.topic || ev.title}
127 |                             </div>
128 |                         ))}
129 |                     </div>
130 |                 </div>
131 |             )}
132 |         )}
133 |     </div>
134 | </div>
```

```
129 |         </div>
130 |     </div>
131 |     );
132 |   }}
133 | </div>
134 | </div>
135 | );
136 | } View Source \(3.1 KB\)
137 |
1 | import { useState } from "react";
2 | import API from "../api";
4 | export default function ChatBot() {
5 |   const [open, setOpen] = useState(false);
6 |   const [messages, setMessages] = useState([
7 |     { role: "bot", text: "Hi! I'm Katalyst AI. Ask me about trainings, mentors, or career tips!" },
8 |   ]);
9 |   const [input, setInput] = useState("");
10 |   const [loading, setLoading] = useState(false);
12 |   const send = async (e) => {
13 |     e.preventDefault();
14 |     if (!input.trim()) return;
15 |     const question = input.trim();
16 |     setInput("");
17 |     setMessages((m) => [...m, { role: "user", text: question }]);
18 |     setLoading(true);
19 |     try {
20 |       const res = await API.post("/ai/chatbot", { question });
21 |       setMessages((m) => [...m, { role: "bot", text: res.data.answer }]);
22 |     } catch {
23 |       setMessages((m) => [
24 |         ...m,
25 |         { role: "bot", text: "Sorry, I couldn't process that. Please try again." },
26 |       ]);
27 |     } finally {
28 |       setLoading(false);
29 |     }
30 |   };
32 |   return (
33 |     <>
34 |       <button
35 |         onClick={() => setOpen(!open)}
36 |         className="fixed bottom-6 right-6 z-50 flex h-14 w-14 items-center justify-center rounded-full text-2x
37 |         style={{ background: "linear-gradient(135deg, var(--accent), var(--accent-dark))" }}
38 |       >
39 |         {open ? "x" : "ðŸ’¬"}
40 |       </button>
42 |       {open && (
43 |         <div className="fixed bottom-24 right-6 z-50 flex w-80 flex-col overflow-hidden rounded-2xl border sha
44 |         style={{ background: "var(--bg-glass)", borderColor: "var(--border)", backdropFilter: "blur(16px)" }}
45 |         >
46 |           <div className="border-b p-4" style={{ borderColor: "var(--border)" }}>
47 |             <h3 className="font-semibold">Katalyst AI Assistant</h3>
48 |             <p className="text-xs" style={{ color: "var(--text-muted)" }}>Always here to help</p>
49 |           </div>
50 |           <div className="flex max-h-64 flex-col gap-2 overflow-y-auto p-4">
51 |             {messages.map((msg, i) => (
52 |               <div
53 |                 key={i}
54 |                 className={`max-w-[85%] rounded-xl px-3 py-2 text-sm ${
55 |                   msg.role === "user"
56 |                     ? "ml-auto bg-katalyst-500 text-white"
57 |                     : "mr-auto"
58 |                 }}
59 |                 style={msg.role === "bot" ? { background: "var(--accent-light)", color: "var(--text-primary)" }
60 |               >
61 |                 {msg.text}
62 |               </div>
63 |             ))}
64 |             {loading && (
65 |               <div className="mr-auto rounded-xl px-3 py-2 text-sm" style={{ background: "var(--accent-light)" }
66 |                 Thinking...
67 |               </div>
```

```

68 |     }}
69 |   </div>
70 |   <form onSubmit={send} className="flex gap-2 border-t p-3" style={{ borderColor: "var(--border)" }}>
71 |     <input
72 |       value={input}
73 |       onChange={(e) => setInput(e.target.value)}
74 |       placeholder="Ask anything..."
75 |       className="input-field !py-2 text-sm"
76 |     />
77 |     <button type="submit" className="btn-primary !px-3 !py-2 text-sm">!</button>
78 |   </form>
79 | </div>
80 | })
81 | </>
82 | );
83 | }
84 |
(2.5 KB)
85 |
86 | import { useState, useEffect } from "react";
87 | import NotificationPanel from "../NotificationPanel";
88 | import ChatBot from "../ChatBot";
89 | import Sidebar from "../Sidebar";
90 | import { useAuth } from "../../context/AuthContext";
91 | import API from "../../api";
92 | export default function DashboardLayout({ title, subtitle, children, actions }) {
93 |   const { user } = useAuth();
94 |   const [mobileOpen, setMobileOpen] = useState(false);
95 |   const [showNotifs, setShowNotifs] = useState(false);
96 |   const [unreadCount, setUnreadCount] = useState(0);
97 |   useEffect(() => {
98 |     API.get("/notifications")
99 |       .then((res) => setUnreadCount(res.data.unreadCount || 0))
100 |      .catch(() => {});
101 |   }, [showNotifs]);
102 |   return (
103 |     <div className="flex min-h-screen" style={{ background: "var(--bg-primary)" }}>
104 |       <Sidebar role={user?.role || "student"} mobileOpen={mobileOpen} onClose={() => setMobileOpen(false)} />
105 |       <div className="flex flex-1 flex-col min-w-0">
106 |         </* Top bar */>
107 |         <header
108 |           className="sticky top-0 z-30 flex h-16 items-center justify-between border-b px-4 lg:px-8"
109 |           style={{ borderColor: "var(--border)", background: "var(--bg-glass)", backdropFilter: "blur(16px)" }}
110 |         >
111 |           <div className="flex items-center gap-3">
112 |             <button
113 |               className="btn-secondary !p-2 lg:hidden"
114 |               onClick={() => setMobileOpen(true)}
115 |             >
116 |               &0
117 |             </button>
118 |             <div>
119 |               {subtitle && <p className="section-subtitle">{subtitle}</p>}
120 |               <h1 className="text-lg font-bold lg:text-xl">{title}</h1>
121 |             </div>
122 |           </div>
123 |           <div className="flex items-center gap-3">
124 |             {actions}
125 |             <div className="relative">
126 |               <button
127 |                 onClick={() => setShowNotifs(!showNotifs)}
128 |                 className="btn-secondary !rounded-full !p-2.5 text-lg relative"
129 |               >
130 |                 &0=Ÿ
131 |                 {unreadCount > 0 && (
132 |                   <span className="absolute -top-1 -right-1 flex h-4 w-4 items-center justify-center rounded-f
133 |                     {unreadCount}
134 |                   </span>
135 |                 )}
136 |               </button>
137 |               {showNotifs && <NotificationPanel onClose={() => setShowNotifs(false)} />}
138 |             </div>
139 |           </div>
140 |         </header>

```

```

62 |         <main className="flex-1 p-4 lg:p-8 animate-fade-in">{children}</main>
63 |     </div>
64 |     <ChatBot />
65 | </div>
66 | );
67 | }
68 | }
69 |
70 |
71 |
72 |
73 |
74 |
75 |
76 |
77 |
78 |
79 |
80 |
81 |
82 |
83 |
84 |
85 |
86 |
87 |
88 |
89 |
90 |
91 |
92 |
93 |
94 |
95 |
96 |
97 |
98 |
99 |
100 |
101 |
102 |
103 |
104 |
105 |
106 |
107 |
108 |
109 |
110 |
111 |
112 |
113 |
114 |
115 |
116 |
117 |
118 |
119 |
120 |
121 |
122 |
123 |
124 |
125 |
126 |
127 |
128 |
129 |
130 |
131 |
132 |
133 |
134 |
135 |
136 |
137 |
138 |
139 |
140 |
141 |
142 |
143 |
144 |
145 |
146 |
147 |
148 |
149 |
150 |
151 |
152 |
153 |
154 |
155 |
156 |
157 |
158 |
159 |
160 |
161 |
162 |
163 |
164 |
165 |
166 |
167 |
168 |
169 |
170 |
171 |
172 |
173 |
174 |
175 |
176 |
177 |
178 |
179 |
180 |
181 |
182 |
183 |
184 |
185 |
186 |
187 |
188 |
189 |
190 |
191 |
192 |
193 |
194 |
195 |
196 |
197 |
198 |
199 |
200 |
201 |
202 |
203 |
204 |
205 |
206 |
207 |
208 |
209 |
210 |
211 |
212 |
213 |
214 |
215 |
216 |
217 |
218 |
219 |
220 |
221 |
222 |
223 |
224 |
225 |
226 |
227 |
228 |
229 |
230 |
231 |
232 |
233 |
234 |
235 |
236 |
237 |
238 |
239 |
240 |
241 |
242 |
243 |
244 |
245 |
246 |
247 |
248 |
249 |
250 |
251 |
252 |
253 |
254 |
255 |
256 |
257 |
258 |
259 |
260 |
261 |
262 |
263 |
264 |
265 |
266 |
267 |
268 |
269 |
270 |
271 |
272 |
273 |
274 |
275 |
276 |
277 |
278 |
279 |
280 |
281 |
282 |
283 |
284 |
285 |
286 |
287 |
288 |
289 |
290 |
291 |
292 |
293 |
294 |
295 |
296 |
297 |
298 |
299 |
300 |
301 |
302 |
303 |
304 |
305 |
306 |
307 |
308 |
309 |
310 |
311 |
312 |
313 |
314 |
315 |
316 |
317 |
318 |
319 |
320 |
321 |
322 |
323 |
324 |
325 |
326 |
327 |
328 |
329 |
330 |
331 |
332 |
333 |
334 |
335 |
336 |
337 |
338 |
339 |
340 |
341 |
342 |
343 |
344 |
345 |
346 |
347 |
348 |
349 |
350 |
351 |
352 |
353 |
354 |
355 |
356 |
357 |
358 |
359 |
360 |
361 |
362 |
363 |
364 |
365 |
366 |
367 |
368 |
369 |
370 |
371 |
372 |
373 |
374 |
375 |
376 |
377 |
378 |
379 |
380 |
381 |
382 |
383 |
384 |
385 |
386 |
387 |
388 |
389 |
390 |
391 |
392 |
393 |
394 |
395 |
396 |
397 |
398 |
399 |
400 |
401 |
402 |
403 |
404 |
405 |
406 |
407 |
408 |
409 |
410 |
411 |
412 |
413 |
414 |
415 |
416 |
417 |
418 |
419 |
420 |
421 |
422 |
423 |
424 |
425 |
426 |
427 |
428 |
429 |
430 |
431 |
432 |
433 |
434 |
435 |
436 |
437 |
438 |
439 |
440 |
441 |
442 |
443 |
444 |
445 |
446 |
447 |
448 |
449 |
450 |
451 |
452 |
453 |
454 |
455 |
456 |
457 |
458 |
459 |
460 |
461 |
462 |
463 |
464 |
465 |
466 |
467 |
468 |
469 |
470 |
471 |
472 |
473 |
474 |
475 |
476 |
477 |
478 |
479 |
480 |
481 |
482 |
483 |
484 |
485 |
486 |
487 |
488 |
489 |
490 |
491 |
492 |
493 |
494 |
495 |
496 |
497 |
498 |
499 |
500 |
501 |
502 |
503 |
504 |
505 |
506 |
507 |
508 |
509 |
510 |
511 |
512 |
513 |
514 |
515 |
516 |
517 |
518 |
519 |
520 |
521 |
522 |
523 |
524 |
525 |
526 |
527 |
528 |
529 |
530 |
531 |
532 |
533 |
534 |
535 |
536 |
537 |
538 |
539 |
540 |
541 |
542 |
543 |
544 |
545 |
546 |
547 |
548 |
549 |
550 |
551 |
552 |
553 |
554 |
555 |
556 |
557 |
558 |
559 |
560 |
561 |
562 |
563 |
564 |
565 |
566 |
567 |
568 |
569 |
570 |
571 |
572 |
573 |
574 |
575 |
576 |
577 |
578 |
579 |
580 |
581 |
582 |
583 |
584 |
585 |
586 |
587 |
588 |
589 |
590 |
591 |
592 |
593 |
594 |
595 |
596 |
597 |
598 |
599 |
600 |
601 |
602 |
603 |
604 |
605 |
606 |
607 |
608 |
609 |
610 |
611 |
612 |
613 |
614 |
615 |
616 |
617 |
618 |
619 |
620 |
621 |
622 |
623 |
624 |
625 |
626 |
627 |
628 |
629 |
630 |
631 |
632 |
633 |
634 |
635 |
636 |
637 |
638 |
639 |
640 |
641 |
642 |
643 |
644 |
645 |
646 |
647 |
648 |
649 |
650 |
651 |
652 |
653 |
654 |
655 |
656 |
657 |
658 |
659 |
660 |
661 |
662 |
663 |
664 |
665 |
666 |
667 |
668 |
669 |
670 |
671 |
672 |
673 |
674 |
675 |
676 |
677 |
678 |
679 |
680 |
681 |
682 |
683 |
684 |
685 |
686 |
687 |
688 |
689 |
690 |
691 |
692 |
693 |
694 |
695 |
696 |
697 |
698 |
699 |
700 |
701 |
702 |
703 |
704 |
705 |
706 |
707 |
708 |
709 |
710 |
711 |
712 |
713 |
714 |
715 |
716 |
717 |
718 |
719 |
720 |
721 |
722 |
723 |
724 |
725 |
726 |
727 |
728 |
729 |
730 |
731 |
732 |
733 |
734 |
735 |
736 |
737 |
738 |
739 |
740 |
741 |
742 |
743 |
744 |
745 |
746 |
747 |
748 |
749 |
750 |
751 |
752 |
753 |
754 |
755 |
756 |
757 |
758 |
759 |
760 |
761 |
762 |
763 |
764 |
765 |
766 |
767 |
768 |
769 |
770 |
771 |
772 |
773 |
774 |
775 |
776 |
777 |
778 |
779 |
780 |
781 |
782 |
783 |
784 |
785 |
786 |
787 |
788 |
789 |
790 |
791 |
792 |
793 |
794 |
795 |
796 |
797 |
798 |
799 |
800 |
801 |
802 |
803 |
804 |
805 |
806 |
807 |
808 |
809 |
810 |
811 |
812 |
813 |
814 |
815 |
816 |
817 |
818 |
819 |
820 |
821 |
822 |
823 |
824 |
825 |
826 |
827 |
828 |
829 |
830 |
831 |
832 |
833 |
834 |
835 |
836 |
837 |
838 |
839 |
840 |
841 |
842 |
843 |
844 |
845 |
846 |
847 |
848 |
849 |
850 |
851 |
852 |
853 |
854 |
855 |
856 |
857 |
858 |
859 |
860 |
861 |
862 |
863 |
864 |
865 |
866 |
867 |
868 |
869 |
870 |
8
```

```
71 |         <X className="h-5 w-5" />
72 |     </button>
73 | </div>
74 |
75 |     {/* Role Badge */}
76 |     <div className="px-4 pt-4">
77 |         <div className="flex items-center gap-3 rounded-xl bg-purple-50 px-3 py-2.5">
78 |             <div className="flex h-8 w-8 items-center justify-center rounded-lg bg-purple-100">
79 |                 {role === "admin" ? (
80 |                     <ShieldCheck className="h-4 w-4 text-purple-600" />
81 |                 ) : role === "mentor" ? (
82 |                     <Users className="h-4 w-4 text-purple-600" />
83 |                 ) : (
84 |                     <User className="h-4 w-4 text-purple-600" />
85 |                 )}
86 |             </div>
87 |             <div className="min-w-0">
88 |                 <p className="text-[10px] text-gray-500">Logged in as</p>
89 |                 <p className="truncate text-sm font-semibold capitalize text-gray-800">{role}</p>
90 |             </div>
91 |         </div>
92 |     </div>
93 |
94 |     {/* Navigation */}
95 |     <nav className="flex-1 overflow-y-auto px-4 py-5">
96 |         <p className="mb-2 px-3 text-[10px] font-semibold uppercase tracking-wider text-gray-400">Menu</p>
97 |         <div className="space-y-1">
98 |             {links.map((item) => {
99 |                 const Icon = item.icon;
100 |                 return (
101 |                     <NavLink
102 |                         key={item.path}
103 |                         to={item.path}
104 |                         end={item.path === `/${role}`}
105 |                         onClick={onClose}
106 |                         className={({ isActive }) =>
107 |                             `flex items-center gap-3 rounded-xl px-4 py-2.5 text-sm font-medium transition-all ${
108 |                                 isActive
109 |                                     ? "bg-purple-600 text-white shadow-md"
110 |                                     : "text-gray-600 hover:bg-purple-50 hover:text-purple-600"
111 |                             }`
112 |                         }
113 |                     >
114 |                         <Icon className="h-5 w-5 shrink-0" />
115 |                         <span>{item.name}</span>
116 |                     </NavLink>
117 |                 );
118 |             })}
119 |         </div>
120 |     </nav>
121 |
122 |     {/* Bottom: Logout */}
123 |     <div className="border-t border-gray-200 p-4">
124 |         <button
125 |             type="button"
126 |             onClick={handleLogout}
127 |             className="flex w-full items-center gap-3 rounded-xl px-4 py-2.5 text-sm font-medium text-gray-600"
128 |             >
129 |             <LogOut className="h-5 w-5" />
130 |             <span>Logout</span>
131 |         </button>
132 |     </div>
133 | </aside>
134 | );
135 |
136 | return (
137 |     <>
138 |         {/* Desktop sidebar – always visible, takes up space in flow */}
139 |         <div className="hidden lg:block lg:w-64 lg:shrink-0">
140 |             <div className="fixed left-0 top-0 z-40 h-screen w-64">
141 |                 {sidebarContent}
142 |             </div>
143 |         </div>
144 |
145 |         {/* Mobile sidebar – slide-in drawer with backdrop */}
146 |         {mobileOpen && (
147 |             <div className="fixed inset-0 z-50 lg:hidden">
```

```
148 |         {/* Backdrop */}
149 |         <div className="absolute inset-0 bg-black/40" onClick={onClose} />
150 |         {/* Drawer */}
151 |         <div className="relative h-full w-64 animate-fade-in">
152 |             {sidebarContent}
153 |         </div>
154 |     </div>
155 |     )}
156 | </>
157 | );
158 | };
159 |
160 | export default Sidebar; components/NotificationPanel (2.6 KB)

1 | import { useState, useEffect } from "react";
2 | import API from "../api";
3 |
4 | export default function NotificationPanel({ onClose }) {
5 |     const [notifications, setNotifications] = useState([]);
6 |     const [loading, setLoading] = useState(true);
7 |
8 |     useEffect(() => {
9 |         API.get("/notifications")
10 |            .then((res) => setNotifications(res.data.notifications || []))
11 |            .catch(() => {})
12 |            .finally(() => setLoading(false));
13 |     }, []);
14 |
15 |     const markAllRead = async () => {
16 |         await API.put("/notifications/read-all");
17 |         setNotifications((n) => n.map((item) => ({ ...item, isRead: true })));
18 |     };
19 |
20 |     const markRead = async (id) => {
21 |         await API.put(`/notifications/${id}/read`);
22 |         setNotifications((n) =>
23 |             n.map((item) => (item._id === id ? { ...item, isRead: true } : item))
24 |         );
25 |     };
26 |
27 |     return (
28 |         <div className="absolute right-0 top-12 z-50 w-80 glass-card animate-fade-in overflow-hidden">
29 |             <div className="flex items-center justify-between border-b p-4" style={{ borderColor: "var(--border)" }}>
30 |                 <h3 className="font-semibold">Notifications</h3>
31 |                 <div className="flex gap-2">
32 |                     <button onClick={markAllRead} className="text-xs text-katalyst-500 hover:underline">
33 |                         Mark all read
34 |                     </button>
35 |                     <button onClick={onClose} className="text-lg leading-none opacity-60 hover:opacity-100">
36 |                         x
37 |                     </button>
38 |                 </div>
39 |             </div>
40 |             <div className="max-h-80 overflow-y-auto">
41 |                 {loading ? (
42 |                     <p className="p-4 text-center text-sm" style={{ color: "var(--text-muted)" }}>
43 |                         Loading...
44 |                     </p>
45 |                 ) : notifications.length === 0 ? (
46 |                     <p className="p-6 text-center text-sm" style={{ color: "var(--text-muted)" }}>
47 |                         No notifications yet
48 |                     </p>
49 |                 ) : (
50 |                     notifications.map((n) => (
51 |                         <div
52 |                             key={n._id}
53 |                             onClick={() => !n.isRead && markRead(n._id)}
54 |                             className={
55 |                                 { cursor: "pointer", border: "1px solid", padding: "4px", transition: "background-color 0.2s",
56 |                                   hover: "bg-katalyst-50", dark: { hover: "bg-kat
57 |                                     !n.isRead ? "bg-katalyst-50/50 dark:bg-katalyst-900/10" : ""
58 |                                 }
59 |                             }
60 |                             style={{ borderColor: "var(--border)" }}
61 |                         >
62 |                             <p className="text-sm font-medium">{n.title}</p>
63 |                             <p className="mt-1 text-xs" style={{ color: "var(--text-secondary)" }}>
64 |                                 {n.message}
65 |                             </p>
66 |                             <span className="mt-1 block text-xs" style={{ color: "var(--text-muted)" }}>
67 |                                 {new Date(n.createdAt).toLocaleDateString()}
68 |                             </span>
69 |                         </div>
70 |                     )
71 |                 )
72 |             </div>
73 |         </div>
74 |     );
75 | }
```

```
65 |         </span>
66 |     </div>
67 |     ))
68 |   }
69 | </div>
70 | </div>
71 | );
72 | } <!-- NotificationPanelComponentNotificationPanel.js (4.4 KB)
73 |
74 | import { useState, useEffect } from "react";
75 | import DashboardLayout from "../layout/DashboardLayout";
76 | import API from "../api";
77 | import { Bell, CheckCircle2, Trash2, Calendar, BookOpen, Trophy } from "lucide-react";
78 |
79 | export default function NotificationsPage({ userRole = "student" }) {
80 |   const [notifications, setNotifications] = useState([]);
81 |   const [loading, setLoading] = useState(true);
82 |
83 |   const fetchNotifications = () => {
84 |     API.get("/notifications")
85 |       .then((res) => setNotifications(res.data.notifications || []))
86 |       .catch(console.error)
87 |       .finally(() => setLoading(false));
88 |   };
89 |
90 |   useEffect(() => {
91 |     fetchNotifications();
92 |   }, []);
93 |
94 |   const markAllRead = async () => {
95 |     await API.put("/notifications/read-all");
96 |     fetchNotifications();
97 |   };
98 |
99 |   const markRead = async (id) => {
100 |    await API.put(`/notifications/${id}/read`);
101 |    fetchNotifications();
102 |   };
103 |
104 |   const deleteNotification = async (id) => {
105 |    await API.delete(`/notifications/${id}`);
106 |    fetchNotifications();
107 |   };
108 |
109 |   const getIcon = (type) => {
110 |     switch (type) {
111 |       case "meeting": return <Calendar className="h-5 w-5 text-blue-500" />;
112 |       case "training": return <BookOpen className="h-5 w-5 text-green-500" />;
113 |       case "certificate": return <Trophy className="h-5 w-5 text-yellow-500" />;
114 |       default: return <Bell className="h-5 w-5 text-katalyst-500" />;
115 |     }
116 |   };
117 |
118 |   return (
119 |     <DashboardLayout
120 |       title="Notifications Center"
121 |       subtitle={` ${userRole.toUpperCase()} PORTAL `}
122 |       actions={
123 |         <button onClick={markAllRead} className="btn-secondary !py-2 text-xs font-semibold">
124 |           ' Mark All as Read
125 |         </button>
126 |       }
127 |     >
128 |       {loading ? (
129 |         <div className="flex h-40 items-center justify-center">
130 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
131 |             </div>
132 |         ) : notifications.length === 0 ? (
133 |           <div className="glass-card p-12 text-center">
134 |             <Bell className="mx-auto h-12 w-12 text-gray-400" />
135 |             <h3 className="mt-4 font-bold text-lg">No Notifications</h3>
136 |             <p className="text-sm mt-1" style={{ color: "var(--text-muted)" }}>
137 |               You're all caught up! Updates regarding meetings and courses will appear here.
138 |             </p>
139 |           </div>
140 |         ) : (
141 |           <div className="space-y-3">
142 |             {notifications.map((n) => (
143 |               <div
```



```
71 |         key={n._id}
72 |         className={`glass-card p-5 flex items-start justify-between gap-4 transition-all ${
73 |           !n.isRead ? "border-l-4 border-l-katalyst-500 bg-katalyst-50/20" : ""
74 |         }`}
75 |       >
76 |         <div className="flex items-start gap-4">
77 |           <div className="p-2.5 rounded-xl bg-gray-100 dark:bg-gray-800">
78 |             {getIcon(n.type)}
79 |           </div>
80 |           <div>
81 |             <h4 className="font-bold flex items-center gap-2">
82 |               {n.title}
83 |               {!n.isRead && (
84 |                 <span className="rounded-full bg-katalyst-500 px-2 py-0.5 text-[10px] text-white font-se
85 |                   NEW
86 |                 </span>
87 |               )}
88 |             </h4>
89 |             <p className="text-sm mt-1" style={{ color: "var(--text-secondary)" }}>
90 |               {n.message}
91 |             </p>
92 |             <span className="text-xs mt-2 block" style={{ color: "var(--text-muted)" }}>
93 |               {new Date(n.createdAt).toLocaleString()}
94 |             </span>
95 |           </div>
96 |         </div>
97 |         <div className="flex items-center gap-2">
98 |           {!n.isRead && (
99 |             <button
100 |               onClick={() => markRead(n._id)}
101 |               className="p-2 rounded-lg text-gray-500 hover:bg-gray-100 hover:text-green-600"
102 |               title="Mark as read"
103 |             >
104 |               <CheckCircle2 className="h-4 w-4" />
105 |             </button>
106 |           )}
107 |           <button
108 |             onClick={() => deleteNotification(n._id)}
109 |             className="p-2 rounded-lg text-gray-500 hover:bg-gray-100 hover:text-red-600"
110 |             title="Delete notification"
111 |           >
112 |             <Trash2 className="h-4 w-4" />
113 |           </button>
114 |         </div>
115 |       </div>
116 |     </div>
117 |   )}
118 | </div>
119 | )}
120 | </DashboardLayout>
121 | );
122 | }
123 | }

import { Navigate } from "react-router-dom";
import { useAuth } from "../context/AuthContext";

export default function ProtectedRoute({ children, roles }) {
  const { user, loading } = useAuth();

  if (loading) {
    return (
      <div className="flex min-h-screen items-center justify-center">
        <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500" />
      </div>
    );
  }

  if (!user) return <Navigate to="/login" replace />;
  if (roles && !roles.includes(user.role))
    return <Navigate to={`/${user.role}`} replace />;
  return children;
}
```

(0.4 KB)

```
1 | import { useTheme } from "../context/ThemeContext";
3 | export default function ThemeToggle() {
4 |   const { darkMode, toggleTheme } = useTheme();
6 |   return (
7 |     <button
8 |       onClick={toggleTheme}
9 |       className="btn-secondary !rounded-full !p-2.5 text-lg"
10 |      title={darkMode ? "Switch to light mode" : "Switch to dark mode"}
11 |    >
12 |      {darkMode ? "& p " : "ð<ß "}
13 |    </button>
14 |  );
15 | }
```

(0.7 KB)

```
16 | export default function StatCard({ title, value, subtitle, icon }) {
17 |   return (
18 |     <div className="glass-card animate-fade-in p-5 transition-transform hover:-translate-y-1">
19 |       <div className="mb-3 flex items-center justify-between">
20 |         <p className="text-sm font-medium" style={{ color: "var(--text-secondary)" }}>
21 |           {title}
22 |         </p>
23 |         {icon && <span className="text-2xl">{icon}</span>}
24 |       </div>
25 |       <h3 className="text-3xl font-bold" style={{ color: "var(--text-primary)" }}>
26 |         {value}
27 |       </h3>
28 |       {subtitle && (
29 |         <p className="mt-1 text-sm font-medium text-katalyst-500">{subtitle}</p>
30 |       )}
31 |     </div>
32 |   );
33 | }
```

(1.1 KB)

```
1 | import { createContext, useContext, useState, useEffect } from "react";
2 | import API from "../api";
4 | const AuthContext = createContext();
6 | export const AuthProvider = ({ children }) => {
7 |   const [user, setUser] = useState(
8 |     () => JSON.parse(localStorage.getItem("user")) || "null"
9 |   );
10 |   const [loading, setLoading] = useState(true);
12 |   useEffect(() => {
13 |     const token = localStorage.getItem("token");
14 |     if (token && user) {
15 |       API.get("/auth/me")
16 |         .then((res) => setUser(res.data.user))
17 |         .catch(() => logout())
18 |         .finally(() => setLoading(false));
19 |     } else {
20 |       setLoading(false);
21 |     }
22 |   }, []);
24 |   const login = (userData, token) => {
25 |     localStorage.setItem("token", token);
26 |     localStorage.setItem("user", JSON.stringify(userData));
27 |     setUser(userData);
28 |   };
30 |   const logout = () => {
31 |     localStorage.removeItem("token");
32 |     localStorage.removeItem("user");
33 |     setUser(null);
34 |   };
36 |   return (
37 |     <AuthContext.Provider value={{ user, login, logout, loading }}>
38 |       {children}
39 |     </AuthContext.Provider>
40 |   );
41 | };
43 | export const useAuth = () => useContext(AuthContext);
44 |
```

KATALYST.

Source Code: frontend/src/context/ThemeContext.jsx

Generated: 22/8/2026 | Frontend

(0.7 KB)

```
1 | import { createContext, useContext, useState, useEffect } from "react";
2 |
3 | const ThemeContext = createContext();
4 |
5 | export const ThemeProvider = ({ children }) => {
6 |   const [darkMode, setDarkMode] = useState(
7 |     () => localStorage.getItem("theme") === "dark"
8 |   );
9 |
10 |  useEffect(() => {
11 |    document.documentElement.classList.toggle("dark", darkMode);
12 |    localStorage.setItem("theme", darkMode ? "dark" : "light");
13 |  }, [darkMode]);
14 |
15 |  const toggleTheme = () => setDarkMode((prev) => !prev);
16 |
17 |  return (
18 |    <ThemeContext.Provider value={{ darkMode, toggleTheme }}>
19 |      {children}
20 |    </ThemeContext.Provider>
21 |  );
22 | };
23 |
24 | export const useTheme = () => useContext(ThemeContext);
25 |
26 | @import url("https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800&display=swap");
27 |
28 | @tailwind base;
29 | @tailwind components;
30 | @tailwind utilities;
31 |
32 | :root {
33 |   --bg-primary: #f8fafc;
34 |   --bg-secondary: #ffffff;
35 |   --bg-glass: rgba(255, 255, 255, 0.85);
36 |   --text-primary: #0f172a;
37 |   --text-secondary: #475569;
38 |   --text-muted: #94a3b8;
39 |   --accent: #2563eb;
40 |   --accent-light: #eff6ff;
41 |   --accent-dark: #1d4ed8;
42 |   --border: rgba(226, 232, 240, 0.8);
43 |   --shadow: 0 10px 30px rgba(37, 99, 235, 0.08);
44 |   --sidebar-width: 260px;
45 | }
46 |
47 | .dark {
48 |   --bg-primary: #0b1120;
49 |   --bg-secondary: #0f172a;
50 |   --bg-glass: rgba(15, 23, 42, 0.85);
51 |   --text-primary: #f8fafc;
52 |   --text-secondary: #94a3b8;
53 |   --text-muted: #64748b;
54 |   --accent: #3b82f6;
55 |   --accent-light: #1e293b;
56 |   --accent-dark: #2563eb;
57 |   --border: rgba(51, 65, 85, 0.7);
58 |   --shadow: 0 10px 30px rgba(0, 0, 0, 0.5);
59 | }
60 |
61 | * {
62 |   margin: 0;
63 |   padding: 0;
64 |   box-sizing: border-box;
65 | }
66 |
67 | html {
68 |   scroll-behavior: smooth;
69 | }
70 |
71 | body {
72 |   font-family: "Inter", system-ui, -apple-system, sans-serif;
73 |   background: var(--bg-primary);
74 |   color: var(--text-primary);
75 |   min-height: 100vh;
76 |   transition: background 0.3s cubic-bezier(0.4, 0, 0.2, 1), color 0.3s cubic-bezier(0.4, 0, 0.2, 1);
77 | }
78 |
79 | @layer components {
80 |   .glass-card {
81 |     @apply rounded-2xl border backdrop-blur-glass transition-all duration-200;
82 |     background: var(--bg-glass);
83 |     border-color: var(--border);
84 |   }
85 | }
```

```
59 |     box-shadow: var(--shadow);
60 | }
61 |
62 | .glass-card:hover {
63 |     box-shadow: 0 12px 36px rgba(37, 99, 235, 0.12);
64 | }
65 |
66 | .btn-primary {
67 |     @apply inline-flex items-center justify-center gap-2 rounded-xl px-5 py-2.5 font-semibold text-white trans
68 |     background: linear-gradient(135deg, var(--accent), var(--accent-dark));
69 |     box-shadow: 0 4px 16px rgba(37, 99, 235, 0.3);
70 | }
71 |
72 | .btn-primary:hover {
73 |     transform: translateY(-1px);
74 |     box-shadow: 0 6px 20px rgba(37, 99, 235, 0.4);
75 | }
76 |
77 | .btn-secondary {
78 |     @apply inline-flex items-center justify-center gap-2 rounded-xl border px-5 py-2.5 font-medium transition-
79 |     border-color: var(--border);
80 |     background: var(--bg-secondary);
81 |     color: var(--text-primary);
82 | }
83 |
84 | .btn-secondary:hover {
85 |     border-color: var(--accent);
86 |     color: var(--accent);
87 |     background: var(--accent-light);
88 | }
89 |
90 | .input-field {
91 |     @apply w-full rounded-xl border px-4 py-2.5 outline-none transition-all duration-200;
92 |     border-color: var(--border);
93 |     background: var(--bg-secondary);
94 |     color: var(--text-primary);
95 | }
96 |
97 | .input-field:focus {
98 |     border-color: var(--accent);
99 |     box-shadow: 0 0 0 3px rgba(37, 99, 235, 0.15);
100 | }
101 |
102 | .progress-bar {
103 |     @apply h-2.5 overflow-hidden rounded-full;
104 |     background: var(--accent-light);
105 | }
106 |
107 | .progress-bar-fill {
108 |     @apply h-full rounded-full transition-all duration-500;
109 |     background: linear-gradient(90deg, #3b82f6, #1d4ed8);
110 | }
111 |
112 | .badge {
113 |     @apply inline-block rounded-full px-3 py-1 text-xs font-semibold uppercase tracking-wider;
114 |     background: var(--accent-light);
115 |     color: var(--accent-dark);
116 | }
117 |
118 | .section-title {
119 |     @apply text-2xl font-bold tracking-tight;
120 |     color: var(--text-primary);
121 | }
122 |
123 | .section-subtitle {
124 |     @apply text-sm font-medium uppercase tracking-wider;
125 |     color: var(--text-muted);
126 | }
127 | }
128 |
129 | /* Scrollbar */
130 | ::-webkit-scrollbar {
131 |     width: 6px;
132 |     height: 6px;
133 | }
134 | ::-webkit-scrollbar-track {
135 |     background: transparent;
136 | }
137 | ::-webkit-scrollbar-thumb {
138 |     background: var(--accent);
139 |     border-radius: 9999px;
140 | }
141 |
142 | /* Animations */
```

```
143 | @keyframes fadeIn {
144 |   from { opacity: 0; transform: translateY(8px); }
145 |   to { opacity: 1; transform: translateY(0); }
146 | }
147 | .animate-fade-in {
148 |   animation: fadeIn 0.3s ease-out forwards;
149 | }
151 | @keyframes pulse-blue {
152 |   0%, 100% { box-shadow: 0 0 0 0 rgba(37, 99, 235, 0.4); }
153 |   50% { box-shadow: 0 0 0 8px rgba(37, 99, 235, 0); }
154 | }
155 | .pulse-blue {
156 |   animation: pulse-blue 2s infinite;
157 | }
158 |
1   | .login-page {
2   |   min-height: 100vh;
3   |   background: #09090b;
4   |   display: flex;
5   |   justify-content: center;
6   |   align-items: center;
7   |   padding: 30px;
8   |   position: relative;
9   | }
11  | .back-button {
12  |   position: absolute;
13  |   top: 30px;
14  |   left: 5%;
15  |   background: transparent;
16  |   border: none;
17  |   color: #a1a1aa;
18  |   font-size: 15px;
19  |   cursor: pointer;
20  | }
22  | .back-button:hover {
23  |   color: white;
24  | }
26  | .login-card {
27  |   width: 100%;
28  |   max-width: 480px;
29  |   padding: 45px;
30  |   background: #111114;
31  |   border: 1px solid #27272a;
32  |   border-radius: 20px;
33  |   box-shadow: 0 30px 80px rgba(0, 0, 0, 0.5);
34  | }
36  | .login-logo {
37  |   font-size: 22px;
38  |   font-weight: 800;
39  |   letter-spacing: 2px;
40  |   margin-bottom: 35px;
41  | }
43  | .login-logo span {
44  |   color: #8b5cf6;
45  | }
47  | .login-card h1 {
48  |   font-size: 38px;
49  |   margin-bottom: 10px;
50  |   color: white;
51  | }
53  | .login-subtitle {
54  |   color: #71717a;
55  |   margin-bottom: 30px;
56  | }
58  | .role-options {
59  |   display: flex;
60  |   flex-direction: column;
61  |   gap: 12px;
62  | }
64  | .role-card {
65  |   width: 100%;
```

(2.2 KB)

```
66 | padding: 17px;
67 | background: #18181b;
68 | border: 1px solid #27272a;
69 | border-radius: 12px;
70 | color: white;
71 | display: flex;
72 | align-items: center;
73 | gap: 15px;
74 | text-align: left;
75 | cursor: pointer;
76 | }
77 |
78 | .role-card:hover {
79 |   border-color: #7c3aed;
80 | }
81 |
82 | .role-card.selected {
83 |   border-color: #8b5cf6;
84 |   background: #1c1729;
85 | }
86 |
87 | .role-icon {
88 |   width: 42px;
89 |   height: 42px;
90 |   display: flex;
91 |   align-items: center;
92 |   justify-content: center;
93 |   background: #27272a;
94 |   border-radius: 10px;
95 |   font-size: 20px;
96 | }
97 |
98 | .role-card h3 {
99 |   margin-bottom: 4px;
100 | }
101 |
102 | .role-card p {
103 |   color: #71717a;
104 |   font-size: 12px;
105 | }
106 |
107 | .continue-button {
108 |   width: 100%;
109 |   padding: 14px;
110 |   margin-top: 25px;
111 |   border: none;
112 |   border-radius: 8px;
113 |   background: #7c3aed;
114 |   color: white;
115 |   font-size: 15px;
116 |   cursor: pointer;
117 | }
118 |
119 | .continue-button:hover {
120 |   background: #8b5cf6;
121 | }
122 |
123 | .demo-button {
124 |   width: 100%;
125 |   padding: 13px;
126 |   margin-top: 10px;
127 |   border: 1px solid #3f3f46;
128 |   border-radius: 8px;
129 |   background: transparent;
130 |   color: white;
131 |   cursor: pointer;
132 | }
133 |
134 | .login-footer {
135 |   text-align: center;
136 |   color: #52525b;
137 |   font-size: 11px;
138 |   line-height: 1.6;
139 |   margin-top: 30px;
140 | }
```

KATALYST

Source Code: frontend/src/Login.jsx

Generated: 22/8/2026 | Frontend

(2.4 KB)

```
1 | import { useState } from "react";
2 | import { Link, useNavigate } from "react-router-dom";
3 |
4 | function Login() {
5 |   const [role, setRole] = useState("student");
6 |
7 |   const [email, setEmail] = useState("");
8 |   const [password, setPassword] = useState("");
9 |
10 |   const navigate = useNavigate();
11 |
12 |   const handleLogin = (e) => {
13 |     e.preventDefault();
14 |
15 |     if (role === "student") {
16 |       navigate("/student-dashboard");
17 |     } else if (role === "mentor") {
18 |       navigate("/mentor-dashboard");
19 |     } else if (role === "admin") {
20 |       navigate("/admin-dashboard");
21 |     }
22 |   };
23 |
24 |   return (
25 |     <div className="auth-page">
26 |       <div className="auth-card">
27 |         <Link to="/" className="back-link">
28 |           !• KATALYST
29 |         </Link>
30 |
31 |         <h1>
32 |           Welcome <span>Back.</span>
33 |         </h1>
34 |
35 |         <p className="auth-subtitle">
36 |           Login to continue your Katalyst journey.
37 |         </p>
38 |
39 |         <div className="role-container">
40 |
41 |           <button
42 |             type="button"
43 |             className={role === "student" ? "role active" : "role"}
44 |             onClick={() => setRole("student")}
45 |           >
46 |             Ø<ß" Student
47 |           </button>
48 |
49 |           <button
50 |             type="button"
51 |             className={role === "mentor" ? "role active" : "role"}
52 |             onClick={() => setRole("mentor")}
53 |           >
54 |             Ø=Üh Ø<ßë Mentor
55 |           </button>
56 |
57 |           <button
58 |             type="button"
59 |             className={role === "admin" ? "role active" : "role"}
60 |             onClick={() => setRole("admin")}
61 |           >
62 |             Ø=Þáp Admin
63 |           </button>
64 |
65 |         </div>
66 |
67 |         <form onSubmit={handleLogin}>
68 |           <label>Email</label>
69 |
70 |           <input
71 |             type="email"
72 |             placeholder="Enter your email"
73 |             value={email}
74 |             onChange={(e) => setEmail(e.target.value)}
75 |             required
76 |           />
77 |
78 |           <label>Password</label>
79 |
80 |           <input
81 |             type="password"
82 |             placeholder="Enter your password"
83 |             value={password}
84 |             onChange={(e) => setPassword(e.target.value)}
85 |             required
86 |           />
87 |
88 |         </form>
89 |       </div>
90 |     </div>
91 |   );
92 | }
```

```
90 |         <button type="submit" className="login-button">
91 |             Login as {role} !'
92 |         </button>
93 |     </form>
94 |     <p className="demo-text">
95 |         Demo mode – any valid email and password will continue.
96 |     </p>
97 | </div>
98 | </div>
99 | );
100 | };
101 | }
102 | export default Login; (0.2 KB)
103 |
104 | import React from "react";
105 | import ReactDOM from "react-dom/client";
106 | import App from "../App";
107 | import "../index.css";
108 | ReactDOM.createRoot(document.getElementById("root")).render(
109 |     <React.StrictMode>
110 |         <App />
111 |     </React.StrictMode>
112 | ); (0.0 KB)
113 | (3.6 KB)
114 |
115 | import { useEffect, useState } from "react";
116 | import { Link } from "react-router-dom";
117 | import { BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer, PieChart, Pie, Cell } from "recharts";
118 | import DashboardLayout from "../../components/layout/DashboardLayout";
119 | import StatCard from "../../components/ui/StatCard";
120 | import API from "../../api";
121 |
122 | const COLORS = ["#ec4899", "#f472b6", "#fbcfe8", "#db2777", "#be185d"];
123 |
124 | export default function AdminDashboard() {
125 |     const [data, setData] = useState(null);
126 |     const [loading, setLoading] = useState(true);
127 |
128 |     useEffect(() => {
129 |         API.get("/admin/dashboard")
130 |             .then((res) => setData(res.data))
131 |             .catch(console.error)
132 |             .finally(() => setLoading(false));
133 |     }, []);
134 |
135 |     if (loading) {
136 |         return (
137 |             <DashboardLayout title="Dashboard" subtitle="Admin Portal">
138 |                 <div className="flex h-64 items-center justify-center">
139 |                     <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-5">
140 |                     </div>
141 |                 </DashboardLayout>
142 |             );
143 |         }
144 |
145 |     const stats = data?.stats || {};
146 |     const pieData = [
147 |         { name: "Completed", value: stats.completedMeetings || 0 },
148 |         { name: "Pending", value: stats.pendingMeetings || 0 },
149 |         { name: "Other", value: Math.max(0, (stats.totalMeetings || 0) - (stats.completedMeetings || 0) - (stats.p
150 |     ]);
151 |
152 |     return (
153 |         <DashboardLayout title="Admin Dashboard" subtitle="Admin Portal">
154 |             <div className="mb-6 grid gap-4 sm:grid-cols-2 xl:grid-cols-4">
155 |                 <StatCard title="Total Students" value={stats.totalStudents || 0} icon="ðŸŒŸ" />
156 |                 <StatCard title="Total Mentors" value={stats.totalMentors || 0} icon="ðŸŒŸ" />
157 |                 <StatCard title="Trainings" value={stats.totalTrainings || 0} icon="ðŸŒŸ" />
158 |                 <StatCard title="Certificates" value={stats.totalCertificates || 0} icon="ðŸŒŸ" />
159 |             </div>
160 |             <div className="grid gap-6 lg:grid-cols-2">
161 |                 <div className="glass-card p-6">
162 |                     <h3 className="section-title mb-4">Top Trainings by Enrollment</h3>
163 |                     <ResponsiveContainer width="100%" height={250}>
164 |                         <BarChart data={data?.topTrainings || []}>
165 |                             <XAxis dataKey="title" tick={{ fontSize: 10 }} />
166 |                             <YAxis tick={{ fontSize: 12 }} />
167 |                             <Tooltip />
168 |                         </BarChart>
169 |                     </div>
170 |                 </div>
171 |             </div>
172 |         </DashboardLayout>
173 |     );
174 | }
```



```
55 |         <Bar dataKey="enrollments" fill="#ec4899" radius={[6, 6, 0, 0]} />
56 |     </BarChart>
57 | </ResponsiveContainer>
58 | </div>
59 |
60 | <div className="glass-card p-6">
61 |     <h3 className="section-title mb-4">Meeting Status</h3>
62 |     <ResponsiveContainer width="100%" height={250}>
63 |         <PieChart>
64 |             <Pie data={pieData} cx="50%" cy="50%" outerRadius={80} dataKey="value" label>
65 |                 {pieData.map((_, i) => <Cell key={i} fill={COLORS[i % COLORS.length]} />)}
66 |             </Pie>
67 |             <Tooltip />
68 |         </PieChart>
69 |     </ResponsiveContainer>
70 | </div>
71 | </div>
72 |
73 | <div className="glass-card mt-6 p-6">
74 |     <h3 className="section-title mb-4">Quick Actions</h3>
75 |     <div className="grid gap-3 sm:grid-cols-2 lg:grid-cols-4">
76 |         {[
77 |             { to: "/admin/students", label: "ðŸ‘Œ Manage Students" },
78 |             { to: "/admin/mentors", label: "ðŸ‘Œ Manage Mentors" },
79 |             { to: "/admin/trainings", label: "ðŸ‘Œ Manage Trainings" },
80 |             { to: "/admin/reports", label: "ðŸ‘Œ View Reports" },
81 |         ].map((a) => (
82 |             <Link key={a.to} to={a.to} className="btn-secondary text-left !py-4">{a.label}</Link>
83 |         ))}
84 |     </div>
85 | </div>
86 | </DashboardLayout>
87 | );
88 | } <!-- End of Admin Meetings --> (5.3 KB)
89 |
90 | import { useEffect, useState } from "react";
91 | import DashboardLayout from "../../components/layout/DashboardLayout";
92 | import CalendarView from "../../components/CalendarView";
93 | import API from "../../api";
94 |
95 | export default function AdminMeetings() {
96 |     const [meetings, setMeetings] = useState([]);
97 |     const [loading, setLoading] = useState(true);
98 |     const [tab, setTab] = useState("calendar");
99 |
100 |     const fetchMeetings = () => {
101 |         API.get("/meetings/admin")
102 |             .then((res) => setMeetings(res.data.meetings || []))
103 |             .catch(console.error)
104 |             .finally(() => setLoading(false));
105 |     };
106 |
107 |     useEffect(() => {
108 |         fetchMeetings();
109 |     }, []);
110 |
111 |     const updateStatus = async (id, status) => {
112 |         await API.put(`/meetings/${id}/status`, { status });
113 |         fetchMeetings();
114 |     };
115 |
116 |     const statusColor = {
117 |         pending: "bg-yellow-100 text-yellow-700 dark:bg-yellow-900/30 dark:text-yellow-300",
118 |         accepted: "bg-green-100 text-green-700 dark:bg-green-900/30 dark:text-green-300",
119 |         rejected: "bg-red-100 text-red-700 dark:bg-red-900/30 dark:text-red-300",
120 |         completed: "bg-purple-100 text-purple-700 dark:bg-purple-900/30 dark:text-purple-300",
121 |     };
122 |
123 |     return (
124 |         <DashboardLayout title="Platform Calendar & Meetings" subtitle="Admin Portal">
125 |             <div className="mb-6 flex gap-2">
126 |                 {[
127 |                     { id: "calendar", label: "ðŸ“… Master Platform Calendar" },
128 |                     { id: "list", label: "ðŸ“… All Scheduled Sessions" },
129 |                 ].map((t) => (
130 |                     <button
131 |                         key={t.id}
132 |                         onClick={() => setTab(t.id)}
133 |                         className={`rounded-full px-4 py-1.5 text-sm font-medium ${
```

```

45 |         tab === t.id ? "bg-katalyst-500 text-white" : "border"
46 |       }`}
47 |       style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
48 |     >
49 |       {t.label}
50 |     </button>
51 |   )}}
52 | </div>
53 |
54 | {loading ? (
55 |   <div className="flex h-40 items-center justify-center">
56 |     <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
57 |     </div>
58 |   ) : tab === "calendar" ? (
59 |     <div className="space-y-6">
60 |       <CalendarView events={meetings} userRole="admin" />
61 |       <div className="glass-card p-6">
62 |         <h3 className="section-title mb-4">All System Sessions</h3>
63 |         <div className="space-y-3">
64 |           {meetings.length === 0 ? (
65 |             <p className="text-sm" style={{ color: "var(--text-muted)" }}>No platform meetings recorded.</p>
66 |           ) : (
67 |             meetings.map((m) => (
68 |               <div key={m._id} className="flex flex-wrap items-center justify-between gap-3 rounded-xl border">
69 |                 <div>
70 |                   <p className="font-bold">{m.topic}</p>
71 |                   <p className="text-xs" style={{ color: "var(--text-muted)" }}>
72 |                     Student: {m.studentId?.name || "Student"} | Mentor: {m.mentorId?.name || "Mentor"} · {
73 |                       </p>
74 |                     </div>
75 |                   <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.status]}`}>
76 |                     {m.status}
77 |                   </span>
78 |                 </div>
79 |               )}
80 |             </div>
81 |           )}
82 |         </div>
83 |       </div>
84 |     </div>
85 |   ) : (
86 |     <div className="space-y-4">
87 |       {meetings.map((m) => (
88 |         <div key={m._id} className="glass-card p-5">
89 |           <div className="flex flex-wrap items-start justify-between gap-3">
90 |             <div>
91 |               <h3 className="font-bold">{m.topic}</h3>
92 |               <p className="text-sm" style={{ color: "var(--text-secondary)" }}>
93 |                 Student: <strong>{m.studentId?.name}</strong> ({m.studentId?.email}) | Mentor: <strong>{m.mentorId?.name}</strong>
94 |               </p>
95 |               <p className="text-xs mt-1" style={{ color: "var(--text-muted)" }}>
96 |                 Date: {new Date(m.scheduledDate).toLocaleDateString()} at {m.scheduledTime} ({m.duration} min)
97 |               </p>
98 |               {m.agenda && <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>Agenda: {m.agenda}</p>}
99 |             </div>
100 |            <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.status]}`}>
101 |              {m.status}
102 |            </span>
103 |          </div>
104 |          <div className="mt-4 flex flex-wrap gap-2">
105 |            {m.status === "pending" && (
106 |              <button onClick={() => updateStatus(m._id, "accepted")} className="btn-primary !py-1.5 text-sm">
107 |                Approve & Send Link
108 |              </button>
109 |              <button onClick={() => updateStatus(m._id, "rejected")} className="btn-secondary !py-1.5 text-sm">
110 |                Decline
111 |              </button>
112 |            )}
113 |          </div>
114 |        </div>
115 |      )}
116 |      {m.meetLink && (
117 |        <a href={m.meetLink} target="_blank" rel="noreferrer" className="btn-secondary !py-1.5 text-sm">
118 |          View Meet Link
119 |        </a>
120 |      )}
121 |    </div>
122 |  )}
123 | </div>

```

```
119 |         })
120 |       </div>
121 |     </div>
122 |   )}
123 | </div>
124 | })
125 | </DashboardLayout>
126 | );
127 | } (4.1 KB)
128 |
1   import { useEffect, useState } from "react";
2   import DashboardLayout from "../../components/layout/DashboardLayout";
3   import API from "../../api";
4
5   export default function AdminMentors() {
6     const [mentors, setMentors] = useState([]);
7     const [loading, setLoading] = useState(true);
8     const [showCreate, setShowCreate] = useState(false);
9     const [form, setForm] = useState({ name: "", email: "", password: "", expertise: "", designation: "", compan
11  const fetchMentors = () => {
12     API.get("/admin/mentors")
13       .then((res) => setMentors(res.data.mentors || []))
14       .catch(console.error)
15       .finally(() => setLoading(false));
16   };
17
18   useEffect(() => { fetchMentors(); }, []);
19
20   const createMentor = async (e) => {
21     e.preventDefault();
22     await API.post("/admin/mentors", {
23       ...form,
24       expertise: form.expertise.split(",").map((s) => s.trim()).filter(Boolean),
25     });
26     setShowCreate(false);
27     fetchMentors();
28   };
29
30   const deleteMentor = async (id) => {
31     if (!confirm("Delete this mentor?")) return;
32     await API.delete(`/admin/mentors/${id}`);
33     fetchMentors();
34   };
35
36   return (
37     <DashboardLayout
38       title="Manage Mentors"
39       subtitle="Admin Portal"
40       actions=<button onClick={() => setShowCreate(true)} className="btn-primary !py-2 text-sm">+ Add Mentor<
41     >
42     {loading ? (
43       <div className="flex h-40 items-center justify-center">
44         <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
45       </div>
46     ) : (
47       <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-3">
48         {mentors.map((m) => (
49           <div key={m._id} className="glass-card p-5">
50             <div className="flex items-center gap-3">
51               <div className="flex h-12 w-12 items-center justify-center rounded-full bg-katalyst-500 text-l
52                 {m.name?.charAt(0)}
53             </div>
54             <div>
55               <p className="font-bold">{m.name}</p>
56               <p className="text-xs" style={{ color: "var(--text-muted)" }}>{m.designation}</p>
57             </div>
58           </div>
59           <p className="mt-3 text-sm" style={{ color: "var(--text-secondary)" }}>{m.email}</p>
60           <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>
61             Students: {m.assignedStudents?.length || 0} · Rating: {m.rating || 5}/5
62           </p>
63           <div className="mt-3 flex flex-wrap gap-1">
64             {m.expertise?.slice(0, 3).map((e) => (
65               <span key={e} className="badge !text-[10px]">{e}</span>
66             ))}
67           </div>
68           <button onClick={() => deleteMentor(m._id)} className="btn-secondary mt-4 w-full !py-2 text-sm !
```

```
69 |         Delete
70 |       </button>
71 |     </div>
72 |   )}
73 | </div>
74 | })
75 | {showCreate && (
76 |   <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
77 |     <div className="glass-card w-full max-w-md p-6 max-h-[90vh] overflow-y-auto">
78 |       <h3 className="text-xl font-bold">Create Mentor</h3>
79 |       <form onSubmit={createMentor} className="mt-4 space-y-3">
80 |         {[ "name", "email", "password", "designation", "company"].map((f) => (
81 |           <input key={f} className="input-field" placeholder={f} type={f === "password" ? "password" : "
82 |             value={form[f]} onChange={(e) => setForm({ ...form, [f]: e.target.value })} required={f !==
83 |             ))}
84 |         <input className="input-field" placeholder="Expertise (comma separated)" value={form.expertise}
85 |           onChange={(e) => setForm({ ...form, expertise: e.target.value })} />
86 |         <div className="flex gap-2">
87 |           <button type="button" onClick={() => setShowCreate(false)} className="btn-secondary flex-1">Ca
88 |           <button type="submit" className="btn-primary flex-1">Create</button>
89 |         </div>
90 |       </form>
91 |     </div>
92 |   </div>
93 | </div>
94 |   )}
95 | </DashboardLayout>
96 | );
97 | }
98 | }
99 |
100 | (0.2 KB)
101 |
102 | import NotificationsPage from "../../components/NotificationsPage";
103 | export default function AdminNotifications() {
104 |   return <NotificationsPage userRole="admin" />;
105 | }
106 | }
107 |
108 | (3.5 KB)
109 |
110 | import { useEffect, useState } from "react";
111 | import DashboardLayout from "../../components/layout/DashboardLayout";
112 | import API from "../../api";
113 | export default function AdminReports() {
114 |   const [reports, setReports] = useState(null);
115 |   const [loading, setLoading] = useState(true);
116 |   const [notifyMsg, setNotifyMsg] = useState({ title: "", message: "", targetRole: "student" });
117 |   useEffect(() => {
118 |     API.get("/admin/reports")
119 |       .then((res) => setReports(res.data))
120 |       .catch(console.error)
121 |       .finally(() => setLoading(false));
122 |   }, []);
123 |   const sendNotification = async (e) => {
124 |     e.preventDefault();
125 |     await API.post("/admin/notify", notifyMsg);
126 |     alert("Notification sent!");
127 |     setNotifyMsg({ title: "", message: "", targetRole: "student" });
128 |   };
129 |   return (
130 |     <DashboardLayout title="Reports & Notifications" subtitle="Admin Portal">
131 |       {loading ? (
132 |         <div className="flex h-40 items-center justify-center">
133 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
134 |             </div>
135 |         ) : (
136 |           <div className="grid gap-6 lg:grid-cols-2">
137 |             <div className="glass-card p-6">
138 |               <h3 className="section-title mb-4">Platform Summary</h3>
139 |               <div className="space-y-3">
140 |                 <div className="flex justify-between rounded-lg p-3" style={{ background: "var(--accent-light)"
141 |                   <span className="text-sm">Students Tracked</span>
142 |                   <span className="font-bold text-katalyst-500">{reports?.progressData?.length || 0}</span>
143 |                 </div>
144 |                 {(reports?.meetingReport || []).map((item) => (
145 |                   <div key={item._id} className="flex justify-between rounded-lg p-3" style={{ background: "var(
146 |                     <span className="text-sm capitalize">Meetings: {item._id}</span>
147 |                     <span className="font-bold text-katalyst-500">{item.count}</span>
148 |                   )}
149 |                 )}
150 |               </div>
151 |             </div>
152 |           </div>
153 |         )}
154 |       </DashboardLayout>
155 |     );
156 |   }
157 | }
```

```
43 |         </div>
44 |     )}
45 |     {(reports?.categoryEnrollment || []).map((item) => (
46 |         <div key={item._id} className="flex justify-between rounded-lg p-3" style={{ background: "var(
47 |             <span className="text-sm">{item._id}</span>
48 |             <span className="font-bold text-katalyst-500">{item.totalEnrollments} enrollments</span>
49 |         </div>
50 |     )}
51 | </div>
52 | </div>
53 | <div className="glass-card p-6">
54 |     <h3 className="section-title mb-4">Send Bulk Notification</h3>
55 |     <form onSubmit={sendNotification} className="space-y-3">
56 |         <select className="input-field" value={notifyMsg.targetRole}
57 |             onChange={(e) => setNotifyMsg({ ...notifyMsg, targetRole: e.target.value })}>
58 |             <option value="student">All Students</option>
59 |             <option value="mentor">All Mentors</option>
60 |             <option value="all">Everyone</option>
61 |         </select>
62 |         <input className="input-field" placeholder="Title" value={notifyMsg.title}
63 |             onChange={(e) => setNotifyMsg({ ...notifyMsg, title: e.target.value })} required />
64 |         <textarea className="input-field" rows={3} placeholder="Message" value={notifyMsg.message}
65 |             onChange={(e) => setNotifyMsg({ ...notifyMsg, message: e.target.value })} required />
66 |         <button type="submit" className="btn-primary w-full">Send Notification</button>
67 |     </form>
68 | </div>
69 | </div>
70 | </div>
71 | )}
72 | </DashboardLayout>
73 | );
74 | } // frontend/src/pages/admin/Reports.jsx (3.7 KB)
75 |
1 | import { useEffect, useState } from "react";
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
3 | import API from "../../api";
4 |
5 | export default function AdminStudents() {
6 |     const [students, setStudents] = useState([]);
7 |     const [mentors, setMentors] = useState([]);
8 |     const [loading, setLoading] = useState(true);
9 |
10 |    useEffect(() => {
11 |        Promise.all([API.get("/admin/students"), API.get("/admin/mentors")])
12 |            .then(([s, m]) => {
13 |                setStudents(s.data.students || []);
14 |                setMentors(m.data.mentors || []);
15 |            })
16 |            .catch(console.error)
17 |            .finally(() => setLoading(false));
18 |    }, []);
19 |
20 |    const assignMentor = async (studentId, mentorId) => {
21 |        await API.post("/admin/assign-mentor", { studentId, mentorId });
22 |        const res = await API.get("/admin/students");
23 |        setStudents(res.data.students || []);
24 |    };
25 |
26 |    const toggleActive = async (id, isActive) => {
27 |        await API.put(`/admin/students/${id}`, { isActive: !isActive });
28 |        const res = await API.get("/admin/students");
29 |        setStudents(res.data.students || []);
30 |    };
31 |
32 |    const deleteStudent = async (id) => {
33 |        if (!confirm("Delete this student?")) return;
34 |        await API.delete(`/admin/students/${id}`);
35 |        setStudents(students.filter((s) => s._id !== id));
36 |    };
37 |
38 |    return (
39 |        <DashboardLayout title="Manage Students" subtitle="Admin Portal">
40 |            {loading ? (
41 |                <div className="flex h-40 items-center justify-center">
42 |                    <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
43 |                </div>
44 |            ) : (
45 |                <div className="glass-card overflow-x-auto">
```

```
46 |         <table className="w-full text-sm">
47 |           <thead>
48 |             <tr className="border-b" style={{ borderColor: "var(--border)" }}>
49 |               {[ "Name", "Email", "Mentor", "Status", "Actions" ].map((h) => (
50 |                 <th key={h} className="p-4 text-left font-semibold">{h}</th>
51 |               ))}
52 |             </tr>
53 |           </thead>
54 |           <tbody>
55 |             {students.map((s) => (
56 |               <tr key={s._id} className="border-b" style={{ borderColor: "var(--border)" }}>
57 |                 <td className="p-4 font-medium">{s.name}</td>
58 |                 <td className="p-4" style={{ color: "var(--text-secondary)" }}>{s.email}</td>
59 |                 <td className="p-4">
60 |                   <select
61 |                     value={s.assignedMentor?._id || ""}
62 |                     onChange={(e) => e.target.value && assignMentor(s._id, e.target.value)}
63 |                     className="input-field !py-1.5 text-xs"
64 |                   >
65 |                     <option value="">Assign mentor</option>
66 |                     {mentors.map((m) => (
67 |                       <option key={m._id} value={m._id}>{m.name}</option>
68 |                     ))}
69 |                   </select>
70 |                 </td>
71 |                 <td className="p-4">
72 |                   <span className={`badge ${s.isActive ? "!bg-green-100 !text-green-700" : "!bg-red-100 !tex
73 |                     {s.isActive ? "Active" : "Inactive"}
74 |                   </span>
75 |                 </td>
76 |                 <td className="p-4">
77 |                   <div className="flex gap-2">
78 |                     <button onClick={() => toggleActive(s._id, s.isActive)} className="btn-secondary !py-1 t
79 |                       {s.isActive ? "Deactivate" : "Activate"}
80 |                     </button>
81 |                     <button onClick={() => deleteStudent(s._id)} className="btn-secondary !py-1 text-xs !tex
82 |                       Delete
83 |                     </button>
84 |                   </div>
85 |                 </td>
86 |               </tr>
87 |             ))}
88 |           </tbody>
89 |         </table>
90 |       </div>
91 |     )}
92 |   </DashboardLayout>
93 | );
94 | } // frontend/src/pages/admin/Students.jsx (6.5 KB)
95 |
96 | import { useEffect, useState } from "react";
97 | import DashboardLayout from "../../components/layout/DashboardLayout";
98 | import API from "../../api";
99 |
100 | export default function AdminTrainings() {
101 |   const [trainings, setTrainings] = useState([]);
102 |   const [loading, setLoading] = useState(true);
103 |   const [showCreate, setShowCreate] = useState(false);
104 |   const [form, setForm] = useState({
105 |     title: "", description: "", category: "", level: "Beginner", duration: "", instructor: "",
106 |   });
107 |
108 |   const [videos, setVideos] = useState([
109 |     { title: "", url: "", duration: "15m" }
110 |   ]);
111 |
112 |   const fetchTrainings = () => {
113 |     API.get("/trainings")
114 |       .then((res) => setTrainings(res.data.trainings || []))
115 |       .catch(console.error)
116 |       .finally(() => setLoading(false));
117 |   };
118 |
119 |   useEffect(() => { fetchTrainings(); }, []);
120 |
121 |   const addVideoField = () => {
122 |     setVideos([...videos, { title: "", url: "", duration: "15m" }]);
123 |   };
124 |
125 |   const updateVideo = (index, field, value) => {
```

```
29 |     const updated = [...videos];
30 |     updated[index][field] = value;
31 |     setVideos(updated);
32 |   };
33 |   const removeVideoField = (index) => {
34 |     setVideos(videos.filter((_, i) => i !== index));
35 |   };
36 |   const createTraining = async (e) => {
37 |     e.preventDefault();
38 |     const formattedVideos = videos
39 |       .filter((v) => v.title.trim())
40 |       .map((v, idx) => ({ ...v, order: idx + 1 }));
41 |     try {
42 |       await API.post("/trainings", {
43 |         ...form,
44 |         videos: formattedVideos,
45 |         quizzes: [
46 |           { question: `What is the primary topic of ${form.title}?`, options: [form.category || "General", "Ot
47 |         ],
48 |         assignments: []
49 |       });
50 |       setShowCreate(false);
51 |       setForm({ title: "", description: "", category: "", level: "Beginner", duration: "", instructor: "" });
52 |       setVideos([{ title: "", url: "", duration: "15m" }]);
53 |       fetchTrainings();
54 |       alert("Training created successfully!");
55 |     } catch (err) {
56 |       alert(err.response?.data?.message || "Failed to create training");
57 |     }
58 |   };
59 |   const deleteTraining = async (id) => {
60 |     if (!confirm("Delete this training?")) return;
61 |     await API.delete(`/trainings/${id}`);
62 |     fetchTrainings();
63 |   };
64 |   return (
65 |     <DashboardLayout
66 |       title="Manage Trainings"
67 |       subtitle="Admin Portal"
68 |       actions=<button onClick={() => setShowCreate(true)} className="btn-primary !py-2 text-sm">+ Add Trainin
69 |     >
70 |     {loading ? (
71 |       <div className="flex h-40 items-center justify-center">
72 |         <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
73 |       </div>
74 |     ) : (
75 |       <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-3">
76 |         {trainings.map((t) => (
77 |           <div key={t._id} className="glass-card p-5">
78 |             <span className="badge">{t.category}</span>
79 |             <h3 className="mt-2 font-bold">{t.title}</h3>
80 |             <p className="mt-1 line-clamp-2 text-sm" style={{ color: "var(--text-secondary)" }}>{t.descripti
81 |             <div className="mt-3 flex gap-3 text-xs" style={{ color: "var(--text-muted)" }}>
82 |               <span>{t.level}</span>
83 |               <span>{t.duration}</span>
84 |               <span>{t.enrolledStudents?.length || 0} enrolled</span>
85 |             </div>
86 |             <button onClick={() => deleteTraining(t._id)} className="btn-secondary mt-4 w-full !py-2 text-sm
87 |               Delete
88 |             </button>
89 |           </div>
90 |         ))}
91 |       </div>
92 |     )}
93 |     {showCreate && (
94 |       <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4 overflow-y-auto">
95 |         <div className="glass-card w-full max-w-lg p-6 max-h-[90vh] overflow-y-auto my-8">
96 |           <h3 className="text-xl font-bold">Create New Training</h3>
97 |           <form onSubmit={createTraining} className="mt-4 space-y-3">
98 |             {[ "title", "description", "category", "duration", "instructor" ].map((f) => (
99 |               <input key={f} className="input-field capitalize" placeholder={f} value={form[f]}
100 |               onChange={(e) => setForm({ ...form, [f]: e.target.value })} required />
101 |             )}
102 |           </form>
103 |         </div>
104 |       </div>
105 |     )}
106 |   );
```

```
107 |         )))
108 |         <select className="input-field" value={form.level}
109 |             onChange={(e) => setForm({ ...form, level: e.target.value })}>
110 |             {["Beginner", "Intermediate", "Advanced"].map((l) => <option key={l}>{l}</option>)}
111 |         </select>
112 |         { /* Video Lessons Section */ }
113 |         <div className="pt-2 border-t mt-4" style={{ borderColor: "var(--border)" }}>
114 |             <div className="flex justify-between items-center mb-2">
115 |                 <h4 className="font-semibold text-sm">ð Course Lessons / Videos</h4>
116 |                 <button type="button" onClick={addVideoField} className="text-xs text-katalyst-500 hover:und
117 |                     + Add Lesson
118 |                 </button>
119 |             </div>
120 |             {videos.map((vid, idx) => (
121 |                 <div key={idx} className="space-y-2 mb-3 p-3 rounded-lg border text-xs" style={{ borderColor
122 |                     <div className="flex justify-between items-center">
123 |                         <span className="font-medium">Lesson #{idx + 1}</span>
124 |                         {videos.length > 1 && (
125 |                             <button type="button" onClick={() => removeVideoField(idx)} className="text-red-500 ho
126 |                                 Remove
127 |                             </button>
128 |                         )}
129 |                     </div>
130 |                     <input className="input-field !py-1.5 text-xs" placeholder="Lesson Title (e.g. Introductio
131 |                         onChange={(e) => updateVideo(idx, "title", e.target.value)} required />
132 |                     <input className="input-field !py-1.5 text-xs" placeholder="Video URL (e.g. https://youtu.
133 |                         onChange={(e) => updateVideo(idx, "url", e.target.value)} />
134 |                     <input className="input-field !py-1.5 text-xs" placeholder="Duration (e.g. 20m)" value={vi
135 |                         onChange={(e) => updateVideo(idx, "duration", e.target.value)} />
136 |                     </div>
137 |                 )))
138 |             </div>
139 |             <div className="flex gap-2 pt-3">
140 |                 <button type="button" onClick={() => setShowCreate(false)} className="btn-secondary flex-1">Ca
141 |                 <button type="submit" className="btn-primary flex-1">Create Training</button>
142 |             </div>
143 |         </form>
144 |     </div>
145 | </div>
146 | </div>
147 | </div>
148 | ))
149 | </DashboardLayout>
150 | );
151 | }
152 | } (4.7 KB)
153 |
154 | 1 | import { Link } from "react-router-dom";
155 | 2 | import ThemeToggle from "../components/ThemeToggle";
156 | 3 |
157 | 4 | export default function Home() {
158 | 5 |     return (
159 | 6 |         <div className="min-h-screen" style={{ background: "var(--bg-primary)" }}>
160 | 7 |             <nav className="flex items-center justify-between border-b px-6 py-5 lg:px-12"
161 | 8 |                 style={{ borderColor: "var(--border)", background: "var(--bg-glass)", backdropFilter: "blur(16px)" }}
162 | 9 |                 >
163 |10 |                 <h1 className="text-2xl font-bold tracking-wider lg:text-3xl">
164 |11 |                     KATALYST<span className="text-katalyst-500">.</span>
165 |12 |                 </h1>
166 |13 |                 <div className="flex items-center gap-3">
167 |14 |                     <ThemeToggle />
168 |15 |                     <Link to="/login" className="btn-secondary">Login</Link>
169 |16 |                     <Link to="/register" className="btn-primary hidden sm:inline-flex">Get Started !'</Link>
170 |17 |                 </div>
171 |18 |             </nav>
172 |19 |
173 |20 |             <section className="mx-auto max-w-6xl px-6 py-16 lg:py-24">
174 |21 |                 <div className="badge mb-8">Student • Mentor • Growth</div>
175 |22 |                 <h2 className="text-5xl font-extrabold leading-tight tracking-tight lg:text-7xl">
176 |23 |                     Learn.<br />
177 |24 |                     Connect.<br />
178 |25 |                     <span className="text-katalyst-500">Grow.</span>
179 |26 |                 </h2>
180 |27 |                 <p className="mt-8 max-w-xl text-lg leading-relaxed" style={{ color: "var(--text-secondary)" }}>
181 |28 |                     Katalyst is your all-in-one student-mentor learning platform. Track progress,
182 |29 |                     book mentorship sessions, earn certificates, and unlock AI-powered career insights.
183 |30 |                 </p>
184 |31 |
185 |32 |             </section>
```



```
34 |         <div className="mt-10 flex flex-wrap items-center gap-4">
35 |             <Link to="/register" className="btn-primary text-lg">Start Learning !</Link>
36 |             <Link to="/login" className="btn-secondary text-lg">Try Demo Accounts </Link>
37 |         </div>
38 |
39 |         { /* Instant Demo Quick-Access for New Users */ }
40 |         <div className="glass-card mt-12 p-6 border-l-4 border-l-katalyst-500">
41 |             <h3 className="font-bold text-lg flex items-center gap-2">
42 |                 <span>'</span> Instant Demo Access for New Users
43 |             </h3>
44 |             <p className="text-sm mt-1" style={{ color: "var(--text-secondary)" }}>
45 |                 Explore the platform instantly with zero setup using pre-configured role demos:
46 |             </p>
47 |             <div className="mt-4 flex flex-wrap gap-3">
48 |                 <Link to="/login" className="btn-primary !py-2 text-xs">
49 |                     <span> Try Student Portal Demo
50 |                 </Link>
51 |                 <Link to="/login" className="btn-secondary !py-2 text-xs">
52 |                     <span> Try Mentor Portal Demo
53 |                 </Link>
54 |                 <Link to="/login" className="btn-secondary !py-2 text-xs">
55 |                     <span> Try Admin Portal Demo
56 |                 </Link>
57 |             </div>
58 |         </div>
59 |
60 |         { /* Feature cards */ }
61 |         <div className="mt-16 grid gap-6 sm:grid-cols-2 lg:grid-cols-3">
62 |             { [
63 |                 { icon: "ðŸ“œ", title: "Structured Trainings", desc: "Videos, quizzes, assignments & certificates" },
64 |                 { icon: "ðŸ“œ", title: "Expert Mentorship", desc: "Book sessions, get feedback & track growth" },
65 |                 { icon: "ðŸ“œ", title: "AI Career Tools", desc: "Resume analyzer, roadmap & scholarship finder" },
66 |                 { icon: "ðŸ“œ", title: "Progress Analytics", desc: "Real-time placement readiness scoring" },
67 |                 { icon: "ðŸ“œ", title: "Certificates", desc: "Earn & download completion certificates" },
68 |                 { icon: "ðŸ“œ", title: "Smart Notifications", desc: "Stay updated on meetings & milestones" },
69 |             ].map((f) => (
70 |                 <div key={f.title} className="glass-card p-6 transition-transform hover:-translate-y-1">
71 |                     <span className="text-3xl">{f.icon}</span>
72 |                     <h3 className="mt-4 text-lg font-bold">{f.title}</h3>
73 |                     <p className="mt-2 text-sm" style={{ color: "var(--text-secondary)" }}>{f.desc}</p>
74 |                 </div>
75 |             ))
76 |         </div>
77 |
78 |         { /* Portal preview */ }
79 |         <div className="glass-card mt-16 flex flex-col items-start justify-between gap-6 p-8 sm:flex-row sm:it
80 |             <div>
81 |                 <p className="section-subtitle">Platform Portals</p>
82 |                 <h3 className="mt-2 text-2xl font-bold lg:text-3xl">Multi-Role Learning & Mentorship</h3>
83 |                 <p className="mt-3 max-w-md" style={{ color: "var(--text-secondary)" }}>
84 |                     Students learn and grow. Mentors guide and track. Admins manage the entire ecosystem.
85 |                 </p>
86 |             </div>
87 |             <div className="flex gap-4">
88 |                 { ["ðŸ“œ", "ðŸ“œ", "ðŸ“œ"].map((e, i) => (
89 |                     <div key={i} className="flex h-16 w-16 items-center justify-center rounded-2xl bg-katalyst-500 t
90 |                         {e}
91 |                     </div>
92 |                 ))
93 |             </div>
94 |         </div>
95 |     </section>
96 | </div>
97 | );
98 | }
99 |
```

(9.1 KB)

```
1 | import { useState } from "react";
2 | import { Link, useNavigate } from "react-router-dom";
3 | import { useAuth } from "../context/AuthContext";
4 | import API from "../api";
5 | import ThemeToggle from "../components/ThemeToggle";
6 |
7 | export default function Login() {
8 |   const [role, setRole] = useState("student");
9 |   const [email, setEmail] = useState("");
10 |   const [password, setPassword] = useState("");
11 |   const [error, setError] = useState("");
12 |   const [loading, setLoading] = useState(false);
13 |
14 |   // Reset password state
15 |   const [showReset, setShowReset] = useState(false);
16 |   const [resetEmail, setResetEmail] = useState("");
17 |   const [newPassword, setNewPassword] = useState("");
18 |   const [resetMessage, setResetMessage] = useState("");
19 |
20 |   const { login } = useAuth();
21 |   const navigate = useNavigate();
22 |
23 |   const handleQuickDemo = async (demoRole) => {
24 |     setError("");
25 |     setLoading(true);
26 |     let demoEmail = "";
27 |     let demoPass = "";
28 |
29 |     if (demoRole === "student") {
30 |       demoEmail = "diksha@katalyst.io";
31 |       demoPass = "Student@123";
32 |     } else if (demoRole === "mentor") {
33 |       demoEmail = "sarah@katalyst.io";
34 |       demoPass = "Mentor@123";
35 |     } else if (demoRole === "admin") {
36 |       demoEmail = "admin@katalyst.io";
37 |       demoPass = "Admin@123";
38 |     }
39 |
40 |     setEmail(demoEmail);
41 |     setPassword(demoPass);
42 |     setRole(demoRole);
43 |
44 |     try {
45 |       const res = await API.post("/auth/login", {
46 |         email: demoEmail,
47 |         password: demoPass,
48 |         role: demoRole
49 |       });
50 |       login(res.data.user, res.data.token);
51 |       navigate(`/${res.data.user.role}`);
52 |     } catch (err) {
53 |       setError(err.response?.data?.message || "Demo login failed");
54 |     } finally {
55 |       setLoading(false);
56 |     }
57 |   };
58 |
59 |   const handleSubmit = async (e) => {
60 |     e.preventDefault();
61 |     setError("");
62 |     setLoading(true);
63 |
64 |     try {
65 |       const res = await API.post("/auth/login", {
66 |         email: email.trim().toLowerCase(),
67 |         password: password.trim(),
68 |         role
69 |       });
70 |       login(res.data.user, res.data.token);
71 |       navigate(`/${res.data.user.role}`);
72 |     } catch (err) {
73 |       setError(err.response?.data?.message || "Login failed");
74 |     } finally {
75 |       setLoading(false);
76 |     }
77 |   };
78 |
79 |   const handleResetPassword = async (e) => {
80 |     e.preventDefault();
81 |     setResetMessage("");
```

```
82 |     try {
83 |       const res = await API.post("/auth/reset-password", {
84 |         email: resetEmail.trim().toLowerCase(),
85 |         newPassword: newPassword.trim(),
86 |       });
87 |       setResetMessage(res.data.message);
88 |       setEmail(resetEmail);
89 |       setPassword(newPassword);
90 |       setTimeout(() => {
91 |         setShowReset(false);
92 |         setResetMessage("");
93 |       }, 2000);
94 |     } catch (err) {
95 |       setResetMessage(err.response?.data?.message || "Reset failed");
96 |     }
97 |   };
98 |
99 |   const roles = [
100 |     { id: "student", label: "ð<ß" Student" },
101 |     { id: "mentor", label: "ð=Üh ð<ßë Mentor" },
102 |     { id: "admin", label: "ð=Þáp Admin" },
103 |   ];
104 |
105 |   return (
106 |     <div className="flex min-h-screen items-center justify-center p-4" style={{ background: "var(--bg-primary)"
107 |       <div className="absolute right-6 top-6"><ThemeToggle /></div>
108 |
109 |       <div className="glass-card w-full max-w-md p-8 animate-fade-in">
110 |         <Link to="/" className="text-sm font-medium text-katalyst-500 hover:underline">
111 |           !• Back to Katalyst
112 |         </Link>
113 |
114 |         <h1 className="mt-6 text-3xl font-bold">
115 |           Welcome <span className="text-katalyst-500">Back.</span>
116 |         </h1>
117 |         <p className="mt-2 text-sm" style={{ color: "var(--text-secondary)" }}>
118 |           Login to continue your Katalyst journey.
119 |         </p>
120 |
121 |         { /* 1-Click Instant Demo Login */ }
122 |         <div className="mt-5 rounded-xl border p-3" style={{ borderColor: "var(--border)", background: "rgba(2
123 |           <p className="text-xs font-bold text-center mb-2 text-katalyst-500 uppercase tracking-wider">
124 |             ð=Þë One-Click Instant Demo Login
125 |           </p>
126 |           <div className="grid grid-cols-3 gap-2">
127 |             <button
128 |               type="button"
129 |               onClick={() => handleQuickDemo("student")}
130 |               className="btn-primary !py-1.5 text-xs font-semibold"
131 |             >
132 |               ð<ß" Student Demo
133 |             </button>
134 |             <button
135 |               type="button"
136 |               onClick={() => handleQuickDemo("mentor")}
137 |               className="btn-primary !py-1.5 text-xs font-semibold"
138 |             >
139 |               ð=Üh ð<ßë Mentor Demo
140 |             </button>
141 |             <button
142 |               type="button"
143 |               onClick={() => handleQuickDemo("admin")}
144 |               className="btn-primary !py-1.5 text-xs font-semibold"
145 |             >
146 |               ð=Þáp Admin Demo
147 |             </button>
148 |           </div>
149 |         </div>
150 |
151 |         <div className="mt-6 grid grid-cols-3 gap-2">
152 |           {roles.map((r) => (
153 |             <button
154 |               key={r.id}
155 |               type="button"
156 |               onClick={() => setRole(r.id)}
157 |               className={`rounded-xl border px-2 py-3 text-sm font-medium transition-all ${
158 |                 role === r.id
159 |                   ? "border-katalyst-500 bg-katalyst-500 text-white"
```

```
160 |         : "border-transparent hover:border-katalyst-300"
161 |       `}`
162 |       style={role !== r.id ? { background: "var(--bg-secondary)" } : {}}
163 |     >
164 |       {r.label}
165 |     </button>
166 |   )))
167 | </div>
168 |
169 | <form onSubmit={handleSubmit} className="mt-6 space-y-4">
170 |   <div>
171 |     <label className="mb-1 block text-sm font-medium">Email</label>
172 |     <input type="email" value={email} onChange={(e) => setEmail(e.target.value)}
173 |       className="input-field" placeholder="you@email.com" required />
174 |   </div>
175 |   <div>
176 |     <div className="flex items-center justify-between mb-1">
177 |       <label className="text-sm font-medium">Password</label>
178 |       <button
179 |         type="button"
180 |         onClick={() => { setResetEmail(email); setShowReset(true); }}
181 |         className="text-xs text-katalyst-500 hover:underline"
182 |       >
183 |         Forgot Password?
184 |       </button>
185 |     </div>
186 |     <input type="password" value={password} onChange={(e) => setPassword(e.target.value)}
187 |       className="input-field" placeholder="....." required />
188 |   </div>
189 |   {error && (
190 |     <div className="rounded-lg bg-red-100 p-3 text-sm text-red-600 dark:bg-red-900/30 dark:text-red-30"
191 |       >{error}</div>
192 |   )}
193 |   <button type="submit" disabled={loading} className="btn-primary w-full">
194 |     {loading ? "Signing in..." : `Login as ${role} !`}
195 |   </button>
196 | </form>
197 |
198 | <p className="mt-4 text-center text-sm" style={{ color: "var(--text-muted)" }}>
199 |   New here?{" "}
200 |   <Link to="/register" className="font-medium text-katalyst-500 hover:underline">
201 |     Create account
202 |   </Link>
203 | </p>
204 | </div>
205 |
206 | {showReset && (
207 |   <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
208 |     <div className="glass-card w-full max-w-md p-6 animate-fade-in">
209 |       <h3 className="text-xl font-bold">Reset Password</h3>
210 |       <p className="text-sm mt-1" style={{ color: "var(--text-secondary)" }}>
211 |         Enter your email and a new password below.
212 |       </p>
213 |       <form onSubmit={handleResetPassword} className="mt-4 space-y-3">
214 |         <div>
215 |           <label className="text-xs font-medium">Account Email</label>
216 |           <input
217 |             type="email"
218 |             className="input-field mt-1"
219 |             placeholder="registered@email.com"
220 |             value={resetEmail}
221 |             onChange={(e) => setResetEmail(e.target.value)}
222 |             required
223 |           />
224 |         </div>
225 |         <div>
226 |           <label className="text-xs font-medium">New Password</label>
227 |           <input
228 |             type="password"
229 |             className="input-field mt-1"
230 |             placeholder="New password (min 6 characters)"
231 |             minLength={6}
232 |             value={newPassword}
233 |             onChange={(e) => setNewPassword(e.target.value)}
234 |           />
235 |         </div>
236 |       </form>
237 |     </div>
238 |   </div>
239 | )}
```

```
237 |         required
238 |       />
239 |     </div>
241 |     {resetMessage && (
242 |       <p className="text-xs font-semibold text-katalyst-500">{resetMessage}</p>
243 |     )}
245 |     <div className="flex gap-2 pt-2">
246 |       <button type="button" onClick={() => setShowReset(false)} className="btn-secondary flex-1">
247 |         Cancel
248 |       </button>
249 |       <button type="submit" className="btn-primary flex-1">
250 |         Update Password
251 |       </button>
252 |     </div>
253 |   </form>
254 | </div>
255 | </div>
256 |   )}
257 | </div>
258 | );
259 | }
260 | }                                     (5.0 KB)
261 |
1 | import { useEffect, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import { BarChart, Bar, XAxis, YAxis, Tooltip, ResponsiveContainer } from "recharts";
4 | import DashboardLayout from "../../components/layout/DashboardLayout";
5 | import StatCard from "../../components/ui/StatCard";
6 | import API from "../../api";
7 | import { useAuth } from "../../context/AuthContext";
8 |
9 | export default function MentorDashboard() {
10 |   const { user } = useAuth();
11 |   const [data, setData] = useState(null);
12 |   const [loading, setLoading] = useState(true);
13 |   useEffect(() => {
14 |     API.get("/mentors/dashboard")
15 |       .then((res) => setData(res.data))
16 |       .catch(console.error)
17 |       .finally(() => setLoading(false));
18 |   }, []);
19 |
21 |   const respond = async (id, status) => {
22 |     try {
23 |       await API.put(`/mentors/meeting/${id}`, { status });
24 |       const res = await API.get("/mentors/dashboard");
25 |       setData(res.data);
26 |     } catch (err) {
27 |       alert(err.response?.data?.message || "Failed");
28 |     }
29 |   };
31 |   if (loading) {
32 |     return (
33 |       <DashboardLayout title="Dashboard" subtitle="Mentor Portal">
34 |         <div className="flex h-64 items-center justify-center">
35 |           <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
36 |             </div>
37 |         </div>
38 |       </DashboardLayout>
39 |     );
41 |   }
42 |   const stats = data?.stats || {};
43 |   const chartData = (data?.mentor?.assignedStudents || []).slice(0, 5).map((s) => ({
44 |     name: s.name?.split(" ")[0] || "Student",
45 |     progress: Math.floor(Math.random() * 40 + 60),
46 |   }));
47 |   return (
48 |     <DashboardLayout title={`Welcome, ${user?.name?.split(" ")[0] || "Mentor"}`} subtitle="Mentor Portal">
49 |       <div className="mb-6 grid gap-4 sm:grid-cols-2 xl:grid-cols-4">
50 |         <StatCard title="Total Students" value={stats.totalStudents || 0} icon="👤" />
51 |         <StatCard title="Pending Requests" value={stats.pendingRequests || 0} subtitle="Need action" icon="#0" />
52 |         <StatCard title="Completed Meetings" value={stats.completedMeetings || 0} icon="🗓️" />
53 |         <StatCard title="Rating" value={`${stats.rating || 5}/5`} icon="⭐" />
54 |       </div>
55 |       <div className="grid gap-6 lg:grid-cols-2">
```

```
57 |         {/* Pending requests */}
58 |         <div className="glass-card p-6">
59 |             <div className="mb-4 flex items-center justify-between">
60 |                 <h3 className="section-title">Pending Requests</h3>
61 |                 <Link to="/mentor/meetings" className="text-sm text-katalyst-500 hover:underline">View all !'</Link>
62 |             </div>
63 |             {(data?.pendingMeetings || []).length === 0 ? (
64 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No pending requests.</p>
65 |             ) : (
66 |                 data.pendingMeetings.slice(0, 3).map((m) => (
67 |                     <div key={m._id} className="mb-3 rounded-xl border p-4" style={{ borderColor: "var(--border)" }}>
68 |                         <p className="font-medium">{m.topic}</p>
69 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
70 |                             {m.studentId?.name} · {new Date(m.scheduledDate).toLocaleDateString()} {m.scheduledTime}
71 |                         </p>
72 |                         <div className="mt-3 flex gap-2">
73 |                             <button onClick={() => respond(m._id, "accepted")} className="btn-primary !py-1.5 text-xs">A
74 |                             <button onClick={() => respond(m._id, "rejected")} className="btn-secondary !py-1.5 text-xs"
75 |                         </div>
76 |                     </div>
77 |                 ))
78 |             )}
79 |         </div>
80 |
81 |         {/* Upcoming meetings */}
82 |         <div className="glass-card p-6">
83 |             <h3 className="section-title mb-4">Upcoming Meetings</h3>
84 |             {(data?.upcomingMeetings || []).length === 0 ? (
85 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No upcoming meetings.</p>
86 |             ) : (
87 |                 data.upcomingMeetings.map((m) => (
88 |                     <div key={m._id} className="mb-3 rounded-xl p-3" style={{ background: "var(--accent-light)" }}>
89 |                         <p className="font-medium">{m.topic}</p>
90 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
91 |                             {m.studentId?.name} · {new Date(m.scheduledDate).toLocaleDateString()}
92 |                         </p>
93 |                         {m.meetLink && (
94 |                             <a href={m.meetLink} target="_blank" rel="noreferrer" className="text-xs text-katalyst-500 h
95 |                                 Join Meet !'
96 |                             </a>
97 |                         )}
98 |                     </div>
99 |                 ))
100 |             )}
101 |         </div>
102 |     </div>
103 |
104 |     {chartData.length > 0 && (
105 |         <div className="glass-card mt-6 p-6">
106 |             <h3 className="section-title mb-4">Student Progress Overview</h3>
107 |             <ResponsiveContainer width="100%" height={250}>
108 |                 <BarChart data={chartData}>
109 |                     <XAxis dataKey="name" tick={{ fontSize: 12 }} />
110 |                     <YAxis domain={[0, 100]} tick={{ fontSize: 12 }} />
111 |                     <Tooltip />
112 |                     <Bar dataKey="progress" fill="#ec4899" radius={[6, 6, 0, 0]} />
113 |                 </BarChart>
114 |             </ResponsiveContainer>
115 |         </div>
116 |     )}
117 | </DashboardLayout>
118 | );
119 | }
120 |
```

(6.3 KB)

```
1 | import { useEffect, useState } from "react";
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
3 | import CalendarView from "../../components/CalendarView";
4 | import API from "../../api";
5 |
6 | export default function MentorMeetings() {
7 |   const [meetings, setMeetings] = useState([]);
8 |   const [loading, setLoading] = useState(true);
9 |   const [notesModal, setNotesModal] = useState(null);
10 |   const [notes, setNotes] = useState("");
11 |   const [tab, setTab] = useState("calendar");
12 |
13 |   const fetchMeetings = () => {
14 |     API.get("/meetings/mentor")
15 |       .then((res) => setMeetings(res.data.meetings || []))
16 |       .catch(console.error)
17 |       .finally(() => setLoading(false));
18 |   };
19 |
20 |   useEffect(() => { fetchMeetings(); }, []);
21 |
22 |   const respond = async (id, status) => {
23 |     await API.put(`/meetings/${id}/status`, { status });
24 |     fetchMeetings();
25 |   };
26 |
27 |   const addNotes = async () => {
28 |     await API.put(`/meetings/${notesModal}/status`, { mentorNotes: notes });
29 |     setNotesModal(null);
30 |     setNotes("");
31 |     fetchMeetings();
32 |   };
33 |
34 |   const completeMeeting = async (id) => {
35 |     await API.put(`/meetings/${id}/status`, { status: "completed" });
36 |     fetchMeetings();
37 |   };
38 |
39 |   const statusColor = {
40 |     pending: "bg-yellow-100 text-yellow-700 dark:bg-yellow-900/30 dark:text-yellow-300",
41 |     accepted: "bg-green-100 text-green-700 dark:bg-green-900/30 dark:text-green-300",
42 |     rejected: "bg-red-100 text-red-700 dark:bg-red-900/30 dark:text-red-300",
43 |     completed: "bg-purple-100 text-purple-700 dark:bg-purple-900/30 dark:text-purple-300",
44 |   };
45 |
46 |   return (
47 |     <DashboardLayout title="Calendar & Meetings" subtitle="Mentor Portal">
48 |       <div className="mb-6 flex gap-2">
49 |         {[
50 |           { id: "calendar", label: "📅 Interactive Calendar" },
51 |           { id: "requests", label: "📝 Meeting Requests" },
52 |         ]}.map((t) => (
53 |           <button key={t.id} onClick={() => setTab(t.id)}
54 |             className={`rounded-full px-4 py-1.5 text-sm font-medium ${
55 |               tab === t.id ? "bg-katalyst-500 text-white" : "border"
56 |             }`}
57 |             style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
58 |           >
59 |             {t.label}
60 |           </button>
61 |         ))}
62 |       </div>
63 |       {loading ? (
64 |         <div className="flex h-40 items-center justify-center">
65 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
66 |             </div>
67 |         </div>
68 |       ) : tab === "calendar" ? (
69 |         <div className="space-y-6">
70 |           <CalendarView events={meetings} userRole="mentor" />
71 |           <div>
72 |             <div className="glass-card p-6">
73 |               <h3 className="section-title mb-4">Scheduled Mentorship Sessions</h3>
74 |               <div className="space-y-3">
75 |                 {meetings.length === 0 ? (
76 |                   <p className="text-sm" style={{ color: "var(--text-muted)" }}>No sessions scheduled.</p>
77 |                 ) : (
78 |                   meetings.map((m) => (
79 |                     <div key={m._id} className="flex flex-wrap items-center justify-between gap-3 rounded-xl bor
80 |                       <div>
```

```
82 |         <p className="font-bold">{m.topic}</p>
83 |         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
84 |             Student: {m.studentId?.name || "Student"} · {new Date(m.scheduledDate).toLocaleDateStr
85 |         </p>
86 |     </div>
87 |     <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.
88 |         {m.status}
89 |     </span>
90 | </div>
91 | ))
92 | }}
93 | </div>
94 | </div>
95 | </div>
96 | ) : (
97 |     <div className="space-y-4">
98 |         {meetings.map((m) => (
99 |             <div key={m._id} className="glass-card p-5">
100 |                 <div className="flex flex-wrap items-start justify-between gap-3">
101 |                     <div>
102 |                         <h3 className="font-bold">{m.topic}</h3>
103 |                         <p className="text-sm" style={{ color: "var(--text-secondary)" }}>
104 |                             Student: {m.studentId?.name} ({m.studentId?.email}) · {new Date(m.scheduledDate).toLocaleD
105 |                         </p>
106 |                         {m.agenda && <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>Agenda: {m.a
107 |                     </div>
108 |                     <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.stat
109 |                         {m.status}
110 |                     </span>
111 |                 </div>
112 |                 <div className="mt-4 flex flex-wrap gap-2">
113 |                     {m.status === "pending" && (
114 |                         <>
115 |                             <button onClick={() => respond(m._id, "accepted")} className="btn-primary !py-1.5 text-xs"
116 |                             <button onClick={() => respond(m._id, "rejected")} className="btn-secondary !py-1.5 text-x
117 |                         </>
118 |                     )}
119 |                     {m.status === "accepted" && (
120 |                         <>
121 |                             {m.meetLink && (
122 |                                 <a href={m.meetLink} target="_blank" rel="noreferrer" className="btn-primary !py-1.5 tex
123 |                             )}
124 |                             <button onClick={() => setNotesModal(m._id)} className="btn-secondary !py-1.5 text-xs">Add
125 |                             <button onClick={() => completeMeeting(m._id)} className="btn-secondary !py-1.5 text-xs">M
126 |                         </>
127 |                     )}
128 |                 </div>
129 |             </div>
130 |         )})
131 |     </div>
132 | )}
133 | {notesModal && (
134 |     <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
135 |         <div className="glass-card w-full max-w-md p-6">
136 |             <h3 className="font-bold">Meeting Notes</h3>
137 |             <textarea className="input-field mt-3" rows={4} value={notes}
138 |                 onChange={(e) => setNotes(e.target.value)} placeholder="Add meeting notes..." />
139 |             <div className="mt-3 flex gap-2">
140 |                 <button onClick={() => setNotesModal(null)} className="btn-secondary flex-1">Cancel</button>
141 |                 <button onClick={addNotes} className="btn-primary flex-1">Save Notes</button>
142 |             </div>
143 |         </div>
144 |     </div>
145 | )}
146 | </DashboardLayout>
147 | );
148 | }
149 | }
150 |
```


(0.2 KB)

```
1 | import NotificationsPage from "../../components/NotificationsPage";
```

```
3 | export default function MentorNotifications() {
```

```
4 |   return <NotificationsPage userRole="mentor" />;
```

```
5 | }
```

(4.2 KB)

```
1 | import { useEffect, useState } from "react";
```

```
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
```

```
3 | import API from "../../api";
```

```
5 | export default function MentorStudents() {
```

```
6 |   const [students, setStudents] = useState([]);
```

```
7 |   const [loading, setLoading] = useState(true);
```

```
8 |   const [selected, setSelected] = useState(null);
```

```
9 |   const [feedback, setFeedback] = useState({ rating: 5, comment: "", category: "general" });
```

```
11 |   useEffect(() => {
```

```
12 |     API.get("/mentors/students")
```

```
13 |       .then((res) => setStudents(res.data.students || []))
```

```
14 |       .catch(console.error)
```

```
15 |       .finally(() => setLoading(false));
```

```
16 |   }, []);
```

```
18 |   const giveFeedback = async (studentId) => {
```

```
19 |     try {
```

```
20 |       await API.post("/mentors/feedback", { studentId, ...feedback });
```

```
21 |       alert("Feedback submitted!");
```

```
22 |       setSelected(null);
```

```
23 |     } catch (err) {
```

```
24 |       alert(err.response?.data?.message || "Failed");
```

```
25 |     }
```

```
26 |   };
```

```
28 |   return (
```

```
29 |     <DashboardLayout title="My Students" subtitle="Mentor Portal">
```

```
30 |       {loading ? (
```

```
31 |         <div className="flex h-40 items-center justify-center">
```

```
32 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500
```

```
33 |             />
```

```
34 |         ) : students.length === 0 ? (
```

```
35 |           <div className="glass-card p-12 text-center">
```

```
36 |             <p className="text-4xl">ðŸ’Š</p>
```

```
37 |             <p className="mt-4">No students assigned yet.</p>
```

```
38 |           </div>
```

```
39 |         ) : (
```

```
40 |           <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-3">
```

```
41 |             {students.map((s) => (
```

```
42 |               <div key={s._id} className="glass-card p-5">
```

```
43 |                 <div className="flex items-center gap-3">
```

```
44 |                   <div className="flex h-12 w-12 items-center justify-center rounded-full bg-katalyst-500 text-l
```

```
45 |                     {s.name?.charAt(0)}</div>
```

```
46 |                   </div>
```

```
47 |                   <div>
```

```
48 |                     <p className="font-bold">{s.name}</p>
```

```
49 |                     <p className="text-xs" style={{ color: "var(--text-muted)" }}>{s.email}</p>
```

```
50 |                   </div>
```

```
51 |                 </div>
```

```
52 |               {s.progress && (
```

```
53 |                 <div className="mt-4">
```

```
54 |                   <div className="flex justify-between text-sm">
```

```
55 |                     <span>Progress</span>
```

```
56 |                     <span className="font-bold text-katalyst-500">{s.progress.overallScore || 0}%</span>
```

```
57 |                   </div>
```

```
58 |                   <div className="progress-bar mt-1">
```

```
59 |                     <div className="progress-bar-fill" style={{ width: `${s.progress.overallScore || 0}%` }} /
```

```
60 |                   </div>
```

```
61 |                 </div>
```

```
62 |               )}
```

```
63 |             {s.skills?.length > 0 && (
```

```
64 |               <div className="mt-3 flex flex-wrap gap-1">
```

```
65 |                 {s.skills.slice(0, 3).map((sk) => (
```

```
66 |                   <span key={sk} className="badge !text-[10px]">{sk}</span>
```

```
67 |                 )}
```

```
68 |               </div>
```

```
69 |             )}
```

```
70 |           <button onClick={() => setSelected(s._id)} className="btn-secondary mt-4 w-full !py-2 text-sm">
```

```
71 |             Give Feedback
```

```
72 |         </button>
73 |     </div>
74 |   )}}
75 | </div>
76 | })
77 | {selected && (
78 |   <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">
79 |     <div className="glass-card w-full max-w-md p-6">
80 |       <h3 className="text-xl font-bold">Give Feedback</h3>
81 |       <div className="mt-4 space-y-3">
82 |         <div>
83 |           <label className="text-sm">Rating (1-5)</label>
84 |           <input type="number" min={1} max={5} className="input-field" value={feedback.rating}
85 |             onChange={(e) => setFeedback({ ...feedback, rating: Number(e.target.value) })} />
86 |         </div>
87 |         <textarea className="input-field" rows={3} placeholder="Your feedback..."
88 |           value={feedback.comment} onChange={(e) => setFeedback({ ...feedback, comment: e.target.value }
89 |         </div>
90 |         <div className="flex gap-2">
91 |           <button onClick={() => setSelected(null)} className="btn-secondary flex-1">Cancel</button>
92 |           <button onClick={() => giveFeedback(selected)} className="btn-primary flex-1">Submit</button>
93 |         </div>
94 |       </div>
95 |     </div>
96 |   </div>
97 | )}
98 | </DashboardLayout>
99 | );
100 | } <!-- mentor/src/pages/Students.jsx (5.4 KB) -->
101 |
1 | import { useState } from "react";
2 | import { Link, useNavigate } from "react-router-dom";
3 | import { useAuth } from "../context/AuthContext";
4 | import API from "../api";
5 | import ThemeToggle from "../components/ThemeToggle";
6 |
7 | export default function Register() {
8 |   const [role, setRole] = useState("student");
9 |   const [form, setForm] = useState({
10 |     name: "",
11 |     email: "",
12 |     password: "",
13 |     phone: "",
14 |   });
15 |
16 |   const [error, setError] = useState("");
17 |   const [loading, setLoading] = useState(false);
18 |
19 |   const { login } = useAuth();
20 |   const navigate = useNavigate();
21 |
22 |   const handleChange = (e) => {
23 |     setForm({
24 |       ...form,
25 |       [e.target.name]: e.target.value,
26 |     });
27 |   };
28 |
29 |   const handleSubmit = async (e) => {
30 |     e.preventDefault();
31 |     setError("");
32 |     setLoading(true);
33 |     try {
34 |       const res = await API.post("/auth/register", {
35 |         name: form.name.trim(),
36 |         email: form.email.trim().toLowerCase(),
37 |         password: form.password,
38 |         phone: form.phone.trim(),
39 |         role,
40 |       });
41 |     } catch (err) {
42 |       console.error("REGISTER ERROR:", err);
43 |     }
44 |     if (!res.data.token || !res.data.user) {
45 |       throw new Error("Server did not return token or user data");
46 |     }
47 |     login(res.data.user, res.data.token);
48 |     navigate(`/${res.data.user.role}`);
49 |   }
50 | }
51 |
52 |
```

```
53 |         if (err.response?.data?.message) {
54 |             setError(err.response.data.message);
55 |         } else if (err.message) {
56 |             setError(err.message);
57 |         } else {
58 |             setError("Registration failed");
59 |         }
60 |     } finally {
61 |         setLoading(false);
62 |     }
63 | };
64 |
65 | const roles = [
66 |   { id: "student", label: "ð<ß" Student" },
67 |   { id: "mentor", label: "ð=Üh ð<ßë Mentor" },
68 |   { id: "admin", label: "ð=Þáp Admin" },
69 | ];
70 |
71 | return (
72 |   <div
73 |     className="flex min-h-screen items-center justify-center p-4"
74 |     style={{ background: "var(--bg-primary)" }}
75 |   >
76 |     <div className="absolute right-6 top-6">
77 |       <ThemeToggle />
78 |     </div>
79 |
80 |     <div className="glass-card w-full max-w-md p-8 animate-fade-in">
81 |       <Link
82 |         to="/"
83 |         className="text-sm font-medium text-katalyst-500 hover:underline"
84 |       >
85 |         !• Back to Katalyst
86 |       </Link>
87 |
88 |       <h1 className="mt-6 text-3xl font-bold">
89 |         Join <span className="text-katalyst-500">Katalyst.</span>
90 |       </h1>
91 |
92 |       <p
93 |         className="mt-2 text-sm"
94 |         style={{ color: "var(--text-secondary)" }}
95 |       >
96 |         Create your account as {role} and start learning.
97 |       </p>
98 |
99 |       <div className="mt-6 grid grid-cols-3 gap-2">
100 |         {roles.map((r) => (
101 |           <button
102 |             key={r.id}
103 |             type="button"
104 |             onClick={() => setRole(r.id)}
105 |             className={`rounded-xl border px-2 py-3 text-sm font-medium transition-all ${
106 |               role === r.id
107 |                 ? "border-katalyst-500 bg-katalyst-500 text-white"
108 |                 : "border-transparent hover:border-katalyst-300"
109 |             }}
110 |             style={role !== r.id ? { background: "var(--bg-secondary)" } : {}}
111 |           >
112 |             {r.label}
113 |           </button>
114 |         ))}
115 |       </div>
116 |
117 |       <form onSubmit={handleSubmit} className="mt-6 space-y-4">
118 |         <div>
119 |           <label className="mb-1 block text-sm font-medium">Name</label>
120 |           <input
121 |             type="text"
122 |             name="name"
123 |             value={form.name}
124 |             onChange={handleChange}
125 |             className="input-field"
126 |             placeholder="Your full name"
127 |             required
128 |           />
129 |         </div>
130 |
131 |       </div>
```

```
132 |         <label className="mb-1 block text-sm font-medium">Email</label>
133 |         <input
134 |           type="email"
135 |           name="email"
136 |           value={form.email}
137 |           onChange={handleChange}
138 |           className="input-field"
139 |           placeholder="you@email.com"
140 |           required
141 |         />
142 |       </div>
144 |       <div>
145 |         <label className="mb-1 block text-sm font-medium">Password</label>
146 |         <input
147 |           type="password"
148 |           name="password"
149 |           value={form.password}
150 |           onChange={handleChange}
151 |           className="input-field"
152 |           placeholder="Minimum 6 characters"
153 |           minLength={6}
154 |           required
155 |         />
156 |       </div>
158 |       <div>
159 |         <label className="mb-1 block text-sm font-medium">Phone</label>
160 |         <input
161 |           type="text"
162 |           name="phone"
163 |           value={form.phone}
164 |           onChange={handleChange}
165 |           className="input-field"
166 |           placeholder="Optional"
167 |         />
168 |       </div>
170 |       {error && (
171 |         <div className="rounded-lg bg-red-100 p-3 text-sm text-red-600">
172 |           {error}
173 |         </div>
174 |       )}
176 |       <button
177 |         type="submit"
178 |         disabled={loading}
179 |         className="btn-primary w-full"
180 |       >
181 |         {loading ? "Creating account..." : `Register as ${role} !`}
182 |       </button>
183 |     </form>
185 |     <p
186 |       className="mt-4 text-center text-sm"
187 |       style={{ color: "var(--text-muted)" }}
188 |     >
189 |       Already have an account?{" "}
190 |       <Link
191 |         to="/login"
192 |         className="font-medium text-katalyst-500 hover:underline"
193 |       >
194 |         Sign in
195 |       </Link>
196 |     </p>
197 |   </div>
198 | </div>
199 | );
200 | }
```

(8.0 KB)

```
1 | import { useState } from "react";
2 | import DashboardLayout from "../../components/layout/DashboardLayout";
3 | import API from "../../api";
4 |
5 | export default function StudentAIHub() {
6 |   const [tab, setTab] = useState("roadmap");
7 |   const [roadmap, setRoadmap] = useState(null);
8 |   const [resumeResult, setResumeResult] = useState(null);
9 |   const [scholarships, setScholarships] = useState(null);
10 |   const [resumeText, setResumeText] = useState("");
11 |   const [interests, setInterests] = useState("");
12 |   const [loading, setLoading] = useState(false);
13 |   const [progress, setProgress] = useState(null);
14 |
15 |   const loadRoadmap = async () => {
16 |     setLoading(true);
17 |     try {
18 |       const res = await API.post("/ai/career-roadmap");
19 |       setRoadmap(res.data);
20 |     } catch (err) {
21 |       alert(err.response?.data?.message || "Failed to load roadmap");
22 |     } finally {
23 |       setLoading(false);
24 |     }
25 |   };
26 |
27 |   const analyzeResume = async () => {
28 |     if (!resumeText.trim()) return alert("Paste your resume content");
29 |     setLoading(true);
30 |     try {
31 |       const res = await API.post("/ai/resume-analyze", { content: resumeText });
32 |       setResumeResult(res.data);
33 |     } catch (err) {
34 |       alert(err.response?.data?.message || "Analysis failed");
35 |     } finally {
36 |       setLoading(false);
37 |     }
38 |   };
39 |
40 |   const getScholarships = async () => {
41 |     setLoading(true);
42 |     try {
43 |       const res = await API.post("/ai/scholarships", {
44 |         interests: interests.split(",").map((s) => s.trim()).filter(Boolean),
45 |       });
46 |       setScholarships(res.data.recommendations);
47 |     } catch (err) {
48 |       alert(err.response?.data?.message || "Failed");
49 |     } finally {
50 |       setLoading(false);
51 |     }
52 |   };
53 |
54 |   const loadProgress = async () => {
55 |     setLoading(true);
56 |     try {
57 |       const res = await API.get("/students/progress");
58 |       setProgress(res.data);
59 |     } catch (err) {
60 |       alert(err.response?.data?.message || "Failed");
61 |     } finally {
62 |       setLoading(false);
63 |     }
64 |   };
65 |
66 |   const tabs = [
67 |     { id: "roadmap", label: "ðŸ“š Career Roadmap", action: loadRoadmap },
68 |     { id: "resume", label: "ðŸ“š Resume Analyzer", action: null },
69 |     { id: "scholarships", label: "ðŸ“š Scholarships", action: null },
70 |     { id: "readiness", label: "ðŸ“š Placement Readiness", action: loadProgress },
71 |   ];
72 |
73 |   return (
74 |     <DashboardLayout title="AI Hub" subtitle="Student Portal">
75 |       <div className="mb-6 flex flex-wrap gap-2">
76 |         {tabs.map((t) => (
77 |           <button key={t.id} onClick={() => { setTab(t.id); t.action?.(); }}
78 |             className={`rounded-full px-4 py-2 text-sm font-medium transition-all $`
```

KATALYST.

Source Code: frontend/src/pages/student/AIHub.jsx (Cont.)

Generated: 22/8/2026 | Frontend

```
79 |         tab === t.id ? "bg-katalyst-500 text-white" : "border"
80 |     }`
81 |     style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
82 |     >
83 |     {t.label}
84 |   </button>
85 |   )))
86 | </div>
87 |
88 | {loading && (
89 |   <div className="flex h-20 items-center justify-center">
90 |     <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500"
91 |   </div>
92 | )}
93 |
94 | {!loading && tab === "roadmap" && (
95 |   <div className="space-y-4">
96 |     {!roadmap ? (
97 |       <div className="glass-card p-8 text-center">
98 |         <button onClick={loadRoadmap} className="btn-primary">Generate Career Roadmap</button>
99 |       </div>
100 |     ) : (
101 |       <>
102 |         <div className="glass-card p-6">
103 |           <h3 className="font-bold">Skills: {roadmap.skills?.join(", ") || "None yet"}</h3>
104 |         </div>
105 |         {roadmap.roadmap?.map((step, i) => (
106 |           <div key={i} className="glass-card p-5">
107 |             <div className="flex items-start gap-4">
108 |               <span className="flex h-8 w-8 shrink-0 items-center justify-center rounded-full bg-katalys"
109 |                 {i + 1}
110 |             </span>
111 |             <div>
112 |               <h4 className="font-bold">{step.title}</h4>
113 |               <p className="mt-1 text-sm" style={{ color: "var(--text-secondary)" }}>{step.description}
114 |               <p className="mt-2 text-xs text-katalyst-500">Target: {new Date(step.dueDate).toLocaleDa
115 |             </div>
116 |           </div>
117 |         </div>
118 |       )))
119 |     </>
120 |   )}
121 | </div>
122 | )}
123 |
124 | {!loading && tab === "resume" && (
125 |   <div className="glass-card p-6">
126 |     <h3 className="section-title mb-4">Paste Your Resume Content</h3>
127 |     <textarea className="input-field mb-4" rows={8} value={resumeText}
128 |       onChange={(e) => setResumeText(e.target.value)} placeholder="Paste resume text here..." />
129 |     <button onClick={analyzeResume} className="btn-primary">Analyze Resume</button>
130 |     {resumeResult && (
131 |       <div className="mt-6 grid gap-4 sm:grid-cols-3">
132 |         <div className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
133 |           <h4 className="font-bold text-green-700">Strengths</h4>
134 |           <ul className="mt-2 space-y-1 text-sm">{resumeResult.strengths?.map((s, i) => <li key={i}>• {s
135 |         </div>
136 |         <div className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
137 |           <h4 className="font-bold text-orange-600">Improve</h4>
138 |           <ul className="mt-2 space-y-1 text-sm">{resumeResult.improvementAreas?.map((s, i) => <li key={
139 |         </div>
140 |         <div className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
141 |           <h4 className="font-bold text-katalyst-600">Actions</h4>
142 |           <ul className="mt-2 space-y-1 text-sm">{resumeResult.actionItems?.map((s, i) => <li key={i}>•
143 |         </div>
144 |       </div>
145 |     )}
146 |   </div>
147 | )}
148 |
149 | {!loading && tab === "scholarships" && (
150 |   <div className="glass-card p-6">
151 |     <input className="input-field mb-4" placeholder="Interests (e.g. Technology, AI/ML)"
152 |       value={interests} onChange={(e) => setInterests(e.target.value)} />
153 |     <button onClick={getScholarships} className="btn-primary">Find Scholarships</button>
154 |     {scholarships && (
```

KATALYST.

Source Code: frontend/src/pages/student/AIHub.jsx (Cont.)

Generated: 22/8/2026 | Frontend

```

156 |         {scholarships.map((s, i) => (
157 |             <div key={i} className="rounded-xl border p-4" style={{ borderColor: "var(--border)" }}>
158 |                 <h4 className="font-bold">{s.name}</h4>
159 |                 <span className="badge mt-1">{s.category}</span>
160 |                 <p className="mt-2 text-sm" style={{ color: "var(--text-secondary)" }}>{s.description}</p>
161 |             </div>
162 |         ))}
163 |     </div>
164 | )}
165 | </div>
166 | )}
167 |
168 | {!loading && tab === "readiness" && progress && (
169 |     <div className="glass-card p-8 text-center">
170 |         <p className="text-6xl font-bold text-katalyst-500">{progress.progress?.placementReadiness || 0}%</p>
171 |         <p className="mt-2 text-lg font-medium">Placement Readiness Score</p>
172 |         <div className="progress-bar mx-auto mt-6 max-w-md">
173 |             <div className="progress-bar-fill" style={{ width: `${progress.progress?.placementReadiness || 0}%` }}>
174 |             </div>
175 |         <div className="mt-8 grid gap-4 sm:grid-cols-2 lg:grid-cols-4 text-left">
176 |             {[
177 |                 { label: "Training", val: progress.progress?.trainingCompletion },
178 |                 { label: "Meetings", val: progress.progress?.meetingsAttended },
179 |                 { label: "Assignments", val: progress.progress?.assignmentsSubmitted },
180 |                 { label: "Attendance", val: progress.progress?.attendanceRate },
181 |             ].map((item) => (
182 |                 <div key={item.label} className="rounded-xl p-4" style={{ background: "var(--accent-light)" }}>
183 |                     <p className="text-sm" style={{ color: "var(--text-muted)" }}>{item.label}</p>
184 |                     <p className="text-2xl font-bold">{item.val || 0}{item.label === "Meetings" || item.label ===
185 |                     </div>
186 |                 )})}
187 |             </div>
188 |         </div>
189 |     )}
190 | </DashboardLayout>
191 | );
192 | }
193 |
194 | View Source on GitHub (2.8 KB)
195 |
196 |
197 |
198 |
199 |
200 |
201 |
202 |
203 |
204 |
205 |
206 |
207 |
208 |
209 |
210 |
211 |
212 |
213 |
214 |
215 |
216 |
217 |
218 |
219 |
220 |
221 |
222 |
223 |
224 |
225 |
226 |
227 |
228 |
229 |
230 |
231 |
232 |
233 |
234 |
235 |
236 |
237 |
238 |
239 |
240 |
241 |
242 |
243 |
244 |
245 |
246 |
247 |
248 |
249 |
250 |
251 |
252 |
253 |
254 |
255 |
256 |
257 |
258 |
259 |
260 |
261 |
262 |
263 |
264 |
265 |
266 |
267 |
268 |
269 |
270 |
271 |
272 |
273 |
274 |
275 |
276 |
277 |
278 |
279 |
280 |
281 |
282 |
283 |
284 |
285 |
286 |
287 |
288 |
289 |
290 |
291 |
292 |
293 |
294 |
295 |
296 |
297 |
298 |
299 |
300 |
301 |
302 |
303 |
304 |
305 |
306 |
307 |
308 |
309 |
310 |
311 |
312 |
313 |
314 |
315 |
316 |
317 |
318 |
319 |
320 |
321 |
322 |
323 |
324 |
325 |
326 |
327 |
328 |
329 |
330 |
331 |
332 |
333 |
334 |
335 |
336 |
337 |
338 |
339 |
340 |
341 |
342 |
343 |
344 |
345 |
346 |
347 |
348 |
349 |
350 |
351 |
352 |
353 |
354 |
355 |
356 |
357 |
358 |
359 |
360 |
361 |
362 |
363 |
364 |
365 |
366 |
367 |
368 |
369 |
370 |
371 |
372 |
373 |
374 |
375 |
376 |
377 |
378 |
379 |
380 |
381 |
382 |
383 |
384 |
385 |
386 |
387 |
388 |
389 |
390 |
391 |
392 |
393 |
394 |
395 |
396 |
397 |
398 |
399 |
400 |
401 |
402 |
403 |
404 |
405 |
406 |
407 |
408 |
409 |
410 |
411 |
412 |
413 |
414 |
415 |
416 |
417 |
418 |
419 |
420 |
421 |
422 |
423 |
424 |
425 |
426 |
427 |
428 |
429 |
430 |
431 |
432 |
433 |
434 |
435 |
436 |
437 |
438 |
439 |
440 |
441 |
442 |
443 |
444 |
445 |
446 |
447 |
448 |
449 |
450 |
451 |
452 |
453 |
454 |
455 |
456 |
457 |
458 |
459 |
460 |
461 |
462 |
463 |
464 |
465 |
466 |
467 |
468 |
469 |
470 |
471 |
472 |
473 |
474 |
475 |
476 |
477 |
478 |
479 |
480 |
481 |
482 |
483 |
484 |
485 |
486 |
487 |
488 |
489 |
490 |
491 |
492 |
493 |
494 |
495 |
496 |
497 |
498 |
499 |
500 |
501 |
502 |
503 |
504 |
505 |
506 |
507 |
508 |
509 |
510 |
511 |
512 |
513 |
514 |
515 |
516 |
517 |
518 |
519 |
520 |
521 |
522 |
523 |
524 |
525 |
526 |
527 |
528 |
529 |
530 |
531 |
532 |
533 |
534 |
535 |
536 |
537 |
538 |
539 |
540 |
541 |
542 |
543 |
544 |
545 |
546 |
547 |
548 |
549 |
550 |
551 |
552 |
553 |
554 |
555 |
556 |
557 |
558 |
559 |
560 |
561 |
562 |
563 |
564 |
565 |
566 |
567 |
568 |
569 |
570 |
571 |
572 |
573 |
574 |
575 |
576 |
577 |
578 |
579 |
580 |
581 |
582 |
583 |
584 |
585 |
586 |
587 |
588 |
589 |
590 |
591 |
592 |
593 |
594 |
595 |
596 |
597 |
598 |
599 |
600 |
601 |
602 |
603 |
604 |
605 |
606 |
607 |
608 |
609 |
610 |
611 |
612 |
613 |
614 |
615 |
616 |
617 |
618 |
619 |
620 |
621 |
622 |
623 |
624 |
625 |
626 |
627 |
628 |
629 |
630 |
631 |
632 |
633 |
634 |
635 |
636 |
637 |
638 |
639 |
640 |
641 |
642 |
643 |
644 |
645 |
646 |
647 |
648 |
649 |
650 |
651 |
652 |
653 |
654 |
655 |
656 |
657 |
658 |
659 |
660 |
661 |
662 |
663 |
664 |
665 |
666 |
667 |
668 |
669 |
670 |
671 |
672 |
673 |
674 |
675 |
676 |
677 |
678 |
679 |
680 |
681 |
682 |
683 |
684 |
685 |
686 |
687 |
688 |
689 |
690 |
691 |
692 |
693 |
694 |
695 |
696 |
697 |
698 |
699 |
700 |
701 |
702 |
703 |
704 |
705 |
706 |
707 |
708 |
709 |
710 |
711 |
712 |
713 |
714 |
715 |
716 |
717 |
718 |
719 |
720 |
721 |
722 |
723 |
724 |
725 |
726 |
727 |
728 |
729 |
730 |
731 |
732 |
733 |
734 |
735 |
736 |
737 |
738 |
739 |
740 |
741 |
742 |
743 |
744 |
745 |
746 |
747 |
748 |
749 |
750 |
751 |
752 |
753 |
754 |
755 |
756 |
757 |
758 |
759 |
760 |
761 |
762 |
763 |
764 |
765 |
766 |
767 |
768 |
769 |
770 |
771 |
772 |
773 |
774 |
775 |
776 |
777 |
778 |
779 |
780 |
781 |
782 |
783 |
784 |
785 |
786 |
787 |
788 |
789 |
790 |
791 |
792 |
793 |
794 |
795 |
796 |
797 |
798 |
799 |
800 |
801 |
802 |
803 |
804 |
805 |
806 |
807 |
808 |
809 |
810 |
811 |
812 |
813 |
814 |
815 |
816 |
817 |
818 |
819 |
820 |
821 |
822 |
823 |
824 |
825 |
826 |
827 |
828 |
829 |
830 |
831 |
832 |
833 |
834 |
835 |
836 |
837 |
838 |
839 |
840 |
841 |
842 |
843 |
844 |
845 |
846 |
847 |
848 |
849 |
850 |
851 |
852 |
853 |
854 |
855 |
856 |
857 |
858 |

```

KATALYST.

Source Code: frontend/src/pages/student/Certificates.jsx (Cont.)

Generated: 22/8/2026 | Frontend

```
38 |         </div>
39 |         <div className="p-4">
40 |             <p className="text-xs" style={{ color: "var(--text-muted)" }}>
41 |                 Issued: {new Date(cert.issuedAt).toLocaleDateString()}
42 |             </p>
43 |             <p className="mt-1 font-mono text-xs text-katalyst-500">{cert.certificateId}</p>
44 |             <button
45 |                 onClick={() => {
46 |                     const content = `Katalyst Certificate\n\n${cert.studentName}\n${cert.trainingTitle}\nID: $
47 |                     const blob = new Blob([content], { type: "text/plain" });
48 |                     const url = URL.createObjectURL(blob);
49 |                     const a = document.createElement("a");
50 |                     a.href = url;
51 |                     a.download = `certificate-${cert.certificateId}.txt`;
52 |                     a.click();
53 |                 }}
54 |                 className="btn-primary mt-3 w-full !py-2 text-sm"
55 |             >
56 |                 Download Certificate
57 |             </button>
58 |         </div>
59 |     </div>
60 |     )}}
61 | </div>
62 | }}
63 | </DashboardLayout>
64 | );
65 | }
66 | }
67 |
68 | (6.9 KB)
69 |
70 | import { useEffect, useState } from "react";
71 | import { Link } from "react-router-dom";
72 | import { PieChart, Pie, Cell, ResponsiveContainer } from "recharts";
73 | import DashboardLayout from "../../components/layout/DashboardLayout";
74 | import StatCard from "../../components/ui/StatCard";
75 | import API from "../../api";
76 | import { useAuth } from "../../context/AuthContext";
77 |
78 | const COLORS = ["#ec4899", "#f472b6", "#fbcfe8", "#fce7f3"];
79 |
80 | export default function StudentDashboard() {
81 |     const { user } = useAuth();
82 |     const [data, setData] = useState(null);
83 |     const [loading, setLoading] = useState(true);
84 |
85 |     useEffect(() => {
86 |         API.get("/students/dashboard")
87 |             .then((res) => setData(res.data))
88 |             .catch(console.error)
89 |             .finally(() => setLoading(false));
90 |     }, []);
91 |
92 |     if (loading) {
93 |         return (
94 |             <DashboardLayout title="Dashboard" subtitle="Student Portal">
95 |                 <div className="flex h-64 items-center justify-center">
96 |                     <div className="h-10 w-10 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-5
97 |                 </div>
98 |             </DashboardLayout>
99 |         );
100 |     }
101 |
102 |     const progress = data?.progress || {};
103 |     const overall = progress.overallScore || 0;
104 |
105 |     const chartData = [
106 |         { name: "Training", value: progress.trainingCompletion || 0 },
107 |         { name: "Meetings", value: progress.meetingsAttended / Math.max(progress.totalMeetings, 1) },
108 |         { name: "Quiz", value: progress.quizScores?.length ? progress.quizScores.reduce((a, q) => a + (q.score / q
109 |         { name: "Attendance", value: progress.attendanceRate || 0 },
110 |     ];
111 |
112 |     return (
113 |         <DashboardLayout title={`Welcome, ${user?.name?.split(" ")[0] || "Student"}`} subtitle="Student Portal">
114 |             <div className="/* Overall progress */>
115 |                 <div className="glass-card mb-6 flex flex-col items-center gap-6 p-6 sm:flex-row">
116 |                     <div className="h-36 w-36">
117 |                         <ResponsiveContainer>
118 |                             <PieChart>
```



```
50 |         <Pie data={[{ value: overall }, { value: 100 - overall }]} cx="50%" cy="50%"
51 |             innerRadius={45} outerRadius={60} dataKey="value" startAngle={90} endAngle={-270}>
52 |             <Cell fill="#ec4899" />
53 |             <Cell fill="#fce7f3" />
54 |         </Pie>
55 |     </PieChart>
56 | </ResponsiveContainer>
57 | <div className="mt-[88px] text-center">
58 |     <p className="text-2xl font-bold">{overall}%</p>
59 |     <p className="text-xs" style={{ color: "var(--text-muted)" }}>Overall</p>
60 | </div>
61 | </div>
62 | <div className="flex-1">
63 |     <h2 className="text-xl font-bold">Your Learning Progress</h2>
64 |     <p className="mt-1 text-sm" style={{ color: "var(--text-secondary)" }}>
65 |         Placement Readiness: <strong className="text-katalyst-500">{progress.placementReadiness || 0}%</st
66 |     </p>
67 |     <div className="progress-bar mt-4">
68 |         <div className="progress-bar-fill" style={{ width: `${overall}%` }} />
69 |     </div>
70 | </div>
71 | </div>
72 |
73 | <div className="mb-6 grid gap-4 sm:grid-cols-2 xl:grid-cols-4">
74 |     <StatCard title="Training Progress" value={`${progress.trainingCompletion || 0}%`} subtitle="Keep goin
75 |     <StatCard title="Meetings" value={`${progress.meetingsAttended || 0}/${progress.totalMeetingsScheduled
76 |     <StatCard title="Certificates" value={data?.certificates || 0} subtitle="Earned" icon="📜" />
77 |     <StatCard title="Notifications" value={data?.unreadNotifications || 0} subtitle="Unread" icon="🔔" />
78 | </div>
79 |
80 | <div className="grid gap-6 lg:grid-cols-2">
81 |     /* Enrolled trainings */
82 |     <div className="glass-card p-6">
83 |         <div className="mb-4 flex items-center justify-between">
84 |             <h3 className="section-title">Your Trainings</h3>
85 |             <Link to="/student/trainings" className="text-sm text-katalyst-500 hover:underline">View all !</Li
86 |         </div>
87 |         <div className="space-y-3">
88 |             {(data?.enrolledTrainings || []).length === 0 ? (
89 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No trainings enrolled yet.</p>
90 |             ) : (
91 |                 data.enrolledTrainings.map((t) => (
92 |                     <div key={t._id} className="flex items-center justify-between rounded-xl p-3"
93 |                         style={{ background: "var(--accent-light)" }}>
94 |                         <div>
95 |                             <p className="font-medium">{t.title}</p>
96 |                             <p className="text-xs" style={{ color: "var(--text-muted)" }}>{t.category}</p>
97 |                         </div>
98 |                         <span className="font-bold text-katalyst-500">
99 |                             {t.isCompleted ? "Done" : `${t.completedVideos} videos`}
100 |                         </span>
101 |                     </div>
102 |                 ))
103 |             )}
104 |         </div>
105 |     </div>
106 |
107 |     /* Upcoming meetings */
108 |     <div className="glass-card p-6">
109 |         <div className="mb-4 flex items-center justify-between">
110 |             <h3 className="section-title">Upcoming Meetings</h3>
111 |             <Link to="/student/meetings" className="text-sm text-katalyst-500 hover:underline">View all !</Lin
112 |         </div>
113 |         <div className="space-y-3">
114 |             {(data?.upcomingMeetings || []).length === 0 ? (
115 |                 <p className="text-sm" style={{ color: "var(--text-muted)" }}>No upcoming meetings.</p>
116 |             ) : (
117 |                 data.upcomingMeetings.map((m) => (
118 |                     <div key={m._id} className="rounded-xl border p-3" style={{ borderColor: "var(--border)" }}>
119 |                         <p className="font-medium">{m.topic}</p>
120 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
121 |                             with {m.mentorId?.name} · {new Date(m.scheduledDate).toLocaleDateString()} {m.scheduledTim
122 |                         </p>
123 |                         {m.meetLink && (
124 |                             <a href={m.meetLink} target="_blank" rel="noreferrer">
```

```
125 |         className="mt-2 inline-block text-xs text-katalyst-500 hover:underline">
126 |             Join Google Meet !'
127 |     </a>
128 |   })
129 | </div>
130 |   ))
131 | })
132 | </div>
133 | </div>
134 | </div>
135 | { /* Progress breakdown chart */ }
136 | <div className="glass-card mt-6 p-6">
137 |   <h3 className="section-title mb-4">Progress Breakdown</h3>
138 |   <div className="grid gap-4 sm:grid-cols-2 lg:grid-cols-4">
139 |     {chartData.map((item, i) => (
140 |       <div key={item.name}>
141 |         <div className="mb-1 flex justify-between text-sm">
142 |           <span>{item.name}</span>
143 |           <span className="font-bold text-katalyst-500">{Math.round(item.value)}%</span>
144 |         </div>
145 |         <div className="progress-bar">
146 |           <div className="progress-bar-fill" style={{ width: `${item.value}%`, background: COLORS[i] }}>
147 |         </div>
148 |       </div>
149 |     ))}
150 |   </div>
151 | </div>
152 | </DashboardLayout>
153 | );
154 | }
155 | }                                     (8.9 KB)
156 |
1  | import { useEffect, useState } from "react";
2  | import DashboardLayout from "../../components/layout/DashboardLayout";
3  | import CalendarView from "../../components/CalendarView";
4  | import API from "../../api";
5  |
6  | export default function StudentMeetings() {
7  |   const [meetings, setMeetings] = useState([]);
8  |   const [mentors, setMentors] = useState([]);
9  |   const [loading, setLoading] = useState(true);
10 |   const [showBook, setShowBook] = useState(false);
11 |   const [form, setForm] = useState({ mentorId: "", topic: "", scheduledDate: "", scheduledTime: "", duration:
12 |   const [tab, setTab] = useState("calendar");
13 |
14 |   const fetchMeetings = () => {
15 |     API.get("/meetings/student")
16 |       .then((res) => setMeetings(res.data.meetings || []))
17 |       .catch(console.error)
18 |       .finally(() => setLoading(false));
19 |   };
20 |
21 |   const fetchMentors = () => {
22 |     API.get("/mentors")
23 |       .then((res) => setMentors(res.data.mentors || []))
24 |       .catch(console.error);
25 |   };
26 |
27 |   useEffect(() => {
28 |     fetchMeetings();
29 |     fetchMentors();
30 |   }, []);
31 |
32 |   const bookMeeting = async (e) => {
33 |     e.preventDefault();
34 |     try {
35 |       await API.post("/meetings", form);
36 |       setShowBook(false);
37 |       setForm({ mentorId: "", topic: "", scheduledDate: "", scheduledTime: "", duration: 30, agenda: "" });
38 |       alert("Meeting requested successfully!");
39 |       fetchMeetings();
40 |     } catch (err) {
41 |       alert(err.response?.data?.message || "Booking failed");
42 |     }
43 |   };
44 |
45 |   const cancelMeeting = async (id) => {
46 |     if (!confirm("Cancel this meeting?")) return;
```

```
47 |     await API.delete(`/meetings/${id}`);
48 |     fetchMeetings();
49 |   };
51 |   const submitFeedback = async (id) => {
52 |     const rating = prompt("Rate 1-5:");
53 |     const comment = prompt("Your feedback:");
54 |     if (!rating) return;
55 |     await API.post(`/meetings/${id}/feedback`, { rating: Number(rating), comment });
56 |     fetchMeetings();
57 |   };
59 |   const now = new Date();
60 |   const filtered = meetings.filter((m) => {
61 |     const date = new Date(m.scheduledDate);
62 |     if (tab === "upcoming") return date >= now && ![ "cancelled", "rejected", "completed" ].includes(m.status);
63 |     if (tab === "past") return date < now || [ "completed", "cancelled", "rejected" ].includes(m.status);
64 |     return true;
65 |   });
67 |   const statusColor = {
68 |     pending: "bg-yellow-100 text-yellow-700 dark:bg-yellow-900/30 dark:text-yellow-300",
69 |     accepted: "bg-green-100 text-green-700 dark:bg-green-900/30 dark:text-green-300",
70 |     rejected: "bg-red-100 text-red-700 dark:bg-red-900/30 dark:text-red-300",
71 |     completed: "bg-purple-100 text-purple-700 dark:bg-purple-900/30 dark:text-purple-300",
72 |     cancelled: "bg-gray-100 text-gray-600 dark:bg-gray-800 dark:text-gray-400",
73 |   };
75 |   return (
76 |     <DashboardLayout
77 |       title="Calendar & Meetings"
78 |       subtitle="Student Portal"
79 |       actions={
80 |         <button onClick={() => setShowBook(true)} className="btn-primary !py-2 text-sm">
81 |           + Book Meeting
82 |         </button>
83 |       }
84 |     >
85 |       <div className="mb-6 flex gap-2">
86 |         {[
87 |           { id: "calendar", label: "📅 Interactive Calendar" },
88 |           { id: "upcoming", label: "📅 Upcoming Meetings" },
89 |           { id: "past", label: "📅 Meeting History" },
90 |         ].map((t) => (
91 |           <button key={t.id} onClick={() => setTab(t.id)}
92 |             className={`rounded-full px-4 py-1.5 text-sm font-medium ${
93 |               tab === t.id ? "bg-katalyst-500 text-white" : "border"
94 |             }`}
95 |             style={tab !== t.id ? { borderColor: "var(--border)" } : {}}
96 |           >
97 |             {t.label}
98 |           </button>
99 |         ))}
100 |       </div>
102 |       {loading ? (
103 |         <div className="flex h-40 items-center justify-center">
104 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
105 |             </div>
106 |         ) : tab === "calendar" ? (
107 |           <div className="space-y-6">
108 |             <CalendarView events={meetings} userRole="student" />
109 |             { /* Quick List under Calendar */ }
110 |             <div className="glass-card p-6">
111 |               <h3 className="section-title mb-4">Scheduled Sessions</h3>
112 |               <div className="space-y-3">
113 |                 {meetings.length === 0 ? (
114 |                   <p className="text-sm" style={{ color: "var(--text-muted)" }}>No meetings scheduled yet.</p>
115 |                 ) : (
116 |                   meetings.map((m) => (
117 |                     <div key={m._id} className="flex flex-wrap items-center justify-between gap-3 rounded-xl bor
118 |                       <div>
119 |                         <p className="font-bold">{m.topic}</p>
120 |                         <p className="text-xs" style={{ color: "var(--text-muted)" }}>
121 |                           with {m.mentorId?.name || "Mentor"} · {new Date(m.scheduledDate).toLocaleDateString()}
122 |                         </p>
123 |                       </div>
124 |                     </div>
```

```
125 |         <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.  
126 |             {m.status}  
127 |         }`}>  
128 |     </span>  
129 | </div>  
130 | ))  
131 | )}  
132 | </div>  
133 | </div>  
134 | ) : filtered.length === 0 ? (  
135 |     <div className="glass-card p-12 text-center">  
136 |         <p className="text-4xl">0</p>  
137 |         <p className="mt-4 font-medium">No {tab} meetings</p>  
138 |         <button onClick={() => setShowBook(true)} className="btn-primary mt-4">Book your first meeting</butt  
139 |     </div>  
140 | ) : (  
141 |     <div className="space-y-4">  
142 |         {filtered.map((m) => (  
143 |             <div key={m._id} className="glass-card p-5">  
144 |                 <div className="flex flex-wrap items-start justify-between gap-3">  
145 |                     <div>  
146 |                         <h3 className="font-bold">{m.topic}</h3>  
147 |                         <p className="text-sm" style={{ color: "var(--text-secondary)" }}>  
148 |                             with {m.mentorId?.name || "Mentor"} · {new Date(m.scheduledDate).toLocaleDateString()} at  
149 |                         </p>  
150 |                         {m.agenda && <p className="mt-1 text-xs" style={{ color: "var(--text-muted)" }}>{m.agenda}</  
151 |                     </div>  
152 |                     <span className={`rounded-full px-3 py-1 text-xs font-semibold capitalize ${statusColor[m.stat  
153 |                         {m.status}  
154 |                     }`}>  
155 |                 </span>  
156 |                 <div className="mt-4 flex flex-wrap gap-2">  
157 |                     {m.meetLink && m.status === "accepted" && (  
158 |                         <a href={m.meetLink} target="_blank" rel="noreferrer" className="btn-primary !py-1.5 text-xs  
159 |                             Join Google Meet  
160 |                     </a>  
161 |                     )}  
162 |                     {m.status === "pending" && (  
163 |                         <button onClick={() => cancelMeeting(m._id)} className="btn-secondary !py-1.5 text-xs">Cance  
164 |                     )}  
165 |                     {m.status === "completed" && !m.studentFeedback?.rating && (  
166 |                         <button onClick={() => submitFeedback(m._id)} className="btn-secondary !py-1.5 text-xs">Give  
167 |                     )}  
168 |                 </div>  
169 |             </div>  
170 |         )})  
171 |     </div>  
172 | )}  
173 | {showBook && (  
174 |     <div className="fixed inset-0 z-50 flex items-center justify-center bg-black/40 p-4">  
175 |         <div className="glass-card w-full max-w-md p-6 animate-fade-in">  
176 |             <h3 className="text-xl font-bold">Book Mentor Meeting</h3>  
177 |             <form onSubmit={bookMeeting} className="mt-4 space-y-3">  
178 |                 {mentors.length > 0 && (  
179 |                     <select  
180 |                         className="input-field"  
181 |                         value={form.mentorId}  
182 |                         onChange={(e) => setForm({ ...form, mentorId: e.target.value })}  
183 |                     >  
184 |                         <option value="">Assigned / Default Mentor</option>  
185 |                         {mentors.map((m) => (  
186 |                             <option key={m._id} value={m._id}>{m.name} {m.expertise?.join(", ") || "Mentor"}</option>  
187 |                         )})  
188 |                     </select>  
189 |                 )}  
190 |                 <input className="input-field" placeholder="Topic (e.g. Code Review & Career Guidance)" value={f  
191 |                     onChange={(e) => setForm({ ...form, topic: e.target.value })} required />  
192 |                 <input type="date" className="input-field" value={form.scheduledDate}  
193 |                     onChange={(e) => setForm({ ...form, scheduledDate: e.target.value })} required />  
194 |                 <input type="time" className="input-field" value={form.scheduledTime}  
195 |                     onChange={(e) => setForm({ ...form, scheduledTime: e.target.value })} required />  
196 |                 <textarea className="input-field" placeholder="Agenda (optional)" rows={3} value={form.agenda}>  
197 |
```

```
198 |         onChange={(e) => setForm({ ...form, agenda: e.target.value })} />
199 |         <div className="flex gap-2">
200 |             <button type="button" onClick={() => setShowBook(false)} className="btn-secondary flex-1">Canc
201 |             <button type="submit" className="btn-primary flex-1">Book Meeting</button>
202 |         </div>
203 |     </form>
204 | </div>
205 | </div>
206 |     })
207 | </DashboardLayout>
208 | );
209 | }
210 | } (0.2 KB)
211 |
212 | import NotificationsPage from "../../components/NotificationsPage";
213 | export default function StudentNotifications() {
214 |     return <NotificationsPage userRole="student" />;
215 | } (4.6 KB)
216 |
217 | import { useEffect, useState } from "react";
218 | import DashboardLayout from "../../components/layout/DashboardLayout";
219 | import API from "../../api";
220 | export default function StudentProfile() {
221 |     const [profile, setProfile] = useState(null);
222 |     const [form, setForm] = useState({ name: "", phone: "", bio: "", skills: "" });
223 |     const [saving, setSaving] = useState(false);
224 |     const [resumeFile, setResumeFile] = useState(null);
225 |     useEffect(() => {
226 |         API.get("/students/profile")
227 |             .then((res) => {
228 |                 const s = res.data.student;
229 |                 setProfile(s);
230 |                 setForm({ name: s.name, phone: s.phone || "", bio: s.bio || "", skills: (s.skills || []).join(", ") })
231 |             })
232 |             .catch(console.error);
233 |     }, []);
234 |     const saveProfile = async (e) => {
235 |         e.preventDefault();
236 |         setSaving(true);
237 |         try {
238 |             const res = await API.put("/students/profile", {
239 |                 ...form,
240 |                 skills: form.skills.split(",").map((s) => s.trim()).filter(Boolean),
241 |             });
242 |             setProfile(res.data.student);
243 |             alert("Profile updated!");
244 |         } catch (err) {
245 |             alert(err.response?.data?.message || "Update failed");
246 |         } finally {
247 |             setSaving(false);
248 |         }
249 |     };
250 |     const uploadResume = async () => {
251 |         if (!resumeFile) return;
252 |         const fd = new FormData();
253 |         fd.append("resume", resumeFile);
254 |         try {
255 |             const res = await API.post("/students/resume", fd, { headers: { "Content-Type": "multipart/form-data" } });
256 |             setProfile({ ...profile, resumeUrl: res.data.resumeUrl });
257 |             alert("Resume uploaded!");
258 |         } catch (err) {
259 |             alert(err.response?.data?.message || "Upload failed");
260 |         }
261 |     };
262 |     return (
263 |         <DashboardLayout title="Profile" subtitle="Student Portal">
264 |             <div className="grid gap-6 lg:grid-cols-2">
265 |                 <div className="glass-card p-6">
266 |                     <h3 className="section-title mb-4">Personal Information</h3>
267 |                     <form onSubmit={saveProfile} className="space-y-4">
268 |                         {[ "name", "phone" ].map((f) => (
269 |                             <div key={f}>
270 |                                 <label className="mb-1 block text-sm font-medium capitalize">{f}</label>
```

```
60 |         <input className="input-field" value={form[f]}
61 |           onChange={(e) => setForm({ ...form, [f]: e.target.value })} />
62 |       </div>
63 |     )))
64 |     <div>
65 |       <label className="mb-1 block text-sm font-medium">Bio</label>
66 |       <textarea className="input-field" rows={3} value={form.bio}
67 |         onChange={(e) => setForm({ ...form, bio: e.target.value })} />
68 |     </div>
69 |     <div>
70 |       <label className="mb-1 block text-sm font-medium">Skills (comma separated)</label>
71 |       <input className="input-field" value={form.skills}
72 |         onChange={(e) => setForm({ ...form, skills: e.target.value })} />
73 |     </div>
74 |     <button type="submit" disabled={saving} className="btn-primary">
75 |       {saving ? "Saving..." : "Save Changes"}
76 |     </button>
77 |   </form>
78 | </div>
79 |
80 |   <div className="space-y-6">
81 |     <div className="glass-card p-6">
82 |       <h3 className="section-title mb-4">ðŸ“œ Resume</h3>
83 |       {profile?.resumeUrl ? (
84 |         <a href={` ${import.meta.env.VITE_API_URL?.replace("/api", "")} || "http://localhost:5000" }${profile?.resumeUrl}`
85 |           className="text-katalyst-500 hover:underline text-sm">
86 |           View current resume !
87 |         </a>
88 |       ) : (
89 |         <p className="text-sm" style={{ color: "var(--text-muted)" }}>No resume uploaded yet.</p>
90 |       )}
91 |     <div className="mt-4">
92 |       <input type="file" accept=".pdf,.doc,.docx" onChange={(e) => setResumeFile(e.target.files[0])}
93 |         className="text-sm" />
94 |       <button onClick={uploadResume} disabled={!resumeFile} className="btn-primary mt-3 !py-2 text-sm">
95 |         Upload Resume
96 |       </button>
97 |     </div>
98 |   </div>
99 |
100 |   {profile?.assignedMentor && (
101 |     <div className="glass-card p-6">
102 |       <h3 className="section-title mb-4">ðŸ“œ ðŸ‘œ Assigned Mentor</h3>
103 |       <p className="font-bold">{profile.assignedMentor.name}</p>
104 |       <p className="text-sm" style={{ color: "var(--text-secondary)" }}>
105 |         {profile.assignedMentor.designation} . {profile.assignedMentor.company}
106 |       </p>
107 |       <p className="mt-2 text-xs" style={{ color: "var(--text-muted)" }}>
108 |         {profile.assignedMentor.expertise?.join(", ")}
109 |       </p>
110 |     </div>
111 |   )}
112 | </div>
113 | </div>
114 | </DashboardLayout>
115 | );
116 | } <!-- KATALYST FRONTEND TRAINING DETAIL PAGE --> (7.0 KB)
117 |
1 | import { useEffect, useState } from "react";
2 | import { useParams } from "react-router-dom";
3 | import DashboardLayout from "../../components/layout/DashboardLayout";
4 | import API from "../../api";
5 |
6 | export default function TrainingDetail() {
7 |   const { id } = useParams();
8 |   const [training, setTraining] = useState(null);
9 |   const [loading, setLoading] = useState(true);
10 |   const [quizAnswers, setQuizAnswers] = useState({});
11 |   const [quizResult, setQuizResult] = useState(null);
12 |   const [userEnrollment, setUserEnrollment] = useState(null);
13 |
14 |   const fetchTrainingDetails = () => {
15 |     API.get(`/trainings/${id}`)
16 |       .then((res) => {
17 |         setTraining(res.data.training);
18 |         setUserEnrollment(res.data.userEnrollment);
19 |       })
20 |   }
```

```
20 |     })
21 |     .catch(console.error)
22 |     .finally(() => setLoading(false));
23 |   };
24 |
25 |   useEffect(() => {
26 |     fetchTrainingDetails();
27 |   }, [id]);
28 |
29 |   const completeVideo = async (videoIndex) => {
30 |     try {
31 |       const res = await API.post(`/trainings/${id}/complete-video`, { videoIndex });
32 |       alert(res.data.message || "Video marked complete!");
33 |       fetchTrainingDetails();
34 |     } catch (err) {
35 |       alert(err.response?.data?.message || "Failed to mark video as completed");
36 |     }
37 |   };
38 |
39 |   const submitQuiz = async () => {
40 |     const formattedAnswers = Object.entries(quizAnswers).map(([qIdx, optIdx]) => ({
41 |       questionIndex: Number(qIdx),
42 |       selectedOption: Number(optIdx),
43 |     }));
44 |     try {
45 |       const res = await API.post(`/trainings/${id}/submit-quiz`, { answers: formattedAnswers });
46 |       setQuizResult(res.data);
47 |       alert(`Quiz Submitted! Score: ${res.data.score}/${res.data.maxScore}`);
48 |       fetchTrainingDetails();
49 |     } catch (err) {
50 |       alert(err.response?.data?.message || "Quiz submission failed");
51 |     }
52 |   };
53 |
54 |   if (loading) {
55 |     return (
56 |       <DashboardLayout title="Training" subtitle="Student Portal">
57 |         <div className="flex h-40 items-center justify-center">
58 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
59 |             </div>
60 |         </div>
61 |       </DashboardLayout>
62 |     );
63 |   }
64 |
65 |   if (!training) {
66 |     return (
67 |       <DashboardLayout title="Not Found" subtitle="Student Portal">
68 |         <p>Training not found.</p>
69 |       </DashboardLayout>
70 |     );
71 |   }
72 |
73 |   const completedVideos = userEnrollment?.completedVideos || [];
74 |
75 |   return (
76 |     <DashboardLayout title={training.title} subtitle={training.category}>
77 |       <div className="grid gap-6 lg:grid-cols-3">
78 |         <div className="lg:col-span-2 space-y-6">
79 |           <div>
80 |             <div className="glass-card p-6">
81 |               <div className="flex items-center justify-between mb-4">
82 |                 <h3 className="section-title">00 Video Lessons</h3>
83 |                 <span className="text-xs font-semibold text-katalyst-500">
84 |                   {completedVideos.length} / {training.videos?.length || 0} Completed
85 |                 </span>
86 |               </div>
87 |               <div className="space-y-3">
88 |                 {(training.videos || []).map((v, i) => {
89 |                   const isCompleted = completedVideos.includes(i);
90 |                   return (
91 |                     <div key={i} className="flex items-center justify-between rounded-xl border p-4"
92 |                       style={{ borderColor: "var(--border)", backgroundColor: isCompleted ? "rgba(16, 185, 129, 0.1)" : "var(--background)" }}
93 |                     >
94 |                       <p className="font-medium flex items-center gap-2">
95 |                         {isCompleted && <span className="text-green-500">'</span>}
96 |                         {v.title}
97 |                       </p>
98 |                       <p className="text-xs" style={{ color: "var(--text-muted)" }}>{v.duration}</p>
```

```
99 |         </div>
100 |         <div className="flex gap-2">
101 |             {v.url && (
102 |                 <a href={v.url} target="_blank" rel="noreferrer" className="btn-secondary !py-1.5 text
103 |                     Watch Video
104 |                 </a>
105 |             )}
106 |             <button
107 |                 onClick={() => completeVideo(i)}
108 |                 disabled={isCompleted}
109 |                 className={`!py-1.5 text-xs ${isCompleted ? "btn-secondary opacity-60 cursor-not-allow
110 |                 }
111 |                 {isCompleted ? "Completed" : "Mark Done"}
112 |             </button>
113 |         </div>
114 |     </div>
115 |     );
116 |     }}}
117 | </div>
118 | </div>
119 |
120 | /* Quiz */
121 | {(training.quizzes || []).length > 0 && (
122 |     <div className="glass-card p-6">
123 |         <h3 className="section-title mb-4">ðŸ”Œ Quiz</h3>
124 |         {training.quizzes.map((q, qi) => (
125 |             <div key={qi} className="mb-4">
126 |                 <p className="font-medium">{q.question}</p>
127 |                 <div className="mt-2 space-y-2">
128 |                     {q.options.map((opt, oi) => (
129 |                         <label key={oi} className="flex items-center gap-2 rounded-lg border p-3 cursor-pointer
130 |                             style={{ borderColor: "var(--border)" }}>
131 |                             <input type="radio" name={`q${qi}`}
132 |                                 onChange={() => setQuizAnswers({ ...quizAnswers, [qi]: oi })} />
133 |                             {opt}
134 |                         </label>
135 |                     ))}
136 |                 </div>
137 |             </div>
138 |         ))}
139 |         <button onClick={submitQuiz} className="btn-primary">Submit Quiz</button>
140 |         {quizResult && (
141 |             <p className="mt-3 text-sm font-semibold text-katalyst-500">
142 |                 Result: {quizResult.score}/{quizResult.maxScore} ({quizResult.percentage}%)
143 |             </p>
144 |         )}
145 |     </div>
146 | )}
147 | </div>
148 |
149 | /* Sidebar info */
150 | <div className="space-y-4">
151 |     <div className="glass-card p-6">
152 |         <h3 className="font-bold">Course Info</h3>
153 |         <div className="mt-4 space-y-2 text-sm" style={{ color: "var(--text-secondary)" }}>
154 |             <p>ðŸ”Œ Level: {training.level}</p>
155 |             <p>ðŸ”Œ Duration: {training.duration}</p>
156 |             <p>ðŸ”Œ ðŸ”Œ Instructor: {training.instructor}</p>
157 |             <p>ðŸ”Œ Videos: {training.videos?.length || 0}</p>
158 |             <p>ðŸ”Œ Assignments: {training.assignments?.length || 0}</p>
159 |         </div>
160 |     </div>
161 |
162 |     {(training.assignments || []).length > 0 && (
163 |         <div className="glass-card p-6">
164 |             <h3 className="font-bold mb-3">ðŸ”Œ Assignments</h3>
165 |             {training.assignments.map((a, i) => (
166 |                 <div key={i} className="mb-3 rounded-lg p-3" style={{ background: "var(--accent-light)" }}>
167 |                     <p className="font-medium text-sm">{a.title}</p>
168 |                     <p className="text-xs mt-1" style={{ color: "var(--text-muted)" }}>{a.description}</p>
169 |                     <p className="text-xs mt-1 text-katalyst-500">Due: {new Date(a.dueDate).toLocaleDateString()}
170 |                 </div>
171 |             ))}
172 |         </div>
173 |     )}
```



```
174 |     </div>
175 |   </div>
176 | </DashboardLayout>
177 | );
178 | } <!-- frontend/src/pages/student/trainings (3.1 KB) -->
179 |
1 | import { useEffect, useState } from "react";
2 | import { Link } from "react-router-dom";
3 | import DashboardLayout from "../../components/layout/DashboardLayout";
4 | import API from "../../api";
5 |
6 | export default function StudentTrainings() {
7 |   const [trainings, setTrainings] = useState([]);
8 |   const [loading, setLoading] = useState(true);
9 |   const [filter, setFilter] = useState("all");
10 |
11 |   useEffect(() => {
12 |     API.get("/trainings")
13 |       .then((res) => setTrainings(res.data.trainings || []))
14 |       .catch(console.error)
15 |       .finally(() => setLoading(false));
16 |   }, []);
17 |
18 |   const categories = ["all", ...new Set(trainings.map((t) => t.category))];
19 |   const filtered = filter === "all" ? trainings : trainings.filter((t) => t.category === filter);
20 |   const enroll = async (id) => {
21 |     try {
22 |       await API.post(`/trainings/${id}/enroll`);
23 |       alert("Enrolled successfully!");
24 |     } catch (err) {
25 |       alert(err.response?.data?.message || "Enrollment failed");
26 |     }
27 |   };
28 |
29 |   return (
30 |     <DashboardLayout title="Trainings" subtitle="Student Portal">
31 |       <div className="mb-6 flex flex-wrap gap-2">
32 |         {categories.map((cat) => (
33 |           <button key={cat} onClick={() => setFilter(cat)}
34 |             className={`rounded-full px-4 py-1.5 text-sm font-medium capitalize transition-all ${
35 |               filter === cat ? "bg-katalyst-500 text-white" : "border"
36 |             }`}
37 |             style={filter !== cat ? { borderColor: "var(--border)" } : {}}
38 |           >
39 |             {cat}
40 |           </button>
41 |         ))}
42 |       </div>
43 |       {loading ? (
44 |         <div className="flex h-40 items-center justify-center">
45 |           <div className="h-8 w-8 animate-spin rounded-full border-4 border-katalyst-200 border-t-katalyst-500">
46 |           </div>
47 |         </div>
48 |       ) : (
49 |         <div className="grid gap-6 sm:grid-cols-2 xl:grid-cols-3">
50 |           {filtered.map((t) => (
51 |             <div key={t._id} className="glass-card overflow-hidden transition-transform hover:-translate-y-1">
52 |               {t.thumbnail} && (
53 |                 <img src={t.thumbnail} alt={t.title} className="h-40 w-full object-cover" />
54 |               )
55 |               <div className="p-5">
56 |                 <span className="badge">{t.category}</span>
57 |                 <h3 className="mt-3 text-lg font-bold">{t.title}</h3>
58 |                 <p className="mt-2 line-clamp-2 text-sm" style={{ color: "var(--text-secondary)" }}>
59 |                   {t.description}
60 |                 </p>
61 |                 <div className="mt-3 flex gap-3 text-xs" style={{ color: "var(--text-muted)" }}>
62 |                   <span>📊 {t.level}</span>
63 |                   <span>⏱ {t.duration}</span>
64 |                   <span>👥 {t.enrolledStudents?.length || 0}</span>
65 |                 </div>
66 |                 <div className="mt-4 flex gap-2">
67 |                   <Link to={`/student/trainings/${t._id}`} className="btn-primary flex-1 !py-2 text-sm text-ce
68 |                     View Details
69 |                   </Link>
70 |                   <button onClick={() => enroll(t._id)} className="btn-secondary !py-2 text-sm">
71 |                     Enroll
72 |                   </button>

```

KATALYST.

Source Code: frontend/src/pages/student/Trainings.jsx (Cont.)

Generated: 22/8/2026 | Frontend

```
73 |         </button>
74 |     </div>
75 | </div>
76 | </div>
77 |     )})
78 | </div>
79 | })
80 | </DashboardLayout>
81 | );
82 | } // frontend/src/pages/student/Trainings.jsx (0.8 KB)
83 |
1 | /** @type {import('tailwindcss').Config} */
2 | export default {
3 |   content: ["../index.html", "./src/**/*.{js,ts,jsx,tsx}"],
4 |   darkMode: "class",
5 |   theme: {
6 |     extend: {
7 |       colors: {
8 |         catalyst: {
9 |           50: "#eff6ff",
10 |           100: "#dbeafe",
11 |           200: "#b2dfdb",
12 |           300: "#93c5fd",
13 |           400: "#60a5fa",
14 |           500: "#3b82f6",
15 |           600: "#2563eb",
16 |           700: "#1d4ed8",
17 |           800: "#1e40af",
18 |           900: "#1e3a8a",
19 |           950: "#172554",
20 |         },
21 |       },
22 |       fontFamily: {
23 |         sans: ["Inter", "system-ui", "sans-serif"],
24 |       },
25 |       boxShadow: {
26 |         glass: "0 8px 32px rgba(37, 99, 235, 0.08)",
27 |         "glass-lg": "0 16px 48px rgba(37, 99, 235, 0.14)",
28 |       },
29 |       backdropBlur: {
30 |         glass: "16px",
31 |       },
32 |     },
33 |   },
34 |   plugins: [],
35 | }; // frontend/src/pages/student/Trainings.jsx (0.2 KB)
36 |
1 | import { defineConfig } from 'vite'
2 | import react from '@vitejs/plugin-react'
3 |
4 | // https://vite.dev/config/
5 | export default defineConfig({
6 |   plugins: [react()],
7 | }) // frontend/vite.config.js (2.6 KB)
8 |
1 | # Katalyst – Student-Mentor Learning Platform
2 |
3 | Katalyst is a multi-role learning platform built with React, Tailwind CSS, Node.js, Express, and MongoDB Atlas
4 |
5 | ## Key Features
6 |
7 | - Role-based application for Students, Mentors, and Admins
8 | - JWT authentication with secure role-based access control
9 | - Training module with videos, quizzes, assignments, progress tracking, certificates
10 | - Meeting module with scheduling, Google Meet links, mentor responses, feedback, and notes
11 | - Progress analytics with placement readiness and career roadmap support
12 | - Notifications, resume upload, certificate downloads, email notifications
13 | - Docker support for backend, frontend, and MongoDB
14 |
15 | ## Folder Structure
16 |
17 | - `backend/` – Express API, models, controllers, middleware, uploads, Docker config
18 | - `frontend/` – React application, Tailwind CSS, pages, components
19 |
20 | ## Setup
21 |
22 | ### Backend
23 |
24 | 1. Copy `.env.example` to `.env` in `backend/`
25 | 2. Fill values for `MONGO_URI`, `JWT_SECRET`, `EMAIL_USER`, and `EMAIL_PASS`
```

```
26 | 3. Install dependencies:
27 |     ````bash
28 |     cd backend
29 |     npm install
30 |     ````
31 | 4. Start development server:
32 |     ````bash
33 |     npm run dev
34 |     ````
35 |
36 | ### Frontend
37 |
38 | 1. Copy `.env.example` to `.env` in `frontend/`
39 | 2. Install dependencies:
40 |     ````bash
41 |     cd frontend
42 |     npm install
43 |     ````
44 | 3. Start development server:
45 |     ````bash
46 |     npm run dev
47 |     ````
48 |
49 | ## Docker
50 |
51 | Run the app using Docker Compose:
52 |     ````bash
53 |     docker-compose up --build
54 |     ````
55 |
56 |
57 | ## Seed Data
58 |
59 | To create starter data for the backend:
60 |     ````bash
61 |     cd backend
62 |     npm run seed
63 |     ````
64 |
65 |
66 | ## Environment Variables
67 |
68 | Backend `.env` variables:
69 | - `MONGO_URI`
70 | - `JWT_SECRET`
71 | - `JWT_EXPIRES_IN`
72 | - `CLIENT_URL`
73 | - `EMAIL_USER`
74 | - `EMAIL_PASS`
75 | - `NODE_ENV`
76 | - `PORT`
77 |
78 | Frontend `.env` variables:
79 | - `VITE_API_URL`
80 |
81 |
82 | ## APIs
83 |
84 | - `POST /api/auth/register` – Student registration
85 | - `POST /api/auth/login` – Login for student, mentor, admin
86 | - `GET /api/students/*` – Student dashboard and profile routes
87 | - `GET /api/mentors/*` – Mentor dashboard and meeting routes
88 | - `GET /api/admin/*` – Admin analytics, user management, reports
89 | - `GET /api/trainings/*` – Training discovery and enrollment
90 | - `GET /api/meetings/*` – Meeting scheduling and status
91 | - `GET /api/notifications/*` – Notification management
92 | - `GET /api/progress/*` – Progress analytics and readiness
93 | - `POST /api/ai/*` – AI-assisted resume analysis and roadmap suggestions
94 |
95 | ## Notes
96 |
97 | The platform is designed for production readiness with secure middleware, rate limiting, and role-based access
98 |
99 |
```


