Experiment - 8

Student Name: Diksha **UID:** 23BCS10994
Branch: BE-CSE **Section/Group:** KRG-2B
Semester: 5th **Date of Performance:** 13/10/25
Subject Name: Design and Analysis of Algorithms
Subject Code: 23CSH-301

1. **Aim:** Develop a program and analyze complexity to find shortest paths in a graph with positive edgeweights using Dijkstra‟s algorithm.

2. **Objective:** Code and analyze to find shortest paths in a graph with positive edge weights using Dijkstra‟s
3. **Input/Apparatus Used:** Graph (G =(V,E)) is taken as input for this problem.

4. **Procedure:**

Follow the steps below to solve the problem:

- Create a set sptSet (shortest path tree set) that keeps track of vertices included in the shortest- path tree, i.e., whose minimum distance from the source is calculated and finalized. Initially, this set is empty.
- Assign a distance value to all vertices in the input graph. Initialize all distance values as INFINITE. Assign the distance value as 0 for the source vertex so that it is picked first.
- While sptSet doesn‟t include all vertices
- Pick a vertex u which is not there in sptSet and has a minimum distance value.
- Include u to sptSet.
- Then update distance value of all adjacent vertices of u.
- To update the distance values, iterate through all adjacent vertices.

- For every adjacent vertex v, if the sum of the distance value of u (fromsource) and weight of edge u-v, is less than the distance value of v, then update the distance value of v.

5. **Algorithm**

- **Step 1:** SET STATUS = 1 (ready state) for each node in G
- **Step 2:** Push the starting node A on the stack and set its STATUS = 2 (waiting state)
- **Step 3:** Repeat Steps 4 and 5 until STACK is empty
- **Step 4:** Pop the top node N. Process it and set its STATUS = 3 (processed state)
- **Step 5:** Push on the stack all the neighbours of N that are in the ready state (whose STATUS = 1) and set their STATUS = 2 (waiting state)

[END OF LOOP]
Step 6: EXIT

6. **Code and Output:**

```
#include <bits/stdc++.h>

using namespace std;

#define INF INT_MAX


int minDistance(vector<int>& dist, vector<bool>& sptSet, int
V) { int minVal = INF, minIndex = -1; for (int v = 0; v < V;
v++) { if (!sptSet[v] && dist[v] <= minVal) { minVal =
dist[v]; minIndex = v;
}
```

```
    } return
minIndex; }

    void printSolution(vector<int>& dist, int
        V) { cout << "\nVertex\tDistance from
        Source\n"; for (int i = 0; i < V; i++) cout
        << i << "\t\t" << dist[i] << "\n";
}

    void dijkstra(vector<vector<int>>& graph, int src, int
        V) { vector<int> dist(V, INF); vector<bool>
        sptSet(V, false);

    dist[src] = 0;

        for (int count = 0; count < V - 1; count++)
            { int u = minDistance(dist, sptSet, V);
            sptSet[u] = true;

            for (int v = 0; v < V; v++) { if (!sptSet[v] &&
                graph[u][v] && dist[u] != INF && dist[u] +
```

```
            graph[u][v] < dist[v]) { dist[v] = dist[u] +
            graph[u][v];
        }
    }
  }

  printSolution(dist, V);
}

int main() {
  cout << "DIJKSTRA'S ALGORITHM - SHORTEST PATH FINDER\n\n";
  int V; cout << "Enter number of
  vertices: "; cin >> V;

  vector<vector<int>> graph(V, vector<int>(V, 0)); cout
  << "\nEnter the adjacency matrix (0 for no edge):\n"; for
  (int i = 0; i < V; i++) { for (int j = 0; j < V; j++) cin >>
  graph[i][j];
  }
  int src;
  cout << "\nEnter source vertex (0 to " << V - 1 << "): ";
  cin >> src;
```

```
    dijkstra(graph, src, V);

    return 0;

}
```

Output

```
DIJKSTRA'S ALGORITHM - SHORTEST PATH FINDER

Enter number of vertices: 5

Enter the adjacency matrix (0 for no edge):
0 10 0 5 0
0 0 1 2 0
0 0 0 0 4
0 3 9 0 2
7 0 6 0 0

Enter source vertex (0 to 4): 0

Vertex  Distance from Source
0       0
1       8
2       9
3       5
4       7
```