



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Experiment - 9

**Student Name:** Diksha

**UID:** 23BCS10994

**Branch:** BE-CSE

**Section/Group:** KRG-2B

**Semester:** 5<sup>th</sup>

**Date of Performance:** 21/10/25

**Subject Name:** Project Based Learning in Java

**Subject Code:** 23CSH-304

### **Aim:**

Perform CRUD (Create, Read, Update, Delete) operations on a Student entity using Hibernate ORM with MySQL.

### **Objective:**

To learn Hibernate configuration, entity mapping, and CRUD execution with MySQL.

### **Apparatus / Tools Used:**

Java, Hibernate, MySQL, Eclipse / IntelliJ, hibernate.cfg.xml

### **Requirements:**

- Create Student entity (id, name, age)
- Configure Hibernate using hibernate.cfg.xml
- Implement SessionFactory
- Perform Insert, Read, Update, Delete

### **Procedure:**

1. Configure MySQL database and add Hibernate dependencies.
2. Create hibernate.cfg.xml with DB credentials.
3. Create Student.java with @Entity, @Id, @GeneratedValue annotations.
4. Create HibernateUtil class for SessionFactory.
5. Implement CRUD using session.save(), session.get(), session.update(),



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

session.delete().

6. Test using a main class.

### Code: (Student.java)

```
@Entity public class Student  
{ @Id  
    @GeneratedValue(strategy = GenerationType.IDENTITY) private int  
    id; private String name; private int age;  
  
    //getters, setters, constructors  
}
```

### Code: (Main CRUD Test)

```
Session session = HibernateUtil.getSessionFactory().openSession();  
Transaction tx = session.beginTransaction();  
  
Student s = new Student(); s.setName("John");  
s.setAge(22); session.save(s);  
  
Student st = session.get(Student.class,1); st.setAge(23); session.update(st);  
  
session.delete(st); tx.commit();  
session.close();
```

### Sample Output:

Insert Success!

Fetch: ID=1, Name=John, Age=22 Update Success:  
Age changed to 23 Delete Success!