

WEEK 3

Task1

Develop a C program using fork() that creates a parent and child process. Display the Process ID (PID), Parent Process ID (PPID), and process states at different stages of execution

Source Code:

```
#include <stdio.h>

#include <unistd.h>

#include <sys/types.h>

#include <sys/wait.h>

#include <stdlib.h>

int main() {
    pid_t pid;
    printf("Parent Process Started\n");
    printf("Parent PID : %d\n", getpid());
    printf("Parent PPID : %d\n", getppid());
    pid=fork();

    if (pid<0) {
        printf("Fork failed\n");
        return 1;
    }
    else if (pid==0) {
        printf("Child Process\n ");
        printf("Child PID : %d\n", getpid());
        printf("Child PPID : %d\n", getppid());
        printf("Child State: Running\n");
        sleep(5);
    }
}
```

```

        printf("Child State: Terminating\n");
        exit(0);
    }
    else {
        printf("Parent Process\n ");
        printf("Parent PID : %d\n", getpid());
        printf("Child PID : %d\n", pid);
        printf("Parent State: Running\n");
        sleep(2);
        printf("Parent State: Waiting for child\n");
        wait(NULL);

        printf("Parent State: Child Terminated\n");
    }
    return 0;
}

```

Output:

```

Parent Process Started
Parent PID : 569
Parent PPID : 338
Parent Process
  Parent PID : 569
Child PID : 570
Child Process
Parent State: Running
  Child PID : 570
Child PPID : 569
Child State: Running
Parent State: Waiting for child

```


Task2

Design an experiment to observe process state transitions (Ready, Running, Waiting, Terminated) using Linux monitoring tools such as ps, top, and /proc. Document the observations.

Source Code:

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
int main() {
    pid_t pid = fork();
    if (pid == 0) {
        printf("Child process started. PID = %d\n", getpid());
        sleep(10);
        printf("Child process terminated.\n");
    }
    else {
        printf("Parent process started. PID = %d\n", getpid());
        printf("Child PID = %d\n", pid);
        wait(NULL);
        printf("Parent: Child terminated.\n");
    }
    return 0;
}
```

Output:



```
Parent process started. PID = 1036
Child process Started. PID= 1037
Child PID = 1037
Child process terminated.
Parent: Child terminated.
```

1. ps: displays the processes that are currently running in the system.

```
root@DESKTOP-VMN932K:~# ps
  PID TTY          TIME CMD
  338 pts/0        00:00:00 bash
 1061 pts/0        00:00:00 ps
```

2. top: It is used to monitor processes. It displayed the PID, user, cpu details, memory usage, and process state.

```
root@DESKTOP-VMN932K:~# top
top - 03:36:31 up 35 min, 1 user, load average: 0.04, 0.01, 0.00
Tasks: 25 total, 1 running, 24 sleeping, 0 stopped, 0 zombie
%Cpu(s): 0.0 us, 0.2 sy, 0.0 ni, 99.8 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
MiB Mem : 7880.6 total, 7420.4 free, 453.6 used, 156.1 buff/cache
MiB Swap: 2048.0 total, 2048.0 free, 0.0 used. 7427.0 avail Mem
```

PID	USER	PR	NI	VIRT	RES	SHR	S	%CPU	%MEM	TIME+	COMMAND
1	root	20	0	21844	13148	9796	S	0.0	0.2	0:01.11	systemd
2	root	20	0	3180	2204	2072	S	0.0	0.0	0:00.00	init-systemd(Ub
9	root	20	0	3196	2124	2008	S	0.0	0.0	0:00.00	init
58	root	19	-1	34056	12672	11600	S	0.0	0.2	0:00.41	systemd-journal
108	root	20	0	25284	6632	5172	S	0.0	0.1	0:00.36	systemd-udev
114	systemd+	20	0	21344	13180	11056	S	0.0	0.2	0:00.15	systemd-resolve
115	systemd+	20	0	91036	7968	6996	S	0.0	0.1	0:00.16	systemd-timesyn
159	root	20	0	4244	2684	2432	S	0.0	0.0	0:00.01	cron

3. /proc: It is a directory

```
root@DESKTOP-VMN932K:~# /proc
-bash: /proc: Is a directory
```