

DİLER DEMİR ÇELİK A.Ş DIŞ PİYASA SİPARİŞ BİLDİRİM FORMU

| Sipariş Tar | | 20/02, | Sipariş No | | | 2018-7915 | | Revizyon No | | 1 | | | |
|-------------|------------|--|-----------------|------|----|------------------|-----------------|-----------------|--------------------------|---|--|---------------------|--------------|
| | Mamul | PRIME NEWLY PRODUCED HOT ROLLED STEEL DEBARS STRAIGHT LENGTH | | | | | | | | | | | |
| Lot No | Mamul Tipi | Mamul Standart | Mamul Kalite | Çap | ND | Boy (M) | Miktar (Ton) | Çubuk Sayısı | Birim Ağırlık (KG) | Paket Ağırlığı (KG) | Hadde Tol Min | Hadde Tol Max | Roto Tipi |
| 1 | Çubuk | ASTM A 615 | GR 40 | BN.3 | N | 20 FEET | 72 | | | | | | - |
| 1 | Çubuk | ASTM A 615 | GR 40 | BN.4 | N | 20 FEET | 472 | | | | | | - |
| 1 | Çubuk | ASTM A 615 | GR 60 | BN.4 | N | 20 FEET | 216 | | | | | | - |
| 1 | Çubuk | ASTM A 615 | GR 40 | BN.5 | Ν | 20 FEET | 48 | | | | | | - |
| 1 | Çubuk | ASTM A 615 | GR 60 | BN.5 | N | 20 FEET | 96 | | | | U | | - |
| 1 | Çubuk | ASTM A 615 | GR 60 | BN.6 | N | 20 FEET | 96 | | | | | | - |
| 2 | Çubuk | ASTM A 615 | GR 40 | BN.3 | N | 20 FEET | 50 | | | | | | - |
| 2 | Çubuk | ASTM A 615 | GR 60 | BN.3 | | 20 FEET 20 | 100 | | | | | | - |
| 2 | Çubuk | ASTM A 615 | GR 60 | BN.4 | 1 | FEET 40 | 100 | | | 011111111111111111111111111111111111111 | | | - |
| 2 | Çubuk | ASTM A 615 | GR 60 | BN.4 | N | FEET 20 | 50 | | | | | | - |
| | Çubuk | ASTM A 615 | GR 40 | BN.4 | | FEET 20 | 100 | | | VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII | U | | - |
| | Çubuk | ASTM A 615 | GR 60 | BN.5 | | FEET 20 | 100 | | | | | | - |
| | Çubuk | ASTM A 615 | GR 60 | BN.3 | | FEET 40 | 105 | | | , , , , , , , , , , , , , , , , , , , | | | - |
| | Çubuk | ASTM A 615 | GR 60 | BN.4 | | FEET 60 | 305 22 | | | | | | - |
| | Çubuk | ASTM A 615 | GR 60 | BN.4 | | FEET 60 | 22 | | | | UIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII | | _ |
| 3 | Çubuk | ASTM A 615 | GR 60 | BN.5 | N | FEET | 87 | | | <u></u> | <u> </u> | | - |



DİLER DEMİR ÇELİK A.Ş DIŞ PİYASA SİPARİŞ BİLDİRİM FORMU

| 3 Cubuk ASTM A 615 GR 60 BN 6 N FEET 133 | | | = | ·=····· | | · · · · · · · · · · · · · · · · · · · | | | | · | · | · | · | ¥ | |
|--|--|---|---------------|-------------|---------|---------------------------------------|----------|----------|----------|-----------------------|--------------|----------|---------|---|--|
| 3 Cubuk ASTM A 615 GR 60 BN.5 N FEET 133 | | | | | | | 20 | | | | | | | | |
| 3 Cubuk ASTM A 615 GR 60 BN.5 N FEET 109 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 87 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 87 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 87 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 87 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 6 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 6 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 7 Cop. Miktar 10 W (Min 5/45 GR 60 BN.6 N FEET 100 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Bas-Bit 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 | 2 (| Cubuk | ACTN4 A 61E | CD 60 | DN 6 | N | | 121 | | | | | | | |
| 3 Cubuk ASTM A 615 GR 60 BN.6 N FEET 109 | 3 (| - Lander | ASTIVI A 013 | | DIV.O | IN | FEEI | 131 | |] | |] |] | - | |
| 3 Cubuk ASTM A 615 GR 60 BN.5 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 200 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 200 5 CR 60 BN.5 N FEET 200 6 CR 60 BN.5 N FEET 200 6 CR 60 BN.5 N FEET 200 6 CR 60 BN.5 N FEET 200 6 CR 60 BN.5 N FEET 200 7 COPAM Miktar (MT) 3920 7 COPAM Miktar TOI % (Mn) 57-55 8 COPAM Miktar TOI % (Mn) 57 | | | | | | | 40 | | | | | | | | |
| 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 CORD BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 200 5 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 7 CORD BN.5 N FEET 100 8 CORD BN.5 N FEET 100 | 3 (| Çubuk | ASTM A 615 | GR 60 | BN.6 | N | | 109 | | | | | | - | |
| 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 65 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 CORD BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 200 5 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 6 CORD BN.5 N FEET 100 7 CORD BN.5 N FEET 100 8 CORD BN.5 N FEET 100 | | | | Ā | | | | | | ā | Ā | Ā | Ā | | |
| 3 Cubuk ASTM A 615 GR 60 BN.7 N FEET 87 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 6 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 7 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 8 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 9 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 9 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 10 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 BN.5 N FEET | | | | | | | | | | | | | | | |
| 3 Çubuk ASTM A 615 GR 60 BN.7 N FEET B7 3 Çubuk ASTM A 615 GR 60 BN.8 N FEET 22 3 Çubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Çubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 6 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 7 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 8 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 9 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 2 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 3 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 4 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 4 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 5 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 BN.6 N F | 3 (| Çubuk | ASTM A 615 | GR 60 | BN.6 | N | FEET | 65 | | | | | | - | |
| 3 Çubuk ASTM A 615 GR 60 BN.7 N FEET B7 3 Çubuk ASTM A 615 GR 60 BN.8 N FEET 22 3 Çubuk ASTM A 615 GR 60 BN.8 N FEET 22 4 Çubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.8 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 100 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 5 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 6 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 7 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 8 Qubuk ASTM A 615 GR 60 BN.5 N FEET 100 9 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 1 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 2 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 3 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 4 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 4 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 5 Qubuk ASTM A 615 GR 60 BN.6 N FEET 100 BN.6 N F | | | | | | | 40 | | | | | | | | |
| 3 Cubuk ASTM A 615 GR 60 BN.8 N FEET 22 | 3 (| Cubuk | ASTM A 615 | GR 60 | BN.7 | N | | 87 | | | | | | - | |
| 3 Çubuk | | 3 | | | | | | | | ā | | å | | | |
| 3 Cubuk | | | | | | | 60 | | | | | | | | |
| 3 Çubuk ASTM A 615 GR 60 BN.8 N FEET 22 | 3 (| Çubuk | ASTM A 615 | GR 60 | BN.7 | N | FEET | 65 | | | | ļ | <u></u> | - | |
| 3 Çubuk ASTM A 615 GR 60 BN.8 N FEET 22 | | | | | | | 40 | | | | | | | | |
| 3 Cubuk | 3 (| Cubuk | ASTM A 615 | GR 60 | BN.8 | N | | 22 | | | | | | _ | |
| A Cubuk | | 3 | | | | ļ. . | ·· | | | ł | | ļ | I | | |
| 4 Cubuk ASTM A 615 GR 60 BN.4 N FEET 400 | | | | | | | | | | | | | | | |
| 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 400 | 3 (| Çubuk | ASTM A 615 | GR 60 | BN.8 | N | FEET | 22 | | <u></u> | <u></u> | <u></u> | <u></u> | - | |
| 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 400 | | | | | | | 40 | | | | | | | | |
| 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 100 | 4 (| ^uhuk | ΔSTM Δ 615 | GR 60 | RN 4 | N | | 400 | | | | | | _ | |
| 4 Çubuk | | | | | DIV.4 | 1 N | | 400 | | | | | I | | |
| 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 | | | | | | | 20 | | | | | | | | |
| 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 | 4 (| Çubuk | ASTM A 615 | GR 40 | BN.5 | N | FEET | 100 | | | | | | - | |
| 4 Cubuk ASTM A 615 GR 60 BN.5 N FEET 400 | | | | | | | | | | | | | | | |
| 4 Çubuk ASTM A 615 GR 60 BN.5 N FEET 200 4 Çubuk ASTM A 615 GR 60 BN.6 N FEET 100 | 4 | Cubul | ACTN4 A C1F | CD CO | DNE | NI. | | 400 | | | | | | | |
| 4 Cubuk ASTM A 615 GR 60 BN.6 N FEET 200 | 4 (| - Lander | ASTIVI A 013 | | C.VID | IN | FEEI | 400 | | ā | | | | | |
| 4 Çubuk ASTM A 615 GR 60 BN.6 N FEET 100 ASTM A 615 GR 60 BN.6 N FEET 200 Toplam Miktar (MT) 3920 Top. Miktar Tol % (Min 5-5+5 Cap. Miktar Tol % (Min 5-5+5 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Termin Baş-Bit Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | | | | | 40 | | | | | | | | |
| A Cubuk ASTM A 615 GR 60 BN.6 N FEET 100 ASTM A 615 GR 60 BN.6 N FEET 200 TOPIAM MIKTAR (MT) 3920 TOPIAM MIKTAR TOI % (Min 5-/+5 Cap. Miktar TOI % (Min 5-/+5 BOY TOI (- / + MM) Termin Baş-Bit 20180220 - 20180220 Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | 4 (| Çubuk | ASTM A 615 | GR 60 | BN.5 | N | FEET | 200 | | | | | | - | |
| A Cubuk ASTM A 615 GR 60 BN.6 N FEET 100 ASTM A 615 GR 60 BN.6 N FEET 200 TOPIAM MIKTAR (MT) 3920 TOPIAM MIKTAR TOI % (Min 5-/+5 Cap. Miktar TOI % (Min 5-/+5 BOY TOI (- / + MM) Termin Baş-Bit 20180220 - 20180220 Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | | | | | | | | | | | | | |
| Toplam Miktar (MT) 3920 Top. Miktar Tol % (Min | , , | C. de de | ACTN4 A C4F | CD CO | DNIC | N.I | | 100 | | | | | | | |
| ASTM A 615 GR 60 BN.6 N FEET 200 | 4 (| -upuk | ASTIVI A 615 | IGK 6U | BN.6 | IN | FEEI | 100 | | | | |]] | - | |
| Toplam Miktar (MT) 3920 Top. Miktar Tol % (Min 5-5/+5 Gap. Miktar Tol % (Min 5-5/+5 Boy Tol (- / + MM) 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Ebat Tol (- / + MM) 50 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Termin Baş-Bit 20180220 - 20180220 Teorik 7 Faturalama 7 Feorik 8 PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | | | | | 40 | | | | | | | | |
| Top. Miktar Tol % (Min 5/+5 Cap. Miktar Tol % (Min -5/+5 Boy Tol (- / + MM) 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Ebat Tol (- / + MM) 20180220 - 20180220 Faturalama Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | 4 (| Çubuk | ASTM A 615 | GR 60 | BN.6 | N | FEET | 200 | | | | | | - | |
| Top. Miktar Tol % (Min 5/+5 Cap. Miktar Tol % (Min -5/+5 Boy Tol (- / + MM) 20 FEETM(-0 / + 50 MM), 60 FEETM(-0 / + 100 MM), 40 FEETM(-0 / + 100 MM) Ebat Tol (- / + MM) 20180220 - 20180220 Faturalama Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | | | | | | | | | | | | | |
| Cap. Miktar Tol % (Min 5-5/+5 Boy Tol (- / + MM) Ebat Tol (- / + MM) Termin Baş-Bit 20180220 - 20180220 Faturalama Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | - 5 mm m m m m m m m m m m m m m m m m m | | Ī | | | | | | | | | | | | |
| Boy Tol (- / + MM) Ebat Tol (- / + MM) Termin Baş-Bit Faturalama Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | 500000000000000000000000000000000000000 | | <u> </u> | | | | | | | | | | | | |
| Ebat Tol (- / + MM) Termin Baş-Bit 20180220 - 20180220 Faturalama Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | Çap. Mikta | Çap. Miktar Tol % (Min | | | | | | | | | | | | | |
| Ebat Tol (- / + MM) Termin Baş-Bit 20180220 - 20180220 Faturalama Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | Bov Tol (- | / + MM) | 20 FEETM(-0 | / + 50 MM), | 60 FEE | TM(| -0 / + 1 | 00 MM), | 40 FEET | M(-0 / + | 100 MM) | | | | |
| Termin Baş-Bit Teorik PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | 200000000000000000000000000000000000000 | | | | | | | | | | | | | | |
| Faturalama PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | 2 | | 20180220 - 20 | 180220 | | | | | | | | | | | |
| PACKING: IN BUNDLE-PACKING SUITABLE FOR OVERSEAS TRANSPORTATION. BUNDLE WEIGHT FOR LENGTH 20 AND 40 TO BE MAX 2.5MT. BUNDLE WEIGT FOR LENGTH 60 TO BE MAX 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | E | | <u> </u> | | | | | | | | | | | | |
| 3MT. UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | PACKING: IN | BUNDLE-PAC | KING S | SUITA | BLE FC | R OVERS | EAS TRAI | NSP <mark>ORTA</mark> | TION. | | | | |
| UNIFORM PIECE COUNTED BUNDLES SECURED FASTENED WITH AT LEAST 3 WIRE ROD AND/OR STEEL STRAPS (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | BUNDLE WEIG | | | | | | | | | | | | |
| (AT EACH END AND IN CENTER). EACH BUNDLE TO BE PRE-SLUNG WITH TWO (2) LIFTING LOOPS. | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| Paketleme | | | (AT EACH END | AND IN CEN | TER). E | ACH | RUNDI | LE TO BE | PRE-SLUN | ig WITH | TWO (2) LIFT | ING LOOI | PS. | | |
| Paket leme | | | | | | | | | | | | | | | |
| | Paketleme | 2 | | | | | | | | | | | | | |



DİLER DEMİR ÇELİK A.Ş DIŞ PİYASA SİPARİŞ BİLDİRİM FORMU

| | TO BE IN ENGLISH AND PER STANDARD ASTM A615 LATEST EDITION. EACH BUNDLE TO HAVE 2 DURABLE TAGS, ONE ON EACH END, WITH THE FOLLOWING INFORMATION: QUALITY, SIZE, LENGTH, HEAT NUMBER, PIECE/BUNDLE, THEORETICAL BUNDLE WEIGHT, MADE IN TURKEY, DISCHARGING PORT, PRODUCER. |
|-----------------------|---|
| | A DIFFERENT COLOUR FOR EACH LOT AND EACH GRADE. |
| Etiket | |
| Gözetim | -VITSAN |
| | ALL MATERIAL TO BE NATURALLY AIR COOLED. |
| | MATERIAL PRODUCED FROM TEMPCOR/THERMAX OR OTHER WATER QUENCHING NOT ACCEPTABLE. |
| | *****AKREDİTİF GEREGİ KONSİMENTOLARDA EBAT BAZINDA MİKTAR VE BAG ADETLERİ GÖSTERİLMESİ GEREKTİĞİNDEN YÜKLEME BİTİSİNDEN 2 GÜN ÖNCE EBAT BAZINDA TEORIK MIKTAR VE BAG SAYILARININ İHRACAT DEPARTMANINA GECİLMESİ GEREKMEKTEDİR. |
| Özel Şartlar | |
| Ülke | ABD |
| Ekli Dosya | |
| Boşaltma Limanı | Lot1:NEW ORLEANS,LA/USA, Lot2:HOUSTON,TX/USA, Lot3:HOUSTON,TX/USA, Lot4:HOUSTON,TX/USA |
| Boyama (Lot / Ebat) | |

Form No:

05.10.1 -

2/R-3