



# DİLER DEMİR ÇELİK A.Ş. DIŞ PIYASA SİPARİŞ BİLDİRİM FORMU

Sipariş Tar	04/07/2017	Sipariş No	2017-7584	Revizyon No	0								
Mamul	PRIME, NEWLY PRODUCED LOW CARBON STEEL WIRE RODS												
Lot No	Mamul Tipi	Mamul Standart	Mamul Kalite	Çap	ND	Boy (M)	Miktar (Ton)	Çubuk Sayısı	Birim Ağırlık (KG)	Paket Ağırlığı (KG)	Hadde Tol Min	Hadde Tol Max	Rotor Tipi
1	Kangal	ASTM A 510M	SAE 1008	5.5	D		600						-
1	Kangal	ASTM A 510M	SAE 1008	6.5	D		750						-
1	Kangal	ASTM A 510M	SAE 1008	7	D		150						-
2	Kangal	ASTM A 510M	SAE 1008	12	D		205						-
2	Kangal	ASTM A 510M	SAE 1008	15	D		205						-
2	Kangal	ASTM A 510M	SAE 1008	18	D		320						-
2	Kangal	ASTM A 510M	SAE 1008	9	D		770						-
3	Kangal	ASTM A 510M	SAE 1008	5.5	D		1500						-
4	Kangal	ASTM A 510M	SAE 1008	5.5	D		1000						-
4	Kangal	ASTM A 510M	SAE 1008	6.5	D		500						-
Toplam Miktar (MT)		6000											
Top. Miktar Tol % ( Min		-5/+5											
Çap. Miktar Tol % ( Min		-5/+5											
Boy Tol ( - / + MM )													
Ebat Tol ( - / + MM)													
Termin Baş-Bit		20170505 - 20170505											
Faturalama		Gerçek											
Paketleme		-COIL WEIGHTMAX 3.0 MT EACH COIL TO HAS 2 TAGS, INDICATING LOT NO MILLS NAME SIZE QUALITY GRADE MADE IN TURKEY COIL WEIGHT HEAT NO PORT OF DISCHARGE TATA INTERNATIONAL LTD											
Etiket													
Gözetim		-VITSAN											



# DİLER DEMİR ÇELİK A.Ş. DIŞ PIYASA SİPARİŞ BİLDİRİM FORMU

	<p>-QUALITY WITH FOLLOWING CHEMICAL COMPOSITION:</p> <p>C 0.10 PCT MAX</p> <p>SI 0.15 PCT MAX</p> <p>MN 0.50 PCT MAX</p> <p>P 0.030 PCT MAX</p> <p>S 0.030 PCT MAX</p> <p>CR 0.20 PCT MAX</p> <p>NI 0.20 PCT MAX</p> <p>CU 0.30 PCT MAX</p> <p>MECHANICAL VALUES:</p> <p>TOLERANCES ACCORDING TO ASTM A510M</p> <p>TENSILE STRENGTH: 440 MPA MAX.</p> <p>***MATERIALS TO BE SEGREGATED BY LOT WITH A RIBBON INSIDE THE VESSEL S HOLD.</p>
Özel Şartlar	
Ülke	ABD
Ekli Dosya	
Boşaltma Limanı	Lot1:NEW ORLEANS, Lot2:NEW ORLEANS, Lot3:NEW ORLEANS, Lot4:HOUSTON
Boyama ( Lot / Ebat )	different color tag per grade and per lot

Form No:  
05.10.1 -  
2 / R - 3