

DİLER DEMİR ÇELİK A.Ş DIŞ PİYASA SİPARİŞ BİLDİRİM FORMU

Sipariş Tar		30/11/	Sipariş No			2017-7794		Revizyon No		4				
Mamul		NEWLY PRODUCED HOT ROLLED WIRE ROD												
Lot No	Mamul Tipi	Mamul Standart	Mamul Kalite	Çap	ND	Boy (M)	Miktar (Ton)	Çubuk Sayısı	Birim Ağırlık (KG)	Paket Ağırlığı (KG)	Hadde Tol Min	Hadde Tol Max	Rotor Tipi	
1	Kangal	ASTM A 510M	SAE 1018	20	D		49				<u>.</u>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-	
1	Kangal	ASTM A 510M	SAE 1018	21	D		75						-	
1	Kangal	ASTM A 510M	SAE 1018	22	D		75						-	
1	Kangal	ASTM A 510M	SAE 1018	24	D		48						-	
1	Kangal	ASTM A 510M	SAE 1018	27	D		147				0		-	
2	Kangal	ASTM A 510M	SAE 1045	23	D		25						-	
2	Kangal	ASTM A 510M	SAE 1045	26	D		25						-	
Горlam Miktar (МТ)		444												
Гор. Miktar Tol % (Min] -5/0												
Çap. Miktar Tol % (Min		_5/0												
Boy Tol (- / + MM)														
Ebat Tol (- / + MM)														
Termin Baş-Bit		20171215 - 20171215												
Faturalama		Gerçek												
Paketleme		IN COILS OF MAX 2.5 MT.												
Etiket		TWO TAGS PI QUALITY, SIZE,		_	_	_	ORMATIO	N:						
Gözetim		SGS												



DİLER DEMİR ÇELİK A.Ş DIŞ PİYASA SİPARİŞ BİLDİRİM FORMU

- SAE 1018 IN OZELLIKLERI:
CHEMICAL ANALYSIS:
C: 0.15-0.20
MN: 0.60-0.70
Si: 0.10-0.20
S: 0.030 MAX
P: 0.030 MAX
CU: 0.30 MAX
Nİ: 0.15 MAX
CR: 0.14 MAX
MO: 0.03 MAX
N ppm max: 100
*yield point: 270-320 Mpa instead of 335 Mpa min
-SAE 1045 İN ÖZELLİKLERİ:
CHEMICAL COMPOSITION:
C: 0.42-0.50%
Si: 0,40%MAX
MN: 0,50-0,80%
P:0,035%MAX
S: 0,035%MAX
CR+NI+MO-0,63%MAX
*VIELD DOINT: 400 450 NA:
*YİELD POİNT: 400-450 Mpa
İspanya
BILBAO, SPAIN
-

Form No:

05.10.1 -

2/R-3