

VWO Digital Experience Optimization Platform

— Test Plan

Document field	Value
Status	Draft — for product, engineering, and QA review
Product	VWO — Digital Experience Optimization Platform
Product URL in PRD	https://app.vwo.com/
Source requirement	Product Requirements Document (PRD) VWO.com.pdf, dated January 7, 2026
Plan basis	RICEPOT_Framework_VWO_Digital_Experience_Optimization_PlatformTest_Plan.md
Owner	Dilip Kumar K
Version	1.0

1. Introduction

This plan defines the QA coverage, methods, responsibilities, environments, data, and release criteria for the VWO digital experience optimization capabilities described in the supplied PRD. It covers functional verification of experimentation, behavioral insights, personalization, program/workflow management, and integrations, together with the stated non-functional requirements.

The PRD is a high-level product description rather than a set of detailed acceptance criteria. Testing must trace to the requirements below and to product-approved stories, role matrices, integration contracts, and measurable workload/privacy policies when those are supplied. QA must not infer unspecified product behavior or treat the examples in this plan as new product requirements.

1.1 Objectives

- Verify that users can configure and run the described experiment types, analyze results with SmartStats, and access current reporting.
- Verify that the described behavioral data, audience targeting, personalization, workflows, and connectors work against their approved requirements.
- Assess the explicit non-functional requirements: editing-workflow response time, security controls, scalability, data privacy, and reliability.
- Report requirement coverage, test evidence, defects, risks, and outstanding requirement gaps to support a release decision.

1.2 Product and users

The PRD describes an enterprise DXO/CRO platform for understanding user behavior, testing experiences, personalizing interactions, and making data-driven optimization decisions across web and mobile digital properties. Its listed users include CRO specialists, product managers, UX designers, digital marketers, analysts, engineering teams, and business executives.

2. Scope of Testing

2.1 Features to be tested

Requirement reference	In-scope capability
FR1; §4.1; §5.1	A/B, split-URL, and multivariate experiments; multiple variations; hypothesis, target metrics, audience parameters, launch, monitoring, and winner-conclusion flow
FR2; §4.1; §5.1	SmartStats Bayesian analysis, statistical validation, and actionable experiment results
FR3; §4.1	Visual/WYSIWYG and code-editor experiment setup; version previews
FR4; §4.2; §5.2	Click, scroll, and focus heatmaps; session recordings; on-page surveys and feedback; funnel analytics and drop-off insights
FR5; §4.1, §4.3	Audience segmentation based on behaviors and attributes; personalization segments by geography, behavior, and demographics
FR6; §4.1	Up-to-date experiment reporting and dashboards
FR7; §4.3	Real-time delivery of customized content to target segments
FR8; §4.1, §4.5	Data synchronization/connector behavior for the named analytics, CRM, commerce, CMS, CDP, and data platforms, subject to approved connector contracts
FR9; §4.4	Central optimization planning, distributed-team collaboration, experiment backlog, and Kanban-style workflow
§7 — Performance	Editing workflows respond within 2 seconds
§7 — Security	Two-factor authentication (2FA), role-based access control (RBAC), and activity logs
§7 — Scalability	High visitor volumes are supported without performance loss
§7 — Data privacy	Compliance with GDPR, CCPA, and applicable regional data policies
§7 — Reliability	99.9% uptime SLA for enterprise customers
§4.1, §4.2, §5.1, §5.2	Cross-browser/cross-device QA and the two user flows described in the PRD

The integrations specifically named in the PRD are Google Analytics, Mixpanel, Shopify, Salesforce, Segment, Snowflake, WordPress, and Drupal. The PRD also refers more generally to CDPs, analytics systems, and tracking/reporting tools; those are testable only when a specific supported connector and expected behavior are approved.

2.2 Features not to be tested

Exclusion	Reason
Pricing, plan tiers, billing, and licensing behavior	The PRD gives general pricing context but no testable pricing, entitlement, or billing requirements.
Future enhancements: AI test-idea suggestions, mobile SDK enhancements, predictive analytics, and ROI forecasting	Explicitly identified as future enhancements, not current requirements.
Marketing-site content, pricing claims, and visual design acceptance	Not part of the in-scope platform behavior; the framework prompt also says to ignore the design aspects of its reference page.
Internal behavior of third-party services	QA verifies VWO's approved connector behavior and observable data exchange, not the external provider's own product.
Unspecified SDK/API behavior, implementation details, or unsupported connectors	The PRD does not define these as independently testable requirements.
Exact permission outcomes, supported browser/device versions, or regional legal interpretations not yet approved	These require an authoritative product/security/legal matrix; QA will not invent expected behavior.

3. Test Approach and Strategy

3.1 Test levels and types

1. **Requirement and test-design review:** map each PRD requirement to approved acceptance criteria, scenarios, test data, and evidence. Raise ambiguities before execution.
2. **Functional testing:** verify each in-scope feature and the setup-to-results user flow, including positive, negative, boundary, and validation paths supported by approved requirements.
3. **Integration testing:** verify authorized connection setup, data exchange, mapping, error handling, and recovery against provider-specific contracts and test tenants. Validate analytics integrations (Google Analytics and Mixpanel) and other named connectors where enabled.
4. **End-to-end testing:** execute the PRD flows for setting up an A/B test and analyzing behavioral data, including relevant transitions between experiment results and behavioral insights.
5. **Cross-device/cross-browser testing:** exercise version previews and the critical in-scope workflows on the product-approved browser/device matrix.
6. **Non-functional testing:** measure editing response time; evaluate security controls, privacy requirements, scalability under approved load profiles, and reliability evidence.
7. **Regression testing:** rerun impacted requirements and critical end-to-end workflows after a fix or release candidate change.
8. **Acceptance/readiness review:** report traceability, test outcomes, open risks, defects, and requirement gaps for product and release stakeholders.

3.2 Feature-specific coverage

- **Experiments:** create and configure A/B, split-URL, and multivariate tests with multiple variations; configure hypotheses, goals/metrics, and audience; use visual and code editors; preview versions; launch, monitor, schedule, and report according to approved behavior.
- **Statistics and reports:** verify SmartStats presents Bayesian analysis, statistically validated results, and actionable reports for approved datasets; check report freshness against the approved real-time definition.
- **Behavioral insights:** verify click/scroll/focus heatmap data, session capture/playback, survey/feedback collection, and funnel setup/drop-off analysis; compare displayed insights with controlled test events.
- **Targeting and personalization:** verify approved behavior/attribute and geography/behavior/demographic segments, eligibility, and real-time customized content delivery. Confirm outcomes at segment boundaries defined by product.
- **Workflow management:** verify central initiative planning, collaboration for distributed teams, and Kanban experiment-backlog behavior against approved workflow and permission rules.
- **Connectors:** verify each enabled, named connector against its approved setup, field mapping, sync, freshness, failure, retry, and duplicate-handling criteria. No unprovided connector behavior is presumed.
- **Security and privacy:** verify 2FA, RBAC, and activity logging against approved security specifications; verify processing and handling against approved GDPR, CCPA, and regional policy requirements using authorized synthetic data.

3.3 Test design, execution, and automation

- Maintain a traceability matrix linking PRD IDs/sections to test cases, execution results, defects, and evidence.
- Prioritize Must requirements and the primary user flows; cover High and Medium requirements in the same release scope according to the approved delivery plan.
- Use risk-based exploratory testing to investigate unclear interactions, without converting observations into pass criteria until product confirms expected behavior.
- Automate stable, repeatable regression checks where the project's existing framework and testability support it. Automation is a means of execution, not a separate product requirement.
- Keep test evidence reproducible: record build/environment, browser/device, account/role, data set, steps, expected and actual results, timestamps, and relevant logs/screenshots.

4. Test Environments and Resources

4.1 Environments

Environment/resource	Use and readiness requirement
QA/staging VWO application	Release-candidate environment with the in-scope features, integrations, and configuration enabled; access and build identifier recorded for each cycle.
Production-like test tenant/workspace	Isolated workspace for realistic configuration and workflows without affecting customer experiments or data.
Supported browsers and devices	Product-approved matrix for the PRD's cross-browser/cross-device QA. The PRD does not specify browser, OS, or device versions; obtain the matrix before coverage is declared complete.
Integration test tenants	Authorized non-production accounts for each enabled named connector. Credentials/secrets must be managed through approved secure channels, not stored in this plan or test cases.
Performance/load environment	Environment and monitoring capable of exercising editing workflows and approved high-visitor-volume profiles without impacting production.
Security/privacy test accounts	Synthetic accounts for approved roles, 2FA states, and regional-policy scenarios; use only authorized test data.

Record application build, configuration, enabled features/connectors, environment URL, test-window dates, and environment owner in the execution record. Test environment parity and data isolation must be confirmed before execution.

4.2 Test data

- Synthetic users/accounts for each product-approved role, 2FA state, and permitted/denied access scenario.
- Synthetic experiment hypotheses, variations, URLs, audiences, goals, metric configurations, schedules, and result/event data that support A/B, split-URL, and multivariate cases.
- Controlled click, scroll, focus, session, survey/feedback, and funnel events, including events that exercise funnel progression and drop-off.
- Synthetic audience attributes and segments for behavior, geography, and demographics, including boundary values approved by product.
- Synthetic planning initiatives, collaborators, Kanban backlog items, and workflow states.
- Synthetic integration records and events with known expected mappings, timestamps, and outcomes for each enabled connector.
- Synthetic high-volume visitor/event datasets sized to the approved workload profile.
- No real customer personal data unless explicit authorization, minimization, and applicable policy approval are documented. Any permitted personal data must follow the approved privacy test protocol.

5. Tools

Use the organization-approved tools available for the project. Confirm exact product/tool versions during kickoff; examples below are tool categories, not requirements imposed by the PRD.

Tool category	Use
Test management/traceability tool	Store test cases, requirement links, execution evidence, and coverage.
Defect tracker	Log, triage, prioritize, assign, and report defects.
Browser developer tools and approved browser/device lab	Inspect browser behavior, network activity, console errors, and cross-browser/device results.
API/integration client, where applicable	Inspect and validate connector or service exchanges using approved test credentials.
Performance/load and monitoring tools	Measure editing-workflow response time and execute agreed visitor-volume profiles.

Tool category	Use
Approved security/privacy verification tools	Support 2FA, RBAC, activity-log, and data-handling checks within authorized scope.
Project-approved automation framework and CI	Run stable functional and regression checks where automation is appropriate.

6. Entry and Exit Criteria

6.1 Entry criteria

- Product and engineering have reviewed the in-scope requirements and supplied testable acceptance criteria for the planned release.
- Open ambiguities affecting expected results (including role permissions, supported browser/device matrix, connector contracts, real-time freshness, privacy policies, and load targets) are resolved or explicitly recorded as blocked coverage.
- QA build is deployed and identified; required features, test tenant, access, integrations, monitoring, and test data are available.
- Test cases and traceability are reviewed; known environment limitations and test risks are documented.
- Smoke checks confirm the application and critical dependencies are available and test data is isolated.

6.2 Exit criteria

- All planned, approved in-scope tests have an execution result and linked evidence; requirement coverage and exclusions are reported.
- All Must requirements and primary user flows pass, or remaining gaps have documented product/release-owner acceptance.
- No open Critical/Blocker defects. Any open High/Medium defects have documented impact, workaround (if any), owner, target resolution, and explicit release-risk acceptance.
- Performance results are reported against the 2-second editing-workflow requirement using the agreed measurement boundary and workload.
- Security, privacy, scalability, and reliability evidence is reported against approved criteria; unmeasurable or unverified criteria are called out rather than marked passed.
- Fix retests and required regression tests are complete; defect status and residual risks are reviewed with stakeholders.
- QA Test Lead issues a test summary and recommendation. Release approval remains with the designated product/release authority.

7. Item Pass/Fail Criteria

- **Pass:** observed behavior meets the approved acceptance criterion for the linked PRD requirement, with reproducible evidence and no material side effect.
- **Fail:** behavior contradicts an approved requirement/acceptance criterion, produces incorrect or missing results, violates an approved security/privacy control, or exceeds a measurable threshold.
- **Blocked:** execution cannot proceed because an environment, dependency, access, data set, or required expected result is unavailable. Record the blocker and affected coverage; do not count it as a pass.
- **Inconclusive:** evidence is insufficient or inconsistent to decide. Investigate and rerun with controlled data; retain as unresolved until dispositioned.
- **Environment-related/unreproducible issue:** capture environment/build/network details and repeat in a controlled supported environment. If not reproducible, document evidence and risk and obtain triage disposition; do not silently close as passed.
- **Unspecified requirement:** seek product clarification and record the coverage as blocked or out of approved scope until expected behavior is agreed.

8. Suspension Criteria and Resumption Requirements

Suspend the affected test activity when

- The QA environment, critical dependency, or integration is unavailable or unstable enough to invalidate results.
- A Critical/Blocker defect prevents core experiment setup, launch, analysis, or creates risk to data integrity, customer data, or security.
- Test data is contaminated, unexpectedly contains real personal data, or cannot be safely isolated.
- A release/build change invalidates the current test baseline or expected results.
- Load or security testing could affect production or systems outside the explicitly authorized scope.

Resume when

- The environment/dependency is restored and QA confirms health with a smoke test.
- The blocking defect is fixed or an approved workaround is available; the affected test and relevant regression checks pass.
- Test data is clean, authorized, and isolated, and the correct build/configuration is recorded.
- Product/engineering confirms changed requirements and expected behavior; impacted tests are updated and reviewed.
- The performance/security test window and target environment are approved and safe to use.

9. QA Activities and Schedule

Schedule dates and duration are release-dependent and are to be baselined with the project schedule; the PRD provides no delivery dates.

Phase	QA activities	Exit evidence
1. Requirement readiness	Review PRD and stories; identify ambiguities, dependencies, risks, priorities, and acceptance criteria; agree supported matrices and thresholds.	Approved requirement clarifications, initial risk/coverage map
2. Planning and setup	Confirm staffing, environments, tool access, test tenant, integrations, data, and security/privacy authorization.	Environment readiness and test-data checklist
3. Test design	Create/review scenarios and cases; map tests to FR1–FR9 and NFRs; define expected outcomes and evidence.	Reviewed test suite and traceability matrix
4. Smoke and functional execution	Run smoke, feature, negative/boundary, workflow, and cross-browser/device checks; record defects and evidence.	Execution results and daily defect status
5. Integration and non-functional execution	Verify enabled connectors; measure editing performance; execute approved load, security, privacy, and reliability checks.	Connector results and non-functional evidence/limitations
6. Fix verification and regression	Retest fixes; run targeted and risk-based regression; update traceability and defect states.	Retest and regression results
7. Closure/readiness	Review exit criteria, outstanding issues, residual risks, deferred coverage, and release recommendation.	Test summary report and QA recommendation

10. Roles and Responsibilities

Names and contacts are assigned by the project; no individuals or contact details were provided in the PRD.

Role	Responsibilities
QA/Test Lead	Own this plan, scope, test strategy, traceability, readiness, risk escalation, triage coordination, status reporting, and final QA recommendation.
QA Engineer(s)	Review requirements; design and execute tests; prepare safe test data; capture evidence; log, retest, and regress defects; report blockers and coverage accurately.

Role	Responsibilities
Product Manager/Product Owner	Clarify requirements and acceptance criteria; approve priorities, supported behavior, role matrix, privacy expectations, workflow rules, and disposition of product gaps/risks.
Engineering/Development	Provide build notes and technical support; investigate/fix defects; document changes and known limitations; support testability and safe environment configuration.
DevOps/SRE	Provision and monitor environments; assist with deployment, availability, load profiles, logs, and evidence relevant to the stated uptime/scalability requirements.
Security/Privacy/Legal representatives	Approve authorized security/privacy test scope, role/access expectations, data handling, regional-policy interpretation, and review of findings.
Integration/Analytics owner	Supply connector contracts, credentials through secure channels, test tenants, expected mappings, and partner-side evidence where needed.
Release Manager	Coordinate the schedule and release decision process; record accepted risks and confirm required approvals.

11. Defect Management

1. Log each defect in the approved tracker with a unique ID, concise title, affected requirement/test, environment/build, severity and priority, reproducible steps, expected/actual result, evidence, impact, and test-data references (no secrets or unnecessary personal data).
2. QA triages with Product and Engineering. Severity reflects user/business impact; priority reflects fix order and release risk. Mark dependency/environment issues distinctly from product defects.
3. Engineering records the fix/build and relevant change notes. QA retests the original failure and executes the agreed impact-based regression set.
4. Close only when the retest passes and evidence is linked. Reopen if the issue persists or regresses. Deferred/rejected defects require a documented rationale and owner.
5. Report open/closed defects, severity, aging, retest status, blockers, and accepted risks at the agreed cadence and in the final summary.

12. Deliverables

Deliverable	Timing
Reviewed test plan and risk register	Planning/readiness phase; update when scope or risk materially changes.
Requirement clarification and traceability matrix	During requirement review and test design; maintained through closure.
Test scenarios/cases and test data specification	Before the relevant execution cycle; update for approved requirement changes.
Environment and test-data readiness record	Before execution and whenever environment/configuration changes.
Defect reports and daily/periodic QA status	Throughout execution; cadence agreed at kickoff.
Functional, integration, cross-browser/device, and non-functional evidence	As each test activity completes.
Regression/retest results	After each fix/build under test.
Test summary and release-readiness recommendation	At test closure, including coverage, outcomes, open defects, deviations, risks, and unverified criteria.

13. Risks and Contingencies

Risk / concern	Impact	Mitigation / contingency
PRD is high-level and lacks detailed acceptance criteria	Different interpretations and unreliable pass/fail decisions	Review with Product before test design; record decisions and block only affected coverage until criteria are approved.
Supported browser/device versions are unspecified	Cross-browser/device coverage cannot be declared complete	Obtain and baseline a supported matrix; prioritize primary workflows on every approved combination.
"Real-time," "high visitor volumes," and editing response-time measurement details are undefined	Results may not be measurable or comparable	Agree freshness definitions, workload, measurement boundary, instrumentation, and thresholds with Product/Engineering before execution. Preserve the explicit 2-second requirement.
Named connector contracts, credentials, or partner test tenants are unavailable	Integration coverage is blocked or partial	Request authorized test tenants and provider-specific mappings early; report each connector's status separately and do not infer success from UI setup alone.
GDPR/CCPA/regional obligations and data lifecycle behavior are not specified	Privacy verification may omit required controls or misuse data	Obtain approved jurisdiction/policy matrix from Privacy/Legal; use synthetic data by default and restrict tests to authorized controls.
RBAC role definitions and expected activity-log events are absent	Security outcomes cannot be asserted consistently	Request approved role-permission and audit-event matrices; test only after approval.
High-scale test environment differs from production or could affect live traffic	Misleading results or service impact	Use an isolated, approved environment and workload; coordinate with SRE and stop if production impact is observed.
Reliability SLA is longer-term than the QA execution window	A short test cycle cannot prove 99.9% uptime	Obtain operational/SRE uptime evidence over the agreed SLA measurement window; identify QA's own observation period and do not equate it with SLA proof.
Requirements or release scope change during testing	Retest effort, coverage gaps, schedule impact	Version the scope and traceability; assess impact, revise cases, and re-baseline dates/priorities with stakeholders.
Analytics/experiment data mismatch or insufficient deterministic data	Incorrect confidence in SmartStats, funnels, or reports	Use controlled known datasets; compare source and destination events; retain reconciliation evidence and escalate unexplained variance.

14. QA Checklist

Mark each item **Pass**, **Fail**, **Blocked**, or **N/A** and link evidence. **N/A** requires a reason and owner approval; blocked items are not passed.

14.1 Readiness and traceability

- ☐ Each in-scope PRD requirement is linked to an approved acceptance criterion and one or more tests.
- ☐ Product has clarified unresolved behavior, including browser/device support, RBAC, connector contracts, real-time freshness, privacy rules, and scale targets.
- ☐ Build, environment, enabled features/connectors, account access, test data, monitoring, and test window are recorded and ready.
- ☐ Synthetic data is used by default; any exception for personal data is authorized and documented.
- ☐ Critical/Blocker defects and known environment limitations have been reviewed before execution.

14.2 Experimentation, statistics, and reporting — FR1, FR2, FR3, FR6

- ☐ A/B, split-URL, and multivariate experiments can be configured with multiple variations.
- ☐ Experiment setup supports hypothesis, target metrics/custom goals, audience parameters, and the approved workflow.

- ☐ Visual/WYSIWYG and code-editor setup both support the approved experiment configuration.
- ☐ Version previews show the intended experiment version on approved browser/device combinations.
- ☐ Launch, monitoring, scheduling, and reporting behaviors match approved criteria.
- ☐ SmartStats provides Bayesian analysis for controlled known test data.
- ☐ Statistical validation and actionable results are consistent with the approved statistical acceptance criteria.
- ☐ Real-time dashboards/reports update within the approved freshness definition and reconcile to the source test events.
- ☐ Google Analytics and Mixpanel data exchanges are verified where enabled and defined by connector contracts.

14.3 Behavioral insights — FR4; §4.2; §5.2

- ☐ Click, scroll, and focus interactions are captured and represented in the corresponding heatmaps.
- ☐ Session recordings capture and replay approved synthetic sessions as expected.
- ☐ On-page survey and feedback collection behave according to approved criteria.
- ☐ Funnel setup and event progression identify the expected drop-off points from controlled data.
- ☐ Insights shown for known test events can be reconciled with the generated heatmap, recording, survey, and funnel data.
- ☐ The behavioral-analysis flow supports accessing Insights, generating heatmaps/recordings/funnels, correlating insights with test outcomes, and prioritizing optimization ideas where those actions are defined.

14.4 Targeting and personalization — FR5, FR7

- ☐ Audience targeting supports approved behavior- and attribute-based segmentation.
- ☐ Personalization supports approved geography, behavior, and demographic segments.
- ☐ Segment eligibility and boundaries produce the expected audience according to approved rules.
- ☐ Customized content is delivered to eligible segments in real time as defined by the approved freshness criterion.
- ☐ Non-eligible segments do not receive the targeted experience where that behavior is specified.
- ☐ Targeted experience/reporting results are traceable to controlled synthetic cohorts and events.

14.5 Program/workflow management — FR9

- ☐ Optimization initiatives can be represented in the central planning interface.
- ☐ Collaboration works for approved distributed-team accounts and permissions.
- ☐ Experiment backlog items can be managed in the approved Kanban-style workflow.
- ☐ Workflow state changes and collaboration outcomes persist and display consistently to authorized users.

14.6 Connectors — FR8

- ☐ Each enabled named connector has an approved test tenant, expected mapping, and success/failure criteria.
- ☐ Connection/setup and authorized data synchronization work for the approved Shopify, Salesforce, Segment, Snowflake, WordPress, and Drupal use cases.
- ☐ Analytics/measurement connectors (including Google Analytics and Mixpanel) reconcile expected events/data where enabled.
- ☐ Sync freshness, mapping, failure visibility, retry/recovery, and duplicate handling pass their approved connector-specific criteria.
- ☐ Unsupported, unavailable, or uncontracted connectors are recorded as exclusions or blocked coverage, not assumed to pass.

14.7 Non-functional requirements — §7

- ☐ Editing workflows meet the PRD response requirement of **within 2 seconds** under the agreed measurement method and representative approved conditions.
- ☐ 2FA can be verified against the approved authentication requirements, including relevant success and failure paths.
- ☐ RBAC permits and denies actions in accordance with the approved role-permission matrix.
- ☐ Activity logs record the approved actions with sufficient approved context for review.
- ☐ GDPR, CCPA, and regional-policy scenarios are checked against the approved legal/privacy control matrix using authorized test data.

- ☐ Scalability is evaluated against approved high-visitor-volume targets; performance loss and observed limits are documented.
- ☐ 99.9% enterprise uptime is supported by evidence over the approved SLA measurement window; short test execution is not treated as proof of the SLA.

14.8 Closure

- ☐ Fixes are retested and impacted workflows receive regression coverage.
- ☐ No Critical/Blocker defects remain open; other open defects and accepted risks have documented owners and disposition.
- ☐ Blocked, inconclusive, excluded, and unverified requirements are listed with reasons and impact.
- ☐ Final requirement coverage, evidence, environment/build, defect status, risks, and QA recommendation are included in the test summary.

15. Requirement Gaps Requiring Clarification

Resolve or explicitly disposition these before claiming complete coverage:

1. Detailed acceptance criteria and workflow rules for all FR1–FR9 features.
2. Supported browsers, operating systems, device types, and versions for cross-browser/cross-device QA.
3. Role names, permission matrix, 2FA policy, and exact activity-log events/retention expectations.
4. Definition and measurement of “real-time” for reports and personalized content.
5. Editing-workflow timing start/end points, representative workflow set, environment, and measurement method for the 2-second target.
6. Numerical visitor-volume profiles and an objective definition of “without performance loss.”
7. GDPR, CCPA, and regional-policy obligations applicable to collection, recording, retention, access, deletion, and any other relevant data handling.
8. Connector-specific supported operations, schemas/mappings, sync frequency, error/retry behavior, and provider test access.
9. Statistical acceptance criteria/data sets for SmartStats and the intended meaning of “statistically validated.”
10. Uptime SLA measurement period, exclusions, and source of operational evidence for 99.9% reliability.
11. Product-approved priority/release disposition for open High/Medium defects and blocked tests.