```
Database changed
mysql> CREATE TABLE employees (
    ->     employee_id INT,
    ->     first_name VARCHAR(50),
    ->     last_name VARCHAR(50),
    ->     device_serial VARCHAR(15),
    ->     salary INT
    -> );
Query OK, 0 rows affected (0.07 sec)

mysql> desc employees;
+---------------+-------------+------+-----+---------+-------+
| Field         | Type        | Null | Key | Default | Extra |
+---------------+-------------+------+-----+---------+-------+
| employee_id   | int         | YES  |     | NULL    |       |
| first_name    | varchar(50) | YES  |     | NULL    |       |
| last_name     | varchar(50) | YES  |     | NULL    |       |
| device_serial | varchar(15) | YES  |     | NULL    |       |
| salary        | int         | YES  |     | NULL    |       |
+---------------+-------------+------+-----+---------+-------+
5 rows in set (0.00 sec)

mysql> INSERT INTO employees VALUES
    -> (1,'John','Smith','ABC123',60000),
    -> (2,'Jane','Doe','DEF456',65000),
    -> (3,'Bob','Brown','GHI789',70000),
    -> (4,'Sally','Fields','JKL012',75000),
    -> (5,'Michael','Smith','MNO345',80000),
    -> (6,'David','Jones','PQR678',85000),
    -> (7,'Emily','Williams','STU901',90000),
    -> (8,'James','Johnson','VWX234',95000),
    -> (9,'Sarah','Miller','YZA567',100000),
    -> (10,'William','Davis','BCD890',105000),
    -> (11,'Olivia','Taylor','EFG123',110000),
    -> (12,'Christopher','Rodriguez','HIJ456',115000),
    -> (13,'Isabella','Wilson','KLM789',120000),
    -> (14,'Matthew','Anderson','NOP012',125000),
    -> (15,'Elizabeth','Martinez','QRS345',130000),
    -> (16,'Sophia','Thomas','TUV678',135000),
    -> (17,'Daniel','Smith','WXY901',140000),
    -> (18,'Mia','Thomas','ZAB234',145000),
    -> (19,'Joseph','Hernandez','CDE567',150000),
    -> (20,'Abigail','Smith','FGH890',155000);
Query OK, 20 rows affected (0.01 sec)
Records: 20  Duplicates: 0  Warnings: 0

mysql> select * from employees;
```

MySQL 8.0 Command Line Cli

```
mysql> select * from employees;
+-------------+-------------+-----------+---------------+--------+
| employee_id | first_name  | last_name | device_serial | salary |
+-------------+-------------+-----------+---------------+--------+
|           1 | John        | Smith     | ABC123        |  60000 |
|           2 | Jane        | Doe       | DEF456        |  65000 |
|           3 | Bob         | Brown     | GHI789        |  70000 |
|           4 | Sally       | Fields    | JKL012        |  75000 |
|           5 | Michael     | Smith     | MNO345        |  80000 |
|           6 | David       | Jones     | PQR678        |  85000 |
|           7 | Emily       | Williams  | STU901        |  90000 |
|           8 | James       | Johnson   | VWX234        |  95000 |
|           9 | Sarah       | Miller    | YZA567        | 100000 |
|          10 | William     | Davis     | BCD890        | 105000 |
|          11 | Olivia      | Taylor    | EFG123        | 110000 |
|          12 | Christopher | Rodriguez | HIJ456        | 115000 |
|          13 | Isabella    | Wilson    | KLM789        | 120000 |
|          14 | Matthew     | Anderson  | NOP012        | 125000 |
|          15 | Elizabeth   | Martinez  | QRS345        | 130000 |
|          16 | Sophia      | Thomas    | TUV678        | 135000 |
|          17 | Daniel      | Smith     | WXY901        | 140000 |
|          18 | Mia         | Thomas    | ZAB234        | 145000 |
|          19 | Joseph      | Hernandez | CDE567        | 150000 |
|          20 | Abigail     | Smith     | FGH890        | 155000 |
+-------------+-------------+-----------+---------------+--------+
20 rows in set (0.00 sec)

mysql> CREATE VIEW v1 AS
    -> SELECT employee_id, salary
    -> FROM employees;
Query OK, 0 rows affected (0.01 sec)

mysql> select * from employees;
+-------------+-------------+-----------+---------------+--------+
| employee_id | first_name  | last_name | device_serial | salary |
+-------------+-------------+-----------+---------------+--------+
|           1 | John        | Smith     | ABC123        |  60000 |
|           2 | Jane        | Doe       | DEF456        |  65000 |
|           3 | Bob         | Brown     | GHI789        |  70000 |
|           4 | Sally       | Fields    | JKL012        |  75000 |
|           5 | Michael     | Smith     | MNO345        |  80000 |
|           6 | David       | Jones     | PQR678        |  85000 |
|           7 | Emily       | Williams  | STU901        |  90000 |
|           8 | James       | Johnson   | VWX234        |  95000 |
|           9 | Sarah       | Miller    | YZA567        | 100000 |
|          10 | William     | Davis     | BCD890        | 105000 |
```

```
mysql>  DESC v1;
+-------------+------+------+-----+---------+-------+
| Field       | Type | Null | Key | Default | Extra |
+-------------+------+------+-----+---------+-------+
| employee_id | int  | YES  |     | NULL    |       |
| salary      | int  | YES  |     | NULL    |       |
+-------------+------+------+-----+---------+-------+
2 rows in set (0.00 sec)

mysql> INSERT INTO v1 VALUES (21, 160000);
Query OK, 1 row affected (0.01 sec)

mysql> SELECT * FROM v1;
+-------------+--------+
| employee_id | salary |
+-------------+--------+
|           1 |  60000 |
|           2 |  65000 |
|           3 |  70000 |
|           4 |  75000 |
|           5 |  80000 |
|           6 |  85000 |
|           7 |  90000 |
|           8 |  95000 |
|           9 | 100000 |
|          10 | 105000 |
|          11 | 110000 |
|          12 | 115000 |
|          13 | 120000 |
|          14 | 125000 |
|          15 | 130000 |
|          16 | 135000 |
|          17 | 140000 |
|          18 | 145000 |
|          19 | 150000 |
|          20 | 155000 |
|          21 | 160000 |
+-------------+--------+
21 rows in set (0.00 sec)

mysql> INSERT INTO v1 VALUES (21, 160000);
Query OK, 1 row affected (0.01 sec)

mysql> SELECT * FROM v1;
+-------------+--------+
| employee_id | salary |
+-------------+--------+
```

```
|           12 | 115000 |
|           13 | 120000 |
|           14 | 125000 |
|           15 | 130000 |
|           16 | 135000 |
|           17 | 140000 |
|           18 | 145000 |
|           19 | 150000 |
|           20 | 155000 |
|           21 | 160000 |
|           21 | 160000 |
+--------------+--------+
22 rows in set (0.00 sec)

mysql> CREATE INDEX idx_salary ON employees(salary);
Query OK, 0 rows affected (0.09 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> SELECT first_name
    -> FROM employees
    -> WHERE salary > 145000;
+------------+
| first_name |
+------------+
| Joseph     |
| Abigail    |
| NULL       |
| NULL       |
+------------+
4 rows in set (0.00 sec)

mysql> CREATE INDEX idx_employee_id ON employees(employee_id);
Query OK, 0 rows affected (0.05 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> SELECT first_name
    -> FROM employees
    -> WHERE employee_id = 10;
+------------+
| first_name |
+------------+
| William    |
+------------+
1 row in set (0.00 sec)

mysql> SELECT first_name
```

```
|          21 | 160000 |
|          21 | 160000 |
+-------------+--------+
22 rows in set (0.00 sec)

mysql> CREATE INDEX idx_salary ON employees(salary);
Query OK, 0 rows affected (0.09 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> SELECT first_name
    -> FROM employees
    -> WHERE salary > 145000;
+------------+
| first_name |
+------------+
| Joseph     |
| Abigail    |
| NULL       |
| NULL       |
+------------+
4 rows in set (0.00 sec)

mysql> CREATE INDEX idx_employee_id ON employees(employee_id);
Query OK, 0 rows affected (0.05 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> SELECT first_name
    -> FROM employees
    -> WHERE employee_id = 10;
+------------+
| first_name |
+------------+
| William    |
+------------+
1 row in set (0.00 sec)

mysql> SELECT first_name
    -> FROM employees
    -> WHERE employee_id = 10;
+------------+
| first_name |
+------------+
| William    |
+------------+
1 row in set (0.00 sec)

mysql>
```