

Indian Institute of Information Technology, Vadodara

Parallel Programming(CS403)

Prof. Reshmi Mitra

Name - Hemant Kumar

ID - 201352026

Collaborator - Dilip Puri(201351014)

Lab 06

Submission Date - October 10, 2016

Deadline - Oct 10, 11:59 PM

1. In the Callgrind tutorial link and the attached file “Lab6_callgrind.pdf” familiarize yourself with the callgrind tool.
2. For the lab exercise, refer to the attached valgrind_eg.c.


```
$ gcc -g -o valgrind_eg valgrind_eg.c -pthread
$ ./valgrind_eg 1
completion time for put phase = 2.758351
0: 0 keys missing
completion time for get phase = 2.270119
This is the same program as used in the previous lab.
valgrind --tool=callgrind --dump-instr=yes --simulate-cache=yes ./val_eg <>
```

Use the above command on this sample C-code to find the call-graph. Toggle the “Cycle Detection” and “% Relative” menu in the top of kcachegrind to observe to menu output. Using this option, find

- callee map



- cost (in terms of cycles) associated with the most expensive function calls.



- cost (in terms of cycles) associated with `pthread_mutex_lock.c` and `pthread_mutex_unlock.c`

```

document.pdf function_call_kcachegrind function_call_kcachegrind.txt- Helpful_commands Lab06.pdf valgrind_eg
raghuvar@raghuvar-HCL-ME-Laptop:~/Desktop/PP/PP_lab/lab06$ valgrind --tool=callgrind --dump-instr=yes --simulate-
==4219== Callgrind, a call-graph generating cache profiler
==4219== Copyright (C) 2002-2015, and GNU GPL'd, by Josef Weidendorfer et al.
==4219== Using Valgrind-3.11.0 and LibVEX; rerun with -h for copyright info
==4219== Command: ./valgrind_eg 2
==4219==
--4219-- warning: L3 cache found, using its data for the LL simulation.
==4219== For interactive control, run 'callgrind_control -h'.
completion time for put phase = 407.358839
i: 0 keys missing
0: 0 keys missing
completion time for get phase = 423.969385
==4219==
==4219== Events      : Ir Dr Dw Iimr Dimr Dimw IImr DImr DImw
==4219== Collected : 30032474217 9009883757 2005841782 1273 373521843 358345 1209 20317 6703
==4219==
==4219== I  refs:      30,032,474,217
==4219== I1 misses:    1,273
==4219== L1l misses:    1,209
==4219== I1 miss rate:    0.00%
==4219== L1l miss rate:  0.00%
==4219==
==4219== D  refs:      11,015,725,539 (9,009,883,757 rd + 2,005,841,782 wr)
==4219== D1 misses:    373,880,188 ( 373,521,843 rd +    358,345 wr)
==4219== L1d misses:    27,020 (    20,317 rd +    6,703 wr)
==4219== D1 miss rate:    3.4% (    4.1% +    0.0% )
==4219== L1d miss rate:  0.0% (    0.0% +    0.0% )
==4219==
==4219== LL refs:      373,881,461 ( 373,523,116 rd +    358,345 wr)
==4219== LL misses:    28,229 (    21,526 rd +    6,703 wr)
==4219== LL miss rate:  0.0% (    0.0% +    0.0% )

```

Incl.	Self	Called	Function	Location
33 764 803 104	2 387	3	start_thread	libpthread-2.19.so: pth
16 887 953 964	3 254 640	2	get_thread	valgrind_eg: valgrind_e
16 884 691 092	16 873 728 058	100 000	get	valgrind_eg: valgrind_e
16 876 830 759	3 153 314	2	put_thread	valgrind_eg: valgrind_e
16 873 677 445	16 873 677 445	100 000	put	valgrind_eg: valgrind_e
8 207 846 900	10	1	clone'2	libc-2.19.so: clone.S
8 207 846 890	225	1	start_thread'2	libpthread-2.19.so: pth
9 308 487	274	(0)	0x000010d0	ld-2.19.so
8 952 337	458	1	0x080486f0	valgrind_eg
8 950 255	633	1	(below main)	libc-2.19.so: libc-start.c
8 936 379	1 789 655	1	main	valgrind_eg: valgrind_e
6 900 330	2 300 330	100 000	random	libc-2.19.so: random.c
6 669 987	6 451 399	100 002	pthread_mutex_lock	libpthread-2.19.so: pth
4 413 860	4 213 240	100 310	random_r	libc-2.19.so: random_r.c
4 290 906	300 126	100 002	pthread_mutex_unlock	libpthread-2.19.so: pth
3 990 780	3 766 826	100 002	__pthread_mutex_unloc...	libpthread-2.19.so: pth

Function Name	Inclusive Cost(In terms of Cycles)	Self Cost(In terms of Cycles)	Ca
get	16 884 691 092	16 873 728 058	
get_thread	16 887 953 964	3 254 640	
put	16 873 677 445	16 873 677 445	
put_thread	16 876 830 759	3 153 314	
main	8 936 379	1 789 655	

