

Generating Random WMC Instances

An Empirical Analysis with Varying Primal Treewidth

Paulius Dilkas

University of Edinburgh, UK

Workshop on Counting and Sampling 2022



THE UNIVERSITY OF EDINBURGH

informatics



EDINBURGH CENTRE FOR

ROBOTICS



Engineering and
Physical Sciences
Research Council

Weighted Model Counting (WMC)

- ▶ A generalisation of propositional model counting (#SAT)
- ▶ Applications:
 - ▶ graphical models
 - ▶ probabilistic programming
 - ▶ neural-symbolic artificial intelligence
- ▶ WMC algorithms use:
 - ▶ dynamic programming
 - ▶ knowledge compilation
 - ▶ SAT solvers

Example


$$w(x) = 0.3, w(\neg x) = 0.7, \\ w(y) = 0.2, w(\neg y) = 0.8$$

$$\text{WMC}(x \vee y) = w(x)w(y) + \\ w(x)w(\neg y) + w(\neg x)w(y) = 0.44$$

(Some of the) WMC Algorithms

- ▶ CACHET (Sang et al. 2004)
 - ▶ component caching
- ▶ C2D (Darwiche 2004)
 - ▶ knowledge compilation to d-DNNF
- ▶ D4 (Lagniez and Marquis 2017)
 - ▶ knowledge compilation to decision-DNNF
- ▶ MINIC2D (Oztok and Darwiche 2015)
 - ▶ knowledge compilation to decision sentential decision diagrams
- ▶ DPMC (Dudek, Phan and Vardi 2020)
 - ▶ dynamic programming with algebraic decision diagrams (ADDs) and tree decomposition based planning

The Performance Characteristics of WMC Algorithms




Data from Dilkas and Belle (2021): various Bayesian networks encoded using the method by Darwiche (2002)

A Note on Primal Treewidth


Formula in CNF:

$$\phi = (x_4 \vee \neg x_3 \vee x_1) \wedge (\neg x_2 \vee x_4) \wedge (\neg x_1 \vee x_2 \vee x_4)$$

Its primal graph:



Its minimum-width tree decomposition:



\therefore the primal treewidth of ϕ is 2

The Parameterised Complexity of WMC Algorithms

Let n be the number of **variables** and m be the number of **clauses**.

- ▶ Component caching (used in CACHET) is $2^{\mathcal{O}(w)} n^{\mathcal{O}(1)}$, where w is the **branchwidth** of the underlying hypergraph (Bacchus, Dalmao and Pitassi 2009)
 - ▶ Branchwidth is within a constant factor of primal treewidth
- ▶ C2D is based on an algorithm, which is $\mathcal{O}(2^w mw)$, where w is at most **primal treewidth** (Darwiche 2001; Darwiche 2004)
- ▶ DPMC can be shown to be $\mathcal{O}(4^w mn)$, where w is an upper bound on **primal treewidth**

Generating Random WMC Instances: The Algorithm

$\phi \leftarrow$ empty CNF formula;

$G \leftarrow$ empty graph;

for $i \leftarrow 1$ **to** m **do** \leftarrow the number of clauses
 $X \leftarrow \emptyset$;
 for $j \leftarrow 1$ **to** k **do** \leftarrow clause width
 $x \leftarrow \text{newVariable}(X, G)$; \leftarrow a function to pick a variable
 $\mathcal{V}(G) \leftarrow \mathcal{V}(G) \cup \{x\}$;
 $\mathcal{E}(G) \leftarrow \mathcal{E}(G) \cup \{\{x, y\} \mid y \in X\}$;
 $X \leftarrow X \cup \{x\}$; \leftarrow a (fair) coin flip
 $\phi \leftarrow \phi \cup \{\{l \leftarrow \mathcal{U}\{x, \neg x\} \mid x \in X\}\}$;

How to Pick a Variable

Parameter $\rho \in [0, 1]$ biases the probability distribution towards adding variables that would introduce fewer new edges.

Function newVariable(*set of variables* X , *primal graph* G):

$N \leftarrow \{ e \in \mathcal{E}(G) \mid |e \cap X| = 1 \};$

if $N = \emptyset$ **then return** $x \leftarrow \mathcal{U}(\{x_1, x_2, \dots, x_n\} \setminus X);$

return

$x \leftarrow \left(\{x_1, x_2, \dots, x_n\} \setminus X, y \mapsto \frac{1-\rho}{n-|X|} + \rho \frac{|\{z \in X \mid \{y, z\} \in \mathcal{E}(G)\}|}{|N|} \right);$


An Example

Setup

Let $n = 5$, $k = 3$, and $\rho = 0.3$.

Partial formula: $(\neg x_5 \vee x_2 \vee x_1) \wedge (x_5 \vee ? \vee ?)$.

Primal graph:




The probability distribution for the next variable

Base probability of each variable being chosen:


$$\frac{1 - \rho}{n - |X|} = \frac{1 - 0.3}{5 - 1} = 0.175.$$

Both x_1 and x_2 get a bonus probability of $\rho/2$ for each being the endpoint of **one** out of the **two** neighbourhood edges.

The Relationship Between ρ and Primal Treewidth




Hardness w.r.t. Density (when $\rho = 0$)



Peak Hardness w.r.t. Density

- ▶ Bayardo Jr. and Pehoushek (2000) show some #SAT algorithms to peak at $\mu = 1.2$ and $\mu = 1.9$
- ▶ CACHET is known to peak at $\mu = 1.8$ (Sang et al. 2004)
- ▶ In our experiments:
 - ▶ DPMC peaks at $\mu = 2.2$
 - ▶ all other algorithms peak at $\mu = 1.9$

Hardness w.r.t. Primal Treewidth (when $\mu = 1.9$)




Is The Relationship Exponential?

Let us fit the model $\ln t \sim \alpha w + \beta$, i.e., $t \sim e^\beta (e^\alpha)^w$, where t is runtime, and w is primal treewidth


Is The Relationship Exponential?

Let us fit the model $\ln t \sim \alpha w + \beta$, i.e., $t \sim e^\beta (e^\alpha)^w$, where t is runtime, and w is primal treewidth




Is The Relationship Exponential?

Let us fit the model $\ln t \sim \alpha w + \beta$, i.e., $t \sim e^\beta (e^\alpha)^w$, where t is runtime, and w is primal treewidth



Bonus: How DPMC Reacts to Redundancy in Weights

Let ϵ be the proportion of variables x s.t. $w(x) = w(\neg x) = 0.5$



Summary

Observations

- ▶ All algorithms scale exponentially w.r.t. primal treewidth
- ▶ The running time of DPMC peaks at a higher density and scales worse w.r.t. primal treewidth
 - ▶ Related to the complexity of ADD multiplication
- ▶ MINIC2D seems to be best at low density high primal treewidth instances

Future work

- ▶ A theoretical relationship between ρ and primal treewidth
- ▶ Non- k -CNF instances
- ▶ Similar observations on real data
- ▶ SATzilla for WMC