

Recursive Solutions to First-Order Model Counting

Paulius Dilkas, Vaishak Belle

AAI Seminar, 28th March 2022

Some Elementary Counting

A Counting Problem

Suppose we were meeting in person, the room had n seats, and there were $m \leq n$ attendees. How many ways would there be to seat everyone?

Some Elementary Counting

A Counting Problem

Suppose we were meeting in person, the room had n seats, and there were $m \leq n$ attendees. How many ways would there be to seat everyone?

More explicitly, we assume that:

- each attendee gets one seat (i.e., at least one **and** at most one),
- and a seat can accommodate at most one person.

Some Elementary Counting

A Counting Problem

Suppose we were meeting in person, the room had n seats, and there were $m \leq n$ attendees. How many ways would there be to seat everyone?


More explicitly, we assume that:

- each attendee gets one seat (i.e., at least one **and** at most one),
- and a seat can accommodate at most one person.

Answer: $n^{\underline{m}} = n \cdot (n - 1) \cdots (n - m + 1)$.

Note: this problem is equivalent to counting $[m] \rightarrow [n]$ injections.

Let's Express This Problem in Logic!



Let's Express This Problem in Logic!

- Let M and N be sets (i.e., **domains**) such that $|M| = m$, and $|N| = n$
- Let $P \subseteq M \times N$ be a relation (i.e., **predicate**) over sets M and N
- We can describe all of the constraints in first-order logic

Let's Express This Problem in Logic!

- Let M and N be sets (i.e., **domains**) such that $|M| = m$, and $|N| = n$
- Let $P \subseteq M \times N$ be a relation (i.e., **predicate**) over sets M and N
- We can describe all of the constraints in first-order logic
 - each attendee gets a seat (i.e., at least one seat)

$$\forall x \in M. \exists y \in N. P(x, y)$$

Let's Express This Problem in Logic!

- Let M and N be sets (i.e., **domains**) such that $|M| = m$, and $|N| = n$
- Let $P \subseteq M \times N$ be a relation (i.e., **predicate**) over sets M and N
- We can describe all of the constraints in first-order logic
 - each attendee gets a seat (i.e., at least one seat)

$$\forall x \in M. \exists y \in N. P(x, y)$$

- one person cannot occupy multiple seats

$$\forall x \in M. \forall y, z \in N. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

Let's Express This Problem in Logic!

- Let M and N be sets (i.e., **domains**) such that $|M| = m$, and $|N| = n$
- Let $P \subseteq M \times N$ be a relation (i.e., **predicate**) over sets M and N
- We can describe all of the constraints in first-order logic
 - each attendee gets a seat (i.e., at least one seat)

$$\forall x \in M. \exists y \in N. P(x, y)$$

- one person cannot occupy multiple seats

$$\forall x \in M. \forall y, z \in N. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

- one seat cannot accommodate multiple attendees

$$\forall w, x \in M. \forall y \in N. P(w, y) \wedge P(x, y) \Rightarrow w = x$$

Let's Express This Problem in Logic!

- Let M and N be sets (i.e., **domains**) such that $|M| = m$, and $|N| = n$
- Let $P \subseteq M \times N$ be a relation (i.e., **predicate**) over sets M and N
- We can describe all of the constraints in first-order logic
 - each attendee gets a seat (i.e., at least one seat)

$$\forall x \in M. \exists y \in N. P(x, y)$$

- one person cannot occupy multiple seats

$$\forall x \in M. \forall y, z \in N. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

- one seat cannot accommodate multiple attendees

$$\forall w, x \in M. \forall y \in N. P(w, y) \wedge P(x, y) \Rightarrow w = x$$

The first two sentences constrain P to be a function, and the last one makes it injective.

Let's Express This Problem in Logic!

- Let M and N be sets (i.e., **domains**) such that $|M| = m$, and $|N| = n$
- Let $P \subseteq M \times N$ be a relation (i.e., **predicate**) over sets M and N
- We can describe all of the following in first order logic

- each attendee

- one person can

$\forall x$

- one seat cannot accommodate multiple attendees

$$\forall w, x \in M. \forall y \in N. P(w, y) \wedge P(x, y) \Rightarrow w = x$$

The first two sentences constrain P to be a function, and the last one makes it injective.



Overview of the Problem

- **First-order model counting** is the problem of counting the models of a sentence in first-order logic.
- The **(symmetric) weighted** variation of the problem adds weights (e.g., probabilities) to predicates.
- Thus, SWFOMC can also be used for efficient **probabilistic inference** in relational models.
- None of the (implemented) (SW)FOMC algorithms are able to count, e.g., **injective** and **bijective** functions.

Recursion to the Rescue!

- Optimal time complexity to compute n^m is $\Theta(\log m)$
-

$$f(m, n) = \begin{cases} 1 & \text{if } m = 0 \text{ and } n = 0 \\ 0 & \text{if } m > 0 \text{ and } n = 0 \\ f(m, n - 1) + mf(m - 1, n - 1) & \text{otherwise.} \end{cases}$$