

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

Algorithm Selection for Maximum Common Subgraph

Paulius Dilkas

FATA seminar

16th January 2018

Algorithm selection

Definition (Bischl et al. 2016)

Given a set \mathcal{I} of problem instances, a space of algorithms \mathcal{A} , and a performance measure $m: \mathcal{I} \times \mathcal{A} \rightarrow \mathbb{R}$, the *algorithm selection problem* is to find a mapping $s: \mathcal{I} \rightarrow \mathcal{A}$ that optimises $\mathbb{E}[m(i, s(i))]$.

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?


Future work

Algorithm selection

Definition (Bischl et al. 2016)

Given a set \mathcal{I} of problem instances, a space of algorithms \mathcal{A} , and a performance measure $m: \mathcal{I} \times \mathcal{A} \rightarrow \mathbb{R}$, the *algorithm selection problem* is to find a mapping $s: \mathcal{I} \rightarrow \mathcal{A}$ that optimises $\mathbb{E}[m(i, s(i))]$.

LLAMA (Kotthoff 2013)



Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

Algorithms

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

- MCSPLIT, MCSPLIT ↓
 - (McCreesh, Prosser and Trimble 2017)
- clique encoding
 - (McCreesh, Ndiaye et al. 2016)
- k ↓
 - (Hoffmann, McCreesh and Reilly 2017)

Labelling

Data from Foggia, Sansone and Vento 2001; Santo et al. 2003
(81400 pairs of graphs)

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

Labelling

Data from Foggia, Sansone and Vento 2001; Santo et al. 2003
(81400 pairs of graphs)

Definition

A *vertex-labelled graph* is a 3-tuple $G = (V, E, \mu)$, where $\mu: V \rightarrow \{0, \dots, N-1\}$ is a vertex labelling function, for some $N \in \mathbb{N}$.

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

Labelling

Data from Foggia, Sansone and Vento 2001; Santo et al. 2003
(81400 pairs of graphs)

Definition

A *vertex-labelled graph* is a 3-tuple $G = (V, E, \mu)$, where $\mu: V \rightarrow \{0, \dots, N-1\}$ is a vertex labelling function, for some $N \in \mathbb{N}$.

Definition

A graph $G = (V, E, \mu)$ is said to have a $p\%$ (*vertex*) *labelling* if

$$N = \max \left\{ 2^n : n \in \mathbb{N}, 2^n < \left\lfloor \frac{p}{100\%} \times |V| \right\rfloor \right\}.$$

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

Labelling

Definition

A graph $G = (V, E, \mu)$ is said to have a $p\%$ (vertex) labelling if

$$N = \max \left\{ 2^n : n \in \mathbb{N}, 2^n < \left\lfloor \frac{p}{100\%} \times |V| \right\rfloor \right\}.$$

- 5% labelling - 20 vertices per label on average
- 50% labelling - 2 vertices per label on average

Labelling

Definition

A graph $G = (V, E, \mu)$ is said to have a $p\%$ (*vertex*) *labelling* if

$$N = \max \left\{ 2^n : n \in \mathbb{N}, 2^n < \left\lfloor \frac{p}{100\%} \times |V| \right\rfloor \right\}.$$

- 5% labelling - 20 vertices per label on average
- 50% labelling - 2 vertices per label on average
- Typical values explored: 33%, 50%, 75%

Labelling

Definition

A graph $G = (V, E, \mu)$ is said to have a $p\%$ (vertex) labelling if

$$N = \max \left\{ 2^n : n \in \mathbb{N}, 2^n < \left\lfloor \frac{p}{100\%} \times |V| \right\rfloor \right\}.$$

- 5% labelling - 20 vertices per label on average
- 50% labelling - 2 vertices per label on average
- Typical values explored: 33%, 50%, 75%
- In my data: 5%, 10%, 15%, 20%, 25%, 33%, 50%

Labelling

Definition

A graph $G = (V, E, \mu)$ is said to have a $p\%$ (*vertex*) *labelling* if

$$N = \max \left\{ 2^n : n \in \mathbb{N}, 2^n < \left\lfloor \frac{p}{100\%} \times |V| \right\rfloor \right\}.$$

- 5% labelling - 20 vertices per label on average
- 50% labelling - 2 vertices per label on average
- Typical values explored: 33%, 50%, 75%
- In my data: 5%, 10%, 15%, 20%, 25%, 33%, 50%
- 3 subproblems
 - no labels
 - vertex labels
 - vertex and edge labels

Features (34 in total)

1–8 are from Kotthoff, McCreesh and Solnon 2016

- 1 number of vertices
- 2 number of edges
- 3 mean/max degree
- 4 density
- 5 mean/max distance between pairs of vertices
- 6 number of loops
- 7 proportion of vertex pairs with distance $\geq 2, 3, 4$
- 8 connectedness
- 9 standard deviation of degrees
- 10 labelling percentage
- 11 ratios of features 1–5

Random forests (Breiman 2001)

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling


Features

Random
forests

Results

What happens
when labelling
changes?

Future work



Source: Tae-Kyun Kim & Bjorn Stenger, Intelligent Systems and Networks (ISN) Research Group, Imperial College London

Results

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features


Random
forests

Results

What happens
when labelling
changes?

Future work

Unlabelled



Results (27%)

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features


Random
forests

Results

What happens
when labelling
changes?

Future work

Unlabelled



Results

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling


Features

Random
forests

Results

What happens
when labelling
changes?

Future work



Results (86%)

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling


Features

Random
forests

Results

What happens
when labelling
changes?

Future work



Results

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features


Random
forests

Results

What happens
when labelling
changes?

Future work

Both labels



Results (88%)

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features


Random
forests

Results

What happens
when labelling
changes?

Future work

Both labels



Errors

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

- Out-of-bag error
- For each algorithm
 - $1 - \text{recall}$

Definition

For an algorithm A , *recall* (sensitivity) is

$$\frac{\text{the number of instances that were correctly predicted as } A}{\text{the number of instances where } A \text{ is the correct prediction}}.$$

Errors (%)

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

Error	Labelling		
	no	vertex	both
out-of-bag	17	13	14
clique	30	8	7
McSPIT	29	22	29
McSPIT ↓	11	11	11
k ↓	80		

Convergence of errors for unlabelled graphs

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling


Features

Random
forests

Results

What happens
when labelling
changes?

Future work



What happens when labelling changes?

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling



Features

Random
forests

Results

What happens
when labelling
changes?

Future work



What happens when labelling changes?

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features


Random
forests

Results


What happens
when labelling
changes?

Future work


Vertex labels




Both labels



Vertex labels



Both labels



Future work

Algorithm
Selection for
Maximum
Common
Subgraph

Paulius Dilkas

Algorithm
selection

Algorithms

Labelling

Features

Random
forests

Results

What happens
when labelling
changes?

Future work

- Relationships between clique algorithm's performance and properties of the association graph
- How the association graph changes after making a decision
- Can $k \downarrow$ and clique work together?