

Generalising Weighted Model Counting

Paulius Dilkas

University of Edinburgh, UK

Viva Voce



THE UNIVERSITY OF EDINBURGH

informatics



EDINBURGH CENTRE FOR

ROBOTICS



Engineering and
Physical Sciences
Research Council

Weighted Model Counting

Example

We have a biased coin that has a probability $p \in [0, 1]$ of landing heads. What is the probability that it lands heads **at least once** if we toss it **three times**?

In Propositional Logic...

- ▶ Formula: $x_1 \vee x_2 \vee x_3$
- ▶ Weights: $w(x_i) = p$, $w(\neg x_i) = 1 - p$ for $i = 1, 2, 3$
- ▶ Models: $\mathcal{P}(\{x_1, x_2, x_3\}) \setminus \{\emptyset\}$

In First-Order Logic...


- ▶ Formula: $\exists x \in \{1, 2, 3\}. P(x)$
- ▶ Weights: $w(P) = p$, $w(\neg P) = 1 - p$
- ▶ Models: $\mathcal{P}(\{P(1), P(2), P(3)\}) \setminus \{\emptyset\}$

Significance of WMC and This Work


Applications

- ▶ Probabilistic inference: graphical models, statistical relational models, probabilistic programming
- ▶ Neural-symbolic artificial intelligence
- ▶ Bioinformatics
- ▶ Robotics
- ▶ Natural language processing
- ▶ Enumerative combinatorics

Impact


- | | | |
|------------------------------|---|-------------------------|
| ▶ Suitable WMC algorithm | | ▶ provable tractability |
| ▶ Appropriate input format |  | ▶ experimental speedup |
| ▶ Lifted reasoning | | |
| ▶ Expressive data structures | | |

Contributions



Generalising Representations

- ▶ Beyond weights on literals
- ▶ Circuits for recursion



Random-Instance Experiments

- ▶ Application-specific parameters
 - ▶ PROLOG predicates, arities
- ▶ Parameters of hardness
 - ▶ density, primal treewidth

Generalising Representations

WMC and Measures on Boolean Algebras

Definition

A **measure** is a function $\mu: \mathcal{P}(\mathcal{P}(X)) \rightarrow \mathbb{R}_{\geq 0}$ such that:

- ▶ $\mu(\perp) = 0$;
- ▶ $\mu(x \vee y) = \mu(x) + \mu(y)$ whenever $x \wedge y = \perp$.

Observation

WMC corresponds to the process of calculating the value of $\mu(x)$ for some $x \in \mathcal{P}(\mathcal{P}(X))$.

WMC and Measures on Boolean Algebras

Definition

A **measure** is a function $\mu: \mathcal{P}(\mathcal{P}(X)) \rightarrow \mathbb{R}_{\geq 0}$ such that:

- ▶ $\mu(\perp) = 0$;
- ▶ $\mu(x \vee y) = \mu(x) + \mu(y)$ whenever $x \wedge y = \perp$.

Observation

WMC corresponds to the process of calculating the value of $\mu(x)$ for some $x \in \mathcal{P}(\mathcal{P}(X))$.

Observation

Classical WMC is only able to evaluate **factorable** measures (c.f., a collection of mutually independent random variables).

Theorem (Informal Version)

It is always possible to add more variables to turn a non-factorable measure into a factorable measure.

However, that is not necessarily a good idea!

Transforming Known WMC Encodings into PBP

For any propositional formula ϕ over a set of variables X and $p, q \in \mathbb{R}$, let $[\phi]_q^p: 2^X \rightarrow \mathbb{R}$ be the pseudo-Boolean function defined as

$$[\phi]_q^p(Y) := \begin{cases} p & \text{if } Y \models \phi \\ q & \text{otherwise} \end{cases}$$

for any $Y \subseteq X$.

Example

Clauses	In CNF	Pseudo-Boolean Functions
$\neg x \Rightarrow p$	$x \vee p$	$[\neg x]_1^{0.2}$
$p \Rightarrow \neg x$	$\neg x \vee \neg p$	
$x \Rightarrow q$	$\neg x \vee q$	$[x]_1^{0.8}$
$q \Rightarrow x$	$x \vee \neg q$	
$\neg x$	$\neg x$	$[\neg x]_0^1$

$[x]_0^{0.8}$

$[\neg x]_0^1$

First-Order Logic and Recursive Computations


Example (Counting $P: M \rightarrow N$ Injections)

Input Formula

$$\forall x \in M. \exists y \in N. P(x, y)$$

$$\forall x \in M. \forall y, z \in N. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

$$\forall w, x \in M. \forall y \in N. P(w, y) \wedge P(x, y) \Rightarrow w = x$$



Recursive Solution

$$f(m, n) = \begin{cases} 1 & \text{if } m = 0 \text{ and } n = 0 \\ 0 & \text{if } m > 0 \text{ and } n = 0 \\ f(m, n - 1) + m \cdot f(m - 1, n - 1) & \text{otherwise.} \end{cases}$$

Resulting Improvements to Counting Functions

Let M and N be two sets with cardinalities $|M| = m$ and $|N| = n$. The new compilation rules enable FORCLIFT to efficiently count $M \rightarrow N$ functions such as:

- ▶ injections in $\Theta(mn)$ time
 - ▶ best: $\Theta(m)$
- ▶ partial injections in $\Theta(mn)$ time
 - ▶ best: $\Theta(\min\{m, n\}^2)$
- ▶ bijections in $\Theta(m)$ time
 - ▶ optimal!


Random-Instance Experiments

A Constraint Model for (Probabilistic) Logic Programs

```
0.2::stress(P):-person(P).
0.3::influences(P1,P2):-friend(P1,P2).
0.1::cancer_spont(P):-person(P).
0.3::cancer_smoke(P):-person(P).
    smokes(X):-stress(X).
    smokes(X):-smokes(Y),influences(Y,X).
    cancer(P):-cancer_spont(P).
    cancer(P):-smokes(P),cancer_smoke(P).
    person(mary).
    person(albert).
    friend(albert,mary).
```

- predicates, arities
- variables
- constants
- probabilities
- length
- complexity

PROBLOG Inference Algorithms on Random Instances



Random WMC Instances

Key Idea

Parameter $\rho \in [0, 1]$ biases the probability distribution towards adding variables that would introduce fewer new edges in the primal graph.

Example

Partially-constructed formula:


$$(\neg x_5 \vee x_2 \vee x_1) \wedge (x_5 \vee ? \vee ?).$$

Base probability of each variable being chosen:

$$\frac{1 - \rho}{4}.$$


Both x_1 and x_2 get a bonus probability of $\rho/2$ for each being the endpoint of **one** out of the **two** neighbourhood edges.

Its primal graph:



How WMC Algorithms Scale w.r.t. Primal Treewidth

We fit the model $\ln t \sim \alpha w + \beta$, i.e., $t \sim e^\beta (e^\alpha)^w$, where t is runtime, and w is primal treewidth.



Summary

What Have We Learned?

- ▶ Pseudo-Boolean functions as an alternative to literal weights
- ▶ Cycles in graphs that encode recursive calls
- ▶ WMC algorithms based on algebraic decision diagrams are fundamentally different:
 - ▶ they can support non-literal weights
 - ▶ their running time depends on the numerical values of weights
 - ▶ they peak at higher density
 - ▶ they scale worse w.r.t. primal treewidth

Future Directions

- ▶ PBP: new encodings, kernelization, pseudo-Boolean solvers
- ▶ WFOMC: full automation and new applications (e.g., in AI)