

# Generating Random Logic Programs Using Constraint Programming

**Paulius Dilkas**<sup>1</sup>    Vaishak Belle<sup>1,2</sup>

<sup>1</sup>University of Edinburgh, Edinburgh, UK

<sup>2</sup>Alan Turing Institute, London, UK

FMAI 2021



THE UNIVERSITY OF EDINBURGH

**informatics**



EDINBURGH CENTRE FOR  
**ROBOTICS**




Engineering and  
Physical Sciences  
Research Council

# Probabilistic Logic Programs (PROBLOG)

“Smokers” (Domingos et al. 2008; Fierens et al. 2015)

```
0.2::stress(P):-person(P).
0.3::influences(P1,P2):-friend(P1,P2).
0.1::cancer_spont(P):-person(P).
0.3::cancer_smoke(P):-person(P).
    smokes(X):-stress(X).
    smokes(X):-smokes(Y),influences(Y,X).
    cancer(P):-cancer_spont(P).
    cancer(P):-smokes(P),cancer_smoke(P).
    person(michelle).
    person(timothy).
    friend(timothy,michelle).
```

# Applications



Moldovan et al. 2012


Q1: In a group of 10 people, 60 percent have brown eyes. Two people are to be selected at random from the group. What is the probability that neither person selected will have brown eyes?

Q2: Mike has a bag of marbles with 4 white, 8 blue, and 6 red marbles. He pulls out one marble from the bag and it is red. What is the probability that the second marble he pulls out of the bag is white?

Dries et al. 2017

```
is_malignant(Case):-
    biopsyProcedure(Case,usCore),
    changes_Sizeinc(Case,missing),
    feature_shape(Case).
is_malignant(Case):-
    assoFinding(Case,asymmetry),
    breastDensity(Case,scatteredFDensities),
    vacuumAssisted(Case,yes).
is_malignant(Case):-
    needleGauge(Case,9),
    offset(Case,14),
    vacuumAssisted(Case,yes).
```

Côrte-Real, Dutra, and Rocha 2017



De Maeyer et al. 2013

# How Many Programs Are Used to Test Algorithms?

# How Many Programs Are Used to Test Algorithms?

## Anytime Inference in Probabilistic Logic Programs with $T_P$ -Compilation

Jonas Vlasselaer, Guy Van den Broeck, **4** Angelika Kimmig, Wannes Meert, Luc De Raedt

Department of Computer Science

KU Leuven, Belgium

firstname.lastname@cs.kuleuven.be

# How Many Programs Are Used to Test Algorithms?

## Anytime Inference in Probabilistic Logic Programs with $T_P$ -Compilation

Jonas Vlasselaer, Guy Van den Broeck, Angelika Kimmig, Wannes Meert, Luc De Raedt

Department of Computer Science

KU Leuven, Belgium

firstname.lastname@cs.kuleuven.be

## *Inference and learning in probabilistic logic programs using weighted Boolean formulas*

DAAN FIERENS, GUY VAN DEN BROECK, JORIS RENKENS,  
DIMITAR SHTERIONOV, BENJAMIN GUTMANN, INGO THON,  
GERDA JANSSENS and LUC DE RAEDT

Department of Computer Science, KU Leuven, Celestijnenlaan 200A, 3001 Heverlee, Belgium  
(e-mail: FirstName.LastName@cs.kuleuven.be)

# How Many Programs Are Used to Test Algorithms?

## Anytime Inference in Probabilistic Logic Programs with $T_p$ -Compilation

Jonas Vlasselaer, Guy Van den Broeck, Angelika Kimmig, Wannes Meert, Luc De Raedt

Department of Computer Science

KU Leuven, Belgium

firstname.lastname@cs.kuleuven.be

## *Inference and learning in probabilistic logic programs using weighted Boolean formulas*

DAAN FIERENS, GUY VAN DEN BROECK, JORIS RENKENS,  
DIMITAR SHTERIONOV, BENJAMIN GUTMANN, INGO THON,  
GERDA JANSSENS and LUC DE RAEDT

Department of Computer Science, KU Leuven, Celestijnenlaan 200A, 3001 Heverlee, Belgium  
(e-mail: FirstName.LastName@cs.kuleuven.be)

## *k*-Optimal: a novel approximate inference algorithm for ProbLog

Joris Renkens · Guy Van den Broeck · Siegfried Nijssen

# How Many Programs Are Used to Test Algorithms?

## Anytime Inference in Probabilistic Logic Programs with $T_p$ -Compilation

Jonas Vlasselaer, Guy Van den Broeck, Angelika Kimmig, Wannes Meert, Luc De Raedt

Department of Computer Science  
KU Leuven, Belgium  
firstname.lastname@cs.kuleuven.be

## *Inference and learning in probabilistic logic programs using weighted Boolean formulas*

DAAN FIERENS, GUY VAN DEN BROECK, JORIS RENKENS,  
DIMITAR SHTERIONOV, BENJAMIN GUTMANN, INGO THON,  
GERDA JANSSENS and LUC DE RAEDT

Department of Computer Science, KU Leuven, Celestijnenlaan 200A, 3001 Heverlee, Belgium  
(e-mail: FirstName.LastName@cs.kuleuven.be)

## ***k*-Optimal: a novel approximate inference algorithm for ProbLog**

Joris Renkens · Guy Van den Broeck · Siegfried Nijssen

## On the Efficient Execution of ProbLog Programs

Angelika Kimmig<sup>1</sup>, Vitor Santos Costa<sup>2</sup>, Ricardo Rocha<sup>2</sup>, Bart Demoen<sup>1</sup>, and  
Luc De Raedt<sup>1</sup>



# How Many Programs Are Used to Test Algorithms?

## Anytime Inference in Probabilistic Logic Programs with $T_p$ -Compilation

4  
Jonas Vlasselaer, Guy Van den Broeck, Angelika Kimmig, Wannes Meert, Luc De Raedt  
Department of Computer Science  
KU Leuven, Belgium  
firstname.lastname@cs.kuleuven.be

## *Inference and learning in probabilistic logic programs using weighted Boolean formulas*

3  
DAAN FIERENS, GUY VAN DEN BROECK, JORIS RENKENS,  
DIMITAR SHTERIONOV, BENNO GUTMANN, INGO THON,  
GERDA JANSSENS and LUC DE RAEDT

Department of Computer Science, KU Leuven, Celestijnenlaan 200A, 3001 Heverlee, Belgium  
(e-mail: FirstName.LastName@cs.kuleuven.be)

## ***k*-Optimal: a novel approximate inference algorithm for ProbLog**

1  
Joris Renkens · Guy Van den Broeck · Siegfried Nijssen

## On the Efficient Execution of ProbLog Programs

1  
Angelika Kimmig<sup>1</sup>, Vítor Santos Costa<sup>2</sup>, Ricardo Rocha<sup>2</sup>, Bart Demoen<sup>1</sup>, and  
Luc De Raedt<sup>1</sup>

## *On the Implementation of the Probabilistic Logic Programming Language ProbLog*

1  
Angelika Kimmig, Bart Demoen and Luc De Raedt

Department Computerwetenschappen, K.U. Leuven  
Celestijnenlaan 200A - bus 2402, B-3001 Heverlee, Belgium  
(e-mail: {Angelika.Kimmig,Bart.Demoen,Luc.DeRaedt}@cs.kuleuven.be)

Vítor Santos Costa and Ricardo Rocha

CRACS & INESC-Porto LA, Faculty of Sciences, University of Porto  
R. do Campo Alegre 1021/1055, 4169-007 Porto, Portugal  
(e-mail: {vsc,ricroc}@dcc.fc.up.pt)

# How Many Programs Are Used to Test Algorithms?

## Anytime Inference in Probabilistic Logic Programs with $T_p$ -Compilation

Jonas Vlasselaer, Guy Van den Broeck, Angelika Kimmig, Wannes Meert, Luc De Raedt  
 Department of Computer Science  
 KU Leuven, Belgium  
 firstname.lastname@cs.kuleuven.be

## *Inference and learning in probabilistic logic programs using weighted Boolean formulas*

DAAN FIERENS, GUY VAN DEN BROECK, JORIS RENKENS,  
 DIMITAR SHTERIONOV, BERND GUTMANN, INGO THON,  
 GERDA JANSSENS and LUC DE RAEDT

Department of Computer Science, KU Leuven, Celestijnenlaan 200A, 3001 Heverlee, Belgium  
 (e-mail: FirstName.LastName@cs.kuleuven.be)

## *k*-Optimal: a novel approximate inference algorithm for ProbLog

Joris Renkens · Guy Van den Broeck · Siegfried Nijssen

## On the Efficient Execution of ProbLog Programs

Angelika Kimmig<sup>1</sup>, Vítor Santos Costa<sup>2</sup>, Ricardo Rocha<sup>2</sup>, Bart Demoen<sup>1</sup>, and  
 Luc De Raedt<sup>1</sup>

## *On the Implementation of the Probabilistic Logic Programming Language ProbLog*

Angelika Kimmig, Bart Demoen and Luc De Raedt

Department Computerwetenschappen, K.U. Leuven  
 Celestijnenlaan 200A - bus 2402, B-3001 Heverlee, Belgium  
 (e-mail: {Angelika.Kimmig,Bart.Demoen,Luc.DeRaedt}@cs.kuleuven.be)

Vítor Santos Costa and Ricardo Rocha

CRACS & INESC-Porto LA, Faculty of Sciences, University of Porto  
 R. do Campo Alegre 1021/1055, 4169-007 Porto, Portugal  
 (e-mail: {vsc,ricroc}@dcc.fc.up.pt)

## ProbLog Technology for Inference in a Probabilistic First Order Logic

Maurice Bruynooghe and Theofrastos Mantaftakis and Angelika Kimmig and Bernd Gutmann  
 and Joost Vennekens and Gerda Janssens and Luc De Raedt<sup>1</sup>

# Outline

Introduction

The Constraint Model

Inference

Summary

## What Characterises a (Probabilistic) Logic Program?

```
0.2::stress(P):-person(P).
0.3::influences(P1,P2):-friend(P1,P2).
0.1::cancer_spont(P):-person(P).
0.3::cancer_smoke(P):-person(P).
    smokes(X):-stress(X).
    smokes(X):-smokes(Y),influences(Y,X).
    cancer(P):-cancer_spont(P).
    cancer(P):-smokes(P),cancer_smoke(P).
    person(michelle).
    person(timothy).
    friend(timothy,michelle).
```

# What Characterises a (Probabilistic) Logic Program?

0.2::**stress**(P):-**person**(P).

0.3::**influences**(P<sub>1</sub>, P<sub>2</sub>):-**friend**(P<sub>1</sub>, P<sub>2</sub>).

0.1::**cancer\_spont**(P):-**person**(P).

0.3::**cancer\_smoke**(P):-**person**(P).

**smokes**(X):-**stress**(X).

**smokes**(X):-**smokes**(Y), **influences**(Y, X).

**cancer**(P):-**cancer\_spont**(P).

**cancer**(P):-**smokes**(P), **cancer\_smoke**(P).

**person**(*michelle*).

**person**(*timothy*).

**friend**(*timothy*, *michelle*).

- predicates, arities

# What Characterises a (Probabilistic) Logic Program?

```
0.2::stress(P):-person(P).
0.3::influences(P1,P2):-friend(P1,P2).
0.1::cancer_spont(P):-person(P).
0.3::cancer_smoke(P):-person(P).
    smokes(X):-stress(X).
    smokes(X):-smokes(Y),influences(Y,X).
cancer(P):-cancer_spont(P).
cancer(P):-smokes(P),cancer_smoke(P).
person(michelle).
person(timothy).
friend(timothy,michelle).
```

- predicates, arities
- variables

# What Characterises a (Probabilistic) Logic Program?

0.2::stress(P):-person(P).

0.3::influences(P<sub>1</sub>,P<sub>2</sub>):-friend(P<sub>1</sub>,P<sub>2</sub>).

0.1::cancer\_spont(P):-person(P).

0.3::cancer\_smoke(P):-person(P).

smokes(X):-stress(X).

smokes(X):-smokes(Y),influences(Y,X).

cancer(P):-cancer\_spont(P).

cancer(P):-smokes(P),cancer\_smoke(P).

person(*michelle*).

person(*timothy*).

friend(*timothy*,*michelle*).

- predicates, arities
- variables
- constants

# What Characterises a (Probabilistic) Logic Program?

0.2::stress(P):-person(P).

0.3::influences(P<sub>1</sub>,P<sub>2</sub>):-friend(P<sub>1</sub>,P<sub>2</sub>).

0.1::cancer\_spont(P):-person(P).

0.3::cancer\_smoke(P):-person(P).

smokes(X):-stress(X).

smokes(X):-smokes(Y),influences(Y,X).

cancer(P):-cancer\_spont(P).

cancer(P):-smokes(P),cancer\_smoke(P).

person(*michelle*).

person(*timothy*).

friend(*timothy*,*michelle*).

- predicates, arities
- variables
- constants
- probabilities



# What Characterises a (Probabilistic) Logic Program?

```
0.2::stress(P):-person(P).
0.3::influences(P1,P2):-friend(P1,P2).
0.1::cancer_spont(P):-person(P).
0.3::cancer_smoke(P):-person(P).
    smokes(X):-stress(X).
    smokes(X):-smokes(Y),influences(Y,X).
cancer(P):-cancer_spont(P).
cancer(P):-smokes(P),cancer_smoke(P).
person(michelle).
person(timothy).
friend(timothy,michelle).
```

- predicates, arities
- variables
- constants
- probabilities
- length

# What Characterises a (Probabilistic) Logic Program?

```
0.2::stress(P):-person(P).
0.3::influences(P1,P2):-friend(P1,P2).
0.1::cancer_spont(P):-person(P).
0.3::cancer_smoke(P):-person(P).
    smokes(X):-stress(X).
    smokes(X):-smokes(Y),influences(Y,X).
cancer(P):-cancer_spont(P).
cancer(P):-smokes(P),cancer_smoke(P).
person(michelle).
person(timothy).
friend(timothy,michelle).
```


- predicates, arities
- variables
- constants
- probabilities
- length
- complexity

## Formulas As Trees

$$\neg p(X) \vee (q(X) \wedge r(X))$$


# Formulas As Trees

$$\neg p(X) \vee (q(X) \wedge r(X))$$




# Formulas As Trees

$$\neg p(X) \vee (q(X) \wedge r(X))$$




0	0	0	1	2	2
∨	¬	∧	p(X)	q(X)	r(X)

## Predicate Dependency Graph




# Stratification and Negative Cycles

```
0.1::friend(X,Y):- \+ smokes(Y).
```




# Stratification and Negative Cycles

```
0.1::friend(X,Y):- \+ smokes(Y).
```







# Predicate Independence: friend $\perp$ stress




# Predicate Independence: friend $\perp$ stress




# Predicate Independence: $\text{friend} \perp \text{stress}$




# Predicate Independence: friend $\perp$ stress



# Predicate Independence: friend $\perp$ stress



# Predicate Independence: $\text{friend} \perp \text{stress}$



# Inference and Knowledge Compilation

**NNF** negation normal form

**d-DNNF** deterministic decomposable negation normal form

**BDD** binary decision diagrams

**SDD** sentential decision diagrams

# Example Diagrams for $C \wedge (A \vee \neg B)$




Figure: NNF




Figure: BDD




Figure: d-DNNF





Figure: SDD



# Properties of Programs vs. Inference Algorithms

Facts: `friend(timothy, michelle).`

Rules: `0.2::stress(P):-person(P).`



## Summary

- The model can generate (approximately) realistic instances of reasonable size.
- Open questions for future work:
  - Can we ensure uniform sampling?
  - Why do all of the algorithms behave so similarly?
  - Why does independence have no effect on inference time?