

Towards Practical First-Order Model Counting

Ananth K. Kidambi¹ Guramrit Singh¹ **Paulius Dilkas**^{2,3}
Kuldeep S. Meel^{4,2}

¹IIT Bombay, India

²University of Toronto, Canada

³Vector Institute, Canada

⁴Georgia Tech, USA

SAT 2025

Motivation

Example Setting

- ▶ Let Δ be a set of cardinality n
- ▶ Suppose we want to count all $P \subseteq \Delta^2$ (as a function of n) that are:
 - ▶ functions,
 - ▶ bijections,
 - ▶ partial orders,
 - ▶ symmetric,
 - ▶ transitive,
 - ▶ etc.

Motivation

Example Setting

- ▶ Let Δ be a set of cardinality n
- ▶ Suppose we want to count all $P \subseteq \Delta^2$ (as a function of n) that are:
 - ▶ functions,
 - ▶ bijections,
 - ▶ partial orders,
 - ▶ symmetric,
 - ▶ transitive,
 - ▶ etc.
- 🗨️ Propositional model counting ($\#SAT$) is $\#P$ -complete
- 👍 But many of these counting problems have efficient solutions
- ▶ And we can find them using first-order model counting
 - ▶ i.e., reasoning about sets, subsets, and arbitrary elements without grounding them

First-Order Model Counting

The Problem with CRANE

A Solution Produced for the Bijection-Counting Problem

$$f(m, n) = \sum_{l=0}^n \binom{n}{l} (-1)^{n-l} g(l, m),$$
$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

The Problem with CRANE

A Solution Produced for the Bijection-Counting Problem

$$f(m, n) = \sum_{l=0}^n \binom{n}{l} (-1)^{n-l} g(l, m),$$
$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

Issues

Completeness: what are the base cases of g ?

Usability: how do I compute, e.g., $f(7, 7)$?

Knowledge Compilation Workflow (1/2)

1. Use CRANE to compile ϕ into a set of equations \mathcal{E}

Knowledge Compilation Workflow (1/2)

1. Use CRANE to compile ϕ into a set of equations \mathcal{E}
2. Simplify them, e.g.,

$$g(l, m) = \sum_{k=0}^m [0 \leq k \leq 1] \binom{m}{k} g(l-1, m-k)$$

becomes

$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

Knowledge Compilation Workflow (1/2)

1. Use CRANE to compile ϕ into a set of equations \mathcal{E}
2. Simplify them, e.g.,

$$g(l, m) = \sum_{k=0}^m [0 \leq k \leq 1] \binom{m}{k} g(l-1, m-k)$$

becomes

$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

3. (\Rightarrow) Identify a sufficient set of base cases
 - ▶ e.g., $\{g(0, m), g(l, 0)\}$

Knowledge Compilation Workflow (2/2)

4. For each base case:

$$g(0, m)$$

$$g(l, 0)$$

Knowledge Compilation Workflow (2/2)

4. For each base case:

$g(0, m)$



$\forall x \in \Gamma. S(x) \vee \neg S(x)$

4.1. (\Rightarrow) Construct the corr. sentence


$g(l, 0)$



\top


Knowledge Compilation Workflow (2/2)

4. For each base case:



4.1. (\Rightarrow) Construct the corr. sentence

4.2. Recurse



Knowledge Compilation Workflow (2/2)

4. For each base case:

$$\begin{array}{c} g(0, m) \\ \downarrow \\ \forall x \in \Gamma. S(x) \vee \neg S(x) \\ \downarrow \\ g(0, m) = 0^m \end{array}$$


4.1. (\Rightarrow) Construct the corr. sentence

4.2. Recurse

$$\begin{array}{c} g(l, 0) \\ \downarrow \\ \top \\ \downarrow \\ g(l, 0) = 1 \end{array}$$


Knowledge Compilation Workflow (2/2)

4. For each base case:




Knowledge Compilation Workflow (2/2)

4. For each base case:



Knowledge Compilation Workflow (2/2)

4. For each base case:




Finding (a Sufficient Set of) Base Cases

Outline

1. For every function call:
 - 1.1 For every argument of the form *var* – *const*:
 - 1.1.1 Replace the signature parameter with 0, 1, ..., *const* – 1
 - 1.2 For every argument of the form *const*:
 - 1.2.1 Replace the corresponding signature parameter with *const*

Example

The signature of g is $g(l, m)$.



Theoretical Results

Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

Theoretical Results

Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

Proof (hint).

Each recursive call eliminates a domain.



Theoretical Results

Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

Proof (hint).

Each recursive call eliminates a domain.



Theorem

*The **evaluation** of a recursive function always **terminates**.*

Theoretical Results

Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

Proof (hint).

Each recursive call eliminates a domain.



Theorem

*The **evaluation** of a recursive function always **terminates**.*

Proof (hints).

- ▶ There exists a **topological ordering** of functions
- ▶ All function calls follow the **structure** from the previous slide
- ▶ Some common-sense assumptions about the **evaluation order** and previous work



From a Base Case to a Sentence

Preliminaries

- ▶ CRANE associates each function f with a sentence ϕ such that $\text{CRANE}(\phi)$ produces the definition of f
- ▶ There is a bijection between the parameters of f and the domains of ϕ

Benchmarks

► Friends & Smokers

$$(\forall x, y \in \Delta. S(x) \wedge F(x, y) \rightarrow S(y)) \wedge (\forall x \in \Delta. S(x) \rightarrow C(x))$$

Benchmarks

► Friends & Smokers

$$(\forall x, y \in \Delta. S(x) \wedge F(x, y) \rightarrow S(y)) \wedge (\forall x \in \Delta. S(x) \rightarrow C(x))$$

► Functions

$$(\forall x \in \Gamma. \exists y \in \Delta. P(x, y)) \wedge \\ (\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \rightarrow y = z)$$

Benchmarks

► Friends & Smokers

$$(\forall x, y \in \Delta. S(x) \wedge F(x, y) \rightarrow S(y)) \wedge (\forall x \in \Delta. S(x) \rightarrow C(x))$$


► Functions

$$(\forall x \in \Gamma. \exists y \in \Delta. P(x, y)) \wedge \\ (\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \rightarrow y = z)$$


► Bijections

$$(\forall x \in \Gamma. \exists y \in \Delta. P(x, y)) \wedge \\ (\forall y \in \Delta. \exists x \in \Gamma. P(x, y)) \wedge \\ (\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \rightarrow y = z) \wedge \\ (\forall x, z \in \Gamma. \forall y \in \Delta. P(x, y) \wedge P(z, y) \rightarrow x = z)$$


Friends & Smokers



Bijections



Functions



Summary

TODO: and future work