

# Towards Practical First-Order Model Counting

Ananth K. Kidambi<sup>1</sup>   Guramrit Singh<sup>1</sup>   **Paulius Dilkas**<sup>2,3</sup>  
Kuldeep S. Meel<sup>4,2</sup>

<sup>1</sup>IIT Bombay, India

<sup>2</sup>University of Toronto, Canada

<sup>3</sup>Vector Institute, Canada

<sup>4</sup>Georgia Tech, USA

SAT 2025

## Example Setting

- ▶ Let  $\Delta$  be a set of cardinality  $n$
- ▶ Suppose we want to count all  $P \subseteq \Delta^2$  (as a function of  $n$ ) that are:
  - ▶ functions,
  - ▶ bijections,
  - ▶ partial orders,
  - ▶ symmetric,
  - ▶ transitive,
  - ▶ etc.

# Motivation

## Example Setting

- ▶ Let  $\Delta$  be a set of cardinality  $n$
- ▶ Suppose we want to count all  $P \subseteq \Delta^2$  (as a function of  $n$ ) that are:
  - ▶ functions,
  - ▶ bijections,
  - ▶ partial orders,
  - ▶ symmetric,
  - ▶ transitive,
  - ▶ etc.
- 👉 Propositional model counting ( $\#SAT$ ) is  $\#P$ -complete
- 👍 But many of these counting problems have efficient solutions
- ▶ And we can find them using first-order model counting
  - ▶ i.e., reasoning about sets, subsets, and arbitrary elements without grounding them

## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

Many-Sorted Function-Free First-Order Logic with Equality

## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

Many-Sorted Function-Free First-Order Logic with Equality

## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

Many-Sorted Function-Free First-Order Logic with Equality

## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

Many-Sorted Function-Free First-Order Logic with Equality

## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

### Many-Sorted Function-Free First-Order Logic with Equality

- ▶ Any number of variables and constants



## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

### Many-Sorted Function-Free First-Order Logic with Equality

- ▶ Any number of variables and constants
- ▶  $\exists$  and  $\forall$  quantifiers can be nested arbitrarily deeply
- ▶ All domains are finite
  - ▶ Solutions are functions that take domain sizes as input

## More Formally: What Is the Input?

$$\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \Rightarrow y = z$$

### Many-Sorted Function-Free First-Order Logic with Equality

- ▶ Any number of variables and constants
- ▶  $\exists$  and  $\forall$  quantifiers can be nested arbitrarily deeply
- ▶ All domains are finite
  - ▶ Solutions are functions that take domain sizes as input

### First-Order Model Counting (FOMC)

- ▶ Each predicate acts like a **subset**
  - ▶ of a domain or
  - ▶ of a Cartesian product of domains
- ▶ Goal: count **combinations of subsets** that satisfy the sentence

## Previous Work: CRANE (Dilkas and Belle 2023)

- ▶ A knowledge compilation approach:
  - ▶ Sentences  $\rightarrow$  labelled digraphs  $\rightarrow$  function-defining equations
- ▶ Capable of constructing recursive solutions

## Previous Work: CRANE (Dilkas and Belle 2023)

- ▶ A knowledge compilation approach:
  - ▶ Sentences  $\rightarrow$  labelled digraphs  $\rightarrow$  function-defining equations
- ▶ Capable of constructing recursive solutions

### An Example Solution for Counting Bijections

$$f(m, n) = \sum_{l=0}^n \binom{n}{l} (-1)^{n-l} g(l, m),$$
$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

## Previous Work: CRANE (Dilkas and Belle 2023)

- ▶ A knowledge compilation approach:
  - ▶ Sentences  $\rightarrow$  labelled digraphs  $\rightarrow$  function-defining equations
- ▶ Capable of constructing recursive solutions

### An Example Solution for Counting Bijections

$$f(m, n) = \sum_{l=0}^n \binom{n}{l} (-1)^{n-l} g(l, m),$$
$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

### Issues

**Completeness:** what are the base cases of  $g$ ?

**Usability:** how do I compute, e.g.,  $f(7, 7)$ ?

# Knowledge Compilation Workflow (1/2)

1. Use CRANE to compile  $\phi$  into a set of equations  $\mathcal{E}$

# Knowledge Compilation Workflow (1/2)

1. Use CRANE to compile  $\phi$  into a set of equations  $\mathcal{E}$
2. Simplify them, e.g.,

$$g(l, m) = \sum_{k=0}^m [0 \leq k \leq 1] \binom{m}{k} g(l-1, m-k)$$

becomes

$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

# Knowledge Compilation Workflow (1/2)

1. Use CRANE to compile  $\phi$  into a set of equations  $\mathcal{E}$
2. Simplify them, e.g.,

$$g(l, m) = \sum_{k=0}^m [0 \leq k \leq 1] \binom{m}{k} g(l-1, m-k)$$

becomes

$$g(l, m) = g(l-1, m) + mg(l-1, m-1)$$

3. ( $\Rightarrow$ ) Identify a sufficient set of base cases
  - ▶ e.g.,  $\{g(0, m), g(l, 0)\}$



## Knowledge Compilation Workflow (2/2)


4. For each base case:

$$g(0, m)$$

$$g(l, 0)$$


## Knowledge Compilation Workflow (2/2)

4. For each base case:




# Knowledge Compilation Workflow (2/2)

4. For each base case:



4.1. ( $\Rightarrow$ ) Construct the corr. sentence

4.2. Recurse



# Knowledge Compilation Workflow (2/2)

4. For each base case:

$$\begin{array}{c} g(0, m) \\ \downarrow \\ \forall y \in \Delta. S(y) \vee \neg S(y) \\ \downarrow \\ g(0, m) = 0^m \end{array}$$


4.1. ( $\Rightarrow$ ) Construct the corr. sentence

4.2. Recurse

$$\begin{array}{c} g(l, 0) \\ \downarrow \\ \top \\ \downarrow \\ g(l, 0) = 1 \end{array}$$


## Knowledge Compilation Workflow (2/2)

4. For each base case:




## Knowledge Compilation Workflow (2/2)

4. For each base case:



## Knowledge Compilation Workflow (2/2)

4. For each base case:



# Finding (a Sufficient Set of) Base Cases

## Outline

1. For every **function call**:
  - 1.1 For every **argument** of the form *var* – *const*:
    - 1.1.1 Replace the **signature parameter** with  $0, 1, \dots, \text{const} - 1$
  - 1.2 For every **argument** of the form *const*:
    - 1.2.1 Replace the corresponding signature parameter with *const*

## Example

The **signature** of *g* is  $g(l, m)$ .

Function calls:

$g(l - 1, m)$

$g(l - 1, m - 1)$

Base cases:

$g(0, m)$

$g(l, 0)$





# Theoretical Results

## Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

# Theoretical Results

## Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

## Proof (hint).

Each recursive call eliminates a domain.



# Theoretical Results

## Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

## Proof (hint).

Each recursive call eliminates a domain.



## Theorem

*The **evaluation** of a recursive function always **terminates**.*

# Theoretical Results

## Theorem

*The maximum **recursion depth** of the compilation algorithm is upper bounded by the **number of domains**.*

## Proof (hint).

Each recursive call eliminates a domain.



## Theorem

*The **evaluation** of a recursive function always **terminates**.*

## Proof (hints).

- ▶ There exists a **topological ordering** of functions
- ▶ All function calls follow the **structure** from the previous slide
- ▶ Some common-sense assumptions about the **evaluation order** and previous work



# From a Base Case to a Sentence

## From Previous Work (Dilkas and Belle 2023)

- ▶ CRANE associates each function  $f$  with a sentence  $\phi$  such that  $\text{CRANE}(\phi)$  produces the definition of  $f$
- ▶ There is a bijection between the parameters of  $f$  and the domains of  $\phi$

## Example

- ▶ Base case:  $g(0, m)$

# From a Base Case to a Sentence

## From Previous Work (Dilkas and Belle 2023)

- ▶ CRANE associates each function  $f$  with a sentence  $\phi$  such that  $\text{CRANE}(\phi)$  produces the definition of  $f$
- ▶ There is a bijection between the parameters of  $f$  and the domains of  $\phi$

## Example

- ▶ Base case:  $g(0, m)$   
                   $\begin{matrix} \Gamma & \Delta \\ \updownarrow & \updownarrow \end{matrix}$

# From a Base Case to a Sentence

## From Previous Work (Dilkas and Belle 2023)

- ▶ CRANE associates each function  $f$  with a sentence  $\phi$  such that  $\text{CRANE}(\phi)$  produces the definition of  $f$
- ▶ There is a bijection between the parameters of  $f$  and the domains of  $\phi$

## Example

- ▶ Base case:  $g(\overset{\Gamma}{\downarrow}0, \overset{\Delta}{\downarrow}m)$
- ▶ Part of the sentence of  $g$ :

$$\forall x \in \Gamma. \forall y \in \Delta. S(y) \vee \neg P(x, y) \quad (1)$$

# From a Base Case to a Sentence

## From Previous Work (Dilkas and Belle 2023)

- ▶ CRANE associates each function  $f$  with a sentence  $\phi$  such that  $\text{CRANE}(\phi)$  produces the definition of  $f$
- ▶ There is a bijection between the parameters of  $f$  and the domains of  $\phi$

## Example

- ▶ Base case:  $g(0, m)$   
 $\begin{matrix} \Gamma & \Delta \\ \updownarrow & \updownarrow \end{matrix}$
- ▶ Part of the sentence of  $g$ :

$$\forall x \in \Gamma. \forall y \in \Delta. S(y) \vee \neg P(x, y) \quad (1)$$

- ▶  $g(0, \dots)$  means we need to simplify (1) by assuming  $|\Gamma| = 0$



# From a Base Case to a Sentence

## From Previous Work (Dilkas and Belle 2023)

- ▶ CRANE associates each function  $f$  with a sentence  $\phi$  such that  $\text{CRANE}(\phi)$  produces the definition of  $f$
- ▶ There is a bijection between the parameters of  $f$  and the domains of  $\phi$

## Example

- ▶ Base case:  $g(0, m)$   
 $\begin{matrix} \Gamma & \Delta \\ \updownarrow & \updownarrow \end{matrix}$
- ▶ Part of the sentence of  $g$ :

$$\forall x \in \Gamma. \forall y \in \Delta. S(y) \vee \neg P(x, y) \quad (1)$$

- ▶  $g(0, \dots)$  means we need to simplify (1) by assuming  $|\Gamma| = 0$
- ▶ Result:  $\forall y \in \Delta. S(y) \vee \neg S(y)$  (Smoothing)

► Friends & Smokers

$$(\forall x, y \in \Delta. S(x) \wedge F(x, y) \rightarrow S(y)) \wedge (\forall x \in \Delta. S(x) \rightarrow C(x))$$

# Benchmarks

## ► Friends & Smokers

$$(\forall x, y \in \Delta. S(x) \wedge F(x, y) \rightarrow S(y)) \wedge (\forall x \in \Delta. S(x) \rightarrow C(x))$$

## ► Functions

$$(\forall x \in \Gamma. \exists y \in \Delta. P(x, y)) \wedge \\ (\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \rightarrow y = z)$$

# Benchmarks

## ► Friends & Smokers

$$(\forall x, y \in \Delta. S(x) \wedge F(x, y) \rightarrow S(y)) \wedge (\forall x \in \Delta. S(x) \rightarrow C(x))$$


## ► Functions

$$(\forall x \in \Gamma. \exists y \in \Delta. P(x, y)) \wedge \\ (\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \rightarrow y = z)$$


## ► Bijections

$$(\forall x \in \Gamma. \exists y \in \Delta. P(x, y)) \wedge \\ (\forall y \in \Delta. \exists x \in \Gamma. P(x, y)) \wedge \\ (\forall x \in \Gamma. \forall y, z \in \Delta. P(x, y) \wedge P(x, z) \rightarrow y = z) \wedge \\ (\forall x, z \in \Gamma. \forall y \in \Delta. P(x, y) \wedge P(z, y) \rightarrow x = z)$$


# Friends & Smokers



# Bijections



# Functions



TODO: and future work