

Weighted Model Counting Without Parameter Variables

Paulius Dilkas Vaishak Belle

University of Edinburgh, Edinburgh, UK

SAT 2021

The Problem of Computing Probability


ProbLog

```
0.001 :: burglary .
0.002 :: earthquake .
0.95  :: alarm      :- burglary, earthquake .
0.94  :: alarm      :- burglary, \+ earthquake .
0.29  :: alarm      :- \+ burglary, earthquake .
0.001 :: alarm      :- \+ burglary, \+ earthquake .
0.9   :: johnCalls  :- alarm .
0.05  :: johnCalls  :- \+ alarm .
0.7   :: maryCalls  :- alarm .
0.01  :: maryCalls  :- \+ alarm .
```


BLOG

```
random Boolean Burglary ~ BooleanDistrib(0.001);
random Boolean Earthquake ~ BooleanDistrib(0.002);
random Boolean Alarm ~
  if Burglary then
    if Earthquake then BooleanDistrib(0.95)
    else BooleanDistrib(0.94)
  else
    if Earthquake then BooleanDistrib(0.29)
    else BooleanDistrib(0.001);
random Boolean JohnCalls ~
  if Alarm then BooleanDistrib(0.9)
  else BooleanDistrib(0.05);
random Boolean MaryCalls ~
  if Alarm then BooleanDistrib(0.7)
  else BooleanDistrib(0.01);
```

Bayesian Network



Markov Random Field



The Problem of Computing Probability

ProbLog


```
0.001 :: burglary.  
0.002 :: earthquake.  
0.95  :: alarm    :- burglary, earthquake.  
0.94  :: alarm    :- burglary, \+ earthquake.  
0.29  :: alarm    :- \+ burglary, earthquake.  
0.001 :: alarm    :- \+ burglary, \+ earthquake.  
0.9   :: johnCalls :- alarm.  
0.05  :: johnCalls :- \+ alarm.  
0.7   :: maryCalls :- alarm.  
0.01  :: maryCalls :- \+ alarm.
```

WMC


BLOG

```
random Boolean Burglary ~ BooleanDist(0.001);  
random Boolean Earthquake ~ BooleanDist(0.002);  
random Boolean Alarm ~  
  if Burglary then  
    if Earthquake then BooleanDistrib(0.95)  
    else BooleanDistrib(0.94)  
  else  
    if Earthquake then BooleanDistrib(0.29)  
    else BooleanDistrib(0.001);  
random Boolean JohnCalls ~  
  if Alarm then BooleanDistrib(0.9)  
  else BooleanDistrib(0.05);  
random Boolean MaryCalls ~  
  if Alarm then BooleanDistrib(0.7)  
  else BooleanDistrib(0.01);
```

Bayesian Network



Markov Random Field



Weighted Model Counting (WMC)

- ▶ Generalises propositional model counting ($\#SAT$)
- ▶ Applications:
 - ▶ graphical models
 - ▶ probabilistic programming
 - ▶ neural-symbolic artificial intelligence
- ▶ Main types of algorithms:
 - ▶ using knowledge compilation
 - ▶ using a SAT solver
 - ▶ manipulating pseudo-Boolean functions


Example

$$w(x) = 0.3, w(\neg x) = 0.7, \\ w(y) = 0.2, w(\neg y) = 0.8$$

$$\text{WMC}(x \vee y) = w(x)w(y) + \\ w(x)w(\neg y) + w(\neg x)w(y) = 0.44$$

The Problem with Assigning Weights to Literals

A Simple Bayesian Network



- ▶ from 2 binary variables
- ▶ to 8 variables and 17 clauses
- ▶ with lots of redundancy

Its WMC Encoding

p cnf 8 17

-2 -1 0

1 2 0

-3 1 0

-1 3 0

-5 -1 0

-5 -4 0

1 4 5 0

-6 -1 0

-6 4 0

-4 1 6 0

-7 1 0

-7 -4 0

-1 4 7 0

-8 1 0

-8 4 0

-4 -1 8 0

-4 0


c weights 1.0 1.0 0.5 1.0 \

0.5 1.0 1.0 1.0 0.6 1.0 \

0.4 1.0 0.1 1.0 0.9 1.0

The Problem with Assigning Weights to Literals

A Simple Bayesian Network



- ▶ from 2 binary variables
- ▶ to 8 variables and 17 clauses
- ▶ with lots of redundancy

Its WMC Encoding

```
p cnf 8 17
-2 -1 0           $\neg x_1 \Leftrightarrow x_2$ 
1 2 0
-3 1 0           $x_1 \Leftrightarrow x_3$ 
-1 3 0
-5 -1 0
-5 -4 0          $\neg x_1 \wedge \neg x_4 \Leftrightarrow x_5$ 
1 4 5 0
-6 -1 0
-6 4 0           $\neg x_1 \wedge x_4 \Leftrightarrow x_6$ 
-4 1 6 0
-7 1 0
-7 -4 0          $x_1 \wedge \neg x_4 \Leftrightarrow x_7$ 
-1 4 7 0
-8 1 0
-8 4 0           $x_1 \wedge x_4 \Leftrightarrow x_8$ 
-4 -1 8 0
-4 0             $\neg x_4$ 
c weights 1.0 1.0 0.5 1.0 \
0.5 1.0 1.0 1.0 0.6 1.0 \
0.4 1.0 0.1 1.0 0.9 1.0
```

Outline

An Alternative Formulation

Correctness

Experimental Results

Summary

Outline

An Alternative Formulation

Correctness

Experimental Results

Summary

Formalising the Intuition from Before

For any propositional formula ϕ over a set of variables X and $p, q \in \mathbb{R}$, let $[\phi]_q^p: 2^X \rightarrow \mathbb{R}$ be the pseudo-Boolean function defined as

$$[\phi]_q^p(Y) := \begin{cases} p & \text{if } Y \models \phi \\ q & \text{otherwise} \end{cases}$$

for any $Y \subseteq X$.

Definition (Pseudo-Boolean Projection (PBP))

A **PBP instance** is a tuple (F, X, ω) , where X is the set of variables, F is a set of two-valued pseudo-Boolean functions $2^X \rightarrow \mathbb{R}$, and $\omega \in \mathbb{R}$ is the scaling factor.

From WMC to PBP

Example

- ▶ Indicator variable: x
- ▶ Parameter variables: p, q
- ▶ Weights: $w(p) = 0.2$, $w(q) = 0.8$, and $w(\neg p) = w(\neg q) = 1$

WMC Clause

$$\neg x \Rightarrow p$$

$$p \Rightarrow \neg x$$

$$x \Rightarrow q$$

$$q \Rightarrow x$$

$$\neg x$$

From WMC to PBP

Example

- ▶ Indicator variable: x
- ▶ Parameter variables: p, q
- ▶ Weights: $w(p) = 0.2$, $w(q) = 0.8$, and $w(\neg p) = w(\neg q) = 1$

WMC Clause	In CNF
$\neg x \Rightarrow p$	$x \vee p$
$p \Rightarrow \neg x$	$\neg x \vee \neg p$
$x \Rightarrow q$	$\neg x \vee q$
$q \Rightarrow x$	$x \vee \neg q$
$\neg x$	$\neg x$

From WMC to PBP

Example

- ▶ Indicator variable: x
- ▶ Parameter variables: p, q
- ▶ Weights: $w(p) = 0.2$, $w(q) = 0.8$, and $w(\neg p) = w(\neg q) = 1$

WMC Clause	In CNF	Pseudo-Boolean Function
$\neg x \Rightarrow p$	$x \vee p$	$[\neg x]_1^{0.2}$
$p \Rightarrow \neg x$	$\neg x \vee \neg p$	
$x \Rightarrow q$	$\neg x \vee q$	$[x]_1^{0.8}$
$q \Rightarrow x$	$x \vee \neg q$	
$\neg x$	$\neg x$	$[\neg x]_0^1$

From WMC to PBP

Example

- ▶ Indicator variable: x
- ▶ Parameter variables: p, q
- ▶ Weights: $w(p) = 0.2$, $w(q) = 0.8$, and $w(\neg p) = w(\neg q) = 1$

WMC Clause	In CNF	Pseudo-Boolean Function	
$\neg x \Rightarrow p$	$x \vee p$	$[\neg x]_1^{0.2}$	
$p \Rightarrow \neg x$	$\neg x \vee \neg p$		$[x]_{0.2}^{0.8}$
$x \Rightarrow q$	$\neg x \vee q$	$[x]_1^{0.8}$	
$q \Rightarrow x$	$x \vee \neg q$		
$\neg x$	$\neg x$	$[\neg x]_0^1$	$[\neg x]_0^1$

Outline

An Alternative Formulation

Correctness

Experimental Results

Summary

Outline


An Alternative Formulation

Correctness


Experimental Results

Summary


Experimental Results




Experimental Results



Experimental Results



Experimental Results



Outline

An Alternative Formulation

Correctness

Experimental Results

Summary

Summary