

Rajabharana Jewellery System — Full Database ER Diagram

All modules · 15 tables · Full attributes · Billing + Reports · Maps to MySQL

■ Implemented ✓ ■ Billing / Payment →soon Sprint 9 ■ Reports →soon Sprint 10 PK · UK · FK

Figure 1 — Complete ER Diagram (Database Mapping — All Attributes)



Syntax error in text
mermaid version 10.9.6

Figure 2 — Entity Boxes: Implemented  (M1–M7)

users (13)

M1 Auth · M2 Customer · M11 RBAC

id	BIGINT PK
name	VARCHAR
email	VARCHAR UK
email_verified_at	TIMESTAMP
password	VARCHAR
role	VARCHAR
phone	VARCHAR
address	TEXT
city	VARCHAR
profile_photo_path	VARCHAR
remember_token	VARCHAR
created_at / updated_at	TIMESTAMP

password_reset_tokens (3)

M1 Auth

email	VARCHAR PK
token	VARCHAR
created_at	TIMESTAMP

sessions (6)

M1 Auth

id	VARCHAR PK
user_id	BIGINT FK
ip_address	VARCHAR
user_agent	TEXT
payload	LONGTEXT
last_activity	INT

catalog_designs (11)

M3 Catalogue · M6 Inventory

id	BIGINT PK
name	VARCHAR
code	VARCHAR UK
description	TEXT
category	VARCHAR
gold_quality	VARCHAR
weight_grams	DECIMAL
selling_price	DECIMAL
availability_status	VARCHAR
created_at / updated_at	TIMESTAMP

catalog_images (7)

M3 Catalogue

id	BIGINT PK
catalog_design_id	FK R8
image_path	VARCHAR
sort_order	SMALLINT
is_primary	BOOLEAN
created_at / updated_at	TIMESTAMP

metal_prices (7)

M7 Metal Price

id	BIGINT PK
gold_price_per_gram	DECIMAL
silver_price_per_gram	DECIMAL
price_date	DATE
updated_by	FK R4
created_at / updated_at	TIMESTAMP

orders (26) — M2 Customer · M4 Orders · M5 Workshop

id	PK	order_number	UK	user_id	FK R1	design_type	VARCHAR
catalog_design_id	FK R9	reference_image_path	VARCHAR	item_type	VARCHAR	item_name	VARCHAR
size	VARCHAR	weight_grams	DECIMAL	specifications	TEXT	gold_quality	VARCHAR
gemstone_type	VARCHAR	gemstone_details	TEXT	quantity	SMALLINT	special_instructions	TEXT
expected_delivery_date	DATE	contact_phone	VARCHAR	delivery_address	TEXT	status	VARCHAR
estimated_price	DECIMAL	admin_notes	TEXT	assigned_technician_id	FK R2	assigned_at	TIMESTAMP
created_at / updated_at	TIMESTAMP						

production_logs (8)	
M5 Workshop	
id	BIGINT PK
order_id	FK R10
user_id	FK R3
from_status / to_status	VARCHAR
note	TEXT
created_at / updated_at	TIMESTAMP

Figure 3 — Entity Boxes: Billing · Payment · Reports 

categories (7)

M6 Inventory 

id	BIGINT PK
name / slug	UK
description	TEXT
is_active	BOOLEAN
created_at / updated_at	TIMESTAMP

invoices (18)

M8 Billing 

id	BIGINT PK
invoice_number	UK
order_id	FK R11 UK
user_id	FK R5
subtotal / making_charge	DECIMAL
discount / tax	DECIMAL
grand_total	DECIMAL
amount_paid / balance_due	DECIMAL
status	VARCHAR
issued_at / due_date	TS / DATE
notes	TEXT
created_by	FK R6
created_at / updated_at	TIMESTAMP

invoice_items (9)

M8 Billing 

id	BIGINT PK
invoice_id	FK R11a
order_id	FK R11b
description	VARCHAR
quantity	INT
unit_price / line_total	DECIMAL
created_at / updated_at	TIMESTAMP

payment_methods (5)

M8/M9 Lookup 

id	BIGINT PK
code	UK cash/card/bank
label	VARCHAR
is_active / sort_order	BOOL/INT
created_at	TIMESTAMP

payments (11)

M9 Payment 

id	BIGINT PK
invoice_id	FK R12
payment_method_id	FK R12a
amount	DECIMAL
payment_status	VARCHAR
payment_date	DATE
reference_number / notes	VARCHAR/TEXT
recorded_by	FK R7
created_at / updated_at	TIMESTAMP

notifications (10)

M10 Notification 

id	UUID PK
user_id	FK R13
type / title / message	VARCHAR/TEXT
channel	VARCHAR
read_at	TIMESTAMP
data	JSON
created_at / updated_at	TIMESTAMP

report_exports (9)

M12 Reports  — saved PDF/CSV metadata

id	BIGINT PK
report_type	VARCHAR
date_from / date_to	DATE
generated_by	FK R15 → users
file_path	VARCHAR
format	VARCHAR pdf/csv
parameters	JSON filters
created_at / updated_at	TIMESTAMP

Report Engine (logical)

M12 — no table; reads via SQL

Order Summary	→ orders
Sales & Revenue	→ orders, invoices
Customer Report	→ users, orders
Production Report	→ orders, production_logs
Delivery Report	→ orders
Inventory Report	→ catalog_designs
Billing Collection	→ invoices, payments
Daily Summary	→ all tables

Figure 4 — All Relationships (Database FK Mapping)

ID	Parent	Child	FK Column	Card.	Module
R-AUTH-1	users	sessions	user_id	1:N	Auth
R-AUTH-2	users	password_reset_tokens	email	1:0..1	Auth
R1	users	orders	user_id	1:N	Customer/Orders
R2	users	orders	assigned_technician_id	1:N	Workshop
R3	users	production_logs	user_id	1:N	Workshop
R4	users	metal_prices	updated_by	1:N	Metal Price
R5	users	invoices	user_id	1:N	Billing
R6	users	invoices	created_by	1:N	Billing
R7	users	payments	recorded_by	1:N	Payment
R8	catalog_designs	catalog_images	catalog_design_id	1:N	Catalogue
R9	catalog_designs	orders	catalog_design_id	1:N	Orders
R10	orders	production_logs	order_id	1:N	Workshop
R11	orders	invoices	order_id	1:1	Billing
R11a	invoices	invoice_items	invoice_id	1:N	Billing
R11b	orders	invoice_items	order_id	1:N	Billing
R12	invoices	payments	invoice_id	1:N	Payment
R12a	payment_methods	payments	payment_method_id	1:N	Payment
R13	users	notifications	user_id	1:N	Notification
R14	categories	catalog_designs	category_id	1:N	Inventory
R15	users	report_exports	generated_by	1:N	Reports

For Word: Print this page → PDF, or screenshot Figures 1–4.

Text source: docs/DATABASE_ER_FULL.md

Implemented today in MySQL: users, password_reset_tokens, sessions, catalog_designs, catalog_images, orders, metal_prices, production_logs (8 tables).

Planned migrations: categories, invoices, invoice_items, payment_methods, payments, notifications, report_exports (7 tables).