

FULL PROJECT DECLARATIONS

This file lists declaration lines (classes, interfaces, enums, objects, and functions) found across the project.

Q_base appwrite/app_write.py

```
L316: def wait_for_attributes(db_id, collection_id):
L336: def setup_database():
```

Q_base appwrite/encrypt_and_sync_keys.py

```
L21: def get_global_decryption_key():
L29: def encrypt_global_key(plain_text: str) -> str:
L42: def main():
```

Q_base appwrite/verify_appwrite_readiness.py

```
L22: def check_readiness():
```

Q_base appwrite/create_global_keys_doc.py

```
L24: def init_global_keys_doc():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/typing_extensions.py

```
L167: class _Sentinel:
L168: def __repr__(self):
L177: def _should_collect_from_parameters(t):
L182: def _should_collect_from_parameters(t):
L202: class _AnyMeta(type):
L203: def __instancecheck__(self, obj):
L208: def __repr__(self):
L213: class Any(metaclass=_AnyMeta):
L222: def __new__(cls, *args, **kwargs):
L233: class _SpecialForm(typing._Final, _root=True):
L236: def __init__(self, getitem):
L241: def __getattr__(self, item):
L247: def __mro_entries__(self, bases):
L250: def __repr__(self):
L253: def __reduce__(self):
L256: def __call__(self, *args, **kwargs):
L259: def __or__(self, other):
```

```

L262: def __ror__(self, other):
L265: def __instancecheck__(self, obj):
L268: def __subclasscheck__(self, cls):
L272: def __getitem__(self, parameters):
L279: class _ExtensionsSpecialForm(typing._SpecialForm, _root=True):
L280: def __repr__(self):
L293: def final(f):
L298: class Base:
L300: def done(self) -> None:
L302: class Sub(Base):
L303: def done(self) -> None: # Error reported by type checker
L306: class Leaf:
L308: class Other(Leaf): # Error reported by type checker
L328: def disjoint_base(cls):
L337: class Disjoint1: pass
L340: class Disjoint2: pass
L342: class Disjoint3(Disjoint1, Disjoint2): pass # Type checker error
L352: def IntVar(name):
L361: def _flatten_literal_params(parameters):
L371: def _value_and_type_iter(params):
L375: class _LiteralGenericAlias(typing._GenericAlias, _root=True):
L376: def __eq__(self, other):
L383: def __hash__(self):
L386: class _LiteralForm(_ExtensionsSpecialForm, _root=True):
L387: def __init__(self, doc: str):
L391: def __getitem__(self, parameters):
L444: def overload(func):
L451: def utf8(value: None) -> None: ...
L453: def utf8(value: bytes) -> bytes: ...
L455: def utf8(value: str) -> bytes: ...
L462: def utf8(value: None) -> None: ...
L464: def utf8(value: bytes) -> bytes: ...
L466: def utf8(value: str) -> bytes: ...
L467: def utf8(value):
L484: def get_overloads(func):
L495: def clear_overloads():
L522: def _is_dunder(attr):
L526: class _SpecialGenericAlias(typing._SpecialGenericAlias, _root=True):
L527: def __init__(self, origin, nparams, *, inst=True, name=None, defaults=()):
L531: def __setattr__(self, attr, val):
L539: def __getitem__(self, params):
L603: def _get_protocol_attrs(cls):
L615: def _caller(depth=1, default='__main__'):
L633: def _allow_reckless_class_checks(depth=2):
L640: def _no_init(self, *args, **kwargs):
L644: def _type_check_issubclass_arg_1(arg):
L663: class _ProtocolMeta(type(typing.Protocol)):
L670: def __new__(mcls, name, bases, namespace, **kwargs):
L686: def __init__(cls, *args, **kwargs):
L691: def __subclasscheck__(cls, other):
L717: def __instancecheck__(cls, instance):

```

```

L749: def __eq__(cls, other):
L760: def __hash__(cls) -> int:
L764: def _proto_hook(cls, other):
L788: class Protocol(typing.Generic, metaclass=_ProtocolMeta):
L794: def __init_subclass__(cls, *args, **kwargs):
L814: def runtime_checkable(cls):
L825: class Closable(Protocol):
L826: def close(self): ...
L882: class SupportsInt(Protocol):
L887: def __int__(self) -> int:
L891: class SupportsFloat(Protocol):
L896: def __float__(self) -> float:
L900: class SupportsComplex(Protocol):
L905: def __complex__(self) -> complex:
L909: class SupportsBytes(Protocol):
L914: def __bytes__(self) -> bytes:
L918: class SupportsIndex(Protocol):
L922: def __index__(self) -> int:
L926: class SupportsAbs(Protocol[T_co]):
L933: def __abs__(self) -> T_co:
L937: class SupportsRound(Protocol[T_co]):
L944: def __round__(self, ndigits: int = 0) -> T_co:
L953: class Reader(Protocol[T_co]):
L962: def read(self, size: int = ..., /) -> T_co:
L970: class Writer(Protocol[T_contra]):
L979: def write(self, data: T_contra, /) -> int:
L988: class SingletonMeta(type):
L989: def __setattr__(cls, attr, value):
L999: class NoDefaultType(metaclass=SingletonMeta):
L1004: def __new__(cls):
L1007: def __repr__(self):
L1010: def __reduce__(self):
L1019: class NoExtraItemsType(metaclass=SingletonMeta):
L1024: def __new__(cls):
L1027: def __repr__(self):
L1030: def __reduce__(self):
L1062: def _get_typeddict_qualifiers(annotation_type):
L1083: class _TypedDictMeta(type):
L1085: def __new__(cls, name, bases, ns, *, total=True, closed=None,
L1203: def __annotate__(format):
L1245: def __subclasscheck__(cls, other):
L1253: def _create_typeddict(
L1315: class _TypedDictSpecialForm(_SpecialForm, _root=True):
L1316: def __call__(
L1337: def __mro_entries__(self, bases):
L1341: def TypedDict(self, args):
L1351: class Point2D(TypedDict):
L1370: class Point2D(TypedDict, total=False):
L1377: class body be required.
L1382: class Point2D(TypedDict):
L1405: def is_typeddict(tp):

```

```

L1409: class Film(TypedDict):
L1423: def assert_type(val, typ, /):
L1429: def greet(name: str) -> None:
L1443: def _strip_extras(t):
L1467: def get_type_hints(obj, globalns=None, localns=None, include_extras=False):
L1511: def _could_be_inserted_optional(t):
L1521: def _clean_optional(obj, hints, globalns=None, localns=None):
L1581: def get_origin(tp):
L1605: def get_args(tp):
L1632: def TypeAlias(self, parameters):
L1646: def _set_default(type_param, default):
L1651: def _set_module(typevarlike):
L1658: class _DefaultMixin:
L1666: class _TypeVarLikeMeta(type):
L1667: def __instancecheck__(cls, __instance: Any) -> bool:
L1675: class TypeVar(metaclass=_TypeVarLikeMeta):
L1680: def __new__(cls, name, *constraints, bound=None,
L1698: def _tvar_prepare_subst(alias, args):
L1709: def __init_subclass__(cls) -> None:
L1719: class _Immutable:
L1723: def __copy__(self):
L1726: def __deepcopy__(self, memo):
L1729: class ParamSpecArgs(_Immutable):
L1741: def __init__(self, origin):
L1744: def __repr__(self):
L1747: def __eq__(self, other):
L1752: class ParamSpecKwargs(_Immutable):
L1764: def __init__(self, origin):
L1767: def __repr__(self):
L1770: def __eq__(self, other):
L1783: class ParamSpec(metaclass=_TypeVarLikeMeta):
L1788: def __new__(cls, name, *, bound=None,
L1806: def _paramspec_prepare_subst(alias, args):
L1825: def __init_subclass__(cls) -> None:
L1832: class ParamSpec(list, _DefaultMixin):
L1851: def add_logging(f: Callable[[P, T]] -> Callable[[P, T]]:
L1853: def inner(*args: P.args, **kwargs: P.kwargs) -> T:
L1859: def add_two(x: float, y: float) -> float:
L1883: def args(self):
L1887: def kwargs(self):
L1890: def __init__(self, name, *, bound=None, covariant=False, contravariant=False,
L1908: def __repr__(self):
L1919: def __hash__(self):
L1922: def __eq__(self, other):
L1925: def __reduce__(self):
L1929: def __call__(self, *args, **kwargs):
L1939: def _type_convert(arg, module=None, *, allow_special_forms=False):
L1953: class _ConcatenateGenericAlias(list):
L1958: def __init__(self, origin, args):
L1963: def __repr__(self):
L1968: def __hash__(self):

```

```

L1972: def __call__(self, *args, **kwargs):
L1976: def __parameters__(self):
L1982: def copy_with(self, params):
L1993: def __getitem__(self, args):
L2076: class _ConcatenateGenericAlias(typing._ConcatenateGenericAlias, _root=True):
L2080: def copy_with(self, params):
L2090: def __getitem__(self, args):
L2098: class _EllipsisDummy: ...
L2102: def _create_concatenate_alias(origin, parameters):
L2127: def _concatenate_getitem(self, parameters):
L2148: def Concatenate(self, parameters):
L2168: def TypeGuard(self, parameters):
L2192: def is_str(val: Union[str, float]):
L2221: def TypeIs(self, parameters):
L2246: def is_awaitable(val: object) -> TypeIs[Awaitable[Any]]:
L2249: def f(val: Union[int, Awaitable[int]]) -> int:
L2267: class _TypeFormForm(_ExtensionsSpecialForm, _root=True):
L2270: def __call__(self, obj, /):
L2274: def TypeForm(self, parameters):
L2286: def cast[T](typ: TypeForm[T], value: Any) -> T: ...
L2302: def LiteralString(self, params):
L2309: def query(sql: LiteralString) -> ...:
L2325: def Self(self, params):
L2332: class ReturnsSelf:
L2333: def parse(self, data: bytes) -> Self:
L2346: def Never(self, params):
L2354: def never_call_me(arg: Never) -> None:
L2357: def int_or_str(arg: int | str) -> None:
L2377: def Required(self, parameters):
L2381: class Movie(TypedDict, total=False):
L2397: def NotRequired(self, parameters):
L2401: class Movie(TypedDict):
L2418: def ReadOnly(self, parameters):
L2423: class Movie(TypedDict):
L2427: def mutate_movie(m: Movie) -> None:
L2452: class Bar(Generic[Unpack[Ts]]): ...
L2459: class Bar(Generic[*Ts]): ...
L2464: class Movie(TypedDict):
L2470: def foo(**kwargs: Unpack[Movie]): ...
L2484: def _is_unpack(obj):
L2488: class _UnpackSpecialForm(_ExtensionsSpecialForm, _root=True):
L2489: def __init__(self, getitem):
L2493: class _UnpackAlias(typing._GenericAlias, _root=True):
L2499: def __typing_unpacked_tuple_args__(self):
L2510: def __typing_is_unpacked_typevartuple__(self):
L2515: def __getitem__(self, args):
L2521: def Unpack(self, parameters):
L2525: def _is_unpack(obj):
L2529: def _unpack_args(*args):
L2546: class TypeVarTuple(metaclass=_TypeVarLikeMeta):
L2551: def __new__(cls, name, *, default=NoDefault):

```

```

L2556: def _typevartuple_prepare_subst(alias, args):
L2604: def __init_subclass__(self, *args, **kwargs):
L2608: class TypeVarTuple(_DefaultMixin):
L2622: class Array(Generic[*Ts]): ...
L2636: class Array(Generic[*Ts]):
L2638: def __init__(self, shape: Tuple[*Ts]):
L2641: def get_shape(self) -> Tuple[*Ts]:
L2655: def __iter__(self):
L2658: def __init__(self, name, *, default=NoDefault):
L2669: def __repr__(self):
L2672: def __hash__(self):
L2675: def __eq__(self, other):
L2678: def __reduce__(self):
L2681: def __init_subclass__(self, *args, **kwargs):
L2689: def reveal_type(obj: T, /) -> T:
L2718: def assert_never(arg: Never, /) -> Never:
L2723: def int_or_str(arg: int | str) -> None:
L2749: def dataclass_transform(
L2772: def create_model(cls: type[_T]) -> type[_T]:
L2777: class CustomerModel:
L2783: class ModelBase: ...
L2785: class CustomerModel(ModelBase):
L2791: class ModelMeta(type): ...
L2793: class ModelBase(metaclass=ModelMeta): ...
L2795: class CustomerModel(ModelBase):
L2822: def decorator(cls_or_fn):
L2840: def override(arg: _F, /) -> _F:
L2845: class Base:
L2846: def method(self) -> None:
L2849: class Child(Base):
L2851: def method(self) -> None:
L2883: class deprecated:
L2892: class A:
L2896: def f():
L2901: def g(x: int) -> int: ...
L2903: def g(x: str) -> int: ...
L2925: def __init__(
L2942: def __call__(self, arg: _T, /) -> _T:
L2958: def __new__(cls, /, *args, **kwargs):
L2978: def __init_subclass__(*args, **kwargs):
L2987: def __init_subclass__(*args, **kwargs):
L3002: def wrapper(*args, **kwargs):
L3023: def _is_param_expr(arg):
L3028: def _is_param_expr(arg):
L3049: def _check_generic(cls, parameters, elen=_marker):
L3105: def _check_generic(cls, parameters, elen):
L3143: def _has_generic_or_protocol_as_origin() -> bool:
L3165: def _is_unpacked_typevartuple(x) -> bool:
L3178: def _collect_type_vars(types, typevar_types=None):
L3228: def _collect_parameters(args):
L3296: def _make_nmtuple(name, types, module, defaults=()):

```

```

L3308: class _NamedTupleMeta(type):
L3309: def __new__(cls, typename, bases, ns):
L3381: def _namedtuple_mro_entries(bases):
L3385: def NamedTuple(typename, fields=_marker, /, **kwargs):
L3390: class Employee(NamedTuple):
L3456: class Buffer(abc.ABC): # noqa: B024
L3486: def get_original_bases(cls, /):
L3495: class Foo(Generic[T]): ...
L3496: class Bar(Foo[int], float): ...
L3497: class Baz(list[str]): ...
L3521: class NewType:
L3527: def name_by_id(user_id: UserId) -> str:
L3535: def __call__(self, obj, /):
L3538: def __init__(self, name, tp):
L3548: def __mro_entries__(self, bases):
L3553: class Dummy:
L3554: def __init_subclass__(cls):
L3564: def __repr__(self):
L3567: def __reduce__(self):
L3575: def __or__(self, other):
L3578: def __ror__(self, other):
L3590: def _is_unionable(obj):
L3601: def _is_unionable(obj):
L3629: class _TypeAliasGenericAlias(typing._GenericAlias, _root=True):
L3630: def __getattr__(self, attr):
L3636: class TypeAliasType:
L3664: def __init__(self, name: str, value, *, type_params=()):
L3701: def __setattr__(self, name: str, value: object, /) -> None:
L3706: def __delattr__(self, name: str, /) -> Never:
L3709: def _raise_attribute_error(self, name: str) -> Never:
L3723: def __repr__(self) -> str:
L3727: def _check_single_param(self, param, recursion=0):
L3741: def _check_parameters(self, parameters):
L3753: def __getitem__(self, parameters):
L3770: def __reduce__(self):
L3773: def __init_subclass__(cls, *args, **kwargs):
L3780: def __call__(self):
L3785: def __or__(self, right):
L3792: def __ror__(self, left):
L3802: def is_protocol(tp: type, /) -> bool:
L3823: def get_protocol_members(tp: type, /) -> typing.FrozenSet[str]:
L3847: class Doc:
L3864: def __init__(self, documentation: str, /) -> None:
L3867: def __repr__(self) -> str:
L3870: def __hash__(self) -> int:
L3873: def __eq__(self, other: object) -> bool:
L3901: class Format(enum.IntEnum):
L3909: def get_annotations(obj, *, globals=None, locals=None, eval_str=False,
L4043: def _eval_with_owner(
L4121: def evaluate_forward_ref(
L4210: class Sentinel:

```

```

L4219: def __init__(
L4227: def __repr__(self):
L4233: def __call__(self, *args, **kwargs):
L4238: def __or__(self, other):
L4241: def __ror__(self, other):
L4244: def __getstate__(self):
L4251: def type_repr(value):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/_collections.py

```

L15: class HasGettableStringKeys(Protocol):
L16: def keys(self) -> typing.Iterator[str]: ...
L18: def __getitem__(self, key: str) -> str: ...
L39: class _Sentinel(Enum):
L43: def ensure_can_construct_http_header_dict(
L63: class RecentlyUsedContainer(typing.Generic[_KT, _VT], typing.MutableMapping[_KT, _VT]):
L82: def __init__(
L93: def __getitem__(self, key: _KT) -> _VT:
L100: def __setitem__(self, key: _KT, value: _VT) -> None:
L125: def __delitem__(self, key: _KT) -> None:
L132: def __len__(self) -> int:
L136: def __iter__(self) -> typing.NoReturn:
L141: def clear(self) -> None:
L151: def keys(self) -> set[_KT]: # type: ignore[override]
L156: class HTTPHeaderDictItemView(set[tuple[str, str]]):
L187: def __init__(self, headers: HTTPHeaderDict) -> None:
L190: def __len__(self) -> int:
L193: def __iter__(self) -> typing.Iterator[tuple[str, str]]:
L196: def __contains__(self, item: object) -> bool:
L204: class HTTPHeaderDict(typing.MutableMapping[str, str]):
L240: def __init__(self, headers: ValidHTTPHeaderSource | None = None, **kwargs: str):
L251: def __setitem__(self, key: str, val: str) -> None:
L257: def __getitem__(self, key: str) -> str:
L263: def __delitem__(self, key: str) -> None:
L268: def __contains__(self, key: object) -> bool:
L275: def setdefault(self, key: str, default: str = "") -> str:
L278: def __eq__(self, other: object) -> bool:
L289: def __ne__(self, other: object) -> bool:
L292: def __len__(self) -> int:
L295: def __iter__(self) -> typing.Iterator[str]:
L300: def discard(self, key: str) -> None:
L306: def add(self, key: str, val: str, *, combine: bool = False) -> None:
L341: def extend(self, *args: ValidHTTPHeaderSource, **kwargs: str) -> None:
L374: def getlist(self, key: str) -> list[str]: ...
L377: def getlist(self, key: str, default: _DT) -> list[str] | _DT: ...
L379: def getlist(
L399: def _prepare_for_method_change(self) -> Self:
L425: def __repr__(self) -> str:

```



```

L428: def _copy_from(self, other: HTTPHeaderDict) -> None:
L433: def copy(self) -> Self:
L438: def iteritems(self) -> typing.Iterator[tuple[str, str]]:
L445: def itermerged(self) -> typing.Iterator[tuple[str, str]]:
L451: def items(self) -> HTTPHeaderDictItemView: # type: ignore[override]
L454: def _has_value_for_header(self, header_name: str, potential_value: str) -> bool:
L459: def __ior__(self, other: object) -> HTTPHeaderDict:
L468: def __or__(self, other: object) -> Self:
L478: def __ror__(self, other: object) -> Self:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/fields.py

```

L15: def guess_content_type(
L31: def format_header_param_rfc2231(name: str, value: _TYPE_FIELD_VALUE) -> str:
L79: def format_multipart_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
L117: def format_header_param_html5(name: str, value: _TYPE_FIELD_VALUE) -> str:
L135: def format_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
L153: class RequestField:
L171: def __init__(
L200: def from_tuples(
L244: def _render_part(self, name: str, value: _TYPE_FIELD_VALUE) -> str:
L260: def _render_parts(
L291: def render_headers(self) -> str:
L310: def make_multipart(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/connection.py

```

L37: class BaseSSLError(BaseException): # type: ignore[no-redef]
L82: class HTTPConnection(_HTTPConnection):
L132: def __init__(
L163: def __str__(self) -> str:
L166: def __repr__(self) -> str:
L170: def host(self) -> str:
L189: def host(self, value: str) -> None:
L198: def _new_conn(self) -> socket.socket:
L227: def set_tunnel(
L244: def _wrap_ipv6(self, ip: bytes) -> bytes:
L253: def _tunnel(self) -> None:
L296: def _tunnel(self) -> None: # noqa: F811
L330: def connect(self) -> None:
L348: def is_closed(self) -> bool:
L352: def is_connected(self) -> bool:
L358: def has_connected_to_proxy(self) -> bool:
L362: def proxy_is_forwarding(self) -> bool:
L369: def proxy_is_tunneling(self) -> bool:
L375: def close(self) -> None:
L390: def putrequest(

```

```

L410: def putheader(self, header: str, *values: str) -> None: # type: ignore[override]
L424: def request( # type: ignore[override]
L521: def request_chunked(
L540: def getresponse( # type: ignore[override]
L603: class HTTPSPConnection(HTTPConnection):
L621: def __init__(
L683: def set_cert(
L724: def connect(self) -> None:
L861: def _connect_tls_proxy(self, hostname: str, sock: socket.socket) -> ssl.SSLSocket:
L891: class _WrappedAndVerifiedSocket(typing.NamedTuple):
L901: def _ssl_wrap_socket_and_match_hostname(
L1026: def _match_hostname(
L1052: def _wrap_proxy_error(err: Exception, proxy_scheme: str | None) -> ProxyError:
L1077: def _get_default_user_agent() -> str:
L1081: class DummyConnection:
L1092: def _url_from_connection(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/response.py

```

L54: class ContentDecoder:
L55: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L59: def has_unconsumed_tail(self) -> bool:
L62: def flush(self) -> bytes:
L66: class DeflateDecoder(ContentDecoder):
L67: def __init__(self) -> None:
L73: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L116: def has_unconsumed_tail(self) -> bool:
L121: def flush(self) -> bytes:
L125: class GzipDecoderState:
L131: class GzipDecoder(ContentDecoder):
L132: def __init__(self) -> None:
L137: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L188: def has_unconsumed_tail(self) -> bool:
L191: def flush(self) -> bytes:
L197: class BrotliDecoder(ContentDecoder):
L201: def __init__(self) -> None:
L209: def _decompress(self, data: bytes, output_buffer_limit: int = -1) -> bytes:
L212: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L228: def has_unconsumed_tail(self) -> bool:
L234: def flush(self) -> bytes:
L250: class ZstdDecoder(ContentDecoder):
L251: def __init__(self) -> None:
L254: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L289: def has_unconsumed_tail(self) -> bool:
L294: def flush(self) -> bytes:
L300: class MultiDecoder(ContentDecoder):
L313: def __init__(self, modes: str) -> None:
L322: def flush(self) -> bytes:

```

```

L325: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L352: def has_unconsumed_tail(self) -> bool:
L356: def _get_decoder(mode: str) -> ContentDecoder:
L374: class BytesQueueBuffer:
L388: def __init__(self) -> None:
L392: def __len__(self) -> int:
L395: def put(self, data: bytes) -> None:
L399: def get(self, n: int) -> bytes:
L434: def get_all(self) -> bytes:
L451: class BaseHTTPResponse(io.IOBase):
L466: def __init__(
L501: def get_redirect_location(self) -> str | None | typing.Literal[False]:
L514: def data(self) -> bytes:
L517: def json(self) -> typing.Any:
L539: def url(self) -> str | None:
L543: def url(self, url: str | None) -> None:
L547: def connection(self) -> BaseHTTPConnection | None:
L551: def retries(self) -> Retry | None:
L555: def retries(self, retries: Retry | None) -> None:
L561: def stream(
L566: def read(
L574: def read1(
L581: def read_chunked(
L588: def release_conn(self) -> None:
L591: def drain_conn(self) -> None:
L594: def shutdown(self) -> None:
L597: def close(self) -> None:
L600: def _init_decoder(self) -> None:
L619: def _decode(
L656: def _flush_decoder(self) -> bytes:
L666: def readinto(self, b: bytearray | memoryview[int]) -> int:
L675: def getheaders(self) -> HTTPHeaderDict:
L678: def getheader(self, name: str, default: str | None = None) -> str | None:
L682: def info(self) -> HTTPHeaderDict:
L685: def geturl(self) -> str | None:
L689: class HTTPResponse(BaseHTTPResponse):
L695: class is also compatible with the Python standard library's :mod:`io`
L722: def __init__(
L787: def release_conn(self) -> None:
L794: def drain_conn(self) -> None:
L811: def data(self) -> bytes:
L822: def connection(self) -> HTTPConnection | None:
L825: def isclosed(self) -> bool:
L828: def tell(self) -> int:
L836: def _init_length(self, request_method: str | None) -> int | None:
L893: def _error_catcher(self) -> typing.Generator[None]:
L954: def _fp_read(
L1007: def _raw_read(
L1059: def read(
L1167: def read1(
L1238: def stream(

```

```

L1273: def readable(self) -> bool:
L1276: def shutdown(self) -> None:
L1285: def close(self) -> None:
L1298: def closed(self) -> bool:
L1310: def fileno(self) -> int:
L1321: def flush(self) -> None:
L1329: def supports_chunked_reads(self) -> bool:
L1338: def _update_chunk_length(self) -> None:
L1356: def _handle_chunk(self, amt: int | None) -> bytes:
L1378: def read_chunked(
L1466: def url(self) -> str | None:
L1475: def url(self, url: str | None) -> None:
L1478: def __iter__(self) -> typing.Iterator[bytes]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/exceptions.py

```

L18: class HTTPError(Exception):
L22: class HTTPWarning(Warning):
L29: class PoolError(HTTPError):
L32: def __init__(self, pool: ConnectionPool, message: str) -> None:
L37: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L42: class RequestError(PoolError):
L45: def __init__(self, pool: ConnectionPool, url: str | None, message: str) -> None:
L49: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L54: class SSLError(HTTPError):
L58: class ProxyError(HTTPError):
L64: def __init__(self, message: str, error: Exception) -> None:
L69: class DecodeError(HTTPError):
L73: class ProtocolError(HTTPError):
L84: class MaxRetryError(RequestError):
L95: def __init__(
L104: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L109: class HostChangedError(RequestError):
L112: def __init__(
L120: class TimeoutStateError(HTTPError):
L124: class TimeoutError(HTTPError):
L132: class ReadTimeoutError(TimeoutError, RequestError):
L138: class ConnectTimeoutError(TimeoutError):
L142: class NewConnectionError(ConnectTimeoutError, HTTPError):
L145: def __init__(self, conn: HTTPConnection, message: str) -> None:
L150: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L155: def pool(self) -> HTTPConnection:
L166: class NameResolutionError(NewConnectionError):
L169: def __init__(self, host: str, conn: HTTPConnection, reason: socket.gaierror):
L175: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L180: class EmptyPoolError(PoolError):
L184: class FullPoolError(PoolError):
L188: class ClosedPoolError(PoolError):

```

```

L192: class LocationValueError(ValueError, HTTPError):
L196: class LocationParseError(LocationValueError):
L199: def __init__(self, location: str) -> None:
L206: class URLSchemeUnknown(LocationValueError):
L209: def __init__(self, scheme: str):
L216: class ResponseError(HTTPError):
L223: class SecurityWarning(HTTPWarning):
L227: class InsecureRequestWarning(SecurityWarning):
L231: class NotOpenSSLWarning(SecurityWarning):
L235: class SystemTimeWarning(SecurityWarning):
L239: class InsecurePlatformWarning(SecurityWarning):
L243: class DependencyWarning(HTTPWarning):
L250: class ResponseNotChunked(ProtocolError, ValueError):
L254: class BodyNotHttpLibCompatible(HTTPError):
L261: class IncompleteRead(HTTPError, httplib_IncompleteRead):
L272: def __init__(self, partial: int, expected: int) -> None:
L276: def __repr__(self) -> str:
L283: class InvalidChunkLength(HTTPError, httplib_IncompleteRead):
L286: def __init__(self, response: HTTPResponse, length: bytes) -> None:
L292: def __repr__(self) -> str:
L299: class InvalidHeader(HTTPError):
L303: class ProxySchemeUnknown(AssertionError, URLSchemeUnknown):
L308: def __init__(self, scheme: str | None) -> None:
L320: class ProxySchemeUnsupported(ValueError):
L324: class HeaderParsingError(HTTPError):
L327: def __init__(
L334: class UnrewindableBodyError(HTTPError):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/_request_methods.py

```

L20: class RequestMethods:
L51: def __init__(self, headers: typing.Mapping[str, str] | None = None) -> None:
L54: def urlopen(
L69: def request(
L147: def request_encode_url(
L184: def request_encode_body(

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/__init__.py

```

L74: def add_stderr_logger(
L107: def disable_warnings(category: type[Warning] = exceptions.HTTPWarning) -> None:
L117: def request(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/poolmanager.py

```

L56: class PoolKey(typing.NamedTuple):
L95: def _default_key_normalizer(
L162: class PoolManager(RequestMethods):
L199: def __init__(
L230: def __enter__(self) -> Self:
L233: def __exit__(
L243: def _new_pool(
L281: def clear(self) -> None:
L290: def connection_from_host(
L319: def connection_from_context(
L344: def connection_from_pool_key(
L370: def connection_from_url(
L388: def _merge_pool_kwargs(
L410: def _proxy_requires_url_absolute_form(self, parsed_url: Url) -> bool:
L423: def urlopen( # type: ignore[override]
L506: class ProxyManager(PoolManager):
L563: def __init__(
L604: def connection_from_host(
L620: def _set_proxy_headers(
L637: def urlopen( # type: ignore[override]
L652: def proxy_from_url(url: str, **kw: typing.Any) -> ProxyManager:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/filepost.py

```

L22: def choose_boundary() -> str:
L29: def iter_field_objects(fields: _TYPE_FIELDS) -> typing.Iterable[RequestField]:
L51: def encode_multipart_formdata(

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/urllib3/_base_connection.py**

```

L14: class ProxyConfig(typing.NamedTuple):
L21: class _ResponseOptions(typing.NamedTuple):
L37: class BaseHTTPConnection(Protocol):
L56: def __init__(
L69: def set_tunnel(
L77: def connect(self) -> None: ...
L79: def request(
L95: def getresponse(self) -> BaseHTTPResponse: ...
L97: def close(self) -> None: ...
L100: def is_closed(self) -> bool:
L107: def is_connected(self) -> bool:
L111: def has_connected_to_proxy(self) -> bool:

```

```
L117: class BaseHTTPSConnection(BaseHTTPConnection, Protocol):
L142: def __init__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/connectionpool.py

```
L67: class ConnectionPool:
L81: def __init__(self, host: str, port: int | None = None) -> None:
L94: def __str__(self) -> str:
L97: def __enter__(self) -> Self:
L100: def __exit__(
L110: def close(self) -> None:
L120: class HTTPConnectionPool(ConnectionPool, RequestMethods):
L175: def __init__(
L236: def _new_conn(self) -> BaseHTTPConnection:
L256: def _get_conn(self, timeout: float | None = None) -> BaseHTTPConnection:
L294: def _put_conn(self, conn: BaseHTTPConnection | None) -> None:
L337: def _validate_conn(self, conn: BaseHTTPConnection) -> None:
L342: def _prepare_proxy(self, conn: BaseHTTPConnection) -> None:
L346: def _get_timeout(self, timeout: _TYPE_TIMEOUT) -> Timeout:
L358: def _raise_timeout(
L377: def _make_request(
L558: def close(self) -> None:
L570: def is_same_host(self, url: str) -> bool:
L592: def urlopen( # type: ignore[override]
L976: class HTTPSConnectionPool(HTTPConnectionPool):
L993: def __init__(
L1042: def _prepare_proxy(self, conn: HTTPSConnection) -> None: # type: ignore[override]
L1057: def _new_conn(self) -> BaseHTTPSConnection:
L1098: def _validate_conn(self, conn: BaseHTTPConnection) -> None:
L1121: def connection_from_url(url: str, **kw: typing.Any) -> HTTPConnectionPool:
L1151: def _normalize_host(host: None, scheme: str | None) -> None: ...
L1155: def _normalize_host(host: str, scheme: str | None) -> str: ...
L1158: def _normalize_host(host: str | None, scheme: str | None) -> str | None:
L1176: def _url_from_pool(
L1183: def _close_pool_connections(pool: queue.LifoQueue[typing.Any]) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/timeout.py

```
L14: class _TYPE_DEFAULT(Enum):
L25: class Timeout:
L109: def __init__(
L120: def __repr__(self) -> str:
L127: def resolve_default_timeout(timeout: _TYPE_TIMEOUT) -> float | None:
L131: def _validate_timeout(cls, value: _TYPE_TIMEOUT, name: str) -> _TYPE_TIMEOUT:
L173: def from_float(cls, timeout: _TYPE_TIMEOUT) -> Timeout:
```

```

L188: def clone(self) -> Timeout:
L202: def start_connect(self) -> float:
L213: def get_connect_duration(self) -> float:
L228: def connect_timeout(self) -> _TYPE_TIMEOUT:
L246: def read_timeout(self) -> float | None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/retry.py

```

L33: class RequestHistory(typing.NamedTuple):
L41: class Retry:
L219: def __init__(
L266: def new(self, **kw: typing.Any) -> Self:
L291: def from_int(
L309: def get_backoff_time(self) -> float:
L328: def parse_retry_after(self, retry_after: str) -> float:
L349: def get_retry_after(self, response: BaseHTTPResponse) -> float | None:
L359: def sleep_for_retry(self, response: BaseHTTPResponse) -> bool:
L367: def _sleep_backoff(self) -> None:
L373: def sleep(self, response: BaseHTTPResponse | None = None) -> None:
L389: def _is_connection_error(self, err: Exception) -> bool:
L397: def _is_read_error(self, err: Exception) -> bool:
L403: def _is_method_retryable(self, method: str) -> bool:
L411: def is_retry(
L433: def is_exhausted(self) -> bool:
L452: def increment(
L549: def __repr__(self) -> str:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/wait.py

```

L33: def select_wait_for_socket(
L57: def poll_wait_for_socket(
L74: def do_poll(t: float | None) -> list[tuple[int, int]]:
L82: def _have_working_poll() -> bool:
L95: def wait_for_socket(
L113: def wait_for_read(sock: socket.socket, timeout: float | None = None) -> bool:
L120: def wait_for_write(sock: socket.socket, timeout: float | None = None) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/connection.py

```

L15: def is_connection_dropped(conn: BaseHTTPConnection) -> bool: # Platform-specific
L27: def create_connection(
L93: def _set_socket_options(
L103: def allowed_gai_family() -> socket.AddressFamily:
L114: def _has_ipv6(host: str) -> bool:

```


Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/url.py

```

L80: class Url(
L100: def __new__( # type: ignore[no-untyped-def]
L117: def hostname(self) -> str | None:
L122: def request_uri(self) -> str:
L132: def authority(self) -> str | None:
L148: def netloc(self) -> str | None:
L162: def url(self) -> str:
L209: def __str__(self) -> str:
L214: def _encode_invalid_chars(
L221: def _encode_invalid_chars(
L227: def _encode_invalid_chars(
L263: def _remove_path_dot_segments(path: str) -> str:
L294: def _normalize_host(host: None, scheme: str | None) -> None: ...
L298: def _normalize_host(host: str, scheme: str | None) -> str: ...
L301: def _normalize_host(host: str | None, scheme: str | None) -> str | None:
L330: def _idna_encode(name: str) -> bytes:
L349: def _encode_target(target: str) -> str:
L367: def parse_url(url: str) -> Url:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/response.py

```

L9: def is_fp_closed(obj: object) -> bool:
L40: def assert_header_parsing(headers: httplib.HTTPMessage) -> None:
L91: def is_response_to_head(response: httplib.HTTPResponse) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/ssltransport.py

```

L22: class SSLTransport:
L34: def _validate_ssl_context_for_tls_in_tls(ssl_context: ssl.SSLContext) -> None:
L49: def __init__(
L72: def __enter__(self) -> Self:
L75: def __exit__(self, *_: typing.Any) -> None:
L78: def fileno(self) -> int:
L81: def read(self, len: int = 1024, buffer: typing.Any | None = None) -> int | bytes:
L84: def recv(self, buflen: int = 1024, flags: int = 0) -> int | bytes:
L89: def recv_into(
L101: def sendall(self, data: bytes, flags: int = 0) -> None:
L111: def send(self, data: bytes, flags: int = 0) -> int:
L116: def makefile(
L168: def unwrap(self) -> None:
L171: def close(self) -> None:
L175: def getpeercert(

```

```

L180: def getpeercert(self, binary_form: typing.Literal[True]) -> bytes | None: ...
L182: def getpeercert(self, binary_form: bool = False) -> _TYPE_PEER_CERT_RET:
L185: def version(self) -> str | None:
L188: def cipher(self) -> tuple[str, str, int] | None:
L191: def selected_alpn_protocol(self) -> str | None:
L194: def shared_ciphers(self) -> list[tuple[str, str, int]] | None:
L197: def compression(self) -> str | None:
L200: def settimeout(self, value: float | None) -> None:
L203: def gettimeout(self) -> float | None:
L206: def _decref_socketios(self) -> None:
L209: def _wrap_ssl_read(self, len: int, buffer: bytearray | None = None) -> int | bytes:
L220: def _ssl_io_loop(self, func: typing.Callable[[], None]) -> None: ...
L224: def _ssl_io_loop(self, func: typing.Callable[[bytes], int], arg1: bytes) -> int: ...
L228: def _ssl_io_loop(
L235: def _ssl_io_loop(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/ssl_match_hostname.py

```

L20: class CertificateError(ValueError):
L24: def _dnsname_match(
L80: def _ipaddress_match(ipname: str, host_ip: IPv4Address | IPv6Address) -> bool:
L95: def match_hostname(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/proxy.py

```

L11: def connection_requires_http_tunnel(

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/ssl_.py

```

L30: def _is_has_never_check_common_name_reliable(
L46: class _TYPE_PEER_CERT_RET_DICT(TypedDict, total=False):
L107: def assert_fingerprint(cert: bytes | None, fingerprint: str) -> None:
L141: def resolve_cert_reqs(candidate: None | int | str) -> VerifyMode:
L164: def resolve_ssl_version(candidate: None | int | str) -> int:
L180: def create_urllib3_context(
L328: def ssl_wrap_socket(
L346: def ssl_wrap_socket(
L363: def ssl_wrap_socket(
L437: def is_ipaddress(hostname: str | bytes) -> bool:
L450: def _is_key_file_encrypted(key_file: str) -> bool:
L461: def _ssl_wrap_socket_impl(

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/util.py

```
L7: def to_bytes(
L19: def to_str(
L31: def reraise(
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/urllib3/util/request.py**

```
L44: class _TYPE_FAILEDTELL(Enum):
L60: def make_headers(
L142: def set_file_position(
L162: def rewind_body(body: typing.IO[typing.AnyStr], body_pos: _TYPE_BODY_POSITION) -> None:
L192: class ChunksAndContentLength(typing.NamedTuple):
L197: def body_to_chunks(
L230: def chunk_readable() -> typing.Iterable[bytes]:
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/urllib3/http2/connection.py**

```
L29: def _is_legal_header_name(name: bytes) -> bool:
L44: def _is_illegal_header_value(value: bytes) -> bool:
L54: class _LockedObject(typing.Generic[T]):
L68: def __init__(self, obj: T):
L72: def __enter__(self) -> T:
L76: def __exit__(
L85: class HTTP2Connection(HTTPSCConnection):
L86: def __init__(
L101: def _new_h2_conn(self) -> _LockedObject[h2.connection.H2Connection]:
L105: def connect(self) -> None:
L112: def putrequest( # type: ignore[override]
L143: def putheader(self, header: str | bytes, *values: str | bytes) -> None: # type:
ignore[override]
L156: def endheaders(self, message_body: typing.Any = None) -> None: # type:
ignore[override]
L170: def send(self, data: typing.Any) -> None:
L215: def set_tunnel(
L226: def getresponse( # type: ignore[override]
L268: def request( # type: ignore[override]
L307: def close(self) -> None:
L324: class HTTP2Response(BaseHTTPResponse):
L326: def __init__(
L349: def data(self) -> bytes:
L352: def get_redirect_location(self) -> None:
L355: def close(self) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/http2/__init__.py

```
L15: def inject_into_urllib3() -> None:
L43: def extract_from_urllib3() -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/http2/probe.py

```
L6: class _HTTP2ProbeCache:
L13: def __init__(self) -> None:
L18: def acquire_and_get(self, host: str, port: int) -> bool | None:
L51: def set_and_release(
L65: def _values(self) -> dict[tuple[str, int], bool | None]:
L70: def _reset(self) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/pyopenssl.py

```
L50: class UnsupportedExtension(Exception): # type: ignore[no-redef]
L138: def inject_into_urllib3() -> None:
L149: def extract_from_urllib3() -> None:
L158: def _validate_dependencies_met() -> None:
L184: def _dnsname_to_stdlib(name: str) -> str | None:
L198: def idna_encode(name: str) -> bytes | None:
L225: def get_subj_alt_name(peer_cert: X509) -> list[tuple[str, str]]:
L273: class WrappedSocket:
L276: def __init__(
L288: def fileno(self) -> int:
L292: def _decref_socketios(self) -> None:
L298: def recv(self, *args: typing.Any, **kwargs: typing.Any) -> bytes:
L323: def recv_into(self, *args: typing.Any, **kwargs: typing.Any) -> int:
L346: def settimeout(self, timeout: float) -> None:
L349: def _send_until_done(self, data: bytes) -> int:
L360: def sendall(self, data: bytes) -> None:
L368: def shutdown(self, how: int) -> None:
L374: def close(self) -> None:
L379: def _real_close(self) -> None:
L385: def getpeercert(
L401: def version(self) -> str:
L404: def selected_alpn_protocol(self) -> str | None:
L412: class PyOpenSSLContext:
L419: def __init__(self, protocol: int) -> None:
L429: def options(self) -> int:
```

```

L433: def options(self, value: int) -> None:
L438: def verify_flags(self) -> int:
L442: def verify_flags(self, value: int) -> None:
L447: def verify_mode(self) -> int:
L451: def verify_mode(self, value: ssl.VerifyMode) -> None:
L454: def set_default_verify_paths(self) -> None:
L457: def set_ciphers(self, ciphers: bytes | str) -> None:
L462: def load_verify_locations(
L479: def load_cert_chain(
L495: def set_alpn_protocols(self, protocols: list[bytes | str]) -> None:
L499: def wrap_socket(
L530: def _set_ctx_options(self) -> None:
L538: def minimum_version(self) -> int:
L542: def minimum_version(self, minimum_version: int) -> None:
L547: def maximum_version(self) -> int:
L551: def maximum_version(self, maximum_version: int) -> None:
L556: def _verify_callback(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/socks.py

```

L75: class _TYPE SOCKS_OPTIONS(typing.TypedDict):
L84: class SOCKSConnection(HTTPConnection):
L89: def __init__(
L98: def _new_conn(self) -> socks.socksocket:
L161: class SOCKSHTTPConnection(SOCKSConnection, HTTPConnection):
L165: class SOCKSHTTPConnectionPool(HTTPConnectionPool):
L169: class SOCKSHTTPConnectionPool(HTTPConnectionPool):
L173: class SOCKSProxyManager(PoolManager):
L184: def __init__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/fetch.py

```

L71: class _RequestError(Exception):
L72: def __init__(
L85: class _StreamingError(_RequestError):
L89: class _TimeoutError(_RequestError):
L93: def _obj_from_dict(dict_val: dict[str, Any]) -> JsProxy:
L97: class _ReadStream(io.RawIOBase):
L98: def __init__(
L118: def __del__(self) -> None:
L122: def is_closed(self) -> bool:
L127: def closed(self) -> bool:
L130: def close(self) -> None:

```

```

L144: def readable(self) -> bool:
L147: def writable(self) -> bool:
L150: def seekable(self) -> bool:
L153: def readinto(self, byte_obj: Buffer) -> int:
L200: class _StreamingFetcher:
L201: def __init__(self) -> None:
L214: def promise_resolver(js_resolve_fn: JsProxy, js_reject_fn: JsProxy) -> None:
L215: def onMsg(e: JsProxy) -> None:
L219: def onErr(e: JsProxy) -> None:
L229: def send(self, request: EmscriptenRequest) -> EmscriptenResponse:
L302: class _JSPiReadStream(io.RawIOBase):
L324: def __init__(
L342: def __del__(self) -> None:
L346: def is_closed(self) -> bool:
L351: def closed(self) -> bool:
L354: def close(self) -> None:
L367: def readable(self) -> bool:
L370: def writable(self) -> bool:
L373: def seekable(self) -> bool:
L376: def _get_next_buffer(self) -> bool:
L392: def readinto(self, byte_obj: Buffer) -> int:
L410: def is_in_browser_main_thread() -> bool:
L414: def is_cross_origin_isolated() -> bool:
L418: def is_in_node() -> bool:
L427: def is_worker_available() -> bool:
L449: def send_streaming_request(request: EmscriptenRequest) -> EmscriptenResponse | None:
L469: def _show_timeout_warning() -> None:
L480: def _show_streaming_warning() -> None:
L499: def send_request(request: EmscriptenRequest) -> EmscriptenResponse:
L548: def send_jspi_request(
L626: def _run_sync_with_timeout(
L680: def has_jspi() -> bool:
L699: def _is_node_js() -> bool:
L714: def streaming_ready() -> bool | None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/
connection.py**

```

L25: class EmscriptenHTTPConnection:
L46: def __init__(
L73: def set_tunnel(
L82: def connect(self) -> None:
L85: def request(
L129: def getresponse(self) -> BaseHTTPResponse:
L139: def close(self) -> None:
L144: def is_closed(self) -> bool:
L152: def is_connected(self) -> bool:

```

```

L157: def has_connected_to_proxy(self) -> bool:
L165: class EmscriptenHTTPConnection(EmscriptenHTTPConnection):
L182: def __init__(
L242: def set_cert(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/
response.py**

```

L23: class EmscriptenResponse:
L30: class EmscriptenHttpResponseWrapper(BaseHTTPResponse):
L31: def __init__(
L57: def url(self) -> str | None:
L61: def url(self, url: str | None) -> None:
L65: def connection(self) -> BaseHTTPConnection | BaseHTTPSConnection | None:
L69: def retries(self) -> Retry | None:
L73: def retries(self, retries: Retry | None) -> None:
L77: def stream(
L103: def _init_length(self, request_method: str | None) -> int | None:
L140: def read(
L180: def read_chunked(
L192: def release_conn(self) -> None:
L199: def drain_conn(self) -> None:
L203: def data(self) -> bytes:
L209: def json(self) -> typing.Any:
L230: def close(self) -> None:
L240: def _error_catcher(self) -> typing.Generator[None]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/
__init__.py**

```

L9: def inject_into_urllib3() -> None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/
request.py**

```

L9: class EmscriptenRequest:
L18: def set_header(self, name: str, value: str) -> None:
L21: def set_body(self, body: _TYPE_BODY | None) -> None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/compat.py

```

L6: def ToASCII(label: str) -> bytes:
L19: def ToUnicode(label: Union[bytes, bytearray]) -> str:
L32: def nameprep(s: Any) -> None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/idnadata.py

```

L109: def joining_types() -> Dict[int, int]:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/core.py

```

L27: class IDNAError(UnicodeError):
L33: class IDNABidiError(IDNAError):
L39: class InvalidCodepoint(IDNAError):
L45: class InvalidCodepointContext(IDNAError):
L51: def _combining_class(cp: int) -> int:
L58: def _is_script(cp: str, script: str) -> bool:
L62: def _punycode(s: str) -> bytes:
L66: def _unot(s: int) -> str:
L70: def valid_label_length(label: Union[bytes, str]) -> bool:
L85: def valid_string_length(domain: Union[bytes, str], trailing_dot: bool) -> bool:
L99: def check_bidi(label: str, check_ltr: bool = False) -> bool:
L173: def check_initial_combiner(label: str) -> bool:
L188: def check_hyphen_ok(label: str) -> bool:
L206: def check_nfc(label: str) -> None:
L216: def valid_contextj(label: str, pos: int) -> bool:
L270: def valid_contexto(label: str, pos: int, exception: bool = False) -> bool:
L316: def check_label(label: Union[str, bytes, bytearray]) -> None:
L373: def alabel(label: str) -> bytes:
L404: def ulabel(label: Union[str, bytes, bytearray]) -> str:
L445: def uts46_remap(domain: str, std3_rules: bool = True, transitional: bool = False) -> str:
L500: def encode(
L570: def decode(

```

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/codec.py

```

L7: class Codec(codecs.Codec):
L18: def encode(self, data: str, errors: str = "strict") -> Tuple[bytes, int]: # ty: ignore[invalid-method-override]
L27: def decode(self, data: bytes, errors: str = "strict") -> Tuple[str, int]: # ty: ignore[invalid-method-override]
L37: class IncrementalEncoder(codecs.BufferedIncrementalEncoder):
L49: def _buffer_encode(self, data: str, errors: str, final: bool) -> Tuple[bytes, int]: # ty: ignore[invalid-method-override]

```



```

L82: class IncrementalDecoder(codecs.BufferedIncrementalDecoder):
L92: def _buffer_decode(self, data: Any, errors: str, final: bool) -> Tuple[str, int]: # ty:
ignore[invalid-method-override]
L127: class StreamWriter(Codec, codecs.StreamWriter):
L131: class StreamReader(Codec, codecs.StreamReader):
L135: def search_function(name: str) -> Optional[codecs.CodecInfo]:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/intranges.py

```

L12: def intranges_from_list(list_: List[int]) -> Tuple[int, ...]:
L33: def _encode_range(start: int, end: int) -> int:
L37: def _decode_range(r: int) -> Tuple[int, int]:
L41: def intranges_contain(int_: int, ranges: Tuple[int, ...]) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_elffile.py

```

L18: class ELFInvalid(ValueError):
L22: class EIClass(enum.IntEnum):
L27: class EIData(enum.IntEnum):
L32: class EMachine(enum.IntEnum):
L40: class ELFFile:
L45: def __init__(self, f: IO[bytes]) -> None:
L90: def _read(self, fmt: str) -> tuple[int, ...]:
L94: def interpreter(self) -> str | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_manylinux.py

```

L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:
L40: def _is_linux_armhf(executable: str) -> bool:
L55: def _is_linux_i686(executable: str) -> bool:
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:
L81: class _GLibCVersion(NamedTuple):
L86: def _glibc_version_string_confstr() -> str | None:
L105: def _glibc_version_string_ctypes() -> str | None:
L149: def _glibc_version_string() -> str | None:
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:
L174: def _get_glibc_version() -> _GLibCVersion:
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/direct_url.py

```

L27: def __dir__() -> list[str]:
L34: class _FromMappingProtocol(Protocol): # pragma: no cover
L36: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L42: def _json_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L46: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L59: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
L66: def _get_object(
L83: def _strip_auth_from_netloc(netloc: str, safe_user_passwords: Collection[str]) -> str:
L94: def _strip_url(url: str, safe_user_passwords: Collection[str]) -> str:
L112: class DirectUrlValidationError(Exception):
L118: def __init__(
L136: def __str__(self) -> str:
L142: class _DirectUrlRequiredKeyError(DirectUrlValidationError):
L143: def __init__(self, key: str) -> None:
L148: class VcsInfo:
L153: def __init__(
L165: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L175: class ArchiveInfo:
L178: def __init__(
L186: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L221: class DirInfo:
L224: def __init__(
L232: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L239: class DirectUrl:
L248: def __init__(
L264: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L289: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L293: def to_dict(
L320: def validate(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/metadata.py

```

L40: def __dir__() -> list[str]:
L44: class InvalidMetadata(ValueError):
L50: def __init__(self, field: str, message: str) -> None:
L59: class RawMetadata(TypedDict, total=False):
L178: def _parse_keywords(data: str) -> list[str]:
L183: def _parse_project_urls(data: list[str]) -> dict[str, str]:
L222: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:
L291: class RFC822Policy(email.policy.EmailPolicy):
L301: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:
L308: class RFC822Message(email.message.EmailMessage):
L315: def __init__(self) -> None:
L318: def as_bytes(
L329: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
L520: class _Validator(Generic[T]):
L534: def __init__(
L541: def __set_name__(self, _owner: Metadata, name: str) -> None:

```

```

L545: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:
L572: def _invalid_metadata(
L581: def _process_metadata_version(self, value: str) -> _MetadataVersion:
L587: def _process_name(self, value: str) -> str:
L600: def _process_version(self, value: str) -> version_module.Version:
L610: def _process_summary(self, value: str) -> str:
L616: def _process_description_content_type(self, value: str) -> str:
L648: def _process_dynamic(self, value: list[str]) -> list[str]:
L660: def _process_provides_extra(
L675: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:
L683: def _process_requires_dist(
L698: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
L706: def _process_license_files(self, value: list[str]) -> list[str]:
L732: def _process_import_names(self, value: list[str]) -> list[str]:
L757: class Metadata:
L769: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata:
L823: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
L932: def as_rfc822(self) -> RFC822Message:
L940: def _write_metadata(self, message: RFC822Message) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/markers.py

```

L30: def __dir__() -> list[str]:
L54: class InvalidMarker(ValueError):
L62: class UndefinedComparison(ValueError):
L71: class UndefinedEnvironmentName(ValueError):
L75: class Environment(TypedDict):
L152: def _normalize_extras(
L168: def _normalize_extra_values(results: MarkerList) -> MarkerList:
L176: def _format_marker(
L216: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
L233: def _normalize(
L254: def _evaluate_markers(
L287: def _format_full_version(info: sys._version_info) -> str:
L295: def default_environment() -> Environment:
L317: class Marker:
L339: def __init__(self, marker: str) -> None:
L370: def _from_markers(cls, markers: MarkerList) -> Marker:
L379: def __str__(self) -> str:
L382: def __repr__(self) -> str:
L385: def __hash__(self) -> int:
L388: def __eq__(self, other: object) -> bool:
L394: def __getstate__(self) -> str:
L399: def __setstate__(self, state: object) -> None:
L423: def __and__(self, other: Marker) -> Marker:
L428: def __or__(self, other: Marker) -> Marker:
L433: def evaluate(
L482: def _repair_python_full_version(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/specifiers.py

```

L48: def __dir__() -> list[str]:
L52: def _validate_spec(spec: object, /) -> TypeGuard[tuple[str, str]]:
L61: def _validate_pre(pre: object, /) -> TypeGuard[bool | None]:
L74: def _trim_release(release: tuple[int, ...]) -> tuple[int, ...]:
L82: class _BoundaryKind(enum.Enum):
L90: class _BoundaryVersion:
L113: def __init__(self, version: Version, kind: _BoundaryKind) -> None:
L118: def _is_family(self, other: Version) -> bool:
L133: def __eq__(self, other: object) -> bool:
L138: def __lt__(self, other: _BoundaryVersion | Version) -> bool:
L145: def __hash__(self) -> int:
L148: def __repr__(self) -> str:
L153: class _LowerBound:
L163: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:
L167: def __eq__(self, other: object) -> bool:
L172: def __lt__(self, other: _LowerBound) -> bool:
L185: def __hash__(self) -> int:
L188: def __repr__(self) -> str:
L194: class _UpperBound:
L204: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:
L208: def __eq__(self, other: object) -> bool:
L213: def __lt__(self, other: _UpperBound) -> bool:
L226: def __hash__(self) -> int:
L229: def __repr__(self) -> str:
L246: def _range_is_empty(lower: _LowerBound, upper: _UpperBound) -> bool:
L255: def _intersect_ranges(
L281: def _next_prefix_dev0(version: Version) -> Version:
L287: def _base_dev0(version: Version) -> Version:
L292: def _coerce_version(version: UnparsedVersion) -> Version | None:
L301: def _public_version(version: Version) -> Version:
L307: def _post_base(version: Version) -> Version:
L315: def _earliest_prerelease(version: Version) -> Version:
L323: def _nearest_non_prerelease(
L344: class InvalidSpecifier(ValueError):
L356: class BaseSpecifier(metaclass=abc.ABCMeta):
L361: def _str(self) -> str:
L366: def __str__(self) -> str:
L373: def __hash__(self) -> int:
L379: def __eq__(self, other: object) -> bool:
L389: def prereleases(self) -> bool | None:
L397: def prereleases(self, value: bool) -> None:
L404: def contains(self, item: str, prereleases: bool | None = None) -> bool:
L410: def filter(
L418: def filter(
L426: def filter(
L438: class Specifier(BaseSpecifier):

```

```

L573: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:
L611: def _get_spec_version(self, version: str) -> Version | None:
L623: def _require_spec_version(self, version: str) -> Version:
L633: def _to_ranges(self) -> Sequence[_VersionRange]:
L657: def _wildcard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:
L670: def _standard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:
L733: def prereleases(self) -> bool | None:
L761: def prereleases(self, value: bool | None) -> None:
L764: def __getstate__(self) -> tuple[tuple[str, str], bool | None]:
L770: def __setstate__(self, state: object) -> None:
L805: def operator(self) -> str:
L814: def version(self) -> str:
L822: def __repr__(self) -> str:
L840: def __str__(self) -> str:
L851: def _canonical_spec(self) -> tuple[str, str]:
L864: def __hash__(self) -> int:
L867: def __eq__(self, other: object) -> bool:
L896: def _get_operator(self, op: str) -> CallableOperator:
L902: def _compare_compatible(self, prospective: Version, spec: str) -> bool:
L922: def _get_wildcard_split(self, spec: str) -> tuple[list[str], int]:
L938: def _compare_equal(self, prospective: Version, spec: str) -> bool:
L974: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:
L977: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:
L983: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
L989: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:
L1014: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
L1046: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
L1049: def __contains__(self, item: str | Version) -> bool:
L1070: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
L1098: def filter(
L1106: def filter(
L1113: def filter(
L1198: def _pep440_filter_prereleases(
L1240: def _version_split(version: str) -> list[str]:
L1262: def _version_join(components: list[str]) -> str:
L1273: def _is_not_suffix(segment: str) -> bool:
L1279: def _numeric_prefix_len(split: list[str]) -> int:
L1293: def _left_pad(split: list[str], target_numeric_len: int) -> list[str]:
L1307: def _operator_cost(op_entry: tuple[CallableOperator, str, str]) -> int:
L1334: class SpecifierSet(BaseSpecifier):
L1362: def __init__(
L1407: def _canonical_specs(self) -> tuple[Specifier, ...]:
L1417: def prereleases(self) -> bool | None:
L1437: def prereleases(self, value: bool | None) -> None:
L1441: def __getstate__(self) -> tuple[tuple[Specifier, ...], bool | None]:
L1447: def __setstate__(self, state: object) -> None:
L1504: def __repr__(self) -> str:
L1525: def __str__(self) -> str:
L1538: def __hash__(self) -> int:
L1541: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:
L1574: def __eq__(self, other: object) -> bool:

```

```

L1600: def __len__(self) -> int:
L1604: def __iter__(self) -> Iterator[Specifier]:
L1614: def _get_ranges(self) -> Sequence[_VersionRange]:
L1636: def is_unsatisfiable(self) -> bool:
L1669: def _check_prerelease_only_ranges(self) -> bool:
L1682: def _check_arbitrary_unsatisfiable(self) -> bool:
L1721: def __contains__(self, item: UnparsedVersion) -> bool:
L1742: def contains(
L1788: def filter(
L1796: def filter(
L1803: def filter(
L1899: def _filter_versions(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/dependency_groups.py

```

L19: def __dir__() -> list[str]:
L28: class DuplicateGroupNames(ValueError):
L34: class CyclicDependencyGroup(ValueError):
L39: def __init__(self, requested_group: str, group: str, include_group: str) -> None:
L57: class InvalidDependencyGroupObject(ValueError):
L69: class DependencyGroupInclude:
L72: def __init__(self, include_group: str) -> None:
L80: def __repr__(self) -> str:
L84: class DependencyGroupResolver:
L96: def __init__(
L115: def lookup(self, group: str) -> tuple[Requirement | DependencyGroupInclude, ...]:
L129: def resolve(self, group: str) -> tuple[Requirement, ...]:
L142: def _resolve(
L200: def _parse_group(
L255: def resolve_dependency_groups(
L277: def _normalize_name(name: str) -> str:
L281: def _normalize_group_names(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_tokenizer.py

```

L12: class Token:
L18: class ParserSyntaxError(Exception):
L21: def __init__(
L34: def __str__(self) -> str:
L91: class Tokenizer:
L98: def __init__(
L109: def consume(self, name: str) -> None:
L114: def check(self, name: str, *, peek: bool = False) -> bool:

```

```

L135: def expect(self, name: str, *, expected: str) -> Token:
L144: def read(self) -> Token:
L154: def raise_syntax_error(
L173: def enclosing_tokens(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_parser.py

```

L15: class Node:
L18: def __init__(self, value: str) -> None:
L21: def __str__(self) -> str:
L24: def __repr__(self) -> str:
L27: def serialize(self) -> str:
L30: def __getstate__(self) -> str:
L34: def _restore_value(self, value: object) -> None:
L41: def __setstate__(self, state: object) -> None:
L59: class Variable(Node):
L62: def serialize(self) -> str:
L66: class Value(Node):
L69: def serialize(self) -> str:
L73: class Op(Node):
L76: def serialize(self) -> str:
L87: class ParsedRequirement(NamedTuple):
L98: def parse_requirement(source: str) -> ParsedRequirement:
L102: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:
L123: def _parse_requirement_details(
L176: def _parse_requirement_marker(
L197: def _parse_extras(tokenizer: Tokenizer) -> list[str]:
L216: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:
L243: def _parse_specifier(tokenizer: Tokenizer) -> str:
L260: def _parse_version_many(tokenizer: Tokenizer) -> str:
L292: def parse_marker(source: str) -> MarkerList:
L296: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:
L302: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:
L314: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:
L336: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:
L350: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar: # noqa: RET503
L364: def process_env_var(env_var: str) -> Variable:
L371: def process_python_str(python_str: str) -> Value:
L376: def _parse_marker_op(tokenizer: Tokenizer) -> Op:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/packaging/utils.py

```

L27: def __dir__() -> list[str]:
L39: class InvalidName(ValueError):
L45: class InvalidWheelFilename(ValueError):
L51: class InvalidSdistFilename(ValueError):
L66: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:

```

```

L103: def is_normalized_name(name: str) -> bool:
L119: def canonicalize_version(
L157: def parse_wheel_filename(
L249: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/version.py

```

L37: def _deprecated(message: str) -> object:
L38: def decorator(func: Callable[[...], object]) -> object:
L40: def wrapper(*args: object, **kwargs: object) -> object:
L66: def __dir__() -> list[str]:
L81: class _VersionReplace(TypedDict, total=False):
L90: def normalize_pre(letter: str, /) -> str:
L111: def parse(version: str) -> Version:
L125: class InvalidVersion(ValueError):
L135: class _BaseVersion:
L144: def _key(self) -> tuple[Any, ...]: ...
L146: def __hash__(self) -> int:
L152: def __lt__(self, other: _BaseVersion) -> bool:
L158: def __le__(self, other: _BaseVersion) -> bool:
L164: def __eq__(self, other: object) -> bool:
L170: def __ge__(self, other: _BaseVersion) -> bool:
L176: def __gt__(self, other: _BaseVersion) -> bool:
L182: def __ne__(self, other: object) -> bool:
L266: def _validate_epoch(value: object, /) -> int:
L274: def _validate_release(value: object, /) -> tuple[int, ...]:
L286: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
L299: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:
L308: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:
L317: def _validate_local(value: object, /) -> LocalType | None:
L327: class _Version(NamedTuple):
L336: class Version(_BaseVersion):
L404: def __init__(self, version: str) -> None:
L455: def from_parts(
L501: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:
L560: def _key(self) -> CmpKey:
L574: def __hash__(self) -> int:
L592: def __lt__(self, other: _BaseVersion) -> bool:
L619: def __le__(self, other: _BaseVersion) -> bool:
L646: def __eq__(self, other: object) -> bool:
L673: def __ge__(self, other: _BaseVersion) -> bool:
L700: def __gt__(self, other: _BaseVersion) -> bool:
L727: def __ne__(self, other: object) -> bool:
L754: def __getstate__(
L776: def __setstate__(self, state: object) -> None:
L823: def _version(self) -> _Version:
L830: def _version(self, value: _Version) -> None:
L840: def __repr__(self) -> str:

```



```

L848: def __str__(self) -> str:
L880: def _str(self) -> str:
L885: def epoch(self) -> int:
L896: def release(self) -> tuple[int, ...]:
L912: def pre(self) -> tuple[Literal["a", "b", "rc"], int] | None:
L927: def post(self) -> int | None:
L938: def dev(self) -> int | None:
L949: def local(self) -> str | None:
L963: def public(self) -> str:
L979: def base_version(self) -> str:
L1000: def is_prerelease(self) -> bool:
L1017: def is_postrelease(self) -> bool:
L1028: def is_devrelease(self) -> bool:
L1039: def major(self) -> int:
L1048: def minor(self) -> int:
L1059: def micro(self) -> int:
L1070: class _TrimmedRelease(Version):
L1073: def __init__(self, version: str | Version) -> None:
L1086: def release(self) -> tuple[int, ...]:
L1104: def _parse_letter_version(
L1131: def _parse_local_version(local: str | None) -> LocalType | None:
L1157: def _cmpkey(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_structures.py

```

L18: class InfinityType:
L21: def __repr__(self) -> str:
L25: class NegativeInfinityType:
L28: def __repr__(self) -> str:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/packaging/tags.py

```

L54: def __dir__() -> list[str]:
L75: def _compute_32_bit_interpreter() -> bool:
L82: class UnsortedTagsError(ValueError):
L88: class Tag:
L108: def __init__(self, interpreter: str, abi: str, platform: str) -> None:
L128: def interpreter(self) -> str:
L137: def abi(self) -> str:
L144: def platform(self) -> str:
L150: def __eq__(self, other: object) -> bool:
L161: def __hash__(self) -> int:
L164: def __str__(self) -> str:
L167: def __repr__(self) -> str:
L170: def __getstate__(self) -> tuple[str, str, str]:
L175: def __setstate__(self, state: object) -> None:
L203: def parse_tag(tag: str, *, validate_order: bool = False) -> frozenset[Tag]:

```

```

L240: def _get_config_var(name: str, warn: bool = False) -> int | str | None:
L249: def _normalize_string(string: str) -> str:
L253: def _is_threaded_cpython(abis: list[str]) -> bool:
L269: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:
L279: def _abi3t_applies(python_version: PythonVersion, threading: bool) -> bool:
L292: def _cpython_abis(py_version: PythonVersion, warn: bool = False) -> list[str]:
L325: def cpython_tags(
L404: def _generic_abi() -> list[str]:
L445: def generic_tags(
L486: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:
L501: def compatible_tags(
L536: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:
L546: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:
L578: def mac_platforms(
L667: def ios_platforms(
L729: def android_platforms(
L766: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:
L785: def _emscripten_platforms() -> Iterator[str]:
L794: def _generic_platforms() -> Iterator[str]:
L798: def platform_tags() -> Iterator[str]:
L816: def interpreter_name() -> str:
L829: def interpreter_version(*, warn: bool = False) -> str:
L841: def _version_nodot(version: PythonVersion) -> str:
L845: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:
L889: def create_compatible_tags_selector(
L919: def selector(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/errors.py

```

L11: def __dir__() -> list[str]:
L19: class ExceptionGroup(Exception):
L29: def __init__(self, message: str, exceptions: list[Exception]) -> None:
L33: def __repr__(self) -> str:
L38: class _ErrorCollector:
L59: def finalize(self, msg: str) -> None:
L65: def on_exit(self, msg: str) -> typing.Generator[_ErrorCollector, None, None]:
L75: def collect(self, *err_cls: type[Exception]) -> typing.Generator[None, None, None]:
L89: def error(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_musllinux.py

```

L18: class _MuslVersion(NamedTuple):
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/requirements.py

```

L20: def __dir__() -> list[str]:
L24: class InvalidRequirement(ValueError):
L30: class Requirement:
L53: def __init__(self, requirement_string: str) -> None:
L68: def _iter_parts(self, name: str) -> Iterator[str]:
L86: def __getstate__(self) -> str:
L91: def __setstate__(self, state: object) -> None:
L110: def __str__(self) -> str:
L113: def __repr__(self) -> str:
L116: def __hash__(self) -> int:
L119: def __eq__(self, other: object) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/pylock.py

```

L54: def __dir__() -> list[str]:
L62: class _FromMappingProtocol(Protocol): # pragma: no cover
L64: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L73: def is_valid_pylock_path(path: Path) -> bool:
L78: def _toml_key(key: str) -> str:
L82: def _toml_value(key: str, value: Any) -> Any: # noqa: ANN401
L90: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L98: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L111: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
L118: def _get_sequence(
L140: def _get_as(
L159: def _get_required_as(
L172: def _get_sequence_as(
L191: def _get_object(
L203: def _get_sequence_of_objects(
L219: def _get_required_sequence_of_objects(
L229: def _validate_normalized_name(name: str) -> NormalizedName:
L236: def _validate_path_url(path: str | None, url: str | None) -> None:
L241: def _path_name(path: str | None) -> str | None:
L254: def _url_name(url: str | None) -> str | None:
L261: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:
L269: class PylockValidationError(Exception):
L275: def __init__(
L293: def __str__(self) -> str:
L299: class _PylockRequiredKeyError(PylockValidationError):
L300: def __init__(self, key: str) -> None:
L304: class PylockUnsupportedVersionError(PylockValidationError):
L308: class PylockSelectError(Exception):

```

```

L313: class PackageVcs:
L321: def __init__(
L340: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L354: class PackageDirectory:
L359: def __init__(
L372: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L381: class PackageArchive:
L389: def __init__(
L408: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L422: class PackageSdist:
L430: def __init__(
L449: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L462: def filename(self) -> str:
L471: class PackageWheel:
L479: def __init__(
L498: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L511: def filename(self) -> str:
L520: class Package:
L535: def __init__(
L568: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L649: def is_direct(self) -> bool:
L654: class Pylock:
L667: def __init__(
L692: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L715: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L723: def to_dict(self) -> Mapping[str, Any]:
L727: def validate(self) -> None:
L733: def select(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):
L10: class SPDXException(TypedDict):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/licenses/__init__.py

```

L47: def __dir__() -> list[str]:
L60: class InvalidLicenseExpression(ValueError):
L71: def canonicalize_license_expression(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/__pip-runner__.py

```

L15: def version_str(version): # type: ignore
L36: class PipImportRedirectingFinder:
L38: def find_spec(self, fullname, path=None, target=None): # type: ignore

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pip/__init__.py

```

L6: def main(args: list[str] | None = None) -> int:

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/pyproject.py**

```

L18: def _is_list_of_str(obj: Any) -> bool:
L22: def make_pyproject_path(unpacked_source_directory: str) -> str:
L31: def load_pyproject_toml(

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/build_env.py**

```

L44: class ExtraEnviron(TypedDict, total=False):
L51: def _dedup(a: str, b: str) -> tuple[str] | tuple[str, str]:
L55: class _Prefix:
L56: def __init__(self, path: str) -> None:
L64: def get_runnable_pip() -> str:
L80: def _get_system_sitepackages() -> set[str]:
L100: class BuildEnvironmentInstaller(Protocol):
L106: def install(
L116: class SubprocessBuildEnvironmentInstaller:
L121: def __init__(
L131: def _deprecation_constraint_check(self) -> None:
L160: def install(
L266: class InprocessBuildEnvironmentInstaller:
L280: def __init__(
L320: def install(
L372: def _install_impl(self, requirements: Iterable[str], prefix: _Prefix) -> None:
L413: def _make_resolver(self) -> BaseResolver:
L437: class BuildEnvironment:
L440: def __init__(self, installer: BuildEnvironmentInstaller) -> None:
L495: def __enter__(self) -> None:
L516: def __exit__(
L528: def check_requirements(
L562: def install_requirements(
L578: class NoOpBuildEnvironment(BuildEnvironment):
L581: def __init__(self) -> None:

```

```

L584: def __enter__(self) -> None:
L587: def __exit__(
L595: def cleanup(self) -> None:
L598: def install_requirements(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/configuration.py

```

L53: def _normalize_name(name: str) -> str:
L60: def _disassemble_key(name: str) -> list[str]:
L70: def get_configuration_files() -> dict[Kind, list[str]]:
L89: class Configuration:
L103: def __init__(self, isolated: bool, load_only: Kind | None = None) -> None:
L124: def load(self) -> None:
L130: def get_file_to_edit(self) -> str | None:
L139: def items(self) -> Iterable[tuple[str, Any]]:
L145: def get_value(self, key: str) -> Any:
L160: def set_value(self, key: str, value: Any) -> None:
L180: def unset_value(self, key: str) -> None:
L214: def save(self) -> None:
L238: def _ensure_have_load_only(self) -> None:
L244: def _dictionary(self) -> dict[str, dict[str, Any]]:
L255: def _load_config_files(self) -> None:
L278: def _load_file(self, variant: Kind, fname: str) -> RawConfigParser:
L289: def _construct_parser(self, fname: str) -> RawConfigParser:
L310: def _load_environment_vars(self) -> None:
L317: def _normalized_keys(
L331: def get_environ_vars(self) -> Iterable[tuple[str, str]]:
L340: def iter_config_files(self) -> Iterable[tuple[Kind, list[str]]]:
L372: def get_values_in_config(self, variant: Kind) -> dict[str, Any]:
L376: def _get_parser_to_modify(self) -> tuple[str, RawConfigParser]:
L390: def _mark_as_modified(self, fname: str, parser: RawConfigParser) -> None:
L395: def __repr__(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/wheel_builder.py

```

L34: def _contains_egg_info(s: str) -> bool:
L42: def _should_cache(
L73: def _get_cache_dir(
L89: def _verify_one(req: InstallRequirement, wheel_path: str) -> None:
L118: def _build_one(
L152: def _build_one_inside_env(
L204: def build(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/exceptions.py

```

L44: def _is_kebab_case(s: str) -> bool:
L48: def _prefix_with_indent(
L65: class PipError(Exception):
L69: class DiagnosticPipError(PipError):
L82: def __init__(
L112: def __repr__(self) -> str:
L123: def __rich_console__(
L187: class ConfigurationError(PipError):
L191: class InstallationError(PipError):
L195: class FailedToPrepareCandidate(InstallationError):
L203: def __init__(
L212: class MissingPyProjectBuildRequires(DiagnosticPipError):
L217: def __init__(self, *, package: str) -> None:
L229: class InvalidPyProjectBuildRequires(DiagnosticPipError):
L234: def __init__(self, *, package: str, reason: str) -> None:
L246: class NoneMetadataError(PipError):
L255: def __init__(
L268: def __str__(self) -> str:
L274: class UserInstallationInvalid(InstallationError):
L277: def __str__(self) -> str:
L281: class InvalidSchemeCombination(InstallationError):
L282: def __str__(self) -> str:
L287: class DistributionNotFound(InstallationError):
L291: class RequirementsFileParseError(InstallationError):
L295: class BestVersionAlreadyInstalled(PipError):
L300: class BadCommand(PipError):
L304: class CommandError(PipError):
L308: class PreviousBuildDirError(PipError):
L312: class NetworkConnectionError(PipError):
L315: def __init__(
L336: def __str__(self) -> str:
L340: class InvalidWheelFilename(InstallationError):
L344: class UnsupportedWheel(InstallationError):
L348: class InvalidWheel(InstallationError):
L351: def __init__(self, location: str, name: str):
L355: def __str__(self) -> str:
L359: class MetadataInconsistent(InstallationError):
L367: def __init__(
L375: def __str__(self) -> str:
L382: class MetadataInvalid(InstallationError):
L385: def __init__(self, ireq: InstallRequirement, error: str) -> None:
L389: def __str__(self) -> str:
L393: class InstallationSubprocessError(DiagnosticPipError, InstallationError):
L398: def __init__(
L430: def __str__(self) -> str:
L434: class MetadataGenerationFailed(DiagnosticPipError, InstallationError):

```

```

L437: def __init__(
L449: def __str__(self) -> str:
L453: class HashErrors(InstallationError):
L456: def __init__(self) -> None:
L459: def append(self, error: HashError) -> None:
L462: def __str__(self) -> str:
L472: def __bool__(self) -> bool:
L476: class HashError(InstallationError):
L497: def body(self) -> str:
L509: def __str__(self) -> str:
L512: def _requirement_name(self) -> str:
L522: class VcsHashUnsupported(HashError):
L533: class DirectoryUrlHashUnsupported(HashError):
L544: class HashMissing(HashError):
L558: def __init__(self, gotten_hash: str) -> None:
L565: def body(self) -> str:
L586: class HashUnpinned(HashError):
L597: class HashMismatch(HashError):
L615: def __init__(self, allowed: dict[str, list[str]], gots: dict[str, _Hash]) -> None:
L625: def body(self) -> str:
L628: def _hash_comparison(self) -> str:
L640: def hash_then_or(hash_name: str) -> chain[str]:
L655: class UnsupportedPythonVersion(InstallationError):
L660: class ConfigurationFileCouldNotBeLoaded(ConfigurationError):
L663: def __init__(
L674: def __str__(self) -> str:
L690: class ExternallyManagedEnvironment(DiagnosticPipError):
L702: def __init__(self, error: str | None) -> None:
L720: def _iter_externally_managed_error_keys() -> Iterator[str]:
L742: def from_config(
L763: class UninstallMissingRecord(DiagnosticPipError):
L766: def __init__(self, *, distribution: BaseDistribution) -> None:
L790: class LegacyDistutilsInstall(DiagnosticPipError):
L793: def __init__(self, *, distribution: BaseDistribution) -> None:
L805: class InvalidInstalledPackage(DiagnosticPipError):
L808: def __init__(
L835: class IncompleteDownloadError(DiagnosticPipError):
L841: def __init__(self, download: _FileDownload) -> None:
L869: class ResolutionTooDeepError(DiagnosticPipError):
L874: def __init__(self) -> None:
L889: class InstallWheelBuildError(DiagnosticPipError):
L892: def __init__(self, failed: list[InstallRequirement]) -> None:
L903: class InvalidEggFragment(DiagnosticPipError):
L906: def __init__(self, link: Link, fragment: str) -> None:
L926: class BuildDependencyInstallError(DiagnosticPipError):
L931: def __init__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/__init__.py


```
L10: def main(args: list[str] | None = None) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cache.py

```
L27: def _hash_dict(d: dict[str, str]) -> str:
L33: class Cache:
L39: def __init__(self, cache_dir: str) -> None:
L44: def _get_cache_path_parts(self, link: Link) -> list[str]:
L77: def _get_candidates(self, link: Link, canonical_package_name: str) -> list[Any]:
L87: def get_path_for_link(self, link: Link) -> str:
L91: def get(
L103: class SimpleWheelCache(Cache):
L106: def __init__(self, cache_dir: str) -> None:
L109: def get_path_for_link(self, link: Link) -> str:
L129: def get(
L173: class EphemWheelCache(SimpleWheelCache):
L176: def __init__(self) -> None:
L185: class CacheEntry:
L186: def __init__(
L209: class WheelCache(Cache):
L216: def __init__(self, cache_dir: str) -> None:
L221: def get_path_for_link(self, link: Link) -> str:
L224: def get_ephem_path_for_link(self, link: Link) -> str:
L227: def get(
L238: def get_cache_entry(
L267: def record_download_origin(cache_dir: str, download_info: DirectUrl) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/self_outdated_check.py

```
L47: def _get_statefile_name(key: str) -> str:
L53: class SelfCheckState:
L54: def __init__(self, cache_dir: str) -> None:
L72: def key(self) -> str:
L75: def get(self, current_time: datetime.datetime) -> str | None:
L94: def set(self, pypi_version: str, current_time: datetime.datetime) -> None:
L133: class UpgradePrompt:
L137: def __rich__(self) -> Group:
L157: def _get_current_remote_pip_version(
L185: def _compute_upgrade_prompt(
L206: def pip_self_version_check_fetch(
L243: def pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/main.py

```
L4: def main(args: list[str] | None = None) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/list.py

```
L27: class _DistWithLatestInfo(BaseDistribution):
L43: class ListCommand(IndexGroupCommand):
L54: def add_options(self) -> None:
L140: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
L147: def _build_package_finder(
L170: def run(self, options: Values, args: list[str]) -> int:
L213: def get_outdated(
L222: def get_uptodate(
L231: def get_not_required(
L245: def iter_packages_latest_infos(
L251: def latest_info(
L282: def output_package_listing(
L305: def output_package_listing_columns(
L322: def format_for_columns(
L335: def wheel_build_tag(dist: BaseDistribution) -> str | None:
L382: def format_for_json(packages: _ProcessedDists, options: Values) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/install.py

```
L91: def _prevent_import_hook(name: str, args: tuple[Any, ...]) -> None:
L109: def _eagerly_import_modules() -> None:
L120: def _prevent_further_imports() -> None:
L134: def _arg_refers_to_pip(arg: str) -> bool:
L142: class InstallCommand(RequirementCommand):
L162: def add_options(self) -> None:
L358: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
L369: def run(self, options: Values, args: list[str]) -> int:
L604: def _handle_target_dir(
L658: def _determine_conflicts(
L670: def _warn_about_conflicts(
L721: def installed_packages_summary(
L745: def get_lib_location_guesses(
L763: def site_packages_writable(root: str | None, isolated: bool) -> bool:
```

```
L770: def decide_user_install(
L839: def create_os_error_message(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/lock.py

```
L26: class LockCommand(RequirementCommand):
L48: def add_options(self) -> None:
L95: def run(self, options: Values, args: list[str]) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/uninstall.py

```
L25: class UninstallCommand(Command, SessionCommandMixin):
L40: def add_options(self) -> None:
L64: def run(self, options: Values, args: list[str]) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/index.py

```
L30: class IndexCommand(IndexGroupCommand):
L40: def add_options(self) -> None:
L60: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:
L65: def run(self, options: Values, args: list[str]) -> int:
L89: def _build_package_finder(
L116: def get_available_package_versions(self, options: Values, args: list[Any]) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/debug.py

```
L28: def show_value(name: str, value: Any) -> None:
L32: def show_sys_implementation() -> None:
L39: def create_vendor_txt_map() -> dict[str, str]:
L51: def get_module_from_module_name(module_name: str) -> ModuleType | None:
L62: def get_vendor_version_from_module(module_name: str) -> str | None:
L77: def show_actual_vendor_versions(vendor_txt_versions: dict[str, str]) -> None:
L98: def show_vendor_versions() -> None:
```

```

L106: def show_tags(options: Values) -> None:
L136: def ca_bundle_info(config: Configuration) -> str:
L153: class DebugCommand(Command):
L162: def add_options(self) -> None:
L167: def run(self, options: Values, args: list[str]) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/help.py

```

L8: class HelpCommand(Command):
L15: def run(self, options: Values, args: list[str]) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/freeze.py

```

L11: def _should_suppress_build_backends() -> bool:
L15: def _dev_pkgs() -> set[str]:
L24: class FreezeCommand(Command):
L35: def add_options(self) -> None:
L87: def run(self, options: Values, args: list[str]) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/configuration.py

```

L24: class ConfigurationCommand(Command):
L60: def add_options(self) -> None:
L98: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:
L108: def run(self, options: Values, args: list[str]) -> int:
L146: def _determine_file(self, options: Values, need_value: bool) -> Kind | None:
L176: def list_values(self, options: Values, args: list[str]) -> None:
L183: def get_name(self, options: Values, args: list[str]) -> None:
L189: def set_name_value(self, options: Values, args: list[str]) -> None:
L195: def unset_name(self, options: Values, args: list[str]) -> None:
L201: def list_config_values(self, options: Values, args: list[str]) -> None:
L217: def print_config_file_values(self, variant: Kind, fname: str) -> None:
L225: def print_env_var_values(self) -> None:
L233: def open_in_editor(self, options: Values, args: list[str]) -> None:
L255: def _get_n_args(self, args: list[str], example: str, n: int) -> Any:
L269: def _save_configuration(self) -> None:
L280: def _determine_editor(self, options: Values) -> str:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/se
arch.py**

```

L26: class TransformedHit(TypedDict):
L35: class SearchCommand(Command, SessionCommandMixin):
L42: def add_options(self) -> None:
L54: def run(self, options: Values, args: list[str]) -> int:
L70: def search(self, query: list[str], options: Values) -> list[dict[str, str]]:
L88: def transform_hits(hits: list[dict[str, str]]) -> list[TransformedHit]:
L116: def print_dist_installation_info(latest: str, dist: BaseDistribution | None) -> None:
L133: def get_installed_distribution(name: str) -> BaseDistribution | None:
L138: def print_results(
L177: def highest_version(versions: list[str]) -> str:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/_
init__.py**

```

L116: def create_command(name: str, **kwargs: Any) -> Command:
L128: def get_similar_commands(name: str) -> str | None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/ca
che.py**

```

L16: class CacheCommand(Command):
L40: def add_options(self) -> None:
L52: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:
L61: def run(self, options: Values, args: list[str]) -> int:
L87: def get_cache_dir(self, options: Values, args: list[str]) -> None:
L93: def get_cache_info(self, options: Values, args: list[str]) -> None:
L135: def list_cache_items(self, options: Values, args: list[str]) -> None:
L150: def format_for_human(self, files: list[str]) -> None:
L163: def format_for_abspath(self, files: list[str]) -> None:
L167: def remove_cache_items(self, options: Values, args: list[str]) -> None:
L218: def purge_cache(self, options: Values, args: list[str]) -> None:
L224: def _cache_dir(self, options: Values, subdir: str) -> str:
L227: def _find_http_files(self, options: Values) -> list[str]:
L234: def _find_wheels(self, options: Values, pattern: str) -> list[str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/completion.py

```
L81: class CompletionCommand(Command):
L86: def add_options(self) -> None:
L122: def run(self, options: Values, args: list[str]) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/show.py

```
L20: def normalize_project_url_label(label: str) -> str:
L27: class ShowCommand(Command):
L38: def add_options(self) -> None:
L50: def run(self, options: Values, args: list[str]) -> int:
L64: class _PackageInfo(NamedTuple):
L85: def search_packages_info(query: list[str]) -> Generator[_PackageInfo, None, None]:
L102: def _get_requiring_packages(current_dist: BaseDistribution) -> Iterator[str]:
L178: def print_results(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/hash.py

```
L14: class HashCommand(Command):
L25: def add_options(self) -> None:
L39: def run(self, options: Values, args: list[str]) -> int:
L52: def _hash_of_file(path: str, algorithm: str) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/download.py

```
L16: class DownloadCommand(RequirementCommand):
L36: def add_options(self) -> None:
L78: def run(self, options: Values, args: list[str]) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/inject.py

```

L19: class InspectCommand(Command):
L28: def add_options(self) -> None:
L48: def run(self, options: Values, args: list[str]) -> int:
L65: def _dist_to_dict(self, dist: BaseDistribution) -> dict[str, Any]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/c
heck.py**

```

L18: class CheckCommand(Command):
L25: def run(self, options: Values, args: list[str]) -> int:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/w
heel.py**

```

L22: class WheelCommand(RequirementCommand):
L42: def add_options(self) -> None:
L94: def run(self, options: Values, args: list[str]) -> int:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/link.p
y**

```

L40: class LinkHash:
L64: def __post_init__(self) -> None:
L69: def find_hash_url_fragment(cls, url: str) -> LinkHash | None:
L77: def as_dict(self) -> dict[str, str]:
L80: def as_hashes(self) -> Hashes:
L84: def is_hash_allowed(self, hashes: Hashes | None) -> bool:
L94: class MetadataFile:
L99: def __post_init__(self) -> None:
L104: def supported_hashes(hashes: dict[str, str] | None) -> dict[str, str] | None:
L115: def _clean_url_path_part(part: str) -> str:
L123: def _clean_file_url_path(part: str) -> str:
L144: def _clean_url_path(path: str, is_local_path: bool) -> str:
L166: def _ensure_quoted_url(url: str) -> str:
L185: def _absolute_link_url(base_url: str, url: str) -> str:
L197: class Link:
L214: def __init__(
L283: def from_json(
L340: def from_element(
L391: def __str__(self) -> str:

```

```

L401: def __repr__(self) -> str:
L404: def __hash__(self) -> int:
L407: def __eq__(self, other: Any) -> bool:
L412: def __lt__(self, other: Any) -> bool:
L418: def url(self) -> str:
L422: def redacted_url(self) -> str:
L426: def filename(self) -> str:
L440: def file_path(self) -> str:
L444: def scheme(self) -> str:
L448: def netloc(self) -> str:
L455: def path(self) -> str:
L458: def splitext(self) -> tuple[str, str]:
L462: def ext(self) -> str:
L466: def url_without_fragment(self) -> str:
L477: def _egg_fragment(self) -> str | None:
L493: def subdirectory_fragment(self) -> str | None:
L499: def metadata_link(self) -> Link | None:
L508: def as_hashes(self) -> Hashes:
L512: def hash(self) -> str | None:
L516: def hash_name(self) -> str | None:
L520: def show_url(self) -> str:
L524: def is_file(self) -> bool:
L527: def is_existing_dir(self) -> bool:
L531: def is_wheel(self) -> bool:
L535: def is_vcs(self) -> bool:
L541: def is_yanked(self) -> bool:
L545: def has_hash(self) -> bool:
L548: def is_hash_allowed(self, hashes: Hashes | None) -> bool:
L557: class _CleanResult(NamedTuple):
L589: def _clean_link(link: Link) -> _CleanResult:
L616: def links_equivalent(link1: Link, link2: Link) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/candidate.py

```

L10: class InstallationCandidate:
L17: def __init__(self, name: str, version: str, link: Link) -> None:
L22: def __str__(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/direct_url.py

```

L30: class DirectUrl(PackagingDirectUrl):
L31: def to_dict_compat(self) -> dict[str, Any]:

```



```
L35: def from_json(cls, s: str) -> DirectUrl:
L38: def to_json(self) -> str:
L41: def is_local_editable(self) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/index.py

```
L4: class PackageIndex:
L9: def __init__(self, url: str, file_storage_domain: str) -> None:
L21: def _url_for_path(self, path: str) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/search_scope.py

```
L18: class SearchScope:
L28: def create(
L69: def get_formatted_locations(self) -> str:
L104: def get_index_urls_locations(self, project_name: str) -> list[str]:
L111: def mkurl_pypi_url(url: str) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/format_control.py

```
L8: class FormatControl:
L13: def __init__(
L26: def __eq__(self, other: object) -> bool:
L35: def __repr__(self) -> str:
L39: def handle_mutual_excludes(value: str, target: set[str], other: set[str]) -> None:
L61: def get_allowed_formats(self, canonical_name: str) -> frozenset[str]:
L73: def disallow_binaries(self) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/target_python.py

```
L11: class TargetPython:
L28: def __init__(
L69: def format_given(self) -> str:
```

```
L89: def get_sorted_tags(self) -> list[Tag]:
L114: def get_unsorted_tags(self) -> set[Tag]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/installation_report.py

```
L10: class InstallationReport:
L11: def __init__(self, install_requirements: Sequence[InstallRequirement]):
L15: def _install_req_to_dict(cls, ireq: InstallRequirement) -> dict[str, Any]:
L43: def to_dict(self) -> dict[str, Any]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/selection_prefs.py

```
L10: class SelectionPreferences:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/scheme.py

```
L14: class Scheme:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/wheel.py

```
L18: class Wheel:
L21: def __init__(self, filename: str) -> None:
L32: def get_formatted_file_tags(self) -> list[str]:
L36: def support_index_min(self, tags: list[Tag]) -> int:
L54: def find_most_preferred_tag(
L75: def supported(self, tags: Iterable[Tag]) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/release_control.py

```

L11: class ReleaseControl:
L20: def handle_mutual_excludes(
L59: def get_ordered_args(self) -> list[tuple[str, str]]:
L74: def allows_prereleases(self, canonical_name: NormalizedName) -> bool | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/compat.py

```

L16: def has_tls() -> bool:
L29: def get_path_uid(path: str) -> int:
L62: def open_text_resource(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/entrypoints.py

```

L24: def _wrapper(args: list[str] | None = None) -> int:
L47: def get_best_invocation_for_this_pip() -> str:
L74: def get_best_invocation_for_this_python() -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/datetime.py

```

L7: def today_is_later_than(year: int, month: int, day: int) -> bool:
L14: def parse_iso_datetime(isodate: str) -> datetime.datetime:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/urls.py

```

L9: def path_to_url(path: str) -> str:
L19: def url_to_path(url: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/_jaraco_text.py

```

L36: def _nonblank(str):

```

```
L41: def yield_lines(iterable):
L60: def _(text):
L64: def drop_comment(line):
L79: def join_continuation(lines):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/appdirs.py

```
L15: def user_cache_dir(appname: str) -> str:
L19: def _macos_user_config_dir(appname: str, roaming: bool = True) -> str:
L33: def user_config_dir(appname: str, roaming: bool = True) -> str:
L42: def site_config_dirs(appname: str) -> list[str]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/filesystem.py

```
L19: def check_path_owner(path: str) -> bool:
L47: def adjacent_tmp_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
L76: def test_writable_dir(path: str) -> bool:
L94: def _test_writable_dir_win(path: str) -> bool:
L122: def find_files(path: str, pattern: str) -> list[str]:
L132: def file_size(path: str) -> int | float:
L139: def format_file_size(path: str) -> str:
L143: def directory_size(path: str) -> int | float:
L152: def format_directory_size(path: str) -> str:
L156: def copy_directory_permissions(directory: str, target_file: BinaryIO) -> None:
L168: def _subdirs_without_generic(
L192: def subdirs_without_files(path: str) -> Generator[Path]:
L197: def subdirs_without_wheels(path: str) -> Generator[Path]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/retry.py

```
L14: def retry(
L28: def wrapper(func: Callable[P, T]) -> Callable[P, T]:
L31: def retry_wrapped(*args: P.args, **kwargs: P.kwargs) -> T:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/logging.py

```

L40: class BrokenStdoutLoggingError(Exception):
L46: def _is_broken_pipe_error(exc_class: type[BaseException], exc: BaseException) -> bool:
L60: def capture_logging() -> Generator[StringIO, None, None]:
L92: def indent_log(num: int = 2) -> Generator[None, None, None]:
L106: def get_indentation() -> int:
L110: class IndentingFormatter(logging.Formatter):
L113: def __init__(
L128: def get_message_start(self, formatted: str, levelno: int) -> str:
L144: def format(self, record: logging.LogRecord) -> str:
L162: class IndentedRenderable:
L166: def __rich_console__(
L177: class PipConsole(Console):
L178: def on_broken_pipe(self) -> None:
L184: def get_console(*, stderr: bool = False) -> Console:
L193: class RichPipStreamHandler(RichHandler):
L196: def __init__(self, console: Console) -> None:
L206: def emit(self, record: logging.LogRecord) -> None:
L234: def handleError(self, record: logging.LogRecord) -> None:
L253: class BetterRotatingFileHandler(logging.handlers.RotatingFileHandler):
L254: def _open(self) -> TextIOWrapper:
L259: class MaxLevelFilter(Filter):
L260: def __init__(self, level: int) -> None:
L263: def filter(self, record: logging.LogRecord) -> bool:
L267: class ExcludeLoggerFilter(Filter):
L272: def filter(self, record: logging.LogRecord) -> bool:
L278: def setup_logging(verbosity: int, no_color: bool, user_log_file: str | None) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/unpacking.py

```

L45: def current_umask() -> int:
L52: def split_leading_dir(path: str) -> list[str]:
L64: def has_leading_dir(paths: Iterable[str]) -> bool:
L79: def is_within_directory(directory: str, target: str) -> bool:
L90: def _get_default_mode_plus_executable() -> int:
L94: def set_extracted_file_to_default_mode_plus_executable(path: str) -> None:
L102: def zip_item_is_executable(info: ZipInfo) -> bool:
L109: def unzip_file(filename: str, location: str, flatten: bool = True) -> None:
L155: def untar_file(filename: str, location: str) -> None:
L206: def pip_filter(member: tarfile.TarInfo, path: str) -> tarfile.TarInfo:
L251: def is_symlink_target_in_tar(tar: tarfile.TarFile, tarinfo: tarfile.TarInfo) -> bool:
L265: def _untar_without_filter(
L334: def unpack_file(
L348: def _unzip() -> None:
L351: def _untar() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/subprocess.py

```

L20: def make_command(*args: str | HiddenText | CommandArgs) -> CommandArgs:
L37: def format_command_args(args: list[str] | CommandArgs) -> str:
L52: def reveal_command_args(args: list[str] | CommandArgs) -> list[str]:
L59: def call_subprocess(
L227: def runner_with_spinner_message(message: str) -> Callable[..., None]:
L234: def runner(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/compatibility_tags.py

```

L23: def version_info_to_nodot(version_info: tuple[int, ...]) -> str:
L28: def _mac_platforms(arch: str) -> list[str]:
L48: def _ios_platforms(arch: str) -> list[str]:
L68: def _android_platforms(arch: str) -> list[str]:
L78: def _custom_manylinux_platforms(arch: str) -> list[str]:
L99: def _get_custom_platforms(arch: str) -> list[str]:
L114: def _expand_allowed_platforms(platforms: list[str] | None) -> list[str] | None:
L131: def _get_python_version(version: str) -> PythonVersion:
L138: def _get_custom_interpreter(
L148: def get_supported(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/glibc.py

```

L7: def glibc_version_string() -> str | None:
L12: def glibc_version_string_confstr() -> str | None:
L32: def glibc_version_string_ctypes() -> str | None:
L92: def libc_ver() -> tuple[str, str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/virtualenv.py

```

L15: def _running_under_venv() -> bool:
L23: def _running_under_legacy_virtualenv() -> bool:
L32: def running_under_virtualenv() -> bool:
L37: def _get_pyvenv_cfg_lines() -> list[str] | None:

```

```
L52: def _no_global_under_venv() -> bool:
L81: def _no_global_under_legacy_virtualenv() -> bool:
L95: def virtualenv_no_global() -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/deprecation.py

```
L18: class PipDeprecationWarning(Warning):
L26: def _showwarning(
L49: def install_warning_logger() -> None:
L60: def deprecated(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/filetypes.py

```
L19: def is_archive_file(name: str) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/egg_link.py

```
L19: def _egg_link_names(raw_name: str) -> list[str]:
L34: def egg_link_path_from_sys_path(raw_name: str) -> str | None:
L47: def egg_link_path_from_location(raw_name: str) -> str | None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/hashes.py

```
L24: class Hashes:
L30: def __init__(self, hashes: dict[str, list[str]] | None = None) -> None:
L42: def __and__(self, other: Hashes) -> Hashes:
L62: def digest_count(self) -> int:
L65: def is_hash_allowed(self, hash_name: str, hex_digest: str) -> bool:
L69: def check_against_chunks(self, chunks: Iterable[bytes]) -> None:
L92: def _raise(self, got: dict[str, _Hash]) -> NoReturn:
L95: def check_against_file(self, file: BinaryIO) -> None:
L103: def check_against_path(self, path: str) -> None:
L107: def has_one_of(self, hashes: Mapping[str, str]) -> bool:
```

```

L114: def __bool__(self) -> bool:
L118: def __eq__(self, other: object) -> bool:
L123: def __hash__(self) -> int:
L135: class MissingHashes(Hashes):
L143: def __init__(self) -> None:
L149: def _raise(self, got: dict[str, _Hash]) -> NoReturn:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/temp_dir.py

```

L38: def global_tempdir_manager() -> Generator[None, None, None]:
L48: class TempDirectoryTypeRegistry:
L51: def __init__(self) -> None:
L54: def set_delete(self, kind: str, value: bool) -> None:
L60: def get_delete(self, kind: str) -> bool:
L71: def tempdir_registry() -> Generator[TempDirectoryTypeRegistry, None, None]:
L84: class _Default:
L91: class TempDirectory:
L112: def __init__(
L148: def path(self) -> str:
L152: def __repr__(self) -> str:
L155: def __enter__(self: _T) -> _T:
L158: def __exit__(self, exc: Any, value: Any, tb: Any) -> None:
L169: def _create(self, kind: str) -> str:
L179: def cleanup(self) -> None:
L187: def onerror(
L224: class AdjacentTempDirectory(TempDirectory):
L246: def __init__(self, original: str, delete: bool | None = None) -> None:
L251: def _generate_names(cls, name: str) -> Generator[str, None, None]:
L276: def _create(self, kind: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/pylock.py

```

L32: def _pylock_package_from_install_requirement(
L116: def pylock_from_install_requirements(
L135: def _is_url(s: str) -> bool:
L139: def is_valid_pylock_filename(filename: str) -> bool:
L147: def _package_dist_url(
L177: def package_vcs_requirement_url(
L192: def package_archive_requirement_url(
L208: def package_directory_requirement_url(
L227: def package_sdist_requirement_url(
L233: def package_wheel_requirement_url(

```



```
L239: def _get_pylock_path_or_url_content(path_or_url: str, session: PipSession) -> str:
L255: def select_from_pylock_path_or_url(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/wheel.py

```
L18: def parse_wheel(wheel_zip: ZipFile, name: str) -> tuple[str, Message]:
L36: def wheel_dist_info_dir(source: ZipFile, name: str) -> str:
L67: def read_wheel_metadata_file(source: ZipFile, path: str) -> bytes:
L76: def wheel_metadata(source: ZipFile, dist_info_dir: str) -> Message:
L95: def wheel_version(wheel_data: Message) -> tuple[int, ...]:
L111: def check_compatibility(version: tuple[int, ...], name: str) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/misc.py

```
L70: def get_pip_version() -> str:
L77: def normalize_version_info(py_version_info: tuple[int, ...]) -> tuple[int, int, int]:
L96: def ensure_dir(path: str) -> None:
L106: def get_prog() -> str:
L120: def rmtree(dir: str, ignore_errors: bool = False, onexc: OnExc | None = None) -> None:
L133: def _onerror_ignore(*args: Any) -> None:
L137: def _onerror_reraise(*args: Any) -> None:
L141: def rmtree_errorhandler(
L182: def display_path(path: str) -> str:
L193: def backup_dir(dir: str, ext: str = ".bak") -> str:
L204: def ask_path_exists(message: str, options: Iterable[str]) -> str:
L211: def _check_no_input(message: str) -> None:
L219: def ask(message: str, options: Iterable[str]) -> str:
L234: def ask_input(message: str) -> str:
L240: def ask_password(message: str) -> str:
L246: def strtobool(val: str) -> int:
L262: def format_size(bytes: float) -> str:
L273: def tabulate(rows: Iterable[Iterable[Any]]) -> tuple[list[str], list[int]]:
L287: def is_installable_dir(path: str) -> bool:
L304: def read_chunks(
L315: def normalize_path(path: str, resolve_symlinks: bool = True) -> str:
L328: def splittext(path: str) -> tuple[str, str]:
L337: def renames(old: str, new: str) -> None:
L354: def is_local(path: str) -> bool:
L368: def write_output(msg: Any, *args: Any) -> None:
L372: class StreamWrapper(StringIO):
L376: def from_stream(cls, orig_stream: TextIO) -> StreamWrapper:
L384: def encoding(self) -> str: # type: ignore
L389: def enum(*sequential: Any, **named: Any) -> type[Any]:
L396: def build_netloc(host: str, port: int | None) -> str:
L408: def build_url_from_netloc(netloc: str, scheme: str = "https") -> str:
```

```

L418: def parse_netloc(netloc: str) -> tuple[str | None, int | None]:
L427: def split_auth_from_netloc(netloc: str) -> NetlocTuple:
L456: def redact_netloc(netloc: str) -> str:
L476: def _transform_url(
L496: def _get_netloc(netloc: str) -> NetlocTuple:
L500: def _redact_netloc(netloc: str) -> tuple[str]:
L504: def split_auth_netloc_from_url(
L516: def remove_auth_from_url(url: str) -> str:
L523: def redact_auth_from_url(url: str) -> str:
L528: def redact_auth_from_requirement(req: Requirement) -> str:
L536: class HiddenText:
L540: def __repr__(self) -> str:
L543: def __str__(self) -> str:
L546: def __eq__(self, other: object) -> bool:
L560: def hide_value(value: str) -> HiddenText:
L564: def hide_url(url: str) -> HiddenText:
L569: def protect_pip_from_modification_on_windows(modifying_pip: bool) -> None:
L595: def check_externally_managed() -> None:
L610: def is_console_interactive() -> bool:
L615: def hash_file(path: str, blocksize: int = 1 << 20) -> tuple[Any, int]:
L627: def pairwise(iterable: Iterable[Any]) -> Iterator[tuple[Any, Any]]:
L638: def partition(
L651: class ConfiguredBuildBackendHookCaller(BuildBackendHookCaller):
L652: def __init__(
L666: def build_wheel(
L677: def build_sdist(
L685: def build_editable(
L696: def get_requires_for_build_wheel(
L702: def get_requires_for_build_sdist(
L708: def get_requires_for_build_editable(
L714: def prepare_metadata_for_build_wheel(
L727: def prepare_metadata_for_build_editable(
L741: def warn_if_run_as_root() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/direct_url_helpers.py

```

L9: def direct_url_as_pep440_direct_reference(direct_url: DirectUrl, name: str) -> str:
L36: def direct_url_for_editable(source_dir: str) -> DirectUrl:
L43: def direct_url_from_link(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/packaging.py

```
L13: def check_requires_python(
L37: def get_requirement(req_string: str) -> Requirement:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/_log.py

```
L16: class VerboseLogger(logging.Logger):
L22: def verbose(self, msg: str, *args: Any, **kwargs: Any) -> None:
L26: def getLogger(name: str) -> VerboseLogger:
L31: def init_logging() -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/freeze.py

```
L25: class _EditableInfo(NamedTuple):
L30: def freeze(
L151: def _format_as_name_version(dist: BaseDistribution) -> str:
L161: def _get_editable_info(dist: BaseDistribution) -> _EditableInfo:
L228: class FrozenRequirement:
L235: def canonical_name(self) -> NormalizedName:
L239: def from_dist(cls, dist: BaseDistribution) -> FrozenRequirement:
L255: def __str__(self) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/preparer.py

```
L65: def _get_prepared_distribution(
L83: def unpack_vcs_link(link: Link, location: str, verbosity: int) -> None:
L90: class File:
L94: def __post_init__(self) -> None:
L104: def get_http_url(
L128: def get_file_url(
L152: def unpack_url(
L195: def _check_download_dir(
L225: class RequirementPreparer:
L228: def __init__(
L288: def _log_preparing_link(self, req: InstallRequirement) -> None:
L315: def _ensure_link_req_src_dir(
L338: def _get_linked_req_hashes(self, req: InstallRequirement) -> Hashes:
L370: def _fetch_metadata_only(
L389: def _fetch_metadata_using_link_data_attr(
L430: def _fetch_metadata_using_lazy_wheel(
```

```

L459: def _complete_partial_requirements(
L500: def prepare_linked_requirement(
L544: def prepare_linked_requirements_more(
L574: def _prepare_linked_requirement(
L670: def save_linked_requirement(self, req: InstallRequirement) -> None:
L696: def prepare_editable_requirement(
L729: def prepare_installed_requirement(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/check.py

```

L28: class PackageDetails(NamedTuple):
L44: def create_package_set_from_installed() -> tuple[PackageSet, bool]:
L61: def check_package_set(
L106: def check_install_conflicts(to_install: list[InstallRequirement]) -> ConflictDetails:
L126: def check_unsupported(
L142: def _simulate_installation_of(
L161: def _create_whitelist(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/install/wheel.py

```

L57: class File(Protocol):
L62: def save(self) -> None:
L72: def rehash(path: str, blocksize: int = 1 << 20) -> tuple[str, str]:
L79: def csv_io_kwargs(mode: str) -> dict[str, Any]:
L86: def fix_script(path: str) -> bool:
L106: def wheel_root_is_purelib(metadata: Message) -> bool:
L110: def get_entrypoints(dist: BaseDistribution) -> tuple[dict[str, str], dict[str, str]]:
L121: def message_about_scripts_not_on_PATH(scripts: Sequence[str]) -> str | None:
L193: def _normalized_outrows(
L219: def _record_to_fs_path(record_path: RecordPath, lib_dir: str) -> str:
L223: def _fs_to_record_path(path: str, lib_dir: str) -> RecordPath:
L233: def get_csv_rows_for_installed(
L265: def get_console_script_specs(console: dict[str, str]) -> list[str]:
L340: class ZipBackedFile:
L341: def __init__(
L349: def _getinfo(self) -> ZipInfo:
L352: def save(self) -> None:
L378: class ScriptFile:
L379: def __init__(self, file: File) -> None:
L385: def save(self) -> None:
L390: class MissingCallableSuffix(InstallationError):
L391: def __init__(self, entry_point: str) -> None:

```

```

L400: def _raise_for_invalid_entrypoint(specification: str) -> None:
L406: class PipScriptMaker(ScriptMaker):
L419: def make(
L426: def _install_wheel( # noqa: C901, PLR0915 function is too long
L466: def record_installed(
L475: def is_dir_path(path: RecordPath) -> bool:
L478: def assert_no_path_traversal(dest_dir_path: str, target_path: str) -> None:
L488: def root_scheme_file_maker(
L491: def make_root_scheme_file(record_path: RecordPath) -> File:
L499: def data_scheme_file_maker(
L504: def make_data_scheme_file(record_path: RecordPath) -> File:
L533: def is_data_scheme_path(path: RecordPath) -> bool:
L543: def is_script_scheme_path(path: RecordPath) -> bool:
L562: def is_entrypoint_wrapper(file: File) -> bool:
L597: def pyc_source_file_paths() -> Generator[str, None, None]:
L610: def pyc_output_path(path: str) -> str:
L666: def _generate_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
L716: def req_error_context(req_description: str) -> Generator[None, None, None]:
L724: def install_wheel(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/_distutils.py

```

L36: def distutils_scheme(
L116: def get_scheme(
L151: def get_bin_prefix() -> str:
L168: def get_purelib() -> str:
L172: def get_platlib() -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/base.py

```

L20: def get_major_minor_version() -> str:
L28: def change_root(new_root: str, pathname: str) -> str:
L56: def get_src_prefix() -> str:
L81: def is_osx_framework() -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/__init__.py

```

L45: def _should_use_sysconfig() -> bool:
L75: def _looks_like_bpo_44860() -> bool:
L89: def _looks_like_red_hat_patched_platlib_purelib(scheme: dict[str, str]) -> bool:
L100: def _looks_like_red_hat_lib() -> bool:
L115: def _looks_like_debian_scheme() -> bool:
L123: def _looks_like_red_hat_scheme() -> bool:
L143: def _looks_like_slackware_scheme() -> bool:
L159: def _looks_like_msys2_mingw_scheme() -> bool:
L177: def _warn_mismatched(old: pathlib.Path, new: pathlib.Path, *, key: str) -> None:
L187: def _warn_if_mismatch(old: pathlib.Path, new: pathlib.Path, *, key: str) -> bool:
L195: def _log_context(
L213: def get_scheme(
L379: def get_bin_prefix() -> str:
L390: def get_bin_user() -> str:
L394: def _looks_like_deb_system_dist_packages(value: str) -> bool:
L411: def get_purelib() -> str:
L425: def get_platlib() -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/_sysconfig.py

```

L33: def _should_use_osx_framework_prefix() -> bool:
L59: def _infer_prefix() -> str:
L90: def _infer_user() -> str:
L105: def _infer_home() -> str:
L128: def get_scheme(
L206: def get_bin_prefix() -> str:
L213: def get_purelib() -> str:
L217: def get_platlib() -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/base.py

```

L44: class BaseEntryPoint(Protocol):
L46: def name(self) -> str:
L50: def value(self) -> str:
L54: def group(self) -> str:
L58: def _convert_installed_files_path(
L88: class RequiresEntry(NamedTuple):
L94: class BaseDistribution(Protocol):
L96: def from_directory(cls, directory: str) -> BaseDistribution:
L104: def from_metadata_file_contents(
L122: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:
L135: def __repr__(self) -> str:

```

```

L138: def __str__(self) -> str:
L142: def location(self) -> str | None:
L156: def editable_project_location(self) -> str | None:
L178: def installed_location(self) -> str | None:
L191: def info_location(self) -> str | None:
L207: def installed_by_distutils(self) -> bool:
L220: def installed_as_egg(self) -> bool:
L234: def installed_with_setuptools_egg_info(self) -> bool:
L252: def installed_with_dist_info(self) -> bool:
L268: def canonical_name(self) -> NormalizedName:
L272: def version(self) -> Version:
L276: def raw_version(self) -> str:
L280: def setuptools_filename(self) -> str:
L288: def direct_url(self) -> DirectUrl | None:
L314: def installer(self) -> str:
L326: def requested(self) -> bool:
L330: def editable(self) -> bool:
L334: def local(self) -> bool:
L344: def in_usersite(self) -> bool:
L350: def in_site_packages(self) -> bool:
L355: def is_file(self, path: InfoPath) -> bool:
L359: def iter_distutils_script_names(self) -> Iterator[str]:
L367: def read_text(self, path: InfoPath) -> str:
L376: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:
L379: def _metadata_impl(self) -> email.message.Message:
L383: def metadata(self) -> email.message.Message:
L396: def metadata_dict(self) -> dict[str, Any]:
L407: def metadata_version(self) -> str | None:
L412: def raw_name(self) -> str:
L419: def requires_python(self) -> SpecifierSet:
L437: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
L445: def iter_raw_dependencies(self) -> Iterable[str]:
L449: def iter_provided_extras(self) -> Iterable[NormalizedName]:
L461: def _iter_declared_entries_from_record(self) -> Iterator[str] | None:
L469: def _iter_declared_entries_from_legacy(self) -> Iterator[str] | None:
L490: def iter_declared_entries(self) -> Iterator[str] | None:
L506: def _iter_requires_txt_entries(self) -> Iterator[RequiresEntry]:
L531: def _iter_egg_info_extras(self) -> Iterable[str]:
L541: def _iter_egg_info_dependencies(self) -> Iterable[str]:
L569: def _add_egg_info_requires(self, metadata: email.message.Message) -> None:
L579: class BaseEnvironment:
L583: def default(cls) -> BaseEnvironment:
L587: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:
L590: def get_distribution(self, name: str) -> BaseDistribution | None:
L598: def _iter_distributions(self) -> Iterator[BaseDistribution]:
L607: def iter_all_distributions(self) -> Iterator[BaseDistribution]:
L628: def iter_installed_distributions(
L664: class Wheel(Protocol):
L667: def as_zipfile(self) -> zipfile.ZipFile:
L671: class FilesystemWheel(Wheel):
L672: def __init__(self, location: str) -> None:

```

```

L675: def as_zipfile(self) -> zipfile.ZipFile:
L679: class MemoryWheel(Wheel):
L680: def __init__(self, location: str, stream: IO[bytes]) -> None:
L684: def as_zipfile(self) -> zipfile.ZipFile:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/_json.py

```

L40: def json_name(field: str) -> str:
L44: def msg_to_json(msg: Message) -> dict[str, Any]:
L47: def sanitise_header(h: Header | str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/__init__.py

```

L30: def _should_use_importlib_metadata() -> bool:
L63: def _emit_pkg_resources_deprecation_if_needed() -> None:
L88: class Backend(Protocol):
L95: def select_backend() -> Backend:
L108: def get_default_environment() -> BaseEnvironment:
L118: def get_environment(paths: list[str] | None) -> BaseEnvironment:
L128: def get_directory_distribution(directory: str) -> BaseDistribution:
L137: def get_wheel_distribution(
L150: def get_metadata_distribution(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/pkg_resources.py

```

L39: class EntryPoint(NamedTuple):
L45: class InMemoryMetadata:
L51: def __init__(self, metadata: Mapping[str, bytes], wheel_name: str) -> None:
L55: def has_metadata(self, name: str) -> bool:
L58: def get_metadata(self, name: str) -> str:
L67: def get_metadata_lines(self, name: str) -> Iterable[str]:
L70: def metadata_isdir(self, name: str) -> bool:
L73: def metadata_listdir(self, name: str) -> list[str]:
L76: def run_script(self, script_name: str, namespace: str) -> None:
L80: class Distribution(BaseDistribution):
L81: def __init__(self, dist: pkg_resources.Distribution) -> None:
L88: def _extra_mapping(self) -> Mapping[NormalizedName, str]:

```



```

L97: def from_directory(cls, directory: str) -> BaseDistribution:
L117: def from_metadata_file_contents(
L134: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:
L155: def location(self) -> str | None:
L159: def installed_location(self) -> str | None:
L170: def info_location(self) -> str | None:
L174: def installed_by_distutils(self) -> bool:
L184: def canonical_name(self) -> NormalizedName:
L188: def version(self) -> Version:
L192: def raw_version(self) -> str:
L195: def is_file(self, path: InfoPath) -> bool:
L198: def iter_distutils_script_names(self) -> Iterator[str]:
L201: def read_text(self, path: InfoPath) -> str:
L210: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:
L216: def _metadata_impl(self) -> email.message.Message:
L238: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
L246: def iter_provided_extras(self) -> Iterable[NormalizedName]:
L250: class Environment(BaseEnvironment):
L251: def __init__(self, ws: pkg_resources.WorkingSet) -> None:
L255: def default(cls) -> BaseEnvironment:
L259: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:
L262: def _iter_distributions(self) -> Iterator[BaseDistribution]:
L266: def _search_distribution(self, name: str) -> BaseDistribution | None:
L278: def get_distribution(self, name: str) -> BaseDistribution | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_compat.py

```

L10: class BadMetadata(ValueError):
L11: def __init__(self, dist: importlib.metadata.Distribution, *, reason: str) -> None:
L15: def __str__(self) -> str:
L19: class BasePath(Protocol):
L31: def name(self) -> str:
L35: def parent(self) -> BasePath:
L39: def get_info_location(d: importlib.metadata.Distribution) -> BasePath | None:
L51: def parse_name_and_version_from_info_directory(
L75: def get_dist_canonical_name(dist: importlib.metadata.Distribution) -> NormalizedName:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_envs.py

```

L28: def _looks_like_wheel(location: str) -> bool:
L40: class _DistributionFinder:
L55: def __init__(self) -> None:

```

```

L58: def _find_impl(self, location: str) -> Iterator[FoundResult]:
L79: def find(self, location: str) -> Iterator[BaseDistribution]:
L91: def find_legacy_editables(self, location: str) -> Iterator[BaseDistribution]:
L116: class Environment(BaseEnvironment):
L117: def __init__(self, paths: Sequence[str]) -> None:
L121: def default(cls) -> BaseEnvironment:
L125: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:
L130: def _iter_distributions(self) -> Iterator[BaseDistribution]:
L136: def get_distribution(self, name: str) -> BaseDistribution | None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/imp
ortlib/_dists.py**

```

L38: class WheelDistribution(importlib.metadata.Distribution):
L49: def __init__(
L58: def from_zipfile(
L77: def iterdir(self, path: InfoPath) -> Iterator[pathlib.PurePosixPath]:
L83: def read_text(self, filename: str) -> str | None:
L96: def locate_file(self, path: str | PathLike[str]) -> pathlib.Path:
L102: class Distribution(BaseDistribution):
L103: def __init__(
L114: def from_directory(cls, directory: str) -> BaseDistribution:
L120: def from_metadata_file_contents(
L137: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:
L146: def location(self) -> str | None:
L152: def info_location(self) -> str | None:
L158: def installed_location(self) -> str | None:
L164: def canonical_name(self) -> NormalizedName:
L168: def version(self) -> Version:
L179: def raw_version(self) -> str:
L182: def is_file(self, path: InfoPath) -> bool:
L185: def iter_distutils_script_names(self) -> Iterator[str]:
L194: def read_text(self, path: InfoPath) -> str:
L200: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:
L204: def _metadata_impl(self) -> email.message.Message:
L218: def iter_provided_extras(self) -> Iterable[NormalizedName]:
L224: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_instal
l.py**

```

L62: class InstallRequirement:
L69: def __init__(
L191: def __str__(self) -> str:

```

```

L215: def __repr__(self) -> str:
L221: def format_debug(self) -> str:
L234: def name(self) -> str | None:
L240: def supports_pyproject_editable(self) -> bool:
L250: def specifier(self) -> SpecifierSet:
L255: def is_direct(self) -> bool:
L260: def is_pinned(self) -> bool:
L269: def match_markers(self, extras_requested: Iterable[str] | None = None) -> bool:
L282: def has_hash_options(self) -> bool:
L291: def hashes(self, trust_internet: bool = True) -> Hashes:
L318: def from_path(self) -> str | None:
L333: def ensure_build_location(
L376: def _set_requirement(self) -> None:
L398: def warn_on_mismatching_name(self) -> None:
L416: def check_if_exists(self, use_user_site: bool) -> None:
L455: def is_wheel(self) -> bool:
L461: def is_wheel_from_cache(self) -> bool:
L468: def unpacked_source_directory(self) -> str:
L475: def setup_py_path(self) -> str:
L482: def pyproject_toml_path(self) -> str:
L486: def load_pyproject_toml(self) -> None:
L506: def editable_sanity_check(self) -> None:
L519: def prepare_metadata(self) -> None:
L555: def metadata(self) -> Any:
L561: def set_dist(self, distribution: BaseDistribution) -> None:
L564: def get_dist(self) -> BaseDistribution:
L580: def assert_source_matches_version(self) -> None:
L598: def ensure_has_source_dir(
L620: def needs_unpacked_archive(self, archive_source: Path) -> None:
L624: def ensure_pristine_source_checkout(self) -> None:
L642: def update_editable(self) -> None:
L662: def uninstall(
L688: def _get_archive_name(self, path: str, parentdir: str, rootdir: str) -> str:
L689: def _clean_zip_name(name: str, prefix: str) -> str:
L702: def archive(self, build_dir: str | None) -> None:
L769: def install(
L804: def check_invalid_constraint_type(req: InstallRequirement) -> str:
L832: def _has_option(options: Values, reqs: list[InstallRequirement], option: str) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/pep723.py

```

L9: class PEP723Exception(ValueError):
L12: def __init__(self, msg: str) -> None:
L16: def pep723_metadata(scriptfile: str) -> dict[str, Any]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_set.py

```

L11: class RequirementSet:
L12: def __init__(self, check_supported_wheels: bool = True) -> None:
L20: def __str__(self) -> str:
L27: def __repr__(self) -> str:
L40: def add_unnamed_requirement(self, install_req: InstallRequirement) -> None:
L44: def add_named_requirement(self, install_req: InstallRequirement) -> None:
L50: def has_requirement(self, name: str) -> bool:
L58: def get_requirement(self, name: str) -> InstallRequirement:
L67: def all_requirements(self) -> list[InstallRequirement]:
L71: def requirements_to_install(self) -> list[InstallRequirement]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/__init__.py

```

L26: class InstallationResult:
L30: def _validate_requirements(
L38: def install_given_reqs(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/constructors.py

```

L58: def _strip_extras(path: str) -> tuple[str, str | None]:
L70: def convert_extras(extras: str | None) -> set[str]:
L76: def _set_requirement_extras(req: Requirement, new_extras: set[str]) -> Requirement:
L101: def _parse_direct_url_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
L119: def _parse_pip_syntax_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
L148: def parse_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
L182: def check_first_requirement_in_file(filename: str) -> None:
L210: def deduce_helpful_msg(req: str) -> str:
L236: class RequirementParts:
L243: def parse_req_from_editable(editable_req: str) -> RequirementParts:
L262: def install_req_from_editable(
L292: def _looks_like_path(name: str) -> bool:
L311: def _get_url_from_path(path: str, name: str) -> str | None:
L345: def parse_req_from_line(name: str, line_source: str | None) -> RequirementParts:
L393: def with_source(text: str) -> str:
L398: def _parse_req_string(req_as_string: str) -> Requirement:
L424: def install_req_from_line(

```

```

L457: def install_req_from_req_string(
L493: def install_req_from_parsed_requirement(
L525: def install_req_from_link_and_ireq(
L541: def install_req_drop_extras(ireq: InstallRequirement) -> InstallRequirement:
L565: def install_req_extend_extras(
L583: def _pylock_hashes_to_hash_options(hashes: Mapping[str, str]) -> dict[str, list[str]]:
L587: def install_req_from_pylock_package(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_file.py

```

L105: class ParsedRequirement:
L115: class ParsedLine:
L123: def is_editable(self) -> bool:
L127: def requirement(self) -> str | None:
L136: def parse_requirements(
L163: def preprocess(content: str) -> ReqFileLines:
L175: def handle_requirement_line(
L209: def handle_option_line(
L287: def handle_line(
L331: class RequirementsFileParser:
L332: def __init__(
L340: def parse(
L348: def _parse_and_recurse(
L400: def _parse_file(
L424: def get_line_parser(finder: PackageFinder | None) -> LineParser:
L425: def parse_line(line: str) -> tuple[str, Values]:
L449: def break_args_options(line: str) -> tuple[str, str]:
L466: class OptionParsingError(Exception):
L467: def __init__(self, msg: str) -> None:
L471: def build_parser() -> optparse.OptionParser:
L484: def parser_exit(self: Any, msg: str) -> NoReturn:
L494: def join_lines(lines_enum: ReqFileLines) -> ReqFileLines:
L525: def ignore_comments(lines_enum: ReqFileLines) -> ReqFileLines:
L536: def expand_env_variables(lines_enum: ReqFileLines) -> ReqFileLines:
L563: def get_file_content(
L596: def _decode_req_file(data: bytes, url: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_dependency_group.py

```

L11: def parse_dependency_groups(groups: list[tuple[str, str]]) -> list[str]:
L21: def _resolve_all_groups(
L41: def _build_resolvers(paths: Iterable[str]) -> dict[str, Any]:

```

```
L72: def _load_pyproject(path: str) -> dict[str, Any]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_uninstall.py

```
L24: def _script_names(
L43: def _unique(
L47: def unique(*args: Any, **kw: Any) -> Generator[Any, None, None]:
L58: def uninstallation_paths(dist: BaseDistribution) -> Generator[str, None, None]:
L91: def compact(paths: Iterable[str]) -> set[str]:
L110: def compress_for_rename(paths: Iterable[str]) -> set[str]:
L121: def norm_join(*a: str) -> str:
L144: def compress_for_output_listing(paths: Iterable[str]) -> tuple[set[str], set[str]]:
L193: class StashedUninstallPathSet:
L197: def __init__(self) -> None:
L205: def _get_directory_stash(self, path: str) -> str:
L219: def _get_file_stash(self, path: str) -> str:
L246: def stash(self, path: str) -> str:
L267: def commit(self) -> None:
L274: def rollback(self) -> None:
L294: def can_rollback(self) -> bool:
L298: class UninstallPathSet:
L302: def __init__(self, dist: BaseDistribution) -> None:
L313: def _permitted(self, path: str) -> bool:
L324: def add(self, path: str) -> None:
L343: def add_pth(self, pth_file: str, entry: str) -> None:
L352: def remove(self, auto_confirm: bool = False, verbose: bool = False) -> None:
L381: def _allowed_to_proceed(self, verbose: bool) -> bool:
L384: def _display(msg: str, paths: Iterable[str]) -> None:
L409: def rollback(self) -> None:
L422: def commit(self) -> None:
L427: def from_dist(cls, dist: BaseDistribution) -> UninstallPathSet:
L568: def iter_scripts_to_remove(
L584: class UninstallPthEntries:
L585: def __init__(self, pth_file: str) -> None:
L590: def add(self, entry: str) -> None:
L605: def remove(self) -> None:
L632: def rollback(self) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/base.py

```
L11: class BaseResolver:
L12: def resolve(
```

```
L17: def get_installation_order(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/base.py**

```
L18: def format_name(project: NormalizedName, extras: frozenset[NormalizedName]) -> str:
L26: class Constraint:
L33: def empty(cls) -> Constraint:
L37: def from_ireq(cls, ireq: InstallRequirement) -> Constraint:
L47: def __bool__(self) -> bool:
L50: def __and__(self, other: InstallRequirement) -> Constraint:
L69: def is_satisfied_by(self, candidate: Candidate) -> bool:
L78: def format_for_error(self) -> str:
L85: class Requirement:
L87: def project_name(self) -> NormalizedName:
L97: def name(self) -> str:
L105: def is_satisfied_by(self, candidate: Candidate) -> bool:
L108: def get_candidate_lookup(self) -> CandidateLookup:
L111: def format_for_error(self) -> str:
L115: def _match_link(link: Link, candidate: Candidate) -> bool:
L121: class Candidate:
L123: def project_name(self) -> NormalizedName:
L133: def name(self) -> str:
L142: def version(self) -> Version:
L146: def is_installed(self) -> bool:
L150: def is_editable(self) -> bool:
L154: def source_link(self) -> Link | None:
L157: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L160: def get_install_requirement(self) -> InstallRequirement | None:
L163: def format_for_error(self) -> str:
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/resolver.py**

```
L41: class Resolver(BaseResolver):
L44: def __init__(
L76: def resolve(
L186: def get_installation_order(
L218: def get_topological_weights(
L249: def visit(node: str | None) -> None:
L321: def _req_set_item_sorter(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/reporter.py

```

L15: class PipReporter(BaseReporter[Requirement, Candidate, str]):
L16: def __init__(self, constraints: Mapping[str, Constraint] | None = None) -> None:
L39: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:
L73: class PipDebuggingReporter(BaseReporter[Requirement, Candidate, str]):
L76: def starting(self) -> None:
L79: def starting_round(self, index: int) -> None:
L82: def ending_round(self, index: int, state: Any) -> None:
L86: def ending(self, state: Any) -> None:
L89: def adding_requirement(
L94: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:
L97: def pinning(self, candidate: Candidate) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/candidates.py

```

L48: def as_base_candidate(candidate: Candidate) -> BaseCandidate | None:
L60: def make_install_req_from_link(
L90: def make_install_req_from_editable(
L112: def _make_install_req_from_dist(
L134: class _InstallRequirementBackedCandidate(Candidate):
L140: class exposes appropriate information to the resolver.
L153: def __init__(
L171: def __str__(self) -> str:
L174: def __repr__(self) -> str:
L177: def __hash__(self) -> int:
L184: def __eq__(self, other: Any) -> bool:
L190: def source_link(self) -> Link | None:
L194: def project_name(self) -> NormalizedName:
L201: def name(self) -> str:
L205: def version(self) -> Version:
L210: def format_for_error(self) -> str:
L217: def _prepare_distribution(self) -> BaseDistribution:
L220: def _check_metadata_consistency(self, dist: BaseDistribution) -> None:
L244: def _prepare(self) -> BaseDistribution:
L271: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L279: def get_install_requirement(self) -> InstallRequirement | None:
L283: class LinkCandidate(_InstallRequirementBackedCandidate):
L286: def __init__(
L335: def _prepare_distribution(self) -> BaseDistribution:
L340: class EditableCandidate(_InstallRequirementBackedCandidate):
L343: def __init__(
L360: def _prepare_distribution(self) -> BaseDistribution:
L364: class AlreadyInstalledCandidate(Candidate):

```



```

L368: def __init__(
L386: def __str__(self) -> str:
L389: def __repr__(self) -> str:
L392: def __eq__(self, other: object) -> bool:
L397: def __hash__(self) -> int:
L401: def project_name(self) -> NormalizedName:
L405: def name(self) -> str:
L409: def version(self) -> Version:
L415: def is_editable(self) -> bool:
L418: def format_for_error(self) -> str:
L421: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L431: def get_install_requirement(self) -> InstallRequirement | None:
L435: class ExtrasCandidate(Candidate):
L460: def __init__(
L479: def __str__(self) -> str:
L483: def __repr__(self) -> str:
L486: def __hash__(self) -> int:
L489: def __eq__(self, other: Any) -> bool:
L495: def project_name(self) -> NormalizedName:
L499: def name(self) -> str:
L504: def version(self) -> Version:
L507: def format_for_error(self) -> str:
L513: def is_installed(self) -> bool:
L517: def is_editable(self) -> bool:
L521: def source_link(self) -> Link | None:
L524: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L552: def get_install_requirement(self) -> InstallRequirement | None:
L559: class RequiresPythonCandidate(Candidate):
L563: def __init__(self, py_version_info: tuple[int, ...] | None) -> None:
L574: def __str__(self) -> str:
L577: def __repr__(self) -> str:
L581: def project_name(self) -> NormalizedName:
L585: def name(self) -> str:
L589: def version(self) -> Version:
L592: def format_for_error(self) -> str:
L595: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L598: def get_install_requirement(self) -> InstallRequirement | None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/provider.py**

```

L56: def _get_with_identifier(
L81: class PipProvider(_ProviderBase):
L92: def __init__(
L109: def constraints(self) -> dict[str, Constraint]:
L117: def identify(self, requirement_or_candidate: Requirement | Candidate) -> str:
L120: def narrow_requirement_selection(

```

```

L176: def get_preference(
L256: def find_matches(
L262: def _eligible_for_upgrade(identifier: str) -> bool:
L300: def is_satisfied_by(requirement: Requirement, candidate: Candidate) -> bool:
L303: def get_dependencies(self, candidate: Candidate) -> Iterable[Requirement]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/factory.py**

```

L74: class ConflictCause(Protocol):
L85: class CollectedRootRequirements(NamedTuple):
L91: class Factory:
L92: def __init__(
L132: def force_reinstall(self) -> bool:
L135: def _fail_if_link_is_unsupported_wheel(self, link: Link) -> None:
L144: def _make_extras_candidate(
L159: def _make_candidate_from_dist(
L174: def _make_candidate_from_link(
L189: def _make_base_candidate_from_link(
L246: def _get_locked_installation_candidate(
L271: def _iter_found_candidates(
L308: def _get_installed_candidate() -> Candidate | None:
L337: def iter_index_candidate_infos() -> Iterator[IndexCandidateInfo]:
L358: def is_pinned(specifier: SpecifierSet) -> bool:
L392: def _iter_explicit_candidates_from_base(
L414: def _iter_candidates_from_constraints(
L448: def find_candidates(
L525: def _make_requirements_from_install_req(
L578: def collect_root_requirements(
L620: def make_requirement_from_candidate(
L625: def make_requirements_from_spec(
L643: def make_requires_python_requirement(
L654: def get_wheel_cache_entry(self, link: Link, name: str | None) -> CacheEntry | None:
L671: def get_dist_to_uninstall(self, candidate: Candidate) -> BaseDistribution | None:
L699: def _report_requires_python_error(
L721: def _report_single_requirement_conflict(
L783: def _has_any_candidates(self, project_name: str) -> bool:
L798: def get_installation_error(
L834: def text_join(parts: list[str]) -> str:
L840: def describe_trigger(parent: Candidate) -> str:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/requirements.py**

```

L14: class ExplicitRequirement(Requirement):
L15: def __init__(self, candidate: Candidate) -> None:
L18: def __str__(self) -> str:
L21: def __repr__(self) -> str:
L24: def __hash__(self) -> int:
L27: def __eq__(self, other: Any) -> bool:
L33: def project_name(self) -> NormalizedName:
L38: def name(self) -> str:
L42: def format_for_error(self) -> str:
L45: def get_candidate_lookup(self) -> CandidateLookup:
L48: def is_satisfied_by(self, candidate: Candidate) -> bool:
L52: class SpecifierRequirement(Requirement):
L53: def __init__(self, ireq: InstallRequirement) -> None:
L61: def _equal(self) -> str:
L68: def __str__(self) -> str:
L71: def __repr__(self) -> str:
L74: def __eq__(self, other: object) -> bool:
L79: def __hash__(self) -> int:
L87: def project_name(self) -> NormalizedName:
L92: def name(self) -> str:
L95: def format_for_error(self) -> str:
L108: def get_candidate_lookup(self) -> CandidateLookup:
L111: def is_satisfied_by(self, candidate: Candidate) -> bool:
L124: class SpecifierWithoutExtrasRequirement(SpecifierRequirement):
L130: def __init__(self, ireq: InstallRequirement) -> None:
L138: def _equal(self) -> str:
L145: def __eq__(self, other: object) -> bool:
L150: def __hash__(self) -> int:
L158: class RequiresPythonRequirement(Requirement):
L161: def __init__(self, specifier: SpecifierSet, match: Candidate) -> None:
L173: def __str__(self) -> str:
L176: def __repr__(self) -> str:
L179: def __hash__(self) -> int:
L186: def __eq__(self, other: Any) -> bool:
L195: def project_name(self) -> NormalizedName:
L199: def name(self) -> str:
L202: def format_for_error(self) -> str:
L205: def get_candidate_lookup(self) -> CandidateLookup:
L208: def is_satisfied_by(self, candidate: Candidate) -> bool:
L216: class UnsatisfiableRequirement(Requirement):
L219: def __init__(self, name: NormalizedName) -> None:
L222: def __str__(self) -> str:
L225: def __repr__(self) -> str:
L228: def __eq__(self, other: object) -> bool:
L233: def __hash__(self) -> int:
L237: def project_name(self) -> NormalizedName:
L241: def name(self) -> str:
L244: def format_for_error(self) -> str:
L247: def get_candidate_lookup(self) -> CandidateLookup:
L250: def is_satisfied_by(self, candidate: Candidate) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/found_candidates.py

```

L28: def _iter_built(infos: Iterator[IndexCandidateInfo]) -> Iterator[Candidate]:
L59: def _iter_built_with_prepended(
L81: def _iter_built_with_inserted(
L113: class FoundCandidates(Sequence[Candidate]):
L122: def __init__(
L135: def __getitem__(self, index: Any) -> Any:
L141: def __iter__(self) -> Iterator[Candidate]:
L151: def __len__(self) -> int:
L157: def __bool__(self) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/legacy/resolver.py

```

L58: def _check_dist_requires_python(
L112: class Resolver(BaseResolver):
L119: def __init__(
L157: def resolve(
L194: def _add_requirement_to_set(
L309: def _is_upgrade_allowed(self, req: InstallRequirement) -> bool:
L318: def _set_req_to_reinstall(self, req: InstallRequirement) -> None:
L329: def _check_skip_installed(self, req_to_install: InstallRequirement) -> str | None:
L381: def _find_requirement_link(self, req: InstallRequirement) -> Link | None:
L403: def _populate_link(self, req: InstallRequirement) -> None:
L442: def _get_dist_for(self, req: InstallRequirement) -> BaseDistribution:
L488: def _resolve_one(
L517: def add_req(subreq: Requirement, extras_requested: Iterable[str]) -> None:
L571: def get_installation_order(
L586: def schedule(req: InstallRequirement) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/index/collector.py

```

L46: def _match_vcs_scheme(url: str) -> str | None:
L57: class _NotAPIContent(Exception):
L58: def __init__(self, content_type: str, request_desc: str) -> None:
L64: def _ensure_api_header(response: Response) -> None:
L86: class _NotHTTP(Exception):
L90: def _ensure_api_response(url: str, session: PipSession) -> None:

```

```

L108: def _get_simple_response(url: str, session: PipSession) -> Response:
L171: def _get_encoding_from_headers(headers: ResponseHeaders) -> str | None:
L182: class CacheablePageContent:
L183: def __init__(self, page: IndexContent) -> None:
L187: def __eq__(self, other: object) -> bool:
L190: def __hash__(self) -> int:
L194: class ParseLinks(Protocol):
L195: def __call__(self, page: IndexContent) -> Iterable[Link]: ...
L198: def with_cached_index_content(fn: ParseLinks) -> ParseLinks:
L206: def wrapper(cacheable_page: CacheablePageContent) -> list[Link]:
L210: def wrapper_wrapper(page: IndexContent) -> list[Link]:
L219: def parse_links(page: IndexContent) -> Iterable[Link]:
L248: class IndexContent:
L264: def __str__(self) -> str:
L268: class HTMLLinkParser(HTMLParser):
L274: def __init__(self, url: str) -> None:
L281: def handle_starttag(self, tag: str, attrs: list[tuple[str, str | None]]) -> None:
L289: def get_href(self, attrs: list[tuple[str, str | None]]) -> str | None:
L296: def _handle_get_simple_fail(
L306: def _make_index_content(
L319: def _get_index_content(link: Link, *, session: PipSession) -> IndexContent | None:
L379: class CollectedSources(NamedTuple):
L384: class LinkCollector:
L392: def __init__(
L401: def create(
L435: def find_links(self) -> list[str]:
L438: def fetch_response(self, location: Link) -> IndexContent | None:
L444: def collect_sources(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/index/source
s.py**

```

L31: class LinkSource:
L33: def link(self) -> Link | None:
L37: def page_candidates(self) -> FoundCandidates:
L41: def file_links(self) -> FoundLinks:
L46: def _is_html_file(file_url: str) -> bool:
L50: class _FlatDirectoryToUrls:
L53: def __init__(self, path: str) -> None:
L59: def _scan_directory(self) -> None:
L83: def page_candidates(self) -> list[str]:
L90: def project_name_to_urls(self) -> dict[str, list[str]]:
L97: class _FlatDirectorySource(LinkSource):
L108: def __init__(
L125: def link(self) -> Link | None:
L128: def page_candidates(self) -> FoundCandidates:
L132: def file_links(self) -> FoundLinks:

```

```

L137: class _LocalFileSource(LinkSource):
L147: def __init__(
L156: def link(self) -> Link | None:
L159: def page_candidates(self) -> FoundCandidates:
L164: def file_links(self) -> FoundLinks:
L170: class _RemoteFileSource(LinkSource):
L179: def __init__(
L190: def link(self) -> Link | None:
L193: def page_candidates(self) -> FoundCandidates:
L198: def file_links(self) -> FoundLinks:
L202: class _IndexDirectorySource(LinkSource):
L209: def __init__(
L218: def link(self) -> Link | None:
L221: def page_candidates(self) -> FoundCandidates:
L224: def file_links(self) -> FoundLinks:
L228: def build_source(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/index/packag
e_finder.py**

```

L63: def _check_link_requires_python(
L110: class LinkType(enum.Enum):
L122: class LinkEvaluator:
L133: def __init__(
L172: def evaluate_link(self, link: Link) -> tuple[LinkType, str]:
L283: def get_version_sort_key(v: str) -> tuple[int, ...]:
L300: def filter_unallowed_hashes(
L375: class CandidatePreferences:
L386: class BestCandidateResult:
L402: def __post_init__(self) -> None:
L411: class CandidateEvaluator:
L418: def create(
L453: def __init__(
L479: def get_applicable_candidates(
L518: def _sort_key(self, candidate: InstallationCandidate) -> CandidateSortingKey:
L583: def sort_best_candidate(
L596: def compute_best_candidate(
L614: class PackageFinder:
L621: def __init__(
L672: def create(
L708: def target_python(self) -> TargetPython:
L712: def search_scope(self) -> SearchScope:
L716: def search_scope(self, search_scope: SearchScope) -> None:
L720: def find_links(self) -> list[str]:
L724: def index_urls(self) -> list[str]:
L728: def proxy(self) -> str | None:
L732: def trusted_hosts(self) -> Iterable[str]:

```

```

L737: def custom_cert(self) -> str | None:
L745: def client_cert(self) -> str | None:
L751: def release_control(self) -> ReleaseControl | None:
L754: def set_release_control(self, release_control: ReleaseControl) -> None:
L758: def prefer_binary(self) -> bool:
L761: def set_prefer_binary(self) -> None:
L765: def uploaded_prior_to(self) -> datetime.datetime | None:
L768: def requires_python_skipped_reasons(self) -> list[str]:
L771: def make_link_evaluator(self, project_name: str) -> LinkEvaluator:
L785: def _sort_links(self, links: Iterable[Link]) -> list[Link]:
L801: def _log_skipped_link(self, link: Link, result: LinkType, detail: str) -> None:
L808: def get_install_candidate(
L833: def evaluate_links(
L847: def process_project_url(
L868: def find_all_candidates(self, project_name: str) -> list[InstallationCandidate]:
L925: def make_candidate_evaluator(
L942: def find_best_candidate(
L971: def find_requirement(
L995: def _format_versions(cand_iter: Iterable[InstallationCandidate]) -> str:
L1030: def _should_install_candidate(
L1072: def _find_name_version_sep(fragment: str, canonical_name: str) -> int:
L1098: def _extract_version_from_fragment(fragment: str, canonical_name: str) -> str | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/lazy_wheel.py

```

L22: class HTTPRangeRequestUnsupported(Exception):
L26: def dist_from_wheel_url(
L45: class LazyZipOverHTTP:
L54: def __init__(
L71: def mode(self) -> str:
L76: def name(self) -> str:
L80: def seekable(self) -> bool:
L84: def close(self) -> None:
L89: def closed(self) -> bool:
L93: def read(self, size: int = -1) -> bytes:
L107: def readable(self) -> bool:
L111: def seek(self, offset: int, whence: int = 0) -> int:
L121: def tell(self) -> int:
L125: def truncate(self, size: int | None = None) -> int:
L135: def writable(self) -> bool:
L139: def __enter__(self) -> LazyZipOverHTTP:
L143: def __exit__(self, *exc: Any) -> None:
L147: def _stay(self) -> Generator[None, None, None]:
L158: def _check_zip(self) -> None:
L173: def _stream_response(
L183: def _merge(

```

```
L205: def _download(self, start: int, end: int) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/session.py

```
L98: def looks_like_ci() -> bool:
L109: def user_agent() -> str:
L210: class LocalFSAdapter(BaseAdapter):
L211: def send(
L251: def close(self) -> None:
L255: class _SSLContextAdapterMixin:
L263: def __init__(
L272: def init_poolmanager(
L288: def proxy_manager_for(self, proxy: str, **proxy_kwargs: Any) -> ProxyManager:
L296: class HTTPAdapter(_SSLContextAdapterMixin, _BaseHTTPAdapter):
L300: class CacheControlAdapter(_SSLContextAdapterMixin, _BaseCacheControlAdapter):
L304: class InsecureHTTPAdapter(HTTPAdapter):
L305: def cert_verify(
L315: class InsecureCacheControlAdapter(CacheControlAdapter):
L316: def cert_verify(
L326: class PipSession(requests.Session):
L329: def __init__(
L413: def update_index_urls(self, new_index_urls: list[str]) -> None:
L420: def add_trusted_host(
L453: def iter_secure_origins(self) -> Generator[SecureOrigin, None, None]:
L458: def is_secure_origin(self, location: Link) -> bool:
L525: def request(self, method: str, url: str, *args: Any, **kwargs: Any) -> Response: #
type: ignore[override]
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/cache.py

```
L24: def is_from_cache(response: Response) -> bool:
L29: def suppressed_cache_errors() -> Generator[None, None, None]:
L39: class SafeFileCache(SeparateBodyBaseCache):
L57: def __init__(self, directory: str) -> None:
L62: def _get_cache_path(self, name: str) -> str:
L70: def get(self, key: str) -> bytes | None:
L80: def _write_to_file(self, path: str, writer_func: Callable[[BinaryIO], Any]) -> None:
L93: def _write(self, path: str, data: bytes) -> None:
L96: def _write_from_io(self, path: str, source_file: BinaryIO) -> None:
L99: def set(
L105: def delete(self, key: str) -> None:
L112: def get_body(self, key: str) -> BinaryIO | None:
```



```
L121: def set_body(self, key: str, body: bytes) -> None:
L125: def set_body_from_io(self, key: str, body_file: BinaryIO) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/utils.py

```
L31: def raise_for_status(resp: Response) -> None:
L59: def response_chunks(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/xmlrpc.py

```
L20: class PipXmlrpcTransport(xmlrpc.client.Transport):
L25: def __init__(
L33: def request(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/auth.py

```
L44: class Credentials(NamedTuple):
L50: class KeyRingBaseProvider(ABC):
L56: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None: ...
L59: def save_auth_info(self, url: str, username: str, password: str) -> None: ...
L62: class KeyRingNullProvider(KeyRingBaseProvider):
L67: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:
L70: def save_auth_info(self, url: str, username: str, password: str) -> None:
L74: class KeyRingPythonProvider(KeyRingBaseProvider):
L79: def __init__(self) -> None:
L84: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:
L102: def save_auth_info(self, url: str, username: str, password: str) -> None:
L106: class KeyRingCliProvider(KeyRingBaseProvider):
L117: def __init__(self, cmd: str) -> None:
L120: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:
L129: def save_auth_info(self, url: str, username: str, password: str) -> None:
L132: def _get_password(self, service_name: str, username: str) -> str | None:
L150: def _set_password(self, service_name: str, username: str, password: str) -> None:
L166: def get_keyring_provider(provider: str) -> KeyRingBaseProvider:
L191: def PATH_as_shutil_which_determines_it() -> str:
L227: class MultiDomainBasicAuth(AuthBase):
L228: def __init__(
```

```

L246: def keyring_provider(self) -> KeyRingBaseProvider:
L250: def keyring_provider(self, provider: str) -> None:
L258: def use_keyring(self) -> bool:
L264: def _get_keyring_auth(
L290: def _get_index_url(self, url: str) -> str | None:
L340: def _get_new_credentials(
L397: def _get_url_and_credentials(
L445: def __call__(self, req: PreparedRequest) -> PreparedRequest:
L463: def _prompt_for_password(self, netloc: str) -> tuple[str | None, str | None, bool]:
L475: def _should_save_password_to_keyring(self) -> bool:
L484: def handle_401(self, resp: Response, **kwargs: Any) -> Response:
L547: def warn_on_401(self, resp: Response, **kwargs: Any) -> None:
L555: def save_credentials(self, resp: Response, **kwargs: Any) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/download.py

```

L31: def _get_http_response_size(resp: Response) -> int | None:
L38: def _get_http_response_etag_or_last_modified(resp: Response) -> str | None:
L46: def _log_download(
L97: def sanitize_content_filename(filename: str) -> str:
L104: def parse_content_disposition(content_disposition: str, default_filename: str) -> str:
L119: def _get_http_response_filename(resp: Response, link: Link) -> str:
L141: class _FileDownload:
L150: def is_incomplete(self) -> bool:
L153: def write_chunk(self, data: bytes) -> None:
L157: def reset_file(self) -> None:
L164: class Downloader:
L165: def __init__(
L177: def batch(
L185: def __call__(self, link: Link, location: str) -> tuple[str, str]:
L200: def _process_response(self, download: _FileDownload, resp: Response) -> None:
L219: def _attempt_resumes_or_redownloads(
L259: def _cache_resumed_download(
L315: def _http_get_resume(
L329: def _http_get(self, link: Link, headers: Mapping[str, str] = HEADERS) -> Response:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/parser.py

```

L27: class PrettyHelpFormatter(optparse.IndentedHelpFormatter):
L41: def __init__(self, *args: Any, **kwargs: Any) -> None:
L48: def format_option_strings(self, option: optparse.Option) -> str:
L66: def format_option(self, option: optparse.Option) -> str:
L96: def format_heading(self, heading: str) -> str:

```

```

L101: def format_usage(self, usage: str) -> str:
L110: def format_description(self, description: str | None) -> str:
L129: def format_epilog(self, epilog: str | None) -> str:
L136: def expand_default(self, option: optparse.Option) -> str:
L143: def indent_lines(self, text: str, indent: str) -> str:
L148: class UpdatingDefaultsHelpFormatter(PrettyHelpFormatter):
L157: def expand_default(self, option: optparse.Option) -> str:
L180: class CustomOptionParser(optparse.OptionParser):
L181: def insert_option_group(
L193: def option_list_all(self) -> list[optparse.Option]:
L202: class ConfigOptionParser(CustomOptionParser):
L206: def __init__(
L219: def check_default(self, option: optparse.Option, key: str, val: Any) -> Any:
L226: def _get_ordered_configuration_items(
L257: def _update_defaults(self, defaults: dict[str, Any]) -> dict[str, Any]:
L321: def get_default_values(self) -> optparse.Values:
L343: def error(self, msg: str) -> NoReturn:
L347: def print_help(self, file: Any = None) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/main_parser.py

```

L21: def create_main_parser() -> ConfigOptionParser:
L52: def identify_python_interpreter(python: str) -> str | None:
L71: def parse_command(args: list[str]) -> tuple[str, list[str]]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/progress_bar.py

```

L33: def _rich_download_progress_bar(
L75: def _rich_install_progress_bar(
L97: def _raw_progress_bar(
L103: def write_progress(current: int, total: int) -> None:
L120: def get_download_progress_renderer(
L144: def get_install_progress_renderer(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/autocompletion.py

```

L17: def autocomplete() -> None:

```

```
L132: def get_path_completion_type(
L156: def auto_complete_paths(current: str, completion_type: str) -> Iterable[str]:
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/req_comm
and.py**

```
L64: def should_ignore_regular_constraints(options: Values) -> bool:
L84: def with_cleanup(
L91: def configure_tempdir_registry(registry: TempDirectoryTypeRegistry) -> None:
L95: def wrapper(self: _CommandT, options: Values, args: list[str]) -> int:
L112: def parse_constraint_files(
L137: class RequirementCommand(IndexGroupCommand):
L138: def __init__(self, *args: Any, **kw: Any) -> None:
L145: def determine_resolver_variant(options: Values) -> str:
L153: def make_requirement_preparer(
L234: def make_resolver(
L290: def get_requirements(
L435: def trace_basic_info(finder: PackageFinder) -> None:
L445: def _build_package_finder(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/index_com
mand.py**

```
L36: def _create_truststore_ssl_context() -> SSLContext | None:
L54: class SessionCommandMixin(CommandContextMixin):
L59: def __init__(self) -> None:
L64: def _get_index_urls(cls, options: Values) -> list[str] | None:
L77: def get_default_session(self, options: Values) -> PipSession:
L87: def _build_session(
L140: def _pip_self_version_check_fetch(
L148: def _pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
L154: class IndexGroupCommand(Command, SessionCommandMixin):
L161: def should_exclude_prerelease(
L179: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/cmdoption
s.py**

```
L42: def raise_option_error(parser: OptionParser, option: Option, msg: str) -> None:
L56: def make_option_group(group: dict[str, Any], parser: ConfigOptionParser) -> OptionGroup:
```

```

L68: def check_dist_restriction(options: Values, check_target: bool = False) -> None:
L116: def check_build_constraints(options: Values) -> None:
L139: def _path_option_check(option: Option, opt: str, value: str) -> str:
L143: def _package_name_option_check(option: Option, opt: str, value: str) -> str:
L147: class PipOption(Option):
L348: def exists_action() -> Option:
L403: def extra_index_url() -> Option:
L426: def find_links() -> Option:
L442: def _handle_uploaded_prior_to(
L487: def uploaded_prior_to() -> Option:
L506: def trusted_host() -> Option:
L518: def constraints() -> Option:
L531: def build_constraints() -> Option:
L546: def requirements() -> Option:
L563: def requirements_from_scripts() -> Option:
L575: def editable() -> Option:
L590: def _handle_src(option: Option, opt_str: str, value: str, parser: OptionParser) ->
None:
L613: def _get_format_control(values: Values, option: Option) -> Any:
L618: def _handle_no_binary(
L629: def _handle_only_binary(
L640: def no_binary() -> Option:
L658: def only_binary() -> Option:
L676: def _get_release_control(values: Values, option: Option) -> Any:
L681: def _handle_all_releases(
L693: def _handle_only_final(
L705: def all_releases() -> Option:
L723: def only_final() -> Option:
L740: def check_release_control_exclusive(options: Values) -> None:
L772: def _convert_python_version(value: str) -> tuple[tuple[int, ...], str | None]:
L801: def _handle_python_version(
L870: def add_target_python_options(cmd_opts: OptionGroup) -> None:
L877: def make_target_python(options: Values) -> TargetPython:
L888: def prefer_binary() -> Option:
L912: def _handle_no_cache_dir(
L961: def _handle_dependency_group(
L1040: def _handle_config_settings(
L1118: def _handle_merge_hash(
L1179: def check_list_path_option(options: Values) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/base_command.py

```

L48: class Command(CommandContextMixIn):
L52: def __init__(self, name: str, summary: str, isolated: bool = False) -> None:
L82: def add_options(self) -> None:
L86: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:

```

```

L96: def run(self, options: Values, args: list[str]) -> int:
L99: def _run_wrapper(self, level_number: int, options: Values, args: list[str]) -> int:
L100: def _inner_run() -> int:
L161: def parse_args(self, args: list[str]) -> tuple[Values, list[str]]:
L165: def main(self, args: list[str]) -> int:
L172: def _main(self, args: list[str]) -> int:
L260: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/command_
context.py

```

L8: class CommandContextMixin:
L9: def __init__(self) -> None:
L15: def main_context(self) -> Generator[None, None, None]:
L25: def enter_context(self, context_provider: AbstractContextManager[_T]) -> _T:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/spinners.p
y

```

L30: class SpinnerInterface:
L31: def spin(self) -> None:
L34: def finish(self, final_status: str) -> None:
L38: class InteractiveSpinner(SpinnerInterface):
L39: def __init__(
L59: def _write(self, status: str) -> None:
L71: def spin(self) -> None:
L78: def finish(self, final_status: str) -> None:
L91: class NonInteractiveSpinner(SpinnerInterface):
L92: def __init__(self, message: str, min_update_interval_seconds: float = 60.0) -> None:
L98: def _update(self, status: str) -> None:
L103: def spin(self) -> None:
L110: def finish(self, final_status: str) -> None:
L117: class RateLimiter:
L118: def __init__(self, min_update_interval_seconds: float) -> None:
L122: def ready(self) -> bool:
L127: def reset(self) -> None:
L132: def open_spinner(message: str) -> Generator[SpinnerInterface, None, None]:
L155: class _PipRichSpinner:
L163: def __init__(self, label: str) -> None:
L170: def __rich_console__(
L175: def __rich_measure__(
L181: def render(self) -> RenderableType:
L187: def finish(self, status: str) -> None:
L194: def open_rich_spinner(label: str, console: Console | None = None) -> Generator[None]:

```

```
L220: def hidden_cursor(file: IO[str]) -> Generator[None, None, None]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/main.py

```
L41: def main(args: list[str] | None = None) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/base.py

```
L13: class AbstractDistribution(metaclass=abc.ABCMeta):
L32: def __init__(self, req: InstallRequirement) -> None:
L37: def build_tracker_id(self) -> str | None:
L45: def get_metadata_distribution(self) -> BaseDistribution:
L49: def prepare_distribution_metadata(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/installed.py

```
L12: class InstalledDistribution(AbstractDistribution):
L20: def build_tracker_id(self) -> str | None:
L23: def get_metadata_distribution(self) -> BaseDistribution:
L27: def prepare_distribution_metadata(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/sdist.py

```
L19: class SourceDistribution(AbstractDistribution):
L27: def build_tracker_id(self) -> str | None:
L32: def get_metadata_distribution(self) -> BaseDistribution:
L35: def prepare_distribution_metadata(
L73: def _prepare_build_backend(
L101: def _get_build_requires_wheel(self) -> Iterable[str]:
L109: def _get_build_requires_editable(self) -> Iterable[str]:
L119: def _install_build_reqs(
L140: def _raise_conflicts(
L157: def _raise_missing_reqs(self, missing: set[str]) -> None:
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/
__init__.py**

```
L7: def make_distribution_for_install_requirement(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/
wheel.py**

```
L18: class WheelDistribution(AbstractDistribution):
L25: def build_tracker_id(self) -> str | None:
L28: def get_metadata_distribution(self) -> BaseDistribution:
L38: def prepare_distribution_metadata(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/versioncon
trol.py**

```
L45: def is_url(name: str) -> bool:
L55: def make_vcs_requirement_url(
L74: def find_path_to_project_root_from_repo_root(
L103: class RemoteNotFoundError(Exception):
L107: class RemoteNotValidError(Exception):
L108: def __init__(self, url: str):
L114: class RevOptions:
L130: def __repr__(self) -> str:
L134: def arg_rev(self) -> str | None:
L140: def to_args(self) -> CommandArgs:
L152: def to_display(self) -> str:
L158: def make_new(self, rev: str) -> RevOptions:
L168: class VcsSupport:
L172: def __init__(self) -> None:
L178: def __iter__(self) -> Iterator[str]:
L182: def backends(self) -> list[VersionControl]:
L186: def dirnames(self) -> list[str]:
L190: def all_schemes(self) -> list[str]:
L196: def register(self, cls: type[VersionControl]) -> None:
L204: def unregister(self, name: str) -> None:
L208: def get_backend_for_dir(self, location: str) -> VersionControl | None:
L231: def get_backend_for_scheme(self, scheme: str) -> VersionControl | None:
L240: def get_backend(self, name: str) -> VersionControl | None:
L251: class VersionControl:
L262: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:
```



```

L270: def get_subdirectory(cls, location: str) -> str | None:
L278: def get_requirement_revision(cls, repo_dir: str) -> str:
L285: def get_src_requirement(cls, repo_dir: str, project_name: str) -> str:
L309: def get_base_rev_args(rev: str) -> list[str]:
L318: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:
L332: def make_rev_options(
L345: def _is_local_repository(cls, repo: str) -> bool:
L354: def get_netloc_and_auth(
L375: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L406: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
L412: def get_url_rev_options(self, url: HiddenText) -> tuple[HiddenText, RevOptions]:
L428: def normalize_url(url: str) -> str:
L436: def compare_urls(cls, url1: str, url2: str) -> bool:
L442: def fetch_new(
L456: def switch(
L471: def update(
L487: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L497: def obtain(self, dest: str, url: HiddenText, verbosity: int) -> None:
L586: def unpack(self, location: str, url: HiddenText, verbosity: int) -> None:
L599: def get_remote_url(cls, location: str) -> str:
L609: def get_revision(cls, location: str) -> str:
L616: def run_command(
L674: def is_repository_directory(cls, path: str) -> bool:
L682: def get_repository_root(cls, location: str) -> str | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/subversion.py

```

L31: class Subversion(VersionControl):
L38: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:
L42: def get_base_rev_args(rev: str) -> list[str]:
L46: def get_revision(cls, location: str) -> str:
L75: def get_netloc_and_auth(
L90: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L98: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
L108: def get_remote_url(cls, location: str) -> str:
L132: def _get_svn_url_rev(cls, location: str) -> tuple[str | None, int]:
L182: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L186: def __init__(self, use_interactive: bool | None = None) -> None:
L200: def call_vcs_version(self) -> tuple[int, ...]:
L228: def get_vcs_version(self) -> tuple[int, ...]:
L248: def get_remote_call_options(self) -> CommandArgs:
L279: def fetch_new(
L303: def switch(
L319: def update(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/bazaar.py

```

L19: class Bazaar(VersionControl):
L34: def get_base_rev_args(rev: str) -> list[str]:
L37: def fetch_new(
L58: def switch(
L67: def update(
L92: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L100: def get_remote_url(cls, location: str) -> str:
L115: def get_revision(cls, location: str) -> str:
L125: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/mercurial.py

```

L21: class Mercurial(VersionControl):
L34: def get_base_rev_args(rev: str) -> list[str]:
L37: def fetch_new(
L61: def switch(
L86: def update(
L103: def get_remote_url(cls, location: str) -> str:
L115: def get_revision(cls, location: str) -> str:
L128: def get_requirement_revision(cls, location: str) -> str:
L142: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L147: def get_subdirectory(cls, location: str) -> str | None:
L161: def get_repository_root(cls, location: str) -> str | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/git.py

```

L58: def looks_like_hash(sha: str) -> bool:
L62: class Git(VersionControl):
L79: def get_base_rev_args(rev: str) -> list[str]:
L83: def run_command(cls, *args: Any, **kwargs: Any) -> str:
L91: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:
L105: def get_git_version(self) -> tuple[int, ...]:
L119: def get_current_branch(cls, location: str) -> str | None:
L144: def get_revision_sha(cls, dest: str, rev: str) -> tuple[str | None, bool]:
L190: def _should_fetch(cls, dest: str, rev: str) -> bool:
L213: def resolve_revision(
L259: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L273: def fetch_new(
L336: def switch(

```

```

L358: def update(
L389: def get_remote_url(cls, location: str) -> str:
L419: def _git_remote_to_pip_url(url: str) -> str:
L450: def has_commit(cls, location: str, rev: str) -> bool:
L466: def get_revision(cls, location: str, rev: str | None = None) -> str:
L478: def get_subdirectory(cls, location: str) -> str | None:
L496: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L527: def update_submodules(cls, location: str, verbosity: int = 0) -> None:
L541: def get_repository_root(cls, location: str) -> str | None:
L566: def should_add_vcs_url_prefix(repo_url: str) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/__init__.py

```

L29: def vendored(modulename):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/tomli_w/_write
r.py**

```

L33: class Context:
L34: def __init__(self, allow_multiline: bool, indent: int):
L43: def dump(
L56: def dumps(
L63: def gen_table_chunks(
L100: def format_literal(obj: object, ctx: Context, *, nest_level: int = 0) -> str:
L126: def format_decimal(obj: Decimal) -> str:
L135: def format_inline_table(obj: Mapping, ctx: Context) -> str:
L156: def format_inline_array(obj: tuple | list, ctx: Context, nest_level: int) -> str:
L171: def format_key_part(part: str) -> str:
L185: def format_string(s: str, *, allow_multiline: bool) -> str:
L215: def is_aot(obj: Any) -> bool:
L225: def is_suitable_inline_table(obj: Mapping, ctx: Context) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_collections.py

```

L15: class HasGettableStringKeys(Protocol):
L16: def keys(self) -> typing.Iterator[str]: ...
L18: def __getitem__(self, key: str) -> str: ...
L39: class _Sentinel(Enum):
L43: def ensure_can_construct_http_header_dict(
L63: class RecentlyUsedContainer(typing.Generic[_KT, _VT], typing.MutableMapping[_KT, _VT]):

```

```

L82: def __init__(
L93: def __getitem__(self, key: _KT) -> _VT:
L100: def __setitem__(self, key: _KT, value: _VT) -> None:
L125: def __delitem__(self, key: _KT) -> None:
L132: def __len__(self) -> int:
L136: def __iter__(self) -> typing.NoReturn:
L141: def clear(self) -> None:
L151: def keys(self) -> set[_KT]: # type: ignore[override]
L156: class HTTPHeaderDictItemView(set[tuple[str, str]]):
L187: def __init__(self, headers: HTTPHeaderDict) -> None:
L190: def __len__(self) -> int:
L193: def __iter__(self) -> typing.Iterator[tuple[str, str]]:
L196: def __contains__(self, item: object) -> bool:
L204: class HTTPHeaderDict(typing.MutableMapping[str, str]):
L240: def __init__(self, headers: ValidHTTPHeaderSource | None = None, **kwargs: str):
L251: def __setitem__(self, key: str, val: str) -> None:
L257: def __getitem__(self, key: str) -> str:
L263: def __delitem__(self, key: str) -> None:
L268: def __contains__(self, key: object) -> bool:
L275: def setdefault(self, key: str, default: str = "") -> str:
L278: def __eq__(self, other: object) -> bool:
L289: def __ne__(self, other: object) -> bool:
L292: def __len__(self) -> int:
L295: def __iter__(self) -> typing.Iterator[str]:
L300: def discard(self, key: str) -> None:
L306: def add(self, key: str, val: str, *, combine: bool = False) -> None:
L341: def extend(self, *args: ValidHTTPHeaderSource, **kwargs: str) -> None:
L375: def getlist(self, key: str) -> list[str]: ...
L378: def getlist(self, key: str, default: _DT) -> list[str] | _DT: ...
L380: def getlist(
L400: def _prepare_for_method_change(self) -> Self:
L426: def __repr__(self) -> str:
L429: def _copy_from(self, other: HTTPHeaderDict) -> None:
L434: def copy(self) -> Self:
L439: def iteritems(self) -> typing.Iterator[tuple[str, str]]:
L446: def itermerged(self) -> typing.Iterator[tuple[str, str]]:
L452: def items(self) -> HTTPHeaderDictItemView: # type: ignore[override]
L455: def _has_value_for_header(self, header_name: str, potential_value: str) -> bool:
L460: def __ior__(self, other: object) -> HTTPHeaderDict:
L469: def __or__(self, other: object) -> Self:
L479: def __ror__(self, other: object) -> Self:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/fields.py

```

L15: def guess_content_type(
L31: def format_header_param_rfc2231(name: str, value: _TYPE_FIELD_VALUE) -> str:

```

```

L79: def format_multipart_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
L117: def format_header_param_html5(name: str, value: _TYPE_FIELD_VALUE) -> str:
L135: def format_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
L153: class RequestField:
L171: def __init__(
L200: def from_tuples(
L244: def _render_part(self, name: str, value: _TYPE_FIELD_VALUE) -> str:
L260: def _render_parts(
L291: def render_headers(self) -> str:
L310: def make_multipart(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connection.py

```

L37: class BaseSSLError(BaseException): # type: ignore[no-redef]
L82: class HTTPConnection(_HTTPConnection):
L132: def __init__(
L163: def __str__(self) -> str:
L166: def __repr__(self) -> str:
L170: def host(self) -> str:
L189: def host(self, value: str) -> None:
L198: def _new_conn(self) -> socket.socket:
L227: def set_tunnel(
L244: def _wrap_ipv6(self, ip: bytes) -> bytes:
L253: def _tunnel(self) -> None:
L296: def _tunnel(self) -> None: # noqa: F811
L330: def connect(self) -> None:
L348: def is_closed(self) -> bool:
L352: def is_connected(self) -> bool:
L358: def has_connected_to_proxy(self) -> bool:
L362: def proxy_is_forwarding(self) -> bool:
L369: def proxy_is_tunneling(self) -> bool:
L375: def close(self) -> None:
L390: def putrequest(
L410: def putheader(self, header: str, *values: str) -> None: # type: ignore[override]
L424: def request( # type: ignore[override]
L521: def request_chunked(
L540: def getresponse( # type: ignore[override]
L603: class HTTPSConnection(HTTPConnection):
L621: def __init__(
L683: def set_cert(
L724: def connect(self) -> None:
L861: def _connect_tls_proxy(self, hostname: str, sock: socket.socket) -> ssl.SSLSocket:
L891: class _WrappedAndVerifiedSocket(typing.NamedTuple):
L901: def _ssl_wrap_socket_and_match_hostname(
L1026: def _match_hostname(
L1052: def _wrap_proxy_error(err: Exception, proxy_scheme: str | None) -> ProxyError:

```

```

L1077: def _get_default_user_agent() -> str:
L1081: class DummyConnection:
L1092: def _url_from_connection(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/respon
se.py**

```

L48: class ContentDecoder:
L49: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L53: def has_unconsumed_tail(self) -> bool:
L56: def flush(self) -> bytes:
L60: class DeflateDecoder(ContentDecoder):
L61: def __init__(self) -> None:
L67: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L110: def has_unconsumed_tail(self) -> bool:
L115: def flush(self) -> bytes:
L119: class GzipDecoderState:
L125: class GzipDecoder(ContentDecoder):
L126: def __init__(self) -> None:
L131: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L182: def has_unconsumed_tail(self) -> bool:
L185: def flush(self) -> bytes:
L191: class BrotliDecoder(ContentDecoder):
L195: def __init__(self) -> None:
L203: def _decompress(self, data: bytes, output_buffer_limit: int = -1) -> bytes:
L206: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L222: def has_unconsumed_tail(self) -> bool:
L228: def flush(self) -> bytes:
L244: class ZstdDecoder(ContentDecoder):
L245: def __init__(self) -> None:
L248: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L283: def has_unconsumed_tail(self) -> bool:
L288: def flush(self) -> bytes:
L294: class MultiDecoder(ContentDecoder):
L307: def __init__(self, modes: str) -> None:
L316: def flush(self) -> bytes:
L319: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L346: def has_unconsumed_tail(self) -> bool:
L350: def _get_decoder(mode: str) -> ContentDecoder:
L368: class BytesQueueBuffer:
L382: def __init__(self) -> None:
L386: def __len__(self) -> int:
L389: def put(self, data: bytes) -> None:
L393: def get(self, n: int) -> bytes:
L428: def get_all(self) -> bytes:
L445: class BaseHTTPResponse(io.IOBase):
L460: def __init__(

```

```

L495: def get_redirect_location(self) -> str | None | typing.Literal[False]:
L508: def data(self) -> bytes:
L511: def json(self) -> typing.Any:
L533: def url(self) -> str | None:
L537: def url(self, url: str | None) -> None:
L541: def connection(self) -> BaseHTTPConnection | None:
L545: def retries(self) -> Retry | None:
L549: def retries(self, retries: Retry | None) -> None:
L555: def stream(
L560: def read(
L568: def read1(
L575: def read_chunked(
L582: def release_conn(self) -> None:
L585: def drain_conn(self) -> None:
L588: def shutdown(self) -> None:
L591: def close(self) -> None:
L594: def _init_decoder(self) -> None:
L613: def _decode(
L650: def _flush_decoder(self) -> bytes:
L660: def readinto(self, b: bytearray) -> int:
L669: def getheaders(self) -> HTTPHeaderDict:
L672: def getheader(self, name: str, default: str | None = None) -> str | None:
L676: def info(self) -> HTTPHeaderDict:
L679: def geturl(self) -> str | None:
L683: class HTTPResponse(BaseHTTPResponse):
L689: class is also compatible with the Python standard library's :mod:`io`
L716: def __init__(
L780: def release_conn(self) -> None:
L787: def drain_conn(self) -> None:
L803: def data(self) -> bytes:
L814: def connection(self) -> HTTPConnection | None:
L817: def isclosed(self) -> bool:
L820: def tell(self) -> int:
L828: def _init_length(self, request_method: str | None) -> int | None:
L885: def _error_catcher(self) -> typing.Generator[None]:
L950: def _fp_read(
L1007: def _raw_read(
L1059: def read(
L1155: def read1(
L1225: def stream(
L1257: def readable(self) -> bool:
L1260: def shutdown(self) -> None:
L1269: def close(self) -> None:
L1282: def closed(self) -> bool:
L1294: def fileno(self) -> int:
L1305: def flush(self) -> None:
L1313: def supports_chunked_reads(self) -> bool:
L1322: def _update_chunk_length(self) -> None:
L1340: def _handle_chunk(self, amt: int | None) -> bytes:
L1362: def read_chunked(
L1447: def url(self) -> str | None:

```

```
L1456: def url(self, url: str | None) -> None:
L1459: def __iter__(self) -> typing.Iterator[bytes]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/exceptions.py

```
L18: class HTTPError(Exception):
L22: class HTTPWarning(Warning):
L29: class PoolError(HTTPError):
L32: def __init__(self, pool: ConnectionPool, message: str) -> None:
L37: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L42: class RequestError(PoolError):
L45: def __init__(self, pool: ConnectionPool, url: str | None, message: str) -> None:
L49: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L54: class SSLError(HTTPError):
L58: class ProxyError(HTTPError):
L64: def __init__(self, message: str, error: Exception) -> None:
L69: class DecodeError(HTTPError):
L73: class ProtocolError(HTTPError):
L84: class MaxRetryError(RequestError):
L95: def __init__(
L104: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L109: class HostChangedError(RequestError):
L112: def __init__(
L120: class TimeoutStateError(HTTPError):
L124: class TimeoutError(HTTPError):
L132: class ReadTimeoutError(TimeoutError, RequestError):
L138: class ConnectTimeoutError(TimeoutError):
L142: class NewConnectionError(ConnectTimeoutError, HTTPError):
L145: def __init__(self, conn: HTTPConnection, message: str) -> None:
L150: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L155: def pool(self) -> HTTPConnection:
L166: class NameResolutionError(NewConnectionError):
L169: def __init__(self, host: str, conn: HTTPConnection, reason: socket.gaierror):
L175: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L180: class EmptyPoolError(PoolError):
L184: class FullPoolError(PoolError):
L188: class ClosedPoolError(PoolError):
L192: class LocationValueError(ValueError, HTTPError):
L196: class LocationParseError(LocationValueError):
L199: def __init__(self, location: str) -> None:
L206: class URLSchemeUnknown(LocationValueError):
L209: def __init__(self, scheme: str):
L216: class ResponseError(HTTPError):
L223: class SecurityWarning(HTTPWarning):
L227: class InsecureRequestWarning(SecurityWarning):
L231: class NotOpenSSLWarning(SecurityWarning):
```



```

L235: class SystemTimeWarning(SecurityWarning):
L239: class InsecurePlatformWarning(SecurityWarning):
L243: class DependencyWarning(HTTPWarning):
L250: class ResponseNotChunked(ProtocolError, ValueError):
L254: class BodyNotHttpLibCompatible(HTTPError):
L261: class IncompleteRead(HTTPError, httplib_IncompleteRead):
L272: def __init__(self, partial: int, expected: int) -> None:
L276: def __repr__(self) -> str:
L283: class InvalidChunkLength(HTTPError, httplib_IncompleteRead):
L286: def __init__(self, response: HTTPResponse, length: bytes) -> None:
L292: def __repr__(self) -> str:
L299: class InvalidHeader(HTTPError):
L303: class ProxySchemeUnknown(AssertionError, URLSchemeUnknown):
L308: def __init__(self, scheme: str | None) -> None:
L320: class ProxySchemeUnsupported(ValueError):
L324: class HeaderParsingError(HTTPError):
L327: def __init__(
L334: class UnrewindableBodyError(HTTPError):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_request_methods.py

```

L20: class RequestMethods:
L51: def __init__(self, headers: typing.Mapping[str, str] | None = None) -> None:
L54: def urlopen(
L69: def request(
L147: def request_encode_url(
L184: def request_encode_body(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/__init__.py

```

L74: def add_stderr_logger(
L107: def disable_warnings(category: type[Warning] = exceptions.HTTPWarning) -> None:
L117: def request(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/poolmanager.py

```

L56: class PoolKey(typing.NamedTuple):

```

```

L95: def _default_key_normalizer(
L162: class PoolManager(RequestMethods):
L199: def __init__(
L230: def __enter__(self) -> Self:
L233: def __exit__(
L243: def _new_pool(
L281: def clear(self) -> None:
L290: def connection_from_host(
L319: def connection_from_context(
L344: def connection_from_pool_key(
L370: def connection_from_url(
L388: def _merge_pool_kwargs(
L410: def _proxy_requires_url_absolute_form(self, parsed_url: Url) -> bool:
L423: def urlopen( # type: ignore[override]
L506: class ProxyManager(PoolManager):
L561: def __init__(
L602: def connection_from_host(
L618: def _set_proxy_headers(
L635: def urlopen( # type: ignore[override]
L650: def proxy_from_url(url: str, **kw: typing.Any) -> ProxyManager:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/filepost.py

```

L22: def choose_boundary() -> str:
L29: def iter_field_objects(fields: _TYPE_FIELDS) -> typing.Iterable[RequestField]:
L51: def encode_multipart_formdata(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_base_connection.py

```

L12: class ProxyConfig(typing.NamedTuple):
L19: class _ResponseOptions(typing.NamedTuple):
L35: class BaseHTTPConnection(Protocol):
L54: def __init__(
L67: def set_tunnel(
L75: def connect(self) -> None: ...
L77: def request(
L93: def getresponse(self) -> BaseHTTPResponse: ...
L95: def close(self) -> None: ...
L98: def is_closed(self) -> bool:
L105: def is_connected(self) -> bool:
L109: def has_connected_to_proxy(self) -> bool:
L115: class BaseHTTPSPConnection(BaseHTTPConnection, Protocol):

```

```
L140: def __init__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connectionpool.py

```
L67: class ConnectionPool:
L81: def __init__(self, host: str, port: int | None = None) -> None:
L94: def __str__(self) -> str:
L97: def __enter__(self) -> Self:
L100: def __exit__(
L110: def close(self) -> None:
L120: class HTTPConnectionPool(ConnectionPool, RequestMethods):
L175: def __init__(
L236: def _new_conn(self) -> BaseHTTPConnection:
L256: def _get_conn(self, timeout: float | None = None) -> BaseHTTPConnection:
L294: def _put_conn(self, conn: BaseHTTPConnection | None) -> None:
L337: def _validate_conn(self, conn: BaseHTTPConnection) -> None:
L342: def _prepare_proxy(self, conn: BaseHTTPConnection) -> None:
L346: def _get_timeout(self, timeout: _TYPE_TIMEOUT) -> Timeout:
L358: def _raise_timeout(
L377: def _make_request(
L558: def close(self) -> None:
L570: def is_same_host(self, url: str) -> bool:
L592: def urlopen( # type: ignore[override]
L963: class HTTPSConnectionPool(HTTPConnectionPool):
L980: def __init__(
L1029: def _prepare_proxy(self, conn: HTTPSConnection) -> None: # type: ignore[override]
L1044: def _new_conn(self) -> BaseHTTPSConnection:
L1085: def _validate_conn(self, conn: BaseHTTPConnection) -> None:
L1108: def connection_from_url(url: str, **kw: typing.Any) -> HTTPConnectionPool:
L1138: def _normalize_host(host: None, scheme: str | None) -> None: ...
L1142: def _normalize_host(host: str, scheme: str | None) -> str: ...
L1145: def _normalize_host(host: str | None, scheme: str | None) -> str | None:
L1163: def _url_from_pool(
L1170: def _close_pool_connections(pool: queue.LifoQueue[typing.Any]) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/timeout.py

```
L14: class _TYPE_DEFAULT(Enum):
L25: class Timeout:
L109: def __init__(
L120: def __repr__(self) -> str:
L127: def resolve_default_timeout(timeout: _TYPE_TIMEOUT) -> float | None:
```

```

L131: def _validate_timeout(cls, value: _TYPE_TIMEOUT, name: str) -> _TYPE_TIMEOUT:
L173: def from_float(cls, timeout: _TYPE_TIMEOUT) -> Timeout:
L188: def clone(self) -> Timeout:
L202: def start_connect(self) -> float:
L213: def get_connect_duration(self) -> float:
L228: def connect_timeout(self) -> _TYPE_TIMEOUT:
L246: def read_timeout(self) -> float | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/retry.py

```

L33: class RequestHistory(typing.NamedTuple):
L41: class Retry:
L211: def __init__(
L258: def new(self, **kw: typing.Any) -> Self:
L283: def from_int(
L301: def get_backoff_time(self) -> float:
L320: def parse_retry_after(self, retry_after: str) -> float:
L341: def get_retry_after(self, response: BaseHTTPResponse) -> float | None:
L351: def sleep_for_retry(self, response: BaseHTTPResponse) -> bool:
L359: def _sleep_backoff(self) -> None:
L365: def sleep(self, response: BaseHTTPResponse | None = None) -> None:
L381: def _is_connection_error(self, err: Exception) -> bool:
L389: def _is_read_error(self, err: Exception) -> bool:
L395: def _is_method_retryable(self, method: str) -> bool:
L403: def is_retry(
L425: def is_exhausted(self) -> bool:
L444: def increment(
L541: def __repr__(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/wait.py

```

L33: def select_wait_for_socket(
L57: def poll_wait_for_socket(
L74: def do_poll(t: float | None) -> list[tuple[int, int]]:
L82: def _have_working_poll() -> bool:
L95: def wait_for_socket(
L113: def wait_for_read(sock: socket.socket, timeout: float | None = None) -> bool:
L120: def wait_for_write(sock: socket.socket, timeout: float | None = None) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/connection.py

```
L15: def is_connection_dropped(conn: BaseHTTPConnection) -> bool: # Platform-specific
L27: def create_connection(
L93: def _set_socket_options(
L103: def allowed_gai_family() -> socket.AddressFamily:
L114: def _has_ipv6(host: str) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/url.py

```
L80: class Url(
L100: def __new__( # type: ignore[no-untyped-def]
L117: def hostname(self) -> str | None:
L122: def request_uri(self) -> str:
L132: def authority(self) -> str | None:
L148: def netloc(self) -> str | None:
L162: def url(self) -> str:
L209: def __str__(self) -> str:
L214: def _encode_invalid_chars(
L221: def _encode_invalid_chars(
L227: def _encode_invalid_chars(
L263: def _remove_path_dot_segments(path: str) -> str:
L294: def _normalize_host(host: None, scheme: str | None) -> None: ...
L298: def _normalize_host(host: str, scheme: str | None) -> str: ...
L301: def _normalize_host(host: str | None, scheme: str | None) -> str | None:
L330: def _idna_encode(name: str) -> bytes:
L349: def _encode_target(target: str) -> str:
L367: def parse_url(url: str) -> Url:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/response.py

```
L9: def is_fp_closed(obj: object) -> bool:
L40: def assert_header_parsing(headers: httplib.HTTPMessage) -> None:
L91: def is_response_to_head(response: httplib.HTTPResponse) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl

ransport.py

```

L22: class SSLTransport:
L34: def _validate_ssl_context_for_tls_in_tls(ssl_context: ssl.SSLContext) -> None:
L49: def __init__(
L72: def __enter__(self) -> Self:
L75: def __exit__(self, *_: typing.Any) -> None:
L78: def fileno(self) -> int:
L81: def read(self, len: int = 1024, buffer: typing.Any | None = None) -> int | bytes:
L84: def recv(self, buflen: int = 1024, flags: int = 0) -> int | bytes:
L89: def recv_into(
L101: def sendall(self, data: bytes, flags: int = 0) -> None:
L111: def send(self, data: bytes, flags: int = 0) -> int:
L116: def makefile(
L168: def unwrap(self) -> None:
L171: def close(self) -> None:
L175: def getpeercert(
L180: def getpeercert(self, binary_form: typing.Literal[True]) -> bytes | None: ...
L182: def getpeercert(self, binary_form: bool = False) -> _TYPE_PEER_CERT_RET:
L185: def version(self) -> str | None:
L188: def cipher(self) -> tuple[str, str, int] | None:
L191: def selected_alpn_protocol(self) -> str | None:
L194: def shared_ciphers(self) -> list[tuple[str, str, int]] | None:
L197: def compression(self) -> str | None:
L200: def settimeout(self, value: float | None) -> None:
L203: def gettimeout(self) -> float | None:
L206: def _decref_socketios(self) -> None:
L209: def _wrap_ssl_read(self, len: int, buffer: bytearray | None = None) -> int | bytes:
L220: def _ssl_io_loop(self, func: typing.Callable[[], None]) -> None: ...
L224: def _ssl_io_loop(self, func: typing.Callable[[bytes], int], arg1: bytes) -> int: ...
L228: def _ssl_io_loop(
L235: def _ssl_io_loop(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl
_match_hostname.py**

```

L20: class CertificateError(ValueError):
L24: def _dnsname_match(
L80: def _ipaddress_match(ipname: str, host_ip: IPv4Address | IPv6Address) -> bool:
L95: def match_hostname(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/pro
xy.py**

```
L11: def connection_requires_http_tunnel(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl
_.py**

```
L30: def _is_bpo_43522_fixed(
L56: def _is_has_never_check_common_name_reliable(
L84: class _TYPE_PEER_CERT_RET_DICT(TypedDict, total=False):
L152: def assert_fingerprint(cert: bytes | None, fingerprint: str) -> None:
L186: def resolve_cert_reqs(candidate: None | int | str) -> VerifyMode:
L209: def resolve_ssl_version(candidate: None | int | str) -> int:
L225: def create_urllib3_context(
L378: def ssl_wrap_socket(
L396: def ssl_wrap_socket(
L413: def ssl_wrap_socket(
L487: def is_ipaddress(hostname: str | bytes) -> bool:
L500: def _is_key_file_encrypted(key_file: str) -> bool:
L511: def _ssl_wrap_socket_impl(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/util.
py**

```
L7: def to_bytes(
L19: def to_str(
L31: def reraise(
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/req
uest.py**

```
L35: class _TYPE_FAILEDTELL(Enum):
L51: def make_headers(
L133: def set_file_position(
L153: def rewind_body(body: typing.IO[typing.AnyStr], body_pos: _TYPE_BODY_POSITION) -> None:
L183: class ChunksAndContentLength(typing.NamedTuple):
L188: def body_to_chunks(
L221: def chunk_readable() -> typing.Iterable[bytes]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/c

onnection.py

```

L29: def _is_legal_header_name(name: bytes) -> bool:
L44: def _is_illegal_header_value(value: bytes) -> bool:
L54: class _LockedObject(typing.Generic[T]):
L68: def __init__(self, obj: T):
L72: def __enter__(self) -> T:
L76: def __exit__(
L85: class HTTP2Connection(HTTPSCConnection):
L86: def __init__(
L101: def _new_h2_conn(self) -> _LockedObject[h2.connection.H2Connection]:
L105: def connect(self) -> None:
L112: def putrequest( # type: ignore[override]
L143: def putheader(self, header: str | bytes, *values: str | bytes) -> None: # type:
ignore[override]
L156: def endheaders(self, message_body: typing.Any = None) -> None: # type:
ignore[override]
L170: def send(self, data: typing.Any) -> None:
L215: def set_tunnel(
L226: def getresponse( # type: ignore[override]
L268: def request( # type: ignore[override]
L307: def close(self) -> None:
L324: class HTTP2Response(BaseHTTPResponse):
L326: def __init__(
L349: def data(self) -> bytes:
L352: def get_redirect_location(self) -> None:
L355: def close(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/_
_init__.py

```

L15: def inject_into_urllib3() -> None:
L43: def extract_from_urllib3() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/p
robe.py

```

L6: class _HTTP2ProbeCache:
L13: def __init__(self) -> None:
L18: def acquire_and_get(self, host: str, port: int) -> bool | None:
L51: def set_and_release(
L65: def _values(self) -> dict[tuple[str, int], bool | None]:
L70: def _reset(self) -> None:

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/pyopenssl.py

```

L50: class UnsupportedExtension(Exception): # type: ignore[no-redef]
L139: def inject_into_urllib3() -> None:
L150: def extract_from_urllib3() -> None:
L159: def _validate_dependencies_met() -> None:
L185: def _dnsname_to_stdlib(name: str) -> str | None:
L199: def idna_encode(name: str) -> bytes | None:
L226: def get_subj_alt_name(peer_cert: X509) -> list[tuple[str, str]]:
L274: class WrappedSocket:
L277: def __init__(
L289: def fileno(self) -> int:
L293: def _decref_socketios(self) -> None:
L299: def recv(self, *args: typing.Any, **kwargs: typing.Any) -> bytes:
L324: def recv_into(self, *args: typing.Any, **kwargs: typing.Any) -> int:
L347: def settimeout(self, timeout: float) -> None:
L350: def _send_until_done(self, data: bytes) -> int:
L361: def sendall(self, data: bytes) -> None:
L369: def shutdown(self, how: int) -> None:
L375: def close(self) -> None:
L380: def _real_close(self) -> None:
L386: def getpeercert(
L402: def version(self) -> str:
L405: def selected_alpn_protocol(self) -> str | None:
L413: class PyOpenSSLContext:
L420: def __init__(self, protocol: int) -> None:
L430: def options(self) -> int:
L434: def options(self, value: int) -> None:
L439: def verify_flags(self) -> int:
L443: def verify_flags(self, value: int) -> None:
L448: def verify_mode(self) -> int:
L452: def verify_mode(self, value: ssl.VerifyMode) -> None:
L455: def set_default_verify_paths(self) -> None:
L458: def set_ciphers(self, ciphers: bytes | str) -> None:
L463: def load_verify_locations(
L480: def load_cert_chain(
L496: def set_alpn_protocols(self, protocols: list[bytes | str]) -> None:
L500: def wrap_socket(
L531: def _set_ctx_options(self) -> None:
L539: def minimum_version(self) -> int:
L543: def minimum_version(self, minimum_version: int) -> None:
L548: def maximum_version(self) -> int:
L552: def maximum_version(self, maximum_version: int) -> None:
L557: def _verify_callback(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/socks.py

```

L75: class _TYPE_SOCKS_OPTIONS(typing.TypedDict):
L84: class SOCKSConnection(HTTPConnection):
L89: def __init__(
L98: def _new_conn(self) -> socks.socksocket:
L161: class SOCKSHTTPConnection(SOCKSConnection, HTTPConnection):
L165: class SOCKSHTTPConnectionPool(HTTPConnectionPool):
L169: class SOCKSHTTPConnectionPool(HTTPConnectionPool):
L173: class SOCKSProxyManager(PoolManager):
L184: def __init__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/fetch.py

```

L71: class _RequestError(Exception):
L72: def __init__(
L85: class _StreamingError(_RequestError):
L89: class _TimeoutError(_RequestError):
L93: def _obj_from_dict(dict_val: dict[str, Any]) -> JsProxy:
L97: class _ReadStream(io.RawIOBase):
L98: def __init__(
L118: def __del__(self) -> None:
L122: def is_closed(self) -> bool:
L127: def closed(self) -> bool:
L130: def close(self) -> None:
L144: def readable(self) -> bool:
L147: def writable(self) -> bool:
L150: def seekable(self) -> bool:
L153: def readinto(self, byte_obj: Buffer) -> int:
L200: class _StreamingFetcher:
L201: def __init__(self) -> None:
L214: def promise_resolver(js_resolve_fn: JsProxy, js_reject_fn: JsProxy) -> None:
L215: def onMsg(e: JsProxy) -> None:
L219: def onErr(e: JsProxy) -> None:
L229: def send(self, request: EmscriptenRequest) -> EmscriptenResponse:
L302: class _JSPIReadStream(io.RawIOBase):
L324: def __init__(
L342: def __del__(self) -> None:
L346: def is_closed(self) -> bool:
L351: def closed(self) -> bool:
L354: def close(self) -> None:
L367: def readable(self) -> bool:
L370: def writable(self) -> bool:
L373: def seekable(self) -> bool:

```

```

L376: def _get_next_buffer(self) -> bool:
L392: def readinto(self, byte_obj: Buffer) -> int:
L410: def is_in_browser_main_thread() -> bool:
L414: def is_cross_origin_isolated() -> bool:
L418: def is_in_node() -> bool:
L427: def is_worker_available() -> bool:
L449: def send_streaming_request(request: EmscriptenRequest) -> EmscriptenResponse | None:
L469: def _show_timeout_warning() -> None:
L480: def _show_streaming_warning() -> None:
L499: def send_request(request: EmscriptenRequest) -> EmscriptenResponse:
L548: def send_jspi_request(
L626: def _run_sync_with_timeout(
L680: def has_jspi() -> bool:
L699: def _is_node_js() -> bool:
L714: def streaming_ready() -> bool | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/connection.py

```

L25: class EmscriptenHTTPConnection:
L46: def __init__(
L73: def set_tunnel(
L82: def connect(self) -> None:
L85: def request(
L129: def getresponse(self) -> BaseHTTPResponse:
L139: def close(self) -> None:
L144: def is_closed(self) -> bool:
L152: def is_connected(self) -> bool:
L157: def has_connected_to_proxy(self) -> bool:
L165: class EmscriptenHTTPConnection(EmscriptenHTTPConnection):
L182: def __init__(
L242: def set_cert(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/response.py

```

L23: class EmscriptenResponse:
L30: class EmscriptenHttpResponseWrapper(BaseHTTPResponse):
L31: def __init__(
L56: def url(self) -> str | None:
L60: def url(self, url: str | None) -> None:
L64: def connection(self) -> BaseHTTPConnection | BaseHTTPSConnection | None:
L68: def retries(self) -> Retry | None:
L72: def retries(self, retries: Retry | None) -> None:

```

```

L76: def stream(
L102: def _init_length(self, request_method: str | None) -> int | None:
L139: def read(
L176: def read_chunked(
L188: def release_conn(self) -> None:
L195: def drain_conn(self) -> None:
L199: def data(self) -> bytes:
L205: def json(self) -> typing.Any:
L226: def close(self) -> None:
L236: def _error_catcher(self) -> typing.Generator[None]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emsripten/__init__.py

```

L9: def inject_into_urllib3() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emsripten/request.py

```

L9: class EmsriptenRequest:
L18: def set_header(self, name: str, value: str) -> None:
L21: def set_body(self, body: _TYPE_BODY | None) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/providers.py

```

L17: class Preference(Protocol):
L18: def __lt__(self, __other: Any) -> bool: ...
L21: class AbstractProvider(Generic[RT, CT, KT]):
L24: def identify(self, requirement_or_candidate: RT | CT) -> KT:
L33: def get_preference(
L92: def find_matches(
L127: def is_satisfied_by(self, requirement: RT, candidate: CT) -> bool:
L138: def get_dependencies(self, candidate: CT) -> Iterable[RT]:
L146: def narrow_requirement_selection(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/stru

cts.py

```

L27: class RequirementInformation(NamedTuple, Generic[RT, CT]):
L31: class State(NamedTuple, Generic[RT, CT, KT]):
L45: class DirectedGraph(Generic[KT]):
L48: def __init__(self) -> None:
L53: def __iter__(self) -> Iterator[KT]:
L56: def __len__(self) -> int:
L59: def __contains__(self, key: KT) -> bool:
L62: def copy(self) -> DirectedGraph[KT]:
L70: def add(self, key: KT) -> None:
L78: def remove(self, key: KT) -> None:
L86: def connected(self, f: KT, t: KT) -> bool:
L89: def connect(self, f: KT, t: KT) -> None:
L99: def iter_edges(self) -> Iterator[tuple[KT, KT]]:
L104: def iter_children(self, key: KT) -> Iterator[KT]:
L107: def iter_parents(self, key: KT) -> Iterator[KT]:
L111: class IteratorMapping(Mapping[KT, Iterator[CT]], Generic[RT, CT, KT]):
L112: def __init__(
L122: def __repr__(self) -> str:
L129: def __bool__(self) -> bool:
L132: def __contains__(self, key: object) -> bool:
L135: def __getitem__(self, k: KT) -> Iterator[CT]:
L142: def __iter__(self) -> Iterator[KT]:
L146: def __len__(self) -> int:
L151: class _FactoryIterableView(Iterable[RT]):
L160: def __init__(self, factory: Callable[[], Iterable[RT]]) -> None:
L164: def __repr__(self) -> str:
L167: def __bool__(self) -> bool:
L174: def __iter__(self) -> Iterator[RT]:
L180: class _SequenceIterableView(Iterable[RT]):
L187: def __init__(self, sequence: Sequence[RT]):
L190: def __repr__(self) -> str:
L193: def __bool__(self) -> bool:
L196: def __iter__(self) -> Iterator[RT]:
L200: def build_iter_view(matches: Matches[CT]) -> Iterable[CT]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/reports.py

```

L11: class BaseReporter(Generic[RT, CT, KT]):
L14: def starting(self) -> None:
L17: def starting_round(self, index: int) -> None:
L23: def ending_round(self, index: int, state: State[RT, CT, KT]) -> None:
L30: def ending(self, state: State[RT, CT, KT]) -> None:
L33: def adding_requirement(self, requirement: RT, parent: CT | None) -> None:

```

```

L43: def resolving_conflicts(
L51: def rejecting_candidate(self, criterion: Criterion[RT, CT], candidate: CT) -> None:
L54: def pinning(self, candidate: CT) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/resolution.py

```

L38: def _build_result(state: State[RT, CT, KT]) -> Result[RT, CT, KT]:
L68: class Resolution(Generic[RT, CT, KT]):
L75: def __init__(
L90: def state(self) -> State[RT, CT, KT]:
L96: def _push_new_state(self) -> None:
L110: def _add_to_criteria(
L154: def _remove_information_from_criteria(
L181: def _get_preference(self, name: KT) -> Preference:
L196: def _is_current_pin_satisfying(
L208: def _get_updated_criteria(self, candidate: CT) -> dict[KT, Criterion[RT, CT]]:
L214: def _attempt_to_pin_criterion(self, name: KT) -> list[Criterion[RT, CT]]:
L251: def _patch_criteria(
L286: def _save_state(self) -> None:
L298: def _rollback_states(self) -> None:
L305: def _backjump(self, causes: list[RequirementInformation[RT, CT]]) -> bool:
L412: def _extract_causes(
L418: def resolve(self, requirements: Iterable[RT], max_rounds: int) -> State[RT, CT, KT]:
L563: class Resolver(AbstractResolver[RT, CT, KT]):
L568: def resolve( # type: ignore[override]
L605: def _has_route_to_root(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/exceptions.py

```

L11: class ResolverException(Exception):
L19: class RequirementsConflicted(ResolverException, Generic[RT, CT]):
L20: def __init__(self, criterion: Criterion[RT, CT]) -> None:
L24: def __str__(self) -> str:
L30: class InconsistentCandidate(ResolverException, Generic[RT, CT]):
L31: def __init__(self, candidate: CT, criterion: Criterion[RT, CT]):
L36: def __str__(self) -> str:
L43: class ResolutionError(ResolverException):
L47: class ResolutionImpossible(ResolutionError, Generic[RT, CT]):
L48: def __init__(self, causes: Collection[RequirementInformation[RT, CT]]):
L54: class ResolutionTooDeep(ResolutionError):
L55: def __init__(self, round_count: int) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/abstract.py

```
L13: class Result(NamedTuple, Generic[RT, CT, KT]):
L22: class AbstractResolver(Generic[RT, CT, KT]):
L27: def __init__(
L35: def resolve(self, requirements: Iterable[RT], **kwargs: Any) -> Result[RT, CT, KT]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/criterion.py

```
L8: class Criterion(Generic[RT, CT]):
L28: def __init__(
L38: def __repr__(self) -> str:
L44: def iter_requirement(self) -> Iterator[RT]:
L47: def iter_parent(self) -> Iterator[CT | None]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/compat.py

```
L6: def ToASCII(label: str) -> bytes:
L10: def ToUnicode(label: Union[bytes, bytearray]) -> str:
L14: def nameprep(s: Any) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/core.py

```
L14: class IDNAError(UnicodeError):
L20: class IDNABidiError(IDNAError):
L26: class InvalidCodepoint(IDNAError):
L32: class InvalidCodepointContext(IDNAError):
L38: def _combining_class(cp: int) -> int:
L46: def _is_script(cp: str, script: str) -> bool:
L50: def _punycode(s: str) -> bytes:
L54: def _unot(s: int) -> str:
L58: def valid_label_length(label: Union[bytes, str]) -> bool:
L64: def valid_string_length(label: Union[bytes, str], trailing_dot: bool) -> bool:
L70: def check_bidi(label: str, check_ltr: bool = False) -> bool:
L140: def check_initial_combiner(label: str) -> bool:
```

```

L146: def check_hyphen_ok(label: str) -> bool:
L154: def check_nfc(label: str) -> None:
L159: def valid_contextj(label: str, pos: int) -> bool:
L203: def valid_contexto(label: str, pos: int, exception: bool = False) -> bool:
L245: def check_label(label: Union[str, bytes, bytearray]) -> None:
L284: def alabel(label: str) -> bytes:
L303: def ulabel(label: Union[str, bytes, bytearray]) -> str:
L332: def uts46_remap(domain: str, std3_rules: bool = True, transitional: bool = False) ->
str:
L366: def encode(
L405: def decode(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/codec.py

```

L10: class Codec(codecs.Codec):
L11: def encode(self, data: str, errors: str = "strict") -> Tuple[bytes, int]:
L20: def decode(self, data: bytes, errors: str = "strict") -> Tuple[str, int]:
L30: class IncrementalEncoder(codecs.BufferedIncrementalEncoder):
L31: def _buffer_encode(self, data: str, errors: str, final: bool) -> Tuple[bytes, int]:
L64: class IncrementalDecoder(codecs.BufferedIncrementalDecoder):
L65: def _buffer_decode(self, data: Any, errors: str, final: bool) -> Tuple[str, int]:
L100: class StreamWriter(Codec, codecs.StreamWriter):
L104: class StreamReader(Codec, codecs.StreamReader):
L108: def search_function(name: str) -> Optional[codecs.CodecInfo]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/intranges.py

```

L12: def intranges_from_list(list_: List[int]) -> Tuple[int, ...]:
L34: def _encode_range(start: int, end: int) -> int:
L38: def _decode_range(r: int) -> Tuple[int, int]:
L42: def intranges_contain(int_: int, ranges: Tuple[int, ...]) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/uts46data.py

```

L12: def _seg_0() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L117: def _seg_1() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L222: def _seg_2() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L327: def _seg_3() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L432: def _seg_4() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:

```



```

L537: def _seg_5() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L642: def _seg_6() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L747: def _seg_7() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L852: def _seg_8() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L957: def _seg_9() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1062: def _seg_10() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1167: def _seg_11() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1272: def _seg_12() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1377: def _seg_13() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1482: def _seg_14() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1587: def _seg_15() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1692: def _seg_16() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1797: def _seg_17() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1902: def _seg_18() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2007: def _seg_19() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2112: def _seg_20() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2217: def _seg_21() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2322: def _seg_22() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2427: def _seg_23() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2532: def _seg_24() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2637: def _seg_25() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2742: def _seg_26() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2847: def _seg_27() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2952: def _seg_28() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3057: def _seg_29() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3162: def _seg_30() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3267: def _seg_31() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3372: def _seg_32() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3477: def _seg_33() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3582: def _seg_34() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3687: def _seg_35() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3792: def _seg_36() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3897: def _seg_37() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4002: def _seg_38() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4107: def _seg_39() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4212: def _seg_40() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4317: def _seg_41() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4422: def _seg_42() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4527: def _seg_43() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4632: def _seg_44() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4737: def _seg_45() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4842: def _seg_46() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4947: def _seg_47() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5052: def _seg_48() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5157: def _seg_49() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5262: def _seg_50() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5367: def _seg_51() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5472: def _seg_52() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5577: def _seg_53() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5682: def _seg_54() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5787: def _seg_55() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:

```

```

L5892: def _seg_56() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5997: def _seg_57() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6102: def _seg_58() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6207: def _seg_59() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6312: def _seg_60() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6417: def _seg_61() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6522: def _seg_62() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6627: def _seg_63() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6732: def _seg_64() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6837: def _seg_65() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6942: def _seg_66() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7047: def _seg_67() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7152: def _seg_68() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7257: def _seg_69() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7362: def _seg_70() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7467: def _seg_71() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7572: def _seg_72() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7677: def _seg_73() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7782: def _seg_74() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7887: def _seg_75() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7992: def _seg_76() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8097: def _seg_77() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8202: def _seg_78() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8307: def _seg_79() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8412: def _seg_80() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8517: def _seg_81() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8622: def _seg_82() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8727: def _seg_83() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_elf
file.py**

```

L18: class ELFInvalid(ValueError):
L22: class EIClass(enum.IntEnum):
L27: class EIData(enum.IntEnum):
L32: class EMachine(enum.IntEnum):
L40: class ELFFile:
L45: def __init__(self, f: IO[bytes]) -> None:
L90: def _read(self, fmt: str) -> tuple[int, ...]:
L94: def interpreter(self) -> str | None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_m
anylinux.py**

```

L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:
L40: def _is_linux_armhf(executable: str) -> bool:
L55: def _is_linux_i686(executable: str) -> bool:
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:
L81: class _GLibCVersion(NamedTuple):
L86: def _glibc_version_string_confstr() -> str | None:
L105: def _glibc_version_string_ctypes() -> str | None:
L149: def _glibc_version_string() -> str | None:
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:
L174: def _get_glibc_version() -> _GLibCVersion:
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/dir
ect_url.py**

```

L27: def __dir__() -> list[str]:
L34: class _FromMappingProtocol(Protocol): # pragma: no cover
L36: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L42: def _json_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L46: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L59: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
L66: def _get_object(
L83: def _strip_auth_from_netloc(netloc: str, safe_user_passwords: Collection[str]) -> str:
L94: def _strip_url(url: str, safe_user_passwords: Collection[str]) -> str:
L112: class DirectUrlValidationError(Exception):
L118: def __init__(
L136: def __str__(self) -> str:
L142: class _DirectUrlRequiredKeyError(DirectUrlValidationError):
L143: def __init__(self, key: str) -> None:
L148: class VcsInfo:
L153: def __init__(
L165: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L175: class ArchiveInfo:
L178: def __init__(
L186: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L221: class DirInfo:
L224: def __init__(
L232: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L239: class DirectUrl:
L248: def __init__(
L264: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L289: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L293: def to_dict(
L320: def validate(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/metadata.py

```

L40: def __dir__() -> list[str]:
L44: class InvalidMetadata(ValueError):
L50: def __init__(self, field: str, message: str) -> None:
L59: class RawMetadata(TypedDict, total=False):
L178: def _parse_keywords(data: str) -> list[str]:
L183: def _parse_project_urls(data: list[str]) -> dict[str, str]:
L222: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:
L291: class RFC822Policy(email.policy.EmailPolicy):
L301: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:
L308: class RFC822Message(email.message.EmailMessage):
L315: def __init__(self) -> None:
L318: def as_bytes(
L329: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
L520: class _Validator(Generic[T]):
L534: def __init__(
L541: def __set_name__(self, _owner: Metadata, name: str) -> None:
L545: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:
L572: def _invalid_metadata(
L581: def _process_metadata_version(self, value: str) -> _MetadataVersion:
L587: def _process_name(self, value: str) -> str:
L600: def _process_version(self, value: str) -> version_module.Version:
L610: def _process_summary(self, value: str) -> str:
L616: def _process_description_content_type(self, value: str) -> str:
L648: def _process_dynamic(self, value: list[str]) -> list[str]:
L660: def _process_provides_extra(
L675: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:
L683: def _process_requires_dist(
L698: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
L706: def _process_license_files(self, value: list[str]) -> list[str]:
L732: def _process_import_names(self, value: list[str]) -> list[str]:
L757: class Metadata:
L769: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata:
L823: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
L932: def as_rfc822(self) -> RFC822Message:
L940: def _write_metadata(self, message: RFC822Message) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/markers.py

```

L30: def __dir__() -> list[str]:
L54: class InvalidMarker(ValueError):

```

```

L62: class UndefinedComparison(ValueError):
L71: class UndefinedEnvironmentName(ValueError):
L75: class Environment(TypedDict):
L152: def _normalize_extras(
L168: def _normalize_extra_values(results: MarkerList) -> MarkerList:
L176: def _format_marker(
L216: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
L233: def _normalize(
L254: def _evaluate_markers(
L287: def _format_full_version(info: sys._version_info) -> str:
L295: def default_environment() -> Environment:
L317: class Marker:
L339: def __init__(self, marker: str) -> None:
L370: def _from_markers(cls, markers: MarkerList) -> Marker:
L379: def __str__(self) -> str:
L382: def __repr__(self) -> str:
L385: def __hash__(self) -> int:
L388: def __eq__(self, other: object) -> bool:
L394: def __getstate__(self) -> str:
L399: def __setstate__(self, state: object) -> None:
L423: def __and__(self, other: Marker) -> Marker:
L428: def __or__(self, other: Marker) -> Marker:
L433: def evaluate(
L482: def _repair_python_full_version(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/specifiers.py

```

L48: def __dir__() -> list[str]:
L52: def _validate_spec(spec: object, /) -> TypeGuard[tuple[str, str]]:
L61: def _validate_pre(pre: object, /) -> TypeGuard[bool | None]:
L74: def _trim_release(release: tuple[int, ...]) -> tuple[int, ...]:
L82: class _BoundaryKind(enum.Enum):
L90: class _BoundaryVersion:
L113: def __init__(self, version: Version, kind: _BoundaryKind) -> None:
L118: def _is_family(self, other: Version) -> bool:
L133: def __eq__(self, other: object) -> bool:
L138: def __lt__(self, other: _BoundaryVersion | Version) -> bool:
L145: def __hash__(self) -> int:
L148: def __repr__(self) -> str:
L153: class _LowerBound:
L163: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:
L167: def __eq__(self, other: object) -> bool:
L172: def __lt__(self, other: _LowerBound) -> bool:
L185: def __hash__(self) -> int:
L188: def __repr__(self) -> str:
L194: class _UpperBound:

```

```

L204: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:
L208: def __eq__(self, other: object) -> bool:
L213: def __lt__(self, other: _UpperBound) -> bool:
L226: def __hash__(self) -> int:
L229: def __repr__(self) -> str:
L246: def _range_is_empty(lower: _LowerBound, upper: _UpperBound) -> bool:
L255: def _intersect_ranges(
L281: def _next_prefix_dev0(version: Version) -> Version:
L287: def _base_dev0(version: Version) -> Version:
L292: def _coerce_version(version: UnparsedVersion) -> Version | None:
L301: def _public_version(version: Version) -> Version:
L307: def _post_base(version: Version) -> Version:
L315: def _earliest_prerelease(version: Version) -> Version:
L323: def _nearest_non_prerelease(
L344: class InvalidSpecifier(ValueError):
L356: class BaseSpecifier(metaclass=abc.ABCMeta):
L361: def _str(self) -> str:
L366: def __str__(self) -> str:
L373: def __hash__(self) -> int:
L379: def __eq__(self, other: object) -> bool:
L389: def prereleases(self) -> bool | None:
L397: def prereleases(self, value: bool) -> None:
L404: def contains(self, item: str, prereleases: bool | None = None) -> bool:
L410: def filter(
L418: def filter(
L426: def filter(
L438: class Specifier(BaseSpecifier):
L573: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:
L611: def _get_spec_version(self, version: str) -> Version | None:
L623: def _require_spec_version(self, version: str) -> Version:
L633: def _to_ranges(self) -> Sequence[_VersionRange]:
L657: def _wildcard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:
L670: def _standard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:
L733: def prereleases(self) -> bool | None:
L761: def prereleases(self, value: bool | None) -> None:
L764: def __getstate__(self) -> tuple[tuple[str, str], bool | None]:
L770: def __setstate__(self, state: object) -> None:
L805: def operator(self) -> str:
L814: def version(self) -> str:
L822: def __repr__(self) -> str:
L840: def __str__(self) -> str:
L851: def _canonical_spec(self) -> tuple[str, str]:
L864: def __hash__(self) -> int:
L867: def __eq__(self, other: object) -> bool:
L896: def _get_operator(self, op: str) -> CallableOperator:
L902: def _compare_compatible(self, prospective: Version, spec: str) -> bool:
L922: def _get_wildcard_split(self, spec: str) -> tuple[list[str], int]:
L938: def _compare_equal(self, prospective: Version, spec: str) -> bool:
L974: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:
L977: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:
L983: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:

```

```

L989: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:
L1014: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
L1046: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
L1049: def __contains__(self, item: str | Version) -> bool:
L1070: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
L1098: def filter(
L1106: def filter(
L1113: def filter(
L1198: def _pep440_filter_prereleases(
L1240: def _version_split(version: str) -> list[str]:
L1262: def _version_join(components: list[str]) -> str:
L1273: def _is_not_suffix(segment: str) -> bool:
L1279: def _numeric_prefix_len(split: list[str]) -> int:
L1293: def _left_pad(split: list[str], target_numeric_len: int) -> list[str]:
L1307: def _operator_cost(op_entry: tuple[CallableOperator, str, str]) -> int:
L1334: class SpecifierSet(BaseSpecifier):
L1362: def __init__(
L1407: def _canonical_specs(self) -> tuple[Specifier, ...]:
L1417: def prereleases(self) -> bool | None:
L1437: def prereleases(self, value: bool | None) -> None:
L1441: def __getstate__(self) -> tuple[tuple[Specifier, ...], bool | None]:
L1447: def __setstate__(self, state: object) -> None:
L1504: def __repr__(self) -> str:
L1525: def __str__(self) -> str:
L1538: def __hash__(self) -> int:
L1541: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:
L1574: def __eq__(self, other: object) -> bool:
L1600: def __len__(self) -> int:
L1604: def __iter__(self) -> Iterator[Specifier]:
L1614: def _get_ranges(self) -> Sequence[_VersionRange]:
L1636: def is_unsatisfiable(self) -> bool:
L1669: def _check_prerelease_only_ranges(self) -> bool:
L1682: def _check_arbitrary_unsatisfiable(self) -> bool:
L1721: def __contains__(self, item: UnparsedVersion) -> bool:
L1742: def contains(
L1788: def filter(
L1796: def filter(
L1803: def filter(
L1899: def _filter_versions(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/de
pendency_groups.py**

```

L19: def __dir__() -> list[str]:
L28: class DuplicateGroupNames(ValueError):
L34: class CyclicDependencyGroup(ValueError):
L39: def __init__(self, requested_group: str, group: str, include_group: str) -> None:

```

```

L57: class InvalidDependencyGroupObject(ValueError):
L69: class DependencyGroupInclude:
L72: def __init__(self, include_group: str) -> None:
L80: def __repr__(self) -> str:
L84: class DependencyGroupResolver:
L96: def __init__(
L115: def lookup(self, group: str) -> tuple[Requirement | DependencyGroupInclude, ...]:
L129: def resolve(self, group: str) -> tuple[Requirement, ...]:
L142: def _resolve(
L200: def _parse_group(
L255: def resolve_dependency_groups(
L277: def _normalize_name(name: str) -> str:
L281: def _normalize_group_names(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_to_kenizer.py

```

L12: class Token:
L18: class ParserSyntaxError(Exception):
L21: def __init__(
L34: def __str__(self) -> str:
L91: class Tokenizer:
L98: def __init__(
L109: def consume(self, name: str) -> None:
L114: def check(self, name: str, *, peek: bool = False) -> bool:
L135: def expect(self, name: str, *, expected: str) -> Token:
L144: def read(self) -> Token:
L154: def raise_syntax_error(
L173: def enclosing_tokens(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_parser.py

```

L15: class Node:
L18: def __init__(self, value: str) -> None:
L21: def __str__(self) -> str:
L24: def __repr__(self) -> str:
L27: def serialize(self) -> str:
L30: def __getstate__(self) -> str:
L34: def _restore_value(self, value: object) -> None:
L41: def __setstate__(self, state: object) -> None:
L59: class Variable(Node):
L62: def serialize(self) -> str:
L66: class Value(Node):

```



```

L69: def serialize(self) -> str:
L73: class Op(Node):
L76: def serialize(self) -> str:
L87: class ParsedRequirement(NamedTuple):
L98: def parse_requirement(source: str) -> ParsedRequirement:
L102: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:
L123: def _parse_requirement_details(
L176: def _parse_requirement_marker(
L197: def _parse_extras(tokenizer: Tokenizer) -> list[str]:
L216: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:
L243: def _parse_specifier(tokenizer: Tokenizer) -> str:
L260: def _parse_version_many(tokenizer: Tokenizer) -> str:
L292: def parse_marker(source: str) -> MarkerList:
L296: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:
L302: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:
L314: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:
L336: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:
L350: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar: # noqa: RET503
L364: def process_env_var(env_var: str) -> Variable:
L371: def process_python_str(python_str: str) -> Value:
L376: def _parse_marker_op(tokenizer: Tokenizer) -> Op:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/util
s.py**

```

L27: def __dir__() -> list[str]:
L39: class InvalidName(ValueError):
L45: class InvalidWheelFilename(ValueError):
L51: class InvalidSdistFilename(ValueError):
L66: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
L103: def is_normalized_name(name: str) -> bool:
L119: def canonicalize_version(
L157: def parse_wheel_filename(
L249: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/ver
sion.py**

```

L37: def _deprecated(message: str) -> object:
L38: def decorator(func: Callable[[...], object]) -> object:
L40: def wrapper(*args: object, **kwargs: object) -> object:
L66: def __dir__() -> list[str]:
L81: class _VersionReplace(TypedDict, total=False):
L90: def normalize_pre(letter: str, /) -> str:

```

```

L111: def parse(version: str) -> Version:
L125: class InvalidVersion(ValueError):
L135: class _BaseVersion:
L144: def __key__(self) -> tuple[Any, ...]: ...
L146: def __hash__(self) -> int:
L152: def __lt__(self, other: _BaseVersion) -> bool:
L158: def __le__(self, other: _BaseVersion) -> bool:
L164: def __eq__(self, other: object) -> bool:
L170: def __ge__(self, other: _BaseVersion) -> bool:
L176: def __gt__(self, other: _BaseVersion) -> bool:
L182: def __ne__(self, other: object) -> bool:
L266: def _validate_epoch(value: object, /) -> int:
L274: def _validate_release(value: object, /) -> tuple[int, ...]:
L286: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
L299: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:
L308: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:
L317: def _validate_local(value: object, /) -> LocalType | None:
L327: class _Version(NamedTuple):
L336: class Version(_BaseVersion):
L404: def __init__(self, version: str) -> None:
L455: def from_parts(
L501: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:
L560: def __key__(self) -> CmpKey:
L574: def __hash__(self) -> int:
L592: def __lt__(self, other: _BaseVersion) -> bool:
L619: def __le__(self, other: _BaseVersion) -> bool:
L646: def __eq__(self, other: object) -> bool:
L673: def __ge__(self, other: _BaseVersion) -> bool:
L700: def __gt__(self, other: _BaseVersion) -> bool:
L727: def __ne__(self, other: object) -> bool:
L754: def __getstate__(
L776: def __setstate__(self, state: object) -> None:
L823: def _version(self) -> _Version:
L830: def _version(self, value: _Version) -> None:
L840: def __repr__(self) -> str:
L848: def __str__(self) -> str:
L880: def _str(self) -> str:
L885: def epoch(self) -> int:
L896: def release(self) -> tuple[int, ...]:
L912: def pre(self) -> tuple[Literal["a", "b", "rc"], int] | None:
L927: def post(self) -> int | None:
L938: def dev(self) -> int | None:
L949: def local(self) -> str | None:
L963: def public(self) -> str:
L979: def base_version(self) -> str:
L1000: def is_prerelease(self) -> bool:
L1017: def is_postrelease(self) -> bool:
L1028: def is_devrelease(self) -> bool:
L1039: def major(self) -> int:
L1048: def minor(self) -> int:
L1059: def micro(self) -> int:

```

```

L1070: class _TrimmedRelease(Version):
L1073: def __init__(self, version: str | Version) -> None:
L1086: def release(self) -> tuple[int, ...]:
L1104: def _parse_letter_version(
L1131: def _parse_local_version(local: str | None) -> LocalType | None:
L1157: def _cmpkey(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_structures.py

```

L18: class InfinityType:
L21: def __repr__(self) -> str:
L25: class NegativeInfinityType:
L28: def __repr__(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/tag.py

```

L54: def __dir__() -> list[str]:
L75: def _compute_32_bit_interpreter() -> bool:
L82: class UnsortedTagsError(ValueError):
L88: class Tag:
L108: def __init__(self, interpreter: str, abi: str, platform: str) -> None:
L128: def interpreter(self) -> str:
L137: def abi(self) -> str:
L144: def platform(self) -> str:
L150: def __eq__(self, other: object) -> bool:
L161: def __hash__(self) -> int:
L164: def __str__(self) -> str:
L167: def __repr__(self) -> str:
L170: def __getstate__(self) -> tuple[str, str, str]:
L175: def __setstate__(self, state: object) -> None:
L203: def parse_tag(tag: str, *, validate_order: bool = False) -> frozenset[Tag]:
L240: def _get_config_var(name: str, warn: bool = False) -> int | str | None:
L249: def _normalize_string(string: str) -> str:
L253: def _is_threaded_cpython(abis: list[str]) -> bool:
L269: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:
L279: def _abi3t_applies(python_version: PythonVersion, threading: bool) -> bool:
L292: def _cpython_abi(py_version: PythonVersion, warn: bool = False) -> list[str]:
L325: def cpython_tags(
L404: def _generic_abi() -> list[str]:
L445: def generic_tags(
L486: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:
L501: def compatible_tags(

```

```

L536: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:
L546: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:
L578: def mac_platforms(
L667: def ios_platforms(
L729: def android_platforms(
L766: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:
L785: def _emscripten_platforms() -> Iterator[str]:
L794: def _generic_platforms() -> Iterator[str]:
L798: def platform_tags() -> Iterator[str]:
L816: def interpreter_name() -> str:
L829: def interpreter_version(*, warn: bool = False) -> str:
L841: def _version_nodot(version: PythonVersion) -> str:
L845: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:
L889: def create_compatible_tags_selector(
L919: def selector(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/err
ors.py**

```

L11: def __dir__() -> list[str]:
L19: class ExceptionGroup(Exception):
L29: def __init__(self, message: str, exceptions: list[Exception]) -> None:
L33: def __repr__(self) -> str:
L38: class _ErrorCollector:
L59: def finalize(self, msg: str) -> None:
L65: def on_exit(self, msg: str) -> typing.Generator[_ErrorCollector, None, None]:
L75: def collect(self, *err_cls: type[Exception]) -> typing.Generator[None, None, None]:
L89: def error(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_m
usllinux.py**

```

L18: class _MuslVersion(NamedTuple):
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/req
uirements.py**

```

L20: def __dir__() -> list[str]:
L24: class InvalidRequirement(ValueError):
L30: class Requirement:
L53: def __init__(self, requirement_string: str) -> None:
L68: def _iter_parts(self, name: str) -> Iterator[str]:
L86: def __getstate__(self) -> str:
L91: def __setstate__(self, state: object) -> None:
L110: def __str__(self) -> str:
L113: def __repr__(self) -> str:
L116: def __hash__(self) -> int:
L119: def __eq__(self, other: object) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/pylock.py

```

L54: def __dir__() -> list[str]:
L62: class _FromMappingProtocol(Protocol): # pragma: no cover
L64: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L73: def is_valid_pylock_path(path: Path) -> bool:
L78: def _toml_key(key: str) -> str:
L82: def _toml_value(key: str, value: Any) -> Any: # noqa: ANN401
L90: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L98: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L111: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
L118: def _get_sequence(
L140: def _get_as(
L159: def _get_required_as(
L172: def _get_sequence_as(
L191: def _get_object(
L203: def _get_sequence_of_objects(
L219: def _get_required_sequence_of_objects(
L229: def _validate_normalized_name(name: str) -> NormalizedName:
L236: def _validate_path_url(path: str | None, url: str | None) -> None:
L241: def _path_name(path: str | None) -> str | None:
L254: def _url_name(url: str | None) -> str | None:
L261: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:
L269: class PylockValidationError(Exception):
L275: def __init__(
L293: def __str__(self) -> str:
L299: class _PylockRequiredKeyError(PylockValidationError):
L300: def __init__(self, key: str) -> None:
L304: class PylockUnsupportedVersionError(PylockValidationError):
L308: class PylockSelectError(Exception):
L313: class PackageVcs:
L321: def __init__(
L340: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L354: class PackageDirectory:

```

```

L359: def __init__(
L372: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L381: class PackageArchive:
L389: def __init__(
L408: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L422: class PackageSdist:
L430: def __init__(
L449: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L462: def filename(self) -> str:
L471: class PackageWheel:
L479: def __init__(
L498: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L511: def filename(self) -> str:
L520: class Package:
L535: def __init__(
L568: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L649: def is_direct(self) -> bool:
L654: class Pylock:
L667: def __init__(
L692: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L715: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L723: def to_dict(self) -> Mapping[str, Any]:
L727: def validate(self) -> None:
L733: def select(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):
L10: class SPDXException(TypedDict):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/__init__.py

```

L47: def __dir__() -> list[str]:
L60: class InvalidLicenseExpression(ValueError):
L71: def canonicalize_license_expression(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_impl.py

```

L16: class SubprocessRunner(Protocol):
L19: def __call__(
L28: def write_json(obj: Mapping[str, Any], path: str, **kwargs) -> None:
L33: def read_json(path: str) -> Mapping[str, Any]:
L38: class BackendUnavailable(Exception):
L41: def __init__(
L55: class HookMissing(Exception):
L58: def __init__(self, hook_name: str) -> None:
L63: class UnsupportedOperation(Exception):
L66: def __init__(self, traceback: str) -> None:
L70: def default_subprocess_runner(
L86: def quiet_subprocess_runner(
L102: def norm_and_check(source_tree: str, requested: str) -> str:
L126: class BuildBackendHookCaller:
L129: def __init__(
L159: def subprocess_runner(self, runner: "SubprocessRunner") -> Iterator[None]:
L178: def _supported_features(self) -> Sequence[str]:
L182: def get_requires_for_build_wheel(
L200: def prepare_metadata_for_build_wheel(
L233: def build_wheel(
L265: def get_requires_for_build_editable(
L283: def prepare_metadata_for_build_editable(
L315: def build_editable(
L348: def get_requires_for_build_sdist(
L360: def build_sdist(
L378: def _call_hook(self, hook_name: str, kwargs: Mapping[str, Any]) -> Any:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/_in_process.py

```

L31: def write_json(obj, path, **kwargs):
L36: def read_json(path):
L41: class BackendUnavailable(Exception):
L44: def __init__(self, message, traceback=None):
L50: class HookMissing(Exception):
L53: def __init__(self, hook_name=None):
L58: def _build_backend():
L81: class _BackendPathFinder:
L89: def __init__(self, backend_path, backend_module):
L94: def find_spec(self, fullname, _path, _target=None):
L111: def find_distributions(self, context=None):
L119: def _supported_features():
L132: def get_requires_for_build_wheel(config_settings):
L146: def get_requires_for_build_editable(config_settings):
L160: def prepare_metadata_for_build_wheel(
L184: def prepare_metadata_for_build_editable(
L215: def _dist_info_files(whl_zip):

```

```

L227: def _get_wheel_metadata_from_wheel(whl_basename, metadata_directory, config_settings):
L245: def _find_already_built_wheel(metadata_directory):
L268: def build_wheel(wheel_directory, config_settings, metadata_directory=None):
L285: def build_editable(wheel_directory, config_settings, metadata_directory=None):
L306: def get_requires_for_build_sdist(config_settings):
L320: class _DummyException(Exception):
L324: class GotUnsupportedOperation(Exception):
L327: def __init__(self, traceback):
L331: def build_sdist(sdist_directory, config_settings):
L353: def main():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/__init__.py

```

L13: def _in_proc_script_path():
L18: def _in_proc_script_path():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_ssl_constants.py

```

L28: def _set_ssl_context_verify_mode(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_windows.py

```

L39: class CERT_CONTEXT(Structure):
L53: class CERT_ENHKEY_USAGE(Structure):
L63: class CERT_USAGE_MATCH(Structure):
L70: class CERT_CHAIN_PARA(Structure):
L90: class CERT_TRUST_STATUS(Structure):
L97: class CERT_CHAIN_ELEMENT(Structure):
L112: class CERT_SIMPLE_CHAIN(Structure):
L127: class CERT_CHAIN_CONTEXT(Structure):
L144: class SSL_EXTRA_CERT_CHAIN_POLICY_PARA(Structure):
L153: class CERT_CHAIN_POLICY_PARA(Structure):
L164: class CERT_CHAIN_POLICY_STATUS(Structure):
L177: class CERT_CHAIN_ENGINE_CONFIG(Structure):
L238: def _handle_win_error(result: bool, _: Any, args: Any) -> Any:
L323: def _verify_peercerts_impl(
L415: def _get_and_verify_cert_chain(

```



```
L505: def _verify_using_custom_ca_certs(
L558: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_api.py

```
L34: def inject_into_ssl() -> None:
L66: def extract_from_ssl() -> None:
L77: class SSLContext(_truststore_SSLContext_super_class): # type: ignore[misc]
L81: def __class__(self) -> type:
L87: def __init__(self, protocol: int = None) -> None: # type: ignore[assignment]
L91: class TruststoreSSLObject(ssl.SSLObject):
L96: def do_handshake(self) -> None:
L103: def wrap_socket(
L136: def wrap_bio(
L154: def load_verify_locations(
L164: def load_cert_chain(
L174: def load_default_certs(
L179: def set_alpn_protocols(self, alpn_protocols: typing.Iterable[str]) -> None:
L182: def set_npn_protocols(self, npn_protocols: typing.Iterable[str]) -> None:
L185: def set_ciphers(self, __cipherlist: str) -> None:
L188: def get_ciphers(self) -> typing.Any:
L191: def session_stats(self) -> dict[str, int]:
L194: def cert_store_stats(self) -> dict[str, int]:
L197: def set_default_verify_paths(self) -> None:
L201: def get_ca_certs(
L206: def get_ca_certs(self, binary_form: typing.Literal[True] = ...) -> list[bytes]: ...
L209: def get_ca_certs(self, binary_form: bool = ...) -> typing.Any: ...
L211: def get_ca_certs(self, binary_form: bool = False) -> list[typing.Any] | list[bytes]:
L215: def check_hostname(self) -> bool:
L219: def check_hostname(self, value: bool) -> None:
L223: def hostname_checks_common_name(self) -> bool:
L227: def hostname_checks_common_name(self, value: bool) -> None:
L231: def keylog_filename(self) -> str:
L235: def keylog_filename(self, value: str) -> None:
L239: def maximum_version(self) -> ssl.TLSVersion:
L243: def maximum_version(self, value: ssl.TLSVersion) -> None:
L249: def minimum_version(self) -> ssl.TLSVersion:
L253: def minimum_version(self, value: ssl.TLSVersion) -> None:
L259: def options(self) -> ssl.Options:
L263: def options(self, value: ssl.Options) -> None:
L269: def post_handshake_auth(self) -> bool:
L273: def post_handshake_auth(self, value: bool) -> None:
L277: def protocol(self) -> ssl._SSLMethod:
L281: def security_level(self) -> int:
L285: def verify_flags(self) -> ssl.VerifyFlags:
L289: def verify_flags(self, value: ssl.VerifyFlags) -> None:
```

```

L295: def verify_mode(self) -> ssl.VerifyMode:
L299: def verify_mode(self, value: ssl.VerifyMode) -> None:
L310: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:
L319: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:
L324: def _verify_peer certs(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_openssl.py

```

L25: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:
L51: def _capath_contains_certs(capath: str) -> bool:
L61: def _verify_peer certs_impl(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_macos.py

```

L31: def _load_cdll(name: str, macos10_16_path: str) -> CDLL:
L223: def _handle_osstatus(result: OSStatus, _: typing.Any, args: typing.Any) -> typing.Any:
L283: class CFConst:
L294: def _bytes_to_cf_data_ref(value: bytes) -> CFDataRef: # type: ignore[valid-type]
L300: def _bytes_to_cf_string(value: bytes) -> CFString:
L314: def _cf_string_ref_to_str(cf_string_ref: CFStringRef) -> str | None: # type:
ignore[valid-type]
L337: def _der_certs_to_cf_cert_array(certs: list[bytes]) -> CFMutableArrayRef: # type:
ignore[valid-type]
L368: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:
L380: def _verify_peer certs_impl(
L469: def _verify_peer certs_impl_macos_10_13(
L513: def _verify_peer certs_impl_macos_10_14(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/certifi/core.py

```

L10: def exit_cacert_ctx() -> None:
L21: def where() -> str:
L46: def contents() -> str:
L56: def where() -> str:
L82: def contents() -> str:

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pip/_vendor/pygments/console.py

```
L40: def reset_color():
L44: def colorize(color_key, text):
L48: def ansiformat(attr, text):
```

Q_base

appwrite/venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexer.py

```
L37: class LexerMeta(type):
L43: def __new__(mcs, name, bases, d):
L49: class Lexer(metaclass=LexerMeta):
L145: def __init__(self, **options):
L156: def __init__(self, **options):
L175: def __repr__(self):
L181: def add_filter(self, filter_, **options):
L189: def analyse_text(text):
L206: def _preprocess_lexer_input(self, text):
L255: def get_tokens(self, text, unfiltered=False):
L271: def streamer():
L279: def get_tokens_unprocessed(self, text):
L291: class DelegatingLexer(Lexer):
L301: def __init__(self, _root_lexer, _language_lexer, _needle=Other, **options):
L307: def get_tokens_unprocessed(self, text):
L330: class include(str): # pylint: disable=invalid-name
L337: class _inherit:
L341: def __repr__(self):
L347: class combined(tuple): # pylint: disable=invalid-name
L352: def __new__(cls, *args):
L355: def __init__(self, *args):
L360: class _PseudoMatch:
L365: def __init__(self, start, text):
L369: def start(self, arg=None):
L372: def end(self, arg=None):
L375: def group(self, arg=None):
L380: def groups(self):
L383: def groupdict(self):
L387: def bygroups(*args):
L391: def callback(lexer, match, ctx=None):
L413: class _This:
L422: def using(_other, **kwargs):
L444: def callback(lexer, match, ctx=None):
L459: def callback(lexer, match, ctx=None):
L472: class default:
L480: def __init__(self, state):
```

```

L484: class words(Future):
L491: def __init__(self, words, prefix='', suffix=''):
L496: def get(self):
L500: class RegexLexerMeta(LexerMeta):
L506: def _process_regex(cls, regex, rflags, state):
L512: def _process_token(cls, token):
L518: def _process_new_state(cls, new_state, unprocessed, processed):
L553: def _process_state(cls, unprocessed, processed, state):
L596: def process_tokendef(cls, name, tokendefs=None):
L604: def get_tokendefs(cls):
L653: def __call__(cls, *args, **kws):
L667: class RegexLexer(Lexer, metaclass=RegexLexerMeta):
L702: def get_tokens_unprocessed(self, text, stack=('root',)):
L764: class LexerContext:
L769: def __init__(self, text, pos, stack=None, end=None):
L775: def __repr__(self):
L779: class ExtendedRegexLexer(RegexLexer):
L784: def get_tokens_unprocessed(self, text=None, context=None):
L851: def do_insertions(insertions, tokens):
L915: class ProfilingRegexLexerMeta(RegexLexerMeta):
L918: def _process_regex(cls, regex, rflags, state):
L926: def match_func(text, pos, endpos=sys.maxsize):
L937: class ProfilingRegexLexer(RegexLexer, metaclass=ProfilingRegexLexerMeta):
L943: def get_tokens_unprocessed(self, text, stack=('root',)):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/reg
exopt.py**

```

L22: def make_charset(letters):
L26: def regex_opt_inner(strings, open_paren):
L82: def regex_opt(strings, prefix='', suffix=''):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/tok
en.py**

```

L12: class _TokenType(tuple):
L15: def split(self):
L24: def __init__(self, *args):
L28: def __contains__(self, val):
L34: def __getattr__(self, val):
L43: def __repr__(self):
L46: def __copy__(self):
L50: def __deepcopy__(self, memo):
L85: def is_token_subtype(ttype, other):

```

```
L94: def string_to_tokentype(s):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/mo
deline.py**

```
L22: def get_filetype_from_line(l): # noqa: E741
L28: def get_filetype_from_buffer(buf, max_lines=5):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/sph
inxext.py**

```
L60: class PygmentsDoc(Directive):
L71: def run(self):
L90: def document_lexers_overview(self):
L101: def format_link(name, url):
L121: def write_row(*columns):
L132: def write_seperator():
L150: def document_lexers(self):
L215: def document_formatters(self):
L233: def document_filters(self):
L246: def setup(app):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/_i
nit_.py**

```
L35: def lex(code, lexer):
L52: def format(tokens, formatter, outfile=None): # pylint: disable=redefined-builtin
L77: def highlight(code, lexer, formatter, outfile=None):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/uni
string.py**

```
L82: def combine(*args):
L86: def allexcept(*args):
L93: def _handle_runs(char_list): # pragma: no cover
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/style
e.py**

```
L58: class StyleMeta(type):
L60: def __new__(mcs, name, bases, dct):
L66: def colorformat(text):
L126: def style_for_token(cls, token):
L156: def list_styles(cls):
L159: def styles_token(cls, ttype):
L162: def __iter__(cls):
L166: def __len__(cls):
L170: class Style(metaclass=StyleMeta):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filte
r.py**

```
L12: def apply_filters(stream, filters, lexer=None):
L18: def _apply(filter_, stream):
L25: def simplefilter(f):
L30: def lowercase(self, lexer, stream, options):
L41: class Filter:
L47: def __init__(self, **options):
L50: def filter(self, lexer, stream):
L54: class FunctionFilter(Filter):
L63: def __init__(self, **options):
L68: def filter(self, lexer, stream):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/sca
nner.py**

```
L20: class EndOfText(RuntimeError):
L27: class Scanner:
L35: def __init__(self, text, flags=0):
L49: def eos(self):
L54: def check(self, pattern):
L66: def test(self, pattern):
L72: def scan(self, pattern):
L95: def get_char(self):
L99: def __repr__(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/util.py

```

L30: class ClassNotFound(ValueError):
L34: class OptionError(Exception):
L40: def get_choice_opt(options, optname, allowed, default=None, normcase=False):
L53: def get_bool_opt(options, optname, default=None):
L82: def get_int_opt(options, optname, default=None):
L94: def get_list_opt(options, optname, default=None):
L110: def docstring_headline(obj):
L122: def make_analysator(f):
L124: def text_analyse(text):
L139: def shebang_matches(text, regex):
L184: def doctype_matches(text, regex):
L197: def html_doctype_matches(text):
L205: def looks_like_xml(text):
L221: def surrogatepair(c):
L230: def format_lines(var_name, seq, raw=False, indent_level=0):
L249: def duplicates_removed(it, already_seen=()):
L265: class Future:
L271: def get(self):
L275: def guess_decode(text):
L296: def guess_decode_from_terminal(text, term):
L313: def terminal_encoding(term):
L321: class UnclosingTextIOWrapper(TextIOWrapper):
L323: def close(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatter.py

```

L19: def _lookup_style(style):
L25: class Formatter:
L83: def __init__(self, **options):
L99: def get_style_defs(self, arg=''):
L114: def format(self, tokensource, outfile):
L128: def __class_getitem__(cls, name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/plugin.py

```

L43: def iter_entry_points(group_name):

```

```

L55: def find_plugin_lexers():
L60: def find_plugin_formatters():
L65: def find_plugin_styles():
L70: def find_plugin_filters():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filters/__init__.py

```

L22: def find_filter_class(filtername):
L32: def get_filter_by_name(filtername, **options):
L45: def get_all_filters():
L52: def _replace_special(ttype, value, regex, specialttype,
L65: class CodeTagFilter(Filter):
L78: def __init__(self, **options):
L86: def filter(self, lexer, stream):
L97: class SymbolFilter(Filter):
L673: def __init__(self, **options):
L679: def filter(self, lexer, stream):
L687: class KeywordCaseFilter(Filter):
L701: def __init__(self, **options):
L707: def filter(self, lexer, stream):
L715: class NameHighlightFilter(Filter):
L739: def __init__(self, **options):
L748: def filter(self, lexer, stream):
L756: class ErrorToken(Exception):
L760: class RaiseOnErrorTokenFilter(Filter):
L772: def __init__(self, **options):
L782: def filter(self, lexer, stream):
L789: class VisibleWhitespaceFilter(Filter):
L819: def __init__(self, **options):
L836: def filter(self, lexer, stream):
L843: def replacefunc(wschar):
L868: class GobbleFilter(Filter):
L882: def __init__(self, **options):
L886: def gobble(self, value, left):
L892: def filter(self, lexer, stream):
L907: class TokenMergeFilter(Filter):
L913: def __init__(self, **options):
L916: def filter(self, lexer, stream):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/python.py

```

L25: class PythonLexer(RegexLexer):

```



```

L65: def innerstring_rules(ttype):
L85: def fstring_rules(ttype):
L408: def analyse_text(text):
L416: class Python2Lexer(RegexLexer):
L433: def innerstring_rules(ttype):
L635: def analyse_text(text):
L639: class _PythonConsoleLexerBase(RegexLexer):
L676: class PythonConsoleLexer(DelegatingLexer):
L706: def __init__(self, **options):
L719: class _ReplaceInnerCode(DelegatingLexer):
L720: def __init__(self, **options):
L725: class PythonTracebackLexer(RegexLexer):
L782: class Python2TracebackLexer(RegexLexer):
L830: class CythonLexer(RegexLexer):
L1009: class DgLexer(RegexLexer):
L1108: class NumPyLexer(PythonLexer):
L1189: def get_tokens_unprocessed(self, text):
L1197: def analyse_text(text):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/_init__.py

```

L35: def _fn_matches(fn, glob):
L43: def _load_lexers(module_name):
L51: def get_all_lexers(plugins=True):
L65: def find_lexer_class(name):
L83: def find_lexer_class_by_name(_alias):
L110: def get_lexer_by_name(_alias, **options):
L135: def load_lexer_from_file(filename, lexername="CustomLexer", **options):
L169: def find_lexer_class_for_filename(_fn, code=None):
L194: def get_rating(info):
L212: def get_lexer_for_filename(_fn, code=None, **options):
L231: def get_lexer_for_mimetype(_mime, **options):
L250: def _iter_lexerclasses(plugins=True):
L261: def guess_lexer_for_filename(_fn, _text, **options):
L292: def type_sort(t):
L304: def guess_lexer(_text, **options):
L308: class is called with the text as argument, and the lexer which returned the
L343: class _automodule(types.ModuleType):
L346: def __getattr__(self, name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/styles/_init__.py

```
L24: def get_style_by_name(name):
L56: def get_all_styles():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatters/__init__.py

```
L28: def _fn_matches(fn, glob):
L36: def _load_formatters(module_name):
L44: def get_all_formatters():
L55: def find_formatter_class(alias):
L70: def get_formatter_by_name(_alias, **options):
L84: def load_formatter_from_file(filename, formattername="CustomFormatter", **options):
L118: def get_formatter_for_filename(fn, **options):
L140: class _automodule(types.ModuleType):
L143: def __getattr__(self, name):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distro/distro.py

```
L61: class VersionDict(TypedDict):
L67: class InfoDict(TypedDict):
L160: def linux_distribution(full_distribution_name: bool = True) -> Tuple[str, str, str]:
L203: def id() -> str:
L287: def name(pretty: bool = False) -> str:
L326: def version(pretty: bool = False, best: bool = False) -> str:
L374: def version_parts(best: bool = False) -> Tuple[str, str, str]:
L391: def major_version(best: bool = False) -> str:
L404: def minor_version(best: bool = False) -> str:
L417: def build_number(best: bool = False) -> str:
L430: def like() -> str:
L447: def codename() -> str:
L471: def info(pretty: bool = False, best: bool = False) -> InfoDict:
L515: def os_release_info() -> Dict[str, str]:
L525: def lsb_release_info() -> Dict[str, str]:
L536: def distro_release_info() -> Dict[str, str]:
L546: def uname_info() -> Dict[str, str]:
L554: def os_release_attr(attribute: str) -> str:
L573: def lsb_release_attr(attribute: str) -> str:
L593: def distro_release_attr(attribute: str) -> str:
L612: def uname_attr(attribute: str) -> str:
L633: class cached_property: # type: ignore
L639: def __init__(self, f: Callable[[Any], Any]) -> None:
L643: def __get__(self, obj: Any, owner: Type[Any]) -> Any:
L649: class LinuxDistribution:
```

```

L667: def __init__(
L800: def __repr__(self) -> str:
L817: def linux_distribution(
L833: def id(self) -> str:
L839: def normalize(distro_id: str, table: Dict[str, str]) -> str:
L861: def name(self, pretty: bool = False) -> str:
L884: def version(self, pretty: bool = False, best: bool = False) -> str:
L926: def version_parts(self, best: bool = False) -> Tuple[str, str, str]:
L942: def major_version(self, best: bool = False) -> str:
L950: def minor_version(self, best: bool = False) -> str:
L958: def build_number(self, best: bool = False) -> str:
L966: def like(self) -> str:
L974: def codename(self) -> str:
L991: def info(self, pretty: bool = False, best: bool = False) -> InfoDict:
L1010: def os_release_info(self) -> Dict[str, str]:
L1019: def lsb_release_info(self) -> Dict[str, str]:
L1029: def distro_release_info(self) -> Dict[str, str]:
L1039: def uname_info(self) -> Dict[str, str]:
L1048: def oslevel_info(self) -> str:
L1054: def os_release_attr(self, attribute: str) -> str:
L1063: def lsb_release_attr(self, attribute: str) -> str:
L1072: def distro_release_attr(self, attribute: str) -> str:
L1081: def uname_attr(self, attribute: str) -> str:
L1091: def _os_release_info(self) -> Dict[str, str]:
L1104: def _parse_os_release_content(lines: TextIO) -> Dict[str, str]:
L1154: def _lsb_release_info(self) -> Dict[str, str]:
L1173: def _parse_lsb_release_content(lines: Iterable[str]) -> Dict[str, str]:
L1197: def _uname_info(self) -> Dict[str, str]:
L1209: def _oslevel_info(self) -> str:
L1219: def _debian_version(self) -> str:
L1229: def _parse_uname_content(lines: Sequence[str]) -> Dict[str, str]:
L1248: def _to_str(bytestring: bytes) -> str:
L1253: def _distro_release_info(self) -> Dict[str, str]:
L1311: def _parse_distro_release_file(self, filepath: str) -> Dict[str, str]:
L1334: def _parse_distro_release_content(line: str) -> Dict[str, str]:
L1362: def main() -> None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/com
pat.py**

```
L29: def _resolve_char_detection():
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/hook
s.py**

```
L16: def default_hooks():
L23: def dispatch_hook(key, hooks, hook_data, **kwargs):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/mod
els.py**

```
L86: class RequestEncodingMixin:
L88: def path_url(self):
L109: def _encode_params(data):
L139: def _encode_files(files, data):
L208: class RequestHooksMixin:
L209: def register_hook(self, event, hook):
L220: def deregister_hook(self, event, hook):
L232: class Request(RequestHooksMixin):
L260: def __init__(
L294: def __repr__(self):
L297: def prepare(self):
L315: class PreparedRequest(RequestEncodingMixin, RequestHooksMixin):
L336: def __init__(self):
L353: def prepare(
L381: def __repr__(self):
L384: def copy(self):
L395: def prepare_method(self, method):
L402: def _get_idna_encoded_host(host):
L411: def prepare_url(self, url, params):
L485: def prepare_headers(self, headers):
L496: def prepare_body(self, data, files, json=None):
L574: def prepare_content_length(self, body):
L590: def prepare_auth(self, auth, url=""):
L612: def prepare_cookies(self, cookies):
L632: def prepare_hooks(self, hooks):
L642: class Response:
L660: def __init__(self):
L707: def __enter__(self):
L710: def __exit__(self, *args):
L713: def __getstate__(self):
L721: def __setstate__(self, state):
L729: def __repr__(self):
L732: def __bool__(self):
L742: def __nonzero__(self):
L752: def __iter__(self):
L757: def ok(self):
L772: def is_redirect(self):
L779: def is_permanent_redirect(self):
L787: def next(self):
L792: def apparent_encoding(self):
L801: def iter_content(self, chunk_size=1, decode_unicode=False):
```

```

L818: def generate():
L859: def iter_lines(
L893: def content(self):
L912: def text(self):
L949: def json(self, **kwargs):
L985: def links(self):
L1001: def raise_for_status(self):
L1030: def close(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/help.py

```

L27: def _implementation():
L59: def info():
L118: def main():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/api.py

```

L14: def request(method, url, **kwargs):
L62: def get(url, params=None, **kwargs):
L76: def options(url, **kwargs):
L88: def head(url, **kwargs):
L103: def post(url, data=None, json=None, **kwargs):
L118: def put(url, data=None, **kwargs):
L133: def patch(url, data=None, **kwargs):
L148: def delete(url, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/exceptions.py

```

L13: class RequestException(IOError):
L18: def __init__(self, *args, **kwargs):
L28: class InvalidJSONError(RequestException):
L32: class JSONDecodeError(InvalidJSONError, CompatJSONDecodeError):
L35: def __init__(self, *args, **kwargs):
L45: def __reduce__(self):
L56: class HTTPError(RequestException):
L60: class ConnectionError(RequestException):
L64: class ProxyError(ConnectionError):

```

```

L68: class SSLError(ConnectionError):
L72: class Timeout(RequestException):
L81: class ConnectTimeout(ConnectionError, Timeout):
L88: class ReadTimeout(Timeout):
L92: class URLRequired(RequestException):
L96: class TooManyRedirects(RequestException):
L100: class MissingSchema(RequestException, ValueError):
L104: class InvalidSchema(RequestException, ValueError):
L108: class InvalidURL(RequestException, ValueError):
L112: class InvalidHeader(RequestException, ValueError):
L116: class InvalidProxyURL(InvalidURL):
L120: class ChunkedEncodingError(RequestException):
L124: class ContentDecodingError(RequestException, BaseHTTPError):
L128: class StreamConsumedError(RequestException, TypeError):
L132: class RetryError(RequestException):
L136: class UnrewindableBodyError(RequestException):
L143: class RequestsWarning(Warning):
L147: class FileModeWarning(RequestsWarning, DeprecationWarning):
L151: class RequestsDependencyWarning(RequestsWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/__init__.py

```

L51: def check_compatibility(urllib3_version, chardet_version, charset_normalizer_version):
L83: def _check_cryptography(cryptography_version):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/sessions.py

```

L62: def merge_setting(request_setting, session_setting, dict_class=OrderedDict):
L92: def merge_hooks(request_hooks, session_hooks, dict_class=OrderedDict):
L107: class SessionRedirectMixin:
L108: def get_redirect_target(self, resp):
L128: def should_strip_auth(self, old_url, new_url):
L160: def resolve_redirects(
L283: def rebuild_auth(self, prepared_request, response):
L303: def rebuild_proxies(self, prepared_request, proxies):
L334: def rebuild_method(self, prepared_request, response):
L357: class Session(SessionRedirectMixin):
L391: def __init__(self):
L454: def __enter__(self):
L457: def __exit__(self, *args):
L460: def prepare_request(self, request):
L503: def request(

```

```

L596: def get(self, url, **kwargs):
L607: def options(self, url, **kwargs):
L618: def head(self, url, **kwargs):
L629: def post(self, url, data=None, json=None, **kwargs):
L642: def put(self, url, data=None, **kwargs):
L654: def patch(self, url, data=None, **kwargs):
L666: def delete(self, url, **kwargs):
L676: def send(self, request, **kwargs):
L753: def merge_environment_settings(self, url, proxies, stream, verify, cert):
L784: def get_adapter(self, url):
L797: def close(self):
L802: def mount(self, prefix, adapter):
L813: def __getstate__(self):
L817: def __setstate__(self, state):
L822: def session():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/utlis.py

```

L76: def proxy_bypass_registry(host):
L114: def proxy_bypass(host): # noqa
L126: def dict_to_sequence(d):
L135: def super_len(o):
L206: def get_netrc_auth(url, raise_errors=False):
L250: def guess_filename(obj):
L257: def extract_zipped_paths(path):
L296: def atomic_open(filename):
L308: def from_key_val_list(value):
L335: def to_key_val_list(value):
L365: def parse_list_header(value):
L397: def parse_dict_header(value):
L432: def unquote_header_value(value, is_filename=False):
L457: def dict_from_cookiejar(cj):
L468: def add_dict_to_cookiejar(cj, cookie_dict):
L479: def get_encodings_from_content(content):
L504: def _parse_content_type_header(header):
L526: def get_encoding_from_headers(headers):
L551: def stream_decode_response_unicode(iterator, r):
L568: def iter_slices(string, slice_length):
L578: def get_unicode_from_response(r):
L623: def unquote_unreserved(uri):
L647: def requote_uri(uri):
L669: def address_in_network(ip, net):
L684: def dotted_netmask(mask):
L695: def is_ipv4_address(string_ip):
L706: def is_valid_cidr(string_network):
L731: def set_environ(env_name, value):

```

```

L752: def should_bypass_proxies(url, no_proxy):
L761: def get_proxy(key):
L813: def get_environ_proxies(url, no_proxy=None):
L825: def select_proxy(url, proxies):
L851: def resolve_proxies(request, proxies, trust_env=True):
L878: def default_user_agent(name="python-requests"):
L887: def default_headers():
L901: def parse_header_links(value):
L944: def guess_json_utf(data):
L976: def prepend_scheme_if_needed(url, new_scheme):
L1005: def get_auth_from_url(url):
L1021: def check_header_validity(header):
L1032: def _validate_header_part(header, header_part, header_validator_index):
L1051: def urldefragauth(url):
L1068: def rewind_body(prepared_request):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/_internal_utils.py

```

L26: def to_native_string(string, encoding="ascii"):
L39: def unicode_is_ascii(u_string):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/cookies.py

```

L23: class MockRequest:
L35: def __init__(self, request):
L40: def get_type(self):
L43: def get_host(self):
L46: def get_origin_req_host(self):
L49: def get_full_url(self):
L69: def is_unverifiable(self):
L72: def has_header(self, name):
L75: def get_header(self, name, default=None):
L78: def add_header(self, key, val):
L84: def add_unredirected_header(self, name, value):
L87: def get_new_headers(self):
L91: def unverifiable(self):
L95: def origin_req_host(self):
L99: def host(self):
L103: class MockResponse:
L110: def __init__(self, headers):
L117: def info(self):
L120: def getheaders(self, name):

```



```

L124: def extract_cookies_to_jar(jar, request, response):
L140: def get_cookie_header(jar, request):
L151: def remove_cookie_by_name(cookiejar, name, domain=None, path=None):
L170: class CookieConflictError(RuntimeError):
L176: class RequestsCookieJar(cookiejar.CookieJar, MutableMapping):
L194: def get(self, name, default=None, domain=None, path=None):
L206: def set(self, name, value, **kwargs):
L225: def iterkeys(self):
L234: def keys(self):
L242: def itervalues(self):
L251: def values(self):
L259: def iteritems(self):
L268: def items(self):
L277: def list_domains(self):
L285: def list_paths(self):
L293: def multiple_domains(self):
L306: def get_dict(self, domain=None, path=None):
L321: def __contains__(self, name):
L327: def __getitem__(self, name):
L336: def __setitem__(self, name, value):
L343: def __delitem__(self, name):
L349: def set_cookie(self, cookie, *args, **kwargs):
L358: def update(self, other):
L366: def _find(self, name, domain=None, path=None):
L386: def _find_no_duplicates(self, name, domain=None, path=None):
L415: def __getstate__(self):
L422: def __setstate__(self, state):
L428: def copy(self):
L435: def get_policy(self):
L440: def _copy_cookie_jar(jar):
L455: def create_cookie(name, value, **kwargs):
L492: def morsel_to_cookie(morsel):
L521: def cookiejar_from_dict(cookie_dict, cookiejar=None, overwrite=True):
L542: def merge_cookies(cookiejar, cookies):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/auth.py

```

L25: def _basic_auth_str(username, password):
L69: class AuthBase:
L72: def __call__(self, r):
L76: class HTTPBasicAuth(AuthBase):
L79: def __init__(self, username, password):
L83: def __eq__(self, other):
L91: def __ne__(self, other):
L94: def __call__(self, r):
L99: class HTTPProxyAuth(HTTPBasicAuth):

```

```

L102: def __call__(self, r):
L107: class HTTPDigestAuth(AuthBase):
L110: def __init__(self, username, password):
L116: def init_per_thread_state(self):
L126: def build_digest_header(self, method, url):
L145: def md5_utf8(x):
L153: def sha_utf8(x):
L161: def sha256_utf8(x):
L169: def sha512_utf8(x):
L236: def handle_redirect(self, r, **kwargs):
L241: def handle_401(self, r, **kwargs):
L285: def __call__(self, r):
L305: def __eq__(self, other):
L313: def __ne__(self, other):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/adapters.py

```

L63: def SOCKSProxyManager(*args, **kwargs):
L77: def _urllib3_request_context(
L114: class BaseAdapter:
L117: def __init__(self):
L120: def send(
L139: def close(self):
L144: class HTTPAdapter(BaseAdapter):
L179: def __init__(
L201: def __getstate__(self):
L204: def __setstate__(self, state):
L217: def init_poolmanager(
L243: def proxy_manager_for(self, proxy, **proxy_kwargs):
L281: def cert_verify(self, conn, url, verify, cert):
L337: def build_response(self, req, resp):
L374: def build_connection_pool_key_attributes(self, request, verify, cert=None):
L424: def get_connection_with_tls_context(self, request, verify, proxies=None, cert=None):
L473: def get_connection(self, url, proxies=None):
L514: def close(self):
L524: def request_url(self, request, proxies):
L556: def add_headers(self, request, **kwargs):
L570: def proxy_headers(self, proxy):
L591: def send(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/structures.py

```

L13: class CaseInsensitiveDict(MutableMapping):
L40: def __init__(self, data=None, **kwargs):
L46: def __setitem__(self, key, value):
L51: def __getitem__(self, key):
L54: def __delitem__(self, key):
L57: def __iter__(self):
L60: def __len__(self):
L63: def lower_items(self):
L67: def __eq__(self, other):
L76: def copy(self):
L79: def __repr__(self):
L83: class LookupDict(dict):
L86: def __init__(self, name=None):
L90: def __repr__(self):
L93: def __getitem__(self, key):
L98: def get(self, key, default=None):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/status_codes.py

```

L109: def _init():
L116: def doc(code):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/unix.py

```

L18: def getuid() -> NoReturn:
L26: class Unix(PlatformDirsABC): # noqa: PLR0904
L40: def user_data_dir(self) -> str:
L51: def _site_data_dirs(self) -> list[str]:
L58: def site_data_dir(self) -> str:
L71: def user_config_dir(self) -> str:
L82: def _site_config_dirs(self) -> list[str]:
L89: def site_config_dir(self) -> str:
L102: def user_cache_dir(self) -> str:
L113: def site_cache_dir(self) -> str:
L118: def user_state_dir(self) -> str:
L129: def user_log_dir(self) -> str:
L138: def user_documents_dir(self) -> str:
L143: def user_downloads_dir(self) -> str:
L148: def user_pictures_dir(self) -> str:
L153: def user_videos_dir(self) -> str:
L158: def user_music_dir(self) -> str:
L163: def user_desktop_dir(self) -> str:

```

```

L168: def user_runtime_dir(self) -> str:
L188: def site_runtime_dir(self) -> str:
L210: def site_data_path(self) -> Path:
L215: def site_config_path(self) -> Path:
L220: def site_cache_path(self) -> Path:
L224: def iter_config_dirs(self) -> Iterator[str]:
L229: def iter_data_dirs(self) -> Iterator[str]:
L235: def _get_user_media_dir(env_var: str, fallback_tilde_path: str) -> str:
L245: def _get_user_dirs_folder(key: str) -> str | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/_main__.py

```

L26: def main() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/api.py

```

L15: class PlatformDirsABC(ABC): # noqa: PLR0904
L18: def __init__( # noqa: PLR0913, PLR0917
L81: def _append_app_name_and_version(self, *base: str) -> str:
L91: def _optionally_create_directory(self, path: str) -> None:
L95: def _first_item_as_path_if_multipath(self, directory: str) -> Path:
L103: def user_data_dir(self) -> str:
L108: def site_data_dir(self) -> str:
L113: def user_config_dir(self) -> str:
L118: def site_config_dir(self) -> str:
L123: def user_cache_dir(self) -> str:
L128: def site_cache_dir(self) -> str:
L133: def user_state_dir(self) -> str:
L138: def user_log_dir(self) -> str:
L143: def user_documents_dir(self) -> str:
L148: def user_downloads_dir(self) -> str:
L153: def user_pictures_dir(self) -> str:
L158: def user_videos_dir(self) -> str:
L163: def user_music_dir(self) -> str:
L168: def user_desktop_dir(self) -> str:
L173: def user_runtime_dir(self) -> str:
L178: def site_runtime_dir(self) -> str:
L182: def user_data_path(self) -> Path:
L187: def site_data_path(self) -> Path:
L192: def user_config_path(self) -> Path:
L197: def site_config_path(self) -> Path:
L202: def user_cache_path(self) -> Path:

```

```

L207: def site_cache_path(self) -> Path:
L212: def user_state_path(self) -> Path:
L217: def user_log_path(self) -> Path:
L222: def user_documents_path(self) -> Path:
L227: def user_downloads_path(self) -> Path:
L232: def user_pictures_path(self) -> Path:
L237: def user_videos_path(self) -> Path:
L242: def user_music_path(self) -> Path:
L247: def user_desktop_path(self) -> Path:
L252: def user_runtime_path(self) -> Path:
L257: def site_runtime_path(self) -> Path:
L261: def iter_config_dirs(self) -> Iterator[str]:
L266: def iter_data_dirs(self) -> Iterator[str]:
L271: def iter_cache_dirs(self) -> Iterator[str]:
L276: def iter_runtime_dirs(self) -> Iterator[str]:
L281: def iter_config_paths(self) -> Iterator[Path]:
L286: def iter_data_paths(self) -> Iterator[Path]:
L291: def iter_cache_paths(self) -> Iterator[Path]:
L296: def iter_runtime_paths(self) -> Iterator[Path]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/_init_.py

```

L30: def _set_platform_dir_class() -> type[PlatformDirsABC]:
L53: def user_data_dir(
L77: def site_data_dir(
L101: def user_config_dir(
L125: def site_config_dir(
L149: def user_cache_dir(
L173: def site_cache_dir(
L197: def user_state_dir(
L221: def user_log_dir(
L245: def user_documents_dir() -> str:
L250: def user_downloads_dir() -> str:
L255: def user_pictures_dir() -> str:
L260: def user_videos_dir() -> str:
L265: def user_music_dir() -> str:
L270: def user_desktop_dir() -> str:
L275: def user_runtime_dir(
L299: def site_runtime_dir(
L323: def user_data_path(
L347: def site_data_path(
L371: def user_config_path(
L395: def site_config_path(
L419: def site_cache_path(
L443: def user_cache_path(
L467: def user_state_path(

```

```

L491: def user_log_path(
L515: def user_documents_path() -> Path:
L520: def user_downloads_path() -> Path:
L525: def user_pictures_path() -> Path:
L530: def user_videos_path() -> Path:
L535: def user_music_path() -> Path:
L540: def user_desktop_path() -> Path:
L545: def user_runtime_path(
L569: def site_runtime_path(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/android.py

```

L14: class Android(PlatformDirsABC):
L24: def user_data_dir(self) -> str:
L29: def site_data_dir(self) -> str:
L34: def user_config_dir(self) -> str:
L42: def site_config_dir(self) -> str:
L47: def user_cache_dir(self) -> str:
L52: def site_cache_dir(self) -> str:
L57: def user_state_dir(self) -> str:
L62: def user_log_dir(self) -> str:
L73: def user_documents_dir(self) -> str:
L78: def user_downloads_dir(self) -> str:
L83: def user_pictures_dir(self) -> str:
L88: def user_videos_dir(self) -> str:
L93: def user_music_dir(self) -> str:
L98: def user_desktop_dir(self) -> str:
L103: def user_runtime_dir(self) -> str:
L114: def site_runtime_dir(self) -> str:
L120: def _android_folder() -> str | None: # noqa: C901
L168: def _android_documents_folder() -> str:
L184: def _android_downloads_folder() -> str:
L200: def _android_pictures_folder() -> str:
L216: def _android_videos_folder() -> str:
L232: def _android_music_folder() -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/macOS.py

```

L15: class MacOS(PlatformDirsABC):
L28: def user_data_dir(self) -> str:
L33: def site_data_dir(self) -> str:
L51: def site_data_path(self) -> Path:

```

```

L56: def user_config_dir(self) -> str:
L61: def site_config_dir(self) -> str:
L66: def user_cache_dir(self) -> str:
L71: def site_cache_dir(self) -> str:
L89: def site_cache_path(self) -> Path:
L94: def user_state_dir(self) -> str:
L99: def user_log_dir(self) -> str:
L104: def user_documents_dir(self) -> str:
L109: def user_downloads_dir(self) -> str:
L114: def user_pictures_dir(self) -> str:
L119: def user_videos_dir(self) -> str:
L124: def user_music_dir(self) -> str:
L129: def user_desktop_dir(self) -> str:
L134: def user_runtime_dir(self) -> str:
L139: def site_runtime_dir(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/windows.py

```

L16: class Windows(PlatformDirsABC):
L28: def user_data_dir(self) -> str:
L38: def _append_parts(self, path: str, *, opinion_value: str | None = None) -> str:
L54: def site_data_dir(self) -> str:
L60: def user_config_dir(self) -> str:
L65: def site_config_dir(self) -> str:
L70: def user_cache_dir(self) -> str:
L79: def site_cache_dir(self) -> str:
L85: def user_state_dir(self) -> str:
L90: def user_log_dir(self) -> str:
L99: def user_documents_dir(self) -> str:
L104: def user_downloads_dir(self) -> str:
L109: def user_pictures_dir(self) -> str:
L114: def user_videos_dir(self) -> str:
L119: def user_music_dir(self) -> str:
L124: def user_desktop_dir(self) -> str:
L129: def user_runtime_dir(self) -> str:
L138: def site_runtime_dir(self) -> str:
L143: def get_win_folder_from_env_vars(csidl_name: str) -> str:
L164: def get_win_folder_if_csidl_name_not_env_var(csidl_name: str) -> str | None:
L183: def get_win_folder_from_registry(csidl_name: str) -> str:
L219: def get_win_folder_via_ctypes(csidl_name: str) -> str:
L258: def _pick_get_win_folder() -> Callable[[str], str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_parser.

py

```

L77: class DEPRECATED_DEFAULT:
L82: class TOMLDecodeError(ValueError):
L93: def __init__(
L143: def load(__fp: IO[bytes], *, parse_float: ParseFloat = float) -> dict[str, Any]:
L155: def loads(__s: str, *, parse_float: ParseFloat = float) -> dict[str, Any]:
L226: class Flags:
L235: def __init__(self) -> None:
L239: def add_pending(self, key: Key, flag: int) -> None:
L242: def finalize_pending(self) -> None:
L247: def unset_all(self, key: Key) -> None:
L255: def set(self, key: Key, flag: int, *, recursive: bool) -> None: # noqa: A003
L266: def is_(self, key: Key, flag: int) -> bool:
L284: class NestedDict:
L285: def __init__(self) -> None:
L289: def get_or_create_nest(
L306: def append_nest_to_list(self, key: Key) -> None:
L318: class Output:
L319: def __init__(self) -> None:
L324: def skip_chars(src: str, pos: Pos, chars: Iterable[str]) -> Pos:
L333: def skip_until(
L355: def skip_comment(src: str, pos: Pos) -> Pos:
L367: def skip_comments_and_array_ws(src: str, pos: Pos) -> Pos:
L376: def create_dict_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:
L396: def create_list_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:
L419: def key_value_rule(
L453: def parse_key_value_pair(
L469: def parse_key(src: str, pos: Pos) -> tuple[Pos, Key]:
L491: def parse_key_part(src: str, pos: Pos) -> tuple[Pos, str]:
L507: def parse_one_line_basic_str(src: str, pos: Pos) -> tuple[Pos, str]:
L512: def parse_array(
L538: def parse_inline_table(
L572: def parse_basic_str_escape(
L601: def parse_basic_str_escape_multiline(src: str, pos: Pos) -> tuple[Pos, str]:
L605: def parse_hex_char(src: str, pos: Pos, hex_len: int) -> tuple[Pos, str]:
L618: def parse_literal_str(src: str, pos: Pos) -> tuple[Pos, str]:
L627: def parse_multiline_str(src: str, pos: Pos, *, literal: bool) -> tuple[Pos, str]:
L658: def parse_basic_str(src: str, pos: Pos, *, multiline: bool) -> tuple[Pos, str]:
L690: def parse_value(
L766: def is_unicode_scalar_value(codepoint: int) -> bool:
L770: def make_safe_parse_float(parse_float: ParseFloat) -> ParseFloat:
L782: def safe_parse_float(float_str: str) -> Any:

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_re.py**

```

L57: def match_to_datetime(match: re.Match[str]) -> datetime | date:

```



```

L96: def cached_tz(hour_str: str, minute_str: str, sign_str: str) -> timezone:
L106: def match_to_localtime(match: re.Match[str]) -> time:
L112: def match_to_number(match: re.Match[str], parse_float: ParseFloat) -> Any:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/exceptions.py

```

L1: class UnpackException(Exception):
L10: class BufferFull(UnpackException):
L14: class OutOfData(UnpackException):
L18: class FormatError(ValueError, UnpackException):
L22: class StackError(ValueError, UnpackException):
L30: class ExtraData(UnpackValueError):
L37: def __init__(self, unpacked, extra):
L41: def __str__(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/__init__.py

```

L20: def pack(o, stream, **kwargs):
L30: def packb(o, **kwargs):
L39: def unpack(stream, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/ext.py

```

L6: class ExtType(namedtuple("ExtType", "code data")):
L9: def __new__(cls, code, data):
L19: class Timestamp:
L31: def __init__(self, seconds, nanoseconds=0):
L53: def __repr__(self):
L57: def __eq__(self, other):
L63: def __ne__(self, other):
L67: def __hash__(self):
L71: def from_bytes(b):
L97: def to_bytes(self):
L119: def from_unix(unix_sec):
L129: def to_unix(self):
L138: def from_unix_nano(unix_ns):
L146: def to_unix_nano(self):

```

```
L154: def to_datetime(self):
L165: def from_datetime(dt):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/fallback.py

```
L13: class BytesIO:
L14: def __init__(self, s=b''):
L21: def write(self, s):
L28: def getvalue(self):
L36: def newlist_hint(size):
L58: def _check_type_strict(obj, t, type=type, tuple=tuple):
L65: def _get_data_from_buffer(obj):
L72: def unpackb(packed, **kwargs):
L130: class Unpacker:
L226: def __init__(
L318: def feed(self, next_bytes):
L334: def _consume(self):
L339: def _got_extradata(self):
L342: def _get_extradata(self):
L345: def read_bytes(self, n):
L350: def _read(self, n, raise_outofdata=True):
L358: def _reserve(self, n, raise_outofdata=True):
L392: def _read_header(self):
L488: def _unpack(self, execute=EX_CONSTRUCT):
L562: def __iter__(self):
L565: def __next__(self):
L578: def skip(self):
L582: def unpack(self):
L590: def read_array_header(self):
L595: def read_map_header(self):
L600: def tell(self):
L604: class Packer:
L653: def __init__(
L676: def _pack(
L800: def pack(self, obj):
L811: def pack_map_pairs(self, pairs):
L818: def pack_array_header(self, n):
L827: def pack_map_header(self, n):
L836: def pack_ext_type(self, typecode, data):
L865: def _pack_array_header(self, n):
L874: def _pack_map_header(self, n):
L883: def _pack_map_pairs(self, n, pairs, nest_limit=DEFAULT_RECURSE_LIMIT):
L889: def _pack_raw_header(self, n):
L901: def _pack_bin_header(self, n):
L913: def bytes(self):
L917: def reset(self):
```

```
L924: def getbuffer(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pkg_resources/
s/__init__.py

```
L135: class _LoaderProtocol(Protocol):
L136: def load_module(self, fullname: str, /) -> types.ModuleType: ...
L139: class _ZipLoaderModule(Protocol):
L146: class PEP440Warning(RuntimeWarning):
L159: def _declare_state(vartype: str, varname: str, initial_value: _T) -> _T:
L164: def __getstate__() -> dict[str, Any]:
L172: def __setstate__(state: dict[str, Any]) -> dict[str, Any]:
L179: def _sget_dict(val):
L183: def _sset_dict(key, ob, state):
L188: def _sget_object(val):
L192: def _sset_object(key, ob, state):
L199: def get_supported_platform():
L309: class ResolutionError(Exception):
L312: def __repr__(self):
L316: class VersionConflict(ResolutionError):
L327: def dist(self) -> Distribution:
L331: def req(self) -> Requirement:
L334: def report(self):
L337: def with_context(self, required_by: set[Distribution | str]):
L348: class ContextualVersionConflict(VersionConflict):
L357: def required_by(self) -> set[str]:
L361: class DistributionNotFound(ResolutionError):
L370: def req(self) -> Requirement:
L374: def requirers(self) -> set[str] | None:
L378: def requirers_str(self):
L383: def report(self):
L386: def __str__(self):
L390: class UnknownExtra(ResolutionError):
L404: def register_loader_type(
L417: def get_provider(moduleOrReq: str) -> IResourceProvider: ...
L419: def get_provider(moduleOrReq: Requirement) -> Distribution: ...
L420: def get_provider(moduleOrReq: str | Requirement) -> IResourceProvider | Distribution:
L434: def _macos_vers():
L447: def _macos_arch(machine):
L451: def get_build_platform():
L482: def compatible_platforms(provided: str | None, required: str | None):
L532: def get_distribution(dist: _DistributionT) -> _DistributionT: ...
L534: def get_distribution(dist: _PkgReqType) -> Distribution: ...
L535: def get_distribution(dist: Distribution | _PkgReqType) -> Distribution:
L547: def load_entry_point(dist: _EPDistType, group: str, name: str) -> _ResolvedEntryPoint:
L553: def get_entry_map(
L557: def get_entry_map(dist: _EPDistType, group: str) -> dict[str, EntryPoint]: ...
```

```

L558: def get_entry_map(dist: _EPDistType, group: str | None = None):
L563: def get_entry_info(dist: _EPDistType, group: str, name: str):
L568: class IMetadataProvider(Protocol):
L569: def has_metadata(self, name: str) -> bool:
L572: def get_metadata(self, name: str) -> str:
L575: def get_metadata_lines(self, name: str) -> Iterator[str]:
L581: def metadata_isdir(self, name: str) -> bool:
L584: def metadata_listdir(self, name: str) -> list[str]:
L587: def run_script(self, script_name: str, namespace: dict[str, Any]) -> None:
L591: class IResourceProvider(IMetadataProvider, Protocol):
L594: def get_resource_filename(
L601: def get_resource_stream(
L608: def get_resource_string(
L615: def has_resource(self, resource_name: str) -> bool:
L618: def resource_isdir(self, resource_name: str) -> bool:
L621: def resource_listdir(self, resource_name: str) -> list[str]:
L625: class WorkingSet:
L628: def __init__(self, entries: Iterable[str] | None = None):
L643: def _build_master(cls):
L663: def _build_from_requirements(cls, req_spec):
L684: def add_entry(self, entry: str):
L699: def __contains__(self, dist: Distribution) -> bool:
L703: def find(self, req: Requirement) -> Distribution | None:
L727: def iter_entry_points(self, group: str, name: str | None = None):
L741: def run_script(self, requires: str, script_name: str):
L749: def __iter__(self) -> Iterator[Distribution]:
L766: def add(
L805: def resolve(
L814: def resolve(
L824: def resolve(
L832: def resolve(
L906: def _resolve_dist(
L938: def find_plugins(
L946: def find_plugins(
L955: def find_plugins(
L962: def find_plugins(
L1052: def require(self, *requirements: _NestedStr):
L1068: def subscribe(
L1084: def _added_new(self, dist):
L1088: def __getstate__(self):
L1097: def __setstate__(self, e_k_b_n_c):
L1106: class _ReqExtras(Dict["Requirement", Tuple[str, ...]]):
L1111: def markers_pass(self, req: Requirement, extras: tuple[str, ...] | None = None):
L1126: class Environment:
L1129: def __init__(
L1156: def can_add(self, dist: Distribution):
L1170: def remove(self, dist: Distribution):
L1174: def scan(self, search_path: Iterable[str] | None = None):
L1189: def __getitem__(self, project_name: str) -> list[Distribution]:
L1200: def add(self, dist: Distribution):
L1209: def best_match(

```

```

L1217: def best_match(
L1224: def best_match(
L1258: def obtain(
L1264: def obtain(
L1270: def obtain(
L1275: def obtain(
L1293: def __iter__(self) -> Iterator[str]:
L1299: def __iadd__(self, other: Distribution | Environment):
L1311: def __add__(self, other: Distribution | Environment):
L1323: class ExtractionError(RuntimeError):
L1343: class ResourceManager:
L1348: def __init__(self):
L1351: def resource_exists(self, package_or_requirement: _PkgReqType, resource_name: str):
L1355: def resource_isdir(self, package_or_requirement: _PkgReqType, resource_name: str):
L1359: def resource_filename(
L1367: def resource_stream(self, package_or_requirement: _PkgReqType, resource_name: str):
L1373: def resource_string(
L1381: def resource_listdir(self, package_or_requirement: _PkgReqType, resource_name: str):
L1385: def extraction_error(self) -> NoReturn:
L1415: def get_cache_path(self, archive_name: str, names: Iterable[StrPath] = ()):
L1441: def _warn_unsafe_extraction_path(path):
L1467: def postprocess(self, tempname: StrOrBytesPath, filename: StrOrBytesPath):
L1487: def set_extraction_path(self, path: str):
L1511: def cleanup_resources(self, force: bool = False) -> list[str]:
L1526: def get_default_cache() -> str:
L1535: def safe_name(name: str):
L1543: def safe_version(version: str):
L1555: def _forgiving_version(version):
L1580: def _safe_segment(segment):
L1587: def safe_extra(extra: str):
L1596: def to_filename(name: str):
L1604: def invalid_marker(text: str):
L1618: def evaluate_marker(text: str, extra: str | None = None) -> bool:
L1633: class NullProvider:
L1640: def __init__(self, module: _ModuleLike):
L1644: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
L1647: def get_resource_stream(self, manager: ResourceManager, resource_name: str):
L1650: def get_resource_string(
L1655: def has_resource(self, resource_name: str):
L1658: def _get_metadata_path(self, name):
L1661: def has_metadata(self, name: str) -> bool:
L1668: def get_metadata(self, name: str):
L1681: def get_metadata_lines(self, name: str) -> Iterator[str]:
L1684: def resource_isdir(self, resource_name: str):
L1687: def metadata_isdir(self, name: str) -> bool:
L1690: def resource_listdir(self, resource_name: str):
L1693: def metadata_listdir(self, name: str) -> list[str]:
L1698: def run_script(self, script_name: str, namespace: dict[str, Any]):
L1727: def _has(self, path) -> bool:
L1732: def _isdir(self, path) -> bool:
L1737: def _listdir(self, path) -> list[str]:

```

```

L1742: def _fn(self, base: str | None, resource_name: str):
L1753: def _validate_resource_path(path):
L1827: def _get(self, path) -> bytes:
L1839: def _parents(path):
L1850: class EggProvider(NullProvider):
L1853: def __init__(self, module: _ModuleLike):
L1857: def _setup_prefix(self):
L1864: def _set_egg(self, path: str):
L1870: class DefaultProvider(EggProvider):
L1873: def _has(self, path) -> bool:
L1876: def _isdir(self, path) -> bool:
L1879: def _listdir(self, path):
L1882: def get_resource_stream(self, manager: object, resource_name: str):
L1885: def _get(self, path) -> bytes:
L1890: def _register(cls):
L1903: class EmptyProvider(NullProvider):
L1911: def _get(self, path) -> bytes:
L1914: def _listdir(self, path):
L1917: def __init__(self):
L1924: class ZipManifests(Dict[str, "MemoizedZipManifests.manifest_mod"]):
L1931: def build(cls, path: str):
L1952: class MemoizedZipManifests(ZipManifests):
L1957: class manifest_mod(NamedTuple):
L1961: def load(self, path: str) -> dict[str, zipfile.ZipInfo]: # type: ignore[override] #
ZipManifests.load is a classmethod
L1975: class ZipProvider(EggProvider):
L1983: def __init__(self, module: _ZipLoaderModule):
L1987: def _zipinfo_name(self, fspath):
L1997: def _parts(self, zip_path):
L2006: def zipinfo(self):
L2009: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
L2023: def _get_date_and_size(zip_stat):
L2032: def _extract_resource(self, manager: ResourceManager, zip_path) -> str: # noqa: C901
L2086: def _is_current(self, file_path, zip_path):
L2102: def _get_eager_resources(self):
L2111: def _index(self):
L2128: def _has(self, fspath) -> bool:
L2132: def _isdir(self, fspath) -> bool:
L2135: def _listdir(self, fspath):
L2138: def _eager_to_zip(self, resource_name: str):
L2141: def _resource_to_zip(self, resource_name: str):
L2148: class FileMetadata(EmptyProvider):
L2160: def __init__(self, path: StrPath):
L2163: def _get_metadata_path(self, name):
L2166: def has_metadata(self, name: str) -> bool:
L2169: def get_metadata(self, name: str):
L2178: def _warn_on_replacement(self, metadata):
L2185: def get_metadata_lines(self, name: str) -> Iterator[str]:
L2189: class PathMetadata(DefaultProvider):
L2209: def __init__(self, path: str, egg_info: str):
L2214: class EggMetadata(ZipProvider):

```

```

L2217: def __init__(self, importer: zipimport.zipimporter):
L2234: def register_finder(importer_type: type[_T], distribution_finder:
_DistFinderType[_T]):
L2244: def find_distributions(path_item: str, only: bool = False):
L2251: def find_eggs_in_zip(
L2282: def find_nothing(
L2291: def find_on_path(importer: object | None, path_item, only=False):
L2311: def dist_factory(path_item, entry, only):
L2330: class NoDists:
L2339: def __bool__(self):
L2342: def __call__(self, fullpath):
L2346: def safe_listdir(path: StrOrBytesPath):
L2362: def distributions_from_metadata(path: str):
L2380: def non_empty_lines(path):
L2390: def resolve_egg_link(path):
L2416: def register_namespace_handler(
L2424: def namespace_handler(importer, path_entry, moduleName, module):
L2436: def _handle_ns(packageName, path_item):
L2473: def _rebuild_mod_path(orig_path, package_name, module: types.ModuleType):
L2480: def safe_sys_path_index(entry):
L2489: def position_in_sys_path(path):
L2507: def declare_namespace(packageName: str):
L2550: def fixup_namespace_packages(path_item: str, parent: str | None = None):
L2562: def file_ns_handler(
L2587: def null_ns_handler(
L2600: def normalize_path(filename: StrPath) -> str: ...
L2602: def normalize_path(filename: BytesPath) -> bytes: ...
L2603: def normalize_path(filename: StrOrBytesPath):
L2608: def _cygwin_patch(filename: StrOrBytesPath): # pragma: nocover
L2623: def _normalize_cached(filename: StrPath) -> str: ...
L2625: def _normalize_cached(filename: BytesPath) -> bytes: ...
L2626: def _normalize_cached(filename: StrOrBytesPath) -> str | bytes: ...
L2630: def _normalize_cached(filename):
L2634: def _is_egg_path(path):
L2641: def _is_zip_egg(path):
L2649: def _is_unpacked_egg(path):
L2658: def _set_parent_ns(packageName):
L2681: class EntryPoint:
L2684: def __init__(
L2700: def __str__(self):
L2708: def __repr__(self):
L2712: def load(
L2719: def load(
L2725: def load(
L2747: def resolve(self) -> _ResolvedEntryPoint:
L2757: def require(
L2785: def parse(cls, src: str, dist: Distribution | None = None):
L2805: def _parse_extras(cls, extras_spec):
L2814: def parse_group(
L2832: def parse_map(
L2856: def _version_from_file(lines):

```

```

L2862: def is_version_line(line):
L2871: class Distribution:
L2876: def __init__(
L2896: def from_location(
L2923: def _reload_version(self):
L2927: def hashcmp(self):
L2937: def __hash__(self):
L2940: def __lt__(self, other: Distribution):
L2943: def __le__(self, other: Distribution):
L2946: def __gt__(self, other: Distribution):
L2949: def __ge__(self, other: Distribution):
L2952: def __eq__(self, other: object):
L2958: def __ne__(self, other: object):
L2966: def key(self):
L2974: def parsed_version(self):
L2988: def _forgiving_parsed_version(self):
L3014: def version(self):
L3029: def _dep_map(self):
L3041: def _filter_extras(dm: dict[str | None, list[Requirement]]):
L3061: def _build_dep_map(self):
L3068: def requires(self, extras: Iterable[str] = ()):
L3082: def _get_metadata_path_for_display(self, name):
L3099: def _get_metadata(self, name):
L3103: def _get_version(self):
L3107: def activate(self, path: list[str] | None = None, replace: bool = False):
L3118: def egg_name(self):
L3130: def __repr__(self):
L3136: def __str__(self):
L3144: def __getattr__(self, attr):
L3150: def __dir__(self):
L3157: def from_filename(
L3167: def as_requirement(self):
L3176: def load_entry_point(self, group: str, name: str) -> _ResolvedEntryPoint:
L3184: def get_entry_map(self, group: None = None) -> dict[str, dict[str, EntryPoint]]: ...
L3186: def get_entry_map(self, group: str) -> dict[str, EntryPoint]: ...
L3187: def get_entry_map(self, group: str | None = None):
L3197: def get_entry_info(self, group: str, name: str):
L3202: def insert_on( # noqa: C901
L3275: def check_version_conflict(self):
L3301: def has_version(self):
L3312: def clone(self, **kw: str | int | IResourceProvider | None):
L3322: def extras(self):
L3326: class EggInfoDistribution(Distribution):
L3327: def _reload_version(self):
L3345: class DistInfoDistribution(Distribution):
L3355: def _parsed_pkg_info(self):
L3365: def _dep_map(self):
L3372: def _compute_dependencies(self) -> dict[str | None, list[Requirement]]:
L3381: def reqs_for_extra(extra):
L3405: def issue_warning(*args, **kw):
L3418: def parse_requirements(strs: _NestedStr):

```



```

L3427: class RequirementParseError(_packaging_requirements.InvalidRequirement):
L3431: class Requirement(_packaging_requirements.Requirement):
L3432: def __init__(self, requirement_string: str):
L3450: def __eq__(self, other: object):
L3453: def __ne__(self, other):
L3456: def __contains__(self, item: Distribution | str | tuple[str, ...]) -> bool:
L3468: def __hash__(self):
L3471: def __repr__(self):
L3475: def parse(s: str | Iterable[str]):
L3480: def _always_object(classes):
L3490: def _find_adapter(registry: Mapping[type, _AdapterT], ob: object) -> _AdapterT:
L3501: def ensure_directory(path: StrOrBytesPath):
L3507: def _bypass_ensure_directory(path):
L3520: def split_sections(s: _NestedStr) -> Iterator[tuple[str | None, list[str]]]:
L3546: def _mkstemp(*args, **kw):
L3564: class PkgResourcesDeprecationWarning(Warning):
L3577: def _read_utf8_with_fallback(file: str, fallback_encoding=_LOCALE_ENCODING) -> str:
L3606: def _call_aside(f, *args, **kwargs):
L3612: def _initialize(g=globals()):
L3624: def _initialize_master_working_set():

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
controller.py**

```

L39: def parse_uri(uri: str) -> tuple[str, str, str, str, str]:
L50: class CacheController:
L53: def __init__(
L66: def _urlnorm(cls, uri: str) -> str:
L86: def cache_url(cls, uri: str) -> str:
L89: def parse_cache_control(self, headers: Mapping[str, str]) -> dict[str, int | None]:
L143: def _load_from_cache(self, request: PreparedRequest) -> HTTPResponse | None:
L169: def cached_request(self, request: PreparedRequest) -> HTTPResponse | Literal[False]:
L279: def conditional_headers(self, request: PreparedRequest) -> dict[str, str]:
L294: def _cache_set(
L324: def cache_response(
L471: def update_cached_response(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
_cmd.py**

```

L22: def setup_logging() -> None:
L28: def get_session() -> requests.Session:
L40: def get_args() -> Namespace:
L46: def main() -> None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
adapter.py**

```

L26: class CacheControlAdapter(HTTPAdapter):
L29: def __init__(
L50: def send(
L80: def build_response( # type: ignore[override]
L137: def _update_chunk_length(
L165: def close(self) -> None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/f
ilewrapper.py**

```

L15: class CallbackFileWrapper:
L34: def __init__(
L41: def __getattr__(self, name: str) -> Any:
L53: def __is_fp_closed(self) -> bool:
L71: def _close(self) -> None:
L99: def read(self, amt: int | None = None) -> bytes:
L110: def _safe_read(self, amt: int) -> bytes:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
cache.py**

```

L19: class BaseCache:
L20: def get(self, key: str) -> bytes | None:
L23: def set(
L28: def delete(self, key: str) -> None:
L31: def close(self) -> None:
L35: class DictCache(BaseCache):
L36: def __init__(self, init_dict: MutableMapping[str, bytes] | None = None) -> None:
L40: def get(self, key: str) -> bytes | None:
L43: def set(
L49: def delete(self, key: str) -> None:
L55: class SeparateBodyBaseCache(BaseCache):
L68: def set_body(self, key: str, body: bytes) -> None:
L71: def get_body(self, key: str) -> IO[bytes] | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/wrapper.py

```
L20: def CacheControl(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/heuristics.py

```
L18: def expire_after(delta: timedelta, date: datetime | None = None) -> datetime:
L23: def datetime_to_header(dt: datetime) -> str:
L27: class BaseHeuristic:
L28: def warning(self, response: HTTPResponse) -> str | None:
L39: def update_headers(self, response: HTTPResponse) -> dict[str, str]:
L48: def apply(self, response: HTTPResponse) -> HTTPResponse:
L60: class OneDayCache(BaseHeuristic):
L66: def update_headers(self, response: HTTPResponse) -> dict[str, str]:
L80: class ExpiresAfter(BaseHeuristic):
L85: def __init__(self, **kw: Any) -> None:
L88: def update_headers(self, response: HTTPResponse) -> dict[str, str]:
L92: def warning(self, response: HTTPResponse) -> str | None:
L97: class LastModified(BaseHeuristic):
L124: def update_headers(self, resp: HTTPResponse) -> dict[str, str]:
L156: def warning(self, resp: HTTPResponse) -> str | None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/serialize.py

```
L17: class Serializer:
L20: def dumps(
L62: def serialize(self, data: dict[str, Any]) -> bytes:
L65: def loads(
L83: def prepare_response(
L135: def _loads_v4(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/caches/file_cache.py

```
L22: class _FileCacheMixin:
L25: def __init__(
```

```

L55: def encode(x: str) -> str:
L58: def _fn(self, name: str) -> str:
L65: def get(self, key: str) -> bytes | None:
L74: def set(
L80: def _write(self, path: str, data: bytes) -> None:
L98: def _delete(self, key: str, suffix: str) -> None:
L107: class FileCache(_FileCacheMixin, BaseCache):
L113: def delete(self, key: str) -> None:
L117: class SeparateBodyFileCache(_FileCacheMixin, SeparateBodyBaseCache):
L123: def get_body(self, key: str) -> IO[bytes] | None:
L130: def set_body(self, key: str, body: bytes) -> None:
L134: def delete(self, key: str) -> None:
L139: def url_to_file_path(url: str, filecache: FileCache) -> str:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
caches/redis_cache.py**

```

L16: class RedisCache(BaseCache):
L17: def __init__(self, conn: Redis[bytes]) -> None:
L20: def get(self, key: str) -> bytes | None:
L23: def set(
L37: def delete(self, key: str) -> None:
L40: def clear(self) -> None:
L46: def close(self) -> None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/compat
.py**

```

L30: def quote(s):
L93: class CertificateError(ValueError):
L96: def _dnsname_match(dn, hostname, max_wildcards=1):
L145: def match_hostname(cert, hostname):
L192: class Container(object):
L197: def __init__(self, **kwargs):
L205: def which(cmd, mode=os.F_OK | os.X_OK, path=None):
L219: def _access_check(fn, mode):
L277: class ZipExtFile(BaseZipExtFile):
L279: def __init__(self, base):
L282: def __enter__(self):
L285: def __exit__(self, *exc_info):
L289: class ZipFile(BaseZipFile):
L291: def __enter__(self):
L294: def __exit__(self, *exc_info):
L298: def open(self, *args, **kwargs):

```

```

L307: def python_implementation():
L325: def callable(obj):
L345: def fsencode(filename):
L354: def fsdecode(filename):
L371: def _get_normal_name(orig_enc):
L382: def detect_encoding(readline):
L407: def read_or_stop():
L413: def find_cookie(line):
L494: def _recursive_repr(fillvalue='...'):
L500: def decorating_function(user_function):
L503: def wrapper(self):
L524: class ChainMap(MutableMapping):
L537: def __init__(self, *maps):
L544: def __missing__(self, key):
L547: def __getitem__(self, key):
L557: def get(self, key, default=None):
L560: def __len__(self):
L564: def __iter__(self):
L567: def __contains__(self, key):
L570: def __bool__(self):
L574: def __repr__(self):
L579: def fromkeys(cls, iterable, *args):
L583: def copy(self):
L589: def new_child(self): # like Django's Context.push()
L594: def parents(self): # like Django's Context.pop()
L598: def __setitem__(self, key, value):
L601: def __delitem__(self, key):
L608: def popitem(self):
L615: def pop(self, key, *args):
L623: def clear(self):
L632: def cache_from_source(path, debug_override=None):
L659: class OrderedDict(dict):
L672: def __init__(self, *args, **kwargs):
L689: def __setitem__(self, key, value, dict_setitem=dict.__setitem__):
L699: def __delitem__(self, key, dict_delitem=dict.__delitem__):
L708: def __iter__(self):
L716: def __reversed__(self):
L724: def clear(self):
L736: def popitem(self, last=True):
L761: def keys(self):
L765: def values(self):
L769: def items(self):
L773: def iterkeys(self):
L777: def itervalues(self):
L782: def iteritems(self):
L787: def update(*args, **kwargs):
L822: def pop(self, key, default=__marker):
L835: def setdefault(self, key, default=None):
L842: def __repr__(self, _repr_running=None):
L857: def __reduce__(self):
L867: def copy(self):

```

```

L872: def fromkeys(cls, iterable, value=None):
L882: def __eq__(self, other):
L892: def __ne__(self, other):
L897: def viewkeys(self):
L901: def viewvalues(self):
L905: def viewitems(self):
L915: def valid_ident(s):
L930: class ConvertingDict(dict):
L933: def __getitem__(self, key):
L945: def get(self, key, default=None):
L957: def pop(self, key, default=None):
L967: class ConvertingList(list):
L970: def __getitem__(self, key):
L982: def pop(self, idx=-1):
L991: class ConvertingTuple(tuple):
L994: def __getitem__(self, key):
L1004: class BaseConfigurator(object):
L1024: def __init__(self, config):
L1028: def resolve(self, s):
L1051: def ext_convert(self, value):
L1055: def cfg_convert(self, value):
L1090: def convert(self, value):
L1119: def configure_custom(self, config):
L1133: def as_tuple(self, value):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/__init__
.py**

```

L12: class DistlibException(Exception):
L20: class NullHandler(logging.Handler):
L22: def handle(self, record):
L25: def emit(self, record):
L28: def createLock(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/scripts.
py**

```

L71: def enquote_executable(executable):
L91: class ScriptMaker(object):
L100: def __init__(self, source_dir, target_dir, add_launchers=True, dry_run=False,
fileop=None):
L114: def _get_alternate_executable(self, executable, options):
L123: def _is_shell(self, executable):
L135: def _fix_jython_executable(self, executable):

```

```

L147: def _build_shebang(self, executable, post_interp):
L183: def _get_shebang(self, encoding, post_interp=b'', options=None):
L249: def _get_script_text(self, entry):
L255: def get_manifest(self, exename):
L259: def _write_script(self, names, shebang, script_bytes, filenames, ext):
L316: def get_script_filenames(self, name):
L326: def _make_script(self, entry, filenames, options=None):
L342: def _copy_script(self, script, filenames):
L393: def dry_run(self):
L397: def dry_run(self, value):
L404: def _get_launcher(self, kind):
L419: def make(self, specification, options=None):
L438: def make_multiple(self, specifications, options=None):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/resourc
es.py**

```

L27: class ResourceCache(Cache):
L28: def __init__(self, base=None):
L34: def is_stale(self, resource, path):
L45: def get(self, resource):
L71: class ResourceBase(object):
L72: def __init__(self, finder, name):
L77: class Resource(ResourceBase):
L85: def as_stream(self):
L95: def file_path(self):
L102: def bytes(self):
L106: def size(self):
L110: class ResourceContainer(ResourceBase):
L114: def resources(self):
L118: class ResourceFinder(object):
L128: def __init__(self, module):
L133: def _adjust_path(self, path):
L136: def _make_path(self, resource_name):
L148: def _find(self, path):
L151: def get_cache_info(self, resource):
L154: def find(self, resource_name):
L166: def get_stream(self, resource):
L169: def get_bytes(self, resource):
L173: def get_size(self, resource):
L176: def get_resources(self, resource):
L177: def allowed(f):
L182: def is_container(self, resource):
L187: def iterator(self, resource_name):
L208: class ZipResourceFinder(ResourceFinder):
L212: def __init__(self, module):
L223: def _adjust_path(self, path):

```

```

L226: def _find(self, path):
L244: def get_cache_info(self, resource):
L249: def get_bytes(self, resource):
L252: def get_stream(self, resource):
L255: def get_size(self, resource):
L259: def get_resources(self, resource):
L274: def _is_directory(self, path):
L306: def register_finder(loader, finder_maker):
L313: def finder(package):
L341: def finder_for_path(path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/util.py

```

L54: def parse_marker(marker_string):
L64: def marker_var(remaining):
L100: def marker_expr(remaining):
L119: def marker_and(remaining):
L130: def marker(remaining):
L144: def parse_requirement(req):
L196: def get_versions(ver_remaining):
L268: def get_resources_dests(resources_root, rules):
L271: def get_rel_path(root, path):
L294: def in_venv():
L304: def get_executable():
L322: def proceed(prompt, allowed_chars, error_prompt=None, default=None):
L338: def extract_by_key(d, keys):
L348: def read_exports(stream):
L368: def read_stream(cp, stream):
L395: def write_exports(exports, stream):
L415: def tempdir():
L424: def chdir(d):
L434: def socket_timeout(seconds=15):
L443: class cached_property(object):
L445: def __init__(self, func):
L450: def __get__(self, obj, cls=None):
L459: def convert_path(pathname):
L486: class FileOperator(object):
L488: def __init__(self, dry_run=False):
L493: def _init_record(self):
L498: def record_as_written(self, path):
L502: def newer(self, source, target):
L521: def copy_file(self, infile, outfile, check=True):
L538: def copy_stream(self, instream, outfile, encoding=None):
L553: def write_binary_file(self, path, data):
L562: def write_text_file(self, path, data, encoding):
L565: def set_mode(self, bits, mask, files):
L579: def ensure_dir(self, path):
L591: def byte_compile(self, path, optimize=False, force=False, prefix=None,

```



```

hashed_invalidation=False):
L610: def ensure_removed(self, path):
L631: def is_writable(self, path):
L643: def commit(self):
L653: def rollback(self):
L672: def resolve(module_name, dotted_path):
L687: class ExportEntry(object):
L689: def __init__(self, name, prefix, suffix, flags):
L696: def value(self):
L699: def __repr__(self): # pragma: no cover
L702: def __eq__(self, other):
L720: def get_export_entry(specification):
L751: def get_cache_base(suffix=None):
L792: def path_to_cache_dir(path, use_abspath=True):
L809: def ensure_slash(s):
L815: def parse_credentials(netloc):
L830: def get_process_umask():
L836: def is_string_sequence(seq):
L852: def split_filename(filename, project_name=None):
L882: def parse_name_and_version(p):
L898: def get_extras(requested, available):
L926: def _get_external_data(url):
L950: def get_project_data(name):
L957: def get_package_data(name, version):
L963: class Cache(object):
L970: def __init__(self, base):
L984: def prefix_to_dir(self, prefix, use_abspath=True):
L990: def clear(self):
L1007: class EventMixin(object):
L1012: def __init__(self):
L1015: def add(self, event, subscriber, append=True):
L1035: def remove(self, event, subscriber):
L1047: def get_subscribers(self, event):
L1054: def publish(self, event, *args, **kwargs):
L1080: class Sequencer(object):
L1082: def __init__(self):
L1087: def add_node(self, node):
L1090: def remove_node(self, node, edges=False):
L1106: def add(self, pred, succ):
L1111: def remove(self, pred, succ):
L1124: def is_step(self, step):
L1127: def get_steps(self, final):
L1153: def strong_connections(self):
L1163: def strongconnect(node):
L1205: def dot(self):
L1224: def unarchive(archive_filename, dest_dir, format=None, check=True):
L1226: def check_path(path):
L1275: def extraction_filter(member, path):
L1292: def zip_dir(directory):
L1313: class Progress(object):
L1316: def __init__(self, minval=0, maxval=100):

```

```

L1324: def update(self, curval):
L1334: def increment(self, incr):
L1338: def start(self):
L1342: def stop(self):
L1348: def maximum(self):
L1352: def percentage(self):
L1362: def format_duration(self, duration):
L1372: def ETA(self):
L1391: def speed(self):
L1412: def iglob(path_glob):
L1423: def _iglob(path_glob):
L1458: class HTTPSConnection(httplib.HTTPSConnection):
L1463: def connect(self):
L1491: class HTTPSHandler(BaseHTTPSHandler):
L1493: def __init__(self, ca_certs, check_domain=True):
L1498: def _conn_maker(self, *args, **kwargs):
L1514: def https_open(self, req):
L1533: class HTTPSOnlyHandler(HTTPSHandler, HTTPHandler):
L1535: def http_open(self, req):
L1543: class Transport(xmlrpclib.Transport):
L1545: def __init__(self, timeout, use_datetime=0):
L1549: def make_connection(self, host):
L1559: class SafeTransport(xmlrpclib.SafeTransport):
L1561: def __init__(self, timeout, use_datetime=0):
L1565: def make_connection(self, host):
L1576: class ServerProxy(xmlrpclib.ServerProxy):
L1578: def __init__(self, uri, **kwargs):
L1601: def _csv_open(fn, mode, **kwargs):
L1612: class CSVBase(object):
L1619: def __enter__(self):
L1622: def __exit__(self, *exc_info):
L1626: class CSVReader(CSVBase):
L1628: def __init__(self, **kwargs):
L1639: def __iter__(self):
L1642: def next(self):
L1653: class CSVWriter(CSVBase):
L1655: def __init__(self, fn, **kwargs):
L1659: def writerow(self, row):
L1675: class Configurator(BaseConfigurator):
L1680: def __init__(self, config, base=None):
L1684: def configure_custom(self, config):
L1686: def convert(o):
L1716: def __getitem__(self, key):
L1722: def inc_convert(self, value):
L1731: class SubprocessMixin(object):
L1736: def __init__(self, verbose=False, progress=None):
L1740: def reader(self, stream, context):
L1761: def run_command(self, cmd, **kwargs):
L1777: def normalize_name(name):
L1794: class PyPIRCFile(object):
L1799: def __init__(self, fn=None, url=None):

```

```

L1805: def read(self):
L1858: def update(self, username, password):
L1871: def _load_pypirc(index):
L1878: def _store_pypirc(index):
L1888: def get_host_platform():
L1978: def get_platform():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_null_file.py

```

L5: class NullFile(IO[str]):
L6: def close(self) -> None:
L9: def isatty(self) -> bool:
L12: def read(self, __n: int = 1) -> str:
L15: def readable(self) -> bool:
L18: def readline(self, __limit: int = 1) -> str:
L21: def readlines(self, __hint: int = 1) -> List[str]:
L24: def seek(self, __offset: int, __whence: int = 1) -> int:
L27: def seekable(self) -> bool:
L30: def tell(self) -> int:
L33: def truncate(self, __size: Optional[int] = 1) -> int:
L36: def writable(self) -> bool:
L39: def writelines(self, __lines: Iterable[str]) -> None:
L42: def __next__(self) -> str:
L45: def __iter__(self) -> Iterator[str]:
L48: def __enter__(self) -> IO[str]:
L51: def __exit__(
L59: def write(self, text: str) -> int:
L62: def flush(self) -> None:
L65: def fileno(self) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/segment.py

```

L35: class ControlType(IntEnum):
L64: class Segment(NamedTuple):
L82: def cell_length(self) -> int:
L91: def __rich_repr__(self) -> Result:
L100: def __bool__(self) -> bool:
L105: def is_control(self) -> bool:
L111: def _split_cells(cls, segment: "Segment", cut: int) -> Tuple["Segment", "Segment"]:
L158: def split_cells(self, cut: int) -> Tuple["Segment", "Segment"]:
L185: def line(cls) -> "Segment":
L190: def apply_style(

```

```

L231: def filter_control(
L250: def split_lines(cls, segments: Iterable["Segment"]) -> Iterable[List["Segment"]]:
L279: def split_and_crop_lines(
L326: def adjust_line_length(
L371: def get_line_length(cls, line: List["Segment"]) -> int:
L384: def get_shape(cls, lines: List[List["Segment"]]) -> Tuple[int, int]:
L398: def set_shape(
L434: def align_top(
L463: def align_bottom(
L492: def align_middle(
L523: def simplify(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L550: def strip_links(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L567: def strip_styles(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L580: def remove_color(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L602: def divide(
L671: class Segments:
L680: def __init__(self, segments: Iterable[Segment], new_lines: bool = False) -> None:
L684: def __rich_console__(
L696: class SegmentLines:
L697: def __init__(self, lines: Iterable[List[Segment]], new_lines: bool = False) -> None:
L708: def __rich_console__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/emoji.py

```

L18: class NoEmoji(Exception):
L22: class Emoji(JupyterMixin):
L27: def __init__(
L53: def replace(cls, text: str) -> str:
L64: def __repr__(self) -> str:
L67: def __str__(self) -> str:
L70: def __rich_console__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/styled.py

```

L11: class Styled:
L19: def __init__(self, renderable: "RenderableType", style: "StyleType") -> None:
L23: def __rich_console__(
L31: def __rich_measure__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_log_render.py

```
L14: class LogRender:
L15: def __init__(
L32: def __call__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/constrain.py

```
L10: class Constrain(JupyterMixin):
L18: def __init__(self, renderable: "RenderableType", width: Optional[int] = 80) -> None:
L22: def __rich_console__(
L31: def __rich_measure__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/tree.py

```
L14: class Tree(JupyterMixin):
L37: def __init__(
L55: def add(
L86: def __rich_console__(
L101: def make_guide(index: int, style: Style) -> Segment:
L176: def __rich_measure__(
L223: class Segment(NamedTuple):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/protocol.py

```
L10: def is_renderable(check_object: Any) -> bool:
L19: def rich_cast(renderable: object) -> "RenderableType":
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/syntax.py

```
L124: class SyntaxTheme(ABC):
L128: def get_style_for_token(self, token_type: TokenType) -> Style:
L133: def get_background_style(self) -> Style:
L138: class PygmentsSyntaxTheme(SyntaxTheme):
L141: def __init__(self, theme: Union[str, Type[PygmentsStyle]]) -> None:
L154: def get_style_for_token(self, token_type: TokenType) -> Style:
L176: def get_background_style(self) -> Style:
L180: class ANSISyntaxTheme(SyntaxTheme):
```

```

L183: def __init__(self, style_map: Dict[TokenType, Style]) -> None:
L189: def get_style_for_token(self, token_type: TokenType) -> Style:
L209: def get_background_style(self) -> Style:
L216: class _SyntaxHighlightRange(NamedTuple):
L229: class PaddingProperty:
L232: def __get__(self, obj: Syntax, objtype: Type[Syntax]) -> Tuple[int, int, int, int]:
L236: def __set__(self, obj: Syntax, padding: PaddingDimensions) -> None:
L240: class Syntax(JupyterMixin):
L265: def get_theme(cls, name: Union[str, SyntaxTheme]) -> SyntaxTheme:
L276: def __init__(
L317: def from_path(
L380: def guess_lexer(cls, path: str, code: Optional[str] = None) -> str:
L421: def _get_base_style(self) -> Style:
L426: def _get_token_color(self, token_type: TokenType) -> Optional[Color]:
L439: def lexer(self) -> Optional[Lexer]:
L458: def default_lexer(self) -> Lexer:
L467: def highlight(
L505: def line_tokenize() -> Iterable[Tuple[Any, str]]:
L514: def tokens_to_spans() -> Iterable[Tuple[str, Optional[Style]]]:
L552: def stylize_range(
L573: def _get_line_numbers_color(self, blend: float = 0.3) -> Color:
L589: def _numbers_column_width(self) -> int:
L599: def _get_number_styles(self, console: Console) -> Tuple[Style, Style, Style]:
L622: def __rich_measure__(
L640: def __rich_console__(
L649: def _get_syntax(
L787: def _apply_stylized_ranges(self, text: Text) -> None:
L820: def _process_code(self, code: str) -> Tuple[bool, str]:
L841: def _get_code_index_for_syntax_position(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_extension
n.py**

```

L4: def load_ipython_extension(ip: Any) -> None: # pragma: no cover

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/control.py

```

L48: class Control:
L58: def __init__(self, *codes: Union[ControlType, ControlCode]) -> None:
L69: def bell(cls) -> "Control":
L74: def home(cls) -> "Control":
L79: def move(cls, x: int = 0, y: int = 0) -> "Control":
L91: def get_codes() -> Iterable[ControlCode]:
L108: def move_to_column(cls, x: int, y: int = 0) -> "Control":

```

```

L132: def move_to(cls, x: int, y: int) -> "Control":
L145: def clear(cls) -> "Control":
L150: def show_cursor(cls, show: bool) -> "Control":
L155: def alt_screen(cls, enable: bool) -> "Control":
L163: def title(cls, title: str) -> "Control":
L171: def __str__(self) -> str:
L174: def __rich_console__(
L181: def strip_control_codes(
L195: def escape_control_codes(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/status.py

```

L11: class Status(JupyterMixin):
L23: def __init__(
L45: def renderable(self) -> Spinner:
L49: def console(self) -> "Console":
L53: def update(
L85: def start(self) -> None:
L89: def stop(self) -> None:
L93: def __rich__(self) -> RenderableType:
L96: def __enter__(self) -> "Status":
L100: def __exit__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/color_triplet.py

```

L4: class ColorTriplet(NamedTuple):
L15: def hex(self) -> str:
L21: def rgb(self) -> str:
L31: def normalized(self) -> Tuple[float, float, float]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress.py

```

L64: class _TrackThread(Thread):
L67: def __init__(self, progress: "Progress", task_id: "TaskID", update_period: float):
L76: def run(self) -> None:
L90: def __enter__(self) -> "_TrackThread":
L94: def __exit__(
L104: def track(
L182: class _Reader(RawIOBase, BinaryIO):

```

```

L185: def __init__(
L198: def __enter__(self) -> "_Reader":
L202: def __exit__(
L210: def __iter__(self) -> BinaryIO:
L213: def __next__(self) -> bytes:
L219: def closed(self) -> bool:
L222: def fileno(self) -> int:
L225: def isatty(self) -> bool:
L229: def mode(self) -> str:
L233: def name(self) -> str:
L236: def readable(self) -> bool:
L239: def seekable(self) -> bool:
L242: def writable(self) -> bool:
L245: def read(self, size: int = -1) -> bytes:
L250: def readinto(self, b: Union[bytearray, memoryview, mmap]): # type:
ignore[no-untyped-def, override]
L255: def readline(self, size: int = -1) -> bytes: # type: ignore[override]
L260: def readlines(self, hint: int = -1) -> List[bytes]:
L265: def close(self) -> None:
L270: def seek(self, offset: int, whence: int = 0) -> int:
L275: def tell(self) -> int:
L278: def write(self, s: Any) -> int:
L281: def writelines(self, lines: Iterable[Any]) -> None:
L285: class _ReadContext(ContextManager[_I], Generic[_I]):
L288: def __init__(self, progress: "Progress", reader: _I) -> None:
L292: def __enter__(self) -> _I:
L296: def __exit__(
L306: def wrap_file(
L372: def open(
L397: def open(
L421: def open(
L507: class ProgressColumn(ABC):
L512: def __init__(self, table_column: Optional[Column] = None) -> None:
L517: def get_table_column(self) -> Column:
L521: def __call__(self, task: "Task") -> RenderableType:
L545: def render(self, task: "Task") -> RenderableType:
L549: class RenderableColumn(ProgressColumn):
L556: def __init__(
L562: def render(self, task: "Task") -> RenderableType:
L566: class SpinnerColumn(ProgressColumn):
L576: def __init__(
L592: def set_spinner(
L607: def render(self, task: "Task") -> RenderableType:
L616: class TextColumn(ProgressColumn):
L619: def __init__(
L635: def render(self, task: "Task") -> Text:
L646: class BarColumn(ProgressColumn):
L657: def __init__(
L673: def render(self, task: "Task") -> ProgressBar:
L688: class TimeElapsedColumn(ProgressColumn):
L691: def render(self, task: "Task") -> Text:

```



```

L700: class TaskProgressColumn(TextColumn):
L714: def __init__(
L737: def render_speed(cls, speed: Optional[float]) -> Text:
L756: def render(self, task: "Task") -> Text:
L772: class TimeRemainingColumn(ProgressColumn):
L783: def __init__(
L793: def render(self, task: "Task") -> Text:
L820: class FileSizeColumn(ProgressColumn):
L823: def render(self, task: "Task") -> Text:
L829: class TotalFileSizeColumn(ProgressColumn):
L832: def render(self, task: "Task") -> Text:
L838: class MofNCompleteColumn(ProgressColumn):
L850: def __init__(self, separator: str = "/", table_column: Optional[Column] = None):
L854: def render(self, task: "Task") -> Text:
L865: class DownloadColumn(ProgressColumn):
L872: def __init__(
L878: def render(self, task: "Task") -> Text:
L914: class TransferSpeedColumn(ProgressColumn):
L917: def render(self, task: "Task") -> Text:
L926: class ProgressSample(NamedTuple):
L936: class Task:
L983: def get_time(self) -> float:
L988: def started(self) -> bool:
L993: def remaining(self) -> Optional[float]:
L1000: def elapsed(self) -> Optional[float]:
L1009: def finished(self) -> bool:
L1014: def percentage(self) -> float:
L1023: def speed(self) -> Optional[float]:
L1041: def time_remaining(self) -> Optional[float]:
L1054: def _reset(self) -> None:
L1061: class Progress(JupyterMixin):
L1077: def __init__(
L1114: def get_default_columns(cls) -> Tuple[ProgressColumn, ...]:
L1145: def console(self) -> Console:
L1149: def tasks(self) -> List[Task]:
L1155: def task_ids(self) -> List[TaskID]:
L1161: def finished(self) -> bool:
L1168: def start(self) -> None:
L1173: def stop(self) -> None:
L1179: def __enter__(self) -> Self:
L1183: def __exit__(
L1191: def track(
L1236: def wrap_file(
L1279: def open(
L1295: def open(
L1310: def open(
L1387: def start_task(self, task_id: TaskID) -> None:
L1401: def stop_task(self, task_id: TaskID) -> None:
L1416: def update(
L1477: def reset(
L1516: def advance(self, task_id: TaskID, advance: float = 1) -> None:

```

```

L1546: def refresh(self) -> None:
L1551: def get_renderable(self) -> RenderableType:
L1556: def get_renderables(self) -> Iterable[RenderableType]:
L1561: def make_tasks_table(self, tasks: Iterable[Task]) -> Table:
L1594: def __rich__(self) -> RenderableType:
L1599: def add_task(
L1642: def remove_task(self, task_id: TaskID) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/cells.py

```

L34: def cached_cell_len(text: str) -> int:
L51: def cell_len(text: str, _cell_len: Callable[[str], int] = cached_cell_len) -> int:
L68: def get_character_cell_size(character: str) -> int:
L96: def set_cell_size(text: str, total: int) -> str:
L131: def chop_cells(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/prompt.py

```

L11: class PromptError(Exception):
L15: class InvalidResponse(PromptError):
L23: def __init__(self, message: TextType) -> None:
L26: def __rich__(self) -> TextType:
L30: class PromptBase(Generic[PromptType]):
L54: def __init__(
L80: def ask(
L97: def ask(
L112: def ask(
L151: def render_default(self, default: DefaultType) -> Text:
L162: def make_prompt(self, default: DefaultType) -> Text:
L194: def get_input(
L213: def check_choice(self, value: str) -> bool:
L227: def process_response(self, value: str) -> PromptType:
L258: def on_validate_error(self, value: str, error: InvalidResponse) -> None:
L267: def pre_prompt(self) -> None:
L271: def __call__(self, *, stream: Optional[TextIO] = None) -> PromptType:
L275: def __call__(
L280: def __call__(self, *, default: Any = ..., stream: Optional[TextIO] = None) -> Any:
L304: class Prompt(PromptBase[str]):
L316: class IntPrompt(PromptBase[int]):
L328: class FloatPrompt(PromptBase[float]):
L340: class Confirm(PromptBase[bool]):
L353: def render_default(self, default: DefaultType) -> Text:
L358: def process_response(self, value: str) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/box.py

```

L10: class Box:
L27: def __init__(self, box: str, *, ascii: bool = False) -> None:
L61: def __repr__(self) -> str:
L64: def __str__(self) -> str:
L67: def substitute(self, options: "ConsoleOptions", safe: bool = True) -> "Box":
L85: def get_plain_headed_box(self) -> "Box":
L95: def get_top(self, widths: Iterable[int]) -> str:
L115: def get_row(
L164: def get_bottom(self, widths: Iterable[int]) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/scope.py

```

L14: def render_scope(
L41: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:
L75: def test(foo: float, bar: float) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_emoji_replace.py

```

L12: def _emoji_replace(
L23: def do_replace(match: Match[str]) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/console.py

```

L79: class NoChange:
L109: class ConsoleDimensions(NamedTuple):
L119: class ConsoleOptions:
L149: def ascii_only(self) -> bool:
L153: def copy(self) -> "ConsoleOptions":
L163: def update(
L200: def update_width(self, width: int) -> "ConsoleOptions":
L213: def update_height(self, height: int) -> "ConsoleOptions":
L226: def reset_height(self) -> "ConsoleOptions":
L236: def update_dimensions(self, width: int, height: int) -> "ConsoleOptions":
L253: class RichCast(Protocol):
L256: def __rich__(

```

```

L263: class ConsoleRenderable(Protocol):
L266: def __rich_console__(
L282: class CaptureError(Exception):
L286: class NewLine:
L289: def __init__(self, count: int = 1) -> None:
L292: def __rich_console__(
L298: class ScreenUpdate:
L301: def __init__(self, lines: List[List[Segment]], x: int, y: int) -> None:
L306: def __rich_console__(
L316: class Capture:
L324: def __init__(self, console: "Console") -> None:
L328: def __enter__(self) -> "Capture":
L332: def __exit__(
L340: def get(self) -> str:
L349: class ThemeContext:
L352: def __init__(self, console: "Console", theme: Theme, inherit: bool = True) -> None:
L357: def __enter__(self) -> "ThemeContext":
L361: def __exit__(
L370: class PagerContext:
L373: def __init__(
L385: def __enter__(self) -> "PagerContext":
L389: def __exit__(
L409: class ScreenContext:
L412: def __init__(
L420: def update(
L438: def __enter__(self) -> "ScreenContext":
L444: def __exit__(
L456: class Group:
L464: def __init__(self, *renderables: "RenderableType", fit: bool = True) -> None:
L470: def renderables(self) -> List["RenderableType"]:
L475: def __rich_measure__(
L483: def __rich_console__(
L489: def group(fit: bool = True) -> Callable[..., Callable[..., Group]]:
L496: def decorator(
L502: def _replace(*args: Any, **kwargs: Any) -> Group:
L511: def _is_jupyter() -> bool: # pragma: no cover
L542: class ConsoleThreadLocals(threading.local):
L550: class RenderHook(ABC):
L554: def process_renderables(
L572: def get_windows_console_features() -> "WindowsConsoleFeatures": # pragma: no cover
L582: def detect_legacy_windows() -> bool:
L587: class Console:
L625: def __init__(
L759: def __repr__(self) -> str:
L763: def file(self) -> IO[str]:
L772: def file(self, new_file: IO[str]) -> None:
L777: def _buffer(self) -> List[Segment]:
L782: def _buffer_index(self) -> int:
L787: def _buffer_index(self, value: int) -> None:
L791: def _theme_stack(self) -> ThemeStack:
L795: def _detect_color_system(self) -> Optional[ColorSystem]:

```

```

L819: def _enter_buffer(self) -> None:
L823: def _exit_buffer(self) -> None:
L828: def set_live(self, live: "Live") -> bool:
L844: def clear_live(self) -> None:
L849: def push_render_hook(self, hook: RenderHook) -> None:
L858: def pop_render_hook(self) -> None:
L863: def __enter__(self) -> "Console":
L868: def __exit__(self, exc_type: Any, exc_value: Any, traceback: Any) -> None:
L872: def begin_capture(self) -> None:
L876: def end_capture(self) -> str:
L887: def push_theme(self, theme: Theme, *, inherit: bool = True) -> None:
L898: def pop_theme(self) -> None:
L902: def use_theme(self, theme: Theme, *, inherit: bool = True) -> ThemeContext:
L915: def color_system(self) -> Optional[str]:
L928: def encoding(self) -> str:
L937: def is_terminal(self) -> bool:
L985: def is_dumb_terminal(self) -> bool:
L997: def options(self) -> ConsoleOptions:
L1011: def size(self) -> ConsoleDimensions:
L1052: def size(self, new_size: Tuple[int, int]) -> None:
L1063: def width(self) -> int:
L1072: def width(self, width: int) -> None:
L1081: def height(self) -> int:
L1090: def height(self, height: int) -> None:
L1098: def bell(self) -> None:
L1102: def capture(self) -> Capture:
L1119: def pager(
L1142: def line(self, count: int = 1) -> None:
L1152: def clear(self, home: bool = True) -> None:
L1163: def status(
L1196: def show_cursor(self, show: bool = True) -> bool:
L1207: def set_alt_screen(self, enable: bool = True) -> bool:
L1229: def is_alt_screen(self) -> bool:
L1237: def set_window_title(self, title: str) -> bool:
L1269: def screen(
L1283: def measure(
L1300: def render(
L1351: def render_lines(
L1415: def render_str(
L1476: def get_style(
L1506: def _collect_renderables(
L1539: def align_append(renderable: RenderableType) -> None:
L1548: def check_text() -> None:
L1585: def rule(
L1606: def control(self, *control: Control) -> None:
L1616: def out(
L1648: def print(
L1747: def print_json(
L1808: def update_screen(
L1842: def update_screen_lines(
L1862: def print_exception(

```

```

L1898: def _caller_frame_info(
L1932: def log(
L2013: def on_broken_pipe(self) -> None:
L2027: def _check_buffer(self) -> None:
L2042: def _write_buffer(self) -> None:
L2115: def _render_buffer(self, buffer: Iterable[Segment]) -> str:
L2139: def input(
L2173: def export_text(self, *, clear: bool = True, styles: bool = False) -> str:
L2205: def save_text(self, path: str, *, clear: bool = True, styles: bool = False) -> None:
L2219: def export_html(
L2294: def save_html(
L2325: def export_svg(
L2356: def get_svg_style(style: Style) -> str:
L2416: def escape_text(text: str) -> str:
L2420: def make_tag(
L2425: def stringify(value: object) -> str:
L2576: def save_svg(
L2615: def _svg_hash(svg_main_code: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/jupyter.py

```

L18: class JupyterRenderable:
L21: def __init__(self, html: str, text: str) -> None:
L25: def _repr_mimebundle_(
L36: class JupyterMixin:
L41: def _repr_mimebundle_(
L59: def _render_segments(segments: Iterable[Segment]) -> str:
L60: def escape(text: str) -> str:
L84: def display(segments: Iterable[Segment], text: str) -> None:
L98: def print(*args: Any, **kwargs: Any) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/abc.py

```

L4: class RichRenderable(ABC):
L16: def __subclasshook__(cls, other: type) -> bool:
L28: class Foo:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress_bar.py

```

L18: class ProgressBar(JupyterMixin):
L33: def __init__(

```

```

L57: def __repr__(self) -> str:
L61: def percentage_completed(self) -> Optional[float]:
L70: def _get_pulse_segments(
L116: def update(self, completed: float, total: Optional[float] = None) -> None:
L126: def _render_pulse(
L156: def __rich_console__(
L200: def __rich_measure__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/json.py

```

L9: class JSON:
L25: def __init__(
L54: def from_data(
L101: def __rich__(self) -> Text:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/__main__.py

```

L18: class ColorBox:
L19: def __rich_console__(
L33: def __rich_measure__(
L39: def make_test_card() -> Table:
L90: def comparison(renderable1: RenderableType, renderable2: RenderableType) -> Table:
L157: def iter_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/measure.py

```

L11: class Measurement(NamedTuple):
L20: def span(self) -> int:
L24: def normalize(self) -> "Measurement":
L34: def with_maximum(self, width: int) -> "Measurement":
L46: def with_minimum(self, width: int) -> "Measurement":
L59: def clamp(
L79: def get(
L125: def measure_renderables(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/text.py

```

L47: class Span(NamedTuple):
L57: def __repr__(self) -> str:
L60: def __bool__(self) -> bool:
L63: def split(self, offset: int) -> Tuple["Span", Optional["Span"]]:
L76: def move(self, offset: int) -> "Span":
L88: def right_crop(self, offset: int) -> "Span":
L102: def extend(self, cells: int) -> "Span":
L118: class Text(JupyterMixin):
L144: def __init__(
L167: def __len__(self) -> int:
L170: def __bool__(self) -> bool:
L173: def __str__(self) -> str:
L176: def __repr__(self) -> str:
L179: def __add__(self, other: Any) -> "Text":
L186: def __eq__(self, other: object) -> bool:
L191: def __contains__(self, other: object) -> bool:
L198: def __getitem__(self, slice: Union[int, slice]) -> "Text":
L199: def get_text_at(offset: int) -> "Text":
L225: def cell_len(self) -> int:
L230: def markup(self) -> str:
L260: def from_markup(
L294: def from_ansi(
L332: def styled(
L357: def assemble(
L403: def plain(self) -> str:
L410: def plain(self, new_text: str) -> None:
L421: def spans(self) -> List[Span]:
L426: def spans(self, spans: List[Span]) -> None:
L430: def blank_copy(self, plain: str = "") -> "Text":
L443: def copy(self) -> "Text":
L457: def stylize(
L483: def stylize_before(
L509: def apply_meta(
L523: def on(self, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Text":
L543: def remove_suffix(self, suffix: str) -> None:
L552: def get_style_at_offset(self, console: "Console", offset: int) -> Style:
L572: def extend_style(self, spaces: int) -> None:
L593: def highlight_regex(
L633: def highlight_words(
L662: def rstrip(self) -> None:
L666: def rstrip_end(self, size: int) -> None:
L680: def set_length(self, new_length: int) -> None:
L689: def __rich_console__(
L708: def __rich_measure__(
L720: def render(self, console: "Console", end: str = "") -> Iterable["Segment"]:
L759: def get_current_style() -> Style:
L779: def join(self, lines: Iterable["Text"]) -> "Text":
L791: def iter_text() -> Iterable["Text"]:
L818: def expand_tabs(self, tab_size: Optional[int] = None) -> None:
L860: def truncate(
L887: def _trim_spans(self) -> None:

```



```

L901: def pad(self, count: int, character: str = " ") -> None:
L918: def pad_left(self, count: int, character: str = " ") -> None:
L934: def pad_right(self, count: int, character: str = " ") -> None:
L945: def align(self, align: AlignMethod, width: int, character: str = " ") -> None:
L965: def append(
L1009: def append_text(self, text: "Text") -> "Text":
L1031: def append_tokens(
L1055: def copy_styles(self, text: "Text") -> None:
L1063: def split(
L1092: def flatten_spans() -> Iterable[int]:
L1107: def divide(self, offsets: Iterable[int]) -> Lines:
L1186: def right_crop(self, amount: int = 1) -> None:
L1202: def wrap(
L1250: def fit(self, width: int) -> Lines:
L1266: def detect_indentation(self) -> int:
L1287: def with_indent_guides(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/live.py

```

L22: class _RefreshThread(Thread):
L25: def __init__(self, live: "Live", refresh_per_second: float) -> None:
L31: def stop(self) -> None:
L34: def run(self) -> None:
L41: class Live(JupyterMixin, RenderHook):
L57: def __init__(
L99: def is_started(self) -> bool:
L103: def get_renderable(self) -> RenderableType:
L111: def start(self, refresh: bool = False) -> None:
L145: def stop(self) -> None:
L179: def __enter__(self) -> Self:
L183: def __exit__(
L191: def _enable_redirect_io(self) -> None:
L201: def _disable_redirect_io(self) -> None:
L211: def renderable(self) -> RenderableType:
L226: def update(self, renderable: RenderableType, *, refresh: bool = False) -> None:
L240: def refresh(self) -> None:
L274: def process_renderables(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/bar.py

```

L17: class Bar(JupyterMixin):
L29: def __init__(
L45: def __repr__(self) -> str:
L48: def __rich_console__(
L86: def __rich_measure__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/logging.py

```

L18: class RichHandler(Handler):
L65: def __init__(
L117: def get_level_text(self, record: LogRecord) -> Text:
L132: def emit(self, record: LogRecord) -> None:
L182: def render_message(self, record: LogRecord, message: str) -> "ConsoleRenderable":
L207: def render(
L283: def divide() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/rule.py

```

L12: class Rule(JupyterMixin):
L23: def __init__(
L46: def __repr__(self) -> str:
L49: def __rich_console__(
L105: def _rule_line(self, chars_len: int, width: int) -> Text:
L111: def __rich_measure__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/pretty.py

```

L60: def _is_attr_object(obj: Any) -> bool:
L65: def _get_attr_fields(obj: Any) -> Sequence["_attr_module.Attribute[Any]"]:
L70: def _is_dataclass_repr(obj: object) -> bool:
L93: def _has_default_namedtuple_repr(obj: object) -> bool:
L113: def _ipy_display_hook(
L161: def _safe_isinstance(
L171: def install(
L200: def display_hook(value: Any) -> None:
L230: class RichFormatter(BaseFormatter): # type: ignore[misc]
L233: def __call__(self, value: Any) -> Any:
L253: class Pretty(JupyterMixin):
L273: def __init__(
L304: def __rich_console__(
L339: def __rich_measure__(
L357: def _get_braces_for_defaultdict(_object: DefaultDict[Any, Any]) -> Tuple[str, str, str]:
L365: def _get_braces_for_deque(_object: Deque[Any]) -> Tuple[str, str, str]:
L375: def _get_braces_for_array(_object: "array[Any]") -> Tuple[str, str, str]:
L398: def is_expandable(obj: Any) -> bool:
L409: class Node:

```

```

L424: def iter_tokens(self) -> Iterable[str]:
L446: def check_length(self, start_length: int, max_length: int) -> bool:
L463: def __str__(self) -> str:
L467: def render(
L494: class _Line:
L507: def expandable(self) -> bool:
L511: def check_length(self, max_length: int) -> bool:
L519: def expand(self, indent_size: int) -> Iterable["_Line"]:
L552: def __str__(self) -> str:
L561: def _is_namedtuple(obj: Any) -> bool:
L580: def traverse(
L601: def to_repr(obj: Any) -> str:
L621: def _traverse(obj: Any, root: bool = False, depth: int = 0) -> Node:
L633: def iter_rich_args(rich_args: Any) -> Iterable[Union[Any, Tuple[str, Any]]]:
L731: def iter_attrs() -> (
L878: def pretty_repr(
L918: def pprint(
L957: class BrokenRepr:
L958: def __repr__(self) -> str:
L964: class StockKeepingUnit(NamedTuple):
L1012: class Thing:
L1013: def __repr__(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/panel.py

```

L17: class Panel(JupyterMixin):
L40: def __init__(
L74: def fit(
L110: def _title(self) -> Optional[Text]:
L126: def _subtitle(self) -> Optional[Text]:
L141: def __rich_console__(
L159: def align_text(
L277: def __rich_measure__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows_renderer.py

```

L7: def legacy_windows_render(buffer: Iterable[Segment], term: LegacyWindowsTerm) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_fileno.py

```

L6: def get_fileno(file_like: IO[str]) -> int | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/palette.py

```

L11: class Palette:
L14: def __init__(self, colors: Sequence[Tuple[int, int, int]]):
L17: def __getitem__(self, number: int) -> ColorTriplet:
L20: def __rich__(self) -> "Table":
L45: def match(self, color: Tuple[int, int, int]) -> int:
L58: def get_color_distance(index: int) -> float:
L83: class ColorBox:
L84: def __rich_console__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/pager.py

```

L5: class Pager(ABC):
L9: def show(self, content: str) -> None:
L17: class SystemPager(Pager):
L20: def _pager(self, content: str) -> Any: # pragma: no cover
L23: def show(self, content: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/repr.py

```

L23: class ReprError(Exception):
L28: def auto(cls: Optional[Type[T]]) -> Type[T]:
L33: def auto(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:
L37: def auto(
L42: def do_replace(cls: Type[T], angular: Optional[bool] = None) -> Type[T]:
L43: def auto_repr(self: T) -> str:
L68: def auto_rich_repr(self: Type[T]) -> Result:
L105: def rich_repr(cls: Optional[Type[T]]) -> Type[T]:
L110: def rich_repr(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:
L114: def rich_repr(
L126: class Foo:
L127: def __rich_repr__(self) -> Result:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/columns.py

```

L16: class Columns(JupyterMixin):
L31: def __init__(

```

```
L54: def add_renderable(self, renderable: RenderableType) -> None:
L62: def __rich_console__(
L86: def iter_renderables(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/ansi.py

```
L20: class _AnsiToken(NamedTuple):
L28: def _ansi_tokenize(ansi_text: str) -> Iterable[_AnsiToken]:
L120: class AnsiDecoder:
L123: def __init__(self) -> None:
L126: def decode(self, terminal_text: str) -> Iterable[Text]:
L138: def decode_line(self, line: str) -> Text:
L224: def read(fd: int) -> bytes:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/live_render.py

```
L14: class LiveRender:
L22: def __init__(
L33: def set_renderable(self, renderable: RenderableType) -> None:
L41: def position_cursor(self) -> Control:
L62: def restore_cursor(self) -> Control:
L76: def __rich_console__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/padding.py

```
L19: class Padding(JupyterMixin):
L33: def __init__(
L47: def indent(cls, renderable: "RenderableType", level: int) -> "Padding":
L61: def unpack(pad: "PaddingDimensions") -> Tuple[int, int, int, int]:
L76: def __repr__(self) -> str:
L79: def __rich_console__(
L125: def __rich_measure__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_timer.py

```
L13: def timer(subject: str = "time") -> Generator[None, None, None]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/align.py

```

L17: class Align(JupyterMixin):
L33: def __init__(
L60: def __repr__(self) -> str:
L64: def left(
L86: def center(
L108: def right(
L129: def __rich_console__(
L147: def generate_segments() -> Iterable[Segment]:
L192: def blank_lines(count: int) -> Iterable[Segment]:
L221: def __rich_measure__(
L228: class VerticalCenter(JupyterMixin):
L240: def __init__(
L248: def __repr__(self) -> str:
L251: def __rich_console__(
L265: def blank_lines(count: int) -> Iterable[Segment]:
L278: def __rich_measure__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/__init__.py

```

L23: def get_console() -> "Console":
L39: def reconfigure(*args: Any, **kwargs: Any) -> None:
L53: def print(
L77: def print_json(
L120: def inspect(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_inspect.py

```

L15: def _first_paragraph(doc: str) -> str:
L21: class Inspect(JupyterMixin):
L37: def __init__(
L64: def _make_title(self, obj: Any) -> Text:
L74: def __rich__(self) -> Panel:
L82: def _get_signature(self, name: str, obj: Any) -> Optional[Text]:
L121: def _render(self) -> Iterable[RenderableType]:
L124: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:
L128: def safe_getattr(attr_name: str) -> Tuple[Any, Any]:
L214: def _get_formatted_doc(self, object_: Any) -> Optional[str]:

```

```

L236: def get_object_types_mro(obj: Union[object, Type[Any]]) -> Tuple[type, ...]:
L245: def get_object_types_mro_as_strings(obj: object) -> Collection[str]:
L258: def is_object_one_of_types(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_loop.py

```

L6: def loop_first(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:
L18: def loop_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:
L31: def loop_first_last(values: Iterable[T]) -> Iterable[Tuple[bool, bool, T]]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/screen.py

```

L18: class Screen:
L28: def __init__(
L40: def __rich_console__(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows
.py**

```

L6: class WindowsConsoleFeatures:
L34: def get_windows_console_features() -> WindowsConsoleFeatures:
L40: def get_windows_console_features() -> WindowsConsoleFeatures:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/highlighte
r.py**

```

L8: def _combine_regex(*regexes: str) -> str:
L17: class Highlighter(ABC):
L20: def __call__(self, text: Union[str, Text]) -> Text:
L42: def highlight(self, text: Text) -> None:
L50: class NullHighlighter(Highlighter):
L57: def highlight(self, text: Text) -> None:
L61: class RegexHighlighter(Highlighter):
L67: def highlight(self, text: Text) -> None:
L80: class ReprHighlighter(RegexHighlighter):
L106: class JSONHighlighter(RegexHighlighter):
L123: def highlight(self, text: Text) -> None:
L143: class ISO8601Highlighter(RegexHighlighter):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_wrap.py

```

L12: def words(text: str) -> Iterable[tuple[int, int, str]]:
L26: def divide_line(text: str, width: int, fold: bool = True) -> list[int]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/spinner.py

```

L13: class Spinner:
L26: def __init__(
L50: def __rich_console__(
L55: def __rich_measure__(
L61: def render(self, time: float) -> "RenderableType":
L95: def update(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/style.py

```

L21: class _Bit:
L26: def __init__(self, bit_no: int) -> None:
L29: def __get__(self, obj: "Style", objtype: Type["Style"]) -> Optional[bool]:
L36: class Style:
L127: def __init__(
L151: def _make_color(color: Union[Color, str]) -> Color:
L204: def null(cls) -> "Style":
L209: def from_color(
L233: def from_meta(cls, meta: Optional[Dict[str, Any]]) -> "Style":
L254: def on(cls, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Style":
L286: def link_id(self) -> str:
L290: def __str__(self) -> str:
L336: def __bool__(self) -> bool:
L340: def _make_ansi_codes(self, color_system: ColorSystem) -> str:
L385: def normalize(cls, style: str) -> str:
L401: def pick_first(cls, *values: Optional[StyleType]) -> StyleType:
L408: def __rich_repr__(self) -> Result:
L427: def __eq__(self, other: Any) -> bool:
L432: def __ne__(self, other: Any) -> bool:
L437: def __hash__(self) -> int:
L444: def color(self) -> Optional[Color]:
L449: def bgcolor(self) -> Optional[Color]:
L454: def link(self) -> Optional[str]:
L459: def transparent_background(self) -> bool:
L464: def background_style(self) -> "Style":

```



```

L469: def meta(self) -> Dict[str, Any]:
L474: def without_color(self) -> "Style":
L494: def parse(cls, style_definition: str) -> "Style":
L560: def get_html_style(self, theme: Optional[TerminalTheme] = None) -> str:
L597: def combine(cls, styles: Iterable["Style"]) -> "Style":
L610: def chain(cls, *styles: "Style") -> "Style":
L622: def copy(self) -> "Style":
L645: def clear_meta_and_links(self) -> "Style":
L667: def update_link(self, link: Optional[str] = None) -> "Style":
L690: def render(
L716: def test(self, text: Optional[str] = None) -> None:
L729: def _add(self, style: Optional["Style"]) -> "Style":
L753: def __add__(self, style: Optional["Style"]) -> "Style":
L761: class StyleStack:
L766: def __init__(self, default_style: "Style") -> None:
L769: def __repr__(self) -> str:
L773: def current(self) -> Style:
L777: def push(self, style: Style) -> None:
L785: def pop(self) -> Style:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/theme.py

```

L8: class Theme:
L18: def __init__(
L31: def config(self) -> str:
L39: def from_file(
L59: def read(
L76: class ThemeStackError(Exception):
L80: class ThemeStack:
L87: def __init__(self, theme: Theme) -> None:
L91: def push_theme(self, theme: Theme, inherit: bool = True) -> None:
L105: def pop_theme(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/terminal_theme.py

```

L9: class TerminalTheme:
L20: def __init__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/layout.py

```

L32: class LayoutRender(NamedTuple):

```

```

L43: class LayoutError(Exception):
L47: class NoSplitter(LayoutError):
L51: class _Placeholder:
L56: def __init__(self, layout: "Layout", style: StyleType = "") -> None:
L60: def __rich_console__(
L80: class Splitter(ABC):
L86: def get_tree_icon(self) -> str:
L90: def divide(
L101: class RowSplitter(Splitter):
L106: def get_tree_icon(self) -> str:
L109: def divide(
L121: class ColumnSplitter(Splitter):
L126: def get_tree_icon(self) -> str:
L129: def divide(
L142: class Layout:
L156: def __init__(
L177: def __rich_repr__(self) -> Result:
L184: def renderable(self) -> RenderableType:
L189: def children(self) -> List["Layout"]:
L194: def map(self) -> RenderMap:
L198: def get(self, name: str) -> Optional["Layout"]:
L216: def __getitem__(self, name: str) -> "Layout":
L223: def tree(self) -> "Tree":
L229: def summary(layout: "Layout") -> Table:
L248: def recurse(tree: "Tree", layout: "Layout") -> None:
L261: def split(
L286: def add_split(self, *layouts: Union["Layout", RenderableType]) -> None:
L299: def split_row(self, *layouts: Union["Layout", RenderableType]) -> None:
L307: def split_column(self, *layouts: Union["Layout", RenderableType]) -> None:
L315: def unsplit(self) -> None:
L319: def update(self, renderable: RenderableType) -> None:
L328: def refresh_screen(self, console: "Console", layout_name: str) -> None:
L345: def _make_region_map(self, width: int, height: int) -> RegionMap:
L366: def render(self, console: Console, options: ConsoleOptions) -> RenderMap:
L395: def __rich_console__(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/diagnose.py

```

L10: def report() -> None: # pragma: no cover

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_pick.py

```

L4: def pick_bool(*values: Optional[bool]) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_win32_console.py

```

L29: class LegacyWindowsError(Exception):
L33: class WindowsCoordinates(NamedTuple):
L44: def from_param(cls, value: "WindowsCoordinates") -> COORD:
L57: class CONSOLE_SCREEN_BUFFER_INFO(Structure):
L67: class CONSOLE_CURSOR_INFO(ctypes.Structure):
L78: def GetStdHandle(handle: int = STDOUT) -> wintypes.HANDLE:
L95: def GetConsoleMode(std_handle: wintypes.HANDLE) -> int:
L128: def FillConsoleOutputCharacter(
L169: def FillConsoleOutputAttribute(
L204: def SetConsoleTextAttribute(
L228: def GetConsoleScreenBufferInfo(
L252: def SetConsoleCursorPosition(
L275: def GetConsoleCursorInfo(
L299: def SetConsoleCursorInfo(
L319: def SetConsoleTitle(title: str) -> bool:
L331: class LegacyWindowsTerm:
L362: def __init__(self, file: "IO[str]") -> None:
L377: def cursor_position(self) -> WindowsCoordinates:
L387: def screen_size(self) -> WindowsCoordinates:
L396: def write_text(self, text: str) -> None:
L405: def write_styled(self, text: str, style: Style) -> None:
L444: def move_cursor_to(self, new_position: WindowsCoordinates) -> None:
L454: def erase_line(self) -> None:
L470: def erase_end_of_line(self) -> None:
L484: def erase_start_of_line(self) -> None:
L493: def move_cursor_up(self) -> None:
L503: def move_cursor_down(self) -> None:
L514: def move_cursor_forward(self) -> None:
L526: def move_cursor_to_column(self, column: int) -> None:
L535: def move_cursor_backward(self) -> None:
L547: def hide_cursor(self) -> None:
L553: def show_cursor(self) -> None:
L559: def set_title(self, title: str) -> None:
L568: def _get_cursor_size(self) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/color.py

```

L21: class ColorSystem(IntEnum):
L29: def __repr__(self) -> str:
L32: def __str__(self) -> str:
L36: class ColorType(IntEnum):
L45: def __repr__(self) -> str:

```

```

L288: class ColorParseError(Exception):
L303: class Color(NamedTuple):
L315: def __rich__(self) -> "Text":
L326: def __rich_repr__(self) -> Result:
L333: def system(self) -> ColorSystem:
L340: def is_system_defined(self) -> bool:
L345: def is_default(self) -> bool:
L349: def get_truecolor(
L381: def from_ansi(cls, number: int) -> "Color":
L397: def from_triplet(cls, triplet: "ColorTriplet") -> "Color":
L409: def from_rgb(cls, red: float, green: float, blue: float) -> "Color":
L423: def default(cls) -> "Color":
L433: def parse(cls, color: str) -> "Color":
L485: def get_ansi_codes(self, foreground: bool = True) -> Tuple[str, ...]:
L513: def downgrade(self, system: ColorSystem) -> "Color":
L571: def parse_rgb_hex(hex_color: str) -> ColorTriplet:
L580: def blend_rgb(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/traceback
.py

```

L55: def _iter_syntax_lines(
L83: def install(
L134: def excepthook(
L159: def ipy_excepthook_closure(ip: Any) -> None: # pragma: no cover
L163: def ipy_show_traceback(*args: Any, **kwargs: Any) -> None:
L169: def ipy_display_traceback(
L215: class Frame:
L225: class _SyntaxError:
L235: class Stack:
L247: class Trace:
L251: class PathHighlighter(RegexHighlighter):
L255: class Traceback:
L286: def __init__(
L340: def from_exception(
L413: def extract(
L454: def safe_str(_object: Any) -> str:
L502: def get_locals(
L603: def __rich_console__(
L635: def render_stack(stack: Stack, last: bool) -> RenderResult:
L706: def _render_syntax_error(self, syntax_error: _SyntaxError) -> RenderResult:
L729: def _guess_lexer(cls, filename: str, code: str) -> str:
L745: def _render_stack(self, stack: Stack) -> RenderResult:
L749: def render_locals(frame: Frame) -> Iterable[ConsoleRenderable]:
L877: def bar(
L883: def foo(a: Any) -> None:
L896: def error() -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/table.py

```

L39: class Column:
L117: def copy(self) -> "Column":
L122: def cells(self) -> Iterable["RenderableType"]:
L127: def flexible(self) -> bool:
L133: class Row:
L143: class _Cell(NamedTuple):
L154: class Table(JupyterMixin):
L189: def __init__(
L254: def grid(
L287: def expand(self) -> bool:
L292: def expand(self, expand: bool) -> None:
L297: def _extra_width(self) -> int:
L307: def row_count(self) -> int:
L311: def get_row_style(self, console: "Console", index: int) -> StyleType:
L321: def __rich_measure__(
L355: def padding(self) -> Tuple[int, int, int, int]:
L360: def padding(self, padding: PaddingDimensions) -> "Table":
L365: def add_column(
L423: def add_row(
L441: def add_cell(column: Column, renderable: "RenderableType") -> None:
L470: def add_section(self) -> None:
L476: def __rich_console__(
L497: def render_annotation(
L523: def _calculate_column_widths(
L588: def _collapse_widths(
L626: def _get_cells(
L641: def get_padding(first_row: bool, last_row: bool) -> Tuple[int, int, int, int]:
L699: def _get_padding_width(self, column_index: int) -> int:
L707: def _measure_column(
L747: def _render(
L839: def align_cell(
L967: def header(text: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/errors.py

```

L1: class ConsoleError(Exception):
L5: class StyleError(Exception):
L9: class StyleSyntaxError(ConsoleError):
L13: class MissingStyle(StyleError):
L17: class StyleStackError(ConsoleError):
L21: class NotRenderableError(ConsoleError):
L25: class MarkupError(ConsoleError):
L29: class LiveError(ConsoleError):

```

```
L33: class NoAltScreen(ConsoleError):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_stack.py

```
L6: class Stack(List[T]):
L10: def top(self) -> T:
L14: def push(self, item: T) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/filesize.py

```
L18: def _to_str(
L43: def pick_unit_and_suffix(size: int, suffixes: List[str], base: int) -> Tuple[int, str]:
L52: def decimal(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/markup.py

```
L20: class Tag(NamedTuple):
L28: def __str__(self) -> str:
L34: def markup(self) -> str:
L48: def escape(
L61: def escape_backslashes(match: Match[str]) -> str:
L73: def _parse(markup: str) -> Iterable[Tuple[int, Optional[str], Optional[Tag]]]:
L106: def render(
L146: def pop_style(style_name: str) -> Tuple[int, Tag]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/region.py

```
L4: class Region(NamedTuple):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/container_s.py

```
L30: class Renderables:
L33: def __init__(
```

```

L40: def __rich_console__(
L46: def __rich_measure__(
L59: def append(self, renderable: "RenderableType") -> None:
L62: def __iter__(self) -> Iterable["RenderableType"]:
L66: class Lines:
L69: def __init__(self, lines: Iterable["Text"] = ()) -> None:
L72: def __repr__(self) -> str:
L75: def __iter__(self) -> Iterator["Text"]:
L79: def __getitem__(self, index: int) -> "Text":
L83: def __getitem__(self, index: slice) -> List["Text"]:
L86: def __getitem__(self, index: Union[slice, int]) -> Union["Text", List["Text"]]:
L89: def __setitem__(self, index: int, value: "Text") -> "Lines":
L93: def __len__(self) -> int:
L96: def __rich_console__(
L102: def append(self, line: "Text") -> None:
L105: def extend(self, lines: Iterable["Text"]) -> None:
L108: def pop(self, index: int = -1) -> "Text":
L111: def justify(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_ratio.py

```

L6: class Edge(Protocol):
L14: def ratio_resolve(total: int, edges: Sequence[Edge]) -> List[int]:
L75: def ratio_reduce(
L107: def ratio_distribute(
L147: class E:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/file_proxy.py

```

L11: class FileProxy(io.TextIOBase):
L14: def __init__(self, console: "Console", file: IO[str]) -> None:
L21: def rich_proxied_file(self) -> IO[str]:
L25: def __getattr__(self, name: str) -> Any:
L28: def write(self, text: str) -> int:
L50: def flush(self) -> None:
L56: def fileno(self) -> int:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/certifi/core.py

```

L10: def exit_cacert_ctx() -> None:
L21: def where() -> str:
L46: def contents() -> str:

```

```
L56: def where() -> str:
L82: def contents() -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic_core/__init__.py

```
L74: class ErrorDetails(_TypedDict):
L100: class InitErrorDetails(_TypedDict):
L114: class ErrorTypeInfo(_TypedDict):
L133: class MultiHostHost(_TypedDict):
L162: class Configuration(BaseModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic_core/core_schema.py

```
L43: class CoreConfig(TypedDict, total=False):
L133: class SerializationInfo(Protocol[ContextT]):
L137: def include(self) -> IncExCall:
L142: def exclude(self) -> IncExCall:
L147: def context(self) -> ContextT:
L152: def mode(self) -> Literal['python', 'json'] | str:
L157: def by_alias(self) -> bool:
L162: def exclude_unset(self) -> bool:
L167: def exclude_defaults(self) -> bool:
L172: def exclude_none(self) -> bool:
L177: def exclude_computed_fields(self) -> bool:
L182: def serialize_as_any(self) -> bool:
L187: def polymorphic_serialization(self) -> bool | None:
L192: def round_trip(self) -> bool:
L196: def mode_is_json(self) -> bool: ...
L198: def __str__(self) -> str: ...
L200: def __repr__(self) -> str: ...
L203: class FieldSerializationInfo(SerializationInfo[ContextT], Protocol):
L207: def field_name(self) -> str:
L212: class ValidationInfo(Protocol[ContextT]):
L216: def context(self) -> ContextT:
L221: def config(self) -> CoreConfig | None:
L226: def mode(self) -> Literal['python', 'json']:
L231: def data(self) -> dict[str, Any]:
L236: def field_name(self) -> str | None:
L270: class SimpleSerSchema(TypedDict, total=False):
L274: def simple_ser_schema(type: ExpectedSerializationTypes) -> SimpleSerSchema:
L310: class PlainSerializerFunctionSerSchema(TypedDict, total=False):
L319: def plain_serializer_function_ser_schema(
L351: class SerializerFunctionWrapHandler(Protocol): # pragma: no cover
```



```

L352: def __call__(self, input_value: Any, index_key: int | str | None = None, /) -> Any: ...
L371: class WrapSerializerFunctionSerSchema(TypedDict, total=False):
L381: def wrap_serializer_function_ser_schema(
L416: class FormatSerSchema(TypedDict, total=False):
L422: def format_ser_schema(formatting_string: str, *, when_used: WhenUsed =
'json-unless-none') -> FormatSerSchema:
L436: class ToStringSerSchema(TypedDict, total=False):
L441: def to_string_ser_schema(*, when_used: WhenUsed = 'json-unless-none') ->
ToStringSerSchema:
L455: class ModelSerSchema(TypedDict, total=False):
L461: def model_ser_schema(cls: type[Any], schema: CoreSchema) -> ModelSerSchema:
L482: class InvalidSchema(TypedDict, total=False):
L491: def invalid_schema(ref: str | None = None, metadata: dict[str, Any] | None = None) ->
InvalidSchema:
L503: class ComputedField(TypedDict, total=False):
L512: def computed_field(
L539: class AnySchema(TypedDict, total=False):
L546: def any_schema(
L568: class NoneSchema(TypedDict, total=False):
L575: def none_schema(
L597: class BoolSchema(TypedDict, total=False):
L605: def bool_schema(
L631: class IntSchema(TypedDict, total=False):
L644: def int_schema(
L692: class FloatSchema(TypedDict, total=False):
L706: def float_schema(
L757: class DecimalSchema(TypedDict, total=False):
L773: def decimal_schema(
L831: class ComplexSchema(TypedDict, total=False):
L839: def complex_schema(
L873: class StringSchema(TypedDict, total=False):
L889: def str_schema(
L951: class BytesSchema(TypedDict, total=False):
L961: def bytes_schema(
L1000: class DateSchema(TypedDict, total=False):
L1016: def date_schema(
L1068: class TimeSchema(TypedDict, total=False):
L1082: def time_schema(
L1134: class DatetimeSchema(TypedDict, total=False):
L1152: def datetime_schema(
L1212: class TimedeltaSchema(TypedDict, total=False):
L1225: def timedelta_schema(
L1274: class LiteralSchema(TypedDict, total=False):
L1282: def literal_schema(
L1309: class EnumSchema(TypedDict, total=False):
L1321: def enum_schema(
L1339: class Color(Enum):
L1372: class MissingSentinelSchema(TypedDict, total=False):
L1378: def missing_sentinel_schema(
L1395: class IsInstanceSchema(TypedDict, total=False):
L1404: def is_instance_schema(

```

```

L1418: class A:
L1438: class IsSubclassSchema(TypedDict, total=False):
L1447: def is_subclass_schema(
L1461: class A:
L1464: class B(A):
L1484: class CallableSchema(TypedDict, total=False):
L1491: def callable_schema(
L1513: class UuidSchema(TypedDict, total=False):
L1522: def uuid_schema(
L1535: class IncExSeqSerSchema(TypedDict, total=False):
L1541: def filter_seq_schema(*, include: set[int] | None = None, exclude: set[int] | None =
None) -> IncExSeqSerSchema:
L1548: class ListSchema(TypedDict, total=False):
L1560: def list_schema(
L1606: def tuple_positional_schema(
L1655: def tuple_variable_schema(
L1699: class TupleSchema(TypedDict, total=False):
L1712: def tuple_schema(
L1763: class SetSchema(TypedDict, total=False):
L1775: def set_schema(
L1822: class FrozenSetSchema(TypedDict, total=False):
L1834: def frozenset_schema(
L1881: class GeneratorSchema(TypedDict, total=False):
L1891: def generator_schema(
L1907: def gen() -> Iterator[int]:
L1941: class IncExDictSerSchema(TypedDict, total=False):
L1947: def filter_dict_schema(*, include: IncExDict | None = None, exclude: IncExDict | None
= None) -> IncExDictSerSchema:
L1954: class DictSchema(TypedDict, total=False):
L1967: def dict_schema(
L2021: class NoInfoValidatorFunctionSchema(TypedDict):
L2030: class WithInfoValidatorFunctionSchema(TypedDict, total=False):
L2039: class _ValidatorFunctionSchema(TypedDict, total=False):
L2047: class BeforeValidatorFunctionSchema(_ValidatorFunctionSchema, total=False):
L2052: def no_info_before_validator_function(
L2067: def fn(v: bytes) -> str:
L2098: def with_info_before_validator_function(
L2115: def fn(v: bytes, info: core_schema.ValidationInfo) -> str:
L2156: class AfterValidatorFunctionSchema(_ValidatorFunctionSchema, total=False):
L2160: def no_info_after_validator_function(
L2175: def fn(v: str) -> str:
L2204: def with_info_after_validator_function(
L2220: def fn(v: str, info: core_schema.ValidationInfo) -> str:
L2259: class ValidatorFunctionWrapHandler(Protocol):
L2260: def __call__(self, input_value: Any, outer_location: str | int | None = None, /) ->
Any: # pragma: no cover
L2268: class NoInfoWrapValidatorFunctionSchema(TypedDict):
L2277: class WithInfoWrapValidatorFunctionSchema(TypedDict, total=False):
L2286: class WrapValidatorFunctionSchema(TypedDict, total=False):
L2296: def no_info_wrap_validator_function(
L2313: def fn(

```

```

L2345: def with_info_wrap_validator_function(
L2363: def fn(
L2404: class PlainValidatorFunctionSchema(TypedDict, total=False):
L2413: def no_info_plain_validator_function(
L2427: def fn(v: str) -> str:
L2453: def with_info_plain_validator_function(
L2468: def fn(v: str, info: core_schema.ValidationInfo) -> str:
L2502: class WithDefaultSchema(TypedDict, total=False):
L2516: def with_default_schema(
L2572: class NullableSchema(TypedDict, total=False):
L2581: def nullable_schema(
L2612: class UnionSchema(TypedDict, total=False):
L2627: def union_schema(
L2678: class TaggedUnionSchema(TypedDict, total=False):
L2692: def tagged_union_schema(
L2775: class ChainSchema(TypedDict, total=False):
L2783: def chain_schema(
L2796: def fn(v: str, info: core_schema.ValidationInfo) -> str:
L2817: class LaxOrStrictSchema(TypedDict, total=False):
L2827: def lax_or_strict_schema(
L2842: def fn(v: str, info: core_schema.ValidationInfo) -> str:
L2881: class JsonOrPythonSchema(TypedDict, total=False):
L2890: def json_or_python_schema(
L2938: class TypedDictField(TypedDict, total=False):
L2949: def typed_dict_field(
L2989: class TypedDictSchema(TypedDict, total=False):
L3006: def typed_dict_schema(
L3029: class MyTypedDict(TypedDict):
L3070: class ModelField(TypedDict, total=False):
L3081: def model_field(
L3121: class ModelFieldsSchema(TypedDict, total=False):
L3136: def model_fields_schema(
L3193: class ModelSchema(TypedDict, total=False):
L3211: def model_schema(
L3239: class MyModel:
L3296: class DataclassField(TypedDict, total=False):
L3311: def dataclass_field(
L3368: class DataclassArgsSchema(TypedDict, total=False):
L3380: def dataclass_args_schema(
L3431: class DataclassSchema(TypedDict, total=False):
L3449: def dataclass_schema(
L3508: class ArgumentsParameter(TypedDict, total=False):
L3515: def arguments_parameter(
L3548: class ArgumentsSchema(TypedDict, total=False):
L3561: def arguments_schema(
L3617: class ArgumentsV3Parameter(TypedDict, total=False):
L3631: def arguments_v3_parameter(
L3669: class ArgumentsV3Schema(TypedDict, total=False):
L3680: def arguments_v3_schema(
L3731: class CallSchema(TypedDict, total=False):
L3742: def call_schema(

```

```

L3796: class CustomErrorSchema(TypedDict, total=False):
L3807: def custom_error_schema(
L3853: class JsonSchema(TypedDict, total=False):
L3861: def json_schema(
L3881: class MyModel:
L3907: class UrlSchema(TypedDict, total=False):
L3921: def url_schema(
L3976: class MultiHostUrlSchema(TypedDict, total=False):
L3990: def multi_host_url_schema(
L4045: class DefinitionsSchema(TypedDict, total=False):
L4053: def definitions_schema(schema: CoreSchema, definitions: list[CoreSchema]) ->
DefinitionsSchema:
L4076: class DefinitionReferenceSchema(TypedDict, total=False):
L4084: def definition_reference_schema(
L4349: def _dict_not_none(**kwargs: Any) -> Any:
L4353: def iter_union_choices(union_schema: UnionSchema) -> Generator[CoreSchema]:
L4368: def field_before_validator_function(function: WithInfoValidatorFunction, field_name:
str, schema: CoreSchema, **kwargs):
L4377: def general_before_validator_function(*args, **kwargs):
L4386: def field_after_validator_function(function: WithInfoValidatorFunction, field_name:
str, schema: CoreSchema, **kwargs):
L4395: def general_after_validator_function(*args, **kwargs):
L4404: def field_wrap_validator_function(
L4415: def general_wrap_validator_function(*args, **kwargs):
L4424: def field_plain_validator_function(function: WithInfoValidatorFunction, field_name:
str, **kwargs):
L4433: def general_plain_validator_function(*args, **kwargs):
L4452: def __getattr__(attr_name: str) -> object:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/functional_validators.py

```

L29: class AfterValidator:
L46: class Model(BaseModel):
L74: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:
L85: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:
L90: class BeforeValidator:
L109: class Model(BaseModel):
L126: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:
L149: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:
L157: class PlainValidator:
L179: def validate(v: object) -> int:
L190: class Model(BaseModel):

```

```

L207: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:
L249: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:
L257: class WrapValidator:
L274: def validate_timestamp(v, handler):
L286: class Model(BaseModel):
L299: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:
L324: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:
L333: class _OnlyValueValidatorClsMethod(Protocol):
L334: def __call__(self, cls: Any, value: Any, /) -> Any: ...
L336: class _V2ValidatorClsMethod(Protocol):
L337: def __call__(self, cls: Any, value: Any, info: core_schema.ValidationInfo[Any], /) ->
Any: ...
L339: class _OnlyValueWrapValidatorClsMethod(Protocol):
L340: def __call__(self, cls: Any, value: Any, handler:
core_schema.ValidatorFunctionWrapHandler, /) -> Any: ...
L342: class _V2WrapValidatorClsMethod(Protocol):
L343: def __call__(
L378: def field_validator(
L389: def field_validator(
L400: def field_validator(
L409: def field_validator( # noqa: D417
L432: class Model(BaseModel):
L437: def ensure_foobar(cls, v: Any):
L497: def dec(
L521: class ModelWrapValidatorHandler(core_schema.ValidatorFunctionWrapHandler,
Protocol[_ModelTypeCo]):
L524: def __call__( # noqa: D102
L533: class ModelWrapValidatorWithoutInfo(Protocol[_ModelType]):
L538: def __call__( # noqa: D102
L550: class ModelWrapValidator(Protocol[_ModelType]):
L553: def __call__( # noqa: D102
L566: class FreeModelBeforeValidatorWithoutInfo(Protocol):
L571: def __call__( # noqa: D102
L581: class ModelBeforeValidatorWithoutInfo(Protocol):
L586: def __call__( # noqa: D102
L597: class FreeModelBeforeValidator(Protocol):
L600: def __call__( # noqa: D102
L611: class ModelBeforeValidator(Protocol):
L614: def __call__( # noqa: D102
L642: def model_validator(
L651: def model_validator(
L660: def model_validator(
L668: def model_validator(
L683: class Square(BaseModel):
L688: def verify_square(self) -> Self:
L717: def dec(f: Any) -> _decorators.PydanticDescriptorProxy[Any]:
L746: class InstanceOf:

```

```

L753: class Foo:
L756: class Bar(BaseModel):
L780: def __class_getitem__(cls, item: AnyType) -> AnyType:
L784: def __get_pydantic_core_schema__(cls, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:
L811: class SkipValidation:
L823: def __class_getitem__(cls, item: Any) -> Any:
L827: def __get_pydantic_core_schema__(cls, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:
L845: class ValidateAs:
L859: class MyCls:
L860: def __init__(self, a: int) -> None:
L863: def __repr__(self) -> str:
L866: class Model(BaseModel):
L880: def __init__(self, from_type: type[_FromTypeT], /, instantiation_hook:
Callable[[[_FromTypeT], Any]] -> None:
L884: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/alias_generators.py

```

L12: def to_pascal(snake: str) -> str:
L25: def to_camel(snake: str) -> str:
L43: def to_snake(camel: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_migration.py

```

L251: def getattr_migration(module: str) -> Callable[[str], Any]:
L264: def wrapper(name: str) -> object:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/mypy.py

```

L111: def plugin(version: str) -> type[Plugin]:
L126: class PydanticPlugin(Plugin):
L129: def __init__(self, options: Options) -> None:
L134: def get_base_class_hook(self, fullname: str) -> Callable[[ClassDefContext], None] |
None:
L143: def get_metaclass_hook(self, fullname: str) -> Callable[[ClassDefContext], None] |
None:
L149: def get_method_hook(self, fullname: str) -> Callable[[MethodContext], Type] | None:
L155: def get_dynamic_class_hook(self, fullname: str) -> Callable[[DynamicClassDefContext],
None] | None:

```

```

L161: def report_config_data(self, ctx: ReportConfigContext) -> dict[str, Any]:
L168: def _pydantic_model_class_maker_callback(self, ctx: ClassDefContext) -> None:
L172: def _pydantic_model_metaclass_marker_callback(self, ctx: ClassDefContext) -> None:
L185: def _pydantic_create_model_callback(self, ctx: DynamicClassDefContext) -> None:
L213: class PydanticPluginConfig:
L235: def __init__(self, options: Options) -> None:
L254: def to_data(self) -> dict[str, Any]:
L259: def from_attributes_callback(ctx: MethodContext) -> Type:
L285: class PydanticModelField:
L288: def __init__(
L312: def to_argument(
L341: def expand_type(
L386: def to_var(
L401: def serialize(self) -> JsonDict:
L417: def deserialize(cls, info: TypeInfo, data: JsonDict, api:
SemanticAnalyzerPluginInterface) -> PydanticModelField:
L423: def expand_typevar_from_subtype(self, sub_type: TypeInfo, api:
SemanticAnalyzerPluginInterface) -> None:
L432: class PydanticModelClassVar:
L441: def __init__(self, name):
L445: def deserialize(cls, data: JsonDict) -> PydanticModelClassVar:
L450: def serialize(self) -> JsonDict:
L457: class PydanticModelTransformer:
L475: def __init__(
L488: def transform(self) -> bool:
L524: def adjust_decorator_signatures(self) -> None:
L551: def collect_config(self) -> ModelConfigData: # noqa: C901 (ignore complexity)
L627: def collect_fields_and_class_vars(
L695: def _get_assignment_statements_from_if_statement(self, stmt: IfStmt) ->
Iterator[AssignmentStmt]:
L702: def _get_assignment_statements_from_block(self, block: Block) ->
Iterator[AssignmentStmt]:
L709: def collect_field_or_class_var_from_stmt( # noqa C901
L846: def _infer_dataclass_attr_init_type(self, sym: SymbolTableNode, name: str, context:
Context) -> Type | None:
L884: def add_initializer(
L941: def add_model_construct_method(
L981: def set_frozen(self, fields: list[PydanticModelField], api:
SemanticAnalyzerPluginInterface, frozen: bool) -> None:
L1006: def get_config_update(self, name: str, arg: Expression, lax_extra: bool = False) ->
ModelConfigData | None:
L1042: def get_has_default(stmt: AssignmentStmt) -> bool:
L1064: def get_strict(stmt: AssignmentStmt) -> bool | None:
L1080: def get_alias_info(stmt: AssignmentStmt) -> tuple[str | None, bool]:
L1110: def is_field_frozen(stmt: AssignmentStmt) -> bool:
L1134: def get_field_arguments(
L1166: def should_init_forbid_extra(self, fields: list[PydanticModelField], config:
ModelConfigData) -> bool:
L1180: def is_dynamic_alias_present(fields: list[PydanticModelField], has_alias_generator:
bool) -> bool:
L1194: class ChangeExplicitTypeOfAny(TypeTranslator):

```

```

L1197: def __init__(self, type_of_any: int) -> None:
L1201: def visit_any(self, t: AnyType) -> Type: # noqa: D102
L1208: class ModelConfigData:
L1211: def __init__(
L1231: def get_values_dict(self) -> dict[str, Any]:
L1238: def update(self, config: ModelConfigData | None) -> None:
L1245: def setdefault(self, key: str, value: Any) -> None:
L1251: def is_root_model(info: TypeInfo) -> bool:
L1265: def error_from_attributes(model_name: str, api: CheckerPluginInterface, context:
Context) -> None:
L1270: def error_invalid_config_value(name: str, api: SemanticAnalyzerPluginInterface,
context: Context) -> None:
L1275: def error_required_dynamic_aliases(api: SemanticAnalyzerPluginInterface, context:
Context) -> None:
L1283: def error_unexpected_behavior(
L1294: def error_untyped_fields(api: SemanticAnalyzerPluginInterface, context: Context) ->
None:
L1299: def error_extra_fields_on_root_model(api: CheckerPluginInterface, context: Context) ->
None:
L1304: def add_method(
L1392: def parse_toml(config_file: str) -> dict[str, Any] | None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/fields.py

```

L50: class _FromFieldInfoInputs(TypedDict, total=False):
L92: class _FieldInfoInputs(_FromFieldInfoInputs, total=False):
L98: class _FieldInfoAsDict(TypedDict, closed=True):
L106: class FieldInfo(_repr.Representation):
L228: def __init__(self, **kwargs: Unpack[_FieldInfoInputs]) -> None:
L291: def from_field(default: Any = PydanticUndefined, **kwargs:
Unpack[_FromFieldInfoInputs]) -> FieldInfo:
L310: class MyModel(pydantic.BaseModel):
L319: def from_annotation(annotation: type[Any], *, _source: AnnotationSource =
AnnotationSource.ANY) -> FieldInfo:
L327: class MyModel(pydantic.BaseModel):
L341: class MyModel(pydantic.BaseModel):
L379: def from_annotated_attribute(
L393: class MyModel(pydantic.BaseModel):
L480: def _construct(cls, metadata: list[Any], **attr_overrides: Any) -> Self:
L486: class Model(BaseModel):
L577: def merge_field_infos(*field_infos: FieldInfo, **overrides: Any) -> FieldInfo:
L643: def _from_dataclass_field(dc_field: DataclassField[Any]) -> FieldInfo:
L671: def _collect_metadata(kwargs: dict[str, Any]) -> list[Any]:
L700: def deprecation_message(self) -> str | None:
L709: def default_factory_takes_validated_data(self) -> bool | None:
L718: def get_default(
L723: def get_default(self, *, call_default_factory: Literal[False] = ...) -> Any: ...
L725: def get_default(self, *, call_default_factory: bool = False, validated_data: dict[str,
Any] | None = None) -> Any:

```



```

L746: def is_required(self) -> bool:
L754: def rebuild_annotation(self) -> Any:
L773: def apply_typevars_map(
L801: def asdict(self) -> _FieldInfoAsDict:
L816: def _copy(self) -> Self:
L835: def __repr_args__(self) -> ReprArgs:
L872: class _EmptyKwargs(TypedDict):
L925: def Field(
L965: def Field(
L1005: def Field(
L1048: def Field( # pyright: ignore[reportOverlappingOverload]
L1088: def Field(
L1131: def Field( # No default set
L1169: def Field( # noqa: C901
L1401: class ModelPrivateAttr(_repr.Representation):
L1417: def __init__(
L1432: def __getattr__(self, item: str) -> Any:
L1441: def __set_name__(self, cls: type[Any], name: str) -> None:
L1451: def default_factory_takes_validated_data(self) -> bool | None:
L1460: def get_default(
L1465: def get_default(self, *, call_default_factory: Literal[False] = ...) -> Any: ...
L1467: def get_default(self, *, call_default_factory: bool = False, validated_data: dict[str,
Any] | None = None) -> Any:
L1488: def __eq__(self, other: Any) -> bool:
L1498: def PrivateAttr(
L1504: def PrivateAttr(
L1510: def PrivateAttr(
L1514: def PrivateAttr(
L1553: class ComputedFieldInfo:
L1587: def __copy__(self) -> Self:
L1606: def deprecation_message(self) -> str | None:
L1614: def _update_from_config(self, config_wrapper: ConfigWrapper, name: str) -> None:
L1622: def _apply_alias_generator(self, alias_generator: Callable[[str], str] |
AliasGenerator, name: str) -> None:
L1654: def _wrapped_property_is_private(property_: cached_property | property) -> bool: #
type: ignore
L1672: def computed_field(func: PropertyT, /) -> PropertyT: ...
L1676: def computed_field(
L1692: def computed_field(
L1718: class Rectangle(BaseModel):
L1724: def area(self) -> int:
L1748: class Square(BaseModel):
L1752: def area(self) -> float: # converted to a `property` by `computed_field`
L1756: def area(self, new_area: float) -> None:
L1760: def random_number(self) -> int:
L1786: class Parent(BaseModel):
L1791: class Child(Parent):
L1794: def a(self) -> str:
L1811: class Model(BaseModel):
L1816: def _private_cached_property(self) -> int:
L1821: def _private_property(self) -> int:

```

```
L1854: def dec(f: Any) -> Any:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/json_schema.py

```
L103: class PydanticJsonSchemaWarning(UserWarning):
L140: class _DefinitionsRemapping:
L145: def from_prioritized_choices(
L196: def remap_defs_ref(self, ref: DefsRef) -> DefsRef:
L199: def remap_json_ref(self, ref: JsonRef) -> JsonRef:
L202: def remap_json_schema(self, schema: Any) -> Any:
L225: class GenerateJsonSchema:
L273: def __init__(
L316: def _config(self) -> _config.ConfigWrapper:
L320: def mode(self) -> JsonSchemaMode:
L326: def build_schema_type_to_method(
L352: def generate_definitions(
L401: def generate(self, schema: CoreSchema, mode: JsonSchemaMode = 'validation') ->
JsonSchemaValue:
L450: def generate_inner(self, schema: CoreSchemaOrField) -> JsonSchemaValue: # noqa: C901
L472: def populate_defs(core_schema: CoreSchema, json_schema: JsonSchemaValue) ->
JsonSchemaValue:
L486: def handler_func(schema_or_field: CoreSchemaOrField) -> JsonSchemaValue:
L531: def js_updates_handler_func(
L542: def js_extra_handler_func(
L558: def new_handler_func(
L576: def new_handler_func(
L590: def sort(self, value: JsonSchemaValue, parent_key: str | None = None) ->
JsonSchemaValue:
L604: def _sort_recursive(self, value: Any, parent_key: str | None = None) -> Any:
L622: def invalid_schema(self, schema: core_schema.InvalidSchema) -> JsonSchemaValue:
L627: def any_schema(self, schema: core_schema.AnySchema) -> JsonSchemaValue:
L638: def none_schema(self, schema: core_schema.NoneSchema) -> JsonSchemaValue:
L649: def bool_schema(self, schema: core_schema.BoolSchema) -> JsonSchemaValue:
L660: def int_schema(self, schema: core_schema.IntSchema) -> JsonSchemaValue:
L674: def float_schema(self, schema: core_schema.FloatSchema) -> JsonSchemaValue:
L688: def decimal_schema(self, schema: core_schema.DecimalSchema) -> JsonSchemaValue:
L698: def get_decimal_pattern(schema: core_schema.DecimalSchema) -> str:
L763: def str_schema(self, schema: core_schema.StringSchema) -> JsonSchemaValue:
L779: def bytes_schema(self, schema: core_schema.BytesSchema) -> JsonSchemaValue:
L792: def date_schema(self, schema: core_schema.DateSchema) -> JsonSchemaValue:
L803: def time_schema(self, schema: core_schema.TimeSchema) -> JsonSchemaValue:
L814: def datetime_schema(self, schema: core_schema.DatetimeSchema) -> JsonSchemaValue:
L825: def timedelta_schema(self, schema: core_schema.TimedeltaSchema) -> JsonSchemaValue:
L838: def literal_schema(self, schema: core_schema.LiteralSchema) -> JsonSchemaValue:
L870: def missing_sentinel_schema(self, schema: core_schema.MissingSentinelSchema) ->
JsonSchemaValue:
L881: def enum_schema(self, schema: core_schema.EnumSchema) -> JsonSchemaValue:
L917: def is_instance_schema(self, schema: core_schema.IsInstanceSchema) -> JsonSchemaValue:
```

```

L930: def is_subclass_schema(self, schema: core_schema.IsSubclassSchema) -> JsonSchemaValue:
L944: def callable_schema(self, schema: core_schema.CallableSchema) -> JsonSchemaValue:
L957: def list_schema(self, schema: core_schema.ListSchema) -> JsonSchemaValue:
L973: def tuple_positional_schema(self, schema: core_schema.TupleSchema) -> JsonSchemaValue:
L984: def tuple_variable_schema(self, schema: core_schema.TupleSchema) -> JsonSchemaValue:
L993: def tuple_schema(self, schema: core_schema.TupleSchema) -> JsonSchemaValue:
L1028: def set_schema(self, schema: core_schema.SetSchema) -> JsonSchemaValue:
L1039: def frozenset_schema(self, schema: core_schema.FrozenSetSchema) -> JsonSchemaValue:
L1050: def _common_set_schema(self, schema: core_schema.SetSchema |
core_schema.FrozenSetSchema) -> JsonSchemaValue:
L1056: def generator_schema(self, schema: core_schema.GeneratorSchema) -> JsonSchemaValue:
L1070: def dict_schema(self, schema: core_schema.DictSchema) -> JsonSchemaValue:
L1118: def function_before_schema(self, schema: core_schema.BeforeValidatorFunctionSchema) ->
JsonSchemaValue:
L1132: def function_after_schema(self, schema: core_schema.AfterValidatorFunctionSchema) ->
JsonSchemaValue:
L1143: def function_plain_schema(self, schema: core_schema.PlainValidatorFunctionSchema) ->
JsonSchemaValue:
L1159: def function_wrap_schema(self, schema: core_schema.WrapValidatorFunctionSchema) ->
JsonSchemaValue:
L1173: def default_schema(self, schema: core_schema.WithDefaultSchema) -> JsonSchemaValue:
L1236: def get_default_value(self, schema: core_schema.WithDefaultSchema) -> Any:
L1251: def nullable_schema(self, schema: core_schema.NullableSchema) -> JsonSchemaValue:
L1268: def union_schema(self, schema: core_schema.UnionSchema) -> JsonSchemaValue:
L1290: def get_union_of_schemas(self, schemas: list[JsonSchemaValue]) -> JsonSchemaValue:
L1326: def tagged_union_schema(self, schema: core_schema.TaggedUnionSchema) ->
JsonSchemaValue:
L1363: def _extract_discriminator(
L1408: def chain_schema(self, schema: core_schema.ChainSchema) -> JsonSchemaValue:
L1423: def lax_or_strict_schema(self, schema: core_schema.LaxOrStrictSchema) ->
JsonSchemaValue:
L1442: def json_or_python_schema(self, schema: core_schema.JsonOrPythonSchema) ->
JsonSchemaValue:
L1457: def typed_dict_schema(self, schema: core_schema.TypedDictSchema) -> JsonSchemaValue:
L1509: def _name_required_computed_fields(
L1514: def _named_required_fields_schema(
L1539: def _get_alias_name(self, field: CoreSchemaField, name: str) -> str:
L1560: def typed_dict_field_schema(self, schema: core_schema.TypedDictField) ->
JsonSchemaValue:
L1571: def dataclass_field_schema(self, schema: core_schema.DataclassField) ->
JsonSchemaValue:
L1582: def model_field_schema(self, schema: core_schema.ModelField) -> JsonSchemaValue:
L1593: def computed_field_schema(self, schema: core_schema.ComputedField) -> JsonSchemaValue:
L1604: def model_schema(self, schema: core_schema.ModelSchema) -> JsonSchemaValue:
L1625: def _update_class_schema(self, json_schema: JsonSchemaValue, cls: type[Any], config:
ConfigDict) -> None:
L1706: def resolve_ref_schema(self, json_schema: JsonSchemaValue) -> JsonSchemaValue:
L1726: def model_fields_schema(self, schema: core_schema.ModelFieldsSchema) ->
JsonSchemaValue:
L1749: def field_is_present(self, field: CoreSchemaField) -> bool:
L1767: def field_is_required(

```

```

L1798: def dataclass_args_schema(self, schema: core_schema.DataclassArgsSchema) ->
JsonSchemaValue:
L1816: def dataclass_schema(self, schema: core_schema.DataclassSchema) -> JsonSchemaValue:
L1836: def arguments_schema(self, schema: core_schema.ArgumentsSchema) -> JsonSchemaValue:
L1872: def kw_arguments_schema(
L1910: def p_arguments_schema(
L1953: def get_argument_name(self, argument: core_schema.ArgumentsParameter |
core_schema.ArgumentsV3Parameter) -> str:
L1971: def arguments_v3_schema(self, schema: core_schema.ArgumentsV3Schema) ->
JsonSchemaValue:
L2010: def call_schema(self, schema: core_schema.CallSchema) -> JsonSchemaValue:
L2021: def custom_error_schema(self, schema: core_schema.CustomErrorSchema) ->
JsonSchemaValue:
L2032: def json_schema(self, schema: core_schema.JsonSchema) -> JsonSchemaValue:
L2049: def url_schema(self, schema: core_schema.UrlSchema) -> JsonSchemaValue:
L2062: def multi_host_url_schema(self, schema: core_schema.MultiHostUrlSchema) ->
JsonSchemaValue:
L2076: def uuid_schema(self, schema: core_schema.UuidSchema) -> JsonSchemaValue:
L2087: def definitions_schema(self, schema: core_schema.DefinitionsSchema) ->
JsonSchemaValue:
L2105: def definition_ref_schema(self, schema: core_schema.DefinitionReferenceSchema) ->
JsonSchemaValue:
L2118: def ser_schema(
L2143: def complex_schema(self, schema: core_schema.ComplexSchema) -> JsonSchemaValue:
L2161: def get_title_from_name(self, name: str) -> str:
L2172: def field_title_should_be_set(self, schema: CoreSchemaOrField) -> bool:
L2207: def normalize_name(self, name: str) -> str:
L2218: def get_defs_ref(self, core_mode_ref: CoreModeRef) -> DefsRef:
L2266: def get_cache_defs_ref_schema(self, core_ref: CoreRef) -> tuple[DefsRef,
JsonSchemaValue]:
L2294: def handle_ref_overrides(self, json_schema: JsonSchemaValue) -> JsonSchemaValue:
L2321: def get_schema_from_definitions(self, json_ref: JsonRef) -> JsonSchemaValue | None:
L2332: def encode_default(self, dft: Any) -> Any:
L2361: def update_with_validations(
L2376: class ValidationsMapping:
L2408: def get_flattened_anyof(self, schemas: list[JsonSchemaValue]) -> JsonSchemaValue:
L2420: def get_json_ref_counts(self, json_schema: JsonSchemaValue) -> dict[JsonRef, int]:
L2424: def _add_json_refs(schema: Any) -> None:
L2456: def handle_invalid_for_json_schema(self, schema: CoreSchemaOrField, error_info: str)
-> JsonSchemaValue:
L2459: def emit_warning(self, kind: JsonSchemaWarningKind, detail: str) -> None:
L2465: def render_warning_message(self, kind: JsonSchemaWarningKind, detail: str) -> str |
None:
L2486: def _build_definitions_remapping(self) -> _DefinitionsRemapping:
L2497: def _garbage_collect_definitions(self, schema: JsonSchemaValue) -> None:
L2518: def model_json_schema(
L2566: def models_json_schema(
L2631: def _deduplicate_schemas(schemas: Iterable[JsonDict]) -> list[JsonDict]:
L2635: def _make_json_hashable(value: JsonValue) -> _HashableJsonValue:
L2645: class WithJsonSchema:
L2668: class Model(BaseModel):

```

```

L2687: class Model(BaseModel):
L2706: def __get_pydantic_json_schema__(
L2717: def __hash__(self) -> int:
L2721: class Examples:
L2733: def __init__(
L2738: def __init__(self, examples: list[Any], mode: Literal['validation', 'serialization'] |
None = None) -> None: ...
L2740: def __init__(
L2752: def __get_pydantic_json_schema__(
L2791: def __hash__(self) -> int:
L2795: def _get_all_json_refs(item: Any) -> set[JsonRef]:
L2830: class SkipJsonSchema:
L2844: class Model(BaseModel):
L2878: def __class_getitem__(cls, item: AnyType) -> AnyType:
L2881: def __get_pydantic_json_schema__(
L2886: def __hash__(self) -> int:
L2890: def _get_typed_dict_config(cls: type[Any] | None) -> ConfigDict:
L2899: def _get_ser_schema_for_default_value(schema: CoreSchema) ->
core_schema.PlainSerializerFunctionSerSchema | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/functional_serializers.py

```

L120: class PlainSerializer:
L135: class StudentModel(BaseModel):
L154: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:
L190: class WrapSerializer:
L102: class EventDatetime(BaseModel):
L106: def convert_to_utc(value: Any, handler, info) -> dict[str, datetime]:
L119: class EventModel(BaseModel):
L157: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:
L209: def field_serializer(
L221: def field_serializer(
L232: def field_serializer( # noqa: D417
L252: class StudentModel(BaseModel):
L257: def serialize_courses_in_order(self, courses: set[str]):
L305: def dec(f: FieldSerializer) -> _decorators.PydanticDescriptorProxy[Any]:
L346: def model_serializer(f: _ModelPlainSerializerT, /) -> _ModelPlainSerializerT: ...
L350: def model_serializer(
L356: def model_serializer(
L364: def model_serializer(
L387: class TemperatureModel(BaseModel):
L392: def serialize_model(self):
L428: def dec(f: ModelSerializer) -> _decorators.PydanticDescriptorProxy[Any]:
L450: class SerializeAsAny:

```

```
L456: def __class_getitem__(cls, item: Any) -> Any:
L459: def __get_pydantic_core_schema__(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/networks.py

```
L71: class UrlConstraints:
L92: def __hash__(self) -> int:
L106: def defined_constraints(self) -> dict[str, Any]:
L110: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:
L126: class _BaseUrl:
L130: def __init__(self, url: str | _CoreUrl | _BaseUrl) -> None:
L134: def scheme(self) -> str:
L142: def username(self) -> str | None:
L150: def password(self) -> str | None:
L158: def host(self) -> str | None:
L166: def unicode_host(self) -> str | None:
L177: def port(self) -> int | None:
L185: def path(self) -> str | None:
L193: def query(self) -> str | None:
L200: def query_params(self) -> list[tuple[str, str]]:
L208: def fragment(self) -> str | None:
L215: def unicode_string(self) -> str:
L223: def encoded_string(self) -> str:
L230: def __str__(self) -> str:
L234: def __repr__(self) -> str:
L237: def __deepcopy__(self, memo: dict) -> Self:
L240: def __eq__(self, other: Any) -> bool:
L243: def __lt__(self, other: Any) -> bool:
L246: def __gt__(self, other: Any) -> bool:
L249: def __le__(self, other: Any) -> bool:
L252: def __ge__(self, other: Any) -> bool:
L255: def __hash__(self) -> int:
L258: def __len__(self) -> int:
L262: def build(
L303: def serialize_url(cls, url: Any, info: core_schema.SerializationInfo) -> str | Self:
L313: def __get_pydantic_core_schema__(
L316: def wrap_val(v, h):
L335: def __get_pydantic_json_schema__(
L346: class _BaseMultiHostUrl:
L350: def __init__(self, url: str | _CoreMultiHostUrl | _BaseMultiHostUrl) -> None:
L354: def scheme(self) -> str:
L362: def path(self) -> str | None:
L370: def query(self) -> str | None:
L377: def query_params(self) -> list[tuple[str, str]]:
L385: def fragment(self) -> str | None:
L392: def hosts(self) -> list[MultiHostHost]:
L411: def encoded_string(self) -> str:
```

```

L418: def unicode_string(self) -> str:
L422: def __str__(self) -> str:
L426: def __repr__(self) -> str:
L429: def __deepcopy__(self, memo: dict) -> Self:
L432: def __eq__(self, other: Any) -> bool:
L435: def __hash__(self) -> int:
L438: def __len__(self) -> int:
L442: def build(
L489: def serialize_url(cls, url: Any, info: core_schema.SerializationInfo) -> str | Self:
L499: def __get_pydantic_core_schema__(
L502: def wrap_val(v, h):
L521: def __get_pydantic_json_schema__(
L533: def _build_type_adapter(cls: type[_BaseUrl | _BaseMultiHostUrl]) -> TypeAdapter:
L537: class AnyUrl(_BaseUrl):
L562: class AnyHttpUrl(AnyUrl):
L572: class HttpUrl(AnyUrl):
L582: class MyModel(BaseModel):
L619: class MyModel(BaseModel):
L653: class AnyWebsocketUrl(AnyUrl):
L663: class WebsocketUrl(AnyUrl):
L674: class FileUrl(AnyUrl):
L683: class FtpUrl(AnyUrl):
L693: class PostgresDsn(_BaseMultiHostUrl):
L712: class MyModel(BaseModel):
L727: class MyDatabaseModel(BaseModel):
L731: def check_db_name(cls, v):
L769: def host(self) -> str:
L774: class CockroachDsn(AnyUrl):
L792: def host(self) -> str:
L797: class AmqpDsn(AnyUrl):
L808: class RedisDsn(AnyUrl):
L825: def host(self) -> str:
L830: class MongoDsn(_BaseMultiHostUrl):
L859: class KafkaDsn(AnyUrl):
L870: class NatsDsn(_BaseMultiHostUrl):
L884: class MySQLDsn(AnyUrl):
L908: class MariaDBDsn(AnyUrl):
L922: class ClickHouseDsn(AnyUrl):
L944: class SnowflakeDsn(AnyUrl):
L958: def host(self) -> str:
L963: def import_email_validator() -> None:
L977: class EmailStr:
L992: class Model(BaseModel):
L1001: def __get_pydantic_core_schema__(
L1010: def __get_pydantic_json_schema__(
L1018: def _validate(cls, input_value: str, /) -> str:
L1022: class NameEmail(_repr.Representation):
L1041: class User(BaseModel):
L1060: def __init__(self, name: str, email: str):
L1064: def __eq__(self, other: Any) -> bool:
L1068: def __get_pydantic_json_schema__(

```

```

L1076: def __get_pydantic_core_schema__(
L1097: def _validate(cls, input_value: Self | str, /) -> Self:
L1104: def __str__(self) -> str:
L1121: class IPvAnyAddress:
L1128: class IpModel(BaseModel):
L1153: def __new__(cls, value: Any) -> IPvAnyAddressType:
L1166: def __get_pydantic_json_schema__(
L1174: def __get_pydantic_core_schema__(
L1184: def _validate(cls, input_value: Any, /) -> IPvAnyAddressType:
L1187: class IPvAnyInterface:
L1192: def __new__(cls, value: NetworkType) -> IPvAnyInterfaceType:
L1205: def __get_pydantic_json_schema__(
L1213: def __get_pydantic_core_schema__(
L1223: def _validate(cls, input_value: NetworkType, /) -> IPvAnyInterfaceType:
L1226: class IPvAnyNetwork:
L1231: def __new__(cls, value: NetworkType) -> IPvAnyNetworkType:
L1246: def __get_pydantic_json_schema__(
L1254: def __get_pydantic_core_schema__(
L1264: def _validate(cls, input_value: NetworkType, /) -> IPvAnyNetworkType:
L1268: def _build_pretty_email_regex() -> re.Pattern[str]:
L1284: def validate_email(value: str) -> tuple[str, str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/type_adapter.py

```

L44: def _getattr_no_parents(obj: Any, attribute: str) -> Any:
L59: def _type_has_config(type_: Any) -> bool:
L70: class TypeAdapter(Generic[T]):
L174: def __init__(
L187: def __init__(
L196: def __init__(
L252: def _fetch_parent_frame(self) -> FrameType | None:
L263: def _init_core_attrs(
L336: def _defer_build(self) -> bool:
L343: def _model_config(self) -> ConfigDict | None:
L349: def __repr__(self) -> str:
L352: def rebuild(
L398: def validate_python(
L452: def validate_json(
L502: def validate_strings(
L549: def get_default_value(self, *, strict: bool | None = None, context: Any | None = None)
-> Some[T] | None:
L561: def dump_python(
L625: def dump_json(
L696: def json_schema(
L736: def json_schemas(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/validate_call_decorator.py

```
L24: def _check_function_type(function: object) -> None:
L73: def validate_call(
L79: def validate_call(func: AnyCallableT, /) -> AnyCallableT: ...
L82: def validate_call(
L106: def validate(function: AnyCallableT) -> AnyCallableT:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/dataclasses.py

```
L33: def dataclass(
L50: def dataclass(
L69: def dataclass(
L84: def dataclass(
L99: def dataclass(
L153: def create_dataclass(cls: type[Any]) -> type[PydanticDataclass]:
L255: def validated_setattr(instance: PydanticDataclass, name: str, value: Any, /) -> None:
L281: def _dataclass_getstate(self: Any) -> list[Any]:
L284: def _dataclass_setstate(self: Any, state: list[Any]) -> None:
L316: def _pydantic_fields_complete(cls: type[PydanticDataclass]) -> bool:
L330: def _call_initvar(*args: Any, **kwargs: Any) -> NoReturn:
L340: def rebuild_dataclass(
L401: def is_pydantic_dataclass(class_: type[Any], /) -> TypeGuard[type[PydanticDataclass]]:
```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/config.py

```
L36: class ConfigDict(TypedDict, total=False):
L73: class User(BaseModel):
L92: class Model(BaseModel):
L114: class Model(BaseModel):
L129: class Model(BaseModel):
L162: class Model(BaseModel):
L209: class Model(BaseModel):
L244: class SomeEnum(Enum):
L249: class SomeModel(BaseModel):
L278: class User(BaseModel):
L297: class User(BaseModel, validate_assignment=True): # (1)!
L327: class Pet:
L328: def __init__(self, name: str):
L331: class Model(BaseModel):
L399: class Voice(BaseModel):
L419: class Athlete(BaseModel):
L444: class without an annotation and has a type that is not in this tuple (or otherwise
recognized by
```

```

L479: class Model(BaseModel):
L512: class User(BaseModel, revalidate_instances='never'): # (1)!
L515: class Transaction(BaseModel):
L536: class User(BaseModel, revalidate_instances='subclass-instances'):
L539: class SubUser(User):
L542: class Transaction(BaseModel):
L683: class Model(BaseModel):
L706: class Model(BaseModel):
L738: class Model(BaseModel):
L765: class Model(BaseModel):
L784: class Model(BaseModel):
L839: class Model(BaseModel):
L885: class Model(BaseModel):
L898: class ForceInputModel(Model):
L936: class Model(BaseModel):
L949: class Model(BaseModel):
L979: class Model(BaseModel):
L1025: class Model(BaseModel):
L1088: class Model(BaseModel):
L1124: class Model(BaseModel):
L1167: class Model(BaseModel):
L1196: class Model(BaseModel):
L1221: def with_config(*, config: ConfigDict) -> Callable[[_TypeT], _TypeT]: ...
L1225: def with_config(config: ConfigDict, /) -> Callable[[_TypeT], _TypeT]: ...
L1229: def with_config(**config: Unpack[ConfigDict]) -> Callable[[_TypeT], _TypeT]: ...
L1232: def with_config(config: ConfigDict | None = None, /, **kwargs: Any) ->
Callable[[_TypeT], _TypeT]:
L1249: class TD(TypedDict):
L1279: def inner(class_: _TypeT, /) -> _TypeT:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/__init__.py

```

L425: def __getattr__(attr_name: str) -> object:
L455: def __dir__() -> list[str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/version.py

```

L25: def version_short() -> str:
L33: def version_info() -> str:
L77: def check_pydantic_core_version() -> bool:
L82: def _ensure_pydantic_core_version() -> None: # pragma: no cover
L101: def parse_mypy_version(version: str) -> tuple[int, int, int]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/aliases.py

```

L16: class AliasPath:
L28: def __init__(self, first_arg: str, *args: str | int) -> None:
L31: def convert_to_aliases(self) -> list[str | int]:
L39: def search_dict_for_path(self, d: dict) -> Any:
L58: class AliasChoices:
L70: def __init__(self, first_choice: str | AliasPath, *choices: str | AliasPath) -> None:
L73: def convert_to_aliases(self) -> list[list[str | int]]:
L89: class AliasGenerator:
L105: def _generate_alias(
L125: def generate_aliases(self, field_name: str) -> tuple[str | None, str | AliasPath |
AliasChoices | None, str | None]:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/types.py

```

L116: class Strict(_fields.PydanticMetadata, BaseMetadata):
L138: def __hash__(self) -> int:
L150: def conint(
L173: class Foo(BaseModel):
L183: class Foo(BaseModel):
L203: class ConstrainedExample(BaseModel):
L243: class Model(BaseModel):
L274: class Model(BaseModel):
L305: class Model(BaseModel):
L336: class Model(BaseModel):
L367: class StrictIntModel(BaseModel):
L386: class AllowInfNan(_fields.PydanticMetadata):
L406: def __hash__(self) -> int:
L410: def confloat(
L434: class Foo(BaseModel):
L444: class Foo(BaseModel):
L465: class ConstrainedExample(BaseModel):
L505: class Model(BaseModel):
L536: class Model(BaseModel):
L567: class Model(BaseModel):
L598: class Model(BaseModel):
L629: class StrictFloatModel(BaseModel):
L649: class Model(BaseModel):
L662: def conbytes(
L693: class StringConstraints(annotated_types.GroupedMetadata):
L729: def __iter__(self) -> Iterator[BaseMetadata]:
L752: def constr(
L777: class Foo(BaseModel):
L787: class Foo(BaseModel):
L801: class Foo(BaseModel):
L845: def conset(
L861: def confrozenset(
L880: def conlist(

```

```

L919: class ImportString:
L935: class ImportThings(BaseModel):
L963: class ImportThingsDefaultPyObj(BaseModel):
L967: class ImportThingsDefaultString(BaseModel):
L975: class ImportThingsMissingValidateDefault(BaseModel):
L987: class ImportThings(BaseModel):
L1000: def __class_getitem__(cls, item: AnyType) -> AnyType:
L1004: def __get_pydantic_core_schema__(
L1019: def __get_pydantic_json_schema__(cls, cs: CoreSchema, handler: GetJsonSchemaHandler)
-> JsonSchemaValue:
L1023: def _serialize(v: Any) -> str:
L1039: def __repr__(self) -> str:
L1046: def condecimal(
L1072: class Foo(BaseModel):
L1083: class Foo(BaseModel):
L1105: class ConstrainedExample(BaseModel):
L1144: class UuidVersion:
L1165: def __get_pydantic_json_schema__(
L1173: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:
L1179: def __hash__(self) -> int:
L1191: class Model(BaseModel):
L1205: class Model(BaseModel):
L1219: class Model(BaseModel):
L1233: class Model(BaseModel):
L1247: class Model(BaseModel):
L1261: class Model(BaseModel):
L1275: class Model(BaseModel):
L1286: class PathType:
L1289: def __get_pydantic_json_schema__(
L1297: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:
L1311: def validate_file(path: Path, _: core_schema.ValidationInfo) -> Path:
L1318: def validate_socket(path: Path, _: core_schema.ValidationInfo) -> Path:
L1325: def validate_directory(path: Path, _: core_schema.ValidationInfo) -> Path:
L1332: def validate_new(path: Path, _: core_schema.ValidationInfo) -> Path:
L1340: def __hash__(self) -> int:
L1352: class Model(BaseModel):
L1394: class Model(BaseModel):
L1442: class Json:
L1453: class AnyJsonModel(BaseModel):
L1456: class ConstrainedJsonModel(BaseModel):
L1503: class ConstrainedJsonModel(BaseModel):
L1516: def __class_getitem__(cls, item: AnyType) -> AnyType:
L1520: def __get_pydantic_core_schema__(cls, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:
L1526: def __repr__(self) -> str:
L1529: def __hash__(self) -> int:
L1532: def __eq__(self, other: Any) -> bool:
L1542: class _SecretBase(Generic[SecretType]):
L1543: def __init__(self, secret_value: SecretType) -> None:

```

```

L1546: def get_secret_value(self) -> SecretType:
L1554: def __eq__(self, other: Any) -> bool:
L1557: def __hash__(self) -> int:
L1560: def __str__(self) -> str:
L1563: def __repr__(self) -> str:
L1566: def _display(self) -> str | bytes:
L1570: def _serialize_secret(value: Secret[SecretType], info: core_schema.SerializationInfo)
-> str | Secret[SecretType]:
L1577: class Secret(_SecretBase[SecretType]):
L1591: class Model(BaseModel):
L1612: class SecretDate(Secret[date]):
L1613: def _display(self) -> str:
L1616: class Model(BaseModel):
L1642: class Model(BaseModel):
L1683: def _display(self) -> str | bytes:
L1687: def __get_pydantic_core_schema__(cls, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:
L1707: def validate_secret_value(value, handler) -> Secret[SecretType]:
L1737: def _secret_display(value: SecretType) -> str: # type: ignore
L1741: def _serialize_secret_field(
L1752: class _SecretField(_SecretBase[SecretType]):
L1757: def __get_pydantic_core_schema__(cls, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:
L1758: def get_json_schema(_core_schema: core_schema.CoreSchema, handler:
GetJsonSchemaHandler) -> JsonSchemaValue:
L1768: def get_secret_schema(strict: bool) -> CoreSchema:
L1807: class SecretStr(_SecretField[str]):
L1816: class User(BaseModel):
L1839: class Model(BaseModel):
L1844: def dump_secret(self, v):
L1867: def __len__(self) -> int:
L1870: def _display(self) -> str:
L1874: class SecretBytes(_SecretField[bytes]):
L1884: class User(BaseModel):
L1900: def __len__(self) -> int:
L1903: def _display(self) -> bytes:
L1910: class PaymentCardBrand(str, Enum):
L1916: def __str__(self) -> str:
L1925: class PaymentCardNumber(str):
L1935: def __init__(self, card_number: str):
L1945: def __get_pydantic_core_schema__(cls, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:
L1954: def validate(cls, input_value: str, /, _: core_schema.ValidationInfo) ->
PaymentCardNumber:
L1959: def masked(self) -> str:
L1969: def validate_digits(cls, card_number: str) -> None:
L1975: def validate_luhn_check_digit(cls, card_number: str) -> str:
L1993: def validate_brand(card_number: str) -> PaymentCardBrand:
L2031: class ByteSize(int):
L2047: class MyModel(BaseModel):
L2102: def __get_pydantic_core_schema__(cls, source: type[Any], handler:

```

```

GetCoreSchemaHandler) -> core_schema.CoreSchema:
L2119: def _validate(cls, input_value: Any, /, _: core_schema.ValidationInfo) -> ByteSize:
L2140: def human_readable(self, decimal: bool = False, separator: str = '') -> str:
L2171: def to(self, unit: str) -> float:
L2194: def _check_annotated_type(annotated_type: str, expected_type: str, annotation: str) ->
None:
L2204: class PastDate:
L2208: def __get_pydantic_core_schema__(
L2220: def __repr__(self) -> str:
L2223: class FutureDate:
L2227: def __get_pydantic_core_schema__(
L2239: def __repr__(self) -> str:
L2243: def conddate(
L2280: class AwareDatetime:
L2284: def __get_pydantic_core_schema__(
L2296: def __repr__(self) -> str:
L2299: class NaiveDatetime:
L2303: def __get_pydantic_core_schema__(
L2315: def __repr__(self) -> str:
L2318: class PastDatetime:
L2322: def __get_pydantic_core_schema__(
L2334: def __repr__(self) -> str:
L2337: class FutureDatetime:
L2341: def __get_pydantic_core_schema__(
L2353: def __repr__(self) -> str:
L2360: class EncoderProtocol(Protocol):
L2364: def decode(cls, data: bytes) -> bytes:
L2376: def encode(cls, value: bytes) -> bytes:
L2388: def get_json_format(cls) -> str:
L2397: class Base64Encoder(EncoderProtocol):
L2401: def decode(cls, data: bytes) -> bytes:
L2416: def encode(cls, value: bytes) -> bytes:
L2428: def get_json_format(cls) -> Literal['base64']:
L2437: class Base64UrlEncoder(EncoderProtocol):
L2441: def decode(cls, data: bytes) -> bytes:
L2456: def encode(cls, value: bytes) -> bytes:
L2468: def get_json_format(cls) -> Literal['base64url']:
L2478: class EncodedBytes:
L2488: class MyEncoder(EncoderProtocol):
L2490: def decode(cls, data: bytes) -> bytes:
L2496: def encode(cls, value: bytes) -> bytes:
L2500: def get_json_format(cls) -> str:
L2505: class Model(BaseModel):
L2534: def __get_pydantic_json_schema__(
L2541: def __get_pydantic_core_schema__(self, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:
L2550: def decode(self, data: bytes, _: core_schema.ValidationInfo) -> bytes:
L2561: def encode(self, value: bytes) -> bytes:
L2572: def __hash__(self) -> int:
L2577: class EncodedStr:
L2587: class MyEncoder(EncoderProtocol):

```

```

L2589: def decode(cls, data: bytes) -> bytes:
L2595: def encode(cls, value: bytes) -> bytes:
L2599: def get_json_format(cls) -> str:
L2604: class Model(BaseModel):
L2633: def __get_pydantic_json_schema__(
L2640: def __get_pydantic_core_schema__(self, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:
L2649: def decode_str(self, data: str, _: core_schema.ValidationInfo) -> str:
L2660: def encode_str(self, value: str) -> str:
L2671: def __hash__(self) -> int:
L2698: class LegacyBase64Encoder(EncoderProtocol):
L2700: def decode(cls, data: bytes) -> bytes:
L2711: def encode(cls, value: bytes) -> bytes:
L2715: def get_json_format(cls) -> Literal['base64']:
L2725: class Model(BaseModel):
L2772: class Model(BaseModel):
L2811: class Model(BaseModel):
L2832: class Model(BaseModel):
L2847: class GetPydanticSchema:
L2864: class Model(BaseModel):
L2881: def __getattr__(self, item: str) -> Any:
L2894: class Tag:
L2912: class Pie(BaseModel):
L2916: class ApplePie(Pie):
L2919: class PumpkinPie(Pie):
L2922: def get_discriminator_value(v: Any) -> str:
L2927: class ThanksgivingDinner(BaseModel):
L2971: def __get_pydantic_core_schema__(self, source_type: Any, handler:
GetCoreSchemaHandler) -> CoreSchema:
L2979: class Discriminator:
L2999: class Pie(BaseModel):
L3003: class ApplePie(Pie):
L3006: class PumpkinPie(Pie):
L3009: def get_discriminator_value(v: Any) -> str:
L3014: class ThanksgivingDinner(BaseModel):
L3066: def __get_pydantic_core_schema__(self, source_type: Any, handler:
GetCoreSchemaHandler) -> CoreSchema:
L3075: def _convert_schema(
L3157: def _get_type_name(x: Any) -> str:
L3178: class _AllowAnyJson:
L3180: def __get_pydantic_core_schema__(cls, source_type: Any, handler: GetCoreSchemaHandler)
-> CoreSchema:
L3216: class Model(BaseModel):
L3262: class _OnErrorOmit:
L3264: def __get_pydantic_core_schema__(cls, source_type: Any, handler: GetCoreSchemaHandler)
-> CoreSchema:
L3281: class FailFast(_fields.PydanticMetadata, BaseMetadata):
L3294: class Model(BaseModel):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/annotated_handlers.py

```

L24: class GetJsonSchemaHandler:
L33: def __call__(self, core_schema: CoreSchemaOrField, /) -> JsonSchemaValue:
L49: def resolve_ref_schema(self, maybe_ref_json_schema: JsonSchemaValue, /) ->
JsonSchemaValue:
L66: class GetCoreSchemaHandler:
L69: def __call__(self, source_type: Any, /) -> core_schema.CoreSchema:
L84: def generate_schema(self, source_type: Any, /) -> core_schema.CoreSchema:
L99: def resolve_ref_schema(self, maybe_ref_schema: core_schema.CoreSchema, /) ->
core_schema.CoreSchema:
L116: def field_name(self) -> str | None:
L120: def _get_types_namespace(self) -> NamespacesTuple:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/warnings.py

```

L22: class PydanticDeprecationWarning(DeprecationWarning):
L38: def __init__(
L46: def __str__(self) -> str:
L56: class PydanticDeprecatedSince20(PydanticDeprecationWarning):
L59: def __init__(self, message: str, *args: object) -> None:
L63: class PydanticDeprecatedSince26(PydanticDeprecationWarning): # pragma: no cover
L66: def __init__(self, message: str, *args: object) -> None:
L70: class PydanticDeprecatedSince29(PydanticDeprecationWarning):
L73: def __init__(self, message: str, *args: object) -> None:
L77: class PydanticDeprecatedSince210(PydanticDeprecationWarning):
L80: def __init__(self, message: str, *args: object) -> None:
L84: class PydanticDeprecatedSince211(PydanticDeprecationWarning):
L87: def __init__(self, message: str, *args: object) -> None:
L91: class PydanticDeprecatedSince212(PydanticDeprecationWarning):
L94: def __init__(self, message: str, *args: object) -> None:
L98: class GenericBeforeBaseModelWarning(Warning):
L102: class PydanticExperimentalWarning(Warning):
L109: class CoreSchemaGenerationWarning(UserWarning):
L113: class ArbitraryTypeWarning(CoreSchemaGenerationWarning):
L117: class UnsupportedFieldAttributeWarning(CoreSchemaGenerationWarning):
L121: class TypedDictExtraConfigWarning(CoreSchemaGenerationWarning):

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/color.py

```

L33: class RGBA:
L38: def __init__(self, r: float, g: float, b: float, alpha: Optional[float]):
L46: def __getitem__(self, item: Any) -> Any:
L77: class Color(_repr.Representation):

```



```

L82: def __init__(self, value: ColorType) -> None:
L101: def __get_pydantic_json_schema__(
L108: def original(self) -> ColorType:
L112: def as_named(self, *, fallback: bool = False) -> str:
L138: def as_hex(self) -> str:
L156: def as_rgb(self) -> str:
L166: def as_rgb_tuple(self, *, alpha: Optional[bool] = None) -> ColorTuple:
L192: def as_hsl(self) -> str:
L201: def as_hsl_tuple(self, *, alpha: Optional[bool] = None) -> HslColorTuple:
L230: def _alpha_float(self) -> float:
L234: def __get_pydantic_core_schema__(
L242: def _validate(cls, __input_value: Any, _: Any) -> 'Color':
L245: def __str__(self) -> str:
L248: def __repr_args__(self) -> '_repr.ReprArgs':
L251: def __eq__(self, other: Any) -> bool:
L254: def __hash__(self) -> int:
L258: def parse_tuple(value: tuple[Any, ...]) -> RGBA:
L280: def parse_str(value: str) -> RGBA:
L339: def ints_to_rgba(r: Union[int, str], g: Union[int, str], b: Union[int, str], alpha:
Optional[float] = None) -> RGBA:
L354: def parse_color_value(value: Union[int, str], max_val: int = 255) -> float:
L381: def parse_float_alpha(value: Union[None, str, float, int]) -> Optional[float]:
L411: def parse_hsl(h: str, h_units: str, sat: str, light: str, alpha: Optional[float] =
None) -> RGBA:
L439: def float_to_255(c: float) -> int:

```

Q_base appwrite/venv/lib/python3.12/site-packages/pydantic/main.py

```

L82: def _check_frozen(model_cls: type[BaseModel], name: str, value: Any) -> None:
L95: def _model_field_setattr_handler(model: BaseModel, name: str, val: Any) -> None:
L100: def _private_setattr_handler(model: BaseModel, name: str, val: Any) -> None:
L119: class BaseModel(metaclass=_model_construction.ModelMetaclass):
L253: def __init__(self, /, **data: Any) -> None:
L277: def model_fields(cls) -> dict[str, FieldInfo]:
L288: def model_computed_fields(cls) -> dict[str, ComputedFieldInfo]:
L298: def model_extra(self) -> dict[str, Any] | None:
L307: def model_fields_set(self) -> set[str]:
L317: def model_construct(cls, _fields_set: set[str] | None = None, **values: Any) -> Self:
# noqa: C901
L393: def model_copy(self, *, update: Mapping[str, Any] | None = None, deep: bool = False) ->
Self:
L427: def model_dump(
L493: def model_dump_json(
L562: def model_json_schema(
L601: def model_parametrized_name(cls, params: tuple[type[Any], ...]) -> str:
L627: def model_post_init(self, context: Any, /) -> None:
L633: def model_rebuild(
L694: def model_validate(
L743: def model_validate_json(

```

```

L787: def model_validate_strings(
L825: def __get_pydantic_core_schema__(cls, source: type[BaseModel], handler:
GetCoreSchemaHandler, /) -> CoreSchema:
L845: def __get_pydantic_json_schema__(
L871: def __pydantic_init_subclass__(cls, **kwargs: Any) -> None:
L894: def __pydantic_on_complete__(cls) -> None:
L904: def __class_getitem__(
L971: def __copy__(self) -> Self:
L990: def __deepcopy__(self, memo: dict[int, Any] | None = None) -> Self:
L1015: def __getattr__(self, item: str) -> Any:
L1044: def __setattr__(self, name: str, value: Any) -> None:
L1052: def _setattr_handler(self, name: str, value: Any) -> Callable[[BaseModel, str, Any],
None] | None:
L1107: def __delattr__(self, item: str) -> Any:
L1142: def __replace__(self, **changes: Any) -> Self:
L1145: def __getstate__(self) -> dict[Any, Any]:
L1156: def __setstate__(self, state: dict[Any, Any]) -> None:
L1164: def __eq__(self, other: Any) -> bool:
L1226: def __init_subclass__(cls, **kwargs: Unpack[ConfigDict]):
L1233: class MyModel(BaseModel, extra='allow'): ...
L1248: def __iter__(self) -> TupleGenerator:
L1255: def __repr__(self) -> str:
L1258: def __repr_args__(self) -> _repr.ReprArgs:
L1293: def __str__(self) -> str:
L1301: def __fields__(self) -> dict[str, FieldInfo]:
L1314: def __fields_set__(self) -> set[str]:
L1323: def dict( # noqa: D102
L1348: def json( # noqa: D102
L1383: def parse_obj(cls, obj: Any) -> Self: # noqa: D102
L1397: def parse_raw( # noqa: D102
L1451: def parse_file( # noqa: D102
L1483: def from_orm(cls, obj: Any) -> Self: # noqa: D102
L1498: def construct(cls, _fields_set: set[str] | None = None, **values: Any) -> Self: #
noqa: D102
L1511: def copy(
L1585: def schema( # noqa: D102
L1600: def schema_json( # noqa: D102
L1620: def validate(cls, value: Any) -> Self: # noqa: D102
L1633: def update_forward_refs(cls, **localns: Any) -> None: # noqa: D102
L1646: def _iter(self, *args: Any, **kwargs: Any) -> Any:
L1660: def _copy_and_set_values(self, *args: Any, **kwargs: Any) -> Any:
L1675: def _get_value(cls, *args: Any, **kwargs: Any) -> Any:
L1689: def _calculate_keys(self, *args: Any, **kwargs: Any) -> Any:
L1704: def create_model(
L1720: def create_model(
L1735: def create_model( # noqa: C901

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/errors.py

```

L82: class PydanticErrorMixin:
L90: def __init__(self, message: str, *, code: PydanticErrorCodes | None) -> None:
L94: def __str__(self) -> str:
L101: class PydanticUserError(PydanticErrorMixin, RuntimeError):
L105: class PydanticUndefinedAnnotation(PydanticErrorMixin, NameError):
L113: def __init__(self, name: str, message: str) -> None:
L118: def from_name_error(cls, name_error: NameError) -> Self:
L134: class PydanticImportError(PydanticErrorMixin, ImportError):
L141: def __init__(self, message: str) -> None:
L145: class PydanticSchemaGenerationError(PydanticUserError):
L152: def __init__(self, message: str) -> None:
L156: class PydanticInvalidForJsonSchema(PydanticUserError):
L163: def __init__(self, message: str) -> None:
L167: class PydanticForbiddenQualifier(PydanticUserError):
L179: def __init__(self, qualifier: Qualifier, annotation: Any) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/root_model.py

```

L23: class _RootModelMetaclass(_model_construction.ModelMetaclass): ...
L32: class RootModel(BaseModel, Generic[RootModelRootType], metaclass=_RootModelMetaclass):
L52: def __init_subclass__(cls, **kwargs):
L60: def __init__(self, /, root: RootModelRootType = PydanticUndefined, **data) -> None: #
type: ignore
L73: def model_construct(cls, root: RootModelRootType, _fields_set: set[str] | None = None)
-> Self: # type: ignore
L88: def __getstate__(self) -> dict[Any, Any]:
L94: def __setstate__(self, state: dict[Any, Any]) -> None:
L98: def __copy__(self) -> Self:
L108: def __deepcopy__(self, memo: dict[int, Any] | None = None) -> Self:
L120: def model_dump( # type: ignore
L149: def __eq__(self, other: Any) -> bool:
L156: def __repr_args__(self) -> _repr.ReprArgs:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_core_metadata.py

```

L13: class CoreMetadata(TypedDict, total=False):
L47: def update_core_metadata(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_generate_schema.py

```

L202: def check_validator_fields_against_field_name(
L219: def check_decorator_fields_exist(decorators: Iterable[AnyFieldDecorator], fields:
Iterable[str]) -> None:
L246: def filter_field_decorator_info_by_field(
L252: def apply_each_item_validators(
L287: def _extract_json_schema_info_from_field_info(
L303: def _add_custom_serialization_from_json_encoders(
L346: class InvalidSchemaError(Exception):
L350: class GenerateSchema:
L362: def __init__(
L376: def __init_subclass__(cls) -> None:
L385: def _config_wrapper(self) -> ConfigWrapper:
L389: def _types_namespace(self) -> NamespacesTuple:
L393: def _arbitrary_types(self) -> bool:
L398: def _list_schema(self, items_type: Any) -> CoreSchema:
L401: def _dict_schema(self, keys_type: Any, values_type: Any) -> CoreSchema:
L404: def _set_schema(self, items_type: Any) -> CoreSchema:
L407: def _frozenset_schema(self, items_type: Any) -> CoreSchema:
L410: def _enum_schema(self, enum_type: type[Enum]) -> CoreSchema:
L439: def get_json_schema(schema: CoreSchema, handler: GetJsonSchemaHandler) ->
JsonSchemaValue:
L465: def get_json_schema_no_cases(_, handler: GetJsonSchemaHandler) -> JsonSchemaValue:
L482: def _ip_schema(self, tp: Any) -> CoreSchema:
L494: def ser_ip(ip: Any, info: core_schema.SerializationInfo) -> str | IpType:
L515: def _path_schema(self, tp: Any, path_type: Any) -> CoreSchema:
L527: def path_validator(input_value: str | bytes) -> os.PathLike[Any]: # type: ignore
L544: def ser_path(path: Any, info: core_schema.SerializationInfo) -> str | os.PathLike[Any]:
L573: def _deque_schema(self, items_type: Any) -> CoreSchema:
L598: def _mapping_schema(self, tp: Any, keys_type: Any, values_type: Any) -> CoreSchema:
L644: def _fraction_schema(self) -> CoreSchema:
L661: def _arbitrary_type_schema(self, tp: Any) -> CoreSchema:
L673: def _unknown_type_schema(self, obj: Any) -> CoreSchema:
L684: def _apply_discriminator_to_union(
L703: def clean_schema(self, schema: CoreSchema) -> CoreSchema:
L706: def _add_js_function(self, metadata_schema: CoreSchema, js_function: Callable[...,
Any]) -> None:
L717: def generate_schema(
L756: def _model_schema(self, cls: type[BaseModel]) -> core_schema.CoreSchema:
L895: def _resolve_self_type(self, obj: Any) -> Any:
L901: def _generate_schema_from_get_schema_method(self, obj: Any, source: Any) ->
core_schema.CoreSchema | None:
L960: def _resolve_forward_ref(self, obj: Any) -> Any:
L983: def _get_args_resolving_forward_refs(self, obj: Any, required: Literal[True]) ->
tuple[Any, ...]: ...
L986: def _get_args_resolving_forward_refs(self, obj: Any) -> tuple[Any, ...] | None: ...
L988: def _get_args_resolving_forward_refs(self, obj: Any, required: bool = False) ->
tuple[Any, ...] | None:
L1002: def _get_first_arg_or_any(self, obj: Any) -> Any:
L1008: def _get_first_two_args_or_any(self, obj: Any) -> tuple[Any, Any]:
L1017: def _generate_schema_inner(self, obj: Any) -> core_schema.CoreSchema:
L1045: def match_type(self, obj: Any) -> core_schema.CoreSchema: # noqa: C901

```

```

L1167: def _match_generic_type(self, obj: Any, origin: Any) -> CoreSchema: # noqa: C901
L1218: def _generate_td_field_schema(
L1238: def _generate_md_field_schema(
L1256: def _generate_dc_field_schema(
L1278: def _common_field_schema( # C901
L1283: def set_discriminator(schema: CoreSchema) -> CoreSchema:
L1335: def _union_schema(self, union_type: Any) -> core_schema.CoreSchema:
L1362: def _type_alias_type_schema(self, obj: TypeAliasType) -> CoreSchema:
L1381: def _literal_schema(self, literal_type: Any) -> CoreSchema:
L1394: def _typed_dict_schema(self, typed_dict_cls: Any, origin: Any) ->
core_schema.CoreSchema:
L1533: def _namedtuple_schema(self, namedtuple_cls: Any, origin: Any) ->
core_schema.CoreSchema:
L1579: def _generate_parameter_schema(
L1624: def _generate_parameter_v3_schema(
L1674: def _tuple_schema(self, tuple_type: Any) -> core_schema.CoreSchema:
L1704: def _type_schema(self) -> core_schema.CoreSchema:
L1711: def _zoneinfo_schema(self) -> core_schema.CoreSchema:
L1722: def _union_is_subclass_schema(self, union_type: Any) -> core_schema.CoreSchema:
L1727: def _subclass_schema(self, type_: Any) -> core_schema.CoreSchema:
L1766: def _sequence_schema(self, items_type: Any) -> core_schema.CoreSchema:
L1789: def _iterable_schema(self, type_: Any) -> core_schema.GeneratorSchema:
L1795: def _pattern_schema(self, pattern_type: Any) -> core_schema.CoreSchema:
L1823: def _hashable_schema(self) -> core_schema.CoreSchema:
L1835: def _dataclass_schema(
L1957: def _call_schema(self, function: ValidateCallSupportedTypes) ->
core_schema.CallSchema:
L1982: def _arguments_schema(
L2057: def _arguments_v3_schema(
L2125: def _unsubstituted_typevar_schema(self, typevar: typing.TypeVar) ->
core_schema.CoreSchema:
L2145: def _computed_field_schema(
L2195: def _annotated_schema(self, annotated_type: Any) -> core_schema.CoreSchema:
L2210: def _apply_annotations(
L2227: def inner_handler(obj: Any) -> CoreSchema:
L2258: def _apply_single_annotation(
L2374: def _apply_single_annotation_json_schema(
L2390: def _get_unsupported_field_info_attributes(self, field_info: FieldInfo) ->
list[tuple[str, Any]]:
L2412: def _get_wrapped_inner_schema(
L2421: def new_handler(source: Any) -> core_schema.CoreSchema:
L2440: def _apply_field_serializers(
L2496: def _apply_model_serializers(
L2561: def apply_validators(
L2587: def _validators_require_validate_default(validators:
Iterable[Decorator[ValidatorDecoratorInfo]]) -> bool:
L2603: def _convert_to_aliases(
L2612: def apply_model_validators(
L2659: def wrap_default(field_info: FieldInfo, schema: core_schema.CoreSchema) ->
core_schema.CoreSchema:
L2684: def _extract_get_pydantic_json_schema(tp: Any) -> GetJsonSchemaFunction | None:

```

```

L2716: def resolve_original_schema(schema: CoreSchema, definitions: _Definitions) ->
CoreSchema | None:
L2725: def _inlining_behavior(
L2745: class _Definitions:
L2766: def __init__(self) -> None:
L2771: def get_schema_or_ref(self, tp: Any, /) -> Generator[tuple[str,
core_schema.DefinitionReferenceSchema | None]]:
L2803: def get_schema_from_ref(self, ref: str) -> CoreSchema | None:
L2807: def create_definition_reference_schema(self, schema: CoreSchema) ->
core_schema.DefinitionReferenceSchema:
L2816: def unpack_definitions(self, schema: core_schema.DefinitionsSchema) -> CoreSchema:
L2822: def finalize_schema(self, schema: CoreSchema) -> CoreSchema:
L2880: def _resolve_definition(self, ref: str, definitions: dict[str, CoreSchema]) ->
CoreSchema:
L2899: class _FieldNameStack:
L2902: def __init__(self) -> None:
L2906: def push(self, field_name: str) -> Iterator[None]:
L2911: def get(self) -> str | None:
L2918: class _ModelTypeStack:
L2921: def __init__(self) -> None:
L2925: def push(self, type_obj: type) -> Iterator[None]:
L2930: def get(self) -> type | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_repr.py

```

L22: class PlainRepr(str):
L27: def __repr__(self) -> str:
L31: class Representation:
L39: def __repr_args__(self) -> ReprArgs:
L52: def __repr_name__(self) -> str:
L56: def __repr_recursion__(self, object: Any) -> str:
L61: def __repr_str__(self, join_str: str) -> str:
L64: def __pretty__(self, fmt: Callable[[Any], Any], **kwargs: Any) -> Generator[Any]:
L77: def __rich_repr__(self) -> RichReprResult:
L85: def __str__(self) -> str:
L88: def __repr__(self) -> str:
L92: def display_as_type(obj: Any) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_serializers.py

```

L32: def serialize_sequence_via_list(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_docs_extraction.py

```

L12: class DocstringVisitor(ast.NodeVisitor):
L13: def __init__(self) -> None:
L20: def visit(self, node: ast.AST) -> Any:
L25: def visit_AnnAssign(self, node: ast.AnnAssign) -> Any:
L29: def visit_Expr(self, node: ast.Expr) -> Any:
L41: def _dedent_source_lines(source: list[str]) -> str:
L52: def _extract_source_from_frame(cls: type[Any]) -> list[str] | None:
L82: def extract_docstrings_from_cls(cls: type[Any], use_inspect: bool = False) -> dict[str, str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_import_utils.py

```

L10: def import_cached_base_model() -> type['BaseModel']:
L17: def import_cached_field_info() -> type['FieldInfo']:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_config.py

```

L29: class ConfigWrapper:
L93: def __init__(self, config: ConfigDict | dict[str, Any] | type[Any] | None, *, check: bool = True):
L100: def for_model(
L154: def __getattr__(self, name: str) -> Any:
L163: def core_config(self, title: str | None) -> core_schema.CoreConfig:
L239: def __repr__(self):
L244: class ConfigWrapperStack:
L247: def __init__(self, config_wrapper: ConfigWrapper):
L251: def tail(self) -> ConfigWrapper:
L255: def push(self, config_wrapper: ConfigWrapper | ConfigDict | None):
L323: def prepare_config(config: ConfigDict | dict[str, Any] | type[Any] | None) -> ConfigDict:
L373: def check_deprecated(config_dict: ConfigDict) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_validation

ors.py

```

L28: def sequence_validator(
L68: def import_string(value: Any) -> Any:
L79: def _import_string_logic(dotted_path: str) -> Any:
L131: def pattern_either_validator(input_value: Any, /) -> re.Pattern[Any]:
L141: def pattern_str_validator(input_value: Any, /) -> re.Pattern[str]:
L155: def pattern_bytes_validator(input_value: Any, /) -> re.Pattern[bytes]:
L172: def compile_pattern(pattern: PatternType) -> re.Pattern[PatternType]:
L179: def ip_v4_address_validator(input_value: Any, /) -> IPv4Address:
L189: def ip_v6_address_validator(input_value: Any, /) -> IPv6Address:
L199: def ip_v4_network_validator(input_value: Any, /) -> IPv4Network:
L214: def ip_v6_network_validator(input_value: Any, /) -> IPv6Network:
L229: def ip_v4_interface_validator(input_value: Any, /) -> IPv4Interface:
L239: def ip_v6_interface_validator(input_value: Any, /) -> IPv6Interface:
L249: def fraction_validator(input_value: Any, /) -> Fraction:
L259: def forbid_inf_nan_check(x: Any) -> Any:
L265: def _safe_repr(v: Any) -> int | float | str:
L275: def greater_than_validator(x: Any, gt: Any) -> Any:
L284: def greater_than_or_equal_validator(x: Any, ge: Any) -> Any:
L293: def less_than_validator(x: Any, lt: Any) -> Any:
L302: def less_than_or_equal_validator(x: Any, le: Any) -> Any:
L311: def multiple_of_validator(x: Any, multiple_of: Any) -> Any:
L320: def min_length_validator(x: Any, min_length: Any) -> Any:
L331: def max_length_validator(x: Any, max_length: Any) -> Any:
L343: def _extract_decimal_digits_info(decimal: Decimal) -> tuple[int, int]:
L386: def max_digits_validator(x: Any, max_digits: Any) -> Any:
L400: def decimal_places_validator(x: Any, decimal_places: Any) -> Any:
L415: def deque_validator(input_value: Any, handler:
core_schema.ValidatorFunctionWrapHandler) -> collections.deque[Any]:
L419: def defaultdict_validator(
L429: def get_defaultdict_default_default_factory(values_source_type: Any) -> Callable[[],
Any]:
L434: def infer_default() -> Callable[[], Any]:
L458: def type_var_default_factory() -> None:
L488: def validate_str_is_valid_iana_tz(value: Any, /) -> ZoneInfo:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_fields.py

```

L39: class PydanticMetadata(Representation):
L46: class PydanticExtraInfo:
L52: def pydantic_general_metadata(**metadata: Any) -> BaseMetadata:
L65: def _general_metadata_cls() -> type[BaseMetadata]:
L69: class _PydanticGeneralMetadata(PydanticMetadata, BaseMetadata):
L72: def __init__(self, metadata: Any):

```



```

L178: def _check_protected_namespaces(
L121: def _update_fields_from_docstrings(cls: type[Any], fields: dict[str, FieldInfo],
use_inspect: bool = False) -> None:
L128: def _apply_field_title_generator_to_field_info(
L141: def _apply_alias_generator_to_field_info(
L191: def update_field_from_config(config_wrapper: ConfigWrapper, field_name: str,
field_info: FieldInfo) -> None:
L224: def collect_model_fields( # noqa: C901
L436: def rebuild_model_fields(
L483: def _recreate_field_info(
L527: def collect_dataclass_fields(
L635: def rebuild_dataclass_fields(
L681: def is_valid_field_name(name: str) -> bool:
L685: def is_valid_privateattr_name(name: str) -> bool:
L689: def takes_validated_data_argument(
L705: def resolve_default_value(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_validate_e_call.py

```

L19: def extract_function_name(func: ValidateCallSupportedTypes) -> str:
L24: def extract_function_qualname(func: ValidateCallSupportedTypes) -> str:
L29: def update_wrapper_attributes(wrapped: ValidateCallSupportedTypes, wrapper:
Callable[..., Any]):
L39: def wrapper_function(*args, **kwargs):
L50: class ValidateCallWrapper:
L66: def __init__(
L92: def _create_validators(self) -> None:
L133: def __call__(self, *args: Any, **kwargs: Any) -> Any:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_schema_generation_shared.py

```

L21: class GenerateJsonSchemaHandler(GetJsonSchemaHandler):
L31: def __init__(self, generate_json_schema: GenerateJsonSchema, handler_override:
HandlerOverride | None) -> None:
L36: def __call__(self, core_schema: CoreSchemaOrField, /) -> JsonSchemaValue:
L39: def resolve_ref_schema(self, maybe_ref_json_schema: JsonSchemaValue) -> JsonSchemaValue:
L65: class CallbackGetCoreSchemaHandler(GetCoreSchemaHandler):
L72: def __init__(
L82: def __call__(self, source_type: Any, /) -> core_schema.CoreSchema:
L92: def _get_types_namespace(self) -> NamespacesTuple:
L95: def generate_schema(self, source_type: Any, /) -> core_schema.CoreSchema:
L99: def field_name(self) -> str | None:

```

```
L102: def resolve_ref_schema(self, maybe_ref_schema: core_schema.CoreSchema) ->
core_schema.CoreSchema:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_git.py

```
L9: def is_git_repo(dir: Path) -> bool:
L14: def have_git() -> bool: # pragma: no cover
L25: def git_revision(dir: Path) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_forward_ref.py

```
L8: class PydanticRecursiveRef:
L14: def __call__(self) -> None:
L19: def __or__(self, other):
L22: def __ror__(self, other):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_model_construction.py

```
L52: class _ModelNamespaceDict(dict):
L57: def __setitem__(self, k: str, v: object) -> None:
L68: def NoInitField(
L83: class ModelMetaclass(ABCMeta):
L84: def __new__(
L142: def wrapped_model_post_init(self: BaseModel, context: Any, /) -> None:
L285: def __getattr__(self, item: str) -> Any:
L293: def __prepare__(cls, *args: Any, **kwargs: Any) -> dict[str, object]:
L300: def register(self, subclass: type[_T]) -> type[_T]:
L312: def _collect_bases_data(bases: tuple[type[Any], ...]) -> tuple[set[str], set[str],
dict[str, ModelPrivateAttr]]:
L330: def __fields__(self) -> dict[str, FieldInfo]:
L339: def __pydantic_fields_complete__(self) -> bool:
L357: def __dir__(self) -> list[str]:
L364: def init_private_attributes(self: BaseModel, context: Any, /) -> None:
L388: def get_model_post_init(namespace: dict[str, Any], bases: tuple[type[Any], ...]) ->
Callable[..., Any] | None:
L400: def inspect_namespace( # noqa C901
L537: def set_default_hash_func(cls: type[BaseModel], bases: tuple[type[Any], ...]) -> None:
L550: def make_hash_func(cls: type[BaseModel]) -> Any:
L553: def hash_func(self: Any) -> int:
```

```

L566: def set_model_fields(
L600: def complete_model_class(
L724: def set_deprecated_descriptors(cls: type[BaseModel]) -> None:
L743: class _DeprecatedFieldDescriptor:
L754: def __init__(self, msg: str, wrapped_property: property | None = None) -> None:
L758: def __set_name__(self, cls: type[BaseModel], name: str) -> None:
L761: def __get__(self, obj: BaseModel | None, obj_type: type[BaseModel] | None = None) ->
Any:
L776: def __set__(self, obj: Any, value: Any) -> NoReturn:
L780: class _PydanticWeakRef:
L797: def __init__(self, obj: Any):
L805: def __call__(self) -> Any:
L811: def __reduce__(self) -> tuple[Callable, tuple[weakref.ReferenceType | None]]:
L815: def build_lenient_weakvaluedict(d: dict[str, Any] | None) -> dict[str, Any] | None:
L835: def unpack_lenient_weakvaluedict(d: dict[str, Any] | None) -> dict[str, Any] | None:
L852: def default_ignored_types() -> tuple[type[Any], ...]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_known_annotated_metadata.py

```

L101: def as_jsonable_value(v: Any) -> Any:
L107: def expand_grouped_metadata(annotations: Iterable[Any]) -> Iterable[Any]:
L148: def _get_at_to_constraint_map() -> dict[type, str]:
L169: def apply_known_metadata(annotation: Any, schema: CoreSchema) -> CoreSchema | None: #
noqa: C901
L231: def _apply_constraint_with_incompatibility_info(
L310: def val_func(v: Any) -> Any:
L321: def val_func(v: Any) -> Any:
L342: def collect_known_metadata(annotations: Iterable[Any]) -> tuple[dict[str, Any],
list[Any]]:
L387: def check_metadata(metadata: dict[str, Any], allowed: Iterable[str], source_type: Any)
-> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_decorators.py

```

L32: class ValidatorDecoratorInfo:
L56: class FieldValidatorDecoratorInfo:
L79: class RootValidatorDecoratorInfo:
L93: class FieldSerializerDecoratorInfo:
L116: class ModelSerializerDecoratorInfo:
L135: class ModelValidatorDecoratorInfo:
L165: class PydanticDescriptorProxy(Generic[ReturnType]):
L183: def __post_init__(self):

```

```

L189: def _call_wrapped_attr(self, func: Callable[[Any], None], *, name: str) ->
PydanticDescriptorProxy[ReturnType]:
L199: def __get__(self, obj: object | None, obj_type: type[object] | None = None) ->
PydanticDescriptorProxy[ReturnType]:
L206: def __set_name__(self, instance: Any, name: str) -> None:
L210: def __getattr__(self, name: str, /) -> Any:
L219: class Decorator(Generic[DecoratorInfoType]):
L240: def build(
L276: def bind_to_cls(self, cls: Any) -> Decorator[DecoratorInfoType]:
L293: def get_bases(tp: type[Any]) -> tuple[type[Any], ...]:
L310: def mro(tp: type[Any]) -> tuple[type[Any], ...]:
L328: def mro_for_bases(bases: tuple[type[Any], ...]) -> tuple[type[Any], ...]:
L329: def merge_seqs(seqs: list[deque[type[Any]]]) -> Iterable[type[Any]]:
L359: def get_attribute_from_bases(tp: type[Any] | tuple[type[Any], ...], name: str) -> Any:
L394: def get_attribute_from_base_dicts(tp: type[Any], name: str) -> Any:
L416: class DecoratorInfos:
L432: def build(
L488: def _validate(self) -> None:
L499: def update_from_config(self, config_wrapper: ConfigWrapper) -> None:
L505: def _decorator_infos_for_class(
L550: def inspect_validator(
L590: def inspect_field_serializer(serializer: Callable[..., Any], mode: Literal['plain',
'wrap']) -> tuple[bool, bool]:
L629: def inspect_annotated_serializer(serializer: Callable[..., Any], mode: Literal['plain',
'wrap']) -> bool:
L657: def inspect_model_serializer(serializer: Callable[..., Any], mode: Literal['plain',
'wrap']) -> bool:
L685: def _serializer_info_arg(mode: Literal['plain', 'wrap'], n_positional: int) -> bool |
None:
L710: def is_instance_method_from_sig(function: AnyDecoratorCallable) -> bool:
L729: def ensure_classmethod_based_on_signature(function: AnyDecoratorCallable) -> Any:
L745: def _is_classmethod_from_sig(function: AnyDecoratorCallable) -> bool:
L753: def unwrap_wrapped_function(
L805: def get_callable_return_type(
L839: def count_positional_required_params(sig: Signature) -> int:
L861: def ensure_property(f: Any) -> Any:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_decorators_v1.py

```

L15: class V1OnlyValueValidator(Protocol):
L18: def __call__(self, __value: Any) -> Any: ...
L21: class V1ValidatorWithValues(Protocol):
L24: def __call__(self, __value: Any, values: dict[str, Any]) -> Any: ...
L27: class V1ValidatorWithValuesKwOnly(Protocol):
L30: def __call__(self, __value: Any, *, values: dict[str, Any]) -> Any: ...
L33: class V1ValidatorWithKwargs(Protocol):

```

```

L36: def __call__(self, __value: Any, **kwargs: Any) -> Any: ...
L39: class V1ValidatorWithValuesAndKwargs(Protocol):
L42: def __call__(self, __value: Any, values: dict[str, Any], **kwargs: Any) -> Any: ...
L50: def can_be_keyword(param: Parameter) -> bool:
L54: def make_generic_v1_field_validator(validator: V1Validator) ->
core_schema.WithInfoValidatorFunction:
L95: def wrapper1(value: Any, info: core_schema.ValidationInfo) -> Any:
L102: def wrapper2(value: Any, _: core_schema.ValidationInfo) -> Any:
L113: class V1RootValidatorFunction(Protocol):
L116: def __call__(self, __values: RootValidatorValues) -> RootValidatorValues: ...
L119: class V2CoreBeforeRootValidator(Protocol):
L122: def __call__(self, __values: RootValidatorValues, __info: core_schema.ValidationInfo)
-> RootValidatorValues: ...
L125: class V2CoreAfterRootValidator(Protocol):
L128: def __call__(
L133: def make_v1_generic_root_validator(
L147: def _wrapper1(values: RootValidatorValues, _: core_schema.ValidationInfo) ->
RootValidatorValues:
L153: def _wrapper2(fields_tuple: RootValidatorFieldsTuple, _: core_schema.ValidationInfo) ->
RootValidatorFieldsTuple:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_names
pace_utils.py**

```

L30: class NamespacesTuple(NamedTuple):
L36: def eval_type(typ: type[Any], ns: NamespacesTuple) -> None:
L48: def get_module_ns_of(obj: Any) -> dict[str, Any]:
L66: class LazyLocalNamespace(Mapping[str, Any]):
L86: def __init__(self, *namespaces: MappingNamespace) -> None:
L90: def data(self) -> dict[str, Any]:
L93: def __len__(self) -> int:
L96: def __getitem__(self, key: str) -> Any:
L99: def __contains__(self, key: object) -> bool:
L102: def __iter__(self) -> Iterator[str]:
L106: def ns_for_function(obj: Callable[..., Any], parent_namespace: MappingNamespace | None
= None) -> NamespacesTuple:
L143: class NsResolver:
L170: def func() -> None:
L173: class Model(BaseModel):
L192: class Sub:
L195: class Model:
L223: def __init__(
L233: def types_namespace(self) -> NamespacesTuple:
L284: def push(self, typ: type[Any] | TypeAliasType, /) -> Generator[None]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_typing_extra.py

```

L47: def is_annotated(tp: Any, /) -> bool:
L59: def annotated_type(tp: Any, /) -> Any | None:
L64: def unpack_type(tp: Any, /) -> Any | None:
L69: def is_hashable(tp: Any, /) -> bool:
L82: def is_callable(tp: Any, /) -> bool:
L102: def is_classvar_annotation(tp: Any, /) -> bool:
L145: def is_finalvar(tp: Any, /) -> bool:
L164: def is_none_type(tp: Any, /) -> bool:
L180: def is_namedtuple(tp: Any, /) -> bool:
L196: def is_generic_alias(tp: Any, /) -> bool:
L215: def parent_frame_namespace(*, parent_depth: int = 2, force: bool = False) -> dict[str, Any] | None:
L225: def func() -> None:
L228: class C:
L279: def _type_convert(arg: Any) -> Any:
L297: def safe_get_annotations(obj: Any) -> dict[str, Any]:
L314: def get_model_type_hints(
L373: def get_cls_type_hints(
L403: def try_eval_type(
L428: def eval_type(
L449: def eval_type_lenient(
L458: def eval_type_backport(
L504: def _eval_type_backport(
L534: def _eval_type(
L569: def is_backport_fixable_error(e: TypeError) -> bool:
L575: def signature_no_eval(f: Callable[..., Any]) -> Signature:
L585: def get_function_type_hints(
L629: def _make_forward_ref(
L662: def get_type_hints( # noqa: C901

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_discriminated_union.py

```

L19: class MissingDefinitionForUnionRef(Exception):
L24: def __init__(self, ref: str) -> None:
L29: def set_discriminator_in_metadata(schema: CoreSchema, discriminator: Any) -> None:
L34: def apply_discriminator(
L73: class _ApplyInferredDiscriminator:
L86: def __init__(self, discriminator: str, definitions: dict[str, core_schema.CoreSchema]):
L140: def apply(self, schema: core_schema.CoreSchema) -> core_schema.CoreSchema:
L170: def _apply_to_root(self, schema: core_schema.CoreSchema) -> core_schema.CoreSchema:
L237: def _handle_choice(self, choice: core_schema.CoreSchema) -> None:
L292: def _is_discriminator_shared(self, choice: core_schema.TaggedUnionSchema) -> bool:

```

```

L304: def _infer_discriminator_values_for_choice( # noqa C901
L375: def _infer_discriminator_values_for_typed_dict_choice(
L389: def _infer_discriminator_values_for_model_choice(
L400: def _infer_discriminator_values_for_dataclass_choice(
L413: def _infer_discriminator_values_for_field(self, field: CoreSchemaField, source: str) ->
list[str | int]:
L432: def _infer_discriminator_values_for_inner_schema(
L478: def _set_unique_choice_for_values(self, choice: core_schema.CoreSchema, values:
Sequence[str | int]) -> None:

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pydantic/_internal/_utils.py

```

L74: def can_be_positional(param: Parameter) -> bool:
L78: def func(a, /, b, *, c):
L93: def sequence_like(v: Any) -> bool:
L97: def lenient_isinstance(o: Any, class_or_tuple: type[Any] | tuple[type[Any], ...] | None)
-> bool: # pragma: no cover
L104: def lenient_issubclass(cls: Any, class_or_tuple: Any) -> bool: # pragma: no cover
L113: def is_model_class(cls: Any) -> TypeGuard[type[BaseModel]]:
L122: def is_valid_identifier(identifier: str) -> bool:
L133: def deep_update(mapping: dict[KeyType, Any], *updating_mappings: dict[KeyType, Any]) ->
dict[KeyType, Any]:
L144: def update_not_none(mapping: dict[Any, Any], **update: Any) -> None:
L151: def unique_list(
L173: class ValueItems(_repr.Representation):
L178: def __init__(self, value: Any, items: AbstractSetIntStr | MappingIntStrAny) -> None:
L186: def is_excluded(self, item: Any) -> bool:
L193: def is_included(self, item: Any) -> bool:
L200: def for_element(self, e: int | str) -> AbstractSetIntStr | MappingIntStrAny | None:
L207: def _normalize_indexes(self, items: MappingIntStrAny, v_length: int) -> dict[int | str,
Any]:
L245: def merge(cls, base: Any, override: Any, intersect: bool = False) -> Any:
L283: def _coerce_items(items: AbstractSetIntStr | MappingIntStrAny) -> MappingIntStrAny:
L294: def _coerce_value(cls, value: Any) -> Any:
L300: def is_true(v: Any) -> bool:
L303: def __repr_args__(self) -> _repr.ReprArgs:
L309: def LazyClassAttribute(name: str, get_value: Callable[[], T]) -> T: ...
L313: class LazyClassAttribute:
L319: def __init__(self, name: str, get_value: Callable[[], Any]) -> None:
L324: def value(self) -> Any:
L327: def __get__(self, instance: Any, owner: type[Any]) -> None:
L336: def smart_deepcopy(obj: Obj) -> Obj:
L360: def all_identical(left: Iterable[Any], right: Iterable[Any]) -> bool:
L375: def get_first_not_none(a: Any, b: Any) -> Any:
L381: class SafeGetItemProxy:
L393: def __getitem__(self, key: str, /) -> Any:
L402: def __contains__(self, key: str, /) -> bool:
L410: class deprecated_instance_property(Generic[_ModelT, _RT]):

```

```

L418: def __init__(self, fget: Callable[[type[_ModelT]], _RT], /) -> None:
L423: def __get__(self, instance: None, objtype: type[_ModelT]) -> _RT: ...
L430: def __get__(self, instance: _ModelT, objtype: type[_ModelT]) -> _RT: ...
L431: def __get__(self, instance: _ModelT | None, objtype: type[_ModelT]) -> _RT:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_signature.py

```

L18: class _HAS_DEFAULT_FACTORY_CLASS:
L19: def __repr__(self):
L26: def _field_name_for_signature(field_name: str, field_info: FieldInfo) -> str:
L47: def _process_param_defaults(param: Parameter) -> Parameter:
L81: def _generate_signature_parameters( # noqa: C901 (ignore complexity, could use a
refactor)
L165: def generate_pydantic_signature(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_dataclasses.py

```

L40: class PydanticDataclass(StandardDataclass, Protocol):
L62: def __pydantic_fields_complete__(cls) -> bool: ...
L65: def set_dataclass_fields(
L85: def complete_dataclass(
L118: def __init__(__dataclass_self__: PydanticDataclass, *args: Any, **kwargs: Any) -> None:
L193: def is_stdlib_dataclass(cls: type[Any], /) -> TypeIs[type[StandardDataclass]]:
L208: def as_dataclass_field(pydantic_field: FieldInfo) -> dataclasses.Field[Any]:
L230: def patch_base_fields(cls: type[Any]) -> Generator[None]:
L249: class A:
L257: class B(A):
L267: class A:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_generics.py

```

L42: class LimitedDict(dict[KT, VT]):
L43: def __init__(self, size_limit: int = _LIMITED_DICT_SIZE) -> None:
L47: def __setitem__(self, key: KT, value: VT, /) -> None:
L62: class DeepChainMap(ChainMap[KT, VT]): # type: ignore
L67: class DeepChainMap(ChainMap):
L74: def clear(self) -> None:

```



```

L78: def __setitem__(self, key: KT, value: VT) -> None:
L82: def __delitem__(self, key: KT) -> None:
L99: class PydanticGenericMetadata(TypedDict):
L105: def create_generic_submodel(
L152: def _get_caller_frame_info(depth: int = 2) -> tuple[str | None, bool]:
L177: def iter_contained_typevars(v: Any) -> Iterator[TypeVar]:
L196: def get_args(v: Any) -> Any:
L203: def get_origin(v: Any) -> Any:
L210: def get_standard_typevars_map(cls: Any) -> dict[TypeVar, Any] | None:
L227: def get_model_typevars_map(cls: type[BaseModel]) -> dict[TypeVar, Any]:
L245: def replace_types(type_: Any, type_map: Mapping[TypeVar, Any] | None) -> Any:
L345: def map_generic_model_arguments(cls: type[BaseModel], args: tuple[Any, ...]) ->
dict[TypeVar, Any]:
L353: class Model[T, U, V = int](BaseModel): ...
L402: def generic_recursion_self_type(
L433: def recursively_defined_type_refs() -> set[str]:
L441: def get_cached_generic_type_early(parent: type[BaseModel], typevar_values: Any) ->
type[BaseModel] | None:
L461: def get_cached_generic_type_late(
L471: def set_cached_generic_type(
L488: def _union_orderings_key(typevar_values: Any) -> Any:
L509: def _early_cache_key(cls: type[BaseModel], typevar_values: Any) ->
GenericTypesCacheKey:
L521: def _late_cache_key(origin: type[BaseModel], args: tuple[Any, ...], typevar_values:
Any) -> GenericTypesCacheKey:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_schema_a_gather.py

```

L19: class GatherResult(TypedDict):
L34: class MissingDefinitionError(LookupError):
L37: def __init__(self, schema_reference: str, /) -> None:
L42: class GatherContext:
L69: def traverse_metadata(schema: AllSchemas, ctx: GatherContext) -> None:
L75: def traverse_definition_ref(def_ref_schema: DefinitionReferenceSchema, ctx:
GatherContext) -> None:
L96: def traverse_schema(schema: AllSchemas, context: GatherContext) -> None:
L195: def gather_schemas_for_cleaning(schema: CoreSchema, definitions: dict[str, CoreSchema])
-> GatherResult:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_mock_val_ser.py

```

L21: class MockCoreSchema(Mapping[str, Any]):

```

```

L28: def __init__(
L40: def __getitem__(self, key: str) -> Any:
L43: def __len__(self) -> int:
L46: def __iter__(self) -> Iterator[str]:
L49: def _get_built(self) -> CoreSchema:
L60: def rebuild(self) -> CoreSchema | None:
L71: class MockValSer(Generic[ValSer]):
L78: def __init__(
L91: def __getattr__(self, item: str) -> None:
L102: def rebuild(self) -> ValSer | None:
L112: def set_type_adapter_mocks(adapter: TypeAdapter) -> None:
L124: def attempt_rebuild_fn(attr_fn: Callable[[TypeAdapter], T]) -> Callable[[], T | None]:
L125: def handler() -> T | None:
L151: def set_model_mocks(cls: type[BaseModel], undefined_name: str = 'all referenced types')
-> None:
L163: def attempt_rebuild_fn(attr_fn: Callable[[type[BaseModel]], T]) -> Callable[[], T |
None]:
L164: def handler() -> T | None:
L190: def set_dataclass_mocks(cls: type[PydanticDataclass], undefined_name: str = 'all
referenced types') -> None:
L204: def attempt_rebuild_fn(attr_fn: Callable[[type[PydanticDataclass]], T]) -> Callable[[],
T | None]:
L205: def handler() -> T | None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_core_u
tils.py**

```

L41: def is_core_schema(
L47: def is_core_schema_field(
L53: def is_function_with_inner_schema(
L59: def is_list_like_schema_with_items_schema(
L65: def get_type_ref(type_: Any, args_override: tuple[type[Any], ...] | None = None) -> str:
L103: def get_ref(s: core_schema.CoreSchema) -> None | str:
L110: def _clean_schema_for_pretty_print(obj: Any, strip_metadata: bool = True) -> Any: #
pragma: no cover
L141: def pretty_print_core_schema(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/plugin/_loader.py

```

L22: def get_plugins() -> Iterable[PydanticPluginProtocol]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/plugin/__init__.py

```

L30: class SchemaTypePath(NamedTuple):
L40: class PydanticPluginProtocol(Protocol):
L43: def new_schema_validator(
L75: class BaseValidateHandlerProtocol(Protocol):
L85: def on_success(self, result: Any) -> None:
L93: def on_error(self, error: ValidationError) -> None:
L101: def on_exception(self, exception: Exception) -> None:
L110: class ValidatePythonHandlerProtocol(BaseValidateHandlerProtocol, Protocol):
L113: def on_enter(
L140: class ValidateJsonHandlerProtocol(BaseValidateHandlerProtocol, Protocol):
L143: def on_enter(
L171: class ValidateStringsHandlerProtocol(BaseValidateHandlerProtocol, Protocol):
L174: def on_enter(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/plugin/_schema_validator.py

```

L22: def create_schema_validator(
L56: class PluggableSchemaValidator:
L61: def __init__(
L95: def __getattr__(self, name: str) -> Any:
L99: def build_wrapper(func: Callable[P, R], event_handlers:
List[BaseValidateHandlerProtocol]) -> Callable[P, R]:
L109: def wrapper(*args: P.args, **kwargs: P.kwargs) -> R:
L131: def filter_handlers(handler_cls: BaseValidateHandlerProtocol, method_name: str) ->
bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/class_validators.py

```

L21: class _OnlyValueValidatorClsMethod(Protocol):
L22: def __call__(self, __cls: Any, __value: Any) -> Any: ...
L24: class _V1ValidatorWithValuesClsMethod(Protocol):
L25: def __call__(self, __cls: Any, __value: Any, values: dict[str, Any]) -> Any: ...
L27: class _V1ValidatorWithValuesKwOnlyClsMethod(Protocol):
L28: def __call__(self, __cls: Any, __value: Any, *, values: dict[str, Any]) -> Any: ...
L30: class _V1ValidatorWithKwargsClsMethod(Protocol):
L31: def __call__(self, __cls: Any, **kwargs: Any) -> Any: ...
L33: class _V1ValidatorWithValuesAndKwargsClsMethod(Protocol):
L34: def __call__(self, __cls: Any, values: dict[str, Any], **kwargs: Any) -> Any: ...
L36: class _V1RootValidatorClsMethod(Protocol):
L37: def __call__(
L82: def validator(
L138: def dec(f: Any) -> _decorators.PydanticDescriptorProxy[Any]:

```

```

L159: def root_validator(
L172: def root_validator(
L185: def root_validator(
L204: def root_validator(
L248: def dec(f: Callable[..., Any] | classmethod[Any, Any, Any] | staticmethod[Any, Any]) ->
Any:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/copy_internals.py

```

L29: def _iter(
L98: def _copy_and_set_values(
L124: def _get_value(
L198: def _calculate_keys(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/json.py

```

L29: def isoformat(o: Union[datetime.date, datetime.time]) -> str:
L33: def decimal_encoder(dec_value: Decimal) -> Union[int, float]:
L86: def pydantic_encoder(obj: Any) -> Any:
L117: def custom_pydantic_encoder(type_encoders: dict[Any, Callable[[type[Any]], Any]], obj:
Any) -> Any:
L136: def timedelta_isoformat(td: datetime.timedelta) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/parse.py

```

L20: class Protocol(str, Enum):
L26: def load_str_bytes(
L60: def load_file(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/config.py

```

L19: class _ConfigMetaclass(type):
L20: def __getattr__(self, item: str) -> Any:

```

```

L30: class BaseConfig(metaclass=_ConfigMetaclass):
L37: def __getattr__(self, item: str) -> Any:
L49: def __init_subclass__(cls, **kwargs: Any) -> None:
L54: class _ExtraMeta(type):
L55: def __getattr__(self, __name: str) -> Any:
L69: class Extra(metaclass=_ExtraMeta):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/tools.py

```

L30: def parse_obj_as(type_: type[T], obj: Any, type_name: NameFactory | None = None) -> T:
L49: def schema_of(
L85: def schema_json_of(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/decorator.py

```

L30: def validate_arguments(
L36: def validate_arguments(func: 'AnyCallableT') -> 'AnyCallableT': ...
L43: def validate_arguments(func: Optional['AnyCallableT'] = None, *, config: 'ConfigType' =
None) -> Any:
L51: def validate(_func: 'AnyCallable') -> 'AnyCallable':
L55: def wrapper_function(*args: Any, **kwargs: Any) -> Any:
L76: class ValidatedFunction:
L77: def __init__(self, function: 'AnyCallable', config: 'ConfigType'):
L145: def init_model_instance(self, *args: Any, **kwargs: Any) -> BaseModel:
L149: def call(self, *args: Any, **kwargs: Any) -> Any:
L153: def build_values(self, args: tuple[Any, ...], kwargs: dict[str, Any]) -> dict[str,
Any]:
L196: def execute(self, m: BaseModel) -> Any:
L229: def create_model(self, fields: dict[str, Any], takes_args: bool, takes_kwargs: bool,
config: 'ConfigType') -> None:
L243: class DecoratorBaseModel(BaseModel):
L246: def check_args(cls, v: Optional[list[Any]]) -> Optional[list[Any]]:
L254: def check_kwargs(cls, v: Optional[dict[str, Any]]) -> Optional[dict[str, Any]]:
L264: def check_positional_only(cls, v: Optional[list[str]]) -> None:
L274: def check_duplicate_kwargs(cls, v: Optional[list[str]]) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/class_validators.py

```

L16: class Validator:
L19: def __init__(
L52: def validator(
L92: def dec(f: AnyCallable) -> 'AnyClassMethod':
L108: def root_validator(_func: AnyCallable) -> 'AnyClassMethod':
L113: def root_validator(
L119: def root_validator(
L133: def dec(f: AnyCallable) -> 'AnyClassMethod':
L143: def _prepare_validator(function: AnyCallable, allow_reuse: bool) -> 'AnyClassMethod':
L161: class ValidatorGroup:
L162: def __init__(self, validators: 'ValidatorListDict') -> None:
L166: def get_validators(self, name: str) -> Optional[Dict[str, Validator]]:
L176: def check_for_unused(self) -> None:
L195: def extract_validators(namespace: Dict[str, Any]) -> Dict[str, List[Validator]]:
L209: def extract_root_validators(namespace: Dict[str, Any]) -> Tuple[List[AnyCallable],
List[Tuple[bool, AnyCallable]]]:
L234: def inherit_validators(base_validators: 'ValidatorListDict', validators:
'ValidatorListDict') -> 'ValidatorListDict':
L242: def make_generic_validator validator: AnyCallable) -> 'ValidatorCallable':
L281: def prep_validators(v_funcs: Iterable[AnyCallable]) -> 'ValidatorsList':
L288: def _generic_validator_cls(validator: AnyCallable, sig: 'Signature', args: Set[str]) ->
'ValidatorCallable':
L322: def _generic_validator_basic(validator: AnyCallable, sig: 'Signature', args: Set[str])
-> 'ValidatorCallable':
L355: def gather_all_validators(type_: 'ModelOrDc') -> Dict[str, 'AnyClassMethod']:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/mypy.py

```

L87: def parse_mypy_version(version: str) -> Tuple[int, ...]:
L98: def plugin(version: str) -> 'TypingType[Plugin]':
L108: class PydanticPlugin(Plugin):
L109: def __init__(self, options: Options) -> None:
L114: def get_base_class_hook(self, fullname: str) -> 'Optional[Callable[[ClassDefContext],
None]]':
L122: def get_metaclass_hook(self, fullname: str) -> 'Optional[Callable[[ClassDefContext],
None]]':
L127: def get_function_hook(self, fullname: str) -> 'Optional[Callable[[FunctionContext],
Type]]':
L133: def get_method_hook(self, fullname: str) -> 'Optional[Callable[[MethodContext], Type]]':
L138: def get_class_decorator_hook(self, fullname: str) ->
Optional[Callable[[ClassDefContext], None]]:
L147: def report_config_data(self, ctx: ReportConfigContext) -> Dict[str, Any]:
L154: def _pydantic_model_class_maker_callback(self, ctx: ClassDefContext) -> None:
L158: def _pydantic_model_metaclass_marker_callback(self, ctx: ClassDefContext) -> None:
L171: def _pydantic_field_callback(self, ctx: FunctionContext) -> 'Type':
L225: class PydanticPluginConfig:
L239: def __init__(self, options: Options) -> None:
L258: def to_data(self) -> Dict[str, Any]:

```

```

L262: def from_orm_callback(ctx: MethodContext) -> Type:
L287: class PydanticModelTransformer:
L297: def __init__(self, ctx: ClassDefContext, plugin_config: PydanticPluginConfig) -> None:
L301: def transform(self) -> None:
L326: def adjust_validator_signatures(self) -> None:
L344: def collect_config(self) -> 'ModelConfigData':
L375: def collect_fields(self, model_config: 'ModelConfigData') ->
List['PydanticModelField']:
L459: def add_initializer(self, fields: List['PydanticModelField'], config:
'ModelConfigData', is_settings: bool) -> None:
L481: def add_construct_method(self, fields: List['PydanticModelField']) -> None:
L539: def set_frozen(self, fields: List['PydanticModelField'], frozen: bool) -> None:
L572: def get_config_update(self, substmt: AssignmentStmt) -> Optional['ModelConfigData']:
L601: def get_is_required(cls: ClassDef, stmt: AssignmentStmt, lhs: NameExpr) -> bool:
L627: def type_has_implicit_default(type_: Optional[ProperType]) -> bool:
L644: def get_alias_info(stmt: AssignmentStmt) -> Tuple[Optional[str], bool]:
L672: def get_field_arguments(
L688: def should_init_forbid_extra(self, fields: List['PydanticModelField'], config:
'ModelConfigData') -> bool:
L703: def is_dynamic_alias_present(fields: List['PydanticModelField'], has_alias_generator:
bool) -> bool:
L718: class PydanticModelField:
L719: def __init__(
L729: def to_var(self, info: TypeInfo, use_alias: bool) -> Var:
L735: def to_argument(self, info: TypeInfo, typed: bool, force_optional: bool, use_alias:
bool) -> Argument:
L747: def serialize(self) -> JsonDict:
L751: def deserialize(cls, info: TypeInfo, data: JsonDict) -> 'PydanticModelField':
L755: class ModelConfigData:
L756: def __init__(
L772: def set_values_dict(self) -> Dict[str, Any]:
L775: def update(self, config: Optional['ModelConfigData']) -> None:
L781: def setdefault(self, key: str, value: Any) -> None:
L794: def error_from_orm(model_name: str, api: CheckerPluginInterface, context: Context) ->
None:
L798: def error_invalid_config_value(name: str, api: SemanticAnalyzerPluginInterface,
context: Context) -> None:
L802: def error_required_dynamic_aliases(api: SemanticAnalyzerPluginInterface, context:
Context) -> None:
L806: def error_unexpected_behavior(
L816: def error_untyped_fields(api: SemanticAnalyzerPluginInterface, context: Context) ->
None:
L820: def error_default_and_default_factory_specified(api: CheckerPluginInterface, context:
Context) -> None:
L824: def add_method(
L907: def get_fullname(x: Union[FuncBase, SymbolNode]) -> str:
L917: def get_name(x: Union[FuncBase, SymbolNode]) -> str:
L927: def parse_toml(config_file: str) -> Optional[Dict[str, Any]]:

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pydantic/v1/fields.py

```

L69: class UndefinedType:
L70: def __repr__(self) -> str:
L73: def __copy__(self: T) -> T:
L76: def __reduce__(self) -> str:
L79: def __deepcopy__(self: T, _: Any) -> T:
L97: class FieldInfo(Representation):
L151: def __init__(self, default: Any = Undefined, **kwargs: Any) -> None:
L180: def __repr_args__(self) -> 'ReprArgs':
L189: def get_constraints(self) -> Set[str]:
L197: def update_from_config(self, from_config: Dict[str, Any]) -> None:
L216: def _validate(self) -> None:
L221: def Field(
L364: class ModelField(Representation):
L393: def __init__(
L436: def get_default(self) -> Any:
L440: def _get_field_info(
L484: def infer(
L516: def set_config(self, config: Type['BaseConfig']) -> None:
L534: def alt_alias(self) -> bool:
L537: def prepare(self) -> None:
L557: def _set_default_and_type(self) -> None:
L581: def _type_analysis(self) -> None: # noqa: C901 (ignore complexity)
L758: def prepare_discriminated_union_sub_fields(self) -> None:
L786: def _create_sub_type(self, type_: Type[Any], name: str, *, for_keys: bool = False) ->
'ModelField':
L814: def populate_validators(self) -> None:
L850: def validate(
L898: def _validate_sequence_like( # noqa: C901 (ignore complexity)
L955: def _validate_iterable(
L970: def _validate_tuple(
L1000: def _validate_mapping_like(
L1035: def _get_mapping_value(self, original: T, converted: Dict[Any, Any]) -> Union[T,
Dict[Any, Any]]:
L1053: def _validate_singleton(
L1100: def _validate_discriminated_union(
L1149: def _apply_validators(
L1159: def is_complex(self) -> bool:
L1171: def _type_display(self) -> PyObjectStr:
L1190: def __repr_args__(self) -> 'ReprArgs':
L1204: class ModelPrivateAttr(Representation):
L1207: def __init__(self, default: Any = Undefined, *, default_factory:
Optional[NoArgAnyCallable] = None) -> None:
L1211: def get_default(self) -> Any:
L1214: def __eq__(self, other: Any) -> bool:
L1221: def PrivateAttr(
L1246: class DeferredType:
L1252: def is_finalvar_with_default_val(type_: Type[Any], val: Any) -> bool:

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/annotated_types.py

```

L13: def is_legacy_typeddict(typeddict_cls: Type['TypedDict']) -> bool: # type:
    ignore[valid-type]
L18: def is_legacy_typeddict(_: Any) -> Any:
L22: def create_model_from_typeddict(
L58: def create_model_from_namedtuple(namedtuple_cls: Type['NamedTuple'], **kwargs: Any) ->
    Type['BaseModel']:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/env_settings.py

```

L19: class SettingsError(ValueError):
L23: class BaseSettings(BaseModel):
L31: def __init__(
L50: def _build_values(
L82: class Config(BaseConfig):
L94: def prepare_field(cls, field: ModelField) -> None:
L122: def customise_sources(
L131: def parse_env_var(cls, field_name: str, raw_val: str) -> Any:
L138: class InitSettingsSource:
L141: def __init__(self, init_kwargs: Dict[str, Any]):
L144: def __call__(self, settings: BaseSettings) -> Dict[str, Any]:
L147: def __repr__(self) -> str:
L151: class EnvSettingsSource:
L154: def __init__(
L166: def __call__(self, settings: BaseSettings) -> Dict[str, Any]: # noqa C901
L213: def _read_env_files(self, case_sensitive: bool) -> Dict[str, Optional[str]]:
L231: def field_is_complex(self, field: ModelField) -> Tuple[bool, bool]:
L247: def explode_env_vars(self, field: ModelField, env_vars: Mapping[str, Optional[str]]) ->
    Dict[str, Any]:
L268: def __repr__(self) -> str:
L275: class SecretsSettingsSource:
L278: def __init__(self, secrets_dir: Optional[StrPath]):
L281: def __call__(self, settings: BaseSettings) -> Dict[str, Any]:
L322: def __repr__(self) -> str:
L326: def read_env_file(
L341: def find_case_path(dir_path: Path, file_name: str, case_sensitive: bool) ->
    Optional[Path]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/networks.py

```

L44: class Parts(TypedDict, total=False):
L56: class HostParts(TypedDict, total=False):
L66: class Parts(dict):
L113: def url_regex() -> Pattern[str]:
L123: def multi_host_url_regex() -> Pattern[str]:
L141: def ascii_domain_regex() -> Pattern[str]:
L152: def int_domain_regex() -> Pattern[str]:
L161: def host_regex() -> Pattern[str]:
L171: class AnyUrl(str):
L184: def __new__(cls, url: Optional[str], **kwargs) -> object:
L187: def __init__(
L215: def build(
L259: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L263: def __get_validators__(cls) -> 'CallableGenerator':
L267: def validate(cls, value: Any, field: 'ModelField', config: 'BaseConfig') -> 'AnyUrl':
L289: def _build_url(cls, m: Match[str], url: str, parts: 'Parts') -> 'AnyUrl':
L311: def _match_url(url: str) -> Optional[Match[str]]:
L315: def _validate_port(port: Optional[str]) -> None:
L320: def validate_parts(cls, parts: 'Parts', validate_port: bool = True) -> 'Parts':
L342: def validate_host(cls, parts: 'Parts') -> Tuple[str, Optional[str], str, bool]:
L384: def get_default_parts(parts: 'Parts') -> 'Parts':
L388: def apply_default_parts(cls, parts: 'Parts') -> 'Parts':
L394: def __repr__(self) -> str:
L399: class AnyHttpUrl(AnyUrl):
L405: class HttpUrl(AnyHttpUrl):
L412: def get_default_parts(parts: 'Parts') -> 'Parts':
L416: class FileUrl(AnyUrl):
L423: class MultiHostDsn(AnyUrl):
L426: def __init__(self, *args: Any, hosts: Optional[List['HostParts']] = None, **kwargs:
Any):
L431: def _match_url(url: str) -> Optional[Match[str]]:
L435: def validate_parts(cls, parts: 'Parts', validate_port: bool = True) -> 'Parts':
L439: def _build_url(cls, m: Match[str], url: str, parts: 'Parts') -> 'MultiHostDsn':
L487: class PostgresDsn(MultiHostDsn):
L504: class CockroachDsn(AnyUrl):
L513: class AmqpDsn(AnyUrl):
L518: class RedisDsn(AnyUrl):
L524: def get_default_parts(parts: 'Parts') -> 'Parts':
L532: class MongoDsn(AnyUrl):
L537: def get_default_parts(parts: 'Parts') -> 'Parts':
L543: class KafkaDsn(AnyUrl):
L547: def get_default_parts(parts: 'Parts') -> 'Parts':
L554: def stricturl(
L575: def import_email_validator() -> None:
L583: class EmailStr(str):
L585: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L589: def __get_validators__(cls) -> 'CallableGenerator':
L597: def validate(cls, value: Union[str]) -> str:
L601: class NameEmail(Representation):
L604: def __init__(self, name: str, email: str):
L608: def __eq__(self, other: Any) -> bool:

```

```

L612: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L616: def __get_validators__(cls) -> 'CallableGenerator':
L622: def validate(cls, value: Any) -> 'NameEmail':
L628: def __str__(self) -> str:
L632: class IPvAnyAddress(_BaseAddress):
L636: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L640: def __get_validators__(cls) -> 'CallableGenerator':
L644: def validate(cls, value: Union[str, bytes, int]) -> Union[IPv4Address, IPv6Address]:
L656: class IPvAnyInterface(_BaseAddress):
L660: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L664: def __get_validators__(cls) -> 'CallableGenerator':
L668: def validate(cls, value: NetworkType) -> Union[IPv4Interface, IPv6Interface]:
L680: class IPvAnyNetwork(_BaseNetwork): # type: ignore
L682: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L686: def __get_validators__(cls) -> 'CallableGenerator':
L690: def validate(cls, value: NetworkType) -> Union[IPv4Network, IPv6Network]:
L711: def validate_email(value: Union[str]) -> Tuple[str, str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/datetime_parsers.py

```

L66: def get_numeric(value: StrBytesIntFloat, native_expected_type: str) -> Union[None, int, float]:
L77: def from_unix_seconds(seconds: Union[int, float]) -> datetime:
L89: def _parse_timezone(value: Optional[str], error: Type[Exception]) -> Union[None, int, timezone]:
L105: def parse_date(value: Union[date, StrBytesIntFloat]) -> date:
L137: def parse_time(value: Union[time, StrBytesIntFloat]) -> time:
L175: def parse_datetime(value: Union[datetime, StrBytesIntFloat]) -> datetime:
L213: def parse_duration(value: StrBytesIntFloat) -> timedelta:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/typing.py

```

L60: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
L65: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
L74: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
L81: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
L101: def get_all_type_hints(obj: Any, globalns: Any = None, localns: Any = None) -> Any:
L126: def get_origin(tp: Type[Any]) -> Optional[Type[Any]]:
L135: def get_origin(tp: Type[Any]) -> Optional[Type[Any]]:
L150: def get_args(tp: Type[Any]) -> Tuple[Any, ...]:
L168: def _generic_get_args(tp: Type[Any]) -> Tuple[Any, ...]:
L188: def get_args(tp: Type[Any]) -> Tuple[Any, ...]:
L207: def convert_generics(tp: Type[Any]) -> Type[Any]:

```

```

L218: def convert_generics(tp: Type[Any]) -> Type[Any]:
L261: def is_union(tp: Optional[Type[Any]]) -> bool:
L270: def is_union(tp: Optional[Type[Any]]) -> bool:
L357: def is_none_type(type_: Any) -> bool:
L362: def is_none_type(type_: Any) -> bool:
L375: def is_none_type(type_: Any) -> bool:
L379: def display_as_type(v: Type[Any]) -> str:
L397: def resolve_annotations(raw_annotations: Dict[str, Type[Any]], module_name:
Optional[str]) -> Dict[str, Type[Any]]:
L432: def is_callable_type(type_: Type[Any]) -> bool:
L436: def is_literal_type(type_: Type[Any]) -> bool:
L440: def literal_values(type_: Type[Any]) -> Tuple[Any, ...]:
L444: def all_literal_values(type_: Type[Any]) -> Tuple[Any, ...]:
L457: def is_namedtuple(type_: Type[Any]) -> bool:
L467: def is_typeddict(type_: Type[Any]) -> bool:
L477: def _check_typeddict_special(type_: Any) -> bool:
L481: def is_typeddict_special(type_: Any) -> bool:
L491: def is_new_type(type_: Type[Any]) -> bool:
L498: def new_type_supertype(type_: Type[Any]) -> Type[Any]:
L504: def _check_classvar(v: Optional[Type[Any]]) -> bool:
L511: def _check_finalvar(v: Optional[Type[Any]]) -> bool:
L521: def is_classvar(ann_type: Type[Any]) -> bool:
L533: def is_finalvar(ann_type: Type[Any]) -> bool:
L537: def update_field_forward_refs(field: 'ModelField', globalns: Any, localns: Any) ->
None:
L559: def update_model_forward_refs(
L598: def get_class(type_: Type[Any]) -> Union[None, bool, Type[Any]]:
L616: def get_sub_types(tp: Any) -> List[Any]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/json.py

```

L19: def isoformat(o: Union[datetime.date, datetime.time]) -> str:
L23: def decimal_encoder(dec_value: Decimal) -> Union[int, float]:
L72: def pydantic_encoder(obj: Any) -> Any:
L93: def custom_pydantic_encoder(type_encoders: Dict[Any, Callable[[Type[Any]], Any]], obj:
Any) -> Any:
L106: def timedelta_isoformat(td: datetime.timedelta) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/parse.py

```

L10: class Protocol(str, Enum):
L15: def load_str_bytes(
L47: def load_file(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/schema.py

```

L96: def _apply_modify_schema(
L109: def schema(
L162: def model_schema(
L200: def get_field_info_schema(field: ModelField, schema_overrides: bool = False) ->
Tuple[Dict[str, Any], bool]:
L222: def field_schema(
L289: def get_field_schema_validations(field: ModelField) -> Dict[str, Any]:
L322: def get_model_name_map(unique_models: TypeModelSet) -> Dict[TypeModelOrEnum, str]:
L349: def get_flat_models_from_model(model: Type['BaseModel'], known_models:
Optional[TypeModelSet] = None) -> TypeModelSet:
L369: def get_flat_models_from_field(field: ModelField, known_models: TypeModelSet) ->
TypeModelSet:
L398: def get_flat_models_from_fields(fields: Sequence[ModelField], known_models:
TypeModelSet) -> TypeModelSet:
L416: def get_flat_models_from_models(models: Sequence[Type['BaseModel']]) -> TypeModelSet:
L428: def get_long_model_name(model: TypeModelOrEnum) -> str:
L432: def field_type_schema(
L551: def model_process_schema(
L601: def model_type_schema(
L655: def enum_process_schema(enum: Type[Enum], *, field: Optional[ModelField] = None) ->
Dict[str, Any]:
L681: def field_singleton_sub_fields_schema(
L804: def add_field_type_to_schema(field_type: Any, schema_: Dict[str, Any]) -> None:
L818: def get_schema_ref(name: str, ref_prefix: Optional[str], ref_template: str,
schema_overrides: bool) -> Dict[str, Any]:
L826: def field_singleton_schema( # noqa: C901 (ignore complexity)
L954: def multitypes_literal_field_for_schema(values: Tuple[Any, ...], field: ModelField) ->
ModelField:
L976: def encode_default(dft: Any) -> Any:
L1001: def get_annotation_from_field_info(
L1030: def get_annotation_with_constraints(annotation: Any, field_info: FieldInfo) ->
Tuple[Type[Any], Set[str]]: # noqa: C901
L1040: def go(type_: Any) -> Type[Any]:
L1093: def constraint_func(**kw: Any) -> Type[Any]: # noqa: F811
L1100: def constraint_func(**kw: Any) -> Type[Any]:
L1109: def constraint_func(**kw: Any) -> Type[Any]:
L1150: def normalize_name(name: str) -> str:
L1157: class SkipField(Exception):
L1162: def __init__(self, message: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/dataclasses.py

```

L17: class M:

```

```

L66: class Dataclass:
L80: def __init__(self, *args: object, **kwargs: object) -> None:
L84: def __get_validators__(cls: Type['Dataclass']) -> 'CallableGenerator':
L88: def __validate__(cls: Type['DataclassT'], v: Any) -> 'DataclassT':
L106: def dataclass(
L123: def dataclass(
L143: def dataclass(
L159: def dataclass(
L176: def dataclass(
L198: def wrap(cls: Type[Any]) -> 'DataclassClassOrWrapper':
L242: def set_validation(cls: Type['DataclassT'], value: bool) ->
Generator[Type['DataclassT'], None, None]:
L251: class DataclassProxy:
L254: def __init__(self, dc_cls: Type['Dataclass']) -> None:
L257: def __call__(self, *args: Any, **kwargs: Any) -> Any:
L261: def __getattr__(self, name: str) -> Any:
L264: def __setattr__(self, __name: str, __value: Any) -> None:
L267: def __instancecheck__(self, instance: Any) -> bool:
L270: def __copy__(self) -> 'DataclassProxy':
L273: def __deepcopy__(self, memo: Any) -> 'DataclassProxy':
L277: def _add_pydantic_validation_attributes( # noqa: C901 (ignore complexity)
L291: def handle_extra_init(self: 'Dataclass', *args: Any, **kwargs: Any) -> None:
L310: def new_post_init(self: 'Dataclass', *args: Any, **kwargs: Any) -> None:
L328: def new_init(self: 'Dataclass', *args: Any, **kwargs: Any) -> None:
L363: def _get_validators(cls: 'DataclassClassOrWrapper') -> 'CallableGenerator':
L367: def _validate_dataclass(cls: Type['DataclassT'], v: Any) -> 'DataclassT':
L380: def create_pydantic_model_from_dataclass(
L421: def _is_field_cached_property(obj: 'Dataclass', k: str) -> bool:
L426: def _is_field_cached_property(obj: 'Dataclass', k: str) -> bool:
L430: def _dataclass_validate_values(self: 'Dataclass') -> None:
L452: def _dataclass_validate_assignment_setattr(self: 'Dataclass', name: str, value: Any) ->
None:
L465: def is_builtin_dataclass(cls: Type[Any]) -> bool:
L477: class A:
L481: class B(A):
L494: def make_dataclass_validator(dc_cls: Type['Dataclass'], config: Type[BaseConfig]) ->
'CallableGenerator':

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/validators.py

```

L60: def str_validator(v: Any) -> Union[str]:
L75: def strict_str_validator(v: Any) -> Union[str]:
L81: def bytes_validator(v: Any) -> Union[bytes]:
L94: def strict_bytes_validator(v: Any) -> Union[bytes]:
L107: def bool_validator(v: Any) -> bool:
L128: def int_validator(v: Any) -> int:
L147: def strict_int_validator(v: Any) -> int:
L153: def float_validator(v: Any) -> float:

```

```

L163: def strict_float_validator(v: Any) -> float:
L169: def float_finite_validator(v: 'Number', field: 'ModelField', config: 'BaseConfig') ->
'Number':
L179: def number_multiple_validator(v: 'Number', field: 'ModelField') -> 'Number':
L188: def number_size_validator(v: 'Number', field: 'ModelField') -> 'Number':
L203: def constant_validator(v: 'Any', field: 'ModelField') -> 'Any':
L216: def anystr_length_validator(v: 'StrBytes', config: 'BaseConfig') -> 'StrBytes':
L230: def anystr_strip_whitespace(v: 'StrBytes') -> 'StrBytes':
L234: def anystr_upper(v: 'StrBytes') -> 'StrBytes':
L238: def anystr_lower(v: 'StrBytes') -> 'StrBytes':
L242: def ordered_dict_validator(v: Any) -> 'AnyOrderedDict':
L252: def dict_validator(v: Any) -> Dict[Any, Any]:
L262: def list_validator(v: Any) -> List[Any]:
L271: def tuple_validator(v: Any) -> Tuple[Any, ...]:
L280: def set_validator(v: Any) -> Set[Any]:
L289: def frozenset_validator(v: Any) -> FrozenSet[Any]:
L298: def deque_validator(v: Any) -> Deque[Any]:
L307: def enum_member_validator(v: Any, field: 'ModelField', config: 'BaseConfig') -> Enum:
L316: def uuid_validator(v: Any, field: 'ModelField') -> UUID:
L340: def decimal_validator(v: Any) -> Decimal:
L359: def hashable_validator(v: Any) -> Hashable:
L366: def ip_v4_address_validator(v: Any) -> IPv4Address:
L376: def ip_v6_address_validator(v: Any) -> IPv6Address:
L386: def ip_v4_network_validator(v: Any) -> IPv4Network:
L402: def ip_v6_network_validator(v: Any) -> IPv6Network:
L418: def ip_v4_interface_validator(v: Any) -> IPv4Interface:
L428: def ip_v6_interface_validator(v: Any) -> IPv6Interface:
L438: def path_validator(v: Any) -> Path:
L448: def path_exists_validator(v: Any) -> Path:
L455: def callable_validator(v: Any) -> AnyCallable:
L467: def enum_validator(v: Any) -> Enum:
L474: def int_enum_validator(v: Any) -> IntEnum:
L481: def make_literal_validator(type_: Any) -> Callable[[Any], Any]:
L489: def literal_validator(v: Any) -> Any:
L498: def constr_length_validator(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig')
-> 'StrBytes':
L512: def constr_strip_whitespace(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig')
-> 'StrBytes':
L520: def constr_upper(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig') ->
'StrBytes':
L528: def constr_lower(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig') ->
'StrBytes':
L535: def validate_json(v: Any, config: 'BaseConfig') -> Any:
L550: def make_arbitrary_type_validator(type_: Type[T]) -> Callable[[T], T]:
L551: def arbitrary_type_validator(v: Any) -> T:
L559: def make_class_validator(type_: Type[T]) -> Callable[[Any], Type[T]]:
L560: def class_validator(v: Any) -> Type[T]:
L568: def any_class_validator(v: Any) -> Type[T]:
L574: def none_validator(v: Any) -> 'Literal[None]':
L580: def pattern_validator(v: Any) -> Pattern[str]:
L595: def make_namedtuple_validator(

```

```

L607: def namedtuple_validator(values: Tuple[Any, ...]) -> NamedTupleT:
L620: def make_typeddict_validator(
L632: def typeddict_validator(values: 'TypedDict') -> Dict[str, Any]: # type:
ignore[valid-type]
L638: class IfConfig:
L639: def __init__(self, validator: AnyCallable, *config_attr_names: str, ignored_value: Any
= False) -> None:
L644: def check(self, config: Type['BaseConfig']) -> bool:
L699: def find_validators( # noqa: C901 (ignore complexity)

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/config.py

```

L19: class SchemaExtraCallable(Protocol):
L21: def __call__(self, schema: Dict[str, Any]) -> None:
L25: def __call__(self, schema: Dict[str, Any], model_class: Type[BaseModel]) -> None:
L34: class Extra(str, Enum):
L46: class ConfigDict(TypedDict, total=False):
L80: class BaseConfig:
L118: def get_field_info(cls, name: str) -> Dict[str, Any]:
L143: def prepare_field(cls, field: 'ModelField') -> None:
L150: def get_config(config: Union[ConfigDict, Type[object], None]) -> Type[BaseConfig]:
L161: class Config(BaseConfig):
L169: def inherit_config(self_config: 'ConfigType', parent_config: 'ConfigType', **namespace:
Any) -> 'ConfigType':
L186: def prepare_config(config: Type[BaseConfig], cls_name: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/_hypothesis_plugin.py

```

L58: def is_valid_email(s: str) -> bool:
L122: def add_luhn_digit(card_number: str) -> str:
L185: def _registered(typ: Type[pydantic.types.T]) -> Type[pydantic.types.T]:
L190: def _registered(typ: pydantic.types.ConstrainedNumberMeta) ->
pydantic.types.ConstrainedNumberMeta:
L194: def _registered(
L208: def resolves(
L211: def inner(f): # type: ignore
L223: def resolve_json(cls): # type: ignore[no-untyped-def]
L243: def resolve_conbytes(cls): # type: ignore[no-untyped-def] # pragma: no cover
L264: def resolve_condecimal(cls): # type: ignore[no-untyped-def]
L282: def resolve_confloat(cls): # type: ignore[no-untyped-def]
L314: def resolve_conint(cls): # type: ignore[no-untyped-def]
L337: def resolve_condate(cls): # type: ignore[no-untyped-def]
L356: def resolve_constr(cls): # type: ignore[no-untyped-def] # pragma: no cover

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/utils.py

```

L122: def import_string(dotted_path: str) -> Any:
L141: def truncate(v: Union[str], *, max_len: int = 80) -> str:
L158: def sequence_like(v: Any) -> bool:
L162: def validate_field_name(bases: Iterable[Type[Any]], field_name: str) -> None:
L174: def lenient_isinstance(o: Any, class_or_tuple: Union[Type[Any], Tuple[Type[Any], ...],
None]) -> bool:
L181: def lenient_issubclass(cls: Any, class_or_tuple: Union[Type[Any], Tuple[Type[Any],
...], None]) -> bool:
L190: def in_ipython() -> bool:
L202: def is_valid_identifier(identifier: str) -> bool:
L214: def deep_update(mapping: Dict[KeyType, Any], *updating_mappings: Dict[KeyType, Any]) ->
Dict[KeyType, Any]:
L225: def update_not_none(mapping: Dict[Any, Any], **update: Any) -> None:
L229: def almost_equal_floats(value_1: float, value_2: float, *, delta: float = 1e-8) ->
bool:
L236: def generate_model_signature(
L301: def get_model(obj: Union[Type['BaseModel'], Type['Dataclass']]) -> Type['BaseModel']:
L314: def to_camel(string: str) -> str:
L318: def to_lower_camel(string: str) -> str:
L328: def unique_list(
L351: class PyObjectStr(str):
L357: def __repr__(self) -> str:
L361: class Representation:
L371: def __repr_args__(self) -> 'ReprArgs':
L382: def __repr_name__(self) -> str:
L388: def __repr_str__(self, join_str: str) -> str:
L391: def __pretty__(self, fmt: Callable[[Any], Any], **kwargs: Any) -> Generator[Any, None,
None]:
L406: def __str__(self) -> str:
L409: def __repr__(self) -> str:
L412: def __rich_repr__(self) -> 'RichReprResult':
L421: class GetterDict(Representation):
L430: def __init__(self, obj: Any):
L433: def __getitem__(self, key: str) -> Any:
L439: def get(self, key: Any, default: Any = None) -> Any:
L442: def extra_keys(self) -> Set[Any]:
L448: def keys(self) -> List[Any]:
L455: def values(self) -> List[Any]:
L458: def items(self) -> Iterator[Tuple[str, Any]]:
L462: def __iter__(self) -> Iterator[str]:
L467: def __len__(self) -> int:
L470: def __contains__(self, item: Any) -> bool:
L473: def __eq__(self, other: Any) -> bool:
L476: def __repr_args__(self) -> 'ReprArgs':
L479: def __repr_name__(self) -> str:
L483: class ValueItems(Representation):

```

```

L490: def __init__(self, value: Any, items: Union['AbstractSetIntStr', 'MappingIntStrAny'])
-> None:
L498: def is_excluded(self, item: Any) -> bool:
L506: def is_included(self, item: Any) -> bool:
L514: def for_element(self, e: 'IntStr') -> Optional[Union['AbstractSetIntStr',
'MappingIntStrAny']]:
L523: def _normalize_indexes(self, items: 'MappingIntStrAny', v_length: int) ->
'DictIntStrAny':
L563: def merge(cls, base: Any, override: Any, intersect: bool = False) -> Any:
L602: def _coerce_items(items: Union['AbstractSetIntStr', 'MappingIntStrAny']) ->
'MappingIntStrAny':
L616: def _coerce_value(cls, value: Any) -> Any:
L622: def is_true(v: Any) -> bool:
L625: def __repr_args__(self) -> 'ReprArgs':
L629: class ClassAttribute:
L639: def __init__(self, name: str, value: Any) -> None:
L643: def __get__(self, instance: Any, owner: Type[Any]) -> None:
L661: def path_type(p: 'Path') -> str:
L676: def smart_deepcopy(obj: Obj) -> Obj:
L697: def is_valid_field(name: str) -> bool:
L717: def is_valid_private_name(name: str) -> bool:
L724: def all_identical(left: Iterable[Any], right: Iterable[Any]) -> bool:
L740: def assert_never(obj: NoReturn, msg: str) -> NoReturn:
L750: def get_unique_discriminator_alias(all_aliases: Collection[str], discriminator_key:
str) -> str:
L760: def get_discriminator_alias_and_values(tp: Any, discriminator_key: str) -> Tuple[str,
Tuple[str, ...]]:
L801: def _get_union_alias_and_all_values(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/generics.py

```

L64: class GenericModel(BaseModel):
L75: def __class_getitem__(cls: Type[GenericModelT], params: Union[Type[Any],
Tuple[Type[Any], ...]]) -> Type[Any]:
L87: def _cache_key(_params: Any) -> CacheKey:
L171: def __concrete_name__(cls: Type[Any], params: Tuple[Type[Any], ...]) -> str:
L187: def __parameterized_bases__(cls, typevars_map: Parametrization) -> Iterator[Type[Any]]:
L200: class A(GenericModel, Generic[T]):
L203: class B(A[V], Generic[V]):
L210: def build_base_model(
L251: def replace_types(type_: Any, type_map: Mapping[Any, Any]) -> Any:
L333: def check_parameters_count(cls: Type[GenericModel], parameters: Tuple[Any, ...]) ->
None:
L344: def iter_contained_typevars(v: Any) -> Iterator[TypeVarType]:
L359: def get_caller_frame_info() -> Tuple[Optional[str], bool]:
L377: def _prepare_model_fields(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/version.py

```
L16: def version_info() -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/tools.py

```
L18: def _generate_parsing_type_name(type_: Any) -> str:
L23: def _get_parsing_type(type_: Any, *, type_name: Optional[NameFactory] = None) -> Any:
L36: def parse_obj_as(type_: Type[T], obj: Any, *, type_name: Optional[NameFactory] = None)
-> T:
L41: def parse_file_as(
L63: def parse_raw_as(
L85: def schema_of(type_: Any, *, title: Optional[NameFactory] = None, **schema_kwargs: Any)
-> 'DictStrAny':
L90: def schema_json_of(type_: Any, *, title: Optional[NameFactory] = None,
**schema_json_kwargs: Any) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/types.py

```
L137: def _registered(typ: Type[T]) -> Type[T]:
L142: def _registered(typ: 'ConstrainedNumberMeta') -> 'ConstrainedNumberMeta':
L146: def _registered(typ: Union[Type[T], 'ConstrainedNumberMeta']) -> Union[Type[T],
'ConstrainedNumberMeta']:
L157: class ConstrainedNumberMeta(type):
L158: def __new__(cls, name: str, bases: Any, dct: Dict[str, Any]) -> 'ConstrainedInt': #
type: ignore
L175: class StrictBool(int):
L181: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L185: def __get_validators__(cls) -> 'CallableGenerator':
L189: def validate(cls, value: Any) -> bool:
L202: class ConstrainedInt(int, metaclass=ConstrainedNumberMeta):
L211: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L222: def __get_validators__(cls) -> 'CallableGenerator':
L228: def conint(
L250: class PositiveInt(ConstrainedInt):
L253: class NegativeInt(ConstrainedInt):
L256: class NonPositiveInt(ConstrainedInt):
L259: class NonNegativeInt(ConstrainedInt):
L262: class StrictInt(ConstrainedInt):
L269: class ConstrainedFloat(float, metaclass=ConstrainedNumberMeta):
L279: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L299: def __get_validators__(cls) -> 'CallableGenerator':
L306: def confloat(
```

```

L330: class PositiveFloat(ConstrainedFloat):
L333: class NegativeFloat(ConstrainedFloat):
L336: class NonPositiveFloat(ConstrainedFloat):
L339: class NonNegativeFloat(ConstrainedFloat):
L342: class StrictFloat(ConstrainedFloat):
L345: class FiniteFloat(ConstrainedFloat):
L352: class ConstrainedBytes(bytes):
L361: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L365: def __get_validators__(cls) -> 'CallableGenerator':
L373: def conbytes(
L398: class StrictBytes(ConstrainedBytes):
L405: class ConstrainedStr(str):
L416: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L425: def __get_validators__(cls) -> 'CallableGenerator':
L434: def validate(cls, value: Union[str]) -> Union[str]:
L445: def _get_pattern(regex: Union[str, Pattern[str]]) -> str:
L449: def constr(
L478: class StrictStr(ConstrainedStr):
L486: class ConstrainedSet(set): # type: ignore
L496: def __get_validators__(cls) -> 'CallableGenerator':
L500: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L504: def set_length_validator(cls, v: 'Optional[Set[T]]') -> 'Optional[Set[T]]':
L520: def conset(item_type: Type[T], *, min_items: Optional[int] = None, max_items:
Optional[int] = None) -> Type[Set[T]]:
L528: class ConstrainedFrozenSet(frozenset): # type: ignore
L538: def __get_validators__(cls) -> 'CallableGenerator':
L542: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L546: def frozenset_length_validator(cls, v: 'Optional[FrozenSet[T]]') ->
'Optional[FrozenSet[T]]':
L562: def confrozenset(
L575: class ConstrainedList(list): # type: ignore
L586: def __get_validators__(cls) -> 'CallableGenerator':
L592: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L596: def list_length_validator(cls, v: 'Optional[List[T]]') -> 'Optional[List[T]]':
L612: def unique_items_validator(cls, v: 'Optional[List[T]]') -> 'Optional[List[T]]':
L623: def conlist(
L641: class PyObject:
L645: def __get_validators__(cls) -> 'CallableGenerator':
L649: def validate(cls, value: Any) -> Any:
L667: class ConstrainedDecimal(Decimal, metaclass=ConstrainedNumberMeta):
L677: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L688: def __get_validators__(cls) -> 'CallableGenerator':
L695: def validate(cls, value: Decimal) -> Decimal:
L735: def condecimal(
L761: class UUID1(UUID):
L765: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L768: class UUID3(UUID1):
L771: class UUID4(UUID1):
L774: class UUID5(UUID1):
L785: class FilePath(Path):
L787: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:

```

```

L791: def __get_validators__(cls) -> 'CallableGenerator':
L797: def validate(cls, value: Path) -> Path:
L803: class DirectoryPath(Path):
L805: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L809: def __get_validators__(cls) -> 'CallableGenerator':
L815: def validate(cls, value: Path) -> Path:
L825: class JsonWrapper:
L829: class JsonMeta(type):
L830: def __getitem__(self, t: Type[Any]) -> Type[JsonWrapper]:
L841: class Json(metaclass=JsonMeta):
L843: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L850: class SecretField(abc.ABC):
L861: def __eq__(self, other: Any) -> bool:
L864: def __str__(self) -> str:
L867: def __hash__(self) -> int:
L871: def get_secret_value(self) -> Any: # pragma: no cover
L875: class SecretStr(SecretField):
L880: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L891: def __get_validators__(cls) -> 'CallableGenerator':
L896: def validate(cls, value: Any) -> 'SecretStr':
L902: def __init__(self, value: str):
L905: def __repr__(self) -> str:
L908: def __len__(self) -> int:
L911: def display(self) -> str:
L915: def get_secret_value(self) -> str:
L919: class SecretBytes(SecretField):
L924: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L935: def __get_validators__(cls) -> 'CallableGenerator':
L940: def validate(cls, value: Any) -> 'SecretBytes':
L946: def __init__(self, value: bytes):
L949: def __repr__(self) -> str:
L952: def __len__(self) -> int:
L955: def display(self) -> str:
L959: def get_secret_value(self) -> bytes:
L966: class PaymentCardBrand(str, Enum):
L974: def __str__(self) -> str:
L978: class PaymentCardNumber(str):
L990: def __init__(self, card_number: str):
L996: def __get_validators__(cls) -> 'CallableGenerator':
L1006: def masked(self) -> str:
L1011: def validate_digits(cls, card_number: str) -> str:
L1017: def validate_luhn_check_digit(cls, card_number: str) -> str:
L1037: def validate_length_for_brand(cls, card_number: 'PaymentCardNumber') ->
'PaymentCardNumber':
L1059: def _get_brand(card_number: str) -> PaymentCardBrand:
L1092: class ByteSize(int):
L1094: def __get_validators__(cls) -> 'CallableGenerator':
L1098: def validate(cls, v: StrIntFloat) -> 'ByteSize':
L1119: def human_readable(self, decimal: bool = False) -> str:
L1137: def to(self, unit: str) -> float:
L1153: class PastDate(date):

```

```

L1155: def __get_validators__(cls) -> 'CallableGenerator':
L1160: def validate(cls, value: date) -> date:
L1166: class FutureDate(date):
L1168: def __get_validators__(cls) -> 'CallableGenerator':
L1173: def validate(cls, value: date) -> date:
L1180: class ConstrainedDate(date, metaclass=ConstrainedNumberMeta):
L1187: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L1191: def __get_validators__(cls) -> 'CallableGenerator':
L1196: def condate(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/decorator.py

```

L21: def validate_arguments(func: None = None, *, config: 'ConfigType' = None) ->
Callable[['AnyCallableT'], 'AnyCallableT']:
L26: def validate_arguments(func: 'AnyCallableT') -> 'AnyCallableT':
L30: def validate_arguments(func: Optional['AnyCallableT'] = None, *, config: 'ConfigType' =
None) -> Any:
L35: def validate(_func: 'AnyCallable') -> 'AnyCallable':
L39: def wrapper_function(*args: Any, **kwargs: Any) -> Any:
L60: class ValidatedFunction:
L61: def __init__(self, function: 'AnyCallableT', config: 'ConfigType'): # noqa C901
L128: def init_model_instance(self, *args: Any, **kwargs: Any) -> BaseModel:
L132: def call(self, *args: Any, **kwargs: Any) -> Any:
L136: def build_values(self, args: Tuple[Any, ...], kwargs: Dict[str, Any]) -> Dict[str,
Any]:
L179: def execute(self, m: BaseModel) -> Any:
L208: def create_model(self, fields: Dict[str, Any], takes_args: bool, takes_kwargs: bool,
config: 'ConfigType') -> None:
L211: class CustomConfig:
L226: class DecoratorBaseModel(BaseModel):
L228: def check_args(cls, v: Optional[List[Any]]) -> Optional[List[Any]]:
L235: def check_kwargs(cls, v: Optional[Dict[str, Any]]) -> Optional[Dict[str, Any]]:
L244: def check_positional_only(cls, v: Optional[List[str]]) -> None:
L253: def check_duplicate_kwargs(cls, v: Optional[List[str]]) -> None:
L261: class Config(CustomConfig):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/color.py

```

L26: class RGBA:
L33: def __init__(self, r: float, g: float, b: float, alpha: Optional[float]):
L41: def __getitem__(self, item: Any) -> Any:
L63: class Color(Representation):
L66: def __init__(self, value: ColorType) -> None:
L83: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:
L86: def original(self) -> ColorType:

```

```

L92: def as_named(self, *, fallback: bool = False) -> str:
L105: def as_hex(self) -> str:
L119: def as_rgb(self) -> str:
L131: def as_rgb_tuple(self, *, alpha: Optional[bool] = None) -> ColorTuple:
L153: def as_hsl(self) -> str:
L164: def as_hsl_tuple(self, *, alpha: Optional[bool] = None) -> HslColorTuple:
L188: def _alpha_float(self) -> float:
L192: def __get_validators__(cls) -> 'CallableGenerator':
L195: def __str__(self) -> str:
L198: def __repr_args__(self) -> 'ReprArgs':
L201: def __eq__(self, other: Any) -> bool:
L204: def __hash__(self) -> int:
L208: def parse_tuple(value: Tuple[Any, ...]) -> RGBA:
L222: def parse_str(value: str) -> RGBA:
L280: def ints_to_rgba(r: Union[int, str], g: Union[int, str], b: Union[int, str], alpha:
Optional[float]) -> RGBA:
L284: def parse_color_value(value: Union[int, str], max_val: int = 255) -> float:
L299: def parse_float_alpha(value: Union[None, str, float, int]) -> Optional[float]:
L321: def parse_hsl(h: str, h_units: str, sat: str, light: str, alpha: Optional[float] =
None) -> RGBA:
L340: def float_to_255(c: float) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/main.py

```

L98: def validate_custom_root_type(fields: Dict[str, ModelField]) -> None:
L103: def generate_hash_function(frozen: bool) -> Optional[Callable[[Any], int]]:
L104: def hash_function(self_: Any) -> int:
L122: class ModelMetaclass(ABCMeta):
L124: def __new__(mcs, name, bases, namespace, **kwargs): # noqa C901
L175: def is_untouched(v: Any) -> bool:
L321: def __instancecheck__(self, instance: Any) -> bool:
L333: class BaseModel(Representation, metaclass=ModelMetaclass):
L355: def __init__(__pydantic_self__, **data: Any) -> None:
L375: def __setattr__(self, name, value): # noqa: C901 (ignore complexity)
L430: def __getstate__(self) -> 'DictAny':
L438: def __setstate__(self, state: 'DictAny') -> None:
L444: def _init_private_attributes(self) -> None:
L450: def dict(
L484: def json(
L530: def _enforce_dict_if_root(cls, obj: Any) -> Any:
L541: def parse_obj(cls: Type['Model'], obj: Any) -> 'Model':
L552: def parse_raw(
L575: def parse_file(
L595: def from_orm(cls: Type['Model'], obj: Any) -> 'Model':
L609: def construct(cls: Type['Model'], _fields_set: Optional['SetStr'] = None, **values:
Any) -> 'Model':
L632: def _copy_and_set_values(self: 'Model', values: 'DictStrAny', fields_set: 'SetStr', *,
deep: bool) -> 'Model':

```

```

L650: def copy(
L683: def schema(cls, by_alias: bool = True, ref_template: str = default_ref_template) ->
'DictStrAny':
L692: def schema_json(
L702: def __get_validators__(cls) -> 'CallableGenerator':
L706: def validate(cls: Type['Model'], value: Any) -> 'Model':
L745: def _decompose_class(cls: Type['Model'], obj: Any) -> GetterDict:
L752: def _get_value(
L825: def __try_update_forward_refs__(cls, **localns: Any) -> None:
L833: def update_forward_refs(cls, **localns: Any) -> None:
L839: def __iter__(self) -> 'TupleGenerator':
L845: def _iter(
L901: def _calculate_keys(
L928: def __eq__(self, other: Any) -> bool:
L934: def __repr_args__(self) -> 'ReprArgs':
L946: def create_model(
L960: def create_model(
L973: def create_model(
L1053: def validate_model( # noqa: C901 (ignore complexity)

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/error_wrapper
s.py**

```

L16: class _ErrorDictRequired(TypedDict):
L21: class ErrorDict(_ErrorDictRequired, total=False):
L28: class ErrorWrapper(Representation):
L31: def __init__(self, exc: Exception, loc: Union[str, 'Loc']) -> None:
L35: def loc_tuple(self) -> 'Loc':
L41: def __repr_args__(self) -> 'ReprArgs':
L50: class ValidationError(Representation, ValueError):
L53: def __init__(self, errors: Sequence[ErrorList], model: 'ModelOrDc') -> None:
L58: def errors(self) -> List['ErrorDict']:
L67: def json(self, *, indent: Union[None, int, str] = 2) -> str:
L70: def __str__(self) -> str:
L78: def __repr_args__(self) -> 'ReprArgs':
L82: def display_errors(errors: List['ErrorDict']) -> str:
L86: def _display_error_loc(error: 'ErrorDict') -> str:
L90: def _display_error_type_and_ctx(error: 'ErrorDict') -> str:
L99: def flatten_errors(
L119: def error_dict(exc: Exception, config: Type['BaseConfig'], loc: 'Loc') -> 'ErrorDict':
L139: def get_exc_type(cls: Type[Exception]) -> str:
L149: def _get_exc_type(cls: Type[Exception]) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/errors.py


```

L108: def cls_kwargs(cls: Type['PydanticErrorMixin'], ctx: 'DictStrAny') ->
'PydanticErrorMixin':
L119: class PydanticErrorMixin:
L123: def __init__(self, **ctx: Any) -> None:
L126: def __str__(self) -> str:
L129: def __reduce__(self) -> Tuple[Callable[...], 'PydanticErrorMixin'],
Tuple[Type['PydanticErrorMixin'], 'DictStrAny']]:
L133: class PydanticTypeError(PydanticErrorMixin, TypeError):
L137: class PydanticValueError(PydanticErrorMixin, ValueError):
L141: class ConfigError(RuntimeError):
L145: class MissingError(PydanticValueError):
L149: class ExtraError(PydanticValueError):
L153: class NoneIsNotAllowedError(PydanticTypeError):
L158: class NoneIsAllowedError(PydanticTypeError):
L163: class WrongConstantError(PydanticValueError):
L166: def __str__(self) -> str:
L171: class NotNoneError(PydanticTypeError):
L176: class BoolError(PydanticTypeError):
L180: class BytesError(PydanticTypeError):
L184: class DictError(PydanticTypeError):
L188: class EmailError(PydanticValueError):
L192: class UrlError(PydanticValueError):
L196: class UrlSchemeError(UrlError):
L201: class UrlSchemePermittedError(UrlError):
L205: def __init__(self, allowed_schemes: Set[str]):
L209: class UrlUserInfoError(UrlError):
L214: class UrlHostError(UrlError):
L219: class UrlHostTldError(UrlError):
L224: class UrlPortError(UrlError):
L229: class UrlExtraError(UrlError):
L234: class EnumMemberError(PydanticTypeError):
L237: def __str__(self) -> str:
L242: class IntegerError(PydanticTypeError):
L246: class FloatError(PydanticTypeError):
L250: class PathError(PydanticTypeError):
L254: class _PathValueError(PydanticValueError):
L255: def __init__(self, *, path: Path) -> None:
L259: class PathNotExistsError(_PathValueError):
L264: class PathNotAFileError(_PathValueError):
L269: class PathNotADirectoryError(_PathValueError):
L274: class PyObjectError(PydanticTypeError):
L278: class SequenceError(PydanticTypeError):
L282: class IterableError(PydanticTypeError):
L286: class ListError(PydanticTypeError):
L290: class SetError(PydanticTypeError):
L294: class FrozenSetError(PydanticTypeError):
L298: class DequeError(PydanticTypeError):
L302: class TupleError(PydanticTypeError):
L306: class TupleLengthError(PydanticValueError):
L310: def __init__(self, *, actual_length: int, expected_length: int) -> None:
L314: class ListMinLengthError(PydanticValueError):

```

```

L318: def __init__(self, *, limit_value: int) -> None:
L322: class ListMaxLengthError(PydanticValueError):
L326: def __init__(self, *, limit_value: int) -> None:
L330: class ListUniqueItemsError(PydanticValueError):
L335: class SetMinLengthError(PydanticValueError):
L339: def __init__(self, *, limit_value: int) -> None:
L343: class SetMaxLengthError(PydanticValueError):
L347: def __init__(self, *, limit_value: int) -> None:
L351: class FrozenSetMinLengthError(PydanticValueError):
L355: def __init__(self, *, limit_value: int) -> None:
L359: class FrozenSetMaxLengthError(PydanticValueError):
L363: def __init__(self, *, limit_value: int) -> None:
L367: class AnyStrMinLengthError(PydanticValueError):
L371: def __init__(self, *, limit_value: int) -> None:
L375: class AnyStrMaxLengthError(PydanticValueError):
L379: def __init__(self, *, limit_value: int) -> None:
L383: class StrError(PydanticTypeError):
L387: class StrRegexError(PydanticValueError):
L391: def __init__(self, *, pattern: str) -> None:
L395: class _NumberBoundError(PydanticValueError):
L396: def __init__(self, *, limit_value: Union[int, float, Decimal]) -> None:
L400: class NumberNotGtError(_NumberBoundError):
L405: class NumberNotGeError(_NumberBoundError):
L410: class NumberNotLtError(_NumberBoundError):
L415: class NumberNotLeError(_NumberBoundError):
L420: class NumberNotFiniteError(PydanticValueError):
L425: class NumberNotMultipleError(PydanticValueError):
L429: def __init__(self, *, multiple_of: Union[int, float, Decimal]) -> None:
L433: class DecimalError(PydanticTypeError):
L437: class DecimalIsNotFiniteError(PydanticValueError):
L442: class DecimalMaxDigitsError(PydanticValueError):
L446: def __init__(self, *, max_digits: int) -> None:
L450: class DecimalMaxPlacesError(PydanticValueError):
L454: def __init__(self, *, decimal_places: int) -> None:
L458: class DecimalWholeDigitsError(PydanticValueError):
L462: def __init__(self, *, whole_digits: int) -> None:
L466: class DateTimeError(PydanticValueError):
L470: class DateError(PydanticValueError):
L474: class DateNotInThePastError(PydanticValueError):
L479: class DateNotInTheFutureError(PydanticValueError):
L484: class TimeError(PydanticValueError):
L488: class DurationError(PydanticValueError):
L492: class HashableError(PydanticTypeError):
L496: class UUIDError(PydanticTypeError):
L500: class UUIDVersionError(PydanticValueError):
L504: def __init__(self, *, required_version: int) -> None:
L508: class ArbitraryTypeError(PydanticTypeError):
L512: def __init__(self, *, expected_arbitrary_type: Type[Any]) -> None:
L516: class ClassError(PydanticTypeError):
L521: class SubclassError(PydanticTypeError):
L525: def __init__(self, *, expected_class: Type[Any]) -> None:

```

```

L529: class JsonError(PydanticValueError):
L533: class JsonTypeError(PydanticTypeError):
L538: class PatternError(PydanticValueError):
L543: class DataclassTypeError(PydanticTypeError):
L548: class CallableError(PydanticTypeError):
L552: class EnumError(PydanticTypeError):
L557: class IntEnumError(PydanticTypeError):
L562: class IPvAnyAddressError(PydanticValueError):
L566: class IPvAnyInterfaceError(PydanticValueError):
L570: class IPvAnyNetworkError(PydanticValueError):
L574: class IPv4AddressError(PydanticValueError):
L578: class IPv6AddressError(PydanticValueError):
L582: class IPv4NetworkError(PydanticValueError):
L586: class IPv6NetworkError(PydanticValueError):
L590: class IPv4InterfaceError(PydanticValueError):
L594: class IPv6InterfaceError(PydanticValueError):
L598: class ColorError(PydanticValueError):
L602: class StrictBoolError(PydanticValueError):
L606: class NotDigitError(PydanticValueError):
L611: class LuhnValidationError(PydanticValueError):
L616: class InvalidLengthForBrand(PydanticValueError):
L621: class InvalidByteSize(PydanticValueError):
L625: class InvalidByteSizeUnit(PydanticValueError):
L629: class MissingDiscriminator(PydanticValueError):
L634: class InvalidDiscriminator(PydanticValueError):
L641: def __init__(self, *, discriminator_key: str, discriminator_value: Any, allowed_values:
Sequence[Any]) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/experimental/arguments_schema.py

```

L14: def generate_arguments_schema(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/experimental/pipe
line.py**

```

L39: class _ValidateAs:
L45: class _ValidateAsDefer:
L49: def tp(self) -> type[Any]:
L54: class _Transform:
L59: class _PipelineOr:
L65: class _PipelineAnd:
L71: class _Eq:
L76: class _NotEq:

```

```

L81: class _In:
L86: class _NotIn:
L111: class _Constraint:
L122: class _FieldTypeMarker:
L131: class _Pipeline(Generic[_InT, _OutT]):
L136: def transform(
L148: def validate_as(self, tp: type[_NewOutT], *, strict: bool = False) -> _Pipeline[_InT,
    _NewOutT]: ...
L151: def validate_as(
L161: def validate_as(self, tp: Any, *, strict: bool = ...) -> _Pipeline[_InT, Any]: ...
L163: def validate_as(self, tp: type[_NewOutT] | EllipsisType | Any, *, strict: bool = False)
    -> _Pipeline[_InT, Any]: # type: ignore
L175: def validate_as_deferred(self, func: Callable[[], type[_NewOutT]]) -> _Pipeline[_InT,
    _NewOutT]:
L185: def constrain(self: _Pipeline[_InT, _NewOutGe], constraint: annotated_types.Ge) ->
    _Pipeline[_InT, _NewOutGe]: ...
L188: def constrain(self: _Pipeline[_InT, _NewOutGt], constraint: annotated_types.Gt) ->
    _Pipeline[_InT, _NewOutGt]: ...
L191: def constrain(self: _Pipeline[_InT, _NewOutLe], constraint: annotated_types.Le) ->
    _Pipeline[_InT, _NewOutLe]: ...
L194: def constrain(self: _Pipeline[_InT, _NewOutLt], constraint: annotated_types.Lt) ->
    _Pipeline[_InT, _NewOutLt]: ...
L197: def constrain(
L202: def constrain(
L207: def constrain(
L212: def constrain(self: _Pipeline[_InT, _OutT], constraint: annotated_types.Predicate) ->
    _Pipeline[_InT, _OutT]: ...
L215: def constrain(
L220: def constrain(self: _Pipeline[_InT, _OutT], constraint: _Eq) -> _Pipeline[_InT, _OutT]:
    ...
L223: def constrain(self: _Pipeline[_InT, _OutT], constraint: _NotEq) -> _Pipeline[_InT,
    _OutT]: ...
L226: def constrain(self: _Pipeline[_InT, _OutT], constraint: _In) -> _Pipeline[_InT, _OutT]:
    ...
L229: def constrain(self: _Pipeline[_InT, _OutT], constraint: _NotIn) -> _Pipeline[_InT,
    _OutT]: ...
L232: def constrain(self: _Pipeline[_InT, _NewOutT], constraint: Pattern[str]) ->
    _Pipeline[_InT, _NewOutT]: ...
L234: def constrain(self, constraint: _ConstraintAnnotation) -> Any:
L244: def predicate(self: _Pipeline[_InT, _NewOutT], func: Callable[[ _NewOutT ], bool]) ->
    _Pipeline[_InT, _NewOutT]:
L248: def gt(self: _Pipeline[_InT, _NewOutGt], gt: _NewOutGt) -> _Pipeline[_InT, _NewOutGt]:
L252: def lt(self: _Pipeline[_InT, _NewOutLt], lt: _NewOutLt) -> _Pipeline[_InT, _NewOutLt]:
L256: def ge(self: _Pipeline[_InT, _NewOutGe], ge: _NewOutGe) -> _Pipeline[_InT, _NewOutGe]:
L260: def le(self: _Pipeline[_InT, _NewOutLe], le: _NewOutLe) -> _Pipeline[_InT, _NewOutLe]:
L264: def len(self: _Pipeline[_InT, _NewOutLen], min_len: int, max_len: int | None = None) ->
    _Pipeline[_InT, _NewOutLen]:
L269: def multiple_of(self: _Pipeline[_InT, _NewOutDiv], multiple_of: _NewOutDiv) ->
    _Pipeline[_InT, _NewOutDiv]: ...
L272: def multiple_of(self: _Pipeline[_InT, _NewOutMod], multiple_of: _NewOutMod) ->
    _Pipeline[_InT, _NewOutMod]: ...

```

```

L274: def multiple_of(self: _Pipeline[_InT, Any], multiple_of: Any) -> _Pipeline[_InT, Any]:
L278: def eq(self: _Pipeline[_InT, _OutT], value: _OutT) -> _Pipeline[_InT, _OutT]:
L282: def not_eq(self: _Pipeline[_InT, _OutT], value: _OutT) -> _Pipeline[_InT, _OutT]:
L286: def in_(self: _Pipeline[_InT, _OutT], values: Container[_OutT]) -> _Pipeline[_InT,
_OutT]:
L290: def not_in(self: _Pipeline[_InT, _OutT], values: Container[_OutT]) -> _Pipeline[_InT,
_OutT]:
L295: def datetime_tz_naive(self: _Pipeline[_InT, datetime.datetime]) -> _Pipeline[_InT,
datetime.datetime]:
L298: def datetime_tz_aware(self: _Pipeline[_InT, datetime.datetime]) -> _Pipeline[_InT,
datetime.datetime]:
L301: def datetime_tz(
L306: def datetime_with_tz(
L312: def str_lower(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:
L315: def str_upper(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:
L318: def str_title(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:
L321: def str_strip(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:
L324: def str_pattern(self: _Pipeline[_InT, str], pattern: str) -> _Pipeline[_InT, str]:
L327: def str_contains(self: _Pipeline[_InT, str], substring: str) -> _Pipeline[_InT, str]:
L330: def str_starts_with(self: _Pipeline[_InT, str], prefix: str) -> _Pipeline[_InT, str]:
L333: def str_ends_with(self: _Pipeline[_InT, str], suffix: str) -> _Pipeline[_InT, str]:
L337: def otherwise(self, other: _Pipeline[_OtherIn, _OtherOut]) -> _Pipeline[_InT |
_OtherIn, _OutT | _OtherOut]:
L343: def then(self, other: _Pipeline[_OutT, _OtherOut]) -> _Pipeline[_InT, _OtherOut]:
L349: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> cs.CoreSchema:
L361: def __supports_type__(self, _: _OutT) -> bool:
L370: def _check_func(
L373: def handler(v: Any) -> Any:
L384: def _apply_step(step: _Step, s: cs.CoreSchema | None, handler: GetCoreSchemaHandler,
source_type: Any) -> cs.CoreSchema:
L401: def _apply_parse(
L420: def _apply_transform(
L443: def _apply_constraint( # noqa: C901
L459: def check_gt(v: Any) -> bool:
L474: def check_ge(v: Any) -> bool:
L489: def check_lt(v: Any) -> bool:
L504: def check_le(v: Any) -> bool:
L527: def check_len(v: Any) -> bool:
L544: def check_multiple_of(v: Any) -> bool:
L557: def check_tz_aware(v: object) -> bool:
L568: def check_tz_naive(v: object) -> bool:
L590: def predicate_func(v: Any) -> Any:
L605: def check_not_eq(v: Any) -> bool:
L612: def check_eq(v: Any) -> bool:
L619: def check_in(v: Any) -> bool:
L626: def check_not_in(v: Any) -> bool:
L637: def check_pattern(v: object) -> bool:
L645: class _SupportsRange(annotated_types.SupportsLe, annotated_types.SupportsGe, Protocol):
L649: class _SupportsLen(Protocol):
L650: def __len__(self) -> int: ...

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/_distutils_hack/__init__.py

```

L10: def warn_distutils_present():
L25: def clear_distutils():
L45: def enabled():
L63: def ensure_local_distutils():
L80: def do_override():
L92: class _TrivialRe:
L93: def __init__(self, *patterns) -> None:
L96: def match(self, string):
L100: class DistutilsMetaFinder:
L101: def find_spec(self, fullname, path, target=None):
L111: def spec_for_distutils(self):
L132: class DistutilsLoader(importlib.abc.Loader):
L133: def create_module(self, spec):
L137: def exec_module(self, module):
L145: def is_cpython():
L152: def spec_for_pip(self):
L163: def pip_imported_during_build(cls):
L174: def frame_file_is_setup(frame):
L181: def spec_for_sensitive_tests(self):
L214: def add_shim():
L218: class shim:
L219: def __enter__(self) -> None:
L222: def __exit__(self, exc: object, value: object, tb: object) -> None:
L226: def insert_shim():
L230: def _remove_shim():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/compat.py

```

L37: def _resolve_char_detection() -> ModuleType | None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/hooks.py

```

L25: def default_hooks() -> dict[str, list[_t.HookType]]:
L32: def dispatch_hook(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/models.py

```

L109: class RequestEncodingMixin:
L113: def path_url(self) -> str:

```

```

L135: def _encode_params(data: str) -> str: ...
L139: def _encode_params(data: bytes) -> bytes: ...
L143: def _encode_params(
L149: def _encode_params(data: _t.KVDataType) -> str: ...
L152: def _encode_params(
L184: def _encode_files(
L255: class RequestHooksMixin:
L258: def register_hook(
L271: def deregister_hook(self, event: str, hook: _t.HookType) -> bool:
L283: class Request(RequestHooksMixin):
L321: def __init__(
L355: def __repr__(self) -> str:
L358: def prepare(self) -> PreparedRequest:
L376: class PreparedRequest(RequestEncodingMixin, RequestHooksMixin):
L405: def __init__(self) -> None:
L422: def prepare(
L451: def __repr__(self) -> str:
L454: def copy(self) -> PreparedRequest:
L465: def prepare_method(self, method: str | None) -> None:
L472: def _get_idna_encoded_host(host: str) -> str:
L481: def prepare_url(
L563: def prepare_headers(self, headers: Mapping[str, str | bytes] | None) -> None:
L574: def prepare_body(
L652: def prepare_content_length(self, body: _t.BodyType) -> None:
L668: def prepare_auth(
L697: def prepare_cookies(
L720: def prepare_hooks(self, hooks: _t.HooksInputType | None) -> None:
L730: class Response:
L763: def __init__(self) -> None:
L810: def __enter__(self) -> Self:
L813: def __exit__(self, *args: Any) -> None:
L816: def __getstate__(self) -> dict[str, Any]:
L824: def __setstate__(self, state: dict[str, Any]) -> None:
L832: def __repr__(self) -> str:
L835: def __bool__(self) -> bool:
L845: def __nonzero__(self) -> bool:
L855: def __iter__(self) -> Iterator[bytes]:
L860: def ok(self) -> bool:
L875: def is_redirect(self) -> bool:
L882: def is_permanent_redirect(self) -> bool:
L890: def next(self) -> PreparedRequest | None:
L895: def apparent_encoding(self) -> str | None:
L905: def iter_content(
L909: def iter_content(
L912: def iter_content(
L933: def generate() -> Generator[bytes, None, None]:
L976: def iter_lines(
L983: def iter_lines(
L990: def iter_lines(
L1031: def content(self) -> bytes:
L1050: def text(self) -> str:

```

```

L1087: def json(self, **kwargs: Any) -> Any:
L1123: def links(self) -> dict[str, dict[str, str]]:
L1140: def raise_for_status(self) -> None:
L1169: def close(self) -> None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/help.py

```

L37: def _implementation():
L69: def info() -> dict[str, Any]:
L128: def main():

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/api.py

```

L24: def request(
L74: def get(
L90: def options(url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
L102: def head(url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
L117: def post(
L137: def put(
L154: def patch(
L171: def delete(url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/exceptions.py

```

L20: class RequestException(IOError):
L28: def __init__(self, *args: Any, **kwargs: Any) -> None:
L38: class InvalidJSONError(RequestException):
L42: class JSONDecodeError(InvalidJSONError, CompatJSONDecodeError):
L45: def __init__(self, *args: Any, **kwargs: Any) -> None:
L55: def __reduce__(self) -> tuple[Any, ...] | str:
L66: class HTTPError(RequestException):
L70: class ConnectionError(RequestException):
L74: class ProxyError(ConnectionError):
L78: class SSLError(ConnectionError):
L82: class Timeout(RequestException):
L91: class ConnectTimeout(ConnectionError, Timeout):
L98: class ReadTimeout(Timeout):
L102: class URLRequired(RequestException):
L106: class TooManyRedirects(RequestException):
L110: class MissingSchema(RequestException, ValueError):
L114: class InvalidSchema(RequestException, ValueError):
L118: class InvalidURL(RequestException, ValueError):
L122: class InvalidHeader(RequestException, ValueError):
L126: class InvalidProxyURL(InvalidURL):
L130: class ChunkedEncodingError(RequestException):

```



```

L134: class ContentDecodingError(RequestException, BaseHTTPError):
L138: class StreamConsumedError(RequestException, TypeError):
L142: class RetryError(RequestException):
L146: class UnrewindableBodyError(RequestException):
L153: class RequestsWarning(Warning):
L157: class FileModeWarning(RequestsWarning, DeprecationWarning):
L161: class RequestsDependencyWarning(RequestsWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/__init__.py

```

L60: def check_compatibility(
L99: def _check_cryptography(cryptography_version: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/sessions.py

```

L76: def merge_setting(
L108: def merge_hooks(
L127: class SessionRedirectMixin:
L132: def send(self, request: PreparedRequest, **kwargs: Any) -> Response: ...
L134: def get_redirect_target(self, resp: Response) -> str | None:
L154: def should_strip_auth(self, old_url: str, new_url: str) -> bool:
L186: def resolve_redirects(
L309: def rebuild_auth(
L334: def rebuild_proxies(
L370: def rebuild_method(
L395: class Session(SessionRedirectMixin):
L442: def __init__(self) -> None:
L505: def __enter__(self) -> Self:
L508: def __exit__(self, *args: Any) -> None:
L511: def prepare_request(self, request: Request) -> PreparedRequest:
L557: def request(
L655: def get(
L673: def options(self, url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
L684: def head(self, url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
L695: def post(
L714: def put(
L728: def patch(
L742: def delete(self, url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
L752: def send(self, request: PreparedRequest, **kwargs: Any) -> Response:
L831: def merge_environment_settings(
L870: def get_adapter(self, url: str) -> BaseAdapter:
L883: def close(self) -> None:
L888: def mount(self, prefix: str, adapter: BaseAdapter) -> None:
L899: def __getstate__(self) -> dict[str, Any]:
L903: def __setstate__(self, state: dict[str, Any]) -> None:

```

```
L908: def session() -> Session:
```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/utils.py

```
L99: def proxy_bypass_registry(host: str) -> bool:
L137: def proxy_bypass(host: str) -> bool: # noqa
L149: def dict_to_sequence(
L160: def super_len(o: Any) -> int:
L231: def get_netrc_auth(
L283: def guess_filename(obj: Any) -> str | None:
L290: def extract_zipped_paths(path: str) -> str:
L329: def atomic_open(filename: str) -> Generator[BufferedWriter, None, None]:
L341: def from_key_val_list(
L371: def to_key_val_list(value: None) -> None: ...
L373: def to_key_val_list(
L376: def to_key_val_list(
L408: def parse_list_header(value: str) -> list[str]:
L440: def parse_dict_header(value: str) -> dict[str, str | None]:
L475: def unquote_header_value(value: str, is_filename: bool = False) -> str:
L500: def dict_from_cookiejar(cj: CookieJar) -> dict[str, str | None]:
L511: def add_dict_to_cookiejar(cj: CookieJar, cookie_dict: dict[str, str]) -> CookieJar:
L522: def get_encodings_from_content(content: str) -> list[str]:
L547: def _parse_content_type_header(header: str) -> tuple[str, dict[str, Any]]:
L569: def get_encoding_from_headers(headers: CaseInsensitiveDict[str]) -> str | None:
L594: def stream_decode_response_unicode(
L614: def iter_slices(
L618: def iter_slices(
L621: def iter_slices(
L633: def get_unicode_from_response(r: Response) -> str | bytes | None:
L680: def unquote_unreserved(uri: str) -> str:
L704: def requote_uri(uri: str) -> str:
L726: def address_in_network(ip: str, net: str) -> bool:
L741: def dotted_netmask(mask: int) -> str:
L752: def is_ipv4_address(string_ip: str) -> bool:
L763: def is_valid_cidr(string_network: str) -> bool:
L788: def set_environ(env_name: str, value: str | None) -> Generator[None, None, None]:
L810: def should_bypass_proxies(url: str, no_proxy: str | None) -> bool:
L819: def get_proxy(key: str) -> str | None:
L873: def get_environ_proxies(url: str, no_proxy: str | None = None) -> dict[str, str]:
L885: def select_proxy(url: str, proxies: dict[str, str] | None) -> str | None:
L911: def resolve_proxies(
L942: def default_user_agent(name: str = "python-requests") -> str:
L951: def default_headers() -> CaseInsensitiveDict[str]:
L965: def parse_header_links(value: str) -> list[dict[str, str]]:
L1008: def guess_json_utf(data: bytes) -> str | None:
L1040: def prepend_scheme_if_needed(url: str, new_scheme: str) -> str:
L1070: def get_auth_from_url(url: str) -> tuple[str, str]:
L1087: def check_header_validity(header: tuple[str | bytes, str | bytes]) -> None:
L1098: def _validate_header_part(
```

```
L1122: def urldefragauth(url: str) -> str:
L1139: def rewind_body(prepared_request: PreparedRequest) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/_internal_utils.py

```
L26: def to_native_string(string: str | bytes, encoding: str = "ascii") -> str:
L39: def unicode_is_ascii(u_string: str) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/cookies.py

```
L31: class MockRequest:
L45: def __init__(self, request: PreparedRequest) -> None:
L51: def get_type(self) -> str:
L54: def get_host(self) -> str:
L57: def get_origin_req_host(self) -> str:
L60: def get_full_url(self) -> str:
L80: def is_unverifiable(self) -> bool:
L83: def has_header(self, name: str) -> bool:
L86: def get_header(self, name: str, default: str | None = None) -> str | None:
L89: def add_header(self, key: str, val: str) -> None:
L95: def add_unredirected_header(self, name: str, value: str) -> None:
L98: def get_new_headers(self) -> dict[str, str]:
L102: def unverifiable(self) -> bool:
L106: def origin_req_host(self) -> str:
L110: def host(self) -> str:
L114: class MockResponse:
L121: def __init__(self, headers: Any) -> None:
L128: def info(self) -> Any:
L131: def getheaders(self, name: str) -> Any:
L135: def extract_cookies_to_jar(
L153: def get_cookie_header(jar: CookieJar, request: PreparedRequest) -> str | None:
L164: def remove_cookie_by_name(
L185: class CookieConflictError(RuntimeError):
L191: class RequestsCookieJar(CookieJar, MutableMapping[str, str | None]): # type:
ignore[misc]
L211: def get( # type: ignore[override]
L229: def set(
L250: def iterkeys(self) -> Iterator[str]:
L259: def keys(self) -> list[str]: # type: ignore[override]
L267: def itervalues(self) -> Iterator[str | None]:
L276: def values(self) -> list[str | None]: # type: ignore[override]
L284: def iteritems(self) -> Iterator[tuple[str, str | None]]:
L293: def items(self) -> list[tuple[str, str | None]]: # type: ignore[override]
L302: def list_domains(self) -> list[str]:
L310: def list_paths(self) -> list[str]:
```

```

L318: def multiple_domains(self) -> bool:
L331: def get_dict(
L348: def __iter__(self) -> Iterator[Cookie]: # type: ignore[override]
L352: def __contains__(self, name: object) -> bool:
L358: def __getitem__(self, name: str) -> str | None:
L367: def __setitem__(
L376: def __delitem__(self, name: str) -> None:
L382: def set_cookie(self, cookie: Cookie, *args: Any, **kwargs: Any) -> None:
L391: def update( # type: ignore[override]
L401: def _find(
L423: def _find_no_duplicates(
L454: def __getstate__(self) -> dict[str, Any]:
L461: def __setstate__(self, state: dict[str, Any]) -> None:
L467: def copy(self) -> RequestsCookieJar:
L474: def get_policy(self) -> CookiePolicy:
L479: def _copy_cookie_jar(jar: CookieJar | None) -> CookieJar | None: # type:
ignore[reportUnusedFunction] # cross-module usage in models.py
L494: def create_cookie(name: str, value: str, **kwargs: Any) -> Cookie:
L531: def morsel_to_cookie(morsel: Morsel[Any]) -> Cookie:
L564: def cookiejar_from_dict(
L572: def cookiejar_from_dict(
L579: def cookiejar_from_dict(
L604: def merge_cookies(

```

Q_base appwrite/venv/lib/python3.12/site-packages/requests/auth.py

```

L34: def _basic_auth_str(username: bytes | str, password: bytes | str) -> str:
L78: class AuthBase:
L81: def __call__(self, r: PreparedRequest) -> PreparedRequest:
L85: class HTTPBasicAuth(AuthBase):
L92: def __init__(self, username: str, password: str) -> None: ...
L94: def __init__(self, username: bytes, password: bytes) -> None: ...
L96: def __init__(self, username: bytes | str, password: bytes | str) -> None:
L100: def __eq__(self, other: object) -> bool:
L108: def __ne__(self, other: Any) -> bool:
L111: def __call__(self, r: PreparedRequest) -> PreparedRequest:
L116: class HTTPProxyAuth(HTTPBasicAuth):
L119: def __call__(self, r: PreparedRequest) -> PreparedRequest:
L124: class HTTPDigestAuth(AuthBase):
L137: def __init__(self, username: str, password: str) -> None: ...
L139: def __init__(self, username: bytes, password: bytes) -> None: ...
L141: def __init__(self, username: bytes | str, password: bytes | str) -> None:
L147: def init_per_thread_state(self) -> None:
L157: def build_digest_header(self, method: str, url: str) -> str | None:
L176: def md5_utf8(x: str | bytes) -> str:
L184: def sha_utf8(x: str | bytes) -> str:
L192: def sha256_utf8(x: str | bytes) -> str:
L200: def sha512_utf8(x: str | bytes) -> str:
L210: def KD(s: str, d: str) -> str:

```

```

L268: def handle_redirect(self, r: Response, **kwargs: Any) -> None:
L273: def handle_401(self, r: Response, **kwargs: Any) -> Response:
L321: def __call__(self, r: PreparedRequest) -> PreparedRequest:
L345: def __eq__(self, other: object) -> bool:
L353: def __ne__(self, other: Any) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/adapters.py

```

L66: def SOCKSProxyManager(*args: Any, **kwargs: Any) -> None:
L85: def _urllib3_request_context(
L122: class BaseAdapter:
L125: def __init__(self) -> None:
L128: def send(
L153: def close(self) -> None:
L158: class HTTPAdapter(BaseAdapter):
L201: def __init__(
L223: def __getstate__(self) -> dict[str, Any]:
L226: def __setstate__(self, state: dict[str, Any]) -> None:
L239: def init_poolmanager(
L269: def proxy_manager_for(self, proxy: str, **proxy_kwargs: Any) -> Any:
L307: def cert_verify(
L365: def build_response(self, req: PreparedRequest, resp: Any) -> Response:
L403: def build_connection_pool_key_attributes(
L455: def get_connection_with_tls_context(
L512: def get_connection(
L555: def close(self) -> None:
L565: def request_url(
L599: def add_headers(self, request: PreparedRequest, **kwargs: Any) -> None:
L613: def proxy_headers(self, proxy: str) -> dict[str, str]:
L634: def send(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/structures.py

```

L20: class CaseInsensitiveDict(MutableMapping[str, _VT], Generic[_VT]):
L49: def __init__(
L59: def __setitem__(self, key: str, value: _VT) -> None:
L64: def __getitem__(self, key: str) -> _VT:
L67: def __delitem__(self, key: str) -> None:
L70: def __iter__(self) -> Iterator[str]:
L73: def __len__(self) -> int:
L76: def lower_items(self) -> Iterator[tuple[str, _VT]]:
L80: def __eq__(self, other: object) -> bool:
L89: def copy(self) -> CaseInsensitiveDict[_VT]:
L92: def __repr__(self) -> str:
L96: class LookupDict(dict[str, _VT]):

```

```

L101: def __init__(self, name: Any = None) -> None:
L105: def __repr__(self) -> str:
L108: def __getattr__(self, key: str) -> _VT | None:
L118: def __getitem__(self, key: str) -> _VT | None: # type: ignore[override]
L124: def get(self, key: str, default: None = None) -> _VT | None: ...
L127: def get(self, key: str, default: _D | _VT) -> _D | _VT: ...
L129: def get(self, key: str, default: _D | None = None) -> _VT | _D | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/_types.py

```

L28: class SupportsRead(Protocol[_T_co]):
L29: def read(self, length: int = ..., /) -> _T_co: ...
L33: class SupportsItems(Protocol[_KT_co, _VT_co]):
L34: def items(self) -> Iterable[tuple[_KT_co, _VT_co]]: ...
L42: def is_prepared(request: PreparedRequest) -> TypeIs[_ValidatedRequest]:
L64: class _ValidatedRequest(PreparedRequest):
L152: class BaseRequestKwargs(TypedDict, total=False):
L165: class RequestKwargs(BaseRequestKwargs, total=False):
L172: class GetKwargs(BaseRequestKwargs, total=False):
L176: class PostKwargs(BaseRequestKwargs, total=False):
L179: class DataKwargs(BaseRequestKwargs, total=False):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/status_codes.py

```

L109: def _init():
L116: def doc(code: int) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_bdist_wheel.py

```

L50: def safe_name(name: str) -> str:
L57: def safe_version(version: str) -> str:
L74: def _is_32bit_interpreter() -> bool:
L78: def python_tag() -> str:
L82: def get_platform(archive_root: str | None) -> str:
L102: def get_flag(
L119: def get_abi_tag() -> str | None:
L159: def safer_name(name: str) -> str:
L163: def safer_version(version: str) -> str:
L167: def remove_readonly(
L175: def remove_readonly_exc(func: Callable[..., object], path: str, exc: Exception) ->
None:
L180: class bdist_wheel(Command):

```

```

L248: def initialize_options(self):
L269: def finalize_options(self):
L313: def wheel_dist_name(self):
L323: def get_tag(self) -> tuple[str, str, str]:
L381: def run(self):
L471: def write_wheelfile(
L495: def _ensure_relative(self, path: str) -> str:
L503: def license_paths(self) -> Iterable[str]:
L547: def egg2dist(self, egginfo_path: str, distinfo_path: str):
L550: def adios(p: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_metadata.py

```

L20: def _nonblank(str: str) -> bool | Literal[""]:
L25: def yield_lines(iterable: Iterable[str]) -> Iterator[str]:
L43: def _(text: str) -> Iterator[str]:
L47: def split_sections(
L74: def safe_extra(extra: str) -> str:
L82: def safe_name(name: str) -> str:
L89: def requires_to_requires_dist(requirement: Requirement) -> str:
L104: def convert_requirements(requirements: list[str]) -> Iterator[str]:
L116: def generate_requirements(
L147: def pkginfo_to_metadata(egg_info_path: str, pkginfo_path: str) -> Message:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/__main__.py

```

L11: def main() -> NoReturn: # needed for console script

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/macosx_libfile.py

```

L252: def swap32(x: int) -> int:
L261: def get_base_class_and_magic_number(
L288: def read_data(struct_class: type[ctypes.Structure], lib_file: BufferedIOBase):
L292: def extract_macosx_min_system_version(path_to_lib: str):
L300: class FatHeader(BaseClass):
L306: class FatArch(BaseClass):
L311: class FatArch(BaseClass):
L350: def read_mach_header(
L363: class SegmentBase(base_class):
L368: class MachHeader(base_class):
L373: class MachHeader(base_class):
L383: class VersionMinCommand(base_class):

```

```

L390: class VersionBuild(base_class):
L400: def parse_version(version: int) -> tuple[int, int, int]:
L407: def calculate_macosx_platform_tag(archive_root: StrPath, platform_tag: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_setuptools_logging.py

```

L8: def _not_warning(record: logging.LogRecord) -> bool:
L12: def configure() -> None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/wheel/wheelfile.py

```

L33: class WheelError(Exception):
L37: def urlsafe_b64encode(data: bytes) -> bytes:
L42: def urlsafe_b64decode(data: bytes) -> bytes:
L48: def get_zipinfo_datetime(
L58: class WheelFile(ZipFile):
L65: def __init__(
L134: def open(
L140: def _update_crc(newdata: bytes) -> None:
L168: def write_files(self, base_dir: str) -> None:
L190: def write(
L207: def writestr(
L238: def close(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/unpack.py

```

L8: def unpack(path: str, dest: str = ".") -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/convert.py

```

L49: def convert_requires(requires: str, metadata: Message) -> None:
L67: def convert_pkg_info(pkginfo: str, metadata: Message) -> None:
L98: def normalize(name: str) -> str:
L102: class ConvertSource(metaclass=ABCMeta):
L111: def dist_info_dir(self) -> str:
L115: def generate_contents(self) -> Iterator[tuple[str, bytes]]:

```



```

L119: class EggFileSource(ConvertSource):
L120: def __init__(self, path: Path):
L136: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L164: class EggDirectorySource(EggFileSource):
L165: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L193: class WininstFileSource(ConvertSource):
L223: def __init__(self, path: Path):
L253: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L287: def convert(files: list[str], dest_dir: str, verbose: bool) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/__init__.py

```

L15: def unpack_f(args: argparse.Namespace) -> None:
L21: def pack_f(args: argparse.Namespace) -> None:
L27: def convert_f(args: argparse.Namespace) -> None:
L33: def tags_f(args: argparse.Namespace) -> None:
L52: def info_f(args: argparse.Namespace) -> None:
L61: def version_f(args: argparse.Namespace) -> None:
L67: def parse_build_tag(build_tag: str) -> str:
L85: def parser() -> argparse.ArgumentParser:
L157: def main() -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/pack.py

```

L14: def pack(directory: str, dest_dir: str, build_number: str | None) -> None:
L75: def compute_tagline(tags: list[str]) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/info.py

```

L15: def info(path: str, verbose: bool = False) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/tags.py

```

L12: def _compute_tags(original_tags: Iterable[str], new_tags: str | None) -> set[str]:
L26: def tags(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/typing_inspection/introspection.py

```

L28: def is_union_origin(obj: Any, /) -> bool:
L62: def is_union_origin(obj: Any, /) -> bool:
L94: def _literal_type_check(value: Any, /) -> None:
L103: def get_literal_values(
L223: class AnnotationSource(IntEnum):
L247: class Test:
L260: class Test:
L272: class TD(TypedDict):
L285: class NT(NamedTuple):
L297: def func(a: int) -> str:
L317: def allowed_qualifiers(self) -> set[Qualifier]:
L336: class ForbiddenQualifier(Exception):
L342: def __init__(self, qualifier: Qualifier, /) -> None:
L346: class _UnknownTypeEnum(Enum):
L349: def __str__(self) -> str:
L352: def __repr__(self) -> str:
L363: class InspectedAnnotation(NamedTuple):
L375: class C:
L387: def inspect_annotation( # noqa: PLR0915
L511: def _unpack_annotated_inner(
L578: def _unpack_annotated(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/typing_inspection/typing_objects.py

```

L60: def _compile_identity_check_function(member: LiteralString, function_name:
LiteralString) -> FunctionType:
L105: def _compile_isinstance_check_function(member: LiteralString, function_name:
LiteralString) -> FunctionType:
L298: def is_namedtuple(obj: Any, /) -> bool:
L348: def is_newtype(obj: Any, /) -> bool:
L496: def is_typealiastype(obj: Any, /) -> 'TypeIs[TypeAliasType]':
L532: def is_deprecated(obj: Any, /) -> 'TypeIs[deprecated]':
L537: def is_deprecated(obj: Any, /) -> 'TypeIs[deprecated]':

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/service.py

```

L12: class Service:
L13: def __init__(self, client: Client):
L16: def _normalize_value(self, value: Any) -> Any:

```

```
L34: def _parse_response(
```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/query.py

```
L4: class Query():
L5: def __init__(self, method, attribute=None, values=None):
L14: def __str__(self):
L22: def equal(attribute, value):
L26: def not_equal(attribute, value):
L30: def regex(attribute, pattern):
L44: def less_than(attribute, value):
L48: def less_than_equal(attribute, value):
L52: def greater_than(attribute, value):
L56: def greater_than_equal(attribute, value):
L60: def is_null(attribute):
L64: def is_not_null(attribute):
L68: def exists(attributes):
L81: def not_exists(attributes):
L94: def between(attribute, start, end):
L98: def starts_with(attribute, value):
L102: def ends_with(attribute, value):
L106: def select(attributes):
L110: def search(attribute, value):
L114: def order_asc(attribute):
L118: def order_desc(attribute):
L122: def order_random():
L126: def cursor_before(id):
L130: def cursor_after(id):
L134: def limit(limit):
L138: def offset(offset):
L142: def contains(attribute, value):
L152: def contains_any(attribute, value):
L161: def contains_all(attribute, value):
L170: def not_contains(attribute, value):
L174: def not_search(attribute, value):
L178: def not_between(attribute, start, end):
L182: def not_starts_with(attribute, value):
L186: def not_ends_with(attribute, value):
L190: def created_before(value):
L194: def created_after(value):
L198: def created_between(start, end):
L202: def updated_before(value):
L206: def updated_after(value):
L210: def updated_between(start, end):
L214: def or_queries(queries):
L218: def and_queries(queries):
L222: def elem_match(attribute, queries):
L236: def distance_equal(attribute, values, distance, meters=True):
L240: def distance_not_equal(attribute, values, distance, meters=True):
```

```

L244: def distance_greater_than(attribute, values, distance, meters=True):
L248: def distance_less_than(attribute, values, distance, meters=True):
L252: def intersects(attribute, values):
L256: def not_intersects(attribute, values):
L260: def crosses(attribute, values):
L264: def not_crosses(attribute, values):
L268: def overlaps(attribute, values):
L272: def not_overlaps(attribute, values):
L276: def touches(attribute, values):
L280: def not_touches(attribute, values):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/input_file.py

```

L4: class InputFile:
L6: def from_path(cls, path):
L15: def from_bytes(cls, bytes, filename, mime_type = None):

```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/role.py

```

L1: class Role:
L4: def any():
L12: def user(id, status = ""):
L32: def users(status = ""):
L51: def guests():
L63: def team(id, role = ""):
L83: def member(id):
L100: def label(name):

```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/client.py

```

L11: class Client:
L12: def __init__(self):
L26: def set_self_signed(self, status=True):
L30: def set_endpoint(self, endpoint):
L37: def add_header(self, key, value):
L41: def get_headers(self):
L44: def set_project(self, value):
L50: def set_key(self, value):
L56: def set_jwt(self, value):
L62: def set_locale(self, value):
L66: def set_session(self, value):
L72: def set_forwarded_user_agent(self, value):
L78: def set_dev_key(self, value):
L84: def set_cookie(self, value):
L90: def set_impersonate_user_id(self, value):

```

```

L96: def set_impersonate_user_email(self, value):
L102: def set_impersonate_user_phone(self, value):
L108: def call(self, method, path='', headers=None, params=None, response_type='json'):
L176: def chunked_upload(
L258: def flatten(self, data, prefix='', stringify=False):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/operator.py

```

L5: class Condition(Enum):
L16: class Operator():
L17: def __init__(self, method, values=None):
L23: def __str__(self):
L31: def increment(value=1, max=None):
L42: def decrement(value=1, min=None):
L53: def multiply(factor, max=None):
L64: def divide(divisor, min=None):
L77: def modulo(divisor):
L85: def power(exponent, max=None):
L96: def array_append(values):
L100: def array_prepend(values):
L104: def array_insert(index, value):
L108: def array_remove(value):
L112: def array_unique():
L116: def array_intersect(values):
L120: def array_diff(values):
L124: def array_filter(condition, value=None):
L129: def string_concat(value):
L133: def string_replace(search, replace):
L137: def toggle():
L141: def date_add_days(days):
L145: def date_sub_days(days):
L149: def date_set_now():

```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/id.py

```

L5: class ID:
L9: def __hex_timestamp():
L17: def custom(id):
L22: def unique(padding = 7):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/exception.py

```

L1: class AppwriteException(Exception):
L2: def __init__(self, message, code = 0, type = None, response = None):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/permission.py**

```

L1: class Permission:
L4: def read(role):
L8: def write(role):
L12: def create(role):
L16: def update(role):
L20: def delete(role):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/session_list.py**

```

L7: class SessionList(AppwriteModel):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_archive_list.py**

```

L7: class BackupArchiveList(AppwriteModel):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_dropbox.py**

```

L6: class OAuth2Dropbox(AppwriteModel):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_x.py**

```

L6: class OAuth2X(AppwriteModel):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_polygon.py**

```
L7: class ColumnPolygon(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_facebook.py

```
L6: class OAuth2Facebook(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/activity_event_list.py

```
L7: class ActivityEventList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/framework.py

```
L7: class Framework(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algorithm_pass.py

```
L6: class AlgoPhpass(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_float.py

```
L7: class AttributeFloat(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_line.py

```
L7: class AttributeLine(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_web.py

```
L7: class PlatformWeb(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/key.py

```
L6: class Key(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/site.py

```
L7: class Site(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/locale_code.py

```
L6: class LocaleCode(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_restoration.py

```
L6: class BackupRestoration(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/project.py

```
L18: class Project(AppwriteModel):
```


Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/transaction.py

```
L6: class Transaction(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_status.py

```
L7: class HealthStatus(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_windows.py

```
L7: class PlatformWindows(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_membership_privacy.py

```
L6: class PolicyMembershipPrivacy(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/continent.py

```
L6: class Continent(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_ip.py

```
L7: class AttributeIp(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algorithm_bcrypt.py****L6: class AlgoBcrypt(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/ephemeral_key.py****L6: class EphemeralKey(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_policy.py****L6: class BackupPolicy(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/index.py****L7: class Index(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/transaction_list.py****L7: class TransactionList(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/bucket_list.py****L7: class BucketList(AppwriteModel):****Q_base**

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/user_list.py

```
L9: class UserList(AppwriteModel, Generic[T]):
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'UserList[T]':
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_zoom.py

```
L6: class OAuth2Zoom(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/country.py

```
L6: class Country(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_okta.py

```
L6: class OAuth2Okta(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/message.py

```
L7: class Message(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_polygon.py

```
L7: class AttributePolygon(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/language.py

```
L6: class Language(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/document_list.py

```
L9: class DocumentList(AppwriteModel, Generic[T]):
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) ->
'DocumentList[T]':
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/subscriber_list.py

```
L7: class SubscriberList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/headers.py

```
L6: class Headers(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_bitbucket.py

```
L6: class OAuth2Bitbucket(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_github.py

```
L6: class OAuth2Github(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_figma.py****L6: class OAuth2Figma(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_yahoo.py****L6: class OAuth2Yahoo(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/function_list.py****L7: class FunctionList(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/log.py****L6: class Log(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_time.py****L6: class HealthTime(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/database.py****L9: class Database(AppwriteModel):****Q_base**

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
microsoft.py**

```
L6: class OAuth2Microsoft(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_
relationship.py**

```
L7: class AttributeRelationship(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_pa
ssword_dictionary.py**

```
L6: class PolicyPasswordDictionary(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_
email.py**

```
L7: class AttributeEmail(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/key_list.p
y**

```
L7: class KeyList(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
amazon.py**

```
L6: class OAuth2Amazon(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algo_scr
pt_modified.py**

```
L6: class AlgoScriptModified(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/billing_li
mits.py**

```
L6: class BillingLimits(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/phone.py

```
L6: class Phone(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_v
archar.py**

```
L7: class ColumnVarchar(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
autodesk.py**

```
L6: class OAuth2Autodesk(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_
point.py**

```
L7: class AttributePoint(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_t

ext.py

```
L7: class ColumnText(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_factors.py

```
L6: class MfaFactors(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/deployment.py

```
L7: class Deployment(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_boolean.py

```
L7: class ColumnBoolean(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_mediumtext.py

```
L7: class ColumnMediumtext(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/email_template.py

```
L6: class EmailTemplate(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/site_list.p

y

```
L7: class SiteList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/phone_list.py

```
L7: class PhoneList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/bucket.py

```
L6: class Bucket(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/country_list.py

```
L7: class CountryList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/variable.py

```
L6: class Variable(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_type.py

```
L6: class MfaType(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/runtime.py

```
L6: class Runtime(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_bigint.py

```
L7: class ColumnBigint(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_etsy.py

```
L6: class OAuth2Etsy(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_linkedin.py

```
L6: class OAuth2Linkedin(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/execution.py

```
L9: class Execution(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_index_list.py

```
L7: class ColumnIndexList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/jwt.py

```
L6: class Jwt(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/provider_
list.py**

```
L7: class ProviderList(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
slack.py**

```
L6: class OAuth2Slack(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/locale_co
de_list.py**

```
L7: class LocaleCodeList(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
auth0.py**

```
L6: class OAuth2Auth0(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
bitly.py**

```
L6: class OAuth2Bitly(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/proxy_ru
le_list.py**

```
L7: class ProxyRuleList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_list.py

```
L24: class ColumnList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/email_template_list.py

```
L7: class EmailTemplateList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/framework_adapter.py

```
L6: class FrameworkAdapter(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/token.py

```
L6: class Token(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_antivirus.py

```
L7: class HealthAntivirus(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_kick.py

```
L6: class OAuth2Kick(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/index_list.py

```
L7: class IndexList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_keycloak.py

```
L6: class OAuth2Keycloak(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_android.py

```
L7: class PlatformAndroid(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/identity.py

```
L6: class Identity(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/preferences.py

```
L8: class Preferences(AppwriteModel, Generic[T]):
L15: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) ->
'Preferences[T]':
L26: def data(self) -> T:
L30: def data(self, value: T) -> None:
L33: def to_dict(self) -> Dict[str, Any]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/topic_list.py

```
L7: class TopicList(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_
disqus.py**

```
L6: class OAuth2Disqus(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/collection
_list.py**

```
L7: class CollectionList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/topic.py

```
L6: class Topic(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/resource
_token.py**

```
L6: class ResourceToken(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/message
_list.py**

```
L7: class MessageList(AppwriteModel):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_ce
rtificate.py**

```
L6: class HealthCertificate(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/resource_token_list.py

```
L7: class ResourceTokenList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_float.py

```
L7: class ColumnFloat(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/team_list.py

```
L9: class TeamList(AppwriteModel, Generic[T]):
```

```
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'TeamList[T]':
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/team.py

```
L9: class Team(AppwriteModel, Generic[T]):
```

```
L36: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'Team[T]':
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/subscriber.py

```
L7: class Subscriber(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_list.py

```
L24: class AttributeList(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/language_list.py**

```
L7: class LanguageList(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_podio.py**

```
L6: class OAuth2Podio(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/base_model.py**

```
L9: class AppwriteModel(BaseModel):
L17: def from_dict(cls: Type[ModelType], data: Optional[Dict[str, Any]]) ->
Optional[ModelType]:
L23: def to_dict(self) -> Dict[str, Any]:
L26: def to_json(self) -> str:
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_point.py**

```
L7: class ColumnPoint(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/currency.py**

```
L6: class Currency(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_challenge.py**


```
L6: class MfaChallenge(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_password_history.py

```
L6: class PolicyPasswordHistory(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/variable_list.py

```
L7: class VariableList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_discord.py

```
L6: class OAuth2Discord(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_list.py

```
L11: class PlatformList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algorithm.py

```
L6: class AlgoSha(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_varchar.py

```
L7: class AttributeVarchar(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_longtext.py

```
L7: class AttributeLongtext(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_restoration_list.py

```
L7: class BackupRestorationList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/continent_list.py

```
L7: class ContinentList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/document.py

```
L8: class Document(AppwriteModel, Generic[T]):
L38: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'Document[T]':
L49: def data(self) -> T:
L53: def data(self, value: T) -> None:
L56: def to_dict(self) -> Dict[str, Any]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_string.py

```
L7: class ColumnString(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_paypal.py

```
L6: class OAuth2Paypal(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/session.py

```
L6: class Session(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/dev_key.py

```
L6: class DevKey(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_policy_list.py

```
L7: class BackupPolicyList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_apple.py

```
L7: class PlatformApple(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algorithm_script.py

```
L6: class AlgoScript(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/collection.py

```
L25: class Collection(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/proxy_rule.py

```
L8: class ProxyRule(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/specification_list.py

```
L7: class SpecificationList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/target_list.py

```
L7: class TargetList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_ip.py

```
L7: class ColumnIp(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/deployment_list.py

```
L7: class DeploymentList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/currency_list.py

```
L7: class CurrencyList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/table_list.py

```
L7: class TableList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_url.py

```
L7: class ColumnUrl(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/file.py

```
L6: class File(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_user_limit.py

```
L6: class PolicyUserLimit(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_password_personal_data.py

```
L6: class PolicyPasswordPersonalData(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/execution

_list.py

```
L7: class ExecutionList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_enum.py

```
L7: class AttributeEnum(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_twitch.py

```
L6: class OAuth2Twitch(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/log_list.py

```
L7: class LogList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_box.py

```
L6: class OAuth2Box(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/provider.py

```
L6: class Provider(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/specificat

ion.py

```
L6: class Specification(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_tradeshift.py

```
L6: class OAuth2Tradeshift(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/webhook.py

```
L6: class Webhook(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/locale.py

```
L6: class Locale(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_notion.py

```
L6: class OAuth2Notion(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_recovery_codes.py

```
L6: class MfaRecoveryCodes(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/identity_list.py

```
L7: class IdentityList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/activity_event.py

```
L6: class ActivityEvent(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_dailymotion.py

```
L6: class OAuth2Dailymotion(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_duration.py

```
L6: class PolicySessionDuration(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/target.py

```
L6: class Target(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_relationship.py

```
L7: class ColumnRelationship(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_enum.py

```
L7: class ColumnEnum(AppwriteModel):
```


Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_google.py

```
L6: class OAuth2Google(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_linux.py

```
L7: class PlatformLinux(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/membership_list.py

```
L7: class MembershipList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_yandex.py

```
L6: class OAuth2Yandex(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_index.py

```
L6: class ColumnIndex(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/user.py

```
L17: class User(AppwriteModel, Generic[T]):
```

```
L89: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'User[T]':
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/webhook_list.py

```
L7: class WebhookList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_provider_list.py

```
L46: class OAuth2ProviderList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_integer.py

```
L7: class ColumnInteger(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_status_list.py

```
L7: class HealthStatusList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/row.py

```
L8: class Row(AppwriteModel, Generic[T]):
L38: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'Row[T]':
L49: def data(self) -> T:
L53: def data(self, value: T) -> None:
L56: def to_dict(self) -> Dict[str, Any]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_stripe.py

```
L6: class OAuth2Stripe(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/database_list.py

```
L7: class DatabaseList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_string.py

```
L7: class AttributeString(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/framework_list.py

```
L7: class FrameworkList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_invalidation.py

```
L6: class PolicySessionInvalidation(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_oidc.py

```
L6: class OAuth2Oidc(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_integer.py

```
L7: class AttributeInteger(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_datetime.py

```
L7: class AttributeDatetime(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_list.py

```
L15: class PolicyList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_queue.py

```
L6: class HealthQueue(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/runtime_list.py

```
L7: class RuntimeList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/file_list.py

```
L7: class FileList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_boolean.py

```
L7: class AttributeBoolean(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_alert.py

```
L6: class PolicySessionAlert(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_mediumtext.py

```
L7: class AttributeMediumtext(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/row_list.py

```
L9: class RowList(AppwriteModel, Generic[T]):
```

```
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'RowList[T]':
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/function.py

```
L7: class Function(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_url.py

```
L7: class AttributeUrl(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_session_auth.py

```
L6: class OAuth2FusionAuth(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_bigint.py

```
L7: class AttributeBigint(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_archive.py

```
L6: class BackupArchive(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_email.py

```
L7: class ColumnEmail(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/table.py

```
L25: class Table(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_spotify.py

```
L6: class OAuth2Spotify(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_datetime.py

```
L7: class ColumnDatetime(AppwriteModel):
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/block.py****L6: class Block(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/auth_provider.py****L6: class AuthProvider(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_authentic.py****L6: class OAuth2Authentic(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_line.py****L7: class ColumnLine(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_salesforce.py****L6: class OAuth2Salesforce(AppwriteModel):****Q_base****appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_longtext.py****L7: class ColumnLongtext(AppwriteModel):****Q_base**

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_zoho.py

```
L6: class OAuth2Zoho(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_word_press.py

```
L6: class OAuth2WordPress(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/membership.py

```
L6: class Membership(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mock_number.py

```
L6: class MockNumber(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_text.py

```
L7: class AttributeText(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mock_number_list.py

```
L7: class MockNumberList(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/argon2.py

```
L6: class Argon2(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_apple.py

```
L6: class OAuth2Apple(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_gitlab.py

```
L6: class OAuth2Gitlab(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_limit.py

```
L6: class PolicySessionLimit(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algorithm_md5.py

```
L6: class AlgoMd5(AppwriteModel):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/utils/deprecated.py

```
L11: def deprecated(reason=None):
L21: def old_function(...):
L24: def decorator(func):
L31: def wrapped(*args, **kwargs):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/encoders/value_class_encoder.py

```
L58: class ValueClassEncoder(json.JSONEncoder):
L59: def default(self, o):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/avatars.py

```
L13: class Avatars(Service):
L15: def __init__(self, client) -> None:
L18: def get_browser(
L72: def get_credit_card(
L127: def get_favicon(
L166: def get_flag(
L221: def get_image(
L272: def get_initials(
L327: def get_qr(
L380: def get_screenshot(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/activities.py

```
L8: class Activities(Service):
L10: def __init__(self, client) -> None:
L13: def list_events(
L48: def get_event(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/projects.py

```
L82: class Project(Service):
L84: def __init__(self, client) -> None:
L87: def delete(
L114: def update_auth_method(
L159: def list_keys(
L199: def create_key(
```

```

L257: def create_ephemeral_key(
L304: def get_key(
L341: def update_key(
L397: def delete_key(
L435: def update_labels(
L473: def list_mock_phones(
L513: def create_mock_phone(
L558: def get_mock_phone(
L595: def update_mock_phone(
L640: def delete_mock_phone(
L678: def list_oauth2_providers(
L718: def update_oauth2_amazon(
L761: def update_oauth2_apple(
L812: def update_oauth2_auth0(
L859: def update_oauth2_authentic(
L906: def update_oauth2_autodesk(
L949: def update_oauth2_bitbucket(
L992: def update_oauth2_bitly(
L1035: def update_oauth2_box(
L1078: def update_oauth2_dailymotion(
L1121: def update_oauth2_discord(
L1164: def update_oauth2_disqus(
L1207: def update_oauth2_dropbox(
L1250: def update_oauth2_etsy(
L1293: def update_oauth2_facebook(
L1336: def update_oauth2_figma(
L1379: def update_oauth2_fusion_auth(
L1426: def update_oauth2_git_hub(
L1469: def update_oauth2_gitlab(
L1516: def update_oauth2_google(
L1559: def update_oauth2_keycloak(
L1610: def update_oauth2_kick(
L1653: def update_oauth2_linkedin(
L1696: def update_oauth2_microsoft(
L1743: def update_oauth2_notion(
L1786: def update_oauth2_oidc(
L1845: def update_oauth2_okta(
L1896: def update_oauth2_paypal(
L1939: def update_oauth2_paypal_sandbox(
L1982: def update_oauth2_podio(
L2025: def update_oauth2_salesforce(
L2068: def update_oauth2_slack(
L2111: def update_oauth2_spotify(
L2154: def update_oauth2_stripe(
L2197: def update_oauth2_tradeshift(
L2240: def update_oauth2_tradeshift_sandbox(
L2283: def update_oauth2_twitch(
L2326: def update_oauth2_word_press(
L2369: def update_oauth2_x(
L2412: def update_oauth2_yahoo(
L2455: def update_oauth2_yandex(

```

```

L2498: def update_o_auth2_zoho(
L2541: def update_o_auth2_zoom(
L2584: def get_o_auth2_provider(
L2743: def list_platforms(
L2783: def create_android_platform(
L2835: def update_android_platform(
L2887: def create_apple_platform(
L2939: def update_apple_platform(
L2991: def create_linux_platform(
L3043: def update_linux_platform(
L3095: def create_web_platform(
L3147: def update_web_platform(
L3199: def create_windows_platform(
L3251: def update_windows_platform(
L3303: def get_platform(
L3357: def delete_platform(
L3395: def list_policies(
L3435: def update_membership_privacy_policy(
L3491: def update_password_dictionary_policy(
L3529: def update_password_history_policy(
L3566: def update_password_personal_data_policy(
L3604: def update_session_alert_policy(
L3642: def update_session_duration_policy(
L3680: def update_session_invalidation_policy(
L3718: def update_session_limit_policy(
L3753: def update_user_limit_policy(
L3788: def get_policy(
L3854: def update_protocol(
L3899: def update_service(
L3944: def update_smtp(
L4015: def create_smtp_test(
L4053: def list_email_templates(
L4093: def update_email_template(
L4160: def get_email_template(
L4202: def list_variables(
L4242: def create_variable(
L4299: def get_variable(
L4336: def update_variable(
L4386: def delete_variable(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/messaging.py

```

L18: class Messaging(Service):
L20: def __init__(self, client) -> None:
L23: def list_messages(
L68: def create_email(

```

```

L164: def update_email(
L247: def create_push(
L373: def update_push(
L484: def create_sms(
L553: def update_sms(
L616: def get_message(
L654: def delete(
L692: def list_message_logs(
L739: def list_targets(
L786: def list_providers(
L831: def create_apns_provider(
L905: def update_apns_provider(
L976: def create_fcm_provider(
L1029: def update_fcm_provider(
L1080: def create_mailgun_provider(
L1163: def update_mailgun_provider(
L1244: def create_msg91_provider(
L1308: def update_msg91_provider(
L1370: def create_resend_provider(
L1444: def update_resend_provider(
L1516: def create_sendgrid_provider(
L1590: def update_sendgrid_provider(
L1662: def create_smtp_provider(
L1768: def update_smtp_provider(
L1868: def create_telemesign_provider(
L1932: def update_telemesign_provider(
L1994: def create_textmagic_provider(
L2058: def update_textmagic_provider(
L2120: def create_twilio_provider(
L2184: def update_twilio_provider(
L2246: def create_vonage_provider(
L2310: def update_vonage_provider(
L2372: def get_provider(
L2410: def delete_provider(
L2448: def list_provider_logs(
L2495: def list_subscriber_logs(
L2542: def list_topics(
L2587: def create_topic(
L2637: def get_topic(
L2675: def update_topic(
L2722: def delete_topic(
L2760: def list_topic_logs(
L2807: def list_subscribers(
L2859: def create_subscriber(
L2911: def get_subscriber(
L2956: def delete_subscriber(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/webhook

ks.py

```

L8: class Webhooks(Service):
L10: def __init__(self, client) -> None:
L13: def list(
L53: def create(
L136: def get(
L173: def update(
L252: def delete(
L290: def update_secret(

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/services/tokens.py**

```

L8: class Tokens(Service):
L10: def __init__(self, client) -> None:
L13: def list(
L67: def create_file_token(
L116: def get(
L153: def update(
L195: def delete(

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/services/functions.py**

```

L23: class Functions(Service):
L25: def __init__(self, client) -> None:
L28: def list(
L73: def create(
L210: def list_runtimes(
L236: def list_specifications(
L262: def get(
L299: def update(
L433: def delete(
L471: def update_function_deployment(
L516: def list_deployments(
L568: def create_deployment(
L642: def create_duplicate_deployment(
L692: def create_template_deployment(
L772: def create_vcs_deployment(
L831: def get_deployment(
L875: def delete_deployment(
L920: def get_deployment_download(

```

```

L969: def update_deployment_status(
L1014: def list_executions(
L1061: def create_execution(
L1128: def get_execution(
L1172: def delete_execution(
L1217: def list_variables(
L1264: def create_variable(
L1328: def get_variable(
L1372: def update_variable(
L1429: def delete_variable(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/sites.py

```

L23: class Sites(Service):
L25: def __init__(self, client) -> None:
L28: def list(
L73: def create(
L217: def list_frameworks(
L243: def list_specifications(
L269: def get(
L306: def update(
L448: def delete(
L486: def update_site_deployment(
L531: def list_deployments(
L583: def create_deployment(
L656: def create_duplicate_deployment(
L701: def create_template_deployment(
L781: def create_vcs_deployment(
L840: def get_deployment(
L884: def delete_deployment(
L929: def get_deployment_download(
L978: def update_deployment_status(
L1023: def list_logs(
L1070: def get_log(
L1114: def delete_log(
L1159: def list_variables(
L1206: def create_variable(
L1270: def get_variable(
L1314: def update_variable(
L1371: def delete_variable(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/services/backups
.py**

```

L13: class Backups(Service):
L15: def __init__(self, client) -> None:
L18: def list_archives(
L53: def create_archive(
L95: def get_archive(
L132: def delete_archive(
L170: def list_policies(
L205: def create_policy(
L278: def get_policy(
L315: def update_policy(
L370: def delete_policy(
L408: def create_restoration(
L463: def list_restorations(
L498: def get_restoration(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/locale.py

```

L13: class Locale(Service):
L15: def __init__(self, client) -> None:
L18: def get(
L46: def list_codes(
L72: def list_continents(
L98: def list_countries(
L124: def list_countries_eu(
L150: def list_countries_phones(
L176: def list_currencies(
L202: def list_languages(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/tables_db.py

```

L41: class TablesDB(Service):
L43: def __init__(self, client) -> None:
L46: def list(
L91: def create(
L142: def list_transactions(
L177: def create_transaction(
L213: def get_transaction(
L250: def update_transaction(
L298: def delete_transaction(
L336: def create_operations(
L379: def get(
L416: def update(

```



```
L464: def delete(  
L502: def list_tables(  
L554: def create_table(  
L630: def get_table(  
L674: def update_table(  
L743: def delete_table(  
L788: def list_columns(  
L842: def create_big_int_column(  
L919: def update_big_int_column(  
L995: def create_boolean_column(  
L1064: def update_boolean_column(  
L1131: def create_datetime_column(  
L1199: def update_datetime_column(  
L1266: def create_email_column(  
L1335: def update_email_column(  
L1403: def create_enum_column(  
L1478: def update_enum_column(  
L1553: def create_float_column(  
L1630: def update_float_column(  
L1706: def create_integer_column(  
L1783: def update_integer_column(  
L1859: def create_ip_column(  
L1928: def update_ip_column(  
L1996: def create_line_column(  
L2059: def update_line_column(  
L2126: def create_longtext_column(  
L2200: def update_longtext_column(  
L2268: def create_mediumtext_column(  
L2342: def update_mediumtext_column(  
L2410: def create_point_column(  
L2473: def update_point_column(  
L2540: def create_polygon_column(  
L2603: def update_polygon_column(  
L2670: def create_relationship_column(  
L2749: def create_string_column(  
L2833: def update_string_column(  
L2907: def create_text_column(  
L2981: def update_text_column(  
L3049: def create_url_column(  
L3118: def update_url_column(  
L3186: def create_varchar_column(  
L3267: def update_varchar_column(  
L3339: def get_column(  
L3422: def delete_column(  
L3474: def update_relationship_column(  
L3535: def list_indexes(  
L3589: def create_index(  
L3666: def get_index(  
L3717: def delete_index(  
L3769: def list_rows(  
L3837: def create_row(  

```

```

L3908: def create_rows(
L3968: def upsert_rows(
L4029: def update_rows(
L4092: def delete_rows(
L4150: def get_row(
L4215: def upsert_row(
L4284: def update_row(
L4353: def delete_row(
L4409: def decrement_row_column(
L4485: def increment_row_column(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/proxy.py

```

L10: class Proxy(Service):
L12: def __init__(self, client) -> None:
L15: def list_rules(
L55: def create_api_rule(
L95: def create_function_rule(
L147: def create_redirect_rule(
L215: def create_site_rule(
L267: def get_rule(
L304: def delete_rule(
L342: def update_rule_status(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/teams.py

```

L13: class Teams(Service):
L15: def __init__(self, client) -> None:
L18: def list(
L67: def create(
L121: def get(
L162: def update_name(
L211: def delete(
L249: def list_memberships(
L301: def create_membership(
L378: def get_membership(
L422: def update_membership(
L475: def delete_membership(
L520: def update_membership_status(
L582: def get_prefs(
L623: def update_prefs(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/graphql.py

```

L6: class GraphQL(Service):
L8: def __init__(self, client) -> None:
L11: def query(
L50: def mutation(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/databases.py

```

L41: class Databases(Service):
L43: def __init__(self, client) -> None:
L47: def list(
L95: def create(
L148: def list_transactions(
L183: def create_transaction(
L219: def get_transaction(
L256: def update_transaction(
L304: def delete_transaction(
L342: def create_operations(
L386: def get(
L426: def update(
L477: def delete(
L518: def list_collections(
L573: def create_collection(
L652: def get_collection(
L699: def update_collection(
L771: def delete_collection(
L819: def list_attributes(
L876: def create_big_int_attribute(
L956: def update_big_int_attribute(
L1035: def create_boolean_attribute(
L1107: def update_boolean_attribute(
L1177: def create_datetime_attribute(
L1248: def update_datetime_attribute(
L1318: def create_email_attribute(
L1390: def update_email_attribute(
L1461: def create_enum_attribute(
L1540: def update_enum_attribute(
L1618: def create_float_attribute(
L1698: def update_float_attribute(
L1777: def create_integer_attribute(
L1857: def update_integer_attribute(

```

```

L1936: def create_ip_attribute(
L2008: def update_ip_attribute(
L2079: def create_line_attribute(
L2145: def update_line_attribute(
L2214: def create_longtext_attribute(
L2288: def update_longtext_attribute(
L2356: def create_mediumtext_attribute(
L2430: def update_mediumtext_attribute(
L2499: def create_point_attribute(
L2565: def update_point_attribute(
L2635: def create_polygon_attribute(
L2701: def update_polygon_attribute(
L2771: def create_relationship_attribute(
L2852: def update_relationship_attribute(
L2917: def create_string_attribute(
L3001: def update_string_attribute(
L3075: def create_text_attribute(
L3149: def update_text_attribute(
L3218: def create_url_attribute(
L3290: def update_url_attribute(
L3360: def create_varchar_attribute(
L3441: def update_varchar_attribute(
L3514: def get_attribute(
L3600: def delete_attribute(
L3655: def list_documents(
L3726: def create_document(
L3800: def create_documents(
L3863: def upsert_documents(
L3927: def update_documents(
L3993: def delete_documents(
L4054: def get_document(
L4122: def upsert_document(
L4194: def update_document(
L4266: def delete_document(
L4325: def decrement_document_attribute(
L4404: def increment_document_attribute(
L4483: def list_indexes(
L4540: def create_index(
L4620: def get_index(
L4674: def delete_index(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/storage.py

```

L14: class Storage(Service):
L16: def __init__(self, client) -> None:
L19: def list_buckets(

```

```

L64: def create_bucket(
L153: def get_bucket(
L190: def update_bucket(
L279: def delete_bucket(
L317: def list_files(
L369: def create_file(
L442: def get_file(
L486: def update_file(
L540: def delete_file(
L585: def get_file_download(
L634: def get_file_preview(
L738: def get_file_view(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/health.py

```

L13: class Health(Service):
L15: def __init__(self, client) -> None:
L18: def get(
L44: def get_antivirus(
L70: def get_cache(
L96: def get_certificate(
L131: def get_console_pausing(
L172: def get_db(
L198: def get_pub_sub(
L224: def get_queue_audits(
L260: def get_queue_builds(
L295: def get_queue_certificates(
L330: def get_queue_databases(
L370: def get_queue_deletes(
L405: def get_failed_jobs(
L448: def get_queue_functions(
L483: def get_queue_logs(
L518: def get_queue_mails(
L553: def get_queue_messaging(
L588: def get_queue_migrations(
L623: def get_queue_stats_resources(
L658: def get_queue_usage(
L693: def get_queue_webhooks(
L728: def get_storage(
L754: def get_storage_local(
L780: def get_time(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/users.py

```

L25: class Users(Service):
L27: def __init__(self, client) -> None:
L30: def list(
L79: def create(
L139: def create_argon2_user(
L200: def create_bcrypt_user(
L261: def list_identities(
L306: def delete_identity(
L344: def create_md5_user(
L405: def create_ph_pass_user(
L466: def create_scrypt_user(
L562: def create_scrypt_modified_user(
L644: def create_sha_user(
L710: def get(
L751: def delete(
L789: def update_email(
L838: def update_impersonator(
L888: def create_jwt(
L936: def update_labels(
L987: def list_logs(
L1034: def list_memberships(
L1086: def update_mfa(
L1135: def delete_mfa_authenticator(
L1180: def list_mfa_factors(
L1217: def get_mfa_recovery_codes(
L1254: def update_mfa_recovery_codes(
L1292: def create_mfa_recovery_codes(
L1330: def update_name(
L1379: def update_password(
L1428: def update_phone(
L1477: def get_prefs(
L1518: def update_prefs(
L1567: def list_sessions(
L1609: def create_session(
L1649: def delete_sessions(
L1687: def delete_session(
L1732: def update_status(
L1781: def list_targets(
L1828: def create_target(
L1897: def get_target(
L1941: def update_target(
L2001: def delete_target(
L2046: def create_token(
L2095: def update_email_verification(
L2144: def update_phone_verification(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/account.

py

```

L23: class Account(Service):
L25: def __init__(self, client) -> None:
L28: def get(
L61: def create(
L122: def update_email(
L173: def list_identities(
L213: def delete_identity(
L251: def create_jwt(
L287: def list_logs(
L327: def update_mfa(
L369: def create_mfa_authenticator(
L407: def update_mfa_authenticator(
L456: def delete_mfa_authenticator(
L494: def create_mfa_challenge(
L532: def update_mfa_challenge(
L577: def list_mfa_factors(
L603: def get_mfa_recovery_codes(
L629: def create_mfa_recovery_codes(
L656: def update_mfa_recovery_codes(
L683: def update_name(
L725: def update_password(
L772: def update_phone(
L821: def get_prefs(
L854: def update_prefs(
L896: def create_recovery(
L941: def update_recovery(
L995: def list_sessions(
L1021: def delete_sessions(
L1048: def create_anonymous_session(
L1075: def create_email_password_session(
L1123: def update_magic_url_session(
L1171: def update_phone_session(
L1218: def create_session(
L1263: def get_session(
L1300: def update_session(
L1338: def delete_session(
L1376: def update_status(
L1410: def create_email_token(
L1463: def create_magic_url_token(
L1521: def create_o_auth2_token(
L1577: def create_phone_token(
L1624: def create_email_verification(
L1666: def create_verification(
L1709: def update_email_verification(
L1755: def update_verification(
L1802: def create_phone_verification(
L1829: def update_phone_verification(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/credit_card.py

```
L3: class CreditCard(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/framework.py

```
L3: class Framework(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/compression.py

```
L3: class Compression(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/message_status.py

```
L3: class MessageStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/image_gravity.py

```
L3: class ImageGravity(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/flag.py

```
L3: class Flag(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/column_status.py

```
L3: class ColumnStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/authentication_factor.py

```
L3: class AuthenticationFactor(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/project_policy.py

```
L3: class ProjectPolicy(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/scopes.py

```
L3: class Scopes(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/browser_permission.py

```
L3: class BrowserPermission(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/relation_mutate.py

```
L3: class RelationMutate(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/email_tem

plate_locale.py

```
L3: class EmailTemplateLocale(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/order_by.py

```
L3: class OrderBy(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/runtime.py

```
L3: class Runtime(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/execution_method.py

```
L3: class ExecutionMethod(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/email_template_type.py

```
L3: class EmailTemplateType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/protocol_id.py

```
L3: class ProtocolId(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/proxy_res

ource_type.py

```
L3: class ProxyResourceType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/password_hash.py

```
L3: class PasswordHash(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/image_format.py

```
L3: class ImageFormat(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/message_priority.py

```
L3: class MessagePriority(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/status_code.py

```
L3: class StatusCode(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/vcs_reference_type.py

```
L3: class VCSReferenceType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/adapter.p

y

```
L3: class Adapter(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/index_status.py

```
L3: class IndexStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/proxy_rule_status.py

```
L3: class ProxyRuleStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/execution_status.py

```
L3: class ExecutionStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/relationship_type.py

```
L3: class RelationshipType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/browser.py

```
L3: class Browser(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/smtp_enc

ryption.py

```
L3: class SmtEncryption(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/proxy_rule_deployment_resource_type.py

```
L3: class ProxyRuleDeploymentResourceType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/attribute_status.py

```
L3: class AttributeStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/backup_services.py

```
L3: class BackupServices(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/authenticator_type.py

```
L3: class AuthenticatorType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/o_auth_provider.py

```
L3: class OAuthProvider(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/deployme

nt_download_type.py

```
L3: class DeploymentDownloadType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/auth_method.py

```
L3: class AuthMethod(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/theme.py

```
L3: class Theme(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/deployment_status.py

```
L3: class DeploymentStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/tables_db_index_type.py

```
L3: class TablesDBIndexType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/template_reference_type.py

```
L3: class TemplateReferenceType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/database_type.py

```
L3: class DatabaseType(Enum):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/service_id
.py**

```
L3: class ServiceId(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/build_runtime.py

```
L3: class BuildRuntime(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/health_check_status.py

```
L3: class HealthCheckStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/platform_type.py

```
L3: class PlatformType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/secure.py

```
L3: class Secure(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/execution_trigger.py

```
L3: class ExecutionTrigger(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/messaging_provider_type.py

```
L3: class MessagingProviderType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/name.py

```
L3: class Name(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/databases_index_type.py

```
L3: class DatabasesIndexType(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/health_antivirus_status.py

```
L3: class HealthAntivirusStatus(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/timezone.py

```
L3: class Timezone(Enum):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/legacy.py

```
L12: class ResultDict(TypedDict):
L18: def detect(
```


Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/md.py

```

L14: def final(cls): # type: ignore[misc,no-untyped-def]
L48: class CharInfo:
L78: def __init__(self) -> None:
L97: def update(self, character: str) -> None:
L206: class MessDetectorPlugin:
L214: def feed_info(self, character: str, info: CharInfo) -> None:
L221: def reset(self) -> None: # Defensive:
L228: def ratio(self) -> float:
L237: class TooManySymbolOrPunctuationPlugin(MessDetectorPlugin):
L246: def __init__(self) -> None:
L254: def feed_info(self, character: str, info: CharInfo) -> None:
L269: def reset(self) -> None: # Abstract
L275: def ratio(self) -> float:
L287: class TooManyAccentedPlugin(MessDetectorPlugin):
L290: def __init__(self) -> None:
L294: def feed_info(self, character: str, info: CharInfo) -> None:
L301: def reset(self) -> None: # Abstract
L306: def ratio(self) -> float:
L315: class UnprintablePlugin(MessDetectorPlugin):
L318: def __init__(self) -> None:
L322: def feed_info(self, character: str, info: CharInfo) -> None:
L333: def reset(self) -> None: # Abstract
L337: def ratio(self) -> float:
L345: class SuspiciousDuplicateAccentPlugin(MessDetectorPlugin):
L353: def __init__(self) -> None:
L360: def feed_info(self, character: str, info: CharInfo) -> None:
L375: def reset(self) -> None: # Abstract
L382: def ratio(self) -> float:
L390: class SuspiciousRange(MessDetectorPlugin):
L398: def __init__(self) -> None:
L404: def feed_info(self, character: str, info: CharInfo) -> None:
L427: def reset(self) -> None: # Abstract
L434: def ratio(self) -> float:
L446: class SuperWeirdWordPlugin(MessDetectorPlugin):
L463: def __init__(self) -> None:
L481: def feed_info(self, character: str, info: CharInfo) -> None:
L556: def reset(self) -> None: # Abstract
L572: def ratio(self) -> float:
L580: class CjkUncommonPlugin(MessDetectorPlugin):
L587: def __init__(self) -> None:
L591: def feed_info(self, character: str, info: CharInfo) -> None:
L598: def reset(self) -> None: # Abstract
L603: def ratio(self) -> float:
L615: class ArchaicUpperLowerPlugin(MessDetectorPlugin):
L628: def __init__(self) -> None:
L643: def feed_info(self, character: str, info: CharInfo) -> None:

```

```

L688: def reset(self) -> None: # Abstract
L700: def ratio(self) -> float:
L708: class ArabicIsolatedFormPlugin(MessDetectorPlugin):
L711: def __init__(self) -> None:
L715: def reset(self) -> None: # Abstract
L719: def feed_info(self, character: str, info: CharInfo) -> None:
L727: def ratio(self) -> float:
L737: def is_suspiciously_successive_range(
L811: def mess_ratio(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/model
s.py**

```

L12: class CharsetMatch:
L13: def __init__(
L41: def __eq__(self, other: object) -> bool:
L48: def __lt__(self, other: object) -> bool:
L71: def multi_byte_usage(self) -> float:
L74: def __str__(self) -> str:
L90: def __repr__(self) -> str:
L93: def add_submatch(self, other: CharsetMatch) -> None:
L105: def encoding(self) -> str:
L109: def encoding_aliases(self) -> list[str]:
L122: def bom(self) -> bool:
L126: def byte_order_mark(self) -> bool:
L130: def languages(self) -> list[str]:
L138: def language(self) -> str:
L166: def chaos(self) -> float:
L170: def coherence(self) -> float:
L176: def percent_chaos(self) -> float:
L180: def percent_coherence(self) -> float:
L184: def raw(self) -> bytes | bytearray:
L191: def submatch(self) -> list[CharsetMatch]:
L195: def has_submatch(self) -> bool:
L199: def alphabets(self) -> list[str]:
L209: def could_be_from_charset(self) -> list[str]:
L217: def output(self, encoding: str = "utf_8") -> bytes:
L247: def fingerprint(self) -> int:
L254: class CharsetMatches:
L260: def __init__(self, results: list[CharsetMatch] | None = None):
L263: def __iter__(self) -> Iterator[CharsetMatch]:
L266: def __getitem__(self, item: int | str) -> CharsetMatch:
L280: def __len__(self) -> int:
L283: def __bool__(self) -> bool:
L286: def append(self, item: CharsetMatch) -> None:
L306: def best(self) -> CharsetMatch | None:
L314: def first(self) -> CharsetMatch | None:

```

```

L325: class CliDetectionResult:
L326: def __init__(
L353: def __dict__(self) -> dict[str, Any]: # type: ignore
L368: def to_json(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/api.py

```

L57: def from_bytes(
L864: def from_fp(
L894: def from_path(
L925: def is_binary(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/utls.py

```

L39: def _character_flags(character: str) -> int:
L74: def is_accentuated(character: str) -> bool:
L79: def remove_accent(character: str) -> str:
L99: def unicode_range(character: str) -> str | None:
L116: def is_latin(character: str) -> bool:
L121: def is_punctuation(character: str) -> bool:
L136: def is_symbol(character: str) -> bool:
L151: def is_emoticon(character: str) -> bool:
L161: def is_separator(character: str) -> bool:
L171: def is_case_variable(character: str) -> bool:
L176: def is_cjk(character: str) -> bool:
L181: def is_hiragana(character: str) -> bool:
L186: def is_katakana(character: str) -> bool:
L191: def is_hangul(character: str) -> bool:
L196: def is_thai(character: str) -> bool:
L201: def is_arabic(character: str) -> bool:
L206: def is_arabic_isolated_form(character: str) -> bool:
L211: def is_cjk_uncommon(character: str) -> bool:
L216: def is_unicode_range_secondary(range_name: str) -> bool:
L221: def is_unprintable(character: str) -> bool:
L231: def any_specified_encoding(
L266: def is_multi_byte_encoding(name: str) -> bool:
L286: def identify_sig_or_bom(sequence: bytes | bytearray) -> tuple[str | None, bytes]:
L304: def should_strip_sig_or_bom(iana_encoding: str) -> bool:
L308: def iana_name(cp_name: str, strict: bool = True) -> str:
L325: def cp_similarity(iana_name_a: str, iana_name_b: str) -> float:
L345: def is_cp_similar(iana_name_a: str, iana_name_b: str) -> bool:
L356: def set_logging_handler(
L369: def cut_sequence_chunks(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/cd.py

```

L29: def encoding_unicode_range(iana_name: str) -> list[str]:
L68: def unicode_range_languages(primary_range: str) -> list[str]:
L84: def encoding_languages(iana_name: str) -> list[str]:
L104: def mb_encoding_languages(iana_name: str) -> list[str]:
L125: def get_target_features(language: str) -> tuple[bool, bool]:
L141: def alphabet_languages(
L175: def characters_popularity_compare(
L276: def alpha_unicode_split(decoded_sequence: str) -> list[str]:
L350: def merge_coherence_ratios(results: list[CoherenceMatches]) -> CoherenceMatches:
L378: def filter_alt_coherence_matches(results: CoherenceMatches) -> CoherenceMatches:
L406: def coherence_ratio(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/cli/__main__.py

```

L17: def query_yes_no(question: str, default: str = "yes") -> bool: # Defensive:
L32: class FileType:
L51: def __init__(
L63: def __call__(self, string: str) -> typing.IO: # type: ignore[type-arg]
L81: def __repr__(self) -> str:
L91: def cli_detect(argv: list[str] | None = None) -> int:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/parser.py

```

L14: def make_regex(string: str, extra_flags: int = 0) -> Pattern[str]:
L35: class Original(NamedTuple):
L40: class Binding(NamedTuple):
L47: class Position:
L48: def __init__(self, chars: int, line: int) -> None:
L53: def start(cls) -> "Position":
L56: def set(self, other: "Position") -> None:
L60: def advance(self, string: str) -> None:
L65: class Error(Exception):
L69: class Reader:
L70: def __init__(self, stream: IO[str]) -> None:
L75: def has_next(self) -> bool:
L78: def set_mark(self) -> None:
L81: def get_marked(self) -> Original:
L87: def peek(self, count: int) -> str:
L90: def read(self, count: int) -> str:
L97: def read_regex(self, regex: Pattern[str]) -> Sequence[str]:
L105: def decode_escapes(regex: Pattern[str], string: str) -> str:

```

```

L106: def decode_match(match: Match[str]) -> str:
L112: def parse_key(reader: Reader) -> Optional[str]:
L123: def parse_unquoted_value(reader: Reader) -> str:
L128: def parse_value(reader: Reader) -> str:
L142: def parse_binding(reader: Reader) -> Binding:
L179: def parse_stream(stream: IO[str]) -> Iterator[Binding]:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/__init__.py

```

L6: def load_ipython_extension(ipython: Any) -> None:
L12: def get_cli_string(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/dotenv/variables.py

```

L18: class Atom(metaclass=ABCMeta):
L19: def __ne__(self, other: object) -> bool:
L26: def resolve(self, env: Mapping[str, Optional[str]]) -> str: ...
L29: class Literal(Atom):
L30: def __init__(self, value: str) -> None:
L33: def __repr__(self) -> str:
L36: def __eq__(self, other: object) -> bool:
L41: def __hash__(self) -> int:
L44: def resolve(self, env: Mapping[str, Optional[str]]) -> str:
L48: class Variable(Atom):
L49: def __init__(self, name: str, default: Optional[str]) -> None:
L53: def __repr__(self) -> str:
L56: def __eq__(self, other: object) -> bool:
L61: def __hash__(self) -> int:
L64: def resolve(self, env: Mapping[str, Optional[str]]) -> str:
L70: def parse_variables(value: str) -> Iterator[Atom]:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/cli.py

```

L24: def enumerate_env() -> Optional[str]:
L62: def cli(ctx: click.Context, file: Any, quote: Any, export: Any) -> None:
L68: def stream_file(path: os.PathLike) -> Iterator[IO[str]]:
L93: def list_values(ctx: click.Context, output_format: str) -> None:
L116: def set_value(ctx: click.Context, key: Any, value: Any) -> None:
L137: def get(ctx: click.Context, key: Any) -> None:
L154: def unset(ctx: click.Context, key: Any) -> None:
L184: def run(ctx: click.Context, override: bool, commandline: tuple[str, ...]) -> None:
L204: def run_command(command: List[str], env: Dict[str, str]) -> None:

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/ipython.py

```

L12: class IPythonDotEnv(Magics):
L34: def dotenv(self, line):
L48: def load_ipython_extension(ipython):

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/main.py

```

L22: def _load_dotenv_disabled() -> bool:
L32: def with_warn_for_invalid_lines(mappings: Iterator[Binding]) -> Iterator[Binding]:
L42: class DotEnv:
L43: def __init__(
L61: def _get_stream(self) -> Iterator[IO[str]]:
L75: def dict(self) -> Dict[str, Optional[str]]:
L91: def parse(self) -> Iterator[Tuple[str, Optional[str]]]:
L97: def set_as_environment_variables(self) -> bool:
L112: def get(self, key: str) -> Optional[str]:
L125: def get_key(
L139: def rewrite(
L193: def set_key(
L248: def unset_key(
L289: def resolve_variables(
L314: def _walk_to_root(path: str) -> Iterator[str]:
L332: def find_dotenv(
L343: def _is_interactive():
L353: def _is_debugger():
L383: def load_dotenv(
L432: def dotenv_values(
L468: def _is_file_or_fifo(path: StrPath) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_core_metadata_a.py

```

L28: def get_metadata_version(self):
L36: def rfc822_unescape(content: str) -> str:
L44: def _read_field_from_msg(msg: Message, field: str) -> str | None:
L52: def _read_field_unescaped_from_msg(msg: Message, field: str) -> str | None:
L60: def _read_list_from_msg(msg: Message, field: str) -> list[str] | None:
L68: def _read_payload_from_msg(msg: Message) -> str | None:
L75: def read_pkg_file(self, file):
L117: def single_line(val):
L131: def write_pkg_info(self, base_dir):
L150: def write_pkg_file(self, file): # noqa: C901 # is too complex (14) # FIXME
L154: def write_field(key, value):
L225: def _write_requirements(self, file):
L245: def _include_extra(req: str, extra: str, condition: str) -> Requirement:
L256: def _write_provides_extra(file, processed_extras, safe, unsafe):
L274: def get_fullname(self):

```

```
L278: def _distribution_fullname(name: str, version: str) -> str:
L297: def _safe_license_file(file):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_normalization.py

```
L20: def safe_identifier(name: str) -> str:
L32: def safe_name(component: str) -> str:
L44: def safe_version(version: str) -> str:
L69: def best_effort_version(version: str) -> str:
L101: def safe_extra(extra: str) -> str:
L111: def filename_component(value: str) -> str:
L120: def filename_component_broken(value: str) -> str:
L135: def safer_name(value: str) -> str:
L148: def safer_best_effort_version(value: str) -> str:
L155: def _missing_canonicalize_license_expression(expression: str) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/discovery.py

```
L63: def _valid_name(path: StrPath) -> bool:
L68: class _Filter:
L74: def __init__(self, *patterns: str) -> None:
L77: def __call__(self, item: str) -> bool:
L80: def __contains__(self, item: str) -> bool:
L84: class _Finder:
L91: def find(
L126: def _find_iter(
L132: class PackageFinder(_Finder):
L140: def _find_iter(
L174: def _looks_like_package(path: StrPath, _package_name: str) -> bool:
L179: class PEP420PackageFinder(PackageFinder):
L181: def _looks_like_package(_path: StrPath, _package_name: str) -> bool:
L185: class ModuleFinder(_Finder):
L191: def _find_iter(
L210: class FlatLayoutPackageFinder(PEP420PackageFinder):
L256: def _looks_like_package(_path: StrPath, package_name: str) -> bool:
L263: class FlatLayoutModuleFinder(ModuleFinder):
L293: def _find_packages_within(root_pkg: str, pkg_dir: StrPath) -> list[str]:
L298: class ConfigDiscovery:
L303: def __init__(self, distribution: Distribution) -> None:
L309: def _disable(self):
L313: def _ignore_ext_modules(self):
L326: def _root_dir(self) -> StrPath:
L331: def _package_dir(self) -> dict[str, str]:
```

```

L336: def __call__(
L359: def _explicitly_specified(self, ignore_ext_modules: bool) -> bool:
L372: def _analyse_package_layout(self, ignore_ext_modules: bool) -> bool:
L390: def _analyse_explicit_layout(self) -> bool:
L408: def _analyse_src_layout(self) -> bool:
L433: def _analyse_flat_layout(self) -> bool:
L446: def _analyse_flat_packages(self) -> bool:
L453: def _analyse_flat_modules(self) -> bool:
L459: def _ensure_no_accidental_inclusion(self, detected: list[str], kind: str):
L482: def analyse_name(self) -> None:
L499: def _find_name_single_package_or_module(self) -> str | None:
L509: def _find_name_from_packages(self) -> str | None:
L526: def remove_nested_packages(packages: list[str]) -> list[str]:
L544: def remove_stubs(packages: list[str]) -> list[str]:
L553: def find_parent_package(
L577: def find_package_path(
L611: def construct_package_dir(packages: list[str], package_path: StrPath) -> dict[str,
str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/installer.py

```

L22: def _fixup_find_links(find_links):
L30: def fetch_build_egg(dist, req) -> metadata.Distribution | metadata.PathDistribution:
L39: def _present(req):
L43: def _fetch_build_eggs(dist, requires: _reqs.StrOrIter) -> list[metadata.Distribution]:
L62: def _dist_matches_req(egg_dist, req):
L70: def _fetch_build_egg_no_warn(dist, req): # noqa: C901 # is too complex (16) # FIXME
L130: def strip_marker(req) -> packaging.requirements.Requirement:
L142: def _warn_wheel_not_available(dist):
L149: class _DeprecatedInstaller(SetuptoolsDeprecationWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_imp.py

```

L19: def find_spec(module, paths):
L28: def find_module(module, paths=None):
L76: def get_frozen_object(module, paths=None):
L83: def get_module(module, paths, info):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/archive_util.py

```

L25: class UnrecognizedFormat(DistutilsError):
L29: def default_filter(src, dst):

```



```

L34: def unpack_archive(
L68: def unpack_directory(filename, extract_dir, progress_filter=default_filter) -> None:
L95: def unpack_zipfile(filename, extract_dir, progress_filter=default_filter) -> None:
L110: def _unpack_zipfile_obj(zipfile_obj, extract_dir, progress_filter=default_filter):
L140: def _resolve_tar_file_or_dir(tar_obj, tar_member_obj):
L161: def _iter_open_tar(tar_obj, extract_dir, progress_filter):
L190: def unpack_tarfile(filename, extract_dir, progress_filter=default_filter) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_entry_points.py

```

L14: def ensure_valid(ep):
L34: def load_group(value, group):
L45: def by_group_and_name(ep):
L49: def validate(eps: metadata.EntryPoints):
L58: def load(eps):
L69: def _(eps):
L86: def render(eps: metadata.EntryPoints):
L93: def render_items(eps):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_reqs.py

```

L23: def parse_strings(strs: _StrOrIter) -> Iterator[str]:
L35: def parse(strs: _StrOrIter) -> Iterator[Requirement]: ...
L37: def parse(strs: _StrOrIter, parser: Callable[[str], _T]) -> Iterator[_T]: ...
L38: def parse(strs: _StrOrIter, parser: Callable[[str], _T] = parse_req) -> Iterator[_T]: #
type: ignore[assignment]

```

Q_base appwrite/.venv/lib/python3.12/site-packages/setuptools/dist.py

```

L73: def __getattr__(name: str) -> Any: # pragma: no cover
L84: def check_importable(dist, attr, value):
L94: def assert_string_list(dist, attr: str, value: _Sequence) -> None:
L108: def check_nsp(dist, attr, value):
L136: def check_extras(dist, attr, value):
L148: def _check_extra(extra, reqs):
L158: def _check_marker(marker):
L165: def assert_bool(dist, attr, value):
L171: def invalid_unless_false(dist, attr, value):
L179: def check_requirements(dist, attr: str, value: _OrderedStrSequence) -> None:
L193: def check_specifier(dist, attr, value):
L202: def check_entry_points(dist, attr, value):
L210: def check_package_data(dist, attr, value):

```

```

L225: def check_packages(dist, attr, value):
L242: class Distribution(_Distribution):
L303: def __init__(self, attrs: MutableMapping[str, Any] | None = None) -> None:
L335: def _validate_metadata(self):
L348: def _set_metadata_defaults(self, attrs):
L359: def _normalize_version(version):
L374: def _finalize_requires(self):
L393: def _normalize_requires(self):
L407: def _finalize_license_expression(self) -> None:
L447: def _finalize_license_files(self) -> None:
L468: def _expand_patterns(
L488: def _find_pattern(pattern: str, enforce_match: bool = True) -> list[str]:
L546: def _parse_config_files(self, filenames=None): # noqa: C901
L625: def _enforce_underscore(self, opt: str, section: str) -> str:
L648: def _enforce_option_lowercase(self, opt: str, section: str) -> str:
L671: def _skip_setupcfg_normalization(self, section: str) -> bool:
L681: def _is_setuptools_section(self, section: str) -> bool:
L689: def _set_command_options(self, command_obj, option_dict=None): # noqa: C901
L734: def _get_project_config_files(self, filenames: Iterable[StrPath] | None):
L746: def parse_config_files(
L768: def fetch_build_eggs(self, requires: _StrOrIter) -> list[metadata.Distribution]:
L774: def finalize_options(self) -> None:
L783: def by_order(hook):
L793: def _removed(ep):
L806: def _finalize_setup_keywords(self):
L812: def get_egg_cache_dir(self) -> str:
L833: def fetch_build_egg(self, req):
L839: def get_command_class(self, command: str) -> type[distutils.cmd.Command]: # type:
ignore[override] # Not doing complex overrides yet
L857: def print_commands(self):
L864: def get_command_list(self):
L871: def include(self, **attrs) -> None:
L893: def exclude_package(self, package: str) -> None:
L914: def has_contents_for(self, package: str) -> bool:
L925: def _exclude_misc(self, name: str, value: _Sequence) -> None:
L942: def _include_misc(self, name: str, value: _Sequence) -> None:
L963: def exclude(self, **attrs) -> None:
L986: def _exclude_packages(self, packages: _Sequence) -> None:
L993: def _parse_command_opts(self, parser, args):
L1020: def get_cmdline_options(self) -> dict[str, dict[str, str | None]]:
L1059: def iter_distribution_names(self) -> Iterator[str]:
L1074: def handle_display_options(self, option_order):
L1102: def run_command(self, command) -> None:
L1111: def _setuptools_commands() -> set[str]:
L1122: class DistDeprecationWarning(SetupToolsDeprecationWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/depends.py

```

L20: class Require:
L23: def __init__(
L43: def full_name(self):
L49: def version_ok(self, version):
L58: def get_version(
L87: def is_present(self, paths=None):
L91: def is_current(self, paths=None):
L99: def maybe_close(f):
L101: def empty():
L115: def get_module_constant(
L145: def extract_constant(

```

Q_base appwrite/.venv/lib/python3.12/site-packages/setuptools/glob.py

```

L23: def glob(pathname: AnyStr, recursive: bool = False) -> list[AnyStr]:
L37: def iglob(pathname: AnyStr, recursive: bool = False) -> Iterator[AnyStr]:
L55: def _iglob(pathname: AnyStr, recursive: bool) -> Iterator[AnyStr]:
L92: def glob1(dirname: StrPath, pattern: str) -> list[str]: ...
L94: def glob1(dirname: BytesPath, pattern: bytes) -> list[bytes]: ...
L95: def glob1(dirname: StrOrBytesPath, pattern: str | bytes) -> list[str] | list[bytes]:
L109: def glob0(dirname, basename):
L126: def glob2(dirname: StrPath, pattern: str) -> Iterator[str]: ...
L128: def glob2(dirname: BytesPath, pattern: bytes) -> Iterator[bytes]: ...
L129: def glob2(dirname: StrOrBytesPath, pattern: str | bytes) -> Iterator[str | bytes]:
L137: def _rlistdir(dirname: StrPath) -> Iterator[str]: ...
L139: def _rlistdir(dirname: BytesPath) -> Iterator[bytes]: ...
L140: def _rlistdir(dirname: StrOrBytesPath) -> Iterator[str | bytes]:
L162: def has_magic(s: str | bytes) -> bool:
L169: def _isrecursive(pattern: str | bytes) -> bool:
L176: def escape(pathname):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/logging.py

```

L10: def _not_warning(record):
L14: def configure() -> None:
L38: def set_threshold(level: int) -> int:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_scripts.py

```

L25: class _SplitArgs(TypedDict, total=False):
L30: class CommandSpec(list):
L40: def best(cls):
L47: def _sys_executable(cls):
L52: def from_param(cls, param: Self | str | Iterable[str] | None) -> Self:

```

```

L68: def from_environment(cls):
L72: def from_string(cls, string: str) -> Self:
L80: def install_options(self, script_text: str):
L87: def _extract_options(orig_script):
L96: def as_header(self):
L100: def _strip_quotes(item):
L108: def _render(items):
L115: class WindowsCommandSpec(CommandSpec):
L119: class ScriptWriter:
L143: def importlib_load_entry_point(spec, group, name):
L165: def get_args(cls, dist, header=None):
L190: def _ensure_safe_name(name):
L199: def best(cls):
L209: def _get_script_args(cls, type_, name, header, script_text):
L214: def get_header(
L225: class WindowsScriptWriter(ScriptWriter):
L229: def best(cls):
L242: def _get_script_args(cls, type_, name, header, script_text):
L258: def _adjust_header(cls, type_, orig_header):
L272: def _use_header(new_header):
L284: class WindowsExecutableLauncherWriter(WindowsScriptWriter):
L286: def _get_script_args(cls, type_, name, header, script_text):
L316: def get_win_launcher(type):
L335: def load_launcher_manifest(name):
L340: def _first_line_re():
L352: def is_64bit():
L356: def isascii(s):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/launch.py

```
L13: def run() -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_shutil.py

```

L16: def chmod(*args: object, **kwargs: object) -> None: # type: ignore[misc] # Mypy reuses
the imported definition anyway
L23: def attempt_chmod_verbose(path, mode):
L32: def _auto_chmod(
L43: def rmtree(path, ignore_errors=False, onexc=_auto_chmod):
L51: def rmdir(path, **opts):
L56: def current_umask():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/__init__.py

```

L52: def _install_setup_requires(attrs):
L55: class MinimalDistribution(distutils.core.Distribution):
L61: def __init__(self, attrs: Mapping[str, object]) -> None:
L68: def _get_project_config_files(self, filenames=None):
L76: def finalize_options(self):
L90: def _fetch_build_eggs(dist: Distribution):
L111: def setup(**attrs) -> Distribution:
L129: class Command(_Command):
L176: def __init__(self, dist: Distribution, **kw) -> None:
L185: def reinitialize_command(
L189: def reinitialize_command(
L192: def reinitialize_command(
L200: def initialize_options(self) -> None:
L209: def finalize_options(self) -> None:
L218: def run(self) -> None:
L227: def _find_all_simple(path):
L239: def findall(dir=os.curdir):
L251: class sic(str):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_path.py

```

L17: def ensure_directory(path):
L23: def same_path(p1: StrPath, p2: StrPath) -> bool:
L42: def _cygwin_patch(filename: StrPath): # pragma: nocover
L53: def normpath(filename: StrPath) -> str:
L59: def paths_on_pythonpath(paths):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/build_meta.py

```

L71: class SetupRequirementsError(BaseException):
L72: def __init__(self, specifiers) -> None:
L76: class Distribution(setuptools.dist.Distribution):
L77: def fetch_build_eggs(self, specifiers) -> NoReturn:
L84: def patch(cls) -> Iterator[None]:
L99: def no_install_setup_requires():
L114: def _get_immediate_subdirectories(a_dir):
L120: def _file_with_extension(directory: StrPath, extension: str | tuple[str, ...]):
L132: def _open_setup_script(setup_script):
L141: def suppress_known_deprecation():
L163: class _ConfigSettingsTranslator:
L170: def _get_config(self, key: str, config_settings: _ConfigSettings) -> list[str]:
L192: def _global_args(self, config_settings: _ConfigSettings) -> Iterator[str]:

```

```

L224: def __dist_info_args(self, config_settings: _ConfigSettings) -> Iterator[str]:
L250: def _editable_args(self, config_settings: _ConfigSettings) -> Iterator[str]:
L266: def _arbitrary_args(self, config_settings: _ConfigSettings) -> Iterator[str]:
L290: class _BuildMetaBackend(_ConfigSettingsTranslator):
L291: def _get_build_requires(
L307: def run_setup(self, setup_script: str = 'setup.py') -> None:
L330: def get_requires_for_build_wheel(
L335: def get_requires_for_build_sdist(
L340: def _bubble_up_info_directory(
L355: def _find_info_directory(self, metadata_directory: StrPath, suffix: str) -> Path:
L368: def prepare_metadata_for_build_wheel(
L385: def _build_with_temp_dir(
L421: def build_wheel(
L427: def _build(cmd: list[str]):
L449: def build_sdist(
L456: def _get_dist_info_dir(self, metadata_directory: StrPath | None) -> str | None:
L463: def build_editable(
L478: def get_requires_for_build_editable(
L483: def prepare_metadata_for_build_editable(
L491: class _BuildMetaLegacyBackend(_BuildMetaBackend):
L503: def run_setup(self, setup_script: str = 'setup.py') -> None:
L531: class _IncompatibleBdistWheel(SetuptoolsDeprecationWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_static.py

```

L9: class Static:
L27: def _prevent_modification(target: type, method: str, copying: str) -> None:
L40: def _replacement(self: Static, *args, **kwargs):
L61: class Str(str, Static):
L65: class Tuple(tuple, Static):
L69: class List(list, Static):
L108: class Dict(dict, Static):
L145: class SpecifierSet(packaging.specifiers.SpecifierSet, Static):
L152: def noop(value: T) -> T:
L163: def attempt_conversion(value: T) -> T:
L173: def is_static(value: object) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/monkey.py

```

L26: def _get_mro(cls):
L41: def get_unpatched(item: _UnpatchT) -> _UnpatchT: ...
L43: def get_unpatched(item: object) -> None: ...
L44: def get_unpatched(
L54: def get_unpatched_class(cls: type[_T]) -> type[_T]:
L72: def patch_all() -> None:

```

```

L93: def _patch_distribution_metadata():
L108: def patch_func(replacement, target_mod, func_name) -> None:
L125: def get_unpatched_function(candidate):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/namespaces.py

```

L11: class Installer:
L14: def install_namespaces(self) -> None:
L28: def uninstall_namespaces(self) -> None:
L35: def _get_nspkg_file(self):
L39: def _get_target(self):
L63: def _get_root(self):
L66: def _gen_nspkg_line(self, pkg):
L75: def _get_all_ns_packages(self):
L81: def _pkg_names(pkg):
L96: class DevelopInstaller(Installer):
L97: def _get_root(self):
L100: def _get_target(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_itertools.py

```

L5: def ensure_unique(iterable, key=lambda x: x):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/unicode_utils.py

```

L10: def decompose(path):
L22: def filesys_decode(path):
L43: def try_encode(string, enc):
L51: def _read_utf8_with_fallback(file: str, fallback_encoding=py39.LOCALE_ENCODING) -> str:
L67: def _cfg_read_utf8_with_fallback(
L83: class _Utf8EncodingNeeded(SetuptoolsDeprecationWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_discovery.py

```

L8: def extras_from_dep(dep):
L20: def extras_from_deps(deps):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/msvc.py

```

L35: class winreg:
L44: class PlatformInfo:
L56: def __init__(self, arch: str) -> None:
L60: def target_cpu(self) -> str:
L71: def target_is_x86(self) -> bool:
L82: def current_is_x86(self) -> bool:
L93: def current_dir(self, hidex86=False, x64=False) -> str:
L117: def target_dir(self, hidex86=False, x64=False) -> str:
L141: def cross_dir(self, forcex86=False) -> str:
L165: class RegistryInfo:
L182: def __init__(self, platform_info: PlatformInfo) -> None:
L186: def visualstudio(self) -> LiteralString:
L198: def xsx(self) -> LiteralString:
L210: def vc(self) -> LiteralString:
L222: def vs(self) -> LiteralString:
L234: def vc_for_python(self) -> LiteralString:
L246: def microsoft_sdk(self) -> LiteralString:
L258: def windows_sdk(self) -> LiteralString:
L270: def netfx_sdk(self) -> LiteralString:
L282: def windows_kits_roots(self) -> LiteralString:
L294: def microsoft(self, key: LiteralString, x86: bool = False) -> LiteralString: ...
L296: def microsoft(self, key: str, x86: bool = False) -> str: ... # type: ignore[misc]
L297: def microsoft(self, key: str, x86: bool = False) -> str:
L316: def lookup(self, key: str, name: str) -> str | None:
L358: class SystemInfo:
L376: def __init__(
L387: def _find_latest_available_vs_ver(self):
L407: def find_reg_vs_vers(self) -> list[float]:
L438: def find_programdata_vs_vers(self) -> dict[float, str]:
L481: def _as_float_version(version):
L498: def VSInstallDir(self) -> str:
L516: def VCInstallDir(self) -> str:
L533: def _guess_vc(self):
L563: def _guess_vc_legacy(self):
L586: def WindowsSdkVersion(self) -> tuple[LiteralString, ...]:
L608: def WindowsSdkLastVersion(self) -> str:
L620: def WindowsSdkDir(self) -> str: # noqa: C901 # is too complex (12) # FIXME
L663: def WindowsSDKExecutablePath(self) -> str | None:
L700: def FSharpInstallDir(self) -> str:
L713: def UniversalCRTSdkDir(self) -> str | None:
L734: def UniversalCRTSdkLastVersion(self) -> str:
L750: def NetFxSdkVersion(self) -> tuple[LiteralString, ...]:
L767: def NetFxSdkDir(self) -> str | None:
L785: def FrameworkDir32(self) -> str:
L801: def FrameworkDir64(self) -> str:
L817: def FrameworkVersion32(self) -> tuple[str, ...]:

```



```

L829: def FrameworkVersion64(self) -> tuple[str, ...]:
L840: def _find_dot_net_versions(self, bits) -> tuple[str, ...]:
L871: def _use_last_dir_name(path: StrPath, prefix: str = '') -> str:
L896: class _EnvironmentDict(TypedDict):
L904: class EnvironmentInfo:
L928: def __init__(self, arch, vc_ver=None, vc_min_ver=0) -> None:
L938: def vs_ver(self):
L950: def vc_ver(self):
L962: def VSTools(self):
L982: def VCIncludes(self):
L997: def VCLibraries(self):
L1018: def VCStoreRefs(self):
L1032: def VCTools(self):
L1083: def OSLibraries(self):
L1103: def OSIncludes(self):
L1129: def OSLibpath(self):
L1169: def SdkTools(self):
L1180: def _sdk_tools(self):
L1216: def _sdk_subdir(self) -> str:
L1229: def SdkSetup(self):
L1244: def FxTools(self):
L1275: def NetFxSDKLibraries(self):
L1291: def NetFxSDKIncludes(self):
L1306: def VsTDb(self):
L1318: def MSBuild(self):
L1346: def HTMLHelpWorkshop(self):
L1361: def UCRTLlibraries(self) -> list[str]:
L1383: def UCRTIncludes(self) -> list[str]:
L1403: def _ucrt_subdir(self) -> str:
L1416: def FSharp(self):
L1431: def VCRuntimeRedist(self) -> str | None:
L1465: def return_env(self, exists: bool = True) -> _EnvironmentDict:
L1526: def _build_paths(self, name, spec_path_lists, exists):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/warnings.py

```

L25: class SetuptoolsWarning(UserWarning):
L29: def emit(
L55: def _format(
L89: class InformationOnly(SetuptoolsWarning):
L99: class SetuptoolsDeprecationWarning(SetuptoolsWarning):
L108: def _should_enforce():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/windows_support.py

```
L4: def windows_only(func):
L11: def hide_file(path: str) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/extension.py

```
L17: def _have_cython() -> bool:
L39: class Extension(_Extension):
L145: def __init__(
L163: def _convert_pyx_sources_to_lang(self):
L178: class Library(Extension):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/errors.py

```
L33: class InvalidConfigError(OptionError): # type: ignore[valid-type, misc] # distutils
imports are `Any` on python 3.12+
L37: class RemovedConfigError(OptionError): # type: ignore[valid-type, misc] # distutils
imports are `Any` on python 3.12+
L41: class RemovedCommandError(BaseError, RuntimeError): # type: ignore[valid-type, misc] #
distutils imports are `Any` on python 3.12+
L51: class PackageDiscoveryError(BaseError, RuntimeError): # type: ignore[valid-type, misc]
# distutils imports are `Any` on python 3.12+
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/wheel.py

```
L39: def _get_supported_tags():
L46: def unpack(src_dir, dst_dir) -> None:
L69: def disable_info_traces() -> Iterator[None]:
L82: class Wheel:
L83: def __init__(self, filename) -> None:
L91: def tags(self):
L99: def is_compatible(self):
L103: def egg_name(self):
L113: def get_dist_info(self, zf):
L123: def install_as_egg(self, destination_eggdir) -> None:
L128: def _install_as_egg(self, destination_eggdir, zf):
L139: def _convert_metadata(zf, destination_eggdir, dist_info, egg_info):
L140: def get_metadata(name):
L176: def _convert_requires(destination_eggdir, dist_info):
L186: def raw_req(req):
L191: def eval(req, **env):
L194: def for_extra(req):
L220: def _move_data_entries(destination_eggdir, dist_data):
```

```
L250: def _fix_namespace_packages(egg_info, destination_egkdir):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_dependencies.py

```
L6: class TestGetModuleConstant:
L7: def test_basic(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_develop.py

```
L27: def temp_user(monkeypatch):
L36: def test_env(tmpdir, temp_user):
L51: class TestNamespaces:
L53: def install_develop(src_dir, target):
L75: def test_namespace_package_importable(self, tmpdir):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_external.py

```
L9: def test_reimport_extern():
L14: def test_distribution_picklable():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_py.py

```
L17: def test_directories_in_package_data_glob(tmpdir_cwd):
L37: def test_recursive_in_package_data_glob(tmpdir_cwd):
L63: def test_read_only(tmpdir_cwd):
L96: def test_executable_data(tmpdir_cwd):
L160: def test_excluded_subpackages(tmpdir_cwd):
L207: def test_existing_egg_info(tmpdir_cwd, monkeypatch):
L303: def test_get_outputs(tmpdir_cwd):
L337: class TestTypeInfoFiles:
L422: def test_type_files_included_by_default(self, tmpdir_cwd, pyproject, example):
L436: def test_type_files_can_be_excluded(self, tmpdir_cwd, pyproject, example):
L448: def test_stub_only_package(self, tmpdir_cwd):
```

```
L467: def get_finalized_build_py(script_name="%build_py-test%"):
L475: def get_outputs(build_py):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_find_py_modules.py

```
L13: class TestModuleFinder:
L14: def find(self, path, *args, **kwargs):
L38: def test_finder(self, tmp_path, example):
L44: def test_symlinked_packages_are_included(self, tmp_path):
L51: class TestFlatLayoutModuleFinder:
L52: def find(self, path, *args, **kwargs):
L70: def test_unwanted_files_not_included(self, tmp_path, example):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/textwrap.py

```
L4: def DALS(s):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_logging.py

```
L24: def test_verbosity_level(tmp_path, monkeypatch, flags, expected_level):
L45: def flaky_on_pypy(func):
L47: def _func():
L60: def test_patching_does_not_cause_problems():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_ext.py

```
L24: class TestBuildExt:
L25: def test_get_ext_filename(self):
L38: def test_abi3_filename(self):
L59: def test_ext_suffix_override(self):
L91: def dist_with_example(self):
L108: def test_get_outputs(self, tmpdir_cwd, monkeypatch):
L140: def test_get_output_mapping_with_stub(self, tmpdir_cwd, monkeypatch):
```

```

L158: def C(file):
L182: class TestBuildExtInplace:
L183: def get_build_ext_cmd(self, optional: bool, **opts) -> build_ext:
L197: def get_log_messages(self, caplog, capsys):
L206: def test_optional(self, tmpdir_cwd, caplog, capsys):
L219: def test_non_optional(self, tmpdir_cwd):
L226: def test_build_ext_config_handling(tmpdir_cwd):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_dist_info.py

```

L19: class TestDistInfo:
L20: def test_invalid_version(self, tmp_path):
L32: def test_tag_arguments(self, tmp_path):
L53: def test_output_dir(self, tmp_path, keep_egg_info):
L69: class TestWheelCompatibility:
L110: def test_dist_info_is_the_same_as_in_wheel(
L133: def run_command_inner(*cmd, **kwargs):
L146: def run_command(*args, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_dist.py

```

L18: def test_dist_fetch_build_egg(tmpdir, setuptools_wheel):
L25: def sdist_with_index(distname, version):
L75: def test_provides_extras_deterministic_order():
L135: def test_check_package_data(package_data, expected_message):
L143: def test_check_specifier():
L159: def test_metadata_name():
L173: def test_dist_default_py_modules(tmp_path, dist_name, py_module):
L216: def test_dist_default_packages(
L267: def test_dist_default_name(tmp_path, dist_name, package_dir, package_files):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_find_packages.py

```

L15: class TestFindPackages:
L16: def setup_method(self, method):
L20: def teardown_method(self, method):
L23: def _make_pkg_structure(self):

```

```

L52: def _mkdir(self, path, parent_dir=None):
L58: def _touch(self, path, dir_=None):
L64: def test_regular_package(self):
L69: def test_exclude(self):
L74: def test_exclude_recursive(self):
L83: def test_include_excludes_other(self):
L93: def test_dir_with_dot_is_skipped(self):
L101: def test_dir_with_packages_in_subdir_is_excluded(self):
L113: def test_symlinked_packages_are_included(self):
L127: def _assert_packages(self, actual, expected):
L130: def test_pep420_ns_package(self):
L136: def test_pep420_ns_package_no_includes(self):
L140: def test_pep420_ns_package_no_includes_or_excludes(self):
L145: def test_regular_package_with_nested_pep420_ns_packages(self):
L152: def test_pep420_ns_package_no_non_package_dirs(self):
L159: class TestFlatLayoutPackageFinder:
L207: def test_unwanted_directories_not_included(self, tmp_path, example):
L214: def ensure_files(root_path, files):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_archive_util.py

```

L10: def tarfile_with_unicode(tmpdir):
L34: def test_unicode_files(tarfile_with_unicode, tmpdir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_install_scripts.py

```

L13: class TestInstallScripts:
L23: def _run_install_scripts(self, install_dir, executable=None):
L36: def test_sys_executable_escaping_unix(self, tmpdir, monkeypatch):
L50: def test_sys_executable_escaping_win32(self, tmpdir, monkeypatch):
L64: def test_executable_with_spaces_escaping_unix(self, tmpdir):
L78: def test_executable_arg_escaping_win32(self, tmpdir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_bdist_egg.py

```

L21: def setup_context(tmpdir):
L30: class Test:

```

```
L33: def test_bdist_egg(self):
L57: def test_exclude_source_files(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_virtualenv.py

```
L11: def pytest_virtualenv_works(venv):
L21: def test_clean_env_install(venv_without_setuptools, setuptools_wheel):
L29: def access_pypi():
L86: def test_pip_upgrade_from_source(
L108: def test_no_missing_dependencies(bare_venv, request):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_glob.py

```
L42: def test_glob(monkeypatch, tmpdir, tree, pattern, matches):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/fixtures.py

```
L21: def user_override(monkeypatch):
L35: def tmpdir_cwd(tmpdir):
L41: def workaround_xdist_376(request):
L58: def sample_project(tmp_path):
L71: def sample_project_cwd(sample_project):
L84: def _build_distributions(tmp_path_factory, request):
L112: def setuptools_sdist(tmp_path_factory, request):
L122: def setuptools_wheel(tmp_path_factory, request):
L132: def venv(tmp_path, setuptools_wheel):
L154: def venv_without_setuptools(tmp_path):
L164: def bare_venv(tmp_path):
L173: def make_sdist(dist_path, files):
L190: def make_trivial_sdist(dist_path, distname, version, setuptools_wheel=None):
L230: def make_nspkg_sdist(dist_path, distname, version):
L266: def make_python_requires_sdist(dist_path, distname, version, python_requires):
L290: def create_setup_requires_package(
L368: def pbr_package(tmp_path, monkeypatch, venv):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_bdist_wheel.py

```

L216: def bdist_wheel_cmd(**kwargs):
L231: def mkexample(tmp_path_factory, name):
L238: def wheel_paths(tmp_path_factory):
L251: def dummy_dist(tmp_path_factory):
L256: def licenses_dist(tmp_path_factory):
L260: def test_no_scripts(wheel_paths):
L267: def test_unicode_record(wheel_paths):
L286: def test_preserve_unicode_metadata(monkeypatch, tmp_path):
L295: class simpler_bdist_wheel(bdist_wheel):
L298: def __init__(self) -> None:
L302: def license_paths(self):
L314: def test_licenses_default(dummy_dist, monkeypatch, tmp_path):
L325: def test_licenses_deprecated(dummy_dist, monkeypatch, tmp_path):
L351: def test_licenses_override(dummy_dist, monkeypatch, tmp_path, config_file, config):
L366: def test_licenses_preserve_folder_structure(licenses_dist, monkeypatch, tmp_path):
L382: def test_licenses_disabled(dummy_dist, monkeypatch, tmp_path):
L392: def test_build_number(dummy_dist, monkeypatch, tmp_path):
L401: def test_universal_deprecated(dummy_dist, monkeypatch, tmp_path):
L446: def test_limited_abi(monkeypatch, tmp_path, tmp_path_factory):
L457: def test_build_from_readonly_tree(dummy_dist, monkeypatch, tmp_path):
L475: def test_compression(dummy_dist, monkeypatch, tmp_path, option, compress_type):
L486: def test_wheelfile_line_endings(wheel_paths):
L494: def test_unix_epoch_timestamps(dummy_dist, monkeypatch, tmp_path):
L503: def test_get_abi_tag_windows(monkeypatch):
L515: def test_get_abi_tag_pypy_old(monkeypatch):
L521: def test_get_abi_tag_pypy_new(monkeypatch):
L527: def test_get_abi_tag_graalpy(monkeypatch):
L535: def test_get_abi_tag_fallback(monkeypatch):
L541: def test_platform_with_space(dummy_dist, monkeypatch):
L547: def test_data_dir_with_tag_build(monkeypatch, tmp_path):
L609: def test_platform_linux32(reported, expected, monkeypatch):
L619: def test_no_ctypes(monkeypatch) -> None:
L620: def _fake_import(name: str, *args, **kwargs):
L641: def test_dist_info_provided(dummy_dist, monkeypatch, tmp_path):
L666: def test_allow_grace_period_parent_directory_license(monkeypatch, tmp_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_config_discovery.py

```

L24: class TestFindParentPackage:
L25: def test_single_package(self, tmp_path):
L33: def test_multiple_toplevel(self, tmp_path):
L43: class TestDiscoverPackagesAndPyModules:

```



```

L70: def _get_info(self, circumstance):
L77: def test_sdist_filelist(self, tmp_path, circumstance):
L88: def test_project(self, tmp_path, circumstance):
L171: def test_purposefully_empty(self, tmp_path, config_file, param, circumstance):
L213: def test_flat_layout_with_extra_files(self, tmp_path, extra_files, pkgs):
L226: def test_flat_layout_with_dangerous_extra_files(self, tmp_path, extra_files):
L232: def test_flat_layout_with_single_module(self, tmp_path):
L238: def test_flat_layout_with_multiple_modules(self, tmp_path):
L244: def test_py_modules_when_wheel_dir_is_cwd(self, tmp_path):
L258: class TestNoConfig:
L271: def test_discover_name(self, tmp_path, example):
L276: def test_build_with_discovered_name(self, tmp_path):
L285: class TestWithAttrDirective:
L293: def test_setupcfg_metadata(self, tmp_path, folder, opts):
L316: def test_pyproject_metadata(self, tmp_path):
L333: class TestWithCEExtension:
L334: def _simulate_package_with_extension(self, tmp_path):
L367: def test_skip_discovery_with_setupcfg_metadata(self, tmp_path):
L395: def test_dont_skip_discovery_with_pyproject_metadata(self, tmp_path):
L415: class TestWithPackageData:
L416: def _simulate_package_with_data_files(self, tmp_path, src_root):
L485: def test_include_package_data(self, tmp_path, src_root, files):
L512: def test_compatible_with_numpy_configuration(tmp_path):
L526: def test_name_discovery_doesnt_break_cli(tmpdir_cwd):
L535: def test_preserve_explicit_name_with_dynamic_version(tmpdir_cwd, monkeypatch):
L559: def spy_analyse_name():
L571: def _populate_project_dir(root, files, options):
L588: def _write_setupcfg(root, options):
L611: def _run_build(path, *flags):
L616: def _get_dist(dist_path, attrs):
L638: def _run_sdist_programatically(dist_path, attrs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_setuptools.py

```

L6: class TestEdit:
L8: def parse_config(filename):
L15: def write_text(file, content):
L19: def test_utf8_encoding_retained(self, tmpdir):
L31: def test_case_retained(self, tmpdir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/text.py

```

L1: class Filenames:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_sdist.py

```

L55: def quiet():
L65: def posix(path):
L73: def decompose(path):
L85: def read_all_bytes(filename):
L90: def latin1_fail():
L115: def touch(path):
L120: def symlink_or_skip_test(src, dst):
L129: class TestSdistTest:
L131: def source_dir(self, tmpdir):
L155: def assert_package_data_in_manifest(self, cmd):
L162: def setup_with_extension(self):
L175: def test_package_data_in_sdist(self):
L191: def test_package_data_and_include_package_data_in_sdist(self):
L209: def test_extension_sources_in_sdist(self):
L220: def test_missing_extension_sources(self):
L234: def test_symlinked_extension_sources(self):
L273: def test_invalid_extension_depends(self, reason, caplog):
L316: def test_custom_build_py(self):
L325: class CustomBuildPy(OrigBuildPy):
L330: def get_data_files(self):
L354: def test_setup_py_exists(self):
L366: def test_setup_py_missing(self):
L380: def test_setup_py_excluded(self):
L395: def test_defaults_case_sensitivity(self, source_dir):
L423: def test_exclude_dev_only_cache_folders(self, source_dir):
L464: def test_manifest_is_written_with_utf8_encoding(self):
L493: def test_write_manifest_allows_utf8_filenames(self):
L526: def test_write_manifest_skips_non_utf8_filenames(self):
L562: def test_manifest_is_read_with_utf8_encoding(self):
L593: def test_read_manifest_skips_non_utf8_filenames(self):
L625: def test_sdist_with_utf8_encoded_filename(self):
L656: def make_strings(cls, item):
L665: def test_sdist_with_latin1_encoded_filename(self):
L736: def test_add_files_referenced_by_config_directives(self, source_dir, config):
L764: def test_pyproject_toml_in_sdist(self, source_dir):
L778: def test_pyproject_toml_excluded(self, source_dir):
L794: def test_build_subcommand_source_files(self, source_dir):
L811: class build_custom(Command):
L812: def initialize_options(self): ...
L814: def finalize_options(self): ...
L816: def run(self): ...
L818: def get_source_files(self):
L832: def test_build_base_pathlib(self, source_dir):
L847: def test_default_revctrl():
L868: class TestRegressions:

```

```

L875: def files_for_symlink_in_extension_depends(tmp_path, dep_path):
L904: def test_symlink_in_extension_depends(self, monkeypatch, tmp_path, dep_path):
L920: def files_for_external_path_in_extension_depends(tmp_path, dep_path):
L952: def test_external_path_in_extension_depends(self, monkeypatch, tmp_path, dep_path):
L963: def run_sdist(monkeypatch, project):
L974: def test_sanity_check_setuptools_own_sdist(setuptools_sdist):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_name_spaces.py

```

L9: class TestNamespaces:
L10: def test_mixed_site_and_non_site(self, tmpdir):
L52: def test_namespace_package_installed_and_cwd(self, tmpdir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_shutil_wrapper.py

```

L8: def test_rmtree_readonly(monkeypatch, tmp_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_windows_wrappers.py

```

L28: class WrapperTester:
L30: def prep_script(cls, template):
L35: def create_script(cls, tmpdir):
L55: def win_launcher_exe(prefix):
L64: class TestCLI(WrapperTester):
L82: def test_basic(self, tmpdir):
L130: def test_symlink(self, tmpdir):
L167: def test_with_options(self, tmpdir):
L216: class TestGUI(WrapperTester):
L236: def test_basic(self, tmpdir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_scripts.py

```

L4: class TestWindowsScriptWriter:

```

```
L15: def test_header(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_bdist_deprecations.py

```
L15: def test_bdist_rpm_warning(distutils_cmd, tmpdir_cwd):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_egg_info.py

```
L24: class Environment(str):
L29: def env():
L49: class TestEggInfo:
L63: def _create_project(self):
L68: def run():
L75: def _extract_mv_version(pkg_info_lines: list[str]) -> tuple[int, int]:
L80: def test_egg_info_save_version_info_setup_empty(self, tmpdir_cwd, env):
L107: def _validate_content_order(content, expected):
L116: def test_egg_info_save_version_info_setup_defaults(self, tmpdir_cwd, env):
L151: def test_expected_files_produced(self, tmpdir_cwd, env):
L167: def test_handling_utime_error(self, tmpdir_cwd, env):
L182: def test_license_is_a_string(self, tmpdir_cwd, env):
L215: def test_rebuilt(self, tmpdir_cwd, env):
L230: def test_manifest_template_is_read(self, tmpdir_cwd, env):
L248: def _setup_script_with_requires(self, requires, use_setup_cfg=False):
L267: class RequiresTestHelper:
L269: def parametrize(*test_list, **format_dict):
L462: def test_requires(
L483: def test_install_requires_unordered_disallowed(self, tmpdir_cwd, env):
L494: def test_extras_require_with_invalid_marker(self, tmpdir_cwd, env):
L502: def test_extras_require_with_invalid_marker_in_req(self, tmpdir_cwd, env):
L510: def test_provides_extra(self, tmpdir_cwd, env):
L527: def test_doesnt_provides_extra(self, tmpdir_cwd, env):
L610: def test_setup_cfg_license_file(self, tmpdir_cwd, env, files, license_in_sources):
L836: def test_setup_cfg_license_files(
L1020: def test_setup_cfg_license_file_license_files(
L1041: def test_license_file_attr_pkg_info(self, tmpdir_cwd, env):
L1080: def test_metadata_version(self, tmpdir_cwd, env):
L1094: def test_long_description_content_type(self, tmpdir_cwd, env):
L1121: def test_long_description(self, tmpdir_cwd, env):
L1144: def test_project_urls(self, tmpdir_cwd, env):
L1176: def test_license(self, tmpdir_cwd, env):
L1189: def test_license_escape(self, tmpdir_cwd, env):
L1207: def test_python_requires_egg_info(self, tmpdir_cwd, env):
```

```

L1224: def test_manifest_maker_warning_suppression(self):
L1233: def test_egg_info_includes_setup_py(self, tmpdir_cwd):
L1247: def _run_egg_info_command(self, tmpdir_cwd, env, cmd=None, output=None):
L1266: def test_egg_info_tag_only_once(self, tmpdir_cwd, env):
L1285: class TestWriteEntries:
L1286: def test_invalid_entry_point(self, tmpdir_cwd, env):
L1296: def test_valid_entry_point(self, tmpdir_cwd, env):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_manifest.py

```

L26: def make_local_path(s):
L45: def quiet():
L54: def touch(filename):
L135: def pattern_match(request):
L146: def pattern_mismatch(request):
L150: def test_translated_pattern_match(pattern_match):
L155: def test_translated_pattern_mismatch(pattern_mismatch):
L160: class TempDirTestCase:
L161: def setup_method(self, method):
L166: def teardown_method(self, method):
L171: class TestManifestTest(TempDirTestCase):
L172: def setup_method(self, method):
L211: def make_manifest(self, contents):
L217: def get_files(self):
L228: def test_no_manifest(self):
L232: def test_empty_files(self):
L237: def test_include(self):
L243: def test_exclude(self):
L255: def test_include_multiple(self):
L269: def test_graft(self):
L281: def test_graft_glob_syntax(self):
L293: def test_graft_global_exclude(self):
L305: def test_global_include(self):
L322: def test_graft_prune(self):
L335: class TestFileListTest(TempDirTestCase):
L342: def _compat_record_logs(self, monkeypatch, caplog):
L345: def _log(_logger, level, msg, args):
L352: def get_records(self, caplog, *levels):
L355: def assertNoWarnings(self, caplog):
L359: def assertWarnings(self, caplog):
L366: def make_files(self, files):
L373: def test_process_template_line(self):
L436: def test_exclude_pattern(self):
L453: def test_include_pattern(self):
L471: def test_process_template_line_invalid(self):
L488: def test_include(self, caplog):

```

```

L505: def test_exclude(self, caplog):
L522: def test_global_include(self, caplog):
L539: def test_global_exclude(self, caplog):
L556: def test_recursive_include(self, caplog):
L573: def test_recursive_exclude(self, caplog):
L590: def test_graft(self, caplog):
L607: def test_prune(self, caplog):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/environm
ent.py**

```

L10: class VirtualEnv(jaraco.envs.VirtualEnv):
L18: def run(self, cmd, *args, **kwargs):
L37: def _which_dirs(cmd):
L46: def run_setup_py(cmd, pypath=None, path=None, data_stream=0, env=None):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/namespac
es.py**

```

L7: def iter_namespace_pkgs(namespace):
L13: def build_namespace_package(tmpdir, name, version="1.0", impl="pkg_resources"):
L58: def build_pep420_namespace_package(tmpdir, name):
L81: def make_site_dir(target):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_whee
l.py**

```

L82: def test_wheel_info(filename, info):
L92: def build_wheel(extra_file_defs=None, **kwargs):
L116: def tree_set(root):
L124: def flatten_tree(tree):
L139: def format_install_tree(tree):
L150: def _check_wheel_install(
L170: class Record:
L171: def __init__(self, id, **kwargs) -> None:
L175: def __repr__(self) -> str:
L554: def test_wheel_install(params):
L579: def test_wheel_no_dist_dir():
L594: def test_wheel_is_compatible(monkeypatch):
L595: def sys_tags():

```

```
L605: def test_wheel_mode():
L607: def build_wheel(extra_file_defs=None, **kwargs):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_warnings.py

```
L62: def test_formatting(monkeypatch, example_name):
L76: def test_due_date_enforcement(monkeypatch):
L77: class _MyDeprecation(SetuptoolsDeprecationWarning):
L105: def _get_message(warn_info):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_distutils_adoption.py

```
L13: def win_sr(env):
L25: def find_distutils(venv, imports='distutils', env=None, **kwargs):
L31: def count_meta_path(venv, env=None):
L50: def test_distutils_stdlib(venv):
L59: def test_distutils_local_with_setuptools(venv):
L70: def test_distutils_local(venv):
L80: def test_pip_import(venv):
L89: def test_distutils_has_origin():
L129: def test_modules_are_not_duplicated_on_import(distutils_version, imported_module,
venv):
L155: def test_log_module_is_not_duplicated_on_import(distutils_version, venv):
L188: def test_consistent_error_from_modified_py(distutils_version, imported_module, venv):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_core_metadata.py

```
L66: def test_rfc822_unescape(content, result):
L70: def __read_test_cases():
L169: def test_read_metadata(name, attrs):
L209: def __maintainer_test_cases():
L212: def merge_dicts(d1, d2):
L278: def test_maintainer_author(name, attrs, tmpdir):
L317: class TestParityWithMetadataFromPyPaWheel:
L318: def base_example(self):
L346: def test_requires_dist(self, tmp_path):
L368: def dist(self, request, monkeypatch, tmp_path):
```

```

L384: def test_pkg_info_roundtrip(self, tmp_path, dist):
L412: class TestPEP643:
L451: def test_static_config_has_no_dynamic(self, file, tmpdir_cwd):
L474: def test_modified_fields_marked_as_dynamic(self, file, fields, tmpdir_cwd):
L498: def test_license_files_dynamic(self, extra_toml, tmpdir_cwd):
L532: def _makedist(**attrs):
L538: def _get_pkginfo(dist: Distribution):
L544: def _get_metadata(dist: Distribution | None = None):
L548: def _valid_metadata(text: str) -> bool:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build
.py**

```

L6: def test_distribution_gives_setuptools_build_obj(tmpdir_cwd):
L23: class Subcommand(Command):
L26: def initialize_options(self):
L29: def finalize_options(self):
L32: def run(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_uni
code_utils.py**

```

L4: def test_filesys_decode_fs_encoding_is_None(monkeypatch):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_setu
uptools.py**

```

L23: def isolated_dir(tmpdir_cwd):
L27: def makeSetup(**args):
L47: class TestDepends:
L48: def testExtractConst(self):
L53: def f1():
L72: def testFindModule(self):
L81: def sample_module(self, monkeypatch, tmp_path):
L90: def testModuleExtract(self, sample_module):
L97: def testRequire(self, sample_module):
L120: def test_require_present(self):
L138: class TestDistro:
L139: def setup_method(self, method):
L150: def testDistroType(self):

```



```

L153: def testExcludePackage(self):
L170: def testIncludeExclude(self):
L183: def testExcludePackages(self):
L189: def testEmpty(self):
L195: def testContents(self):
L208: def testInvalidIncludeExclude(self):
L229: def example_source(tmpdir):
L236: def test_findall(example_source):
L243: def test_findall_curdir(example_source):
L251: def can_symlink(tmpdir):
L265: def test_findall_missing_symlink(tmpdir):
L273: def test_its_own_wheel_does_not_contain_tests(setuptools_wheel):
L281: def test_wheel_includes_cli_scripts(setuptools_wheel):
L288: def test_wheel_includes_vendored_metadata(setuptools_wheel):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/contexts.py

```

L13: def tmpdir(cd=lambda dir: None, **kwargs):
L25: def environment(**replacements):
L49: def quiet():
L69: def save_user_site_setting():
L78: def suppress_exceptions(*excs):
L85: def multiproc(request):
L98: def session_locked_tmp_dir(request, tmp_path_factory, name):
L112: def save_paths():
L123: def save_sys_modules():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_meta.py

```

L37: class BuildBackendBase:
L38: def __init__(self, cwd='.', env=None, backend_name='setuptools.build_meta') -> None:
L44: class BuildBackend(BuildBackendBase):
L47: def __init__(self, *args, **kwargs) -> None:
L51: def __getattr__(self, name: str) -> Callable[..., Any]:
L54: def method(*args, **kw):
L72: def _kill(self, pid):
L79: class BuildBackendCaller(BuildBackendBase):
L80: def __init__(self, *args, **kwargs) -> None:
L85: def __call__(self, name, *args, **kw) -> Any:
L113: def run():
L132: def run():
L141: def function():

```

```

L154: def run():
L198: def run():
L218: def run():
L226: class TestBuildMetaBackend:
L229: def get_build_backend(self):
L233: def build_backend(self, tmpdir, request):
L238: def test_get_requires_for_build_wheel(self, build_backend):
L243: def test_get_requires_for_build_sdist(self, build_backend):
L248: def test_build_wheel(self, build_backend):
L269: def test_build_with_existing_file_present(self, build_type, tmpdir_cwd):
L320: def test_build_with_pyproject_config(self, tmpdir, setup_script):
L465: def test_static_metadata_in_pyproject_config(self, tmpdir):
L484: def run():
L528: def test_build_sdist(self, build_backend):
L535: def test_prepare_metadata_for_build_wheel(self, build_backend):
L543: def test_prepare_metadata_inplace(self, build_backend):
L560: def test_build_sdist_explicit_dist(self, build_backend):
L567: def test_build_sdist_version_change(self, build_backend):
L592: def test_build_sdist_pyproject_toml_exists(self, tmpdir_cwd):
L617: def test_build_sdist_setup_py_exists(self, tmpdir_cwd):
L627: def test_build_sdist_setup_py_manifest_excluded(self, tmpdir_cwd):
L653: def test_build_sdist_builds_targz_even_if_zip_indicated(self, tmpdir_cwd):
L695: def test_build_sdist_relative_path_import(self, tmpdir_cwd):
L712: def _assert_link_tree(self, parent_dir):
L719: def test_editable_without_config_settings(self, tmpdir_cwd):
L733: def test_build_wheel_inplace(self, tmpdir_cwd):
L744: def test_editable_with_config_settings(self, tmpdir_cwd, config_settings):
L769: def test_setup_requires(self, setup_literal, requirements, use_wheel, tmpdir_cwd):
L785: def run():
L806: def test_setup_requires_with_auto_discovery(self, tmpdir_cwd):
L834: def test_dont_install_setup_requires(self, tmpdir_cwd):
L850: def run():
L885: def test_sys_argv_passthrough(self, tmpdir_cwd):
L906: def test_setup_py_file_abspath(self, tmpdir_cwd):
L912: def test_build_with_empty_setuptools(self, build_backend, build_hook):
L921: class TestBuildMetaLegacyBackend(TestBuildMetaBackend):
L925: def test_build_sdist_relative_path_import(self, tmpdir_cwd):
L932: def test_sys_argv_passthrough(self, tmpdir_cwd):
L940: def test_sys_exit_0_in_setuptools(monkeypatch, tmp_path):
L953: def test_system_exit_in_setuptools(monkeypatch, tmp_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_clib.py

```

L12: class TestBuildCLib:
L14: def test_build_libraries(self, mock_newer):
L61: def test_build_libraries_reproducible(self, mock_newer):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_editable_install.py

```

L43: def editable_opts(request):
L131: def test_editable_with_pyproject(tmp_path, venv, files, editable_opts):
L156: def test_editable_with_flat_layout(tmp_path, venv, editable_opts):
L196: def test_editable_with_single_module(tmp_path, venv, editable_opts):
L234: class TestLegacyNamespaces:
L237: def test_nspkg_file_is_unique(self, tmp_path, monkeypatch):
L271: def test_namespace_package_importable(
L298: class TestPep420Namespaces:
L299: def test_namespace_package_importable(self, venv, tmp_path, editable_opts):
L314: def test_namespace_created_via_package_dir(self, venv, tmp_path, editable_opts):
L348: def test_namespace_accidental_config_in_lenient_mode(self, venv, tmp_path):
L399: def test_editable_with_prefix(tmp_path, sample_project, editable_opts):
L439: class TestFinderTemplate:
L445: def install_finder(self, finder):
L450: def test_packages(self, tmp_path):
L482: def test_namespace(self, tmp_path):
L505: def test_combine_namespaces(self, tmp_path):
L532: def test_combine_namespaces_nested(self, tmp_path):
L575: def test_dynamic_path_computation(self, tmp_path):
L611: def test_no_recursion(self, tmp_path):
L632: def test_similar_name(self, tmp_path):
L656: def test_case_sensitivity(self, tmp_path):
L697: def test_namespace_case_sensitivity(self, tmp_path):
L738: def test_intermediate_packages(self, tmp_path):
L783: def test_pkg_roots(tmp_path):
L832: class TestOverallBehaviour:
L901: def test_editable_install(self, tmp_path, venv, layout, editable_opts):
L952: class TestLinkTree:
L969: def test_generated_tree(self, tmp_path):
L1003: def test_strict_install(self, tmp_path, venv):
L1036: def test_compat_install(tmp_path, venv):
L1069: def test_pbr_integration(pbr_package, venv, editable_opts):
L1086: class TestCustomBuildPy:
L1107: class my_build_py(orig):
L1108: def run(self):
L1117: def test_safeguarded_from_errors(self, tmp_path, venv):
L1128: class TestCustomBuildWheel:
L1129: def install_custom_build_wheel(self, dist):
L1132: class MyBdistWheel(bdist_wheel_cls):
L1133: def get_tag(self):
L1142: def test_access_plat_name(self, tmpdir_cwd):
L1157: class TestCustomBuildExt:
L1158: def install_custom_build_ext_distutils(self, dist):
L1161: class MyBuildExt(build_ext_cls):
L1169: def test_distutils_leave_inplace_files(self, tmpdir_cwd):

```

```

L1189: def test_debugging_tips(tmpdir_cwd, monkeypatch):
L1208: def test_encode_pth():
L1214: def install_project(name, venv, tmp_path, files, *opts):
L1226: def _addsitedirs(new_dirs):
L1242: def assert_path(pkg, expected):
L1250: def assert_link_to(file: Path, other: Path) -> None:
L1260: def comparable_path(str_with_path: str) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/integration/helpers.py

```

L18: def run(cmd, env=None):
L38: class Archive:
L41: def __init__(self, filename) -> None:
L50: def __iter__(self) -> Iterator[ZipInfo] | Iterator[tarfile.TarInfo]:
L55: def get_name(self, zip_or_tar_info):
L60: def get_content(self, zip_or_tar_info):
L70: def get_sdist_members(sdist_path):
L78: def get_wheel_members(wheel_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/integration/test_pip_install_sdist.py

```

L100: def venv_python(tmp_path):
L107: def _prepare(tmp_path, venv_python, monkeypatch):
L127: def test_install_sdist(package, version, tmp_path, venv_python, setuptools_wheel):
L151: def retrieve_sdist(package, version, tmp_path):
L171: def retrieve_pypi_sdist_metadata(package, version):
L186: def download(url, dest, md5_digest):
L198: def build_deps(package, sdist_file):
L217: def _read_pyproject(archive):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/integration/test_pbr.py

```

L7: def test_pbr_integration(pbr_package, venv):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/tes

t_setupcfg.py

```

L23: class ErrConfigHandler(ConfigHandler[Target]):
L29: def make_package_dir(name, base_dir, ns=False):
L40: def fake_env(
L66: def get_dist(tmpdir, kwargs_initial=None, parse=True):
L77: def test_parsers_implemented():
L83: class TestConfigurationReader:
L84: def test_basic(self, tmpdir):
L99: def test_no_config(self, tmpdir):
L103: def test_ignore_errors(self, tmpdir):
L119: class TestMetadata:
L120: def test_basic(self, tmpdir):
L157: def test_license_cfg(self, tmpdir):
L177: def test_file_mixed(self, tmpdir):
L191: def test_file_sandboxed(self, tmpdir):
L201: def test_aliases(self, tmpdir):
L225: def test_multiline(self, tmpdir):
L245: def test_dict(self, tmpdir):
L260: def test_version(self, tmpdir):
L294: def test_version_file(self, tmpdir):
L306: def test_version_with_package_dir_simple(self, tmpdir):
L320: def test_version_with_package_dir_rename(self, tmpdir):
L334: def test_version_with_package_dir_complex(self, tmpdir):
L348: def test_unknown_meta_item(self, tmpdir):
L353: def test_usupported_section(self, tmpdir):
L359: def test_classifiers(self, tmpdir):
L389: def test_interpolation(self, tmpdir):
L395: def test_non_ascii_1(self, tmpdir):
L400: def test_non_ascii_3(self, tmpdir):
L405: def test_non_ascii_4(self, tmpdir):
L414: def test_not_utf8(self, tmpdir):
L454: def test_invalid_options_previously_deprecated(
L471: class TestOptions:
L472: def test_basic(self, tmpdir):
L515: def test_multiline(self, tmpdir):
L567: def test_package_dir_fail(self, tmpdir):
L573: def test_package_data(self, tmpdir):
L595: def test_packages(self, tmpdir):
L601: def test_find_directive(self, tmpdir):
L638: def test_find_namespace_directive(self, tmpdir):
L677: def test_extras_require(self, tmpdir):
L709: def test_raises_accidental_env_marker_misconfig(self, config, tmpdir):
L730: def test_warn_accidental_env_marker_misconfig(self, config, tmpdir):
L756: def test_nowarn_accidental_env_marker_misconfig(self, config, tmpdir, recwarn):
L764: def test_dash_preserved_extras_require(self, tmpdir):
L770: def test_entry_points(self, tmpdir):
L801: def test_case_sensitive_entry_points(self, tmpdir):
L819: def test_data_files(self, tmpdir):
L836: def test_data_files_globby(self, tmpdir):

```

```

L871: def test_python_requires_simple(self, tmpdir):
L884: def test_python_requires_compound(self, tmpdir):
L897: def test_python_requires_invalid(self, tmpdir):
L911: def test_cmdclass(self, tmpdir):
L932: def test_requirements_file(self, tmpdir):
L956: class TestExternalSetters:
L967: def _fake_distribution_init(self, dist, attrs):
L978: def test_external_setters(self, mock_parent_init, tmpdir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_pyprojecttoml.py

```

L85: def create_example(path, pkg_root):
L114: def verify_example(config, path, pkg_root):
L140: def test_read_configuration(tmp_path):
L159: def test_discovered_package_dir_with_attr_directive_in_config(tmp_path, pkg_root,
opts):
L181: class TestEntryPoints:
L182: def write_entry_points(self, tmp_path):
L188: def pyproject(self, dynamic=None):
L193: def test_all_listed_in_dynamic(self, tmp_path):
L205: def test_scripts_not_listed_in_dynamic(self, tmp_path, missing_dynamic):
L214: class TestClassifiers:
L215: def test_dynamic(self, tmp_path):
L244: def test_dynamic_without_config(self, tmp_path):
L257: def test_dynamic_readme_from_setup_script_args(self, tmp_path):
L271: def test_dynamic_without_file(self, tmp_path):
L289: class TestImportNames:
L298: def test_not_implemented(self, monkeypatch, tmp_path, example):
L325: def test_ignore_unrelated_config(tmp_path, example):
L347: def test_invalid_example(tmp_path, example, error_msg):
L359: def test_empty(tmp_path, config):
L368: def test_include_package_data_by_default(tmp_path, config):
L379: def test_include_package_data_in_setuptools(tmp_path):
L399: def test_warn_tools_typo(tmp_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_expand.py

```

L14: def write_files(files, root_dir):
L21: def test_glob_relative(tmp_path, monkeypatch):
L40: def test_read_files(tmp_path, monkeypatch):
L69: class TestReadAttr:
L80: def test_read_attr_encoding_cookie(self, example, tmp_path):

```

```

L84: def test_read_attr(self, tmp_path, monkeypatch):
L119: def test_read_annotated_attr(self, tmp_path, example):
L138: def test_read_dynamic_attr(self, tmp_path, monkeypatch, example):
L149: def test_import_order(self, tmp_path):
L178: def test_resolve_class(monkeypatch, tmp_path, package_dir, file, module, return_value):
L195: def test_find_packages(tmp_path, args, pkgs):
L239: def test_fill_package_dir(tmp_path, files, where, expected_package_dir):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_pyprojecttoml_dynamic_deps.py

```

L11: def test_dynamic_dependencies(tmp_path):
L36: def test_dynamic_optional_dependencies(tmp_path):
L61: def test_mixed_dynamic_optional_dependencies(tmp_path):
L91: def test_mixed_extras_require_optional_dependencies(tmp_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_apply_pyprojecttoml.py

```

L35: def makedist(path, **attrs):
L39: def _mock_expand_patterns(patterns, *, **__):
L52: def test_apply_pyproject_equivalent_to_setupcfg(url, monkeypatch, tmp_path):
L168: def main_cli(): pass
L169: def main_gui(): pass
L170: def main_tomatoes(): pass
L200: def _pep621_example_project(
L218: def test_pep621_example(tmp_path):
L233: def test_readme_content_type(tmp_path, readme, ctype):
L239: def test_undefined_content_type(tmp_path):
L245: def test_no_explicit_content_type_for_missing_extension(tmp_path):
L274: def test_utf8_maintainer_in_metadata( # issue-3663
L325: def test_license_in_metadata(
L350: def test_license_classifier_with_license_expression(tmp_path):
L364: def test_license_classifier_without_license_expression(tmp_path):
L386: class TestLicenseFiles:
L387: def base_pyproject(
L411: def base_pyproject_license_pep639(self, tmp_path, additional_text=""):
L419: def test_both_license_and_license_files_defined(self, tmp_path):
L441: def test_both_license_and_license_files_defined_pep639(self, tmp_path):
L456: def test_license_files_defined_twice(self, tmp_path):
L465: def test_default_patterns(self, tmp_path):
L480: def test_missing_patterns(self, tmp_path):
L492: def test_deprecated_file_expands_to_text(self, tmp_path):
L510: class TestPyModules:

```

```

L513: def dist(self, name):
L526: def test_valid_module_name(self, tmp_path, monkeypatch, module):
L531: def test_invalid_module_name(self, tmp_path, monkeypatch, module):
L537: class TestExtModules:
L538: def make_dist(self, toml_config):
L544: def test_pyproject_sets_attribute(self, tmp_path, monkeypatch):
L560: def test_pyproject_define_macros_as_tuples(self, tmp_path, monkeypatch):
L578: class TestDeprecatedFields:
L579: def test_namespace_packages(self, tmp_path):
L593: class TestPresetField:
L594: def pyproject(self, tmp_path, dynamic, extra_content=""):
L621: def test_not_listed_in_dynamic(self, tmp_path, attr, field, value):
L642: def test_listed_in_dynamic(self, tmp_path, attr, field, value):
L649: def test_license_files_exempt_from_dynamic(self, monkeypatch, tmp_path):
L669: def test_warning_overwritten_dependencies(self, tmp_path):
L678: def test_optional_dependencies_dont_remove_env_markers(self, tmp_path):
L705: def test_scripts_dont_require_dynamic_entry_points(self, tmp_path, field, group):
L713: class TestMeta:
L714: def test_example_file_in_sdist(self, setuptools_sdist):
L720: class TestInteropCommandLineParsing:
L721: def test_version(self, tmp_path, monkeypatch, capsys):
L739: class TestStaticConfig:
L740: def test_mark_static_fields(self, tmp_path, monkeypatch):
L768: def core_metadata(dist) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/download/__init__.py

```

L21: def output_file(url: str, download_dir: Path = DOWNLOAD_DIR) -> Path:
L28: def retrieve_file(url: str, download_dir: Path = DOWNLOAD_DIR, wait: float = 5) -> Path:
L43: def urls_from_file(list_file: Path) -> list[str]:
L52: def download(url: str, dest: Path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/log.py

```

L26: def set_threshold(level):
L32: def set_verbosity(v):
L41: class Log(logging.Logger):
L44: def __init__(self, threshold=WARN):
L49: def threshold(self):
L53: def threshold(self, level):

```


Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/archi
ve_util.py**

```

L33: def _get_gid(name):
L46: def _get_uid(name):
L59: def make_tarball(
L108: def _set_uid_gid(tarinfo):
L126: def make_zipfile(
L198: def check_archive_formats(formats):
L210: def make_archive(
L220: def make_archive(
L229: def make_archive(

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/dist.p
y**

```

L62: def _ensure_list(value: str | Iterable[str], fieldname) -> str | list[str]:
L77: class Distribution:
L153: def __init__(self, attrs: MutableMapping[str, Any] | None = None) -> None: # noqa:
C901
L309: def get_option_dict(self, command):
L320: def dump_option_dicts(self, header=None, commands=None, indent: str = "") -> None:
L346: def find_config_files(self):
L369: def _gen_paths(self):
L388: def parse_config_files(self, filenames=None): # noqa: C901
L456: def parse_command_line(self):
L523: def _get_toplevel_options(self):
L537: def _parse_command_opts(self, parser, args): # noqa: C901
L635: def finalize_options(self) -> None:
L648: def _show_help(
L699: def handle_display_options(self, option_order):
L738: def print_command_list(self, commands, header, max_length) -> None:
L755: def print_commands(self) -> None:
L780: def get_command_list(self):
L810: def get_command_packages(self):
L822: def get_command_class(self, command: str) -> type[Command]:
L861: def get_command_obj(
L865: def get_command_obj(
L868: def get_command_obj(self, command: str, create: bool = True) -> Command | None:
L897: def _set_command_options(self, command_obj, option_dict=None): # noqa: C901
L940: def reinitialize_command(
L944: def reinitialize_command(
L947: def reinitialize_command(
L991: def announce(self, msg, level: int = logging.INFO) -> None:

```

```

L994: def run_commands(self) -> None:
L1004: def run_command(self, command: str) -> None:
L1024: def has_pure_modules(self) -> bool:
L1027: def has_ext_modules(self) -> bool:
L1030: def has_c_libraries(self) -> bool:
L1033: def has_modules(self) -> bool:
L1036: def has_headers(self) -> bool:
L1039: def has_scripts(self) -> bool:
L1042: def has_data_files(self) -> bool:
L1045: def is_pure(self) -> bool:
L1060: def _(self) -> None:
L1107: class DistributionMetadata:
L1136: def __init__(
L1161: def read_pkg_file(self, file: IO[str]) -> None:
L1165: def _read_field(name: str) -> str | None:
L1171: def _read_list(name):
L1213: def write_pkg_info(self, base_dir: str | os.PathLike[str]) -> None:
L1220: def write_pkg_file(self, file: SupportsWrite[str]) -> None:
L1237: def maybe_write(header, val):
L1259: def _write_list(self, file, name, values):
L1266: def get_name(self) -> str:
L1269: def get_version(self) -> str:
L1272: def get_fullname(self) -> str:
L1276: def _fullname(name: str, version: str) -> str:
L1294: def get_author(self) -> str | None:
L1297: def get_author_email(self) -> str | None:
L1300: def get_maintainer(self) -> str | None:
L1303: def get_maintainer_email(self) -> str | None:
L1306: def get_contact(self) -> str | None:
L1309: def get_contact_email(self) -> str | None:
L1312: def get_url(self) -> str | None:
L1315: def get_license(self) -> str | None:
L1320: def get_description(self) -> str | None:
L1323: def get_long_description(self) -> str | None:
L1326: def get_keywords(self) -> str | list[str]:
L1329: def set_keywords(self, value: str | Iterable[str]) -> None:
L1332: def get_platforms(self) -> str | list[str] | None:
L1335: def set_platforms(self, value: str | Iterable[str]) -> None:
L1338: def get_classifiers(self) -> str | list[str]:
L1341: def set_classifiers(self, value: str | Iterable[str]) -> None:
L1344: def get_download_url(self) -> str | None:
L1348: def get_requires(self) -> str | list[str]:
L1351: def set_requires(self, value: Iterable[str]) -> None:
L1358: def get_provides(self) -> str | list[str]:
L1361: def set_provides(self, value: Iterable[str]) -> None:
L1369: def get_obsoletes(self) -> str | list[str]:
L1372: def set_obsoletes(self, value: Iterable[str]) -> None:
L1380: def fix_help_options(options):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/cmd.py

```

L34: class Command:
L75: def __init__(self, dist: Distribution) -> None:
L117: def ensure_finalized(self) -> None:
L136: def initialize_options(self) -> None:
L151: def finalize_options(self) -> None:
L166: def dump_options(self, header=None, indent=""):
L181: def run(self) -> None:
L195: def announce(self, msg: object, level: int = logging.DEBUG) -> None:
L198: def debug_print(self, msg: object) -> None:
L221: def _ensure_stringlike(self, option, what, default=None):
L230: def ensure_string(self, option: str, default: str | None = None) -> None:
L236: def ensure_string_list(self, option: str) -> None:
L257: def _ensure_tested_string(self, option, tester, what, error_fmt, default=None):
L264: def ensure_filename(self, option: str) -> None:
L270: def ensure_dirname(self, option: str) -> None:
L280: def get_command_name(self) -> str:
L286: def set_undefined_options(
L311: def get_finalized_command(self, command: str, create: bool = True) -> Command:
L324: def reinitialize_command(
L328: def reinitialize_command(
L331: def reinitialize_command(
L336: def run_command(self, command: str) -> None:
L343: def get_sub_commands(self) -> list[str]:
L358: def warn(self, msg: object) -> None:
L361: def execute(
L370: def mkpath(self, name: str, mode: int = 0o777) -> None:
L374: def copy_file(
L384: def copy_file(
L393: def copy_file(
L414: def copy_tree(
L436: def move_file(
L440: def move_file(
L443: def move_file(
L452: def spawn(
L461: def make_archive(
L471: def make_archive(
L480: def make_archive(
L498: def make_file(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/_modified.py

```

L23: def _newer(source, target):

```

```

L29: def newer(
L47: def newer_pairwise(
L64: def newer_group(
L85: def missing_as_newer(source):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/text_file.py

```

L10: class TextFile:
L79: def __init__(self, filename=None, file=None, **options):
L114: def open(self, filename):
L121: def close(self):
L130: def gen_error(self, msg, line=None):
L142: def error(self, msg, line=None):
L145: def warn(self, msg, line=None):
L155: def readline(self): # noqa: C901
L272: def readlines(self):
L282: def unreadline(self, line):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/filelist.py

```

L21: class FileList:
L36: def __init__(self, warn: object = None, debug_print: object = None) -> None:
L42: def set_allfiles(self, allfiles: Iterable[str]) -> None:
L45: def findall(self, dir: str | os.PathLike[str] = os.curdir) -> None:
L48: def debug_print(self, msg: object) -> None:
L59: def append(self, item: str) -> None:
L62: def extend(self, items: Iterable[str]) -> None:
L65: def sort(self) -> None:
L74: def remove_duplicates(self) -> None:
L82: def _parse_template_line(self, line):
L112: def process_template_line(self, line: str) -> None: # noqa: C901
L201: def include_pattern(
L209: def include_pattern(
L218: def include_pattern(
L225: def include_pattern(
L273: def exclude_pattern(
L281: def exclude_pattern(
L290: def exclude_pattern(
L297: def exclude_pattern(
L324: def _find_all_simple(path):
L335: class _UniqueDirs(set):
L342: def __call__(self, walk_item):

```

```

L358: def filter(cls, items):
L362: def findall(dir: str | os.PathLike[str] = os.curdir):
L374: def glob_to_re(pattern):
L397: def translate_pattern(pattern, anchor=True, prefix=None, is_regex=False):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/_msvccompiler.py

```

L10: def __getattr__(name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/core.py

```

L43: def gen_usage(script_name):
L97: def setup(**attrs): # noqa: C901
L114: class found in 'cmdclass' is used in place of the default, which is
L194: def run_commands(dist):
L221: def run_setup(script_name, script_args: Iterable[str] | None = None, stop_after="run"):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/dir_util.py

```

L15: class SkipRepeatAbsolutePaths(set):
L23: def __init__(self):
L27: def clear(cls):
L30: def wrap(self, func):
L32: def wrapper(path, *args, **kwargs):
L48: def mkpath(name: pathlib.Path, mode=0o777, verbose=True) -> None:
L67: def _(name: str, *args, **kwargs):
L72: def _(name: None, *args, **kwargs):
L79: def create_tree(base_dir, files, mode=0o777, verbose=True):
L97: def copy_tree(
L147: def _copy_one(
L194: def _build_cmdtuple(path, cmdtuples):
L205: def remove_tree(directory, verbose=True):
L224: def ensure_relative(path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/file_u

til.py

```

L15: def _copy_file_contents(src, dst, buffer_size=16 * 1024): # noqa: C901
L63: def copy_file( # noqa: C901
L167: def move_file(src, dst, verbose=True): # noqa: C901
L223: def write_file(filename, contents):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/fancy_getopt.py

```

L37: class FancyGetopt:
L49: def __init__(self, option_table=None):
L89: def _build_index(self):
L94: def set_option_table(self, option_table):
L98: def add_option(self, long_option, short_option=None, help_string=None):
L108: def has_option(self, long_option):
L113: def get_attr_name(self, long_option):
L119: def _check_alias_dict(self, aliases, what):
L131: def set_aliases(self, alias):
L136: def set_negative_aliases(self, negative_alias):
L144: def _grok_option_table(self): # noqa: C901
L224: def getopt(self, args: Sequence[str] | None = None, object=None): # noqa: C901
L285: def get_option_order(self):
L295: def generate_help(self, header=None): # noqa: C901
L373: def print_help(self, header=None, file=None):
L380: def fancy_getopt(options, negative_opt, object, args: Sequence[str] | None):
L389: def wrap_text(text, width):
L443: def translate_longopt(opt):
L450: class OptionDummy:
L454: def __init__(self, options: Sequence[Any] = []):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/version.py

```

L35: def suppress_known_deprecation():
L45: class Version:
L52: def __init__(self, vstring=None):
L61: def __repr__(self):
L64: def __eq__(self, other):
L70: def __lt__(self, other):
L76: def __le__(self, other):
L82: def __gt__(self, other):
L88: def __ge__(self, other):

```

```

L112: class StrictVersion(Version):
L152: def parse(self, vstring):
L169: def __str__(self):
L180: def _cmp(self, other):
L193: def _cmp_prerelease(self, other):
L280: class LooseVersion(Version):
L314: def parse(self, vstring):
L328: def __str__(self):
L331: def __repr__(self):
L334: def _cmp(self, other):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/_macos_compat.py

```

L5: def bypass_compiler_fixup(cmd, args):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/spawn.py

```

L29: def _debug(cmd):
L36: def _inject_macos_ver(env: _MappingT | None) -> _MappingT | dict[str, str | int] | None:
L48: def _resolve(env: None) -> os._Environ[str]: ...
L50: def _resolve(env: _MappingT) -> _MappingT: ...
L51: def _resolve(env: _MappingT | None) -> _MappingT | os._Environ[str]:
L55: def spawn(
L94: def find_executable(executable: str, path: str | None = None) -> str | None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/dep_util.py

```

L6: def __getattr__(name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/extension.py

```

L23: class Extension:
L92: def __init__(

```

```
L152: def __repr__(self):
L156: def read_setup_file(filename): # noqa: C901
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/errors.py

```
L20: class DistutilsError(Exception):
L26: class DistutilsModuleError(DistutilsError):
L33: class DistutilsClassError(DistutilsError):
L42: class DistutilsGetoptError(DistutilsError):
L48: class DistutilsArgError(DistutilsError):
L55: class DistutilsFileError(DistutilsError):
L63: class DistutilsOptionError(DistutilsError):
L74: class DistutilsSetupError(DistutilsError):
L81: class DistutilsPlatformError(DistutilsError):
L89: class DistutilsExecError(DistutilsError):
L96: class DistutilsInternalError(DistutilsError):
L103: class DistutilsTemplateError(DistutilsError):
L107: class DistutilsByteCompileError(DistutilsError):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/versionpredicate.py

```
L16: def splitUp(pred):
L40: class VersionPredicate:
L105: def __init__(self, versionPredicateStr):
L130: def __str__(self):
L137: def satisfied_by(self, version):
L151: def split_provision(value):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/util.py

```
L35: def get_host_platform() -> str:
L49: def get_platform() -> str:
L67: def _clear_cached_macosx_ver():
L73: def get_macosx_target_ver_from_syscfg():
L86: def get_macosx_target_ver():
L118: def split_version(s: str) -> list[int]:
L124: def convert_path(pathname: str | os.PathLike[str]) -> str:
```



```

L142: def change_root(
L166: def check_envron() -> None:
L188: def subst_vars(s, local_vars: Mapping[str, object]) -> str:
L207: def _subst_compat(s):
L213: def _subst(match):
L227: def grok_environment_error(exc: object, prefix: str = "error: ") -> str:
L238: def _init_regex():
L245: def split_quoted(s: str) -> list[str]:
L311: def execute(
L331: def strtobool(val: str) -> bool:
L347: def byte_compile( # noqa: C901
L480: def rfc822_escape(header: str) -> str:
L495: def is_mingw() -> bool:
L504: def is_freethreaded():

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/sysconf.py

```

L33: def deprecated(message):
L59: def _is_python_source_dir(d):
L71: def _is_parent(dir_a, dir_b):
L81: def _fix_pcbuild(d):
L95: def _python_build():
L117: def get_python_version():
L125: def get_python_inc(plat_specific: bool = False, prefix: str | None = None) -> str:
L151: def _extant(path):
L158: def _get_python_inc_posix(prefix, spec_prefix, plat_specific):
L166: def _get_python_inc_posix_python(plat_specific):
L182: def _get_python_inc_from_config(plat_specific, spec_prefix):
L205: def _get_python_inc_posix_prefix(prefix):
L211: def _get_python_inc_nt(prefix, spec_prefix, plat_specific):
L223: def _posix_lib(standard_lib, libpython, early_prefix, prefix):
L230: def get_python_lib(
L278: def _customize_macos():
L295: def customize_compiler(compiler: CCompiler) -> None:
L382: def get_config_h_filename() -> str:
L387: def get_makefile_filename() -> str:
L392: def parse_config_h(fp, g=None):
L409: def parse_makefile(fn, g=None): # noqa: C901
L521: def expand_makefile_vars(s, vars):
L550: def get_config_vars() -> dict[str, str | int]: ...
L552: def get_config_vars(arg: str, /, *args: str) -> list[str | int]: ...
L553: def get_config_vars(*args: str) -> list[str | int] | dict[str, str | int]:
L575: def get_config_var(name: Literal["SO"]) -> int | str | None: ...
L577: def get_config_var(name: str) -> int | str | None: ...
L578: def get_config_var(name: str) -> int | str | None:
L591: def _add_flags(value: str, type: str) -> str:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_cmd.py**

```
L12: class MyCmd(Command):
L13: def initialize_options(self):
L18: def cmd(request):
L22: class TestCommand:
L23: def test_ensure_string_list(self, cmd):
L48: def test_make_file(self, cmd):
L54: def _execute(func, args, exec_msg, level):
L61: def test_dump_options(self, cmd):
L64: def _announce(msg, level):
L76: def test_ensure_string(self, cmd):
L88: def test_ensure_filename(self, cmd):
L95: def test_ensure_dirname(self, cmd):
L102: def test_debug_print(self, cmd, capsys, monkeypatch):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_install.py**

```
L21: def _make_ext_name(modname):
L27: class TestInstall(
L34: def test_home_installation_scheme(self):
L56: def check_path(got, expected):
L75: def test_user_site(self, monkeypatch):
L86: def _expanduser(path):
L130: def test_handle_extra_path(self):
L159: def test_finalize_options(self):
L183: def test_record(self):
L208: def test_record_extensions(self):
L240: def test_debug_mode(self, caplog, monkeypatch):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_build_py.py**

```
L15: class TestBuildPy(support.TempdirManager):
L16: def test_package_data(self):
L60: def test_empty_package_dir(self):
L82: def test_byte_compile(self):
L98: def test_byte_compile_optimized(self):
L115: def test_dir_in_package_data(self):
```

```
L147: def test_dont_write_bytecode(self, caplog):
L163: def test_namespace_package_does_not_warn(self, caplog):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_bdist_rpm.py**

```
L24: def sys_executable_encodable():
L40: class TestBuildRpm(
L47: def test_quiet(self):
L90: def test_no_optimize_flag(self):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_core.py**

```
L39: class install(_install):
L48: def main():
L57: def save_stdout(monkeypatch):
L62: def temp_file(tmp_path):
L68: class TestCore:
L69: def test_run_setup_provides_file(self, temp_file):
L75: def test_run_setup_preserves_sys_argv(self, temp_file):
L82: def test_run_setup_defines_subclass(self, temp_file):
L90: def test_run_setup_uses_current_dir(self, tmp_path):
L108: def test_run_setup_within_if_main(self, temp_file):
L114: def test_run_commands(self, temp_file):
L122: def test_debug_mode(self, capsys, monkeypatch):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_config_cmd.py**

```
L15: def info_log(request, monkeypatch):
L22: class TestConfig(support.TempdirManager):
L23: def _info(self, msg, *args):
L27: def test_dump_file(self):
L36: def test_search_cpp(self):
L56: def test_finalize_options(self):
L70: def test_clean(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_build_ext.py

```

L37: def user_site_dir(request):
L62: def safe_extension_import(name, path):
L70: def extension_redirect(mod, path):
L91: class TestBuildExt(TempdirManager):
L92: def build_ext(self, *args, **kwargs):
L96: def test_build_ext(self, copy_so):
L148: def _test_xx(copy_so):
L185: def test_solaris_enable_shared(self):
L207: def test_user_site(self):
L235: def test_optional_extension(self):
L251: def test_finalize_options(self):
L323: def test_check_extensions_list(self):
L383: def test_get_source_files(self):
L390: def test_unicode_module_names(self):
L403: def test_export_symbols__init__(self):
L416: def test_compiler_option(self):
L427: def test_get_outputs(self):
L490: def test_ext_fullpath(self):
L529: def test_deployment_target_default(self):
L537: def test_deployment_target_too_low(self):
L545: def test_deployment_target_higher_ok(self): # pragma: no cover
L557: def _try_compile_deployment_target(self, operator, target): # pragma: no cover
L624: class TestParallelBuildExt(TestBuildExt):
L625: def build_ext(self, *args, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_version.py

```

L10: def suppress_deprecation():
L15: class TestVersion:
L16: def test_prerelease(self):
L25: def test_cmp_strict(self):
L60: def test_cmp(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_log.py

```

L7: class TestLog:
L8: def test_non_ascii(self, caplog):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_file_util.py**

```
L14: def stuff(request, tmp_path):
L21: class TestFileUtil:
L22: def test_move_file_verbosity(self, caplog):
L45: def test_move_file_exception_unpacking_rename(self):
L54: def test_move_file_exception_unpacking_unlink(self):
L64: def test_copy_file_hard_link(self):
L82: def test_copy_file_hard_link_failure(self):
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_dist.py**

```
L24: class test_dist(Command):
L31: def initialize_options(self):
L35: class TestDistribution(Distribution):
L43: def find_config_files(self):
L48: def clear_argv():
L55: class TestDistributionBehavior(support.TempdirManager):
L56: def create_distribution(self, configfiles=()):
L63: def test_command_packages_unspecified(self, clear_argv):
L68: def test_command_packages_cmdline(self, clear_argv):
L92: def test_venv_install_options(self, tmp_path, clear_argv):
L153: def test_command_packages_configfile(self, tmp_path, clear_argv):
L177: def test_empty_options(self, request):
L184: def _warn(msg):
L204: def test_finalize_options(self):
L220: def test_get_command_packages(self):
L231: def test_announce(self):
L237: def test_find_config_files_disable(self, temp_home):
L250: def test_script_args_list_coercion(self):
L260: def test_find_config_files_permission_error(self, fake_home):
L271: class TestMetadata(support.TempdirManager):
L272: def format_metadata(self, dist):
L277: def test_simple_metadata(self):
L286: def test_provides(self):
L300: def test_provides_illegal(self):
L306: def test_requires(self):
L322: def test_requires_illegal(self):
L328: def test_requires_to_list(self):
L333: def test_obsoletes(self):
L349: def test_obsoletes_illegal(self):
L355: def test_obsoletes_to_list(self):
```

```

L360: def test_classifier(self):
L371: def test_classifier_invalid_type(self, caplog):
L384: def test_keywords(self):
L393: def test_keywords_invalid_type(self, caplog):
L406: def test_platforms(self):
L415: def test_platforms_invalid_types(self, caplog):
L428: def test_download_url(self):
L438: def test_long_description(self):
L453: def test_custom_pydistutils(self, temp_home):
L462: def test_extra_pydistutils(self, monkeypatch, tmp_path):
L468: def test_fix_help_options(self):
L474: def test_show_help(self, request, capsys):
L487: def test_read_metadata(self):
L516: def test_round_trip_through_email_generator(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_archive_util.py**

```

L28: def can_fs_encode(filename):
L41: def all_equal(values):
L45: def same_drive(*paths):
L49: class ArchiveUtilTestCase(support.TempdirManager):
L51: def test_make_tarball(self, name='archive'):
L59: def test_make_tarball_gzip(self):
L63: def test_make_tarball_bzip2(self):
L68: def test_make_tarball_xz(self):
L74: def test_make_tarball_latin1(self):
L81: def test_make_tarball_extended(self):
L88: def _make_tarball(self, tmpdir, target_name, suffix, **kwargs):
L104: def _tarinfo(self, path):
L123: def _create_files(self):
L137: def test_tarfile_vs_tar(self):
L181: def test_make_zipfile(self):
L195: def test_make_zipfile_no_zlib(self):
L202: def fake_zipfile(*a, **kw):
L221: def test_check_archive_formats(self):
L228: def test_make_archive(self):
L234: def test_make_archive_cwd(self):
L237: def _breaks(*args, **kw):
L250: def test_make_archive_tar(self):
L259: def test_make_archive_gztar(self):
L267: def test_make_archive_bztar(self):
L276: def test_make_archive_xztar(self):
L285: def test_make_archive_owner_group(self):
L318: def test_tarfile_root_owner(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_build_scripts.py

```

L13: class TestBuildScripts(support.TempdirManager):
L14: def test_default_settings(self):
L24: def test_build(self):
L39: def get_build_scripts_cmd(self, target, scripts):
L50: def write_sample_scripts(dir):
L71: def test_version_int(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_filelist.py

```

L31: def make_local_path(s):
L36: class TestFileList:
L37: def assertNoWarnings(self, caplog):
L42: def assertWarnings(self, caplog):
L47: def test_glob_to_re(self):
L66: def test_process_template_line(self):
L111: def test_debug_print(self, capsys, monkeypatch):
L120: def test_set_allfiles(self):
L126: def test_remove_duplicates(self):
L134: def test_translate_pattern(self):
L150: def test_exclude_pattern(self):
L166: def test_include_pattern(self):
L184: def test_process_template(self, caplog):
L299: class TestFindAll:
L301: def test_missing_symlink(self, temp_cwd):
L305: def test_basic_discovery(self, temp_cwd):
L317: def test_non_local_discovery(self, tmp_path):
L327: def test_symlink_loop(self, tmp_path):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_install_scripts.py

```

L11: class TestInstallScripts(support.TempdirManager):
L12: def test_default_settings(self):
L33: def test_installation(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_install_headers.py

```
L11: class TestInstallHeaders(
L14: def test_simple_run(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_install_lib.py

```
L16: class TestInstallLib(
L19: def test_finalize_options(self):
L40: def test_byte_compile(self):
L56: def test_get_outputs(self):
L76: def test_get_inputs(self):
L96: def test_dont_write_bytecode(self, caplog):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_bdist.py

```
L7: class TestBuild(support.TempdirManager):
L8: def test_formats(self):
L30: def test_skip_build(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_sdist.py

```
L48: def project_dir(request, distutils_managed_tempdir):
L65: def clean_lines(filepath):
L70: class TestSDist(support.TempdirManager):
L71: def get_cmd(self, metadata=None):
L90: def test_prune_file_list(self):
L141: def test_make_distribution(self):
L170: def test_add_defaults(self):
L255: def warnings(messages, prefix='warning: '):
L259: def test_metadata_check_option(self, caplog):
L277: def test_show_formats(self, capsys):
L289: def test_finalize_options(self):
L314: def _check_template(self, content, caplog):
L323: def test_invalid_template_unknown_command(self, caplog):
```



```

L326: def test_invalid_template_wrong_arguments(self, caplog):
L331: def test_invalid_template_wrong_path(self, caplog):
L337: def test_get_file_list(self):
L367: def test_manifest_marker(self):
L379: def test_manifest_comments(self):
L398: def test_manual_manifest(self):
L430: def test_make_distribution_owner_group(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_modified.py**

```

L12: class TestDepUtil(support.TempdirManager):
L13: def test_newer(self):
L32: def _setup_1234(self):
L47: def test_newer_pairwise(self):
L52: def test_newer_pairwise_mismatch(self):
L61: def test_newer_pairwise_empty(self):
L64: def test_newer_pairwise_fresh(self):
L69: def test_newer_group(self):
L97: def groups_target(tmp_path):
L115: def test_newer_pairwise_group(groups_target):
L122: def test_newer_group_no_sources_no_target(tmp_path):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_clean.py**

```

L8: class TestClean(support.TempdirManager):
L9: def test_simple_run(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_check.py**

```

L21: class TestCheck(support.TempdirManager):
L22: def _run(self, metadata=None, cwd=None, **options):
L39: def test_check_metadata(self):
L81: def test_check_author_maintainer(self):
L105: def test_check_document(self):
L120: def test_check_restructuredtext(self):
L151: def test_check_restructuredtext_with_syntax_highlight(self):
L162: def foo():

```

```
L172: def foo():
L192: def test_check_all(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
__init__.py

```
L14: def missing_compiler_executable(cmd_names: Sequence[str] = []): # pragma: no cover
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_install_data.py

```
L12: class TestInstallData(
L15: def test_simple_run(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_extension.py

```
L12: class TestExtension:
L13: def test_read_setup_file(self):
L63: def test_extension_init(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_bdist_dumb.py

```
L26: class TestBuildDumb(
L30: def test_simple_built(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_util.py

```
L32: def environment(monkeypatch):
L44: class TestUtil:
L45: def test_get_host_platform(self):
L55: def test_get_platform(self):
```

```

L66: def test_convert_path(self):
L72: def test_change_root(self):
L76: def _isabs(path):
L81: def _join(*path):
L93: def _isabs(path):
L98: def _splitdrive(path):
L105: def _join(*path):
L122: def test_check_envron(self):
L131: def test_check_envron_getpwuid(self):
L159: def test_split_quoted(self):
L167: def test_strtobool(self):
L192: def test_rfc822_escape(self, given, wanted):
L228: def test_dont_write_bytecode(self):
L239: def test_grok_environment_error(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_build.py**

```

L10: class TestBuild(support.TempdirManager):
L11: def test_finalize_options(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_text_file.py**

```

L17: class TestTextFile(support.TempdirManager):
L18: def test_class(self):
L54: def test_input(count, description, file, expected_result):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_dir_util.py**

```

L24: def stuff(request, monkeypatch, distutils_managed_tempdir):
L32: class TestDirUtil(support.TempdirManager):
L33: def test_mkpath_remove_tree_verbosity(self, caplog):
L48: def test_mkpath_with_custom_mode(self):
L57: def test_create_tree_verbosity(self, caplog):
L68: def test_copy_tree_verbosity(self, caplog):
L87: def test_copy_tree_skips_nfs_temp_files(self):
L98: def test_ensure_relative(self):
L106: def test_copy_tree_exception_in_listdir(self):

```

```

L117: def test_mkpath_exception_uncached(self, monkeypatch, tmp_path):
L124: class FailPath(pathlib.Path):
L125: def mkdir(self, *args, **kwargs):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
support.py**

```

L17: class TempdirManager:
L22: def mkdtemp(self):
L31: def write_file(self, path, content='xxx'):
L38: def create_dist(self, pkg_name='foo', **kw):
L56: class DummyCommand:
L59: def __init__(self, **kwargs):
L62: def ensure_finalized(self):
L66: def copy_xmodule_c(directory):
L71: def test_compile(self):
L81: def _get_xmodule_path():
L86: def fixup_build_ext(cmd):
L123: def combine_markers(cls):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_spawn.py**

```

L18: class TestSpawn(support.TempdirManager):
L20: def test_spawn(self):
L47: def test_find_executable(self, tmp_path):
L130: def _make_executable(tmp_path, ext):
L138: def test_spawn_missing_exe(self):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_build_clib.py**

```

L11: class TestBuildCLib(support.TempdirManager):
L12: def test_check_library_dist(self):
L45: def test_get_source_files(self):
L71: def test_build_libraries(self):
L75: class FakeCompiler:
L76: def compile(*args, **kw):
L94: def test_finalize_options(self):
L111: def test_run(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_sysconfig.py

```

L20: def _gen_makefile(root, contents):
L26: class TestSysconfig:
L27: def test_get_config_h_filename(self):
L33: def test_get_makefile_filename(self):
L37: def test_get_python_lib(self, tmp_path):
L40: def test_get_config_vars(self):
L48: def test_srcdir_simple(self):
L60: def test_srcdir_python_build(self):
L71: def test_srcdir_independent_of_cwd(self):
L81: def customize_compiler(self):
L83: class compiler:
L87: def __init__(self):
L90: def set_executables(self, **kw):
L115: def test_customize_compiler(self):
L174: def test_parse_makefile_base(self, tmp_path):
L186: def test_parse_makefile_literal_dollar(self, tmp_path):
L198: def test_sysconfig_module(self):
L222: def test_sysconfig_compiler_vars(self):
L233: def test_SO_deprecation(self):
L237: def test_customize_compiler_before_get_config_vars(self, tmp_path):
L263: def test_parse_config_h(self):
L275: def test_win_ext_suffix(self):
L285: def test_win_build_venv_from_source_tree(self, tmp_path):
L302: def test_get_python_inc_missing_config_dir(self, monkeypatch):
L312: def override(name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install.py

```

L99: def _load_sysconfig_schemes():
L107: def _load_schemes():
L123: def _get_implementation():
L130: def _select_scheme(ob, name):
L135: def _remove_set(ob, attrs):
L142: def _resolve_scheme(name):
L151: def _load_scheme(name):
L155: def _inject_headers(name, scheme):
L169: def _scheme_attrs(scheme):
L174: class install(Command):
L247: def initialize_options(self) -> None:
L324: def finalize_options(self) -> None: # noqa: C901

```

```

L507: def dump_dirs(self, msg) -> None:
L527: def finalize_unix(self) -> None:
L576: def finalize_other(self) -> None:
L598: def select_scheme(self, name) -> None:
L601: def _expand_attrs(self, attrs):
L610: def expand_basedirs(self) -> None:
L615: def expand_dirs(self) -> None:
L626: def convert_paths(self, *names) -> None:
L632: def handle_extra_path(self) -> None:
L667: def change_roots(self, *names) -> None:
L673: def create_home_path(self) -> None:
L685: def run(self):
L735: def create_path_file(self):
L747: def get_outputs(self):
L763: def get_inputs(self):
L775: def has_lib(self):
L782: def has_headers(self):
L787: def has_scripts(self):
L792: def has_data(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_egg_info.py

```

L18: class install_egg_info(Command):
L26: def initialize_options(self):
L30: def basename(self):
L39: def finalize_options(self):
L44: def run(self):
L58: def get_outputs(self):
L67: def safe_name(name):
L75: def safe_version(version):
L85: def to_filename(name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/bdist.py

```

L21: def deprecated(message):
L25: def show_formats():
L37: class ListCompat(dict[str, tuple[str, str]]):
L40: def append(self, item: object) -> None:
L48: class bdist(Command):
L105: def initialize_options(self):
L114: def finalize_options(self) -> None:
L142: def run(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build.py

```

L19: class build(Command):
L51: def initialize_options(self):
L67: def finalize_options(self) -> None: # noqa: C901
L128: def run(self) -> None:
L139: def has_pure_modules(self):
L142: def has_c_libraries(self):
L145: def has_ext_modules(self):
L148: def has_scripts(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/bdist_dumb.py

```

L18: class bdist_dumb(Command):
L62: def initialize_options(self):
L73: def finalize_options(self):
L94: def run(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_clib.py

```

L28: class build_clib(Command):
L45: def initialize_options(self):
L60: def finalize_options(self) -> None:
L87: def run(self) -> None:
L106: def check_library_list(self, libraries) -> None:
L142: def get_library_names(self):
L153: def get_source_files(self):
L168: def build_libraries(self, libraries) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_scripts.py

```

L16: class install_scripts(Command):
L28: def initialize_options(self):

```

```

L34: def finalize_options(self) -> None:
L43: def run(self) -> None:
L55: def get_inputs(self):
L58: def get_outputs(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_scripts.py

```

L25: class build_scripts(Command):
L36: def initialize_options(self):
L42: def finalize_options(self):
L51: def get_source_files(self):
L54: def run(self):
L59: def copy_scripts(self):
L78: def _copy_script(self, script, outfiles, updated_files):
L115: def _change_modes(self, outfiles):
L122: def _change_mode(self, file):
L130: def _validate_shebang(shebang, encoding):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_lib.py

```

L20: class install_lib(Command):
L56: def initialize_options(self):
L65: def finalize_options(self) -> None:
L92: def run(self) -> None:
L108: def build(self) -> None:
L116: def install(self) -> list[str] | Any:
L126: def byte_compile(self, files) -> None:
L157: def _mutate_outputs(self, has_any, build_cmd, cmd_option, output_dir):
L170: def _bytecode_filenames(self, py_filenames):
L195: def get_outputs(self):
L220: def get_inputs(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_py.py

```

L17: class build_py(Command):
L36: def initialize_options(self):
L46: def finalize_options(self) -> None:

```



```

L71: def run(self) -> None:
L101: def get_data_files(self):
L123: def find_data_files(self, package, src_dir):
L138: def build_package_data(self) -> None:
L148: def get_package_dir(self, package):
L187: def check_package(self, package, package_dir):
L213: def check_module(self, module, module_file):
L220: def find_package_modules(self, package, package_dir):
L235: def find_modules(self):
L287: def find_all_modules(self):
L303: def get_source_files(self):
L306: def get_module_outfile(self, build_dir, package, module):
L310: def get_outputs(self, include_bytecode: bool = True) -> list[str]:
L337: def build_module(self, module, module_file, package):
L353: def build_modules(self) -> None:
L362: def build_packages(self) -> None:
L382: def byte_compile(self, files) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_headers.py

```

L12: class install_headers(Command):
L22: def initialize_options(self):
L27: def finalize_options(self):
L32: def run(self):
L42: def get_inputs(self):
L45: def get_outputs(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/_framework_compat.py

```

L13: def enabled():
L41: def vars():
L48: def scheme(name):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/clean.py

```

L15: class clean(Command):
L36: def initialize_options(self):

```

```
L44: def finalize_options(self):
L54: def run(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/sdist.py

```
L23: def show_formats():
L37: class sdist(Command):
L40: def checking_metadata(self) -> bool:
L126: def initialize_options(self):
L149: def finalize_options(self) -> None:
L164: def run(self) -> None:
L186: def get_file_list(self) -> None:
L227: def add_defaults(self) -> None:
L250: def _cs_path_exists(fspath):
L266: def _add_defaults_standards(self):
L288: def _add_defaults_optional(self):
L294: def _add_defaults_python(self):
L310: def _add_defaults_data_files(self):
L327: def _add_defaults_ext(self):
L332: def _add_defaults_c_libs(self):
L337: def _add_defaults_scripts(self):
L342: def read_template(self) -> None:
L377: def prune_file_list(self) -> None:
L400: def write_manifest(self) -> None:
L419: def _manifest_is_not_generated(self):
L428: def read_manifest(self) -> None:
L440: def make_release_tree(self, base_dir, files) -> None:
L482: def make_distribution(self) -> None:
L513: def get_archive_files(self):
L520: def is_comment(line: str) -> bool:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/config.py

```
L28: class config(Command):
L50: def initialize_options(self):
L65: def finalize_options(self):
L81: def run(self):
L88: def _check_compiler(self):
L102: def _gen_temp_sourcefile(self, body, headers, lang):
L114: def _preprocess(self, body, headers, include_dirs, lang):
L121: def _compile(self, body, headers, include_dirs, lang):
L130: def _link(self, body, headers, include_dirs, libraries, library_dirs, lang):
```

```

L147: def _clean(self, *filenames):
L160: def try_cpp(self, body=None, headers=None, include_dirs=None, lang="c"):
L177: def search_cpp(self, pattern, body=None, headers=None, include_dirs=None, lang="c"):
L197: def try_compile(self, body, headers=None, include_dirs=None, lang="c"):
L212: def try_link(
L236: def try_run(
L267: def check_func(
L304: def check_lib(
L329: def check_header(self, header, include_dirs=None, library_dirs=None, lang="c"):
L339: def dump_file(filename, head=None):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_ext.py

```

L38: class build_ext(Command):
L112: def initialize_options(self):
L137: def _python_lib_dir(sysconfig):
L161: def finalize_options(self) -> None: # noqa: C901
L300: def run(self) -> None: # noqa: C901
L369: def check_extensions_list(self, extensions) -> None: # noqa: C901
L457: def get_source_files(self):
L466: def get_outputs(self):
L477: def build_extensions(self) -> None:
L485: def _build_extensions_parallel(self):
L506: def _build_extensions_serial(self):
L512: def _filter_build_errors(self, ext):
L520: def build_extension(self, ext) -> None:
L601: def swig_sources(self, sources, extension):
L657: def find_swig(self):
L681: def get_ext_fullpath(self, ext_name: str) -> str:
L708: def get_ext_fullname(self, ext_name: str) -> str:
L717: def get_ext_filename(self, ext_name: str) -> str:
L728: def get_export_symbols(self, ext: Extension) -> list[str]:
L749: def _get_module_name_for_symbol(self, ext):
L758: def get_libraries(self, ext: Extension) -> list[str]: # noqa: C901

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_data.py

```

L19: class install_data(Command):
L34: def initialize_options(self):
L42: def finalize_options(self) -> None:
L50: def run(self) -> None:
L56: def _copy(self, f: tuple[str | os.PathLike, Iterable[str | os.PathLike]]):

```

```

L79: def _(self, f: str | os.PathLike):
L90: def get_inputs(self):
L93: def get_outputs(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/bdist_rpm.py

```

L24: class bdist_rpm(Command):
L154: def initialize_options(self):
L199: def finalize_options(self) -> None:
L232: def finalize_package_data(self) -> None:
L278: def run(self) -> None: # noqa: C901
L405: def _dist_path(self, path):
L408: def _make_spec_file(self): # noqa: C901
L579: def _format_changelog(self, changelog):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/check.py

```

L18: class SilentReporter(docutils.utils.Reporter):
L19: def __init__(
L34: def system_message(self, level, message, *children, **kwargs):
L41: class check(Command):
L57: def initialize_options(self):
L64: def finalize_options(self):
L67: def warn(self, msg):
L72: def run(self):
L91: def check_metadata(self):
L108: def check_restructuredtext(self):
L119: def _check_rst_data(self, data):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/unix.py

```

L55: def _split_env(cmd):
L73: def _split_aix(cmd):
L87: def _linker_params(linker_cmd, compiler_cmd):
L115: class Compiler(base.Compiler):
L161: def _fix_lib_args(self, libraries, library_dirs, runtime_library_dirs):
L175: def preprocess(

```

```

L212: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):
L225: def create_static_lib(
L249: def link(
L317: def library_dir_option(self, dir):
L320: def _is_gcc(self):
L325: def runtime_library_dir_option(self, dir: str) -> str | list[str]: # type:
ignore[override] # Fixed in pypa/distutils#339
L365: def library_option(self, lib):
L369: def _library_root(dir):
L403: def find_library_file(self, dirs, lib, debug=False):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/base.py

```

L51: class Compiler:
L133: def __init__(self, verbose: bool = False, force: bool = False) -> None:
L168: def set_executables(self, **kwargs: str) -> None:
L201: def set_executable(self, key, value):
L207: def _find_macro(self, name):
L215: def _check_macro_definitions(self, definitions):
L220: def _check_macro_definition(self, defn):
L233: def _is_valid_macro(name, value=None):
L244: def define_macro(self, name: str, value: str | None = None) -> None:
L259: def undefine_macro(self, name: str) -> None:
L277: def add_include_dir(self, dir: str) -> None:
L285: def set_include_dirs(self, dirs: list[str]) -> None:
L295: def add_library(self, libname: str) -> None:
L311: def set_libraries(self, libnames: list[str]) -> None:
L319: def add_library_dir(self, dir: str) -> None:
L327: def set_library_dirs(self, dirs: list[str]) -> None:
L334: def add_runtime_library_dir(self, dir: str) -> None:
L340: def set_runtime_library_dirs(self, dirs: list[str]) -> None:
L348: def add_link_object(self, object: str) -> None:
L356: def set_link_objects(self, objects: list[str]) -> None:
L369: def _setup_compile(
L400: def _get_cc_args(self, pp_opts, debug, before):
L409: def _fix_compile_args(
L448: def _prep_compile(self, sources, output_dir, depends=None):
L464: def _fix_object_args(
L483: def _fix_lib_args(
L525: def _need_link(self, objects, output_file):
L534: def detect_language(self, sources: str | list[str]) -> str | None:
L557: def preprocess(
L577: def compile(
L653: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):
L659: def create_static_lib(
L696: def link(

```

```

L759: def link_shared_lib(
L790: def link_shared_object(
L821: def link_executable(
L855: def library_dir_option(self, dir: str) -> str:
L861: def runtime_library_dir_option(self, dir: str) -> str:
L867: def library_option(self, lib: str) -> str:
L873: def has_function( # noqa: C901
L963: def find_library_file(
L1008: def object_filenames(
L1022: def out_extensions(self):
L1025: def _make_out_path(self, output_dir, strip_dir, src_name):
L1031: def _make_out_path_exts(cls, output_dir, strip_dir, src_name, extensions):
L1051: def _make_relative(base: pathlib.Path):
L1055: def shared_object_filename(
L1062: def shared_object_filename(
L1068: def shared_object_filename(
L1080: def executable_filename(
L1087: def executable_filename(
L1093: def executable_filename(
L1104: def library_filename(
L1127: def announce(self, msg: object, level: int = 1) -> None:
L1130: def debug_print(self, msg: object) -> None:
L1136: def warn(self, msg: object) -> None:
L1139: def execute(
L1148: def spawn(
L1154: def move_file(
L1158: def move_file(
L1161: def move_file(
L1168: def mkpath(self, name, mode=0o777):
L1188: def get_default_compiler(osname: str | None = None, platform: str | None = None) ->
str:
L1237: def show_compilers() -> None:
L1254: def new_compiler(
L1305: def gen_preprocess_options(
L1351: def gen_lib_options(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/msvc.py

```

L43: def _find_vc2015():
L72: def _find_vc2017():
L130: def _find_vcvarsall(plat_spec):
L149: def _get_vc_env(plat_spec):
L179: def _find_exe(exe, paths=None):
L205: def _get_vcvars_spec(host_platform, platform):
L234: class Compiler(base.Compiler):
L263: def __init__(self, verbose=False, force=False) -> None:

```

```

L270: def _configure(cls, vc_env):
L278: def _parse_path(val):
L281: def initialize(self, plat_name: str | None = None) -> None:
L363: def out_extensions(self) -> dict[str, str]:
L372: def compile( # noqa: C901
L466: def create_static_lib(
L491: def link(
L560: def spawn(self, cmd):
L567: def _fallback_spawn(self, cmd, env):
L589: def library_dir_option(self, dir):
L592: def runtime_library_dir_option(self, dir):
L597: def library_option(self, lib):
L600: def find_library_file(self, dirs, lib, debug=False):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/zos.py

```

L105: class Compiler(unix.Compiler):
L110: def _get_zos_compiler_name(self):
L139: def __init__(self, verbose=False, force=False):
L144: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):
L163: def runtime_library_dir_option(self, dir):
L166: def link(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/errors.py

```

L1: class Error(Exception):
L5: class PreprocessError(Error):
L9: class CompileError(Error):
L13: class LibError(Error):
L18: class LinkError(Error):
L23: class UnknownFileType(Error):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/cygwin.py

```

L31: def get_msvcr():
L42: class Compiler(unix.Compiler):
L55: def __init__(self, verbose=False, force=False):

```

```

L92: def gcc_version(self):
L106: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):
L130: def link(
L218: def runtime_library_dir_option(self, dir):
L227: def _make_out_path(self, output_dir, strip_dir, src_name):
L233: def out_extensions(self):
L244: class MinGW32Compiler(Compiler):
L249: def __init__(self, verbose=False, force=False):
L268: def runtime_library_dir_option(self, dir):
L281: def check_config_h():
L330: def is_cygwincc(cc):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_unix.py

```

L19: def save_values(monkeypatch):
L26: def compiler_wrapper(request):
L27: class CompilerWrapper(unix.Compiler):
L28: def rpath_foo(self):
L34: class TestUnixCCompiler(support.TempdirManager):
L36: def test_runtime_libdir_option(self): # noqa: C901
L66: def make_darwin_gcv(syscfg_macosx_ver):
L67: def gcv(var):
L74: def do_darwin_test(syscfg_macosx_ver, env_macosx_ver, expected_flag):
L123: def gcv(v):
L129: def gcv(v):
L135: def gcv(v):
L146: def gcv(v):
L158: def gcv(v):
L173: def gcv(v):
L186: def gcv(v):
L201: def gcv(v):
L216: def gcv(v):
L226: def test_cc_overrides_ldshared(self):
L229: def gcv(v):
L234: def gcvs(*args, _orig=sysconfig.get_config_vars):
L248: def test_cxx_commands_used_are_correct(self):
L249: def gcv(v):
L260: def gcvs(*args, _orig=sysconfig.get_config_vars):
L312: def test_cc_overrides_ldshared_for_cxx_correctly(self):
L320: def gcv(v):
L331: def gcvs(*args, _orig=sysconfig.get_config_vars):
L355: def test_explicit_ldshared(self):
L359: def gcv(v):
L364: def gcvs(*args, _orig=sysconfig.get_config_vars):
L377: def test_has_function(self):
L385: def test_find_library_file(self, monkeypatch):

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_base.py

```
L13: def c_file(tmp_path):
L34: def test_set_include_dirs(c_file):
L49: def test_has_function_prototype():
L72: def test_include_dirs_after_multiple_compile_calls(c_file):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_cygwin.py

```
L14: def stuff(request, monkeypatch, distutils_managed_tempdir):
L21: class TestCygwinCCompiler(support.TempdirManager):
L22: def _get_config_h_filename(self):
L27: def test_find_library_file(self):
L38: def test_runtime_library_dir_option(self):
L44: def test_check_config_h(self):
L68: def test_get_msvcr(self):
L72: def test_dll_libraries_not_none(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_msvc.py

```
L17: class Testmsvccompiler(support.TempdirManager):
L18: def test_no_compiler(self, monkeypatch):
L22: def _find_vcvarsall(plat_spec):
L44: def test_cross_platform_compilation_paths(self, monkeypatch, plat_name, expected):
L50: def _get_vcvars_spec(host_platform, platform):
L57: def test_get_vc_env_unicode(self):
L75: def test_get_vc(self, ver):
L87: class CheckThread(threading.Thread):
L90: def run(self):
L96: def __bool__(self):
L100: class TestSpawn:
L101: def test_concurrent_safe(self):
L119: def test_concurrent_safe_fallback(self):
L129: def CCompiler_spawn(self, cmd):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_mingw.py

```
L10: class TestMinGW32Compiler:
L12: def test_compiler_type(self):
L17: def test_set_executables(self, monkeypatch):
L30: def test_runtime_library_dir_option(self):
L36: def test_cygwincc_error(self, monkeypatch):
L43: def test_customize_compiler_with_msvc_python(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compat/__init__.py

```
L9: def consolidate_linker_args(args: _IterableT) -> _IterableT | str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compat/py39.py

```
L7: def add_ext_suffix_39(vars):
L28: class UnequalIterablesError(ValueError):
L29: def __init__(self, details=None):
L38: def _zip_equal_generator(iterables):
L48: def _zip_equal(*iterables):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/install.py

```
L21: def __getattr__(name: str): # pragma: no cover
L32: class install(orig.install):
L57: def initialize_options(self):
L73: def finalize_options(self) -> None:
L83: def handle_extra_path(self):
L95: def _called_from_setup(run_frame):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/install_egg_info.py

```

L11: class install_egg_info(namespaces.Installer, Command):
L20: def initialize_options(self):
L23: def finalize_options(self) -> None:
L31: def run(self) -> None:
L41: def get_outputs(self):
L44: def copytree(self) -> None:
L46: def skimmer(src, dst):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build
.py**

```

L12: class build(_build):
L19: class SubCommand(Protocol):
L83: def finalize_options(self):
L88: def initialize_options(self) -> None:
L92: def finalize_options(self) -> None:
L96: def run(self) -> None:
L100: def get_source_files(self) -> list[str]:
L112: def get_outputs(self) -> list[str]:
L126: def get_output_mapping(self) -> dict[str, str]:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/egg_
info.py**

```

L40: def translate_pattern(glob): # noqa: C901 # is too complex (14) # FIXME
L123: class InfoCommon:
L128: def name(self):
L131: def tagged_version(self):
L135: def _maybe_tag(self, version):
L146: def _already_tagged(self, version: str) -> bool:
L151: def _safe_tags(self) -> str:
L159: def tags(self) -> str:
L170: class egg_info(InfoCommon, Command):
L190: def initialize_options(self):
L201: def tag_svn_revision(self) -> int | None:
L205: def tag_svn_revision(self, value) -> None:
L210: def save_version_info(self, filename) -> None:
L221: def finalize_options(self) -> None:
L253: def _get_egg_basename(self, py_version=PY_MAJOR, platform=None):
L257: def write_or_delete_file(self, what, filename, data, force: bool = False) -> None:
L275: def write_file(self, what, filename, data) -> None:
L287: def delete_file(self, filename) -> None:
L292: def run(self) -> None:
L314: def find_sources(self) -> None:

```

```

L324: class FileList(_FileList):
L327: def __init__(
L333: def process_template_line(self, line) -> None:
L403: def _remove_files(self, predicate):
L416: def include(self, pattern):
L422: def exclude(self, pattern):
L427: def recursive_include(self, dir, pattern):
L436: def recursive_exclude(self, dir, pattern):
L443: def graft(self, dir):
L453: def prune(self, dir):
L458: def global_include(self, pattern):
L470: def global_exclude(self, pattern):
L477: def append(self, item) -> None:
L484: def extend(self, paths) -> None:
L487: def _repair(self):
L497: def _safe_path(self, path):
L525: class manifest_maker(sdist):
L528: def initialize_options(self) -> None:
L535: def finalize_options(self) -> None:
L538: def run(self) -> None:
L552: def _manifest_normalize(self, path):
L556: def write_manifest(self) -> None:
L568: def warn(self, msg) -> None:
L573: def _should_suppress_warning(msg):
L579: def add_defaults(self) -> None:
L597: def add_license_files(self) -> None:
L603: def _add_referenced_files(self):
L611: def _safe_data_files(self, build_py):
L636: def write_file(filename, contents) -> None:
L649: def write_pkg_info(cmd, basename, filename) -> None:
L665: def warn_depends_obsolete(cmd, basename, filename) -> None:
L680: def write_toplevel_names(cmd, basename, filename) -> None:
L687: def overwrite_arg(cmd, basename, filename) -> None:
L691: def write_arg(cmd, basename, filename, force: bool = False) -> None:
L699: def write_entries(cmd, basename, filename) -> None:
L705: def _egg_basename(egg_name, egg_version, py_version=None, platform=None):
L715: class EggInfoDeprecationWarning(SetuptoolsDeprecationWarning):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build
_clib.py**

```

L9: class build_clib(orig.build_clib):
L27: def build_libraries(self, libraries) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/insta

ll_scripts.py

```
L13: class install_scripts(orig.install_scripts):
L18: def initialize_options(self) -> None:
L22: def run(self) -> None:
L33: def _install_ep_scripts(self):
L53: def write_script(self, script_name, contents, mode: str = "t", *ignored) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/saveopts.py

```
L4: class saveopts(option_base):
L9: def run(self) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/bdist_egg.py

```
L33: def _get_purelib():
L37: def strip_module(filename):
L44: def sorted_walk(
L56: def write_stub(resource, pyfile) -> None:
L59: def __bootstrap__():
L74: class bdist_egg(Command):
L98: def initialize_options(self):
L107: def finalize_options(self) -> None:
L129: def do_install_data(self) -> None:
L154: def get_outputs(self):
L157: def call_command(self, cmdname, **kw):
L166: def run(self) -> None: # noqa: C901 # is too complex (14) # FIXME
L246: def zap_pyfiles(self) -> None:
L271: def zip_safe(self):
L278: def gen_header(self) -> Literal["w"]:
L281: def copy_metadata_to(self, target_dir) -> None:
L293: def get_ext_outputs(self):
L326: def walk_egg(egg_dir: StrPath) -> Iterator[tuple[str, list[str], list[str]]]:
L336: def analyze_egg(egg_dir, stubs):
L354: def write_safety_flag(egg_dir, safe) -> None:
L372: def scan_module(egg_dir, base, name, stubs):
L412: def iter_symbols(code: CodeType) -> Iterator[str]:
L422: def can_scan() -> bool:
L440: def make_zipfile(
L458: def visit(z, dirname, names):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/alias.py

```

L6: def shquote(arg):
L16: class alias(option_base):
L28: def initialize_options(self):
L33: def finalize_options(self) -> None:
L40: def run(self) -> None:
L67: def format_alias(name, aliases):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/install_lib.py

```

L13: class install_lib(orig.install_lib):
L18: def run(self) -> None:
L25: def get_exclusions(self):
L39: def _exclude_pkg_path(self, pkg, exclusion_path):
L48: def _all_packages(pkg_name):
L57: def _get_SVEM_NSPPs(self):
L74: def _gen_exclusion_paths():
L94: def copy_tree(
L120: def pf(src: str, dst: str):
L132: def get_outputs(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build_py.py

```

L28: def make_writable(target) -> None:
L32: class build_py(orig.build_py):
L46: def finalize_options(self) -> None:
L53: def copy_file( # type: ignore[override] # No overload, no bytes support
L70: def run(self) -> None:
L87: def __getattr__(self, attr: str) -> Any:
L94: def _get_data_files(self):
L99: def get_data_files_without_manifest(self) -> list[tuple[str, str, str, list[str]]]:
L109: def _get_pkg_data_files(self, package: str) -> tuple[str, str, str, list[str]]:
L123: def find_data_files(self, package, src_dir):
L141: def get_outputs(self, include_bytecode: bool = True) -> list[str]: # type:
ignore[override] # Using a real boolean instead of 0|1
L147: def get_output_mapping(self) -> dict[str, str]:
L155: def _get_module_mapping(self) -> Iterator[tuple[str, str]]:

```

```

L162: def _get_package_data_output_mapping(self) -> Iterator[tuple[str, str]]:
L170: def build_package_data(self) -> None:
L177: def analyze_manifest(self) -> None:
L218: def _filter_build_files(
L239: def get_data_files(self) -> None:
L242: def check_package(self, package, package_dir):
L272: def initialize_options(self):
L278: def get_package_dir(self, package: str) -> str:
L284: def exclude_data_files(self, package, src_dir, files):
L301: def _get_platform_patterns(spec, package, src_dir, extra_patterns=()):
L320: def assert_relative(path):
L341: class _IncludePackageDataAbuse:
L344: class _Warning(SetuptoolsDeprecationWarning):
L387: def __init__(self) -> None:
L390: def is_module(self, file):
L393: def importable_subpackage(self, parent, file):
L400: def warn(self, importable):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/editable_wheel.py

```

L53: class _EditableMode(Enum):
L66: def convert(cls, mode: str | None) -> _EditableMode:
L104: class editable_wheel(Command):
L118: def initialize_options(self):
L124: def finalize_options(self) -> None:
L130: def run(self) -> None:
L151: def _ensure_dist_info(self):
L162: def _install_namespaces(self, installation_dir, pth_prefix):
L172: def _find_egg_info_dir(self) -> str | None:
L177: def _configure_build(
L240: def _set_editable_mode(self):
L251: def _collect_build_outputs(self) -> tuple[list[str], dict[str, str]]:
L265: def _run_build_commands(
L280: def _run_build_subcommands(self) -> None:
L302: def _safely_run(self, cmd_name: str):
L330: def _create_wheel_file(self, bdist_wheel):
L358: def _run_install(self, category: str):
L364: def _select_strategy(
L391: class EditableStrategy(Protocol):
L392: def __call__(
L395: def __enter__(self) -> Self: ...
L396: def __exit__(
L404: class _StaticPth:
L405: def __init__(self, dist: Distribution, name: str, path_entries: list[Path]) -> None:
L410: def __call__(
L417: def __enter__(self) -> Self:

```

```

L425: def __exit__(
L434: class _LinkTree(_StaticPth):
L445: def __init__(
L457: def __call__(
L463: def _normalize_output(self, file: str) -> str | None:
L470: def _create_file(self, relative_output: str, src_file: str, link=None):
L476: def _create_links(self, outputs, output_mapping: Mapping[str, str]):
L491: def __enter__(self) -> Self:
L496: def __exit__(
L512: class _TopLevelFinder:
L513: def __init__(self, dist: Distribution, name: str) -> None:
L517: def template_vars(self) -> tuple[str, str, dict[str, str], dict[str, list[str]]]:
L544: def get_implementation(self) -> Iterator[tuple[str, bytes]]:
L553: def __call__(
L559: def __enter__(self) -> Self:
L564: def __exit__(
L577: def _encode_pth(content: str) -> bytes:
L598: def _can_symlink_files(base_dir: Path) -> bool:
L618: def _simple_layout(
L659: def _parent_path(pkg, pkg_path):
L673: def _find_packages(dist: Distribution) -> Iterator[str]:
L689: def _find_top_level_modules(dist: Distribution) -> Iterator[str]:
L698: def _find_package_roots(
L711: def _absolute_root(path: StrPath) -> str:
L722: def _find_virtual_namespaces(pkg_roots: dict[str, str]) -> Iterator[str]:
L746: def _find_namespaces(
L755: def _remove_nested(pkg_roots: dict[str, str]) -> dict[str, str]:
L768: def _is_nested(pkg: str, pkg_path: str, parent: str, parent_path: str) -> bool:
L790: def _empty_dir(dir_: _P) -> _P:
L797: class _NamespaceInstaller(namespaces.Installer):
L798: def __init__(self, distribution, installation_dir, editable_name, src_root) -> None:
L805: def _get_nspkg_file(self):
L809: def _get_root(self):
L828: class _EditableFinder: # MetaPathFinder
L830: def find_spec(cls, fullname: str, path=None, target=None) -> ModuleSpec | None: #
type: ignore
L848: def _find_spec(cls, fullname: str, candidate_path: Path) -> ModuleSpec | None:
L857: class _EditableNamespaceFinder: # PathEntryFinder
L859: def _path_hook(cls, path) -> type[_EditableNamespaceFinder]:
L865: def _paths(cls, fullname: str) -> list[str]:
L876: def find_spec(cls, fullname: str, target=None) -> ModuleSpec | None: # type: ignore
L884: def find_module(cls, _fullname) -> None:
L888: def install():
L903: def _finder_template(
L913: class LinksNotSupported(errors.FileError):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/dist_

info.py

```

L20: class dist_info(Command):
L44: def initialize_options(self):
L52: def finalize_options(self) -> None:
L79: def _maybe_bkp_dir(self, dir_path: str, requires_bkp: bool):
L92: def run(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/sdist
.py

```

L20: def walk_revctrl(dirname='') -> Iterator:
L26: class sdist(orig.sdist):
L59: def run(self) -> None:
L78: def initialize_options(self) -> None:
L81: def make_distribution(self) -> None:
L90: def _remove_os_link():
L95: class NoValue:
L109: def add_defaults(self) -> None:
L113: def _add_defaults_optional(self):
L118: def _add_defaults_python(self):
L125: def _add_defaults_build_sub_commands(self):
L133: def _safe_data_files(self, build_py):
L146: def _add_data_files(self, data_files):
L156: def _add_defaults_data_files(self):
L162: def prune_file_list(self) -> None:
L168: def check_readme(self) -> None:
L177: def make_release_tree(self, base_dir, files) -> None:
L190: def _manifest_is_not_generated(self):
L199: def read_manifest(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/seto
pt.py

```

L15: def config_file(kind="local"):
L30: def edit_config(filename, settings) -> None:
L71: class option_base(Command):
L85: def initialize_options(self):
L90: def finalize_options(self) -> None:
L107: class setopt(option_base):
L121: def initialize_options(self):
L128: def finalize_options(self) -> None:
L135: def run(self) -> None:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/_req
uiresxt.py**

```

L29: def _prepare(
L39: def _convert_extras_requirements(
L57: def _move_install_requirements_markers(
L89: def _suffix_for(req):
L94: def _clean_req(req):
L101: def _no_marker(req):
L105: def _write_requirements(stream, reqs):
L108: def append_cr(line):
L115: def write_requirements(cmd, basename, filename):
L128: def write_setup_requirements(cmd, basename, filename):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build
_ext.py**

```

L43: def _customize_compiler_for_shlib(compiler):
L79: def get_abi3_suffix():
L89: class build_ext(_build_ext):
L94: def run(self) -> None:
L102: def _get_inplace_equivalent(self, build_py, ext: Extension) -> tuple[str, str]:
L112: def copy_extensions_to_source(self) -> None:
L129: def _get_equivalent_stub(self, ext: Extension, output_file: str) -> str:
L134: def _get_output_mapping(self) -> Iterator[tuple[str, str]]:
L159: def get_ext_filename(self, fullname: str) -> str:
L186: def initialize_options(self):
L193: def finalize_options(self) -> None:
L224: def setup_shlib_compiler(self) -> None:
L251: def get_export_symbols(self, ext):
L256: def build_extension(self, ext) -> None:
L269: def links_to_dynamic(self, ext):
L278: def get_source_files(self) -> list[str]:
L281: def _get_internal_depends(self) -> Iterator[str]:
L286: def skip(orig_path: str, reason: str) -> None:
L319: def get_outputs(self) -> list[str]:
L324: def get_output_mapping(self) -> dict[str, str]:
L329: def __get_stubs_outputs(self):
L340: def __get_output_extensions(self):
L346: def write_stub(self, output_dir, ext, compile=False) -> None:
L350: def _write_stub_file(self, stub_file: str, ext: Extension, compile=False):
L358: def __bootstrap__():
L388: def _compile_and_remove_stub(self, stub_file: str):
L406: def link_shared_object(

```

```
L441: def link_shared_object(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/rotate.py

```
L13: class rotate(Command):
L25: def initialize_options(self):
L30: def finalize_options(self) -> None:
L46: def run(self) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/develop.py

```
L10: class develop(Command):
L31: def run(self) -> None:
L44: def initialize_options(self) -> None:
L47: def finalize_options(self) -> None:
L51: class DevelopDeprecationWarning(SetuptoolsDeprecationWarning):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/bdist_wheel.py

```
L34: def safe_version(version: str) -> str:
L51: def _is_32bit_interpreter() -> bool:
L55: def python_tag() -> str:
L59: def get_platform(archive_root: str | None) -> str:
L79: def get_flag(
L96: def get_abi_tag() -> str | None:
L131: def safer_version(version: str) -> str:
L135: class bdist_wheel(Command):
L208: def initialize_options(self) -> None:
L230: def finalize_options(self) -> None:
L277: def _validate_py_limited_api(self) -> None:
L293: def wheel_dist_name(self) -> str:
L303: def get_tag(self) -> tuple[str, str, str]:
L361: def run(self):
L454: def write_wheel_file(
L478: def _ensure_relative(self, path: str) -> str:
L486: def license_paths(self) -> Iterable[str]:
L530: def egg2dist(self, egginfo_path: str, distinfo_path: str) -> None:
```

```
L533: def adios(p: str) -> None:
L592: def _zip_compression(self) -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/easy_install.py

```
L10: class easy_install(Command):
L14: def __getattr__(name):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/test.py

```
L10: def __getattr__(name: str) -> type[_test]:
L23: class _test(Command):
L40: def initialize_options(self) -> None:
L43: def finalize_options(self) -> None:
L46: def run(self) -> NoReturn:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/bdist_rpm.py

```
L7: class bdist_rpm(orig.bdist_rpm):
L18: def run(self) -> None:
L34: def _make_spec_file(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/expand.py

```
L53: class StaticModule:
L56: def __init__(self, name: str, spec: ModuleSpec) -> None:
L61: def _find_assignments(self) -> Iterator[tuple[ast.AST, ast.AST]]:
L68: def __getattr__(self, attr: str) -> Any:
L80: def glob_relative(
L113: def read_files(
L133: def _filter_existing_files(filepaths: Iterable[StrPath]) -> Iterator[StrPath]:
L141: def _read_file(filepath: bytes | StrPath) -> str:
L146: def _assert_local(filepath: StrPath, root_dir: str):
```

```

L154: def read_attr(
L194: def _find_spec(module_name: str, module_path: StrPath | None) -> ModuleSpec:
L204: def _load_spec(spec: ModuleSpec, module_name: str) -> ModuleType:
L215: def _find_module(
L238: def resolve_class(
L254: def cmdclass(
L265: def find_packages(
L320: def _nest_path(parent: StrPath, path: StrPath) -> str:
L325: def version(value: Callable | Iterable[str | int] | str) -> str:
L338: def canonic_package_data(package_data: dict) -> dict:
L344: def canonic_data_files(
L361: def entry_points(
L379: class EnsurePackagesDiscovered:
L389: def __init__(self, distribution: Distribution) -> None:
L393: def __call__(self) -> None:
L399: def __enter__(self) -> Self:
L402: def __exit__(
L411: def _get_package_dir(self) -> Mapping[str, str]:
L417: def package_dir(self) -> Mapping[str, str]:
L422: class LazyMappingProxy(Mapping[_K, _V_co]):
L436: def __init__(self, obtain_mapping_value: Callable[[], Mapping[_K, _V_co]]) -> None:
L440: def _target(self) -> Mapping[_K, _V_co]:
L445: def __getitem__(self, key: _K) -> _V_co:
L448: def __len__(self) -> int:
L451: def __iter__(self) -> Iterator[_K]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/pyproject.toml.py

```

L36: def load_file(filepath: StrPath) -> dict:
L43: def validate(config: dict, filepath: StrPath) -> bool:
L64: def apply_configuration(
L76: def read_configuration(
L158: def expand_configuration(
L181: class _ConfigExpander:
L182: def __init__(
L199: def _ensure_dist(self) -> Distribution:
L205: def _process_field(self, container: dict, field: str, fn: Callable):
L210: def _canonic_package_data(self, field="package-data"):
L214: def expand(self):
L231: def _expand_packages(self):
L243: def _expand_data_files(self):
L247: def _expand_cmdclass(self, package_dir: Mapping[str, str]):
L252: def _expand_all_dynamic(self, dist: Distribution, package_dir: Mapping[str, str]):
L282: def _ensure_previously_set(self, dist: Distribution, field: str):
L292: def _expand_directive(
L307: def _obtain(self, dist: Distribution, field: str, package_dir: Mapping[str, str]):

```

```

L317: def _obtain_version(self, dist: Distribution, package_dir: Mapping[str, str]):
L326: def _obtain_readme(self, dist: Distribution) -> dict[str, str] | None:
L341: def _obtain_entry_points(
L356: def _set_scripts(field: str, group: str):
L368: def _obtain_classifiers(self, dist: Distribution):
L375: def _obtain_dependencies(self, dist: Distribution):
L382: def _obtain_optional_dependencies(self, dist: Distribution):
L402: def _parse_requirements_list(value):
L411: def _ignore_errors(ignore_option_errors: bool):
L422: class _EnsurePackagesDiscovered(_expand.EnsurePackagesDiscovered):
L423: def __init__(
L430: def __enter__(self) -> Self:
L452: def __exit__(
L467: class _ExperimentalConfiguration(SetuptoolsWarning):
L474: class _ToolsTypoInMetadata(SetuptoolsWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/setupcfg.py

```

L51: def read_configuration(
L77: def apply_configuration(dist: Distribution, filepath: StrPath) -> Distribution:
L86: def _apply(
L117: def _get_option(target_obj: Distribution | DistributionMetadata, key: str):
L129: def configuration_to_dict(
L151: def parse_configuration(
L197: def _warn_accidental_env_marker_misconfig(label: str, orig_value: str, parsed: list):
L229: class ConfigHandler(Generic[Target]):
L245: def __init__(
L263: def _section_options(
L274: def parsers(self) -> dict[str, Callable]:
L280: def __setitem__(self, option_name, value) -> None:
L307: def _parse_list(cls, value, separator=','):
L327: def _parse_dict(cls, value):
L344: def _parse_bool(cls, value):
L354: def _exclude_files_parser(cls, key):
L365: def parser(value):
L376: def _parse_file(self, value, root_dir: StrPath | None):
L403: def _parse_attr(self, value, package_dir, root_dir: StrPath):
L424: def _get_parser_compound(cls, *parse_methods):
L433: def parse(value):
L444: def _parse_section_to_dict_with_key(cls, section_options, values_parser):
L459: def _parse_section_to_dict(cls, section_options, values_parser=None):
L471: def parse_section(self, section_options) -> None:
L481: def parse(self) -> None:
L506: def _deprecated_config_handler(self, func, msg, **kw):
L514: def config_handler(*args, **kwargs):
L522: class ConfigMetadataHandler(ConfigHandler["DistributionMetadata"]):

```

```

L538: def __init__(
L552: def parsers(self) -> dict[str, Callable]:
L579: def _parse_version(self, value):
L605: class ConfigOptionsHandler(ConfigHandler["Distribution"]):
L608: def __init__(
L620: def _parse_list_semicolon(cls, value):
L623: def _parse_file_in_root(self, value):
L626: def _parse_requirements_list(self, label: str, value: str):
L636: def parsers(self) -> dict[str, Callable]:
L666: def _parse_cmdclass(self, value):
L670: def _parse_packages(self, value):
L695: def parse_section_packages__find(self, section_options):
L713: def parse_section_entry_points(self, section_options) -> None:
L721: def _parse_package_data(self, section_options):
L725: def parse_section_package_data(self, section_options) -> None:
L732: def parse_section_exclude_package_data(self, section_options) -> None:
L739: def parse_section_extras_require(self, section_options) -> None: # Core Metadata
L752: def parse_section_data_files(self, section_options) -> None:
L761: class _AmbiguousMarker(SetuptoolsDeprecationWarning):
L776: def message(cls, **kw):
L781: class _DeprecatedConfig(SetuptoolsDeprecationWarning):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_apply_pyprojecttoml.py

```

L46: def apply(dist: Distribution, config: dict, filename: StrPath) -> Distribution:
L69: def _apply_project_table(dist: Distribution, config: dict, root_dir: StrPath):
L87: def _apply_tool_table(dist: Distribution, config: dict, filename: StrPath):
L129: def _handle_missing_dynamic(dist: Distribution, project_table: dict):
L140: def json_compatible_key(key: str) -> str:
L145: def _set_config(dist: Distribution, field: str, value: Any):
L163: def _guess_content_type(file: str) -> str | None:
L176: def _long_description(
L201: def _license(dist: Distribution, val: str | dict, root_dir: StrPath | None):
L228: def _people(dist: Distribution, val: list[dict], _root_dir: StrPath | None, kind: str):
L246: def _project_urls(dist: Distribution, val: dict, _root_dir: StrPath | None):
L250: def _python_requires(dist: Distribution, val: str, _root_dir: StrPath | None):
L254: def _dependencies(dist: Distribution, val: list, _root_dir: StrPath | None):
L261: def _optional_dependencies(dist: Distribution, val: dict, _root_dir: StrPath | None):
L268: def _ext_modules(dist: Distribution, val: list[dict]) -> list[Extension]:
L275: def _adjust_ext_attrs(attrs: dict) -> dict:
L283: def _noop(_dist: Distribution, val: _T) -> _T:
L287: def _identity(val: _T) -> _T:
L291: def _unify_entry_points(project_table: dict):
L312: def _copy_command_options(pyproject: dict, dist: Distribution, filename: StrPath):
L331: def _valid_command_options(cmdclass: Mapping = EMPTY) -> dict[str, set[str]]:
L349: def _load_ep(ep: metadata.EntryPoint) -> tuple[str, type] | None:

```

```

L364: def _normalise_cmd_option_key(name: str) -> str:
L368: def _normalise_cmd_options(desc: _OptionsList) -> set[str]:
L372: def _get_previous_entrypoints(dist: Distribution) -> dict[str, list]:
L378: def _get_previous_scripts(dist: Distribution) -> list | None:
L383: def _get_previous_gui_scripts(dist: Distribution) -> list | None:
L388: def _set_static_list_metadata(attr: str, dist: Distribution, val: list) -> None:
L396: def _attrgetter(attr):
L411: def _some_attrgetter(*items):
L424: def _acessor(obj):
L511: class _MissingDynamic(SetuptoolsWarning):
L533: def details(cls, field: str, value: Any) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/__init__.py

```

L16: def _deprecation_notice(fn: Fn) -> Fn:
L18: def _wrapper(*args, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate_pyproject/fastjsonschema_exceptions.py

```

L7: class JsonSchemaException(ValueError):
L13: class JsonSchemaValueException(JsonSchemaException):
L29: def __init__(self, message, value=None, name=None, definition=None, rule=None):
L38: def path(self):
L42: def rule_definition(self):
L48: class JsonSchemaDefinitionException(JsonSchemaException):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate_pyproject/formats.py

```

L66: def pep440(version: str) -> bool:
L80: def pep508_identifier(name: str) -> bool:
L96: def pep508(value: str) -> bool:
L113: def pep508(value: str) -> bool: # noqa: ARG001
L117: def pep508_versionspec(value: str) -> bool:
L136: def pep517_backend_reference(value: str) -> bool:
L151: def _download_classifiers() -> str:
L164: class _TroveClassifier:
L179: def __init__(self) -> None:

```



```

L184: def _disable_download(self) -> None:
L188: def __call__(self, value: str) -> bool:
L220: def trove_classifier(value: str) -> bool:
L232: def pep561_stub_name(value: str) -> bool:
L247: def url(value: str) -> bool:
L281: def python_identifier(value: str) -> bool:
L288: def python_qualified_identifier(value: str) -> bool:
L298: def python_module_name(value: str) -> bool:
L305: def python_module_name_relaxed(value: str) -> bool:
L324: def python_entrypoint_group(value: str) -> bool:
L331: def python_entrypoint_name(value: str) -> bool:
L344: def python_entrypoint_reference(value: str) -> bool:
L369: def uint8(value: builtins.int) -> bool:
L374: def uint16(value: builtins.int) -> bool:
L379: def uint32(value: builtins.int) -> bool:
L384: def uint64(value: builtins.int) -> bool:
L389: def uint(value: builtins.int) -> bool:
L394: def int8(value: builtins.int) -> bool:
L399: def int16(value: builtins.int) -> bool:
L404: def int32(value: builtins.int) -> bool:
L409: def int64(value: builtins.int) -> bool:
L414: def int(value: builtins.int) -> bool:
L422: def SPDX(value: str) -> bool:
L439: def SPDX(value: str) -> bool: # noqa: ARG001
L455: def import_name(value: str) -> bool:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/__init__.py**

```

L27: def validate(data: Any) -> bool:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/error_reporting.py**

```

L56: class ValidationError(JsonSchemaValueException):
L78: def _from_jsonschema(cls, ex: JsonSchemaValueException) -> Self:
L91: def detailed_errors() -> Generator[None, None, None]:
L98: class _ErrorFormatting:
L99: def __init__(self, ex: JsonSchemaValueException):
L106: def __str__(self) -> str:
L113: def summary(self) -> str:
L120: def details(self) -> str:
L127: def _simplify_name(name: str) -> str:
L131: def _expand_summary(self) -> str:

```

```

L147: def _expand_details(self) -> str:
L175: class _SummaryWriter:
L178: def __init__(self, jargon: dict[str, str] | None = None):
L212: def _jargon(self, term: str | list[str]) -> str | list[str]:
L217: def __call__(
L259: def _is_unnecessary(self, path: Sequence[str]) -> bool:
L265: def _filter_unnecessary(
L274: def _handle_simple_dict(self, value: dict, path: Sequence[str]) -> str | None:
L281: def _handle_list(
L296: def _is_property(self, path: Sequence[str]) -> bool:
L308: def _label(self, path: Sequence[str]) -> str:
L318: def _value(self, value: Any, path: Sequence[str]) -> str:
L324: def _inline_attrs(self, schema: dict, path: Sequence[str]) -> Iterator[str]:
L329: def _child_prefix(self, parent_prefix: str, child_prefix: str) -> str:
L333: def _separate_terms(word: str) -> list[str]:

```

Q_base

appwrite/venv/lib/python3.12/site-packages/setuptools/config/_validate_pyproject/fastjsonschema_validations.py

```

L29: def validate(data, custom_formats={}, name_prefix=None):
L33: def
validate_https__packaging_python_org_en_latest_specifications_declaring_build_dependencies(d
ata, custom_formats={}, name_prefix=None):
L157: def validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html(data,
custom_formats={}, name_prefix=None):
L584: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
le_directive_properties_file(data, custom_formats={}, name_prefix=None):
L608: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
le_directive_for_dependencies(data, custom_formats={}, name_prefix=None):
L612: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
le_directive(data, custom_formats={}, name_prefix=None):
L649: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_at
tr_directive(data, custom_formats={}, name_prefix=None):
L670: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_ex
t_module(data, custom_formats={}, name_prefix=None):
L875: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
nd_directive(data, custom_formats={}, name_prefix=None):
L933: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_pa
ckage_name(data, custom_formats={}, name_prefix=None):
L959: def

```

```

validate_https__setuptools_pypa_io_en_latest_deprecated_distutils_configfile_html(data,
custom_formats={}, name_prefix=None):
L978: def validate_https__packaging_python_org_en_latest_specifications_pyproject_toml(data,
custom_formats={}, name_prefix=None):
L1372: def
validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_d
ependency(data, custom_formats={}, name_prefix=None):
L1380: def
validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_e
ntry_point_group(data, custom_formats={}, name_prefix=None):
L1411: def
validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_a
uthor(data, custom_formats={}, name_prefix=None):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/extra_validations.py**

```

L16: class RedefiningStaticFieldAsDynamic(ValidationError):
L28: class IncludedDependencyGroupMustExist(ValidationError):
L35: class ImportNameCollision(ValidationError):
L44: class ImportNameMissing(ValidationError):
L53: def validate_project_dynamic(pyproject: T) -> T:
L78: def validate_include_depenency(pyproject: T) -> T:
L101: def _remove_private(items: Iterable[str]) -> Generator[str, None, None]:
L106: def validate_import_name_issues(pyproject: T) -> T:

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/compat/py310.p
y**

```

L14: def add_note(ex, note):
L19: def add_note(ex, note):

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/compat/py311.p
y**

```

L15: def shutil_rmtree(
L23: def _handler(fn: Callable[..., Any], path: str, excinfo: ExcInfo) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_elffile.py

```
L18: class ELFInvalid(ValueError):
L22: class EIClass(enum.IntEnum):
L27: class EIData(enum.IntEnum):
L32: class EMachine(enum.IntEnum):
L40: class ELFFile:
L45: def __init__(self, f: IO[bytes]) -> None:
L90: def _read(self, fmt: str) -> tuple[int, ...]:
L94: def interpreter(self) -> str | None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_manylinux.py

```
L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:
L40: def _is_linux_armhf(executable: str) -> bool:
L55: def _is_linux_i686(executable: str) -> bool:
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:
L81: class _GLibCVersion(NamedTuple):
L86: def _glibc_version_string_confstr() -> str | None:
L105: def _glibc_version_string_ctypes() -> str | None:
L149: def _glibc_version_string() -> str | None:
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:
L174: def _get_glibc_version() -> _GLibCVersion:
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/metadata.py

```
L34: class ExceptionGroup(Exception):
L44: def __init__(self, message: str, exceptions: list[Exception]) -> None:
L48: def __repr__(self) -> str:
L52: class InvalidMetadata(ValueError):
L58: def __init__(self, field: str, message: str) -> None:
L67: class RawMetadata(TypedDict, total=False):
L186: def _parse_keywords(data: str) -> list[str]:
L191: def _parse_project_urls(data: list[str]) -> dict[str, str]:
L230: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:
L299: class RFC822Policy(email.policy.EmailPolicy):
L309: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:
```

```

L316: class RFC822Message(email.message.EmailMessage):
L323: def __init__(self) -> None:
L326: def as_bytes(
L337: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
L528: class _Validator(Generic[T]):
L542: def __init__(
L549: def __set_name__(self, _owner: Metadata, name: str) -> None:
L553: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:
L580: def _invalid_metadata(
L589: def _process_metadata_version(self, value: str) -> _MetadataVersion:
L595: def _process_name(self, value: str) -> str:
L608: def _process_version(self, value: str) -> version_module.Version:
L618: def _process_summary(self, value: str) -> str:
L624: def _process_description_content_type(self, value: str) -> str:
L656: def _process_dynamic(self, value: list[str]) -> list[str]:
L668: def _process_provides_extra(
L683: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:
L691: def _process_requires_dist(
L706: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
L714: def _process_license_files(self, value: list[str]) -> list[str]:
L740: def _process_import_names(self, value: list[str]) -> list[str]:
L765: class Metadata:
L777: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata:
L834: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
L946: def as_rfc822(self) -> RFC822Message:
L954: def _write_metadata(self, message: RFC822Message) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/markers.py

```

L40: class InvalidMarker(ValueError):
L46: class UndefinedComparison(ValueError):
L52: class UndefinedEnvironmentName(ValueError):
L59: class Environment(TypedDict):
L131: def _normalize_extras(
L147: def _normalize_extra_values(results: MarkerList) -> MarkerList:
L155: def _format_marker(
L195: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
L212: def _normalize(
L233: def _evaluate_markers(
L266: def format_full_version(info: sys._version_info) -> str:
L274: def default_environment() -> Environment:
L292: class Marker:
L293: def __init__(self, marker: str) -> None:
L323: def __str__(self) -> str:
L326: def __repr__(self) -> str:
L329: def __hash__(self) -> int:

```

```

L332: def __eq__(self, other: object) -> bool:
L338: def evaluate(
L378: def _repair_python_full_version(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/specifiers.py

```

L26: def _coerce_version(version: UnparsedVersion) -> Version | None:
L35: def _public_version(version: Version) -> Version:
L39: def _base_version(version: Version) -> Version:
L43: class InvalidSpecifier(ValueError):
L55: class BaseSpecifier(metaclass=abc.ABCMeta):
L60: def _str(self) -> str:
L65: def __str__(self) -> str:
L72: def __hash__(self) -> int:
L78: def __eq__(self, other: object) -> bool:
L88: def prereleases(self) -> bool | None:
L96: def prereleases(self, value: bool) -> None:
L103: def contains(self, item: str, prereleases: bool | None = None) -> bool:
L109: def filter(
L118: class Specifier(BaseSpecifier):
L243: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:
L271: def _get_spec_version(self, version: str) -> Version | None:
L283: def _require_spec_version(self, version: str) -> Version:
L294: def prereleases(self) -> bool | None:
L323: def prereleases(self, value: bool | None) -> None:
L327: def operator(self) -> str:
L336: def version(self) -> str:
L344: def __repr__(self) -> str:
L362: def __str__(self) -> str:
L373: def _canonical_spec(self) -> tuple[str, str]:
L386: def __hash__(self) -> int:
L389: def __eq__(self, other: object) -> bool:
L418: def _get_operator(self, op: str) -> CallableOperator:
L424: def _compare_compatible(self, prospective: Version, spec: str) -> bool:
L444: def _compare_equal(self, prospective: Version, spec: str) -> bool:
L484: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:
L487: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:
L493: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
L499: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:
L526: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
L560: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
L563: def __contains__(self, item: str | Version) -> bool:
L584: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
L611: def filter(
L677: def _version_split(version: str) -> list[str]:
L699: def _version_join(components: list[str]) -> str:

```

```

L710: def _is_not_suffix(segment: str) -> bool:
L716: def _pad_version(left: list[str], right: list[str]) -> tuple[list[str], list[str]]:
L737: class SpecifierSet(BaseSpecifier):
L746: def __init__(
L785: def prereleases(self) -> bool | None:
L805: def prereleases(self, value: bool | None) -> None:
L808: def __repr__(self) -> str:
L829: def __str__(self) -> str:
L842: def __hash__(self) -> int:
L845: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:
L876: def __eq__(self, other: object) -> bool:
L902: def __len__(self) -> int:
L906: def __iter__(self) -> Iterator[Specifier]:
L916: def __contains__(self, item: UnparsedVersion) -> bool:
L937: def contains(
L977: def filter(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_tokenizer.py

```

L12: class Token:
L18: class ParserSyntaxError(Exception):
L21: def __init__(
L34: def __str__(self) -> str:
L91: class Tokenizer:
L98: def __init__(
L109: def consume(self, name: str) -> None:
L114: def check(self, name: str, *, peek: bool = False) -> bool:
L135: def expect(self, name: str, *, expected: str) -> Token:
L144: def read(self) -> Token:
L154: def raise_syntax_error(
L173: def enclosing_tokens(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_parser.py

```

L15: class Node:
L18: def __init__(self, value: str) -> None:
L21: def __str__(self) -> str:
L24: def __repr__(self) -> str:
L27: def serialize(self) -> str:
L31: class Variable(Node):
L34: def serialize(self) -> str:
L38: class Value(Node):

```

```

L41: def serialize(self) -> str:
L45: class Op(Node):
L48: def serialize(self) -> str:
L59: class ParsedRequirement(NamedTuple):
L70: def parse_requirement(source: str) -> ParsedRequirement:
L74: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:
L95: def _parse_requirement_details(
L148: def _parse_requirement_marker(
L169: def _parse_extras(tokenizer: Tokenizer) -> list[str]:
L188: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:
L215: def _parse_specifier(tokenizer: Tokenizer) -> str:
L232: def _parse_version_many(tokenizer: Tokenizer) -> str:
L264: def parse_marker(source: str) -> MarkerList:
L268: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:
L274: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:
L286: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:
L308: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:
L322: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar: # noqa: RET503
L336: def process_env_var(env_var: str) -> Variable:
L343: def process_python_str(python_str: str) -> Value:
L348: def _parse_marker_op(tokenizer: Tokenizer) -> Op:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/typing.py

```

L17: class InvalidName(ValueError):
L23: class InvalidWheelFilename(ValueError):
L29: class InvalidSdistFilename(ValueError):
L42: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
L55: def is_normalized_name(name: str) -> bool:
L59: def canonicalize_version(
L89: def parse_wheel_filename(
L132: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/version.py

```

L39: def _deprecated(message: str) -> object:
L40: def decorator(func: object) -> object:
L42: def wrapper(*args: object, **kwargs: object) -> object:
L85: class _VersionReplace(TypedDict, total=False):
L94: def parse(version: str) -> Version:
L106: class InvalidVersion(ValueError):
L116: class _BaseVersion:

```



```

L125: def _key(self) -> tuple[Any, ...]: ...
L127: def __hash__(self) -> int:
L133: def __lt__(self, other: _BaseVersion) -> bool:
L139: def __le__(self, other: _BaseVersion) -> bool:
L145: def __eq__(self, other: object) -> bool:
L151: def __ge__(self, other: _BaseVersion) -> bool:
L157: def __gt__(self, other: _BaseVersion) -> bool:
L163: def __ne__(self, other: object) -> bool:
L238: def _validate_epoch(value: object, /) -> int:
L246: def _validate_release(value: object, /) -> tuple[int, ...]:
L258: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
L273: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:
L282: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:
L291: def _validate_local(value: object, /) -> LocalType | None:
L301: class _Version(NamedTuple):
L310: class Version(_BaseVersion):
L348: def __init__(self, version: str) -> None:
L374: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:
L408: def _key(self) -> CmpKey:
L422: def _version(self) -> _Version:
L429: def _version(self, value: _Version) -> None:
L438: def __repr__(self) -> str:
L446: def __str__(self) -> str:
L478: def _str(self) -> str:
L483: def epoch(self) -> int:
L494: def release(self) -> tuple[int, ...]:
L510: def pre(self) -> tuple[str, int] | None:
L525: def post(self) -> int | None:
L536: def dev(self) -> int | None:
L547: def local(self) -> str | None:
L561: def public(self) -> str:
L574: def base_version(self) -> str:
L591: def is_prerelease(self) -> bool:
L608: def is_postrelease(self) -> bool:
L619: def is_devrelease(self) -> bool:
L630: def major(self) -> int:
L639: def minor(self) -> int:
L650: def micro(self) -> int:
L661: class _TrimmedRelease(Version):
L664: def __init__(self, version: str | Version) -> None:
L677: def release(self) -> tuple[int, ...]:
L695: def _parse_letter_version(
L722: def _parse_local_version(local: str | None) -> LocalType | None:
L734: def _cmpkey(

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_structures.py

```

L9: class InfinityType:
L12: def __repr__(self) -> str:
L15: def __hash__(self) -> int:
L18: def __lt__(self, other: object) -> bool:
L21: def __le__(self, other: object) -> bool:
L24: def __eq__(self, other: object) -> bool:
L27: def __gt__(self, other: object) -> bool:
L30: def __ge__(self, other: object) -> bool:
L33: def __neg__(self: object) -> "NegativeInfinityType":
L41: class NegativeInfinityType:
L44: def __repr__(self) -> str:
L47: def __hash__(self) -> int:
L50: def __lt__(self, other: object) -> bool:
L53: def __le__(self, other: object) -> bool:
L56: def __eq__(self, other: object) -> bool:
L59: def __gt__(self, other: object) -> bool:
L62: def __ge__(self, other: object) -> bool:
L65: def __neg__(self: object) -> InfinityType:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/tags.py

```

L43: class Tag:
L53: def __init__(self, interpreter: str, abi: str, platform: str) -> None:
L65: def interpreter(self) -> str:
L69: def abi(self) -> str:
L73: def platform(self) -> str:
L76: def __eq__(self, other: object) -> bool:
L87: def __hash__(self) -> int:
L90: def __str__(self) -> str:
L93: def __repr__(self) -> str:
L96: def __setstate__(self, state: tuple[None, dict[str, Any]]) -> None:
L104: def parse_tag(tag: str) -> frozenset[Tag]:
L120: def _get_config_var(name: str, warn: bool = False) -> int | str | None:
L129: def _normalize_string(string: str) -> str:
L133: def _is_threaded_cpython(abis: list[str]) -> bool:
L149: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:
L159: def _cpython_abi(py_version: PythonVersion, warn: bool = False) -> list[str]:
L192: def cpython_tags(
L248: def _generic_abi() -> list[str]:
L289: def generic_tags(
L317: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:
L332: def compatible_tags(
L357: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:
L367: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:
L399: def mac_platforms(
L475: def ios_platforms(

```

```

L532: def android_platforms(
L569: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:
L588: def _generic_platforms() -> Iterator[str]:
L592: def platform_tags() -> Iterator[str]:
L608: def interpreter_name() -> str:
L619: def interpreter_version(*, warn: bool = False) -> str:
L627: def _version_nodot(version: PythonVersion) -> str:
L631: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_musllinux.py

```

L18: class _MuslVersion(NamedTuple):
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/requirements.py

```

L15: class InvalidRequirement(ValueError):
L21: class Requirement:
L34: def __init__(self, requirement_string: str) -> None:
L49: def _iter_parts(self, name: str) -> Iterator[str]:
L67: def __str__(self) -> str:
L70: def __repr__(self) -> str:
L73: def __hash__(self) -> int:
L76: def __eq__(self, other: object) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/pylock.py

```

L46: class _FromMappingProtocol(Protocol): # pragma: no cover
L48: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L57: def is_valid_pylock_path(path: Path) -> bool:
L62: def _toml_key(key: str) -> str:
L66: def _toml_value(key: str, value: Any) -> Any: # noqa: ANN401
L74: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L82: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L95: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:

```

```

L102: def _get_sequence(
L124: def _get_as(
L143: def _get_required_as(
L156: def _get_sequence_as(
L175: def _get_object(
L187: def _get_sequence_of_objects(
L203: def _get_required_sequence_of_objects(
L213: def _validate_normalized_name(name: str) -> NormalizedName:
L220: def _validate_path_url(path: str | None, url: str | None) -> None:
L225: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:
L233: class PylockValidationError(Exception):
L239: def __init__(
L257: def __str__(self) -> str:
L263: class _PylockRequiredKeyError(PylockValidationError):
L264: def __init__(self, key: str) -> None:
L268: class PylockUnsupportedVersionError(PylockValidationError):
L273: class PackageVcs:
L281: def __init__(
L300: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L314: class PackageDirectory:
L319: def __init__(
L332: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L341: class PackageArchive:
L349: def __init__(
L368: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L382: class PackageSdist:
L390: def __init__(
L409: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L423: class PackageWheel:
L431: def __init__(
L450: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L464: class Package:
L479: def __init__(
L512: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L553: def is_direct(self) -> bool:
L558: class Pylock:
L571: def __init__(
L596: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L619: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L627: def to_dict(self) -> Mapping[str, Any]:
L631: def validate(self) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):
L10: class SPDXException(TypedDict):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/licenses/__init__.py

```
L50: class InvalidLicenseExpression(ValueError):
L60: def canonicalize_license_expression(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/functools/__init__.py

```
L16: def compose(*funcs):
L42: def compose_two(f1, f2):
L48: def once(func):
L81: def wrapper(*args, **kwargs):
L90: def method_cache(method, cache_wrapper=functools.lru_cache()):
L158: def wrapper(self, *args, **kwargs):
L171: def _special_method_cache(method, cache_wrapper):
L190: def proxy(self, /, *args, **kwargs):
L202: def apply(transform):
L217: def wrap(func):
L223: def result_invoke(action):
L239: def wrap(func):
L241: def wrapper(*args, **kwargs):
L251: def invoke(f, /, *args, **kwargs):
L296: def passthrough(func: Callable[..., object]) -> Callable[[_T], _T]:
L306: def wrapper(first: _T, *args, **kwargs) -> _T:
L313: class Throttler:
L316: def __init__(self, func, max_rate=float('Inf')):
L323: def reset(self):
L326: def __call__(self, *args, **kwargs):
L330: def _wait(self):
L337: def __get__(self, obj, owner=None):
L341: def first_invoke(func1, func2):
L348: def wrapper(*args, **kwargs):
L366: def retry_call(func, cleanup=lambda: None, retries=0, trap=()):
L383: def retry(*r_args, **r_kwargs):
L398: def decorate(func):
L400: def wrapper(*f_args, **f_kwargs):
L409: def print_yielded(func):
L425: def pass_none(func):
L436: def wrapper(param, /, *args, **kwargs):
L444: def none_as(value, replacement=None):
L454: def assign_params(func, namespace):
L486: def save_method_args(method):
L523: def wrapper(self, /, *args, **kwargs):
```

```

L532: def except_(*exceptions, replace=None, use=None):
L556: def decorate(func):
L558: def wrapper(*args, **kwargs):
L572: def identity(x):
L583: def bypass_when(check, *, _op=identity):
L599: def decorate(func):
L601: def wrapper(param, /):
L609: def bypass_unless(check):
L628: def _splat_inner(args, func):
L634: def _(args: collections.abc.Mapping, func):
L639: def splat(func):
L680: def chainable(method: Callable[[_T, ...], None]) -> Callable[[_T, ...], _T]:
L710: def wrapper(self, *args, **kwargs):
L717: def noop(*args, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/show-newlines.py

```

L8: def report_newlines(filename):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/layouts.py

```

L9: def translate(input, translation):
L19: def _translate_stream(stream, translation):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/__init__.py

```

L17: def substitution(old, new):
L24: def multi_substitution(*substitutions):
L39: class FoldedCase(str):
L102: def __lt__(self, other):
L105: def __gt__(self, other):
L108: def __eq__(self, other):
L111: def __ne__(self, other):
L114: def __hash__(self):
L117: def __contains__(self, other):
L120: def in_(self, other):
L126: def casefold(self):

```

```

L129: def index(self, sub):
L132: def split(self, splitter=' ', maxsplit=0):
L142: def is_decodable(value):
L155: def is_binary(value):
L168: def trim(s):
L179: def wrap(s):
L212: def unwrap(s):
L237: class Splitter:
L245: def __init__(self, *args):
L248: def __call__(self, s):
L252: def indent(string, prefix=' ' * 4):
L260: class WordSet(tuple):
L316: def capitalized(self):
L319: def lowered(self):
L322: def camel_case(self):
L325: def headless_camel_case(self):
L331: def underscore_separated(self):
L334: def dash_separated(self):
L337: def space_separated(self):
L340: def trim_right(self, item):
L353: def trim_left(self, item):
L366: def trim(self, item):
L373: def __getitem__(self, item):
L380: def parse(cls, identifier):
L385: def from_class_name(cls, subject):
L393: def simple_html_strip(s):
L415: class SeparatedValues(str):
L431: def __iter__(self):
L436: class Stripper:
L463: def __init__(self, prefix, lines):
L468: def strip_prefix(cls, lines):
L473: def __call__(self, line):
L480: def common_prefix(s1, s2):
L490: def remove_prefix(text, prefix):
L504: def remove_suffix(text, suffix):
L518: def normalize_newlines(text):
L534: def _nonblank(str):
L539: def yield_lines(iterable):
L558: def _(text):
L562: def clean(lines: Iterable[str]):
L569: def drop_comment(line):
L584: def join_continuation(lines):
L617: def read_newlines(filename, limit=1024):
L636: def lines_from(input):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/strip-prefix.py

```
L8: def strip_prefix():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/context/__init__.py

```
L24: def pushd(dir: str | os.PathLike) -> Iterator[str | os.PathLike]:
L41: def tarball(
L86: def _compose_tarfile_filters(*filters):
L87: def compose_two(f1, f2):
L93: def strip_first_component(
L104: def _compose(*cmgrs):
L124: def compose_two(inner, outer):
L125: def composed(*args, **kwargs):
L140: def remove_readonly(func, path, exc_info):
L154: def robust_remover():
L163: def temp_dir(remover=shutil.rmtree):
L184: def repo_context(
L210: class ExceptionTrap:
L246: def __init__(self, exceptions=(Exception,)):
L249: def __enter__(self):
L253: def type(self):
L257: def value(self):
L261: def tb(self):
L264: def __exit__(self, *exc_info):
L271: def __bool__(self):
L274: def raises(self, func, *, _test=bool):
L294: def wrapper(*args, **kwargs):
L301: def passes(self, func):
L323: class suppress(contextlib.suppress, contextlib.ContextDecorator):
L334: class on_interrupt(contextlib.ContextDecorator):
L355: def __init__(self, action='error', /, code=1):
L359: def __enter__(self):
L362: def __exit__(self, exctype, excinst, exctb):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/autocommand.py

```
L26: def autocommand(
L39: def autocommand_decorator(func):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autoco

mmand/automain.py

```

L22: class AutomainRequiresModuleError(AutocommandError, TypeError):
L26: def automain(module, *, args=(), kwargs=None):
L38: def main():
L54: def automain_decorator(main):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/autoparse.py**

```

L31: class AnnotationError(AutocommandError):
L35: class PositionalArgError(AutocommandError):
L41: class KWArgError(AutocommandError):
L45: class DocstringError(AutocommandError):
L49: class TooManySplitsError(DocstringError):
L57: def _get_type_description(annotation):
L83: def _add_arguments(param, parser, used_char_args, add_nos):
L191: def make_parser(func_sig, description, epilog, add_nos):
L215: def parse_docstring(docstring):
L232: def autoparse(
L291: def autoparse_wrapper(argv=None):
L312: def smart_open(filename_or_file, *args, **kwargs):
L323: def work_with_file(name=sys.stdout):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/autoasync.py**

```

L54: def autoasync(coro=None, *, loop=None, forever=False, pass_loop=False):
L84: def get_file(host, port):
L92: def server(host, port, loop):
L115: def autoasync_wrapper(*args, **kwargs):

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/errors.py**

```

L19: class AutocommandError(Exception):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_bdist_wheel.py

```

L50: def safe_name(name: str) -> str:
L57: def safe_version(version: str) -> str:
L74: def _is_32bit_interpreter() -> bool:
L78: def python_tag() -> str:
L82: def get_platform(archive_root: str | None) -> str:
L102: def get_flag(
L119: def get_abi_tag() -> str | None:
L159: def safer_name(name: str) -> str:
L163: def safer_version(version: str) -> str:
L167: def remove_readonly(
L175: def remove_readonly_exc(func: Callable[..., object], path: str, exc: Exception) ->
None:
L180: class bdist_wheel(Command):
L248: def initialize_options(self):
L269: def finalize_options(self):
L313: def wheel_dist_name(self):
L323: def get_tag(self) -> tuple[str, str, str]:
L381: def run(self):
L471: def write_wheelfile(
L495: def _ensure_relative(self, path: str) -> str:
L503: def license_paths(self) -> Iterable[str]:
L547: def egg2dist(self, egginfo_path: str, distinfo_path: str):
L550: def adios(p: str) -> None:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_metadata.py

```

L20: def _nonblank(str: str) -> bool | Literal[""]:
L25: def yield_lines(iterable: Iterable[str]) -> Iterator[str]:
L43: def _(text: str) -> Iterator[str]:
L47: def split_sections(
L74: def safe_extra(extra: str) -> str:
L82: def safe_name(name: str) -> str:
L89: def requires_to_requires_dist(requirement: Requirement) -> str:
L104: def convert_requirements(requirements: list[str]) -> Iterator[str]:
L116: def generate_requirements(
L147: def pkginfo_to_metadata(egg_info_path: str, pkginfo_path: str) -> Message:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/__main__.py

```
L11: def main() -> NoReturn: # needed for console script
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/
macosx_libfile.py**

```
L252: def swap32(x: int) -> int:
L261: def get_base_class_and_magic_number(
L288: def read_data(struct_class: type[ctypes.Structure], lib_file: BufferedIOBase):
L292: def extract_macosx_min_system_version(path_to_lib: str):
L300: class FatHeader(BaseClass):
L306: class FatArch(BaseClass):
L311: class FatArch(BaseClass):
L350: def read_mach_header(
L363: class SegmentBase(base_class):
L368: class MachHeader(base_class):
L373: class MachHeader(base_class):
L383: class VersionMinCommand(base_class):
L390: class VersionBuild(base_class):
L400: def parse_version(version: int) -> tuple[int, int, int]:
L407: def calculate_macosx_platform_tag(archive_root: StrPath, platform_tag: str) -> str:
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/
_setuptools_logging.py**

```
L8: def _not_warning(record: logging.LogRecord) -> bool:
L12: def configure() -> None:
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/
wheelfile.py**

```
L33: class WheelError(Exception):
L37: def urlsafe_b64encode(data: bytes) -> bytes:
L42: def urlsafe_b64decode(data: bytes) -> bytes:
L48: def get_zipinfo_datetime(
L58: class WheelFile(ZipFile):
L65: def __init__(
L123: def open(
L129: def _update_crc(newdata: bytes) -> None:
L157: def write_files(self, base_dir: str) -> None:
L179: def write(
```

```
L196: def writestr(
L227: def close(self) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/unpack.py

```
L8: def unpack(path: str, dest: str = ".") -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/convert.py

```
L49: def convert_requires(requires: str, metadata: Message) -> None:
L67: def convert_pkg_info(pkginfo: str, metadata: Message) -> None:
L98: def normalize(name: str) -> str:
L102: class ConvertSource(metaclass=ABCMeta):
L111: def dist_info_dir(self) -> str:
L115: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L119: class EggFileSource(ConvertSource):
L120: def __init__(self, path: Path):
L136: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L164: class EggDirectorySource(EggFileSource):
L165: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L193: class WininstFileSource(ConvertSource):
L223: def __init__(self, path: Path):
L253: def generate_contents(self) -> Iterator[tuple[str, bytes]]:
L287: def convert(files: list[str], dest_dir: str, verbose: bool) -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/__init__.py

```
L15: def unpack_f(args: argparse.Namespace) -> None:
L21: def pack_f(args: argparse.Namespace) -> None:
L27: def convert_f(args: argparse.Namespace) -> None:
L33: def tags_f(args: argparse.Namespace) -> None:
L52: def version_f(args: argparse.Namespace) -> None:
L58: def parse_build_tag(build_tag: str) -> str:
L76: def parser() -> argparse.ArgumentParser:
L141: def main() -> int:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/pack.py

```
L14: def pack(directory: str, dest_dir: str, build_number: str | None) -> None:
L75: def compute_tagline(tags: list[str]) -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/tags.py

```
L12: def _compute_tags(original_tags: Iterable[str], new_tags: str | None) -> set[str]:
L26: def tags(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/unix.py

```
L18: def getuid() -> NoReturn:
L26: class Unix(PlatformDirsABC): # noqa: PLR0904
L40: def user_data_dir(self) -> str:
L51: def _site_data_dirs(self) -> list[str]:
L58: def site_data_dir(self) -> str:
L71: def user_config_dir(self) -> str:
L82: def _site_config_dirs(self) -> list[str]:
L89: def site_config_dir(self) -> str:
L102: def user_cache_dir(self) -> str:
L113: def site_cache_dir(self) -> str:
L118: def user_state_dir(self) -> str:
L129: def user_log_dir(self) -> str:
L138: def user_documents_dir(self) -> str:
L143: def user_downloads_dir(self) -> str:
L148: def user_pictures_dir(self) -> str:
L153: def user_videos_dir(self) -> str:
L158: def user_music_dir(self) -> str:
L163: def user_desktop_dir(self) -> str:
L168: def user_runtime_dir(self) -> str:
L188: def site_runtime_dir(self) -> str:
L210: def site_data_path(self) -> Path:
L215: def site_config_path(self) -> Path:
L220: def site_cache_path(self) -> Path:
L224: def iter_config_dirs(self) -> Iterator[str]:
L229: def iter_data_dirs(self) -> Iterator[str]:
L235: def _get_user_media_dir(env_var: str, fallback_tilde_path: str) -> str:
```

```
L245: def _get_user_dirs_folder(key: str) -> str | None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/___main___py

```
L26: def main() -> None:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/api.py

```
L15: class PlatformDirsABC(ABC): # noqa: PLR0904
L18: def __init__( # noqa: PLR0913, PLR0917
L81: def _append_app_name_and_version(self, *base: str) -> str:
L91: def _optionally_create_directory(self, path: str) -> None:
L95: def _first_item_as_path_if_multipath(self, directory: str) -> Path:
L103: def user_data_dir(self) -> str:
L108: def site_data_dir(self) -> str:
L113: def user_config_dir(self) -> str:
L118: def site_config_dir(self) -> str:
L123: def user_cache_dir(self) -> str:
L128: def site_cache_dir(self) -> str:
L133: def user_state_dir(self) -> str:
L138: def user_log_dir(self) -> str:
L143: def user_documents_dir(self) -> str:
L148: def user_downloads_dir(self) -> str:
L153: def user_pictures_dir(self) -> str:
L158: def user_videos_dir(self) -> str:
L163: def user_music_dir(self) -> str:
L168: def user_desktop_dir(self) -> str:
L173: def user_runtime_dir(self) -> str:
L178: def site_runtime_dir(self) -> str:
L182: def user_data_path(self) -> Path:
L187: def site_data_path(self) -> Path:
L192: def user_config_path(self) -> Path:
L197: def site_config_path(self) -> Path:
L202: def user_cache_path(self) -> Path:
L207: def site_cache_path(self) -> Path:
L212: def user_state_path(self) -> Path:
L217: def user_log_path(self) -> Path:
L222: def user_documents_path(self) -> Path:
L227: def user_downloads_path(self) -> Path:
L232: def user_pictures_path(self) -> Path:
L237: def user_videos_path(self) -> Path:
L242: def user_music_path(self) -> Path:
```

```

L247: def user_desktop_path(self) -> Path:
L252: def user_runtime_path(self) -> Path:
L257: def site_runtime_path(self) -> Path:
L261: def iter_config_dirs(self) -> Iterator[str]:
L266: def iter_data_dirs(self) -> Iterator[str]:
L271: def iter_cache_dirs(self) -> Iterator[str]:
L276: def iter_runtime_dirs(self) -> Iterator[str]:
L281: def iter_config_paths(self) -> Iterator[Path]:
L286: def iter_data_paths(self) -> Iterator[Path]:
L291: def iter_cache_paths(self) -> Iterator[Path]:
L296: def iter_runtime_paths(self) -> Iterator[Path]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/__init__.py

```

L30: def _set_platform_dir_class() -> type[PlatformDirsABC]:
L53: def user_data_dir(
L77: def site_data_dir(
L101: def user_config_dir(
L125: def site_config_dir(
L149: def user_cache_dir(
L173: def site_cache_dir(
L197: def user_state_dir(
L221: def user_log_dir(
L245: def user_documents_dir() -> str:
L250: def user_downloads_dir() -> str:
L255: def user_pictures_dir() -> str:
L260: def user_videos_dir() -> str:
L265: def user_music_dir() -> str:
L270: def user_desktop_dir() -> str:
L275: def user_runtime_dir(
L299: def site_runtime_dir(
L323: def user_data_path(
L347: def site_data_path(
L371: def user_config_path(
L395: def site_config_path(
L419: def site_cache_path(
L443: def user_cache_path(
L467: def user_state_path(
L491: def user_log_path(
L515: def user_documents_path() -> Path:
L520: def user_downloads_path() -> Path:
L525: def user_pictures_path() -> Path:
L530: def user_videos_path() -> Path:
L535: def user_music_path() -> Path:
L540: def user_desktop_path() -> Path:
L545: def user_runtime_path(

```

```
L569: def site_runtime_path(
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/android.py

```
L14: class Android(PlatformDirsABC):
L24: def user_data_dir(self) -> str:
L29: def site_data_dir(self) -> str:
L34: def user_config_dir(self) -> str:
L42: def site_config_dir(self) -> str:
L47: def user_cache_dir(self) -> str:
L52: def site_cache_dir(self) -> str:
L57: def user_state_dir(self) -> str:
L62: def user_log_dir(self) -> str:
L73: def user_documents_dir(self) -> str:
L78: def user_downloads_dir(self) -> str:
L83: def user_pictures_dir(self) -> str:
L88: def user_videos_dir(self) -> str:
L93: def user_music_dir(self) -> str:
L98: def user_desktop_dir(self) -> str:
L103: def user_runtime_dir(self) -> str:
L114: def site_runtime_dir(self) -> str:
L120: def _android_folder() -> str | None: # noqa: C901
L168: def _android_documents_folder() -> str:
L184: def _android_downloads_folder() -> str:
L200: def _android_pictures_folder() -> str:
L216: def _android_videos_folder() -> str:
L232: def _android_music_folder() -> str:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/macos.py

```
L15: class MacOS(PlatformDirsABC):
L28: def user_data_dir(self) -> str:
L33: def site_data_dir(self) -> str:
L51: def site_data_path(self) -> Path:
L56: def user_config_dir(self) -> str:
L61: def site_config_dir(self) -> str:
L66: def user_cache_dir(self) -> str:
L71: def site_cache_dir(self) -> str:
L89: def site_cache_path(self) -> Path:
L94: def user_state_dir(self) -> str:
L99: def user_log_dir(self) -> str:
L104: def user_documents_dir(self) -> str:
```



```

L109: def user_downloads_dir(self) -> str:
L114: def user_pictures_dir(self) -> str:
L119: def user_videos_dir(self) -> str:
L124: def user_music_dir(self) -> str:
L129: def user_desktop_dir(self) -> str:
L134: def user_runtime_dir(self) -> str:
L139: def site_runtime_dir(self) -> str:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/windows.py

```

L16: class Windows(PlatformDirsABC):
L28: def user_data_dir(self) -> str:
L38: def _append_parts(self, path: str, *, opinion_value: str | None = None) -> str:
L54: def site_data_dir(self) -> str:
L60: def user_config_dir(self) -> str:
L65: def site_config_dir(self) -> str:
L70: def user_cache_dir(self) -> str:
L79: def site_cache_dir(self) -> str:
L85: def user_state_dir(self) -> str:
L90: def user_log_dir(self) -> str:
L99: def user_documents_dir(self) -> str:
L104: def user_downloads_dir(self) -> str:
L109: def user_pictures_dir(self) -> str:
L114: def user_videos_dir(self) -> str:
L119: def user_music_dir(self) -> str:
L124: def user_desktop_dir(self) -> str:
L129: def user_runtime_dir(self) -> str:
L138: def site_runtime_dir(self) -> str:
L143: def get_win_folder_from_env_vars(csidl_name: str) -> str:
L164: def get_win_folder_if_csidl_name_not_env_var(csidl_name: str) -> str | None:
L183: def get_win_folder_from_registry(csidl_name: str) -> str:
L213: def get_win_folder_via_ctypes(csidl_name: str) -> str:
L252: def _pick_get_win_folder() -> Callable[[str], str]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zipper/glob.py

```

L9: class Translator:
L24: def __init__(self, seps: str = _default_seps):
L28: def translate(self, pattern):
L35: def extend(self, pattern):
L46: def match_dirs(self, pattern):
L54: def translate_core(self, pattern):

```

```

L69: def replace(self, match):
L80: def restrict_rglob(self, pattern):
L94: def star_not_empty(self, pattern):
L99: def handle_segment(match):
L107: def separate(pattern):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl/____init__.py

```

L27: def _parents(path):
L46: def _ancestry(path):
L77: def _difference(minuend, subtrahend):
L85: class InitializedState:
L91: def __init__(self, *args, **kwargs):
L94: def __getstate__(self):
L97: def __setstate__(self, state):
L102: class CompleteDirs(InitializedState, zipfile.ZipFile):
L114: def _implied_dirs(names):
L119: def namelist(self):
L123: def _name_set(self):
L126: def resolve_dir(self, name):
L136: def getinfo(self, name):
L148: def make(cls, source):
L167: def inject(cls, zf: zipfile.ZipFile) -> zipfile.ZipFile:
L177: class FastLookup(CompleteDirs):
L183: def namelist(self):
L187: def _namelist(self):
L190: def _name_set(self):
L194: def _name_set_prop(self):
L198: def _extract_text_encoding(encoding=None, *args, **kwargs):
L208: class Path:
L313: def __init__(self, root, at=""):
L326: def __eq__(self, other):
L335: def __hash__(self):
L338: def open(self, mode='r', *args, pwd=None, **kwargs):
L358: def _base(self):
L362: def name(self):
L366: def suffix(self):
L370: def suffixes(self):
L374: def stem(self):
L378: def filename(self):
L381: def read_text(self, *args, **kwargs):
L386: def read_bytes(self):
L390: def _is_child(self, path):
L393: def _next(self, at):
L396: def is_dir(self):
L399: def is_file(self):

```

```

L402: def exists(self):
L405: def iterdir(self):
L411: def match(self, path_pattern):
L414: def is_symlink(self):
L422: def glob(self, pattern):
L431: def rglob(self, pattern):
L434: def relative_to(self, other, *extra):
L437: def __str__(self):
L440: def __repr__(self):
L443: def joinpath(self, *other):
L450: def parent(self):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl_functools.py

```

L6: def save_method_args(method):
L14: def wrapper(self, /, *args, **kwargs):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl_compat/py313.py

```

L6: def identity(x):
L11: def apply(transform):
L12: def wrap(func):
L19: def compose(*funcs):
L20: def compose_two(f1, f2):
L26: def replace(pattern):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl_compat/py310.py

```

L5: def _text_encoding(encoding, stacklevel=2, /): # pragma: no cover

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl_compat/overlay.py

```

L28: class HashableNamespace(types.SimpleNamespace):

```

```
L29: def __hash__(self):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/tomli/_parser.py

```
L71: class DEPRECATED_DEFAULT:
L76: class TOMLDecodeError(ValueError):
L87: def __init__(
L137: def load(__fp: IO[bytes], *, parse_float: ParseFloat = float) -> dict[str, Any]:
L149: def loads(__s: str, *, parse_float: ParseFloat = float) -> dict[str, Any]:
L220: class Flags:
L229: def __init__(self) -> None:
L233: def add_pending(self, key: Key, flag: int) -> None:
L236: def finalize_pending(self) -> None:
L241: def unset_all(self, key: Key) -> None:
L249: def set(self, key: Key, flag: int, *, recursive: bool) -> None: # noqa: A003
L260: def is_(self, key: Key, flag: int) -> bool:
L278: class NestedDict:
L279: def __init__(self) -> None:
L283: def get_or_create_nest(
L300: def append_nest_to_list(self, key: Key) -> None:
L312: class Output:
L313: def __init__(self) -> None:
L318: def skip_chars(src: str, pos: Pos, chars: Iterable[str]) -> Pos:
L327: def skip_until(
L349: def skip_comment(src: str, pos: Pos) -> Pos:
L361: def skip_comments_and_array_ws(src: str, pos: Pos) -> Pos:
L370: def create_dict_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:
L390: def create_list_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:
L413: def key_value_rule(
L447: def parse_key_value_pair(
L463: def parse_key(src: str, pos: Pos) -> tuple[Pos, Key]:
L481: def parse_key_part(src: str, pos: Pos) -> tuple[Pos, str]:
L497: def parse_one_line_basic_str(src: str, pos: Pos) -> tuple[Pos, str]:
L502: def parse_array(
L528: def parse_inline_table(
L564: def parse_basic_str_escape(
L595: def parse_basic_str_escape_multiline(src: str, pos: Pos) -> tuple[Pos, str]:
L599: def parse_hex_char(src: str, pos: Pos, hex_len: int) -> tuple[Pos, str]:
L612: def parse_literal_str(src: str, pos: Pos) -> tuple[Pos, str]:
L621: def parse_multiline_str(src: str, pos: Pos, *, literal: bool) -> tuple[Pos, str]:
L652: def parse_basic_str(src: str, pos: Pos, *, multiline: bool) -> tuple[Pos, str]:
L684: def parse_value(
L760: def is_unicode_scalar_value(codepoint: int) -> bool:
L764: def make_safe_parse_float(parse_float: ParseFloat) -> ParseFloat:
L776: def safe_parse_float(float_str: str) -> Any:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/tomli/_re.py

```
L159: def match_to_datetime(match: re.Match[str]) -> datetime | date:
L199: def cached_tz(hour_str: str, minute_str: str, sign_str: str) -> timezone:
L109: def match_to_localtime(match: re.Match[str]) -> time:
L116: def match_to_number(match: re.Match[str], parse_float: ParseFloat) -> Any:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/more_itertools/more.py

```
L189: def dl_split(x: float):
L196: def dl_mul(x, y):
L206: def _fsumprod(p, q):
L210: def chunked(iterable, n, strict=False):
L234: def ret():
L245: def first(iterable, default=_marker):
L272: def last(iterable, default=_marker):
L300: def nth_or_last(iterable, n, default=_marker):
L317: class peekable:
L376: def __init__(self, iterable):
L380: def __iter__(self):
L383: def __bool__(self):
L390: def peek(self, default=_marker):
L406: def prepend(self, *items):
L437: def __next__(self):
L443: def _get_slice(self, index):
L469: def __getitem__(self, index):
L482: def consumer(func):
L506: def wrapper(*args, **kwargs):
L514: def ilen(iterable):
L524: def ilen(iterable):
L539: def iterate(func, start):
L559: def with_iter(context_manager):
L574: def one(iterable, too_short=None, too_long=None):
L630: def raise_(exception, *args):
L634: def strictly_n(iterable, n, too_short=None, too_long=None):
L709: def distinct_permutations(iterable, r=None):
L754: def _full(A):
L778: def _partial(A, r):
L835: def permuted_items(permuted_indices):
L859: def derangements(iterable, r=None):
L921: def intersperse(e, iterable, n=1):
L947: def unique_to_each(*iterables):
```

```

L980: def windowed(seq, n, fillvalue=None, step=1):
L1038: def substrings(iterable):
L1064: def substrings_indexes(seq, reverse=False):
L1098: class bucket:
L1134: def __init__(self, iterable, key, validator=None):
L1140: def __contains__(self, value):
L1153: def _get_values(self, value):
L1179: def __iter__(self):
L1187: def __getitem__(self, value):
L1194: def spy(iterable, n=1):
L1235: def interleave(*iterables):
L1249: def interleave_longest(*iterables):
L1267: def interleave_evenly(iterables, lengths=None):
L1333: def interleave_randomly(*iterables):
L1356: def collapse(iterable, base_type=None, levels=None):
L1416: def side_effect(func, iterable, chunk_size=None, before=None, after=None):
L1477: def sliced(seq, n, strict=False):
L1500: def ret():
L1511: def split_at(iterable, pred, maxsplit=-1, keep_separator=False):
L1555: def split_before(iterable, pred, maxsplit=-1):
L1590: def split_after(iterable, pred, maxsplit=-1):
L1628: def split_when(iterable, pred, maxsplit=-1):
L1673: def split_into(iterable, sizes):
L1718: def padded(iterable, fillvalue=None, n=None, next_multiple=False):
L1751: def slice_generator():
L1763: def repeat_each(iterable, n=2):
L1772: def repeat_last(iterable, default=None):
L1791: def distribute(n, iterable):
L1828: def stagger(iterable, offsets=(-1, 0, 1), longest=False, fillvalue=None):
L1856: def zip_equal(*iterables):
L1887: def zip_offset(*iterables, offsets, longest=False, fillvalue=None):
L1926: def sort_together(
L1999: def unzip(iterable):
L2040: def divide(n, iterable):
L2091: def always_iterable(obj, base_type=(str, bytes)):
L2144: def adjacent(predicate, iterable, distance=1):
L2183: def groupby_transform(iterable, keyfunc=None, valuefunc=None, reducefunc=None):
L2228: class numeric_range(abc.Sequence, abc.Hashable):
L2282: def __init__(self, *args):
L2307: def __bool__(self):
L2313: def __contains__(self, elem):
L2323: def __eq__(self, other):
L2338: def __getitem__(self, key):
L2365: def __hash__(self):
L2371: def __iter__(self):
L2378: def __len__(self):
L2382: def _len(self):
L2398: def __reduce__(self):
L2401: def __repr__(self):
L2408: def __reversed__(self):
L2415: def count(self, value):

```

```

L2418: def index(self, value):
L2432: def _get_by_index(self, i):
L2440: def count_cycle(iterable, n=None):
L2456: def mark_ends(iterable):
L2486: def locate(iterable, pred=bool, window_size=None):
L2534: def longest_common_prefix(iterables):
L2544: def lstrip(iterable, pred):
L2562: def rstrip(iterable, pred):
L2588: def strip(iterable, pred):
L2605: class islice_extended:
L2631: def __init__(self, iterable, *args):
L2638: def __iter__(self):
L2641: def __next__(self):
L2644: def __getitem__(self, key):
L2651: def _islice_helper(it, s):
L2759: def always_reversible(iterable):
L2777: def consecutive_groups(iterable, ordering=None):
L2827: def difference(iterable, func=sub, *, initial=None):
L2869: class SequenceView(Sequence):
L2899: def __init__(self, target):
L2904: def __getitem__(self, index):
L2907: def __len__(self):
L2910: def __repr__(self):
L2914: class seekable:
L3015: def __init__(self, iterable, maxlen=None):
L3023: def __iter__(self):
L3026: def __next__(self):
L3040: def __bool__(self):
L3047: def peek(self, default=_marker):
L3059: def elements(self):
L3062: def seek(self, index):
L3068: def relative_seek(self, count):
L3075: class run_length:
L3096: def encode(iterable):
L3100: def decode(iterable):
L3104: def exactly_n(iterable, n, predicate=bool):
L3122: def circular_shifts(iterable, steps=1):
L3152: def make_decorator(wrapping_func, result_index=0):
L3203: def decorator(*wrapping_args, **wrapping_kwargs):
L3204: def outer_wrapper(f):
L3205: def inner_wrapper(*args, **kwargs):
L3218: def map_reduce(iterable, keyfunc, valuefunc=None, reducefunc=None):
L3291: def rlocate(iterable, pred=bool, window_size=None):
L3334: def replace(iterable, pred, substitutes, count=None, window_size=1):
L3395: def partitions(iterable):
L3415: def set_partitions(iterable, k=None, min_size=None, max_size=None):
L3469: def set_partitions_helper(L, k):
L3496: class time_limited:
L3523: def __init__(self, limit_seconds, iterable):
L3531: def __iter__(self):
L3534: def __next__(self):

```

```

L3546: def only(iterable, default=None, too_long=None):
L3583: def _ichunk(iterator, n):
L3587: def generator():
L3595: def materialize_next(n=1):
L3613: def ichunked(iterable, n):
L3649: def iequals(*iterables):
L3669: def distinct_combinations(iterable, r):
L3709: def filter_except(validator, iterable, *exceptions):
L3733: def map_except(function, iterable, *exceptions):
L3754: def map_if(iterable, pred, func, func_else=None):
L3782: def _sample_unweighted(iterator, k, strict):
L3802: def _sample_weighted(iterator, k, weights, strict):
L3841: def _sample_counted(population, k, counts, strict):
L3845: def feed(i):
L3876: def sample(iterable, k, weights=None, *, counts=None, strict=False):
L3959: def is_sorted(iterable, key=None, reverse=False, strict=False):
L3991: class AbortThread(BaseException):
L3995: class callback_iter:
L4046: def __init__(self, func, callback_kwd='callback', wait_seconds=0.1):
L4058: def __enter__(self):
L4061: def __exit__(self, exc_type, exc_value, traceback):
L4065: def __iter__(self):
L4068: def __next__(self):
L4072: def done(self):
L4078: def result(self):
L4084: def _reader(self):
L4087: def callback(*args, **kwargs):
L4122: def windowed_complete(iterable, n):
L4162: def all_unique(iterable, key=None):
L4197: def nth_product(index, *args):
L4228: def nth_permutation(iterable, r, index):
L4272: def nth_combination_with_replacement(iterable, r, index):
L4318: def value_chain(*args):
L4352: def product_index(element, *args):
L4377: def combination_index(element, iterable):
L4420: def combination_with_replacement_index(element, iterable):
L4477: def permutation_index(element, iterable):
L4501: class countable:
L4519: def __init__(self, iterable):
L4523: def __iter__(self):
L4526: def __next__(self):
L4533: def chunked_even(iterable, n):
L4583: def zip_broadcast(*objects, scalar_types=(str, bytes), strict=False):
L4605: def is_scalar(obj):
L4639: def unique_in_window(iterable, n, key=None):
L4678: def duplicates_everseen(iterable, key=None):
L4708: def duplicates_justseen(iterable, key=None):
L4722: def classify_unique(iterable, key=None):
L4764: def minmax(iterable_or_value, *others, key=None, default=_marker):
L4841: def constrained_batches(
L4891: def gray_product(*iterables):

```



```

L4933: def partial_product(*iterables):
L4958: def takewhile_inclusive(predicate, iterable):
L4972: def outer_product(func, xs, ys, *args, **kwargs):
L5005: def iter_suppress(iterable, *exceptions):
L5028: def filter_map(func, iterable):
L5042: def powerset_of_sets(iterable):
L5060: def join_mappings(**field_to_map):
L5078: def _complex_sumprod(v1, v2):
L5092: def dft(xarr):
L5116: def idft(Xarr):
L5140: def doublestarmap(func, iterable):
L5158: def _nth_prime_bounds(n):
L5177: def nth_prime(n, *, approximate=False):
L5203: def argmin(iterable, *, key=None):
L5236: def argmax(iterable, *, key=None):
L5264: def extract(iterable, indices):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/more_itertools/recipes.py

```

L120: def take(n, iterable):
L136: def tabulate(function, start=0):
L154: def tail(n, iterable):
L170: def consume(iterator, n=None):
L210: def nth(iterable, n, default=None):
L223: def all_equal(iterable, key=None):
L249: def quantify(iterable, pred=bool):
L259: def pad_none(iterable):
L276: def ncycles(iterable, n):
L286: def dotproduct(vec1, vec2):
L299: def flatten(listOfLists):
L311: def repeatfunc(func, times=None, *args):
L338: def _pairwise(iterable):
L358: def pairwise(iterable):
L364: class UnequalIterablesError(ValueError):
L365: def __init__(self, details=None):
L375: def _zip_equal_generator(iterables):
L383: def _zip_equal(*iterables):
L399: def grouper(iterable, n, incomplete='fill', fillvalue=None):
L439: def roundrobin(*iterables):
L457: def partition(pred, iterable):
L485: def powerset(iterable):
L506: def unique_everseen(iterable, key=None):
L551: def unique_justseen(iterable, key=None):
L566: def unique(iterable, key=None, reverse=False):
L586: def iter_except(func, exception, first=None):
L615: def first_true(iterable, default=None, pred=None):

```

```

L635: def random_product(*args, repeat=1):
L655: def random_permutation(iterable, r=None):
L673: def random_combination(iterable, r):
L689: def random_combination_with_replacement(iterable, r):
L706: def nth_combination(iterable, r, index):
L748: def prepend(value, iterator):
L763: def convolve(signal, kernel):
L806: def before_and_after(predicate, it):
L825: def triplewise(iterable):
L841: def _sliding_window_islice(iterable, n):
L849: def _sliding_window_deque(iterable, n):
L858: def sliding_window(iterable, n):
L883: def subslices(iterable):
L897: def polynomial_from_roots(roots):
L919: def iter_index(iterable, value, start=0, stop=None):
L960: def sieve(n):
L981: def _batched(iterable, n, *, strict=False): # pragma: no cover
L1004: def batched(iterable, n, *, strict=False):
L1012: def transpose(it):
L1024: def _is_scalar(value, stringlike=(str, bytes)):
L1033: def _flatten_tensor(tensor):
L1047: def reshape(matrix, shape):
L1088: def matmul(m1, m2):
L1103: def _factor_pollard(n):
L1122: def factor(n):
L1155: def polynomial_eval(coefficients, x):
L1178: def sum_of_squares(it):
L1189: def polynomial_derivative(coefficients):
L1208: def totient(n):
L1249: def _shift_to_odd(n):
L1257: def _strong_probable_prime(n, base):
L1279: def is_prime(n):
L1327: def loops(n):
L1341: def multinomial(*counts):
L1386: def _running_median_minheap_and_maxheap(iterator): # pragma: no cover
L1402: def _running_median_minheap_only(iterator): # pragma: no cover
L1418: def _running_median_windowed(iterator, maxlen):
L1437: def running_median(iterable, *, maxlen=None):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/backports/tarfile/__init__.py

```

L159: def stn(s, length, encoding, errors):
L167: def nts(s, encoding, errors):
L175: def nti(s):
L195: def itn(n, digits=8, format=DEFAULT_FORMAT):
L225: def calc_chksums(buf):

```

```

L238: def copyfileobj(src, dst, length=None, exception=OSError, bufsize=None):
L263: def _safe_print(s):
L270: class TarError(Exception):
L273: class ExtractError(TarError):
L276: class ReadError(TarError):
L279: class CompressionError(TarError):
L282: class StreamError(TarError):
L285: class HeaderError(TarError):
L288: class EmptyHeaderError(HeaderError):
L291: class TruncatedHeaderError(HeaderError):
L294: class EOFHeaderError(HeaderError):
L297: class InvalidHeaderError(HeaderError):
L300: class SubsequentHeaderError(HeaderError):
L307: class _LowLevelFile:
L313: def __init__(self, name, mode):
L322: def close(self):
L325: def read(self, size):
L328: def write(self, s):
L331: class _Stream:
L343: def __init__(self, name, mode, comptype, fileobj, bufsize,
L414: def __del__(self):
L418: def _init_write_gz(self, compresslevel):
L435: def write(self, s):
L445: def __write(self, s):
L454: def close(self):
L476: def _init_read_gz(self):
L507: def tell(self):
L512: def seek(self, pos=0):
L525: def read(self, size):
L532: def _read(self, size):
L559: def __read(self, size):
L576: class _StreamProxy(object):
L581: def __init__(self, fileobj):
L585: def read(self, size):
L589: def getcomptype(self):
L599: def close(self):
L606: class _FileInFile(object):
L612: def __init__(self, fileobj, offset, size, name, blockinfo=None):
L637: def flush(self):
L641: def mode(self):
L644: def readable(self):
L647: def writable(self):
L650: def seekable(self):
L653: def tell(self):
L658: def seek(self, position, whence=io.SEEK_SET):
L674: def read(self, size=None):
L705: def readinto(self, b):
L710: def close(self):
L714: class ExFileObject(io.BufferedReader):
L716: def __init__(self, tarfile, tarinfo):
L727: class FilterError(TarError):

```

```

L730: class AbsolutePathError(FilterError):
L731: def __init__(self, tarinfo):
L735: class OutsideDestinationError(FilterError):
L736: def __init__(self, tarinfo, path):
L742: class SpecialFileError(FilterError):
L743: def __init__(self, tarinfo):
L747: class AbsoluteLinkError(FilterError):
L748: def __init__(self, tarinfo):
L752: class LinkOutsideDestinationError(FilterError):
L753: def __init__(self, tarinfo, path):
L759: def _get_filtered_attrs(member, dest_path, for_data=True):
L822: def fully_trusted_filter(member, dest_path):
L825: def tar_filter(member, dest_path):
L831: def data_filter(member, dest_path):
L850: class TarInfo(object):
L885: def __init__(self, name=""):
L910: def tarfile(self):
L919: def tarfile(self, tarfile):
L928: def path(self):
L933: def path(self, name):
L937: def linkpath(self):
L942: def linkpath(self, linkname):
L945: def __repr__(self):
L948: def replace(self, *,
L976: def get_info(self):
L1004: def tobuf(self, format=DEFAULT_FORMAT, encoding=ENCODING, errors="surrogateescape"):
L1021: def create_ustar_header(self, info, encoding, errors):
L1034: def create_gnu_header(self, info, encoding, errors):
L1048: def create_pax_header(self, info, encoding):
L1107: def create_pax_global_header(cls, pax_headers):
L1112: def _posix_split_name(self, name, encoding, errors):
L1129: def _create_header(info, format, encoding, errors):
L1171: def _create_payload(payload):
L1181: def _create_gnu_long_header(cls, name, type, encoding, errors):
L1198: def _create_pax_generic_header(cls, pax_headers, type, encoding):
L1249: def frombuf(cls, buf, encoding, errors):
L1312: def fromtarfile(cls, tarfile):
L1332: def _proc_member(self, tarfile):
L1345: def _proc_builtin(self, tarfile):
L1367: def _proc_gnulong(self, tarfile):
L1394: def _proc_sparse(self, tarfile):
L1422: def _proc_pax(self, tarfile):
L1522: def _proc_gnusparses_00(self, next, pax_headers, buf):
L1533: def _proc_gnusparses_01(self, next, pax_headers):
L1539: def _proc_gnusparses_10(self, next, pax_headers, tarfile):
L1555: def _apply_pax_info(self, pax_headers, encoding, errors):
L1578: def _decode_pax_field(self, value, encoding, fallback_encoding, fallback_errors):
L1586: def _block(self, count):
L1595: def isreg(self):
L1599: def isfile(self):
L1603: def isdir(self):

```

```

L1607: def issym(self):
L1611: def islnk(self):
L1615: def ischr(self):
L1619: def isblk(self):
L1623: def isfifo(self):
L1627: def issparse(self):
L1630: def isdev(self):
L1635: class TarFile(object):
L1663: def __init__(self, name=None, mode="r", fileobj=None, format=None,
L1777: def open(cls, name=None, mode="r", fileobj=None, bufsize=RECORDSIZE, **kwargs):
L1818: def not_compressed(comptype):
L1873: def taropen(cls, name, mode="r", fileobj=None, **kwargs):
L1881: def gzopen(cls, name, mode="r", fileobj=None, compresslevel=9, **kwargs):
L1914: def bz2open(cls, name, mode="r", fileobj=None, compresslevel=9, **kwargs):
L1942: def xzopen(cls, name, mode="r", fileobj=None, preset=None, **kwargs):
L1980: def close(self):
L2001: def getmember(self, name):
L2012: def getmembers(self):
L2022: def getnames(self):
L2028: def gettarinfo(self, name=None, arcname=None, fileobj=None):
L2127: def list(self, verbose=True, *, members=None):
L2170: def add(self, name, arcname=None, recursive=True, *, filter=None):
L2221: def addfile(self, tarinfo, fileobj=None):
L2249: def _get_filter_function(self, filter):
L2273: def extractall(self, path=".", members=None, *, numeric_owner=False,
L2318: def extract(self, member, path="", set_attrs=True, *, numeric_owner=False,
L2337: def _get_extract_tarinfo(self, member, filter_function, path):
L2360: def _extract_one(self, tarinfo, path, set_attrs, numeric_owner):
L2373: def _handle_nonfatal_error(self, e):
L2380: def _handle_fatal_error(self, e):
L2392: def extractfile(self, member):
L2424: def _extract_member(self, tarinfo, targetpath, set_attrs=True,
L2473: def mkdir(self, tarinfo, targetpath):
L2488: def makefile(self, tarinfo, targetpath):
L2504: def makeunknown(self, tarinfo, targetpath):
L2512: def makefifo(self, tarinfo, targetpath):
L2520: def makedev(self, tarinfo, targetpath):
L2538: def makelink(self, tarinfo, targetpath):
L2563: def chown(self, tarinfo, targetpath, numeric_owner):
L2597: def chmod(self, tarinfo, targetpath):
L2607: def utime(self, tarinfo, targetpath):
L2621: def next(self):
L2688: def _getmember(self, name, tarinfo=None, normalize=False):
L2728: def _load(self):
L2737: def _check(self, mode=None):
L2746: def _find_link_target(self, tarinfo):
L2765: def __iter__(self):
L2796: def _dbg(self, level, msg):
L2802: def __enter__(self):
L2806: def __exit__(self, type, value, traceback):
L2820: def is_tarfile(name):

```

```
L2841: def main():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/backports/tarfile/compat/py38.py

```
L6: def removesuffix(self, suffix):
L13: def removeprefix(self, prefix):
L20: def removesuffix(self, suffix):
L23: def removeprefix(self, prefix):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_text.py

```
L7: class FoldedCase(str):
L67: def __lt__(self, other):
L70: def __gt__(self, other):
L73: def __eq__(self, other):
L76: def __ne__(self, other):
L79: def __hash__(self):
L82: def __contains__(self, other):
L85: def in_(self, other):
L91: def lower(self):
L94: def index(self, sub):
L97: def split(self, splitter=' ', maxsplit=0):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_collections.py

```
L6: class FreezableDefaultDict(collections.defaultdict):
L21: def __missing__(self, key):
L24: def freeze(self):
L28: class Pair(typing.NamedTuple):
L33: def parse(cls, text):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_meta.py

```

L15: class PackageMetadata(Protocol):
L16: def __len__(self) -> int: ... # pragma: no cover
L18: def __contains__(self, item: str) -> bool: ... # pragma: no cover
L20: def __getitem__(self, key: str) -> str: ... # pragma: no cover
L22: def __iter__(self) -> Iterator[str]: ... # pragma: no cover
L25: def get(
L30: def get(self, name: str, failobj: _T) -> str | _T: ... # pragma: no cover
L34: def get_all(
L39: def get_all(self, name: str, failobj: _T) -> list[Any] | _T:
L45: def json(self) -> dict[str, str | list[str]]:
L51: class SimplePath(Protocol):
L56: def joinpath(
L60: def __truediv__(
L65: def parent(self) -> SimplePath: ... # pragma: no cover
L67: def read_text(self, encoding=None) -> str: ... # pragma: no cover
L69: def read_bytes(self) -> bytes: ... # pragma: no cover
L71: def exists(self) -> bool: ... # pragma: no cover

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_compat.py

```

L7: def install(cls):
L20: def disable_stdlib_finder():
L29: def matches(finder):
L38: class NullFinder:
L45: def find_spec(*args, **kwargs):
L49: def pypy_partial(val):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/__init__.py

```

L61: class PackageNotFoundError(ModuleNotFoundError):
L64: def __str__(self) -> str:
L68: def name(self) -> str: # type: ignore[override] # make readonly
L73: class Sectioned:
L115: def section_pairs(cls, text):
L123: def read(text, filter_=None):
L134: def valid(line: str):
L138: class _EntryPointMatch(types.SimpleNamespace):
L144: class EntryPoint:
L212: def __init__(self, name: str, value: str, group: str) -> None:
L216: def load(self) -> Any:
L226: def module(self) -> str:
L230: def attr(self) -> str:

```

```

L234: def extras(self) -> list[str]:
L238: def _match(self) -> _EntryPointMatch:
L249: def _for(self, dist):
L253: def matches(self, **params):
L278: def _disallow_dist(params):
L293: def _key(self):
L296: def __lt__(self, other):
L299: def __eq__(self, other):
L302: def __setattr__(self, name, value):
L305: def __repr__(self):
L311: def __hash__(self) -> int:
L315: class EntryPoints(tuple):
L322: def __getitem__(self, name: str) -> EntryPoint: # type: ignore[override] # Work with
str instead of int
L331: def __repr__(self):
L338: def select(self, **params) -> EntryPoints:
L346: def names(self) -> set[str]:
L353: def groups(self) -> set[str]:
L360: def _from_text_for(cls, text, dist):
L364: def _from_text(text):
L371: class PackagePath(pathlib.PurePosixPath):
L378: def read_text(self, encoding: str = 'utf-8') -> str:
L381: def read_binary(self) -> bytes:
L384: def locate(self) -> SimplePath:
L389: class FileHash:
L390: def __init__(self, spec: str) -> None:
L393: def __repr__(self) -> str:
L397: class Distribution(metaclass=abc.ABCMeta):
L409: def read_text(self, filename) -> str | None:
L432: def locate_file(self, path: str | os.PathLike[str]) -> SimplePath:
L450: def from_name(cls, name: str) -> Distribution:
L468: def discover(
L488: def _prefer_valid(dists: Iterable[Distribution]) -> Iterable[Distribution]:
L498: def at(path: str | os.PathLike[str]) -> Distribution:
L507: def _discover_resolvers():
L515: def metadata(self) -> _meta.PackageMetadata | None:
L538: def _assemble_message(text: str) -> _meta.PackageMetadata:
L545: def name(self) -> str:
L550: def _normalized_name(self):
L555: def version(self) -> str:
L560: def entry_points(self) -> EntryPoints:
L570: def files(self) -> list[PackagePath] | None:
L585: def make_file(name, hash=None, size_str=None):
L593: def make_files(lines):
L601: def skip_missing_files(package_paths):
L612: def _read_files_distinfo(self):
L619: def _read_files_egginfo_installed(self):
L647: def _read_files_egginfo_sources(self):
L663: def requires(self) -> list[str] | None:
L668: def _read_dist_info_reqs(self):
L671: def _read_egg_info_reqs(self):

```



```

L676: def _deps_from_requires_text(cls, source):
L680: def _convert_egg_info_reqs_to_simple_reqs(sections):
L691: def make_condition(name):
L694: def quoted_marker(section):
L702: def url_req_space(req):
L715: def origin(self):
L718: def _load_json(self, filename):
L728: class DistributionFinder(MetaPathFinder):
L736: class Context:
L765: def __init__(self, **kwargs):
L769: def path(self) -> list[str]:
L780: def find_distributions(self, context=Context()) -> Iterable[Distribution]:
L791: def _clear_after_fork(cached):
L804: class FastPath:
L822: def __new__(cls, root):
L825: def __init__(self, root):
L828: def joinpath(self, child):
L831: def children(self):
L838: def zip_children(self):
L848: def search(self, name):
L852: def mtime(self):
L858: def lookup(self, mtime):
L862: class Lookup:
L867: def __init__(self, path: FastPath):
L896: def search(self, prepared: Prepared):
L913: class Prepared:
L936: def __init__(self, name: str | None):
L944: def normalize(name):
L951: def legacy_normalize(name):
L958: def __bool__(self):
L963: class MetadataPathFinder(NullFinder, DistributionFinder):
L971: def find_distributions(
L986: def _search_paths(cls, name, paths):
L994: def invalidate_caches(cls) -> None:
L998: class PathDistribution(Distribution):
L999: def __init__(self, path: SimplePath) -> None:
L1006: def read_text(self, filename: str | os.PathLike[str]) -> str | None:
L1020: def locate_file(self, path: str | os.PathLike[str]) -> SimplePath:
L1024: def _normalized_name(self):
L1036: def _name_from_stem(stem):
L1053: def distribution(distribution_name: str) -> Distribution:
L1062: def distributions(**kwargs) -> Iterable[Distribution]:
L1070: def metadata(distribution_name: str) -> _meta.PackageMetadata | None:
L1079: def version(distribution_name: str) -> str:
L1098: def entry_points(**params) -> EntryPoints:
L1113: def files(distribution_name: str) -> list[PackagePath] | None:
L1122: def requires(distribution_name: str) -> list[str] | None:
L1132: def packages_distributions() -> Mapping[str, list[str]]:
L1149: def _top_level_declared(dist):
L1153: def _topmost(name: PackagePath) -> str | None:
L1161: def _get_toplevel_name(name: PackagePath) -> str:

```

```
L1185: def _top_level_inferred(dist):
L1188: def importable_name(name):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_itertools.py

```
L5: def unique_everseen(iterable, key=None):
L24: def always_iterable(obj, base_type=(str, bytes)):
L78: class bucket:
L114: def __init__(self, iterable, key, validator=None):
L120: def __contains__(self, value):
L133: def _get_values(self, value):
L159: def __iter__(self):
L167: def __getitem__(self, value):
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/diagnose.py

```
L6: def inspect(path):
L15: def run():
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_functools.py

```
L7: def method_cache(method, cache_wrapper=None):
L76: def wrapper(self, *args, **kwargs):
L90: def pass_none(func):
L101: def wrapper(param, *args, **kwargs):
L109: def noop(*args, **kwargs):
L121: def passthrough(func: Callable[..., object]) -> Callable[[_T], _T]:
L131: def wrapper(first: _T, *args, **kwargs) -> _T:
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_adapters.py

```
L9: class RawPolicy(email.policy.EmailPolicy):
L10: def fold(self, name, value):
```

```

L20: class Message(email.message.Message):
L78: def __new__(cls, orig: email.message.Message):
L83: def __init__(self, *args, **kwargs):
L87: def __iter__(self):
L90: def __getitem__(self, item):
L105: def _repair_headers(self):
L106: def redent(value):
L119: def as_string(self):
L123: def json(self):
L129: def transform(key):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/compat/py311.py

```

L7: def wrap(path): # pragma: no cover
L16: def relative_to(root, *, walk_up=False):

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/compat/py39.py

```

L18: def normalized_name(dist: Distribution) -> str | None:
L32: def ep_matches(ep: EntryPoint, **params) -> bool:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/annotated_types/test_cases.py

```

L15: class Case(NamedTuple):
L25: def cases() -> Iterable[Case]:
L147: class MyCustomGroupedMetadata(at.GroupedMetadata):
L148: def __iter__(self) -> Iterator[at.Predicate]:

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/annotated_types/__init__.py

```

L68: class SupportsGt(Protocol):
L69: def __gt__(self: T, __other: T) -> bool:
L73: class SupportsGe(Protocol):

```

```

L74: def __ge__(self: T, __other: T) -> bool:
L78: class SupportsLt(Protocol):
L79: def __lt__(self: T, __other: T) -> bool:
L83: class SupportsLe(Protocol):
L84: def __le__(self: T, __other: T) -> bool:
L88: class SupportsMod(Protocol):
L89: def __mod__(self: T, __other: T) -> T:
L93: class SupportsDiv(Protocol):
L94: def __div__(self: T, __other: T) -> T:
L98: class BaseMetadata:
L109: class Gt(BaseMetadata):
L120: class Ge(BaseMetadata):
L131: class Lt(BaseMetadata):
L142: class Le(BaseMetadata):
L153: class GroupedMetadata(Protocol):
L185: def __is_annotated_types_grouped_metadata__(self) -> Literal[True]:
L188: def __iter__(self) -> Iterator[object]:
L194: def __init_subclass__(cls, *args: Any, **kwargs: Any) -> None:
L200: def __iter__(self) -> Iterator[object]: # noqa: F811
L205: class Interval(GroupedMetadata):
L217: def __iter__(self) -> Iterator[BaseMetadata]:
L230: class MultipleOf(BaseMetadata):
L244: class MinLen(BaseMetadata):
L254: class MaxLen(BaseMetadata):
L264: class Len(GroupedMetadata):
L274: def __iter__(self) -> Iterator[BaseMetadata]:
L283: class Timezone(BaseMetadata):
L300: class Unit(BaseMetadata):
L323: class Predicate(BaseMetadata):
L346: def __repr__(self) -> str:
L359: class Not:
L362: def __call__(self, __v: Any) -> bool:
L413: class DocInfo: # type: ignore [no-redef]
L422: def doc(

```

Q_base appwrite/functions/validate_admin_writes/main.py

```

L25: def read_stdin():
L34: def make_client():
L47: def main():

```

archive/ui/ActiveSessionViewModelFactory.kt

```

L11: class ActiveSessionViewModelFactory(

```

archive/ui/SessionsViewModelFactory.kt

```
L10: class SessionsViewModelFactory(
```

archive/ui/ExtractionConfigScreen.kt

```
L20: fun ExtractionConfigScreen(
```

archive/ui/BaseAiViewModel.kt

```
L13: sealed class AiState {
L14: object Idle : AiState()
L15: object Loading : AiState()
L16: data class Success(val result: String) : AiState()
L17: data class Error(val message: String) : AiState()
L37: protected fun executeAiTask(
L62: fun resetAiState() {
L66: fun cancelCurrentAiTask() {
```

docs/generate_pdf.py

```
L6: class QbasePDF(FPDF):
L7: def header(self):
L17: def footer(self):
L23: def sanitize_text(text):
L27: def build_pdf(md_path, pdf_path):
```

core-auth/src/main/java/com/algorithmx/q_base/data/di/AuthModule.kt

```
L13: object AuthModule {
L17: fun provideAppwriteAccount(client: Client): Account = Account(client)
```

core-auth/src/main/java/com/algorithmx/q_base/data/auth/UserProfile.kt

```
L7: data class UserProfile(
```

core-auth/src/main/java/com/algorithmx/q_base/data/auth/ProfileRepository.kt

```
L14: class ProfileRepository @Inject constructor(
L21: private fun mapToUserProfile(map: Map<String, Any>): UserProfile {
L35: private fun userProfileToMap(profile: UserProfile): Map<String, Any> {
L48: suspend fun createOrUpdateProfile(
```

```

L94: suspend fun updateProfile(profile: UserProfile): Result<Unit> {
L107: private suspend fun saveProfile(profile: UserProfile, email: String) {
L129: suspend fun findUserByFriendCode(friendCode: String): Result<UserProfile?> {
L148: suspend fun syncUserProfile(userId: String) {
L219: private suspend fun generateUniqueFriendCode(): String {
L238: private suspend fun isFriendCodeUnique(friendCode: String): Boolean {
L251: private fun generateFriendCode(): String {
L259: suspend fun setupSecureBackup(userId: String, passphrase: String): Result<Unit> {
L277: suspend fun checkHasSecureBackup(userId: String): Boolean {
L287: suspend fun restoreSecureBackup(userId: String, passphrase: String): Result<Unit> {

```

core-auth/src/main/java/com/algorithmx/q_base/data/auth/ProfileCache.kt

```

L3: interface ProfileCache {
L4: suspend fun upsert(profile: UserProfile)

```

core-auth/src/main/java/com/algorithmx/q_base/data/auth/AuthRepository.kt

```

L23: data class AppwriteUser(
L31: class AuthRepository @Inject constructor(
L52: private fun saveUserToPrefs(user: AppwriteUser) {
L62: private fun getUserFromPrefs(): AppwriteUser? {
L71: private fun clearUserFromPrefs() {
L81: fun checkCurrentSession() {
L103: private fun mapAppwriteUser(user: User<*>, photoUrl: String? = null): AppwriteUser {
L116: private suspend fun fetchGooglePhotoUrl(): String? {
L153: suspend fun signInWithEmail(email: String, pass: String): Result<AppwriteUser> {
L168: suspend fun signUpWithEmail(email: String, pass: String, username: String, photoUrl: String? = null): Result<AppwriteUser> {
L184: suspend fun signInWithGoogle(activity: ComponentActivity): Result<AppwriteUser> {
L201: fun signOut() {

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/FirebaseAuthImpl.kt

```

L21: class FirebaseAuthImpl @Inject constructor(

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/CoreDatabase.kt

```

L5: enum class CoreQueryOperator {

```

```

L13: data class CoreQuery(
L19: interface CoreDatabase {
L20: suspend fun createDocument(collectionId: String, documentId: String, data: Map<String,
Any>): Result<Unit>
L21: suspend fun getDocument(collectionId: String, documentId: String): Result<Map<String,
Any>?>
L22: suspend fun updateDocument(collectionId: String, documentId: String, data: Map<String,
Any>): Result<Unit>
L23: suspend fun deleteDocument(collectionId: String, documentId: String): Result<Unit>
L24: suspend fun listDocuments(collectionId: String): Result<List<Map<String, Any>>>
L25: suspend fun queryDocuments(collectionId: String, queries: List<CoreQuery>):
Result<List<Map<String, Any>>>
L26: fun observeDocument(collectionId: String, documentId: String): Flow<Map<String, Any>?>
L27: fun observeCollection(collectionId: String): Flow<List<Map<String, Any>>>

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/Appwrite DatabaseImpl.kt

```

L19: class AppwriteDatabaseImpl @Inject constructor(
L30: private suspend fun invokeSuspendReflective(
L56: private fun mapRow(row: Any): Map<String, Any> {
L132: private fun mapRowList(rowList: Any): List<Map<String, Any>> {
L143: private fun mapDocument(doc: io.appwrite.models.Document<*>): Map<String, Any> {
L393: fun wrapValue(v: Any): List<Any> = if (v is List<*>) v.filterNotNull() else listOf(v)

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/Firebase DatabaseImpl.kt

```

L13: class FirebaseDatabaseImpl @Inject constructor(

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/Backend Module.kt

```

L16: annotation class FirebaseBackend
L20: annotation class AppwriteBackend
L24: object BackendModule {
L28: fun provideFirebaseAuth(): FirebaseAuth {
L35: fun provideFirebaseAuthImpl(
L45: fun provideFirebaseDatabaseImpl(
L54: fun provideAppwriteAuthImpl(
L64: fun provideAppwriteDatabaseImpl(
L74: fun provideActiveAuth(
L82: fun provideActiveDatabase(

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/CoreAuth.h.kt

```
L6: data class CoreUser(
L13: interface CoreAuth {
L17: suspend fun signInWithEmail(email: String, pass: String): Result<CoreUser>
L18: suspend fun signUpWithEmail(email: String, pass: String, username: String):
Result<CoreUser>
L19: suspend fun signInWithGoogle(activity: ComponentActivity): Result<CoreUser>
L20: suspend fun signOut(): Result<Unit>
L21: suspend fun checkCurrentSession(): Result<CoreUser?>
```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/AppwriteAuthImpl.kt

```
L18: class AppwriteAuthImpl @Inject constructor(
L37: private fun mapUser(user: User<*>): CoreUser {
```

core-auth/src/main/java/com/algorithmx/q_base/ui/components/AuthComponents.kt

```
L45: fun AuthFormSection(
L193: fun GoogleSignInButton(
L284: fun GoogleIconGraphic() {
```

.venv/lib/python3.12/site-packages/pip/__pip-runner__.py

```
L15: def version_str(version): # type: ignore
L36: class PipImportRedirectingFinder:
L38: def find_spec(self, fullname, path=None, target=None): # type: ignore
```

.venv/lib/python3.12/site-packages/pip/__init__.py

```
L6: def main(args: list[str] | None = None) -> int:
```

.venv/lib/python3.12/site-packages/pip/_internal/pyproject.py

```
L18: def _is_list_of_str(obj: Any) -> bool:
L22: def make_pyproject_path(unpacked_source_directory: str) -> str:
L31: def load_pyproject_toml(
```


.venv/lib/python3.12/site-packages/pip/_internal/build_env.py

```

L44: class ExtraEnviron(TypedDict, total=False):
L51: def _dedup(a: str, b: str) -> tuple[str] | tuple[str, str]:
L55: class _Prefix:
L56: def __init__(self, path: str) -> None:
L64: def get_runnable_pip() -> str:
L80: def _get_system_sitepackages() -> set[str]:
L100: class BuildEnvironmentInstaller(Protocol):
L106: def install(
L116: class SubprocessBuildEnvironmentInstaller:
L121: def __init__(
L131: def _deprecation_constraint_check(self) -> None:
L160: def install(
L266: class InprocessBuildEnvironmentInstaller:
L280: def __init__(
L320: def install(
L372: def _install_impl(self, requirements: Iterable[str], prefix: _Prefix) -> None:
L413: def _make_resolver(self) -> BaseResolver:
L437: class BuildEnvironment:
L440: def __init__(self, installer: BuildEnvironmentInstaller) -> None:
L495: def __enter__(self) -> None:
L516: def __exit__(
L528: def check_requirements(
L562: def install_requirements(
L578: class NoOpBuildEnvironment(BuildEnvironment):
L581: def __init__(self) -> None:
L584: def __enter__(self) -> None:
L587: def __exit__(
L595: def cleanup(self) -> None:
L598: def install_requirements(

```

.venv/lib/python3.12/site-packages/pip/_internal/configuration.py

```

L53: def _normalize_name(name: str) -> str:
L60: def _disassemble_key(name: str) -> list[str]:
L70: def get_configuration_files() -> dict[Kind, list[str]]:
L89: class Configuration:
L103: def __init__(self, isolated: bool, load_only: Kind | None = None) -> None:
L124: def load(self) -> None:
L130: def get_file_to_edit(self) -> str | None:
L139: def items(self) -> Iterable[tuple[str, Any]]:
L145: def get_value(self, key: str) -> Any:
L160: def set_value(self, key: str, value: Any) -> None:
L180: def unset_value(self, key: str) -> None:
L214: def save(self) -> None:
L238: def _ensure_have_load_only(self) -> None:
L244: def _dictionary(self) -> dict[str, dict[str, Any]]:
L255: def _load_config_files(self) -> None:

```

```

L278: def _load_file(self, variant: Kind, fname: str) -> RawConfigParser:
L289: def _construct_parser(self, fname: str) -> RawConfigParser:
L310: def _load_environment_vars(self) -> None:
L317: def _normalized_keys(
L331: def get_envIRON_vars(self) -> Iterable[tuple[str, str]]:
L340: def iter_config_files(self) -> Iterable[tuple[Kind, list[str]]]:
L372: def get_values_in_config(self, variant: Kind) -> dict[str, Any]:
L376: def _get_parser_to_modify(self) -> tuple[str, RawConfigParser]:
L390: def _mark_as_modified(self, fname: str, parser: RawConfigParser) -> None:
L395: def __repr__(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/wheel_builder.py

```

L34: def _contains_egg_info(s: str) -> bool:
L42: def _should_cache(
L73: def _get_cache_dir(
L89: def _verify_one(req: InstallRequirement, wheel_path: str) -> None:
L118: def _build_one(
L152: def _build_one_inside_env(
L204: def build(

```

.venv/lib/python3.12/site-packages/pip/_internal/exceptions.py

```

L44: def _is_kebab_case(s: str) -> bool:
L48: def _prefix_with_indent(
L65: class PipError(Exception):
L69: class DiagnosticPipError(PipError):
L82: def __init__(
L112: def __repr__(self) -> str:
L123: def __rich_console__(
L187: class ConfigurationError(PipError):
L191: class InstallationError(PipError):
L195: class FailedToPrepareCandidate(InstallationError):
L203: def __init__(
L212: class MissingPyProjectBuildRequires(DiagnosticPipError):
L217: def __init__(self, *, package: str) -> None:
L229: class InvalidPyProjectBuildRequires(DiagnosticPipError):
L234: def __init__(self, *, package: str, reason: str) -> None:
L246: class NoneMetadataError(PipError):
L255: def __init__(
L268: def __str__(self) -> str:
L274: class UserInstallationInvalid(InstallationError):
L277: def __str__(self) -> str:
L281: class InvalidSchemeCombination(InstallationError):
L282: def __str__(self) -> str:
L287: class DistributionNotFound(InstallationError):
L291: class RequirementsFileParseError(InstallationError):
L295: class BestVersionAlreadyInstalled(PipError):

```

```

L300: class BadCommand(PipError):
L304: class CommandError(PipError):
L308: class PreviousBuildDirError(PipError):
L312: class NetworkConnectionError(PipError):
L315: def __init__(
L336: def __str__(self) -> str:
L340: class InvalidWheelFilename(InstallationError):
L344: class UnsupportedWheel(InstallationError):
L348: class InvalidWheel(InstallationError):
L351: def __init__(self, location: str, name: str):
L355: def __str__(self) -> str:
L359: class MetadataInconsistent(InstallationError):
L367: def __init__(
L375: def __str__(self) -> str:
L382: class MetadataInvalid(InstallationError):
L385: def __init__(self, ireq: InstallRequirement, error: str) -> None:
L389: def __str__(self) -> str:
L393: class InstallationSubprocessError(DiagnosticPipError, InstallationError):
L398: def __init__(
L430: def __str__(self) -> str:
L434: class MetadataGenerationFailed(DiagnosticPipError, InstallationError):
L437: def __init__(
L449: def __str__(self) -> str:
L453: class HashErrors(InstallationError):
L456: def __init__(self) -> None:
L459: def append(self, error: HashError) -> None:
L462: def __str__(self) -> str:
L472: def __bool__(self) -> bool:
L476: class HashError(InstallationError):
L497: def body(self) -> str:
L509: def __str__(self) -> str:
L512: def _requirement_name(self) -> str:
L522: class VcsHashUnsupported(HashError):
L533: class DirectoryUrlHashUnsupported(HashError):
L544: class HashMissing(HashError):
L558: def __init__(self, gotten_hash: str) -> None:
L565: def body(self) -> str:
L586: class HashUnpinned(HashError):
L597: class HashMismatch(HashError):
L615: def __init__(self, allowed: dict[str, list[str]], got: dict[str, _Hash]) -> None:
L625: def body(self) -> str:
L628: def _hash_comparison(self) -> str:
L640: def hash_then_or(hash_name: str) -> chain[str]:
L655: class UnsupportedPythonVersion(InstallationError):
L660: class ConfigurationFileCouldNotBeLoaded(ConfigurationError):
L663: def __init__(
L674: def __str__(self) -> str:
L690: class ExternallyManagedEnvironment(DiagnosticPipError):
L702: def __init__(self, error: str | None) -> None:
L720: def _iter_externally_managed_error_keys() -> Iterator[str]:
L742: def from_config(

```

```

L763: class UninstallMissingRecord(DiagnosticPipError):
L766: def __init__(self, *, distribution: BaseDistribution) -> None:
L790: class LegacyDistutilsInstall(DiagnosticPipError):
L793: def __init__(self, *, distribution: BaseDistribution) -> None:
L805: class InvalidInstalledPackage(DiagnosticPipError):
L808: def __init__(
L835: class IncompleteDownloadError(DiagnosticPipError):
L841: def __init__(self, download: _FileDownload) -> None:
L869: class ResolutionTooDeepError(DiagnosticPipError):
L874: def __init__(self) -> None:
L889: class InstallWheelBuildError(DiagnosticPipError):
L892: def __init__(self, failed: list[InstallRequirement]) -> None:
L903: class InvalidEggFragment(DiagnosticPipError):
L906: def __init__(self, link: Link, fragment: str) -> None:
L926: class BuildDependencyInstallError(DiagnosticPipError):
L931: def __init__(

```

.venv/lib/python3.12/site-packages/pip/_internal/__init__.py

```

L10: def main(args: list[str] | None = None) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/cache.py

```

L27: def _hash_dict(d: dict[str, str]) -> str:
L33: class Cache:
L39: def __init__(self, cache_dir: str) -> None:
L44: def _get_cache_path_parts(self, link: Link) -> list[str]:
L77: def _get_candidates(self, link: Link, canonical_package_name: str) -> list[Any]:
L87: def get_path_for_link(self, link: Link) -> str:
L91: def get(
L103: class SimpleWheelCache(Cache):
L106: def __init__(self, cache_dir: str) -> None:
L109: def get_path_for_link(self, link: Link) -> str:
L129: def get(
L173: class EphemWheelCache(SimpleWheelCache):
L176: def __init__(self) -> None:
L185: class CacheEntry:
L186: def __init__(
L209: class WheelCache(Cache):
L216: def __init__(self, cache_dir: str) -> None:
L221: def get_path_for_link(self, link: Link) -> str:
L224: def get_ephem_path_for_link(self, link: Link) -> str:
L227: def get(
L238: def get_cache_entry(
L267: def record_download_origin(cache_dir: str, download_info: DirectUrl) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/self_outdated_check.p

y

```

L47: def _get_statefile_name(key: str) -> str:
L53: class SelfCheckState:
L54: def __init__(self, cache_dir: str) -> None:
L72: def key(self) -> str:
L75: def get(self, current_time: datetime.datetime) -> str | None:
L94: def set(self, pypi_version: str, current_time: datetime.datetime) -> None:
L133: class UpgradePrompt:
L137: def __rich__(self) -> Group:
L157: def _get_current_remote_pip_version(
L185: def _compute_upgrade_prompt(
L206: def pip_self_version_check_fetch(
L243: def pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/main.py

```

L4: def main(args: list[str] | None = None) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/list.py

```

L27: class _DistWithLatestInfo(BaseDistribution):
L43: class ListCommand(IndexGroupCommand):
L54: def add_options(self) -> None:
L140: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
L147: def _build_package_finder(
L170: def run(self, options: Values, args: list[str]) -> int:
L213: def get_outdated(
L222: def get_uptodate(
L231: def get_not_required(
L245: def iter_packages_latest_infos(
L251: def latest_info(
L282: def output_package_listing(
L305: def output_package_listing_columns(
L322: def format_for_columns(
L335: def wheel_build_tag(dist: BaseDistribution) -> str | None:
L382: def format_for_json(packages: _ProcessedDists, options: Values) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/install.py

```

L91: def _prevent_import_hook(name: str, args: tuple[Any, ...]) -> None:
L109: def _eagerly_import_modules() -> None:
L120: def _prevent_further_imports() -> None:
L134: def _arg_refers_to_pip(arg: str) -> bool:
L142: class InstallCommand(RequirementCommand):
L162: def add_options(self) -> None:

```

```

L358: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
L369: def run(self, options: Values, args: list[str]) -> int:
L604: def _handle_target_dir(
L658: def _determine_conflicts(
L670: def _warn_about_conflicts(
L721: def installed_packages_summary(
L745: def get_lib_location_guesses(
L763: def site_packages_writable(root: str | None, isolated: bool) -> bool:
L770: def decide_user_install(
L839: def create_os_error_message(

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/lock.py

```

L26: class LockCommand(RequirementCommand):
L48: def add_options(self) -> None:
L95: def run(self, options: Values, args: list[str]) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/uninstall.py

```

L25: class UninstallCommand(Command, SessionCommandMixin):
L40: def add_options(self) -> None:
L64: def run(self, options: Values, args: list[str]) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/index.py

```

L30: class IndexCommand(IndexGroupCommand):
L40: def add_options(self) -> None:
L60: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:
L65: def run(self, options: Values, args: list[str]) -> int:
L89: def _build_package_finder(
L116: def get_available_package_versions(self, options: Values, args: list[Any]) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/debug.py

```

L28: def show_value(name: str, value: Any) -> None:
L32: def show_sys_implementation() -> None:
L39: def create_vendor_txt_map() -> dict[str, str]:
L51: def get_module_from_module_name(module_name: str) -> ModuleType | None:
L62: def get_vendor_version_from_module(module_name: str) -> str | None:
L77: def show_actual_vendor_versions(vendor_txt_versions: dict[str, str]) -> None:
L98: def show_vendor_versions() -> None:
L106: def show_tags(options: Values) -> None:
L136: def ca_bundle_info(config: Configuration) -> str:
L153: class DebugCommand(Command):

```

```
L162: def add_options(self) -> None:
L167: def run(self, options: Values, args: list[str]) -> int:
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/help.py

```
L8: class HelpCommand(Command):
L15: def run(self, options: Values, args: list[str]) -> int:
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/freeze.py

```
L11: def _should_suppress_build_backends() -> bool:
L15: def _dev_pkgs() -> set[str]:
L24: class FreezeCommand(Command):
L35: def add_options(self) -> None:
L87: def run(self, options: Values, args: list[str]) -> int:
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/configuration.py

```
L24: class ConfigurationCommand(Command):
L60: def add_options(self) -> None:
L98: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:
L108: def run(self, options: Values, args: list[str]) -> int:
L146: def _determine_file(self, options: Values, need_value: bool) -> Kind | None:
L176: def list_values(self, options: Values, args: list[str]) -> None:
L183: def get_name(self, options: Values, args: list[str]) -> None:
L189: def set_name_value(self, options: Values, args: list[str]) -> None:
L195: def unset_name(self, options: Values, args: list[str]) -> None:
L201: def list_config_values(self, options: Values, args: list[str]) -> None:
L217: def print_config_file_values(self, variant: Kind, fname: str) -> None:
L225: def print_env_var_values(self) -> None:
L233: def open_in_editor(self, options: Values, args: list[str]) -> None:
L255: def _get_n_args(self, args: list[str], example: str, n: int) -> Any:
L269: def _save_configuration(self) -> None:
L280: def _determine_editor(self, options: Values) -> str:
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/search.py

```
L26: class TransformedHit(TypedDict):
L35: class SearchCommand(Command, SessionCommandMixin):
L42: def add_options(self) -> None:
L54: def run(self, options: Values, args: list[str]) -> int:
L70: def search(self, query: list[str], options: Values) -> list[dict[str, str]]:
L88: def transform_hits(hits: list[dict[str, str]]) -> list[TransformedHit]:
L116: def print_dist_installation_info(latest: str, dist: BaseDistribution | None) -> None:
```

```

L133: def get_installed_distribution(name: str) -> BaseDistribution | None:
L138: def print_results(
L177: def highest_version(versions: list[str]) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/__init__.py

```

L116: def create_command(name: str, **kwargs: Any) -> Command:
L128: def get_similar_commands(name: str) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/cache.py

```

L16: class CacheCommand(Command):
L40: def add_options(self) -> None:
L52: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:
L61: def run(self, options: Values, args: list[str]) -> int:
L87: def get_cache_dir(self, options: Values, args: list[str]) -> None:
L93: def get_cache_info(self, options: Values, args: list[str]) -> None:
L135: def list_cache_items(self, options: Values, args: list[str]) -> None:
L150: def format_for_human(self, files: list[str]) -> None:
L163: def format_for_abspath(self, files: list[str]) -> None:
L167: def remove_cache_items(self, options: Values, args: list[str]) -> None:
L218: def purge_cache(self, options: Values, args: list[str]) -> None:
L224: def _cache_dir(self, options: Values, subdir: str) -> str:
L227: def _find_http_files(self, options: Values) -> list[str]:
L234: def _find_wheels(self, options: Values, pattern: str) -> list[str]:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/completion.py

```

L81: class CompletionCommand(Command):
L86: def add_options(self) -> None:
L122: def run(self, options: Values, args: list[str]) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/show.py

```

L20: def normalize_project_url_label(label: str) -> str:
L27: class ShowCommand(Command):
L38: def add_options(self) -> None:
L50: def run(self, options: Values, args: list[str]) -> int:
L64: class _PackageInfo(NamedTuple):
L85: def search_packages_info(query: list[str]) -> Generator[_PackageInfo, None, None]:
L102: def _get_requiring_packages(current_dist: BaseDistribution) -> Iterator[str]:
L178: def print_results(

```


.venv/lib/python3.12/site-packages/pip/_internal/commands/hash.py

```

L14: class HashCommand(Command):
L25: def add_options(self) -> None:
L39: def run(self, options: Values, args: list[str]) -> int:
L52: def _hash_of_file(path: str, algorithm: str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/download.py

```

L16: class DownloadCommand(RequirementCommand):
L36: def add_options(self) -> None:
L78: def run(self, options: Values, args: list[str]) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/inspect.py

```

L19: class InspectCommand(Command):
L28: def add_options(self) -> None:
L48: def run(self, options: Values, args: list[str]) -> int:
L65: def _dist_to_dict(self, dist: BaseDistribution) -> dict[str, Any]:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/check.py

```

L18: class CheckCommand(Command):
L25: def run(self, options: Values, args: list[str]) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/wheel.py

```

L22: class WheelCommand(RequirementCommand):
L42: def add_options(self) -> None:
L94: def run(self, options: Values, args: list[str]) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/link.py

```

L40: class LinkHash:
L64: def __post_init__(self) -> None:
L69: def find_hash_url_fragment(cls, url: str) -> LinkHash | None:
L77: def as_dict(self) -> dict[str, str]:
L80: def as_hashes(self) -> Hashes:
L84: def is_hash_allowed(self, hashes: Hashes | None) -> bool:
L94: class MetadataFile:
L99: def __post_init__(self) -> None:
L104: def supported_hashes(hashes: dict[str, str] | None) -> dict[str, str] | None:

```

```

L115: def _clean_url_path_part(part: str) -> str:
L123: def _clean_file_url_path(part: str) -> str:
L144: def _clean_url_path(path: str, is_local_path: bool) -> str:
L166: def _ensure_quoted_url(url: str) -> str:
L185: def _absolute_link_url(base_url: str, url: str) -> str:
L197: class Link:
L214: def __init__(
L283: def from_json(
L340: def from_element(
L391: def __str__(self) -> str:
L401: def __repr__(self) -> str:
L404: def __hash__(self) -> int:
L407: def __eq__(self, other: Any) -> bool:
L412: def __lt__(self, other: Any) -> bool:
L418: def url(self) -> str:
L422: def redacted_url(self) -> str:
L426: def filename(self) -> str:
L440: def file_path(self) -> str:
L444: def scheme(self) -> str:
L448: def netloc(self) -> str:
L455: def path(self) -> str:
L458: def splitext(self) -> tuple[str, str]:
L462: def ext(self) -> str:
L466: def url_without_fragment(self) -> str:
L477: def _egg_fragment(self) -> str | None:
L493: def subdirectory_fragment(self) -> str | None:
L499: def metadata_link(self) -> Link | None:
L508: def as_hashes(self) -> Hashes:
L512: def hash(self) -> str | None:
L516: def hash_name(self) -> str | None:
L520: def show_url(self) -> str:
L524: def is_file(self) -> bool:
L527: def is_existing_dir(self) -> bool:
L531: def is_wheel(self) -> bool:
L535: def is_vcs(self) -> bool:
L541: def is_yanked(self) -> bool:
L545: def has_hash(self) -> bool:
L548: def is_hash_allowed(self, hashes: Hashes | None) -> bool:
L557: class _CleanResult(NamedTuple):
L589: def _clean_link(link: Link) -> _CleanResult:
L616: def links_equivalent(link1: Link, link2: Link) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/candidate.py

```

L10: class InstallationCandidate:
L17: def __init__(self, name: str, version: str, link: Link) -> None:
L22: def __str__(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/direct_url.py

```

L30: class DirectUrl(PackagingDirectUrl):
L31: def to_dict_compat(self) -> dict[str, Any]:
L35: def from_json(cls, s: str) -> DirectUrl:
L38: def to_json(self) -> str:
L41: def is_local_editable(self) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/index.py

```

L4: class PackageIndex:
L9: def __init__(self, url: str, file_storage_domain: str) -> None:
L21: def _url_for_path(self, path: str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/search_scope.py

```

L18: class SearchScope:
L28: def create(
L69: def get_formatted_locations(self) -> str:
L104: def get_index_urls_locations(self, project_name: str) -> list[str]:
L111: def mkurl_pypi_url(url: str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/format_control.py

```

L8: class FormatControl:
L13: def __init__(
L26: def __eq__(self, other: object) -> bool:
L35: def __repr__(self) -> str:
L39: def handle_mutual_excludes(value: str, target: set[str], other: set[str]) -> None:
L61: def get_allowed_formats(self, canonical_name: str) -> frozenset[str]:
L73: def disallow_binaries(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/target_python.py

```

L11: class TargetPython:
L28: def __init__(
L69: def format_given(self) -> str:
L89: def get_sorted_tags(self) -> list[Tag]:
L114: def get_unsorted_tags(self) -> set[Tag]:

```

.venv/lib/python3.12/site-packages/pip/_internal/models/installation_report.py

```
L10: class InstallationReport:
L11: def __init__(self, install_requirements: Sequence[InstallRequirement]):
L15: def _install_req_to_dict(cls, ireq: InstallRequirement) -> dict[str, Any]:
L43: def to_dict(self) -> dict[str, Any]:
```

.venv/lib/python3.12/site-packages/pip/_internal/models/selection_prefs.py

```
L10: class SelectionPreferences:
```

.venv/lib/python3.12/site-packages/pip/_internal/models/scheme.py

```
L14: class Scheme:
```

.venv/lib/python3.12/site-packages/pip/_internal/models/wheel.py

```
L18: class Wheel:
L21: def __init__(self, filename: str) -> None:
L32: def get_formatted_file_tags(self) -> list[str]:
L36: def support_index_min(self, tags: list[Tag]) -> int:
L54: def find_most_preferred_tag(
L75: def supported(self, tags: Iterable[Tag]) -> bool:
```

.venv/lib/python3.12/site-packages/pip/_internal/models/release_control.py

```
L11: class ReleaseControl:
L20: def handle_mutual_excludes(
L59: def get_ordered_args(self) -> list[tuple[str, str]]:
L74: def allows_prereleases(self, canonical_name: NormalizedName) -> bool | None:
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/compat.py

```
L16: def has_tls() -> bool:
L29: def get_path_uid(path: str) -> int:
L62: def open_text_resource(
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/entrypoints.py

```
L24: def _wrapper(args: list[str] | None = None) -> int:
L47: def get_best_invocation_for_this_pip() -> str:
L74: def get_best_invocation_for_this_python() -> str:
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/datetime.py

```
L7: def today_is_later_than(year: int, month: int, day: int) -> bool:
L14: def parse_iso_datetime(isodate: str) -> datetime.datetime:
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/urls.py

```
L9: def path_to_url(path: str) -> str:
L19: def url_to_path(url: str) -> str:
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/_jaraco_text.py

```
L36: def _nonblank(str):
L41: def yield_lines(iterable):
L60: def _(text):
L64: def drop_comment(line):
L79: def join_continuation(lines):
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/appdirs.py

```
L15: def user_cache_dir(appname: str) -> str:
L19: def _macos_user_config_dir(appname: str, roaming: bool = True) -> str:
L33: def user_config_dir(appname: str, roaming: bool = True) -> str:
L42: def site_config_dirs(appname: str) -> list[str]:
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/filesystem.py

```
L19: def check_path_owner(path: str) -> bool:
L47: def adjacent_tmp_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
L76: def test_writable_dir(path: str) -> bool:
L94: def _test_writable_dir_win(path: str) -> bool:
L122: def find_files(path: str, pattern: str) -> list[str]:
L132: def file_size(path: str) -> int | float:
L139: def format_file_size(path: str) -> str:
L143: def directory_size(path: str) -> int | float:
L152: def format_directory_size(path: str) -> str:
L156: def copy_directory_permissions(directory: str, target_file: BinaryIO) -> None:
L168: def _subdirs_without_generic(
L192: def subdirs_without_files(path: str) -> Generator[Path]:
L197: def subdirs_without_wheels(path: str) -> Generator[Path]:
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/retry.py

```

L14: def retry(
L28: def wrapper(func: Callable[P, T]) -> Callable[P, T]:
L31: def retry_wrapped(*args: P.args, **kwargs: P.kwargs) -> T:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/logging.py

```

L40: class BrokenStdoutLoggingError(Exception):
L46: def _is_broken_pipe_error(exc_class: type[BaseException], exc: BaseException) -> bool:
L60: def capture_logging() -> Generator[StringIO, None, None]:
L92: def indent_log(num: int = 2) -> Generator[None, None, None]:
L106: def get_indentation() -> int:
L110: class IndentingFormatter(logging.Formatter):
L113: def __init__(
L128: def get_message_start(self, formatted: str, levelno: int) -> str:
L144: def format(self, record: logging.LogRecord) -> str:
L162: class IndentedRenderable:
L166: def __rich_console__(
L177: class PipConsole(Console):
L178: def on_broken_pipe(self) -> None:
L184: def get_console(*, stderr: bool = False) -> Console:
L193: class RichPipStreamHandler(RichHandler):
L196: def __init__(self, console: Console) -> None:
L206: def emit(self, record: logging.LogRecord) -> None:
L234: def handleError(self, record: logging.LogRecord) -> None:
L253: class BetterRotatingFileHandler(logging.handlers.RotatingFileHandler):
L254: def _open(self) -> TextIOWrapper:
L259: class MaxLevelFilter(Filter):
L260: def __init__(self, level: int) -> None:
L263: def filter(self, record: logging.LogRecord) -> bool:
L267: class ExcludeLoggerFilter(Filter):
L272: def filter(self, record: logging.LogRecord) -> bool:
L278: def setup_logging(verbosity: int, no_color: bool, user_log_file: str | None) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/unpacking.py

```

L45: def current_umask() -> int:
L52: def split_leading_dir(path: str) -> list[str]:
L64: def has_leading_dir(paths: Iterable[str]) -> bool:
L79: def is_within_directory(directory: str, target: str) -> bool:
L90: def _get_default_mode_plus_executable() -> int:
L94: def set_extracted_file_to_default_mode_plus_executable(path: str) -> None:
L102: def zip_item_is_executable(info: ZipInfo) -> bool:
L109: def unzip_file(filename: str, location: str, flatten: bool = True) -> None:
L155: def untar_file(filename: str, location: str) -> None:
L206: def pip_filter(member: tarfile.TarInfo, path: str) -> tarfile.TarInfo:

```

```

L251: def is_symlink_target_in_tar(tar: tarfile.TarFile, tarinfo: tarfile.TarInfo) -> bool:
L265: def _untar_without_filter(
L334: def unpack_file(
L348: def _unzip() -> None:
L351: def _untar() -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/subprocess.py

```

L20: def make_command(*args: str | HiddenText | CommandArgs) -> CommandArgs:
L37: def format_command_args(args: list[str] | CommandArgs) -> str:
L52: def reveal_command_args(args: list[str] | CommandArgs) -> list[str]:
L59: def call_subprocess(
L227: def runner_with_spinner_message(message: str) -> Callable[..., None]:
L234: def runner(

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/compatibility_tag s.py

```

L23: def version_info_to_nodot(version_info: tuple[int, ...]) -> str:
L28: def _mac_platforms(arch: str) -> list[str]:
L48: def _ios_platforms(arch: str) -> list[str]:
L68: def _android_platforms(arch: str) -> list[str]:
L78: def _custom_manylinux_platforms(arch: str) -> list[str]:
L99: def _get_custom_platforms(arch: str) -> list[str]:
L114: def _expand_allowed_platforms(platforms: list[str] | None) -> list[str] | None:
L131: def _get_python_version(version: str) -> PythonVersion:
L138: def _get_custom_interpreter(
L148: def get_supported(

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/glibc.py

```

L7: def glibc_version_string() -> str | None:
L12: def glibc_version_string_confstr() -> str | None:
L32: def glibc_version_string_ctypes() -> str | None:
L92: def libc_ver() -> tuple[str, str]:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/virtualenv.py

```

L15: def _running_under_venv() -> bool:
L23: def _running_under_legacy_virtualenv() -> bool:
L32: def running_under_virtualenv() -> bool:
L37: def _get_pyvenv_cfg_lines() -> list[str] | None:
L52: def _no_global_under_venv() -> bool:
L81: def _no_global_under_legacy_virtualenv() -> bool:
L95: def virtualenv_no_global() -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/deprecation.py

```

L18: class PipDeprecationWarning(Warning):
L26: def _showwarning(
L49: def install_warning_logger() -> None:
L60: def deprecated(

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/filetypes.py

```

L19: def is_archive_file(name: str) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/egg_link.py

```

L19: def _egg_link_names(raw_name: str) -> list[str]:
L34: def egg_link_path_from_sys_path(raw_name: str) -> str | None:
L47: def egg_link_path_from_location(raw_name: str) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/hashes.py

```

L24: class Hashes:
L30: def __init__(self, hashes: dict[str, list[str]] | None = None) -> None:
L42: def __and__(self, other: Hashes) -> Hashes:
L62: def digest_count(self) -> int:
L65: def is_hash_allowed(self, hash_name: str, hex_digest: str) -> bool:
L69: def check_against_chunks(self, chunks: Iterable[bytes]) -> None:
L92: def _raise(self, gots: dict[str, _Hash]) -> NoReturn:
L95: def check_against_file(self, file: BinaryIO) -> None:
L103: def check_against_path(self, path: str) -> None:
L107: def has_one_of(self, hashes: Mapping[str, str]) -> bool:
L114: def __bool__(self) -> bool:
L118: def __eq__(self, other: object) -> bool:
L123: def __hash__(self) -> int:
L135: class MissingHashes(Hashes):
L143: def __init__(self) -> None:
L149: def _raise(self, gots: dict[str, _Hash]) -> NoReturn:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/temp_dir.py

```

L38: def global_tempdir_manager() -> Generator[None, None, None]:
L48: class TempDirectoryTypeRegistry:
L51: def __init__(self) -> None:
L54: def set_delete(self, kind: str, value: bool) -> None:
L60: def get_delete(self, kind: str) -> bool:
L71: def tempdir_registry() -> Generator[TempDirectoryTypeRegistry, None, None]:
L84: class _Default:

```



```

L91: class TempDirectory:
L112: def __init__(
L148: def path(self) -> str:
L152: def __repr__(self) -> str:
L155: def __enter__(self: _T) -> _T:
L158: def __exit__(self, exc: Any, value: Any, tb: Any) -> None:
L169: def _create(self, kind: str) -> str:
L179: def cleanup(self) -> None:
L187: def onerror(
L224: class AdjacentTempDirectory(TempDirectory):
L246: def __init__(self, original: str, delete: bool | None = None) -> None:
L251: def _generate_names(cls, name: str) -> Generator[str, None, None]:
L276: def _create(self, kind: str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/pylock.py

```

L32: def _pylock_package_from_install_requirement(
L116: def pylock_from_install_requirements(
L135: def _is_url(s: str) -> bool:
L139: def is_valid_pylock_filename(filename: str) -> bool:
L147: def _package_dist_url(
L177: def package_vcs_requirement_url(
L192: def package_archive_requirement_url(
L208: def package_directory_requirement_url(
L227: def package_sdist_requirement_url(
L233: def package_wheel_requirement_url(
L239: def _get_pylock_path_or_url_content(path_or_url: str, session: PipSession) -> str:
L255: def select_from_pylock_path_or_url(

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/wheel.py

```

L18: def parse_wheel(wheel_zip: ZipFile, name: str) -> tuple[str, Message]:
L36: def wheel_dist_info_dir(source: ZipFile, name: str) -> str:
L67: def read_wheel_metadata_file(source: ZipFile, path: str) -> bytes:
L76: def wheel_metadata(source: ZipFile, dist_info_dir: str) -> Message:
L95: def wheel_version(wheel_data: Message) -> tuple[int, ...]:
L111: def check_compatibility(version: tuple[int, ...], name: str) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/misc.py

```

L70: def get_pip_version() -> str:
L77: def normalize_version_info(py_version_info: tuple[int, ...]) -> tuple[int, int, int]:
L96: def ensure_dir(path: str) -> None:
L106: def get_prog() -> str:
L120: def rmtree(dir: str, ignore_errors: bool = False, onexc: OnExc | None = None) -> None:
L133: def _onerror_ignore(*_args: Any) -> None:
L137: def _onerror_reraise(*_args: Any) -> None:

```

```

L141: def rmtree_errorhandler(
L182: def display_path(path: str) -> str:
L193: def backup_dir(dir: str, ext: str = ".bak") -> str:
L204: def ask_path_exists(message: str, options: Iterable[str]) -> str:
L211: def _check_no_input(message: str) -> None:
L219: def ask(message: str, options: Iterable[str]) -> str:
L234: def ask_input(message: str) -> str:
L240: def ask_password(message: str) -> str:
L246: def strtobool(val: str) -> int:
L262: def format_size(bytes: float) -> str:
L273: def tabulate(rows: Iterable[Iterable[Any]]) -> tuple[list[str], list[int]]:
L287: def is_installable_dir(path: str) -> bool:
L304: def read_chunks(
L315: def normalize_path(path: str, resolve_symlinks: bool = True) -> str:
L328: def splitext(path: str) -> tuple[str, str]:
L337: def renames(old: str, new: str) -> None:
L354: def is_local(path: str) -> bool:
L368: def write_output(msg: Any, *args: Any) -> None:
L372: class StreamWrapper(StringIO):
L376: def from_stream(cls, orig_stream: TextIO) -> StreamWrapper:
L384: def encoding(self) -> str: # type: ignore
L389: def enum(*sequential: Any, **named: Any) -> type[Any]:
L396: def build_netloc(host: str, port: int | None) -> str:
L408: def build_url_from_netloc(netloc: str, scheme: str = "https") -> str:
L418: def parse_netloc(netloc: str) -> tuple[str | None, int | None]:
L427: def split_auth_from_netloc(netloc: str) -> NetlocTuple:
L456: def redact_netloc(netloc: str) -> str:
L476: def _transform_url(
L496: def _get_netloc(netloc: str) -> NetlocTuple:
L500: def _redact_netloc(netloc: str) -> tuple[str]:
L504: def split_auth_netloc_from_url(
L516: def remove_auth_from_url(url: str) -> str:
L523: def redact_auth_from_url(url: str) -> str:
L528: def redact_auth_from_requirement(req: Requirement) -> str:
L536: class HiddenText:
L540: def __repr__(self) -> str:
L543: def __str__(self) -> str:
L546: def __eq__(self, other: object) -> bool:
L560: def hide_value(value: str) -> HiddenText:
L564: def hide_url(url: str) -> HiddenText:
L569: def protect_pip_from_modification_on_windows(modifying_pip: bool) -> None:
L595: def check_externally_managed() -> None:
L610: def is_console_interactive() -> bool:
L615: def hash_file(path: str, blocksize: int = 1 << 20) -> tuple[Any, int]:
L627: def pairwise(iterable: Iterable[Any]) -> Iterator[tuple[Any, Any]]:
L638: def partition(
L651: class ConfiguredBuildBackendHookCaller(BuildBackendHookCaller):
L652: def __init__(
L666: def build_wheel(
L677: def build_sdist(
L685: def build_editable(

```

```

L696: def get_requires_for_build_wheel(
L702: def get_requires_for_build_sdist(
L708: def get_requires_for_build_editable(
L714: def prepare_metadata_for_build_wheel(
L727: def prepare_metadata_for_build_editable(
L741: def warn_if_run_as_root() -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/direct_url_helpers.py

```

L9: def direct_url_as_pep440_direct_reference(direct_url: DirectUrl, name: str) -> str:
L36: def direct_url_for_editable(source_dir: str) -> DirectUrl:
L43: def direct_url_from_link(

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/packaging.py

```

L13: def check_requires_python(
L37: def get_requirement(req_string: str) -> Requirement:

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/_log.py

```

L16: class VerboseLogger(logging.Logger):
L22: def verbose(self, msg: str, *args: Any, **kwargs: Any) -> None:
L26: def getLogger(name: str) -> VerboseLogger:
L31: def init_logging() -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/operations/freeze.py

```

L25: class _EditableInfo(NamedTuple):
L30: def freeze(
L151: def _format_as_name_version(dist: BaseDistribution) -> str:
L161: def _get_editable_info(dist: BaseDistribution) -> _EditableInfo:
L228: class FrozenRequirement:
L235: def canonical_name(self) -> NormalizedName:
L239: def from_dist(cls, dist: BaseDistribution) -> FrozenRequirement:
L255: def __str__(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/operations/prepare.py

```

L65: def _get_prepared_distribution(
L83: def unpack_vcs_link(link: Link, location: str, verbosity: int) -> None:
L90: class File:
L94: def __post_init__(self) -> None:
L104: def get_http_url(

```

```

L128: def get_file_url(
L152: def unpack_url(
L195: def _check_download_dir(
L225: class RequirementPreparer:
L228: def __init__(
L288: def _log_preparing_link(self, req: InstallRequirement) -> None:
L315: def _ensure_link_req_src_dir(
L338: def _get_linked_req_hashes(self, req: InstallRequirement) -> Hashes:
L370: def _fetch_metadata_only(
L389: def _fetch_metadata_using_link_data_attr(
L430: def _fetch_metadata_using_lazy_wheel(
L459: def _complete_partial_requirements(
L500: def prepare_linked_requirement(
L544: def prepare_linked_requirements_more(
L574: def _prepare_linked_requirement(
L670: def save_linked_requirement(self, req: InstallRequirement) -> None:
L696: def prepare_editable_requirement(
L729: def prepare_installed_requirement(

```

.venv/lib/python3.12/site-packages/pip/_internal/operations/check.py

```

L28: class PackageDetails(NamedTuple):
L44: def create_package_set_from_installed() -> tuple[PackageSet, bool]:
L61: def check_package_set(
L106: def check_install_conflicts(to_install: list[InstallRequirement]) -> ConflictDetails:
L126: def check_unsupported(
L142: def _simulate_installation_of(
L161: def _create_whitelist(

```

.venv/lib/python3.12/site-packages/pip/_internal/operations/install/wheel.py

```

L57: class File(Protocol):
L62: def save(self) -> None:
L72: def rehash(path: str, blocksize: int = 1 << 20) -> tuple[str, str]:
L79: def csv_io_kwargs(mode: str) -> dict[str, Any]:
L86: def fix_script(path: str) -> bool:
L106: def wheel_root_is_purelib(metadata: Message) -> bool:
L110: def get_entrypoints(dist: BaseDistribution) -> tuple[dict[str, str], dict[str, str]]:
L121: def message_about_scripts_not_on_PATH(scripts: Sequence[str]) -> str | None:
L193: def _normalized_outrows(
L219: def _record_to_fs_path(record_path: RecordPath, lib_dir: str) -> str:
L223: def _fs_to_record_path(path: str, lib_dir: str) -> RecordPath:
L233: def get_csv_rows_for_installed(
L265: def get_console_script_specs(console: dict[str, str]) -> list[str]:
L340: class ZipBackedFile:
L341: def __init__(
L349: def _getinfo(self) -> ZipInfo:

```

```

L352: def save(self) -> None:
L378: class ScriptFile:
L379: def __init__(self, file: File) -> None:
L385: def save(self) -> None:
L390: class MissingCallableSuffix(InstallationError):
L391: def __init__(self, entry_point: str) -> None:
L400: def _raise_for_invalid_entrpoint(specification: str) -> None:
L406: class PipScriptMaker(ScriptMaker):
L419: def make(
L426: def _install_wheel( # noqa: C901, PLR0915 function is too long
L466: def record_installed(
L475: def is_dir_path(path: RecordPath) -> bool:
L478: def assert_no_path_traversal(dest_dir_path: str, target_path: str) -> None:
L488: def root_scheme_file_maker(
L491: def make_root_scheme_file(record_path: RecordPath) -> File:
L499: def data_scheme_file_maker(
L504: def make_data_scheme_file(record_path: RecordPath) -> File:
L533: def is_data_scheme_path(path: RecordPath) -> bool:
L543: def is_script_scheme_path(path: RecordPath) -> bool:
L562: def is_entrpoint_wrapper(file: File) -> bool:
L597: def pyc_source_file_paths() -> Generator[str, None, None]:
L610: def pyc_output_path(path: str) -> str:
L666: def _generate_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
L716: def req_error_context(req_description: str) -> Generator[None, None, None]:
L724: def install_wheel(

```

.venv/lib/python3.12/site-packages/pip/_internal/locations/_distutils.py

```

L36: def distutils_scheme(
L116: def get_scheme(
L151: def get_bin_prefix() -> str:
L168: def get_purelib() -> str:
L172: def get_platlib() -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/locations/base.py

```

L20: def get_major_minor_version() -> str:
L28: def change_root(new_root: str, pathname: str) -> str:
L56: def get_src_prefix() -> str:
L81: def is_osx_framework() -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/locations/__init__.py

```

L45: def _should_use_sysconfig() -> bool:
L75: def _looks_like_bpo_44860() -> bool:
L89: def _looks_like_red_hat_patched_platlib_purelib(scheme: dict[str, str]) -> bool:
L100: def _looks_like_red_hat_lib() -> bool:

```

```

L115: def _looks_like_debian_scheme() -> bool:
L123: def _looks_like_red_hat_scheme() -> bool:
L143: def _looks_like_slackware_scheme() -> bool:
L159: def _looks_like_msys2_mingw_scheme() -> bool:
L177: def _warn_mismatched(old: pathlib.Path, new: pathlib.Path, *, key: str) -> None:
L187: def _warn_if_mismatch(old: pathlib.Path, new: pathlib.Path, *, key: str) -> bool:
L195: def _log_context(
L213: def get_scheme(
L379: def get_bin_prefix() -> str:
L390: def get_bin_user() -> str:
L394: def _looks_like_deb_system_dist_packages(value: str) -> bool:
L411: def get_purelib() -> str:
L425: def get_platlib() -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/locations/_sysconfig.py

```

L33: def _should_use_osx_framework_prefix() -> bool:
L59: def _infer_prefix() -> str:
L90: def _infer_user() -> str:
L105: def _infer_home() -> str:
L128: def get_scheme(
L206: def get_bin_prefix() -> str:
L213: def get_purelib() -> str:
L217: def get_platlib() -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/base.py

```

L44: class BaseEntryPoint(Protocol):
L46: def name(self) -> str:
L50: def value(self) -> str:
L54: def group(self) -> str:
L58: def _convert_installed_files_path(
L88: class RequiresEntry(NamedTuple):
L94: class BaseDistribution(Protocol):
L96: def from_directory(cls, directory: str) -> BaseDistribution:
L104: def from_metadata_file_contents(
L122: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:
L135: def __repr__(self) -> str:
L138: def __str__(self) -> str:
L142: def location(self) -> str | None:
L156: def editable_project_location(self) -> str | None:
L178: def installed_location(self) -> str | None:
L191: def info_location(self) -> str | None:
L207: def installed_by_distutils(self) -> bool:
L220: def installed_as_egg(self) -> bool:
L234: def installed_with_setuptools_egg_info(self) -> bool:
L252: def installed_with_dist_info(self) -> bool:

```

```

L268: def canonical_name(self) -> NormalizedName:
L272: def version(self) -> Version:
L276: def raw_version(self) -> str:
L280: def setuptools_filename(self) -> str:
L288: def direct_url(self) -> DirectUrl | None:
L314: def installer(self) -> str:
L326: def requested(self) -> bool:
L330: def editable(self) -> bool:
L334: def local(self) -> bool:
L344: def in_usersite(self) -> bool:
L350: def in_site_packages(self) -> bool:
L355: def is_file(self, path: InfoPath) -> bool:
L359: def iter_distutils_script_names(self) -> Iterator[str]:
L367: def read_text(self, path: InfoPath) -> str:
L376: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:
L379: def _metadata_impl(self) -> email.message.Message:
L383: def metadata(self) -> email.message.Message:
L396: def metadata_dict(self) -> dict[str, Any]:
L407: def metadata_version(self) -> str | None:
L412: def raw_name(self) -> str:
L419: def requires_python(self) -> SpecifierSet:
L437: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
L445: def iter_raw_dependencies(self) -> Iterable[str]:
L449: def iter_provided_extras(self) -> Iterable[NormalizedName]:
L461: def _iter_declared_entries_from_record(self) -> Iterator[str] | None:
L469: def _iter_declared_entries_from_legacy(self) -> Iterator[str] | None:
L490: def iter_declared_entries(self) -> Iterator[str] | None:
L506: def _iter_requires_txt_entries(self) -> Iterator[RequiresEntry]:
L531: def _iter_egg_info_extras(self) -> Iterable[str]:
L541: def _iter_egg_info_dependencies(self) -> Iterable[str]:
L569: def _add_egg_info_requires(self, metadata: email.message.Message) -> None:
L579: class BaseEnvironment:
L583: def default(cls) -> BaseEnvironment:
L587: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:
L590: def get_distribution(self, name: str) -> BaseDistribution | None:
L598: def _iter_distributions(self) -> Iterator[BaseDistribution]:
L607: def iter_all_distributions(self) -> Iterator[BaseDistribution]:
L628: def iter_installed_distributions(
L664: class Wheel(Protocol):
L667: def as_zipfile(self) -> zipfile.ZipFile:
L671: class FilesystemWheel(Wheel):
L672: def __init__(self, location: str) -> None:
L675: def as_zipfile(self) -> zipfile.ZipFile:
L679: class MemoryWheel(Wheel):
L680: def __init__(self, location: str, stream: IO[bytes]) -> None:
L684: def as_zipfile(self) -> zipfile.ZipFile:

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/_json.py

```

L40: def json_name(field: str) -> str:
L44: def msg_to_json(msg: Message) -> dict[str, Any]:
L47: def sanitise_header(h: Header | str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/__init__.py

```

L30: def _should_use_importlib_metadata() -> bool:
L63: def _emit_pkg_resources_deprecation_if_needed() -> None:
L88: class Backend(Protocol):
L95: def select_backend() -> Backend:
L108: def get_default_environment() -> BaseEnvironment:
L118: def get_environment(paths: list[str] | None) -> BaseEnvironment:
L128: def get_directory_distribution(directory: str) -> BaseDistribution:
L137: def get_wheel_distribution(
L150: def get_metadata_distribution(

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/pkg_resources.py

```

L39: class EntryPoint(NamedTuple):
L45: class InMemoryMetadata:
L51: def __init__(self, metadata: Mapping[str, bytes], wheel_name: str) -> None:
L55: def has_metadata(self, name: str) -> bool:
L58: def get_metadata(self, name: str) -> str:
L67: def get_metadata_lines(self, name: str) -> Iterable[str]:
L70: def metadata_isdir(self, name: str) -> bool:
L73: def metadata_listdir(self, name: str) -> list[str]:
L76: def run_script(self, script_name: str, namespace: str) -> None:
L80: class Distribution(BaseDistribution):
L81: def __init__(self, dist: pkg_resources.Distribution) -> None:
L88: def _extra_mapping(self) -> Mapping[NormalizedName, str]:
L97: def from_directory(cls, directory: str) -> BaseDistribution:
L117: def from_metadata_file_contents(
L134: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:
L155: def location(self) -> str | None:
L159: def installed_location(self) -> str | None:
L170: def info_location(self) -> str | None:
L174: def installed_by_distutils(self) -> bool:
L184: def canonical_name(self) -> NormalizedName:
L188: def version(self) -> Version:
L192: def raw_version(self) -> str:
L195: def is_file(self, path: InfoPath) -> bool:
L198: def iter_distutils_script_names(self) -> Iterator[str]:
L201: def read_text(self, path: InfoPath) -> str:
L210: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:
L216: def _metadata_impl(self) -> email.message.Message:
L238: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
L246: def iter_provided_extras(self) -> Iterable[NormalizedName]:

```



```

L250: class Environment(BaseEnvironment):
L251: def __init__(self, ws: pkg_resources.WorkingSet) -> None:
L255: def default(cls) -> BaseEnvironment:
L259: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:
L262: def _iter_distributions(self) -> Iterator[BaseDistribution]:
L266: def _search_distribution(self, name: str) -> BaseDistribution | None:
L278: def get_distribution(self, name: str) -> BaseDistribution | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_compat.py

```

L10: class BadMetadata(ValueError):
L11: def __init__(self, dist: importlib.metadata.Distribution, *, reason: str) -> None:
L15: def __str__(self) -> str:
L19: class BasePath(Protocol):
L31: def name(self) -> str:
L35: def parent(self) -> BasePath:
L39: def get_info_location(d: importlib.metadata.Distribution) -> BasePath | None:
L51: def parse_name_and_version_from_info_directory(
L75: def get_dist_canonical_name(dist: importlib.metadata.Distribution) -> NormalizedName:

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_envs.py

```

L28: def _looks_like_wheel(location: str) -> bool:
L40: class _DistributionFinder:
L55: def __init__(self) -> None:
L58: def _find_impl(self, location: str) -> Iterator[FoundResult]:
L79: def find(self, location: str) -> Iterator[BaseDistribution]:
L91: def find_legacy_editables(self, location: str) -> Iterator[BaseDistribution]:
L116: class Environment(BaseEnvironment):
L117: def __init__(self, paths: Sequence[str]) -> None:
L121: def default(cls) -> BaseEnvironment:
L125: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:
L130: def _iter_distributions(self) -> Iterator[BaseDistribution]:
L136: def get_distribution(self, name: str) -> BaseDistribution | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_dists.py

```

L38: class WheelDistribution(importlib.metadata.Distribution):
L49: def __init__(
L58: def from_zipfile(
L77: def iterdir(self, path: InfoPath) -> Iterator[pathlib.PurePosixPath]:
L83: def read_text(self, filename: str) -> str | None:

```

```

L96: def locate_file(self, path: str | PathLike[str]) -> pathlib.Path:
L102: class Distribution(BaseDistribution):
L103: def __init__(
L114: def from_directory(cls, directory: str) -> BaseDistribution:
L120: def from_metadata_file_contents(
L137: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:
L146: def location(self) -> str | None:
L152: def info_location(self) -> str | None:
L158: def installed_location(self) -> str | None:
L164: def canonical_name(self) -> NormalizedName:
L168: def version(self) -> Version:
L179: def raw_version(self) -> str:
L182: def is_file(self, path: InfoPath) -> bool:
L185: def iter_distutils_script_names(self) -> Iterator[str]:
L194: def read_text(self, path: InfoPath) -> str:
L200: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:
L204: def _metadata_impl(self) -> email.message.Message:
L218: def iter_provided_extras(self) -> Iterable[NormalizedName]:
L224: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_install.py

```

L62: class InstallRequirement:
L69: def __init__(
L191: def __str__(self) -> str:
L215: def __repr__(self) -> str:
L221: def format_debug(self) -> str:
L234: def name(self) -> str | None:
L240: def supports_pyproject_editable(self) -> bool:
L250: def specifier(self) -> SpecifierSet:
L255: def is_direct(self) -> bool:
L260: def is_pinned(self) -> bool:
L269: def match_markers(self, extras_requested: Iterable[str] | None = None) -> bool:
L282: def has_hash_options(self) -> bool:
L291: def hashes(self, trust_internet: bool = True) -> Hashes:
L318: def from_path(self) -> str | None:
L333: def ensure_build_location(
L376: def _set_requirement(self) -> None:
L398: def warn_on_mismatching_name(self) -> None:
L416: def check_if_exists(self, use_user_site: bool) -> None:
L455: def is_wheel(self) -> bool:
L461: def is_wheel_from_cache(self) -> bool:
L468: def unpacked_source_directory(self) -> str:
L475: def setup_py_path(self) -> str:
L482: def pyproject_toml_path(self) -> str:
L486: def load_pyproject_toml(self) -> None:
L506: def editable_sanity_check(self) -> None:
L519: def prepare_metadata(self) -> None:
L555: def metadata(self) -> Any:

```

```

L561: def set_dist(self, distribution: BaseDistribution) -> None:
L564: def get_dist(self) -> BaseDistribution:
L580: def assert_source_matches_version(self) -> None:
L598: def ensure_has_source_dir(
L620: def needs_unpacked_archive(self, archive_source: Path) -> None:
L624: def ensure_pristine_source_checkout(self) -> None:
L642: def update_editable(self) -> None:
L662: def uninstall(
L688: def _get_archive_name(self, path: str, parentdir: str, rootdir: str) -> str:
L689: def _clean_zip_name(name: str, prefix: str) -> str:
L702: def archive(self, build_dir: str | None) -> None:
L769: def install(
L804: def check_invalid_constraint_type(req: InstallRequirement) -> str:
L832: def _has_option(options: Values, reqs: list[InstallRequirement], option: str) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/req/pep723.py

```

L9: class PEP723Exception(ValueError):
L12: def __init__(self, msg: str) -> None:
L16: def pep723_metadata(scriptfile: str) -> dict[str, Any]:

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_set.py

```

L11: class RequirementSet:
L12: def __init__(self, check_supported_wheels: bool = True) -> None:
L20: def __str__(self) -> str:
L27: def __repr__(self) -> str:
L40: def add_unnamed_requirement(self, install_req: InstallRequirement) -> None:
L44: def add_named_requirement(self, install_req: InstallRequirement) -> None:
L50: def has_requirement(self, name: str) -> bool:
L58: def get_requirement(self, name: str) -> InstallRequirement:
L67: def all_requirements(self) -> list[InstallRequirement]:
L71: def requirements_to_install(self) -> list[InstallRequirement]:

```

.venv/lib/python3.12/site-packages/pip/_internal/req/__init__.py

```

L26: class InstallationResult:
L30: def _validate_requirements(
L38: def install_given_reqs(

```

.venv/lib/python3.12/site-packages/pip/_internal/req/constructors.py

```

L58: def _strip_extras(path: str) -> tuple[str, str | None]:
L70: def convert_extras(extras: str | None) -> set[str]:
L76: def _set_requirement_extras(req: Requirement, new_extras: set[str]) -> Requirement:
L101: def _parse_direct_url_editable(editable_req: str) -> tuple[str | None, str, set[str]]:

```

```

L119: def _parse_pip_syntax_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
L148: def parse_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
L182: def check_first_requirement_in_file(filename: str) -> None:
L210: def deduce_helpful_msg(req: str) -> str:
L236: class RequirementParts:
L243: def parse_req_from_editable(editable_req: str) -> RequirementParts:
L262: def install_req_from_editable(
L292: def _looks_like_path(name: str) -> bool:
L311: def _get_url_from_path(path: str, name: str) -> str | None:
L345: def parse_req_from_line(name: str, line_source: str | None) -> RequirementParts:
L393: def with_source(text: str) -> str:
L398: def _parse_req_string(req_as_string: str) -> Requirement:
L424: def install_req_from_line(
L457: def install_req_from_req_string(
L493: def install_req_from_parsed_requirement(
L525: def install_req_from_link_and_ireq(
L541: def install_req_drop_extras(ireq: InstallRequirement) -> InstallRequirement:
L565: def install_req_extend_extras(
L583: def _pylock_hashes_to_hash_options(hashes: Mapping[str, str]) -> dict[str, list[str]]:
L587: def install_req_from_pylock_package(

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_file.py

```

L105: class ParsedRequirement:
L115: class ParsedLine:
L123: def is_editable(self) -> bool:
L127: def requirement(self) -> str | None:
L136: def parse_requirements(
L163: def preprocess(content: str) -> ReqFileLines:
L175: def handle_requirement_line(
L209: def handle_option_line(
L287: def handle_line(
L331: class RequirementsFileParser:
L332: def __init__(
L340: def parse(
L348: def _parse_and_recurse(
L400: def _parse_file(
L424: def get_line_parser(finder: PackageFinder | None) -> LineParser:
L425: def parse_line(line: str) -> tuple[str, Values]:
L449: def break_args_options(line: str) -> tuple[str, str]:
L466: class OptionParsingError(Exception):
L467: def __init__(self, msg: str) -> None:
L471: def build_parser() -> optparse.OptionParser:
L484: def parser_exit(self: Any, msg: str) -> NoReturn:
L494: def join_lines(lines_enum: ReqFileLines) -> ReqFileLines:
L525: def ignore_comments(lines_enum: ReqFileLines) -> ReqFileLines:
L536: def expand_env_variables(lines_enum: ReqFileLines) -> ReqFileLines:
L563: def get_file_content(
L596: def _decode_req_file(data: bytes, url: str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_dependency_group.py

```
L11: def parse_dependency_groups(groups: list[tuple[str, str]]) -> list[str]:
L21: def _resolve_all_groups(
L41: def _build_resolvers(paths: Iterable[str]) -> dict[str, Any]:
L72: def _load_pyproject(path: str) -> dict[str, Any]:
```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_uninstall.py

```
L24: def _script_names(
L43: def _unique(
L47: def unique(*args: Any, **kw: Any) -> Generator[Any, None, None]:
L58: def uninstallation_paths(dist: BaseDistribution) -> Generator[str, None, None]:
L91: def compact(paths: Iterable[str]) -> set[str]:
L110: def compress_for_rename(paths: Iterable[str]) -> set[str]:
L121: def norm_join(*a: str) -> str:
L144: def compress_for_output_listing(paths: Iterable[str]) -> tuple[set[str], set[str]]:
L193: class StashedUninstallPathSet:
L197: def __init__(self) -> None:
L205: def _get_directory_stash(self, path: str) -> str:
L219: def _get_file_stash(self, path: str) -> str:
L246: def stash(self, path: str) -> str:
L267: def commit(self) -> None:
L274: def rollback(self) -> None:
L294: def can_rollback(self) -> bool:
L298: class UninstallPathSet:
L302: def __init__(self, dist: BaseDistribution) -> None:
L313: def _permitted(self, path: str) -> bool:
L324: def add(self, path: str) -> None:
L343: def add_pth(self, pth_file: str, entry: str) -> None:
L352: def remove(self, auto_confirm: bool = False, verbose: bool = False) -> None:
L381: def _allowed_to_proceed(self, verbose: bool) -> bool:
L384: def _display(msg: str, paths: Iterable[str]) -> None:
L409: def rollback(self) -> None:
L422: def commit(self) -> None:
L427: def from_dist(cls, dist: BaseDistribution) -> UninstallPathSet:
L568: def iter_scripts_to_remove(
L584: class UninstallPthEntries:
L585: def __init__(self, pth_file: str) -> None:
L590: def add(self, entry: str) -> None:
L605: def remove(self) -> None:
L632: def rollback(self) -> bool:
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/base.py

```
L11: class BaseResolver:
```

```
L12: def resolve(
L17: def get_installation_order(
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/b ase.py

```
L18: def format_name(project: NormalizedName, extras: frozenset[NormalizedName]) -> str:
L26: class Constraint:
L33: def empty(cls) -> Constraint:
L37: def from_ireq(cls, ireq: InstallRequirement) -> Constraint:
L47: def __bool__(self) -> bool:
L50: def __and__(self, other: InstallRequirement) -> Constraint:
L69: def is_satisfied_by(self, candidate: Candidate) -> bool:
L78: def format_for_error(self) -> str:
L85: class Requirement:
L87: def project_name(self) -> NormalizedName:
L97: def name(self) -> str:
L105: def is_satisfied_by(self, candidate: Candidate) -> bool:
L108: def get_candidate_lookup(self) -> CandidateLookup:
L111: def format_for_error(self) -> str:
L115: def _match_link(link: Link, candidate: Candidate) -> bool:
L121: class Candidate:
L123: def project_name(self) -> NormalizedName:
L133: def name(self) -> str:
L142: def version(self) -> Version:
L146: def is_installed(self) -> bool:
L150: def is_editable(self) -> bool:
L154: def source_link(self) -> Link | None:
L157: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L160: def get_install_requirement(self) -> InstallRequirement | None:
L163: def format_for_error(self) -> str:
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/re solver.py

```
L41: class Resolver(BaseResolver):
L44: def __init__(
L76: def resolve(
L186: def get_installation_order(
L218: def get_topological_weights(
L249: def visit(node: str | None) -> None:
L321: def _req_set_item_sorter(
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/re porter.py

```

L15: class PipReporter(BaseReporter[Requirement, Candidate, str]):
L16: def __init__(self, constraints: Mapping[str, Constraint] | None = None) -> None:
L39: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:
L73: class PipDebuggingReporter(BaseReporter[Requirement, Candidate, str]):
L76: def starting(self) -> None:
L79: def starting_round(self, index: int) -> None:
L82: def ending_round(self, index: int, state: Any) -> None:
L86: def ending(self, state: Any) -> None:
L89: def adding_requirement(
L94: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:
L97: def pinning(self, candidate: Candidate) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/candidates.py

```

L48: def as_base_candidate(candidate: Candidate) -> BaseCandidate | None:
L60: def make_install_req_from_link(
L90: def make_install_req_from_editable(
L112: def _make_install_req_from_dist(
L134: class _InstallRequirementBackedCandidate(Candidate):
L140: class exposes appropriate information to the resolver.
L153: def __init__(
L171: def __str__(self) -> str:
L174: def __repr__(self) -> str:
L177: def __hash__(self) -> int:
L184: def __eq__(self, other: Any) -> bool:
L190: def source_link(self) -> Link | None:
L194: def project_name(self) -> NormalizedName:
L201: def name(self) -> str:
L205: def version(self) -> Version:
L210: def format_for_error(self) -> str:
L217: def _prepare_distribution(self) -> BaseDistribution:
L220: def _check_metadata_consistency(self, dist: BaseDistribution) -> None:
L244: def _prepare(self) -> BaseDistribution:
L271: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L279: def get_install_requirement(self) -> InstallRequirement | None:
L283: class LinkCandidate(_InstallRequirementBackedCandidate):
L286: def __init__(
L335: def _prepare_distribution(self) -> BaseDistribution:
L340: class EditableCandidate(_InstallRequirementBackedCandidate):
L343: def __init__(
L360: def _prepare_distribution(self) -> BaseDistribution:
L364: class AlreadyInstalledCandidate(Candidate):
L368: def __init__(
L386: def __str__(self) -> str:
L389: def __repr__(self) -> str:
L392: def __eq__(self, other: object) -> bool:
L397: def __hash__(self) -> int:
L401: def project_name(self) -> NormalizedName:

```

```

L405: def name(self) -> str:
L409: def version(self) -> Version:
L415: def is_editable(self) -> bool:
L418: def format_for_error(self) -> str:
L421: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L431: def get_install_requirement(self) -> InstallRequirement | None:
L435: class ExtrasCandidate(Candidate):
L460: def __init__(
L479: def __str__(self) -> str:
L483: def __repr__(self) -> str:
L486: def __hash__(self) -> int:
L489: def __eq__(self, other: Any) -> bool:
L495: def project_name(self) -> NormalizedName:
L499: def name(self) -> str:
L504: def version(self) -> Version:
L507: def format_for_error(self) -> str:
L513: def is_installed(self) -> bool:
L517: def is_editable(self) -> bool:
L521: def source_link(self) -> Link | None:
L524: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L552: def get_install_requirement(self) -> InstallRequirement | None:
L559: class RequiresPythonCandidate(Candidate):
L563: def __init__(self, py_version_info: tuple[int, ...] | None) -> None:
L574: def __str__(self) -> str:
L577: def __repr__(self) -> str:
L581: def project_name(self) -> NormalizedName:
L585: def name(self) -> str:
L589: def version(self) -> Version:
L592: def format_for_error(self) -> str:
L595: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
L598: def get_install_requirement(self) -> InstallRequirement | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/provider.py

```

L56: def _get_with_identifier(
L81: class PipProvider(_ProviderBase):
L92: def __init__(
L109: def constraints(self) -> dict[str, Constraint]:
L117: def identify(self, requirement_or_candidate: Requirement | Candidate) -> str:
L120: def narrow_requirement_selection(
L176: def get_preference(
L256: def find_matches(
L262: def _eligible_for_upgrade(identifier: str) -> bool:
L300: def is_satisfied_by(requirement: Requirement, candidate: Candidate) -> bool:
L303: def get_dependencies(self, candidate: Candidate) -> Iterable[Requirement]:

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/fa

ctory.py

```

L74: class ConflictCause(Protocol):
L85: class CollectedRootRequirements(NamedTuple):
L91: class Factory:
L92: def __init__(
L132: def force_reinstall(self) -> bool:
L135: def _fail_if_link_is_unsupported_wheel(self, link: Link) -> None:
L144: def _make_extras_candidate(
L159: def _make_candidate_from_dist(
L174: def _make_candidate_from_link(
L189: def _make_base_candidate_from_link(
L246: def _get_locked_installation_candidate(
L271: def _iter_found_candidates(
L308: def _get_installed_candidate() -> Candidate | None:
L337: def iter_index_candidate_infos() -> Iterator[IndexCandidateInfo]:
L358: def is_pinned(specifier: SpecifierSet) -> bool:
L392: def _iter_explicit_candidates_from_base(
L414: def _iter_candidates_from_constraints(
L448: def find_candidates(
L525: def _make_requirements_from_install_req(
L578: def collect_root_requirements(
L620: def make_requirement_from_candidate(
L625: def make_requirements_from_spec(
L643: def make_requires_python_requirement(
L654: def get_wheel_cache_entry(self, link: Link, name: str | None) -> CacheEntry | None:
L671: def get_dist_to_uninstall(self, candidate: Candidate) -> BaseDistribution | None:
L699: def _report_requires_python_error(
L721: def _report_single_requirement_conflict(
L783: def _has_any_candidates(self, project_name: str) -> bool:
L798: def get_installation_error(
L834: def text_join(parts: list[str]) -> str:
L840: def describe_trigger(parent: Candidate) -> str:

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/requirements.py

```

L14: class ExplicitRequirement(Requirement):
L15: def __init__(self, candidate: Candidate) -> None:
L18: def __str__(self) -> str:
L21: def __repr__(self) -> str:
L24: def __hash__(self) -> int:
L27: def __eq__(self, other: Any) -> bool:
L33: def project_name(self) -> NormalizedName:
L38: def name(self) -> str:
L42: def format_for_error(self) -> str:
L45: def get_candidate_lookup(self) -> CandidateLookup:
L48: def is_satisfied_by(self, candidate: Candidate) -> bool:

```

```

L52: class SpecifierRequirement(Requirement):
L53: def __init__(self, ireq: InstallRequirement) -> None:
L61: def _equal(self) -> str:
L68: def __str__(self) -> str:
L71: def __repr__(self) -> str:
L74: def __eq__(self, other: object) -> bool:
L79: def __hash__(self) -> int:
L87: def project_name(self) -> NormalizedName:
L92: def name(self) -> str:
L95: def format_for_error(self) -> str:
L108: def get_candidate_lookup(self) -> CandidateLookup:
L111: def is_satisfied_by(self, candidate: Candidate) -> bool:
L124: class SpecifierWithoutExtrasRequirement(SpecifierRequirement):
L130: def __init__(self, ireq: InstallRequirement) -> None:
L138: def _equal(self) -> str:
L145: def __eq__(self, other: object) -> bool:
L150: def __hash__(self) -> int:
L158: class RequiresPythonRequirement(Requirement):
L161: def __init__(self, specifier: SpecifierSet, match: Candidate) -> None:
L173: def __str__(self) -> str:
L176: def __repr__(self) -> str:
L179: def __hash__(self) -> int:
L186: def __eq__(self, other: Any) -> bool:
L195: def project_name(self) -> NormalizedName:
L199: def name(self) -> str:
L202: def format_for_error(self) -> str:
L205: def get_candidate_lookup(self) -> CandidateLookup:
L208: def is_satisfied_by(self, candidate: Candidate) -> bool:
L216: class UnsatisfiableRequirement(Requirement):
L219: def __init__(self, name: NormalizedName) -> None:
L222: def __str__(self) -> str:
L225: def __repr__(self) -> str:
L228: def __eq__(self, other: object) -> bool:
L233: def __hash__(self) -> int:
L237: def project_name(self) -> NormalizedName:
L241: def name(self) -> str:
L244: def format_for_error(self) -> str:
L247: def get_candidate_lookup(self) -> CandidateLookup:
L250: def is_satisfied_by(self, candidate: Candidate) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/finder_and_candidates.py

```

L28: def _iter_built(infos: Iterator[IndexCandidateInfo]) -> Iterator[Candidate]:
L59: def _iter_built_with_prepended(
L81: def _iter_built_with_inserted(
L113: class FoundCandidates(Sequence[Candidate]):
L122: def __init__(
L135: def __getitem__(self, index: Any) -> Any:

```

```

L141: def __iter__(self) -> Iterator[Candidate]:
L151: def __len__(self) -> int:
L157: def __bool__(self) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/legacy/resolver.py

```

L58: def _check_dist_requires_python(
L112: class Resolver(BaseResolver):
L119: def __init__(
L157: def resolve(
L194: def _add_requirement_to_set(
L309: def _is_upgrade_allowed(self, req: InstallRequirement) -> bool:
L318: def _set_req_to_reinstall(self, req: InstallRequirement) -> None:
L329: def _check_skip_installed(self, req_to_install: InstallRequirement) -> str | None:
L381: def _find_requirement_link(self, req: InstallRequirement) -> Link | None:
L403: def _populate_link(self, req: InstallRequirement) -> None:
L442: def _get_dist_for(self, req: InstallRequirement) -> BaseDistribution:
L488: def _resolve_one(
L517: def add_req(subreq: Requirement, extras_requested: Iterable[str]) -> None:
L571: def get_installation_order(
L586: def schedule(req: InstallRequirement) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/index/collector.py

```

L46: def _match_vcs_scheme(url: str) -> str | None:
L57: class _NotAPIContent(Exception):
L58: def __init__(self, content_type: str, request_desc: str) -> None:
L64: def _ensure_api_header(response: Response) -> None:
L86: class _NotHTTP(Exception):
L90: def _ensure_api_response(url: str, session: PipSession) -> None:
L108: def _get_simple_response(url: str, session: PipSession) -> Response:
L171: def _get_encoding_from_headers(headers: ResponseHeaders) -> str | None:
L182: class CacheablePageContent:
L183: def __init__(self, page: IndexContent) -> None:
L187: def __eq__(self, other: object) -> bool:
L190: def __hash__(self) -> int:
L194: class ParseLinks(Protocol):
L195: def __call__(self, page: IndexContent) -> Iterable[Link]: ...
L198: def with_cached_index_content(fn: ParseLinks) -> ParseLinks:
L206: def wrapper(cacheable_page: CacheablePageContent) -> list[Link]:
L210: def wrapper_wrapper(page: IndexContent) -> list[Link]:
L219: def parse_links(page: IndexContent) -> Iterable[Link]:
L248: class IndexContent:
L264: def __str__(self) -> str:
L268: class HTMLLinkParser(HTMLParser):
L274: def __init__(self, url: str) -> None:
L281: def handle_starttag(self, tag: str, attrs: list[tuple[str, str | None]]) -> None:

```

```

L289: def get_href(self, attrs: list[tuple[str, str | None]]) -> str | None:
L296: def _handle_get_simple_fail(
L306: def _make_index_content(
L319: def _get_index_content(link: Link, *, session: PipSession) -> IndexContent | None:
L379: class CollectedSources(NamedTuple):
L384: class LinkCollector:
L392: def __init__(
L401: def create(
L435: def find_links(self) -> list[str]:
L438: def fetch_response(self, location: Link) -> IndexContent | None:
L444: def collect_sources(

```

.venv/lib/python3.12/site-packages/pip/_internal/index/sources.py

```

L31: class LinkSource:
L33: def link(self) -> Link | None:
L37: def page_candidates(self) -> FoundCandidates:
L41: def file_links(self) -> FoundLinks:
L46: def _is_html_file(file_url: str) -> bool:
L50: class _FlatDirectoryToUrls:
L53: def __init__(self, path: str) -> None:
L59: def _scan_directory(self) -> None:
L83: def page_candidates(self) -> list[str]:
L90: def project_name_to_urls(self) -> dict[str, list[str]]:
L97: class _FlatDirectorySource(LinkSource):
L108: def __init__(
L125: def link(self) -> Link | None:
L128: def page_candidates(self) -> FoundCandidates:
L132: def file_links(self) -> FoundLinks:
L137: class _LocalFileSource(LinkSource):
L147: def __init__(
L156: def link(self) -> Link | None:
L159: def page_candidates(self) -> FoundCandidates:
L164: def file_links(self) -> FoundLinks:
L170: class _RemoteFileSource(LinkSource):
L179: def __init__(
L190: def link(self) -> Link | None:
L193: def page_candidates(self) -> FoundCandidates:
L198: def file_links(self) -> FoundLinks:
L202: class _IndexDirectorySource(LinkSource):
L209: def __init__(
L218: def link(self) -> Link | None:
L221: def page_candidates(self) -> FoundCandidates:
L224: def file_links(self) -> FoundLinks:
L228: def build_source(

```

.venv/lib/python3.12/site-packages/pip/_internal/index/package_finder.py

```

L63: def _check_link_requires_python(
L110: class LinkType(enum.Enum):
L122: class LinkEvaluator:
L133: def __init__(
L172: def evaluate_link(self, link: Link) -> tuple[LinkType, str]:
L283: def get_version_sort_key(v: str) -> tuple[int, ...]:
L300: def filter_unallowed_hashes(
L375: class CandidatePreferences:
L386: class BestCandidateResult:
L402: def __post_init__(self) -> None:
L411: class CandidateEvaluator:
L418: def create(
L453: def __init__(
L479: def get_applicable_candidates(
L518: def _sort_key(self, candidate: InstallationCandidate) -> CandidateSortingKey:
L583: def sort_best_candidate(
L596: def compute_best_candidate(
L614: class PackageFinder:
L621: def __init__(
L672: def create(
L708: def target_python(self) -> TargetPython:
L712: def search_scope(self) -> SearchScope:
L716: def search_scope(self, search_scope: SearchScope) -> None:
L720: def find_links(self) -> list[str]:
L724: def index_urls(self) -> list[str]:
L728: def proxy(self) -> str | None:
L732: def trusted_hosts(self) -> Iterable[str]:
L737: def custom_cert(self) -> str | None:
L745: def client_cert(self) -> str | None:
L751: def release_control(self) -> ReleaseControl | None:
L754: def set_release_control(self, release_control: ReleaseControl) -> None:
L758: def prefer_binary(self) -> bool:
L761: def set_prefer_binary(self) -> None:
L765: def uploaded_prior_to(self) -> datetime.datetime | None:
L768: def requires_python_skipped_reasons(self) -> list[str]:
L771: def make_link_evaluator(self, project_name: str) -> LinkEvaluator:
L785: def _sort_links(self, links: Iterable[Link]) -> list[Link]:
L801: def _log_skipped_link(self, link: Link, result: LinkType, detail: str) -> None:
L808: def get_install_candidate(
L833: def evaluate_links(
L847: def process_project_url(
L868: def find_all_candidates(self, project_name: str) -> list[InstallationCandidate]:
L925: def make_candidate_evaluator(
L942: def find_best_candidate(
L971: def find_requirement(
L995: def _format_versions(cand_iter: Iterable[InstallationCandidate]) -> str:
L1030: def _should_install_candidate(
L1072: def _find_name_version_sep(fragment: str, canonical_name: str) -> int:
L1098: def _extract_version_from_fragment(fragment: str, canonical_name: str) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/network/lazy_wheel.py

```

L22: class HTTPRangeRequestUnsupported(Exception):
L26: def dist_from_wheel_url(
L45: class LazyZipOverHTTP:
L54: def __init__(
L71: def mode(self) -> str:
L76: def name(self) -> str:
L80: def seekable(self) -> bool:
L84: def close(self) -> None:
L89: def closed(self) -> bool:
L93: def read(self, size: int = -1) -> bytes:
L107: def readable(self) -> bool:
L111: def seek(self, offset: int, whence: int = 0) -> int:
L121: def tell(self) -> int:
L125: def truncate(self, size: int | None = None) -> int:
L135: def writable(self) -> bool:
L139: def __enter__(self) -> LazyZipOverHTTP:
L143: def __exit__(self, *exc: Any) -> None:
L147: def _stay(self) -> Generator[None, None, None]:
L158: def _check_zip(self) -> None:
L173: def _stream_response(
L183: def _merge(
L205: def _download(self, start: int, end: int) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/network/session.py

```

L98: def looks_like_ci() -> bool:
L109: def user_agent() -> str:
L210: class LocalFSAdapter(BaseAdapter):
L211: def send(
L251: def close(self) -> None:
L255: class _SSLContextAdapterMixin:
L263: def __init__(
L272: def init_poolmanager(
L288: def proxy_manager_for(self, proxy: str, **proxy_kwargs: Any) -> ProxyManager:
L296: class HTTPAdapter(_SSLContextAdapterMixin, _BaseHTTPAdapter):
L300: class CacheControlAdapter(_SSLContextAdapterMixin, _BaseCacheControlAdapter):
L304: class InsecureHTTPAdapter(HTTPAdapter):
L305: def cert_verify(
L315: class InsecureCacheControlAdapter(CacheControlAdapter):
L316: def cert_verify(
L326: class PipSession(requests.Session):
L329: def __init__(
L413: def update_index_urls(self, new_index_urls: list[str]) -> None:
L420: def add_trusted_host(
L453: def iter_secure_origins(self) -> Generator[SecureOrigin, None, None]:
L458: def is_secure_origin(self, location: Link) -> bool:
L525: def request(self, method: str, url: str, *args: Any, **kwargs: Any) -> Response: #

```

```
type: ignore[override]
```

.venv/lib/python3.12/site-packages/pip/_internal/network/cache.py

```
L24: def is_from_cache(response: Response) -> bool:
L29: def suppressed_cache_errors() -> Generator[None, None, None]:
L39: class SafeFileCache(SeparateBodyBaseCache):
L57: def __init__(self, directory: str) -> None:
L62: def _get_cache_path(self, name: str) -> str:
L70: def get(self, key: str) -> bytes | None:
L80: def _write_to_file(self, path: str, writer_func: Callable[[BinaryIO], Any]) -> None:
L93: def _write(self, path: str, data: bytes) -> None:
L96: def _write_from_io(self, path: str, source_file: BinaryIO) -> None:
L99: def set(
L105: def delete(self, key: str) -> None:
L112: def get_body(self, key: str) -> BinaryIO | None:
L121: def set_body(self, key: str, body: bytes) -> None:
L125: def set_body_from_io(self, key: str, body_file: BinaryIO) -> None:
```

.venv/lib/python3.12/site-packages/pip/_internal/network/utils.py

```
L31: def raise_for_status(resp: Response) -> None:
L59: def response_chunks(
```

.venv/lib/python3.12/site-packages/pip/_internal/network/xmlrpc.py

```
L20: class PipXmlrpcTransport(xmlrpc.client.Transport):
L25: def __init__(
L33: def request(
```

.venv/lib/python3.12/site-packages/pip/_internal/network/auth.py

```
L44: class Credentials(NamedTuple):
L50: class KeyRingBaseProvider(ABC):
L56: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None: ...
L59: def save_auth_info(self, url: str, username: str, password: str) -> None: ...
L62: class KeyRingNullProvider(KeyRingBaseProvider):
L67: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:
L70: def save_auth_info(self, url: str, username: str, password: str) -> None:
L74: class KeyRingPythonProvider(KeyRingBaseProvider):
L79: def __init__(self) -> None:
L84: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:
L102: def save_auth_info(self, url: str, username: str, password: str) -> None:
L106: class KeyRingCliProvider(KeyRingBaseProvider):
L117: def __init__(self, cmd: str) -> None:
L120: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:
```

```

L129: def save_auth_info(self, url: str, username: str, password: str) -> None:
L132: def _get_password(self, service_name: str, username: str) -> str | None:
L150: def _set_password(self, service_name: str, username: str, password: str) -> None:
L166: def get_keyring_provider(provider: str) -> KeyRingBaseProvider:
L191: def PATH_as_shutil_which_determines_it() -> str:
L227: class MultiDomainBasicAuth(AuthBase):
L228: def __init__(
L246: def keyring_provider(self) -> KeyRingBaseProvider:
L250: def keyring_provider(self, provider: str) -> None:
L258: def use_keyring(self) -> bool:
L264: def _get_keyring_auth(
L290: def _get_index_url(self, url: str) -> str | None:
L340: def _get_new_credentials(
L397: def _get_url_and_credentials(
L445: def __call__(self, req: PreparedRequest) -> PreparedRequest:
L463: def _prompt_for_password(self, netloc: str) -> tuple[str | None, str | None, bool]:
L475: def _should_save_password_to_keyring(self) -> bool:
L484: def handle_401(self, resp: Response, **kwargs: Any) -> Response:
L547: def warn_on_401(self, resp: Response, **kwargs: Any) -> None:
L555: def save_credentials(self, resp: Response, **kwargs: Any) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/network/download.py

```

L31: def _get_http_response_size(resp: Response) -> int | None:
L38: def _get_http_response_etag_or_last_modified(resp: Response) -> str | None:
L46: def _log_download(
L97: def sanitize_content_filename(filename: str) -> str:
L104: def parse_content_disposition(content_disposition: str, default_filename: str) -> str:
L119: def _get_http_response_filename(resp: Response, link: Link) -> str:
L141: class _FileDownload:
L150: def is_incomplete(self) -> bool:
L153: def write_chunk(self, data: bytes) -> None:
L157: def reset_file(self) -> None:
L164: class Downloader:
L165: def __init__(
L177: def batch(
L185: def __call__(self, link: Link, location: str) -> tuple[str, str]:
L200: def _process_response(self, download: _FileDownload, resp: Response) -> None:
L219: def _attempt_resumes_or_redownloads(
L259: def _cache_resumed_download(
L315: def _http_get_resume(
L329: def _http_get(self, link: Link, headers: Mapping[str, str] = HEADERS) -> Response:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/parser.py

```

L27: class PrettyHelpFormatter(optparse.IndentedHelpFormatter):
L41: def __init__(self, *args: Any, **kwargs: Any) -> None:
L48: def format_option_strings(self, option: optparse.Option) -> str:

```



```

L66: def format_option(self, option: optparse.Option) -> str:
L96: def format_heading(self, heading: str) -> str:
L101: def format_usage(self, usage: str) -> str:
L110: def format_description(self, description: str | None) -> str:
L129: def format_epilog(self, epilog: str | None) -> str:
L136: def expand_default(self, option: optparse.Option) -> str:
L143: def indent_lines(self, text: str, indent: str) -> str:
L148: class UpdatingDefaultsHelpFormatter(PrettyHelpFormatter):
L157: def expand_default(self, option: optparse.Option) -> str:
L180: class CustomOptionParser(optparse.OptionParser):
L181: def insert_option_group(
L193: def option_list_all(self) -> List[optparse.Option]:
L202: class ConfigOptionParser(CustomOptionParser):
L206: def __init__(
L219: def check_default(self, option: optparse.Option, key: str, val: Any) -> Any:
L226: def _get_ordered_configuration_items(
L257: def _update_defaults(self, defaults: dict[str, Any]) -> dict[str, Any]:
L321: def get_default_values(self) -> optparse.Values:
L343: def error(self, msg: str) -> NoReturn:
L347: def print_help(self, file: Any = None) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/main_parser.py

```

L21: def create_main_parser() -> ConfigOptionParser:
L52: def identify_python_interpreter(python: str) -> str | None:
L71: def parse_command(args: list[str]) -> tuple[str, list[str]]:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/progressBars.py

```

L33: def _rich_download_progress_bar(
L75: def _rich_install_progress_bar(
L97: def _raw_progress_bar(
L103: def write_progress(current: int, total: int) -> None:
L120: def get_download_progress_renderer(
L144: def get_install_progress_renderer(

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/autocompletion.py

```

L17: def autocomplete() -> None:
L132: def get_path_completion_type(
L156: def auto_complete_paths(current: str, completion_type: str) -> Iterable[str]:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/req_command.py

```

L64: def should_ignore_regular_constraints(options: Values) -> bool:
L84: def with_cleanup(

```

```

L91: def configure_tempdir_registry(registry: TempDirectoryTypeRegistry) -> None:
L95: def wrapper(self: _CommandT, options: Values, args: list[str]) -> int:
L112: def parse_constraint_files(
L137: class RequirementCommand(IndexGroupCommand):
L138: def __init__(self, *args: Any, **kw: Any) -> None:
L145: def determine_resolver_variant(options: Values) -> str:
L153: def make_requirement_preparer(
L234: def make_resolver(
L290: def get_requirements(
L435: def trace_basic_info(finder: PackageFinder) -> None:
L445: def _build_package_finder(

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/index_command.py

```

L36: def _create_truststore_ssl_context() -> SSLContext | None:
L54: class SessionCommandMixin(CommandContextMixin):
L59: def __init__(self) -> None:
L64: def _get_index_urls(cls, options: Values) -> list[str] | None:
L77: def get_default_session(self, options: Values) -> PipSession:
L87: def _build_session(
L140: def _pip_self_version_check_fetch(
L148: def _pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
L154: class IndexGroupCommand(Command, SessionCommandMixin):
L161: def should_exclude_prerelease(
L179: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/cmdoptions.py

```

L42: def raise_option_error(parser: OptionParser, option: Option, msg: str) -> None:
L56: def make_option_group(group: dict[str, Any], parser: ConfigOptionParser) -> OptionGroup:
L68: def check_dist_restriction(options: Values, check_target: bool = False) -> None:
L116: def check_build_constraints(options: Values) -> None:
L139: def _path_option_check(option: Option, opt: str, value: str) -> str:
L143: def _package_name_option_check(option: Option, opt: str, value: str) -> str:
L147: class PipOption(Option):
L348: def exists_action() -> Option:
L403: def extra_index_url() -> Option:
L426: def find_links() -> Option:
L442: def _handle_uploaded_prior_to(
L487: def uploaded_prior_to() -> Option:
L506: def trusted_host() -> Option:
L518: def constraints() -> Option:
L531: def build_constraints() -> Option:
L546: def requirements() -> Option:
L563: def requirements_from_scripts() -> Option:
L575: def editable() -> Option:
L590: def _handle_src(option: Option, opt_str: str, value: str, parser: OptionParser) ->
None:

```

```

L613: def _get_format_control(values: Values, option: Option) -> Any:
L618: def _handle_no_binary(
L629: def _handle_only_binary(
L640: def no_binary() -> Option:
L658: def only_binary() -> Option:
L676: def _get_release_control(values: Values, option: Option) -> Any:
L681: def _handle_all_releases(
L693: def _handle_only_final(
L705: def all_releases() -> Option:
L723: def only_final() -> Option:
L740: def check_release_control_exclusive(options: Values) -> None:
L772: def _convert_python_version(value: str) -> tuple[tuple[int, ...], str | None]:
L801: def _handle_python_version(
L870: def add_target_python_options(cmd_opts: OptionGroup) -> None:
L877: def make_target_python(options: Values) -> TargetPython:
L888: def prefer_binary() -> Option:
L912: def _handle_no_cache_dir(
L961: def _handle_dependency_group(
L1040: def _handle_config_settings(
L1118: def _handle_merge_hash(
L1179: def check_list_path_option(options: Values) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/base_command.py

```

L48: class Command(CommandContextMixIn):
L52: def __init__(self, name: str, summary: str, isolated: bool = False) -> None:
L82: def add_options(self) -> None:
L86: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
L96: def run(self, options: Values, args: list[str]) -> int:
L99: def _run_wrapper(self, level_number: int, options: Values, args: list[str]) -> int:
L100: def _inner_run() -> int:
L161: def parse_args(self, args: list[str]) -> tuple[Values, list[str]]:
L165: def main(self, args: list[str]) -> int:
L172: def _main(self, args: list[str]) -> int:
L260: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/command_context.py

```

L8: class CommandContextMixIn:
L9: def __init__(self) -> None:
L15: def main_context(self) -> Generator[None, None, None]:
L25: def enter_context(self, context_provider: AbstractContextManager[_T]) -> _T:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/spinners.py

```

L30: class SpinnerInterface:
L31: def spin(self) -> None:
L34: def finish(self, final_status: str) -> None:
L38: class InteractiveSpinner(SpinnerInterface):
L39: def __init__(
L59: def _write(self, status: str) -> None:
L71: def spin(self) -> None:
L78: def finish(self, final_status: str) -> None:
L91: class NonInteractiveSpinner(SpinnerInterface):
L92: def __init__(self, message: str, min_update_interval_seconds: float = 60.0) -> None:
L98: def _update(self, status: str) -> None:
L103: def spin(self) -> None:
L110: def finish(self, final_status: str) -> None:
L117: class RateLimiter:
L118: def __init__(self, min_update_interval_seconds: float) -> None:
L122: def ready(self) -> bool:
L127: def reset(self) -> None:
L132: def open_spinner(message: str) -> Generator[SpinnerInterface, None, None]:
L155: class _PipRichSpinner:
L163: def __init__(self, label: str) -> None:
L170: def __rich_console__(
L175: def __rich_measure__(
L181: def render(self) -> RenderableType:
L187: def finish(self, status: str) -> None:
L194: def open_rich_spinner(label: str, console: Console | None = None) -> Generator[None]:
L220: def hidden_cursor(file: IO[str]) -> Generator[None, None, None]:

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/main.py

```

L41: def main(args: list[str] | None = None) -> int:

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/base.py

```

L13: class AbstractDistribution(metaclass=abc.ABCMeta):
L32: def __init__(self, req: InstallRequirement) -> None:
L37: def build_tracker_id(self) -> str | None:
L45: def get_metadata_distribution(self) -> BaseDistribution:
L49: def prepare_distribution_metadata(

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/installed.py

```

L12: class InstalledDistribution(AbstractDistribution):
L20: def build_tracker_id(self) -> str | None:
L23: def get_metadata_distribution(self) -> BaseDistribution:
L27: def prepare_distribution_metadata(

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/sdist.py

```

L19: class SourceDistribution(AbstractDistribution):
L27: def build_tracker_id(self) -> str | None:
L32: def get_metadata_distribution(self) -> BaseDistribution:
L35: def prepare_distribution_metadata(
L73: def _prepare_build_backend(
L101: def _get_build_requires_wheel(self) -> Iterable[str]:
L109: def _get_build_requires_editable(self) -> Iterable[str]:
L119: def _install_build_reqs(
L140: def _raise_conflicts(
L157: def _raise_missing_reqs(self, missing: set[str]) -> None:

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/___init___.py

```

L7: def make_distribution_for_install_requirement(

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/wheel.py

```

L18: class WheelDistribution(AbstractDistribution):
L25: def build_tracker_id(self) -> str | None:
L28: def get_metadata_distribution(self) -> BaseDistribution:
L38: def prepare_distribution_metadata(

```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/versioncontrol.py

```

L45: def is_url(name: str) -> bool:
L55: def make_vcs_requirement_url(
L74: def find_path_to_project_root_from_repo_root(
L103: class RemoteNotFoundError(Exception):
L107: class RemoteNotValidError(Exception):
L108: def __init__(self, url: str):
L114: class RevOptions:
L130: def __repr__(self) -> str:
L134: def arg_rev(self) -> str | None:
L140: def to_args(self) -> CommandArgs:
L152: def to_display(self) -> str:
L158: def make_new(self, rev: str) -> RevOptions:
L168: class VcsSupport:
L172: def __init__(self) -> None:
L178: def __iter__(self) -> Iterator[str]:
L182: def backends(self) -> list[VersionControl]:
L186: def dirnames(self) -> list[str]:
L190: def all_schemes(self) -> list[str]:
L196: def register(self, cls: type[VersionControl]) -> None:

```

```

L204: def unregister(self, name: str) -> None:
L208: def get_backend_for_dir(self, location: str) -> VersionControl | None:
L231: def get_backend_for_scheme(self, scheme: str) -> VersionControl | None:
L240: def get_backend(self, name: str) -> VersionControl | None:
L251: class VersionControl:
L262: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:
L270: def get_subdirectory(cls, location: str) -> str | None:
L278: def get_requirement_revision(cls, repo_dir: str) -> str:
L285: def get_src_requirement(cls, repo_dir: str, project_name: str) -> str:
L309: def get_base_rev_args(rev: str) -> list[str]:
L318: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:
L332: def make_rev_options(
L345: def _is_local_repository(cls, repo: str) -> bool:
L354: def get_netloc_and_auth(
L375: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L406: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
L412: def get_url_rev_options(self, url: HiddenText) -> tuple[HiddenText, RevOptions]:
L428: def normalize_url(url: str) -> str:
L436: def compare_urls(cls, url1: str, url2: str) -> bool:
L442: def fetch_new(
L456: def switch(
L471: def update(
L487: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L497: def obtain(self, dest: str, url: HiddenText, verbosity: int) -> None:
L586: def unpack(self, location: str, url: HiddenText, verbosity: int) -> None:
L599: def get_remote_url(cls, location: str) -> str:
L609: def get_revision(cls, location: str) -> str:
L616: def run_command(
L674: def is_repository_directory(cls, path: str) -> bool:
L682: def get_repository_root(cls, location: str) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/subversion.py

```

L31: class Subversion(VersionControl):
L38: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:
L42: def get_base_rev_args(rev: str) -> list[str]:
L46: def get_revision(cls, location: str) -> str:
L75: def get_netloc_and_auth(
L90: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L98: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
L108: def get_remote_url(cls, location: str) -> str:
L132: def _get_svn_url_rev(cls, location: str) -> tuple[str | None, int]:
L182: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L186: def __init__(self, use_interactive: bool | None = None) -> None:
L200: def call_vcs_version(self) -> tuple[int, ...]:
L228: def get_vcs_version(self) -> tuple[int, ...]:
L248: def get_remote_call_options(self) -> CommandArgs:
L279: def fetch_new(
L303: def switch(

```

```
L319: def update(
```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/bazaar.py

```
L19: class Bazaar(VersionControl):
L34: def get_base_rev_args(rev: str) -> list[str]:
L37: def fetch_new(
L58: def switch(
L67: def update(
L92: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L100: def get_remote_url(cls, location: str) -> str:
L115: def get_revision(cls, location: str) -> str:
L125: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/mercurial.py

```
L21: class Mercurial(VersionControl):
L34: def get_base_rev_args(rev: str) -> list[str]:
L37: def fetch_new(
L61: def switch(
L86: def update(
L103: def get_remote_url(cls, location: str) -> str:
L115: def get_revision(cls, location: str) -> str:
L128: def get_requirement_revision(cls, location: str) -> str:
L142: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L147: def get_subdirectory(cls, location: str) -> str | None:
L161: def get_repository_root(cls, location: str) -> str | None:
```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/git.py

```
L58: def looks_like_hash(sha: str) -> bool:
L62: class Git(VersionControl):
L79: def get_base_rev_args(rev: str) -> list[str]:
L83: def run_command(cls, *args: Any, **kwargs: Any) -> str:
L91: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:
L105: def get_git_version(self) -> tuple[int, ...]:
L119: def get_current_branch(cls, location: str) -> str | None:
L144: def get_revision_sha(cls, dest: str, rev: str) -> tuple[str | None, bool]:
L190: def _should_fetch(cls, dest: str, rev: str) -> bool:
L213: def resolve_revision(
L259: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:
L273: def fetch_new(
L336: def switch(
L358: def update(
L389: def get_remote_url(cls, location: str) -> str:
L419: def _git_remote_to_pip_url(url: str) -> str:
L450: def has_commit(cls, location: str, rev: str) -> bool:
```

```

L466: def get_revision(cls, location: str, rev: str | None = None) -> str:
L478: def get_subdirectory(cls, location: str) -> str | None:
L496: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:
L527: def update_submodules(cls, location: str, verbosity: int = 0) -> None:
L541: def get_repository_root(cls, location: str) -> str | None:
L566: def should_add_vcs_url_prefix(repo_url: str) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_vendor/__init__.py

```

L29: def vendored(modulename):

```

.venv/lib/python3.12/site-packages/pip/_vendor/tomli_w/_writer.py

```

L33: class Context:
L34: def __init__(self, allow_multiline: bool, indent: int):
L43: def dump(
L56: def dumps(
L63: def gen_table_chunks(
L100: def format_literal(obj: object, ctx: Context, *, nest_level: int = 0) -> str:
L126: def format_decimal(obj: Decimal) -> str:
L135: def format_inline_table(obj: Mapping, ctx: Context) -> str:
L156: def format_inline_array(obj: tuple | list, ctx: Context, nest_level: int) -> str:
L171: def format_key_part(part: str) -> str:
L185: def format_string(s: str, *, allow_multiline: bool) -> str:
L215: def is_aot(obj: Any) -> bool:
L225: def is_suitable_inline_table(obj: Mapping, ctx: Context) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_collections.py

```

L15: class HasGettableStringKeys(Protocol):
L16: def keys(self) -> typing.Iterator[str]: ...
L18: def __getitem__(self, key: str) -> str: ...
L39: class _Sentinel(Enum):
L43: def ensure_can_construct_http_header_dict(
L63: class RecentlyUsedContainer(typing.Generic[_KT, _VT], typing.MutableMapping[_KT, _VT]):
L82: def __init__(
L93: def __getitem__(self, key: _KT) -> _VT:
L100: def __setitem__(self, key: _KT, value: _VT) -> None:
L125: def __delitem__(self, key: _KT) -> None:
L132: def __len__(self) -> int:
L136: def __iter__(self) -> typing.NoReturn:
L141: def clear(self) -> None:
L151: def keys(self) -> set[_KT]: # type: ignore[override]
L156: class HTTPHeaderDictItemView(set[tuple[str, str]]):
L187: def __init__(self, headers: HTTPHeaderDict) -> None:
L190: def __len__(self) -> int:
L193: def __iter__(self) -> typing.Iterator[tuple[str, str]]:

```



```

L196: def __contains__(self, item: object) -> bool:
L204: class HTTPHeaderDict(typing.MutableMapping[str, str]):
L240: def __init__(self, headers: ValidHTTPHeaderSource | None = None, **kwargs: str):
L251: def __setitem__(self, key: str, val: str) -> None:
L257: def __getitem__(self, key: str) -> str:
L263: def __delitem__(self, key: str) -> None:
L268: def __contains__(self, key: object) -> bool:
L275: def setdefault(self, key: str, default: str = "") -> str:
L278: def __eq__(self, other: object) -> bool:
L289: def __ne__(self, other: object) -> bool:
L292: def __len__(self) -> int:
L295: def __iter__(self) -> typing.Iterator[str]:
L300: def discard(self, key: str) -> None:
L306: def add(self, key: str, val: str, *, combine: bool = False) -> None:
L341: def extend(self, *args: ValidHTTPHeaderSource, **kwargs: str) -> None:
L375: def getlist(self, key: str) -> list[str]: ...
L378: def getlist(self, key: str, default: _DT) -> list[str] | _DT: ...
L380: def getlist(
L400: def _prepare_for_method_change(self) -> Self:
L426: def __repr__(self) -> str:
L429: def _copy_from(self, other: HTTPHeaderDict) -> None:
L434: def copy(self) -> Self:
L439: def iteritems(self) -> typing.Iterator[tuple[str, str]]:
L446: def itermerged(self) -> typing.Iterator[tuple[str, str]]:
L452: def items(self) -> HTTPHeaderDictItemView: # type: ignore[override]
L455: def _has_value_for_header(self, header_name: str, potential_value: str) -> bool:
L460: def __ior__(self, other: object) -> HTTPHeaderDict:
L469: def __or__(self, other: object) -> Self:
L479: def __ror__(self, other: object) -> Self:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/fields.py

```

L15: def guess_content_type(
L31: def format_header_param_rfc2231(name: str, value: _TYPE_FIELD_VALUE) -> str:
L79: def format_multipart_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
L117: def format_header_param_html5(name: str, value: _TYPE_FIELD_VALUE) -> str:
L135: def format_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
L153: class RequestField:
L171: def __init__(
L200: def from_tuples(
L244: def _render_part(self, name: str, value: _TYPE_FIELD_VALUE) -> str:
L260: def _render_parts(
L291: def render_headers(self) -> str:
L310: def make_multipart(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connection.py

```

L37: class BaseSSLError(BaseException): # type: ignore[no-redef]

```

```

L82: class HTTPConnection(_HTTPConnection):
L132: def __init__(
L163: def __str__(self) -> str:
L166: def __repr__(self) -> str:
L170: def host(self) -> str:
L189: def host(self, value: str) -> None:
L198: def _new_conn(self) -> socket.socket:
L227: def set_tunnel(
L244: def _wrap_ipv6(self, ip: bytes) -> bytes:
L253: def _tunnel(self) -> None:
L296: def _tunnel(self) -> None: # noqa: F811
L330: def connect(self) -> None:
L348: def is_closed(self) -> bool:
L352: def is_connected(self) -> bool:
L358: def has_connected_to_proxy(self) -> bool:
L362: def proxy_is_forwarding(self) -> bool:
L369: def proxy_is_tunneling(self) -> bool:
L375: def close(self) -> None:
L390: def putrequest(
L410: def putheader(self, header: str, *values: str) -> None: # type: ignore[override]
L424: def request( # type: ignore[override]
L521: def request_chunked(
L540: def getresponse( # type: ignore[override]
L603: class HTTPSConnection(HTTPConnection):
L621: def __init__(
L683: def set_cert(
L724: def connect(self) -> None:
L861: def _connect_tls_proxy(self, hostname: str, sock: socket.socket) -> ssl.SSLSocket:
L891: class _WrappedAndVerifiedSocket(typing.NamedTuple):
L901: def _ssl_wrap_socket_and_match_hostname(
L1026: def _match_hostname(
L1052: def _wrap_proxy_error(err: Exception, proxy_scheme: str | None) -> ProxyError:
L1077: def _get_default_user_agent() -> str:
L1081: class DummyConnection:
L1092: def _url_from_connection(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/response.py

```

L48: class ContentDecoder:
L49: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L53: def has_unconsumed_tail(self) -> bool:
L56: def flush(self) -> bytes:
L60: class DeflateDecoder(ContentDecoder):
L61: def __init__(self) -> None:
L67: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L110: def has_unconsumed_tail(self) -> bool:
L115: def flush(self) -> bytes:
L119: class GzipDecoderState:
L125: class GzipDecoder(ContentDecoder):

```

```

L126: def __init__(self) -> None:
L131: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L182: def has_unconsumed_tail(self) -> bool:
L185: def flush(self) -> bytes:
L191: class BrotliDecoder(ContentDecoder):
L195: def __init__(self) -> None:
L203: def _decompress(self, data: bytes, output_buffer_limit: int = -1) -> bytes:
L206: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L222: def has_unconsumed_tail(self) -> bool:
L228: def flush(self) -> bytes:
L244: class ZstdDecoder(ContentDecoder):
L245: def __init__(self) -> None:
L248: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L283: def has_unconsumed_tail(self) -> bool:
L288: def flush(self) -> bytes:
L294: class MultiDecoder(ContentDecoder):
L307: def __init__(self, modes: str) -> None:
L316: def flush(self) -> bytes:
L319: def decompress(self, data: bytes, max_length: int = -1) -> bytes:
L346: def has_unconsumed_tail(self) -> bool:
L350: def _get_decoder(mode: str) -> ContentDecoder:
L368: class BytesQueueBuffer:
L382: def __init__(self) -> None:
L386: def __len__(self) -> int:
L389: def put(self, data: bytes) -> None:
L393: def get(self, n: int) -> bytes:
L428: def get_all(self) -> bytes:
L445: class BaseHTTPResponse(io.IOBase):
L460: def __init__(
L495: def get_redirect_location(self) -> str | None | typing.Literal[False]:
L508: def data(self) -> bytes:
L511: def json(self) -> typing.Any:
L533: def url(self) -> str | None:
L537: def url(self, url: str | None) -> None:
L541: def connection(self) -> BaseHTTPConnection | None:
L545: def retries(self) -> Retry | None:
L549: def retries(self, retries: Retry | None) -> None:
L555: def stream(
L560: def read(
L568: def read1(
L575: def read_chunked(
L582: def release_conn(self) -> None:
L585: def drain_conn(self) -> None:
L588: def shutdown(self) -> None:
L591: def close(self) -> None:
L594: def _init_decoder(self) -> None:
L613: def _decode(
L650: def _flush_decoder(self) -> bytes:
L660: def readinto(self, b: bytearray) -> int:
L669: def getheaders(self) -> HTTPHeaderDict:
L672: def getheader(self, name: str, default: str | None = None) -> str | None:

```

```

L676: def info(self) -> HTTPHeaderDict:
L679: def geturl(self) -> str | None:
L683: class HTTPResponse(BaseHTTPResponse):
L689: class is also compatible with the Python standard library's :mod:`io`
L716: def __init__(
L780: def release_conn(self) -> None:
L787: def drain_conn(self) -> None:
L803: def data(self) -> bytes:
L814: def connection(self) -> HTTPConnection | None:
L817: def isclosed(self) -> bool:
L820: def tell(self) -> int:
L828: def _init_length(self, request_method: str | None) -> int | None:
L885: def _error_catcher(self) -> typing.Generator[None]:
L950: def _fp_read(
L1007: def _raw_read(
L1059: def read(
L1155: def read1(
L1225: def stream(
L1257: def readable(self) -> bool:
L1260: def shutdown(self) -> None:
L1269: def close(self) -> None:
L1282: def closed(self) -> bool:
L1294: def fileno(self) -> int:
L1305: def flush(self) -> None:
L1313: def supports_chunked_reads(self) -> bool:
L1322: def _update_chunk_length(self) -> None:
L1340: def _handle_chunk(self, amt: int | None) -> bytes:
L1362: def read_chunked(
L1447: def url(self) -> str | None:
L1456: def url(self, url: str | None) -> None:
L1459: def __iter__(self) -> typing.Iterator[bytes]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/exceptions.py

```

L18: class HTTPError(Exception):
L22: class HTTPWarning(Warning):
L29: class PoolError(HTTPError):
L32: def __init__(self, pool: ConnectionPool, message: str) -> None:
L37: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L42: class RequestError(PoolError):
L45: def __init__(self, pool: ConnectionPool, url: str | None, message: str) -> None:
L49: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L54: class SSLError(HTTPError):
L58: class ProxyError(HTTPError):
L64: def __init__(self, message: str, error: Exception) -> None:
L69: class DecodeError(HTTPError):
L73: class ProtocolError(HTTPError):
L84: class MaxRetryError(RequestError):
L95: def __init__(

```

```

L104: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L109: class HostChangedError(RequestError):
L112: def __init__(
L120: class TimeoutStateError(HTTPError):
L124: class TimeoutError(HTTPError):
L132: class ReadTimeoutError(TimeoutError, RequestError):
L138: class ConnectTimeoutError(TimeoutError):
L142: class NewConnectionError(ConnectTimeoutError, HTTPError):
L145: def __init__(self, conn: HTTPConnection, message: str) -> None:
L150: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L155: def pool(self) -> HTTPConnection:
L166: class NameResolutionError(NewConnectionError):
L169: def __init__(self, host: str, conn: HTTPConnection, reason: socket.gaierror):
L175: def __reduce__(self) -> _TYPE_REDUCE_RESULT:
L180: class EmptyPoolError(PoolError):
L184: class FullPoolError(PoolError):
L188: class ClosedPoolError(PoolError):
L192: class LocationValueError(ValueError, HTTPError):
L196: class LocationParseError(LocationValueError):
L199: def __init__(self, location: str) -> None:
L206: class URLSchemeUnknown(LocationValueError):
L209: def __init__(self, scheme: str):
L216: class ResponseError(HTTPError):
L223: class SecurityWarning(HTTPWarning):
L227: class InsecureRequestWarning(SecurityWarning):
L231: class NotOpenSSLWarning(SecurityWarning):
L235: class SystemTimeWarning(SecurityWarning):
L239: class InsecurePlatformWarning(SecurityWarning):
L243: class DependencyWarning(HTTPWarning):
L250: class ResponseNotChunked(ProtocolError, ValueError):
L254: class BodyNotHttpLibCompatible(HTTPError):
L261: class IncompleteRead(HTTPError, httplib_IncompleteRead):
L272: def __init__(self, partial: int, expected: int) -> None:
L276: def __repr__(self) -> str:
L283: class InvalidChunkLength(HTTPError, httplib_IncompleteRead):
L286: def __init__(self, response: HTTPResponse, length: bytes) -> None:
L292: def __repr__(self) -> str:
L299: class InvalidHeader(HTTPError):
L303: class ProxySchemeUnknown(AssertionError, URLSchemeUnknown):
L308: def __init__(self, scheme: str | None) -> None:
L320: class ProxySchemeUnsupported(ValueError):
L324: class HeaderParsingError(HTTPError):
L327: def __init__(
L334: class UnrewindableBodyError(HTTPError):

```

**.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_request_metho
ds.py**

```

L20: class RequestMethods:

```

```

L51: def __init__(self, headers: typing.Mapping[str, str] | None = None) -> None:
L54: def urlopen(
L69: def request(
L147: def request_encode_url(
L184: def request_encode_body(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/__init__.py

```

L74: def add_stderr_logger(
L107: def disable_warnings(category: type[Warning] = exceptions.HTTPWarning) -> None:
L117: def request(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/poolmanager.py

```

L56: class PoolKey(typing.NamedTuple):
L95: def _default_key_normalizer(
L162: class PoolManager(RequestMethods):
L199: def __init__(
L230: def __enter__(self) -> Self:
L233: def __exit__(
L243: def _new_pool(
L281: def clear(self) -> None:
L290: def connection_from_host(
L319: def connection_from_context(
L344: def connection_from_pool_key(
L370: def connection_from_url(
L388: def _merge_pool_kwargs(
L410: def _proxy_requires_url_absolute_form(self, parsed_url: Url) -> bool:
L423: def urlopen( # type: ignore[override]
L506: class ProxyManager(PoolManager):
L561: def __init__(
L602: def connection_from_host(
L618: def _set_proxy_headers(
L635: def urlopen( # type: ignore[override]
L650: def proxy_from_url(url: str, **kw: typing.Any) -> ProxyManager:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/filepost.py

```

L22: def choose_boundary() -> str:
L29: def iter_field_objects(fields: _TYPE_FIELDS) -> typing.Iterable[RequestField]:
L51: def encode_multipart_formdata(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_base_connection.py

```

L12: class ProxyConfig(typing.NamedTuple):
L19: class _ResponseOptions(typing.NamedTuple):
L35: class BaseHTTPConnection(Protocol):
L54: def __init__(
L67: def set_tunnel(
L75: def connect(self) -> None: ...
L77: def request(
L93: def getresponse(self) -> BaseHTTPResponse: ...
L95: def close(self) -> None: ...
L98: def is_closed(self) -> bool:
L105: def is_connected(self) -> bool:
L109: def has_connected_to_proxy(self) -> bool:
L115: class BaseHTTPSConnection(BaseHTTPConnection, Protocol):
L140: def __init__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connectionpool.py

```

L67: class ConnectionPool:
L81: def __init__(self, host: str, port: int | None = None) -> None:
L94: def __str__(self) -> str:
L97: def __enter__(self) -> Self:
L100: def __exit__(
L110: def close(self) -> None:
L120: class HTTPConnectionPool(ConnectionPool, RequestMethods):
L175: def __init__(
L236: def _new_conn(self) -> BaseHTTPConnection:
L256: def _get_conn(self, timeout: float | None = None) -> BaseHTTPConnection:
L294: def _put_conn(self, conn: BaseHTTPConnection | None) -> None:
L337: def _validate_conn(self, conn: BaseHTTPConnection) -> None:
L342: def _prepare_proxy(self, conn: BaseHTTPConnection) -> None:
L346: def _get_timeout(self, timeout: _TYPE_TIMEOUT) -> Timeout:
L358: def _raise_timeout(
L377: def _make_request(
L558: def close(self) -> None:
L570: def is_same_host(self, url: str) -> bool:
L592: def urlopen( # type: ignore[override]
L963: class HTTPSConnectionPool(HTTPConnectionPool):
L980: def __init__(
L1029: def _prepare_proxy(self, conn: HTTPSConnection) -> None: # type: ignore[override]
L1044: def _new_conn(self) -> BaseHTTPSConnection:
L1085: def _validate_conn(self, conn: BaseHTTPConnection) -> None:
L1108: def connection_from_url(url: str, **kw: typing.Any) -> HTTPConnectionPool:
L1138: def _normalize_host(host: None, scheme: str | None) -> None: ...
L1142: def _normalize_host(host: str, scheme: str | None) -> str: ...
L1145: def _normalize_host(host: str | None, scheme: str | None) -> str | None:
L1163: def _url_from_pool(
L1170: def _close_pool_connections(pool: queue.LifoQueue[typing.Any]) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/timeout.py

```

L14: class _TYPE_DEFAULT(Enum):
L25: class Timeout:
L109: def __init__(
L120: def __repr__(self) -> str:
L127: def resolve_default_timeout(timeout: _TYPE_TIMEOUT) -> float | None:
L131: def _validate_timeout(cls, value: _TYPE_TIMEOUT, name: str) -> _TYPE_TIMEOUT:
L173: def from_float(cls, timeout: _TYPE_TIMEOUT) -> Timeout:
L188: def clone(self) -> Timeout:
L202: def start_connect(self) -> float:
L213: def get_connect_duration(self) -> float:
L228: def connect_timeout(self) -> _TYPE_TIMEOUT:
L246: def read_timeout(self) -> float | None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/retry.py

```

L33: class RequestHistory(typing.NamedTuple):
L41: class Retry:
L211: def __init__(
L258: def new(self, **kw: typing.Any) -> Self:
L283: def from_int(
L301: def get_backoff_time(self) -> float:
L320: def parse_retry_after(self, retry_after: str) -> float:
L341: def get_retry_after(self, response: BaseHTTPResponse) -> float | None:
L351: def sleep_for_retry(self, response: BaseHTTPResponse) -> bool:
L359: def _sleep_backoff(self) -> None:
L365: def sleep(self, response: BaseHTTPResponse | None = None) -> None:
L381: def _is_connection_error(self, err: Exception) -> bool:
L389: def _is_read_error(self, err: Exception) -> bool:
L395: def _is_method_retryable(self, method: str) -> bool:
L403: def is_retry(
L425: def is_exhausted(self) -> bool:
L444: def increment(
L541: def __repr__(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/wait.py

```

L33: def select_wait_for_socket(
L57: def poll_wait_for_socket(
L74: def do_poll(t: float | None) -> list[tuple[int, int]]:
L82: def _have_working_poll() -> bool:
L95: def wait_for_socket(
L113: def wait_for_read(sock: socket.socket, timeout: float | None = None) -> bool:
L120: def wait_for_write(sock: socket.socket, timeout: float | None = None) -> bool:

```


.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/connection.py

```
L15: def is_connection_dropped(conn: BaseHTTPConnection) -> bool: # Platform-specific
L27: def create_connection(
L93: def _set_socket_options(
L103: def allowed_gai_family() -> socket.AddressFamily:
L114: def _has_ipv6(host: str) -> bool:
```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/url.py

```
L80: class Url(
L100: def __new__( # type: ignore[no-untyped-def]
L117: def hostname(self) -> str | None:
L122: def request_uri(self) -> str:
L132: def authority(self) -> str | None:
L148: def netloc(self) -> str | None:
L162: def url(self) -> str:
L209: def __str__(self) -> str:
L214: def _encode_invalid_chars(
L221: def _encode_invalid_chars(
L227: def _encode_invalid_chars(
L263: def _remove_path_dot_segments(path: str) -> str:
L294: def _normalize_host(host: None, scheme: str | None) -> None: ...
L298: def _normalize_host(host: str, scheme: str | None) -> str: ...
L301: def _normalize_host(host: str | None, scheme: str | None) -> str | None:
L330: def _idna_encode(name: str) -> bytes:
L349: def _encode_target(target: str) -> str:
L367: def parse_url(url: str) -> Url:
```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/response.py

```
L9: def is_fp_closed(obj: object) -> bool:
L40: def assert_header_parsing(headers: httplib.HTTPMessage) -> None:
L91: def is_response_to_head(response: httplib.HTTPResponse) -> bool:
```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssltransport.py

```
L22: class SSLTransport:
L34: def _validate_ssl_context_for_tls_in_tls(ssl_context: ssl.SSLContext) -> None:
L49: def __init__(
L72: def __enter__(self) -> Self:
L75: def __exit__(self, *_: typing.Any) -> None:
L78: def fileno(self) -> int:
```

```

L81: def read(self, len: int = 1024, buffer: typing.Any | None = None) -> int | bytes:
L84: def recv(self, buflen: int = 1024, flags: int = 0) -> int | bytes:
L89: def recv_into(
L101: def sendall(self, data: bytes, flags: int = 0) -> None:
L111: def send(self, data: bytes, flags: int = 0) -> int:
L116: def makefile(
L168: def unwrap(self) -> None:
L171: def close(self) -> None:
L175: def getpeercert(
L180: def getpeercert(self, binary_form: typing.Literal[True]) -> bytes | None: ...
L182: def getpeercert(self, binary_form: bool = False) -> _TYPE_PEER_CERT_RET:
L185: def version(self) -> str | None:
L188: def cipher(self) -> tuple[str, str, int] | None:
L191: def selected_alpn_protocol(self) -> str | None:
L194: def shared_ciphers(self) -> list[tuple[str, str, int]] | None:
L197: def compression(self) -> str | None:
L200: def settimeout(self, value: float | None) -> None:
L203: def gettimeout(self) -> float | None:
L206: def _decref_socketios(self) -> None:
L209: def _wrap_ssl_read(self, len: int, buffer: bytearray | None = None) -> int | bytes:
L220: def _ssl_io_loop(self, func: typing.Callable[[], None]) -> None: ...
L224: def _ssl_io_loop(self, func: typing.Callable[[bytes], int], arg1: bytes) -> int: ...
L228: def _ssl_io_loop(
L235: def _ssl_io_loop(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl_match_hostname.py

```

L20: class CertificateError(ValueError):
L24: def _dnsname_match(
L80: def _ipaddress_match(ipname: str, host_ip: IPv4Address | IPv6Address) -> bool:
L95: def match_hostname(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/proxy.py

```

L11: def connection_requires_http_tunnel(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl_.py

```

L30: def _is_bpo_43522_fixed(
L56: def _is_has_never_check_common_name_reliable(
L84: class _TYPE_PEER_CERT_RET_DICT(TypedDict, total=False):
L152: def assert_fingerprint(cert: bytes | None, fingerprint: str) -> None:
L186: def resolve_cert_reqs(candidate: None | int | str) -> VerifyMode:
L209: def resolve_ssl_version(candidate: None | int | str) -> int:
L225: def create_urllib3_context(

```

```

L378: def ssl_wrap_socket(
L396: def ssl_wrap_socket(
L413: def ssl_wrap_socket(
L487: def is_ipaddress(hostname: str | bytes) -> bool:
L500: def _is_key_file_encrypted(key_file: str) -> bool:
L511: def _ssl_wrap_socket_impl(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/util.py

```

L7: def to_bytes(
L19: def to_str(
L31: def reraise(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/request.py

```

L35: class _TYPE_FAILEDTELL(Enum):
L51: def make_headers(
L133: def set_file_position(
L153: def rewind_body(body: typing.IO[typing.AnyStr], body_pos: _TYPE_BODY_POSITION) -> None:
L183: class ChunksAndContentLength(typing.NamedTuple):
L188: def body_to_chunks(
L221: def chunk_readable() -> typing.Iterable[bytes]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/connection.py

```

L29: def _is_legal_header_name(name: bytes) -> bool:
L44: def _is_illegal_header_value(value: bytes) -> bool:
L54: class _LockedObject(typing.Generic[T]):
L68: def __init__(self, obj: T):
L72: def __enter__(self) -> T:
L76: def __exit__(
L85: class HTTP2Connection(HTTPSSConnection):
L86: def __init__(
L101: def _new_h2_conn(self) -> _LockedObject[h2.connection.H2Connection]:
L105: def connect(self) -> None:
L112: def putrequest( # type: ignore[override]
L143: def putheader(self, header: str | bytes, *values: str | bytes) -> None: # type:
ignore[override]
L156: def endheaders(self, message_body: typing.Any = None) -> None: # type:
ignore[override]
L170: def send(self, data: typing.Any) -> None:
L215: def set_tunnel(
L226: def getresponse( # type: ignore[override]
L268: def request( # type: ignore[override]
L307: def close(self) -> None:

```

```

L324: class HTTP2Response(BaseHTTPResponse):
L326: def __init__(
L349: def data(self) -> bytes:
L352: def get_redirect_location(self) -> None:
L355: def close(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/__init__.py

```

L15: def inject_into_urllib3() -> None:
L43: def extract_from_urllib3() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/probe.py

```

L6: class _HTTP2ProbeCache:
L13: def __init__(self) -> None:
L18: def acquire_and_get(self, host: str, port: int) -> bool | None:
L51: def set_and_release(
L65: def _values(self) -> dict[tuple[str, int], bool | None]:
L70: def _reset(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/pyopenssl.py

```

L50: class UnsupportedExtension(Exception): # type: ignore[no-redef]
L139: def inject_into_urllib3() -> None:
L150: def extract_from_urllib3() -> None:
L159: def _validate_dependencies_met() -> None:
L185: def _dnsname_to_stdlib(name: str) -> str | None:
L199: def idna_encode(name: str) -> bytes | None:
L226: def get_subj_alt_name(peer_cert: X509) -> list[tuple[str, str]]:
L274: class WrappedSocket:
L277: def __init__(
L289: def fileno(self) -> int:
L293: def _decref_socketios(self) -> None:
L299: def recv(self, *args: typing.Any, **kwargs: typing.Any) -> bytes:
L324: def recv_into(self, *args: typing.Any, **kwargs: typing.Any) -> int:
L347: def settimeout(self, timeout: float) -> None:
L350: def _send_until_done(self, data: bytes) -> int:
L361: def sendall(self, data: bytes) -> None:
L369: def shutdown(self, how: int) -> None:
L375: def close(self) -> None:
L380: def _real_close(self) -> None:
L386: def getpeercert(
L402: def version(self) -> str:
L405: def selected_alpn_protocol(self) -> str | None:
L413: class PyOpenSSLContext:

```

```

L420: def __init__(self, protocol: int) -> None:
L430: def options(self) -> int:
L434: def options(self, value: int) -> None:
L439: def verify_flags(self) -> int:
L443: def verify_flags(self, value: int) -> None:
L448: def verify_mode(self) -> int:
L452: def verify_mode(self, value: ssl.VerifyMode) -> None:
L455: def set_default_verify_paths(self) -> None:
L458: def set_ciphers(self, ciphers: bytes | str) -> None:
L463: def load_verify_locations(
L480: def load_cert_chain(
L496: def set_alpn_protocols(self, protocols: list[bytes | str]) -> None:
L500: def wrap_socket(
L531: def _set_ctx_options(self) -> None:
L539: def minimum_version(self) -> int:
L543: def minimum_version(self, minimum_version: int) -> None:
L548: def maximum_version(self) -> int:
L552: def maximum_version(self, maximum_version: int) -> None:
L557: def _verify_callback(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/socks.py

```

L75: class _TYPE SOCKS_OPTIONS(typing.TypedDict):
L84: class SOCKSConnection(HTTPConnection):
L89: def __init__(
L98: def _new_conn(self) -> socks.socksocket:
L161: class SOCKSHTTPConnection(SOCKSConnection, HTTPConnection):
L165: class SOCKSHTTPConnectionPool(HTTPConnectionPool):
L169: class SOCKSHTTPConnectionPool(HTTPConnectionPool):
L173: class SOCKSProxyManager(PoolManager):
L184: def __init__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/fetch.py

```

L71: class _RequestError(Exception):
L72: def __init__(
L85: class _StreamingError(_RequestError):
L89: class _TimeoutError(_RequestError):
L93: def _obj_from_dict(dict_val: dict[str, Any]) -> JsProxy:
L97: class _ReadStream(io.RawIOBase):
L98: def __init__(
L118: def __del__(self) -> None:
L122: def is_closed(self) -> bool:
L127: def closed(self) -> bool:
L130: def close(self) -> None:
L144: def readable(self) -> bool:
L147: def writable(self) -> bool:

```

```

L150: def seekable(self) -> bool:
L153: def readinto(self, byte_obj: Buffer) -> int:
L200: class _StreamingFetcher:
L201: def __init__(self) -> None:
L214: def promise_resolver(js_resolve_fn: JsProxy, js_reject_fn: JsProxy) -> None:
L215: def onMsg(e: JsProxy) -> None:
L219: def onErr(e: JsProxy) -> None:
L229: def send(self, request: EmscriptenRequest) -> EmscriptenResponse:
L302: class _JSPiReadStream(io.RawIOBase):
L324: def __init__(
L342: def __del__(self) -> None:
L346: def is_closed(self) -> bool:
L351: def closed(self) -> bool:
L354: def close(self) -> None:
L367: def readable(self) -> bool:
L370: def writable(self) -> bool:
L373: def seekable(self) -> bool:
L376: def _get_next_buffer(self) -> bool:
L392: def readinto(self, byte_obj: Buffer) -> int:
L410: def is_in_browser_main_thread() -> bool:
L414: def is_cross_origin_isolated() -> bool:
L418: def is_in_node() -> bool:
L427: def is_worker_available() -> bool:
L449: def send_streaming_request(request: EmscriptenRequest) -> EmscriptenResponse | None:
L469: def _show_timeout_warning() -> None:
L480: def _show_streaming_warning() -> None:
L499: def send_request(request: EmscriptenRequest) -> EmscriptenResponse:
L548: def send_jspi_request(
L626: def _run_sync_with_timeout(
L680: def has_jspi() -> bool:
L699: def _is_node_js() -> bool:
L714: def streaming_ready() -> bool | None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/connection.py

```

L25: class EmscriptenHTTPConnection:
L46: def __init__(
L73: def set_tunnel(
L82: def connect(self) -> None:
L85: def request(
L129: def getresponse(self) -> BaseHTTPResponse:
L139: def close(self) -> None:
L144: def is_closed(self) -> bool:
L152: def is_connected(self) -> bool:
L157: def has_connected_to_proxy(self) -> bool:
L165: class EmscriptenHTTPConnection(EmscriptenHTTPConnection):
L182: def __init__(
L242: def set_cert(

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/response.py

```

L23: class EmscriptenResponse:
L30: class EmscriptenHttpResponseWrapper(BaseHTTPResponse):
L31: def __init__(
L56: def url(self) -> str | None:
L60: def url(self, url: str | None) -> None:
L64: def connection(self) -> BaseHTTPConnection | BaseHTTPSConnection | None:
L68: def retries(self) -> Retry | None:
L72: def retries(self, retries: Retry | None) -> None:
L76: def stream(
L102: def _init_length(self, request_method: str | None) -> int | None:
L139: def read(
L176: def read_chunked(
L188: def release_conn(self) -> None:
L195: def drain_conn(self) -> None:
L199: def data(self) -> bytes:
L205: def json(self) -> typing.Any:
L226: def close(self) -> None:
L236: def _error_catcher(self) -> typing.Generator[None]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/__init__.py

```

L9: def inject_into_urllib3() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/request.py

```

L9: class EmscriptenRequest:
L18: def set_header(self, name: str, value: str) -> None:
L21: def set_body(self, body: _TYPE_BODY | None) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/providers.py

```

L17: class Preference(Protocol):
L18: def __lt__(self, __other: Any) -> bool: ...
L21: class AbstractProvider(Generic[RT, CT, KT]):
L24: def identify(self, requirement_or_candidate: RT | CT) -> KT:
L33: def get_preference(
L92: def find_matches(
L127: def is_satisfied_by(self, requirement: RT, candidate: CT) -> bool:
L138: def get_dependencies(self, candidate: CT) -> Iterable[RT]:

```

```
L146: def narrow_requirement_selection(
```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/structs.py

```
L27: class RequirementInformation(NamedTuple, Generic[RT, CT]):
L31: class State(NamedTuple, Generic[RT, CT, KT]):
L45: class DirectedGraph(Generic[KT]):
L48: def __init__(self) -> None:
L53: def __iter__(self) -> Iterator[KT]:
L56: def __len__(self) -> int:
L59: def __contains__(self, key: KT) -> bool:
L62: def copy(self) -> DirectedGraph[KT]:
L70: def add(self, key: KT) -> None:
L78: def remove(self, key: KT) -> None:
L86: def connected(self, f: KT, t: KT) -> bool:
L89: def connect(self, f: KT, t: KT) -> None:
L99: def iter_edges(self) -> Iterator[tuple[KT, KT]]:
L104: def iter_children(self, key: KT) -> Iterator[KT]:
L107: def iter_parents(self, key: KT) -> Iterator[KT]:
L111: class IteratorMapping(Mapping[KT, Iterator[CT]], Generic[RT, CT, KT]):
L112: def __init__(
L122: def __repr__(self) -> str:
L129: def __bool__(self) -> bool:
L132: def __contains__(self, key: object) -> bool:
L135: def __getitem__(self, k: KT) -> Iterator[CT]:
L142: def __iter__(self) -> Iterator[KT]:
L146: def __len__(self) -> int:
L151: class _FactoryIterableView(Iterable[RT]):
L160: def __init__(self, factory: Callable[[], Iterable[RT]]) -> None:
L164: def __repr__(self) -> str:
L167: def __bool__(self) -> bool:
L174: def __iter__(self) -> Iterator[RT]:
L180: class _SequenceIterableView(Iterable[RT]):
L187: def __init__(self, sequence: Sequence[RT]):
L190: def __repr__(self) -> str:
L193: def __bool__(self) -> bool:
L196: def __iter__(self) -> Iterator[RT]:
L200: def build_iter_view(matches: Matches[CT]) -> Iterable[CT]:
```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/reporters.py

```
L11: class BaseReporter(Generic[RT, CT, KT]):
L14: def starting(self) -> None:
L17: def starting_round(self, index: int) -> None:
L23: def ending_round(self, index: int, state: State[RT, CT, KT]) -> None:
L30: def ending(self, state: State[RT, CT, KT]) -> None:
L33: def adding_requirement(self, requirement: RT, parent: CT | None) -> None:
L43: def resolving_conflicts(
```



```

L51: def rejecting_candidate(self, criterion: Criterion[RT, CT], candidate: CT) -> None:
L54: def pinning(self, candidate: CT) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/resolution.py

```

L38: def _build_result(state: State[RT, CT, KT]) -> Result[RT, CT, KT]:
L68: class Resolution(Generic[RT, CT, KT]):
L75: def __init__(
L90: def state(self) -> State[RT, CT, KT]:
L96: def _push_new_state(self) -> None:
L110: def _add_to_criteria(
L154: def _remove_information_from_criteria(
L181: def _get_preference(self, name: KT) -> Preference:
L196: def _is_current_pin_satisfying(
L208: def _get_updated_criteria(self, candidate: CT) -> dict[KT, Criterion[RT, CT]]:
L214: def _attempt_to_pin_criterion(self, name: KT) -> list[Criterion[RT, CT]]:
L251: def _patch_criteria(
L286: def _save_state(self) -> None:
L298: def _rollback_states(self) -> None:
L305: def _backjump(self, causes: list[RequirementInformation[RT, CT]]) -> bool:
L412: def _extract_causes(
L418: def resolve(self, requirements: Iterable[RT], max_rounds: int) -> State[RT, CT, KT]:
L563: class Resolver(AbstractResolver[RT, CT, KT]):
L568: def resolve( # type: ignore[override]
L605: def _has_route_to_root(

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/exceptions.py

```

L11: class ResolverException(Exception):
L19: class RequirementsConflicted(ResolverException, Generic[RT, CT]):
L20: def __init__(self, criterion: Criterion[RT, CT]) -> None:
L24: def __str__(self) -> str:
L30: class InconsistentCandidate(ResolverException, Generic[RT, CT]):
L31: def __init__(self, candidate: CT, criterion: Criterion[RT, CT]):
L36: def __str__(self) -> str:
L43: class ResolutionError(ResolverException):
L47: class ResolutionImpossible(ResolutionError, Generic[RT, CT]):
L48: def __init__(self, causes: Collection[RequirementInformation[RT, CT]]):
L54: class ResolutionTooDeep(ResolutionError):
L55: def __init__(self, round_count: int) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/abstract.py

```

L13: class Result(NamedTuple, Generic[RT, CT, KT]):
L22: class AbstractResolver(Generic[RT, CT, KT]):
L27: def __init__(
L35: def resolve(self, requirements: Iterable[RT], **kwargs: Any) -> Result[RT, CT, KT]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/criterion.py

```

L8: class Criterion(Generic[RT, CT]):
L28: def __init__(
L38: def __repr__(self) -> str:
L44: def iter_requirement(self) -> Iterator[RT]:
L47: def iter_parent(self) -> Iterator[CT | None]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/compat.py

```

L6: def ToASCII(label: str) -> bytes:
L10: def ToUnicode(label: Union[bytes, bytearray]) -> str:
L14: def nameprep(s: Any) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/core.py

```

L14: class IDNAError(UnicodeError):
L20: class IDNABidiError(IDNAError):
L26: class InvalidCodepoint(IDNAError):
L32: class InvalidCodepointContext(IDNAError):
L38: def _combining_class(cp: int) -> int:
L46: def _is_script(cp: str, script: str) -> bool:
L50: def _punycode(s: str) -> bytes:
L54: def _unot(s: int) -> str:
L58: def valid_label_length(label: Union[bytes, str]) -> bool:
L64: def valid_string_length(label: Union[bytes, str], trailing_dot: bool) -> bool:
L70: def check_bidi(label: str, check_ltr: bool = False) -> bool:
L140: def check_initial_combiner(label: str) -> bool:
L146: def check_hyphen_ok(label: str) -> bool:
L154: def check_nfc(label: str) -> None:
L159: def valid_contextj(label: str, pos: int) -> bool:
L203: def valid_contexto(label: str, pos: int, exception: bool = False) -> bool:
L245: def check_label(label: Union[str, bytes, bytearray]) -> None:
L284: def alabel(label: str) -> bytes:
L303: def ulabel(label: Union[str, bytes, bytearray]) -> str:
L332: def uts46_remap(domain: str, std3_rules: bool = True, transitional: bool = False) -> str:
L366: def encode(
L405: def decode(

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/codec.py

```

L10: class Codec(codecs.Codec):
L11: def encode(self, data: str, errors: str = "strict") -> Tuple[bytes, int]:
L20: def decode(self, data: bytes, errors: str = "strict") -> Tuple[str, int]:
L30: class IncrementalEncoder(codecs.BufferedIncrementalEncoder):
L31: def _buffer_encode(self, data: str, errors: str, final: bool) -> Tuple[bytes, int]:
L64: class IncrementalDecoder(codecs.BufferedIncrementalDecoder):
L65: def _buffer_decode(self, data: Any, errors: str, final: bool) -> Tuple[str, int]:
L100: class StreamWriter(Codec, codecs.StreamWriter):
L104: class StreamReader(Codec, codecs.StreamReader):
L108: def search_function(name: str) -> Optional[codecs.CodecInfo]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/intranges.py

```

L12: def intranges_from_list(list_: List[int]) -> Tuple[int, ...]:
L34: def _encode_range(start: int, end: int) -> int:
L38: def _decode_range(r: int) -> Tuple[int, int]:
L42: def intranges_contain(int_: int, ranges: Tuple[int, ...]) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/uts46data.py

```

L12: def _seg_0() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L117: def _seg_1() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L222: def _seg_2() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L327: def _seg_3() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L432: def _seg_4() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L537: def _seg_5() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L642: def _seg_6() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L747: def _seg_7() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L852: def _seg_8() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L957: def _seg_9() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1062: def _seg_10() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1167: def _seg_11() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1272: def _seg_12() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1377: def _seg_13() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1482: def _seg_14() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1587: def _seg_15() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1692: def _seg_16() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1797: def _seg_17() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L1902: def _seg_18() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2007: def _seg_19() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2112: def _seg_20() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2217: def _seg_21() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2322: def _seg_22() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2427: def _seg_23() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2532: def _seg_24() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:

```

```

L2637: def _seg_25() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2742: def _seg_26() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2847: def _seg_27() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L2952: def _seg_28() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3057: def _seg_29() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3162: def _seg_30() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3267: def _seg_31() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3372: def _seg_32() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3477: def _seg_33() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3582: def _seg_34() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3687: def _seg_35() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3792: def _seg_36() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L3897: def _seg_37() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4002: def _seg_38() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4107: def _seg_39() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4212: def _seg_40() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4317: def _seg_41() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4422: def _seg_42() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4527: def _seg_43() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4632: def _seg_44() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4737: def _seg_45() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4842: def _seg_46() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L4947: def _seg_47() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5052: def _seg_48() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5157: def _seg_49() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5262: def _seg_50() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5367: def _seg_51() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5472: def _seg_52() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5577: def _seg_53() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5682: def _seg_54() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5787: def _seg_55() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5892: def _seg_56() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L5997: def _seg_57() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6102: def _seg_58() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6207: def _seg_59() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6312: def _seg_60() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6417: def _seg_61() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6522: def _seg_62() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6627: def _seg_63() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6732: def _seg_64() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6837: def _seg_65() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L6942: def _seg_66() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7047: def _seg_67() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7152: def _seg_68() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7257: def _seg_69() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7362: def _seg_70() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7467: def _seg_71() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7572: def _seg_72() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7677: def _seg_73() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7782: def _seg_74() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L7887: def _seg_75() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:

```

```

L7992: def _seg_76() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8097: def _seg_77() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8202: def _seg_78() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8307: def _seg_79() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8412: def _seg_80() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8517: def _seg_81() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8622: def _seg_82() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:
L8727: def _seg_83() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_elffile.py

```

L18: class ELFInvalid(ValueError):
L22: class EIClass(enum.IntEnum):
L27: class EIData(enum.IntEnum):
L32: class EMachine(enum.IntEnum):
L40: class ELFFile:
L45: def __init__(self, f: IO[bytes]) -> None:
L90: def _read(self, fmt: str) -> tuple[int, ...]:
L94: def interpreter(self) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_manylinux.py

```

L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:
L40: def _is_linux_armhf(executable: str) -> bool:
L55: def _is_linux_i686(executable: str) -> bool:
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:
L81: class _GLibCVersion(NamedTuple):
L86: def _glibc_version_string_confstr() -> str | None:
L105: def _glibc_version_string_ctypes() -> str | None:
L149: def _glibc_version_string() -> str | None:
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:
L174: def _get_glibc_version() -> _GLibCVersion:
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/direct_url.py

```

L27: def __dir__() -> list[str]:
L34: class _FromMappingProtocol(Protocol): # pragma: no cover
L36: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L42: def _json_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L46: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L59: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
L66: def _get_object(
L83: def _strip_auth_from_netloc(netloc: str, safe_user_passwords: Collection[str]) -> str:

```

```

L94: def _strip_url(url: str, safe_user_passwords: Collection[str]) -> str:
L112: class DirectUrlValidationError(Exception):
L118: def __init__(
L136: def __str__(self) -> str:
L142: class _DirectUrlRequiredKeyError(DirectUrlValidationError):
L143: def __init__(self, key: str) -> None:
L148: class VcsInfo:
L153: def __init__(
L165: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L175: class ArchiveInfo:
L178: def __init__(
L186: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L221: class DirInfo:
L224: def __init__(
L232: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L239: class DirectUrl:
L248: def __init__(
L264: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L289: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L293: def to_dict(
L320: def validate(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/metadata.py

```

L40: def __dir__() -> list[str]:
L44: class InvalidMetadata(ValueError):
L50: def __init__(self, field: str, message: str) -> None:
L59: class RawMetadata(TypedDict, total=False):
L178: def _parse_keywords(data: str) -> list[str]:
L183: def _parse_project_urls(data: list[str]) -> dict[str, str]:
L222: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:
L291: class RFC822Policy(email.policy.EmailPolicy):
L301: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:
L308: class RFC822Message(email.message.EmailMessage):
L315: def __init__(self) -> None:
L318: def as_bytes(
L329: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
L520: class _Validator(Generic[T]):
L534: def __init__(
L541: def __set_name__(self, _owner: Metadata, name: str) -> None:
L545: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:
L572: def _invalid_metadata(
L581: def _process_metadata_version(self, value: str) -> _MetadataVersion:
L587: def _process_name(self, value: str) -> str:
L600: def _process_version(self, value: str) -> version_module.Version:
L610: def _process_summary(self, value: str) -> str:
L616: def _process_description_content_type(self, value: str) -> str:
L648: def _process_dynamic(self, value: list[str]) -> list[str]:
L660: def _process_provides_extra(

```

```

L675: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:
L683: def _process_requires_dist(
L698: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
L706: def _process_license_files(self, value: list[str]) -> list[str]:
L732: def _process_import_names(self, value: list[str]) -> list[str]:
L757: class Metadata:
L769: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata:
L823: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
L932: def as_rfc822(self) -> RFC822Message:
L940: def _write_metadata(self, message: RFC822Message) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/markers.py

```

L30: def __dir__() -> list[str]:
L54: class InvalidMarker(ValueError):
L62: class UndefinedComparison(ValueError):
L71: class UndefinedEnvironmentName(ValueError):
L75: class Environment(TypedDict):
L152: def _normalize_extras(
L168: def _normalize_extra_values(results: MarkerList) -> MarkerList:
L176: def _format_marker(
L216: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
L233: def _normalize(
L254: def _evaluate_markers(
L287: def _format_full_version(info: sys._version_info) -> str:
L295: def default_environment() -> Environment:
L317: class Marker:
L339: def __init__(self, marker: str) -> None:
L370: def _from_markers(cls, markers: MarkerList) -> Marker:
L379: def __str__(self) -> str:
L382: def __repr__(self) -> str:
L385: def __hash__(self) -> int:
L388: def __eq__(self, other: object) -> bool:
L394: def __getstate__(self) -> str:
L399: def __setstate__(self, state: object) -> None:
L423: def __and__(self, other: Marker) -> Marker:
L428: def __or__(self, other: Marker) -> Marker:
L433: def evaluate(
L482: def _repair_python_full_version(

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/specifiers.py

```

L48: def __dir__() -> list[str]:
L52: def _validate_spec(spec: object, /) -> TypeGuard[tuple[str, str]]:
L61: def _validate_pre(pre: object, /) -> TypeGuard[bool | None]:
L74: def _trim_release(release: tuple[int, ...]) -> tuple[int, ...]:
L82: class _BoundaryKind(enum.Enum):
L90: class _BoundaryVersion:

```

```

L113: def __init__(self, version: Version, kind: _BoundaryKind) -> None:
L118: def __is_family(self, other: Version) -> bool:
L133: def __eq__(self, other: object) -> bool:
L138: def __lt__(self, other: _BoundaryVersion | Version) -> bool:
L145: def __hash__(self) -> int:
L148: def __repr__(self) -> str:
L153: class _LowerBound:
L163: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:
L167: def __eq__(self, other: object) -> bool:
L172: def __lt__(self, other: _LowerBound) -> bool:
L185: def __hash__(self) -> int:
L188: def __repr__(self) -> str:
L194: class _UpperBound:
L204: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:
L208: def __eq__(self, other: object) -> bool:
L213: def __lt__(self, other: _UpperBound) -> bool:
L226: def __hash__(self) -> int:
L229: def __repr__(self) -> str:
L246: def _range_is_empty(lower: _LowerBound, upper: _UpperBound) -> bool:
L255: def _intersect_ranges(
L281: def _next_prefix_dev0(version: Version) -> Version:
L287: def _base_dev0(version: Version) -> Version:
L292: def _coerce_version(version: UnparsedVersion) -> Version | None:
L301: def _public_version(version: Version) -> Version:
L307: def _post_base(version: Version) -> Version:
L315: def _earliest_prerelease(version: Version) -> Version:
L323: def _nearest_non_prerelease(
L344: class InvalidSpecifier(ValueError):
L356: class BaseSpecifier(metaclass=abc.ABCMeta):
L361: def _str(self) -> str:
L366: def __str__(self) -> str:
L373: def __hash__(self) -> int:
L379: def __eq__(self, other: object) -> bool:
L389: def prereleases(self) -> bool | None:
L397: def prereleases(self, value: bool) -> None:
L404: def contains(self, item: str, prereleases: bool | None = None) -> bool:
L410: def filter(
L418: def filter(
L426: def filter(
L438: class Specifier(BaseSpecifier):
L573: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:
L611: def _get_spec_version(self, version: str) -> Version | None:
L623: def _require_spec_version(self, version: str) -> Version:
L633: def _to_ranges(self) -> Sequence[_VersionRange]:
L657: def _wildcard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:
L670: def _standard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:
L733: def prereleases(self) -> bool | None:
L761: def prereleases(self, value: bool | None) -> None:
L764: def __getstate__(self) -> tuple[tuple[str, str], bool | None]:
L770: def __setstate__(self, state: object) -> None:
L805: def operator(self) -> str:

```



```

L814: def version(self) -> str:
L822: def __repr__(self) -> str:
L840: def __str__(self) -> str:
L851: def _canonical_spec(self) -> tuple[str, str]:
L864: def __hash__(self) -> int:
L867: def __eq__(self, other: object) -> bool:
L896: def _get_operator(self, op: str) -> CallableOperator:
L902: def _compare_compatible(self, prospective: Version, spec: str) -> bool:
L922: def _get_wildcard_split(self, spec: str) -> tuple[list[str], int]:
L938: def _compare_equal(self, prospective: Version, spec: str) -> bool:
L974: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:
L977: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:
L983: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
L989: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:
L1014: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
L1046: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
L1049: def __contains__(self, item: str | Version) -> bool:
L1070: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
L1098: def filter(
L1106: def filter(
L1113: def filter(
L1198: def _pep440_filter_prereleases(
L1240: def _version_split(version: str) -> list[str]:
L1262: def _version_join(components: list[str]) -> str:
L1273: def _is_not_suffix(segment: str) -> bool:
L1279: def _numeric_prefix_len(split: list[str]) -> int:
L1293: def _left_pad(split: list[str], target_numeric_len: int) -> list[str]:
L1307: def _operator_cost(op_entry: tuple[CallableOperator, str, str]) -> int:
L1334: class SpecifierSet(BaseSpecifier):
L1362: def __init__(
L1407: def _canonical_specs(self) -> tuple[Specifier, ...]:
L1417: def prereleases(self) -> bool | None:
L1437: def prereleases(self, value: bool | None) -> None:
L1441: def __getstate__(self) -> tuple[tuple[Specifier, ...], bool | None]:
L1447: def __setstate__(self, state: object) -> None:
L1504: def __repr__(self) -> str:
L1525: def __str__(self) -> str:
L1538: def __hash__(self) -> int:
L1541: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:
L1574: def __eq__(self, other: object) -> bool:
L1600: def __len__(self) -> int:
L1604: def __iter__(self) -> Iterator[Specifier]:
L1614: def _get_ranges(self) -> Sequence[_VersionRange]:
L1636: def is_unsatisfiable(self) -> bool:
L1669: def _check_prerelease_only_ranges(self) -> bool:
L1682: def _check_arbitrary_unsatisfiable(self) -> bool:
L1721: def __contains__(self, item: UnparsedVersion) -> bool:
L1742: def contains(
L1788: def filter(
L1796: def filter(
L1803: def filter(

```

```
L1899: def _filter_versions(
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/dependency_groups.py

```
L19: def __dir__() -> list[str]:
L28: class DuplicateGroupNames(ValueError):
L34: class CyclicDependencyGroup(ValueError):
L39: def __init__(self, requested_group: str, group: str, include_group: str) -> None:
L57: class InvalidDependencyGroupObject(ValueError):
L69: class DependencyGroupInclude:
L72: def __init__(self, include_group: str) -> None:
L80: def __repr__(self) -> str:
L84: class DependencyGroupResolver:
L96: def __init__(
L115: def lookup(self, group: str) -> tuple[Requirement | DependencyGroupInclude, ...]:
L129: def resolve(self, group: str) -> tuple[Requirement, ...]:
L142: def _resolve(
L200: def _parse_group(
L255: def resolve_dependency_groups(
L277: def _normalize_name(name: str) -> str:
L281: def _normalize_group_names(
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_tokenizer.py

```
L12: class Token:
L18: class ParserSyntaxError(Exception):
L21: def __init__(
L34: def __str__(self) -> str:
L91: class Tokenizer:
L98: def __init__(
L109: def consume(self, name: str) -> None:
L114: def check(self, name: str, *, peek: bool = False) -> bool:
L135: def expect(self, name: str, *, expected: str) -> Token:
L144: def read(self) -> Token:
L154: def raise_syntax_error(
L173: def enclosing_tokens(
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_parser.py

```
L15: class Node:
L18: def __init__(self, value: str) -> None:
L21: def __str__(self) -> str:
L24: def __repr__(self) -> str:
L27: def serialize(self) -> str:
```

```

L30: def __getstate__(self) -> str:
L34: def _restore_value(self, value: object) -> None:
L41: def __setstate__(self, state: object) -> None:
L59: class Variable(Node):
L62: def serialize(self) -> str:
L66: class Value(Node):
L69: def serialize(self) -> str:
L73: class Op(Node):
L76: def serialize(self) -> str:
L87: class ParsedRequirement(NamedTuple):
L98: def parse_requirement(source: str) -> ParsedRequirement:
L102: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:
L123: def _parse_requirement_details(
L176: def _parse_requirement_marker(
L197: def _parse_extras(tokenizer: Tokenizer) -> list[str]:
L216: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:
L243: def _parse_specifier(tokenizer: Tokenizer) -> str:
L260: def _parse_version_many(tokenizer: Tokenizer) -> str:
L292: def parse_marker(source: str) -> MarkerList:
L296: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:
L302: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:
L314: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:
L336: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:
L350: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar: # noqa: RET503
L364: def process_env_var(env_var: str) -> Variable:
L371: def process_python_str(python_str: str) -> Value:
L376: def _parse_marker_op(tokenizer: Tokenizer) -> Op:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/utils.py

```

L27: def __dir__() -> list[str]:
L39: class InvalidName(ValueError):
L45: class InvalidWheelFilename(ValueError):
L51: class InvalidSdistFilename(ValueError):
L66: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
L103: def is_normalized_name(name: str) -> bool:
L119: def canonicalize_version(
L157: def parse_wheel_filename(
L249: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/version.py

```

L37: def _deprecated(message: str) -> object:
L38: def decorator(func: Callable[[...], object]) -> object:
L40: def wrapper(*args: object, **kwargs: object) -> object:
L66: def __dir__() -> list[str]:
L81: class _VersionReplace(TypedDict, total=False):
L90: def normalize_pre(letter: str, /) -> str:

```

```

L111: def parse(version: str) -> Version:
L125: class InvalidVersion(ValueError):
L135: class _BaseVersion:
L144: def __key__(self) -> tuple[Any, ...]: ...
L146: def __hash__(self) -> int:
L152: def __lt__(self, other: _BaseVersion) -> bool:
L158: def __le__(self, other: _BaseVersion) -> bool:
L164: def __eq__(self, other: object) -> bool:
L170: def __ge__(self, other: _BaseVersion) -> bool:
L176: def __gt__(self, other: _BaseVersion) -> bool:
L182: def __ne__(self, other: object) -> bool:
L266: def _validate_epoch(value: object, /) -> int:
L274: def _validate_release(value: object, /) -> tuple[int, ...]:
L286: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
L299: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:
L308: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:
L317: def _validate_local(value: object, /) -> LocalType | None:
L327: class _Version(NamedTuple):
L336: class Version(_BaseVersion):
L404: def __init__(self, version: str) -> None:
L455: def from_parts(
L501: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:
L560: def __key__(self) -> CmpKey:
L574: def __hash__(self) -> int:
L592: def __lt__(self, other: _BaseVersion) -> bool:
L619: def __le__(self, other: _BaseVersion) -> bool:
L646: def __eq__(self, other: object) -> bool:
L673: def __ge__(self, other: _BaseVersion) -> bool:
L700: def __gt__(self, other: _BaseVersion) -> bool:
L727: def __ne__(self, other: object) -> bool:
L754: def __getstate__(
L776: def __setstate__(self, state: object) -> None:
L823: def _version(self) -> _Version:
L830: def _version(self, value: _Version) -> None:
L840: def __repr__(self) -> str:
L848: def __str__(self) -> str:
L880: def _str(self) -> str:
L885: def epoch(self) -> int:
L896: def release(self) -> tuple[int, ...]:
L912: def pre(self) -> tuple[Literal["a", "b", "rc"], int] | None:
L927: def post(self) -> int | None:
L938: def dev(self) -> int | None:
L949: def local(self) -> str | None:
L963: def public(self) -> str:
L979: def base_version(self) -> str:
L1000: def is_prerelease(self) -> bool:
L1017: def is_postrelease(self) -> bool:
L1028: def is_devrelease(self) -> bool:
L1039: def major(self) -> int:
L1048: def minor(self) -> int:
L1059: def micro(self) -> int:

```

```

L1070: class _TrimmedRelease(Version):
L1073: def __init__(self, version: str | Version) -> None:
L1086: def release(self) -> tuple[int, ...]:
L1104: def _parse_letter_version(
L1131: def _parse_local_version(local: str | None) -> LocalType | None:
L1157: def _cmpkey(

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_structures.py

```

L18: class InfinityType:
L21: def __repr__(self) -> str:
L25: class NegativeInfinityType:
L28: def __repr__(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/tags.py

```

L54: def __dir__() -> list[str]:
L75: def _compute_32_bit_interpreter() -> bool:
L82: class UnsortedTagsError(ValueError):
L88: class Tag:
L108: def __init__(self, interpreter: str, abi: str, platform: str) -> None:
L128: def interpreter(self) -> str:
L137: def abi(self) -> str:
L144: def platform(self) -> str:
L150: def __eq__(self, other: object) -> bool:
L161: def __hash__(self) -> int:
L164: def __str__(self) -> str:
L167: def __repr__(self) -> str:
L170: def __getstate__(self) -> tuple[str, str, str]:
L175: def __setstate__(self, state: object) -> None:
L203: def parse_tag(tag: str, *, validate_order: bool = False) -> frozenset[Tag]:
L240: def _get_config_var(name: str, warn: bool = False) -> int | str | None:
L249: def _normalize_string(string: str) -> str:
L253: def _is_threaded_cpython(abis: list[str]) -> bool:
L269: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:
L279: def _abi3t_applies(python_version: PythonVersion, threading: bool) -> bool:
L292: def _cpython_abis(py_version: PythonVersion, warn: bool = False) -> list[str]:
L325: def cpython_tags(
L404: def _generic_abi() -> list[str]:
L445: def generic_tags(
L486: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:
L501: def compatible_tags(
L536: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:
L546: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:
L578: def mac_platforms(
L667: def ios_platforms(
L729: def android_platforms(

```

```

L766: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:
L785: def _emscripten_platforms() -> Iterator[str]:
L794: def _generic_platforms() -> Iterator[str]:
L798: def platform_tags() -> Iterator[str]:
L816: def interpreter_name() -> str:
L829: def interpreter_version(*, warn: bool = False) -> str:
L841: def _version_nodot(version: PythonVersion) -> str:
L845: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:
L889: def create_compatible_tags_selector(
L919: def selector(

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/errors.py

```

L11: def __dir__() -> list[str]:
L19: class ExceptionGroup(Exception):
L29: def __init__(self, message: str, exceptions: list[Exception]) -> None:
L33: def __repr__(self) -> str:
L38: class _ErrorCollector:
L59: def finalize(self, msg: str) -> None:
L65: def on_exit(self, msg: str) -> typing.Generator[_ErrorCollector, None, None]:
L75: def collect(self, *err_cls: type[Exception]) -> typing.Generator[None, None, None]:
L89: def error(

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_musllinux.py

```

L18: class _MuslVersion(NamedTuple):
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/requirements.py

```

L20: def __dir__() -> list[str]:
L24: class InvalidRequirement(ValueError):
L30: class Requirement:
L53: def __init__(self, requirement_string: str) -> None:
L68: def _iter_parts(self, name: str) -> Iterator[str]:
L86: def __getstate__(self) -> str:
L91: def __setstate__(self, state: object) -> None:
L110: def __str__(self) -> str:
L113: def __repr__(self) -> str:
L116: def __hash__(self) -> int:
L119: def __eq__(self, other: object) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/pylock.py

```

L54: def __dir__() -> list[str]:
L62: class _FromMappingProtocol(Protocol): # pragma: no cover
L64: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...
L73: def is_valid_pylock_path(path: Path) -> bool:
L78: def _toml_key(key: str) -> str:
L82: def _toml_value(key: str, value: Any) -> Any: # noqa: ANN401
L90: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:
L98: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
L111: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
L118: def _get_sequence(
L140: def _get_as(
L159: def _get_required_as(
L172: def _get_sequence_as(
L191: def _get_object(
L203: def _get_sequence_of_objects(
L219: def _get_required_sequence_of_objects(
L229: def _validate_normalized_name(name: str) -> NormalizedName:
L236: def _validate_path_url(path: str | None, url: str | None) -> None:
L241: def _path_name(path: str | None) -> str | None:
L254: def _url_name(url: str | None) -> str | None:
L261: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:
L269: class PylockValidationError(Exception):
L275: def __init__(
L293: def __str__(self) -> str:
L299: class _PylockRequiredKeyError(PylockValidationError):
L300: def __init__(self, key: str) -> None:
L304: class PylockUnsupportedVersionError(PylockValidationError):
L308: class PylockSelectError(Exception):
L313: class PackageVcs:
L321: def __init__(
L340: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L354: class PackageDirectory:
L359: def __init__(
L372: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L381: class PackageArchive:
L389: def __init__(
L408: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L422: class PackageSdist:
L430: def __init__(
L449: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L462: def filename(self) -> str:
L471: class PackageWheel:
L479: def __init__(
L498: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L511: def filename(self) -> str:
L520: class Package:
L535: def __init__(
L568: def _from_dict(cls, d: Mapping[str, Any]) -> Self:

```

```

L649: def is_direct(self) -> bool:
L654: class Pylock:
L667: def __init__(
L692: def _from_dict(cls, d: Mapping[str, Any]) -> Self:
L715: def from_dict(cls, d: Mapping[str, Any], /) -> Self:
L723: def to_dict(self) -> Mapping[str, Any]:
L727: def validate(self) -> None:
L733: def select(

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):
L10: class SPDXException(TypedDict):

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/__init__.py

```

L47: def __dir__() -> list[str]:
L60: class InvalidLicenseExpression(ValueError):
L71: def canonicalize_license_expression(

```

.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_impl.py

```

L16: class SubprocessRunner(Protocol):
L19: def __call__(
L28: def write_json(obj: Mapping[str, Any], path: str, **kwargs) -> None:
L33: def read_json(path: str) -> Mapping[str, Any]:
L38: class BackendUnavailable(Exception):
L41: def __init__(
L55: class HookMissing(Exception):
L58: def __init__(self, hook_name: str) -> None:
L63: class UnsupportedOperation(Exception):
L66: def __init__(self, traceback: str) -> None:
L70: def default_subprocess_runner(
L86: def quiet_subprocess_runner(
L102: def norm_and_check(source_tree: str, requested: str) -> str:
L126: class BuildBackendHookCaller:
L129: def __init__(
L159: def subprocess_runner(self, runner: "SubprocessRunner") -> Iterator[None]:
L178: def _supported_features(self) -> Sequence[str]:
L182: def get_requires_for_build_wheel(
L200: def prepare_metadata_for_build_wheel(
L233: def build_wheel(

```



```

L265: def get_requires_for_build_editable(
L283: def prepare_metadata_for_build_editable(
L315: def build_editable(
L348: def get_requires_for_build_sdist(
L360: def build_sdist(
L378: def _call_hook(self, hook_name: str, kwargs: Mapping[str, Any]) -> Any:

```

.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/_in_process.py

```

L31: def write_json(obj, path, **kwargs):
L36: def read_json(path):
L41: class BackendUnavailable(Exception):
L44: def __init__(self, message, traceback=None):
L50: class HookMissing(Exception):
L53: def __init__(self, hook_name=None):
L58: def _build_backend():
L81: class _BackendPathFinder:
L89: def __init__(self, backend_path, backend_module):
L94: def find_spec(self, fullname, _path, _target=None):
L111: def find_distributions(self, context=None):
L119: def _supported_features():
L132: def get_requires_for_build_wheel(config_settings):
L146: def get_requires_for_build_editable(config_settings):
L160: def prepare_metadata_for_build_wheel(
L184: def prepare_metadata_for_build_editable(
L215: def _dist_info_files(whl_zip):
L227: def _get_wheel_metadata_from_wheel(whl_basename, metadata_directory, config_settings):
L245: def _find_already_built_wheel(metadata_directory):
L268: def build_wheel(wheel_directory, config_settings, metadata_directory=None):
L285: def build_editable(wheel_directory, config_settings, metadata_directory=None):
L306: def get_requires_for_build_sdist(config_settings):
L320: class _DummyException(Exception):
L324: class GotUnsupportedOperation(Exception):
L327: def __init__(self, traceback):
L331: def build_sdist(sdist_directory, config_settings):
L353: def main():

```

.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/_init_.py

```

L13: def _in_proc_script_path():
L18: def _in_proc_script_path():

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_ssl_constants

ts.py

```
L28: def _set_ssl_context_verify_mode(
```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_windows.py

```
L39: class CERT_CONTEXT(Structure):
L53: class CERT_ENHKEY_USAGE(Structure):
L63: class CERT_USAGE_MATCH(Structure):
L70: class CERT_CHAIN_PARA(Structure):
L90: class CERT_TRUST_STATUS(Structure):
L97: class CERT_CHAIN_ELEMENT(Structure):
L112: class CERT_SIMPLE_CHAIN(Structure):
L127: class CERT_CHAIN_CONTEXT(Structure):
L144: class SSL_EXTRA_CERT_CHAIN_POLICY_PARA(Structure):
L153: class CERT_CHAIN_POLICY_PARA(Structure):
L164: class CERT_CHAIN_POLICY_STATUS(Structure):
L177: class CERT_CHAIN_ENGINE_CONFIG(Structure):
L238: def _handle_win_error(result: bool, _: Any, args: Any) -> Any:
L323: def _verify_peercerts_impl(
L415: def _get_and_verify_cert_chain(
L505: def _verify_using_custom_ca_certs(
L558: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:
```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_api.py

```
L34: def inject_into_ssl() -> None:
L66: def extract_from_ssl() -> None:
L77: class SSLContext(_truststore_SSLContext_super_class): # type: ignore[misc]
L81: def __class__(self) -> type:
L87: def __init__(self, protocol: int = None) -> None: # type: ignore[assignment]
L91: class TruststoreSSLObject(ssl.SSLObject):
L96: def do_handshake(self) -> None:
L103: def wrap_socket(
L136: def wrap_bio(
L154: def load_verify_locations(
L164: def load_cert_chain(
L174: def load_default_certs(
L179: def set_alpn_protocols(self, alpn_protocols: typing.Iterable[str]) -> None:
L182: def set_npn_protocols(self, npn_protocols: typing.Iterable[str]) -> None:
L185: def set_ciphers(self, __cipherlist: str) -> None:
L188: def get_ciphers(self) -> typing.Any:
L191: def session_stats(self) -> dict[str, int]:
L194: def cert_store_stats(self) -> dict[str, int]:
L197: def set_default_verify_paths(self) -> None:
L201: def get_ca_certs(
L206: def get_ca_certs(self, binary_form: typing.Literal[True] = ...) -> list[bytes]: ...
```

```

L209: def get_ca_certs(self, binary_form: bool = ...) -> typing.Any: ...
L211: def get_ca_certs(self, binary_form: bool = False) -> list[typing.Any] | list[bytes]:
L215: def check_hostname(self) -> bool:
L219: def check_hostname(self, value: bool) -> None:
L223: def hostname_checks_common_name(self) -> bool:
L227: def hostname_checks_common_name(self, value: bool) -> None:
L231: def keylog_filename(self) -> str:
L235: def keylog_filename(self, value: str) -> None:
L239: def maximum_version(self) -> ssl.TLSVersion:
L243: def maximum_version(self, value: ssl.TLSVersion) -> None:
L249: def minimum_version(self) -> ssl.TLSVersion:
L253: def minimum_version(self, value: ssl.TLSVersion) -> None:
L259: def options(self) -> ssl.Options:
L263: def options(self, value: ssl.Options) -> None:
L269: def post_handshake_auth(self) -> bool:
L273: def post_handshake_auth(self, value: bool) -> None:
L277: def protocol(self) -> ssl._SSLMethod:
L281: def security_level(self) -> int:
L285: def verify_flags(self) -> ssl.VerifyFlags:
L289: def verify_flags(self, value: ssl.VerifyFlags) -> None:
L295: def verify_mode(self) -> ssl.VerifyMode:
L299: def verify_mode(self, value: ssl.VerifyMode) -> None:
L310: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:
L319: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:
L324: def _verify_peercerts(

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_openssl.py

```

L25: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:
L51: def _capath_contains_certs(capath: str) -> bool:
L61: def _verify_peercerts_impl(

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_macos.py

```

L31: def _load_cdll(name: str, macos10_16_path: str) -> CDLL:
L223: def _handle_osstatus(result: OSStatus, _: typing.Any, args: typing.Any) -> typing.Any:
L283: class CFConst:
L294: def _bytes_to_cf_data_ref(value: bytes) -> CFDataRef: # type: ignore[valid-type]
L300: def _bytes_to_cf_string(value: bytes) -> CFString:
L314: def _cf_string_ref_to_str(cf_string_ref: CFStringRef) -> str | None: # type:
ignore[valid-type]
L337: def _der_certs_to_cf_cert_array(certs: list[bytes]) -> CFMutableArrayRef: # type:
ignore[valid-type]
L368: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:
L380: def _verify_peercerts_impl(
L469: def _verify_peercerts_impl_macos_10_13(
L513: def _verify_peercerts_impl_macos_10_14(

```

.venv/lib/python3.12/site-packages/pip/_vendor/certifi/core.py

```

L10: def exit_cacert_ctx() -> None:
L21: def where() -> str:
L46: def contents() -> str:
L56: def where() -> str:
L82: def contents() -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/console.py

```

L40: def reset_color():
L44: def colorize(color_key, text):
L48: def ansiformat(attr, text):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexer.py

```

L37: class LexerMeta(type):
L43: def __new__(mcs, name, bases, d):
L49: class Lexer(metaclass=LexerMeta):
L145: def __init__(self, **options):
L156: def __init__(self, **options):
L175: def __repr__(self):
L181: def add_filter(self, filter_, **options):
L189: def analyse_text(text):
L206: def _preprocess_lexer_input(self, text):
L255: def get_tokens(self, text, unfiltered=False):
L271: def streamer():
L279: def get_tokens_unprocessed(self, text):
L291: class DelegatingLexer(Lexer):
L301: def __init__(self, _root_lexer, _language_lexer, _needle=Other, **options):
L307: def get_tokens_unprocessed(self, text):
L330: class include(str): # pylint: disable=invalid-name
L337: class _inherit:
L341: def __repr__(self):
L347: class combined(tuple): # pylint: disable=invalid-name
L352: def __new__(cls, *args):
L355: def __init__(self, *args):
L360: class _PseudoMatch:
L365: def __init__(self, start, text):
L369: def start(self, arg=None):
L372: def end(self, arg=None):
L375: def group(self, arg=None):
L380: def groups(self):
L383: def groupdict(self):
L387: def bygroups(*args):
L391: def callback(lexer, match, ctx=None):
L413: class _This:

```

```

L422: def using(_other, **kwargs):
L444: def callback(lexer, match, ctx=None):
L459: def callback(lexer, match, ctx=None):
L472: class default:
L480: def __init__(self, state):
L484: class words(Future):
L491: def __init__(self, words, prefix='', suffix=''):
L496: def get(self):
L500: class RegexLexerMeta(LexerMeta):
L506: def _process_regex(cls, regex, rflags, state):
L512: def _process_token(cls, token):
L518: def _process_new_state(cls, new_state, unprocessed, processed):
L553: def _process_state(cls, unprocessed, processed, state):
L596: def process_tokendef(cls, name, tokendefs=None):
L604: def get_tokendefs(cls):
L653: def __call__(cls, *args, **kws):
L667: class RegexLexer(Lexer, metaclass=RegexLexerMeta):
L702: def get_tokens_unprocessed(self, text, stack=('root',)):
L764: class LexerContext:
L769: def __init__(self, text, pos, stack=None, end=None):
L775: def __repr__(self):
L779: class ExtendedRegexLexer(RegexLexer):
L784: def get_tokens_unprocessed(self, text=None, context=None):
L851: def do_insertions(insertions, tokens):
L915: class ProfilingRegexLexerMeta(RegexLexerMeta):
L918: def _process_regex(cls, regex, rflags, state):
L926: def match_func(text, pos, endpos=sys.maxsize):
L937: class ProfilingRegexLexer(RegexLexer, metaclass=ProfilingRegexLexerMeta):
L943: def get_tokens_unprocessed(self, text, stack=('root',)):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/regexopt.py

```

L22: def make_charset(letters):
L26: def regex_opt_inner(strings, open_paren):
L82: def regex_opt(strings, prefix='', suffix=''):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/token.py

```

L12: class _TokenType(tuple):
L15: def split(self):
L24: def __init__(self, *args):
L28: def __contains__(self, val):
L34: def __getattr__(self, val):
L43: def __repr__(self):
L46: def __copy__(self):
L50: def __deepcopy__(self, memo):
L85: def is_token_subtype(ttype, other):
L94: def string_to_tokentype(s):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/modeline.py

```
L22: def get_filetype_from_line(l): # noqa: E741
L28: def get_filetype_from_buffer(buf, max_lines=5):
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/sphinxext.py

```
L60: class PygmentsDoc(Directive):
L71: def run(self):
L90: def document_lexers_overview(self):
L101: def format_link(name, url):
L121: def write_row(*columns):
L132: def write_seperator():
L150: def document_lexers(self):
L215: def document_formatters(self):
L233: def document_filters(self):
L246: def setup(app):
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/__init__.py

```
L35: def lex(code, lexer):
L52: def format(tokens, formatter, outfile=None): # pylint: disable=redefined-builtin
L77: def highlight(code, lexer, formatter, outfile=None):
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/unistring.py

```
L82: def combine(*args):
L86: def allexcept(*args):
L93: def _handle_runs(char_list): # pragma: no cover
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/style.py

```
L58: class StyleMeta(type):
L60: def __new__(mcs, name, bases, dct):
L66: def colorformat(text):
L126: def style_for_token(cls, token):
L156: def list_styles(cls):
L159: def styles_token(cls, ttype):
L162: def __iter__(cls):
L166: def __len__(cls):
L170: class Style(metaclass=StyleMeta):
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filter.py

```

L12: def apply_filters(stream, filters, lexer=None):
L18: def _apply(filter_, stream):
L25: def simplefilter(f):
L30: def lowercase(self, lexer, stream, options):
L41: class Filter:
L47: def __init__(self, **options):
L50: def filter(self, lexer, stream):
L54: class FunctionFilter(Filter):
L63: def __init__(self, **options):
L68: def filter(self, lexer, stream):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/scanner.py

```

L20: class EndOfText(RuntimeError):
L27: class Scanner:
L35: def __init__(self, text, flags=0):
L49: def eos(self):
L54: def check(self, pattern):
L66: def test(self, pattern):
L72: def scan(self, pattern):
L95: def get_char(self):
L99: def __repr__(self):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/util.py

```

L30: class ClassNotFound(ValueError):
L34: class OptionError(Exception):
L40: def get_choice_opt(options, optname, allowed, default=None, normcase=False):
L53: def get_bool_opt(options, optname, default=None):
L82: def get_int_opt(options, optname, default=None):
L94: def get_list_opt(options, optname, default=None):
L110: def docstring_headline(obj):
L122: def make_analysator(f):
L124: def text_analyse(text):
L139: def shebang_matches(text, regex):
L184: def doctype_matches(text, regex):
L197: def html_doctype_matches(text):
L205: def looks_like_xml(text):
L221: def surrogatepair(c):
L230: def format_lines(var_name, seq, raw=False, indent_level=0):
L249: def duplicates_removed(it, already_seen=()):
L265: class Future:
L271: def get(self):
L275: def guess_decode(text):
L296: def guess_decode_from_terminal(text, term):
L313: def terminal_encoding(term):
L321: class UnclosingTextIOWrapper(TextIOWrapper):
L323: def close(self):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatter.py

```

L19: def _lookup_style(style):
L25: class Formatter:
L83: def __init__(self, **options):
L99: def get_style_defs(self, arg=''):
L114: def format(self, tokensource, outfile):
L128: def __class_getitem__(cls, name):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/plugin.py

```

L43: def iter_entry_points(group_name):
L55: def find_plugin_lexers():
L60: def find_plugin_formatters():
L65: def find_plugin_styles():
L70: def find_plugin_filters():

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filters/_init_.py

```

L22: def find_filter_class(filtername):
L32: def get_filter_by_name(filtername, **options):
L45: def get_all_filters():
L52: def _replace_special(ttype, value, regex, specialttype,
L65: class CodeTagFilter(Filter):
L78: def __init__(self, **options):
L86: def filter(self, lexer, stream):
L97: class SymbolFilter(Filter):
L673: def __init__(self, **options):
L679: def filter(self, lexer, stream):
L687: class KeywordCaseFilter(Filter):
L701: def __init__(self, **options):
L707: def filter(self, lexer, stream):
L715: class NameHighlightFilter(Filter):
L739: def __init__(self, **options):
L748: def filter(self, lexer, stream):
L756: class ErrorToken(Exception):
L760: class RaiseOnErrorTokenFilter(Filter):
L772: def __init__(self, **options):
L782: def filter(self, lexer, stream):
L789: class VisibleWhitespaceFilter(Filter):
L819: def __init__(self, **options):
L836: def filter(self, lexer, stream):
L843: def replacefunc(wschar):
L868: class GobbleFilter(Filter):
L882: def __init__(self, **options):
L886: def gobble(self, value, left):

```



```

L892: def filter(self, lexer, stream):
L907: class TokenMergeFilter(Filter):
L913: def __init__(self, **options):
L916: def filter(self, lexer, stream):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/python.py

```

L25: class PythonLexer(RegexLexer):
L65: def innerstring_rules(ttype):
L85: def fstring_rules(ttype):
L408: def analyse_text(text):
L416: class Python2Lexer(RegexLexer):
L433: def innerstring_rules(ttype):
L635: def analyse_text(text):
L639: class _PythonConsoleLexerBase(RegexLexer):
L676: class PythonConsoleLexer(DelegatingLexer):
L706: def __init__(self, **options):
L719: class _ReplaceInnerCode(DelegatingLexer):
L720: def __init__(self, **options):
L725: class PythonTracebackLexer(RegexLexer):
L782: class Python2TracebackLexer(RegexLexer):
L830: class CythonLexer(RegexLexer):
L1009: class DgLexer(RegexLexer):
L1108: class NumPyLexer(PythonLexer):
L1189: def get_tokens_unprocessed(self, text):
L1197: def analyse_text(text):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/__init__.py

```

L35: def _fn_matches(fn, glob):
L43: def _load_lexers(module_name):
L51: def get_all_lexers(plugins=True):
L65: def find_lexer_class(name):
L83: def find_lexer_class_by_name(_alias):
L110: def get_lexer_by_name(_alias, **options):
L135: def load_lexer_from_file(filename, lexername="CustomLexer", **options):
L169: def find_lexer_class_for_filename(_fn, code=None):
L194: def get_rating(info):
L212: def get_lexer_for_filename(_fn, code=None, **options):
L231: def get_lexer_for_mimetype(_mime, **options):
L250: def _iter_lexerclasses(plugins=True):
L261: def guess_lexer_for_filename(_fn, _text, **options):
L292: def type_sort(t):
L304: def guess_lexer(_text, **options):
L308: class is called with the text as argument, and the lexer which returned the

```

```
L343: class _automodule(types.ModuleType):
L346: def __getattr__(self, name):
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/styles/__init__.py

```
L24: def get_style_by_name(name):
L56: def get_all_styles():
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatters/__init__.py

```
L28: def _fn_matches(fn, glob):
L36: def _load_formatters(module_name):
L44: def get_all_formatters():
L55: def find_formatter_class(alias):
L70: def get_formatter_by_name(_alias, **options):
L84: def load_formatter_from_file(filename, formattername="CustomFormatter", **options):
L118: def get_formatter_for_filename(fn, **options):
L140: class _automodule(types.ModuleType):
L143: def __getattr__(self, name):
```

.venv/lib/python3.12/site-packages/pip/_vendor/distro/distro.py

```
L61: class VersionDict(TypedDict):
L67: class InfoDict(TypedDict):
L160: def linux_distribution(full_distribution_name: bool = True) -> Tuple[str, str, str]:
L203: def id() -> str:
L287: def name(pretty: bool = False) -> str:
L326: def version(pretty: bool = False, best: bool = False) -> str:
L374: def version_parts(best: bool = False) -> Tuple[str, str, str]:
L391: def major_version(best: bool = False) -> str:
L404: def minor_version(best: bool = False) -> str:
L417: def build_number(best: bool = False) -> str:
L430: def like() -> str:
L447: def codename() -> str:
L471: def info(pretty: bool = False, best: bool = False) -> InfoDict:
L515: def os_release_info() -> Dict[str, str]:
L525: def lsb_release_info() -> Dict[str, str]:
L536: def distro_release_info() -> Dict[str, str]:
L546: def uname_info() -> Dict[str, str]:
L554: def os_release_attr(attribute: str) -> str:
L573: def lsb_release_attr(attribute: str) -> str:
L593: def distro_release_attr(attribute: str) -> str:
L612: def uname_attr(attribute: str) -> str:
L633: class cached_property: # type: ignore
```

```

L639: def __init__(self, f: Callable[[Any], Any]) -> None:
L643: def __get__(self, obj: Any, owner: Type[Any]) -> Any:
L649: class LinuxDistribution:
L667: def __init__(
L800: def __repr__(self) -> str:
L817: def linux_distribution(
L833: def id(self) -> str:
L839: def normalize(distro_id: str, table: Dict[str, str]) -> str:
L861: def name(self, pretty: bool = False) -> str:
L884: def version(self, pretty: bool = False, best: bool = False) -> str:
L926: def version_parts(self, best: bool = False) -> Tuple[str, str, str]:
L942: def major_version(self, best: bool = False) -> str:
L950: def minor_version(self, best: bool = False) -> str:
L958: def build_number(self, best: bool = False) -> str:
L966: def like(self) -> str:
L974: def codename(self) -> str:
L991: def info(self, pretty: bool = False, best: bool = False) -> InfoDict:
L1010: def os_release_info(self) -> Dict[str, str]:
L1019: def lsb_release_info(self) -> Dict[str, str]:
L1029: def distro_release_info(self) -> Dict[str, str]:
L1039: def uname_info(self) -> Dict[str, str]:
L1048: def oslevel_info(self) -> str:
L1054: def os_release_attr(self, attribute: str) -> str:
L1063: def lsb_release_attr(self, attribute: str) -> str:
L1072: def distro_release_attr(self, attribute: str) -> str:
L1081: def uname_attr(self, attribute: str) -> str:
L1091: def _os_release_info(self) -> Dict[str, str]:
L1104: def _parse_os_release_content(lines: TextIO) -> Dict[str, str]:
L1154: def _lsb_release_info(self) -> Dict[str, str]:
L1173: def _parse_lsb_release_content(lines: Iterable[str]) -> Dict[str, str]:
L1197: def _uname_info(self) -> Dict[str, str]:
L1209: def _oslevel_info(self) -> str:
L1219: def _debian_version(self) -> str:
L1229: def _parse_uname_content(lines: Sequence[str]) -> Dict[str, str]:
L1248: def _to_str(bytestring: bytes) -> str:
L1253: def _distro_release_info(self) -> Dict[str, str]:
L1311: def _parse_distro_release_file(self, filepath: str) -> Dict[str, str]:
L1334: def _parse_distro_release_content(line: str) -> Dict[str, str]:
L1362: def main() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/compat.py

```
L29: def _resolve_char_detection():
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/hooks.py

```

L16: def default_hooks():
L23: def dispatch_hook(key, hooks, hook_data, **kwargs):

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/models.py

```

L86: class RequestEncodingMixin:
L88: def path_url(self):
L109: def _encode_params(data):
L139: def _encode_files(files, data):
L208: class RequestHooksMixin:
L209: def register_hook(self, event, hook):
L220: def deregister_hook(self, event, hook):
L232: class Request(RequestHooksMixin):
L260: def __init__(
L294: def __repr__(self):
L297: def prepare(self):
L315: class PreparedRequest(RequestEncodingMixin, RequestHooksMixin):
L336: def __init__(self):
L353: def prepare(
L381: def __repr__(self):
L384: def copy(self):
L395: def prepare_method(self, method):
L402: def _get_idna_encoded_host(host):
L411: def prepare_url(self, url, params):
L485: def prepare_headers(self, headers):
L496: def prepare_body(self, data, files, json=None):
L574: def prepare_content_length(self, body):
L590: def prepare_auth(self, auth, url=""):
L612: def prepare_cookies(self, cookies):
L632: def prepare_hooks(self, hooks):
L642: class Response:
L660: def __init__(self):
L707: def __enter__(self):
L710: def __exit__(self, *args):
L713: def __getstate__(self):
L721: def __setstate__(self, state):
L729: def __repr__(self):
L732: def __bool__(self):
L742: def __nonzero__(self):
L752: def __iter__(self):
L757: def ok(self):
L772: def is_redirect(self):
L779: def is_permanent_redirect(self):
L787: def next(self):
L792: def apparent_encoding(self):
L801: def iter_content(self, chunk_size=1, decode_unicode=False):
L818: def generate():
L859: def iter_lines(
L893: def content(self):
L912: def text(self):
L949: def json(self, **kwargs):
L985: def links(self):
L1001: def raise_for_status(self):

```

```
L1030: def close(self):
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/help.py

```
L27: def _implementation():
L59: def info():
L118: def main():
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/api.py

```
L14: def request(method, url, **kwargs):
L62: def get(url, params=None, **kwargs):
L76: def options(url, **kwargs):
L88: def head(url, **kwargs):
L103: def post(url, data=None, json=None, **kwargs):
L118: def put(url, data=None, **kwargs):
L133: def patch(url, data=None, **kwargs):
L148: def delete(url, **kwargs):
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/exceptions.py

```
L13: class RequestException(IOError):
L18: def __init__(self, *args, **kwargs):
L28: class InvalidJSONError(RequestException):
L32: class JSONDecodeError(InvalidJSONError, CompatJSONDecodeError):
L35: def __init__(self, *args, **kwargs):
L45: def __reduce__(self):
L56: class HTTPError(RequestException):
L60: class ConnectionError(RequestException):
L64: class ProxyError(ConnectionError):
L68: class SSLError(ConnectionError):
L72: class Timeout(RequestException):
L81: class ConnectTimeout(ConnectionError, Timeout):
L88: class ReadTimeout(Timeout):
L92: class URLRequired(RequestException):
L96: class TooManyRedirects(RequestException):
L100: class MissingSchema(RequestException, ValueError):
L104: class InvalidSchema(RequestException, ValueError):
L108: class InvalidURL(RequestException, ValueError):
L112: class InvalidHeader(RequestException, ValueError):
L116: class InvalidProxyURL(InvalidURL):
L120: class ChunkedEncodingError(RequestException):
L124: class ContentDecodingError(RequestException, BaseHTTPError):
L128: class StreamConsumedError(RequestException, TypeError):
L132: class RetryError(RequestException):
L136: class UnrewindableBodyError(RequestException):
L143: class RequestsWarning(Warning):
```

```
L147: class FileModeWarning(RequestsWarning, DeprecationWarning):
L151: class RequestsDependencyWarning(RequestsWarning):
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/__init__.py

```
L51: def check_compatibility(urllib3_version, chardet_version, charset_normalizer_version):
L83: def _check_cryptography(cryptography_version):
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/sessions.py

```
L62: def merge_setting(request_setting, session_setting, dict_class=OrderedDict):
L92: def merge_hooks(request_hooks, session_hooks, dict_class=OrderedDict):
L107: class SessionRedirectMixin:
L108: def get_redirect_target(self, resp):
L128: def should_strip_auth(self, old_url, new_url):
L160: def resolve_redirects(
L283: def rebuild_auth(self, prepared_request, response):
L303: def rebuild_proxies(self, prepared_request, proxies):
L334: def rebuild_method(self, prepared_request, response):
L357: class Session(SessionRedirectMixin):
L391: def __init__(self):
L454: def __enter__(self):
L457: def __exit__(self, *args):
L460: def prepare_request(self, request):
L503: def request(
L596: def get(self, url, **kwargs):
L607: def options(self, url, **kwargs):
L618: def head(self, url, **kwargs):
L629: def post(self, url, data=None, json=None, **kwargs):
L642: def put(self, url, data=None, **kwargs):
L654: def patch(self, url, data=None, **kwargs):
L666: def delete(self, url, **kwargs):
L676: def send(self, request, **kwargs):
L753: def merge_environment_settings(self, url, proxies, stream, verify, cert):
L784: def get_adapter(self, url):
L797: def close(self):
L802: def mount(self, prefix, adapter):
L813: def __getstate__(self):
L817: def __setstate__(self, state):
L822: def session():
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/utils.py

```
L76: def proxy_bypass_registry(host):
L114: def proxy_bypass(host): # noqa
L126: def dict_to_sequence(d):
L135: def super_len(o):
```

```

L206: def get_netrc_auth(url, raise_errors=False):
L250: def guess_filename(obj):
L257: def extract_zipped_paths(path):
L296: def atomic_open(filename):
L308: def from_key_val_list(value):
L335: def to_key_val_list(value):
L365: def parse_list_header(value):
L397: def parse_dict_header(value):
L432: def unquote_header_value(value, is_filename=False):
L457: def dict_from_cookiejar(cj):
L468: def add_dict_to_cookiejar(cj, cookie_dict):
L479: def get_encodings_from_content(content):
L504: def _parse_content_type_header(header):
L526: def get_encoding_from_headers(headers):
L551: def stream_decode_response_unicode(iterator, r):
L568: def iter_slices(string, slice_length):
L578: def get_unicode_from_response(r):
L623: def unquote_unreserved(uri):
L647: def requote_uri(uri):
L669: def address_in_network(ip, net):
L684: def dotted_netmask(mask):
L695: def is_ipv4_address(string_ip):
L706: def is_valid_cidr(string_network):
L731: def set_environ(env_name, value):
L752: def should_bypass_proxies(url, no_proxy):
L761: def get_proxy(key):
L813: def get_environ_proxies(url, no_proxy=None):
L825: def select_proxy(url, proxies):
L851: def resolve_proxies(request, proxies, trust_env=True):
L878: def default_user_agent(name="python-requests"):
L887: def default_headers():
L901: def parse_header_links(value):
L944: def guess_json_utf(data):
L976: def prepend_scheme_if_needed(url, new_scheme):
L1005: def get_auth_from_url(url):
L1021: def check_header_validity(header):
L1032: def _validate_header_part(header, header_part, header_validator_index):
L1051: def urldefragauth(url):
L1068: def rewind_body(prepared_request):

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/_internal_utils.py

```

L26: def to_native_string(string, encoding="ascii"):
L39: def unicode_is_ascii(u_string):

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/cookies.py

```

L23: class MockRequest:
L35: def __init__(self, request):
L40: def get_type(self):
L43: def get_host(self):
L46: def get_origin_req_host(self):
L49: def get_full_url(self):
L69: def is_unverifiable(self):
L72: def has_header(self, name):
L75: def get_header(self, name, default=None):
L78: def add_header(self, key, val):
L84: def add_unredirected_header(self, name, value):
L87: def get_new_headers(self):
L91: def unverifiable(self):
L95: def origin_req_host(self):
L99: def host(self):
L103: class MockResponse:
L110: def __init__(self, headers):
L117: def info(self):
L120: def getheaders(self, name):
L124: def extract_cookies_to_jar(jar, request, response):
L140: def get_cookie_header(jar, request):
L151: def remove_cookie_by_name(cookiejar, name, domain=None, path=None):
L170: class CookieConflictError(RuntimeError):
L176: class RequestsCookieJar(cookielib.CookieJar, MutableMapping):
L194: def get(self, name, default=None, domain=None, path=None):
L206: def set(self, name, value, **kwargs):
L225: def iterkeys(self):
L234: def keys(self):
L242: def itervalues(self):
L251: def values(self):
L259: def iteritems(self):
L268: def items(self):
L277: def list_domains(self):
L285: def list_paths(self):
L293: def multiple_domains(self):
L306: def get_dict(self, domain=None, path=None):
L321: def __contains__(self, name):
L327: def __getitem__(self, name):
L336: def __setitem__(self, name, value):
L343: def __delitem__(self, name):
L349: def set_cookie(self, cookie, *args, **kwargs):
L358: def update(self, other):
L366: def _find(self, name, domain=None, path=None):
L386: def _find_no_duplicates(self, name, domain=None, path=None):
L415: def __getstate__(self):
L422: def __setstate__(self, state):
L428: def copy(self):
L435: def get_policy(self):
L440: def _copy_cookie_jar(jar):
L455: def create_cookie(name, value, **kwargs):
L492: def morsel_to_cookie(morsel):

```



```
L521: def cookiejar_from_dict(cookie_dict, cookiejar=None, overwrite=True):
L542: def merge_cookies(cookiejar, cookies):
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/auth.py

```
L25: def _basic_auth_str(username, password):
L69: class AuthBase:
L72: def __call__(self, r):
L76: class HTTPBasicAuth(AuthBase):
L79: def __init__(self, username, password):
L83: def __eq__(self, other):
L91: def __ne__(self, other):
L94: def __call__(self, r):
L99: class HTTPProxyAuth(HTTPBasicAuth):
L102: def __call__(self, r):
L107: class HTTPDigestAuth(AuthBase):
L110: def __init__(self, username, password):
L116: def init_per_thread_state(self):
L126: def build_digest_header(self, method, url):
L145: def md5_utf8(x):
L153: def sha_utf8(x):
L161: def sha256_utf8(x):
L169: def sha512_utf8(x):
L236: def handle_redirect(self, r, **kwargs):
L241: def handle_401(self, r, **kwargs):
L285: def __call__(self, r):
L305: def __eq__(self, other):
L313: def __ne__(self, other):
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/adapters.py

```
L63: def SOCKSProxyManager(*args, **kwargs):
L77: def _urllib3_request_context(
L114: class BaseAdapter:
L117: def __init__(self):
L120: def send(
L139: def close(self):
L144: class HTTPAdapter(BaseAdapter):
L179: def __init__(
L201: def __getstate__(self):
L204: def __setstate__(self, state):
L217: def init_poolmanager(
L243: def proxy_manager_for(self, proxy, **proxy_kwargs):
L281: def cert_verify(self, conn, url, verify, cert):
L337: def build_response(self, req, resp):
L374: def build_connection_pool_key_attributes(self, request, verify, cert=None):
L424: def get_connection_with_tls_context(self, request, verify, proxies=None, cert=None):
L473: def get_connection(self, url, proxies=None):
```

```

L514: def close(self):
L524: def request_url(self, request, proxies):
L556: def add_headers(self, request, **kwargs):
L570: def proxy_headers(self, proxy):
L591: def send(

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/structures.py

```

L13: class CaseInsensitiveDict(MutableMapping):
L40: def __init__(self, data=None, **kwargs):
L46: def __setitem__(self, key, value):
L51: def __getitem__(self, key):
L54: def __delitem__(self, key):
L57: def __iter__(self):
L60: def __len__(self):
L63: def lower_items(self):
L67: def __eq__(self, other):
L76: def copy(self):
L79: def __repr__(self):
L83: class LookupDict(dict):
L86: def __init__(self, name=None):
L90: def __repr__(self):
L93: def __getitem__(self, key):
L98: def get(self, key, default=None):

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/status_codes.py

```

L109: def _init():
L116: def doc(code):

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/unix.py

```

L18: def getuid() -> NoReturn:
L26: class Unix(PlatformDirsABC): # noqa: PLR0904
L40: def user_data_dir(self) -> str:
L51: def _site_data_dirs(self) -> list[str]:
L58: def site_data_dir(self) -> str:
L71: def user_config_dir(self) -> str:
L82: def _site_config_dirs(self) -> list[str]:
L89: def site_config_dir(self) -> str:
L102: def user_cache_dir(self) -> str:
L113: def site_cache_dir(self) -> str:
L118: def user_state_dir(self) -> str:
L129: def user_log_dir(self) -> str:
L138: def user_documents_dir(self) -> str:

```

```

L143: def user_downloads_dir(self) -> str:
L148: def user_pictures_dir(self) -> str:
L153: def user_videos_dir(self) -> str:
L158: def user_music_dir(self) -> str:
L163: def user_desktop_dir(self) -> str:
L168: def user_runtime_dir(self) -> str:
L188: def site_runtime_dir(self) -> str:
L210: def site_data_path(self) -> Path:
L215: def site_config_path(self) -> Path:
L220: def site_cache_path(self) -> Path:
L224: def iter_config_dirs(self) -> Iterator[str]:
L229: def iter_data_dirs(self) -> Iterator[str]:
L235: def _get_user_media_dir(env_var: str, fallback_tilde_path: str) -> str:
L245: def _get_user_dirs_folder(key: str) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/__main__.py

```

L26: def main() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/api.py

```

L15: class PlatformDirsABC(ABC): # noqa: PLR0904
L18: def __init__( # noqa: PLR0913, PLR0917
L81: def _append_app_name_and_version(self, *base: str) -> str:
L91: def _optionally_create_directory(self, path: str) -> None:
L95: def _first_item_as_path_if_multipath(self, directory: str) -> Path:
L103: def user_data_dir(self) -> str:
L108: def site_data_dir(self) -> str:
L113: def user_config_dir(self) -> str:
L118: def site_config_dir(self) -> str:
L123: def user_cache_dir(self) -> str:
L128: def site_cache_dir(self) -> str:
L133: def user_state_dir(self) -> str:
L138: def user_log_dir(self) -> str:
L143: def user_documents_dir(self) -> str:
L148: def user_downloads_dir(self) -> str:
L153: def user_pictures_dir(self) -> str:
L158: def user_videos_dir(self) -> str:
L163: def user_music_dir(self) -> str:
L168: def user_desktop_dir(self) -> str:
L173: def user_runtime_dir(self) -> str:
L178: def site_runtime_dir(self) -> str:
L182: def user_data_path(self) -> Path:
L187: def site_data_path(self) -> Path:
L192: def user_config_path(self) -> Path:
L197: def site_config_path(self) -> Path:
L202: def user_cache_path(self) -> Path:

```

```

L207: def site_cache_path(self) -> Path:
L212: def user_state_path(self) -> Path:
L217: def user_log_path(self) -> Path:
L222: def user_documents_path(self) -> Path:
L227: def user_downloads_path(self) -> Path:
L232: def user_pictures_path(self) -> Path:
L237: def user_videos_path(self) -> Path:
L242: def user_music_path(self) -> Path:
L247: def user_desktop_path(self) -> Path:
L252: def user_runtime_path(self) -> Path:
L257: def site_runtime_path(self) -> Path:
L261: def iter_config_dirs(self) -> Iterator[str]:
L266: def iter_data_dirs(self) -> Iterator[str]:
L271: def iter_cache_dirs(self) -> Iterator[str]:
L276: def iter_runtime_dirs(self) -> Iterator[str]:
L281: def iter_config_paths(self) -> Iterator[Path]:
L286: def iter_data_paths(self) -> Iterator[Path]:
L291: def iter_cache_paths(self) -> Iterator[Path]:
L296: def iter_runtime_paths(self) -> Iterator[Path]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/__init__.py

```

L30: def _set_platform_dir_class() -> type[PlatformDirsABC]:
L53: def user_data_dir(
L77: def site_data_dir(
L101: def user_config_dir(
L125: def site_config_dir(
L149: def user_cache_dir(
L173: def site_cache_dir(
L197: def user_state_dir(
L221: def user_log_dir(
L245: def user_documents_dir() -> str:
L250: def user_downloads_dir() -> str:
L255: def user_pictures_dir() -> str:
L260: def user_videos_dir() -> str:
L265: def user_music_dir() -> str:
L270: def user_desktop_dir() -> str:
L275: def user_runtime_dir(
L299: def site_runtime_dir(
L323: def user_data_path(
L347: def site_data_path(
L371: def user_config_path(
L395: def site_config_path(
L419: def site_cache_path(
L443: def user_cache_path(
L467: def user_state_path(
L491: def user_log_path(
L515: def user_documents_path() -> Path:
L520: def user_downloads_path() -> Path:

```

```

L525: def user_pictures_path() -> Path:
L530: def user_videos_path() -> Path:
L535: def user_music_path() -> Path:
L540: def user_desktop_path() -> Path:
L545: def user_runtime_path(
L569: def site_runtime_path(

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/android.py

```

L14: class Android(PlatformDirsABC):
L24: def user_data_dir(self) -> str:
L29: def site_data_dir(self) -> str:
L34: def user_config_dir(self) -> str:
L42: def site_config_dir(self) -> str:
L47: def user_cache_dir(self) -> str:
L52: def site_cache_dir(self) -> str:
L57: def user_state_dir(self) -> str:
L62: def user_log_dir(self) -> str:
L73: def user_documents_dir(self) -> str:
L78: def user_downloads_dir(self) -> str:
L83: def user_pictures_dir(self) -> str:
L88: def user_videos_dir(self) -> str:
L93: def user_music_dir(self) -> str:
L98: def user_desktop_dir(self) -> str:
L103: def user_runtime_dir(self) -> str:
L114: def site_runtime_dir(self) -> str:
L120: def _android_folder() -> str | None: # noqa: C901
L168: def _android_documents_folder() -> str:
L184: def _android_downloads_folder() -> str:
L200: def _android_pictures_folder() -> str:
L216: def _android_videos_folder() -> str:
L232: def _android_music_folder() -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/macos.py

```

L15: class MacOS(PlatformDirsABC):
L28: def user_data_dir(self) -> str:
L33: def site_data_dir(self) -> str:
L51: def site_data_path(self) -> Path:
L56: def user_config_dir(self) -> str:
L61: def site_config_dir(self) -> str:
L66: def user_cache_dir(self) -> str:
L71: def site_cache_dir(self) -> str:
L89: def site_cache_path(self) -> Path:
L94: def user_state_dir(self) -> str:
L99: def user_log_dir(self) -> str:
L104: def user_documents_dir(self) -> str:
L109: def user_downloads_dir(self) -> str:

```

```

L114: def user_pictures_dir(self) -> str:
L119: def user_videos_dir(self) -> str:
L124: def user_music_dir(self) -> str:
L129: def user_desktop_dir(self) -> str:
L134: def user_runtime_dir(self) -> str:
L139: def site_runtime_dir(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/windows.py

```

L16: class Windows(PlatformDirsABC):
L28: def user_data_dir(self) -> str:
L38: def _append_parts(self, path: str, *, opinion_value: str | None = None) -> str:
L54: def site_data_dir(self) -> str:
L60: def user_config_dir(self) -> str:
L65: def site_config_dir(self) -> str:
L70: def user_cache_dir(self) -> str:
L79: def site_cache_dir(self) -> str:
L85: def user_state_dir(self) -> str:
L90: def user_log_dir(self) -> str:
L99: def user_documents_dir(self) -> str:
L104: def user_downloads_dir(self) -> str:
L109: def user_pictures_dir(self) -> str:
L114: def user_videos_dir(self) -> str:
L119: def user_music_dir(self) -> str:
L124: def user_desktop_dir(self) -> str:
L129: def user_runtime_dir(self) -> str:
L138: def site_runtime_dir(self) -> str:
L143: def get_win_folder_from_env_vars(csidl_name: str) -> str:
L164: def get_win_folder_if_csidl_name_not_env_var(csidl_name: str) -> str | None:
L183: def get_win_folder_from_registry(csidl_name: str) -> str:
L219: def get_win_folder_via_ctypes(csidl_name: str) -> str:
L258: def _pick_get_win_folder() -> Callable[[str], str]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_parser.py

```

L77: class DEPRECATED_DEFAULT:
L82: class TOMLDecodeError(ValueError):
L93: def __init__(
L143: def load(__fp: IO[bytes], *, parse_float: ParseFloat = float) -> dict[str, Any]:
L155: def loads(__s: str, *, parse_float: ParseFloat = float) -> dict[str, Any]:
L226: class Flags:
L235: def __init__(self) -> None:
L239: def add_pending(self, key: Key, flag: int) -> None:
L242: def finalize_pending(self) -> None:
L247: def unset_all(self, key: Key) -> None:
L255: def set(self, key: Key, flag: int, *, recursive: bool) -> None: # noqa: A003
L266: def is_(self, key: Key, flag: int) -> bool:

```

```

L284: class NestedDict:
L285: def __init__(self) -> None:
L289: def get_or_create_nest(
L306: def append_nest_to_list(self, key: Key) -> None:
L318: class Output:
L319: def __init__(self) -> None:
L324: def skip_chars(src: str, pos: Pos, chars: Iterable[str]) -> Pos:
L333: def skip_until(
L355: def skip_comment(src: str, pos: Pos) -> Pos:
L367: def skip_comments_and_array_ws(src: str, pos: Pos) -> Pos:
L376: def create_dict_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:
L396: def create_list_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:
L419: def key_value_rule(
L453: def parse_key_value_pair(
L469: def parse_key(src: str, pos: Pos) -> tuple[Pos, Key]:
L491: def parse_key_part(src: str, pos: Pos) -> tuple[Pos, str]:
L507: def parse_one_line_basic_str(src: str, pos: Pos) -> tuple[Pos, str]:
L512: def parse_array(
L538: def parse_inline_table(
L572: def parse_basic_str_escape(
L601: def parse_basic_str_escape_multiline(src: str, pos: Pos) -> tuple[Pos, str]:
L605: def parse_hex_char(src: str, pos: Pos, hex_len: int) -> tuple[Pos, str]:
L618: def parse_literal_str(src: str, pos: Pos) -> tuple[Pos, str]:
L627: def parse_multiline_str(src: str, pos: Pos, *, literal: bool) -> tuple[Pos, str]:
L658: def parse_basic_str(src: str, pos: Pos, *, multiline: bool) -> tuple[Pos, str]:
L690: def parse_value(
L766: def is_unicode_scalar_value(codepoint: int) -> bool:
L770: def make_safe_parse_float(parse_float: ParseFloat) -> ParseFloat:
L782: def safe_parse_float(float_str: str) -> Any:

```

.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_re.py

```

L57: def match_to_datetime(match: re.Match[str]) -> datetime | date:
L96: def cached_tz(hour_str: str, minute_str: str, sign_str: str) -> timezone:
L106: def match_to_localtime(match: re.Match[str]) -> time:
L112: def match_to_number(match: re.Match[str], parse_float: ParseFloat) -> Any:

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/exceptions.py

```

L1: class UnpackException(Exception):
L10: class BufferFull(UnpackException):
L14: class OutOfData(UnpackException):
L18: class FormatError(ValueError, UnpackException):
L22: class StackError(ValueError, UnpackException):
L30: class ExtraData(UnpackValueError):
L37: def __init__(self, unpacked, extra):
L41: def __str__(self):

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/__init__.py

```

L20: def pack(o, stream, **kwargs):
L30: def packb(o, **kwargs):
L39: def unpack(stream, **kwargs):

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/ext.py

```

L6: class ExtType(namedtuple("ExtType", "code data")):
L9: def __new__(cls, code, data):
L19: class Timestamp:
L31: def __init__(self, seconds, nanoseconds=0):
L53: def __repr__(self):
L57: def __eq__(self, other):
L63: def __ne__(self, other):
L67: def __hash__(self):
L71: def from_bytes(b):
L97: def to_bytes(self):
L119: def from_unix(unix_sec):
L129: def to_unix(self):
L138: def from_unix_nano(unix_ns):
L146: def to_unix_nano(self):
L154: def to_datetime(self):
L165: def from_datetime(dt):

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/fallback.py

```

L13: class BytesIO:
L14: def __init__(self, s=b''):
L21: def write(self, s):
L28: def getvalue(self):
L36: def newlist_hint(size):
L58: def _check_type_strict(obj, t, type=type, tuple=tuple):
L65: def _get_data_from_buffer(obj):
L72: def unpackb(packed, **kwargs):
L130: class Unpacker:
L226: def __init__(
L318: def feed(self, next_bytes):
L334: def _consume(self):
L339: def _got_extradata(self):
L342: def _get_extradata(self):
L345: def read_bytes(self, n):
L350: def _read(self, n, raise_outofdata=True):
L358: def _reserve(self, n, raise_outofdata=True):
L392: def _read_header(self):
L488: def _unpack(self, execute=EX_CONSTRUCT):
L562: def __iter__(self):

```



```

L565: def __next__(self):
L578: def skip(self):
L582: def unpack(self):
L590: def read_array_header(self):
L595: def read_map_header(self):
L600: def tell(self):
L604: class Packer:
L653: def __init__(
L676: def _pack(
L800: def pack(self, obj):
L811: def pack_map_pairs(self, pairs):
L818: def pack_array_header(self, n):
L827: def pack_map_header(self, n):
L836: def pack_ext_type(self, typecode, data):
L865: def _pack_array_header(self, n):
L874: def _pack_map_header(self, n):
L883: def _pack_map_pairs(self, n, pairs, nest_limit=DEFAULT_RECURSE_LIMIT):
L889: def _pack_raw_header(self, n):
L901: def _pack_bin_header(self, n):
L913: def bytes(self):
L917: def reset(self):
L924: def getbuffer(self):

```

.venv/lib/python3.12/site-packages/pip/_vendor/pkg_resources/__init__.py

```

L135: class _LoaderProtocol(Protocol):
L136: def load_module(self, fullname: str, /) -> types.ModuleType: ...
L139: class _ZipLoaderModule(Protocol):
L146: class PEP440Warning(RuntimeWarning):
L159: def _declare_state(vartype: str, varname: str, initial_value: _T) -> _T:
L164: def __getstate__() -> dict[str, Any]:
L172: def __setstate__(state: dict[str, Any]) -> dict[str, Any]:
L179: def _sget_dict(val):
L183: def _sset_dict(key, ob, state):
L188: def _sget_object(val):
L192: def _sset_object(key, ob, state):
L199: def get_supported_platform():
L309: class ResolutionError(Exception):
L312: def __repr__(self):
L316: class VersionConflict(ResolutionError):
L327: def dist(self) -> Distribution:
L331: def req(self) -> Requirement:
L334: def report(self):
L337: def with_context(self, required_by: set[Distribution | str]):
L348: class ContextualVersionConflict(VersionConflict):
L357: def required_by(self) -> set[str]:
L361: class DistributionNotFound(ResolutionError):
L370: def req(self) -> Requirement:

```

```

L374: def requirers(self) -> set[str] | None:
L378: def requirers_str(self):
L383: def report(self):
L386: def __str__(self):
L390: class UnknownExtra(ResolutionError):
L404: def register_loader_type(
L417: def get_provider(moduleOrReq: str) -> IResourceProvider: ...
L419: def get_provider(moduleOrReq: Requirement) -> Distribution: ...
L420: def get_provider(moduleOrReq: str | Requirement) -> IResourceProvider | Distribution:
L434: def _macos_vers():
L447: def _macos_arch(machine):
L451: def get_build_platform():
L482: def compatible_platforms(provided: str | None, required: str | None):
L532: def get_distribution(dist: _DistributionT) -> _DistributionT: ...
L534: def get_distribution(dist: _PkgReqType) -> Distribution: ...
L535: def get_distribution(dist: Distribution | _PkgReqType) -> Distribution:
L547: def load_entry_point(dist: _EPDistType, group: str, name: str) -> _ResolvedEntryPoint:
L553: def get_entry_map(
L557: def get_entry_map(dist: _EPDistType, group: str) -> dict[str, EntryPoint]: ...
L558: def get_entry_map(dist: _EPDistType, group: str | None = None):
L563: def get_entry_info(dist: _EPDistType, group: str, name: str):
L568: class IMetadataProvider(Protocol):
L569: def has_metadata(self, name: str) -> bool:
L572: def get_metadata(self, name: str) -> str:
L575: def get_metadata_lines(self, name: str) -> Iterator[str]:
L581: def metadata_isdir(self, name: str) -> bool:
L584: def metadata_listdir(self, name: str) -> list[str]:
L587: def run_script(self, script_name: str, namespace: dict[str, Any]) -> None:
L591: class IResourceProvider(IMetadataProvider, Protocol):
L594: def get_resource_filename(
L601: def get_resource_stream(
L608: def get_resource_string(
L615: def has_resource(self, resource_name: str) -> bool:
L618: def resource_isdir(self, resource_name: str) -> bool:
L621: def resource_listdir(self, resource_name: str) -> list[str]:
L625: class WorkingSet:
L628: def __init__(self, entries: Iterable[str] | None = None):
L643: def _build_master(cls):
L663: def _build_from_requirements(cls, req_spec):
L684: def add_entry(self, entry: str):
L699: def __contains__(self, dist: Distribution) -> bool:
L703: def find(self, req: Requirement) -> Distribution | None:
L727: def iter_entry_points(self, group: str, name: str | None = None):
L741: def run_script(self, requires: str, script_name: str):
L749: def __iter__(self) -> Iterator[Distribution]:
L766: def add(
L805: def resolve(
L814: def resolve(
L824: def resolve(
L832: def resolve(
L906: def _resolve_dist(

```

```

L938: def find_plugins(
L946: def find_plugins(
L955: def find_plugins(
L962: def find_plugins(
L1052: def require(self, *requirements: _NestedStr):
L1068: def subscribe(
L1084: def _added_new(self, dist):
L1088: def __getstate__(self):
L1097: def __setstate__(self, e_k_b_n_c):
L1106: class _ReqExtras(Dict["Requirement", Tuple[str, ...]]):
L1111: def markers_pass(self, req: Requirement, extras: tuple[str, ...] | None = None):
L1126: class Environment:
L1129: def __init__(
L1156: def can_add(self, dist: Distribution):
L1170: def remove(self, dist: Distribution):
L1174: def scan(self, search_path: Iterable[str] | None = None):
L1189: def __getitem__(self, project_name: str) -> list[Distribution]:
L1200: def add(self, dist: Distribution):
L1209: def best_match(
L1217: def best_match(
L1224: def best_match(
L1258: def obtain(
L1264: def obtain(
L1270: def obtain(
L1275: def obtain(
L1293: def __iter__(self) -> Iterator[str]:
L1299: def __iadd__(self, other: Distribution | Environment):
L1311: def __add__(self, other: Distribution | Environment):
L1323: class ExtractionError(RuntimeError):
L1343: class ResourceManager:
L1348: def __init__(self):
L1351: def resource_exists(self, package_or_requirement: _PkgReqType, resource_name: str):
L1355: def resource_isdir(self, package_or_requirement: _PkgReqType, resource_name: str):
L1359: def resource_filename(
L1367: def resource_stream(self, package_or_requirement: _PkgReqType, resource_name: str):
L1373: def resource_string(
L1381: def resource_listdir(self, package_or_requirement: _PkgReqType, resource_name: str):
L1385: def extraction_error(self) -> NoReturn:
L1415: def get_cache_path(self, archive_name: str, names: Iterable[StrPath] = ()):
L1441: def _warn_unsafe_extraction_path(path):
L1467: def postprocess(self, tempname: StrOrBytesPath, filename: StrOrBytesPath):
L1487: def set_extraction_path(self, path: str):
L1511: def cleanup_resources(self, force: bool = False) -> list[str]:
L1526: def get_default_cache() -> str:
L1535: def safe_name(name: str):
L1543: def safe_version(version: str):
L1555: def _forgiving_version(version):
L1580: def _safe_segment(segment):
L1587: def safe_extra(extra: str):
L1596: def to_filename(name: str):
L1604: def invalid_marker(text: str):

```

```

L1618: def evaluate_marker(text: str, extra: str | None = None) -> bool:
L1633: class NullProvider:
L1640: def __init__(self, module: _ModuleLike):
L1644: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
L1647: def get_resource_stream(self, manager: ResourceManager, resource_name: str):
L1650: def get_resource_string(
L1655: def has_resource(self, resource_name: str):
L1658: def _get_metadata_path(self, name):
L1661: def has_metadata(self, name: str) -> bool:
L1668: def get_metadata(self, name: str):
L1681: def get_metadata_lines(self, name: str) -> Iterator[str]:
L1684: def resource_isdir(self, resource_name: str):
L1687: def metadata_isdir(self, name: str) -> bool:
L1690: def resource_listdir(self, resource_name: str):
L1693: def metadata_listdir(self, name: str) -> list[str]:
L1698: def run_script(self, script_name: str, namespace: dict[str, Any]):
L1727: def _has(self, path) -> bool:
L1732: def _isdir(self, path) -> bool:
L1737: def _listdir(self, path) -> list[str]:
L1742: def _fn(self, base: str | None, resource_name: str):
L1753: def _validate_resource_path(path):
L1827: def _get(self, path) -> bytes:
L1839: def _parents(path):
L1850: class EggProvider(NullProvider):
L1853: def __init__(self, module: _ModuleLike):
L1857: def _setup_prefix(self):
L1864: def _set_egg(self, path: str):
L1870: class DefaultProvider(EggProvider):
L1873: def _has(self, path) -> bool:
L1876: def _isdir(self, path) -> bool:
L1879: def _listdir(self, path):
L1882: def get_resource_stream(self, manager: object, resource_name: str):
L1885: def _get(self, path) -> bytes:
L1890: def _register(cls):
L1903: class EmptyProvider(NullProvider):
L1911: def _get(self, path) -> bytes:
L1914: def _listdir(self, path):
L1917: def __init__(self):
L1924: class ZipManifests(Dict[str, "MemoizedZipManifests.manifest_mod"]):
L1931: def build(cls, path: str):
L1952: class MemoizedZipManifests(ZipManifests):
L1957: class manifest_mod(NamedTuple):
L1961: def load(self, path: str) -> dict[str, zipfile.ZipInfo]: # type: ignore[override] #
ZipManifests.load is a classmethod
L1975: class ZipProvider(EggProvider):
L1983: def __init__(self, module: _ZipLoaderModule):
L1987: def _zipinfo_name(self, fspath):
L1997: def _parts(self, zip_path):
L2006: def zipinfo(self):
L2009: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
L2023: def _get_date_and_size(zip_stat):

```

```

L2032: def _extract_resource(self, manager: ResourceManager, zip_path) -> str: # noqa: C901
L2086: def _is_current(self, file_path, zip_path):
L2102: def _get_eager_resources(self):
L2111: def _index(self):
L2128: def _has(self, fspath) -> bool:
L2132: def _isdir(self, fspath) -> bool:
L2135: def _listdir(self, fspath):
L2138: def _eager_to_zip(self, resource_name: str):
L2141: def _resource_to_zip(self, resource_name: str):
L2148: class FileMetadata(EmptyProvider):
L2160: def __init__(self, path: StrPath):
L2163: def _get_metadata_path(self, name):
L2166: def has_metadata(self, name: str) -> bool:
L2169: def get_metadata(self, name: str):
L2178: def _warn_on_replacement(self, metadata):
L2185: def get_metadata_lines(self, name: str) -> Iterator[str]:
L2189: class PathMetadata(DefaultProvider):
L2209: def __init__(self, path: str, egg_info: str):
L2214: class EggMetadata(ZipProvider):
L2217: def __init__(self, importer: zipimport.zipimporter):
L2234: def register_finder(importer_type: type[_T], distribution_finder:
_DistFinderType[_T]):
L2244: def find_distributions(path_item: str, only: bool = False):
L2251: def find_eggs_in_zip(
L2282: def find_nothing(
L2291: def find_on_path(importer: object | None, path_item, only=False):
L2311: def dist_factory(path_item, entry, only):
L2330: class NoDists:
L2339: def __bool__(self):
L2342: def __call__(self, fullpath):
L2346: def safe_listdir(path: StrOrBytesPath):
L2362: def distributions_from_metadata(path: str):
L2380: def non_empty_lines(path):
L2390: def resolve_egg_link(path):
L2416: def register_namespace_handler(
L2424: def namespace_handler(importer, path_entry, moduleName, module):
L2436: def _handle_ns(packageName, path_item):
L2473: def _rebuild_mod_path(orig_path, package_name, module: types.ModuleType):
L2480: def safe_sys_path_index(entry):
L2489: def position_in_sys_path(path):
L2507: def declare_namespace(packageName: str):
L2550: def fixup_namespace_packages(path_item: str, parent: str | None = None):
L2562: def file_ns_handler(
L2587: def null_ns_handler(
L2600: def normalize_path(filename: StrPath) -> str: ...
L2602: def normalize_path(filename: BytesPath) -> bytes: ...
L2603: def normalize_path(filename: StrOrBytesPath):
L2608: def _cygwin_patch(filename: StrOrBytesPath): # pragma: nocover
L2623: def _normalize_cached(filename: StrPath) -> str: ...
L2625: def _normalize_cached(filename: BytesPath) -> bytes: ...
L2626: def _normalize_cached(filename: StrOrBytesPath) -> str | bytes: ...

```

```

L2630: def _normalize_cached(filename):
L2634: def _is_egg_path(path):
L2641: def _is_zip_egg(path):
L2649: def _is_unpacked_egg(path):
L2658: def _set_parent_ns(packageName):
L2681: class EntryPoint:
L2684: def __init__(
L2700: def __str__(self):
L2708: def __repr__(self):
L2712: def load(
L2719: def load(
L2725: def load(
L2747: def resolve(self) -> _ResolvedEntryPoint:
L2757: def require(
L2785: def parse(cls, src: str, dist: Distribution | None = None):
L2805: def _parse_extras(cls, extras_spec):
L2814: def parse_group(
L2832: def parse_map(
L2856: def _version_from_file(lines):
L2862: def is_version_line(line):
L2871: class Distribution:
L2876: def __init__(
L2896: def from_location(
L2923: def _reload_version(self):
L2927: def hashcmp(self):
L2937: def __hash__(self):
L2940: def __lt__(self, other: Distribution):
L2943: def __le__(self, other: Distribution):
L2946: def __gt__(self, other: Distribution):
L2949: def __ge__(self, other: Distribution):
L2952: def __eq__(self, other: object):
L2958: def __ne__(self, other: object):
L2966: def key(self):
L2974: def parsed_version(self):
L2988: def _forgiving_parsed_version(self):
L3014: def version(self):
L3029: def _dep_map(self):
L3041: def _filter_extras(dm: dict[str | None, list[Requirement]]):
L3061: def _build_dep_map(self):
L3068: def requires(self, extras: Iterable[str] = ()):
L3082: def _get_metadata_path_for_display(self, name):
L3099: def _get_metadata(self, name):
L3103: def _get_version(self):
L3107: def activate(self, path: list[str] | None = None, replace: bool = False):
L3118: def egg_name(self):
L3130: def __repr__(self):
L3136: def __str__(self):
L3144: def __getattr__(self, attr):
L3150: def __dir__(self):
L3157: def from_filename(
L3167: def as_requirement(self):

```

```

L3176: def load_entry_point(self, group: str, name: str) -> _ResolvedEntryPoint:
L3184: def get_entry_map(self, group: None = None) -> dict[str, dict[str, EntryPoint]]: ...
L3186: def get_entry_map(self, group: str) -> dict[str, EntryPoint]: ...
L3187: def get_entry_map(self, group: str | None = None):
L3197: def get_entry_info(self, group: str, name: str):
L3202: def insert_on( # noqa: C901
L3275: def check_version_conflict(self):
L3301: def has_version(self):
L3312: def clone(self, **kw: str | int | IResourceProvider | None):
L3322: def extras(self):
L3326: class EggInfoDistribution(Distribution):
L3327: def _reload_version(self):
L3345: class DistInfoDistribution(Distribution):
L3355: def _parsed_pkg_info(self):
L3365: def _dep_map(self):
L3372: def _compute_dependencies(self) -> dict[str | None, list[Requirement]]:
L3381: def reqs_for_extra(extra):
L3405: def issue_warning(*args, **kw):
L3418: def parse_requirements(strs: _NestedStr):
L3427: class RequirementParseError(_packaging_requirements.InvalidRequirement):
L3431: class Requirement(_packaging_requirements.Requirement):
L3432: def __init__(self, requirement_string: str):
L3450: def __eq__(self, other: object):
L3453: def __ne__(self, other):
L3456: def __contains__(self, item: Distribution | str | tuple[str, ...]) -> bool:
L3468: def __hash__(self):
L3471: def __repr__(self):
L3475: def parse(s: str | Iterable[str]):
L3480: def _always_object(classes):
L3490: def _find_adapter(registry: Mapping[type, _AdapterT], ob: object) -> _AdapterT:
L3501: def ensure_directory(path: StrOrBytesPath):
L3507: def _bypass_ensure_directory(path):
L3520: def split_sections(s: _NestedStr) -> Iterator[tuple[str | None, list[str]]]:
L3546: def _mkstemp(*args, **kw):
L3564: class PkgResourcesDeprecationWarning(Warning):
L3577: def _read_utf8_with_fallback(file: str, fallback_encoding=_LOCALE_ENCODING) -> str:
L3606: def _call_aside(f, *args, **kwargs):
L3612: def _initialize(g=globals()):
L3624: def _initialize_master_working_set():

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/controller **.py**

```

L39: def parse_uri(uri: str) -> tuple[str, str, str, str, str]:
L50: class CacheController:
L53: def __init__(
L66: def _urlnorm(cls, uri: str) -> str:
L86: def cache_url(cls, uri: str) -> str:
L89: def parse_cache_control(self, headers: Mapping[str, str]) -> dict[str, int | None]:

```

```

L143: def _load_from_cache(self, request: PreparedRequest) -> HTTPResponse | None:
L169: def cached_request(self, request: PreparedRequest) -> HTTPResponse | Literal[False]:
L279: def conditional_headers(self, request: PreparedRequest) -> dict[str, str]:
L294: def _cache_set(
L324: def cache_response(
L471: def update_cached_response(

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/_cmd.py

```

L22: def setup_logging() -> None:
L28: def get_session() -> requests.Session:
L40: def get_args() -> Namespace:
L46: def main() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/adapter.py

```

L26: class CacheControlAdapter(HTTPAdapter):
L29: def __init__(
L50: def send(
L80: def build_response( # type: ignore[override]
L137: def _update_chunk_length(
L165: def close(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/filewrapper.py

```

L15: class CallbackFileWrapper:
L34: def __init__(
L41: def __getattr__(self, name: str) -> Any:
L53: def __is_fp_closed(self) -> bool:
L71: def _close(self) -> None:
L99: def read(self, amt: int | None = None) -> bytes:
L110: def _safe_read(self, amt: int) -> bytes:

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/cache.py

```

L19: class BaseCache:
L20: def get(self, key: str) -> bytes | None:
L23: def set(
L28: def delete(self, key: str) -> None:
L31: def close(self) -> None:
L35: class DictCache(BaseCache):
L36: def __init__(self, init_dict: MutableMapping[str, bytes] | None = None) -> None:
L40: def get(self, key: str) -> bytes | None:

```



```

L43: def set(
L49: def delete(self, key: str) -> None:
L55: class SeparateBodyBaseCache(BaseCache):
L68: def set_body(self, key: str, body: bytes) -> None:
L71: def get_body(self, key: str) -> IO[bytes] | None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/wrapper.py

```

L20: def CacheControl(

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/heuristics.py

```

L18: def expire_after(delta: timedelta, date: datetime | None = None) -> datetime:
L23: def datetime_to_header(dt: datetime) -> str:
L27: class BaseHeuristic:
L28: def warning(self, response: HTTPResponse) -> str | None:
L39: def update_headers(self, response: HTTPResponse) -> dict[str, str]:
L48: def apply(self, response: HTTPResponse) -> HTTPResponse:
L60: class OneDayCache(BaseHeuristic):
L66: def update_headers(self, response: HTTPResponse) -> dict[str, str]:
L80: class ExpiresAfter(BaseHeuristic):
L85: def __init__(self, **kw: Any) -> None:
L88: def update_headers(self, response: HTTPResponse) -> dict[str, str]:
L92: def warning(self, response: HTTPResponse) -> str | None:
L97: class LastModified(BaseHeuristic):
L124: def update_headers(self, resp: HTTPResponse) -> dict[str, str]:
L156: def warning(self, resp: HTTPResponse) -> str | None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/serialize.py

```

L17: class Serializer:
L20: def dumps(
L62: def serialize(self, data: dict[str, Any]) -> bytes:
L65: def loads(
L83: def prepare_response(
L135: def _loads_v4(

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/caches/file_cache.py

```

L22: class _FileCacheMixin:
L25: def __init__(
L55: def encode(x: str) -> str:
L58: def _fn(self, name: str) -> str:
L65: def get(self, key: str) -> bytes | None:
L74: def set(
L80: def _write(self, path: str, data: bytes) -> None:
L98: def _delete(self, key: str, suffix: str) -> None:
L107: class FileCache(_FileCacheMixin, BaseCache):
L113: def delete(self, key: str) -> None:
L117: class SeparateBodyFileCache(_FileCacheMixin, SeparateBodyBaseCache):
L123: def get_body(self, key: str) -> IO[bytes] | None:
L130: def set_body(self, key: str, body: bytes) -> None:
L134: def delete(self, key: str) -> None:
L139: def url_to_file_path(url: str, filecache: FileCache) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/caches/redis_cache.py

```

L16: class RedisCache(BaseCache):
L17: def __init__(self, conn: Redis[bytes]) -> None:
L20: def get(self, key: str) -> bytes | None:
L23: def set(
L37: def delete(self, key: str) -> None:
L40: def clear(self) -> None:
L46: def close(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/compat.py

```

L30: def quote(s):
L93: class CertificateError(ValueError):
L96: def _dnsname_match(dn, hostname, max_wildcards=1):
L145: def match_hostname(cert, hostname):
L192: class Container(object):
L197: def __init__(self, **kwargs):
L205: def which(cmd, mode=os.F_OK | os.X_OK, path=None):
L219: def _access_check(fn, mode):
L277: class ZipExtFile(BaseZipExtFile):
L279: def __init__(self, base):
L282: def __enter__(self):
L285: def __exit__(self, *exc_info):
L289: class ZipFile(BaseZipFile):
L291: def __enter__(self):
L294: def __exit__(self, *exc_info):
L298: def open(self, *args, **kwargs):
L307: def python_implementation():
L325: def callable(obj):
L345: def fsencode(filename):

```

```

L354: def fsdecode(filename):
L371: def _get_normal_name(orig_enc):
L382: def detect_encoding(readline):
L407: def read_or_stop():
L413: def find_cookie(line):
L494: def _recursive_repr(fillvalue='...'):
L500: def decorating_function(user_function):
L503: def wrapper(self):
L524: class ChainMap(MutableMapping):
L537: def __init__(self, *maps):
L544: def __missing__(self, key):
L547: def __getitem__(self, key):
L557: def get(self, key, default=None):
L560: def __len__(self):
L564: def __iter__(self):
L567: def __contains__(self, key):
L570: def __bool__(self):
L574: def __repr__(self):
L579: def fromkeys(cls, iterable, *args):
L583: def copy(self):
L589: def new_child(self): # like Django's Context.push()
L594: def parents(self): # like Django's Context.pop()
L598: def __setitem__(self, key, value):
L601: def __delitem__(self, key):
L608: def popitem(self):
L615: def pop(self, key, *args):
L623: def clear(self):
L632: def cache_from_source(path, debug_override=None):
L659: class OrderedDict(dict):
L672: def __init__(self, *args, **kwds):
L689: def __setitem__(self, key, value, dict_setitem=dict.__setitem__):
L699: def __delitem__(self, key, dict_delitem=dict.__delitem__):
L708: def __iter__(self):
L716: def __reversed__(self):
L724: def clear(self):
L736: def popitem(self, last=True):
L761: def keys(self):
L765: def values(self):
L769: def items(self):
L773: def iterkeys(self):
L777: def itervalues(self):
L782: def iteritems(self):
L787: def update(*args, **kwds):
L822: def pop(self, key, default=__marker):
L835: def setdefault(self, key, default=None):
L842: def __repr__(self, _repr_running=None):
L857: def __reduce__(self):
L867: def copy(self):
L872: def fromkeys(cls, iterable, value=None):
L882: def __eq__(self, other):
L892: def __ne__(self, other):

```

```

L897: def viewkeys(self):
L901: def viewvalues(self):
L905: def viewitems(self):
L915: def valid_ident(s):
L930: class ConvertingDict(dict):
L933: def __getitem__(self, key):
L945: def get(self, key, default=None):
L957: def pop(self, key, default=None):
L967: class ConvertingList(list):
L970: def __getitem__(self, key):
L982: def pop(self, idx=-1):
L991: class ConvertingTuple(tuple):
L994: def __getitem__(self, key):
L1004: class BaseConfigurator(object):
L1024: def __init__(self, config):
L1028: def resolve(self, s):
L1051: def ext_convert(self, value):
L1055: def cfg_convert(self, value):
L1090: def convert(self, value):
L1119: def configure_custom(self, config):
L1133: def as_tuple(self, value):

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/__init__.py

```

L12: class DistlibException(Exception):
L20: class NullHandler(logging.Handler):
L22: def handle(self, record):
L25: def emit(self, record):
L28: def createLock(self):

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/scripts.py

```

L71: def enquote_executable(executable):
L91: class ScriptMaker(object):
L100: def __init__(self, source_dir, target_dir, add_launchers=True, dry_run=False,
fileop=None):
L114: def _get_alternate_executable(self, executable, options):
L123: def _is_shell(self, executable):
L135: def _fix_jython_executable(self, executable):
L147: def _build_shebang(self, executable, post_interp):
L183: def _get_shebang(self, encoding, post_interp=b'', options=None):
L249: def _get_script_text(self, entry):
L255: def get_manifest(self, exename):
L259: def _write_script(self, names, shebang, script_bytes, filenames, ext):
L316: def get_script_filenames(self, name):
L326: def _make_script(self, entry, filenames, options=None):
L342: def _copy_script(self, script, filenames):
L393: def dry_run(self):

```

```

L397: def dry_run(self, value):
L404: def _get_launcher(self, kind):
L419: def make(self, specification, options=None):
L438: def make_multiple(self, specifications, options=None):

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/resources.py

```

L27: class ResourceCache(Cache):
L28: def __init__(self, base=None):
L34: def is_stale(self, resource, path):
L45: def get(self, resource):
L71: class ResourceBase(object):
L72: def __init__(self, finder, name):
L77: class Resource(ResourceBase):
L85: def as_stream(self):
L95: def file_path(self):
L102: def bytes(self):
L106: def size(self):
L110: class ResourceContainer(ResourceBase):
L114: def resources(self):
L118: class ResourceFinder(object):
L128: def __init__(self, module):
L133: def _adjust_path(self, path):
L136: def _make_path(self, resource_name):
L148: def _find(self, path):
L151: def get_cache_info(self, resource):
L154: def find(self, resource_name):
L166: def get_stream(self, resource):
L169: def get_bytes(self, resource):
L173: def get_size(self, resource):
L176: def get_resources(self, resource):
L177: def allowed(f):
L182: def is_container(self, resource):
L187: def iterator(self, resource_name):
L208: class ZipResourceFinder(ResourceFinder):
L212: def __init__(self, module):
L223: def _adjust_path(self, path):
L226: def _find(self, path):
L244: def get_cache_info(self, resource):
L249: def get_bytes(self, resource):
L252: def get_stream(self, resource):
L255: def get_size(self, resource):
L259: def get_resources(self, resource):
L274: def _is_directory(self, path):
L306: def register_finder(loader, finder_maker):
L313: def finder(package):
L341: def finder_for_path(path):

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/util.py

```

L54: def parse_marker(marker_string):
L64: def marker_var(remaining):
L100: def marker_expr(remaining):
L119: def marker_and(remaining):
L130: def marker(remaining):
L144: def parse_requirement(req):
L196: def get_versions(ver_remaining):
L268: def get_resources_dests(resources_root, rules):
L271: def get_rel_path(root, path):
L294: def in_venv():
L304: def get_executable():
L322: def proceed(prompt, allowed_chars, error_prompt=None, default=None):
L338: def extract_by_key(d, keys):
L348: def read_exports(stream):
L368: def read_stream(cp, stream):
L395: def write_exports(exports, stream):
L415: def tempdir():
L424: def chdir(d):
L434: def socket_timeout(seconds=15):
L443: class cached_property(object):
L445: def __init__(self, func):
L450: def __get__(self, obj, cls=None):
L459: def convert_path(pathname):
L486: class FileOperator(object):
L488: def __init__(self, dry_run=False):
L493: def _init_record(self):
L498: def record_as_written(self, path):
L502: def newer(self, source, target):
L521: def copy_file(self, infile, outfile, check=True):
L538: def copy_stream(self, instream, outfile, encoding=None):
L553: def write_binary_file(self, path, data):
L562: def write_text_file(self, path, data, encoding):
L565: def set_mode(self, bits, mask, files):
L579: def ensure_dir(self, path):
L591: def byte_compile(self, path, optimize=False, force=False, prefix=None,
hashed_invalidation=False):
L610: def ensure_removed(self, path):
L631: def is_writable(self, path):
L643: def commit(self):
L653: def rollback(self):
L672: def resolve(module_name, dotted_path):
L687: class ExportEntry(object):
L689: def __init__(self, name, prefix, suffix, flags):
L696: def value(self):
L699: def __repr__(self): # pragma: no cover
L702: def __eq__(self, other):
L720: def get_export_entry(specification):
L751: def get_cache_base(suffix=None):

```

```

L792: def path_to_cache_dir(path, use_abspath=True):
L809: def ensure_slash(s):
L815: def parse_credentials(netloc):
L830: def get_process_umask():
L836: def is_string_sequence(seq):
L852: def split_filename(filename, project_name=None):
L882: def parse_name_and_version(p):
L898: def get_extras(requested, available):
L926: def _get_external_data(url):
L950: def get_project_data(name):
L957: def get_package_data(name, version):
L963: class Cache(object):
L970: def __init__(self, base):
L984: def prefix_to_dir(self, prefix, use_abspath=True):
L990: def clear(self):
L1007: class EventMixin(object):
L1012: def __init__(self):
L1015: def add(self, event, subscriber, append=True):
L1035: def remove(self, event, subscriber):
L1047: def get_subscribers(self, event):
L1054: def publish(self, event, *args, **kwargs):
L1080: class Sequencer(object):
L1082: def __init__(self):
L1087: def add_node(self, node):
L1090: def remove_node(self, node, edges=False):
L1106: def add(self, pred, succ):
L1111: def remove(self, pred, succ):
L1124: def is_step(self, step):
L1127: def get_steps(self, final):
L1153: def strong_connections(self):
L1163: def strongconnect(node):
L1205: def dot(self):
L1224: def unarchive(archive_filename, dest_dir, format=None, check=True):
L1226: def check_path(path):
L1275: def extraction_filter(member, path):
L1292: def zip_dir(directory):
L1313: class Progress(object):
L1316: def __init__(self, minval=0, maxval=100):
L1324: def update(self, curval):
L1334: def increment(self, incr):
L1338: def start(self):
L1342: def stop(self):
L1348: def maximum(self):
L1352: def percentage(self):
L1362: def format_duration(self, duration):
L1372: def ETA(self):
L1391: def speed(self):
L1412: def iglob(path_glob):
L1423: def _iglob(path_glob):
L1458: class HTTPSConnection(httplib.HTTPSConnection):
L1463: def connect(self):

```

```

L1491: class HTTPSHandler(BaseHTTPSHandler):
L1493: def __init__(self, ca_certs, check_domain=True):
L1498: def _conn_maker(self, *args, **kwargs):
L1514: def https_open(self, req):
L1533: class HTTPSOnlyHandler(HTTPSHandler, HTTPHandler):
L1535: def http_open(self, req):
L1543: class Transport(xmlrpclib.Transport):
L1545: def __init__(self, timeout, use_datetime=0):
L1549: def make_connection(self, host):
L1559: class SafeTransport(xmlrpclib.SafeTransport):
L1561: def __init__(self, timeout, use_datetime=0):
L1565: def make_connection(self, host):
L1576: class ServerProxy(xmlrpclib.ServerProxy):
L1578: def __init__(self, uri, **kwargs):
L1601: def _csv_open(fn, mode, **kwargs):
L1612: class CSVBase(object):
L1619: def __enter__(self):
L1622: def __exit__(self, *exc_info):
L1626: class CSVReader(CSVBase):
L1628: def __init__(self, **kwargs):
L1639: def __iter__(self):
L1642: def next(self):
L1653: class CSVWriter(CSVBase):
L1655: def __init__(self, fn, **kwargs):
L1659: def writerow(self, row):
L1675: class Configurator(BaseConfigurator):
L1680: def __init__(self, config, base=None):
L1684: def configure_custom(self, config):
L1686: def convert(o):
L1716: def __getitem__(self, key):
L1722: def inc_convert(self, value):
L1731: class SubprocessMixin(object):
L1736: def __init__(self, verbose=False, progress=None):
L1740: def reader(self, stream, context):
L1761: def run_command(self, cmd, **kwargs):
L1777: def normalize_name(name):
L1794: class PyPIRCFile(object):
L1799: def __init__(self, fn=None, url=None):
L1805: def read(self):
L1858: def update(self, username, password):
L1871: def _load_pypirc(index):
L1878: def _store_pypirc(index):
L1888: def get_host_platform():
L1978: def get_platform():

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_null_file.py

```

L5: class NullFile(IO[str]):
L6: def close(self) -> None:

```



```

L9: def isatty(self) -> bool:
L12: def read(self, __n: int = 1) -> str:
L15: def readable(self) -> bool:
L18: def readline(self, __limit: int = 1) -> str:
L21: def readlines(self, __hint: int = 1) -> List[str]:
L24: def seek(self, __offset: int, __whence: int = 1) -> int:
L27: def seekable(self) -> bool:
L30: def tell(self) -> int:
L33: def truncate(self, __size: Optional[int] = 1) -> int:
L36: def writable(self) -> bool:
L39: def writelines(self, __lines: Iterable[str]) -> None:
L42: def __next__(self) -> str:
L45: def __iter__(self) -> Iterator[str]:
L48: def __enter__(self) -> IO[str]:
L51: def __exit__(
L59: def write(self, text: str) -> int:
L62: def flush(self) -> None:
L65: def fileno(self) -> int:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/segment.py

```

L35: class ControlType(IntEnum):
L64: class Segment(NamedTuple):
L82: def cell_length(self) -> int:
L91: def __rich_repr__(self) -> Result:
L100: def __bool__(self) -> bool:
L105: def is_control(self) -> bool:
L111: def _split_cells(cls, segment: "Segment", cut: int) -> Tuple["Segment", "Segment"]:
L158: def split_cells(self, cut: int) -> Tuple["Segment", "Segment"]:
L185: def line(cls) -> "Segment":
L190: def apply_style(
L231: def filter_control(
L250: def split_lines(cls, segments: Iterable["Segment"]) -> Iterable[List["Segment"]]:
L279: def split_and_crop_lines(
L326: def adjust_line_length(
L371: def get_line_length(cls, line: List["Segment"]) -> int:
L384: def get_shape(cls, lines: List[List["Segment"]]) -> Tuple[int, int]:
L398: def set_shape(
L434: def align_top(
L463: def align_bottom(
L492: def align_middle(
L523: def simplify(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L550: def strip_links(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L567: def strip_styles(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L580: def remove_color(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:
L602: def divide(
L671: class Segments:
L680: def __init__(self, segments: Iterable[Segment], new_lines: bool = False) -> None:
L684: def __rich_console__(

```

```

L696: class SegmentLines:
L697: def __init__(self, lines: Iterable[List[Segment]], new_lines: bool = False) -> None:
L708: def __rich_console__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/emoji.py

```

L18: class NoEmoji(Exception):
L22: class Emoji(JupyterMixin):
L27: def __init__(
L53: def replace(cls, text: str) -> str:
L64: def __repr__(self) -> str:
L67: def __str__(self) -> str:
L70: def __rich_console__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/styled.py

```

L11: class Styled:
L19: def __init__(self, renderable: "RenderableType", style: "StyleType") -> None:
L23: def __rich_console__(
L31: def __rich_measure__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_log_render.py

```

L14: class LogRender:
L15: def __init__(
L32: def __call__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/constrain.py

```

L10: class Constrain(JupyterMixin):
L18: def __init__(self, renderable: "RenderableType", width: Optional[int] = 80) -> None:
L22: def __rich_console__(
L31: def __rich_measure__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/tree.py

```

L14: class Tree(JupyterMixin):
L37: def __init__(
L55: def add(
L86: def __rich_console__(
L101: def make_guide(index: int, style: Style) -> Segment:
L176: def __rich_measure__(
L223: class Segment(NamedTuple):

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/protocol.py

```
L10: def is_renderable(check_object: Any) -> bool:
L19: def rich_cast(renderable: object) -> "RenderableType":
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/syntax.py

```
L124: class SyntaxTheme(ABC):
L128: def get_style_for_token(self, token_type: TokenType) -> Style:
L133: def get_background_style(self) -> Style:
L138: class PygmentsSyntaxTheme(SyntaxTheme):
L141: def __init__(self, theme: Union[str, Type[PygmentsStyle]]) -> None:
L154: def get_style_for_token(self, token_type: TokenType) -> Style:
L176: def get_background_style(self) -> Style:
L180: class ANSISyntaxTheme(SyntaxTheme):
L183: def __init__(self, style_map: Dict[TokenType, Style]) -> None:
L189: def get_style_for_token(self, token_type: TokenType) -> Style:
L209: def get_background_style(self) -> Style:
L216: class _SyntaxHighlightRange(NamedTuple):
L229: class PaddingProperty:
L232: def __get__(self, obj: Syntax, objtype: Type[Syntax]) -> Tuple[int, int, int, int]:
L236: def __set__(self, obj: Syntax, padding: PaddingDimensions) -> None:
L240: class Syntax(JupyterMixin):
L265: def get_theme(cls, name: Union[str, SyntaxTheme]) -> SyntaxTheme:
L276: def __init__(
L317: def from_path(
L380: def guess_lexer(cls, path: str, code: Optional[str] = None) -> str:
L421: def _get_base_style(self) -> Style:
L426: def _get_token_color(self, token_type: TokenType) -> Optional[Color]:
L439: def lexer(self) -> Optional[Lexer]:
L458: def default_lexer(self) -> Lexer:
L467: def highlight(
L505: def line_tokenize() -> Iterable[Tuple[Any, str]]:
L514: def tokens_to_spans() -> Iterable[Tuple[str, Optional[Style]]]:
L552: def stylize_range(
L573: def _get_line_numbers_color(self, blend: float = 0.3) -> Color:
L589: def _numbers_column_width(self) -> int:
L599: def _get_number_styles(self, console: Console) -> Tuple[Style, Style, Style]:
L622: def __rich_measure__(
L640: def __rich_console__(
L649: def _get_syntax(
L787: def _apply_stylized_ranges(self, text: Text) -> None:
L820: def _process_code(self, code: str) -> Tuple[bool, str]:
L841: def _get_code_index_for_syntax_position(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_extension.py

```
L4: def load_ipython_extension(ip: Any) -> None: # pragma: no cover
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/control.py

```
L48: class Control:
L58: def __init__(self, *codes: Union[ControlType, ControlCode]) -> None:
L69: def bell(cls) -> "Control":
L74: def home(cls) -> "Control":
L79: def move(cls, x: int = 0, y: int = 0) -> "Control":
L91: def get_codes() -> Iterable[ControlCode]:
L108: def move_to_column(cls, x: int, y: int = 0) -> "Control":
L132: def move_to(cls, x: int, y: int) -> "Control":
L145: def clear(cls) -> "Control":
L150: def show_cursor(cls, show: bool) -> "Control":
L155: def alt_screen(cls, enable: bool) -> "Control":
L163: def title(cls, title: str) -> "Control":
L171: def __str__(self) -> str:
L174: def __rich_console__(
L181: def strip_control_codes(
L195: def escape_control_codes(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/status.py

```
L11: class Status(JupyterMixin):
L23: def __init__(
L45: def renderable(self) -> Spinner:
L49: def console(self) -> "Console":
L53: def update(
L85: def start(self) -> None:
L89: def stop(self) -> None:
L93: def __rich__(self) -> RenderableType:
L96: def __enter__(self) -> "Status":
L100: def __exit__(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/color_triplet.py

```
L4: class ColorTriplet(NamedTuple):
L15: def hex(self) -> str:
L21: def rgb(self) -> str:
L31: def normalized(self) -> Tuple[float, float, float]:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress.py

```
L64: class _TrackThread(Thread):
L67: def __init__(self, progress: "Progress", task_id: "TaskID", update_period: float):
L76: def run(self) -> None:
```

```

L90: def __enter__(self) -> "_TrackThread":
L94: def __exit__(
L104: def track(
L182: class _Reader(RawIOBase, BinaryIO):
L185: def __init__(
L198: def __enter__(self) -> "_Reader":
L202: def __exit__(
L210: def __iter__(self) -> BinaryIO:
L213: def __next__(self) -> bytes:
L219: def closed(self) -> bool:
L222: def fileno(self) -> int:
L225: def isatty(self) -> bool:
L229: def mode(self) -> str:
L233: def name(self) -> str:
L236: def readable(self) -> bool:
L239: def seekable(self) -> bool:
L242: def writable(self) -> bool:
L245: def read(self, size: int = -1) -> bytes:
L250: def readinto(self, b: Union[bytearray, memoryview, mmap]): # type:
ignore[no-untyped-def, override]
L255: def readline(self, size: int = -1) -> bytes: # type: ignore[override]
L260: def readlines(self, hint: int = -1) -> List[bytes]:
L265: def close(self) -> None:
L270: def seek(self, offset: int, whence: int = 0) -> int:
L275: def tell(self) -> int:
L278: def write(self, s: Any) -> int:
L281: def writelines(self, lines: Iterable[Any]) -> None:
L285: class _ReadContext(ContextManager[_I], Generic[_I]):
L288: def __init__(self, progress: "Progress", reader: _I) -> None:
L292: def __enter__(self) -> _I:
L296: def __exit__(
L306: def wrap_file(
L372: def open(
L397: def open(
L421: def open(
L507: class ProgressColumn(ABC):
L512: def __init__(self, table_column: Optional[Column] = None) -> None:
L517: def get_table_column(self) -> Column:
L521: def __call__(self, task: "Task") -> RenderableType:
L545: def render(self, task: "Task") -> RenderableType:
L549: class RenderableColumn(ProgressColumn):
L556: def __init__(
L562: def render(self, task: "Task") -> RenderableType:
L566: class SpinnerColumn(ProgressColumn):
L576: def __init__(
L592: def set_spinner(
L607: def render(self, task: "Task") -> RenderableType:
L616: class TextColumn(ProgressColumn):
L619: def __init__(
L635: def render(self, task: "Task") -> Text:
L646: class BarColumn(ProgressColumn):

```

```

L657: def __init__(
L673: def render(self, task: "Task") -> ProgressBar:
L688: class TimeElapsedColumn(ProgressColumn):
L691: def render(self, task: "Task") -> Text:
L700: class TaskProgressColumn(TextColumn):
L714: def __init__(
L737: def render_speed(cls, speed: Optional[float]) -> Text:
L756: def render(self, task: "Task") -> Text:
L772: class TimeRemainingColumn(ProgressColumn):
L783: def __init__(
L793: def render(self, task: "Task") -> Text:
L820: class FileSizeColumn(ProgressColumn):
L823: def render(self, task: "Task") -> Text:
L829: class TotalFileSizeColumn(ProgressColumn):
L832: def render(self, task: "Task") -> Text:
L838: class MofNCompleteColumn(ProgressColumn):
L850: def __init__(self, separator: str = "/", table_column: Optional[Column] = None):
L854: def render(self, task: "Task") -> Text:
L865: class DownloadColumn(ProgressColumn):
L872: def __init__(
L878: def render(self, task: "Task") -> Text:
L914: class TransferSpeedColumn(ProgressColumn):
L917: def render(self, task: "Task") -> Text:
L926: class ProgressSample(NamedTuple):
L936: class Task:
L983: def get_time(self) -> float:
L988: def started(self) -> bool:
L993: def remaining(self) -> Optional[float]:
L1000: def elapsed(self) -> Optional[float]:
L1009: def finished(self) -> bool:
L1014: def percentage(self) -> float:
L1023: def speed(self) -> Optional[float]:
L1041: def time_remaining(self) -> Optional[float]:
L1054: def _reset(self) -> None:
L1061: class Progress(JupyterMixin):
L1077: def __init__(
L1114: def get_default_columns(cls) -> Tuple[ProgressColumn, ...]:
L1145: def console(self) -> Console:
L1149: def tasks(self) -> List[Task]:
L1155: def task_ids(self) -> List[TaskID]:
L1161: def finished(self) -> bool:
L1168: def start(self) -> None:
L1173: def stop(self) -> None:
L1179: def __enter__(self) -> Self:
L1183: def __exit__(
L1191: def track(
L1236: def wrap_file(
L1279: def open(
L1295: def open(
L1310: def open(
L1387: def start_task(self, task_id: TaskID) -> None:

```

```

L1401: def stop_task(self, task_id: TaskID) -> None:
L1416: def update(
L1477: def reset(
L1516: def advance(self, task_id: TaskID, advance: float = 1) -> None:
L1546: def refresh(self) -> None:
L1551: def get_renderable(self) -> RenderableType:
L1556: def get_renderables(self) -> Iterable[RenderableType]:
L1561: def make_tasks_table(self, tasks: Iterable[Task]) -> Table:
L1594: def __rich__(self) -> RenderableType:
L1599: def add_task(
L1642: def remove_task(self, task_id: TaskID) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/cells.py

```

L34: def cached_cell_len(text: str) -> int:
L51: def cell_len(text: str, _cell_len: Callable[[str], int] = cached_cell_len) -> int:
L68: def get_character_cell_size(character: str) -> int:
L96: def set_cell_size(text: str, total: int) -> str:
L131: def chop_cells(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/prompt.py

```

L11: class PromptError(Exception):
L15: class InvalidResponse(PromptError):
L23: def __init__(self, message: TextType) -> None:
L26: def __rich__(self) -> TextType:
L30: class PromptBase(Generic[PromptType]):
L54: def __init__(
L80: def ask(
L97: def ask(
L112: def ask(
L151: def render_default(self, default: DefaultType) -> Text:
L162: def make_prompt(self, default: DefaultType) -> Text:
L194: def get_input(
L213: def check_choice(self, value: str) -> bool:
L227: def process_response(self, value: str) -> PromptType:
L258: def on_validate_error(self, value: str, error: InvalidResponse) -> None:
L267: def pre_prompt(self) -> None:
L271: def __call__(self, *, stream: Optional[TextIO] = None) -> PromptType:
L275: def __call__(
L280: def __call__(self, *, default: Any = ..., stream: Optional[TextIO] = None) -> Any:
L304: class Prompt(PromptBase[str]):
L316: class IntPrompt(PromptBase[int]):
L328: class FloatPrompt(PromptBase[float]):
L340: class Confirm(PromptBase[bool]):
L353: def render_default(self, default: DefaultType) -> Text:
L358: def process_response(self, value: str) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/box.py

```

L10: class Box:
L27: def __init__(self, box: str, *, ascii: bool = False) -> None:
L61: def __repr__(self) -> str:
L64: def __str__(self) -> str:
L67: def substitute(self, options: "ConsoleOptions", safe: bool = True) -> "Box":
L85: def get_plain_headed_box(self) -> "Box":
L95: def get_top(self, widths: Iterable[int]) -> str:
L115: def get_row(
L164: def get_bottom(self, widths: Iterable[int]) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/scope.py

```

L14: def render_scope(
L41: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:
L75: def test(foo: float, bar: float) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_emoji_replace.py

```

L12: def _emoji_replace(
L23: def do_replace(match: Match[str]) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/console.py

```

L79: class NoChange:
L109: class ConsoleDimensions(NamedTuple):
L119: class ConsoleOptions:
L149: def ascii_only(self) -> bool:
L153: def copy(self) -> "ConsoleOptions":
L163: def update(
L200: def update_width(self, width: int) -> "ConsoleOptions":
L213: def update_height(self, height: int) -> "ConsoleOptions":
L226: def reset_height(self) -> "ConsoleOptions":
L236: def update_dimensions(self, width: int, height: int) -> "ConsoleOptions":
L253: class RichCast(Protocol):
L256: def __rich__(
L263: class ConsoleRenderable(Protocol):
L266: def __rich_console__(
L282: class CaptureError(Exception):
L286: class NewLine:
L289: def __init__(self, count: int = 1) -> None:
L292: def __rich_console__(
L298: class ScreenUpdate:
L301: def __init__(self, lines: List[List[Segment]], x: int, y: int) -> None:
L306: def __rich_console__(

```



```

L316: class Capture:
L324: def __init__(self, console: "Console") -> None:
L328: def __enter__(self) -> "Capture":
L332: def __exit__(
L340: def get(self) -> str:
L349: class ThemeContext:
L352: def __init__(self, console: "Console", theme: Theme, inherit: bool = True) -> None:
L357: def __enter__(self) -> "ThemeContext":
L361: def __exit__(
L370: class PagerContext:
L373: def __init__(
L385: def __enter__(self) -> "PagerContext":
L389: def __exit__(
L409: class ScreenContext:
L412: def __init__(
L420: def update(
L438: def __enter__(self) -> "ScreenContext":
L444: def __exit__(
L456: class Group:
L464: def __init__(self, *renderables: "RenderableType", fit: bool = True) -> None:
L470: def renderables(self) -> List["RenderableType"]:
L475: def __rich_measure__(
L483: def __rich_console__(
L489: def group(fit: bool = True) -> Callable[..., Callable[..., Group]]:
L496: def decorator(
L502: def _replace(*args: Any, **kwargs: Any) -> Group:
L511: def _is_jupyter() -> bool: # pragma: no cover
L542: class ConsoleThreadLocals(threading.local):
L550: class RenderHook(ABC):
L554: def process_renderables(
L572: def get_windows_console_features() -> "WindowsConsoleFeatures": # pragma: no cover
L582: def detect_legacy_windows() -> bool:
L587: class Console:
L625: def __init__(
L759: def __repr__(self) -> str:
L763: def file(self) -> IO[str]:
L772: def file(self, new_file: IO[str]) -> None:
L777: def _buffer(self) -> List[Segment]:
L782: def _buffer_index(self) -> int:
L787: def _buffer_index(self, value: int) -> None:
L791: def _theme_stack(self) -> ThemeStack:
L795: def _detect_color_system(self) -> Optional[ColorSystem]:
L819: def _enter_buffer(self) -> None:
L823: def _exit_buffer(self) -> None:
L828: def set_live(self, live: "Live") -> bool:
L844: def clear_live(self) -> None:
L849: def push_render_hook(self, hook: RenderHook) -> None:
L858: def pop_render_hook(self) -> None:
L863: def __enter__(self) -> "Console":
L868: def __exit__(self, exc_type: Any, exc_value: Any, traceback: Any) -> None:
L872: def begin_capture(self) -> None:

```

```

L876: def end_capture(self) -> str:
L887: def push_theme(self, theme: Theme, *, inherit: bool = True) -> None:
L898: def pop_theme(self) -> None:
L902: def use_theme(self, theme: Theme, *, inherit: bool = True) -> ThemeContext:
L915: def color_system(self) -> Optional[str]:
L928: def encoding(self) -> str:
L937: def is_terminal(self) -> bool:
L985: def is_dumb_terminal(self) -> bool:
L997: def options(self) -> ConsoleOptions:
L1011: def size(self) -> ConsoleDimensions:
L1052: def size(self, new_size: Tuple[int, int]) -> None:
L1063: def width(self) -> int:
L1072: def width(self, width: int) -> None:
L1081: def height(self) -> int:
L1090: def height(self, height: int) -> None:
L1098: def bell(self) -> None:
L1102: def capture(self) -> Capture:
L1119: def pager(
L1142: def line(self, count: int = 1) -> None:
L1152: def clear(self, home: bool = True) -> None:
L1163: def status(
L1196: def show_cursor(self, show: bool = True) -> bool:
L1207: def set_alt_screen(self, enable: bool = True) -> bool:
L1229: def is_alt_screen(self) -> bool:
L1237: def set_window_title(self, title: str) -> bool:
L1269: def screen(
L1283: def measure(
L1300: def render(
L1351: def render_lines(
L1415: def render_str(
L1476: def get_style(
L1506: def _collect_renderables(
L1539: def align_append(renderable: RenderableType) -> None:
L1548: def check_text() -> None:
L1585: def rule(
L1606: def control(self, *control: Control) -> None:
L1616: def out(
L1648: def print(
L1747: def print_json(
L1808: def update_screen(
L1842: def update_screen_lines(
L1862: def print_exception(
L1898: def _caller_frame_info(
L1932: def log(
L2013: def on_broken_pipe(self) -> None:
L2027: def _check_buffer(self) -> None:
L2042: def _write_buffer(self) -> None:
L2115: def _render_buffer(self, buffer: Iterable[Segment]) -> str:
L2139: def input(
L2173: def export_text(self, *, clear: bool = True, styles: bool = False) -> str:
L2205: def save_text(self, path: str, *, clear: bool = True, styles: bool = False) -> None:

```

```

L2219: def export_html(
L2294: def save_html(
L2325: def export_svg(
L2356: def get_svg_style(style: Style) -> str:
L2416: def escape_text(text: str) -> str:
L2420: def make_tag(
L2425: def stringify(value: object) -> str:
L2576: def save_svg(
L2615: def _svg_hash(svg_main_code: str) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/jupyter.py

```

L18: class JupyterRenderable:
L21: def __init__(self, html: str, text: str) -> None:
L25: def _repr_mimebundle_(
L36: class JupyterMixin:
L41: def _repr_mimebundle_(
L59: def _render_segments(segments: Iterable[Segment]) -> str:
L60: def escape(text: str) -> str:
L84: def display(segments: Iterable[Segment], text: str) -> None:
L98: def print(*args: Any, **kwargs: Any) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/abc.py

```

L4: class RichRenderable(ABC):
L16: def __subclasshook__(cls, other: type) -> bool:
L28: class Foo:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress_bar.py

```

L18: class ProgressBar(JupyterMixin):
L33: def __init__(
L57: def __repr__(self) -> str:
L61: def percentage_completed(self) -> Optional[float]:
L70: def _get_pulse_segments(
L116: def update(self, completed: float, total: Optional[float] = None) -> None:
L126: def _render_pulse(
L156: def __rich_console__(
L200: def __rich_measure__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/json.py

```

L9: class JSON:
L25: def __init__(
L54: def from_data(
L101: def __rich__(self) -> Text:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/__main__.py

```

L18: class ColorBox:
L19: def __rich_console__(
L33: def __rich_measure__(
L39: def make_test_card() -> Table:
L90: def comparison(renderable1: RenderableType, renderable2: RenderableType) -> Table:
L157: def iter_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/measure.py

```

L11: class Measurement(NamedTuple):
L20: def span(self) -> int:
L24: def normalize(self) -> "Measurement":
L34: def with_maximum(self, width: int) -> "Measurement":
L46: def with_minimum(self, width: int) -> "Measurement":
L59: def clamp(
L79: def get(
L125: def measure_renderables(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/text.py

```

L47: class Span(NamedTuple):
L57: def __repr__(self) -> str:
L60: def __bool__(self) -> bool:
L63: def split(self, offset: int) -> Tuple["Span", Optional["Span"]]:
L76: def move(self, offset: int) -> "Span":
L88: def right_crop(self, offset: int) -> "Span":
L102: def extend(self, cells: int) -> "Span":
L118: class Text(JupyterMixin):
L144: def __init__(
L167: def __len__(self) -> int:
L170: def __bool__(self) -> bool:
L173: def __str__(self) -> str:
L176: def __repr__(self) -> str:
L179: def __add__(self, other: Any) -> "Text":
L186: def __eq__(self, other: object) -> bool:
L191: def __contains__(self, other: object) -> bool:
L198: def __getitem__(self, slice: Union[int, slice]) -> "Text":
L199: def get_text_at(offset: int) -> "Text":
L225: def cell_len(self) -> int:
L230: def markup(self) -> str:
L260: def from_markup(
L294: def from_ansi(
L332: def styled(
L357: def assemble(
L403: def plain(self) -> str:

```

```

L410: def plain(self, new_text: str) -> None:
L421: def spans(self) -> List[Span]:
L426: def spans(self, spans: List[Span]) -> None:
L430: def blank_copy(self, plain: str = "") -> "Text":
L443: def copy(self) -> "Text":
L457: def stylize(
L483: def stylize_before(
L509: def apply_meta(
L523: def on(self, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Text":
L543: def remove_suffix(self, suffix: str) -> None:
L552: def get_style_at_offset(self, console: "Console", offset: int) -> Style:
L572: def extend_style(self, spaces: int) -> None:
L593: def highlight_regex(
L633: def highlight_words(
L662: def rstrip(self) -> None:
L666: def rstrip_end(self, size: int) -> None:
L680: def set_length(self, new_length: int) -> None:
L689: def __rich_console__(
L708: def __rich_measure__(
L720: def render(self, console: "Console", end: str = "") -> Iterable["Segment"]:
L759: def get_current_style() -> Style:
L779: def join(self, lines: Iterable["Text"]) -> "Text":
L791: def iter_text() -> Iterable["Text"]:
L818: def expand_tabs(self, tab_size: Optional[int] = None) -> None:
L860: def truncate(
L887: def _trim_spans(self) -> None:
L901: def pad(self, count: int, character: str = " ") -> None:
L918: def pad_left(self, count: int, character: str = " ") -> None:
L934: def pad_right(self, count: int, character: str = " ") -> None:
L945: def align(self, align: AlignMethod, width: int, character: str = " ") -> None:
L965: def append(
L1009: def append_text(self, text: "Text") -> "Text":
L1031: def append_tokens(
L1055: def copy_styles(self, text: "Text") -> None:
L1063: def split(
L1092: def flatten_spans() -> Iterable[int]:
L1107: def divide(self, offsets: Iterable[int]) -> Lines:
L1186: def right_crop(self, amount: int = 1) -> None:
L1202: def wrap(
L1250: def fit(self, width: int) -> Lines:
L1266: def detect_indentation(self) -> int:
L1287: def with_indent_guides(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/live.py

```

L22: class _RefreshThread(Thread):
L25: def __init__(self, live: "Live", refresh_per_second: float) -> None:
L31: def stop(self) -> None:
L34: def run(self) -> None:

```

```

L41: class Live(JupyterMixin, RenderHook):
L57: def __init__(
L99: def is_started(self) -> bool:
L103: def get_renderable(self) -> RenderableType:
L111: def start(self, refresh: bool = False) -> None:
L145: def stop(self) -> None:
L179: def __enter__(self) -> Self:
L183: def __exit__(
L191: def _enable_redirect_io(self) -> None:
L201: def _disable_redirect_io(self) -> None:
L211: def renderable(self) -> RenderableType:
L226: def update(self, renderable: RenderableType, *, refresh: bool = False) -> None:
L240: def refresh(self) -> None:
L274: def process_renderables(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/bar.py

```

L17: class Bar(JupyterMixin):
L29: def __init__(
L45: def __repr__(self) -> str:
L48: def __rich_console__(
L86: def __rich_measure__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/logging.py

```

L18: class RichHandler(Handler):
L65: def __init__(
L117: def get_level_text(self, record: LogRecord) -> Text:
L132: def emit(self, record: LogRecord) -> None:
L182: def render_message(self, record: LogRecord, message: str) -> "ConsoleRenderable":
L207: def render(
L283: def divide() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/rule.py

```

L12: class Rule(JupyterMixin):
L23: def __init__(
L46: def __repr__(self) -> str:
L49: def __rich_console__(
L105: def _rule_line(self, chars_len: int, width: int) -> Text:
L111: def __rich_measure__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/pretty.py

```

L60: def _is_attr_object(obj: Any) -> bool:
L65: def _get_attr_fields(obj: Any) -> Sequence["_attr_module.Attribute[Any]"]:

```

```

L70: def _is_dataclass_repr(obj: object) -> bool:
L93: def _has_default_namedtuple_repr(obj: object) -> bool:
L113: def _ipy_display_hook(
L161: def _safe_isinstance(
L171: def install(
L200: def display_hook(value: Any) -> None:
L230: class RichFormatter(BaseFormatter): # type: ignore[misc]
L233: def __call__(self, value: Any) -> Any:
L253: class Pretty(JupyterMixin):
L273: def __init__(
L304: def __rich_console__(
L339: def __rich_measure__(
L357: def _get_braces_for_defaultdict(_object: DefaultDict[Any, Any]) -> Tuple[str, str,
str]:
L365: def _get_braces_for_deque(_object: Deque[Any]) -> Tuple[str, str, str]:
L375: def _get_braces_for_array(_object: "array[Any]") -> Tuple[str, str, str]:
L398: def is_expandable(obj: Any) -> bool:
L409: class Node:
L424: def iter_tokens(self) -> Iterable[str]:
L446: def check_length(self, start_length: int, max_length: int) -> bool:
L463: def __str__(self) -> str:
L467: def render(
L494: class _Line:
L507: def expandable(self) -> bool:
L511: def check_length(self, max_length: int) -> bool:
L519: def expand(self, indent_size: int) -> Iterable["_Line"]:
L552: def __str__(self) -> str:
L561: def _is_namedtuple(obj: Any) -> bool:
L580: def traverse(
L601: def to_repr(obj: Any) -> str:
L621: def _traverse(obj: Any, root: bool = False, depth: int = 0) -> Node:
L633: def iter_rich_args(rich_args: Any) -> Iterable[Union[Any, Tuple[str, Any]]]:
L731: def iter_attrs() -> (
L878: def pretty_repr(
L918: def pprint(
L957: class BrokenRepr:
L958: def __repr__(self) -> str:
L964: class StockKeepingUnit(NamedTuple):
L1012: class Thing:
L1013: def __repr__(self) -> str:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/panel.py

```

L17: class Panel(JupyterMixin):
L40: def __init__(
L74: def fit(
L110: def _title(self) -> Optional[Text]:
L126: def _subtitle(self) -> Optional[Text]:
L141: def __rich_console__(

```

```
L159: def align_text(
L277: def __rich_measure__(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows_rendere r.py

```
L7: def legacy_windows_render(buffer: Iterable[Segment], term: LegacyWindowsTerm) -> None:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_fileno.py

```
L6: def get_fileno(file_like: IO[str]) -> int | None:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/palette.py

```
L11: class Palette:
L14: def __init__(self, colors: Sequence[Tuple[int, int, int]]):
L17: def __getitem__(self, number: int) -> ColorTriplet:
L20: def __rich__(self) -> "Table":
L45: def match(self, color: Tuple[int, int, int]) -> int:
L58: def get_color_distance(index: int) -> float:
L83: class ColorBox:
L84: def __rich_console__(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/pager.py

```
L5: class Pager(ABC):
L9: def show(self, content: str) -> None:
L17: class SystemPager(Pager):
L20: def _pager(self, content: str) -> Any: # pragma: no cover
L23: def show(self, content: str) -> None:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/repr.py

```
L23: class ReprError(Exception):
L28: def auto(cls: Optional[Type[T]]) -> Type[T]:
L33: def auto(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:
L37: def auto(
L42: def do_replace(cls: Type[T], angular: Optional[bool] = None) -> Type[T]:
L43: def auto_repr(self: T) -> str:
L68: def auto_rich_repr(self: Type[T]) -> Result:
L105: def rich_repr(cls: Optional[Type[T]]) -> Type[T]:
L110: def rich_repr(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:
L114: def rich_repr(
L126: class Foo:
```



```
L127: def __rich_repr__(self) -> Result:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/columns.py

```
L16: class Columns(JupyterMixin):
L31: def __init__(
L54: def add_renderable(self, renderable: RenderableType) -> None:
L62: def __rich_console__(
L86: def iter_renderables(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/ansi.py

```
L20: class _AnsiToken(NamedTuple):
L28: def _ansi_tokenize(ansi_text: str) -> Iterable[_AnsiToken]:
L120: class AnsiDecoder:
L123: def __init__(self) -> None:
L126: def decode(self, terminal_text: str) -> Iterable[Text]:
L138: def decode_line(self, line: str) -> Text:
L224: def read(fd: int) -> bytes:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/live_render.py

```
L14: class LiveRender:
L22: def __init__(
L33: def set_renderable(self, renderable: RenderableType) -> None:
L41: def position_cursor(self) -> Control:
L62: def restore_cursor(self) -> Control:
L76: def __rich_console__(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/padding.py

```
L19: class Padding(JupyterMixin):
L33: def __init__(
L47: def indent(cls, renderable: "RenderableType", level: int) -> "Padding":
L61: def unpack(pad: "PaddingDimensions") -> Tuple[int, int, int, int]:
L76: def __repr__(self) -> str:
L79: def __rich_console__(
L125: def __rich_measure__(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_timer.py

```
L13: def timer(subject: str = "time") -> Generator[None, None, None]:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/align.py

```

L17: class Align(JupyterMixin):
L33: def __init__(
L60: def __repr__(self) -> str:
L64: def left(
L86: def center(
L108: def right(
L129: def __rich_console__(
L147: def generate_segments() -> Iterable[Segment]:
L192: def blank_lines(count: int) -> Iterable[Segment]:
L221: def __rich_measure__(
L228: class VerticalCenter(JupyterMixin):
L240: def __init__(
L248: def __repr__(self) -> str:
L251: def __rich_console__(
L265: def blank_lines(count: int) -> Iterable[Segment]:
L278: def __rich_measure__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/__init__.py

```

L23: def get_console() -> "Console":
L39: def reconfigure(*args: Any, **kwargs: Any) -> None:
L53: def print(
L77: def print_json(
L120: def inspect(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_inspect.py

```

L15: def _first_paragraph(doc: str) -> str:
L21: class Inspect(JupyterMixin):
L37: def __init__(
L64: def _make_title(self, obj: Any) -> Text:
L74: def __rich__(self) -> Panel:
L82: def _get_signature(self, name: str, obj: Any) -> Optional[Text]:
L121: def _render(self) -> Iterable[RenderableType]:
L124: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:
L128: def safe_getattr(attr_name: str) -> Tuple[Any, Any]:
L214: def _get_formatted_doc(self, object_: Any) -> Optional[str]:
L236: def get_object_types_mro(obj: Union[object, Type[Any]]) -> Tuple[type, ...]:
L245: def get_object_types_mro_as_strings(obj: object) -> Collection[str]:
L258: def is_object_one_of_types(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_loop.py

```

L6: def loop_first(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:
L18: def loop_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:
L31: def loop_first_last(values: Iterable[T]) -> Iterable[Tuple[bool, bool, T]]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/screen.py

```
L18: class Screen:
L28: def __init__(
L40: def __rich_console__(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows.py

```
L6: class WindowsConsoleFeatures:
L34: def get_windows_console_features() -> WindowsConsoleFeatures:
L40: def get_windows_console_features() -> WindowsConsoleFeatures:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/highlighter.py

```
L8: def _combine_regex(*regexes: str) -> str:
L17: class Highlighter(ABC):
L20: def __call__(self, text: Union[str, Text]) -> Text:
L42: def highlight(self, text: Text) -> None:
L50: class NullHighlighter(Highlighter):
L57: def highlight(self, text: Text) -> None:
L61: class RegexHighlighter(Highlighter):
L67: def highlight(self, text: Text) -> None:
L80: class ReprHighlighter(RegexHighlighter):
L106: class JSONHighlighter(RegexHighlighter):
L123: def highlight(self, text: Text) -> None:
L143: class ISO8601Highlighter(RegexHighlighter):
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_wrap.py

```
L12: def words(text: str) -> Iterable[tuple[int, int, str]]:
L26: def divide_line(text: str, width: int, fold: bool = True) -> list[int]:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/spinner.py

```
L13: class Spinner:
L26: def __init__(
L50: def __rich_console__(
L55: def __rich_measure__(
L61: def render(self, time: float) -> "RenderableType":
L95: def update(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/style.py

```
L21: class _Bit:
```

```

L26: def __init__(self, bit_no: int) -> None:
L29: def __get__(self, obj: "Style", objtype: Type["Style"]) -> Optional[bool]:
L36: class Style:
L127: def __init__(
L151: def _make_color(color: Union[Color, str]) -> Color:
L204: def null(cls) -> "Style":
L209: def from_color(
L233: def from_meta(cls, meta: Optional[Dict[str, Any]]) -> "Style":
L254: def on(cls, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Style":
L286: def link_id(self) -> str:
L290: def __str__(self) -> str:
L336: def __bool__(self) -> bool:
L340: def _make_ansi_codes(self, color_system: ColorSystem) -> str:
L385: def normalize(cls, style: str) -> str:
L401: def pick_first(cls, *values: Optional[StyleType]) -> StyleType:
L408: def __rich_repr__(self) -> Result:
L427: def __eq__(self, other: Any) -> bool:
L432: def __ne__(self, other: Any) -> bool:
L437: def __hash__(self) -> int:
L444: def color(self) -> Optional[Color]:
L449: def bgcolor(self) -> Optional[Color]:
L454: def link(self) -> Optional[str]:
L459: def transparent_background(self) -> bool:
L464: def background_style(self) -> "Style":
L469: def meta(self) -> Dict[str, Any]:
L474: def without_color(self) -> "Style":
L494: def parse(cls, style_definition: str) -> "Style":
L560: def get_html_style(self, theme: Optional[TerminalTheme] = None) -> str:
L597: def combine(cls, styles: Iterable["Style"]) -> "Style":
L610: def chain(cls, *styles: "Style") -> "Style":
L622: def copy(self) -> "Style":
L645: def clear_meta_and_links(self) -> "Style":
L667: def update_link(self, link: Optional[str] = None) -> "Style":
L690: def render(
L716: def test(self, text: Optional[str] = None) -> None:
L729: def _add(self, style: Optional["Style"]) -> "Style":
L753: def __add__(self, style: Optional["Style"]) -> "Style":
L761: class StyleStack:
L766: def __init__(self, default_style: "Style") -> None:
L769: def __repr__(self) -> str:
L773: def current(self) -> Style:
L777: def push(self, style: Style) -> None:
L785: def pop(self) -> Style:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/theme.py

```

L8: class Theme:
L18: def __init__(
L31: def config(self) -> str:

```

```

L39: def from_file(
L59: def read(
L76: class ThemeStackError(Exception):
L80: class ThemeStack:
L87: def __init__(self, theme: Theme) -> None:
L91: def push_theme(self, theme: Theme, inherit: bool = True) -> None:
L105: def pop_theme(self) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/terminal_theme.py

```

L9: class TerminalTheme:
L20: def __init__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/layout.py

```

L32: class LayoutRender(NamedTuple):
L43: class LayoutError(Exception):
L47: class NoSplitter(LayoutError):
L51: class _Placeholder:
L56: def __init__(self, layout: "Layout", style: StyleType = "") -> None:
L60: def __rich_console__(
L80: class Splitter(ABC):
L86: def get_tree_icon(self) -> str:
L90: def divide(
L101: class RowSplitter(Splitter):
L106: def get_tree_icon(self) -> str:
L109: def divide(
L121: class ColumnSplitter(Splitter):
L126: def get_tree_icon(self) -> str:
L129: def divide(
L142: class Layout:
L156: def __init__(
L177: def __rich_repr__(self) -> Result:
L184: def renderable(self) -> RenderableType:
L189: def children(self) -> List["Layout"]:
L194: def map(self) -> RenderMap:
L198: def get(self, name: str) -> Optional["Layout"]:
L216: def __getitem__(self, name: str) -> "Layout":
L223: def tree(self) -> "Tree":
L229: def summary(layout: "Layout") -> Table:
L248: def recurse(tree: "Tree", layout: "Layout") -> None:
L261: def split(
L286: def add_split(self, *layouts: Union["Layout", RenderableType]) -> None:
L299: def split_row(self, *layouts: Union["Layout", RenderableType]) -> None:
L307: def split_column(self, *layouts: Union["Layout", RenderableType]) -> None:
L315: def unsplit(self) -> None:
L319: def update(self, renderable: RenderableType) -> None:
L328: def refresh_screen(self, console: "Console", layout_name: str) -> None:

```

```

L345: def _make_region_map(self, width: int, height: int) -> RegionMap:
L366: def render(self, console: Console, options: ConsoleOptions) -> RenderMap:
L395: def __rich_console__(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/diagnose.py

```

L10: def report() -> None: # pragma: no cover

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_pick.py

```

L4: def pick_bool(*values: Optional[bool]) -> bool:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_win32_console.py

```

L29: class LegacyWindowsError(Exception):
L33: class WindowsCoordinates(NamedTuple):
L44: def from_param(cls, value: "WindowsCoordinates") -> COORD:
L57: class CONSOLE_SCREEN_BUFFER_INFO(Structure):
L67: class CONSOLE_CURSOR_INFO(ctypes.Structure):
L78: def GetStdHandle(handle: int = STDOUT) -> wintypes.HANDLE:
L95: def GetConsoleMode(std_handle: wintypes.HANDLE) -> int:
L128: def FillConsoleOutputCharacter(
L169: def FillConsoleOutputAttribute(
L204: def SetConsoleTextAttribute(
L228: def GetConsoleScreenBufferInfo(
L252: def SetConsoleCursorPosition(
L275: def GetConsoleCursorInfo(
L299: def SetConsoleCursorInfo(
L319: def SetConsoleTitle(title: str) -> bool:
L331: class LegacyWindowsTerm:
L362: def __init__(self, file: "IO[str]") -> None:
L377: def cursor_position(self) -> WindowsCoordinates:
L387: def screen_size(self) -> WindowsCoordinates:
L396: def write_text(self, text: str) -> None:
L405: def write_styled(self, text: str, style: Style) -> None:
L444: def move_cursor_to(self, new_position: WindowsCoordinates) -> None:
L454: def erase_line(self) -> None:
L470: def erase_end_of_line(self) -> None:
L484: def erase_start_of_line(self) -> None:
L493: def move_cursor_up(self) -> None:
L503: def move_cursor_down(self) -> None:
L514: def move_cursor_forward(self) -> None:
L526: def move_cursor_to_column(self, column: int) -> None:
L535: def move_cursor_backward(self) -> None:
L547: def hide_cursor(self) -> None:
L553: def show_cursor(self) -> None:
L559: def set_title(self, title: str) -> None:

```

```
L568: def _get_cursor_size(self) -> int:
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/color.py

```
L21: class ColorSystem(IntEnum):
L29: def __repr__(self) -> str:
L32: def __str__(self) -> str:
L36: class ColorType(IntEnum):
L45: def __repr__(self) -> str:
L288: class ColorParseError(Exception):
L303: class Color(NamedTuple):
L315: def __rich__(self) -> "Text":
L326: def __rich_repr__(self) -> Result:
L333: def system(self) -> ColorSystem:
L340: def is_system_defined(self) -> bool:
L345: def is_default(self) -> bool:
L349: def get_truecolor(
L381: def from_ansi(cls, number: int) -> "Color":
L397: def from_triplet(cls, triplet: "ColorTriplet") -> "Color":
L409: def from_rgb(cls, red: float, green: float, blue: float) -> "Color":
L423: def default(cls) -> "Color":
L433: def parse(cls, color: str) -> "Color":
L485: def get_ansi_codes(self, foreground: bool = True) -> Tuple[str, ...]:
L513: def downgrade(self, system: ColorSystem) -> "Color":
L571: def parse_rgb_hex(hex_color: str) -> ColorTriplet:
L580: def blend_rgb(
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/traceback.py

```
L55: def _iter_syntax_lines(
L83: def install(
L134: def excepthook(
L159: def ipy_excepthook_closure(ip: Any) -> None: # pragma: no cover
L163: def ipy_show_traceback(*args: Any, **kwargs: Any) -> None:
L169: def ipy_display_traceback(
L215: class Frame:
L225: class _SyntaxError:
L235: class Stack:
L247: class Trace:
L251: class PathHighlighter(RegexHighlighter):
L255: class Traceback:
L286: def __init__(
L340: def from_exception(
L413: def extract(
L454: def safe_str(_object: Any) -> str:
L502: def get_locals(
L603: def __rich_console__(
L635: def render_stack(stack: Stack, last: bool) -> RenderResult:
```

```

L706: def _render_syntax_error(self, syntax_error: _SyntaxError) -> RenderResult:
L729: def _guess_lexer(cls, filename: str, code: str) -> str:
L745: def _render_stack(self, stack: Stack) -> RenderResult:
L749: def render_locals(frame: Frame) -> Iterable[ConsoleRenderable]:
L877: def bar(
L883: def foo(a: Any) -> None:
L896: def error() -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/table.py

```

L39: class Column:
L117: def copy(self) -> "Column":
L122: def cells(self) -> Iterable["RenderableType"]:
L127: def flexible(self) -> bool:
L133: class Row:
L143: class _Cell(NamedTuple):
L154: class Table(JupyterMixin):
L189: def __init__(
L254: def grid(
L287: def expand(self) -> bool:
L292: def expand(self, expand: bool) -> None:
L297: def _extra_width(self) -> int:
L307: def row_count(self) -> int:
L311: def get_row_style(self, console: "Console", index: int) -> StyleType:
L321: def __rich_measure__(
L355: def padding(self) -> Tuple[int, int, int, int]:
L360: def padding(self, padding: PaddingDimensions) -> "Table":
L365: def add_column(
L423: def add_row(
L441: def add_cell(column: Column, renderable: "RenderableType") -> None:
L470: def add_section(self) -> None:
L476: def __rich_console__(
L497: def render_annotation(
L523: def _calculate_column_widths(
L588: def _collapse_widths(
L626: def _get_cells(
L641: def get_padding(first_row: bool, last_row: bool) -> Tuple[int, int, int, int]:
L699: def _get_padding_width(self, column_index: int) -> int:
L707: def _measure_column(
L747: def _render(
L839: def align_cell(
L967: def header(text: str) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/errors.py

```

L1: class ConsoleError(Exception):
L5: class StyleError(Exception):
L9: class StyleSyntaxError(ConsoleError):

```



```

L13: class MissingStyle(StyleError):
L17: class StyleStackError(ConsoleError):
L21: class NotRenderableError(ConsoleError):
L25: class MarkupError(ConsoleError):
L29: class LiveError(ConsoleError):
L33: class NoAltScreen(ConsoleError):

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_stack.py

```

L6: class Stack(List[T]):
L10: def top(self) -> T:
L14: def push(self, item: T) -> None:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/filesize.py

```

L18: def _to_str(
L43: def pick_unit_and_suffix(size: int, suffixes: List[str], base: int) -> Tuple[int, str]:
L52: def decimal(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/markup.py

```

L20: class Tag(NamedTuple):
L28: def __str__(self) -> str:
L34: def markup(self) -> str:
L48: def escape(
L61: def escape_backslashes(match: Match[str]) -> str:
L73: def _parse(markup: str) -> Iterable[Tuple[int, Optional[str], Optional[Tag]]]:
L106: def render(
L146: def pop_style(style_name: str) -> Tuple[int, Tag]:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/region.py

```

L4: class Region(NamedTuple):

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/containers.py

```

L30: class Renderables:
L33: def __init__(
L40: def __rich_console__(
L46: def __rich_measure__(
L59: def append(self, renderable: "RenderableType") -> None:
L62: def __iter__(self) -> Iterable["RenderableType"]:
L66: class Lines:
L69: def __init__(self, lines: Iterable["Text"] = ()) -> None:
L72: def __repr__(self) -> str:

```

```

L75: def __iter__(self) -> Iterator["Text"]:
L79: def __getitem__(self, index: int) -> "Text":
L83: def __getitem__(self, index: slice) -> List["Text"]:
L86: def __getitem__(self, index: Union[slice, int]) -> Union["Text", List["Text"]]:
L89: def __setitem__(self, index: int, value: "Text") -> "Lines":
L93: def __len__(self) -> int:
L96: def __rich_console__(
L102: def append(self, line: "Text") -> None:
L105: def extend(self, lines: Iterable["Text"]) -> None:
L108: def pop(self, index: int = -1) -> "Text":
L111: def justify(

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_ratio.py

```

L6: class Edge(Protocol):
L14: def ratio_resolve(total: int, edges: Sequence[Edge]) -> List[int]:
L75: def ratio_reduce(
L107: def ratio_distribute(
L147: class E:

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/file_proxy.py

```

L11: class FileProxy(io.TextIOBase):
L14: def __init__(self, console: "Console", file: IO[str]) -> None:
L21: def rich_proxied_file(self) -> IO[str]:
L25: def __getattr__(self, name: str) -> Any:
L28: def write(self, text: str) -> int:
L50: def flush(self) -> None:
L56: def fileno(self) -> int:

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatEntity.kt

```

L9: data class ChatEntity(
L22: fun ChatEntity.isAdmin(userId: String): Boolean {

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/MessageEntity.kt

```

L20: data class MessageEntity(

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatDao.kt

```

L6: data class ChatSummary(
L19: interface ChatDao {

```

```

L21: suspend fun insertChat(chat: ChatEntity)
L24: suspend fun getChatById(chatId: String): ChatEntity?
L27: fun getChatByIdFlow(chatId: String): Flow<ChatEntity?>
L30: suspend fun getP2PChat(ids1: String, ids2: String): ChatEntity?
L33: fun getAllChats(): Flow<List<ChatEntity>>
L46: fun getChatSummaries(): Flow<List<ChatSummary>>
L49: suspend fun updateBlockedStatus(chatId: String, isBlocked: Boolean)
L52: suspend fun updateReportedStatus(chatId: String, isReported: Boolean)
L55: suspend fun updateMutedStatus(chatId: String, isMuted: Boolean)
L58: suspend fun updateParticipants(chatId: String, participantIds: String)
L61: suspend fun deleteChat(chat: ChatEntity)
L64: suspend fun deleteChatById(chatId: String)
L67: suspend fun incrementUnreadCount(chatId: String)
L70: suspend fun clearUnreadCount(chatId: String)
L73: fun getTotalUnreadCount(): Flow<Int?>
L76: suspend fun deleteAllChats()

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatDatabase.kt

```

L25: fun getDatabase(context: Context): ChatDatabase {

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatTypeConverters.kt

```

L8: object ChatTypeConverters {
L13: fun fromAdminIds(adminIds: List<String>?): String {
L19: fun toAdminIds(value: String?): List<String> {

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatRemoteRepository.kt

```

L14: class ChatRemoteRepository @Inject constructor(
L18: private suspend fun getCurrentUserId(): String? {
L26: suspend fun createChatOnRemote(chat: ChatEntity) {
L82: suspend fun addParticipantToRemote(chatId: String, userId: String) {
L104: suspend fun removeParticipantFromRemote(chatId: String, userId: String) {
L126: suspend fun promoteParticipantToAdminOnRemote(chatId: String, userId: String) {
L148: suspend fun demoteAdminOnRemote(chatId: String, userId: String) {
L170: suspend fun clearChatMessagesOnRemote(chatId: String) {
L204: suspend fun deleteChatOnRemote(chatId: String) {
L234: suspend fun reportGroup(group: ChatEntity, reason: String) {
L254: suspend fun reportMessage(message: MessageEntity, reason: String) {

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/MessageDao. kt

```

L7: interface MessageDao {
L9: suspend fun insertMessage(message: MessageEntity)
L12: fun getMessagesForChat(chatId: String): Flow<List<MessageEntity>>
L15: suspend fun getMessageById(messageId: String): MessageEntity?
L18: fun getAllMessages(): Flow<List<MessageEntity>>
L21: suspend fun deleteMessage(message: MessageEntity)
L24: suspend fun deleteMessagesByChatId(chatId: String)
L27: suspend fun deleteAllMessages()
L30: suspend fun getPendingMessages(): List<MessageEntity>
L33: suspend fun updateMessageStatus(messageId: String, status: String)

```

core-crypto/src/main/java/com/algorithmx/q_base/core_crypto/CryptoM anager.kt

```

L21: class CryptoManager @Inject constructor(
L37: fun initializeAndGetPublicKey(): String {
L57: fun encryptMessage(plaintext: String, receiverPublicKeyBase64: String): String {
L69: fun encryptSessionKey(sessionKey: ByteArray, receiverPublicKeyBase64: String): String {
L81: fun decryptMessage(ciphertextBase64: String): Result<String> {
L91: fun decryptSessionKey(wrappedKeyBase64: String): Result<ByteArray> {
L100: private fun decryptRaw(ciphertextBase64: String): ByteArray {
L122: fun clearKeys() {
L130: fun getPublicKeyFingerprint(): String {
L142: fun encryptFileContent(plaintext: ByteArray): Pair<ByteArray, String> {
L158: fun encryptWithSessionKey(plaintext: String): Pair<String, String> {
L174: fun decryptWithSessionKey(ciphertextBase64: String, keyHandleBase64: String):
Result<String> {
L190: fun decryptFileContent(ciphertext: ByteArray, keyBase64: String): ByteArray {
L206: fun exportEncryptedKeyset(passphrase: String): String {
L219: fun importEncryptedKeyset(encryptedBackupBase64: String, passphrase: String):
Result<Unit> {
L242: private fun deriveKey(passphrase: String, salt: ByteArray): ByteArray {
L248: private fun encryptBackup(data: ByteArray, passphrase: String): String {
L271: private fun decryptBackup(encryptedBase64: String, passphrase: String): ByteArray {
L290: private fun getLocalAead(): Aead {
L305: fun encryptLocalString(plaintext: String): String {
L312: fun decryptLocalString(ciphertextBase64: String): Result<String> {
L325: private fun getGlobalDecryptionKey(): javax.crypto.spec.SecretKeySpec {
L340: fun encryptGlobalKey(plainText: String): String {
L355: fun decryptGlobalKey(combinedBase64: String): Result<String> {

```

app/src/androidTest/java/com/algorithmx/q_base/ExampleInstrumented Test.kt

```
L17: class ExampleInstrumentedTest {
L19: fun useAppContext() {
```

app/src/test/java/com/algorithmx/q_base/ExampleUnitTest.kt

```
L12: class ExampleUnitTest {
L14: fun addition_isCorrect() {
```

app/src/test/java/com/algorithmx/q_base/ui/settings/ProfileViewModelTest.kt

```
L25: class ProfileViewModelTest {
L40: fun setup() {
L66: fun tearDown() {
```

app/src/main/java/com/algorithmx/q_base/QbaseApplication.kt

```
L9: class QbaseApplication : Application() {
```

app/src/main/java/com/algorithmx/q_base/MainActivity.kt

```
L47: class MainActivity : ComponentActivity() {
L60: private fun checkNotificationPermission() {
L275: fun LoadingScreenCircularArchive() {
L299: fun LoadingScreen() {
L339: fun MainScreen(
L453: fun AppNavDisplay(navigationState: NavigationState, navigator: Navigator) {
```

app/src/main/java/com/algorithmx/q_base/data/AppDatabase.kt

```
L50: fun getDatabase(context: Context): AppDatabase {
```

app/src/main/java/com/algorithmx/q_base/data/DatabaseSeeder.kt

```
L22: class DatabaseSeeder @Inject constructor(
L32: private fun getColumnString(cursor: android.database.Cursor, index: Int): String? {
L36: suspend fun seedDatabaseIfNeeded() = withContext(Dispatchers.IO) {
L229: private suspend fun seedSampleChats() {
L336: private suspend fun seedAncientSriLanka() {
```

app/src/main/java/com/algorithmx/q_base/data/di/NetworkModule.kt

```

L23: object NetworkModule {
L27: fun provideOkHttpClient(): OkHttpClient {
L38: fun provideFirestore(): FirebaseFirestore = Firebase.firestore
L42: fun provideAppwriteClient(@ApplicationContext context: Context): Client {
L99: fun shieldJsonObject(obj: org.json.JSONObject) {
L149: fun provideAppwriteStorage(client: Client): Storage {
L155: fun provideAppwriteDatabases(client: Client): Databases {
L161: fun provideAppwriteTables(client: Client): Any? {
L178: fun provideNetworkMonitor(@ApplicationContext context: Context): NetworkMonitor {

```

app/src/main/java/com/algorithmx/q_base/data/di/DatabaseModule.kt

```

L33: object DatabaseModule {
L37: fun provideDatabase(@ApplicationContext context: Context): AppDatabase {
L42: fun provideQuestionDao(database: AppDatabase): QuestionDao = database.questionDao()
L45: fun provideCollectionDao(database: AppDatabase): CollectionDao =
database.collectionDao()
L48: fun provideSessionDao(database: AppDatabase): SessionDao = database.sessionDao()
L51: fun provideProblemReportDao(database: AppDatabase): ProblemReportDao =
database.problemReportDao()
L54: fun provideUserDao(database: AppDatabase): UserDao = database.userDao()
L58: fun provideChatDatabase(@ApplicationContext context: Context): ChatDatabase {
L63: fun provideChatDao(database: ChatDatabase): ChatDao = database.chatDao()
L66: fun provideMessageDao(database: ChatDatabase): MessageDao = database.messageDao()
L69: fun provideAiResponseDao(database: AppDatabase): AiResponseDao =
database.aiResponseDao()
L72: fun provideBrainUsageDao(database: AppDatabase): BrainUsageDao =
database.brainUsageDao()
L75: fun provideCollectionVersionLedgerDao(database: AppDatabase): CollectionVersionLedgerDao
= database.collectionVersionLedgerDao()
L78: fun provideActionQueueDao(database: AppDatabase):
com.algorithmx.q_base.data.sync.ActionQueueDao = database.actionQueueDao()
L82: fun provideExploreRepository(
L94: fun provideSessionRepository(
L105: fun provideHomeRepository(
L117: fun provideImportRepository(@ApplicationContext context: Context): ImportRepository {
L123: fun provideDataClearingRepository(
L141: fun provideProfileCache(userDao: UserDao): ProfileCache {

```

app/src/main/java/com/algorithmx/q_base/data/di/BrainModule.kt

```

L14: object BrainModule {
L18: fun provideAiRepository(

```

app/src/main/java/com/algorithmx/q_base/data/util/TypeConverters.kt

```

L7: class TypeConverters {

```

```

L9: fun fromBrainTask(task: BrainTask): String {
L14: fun toBrainTask(name: String): BrainTask {
L23: fun fromBrainProvider(provider: BrainProvider): String {
L28: fun toBrainProvider(name: String): BrainProvider {

```

app/src/main/java/com/algorithmx/q_base/data/util/ExportUtils.kt

```

L22: class ExportUtils @Inject constructor(
L31: suspend fun prepareZip(setWithQuestions: SetWithQuestions): File =
withContext(Dispatchers.IO) {

```

app/src/main/java/com/algorithmx/q_base/data/util/MockExporter.kt

```

L24: class MockExporter @Inject constructor(
L32: suspend fun exportCollection(collectionId: String): File? = withContext(Dispatchers.IO)
{
L68: suspend fun exportSession(sessionId: String): File? = withContext(Dispatchers.IO) {
L93: fun cleanup(file: File) {

```

app/src/main/java/com/algorithmx/q_base/data/util/MockDownloader.kt

```

L22: class MockDownloader @Inject constructor(
L35: suspend fun downloadAndImportMock(
L89: suspend fun downloadAndImportSession(
L134: private suspend fun importCollectionData(
L185: private suspend fun importMockData(mockData: MockExport) {

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionDao.kt

```

L9: interface SessionDao {
L11: suspend fun insertSession(session: StudySession)
L14: suspend fun insertSet(set: QuestionSet)
L17: suspend fun updateSession(session: StudySession)
L20: fun getAllSessions(): Flow<List<StudySession>>
L23: fun getOngoingSessions(): Flow<List<StudySession>>
L26: suspend fun getSessionById(sessionId: String): StudySession?
L29: fun getAllSets(): Flow<List<QuestionSet>>
L32: fun getRecentSets(): Flow<List<QuestionSet>>
L35: fun getPinnedQuestions(): Flow<List<Question>>
L38: suspend fun insertAttempts(attempts: List<SessionAttempt>)
L41: fun getAttemptsForSession(sessionId: String): Flow<List<SessionAttempt>>
L44: suspend fun getAttemptsForSessionOnce(sessionId: String): List<SessionAttempt>
L47: suspend fun updateAttempt(attempt: SessionAttempt)
L50: suspend fun getAttempt(sessionId: String, questionId: String): SessionAttempt?
L53: fun getLastSessionForStudyCollection(collectionId: String): Flow<StudySession?>
L56: suspend fun deleteSessionsByIds(sessionIds: List<String>)

```

```

L59: suspend fun deleteAttemptsForSessions(sessionIds: List<String>)
L62: suspend fun deleteAllSessions()
L65: suspend fun deleteAllAttempts()
L68: suspend fun deleteAllSets()

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionExport.kt

```

L6: data class SessionExport(

```

app/src/main/java/com/algorithmx/q_base/data/sessions/StudySession.kt

```

L10: data class StudySession(

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionAttempt.kt

```

L33: data class SessionAttempt(

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionRepository.kt

```

L19: class SessionRepository @Inject constructor(
L25: fun getCurrentUser(userId: String): Flow<UserEntity?> =
L28: fun getAllSessions(): Flow<List<StudySession>> = sessionDao.getAllSessions()
L30: fun getAllStudyCollections(): Flow<List<StudyCollection>> =
collectionDao.getAllStudyCollections()
L32: suspend fun getStudyCollectionByIdOnce(collectionId: String): StudyCollection? =
L35: suspend fun getStudyCollectionByNameOnce(name: String): StudyCollection? =
L38: fun getAllSets(): Flow<List<QuestionSet>> = sessionDao.getAllSets()
L40: suspend fun getSessionById(sessionId: String): StudySession? =
sessionDao.getSessionById(sessionId)
L45: suspend fun createNewSession(
L87: suspend fun createNewSessionSmart(
L107: fun getQuestionsByStudyCollection(collection: String): Flow<List<Question>> =
L110: fun getAttemptsForSession(sessionId: String): Flow<List<SessionAttempt>> =
L113: suspend fun getQuestionById(questionId: String): Question? =
L116: fun getOptionsForQuestion(questionId: String): Flow<List<QuestionOption>> =
L119: suspend fun getAnswerForQuestion(questionId: String): Answer? =
L122: suspend fun updateAttemptAndRecalculate(attempt: SessionAttempt) {
L191: suspend fun updateAttempt(attempt: SessionAttempt) {
L195: suspend fun updateSession(session: StudySession) {

```



```
L199: suspend fun saveAnswer(answer: Answer) {
L203: suspend fun deleteSessions(sessionIds: List<String>) {
```

app/src/main/java/com/algorithmx/q_base/data/core/UserDao.kt

```
L7: interface UserDao {
L9: suspend fun insertUser(user: UserEntity)
L12: suspend fun getUserById(userId: String): UserEntity?
L15: fun getCurrentUser(userId: String): Flow<UserEntity?>
L18: fun getAllUsers(): Flow<List<UserEntity>>
L21: suspend fun deleteAllUsers()
```

app/src/main/java/com/algorithmx/q_base/data/core/HomeRepository.kt

```
L18: class HomeRepository @Inject constructor(
L25: fun getCurrentUser(userId: String): Flow<com.algorithmx.q_base.data.core.UserEntity?> =
L28: fun getOngoingSessions(): Flow<List<StudySession>> = sessionDao.getOngoingSessions()
L30: fun getPinnedQuestions(): Flow<List<Question>> = sessionDao.getPinnedQuestions()
L32: fun getRecentSessions(): Flow<List<StudySession>> = sessionDao.getAllSessions()
L34: fun getAllStudyCollections(): Flow<List<StudyCollection>> =
collectionDao.getAllStudyCollections()
L36: fun getAllStudyCollectionsWithCount(): Flow<List<StudyCollectionWithCount>> =
L39: fun getTotalUnreadCount(): Flow<Int> = chatDao.getTotalUnreadCount().map { it ?: 0 }
```

app/src/main/java/com/algorithmx/q_base/data/core/UserEntity.kt

```
L7: data class UserEntity{
```

app/src/main/java/com/algorithmx/q_base/data/core/ConfigRepository.kt

```
L19: class ConfigRepository @Inject constructor(
L47: suspend fun saveGeminiKey(key: String) {
L54: suspend fun saveGroqKey(key: String) {
L61: suspend fun fetchRemoteConfig() {
L100: suspend fun getGeminiKeyDirectly(): String = geminiApiKey.first()
L101: suspend fun getGroqKeyDirectly(): String = groqApiKey.first()
L103: suspend fun backupKeysToCloud(userId: String) {
L137: suspend fun restoreKeysFromCloud(userId: String) {
```

app/src/main/java/com/algorithmx/q_base/data/core/DataClearingRepository.kt

```
L17: class DataClearingRepository @Inject constructor(
L28: suspend fun clearAllData(clearCollections: Boolean) = withContext(Dispatchers.IO) {
```

app/src/main/java/com/algorithmx/q_base/data/ai/BrainUsageEntity.kt

```
L9: data class BrainUsageEntity(
```

app/src/main/java/com/algorithmx/q_base/data/ai/AiResponseDao.kt

```
L7: interface AiResponseDao {
L9: fun getAllResponses(): Flow<List<AiResponseEntity>>
L12: suspend fun getResponseById(responseId: String): AiResponseEntity?
L15: suspend fun insertResponse(response: AiResponseEntity)
L18: suspend fun updateResponse(response: AiResponseEntity)
L21: suspend fun deleteResponseById(responseId: String)
L24: suspend fun deleteAllAiResponses()
```

app/src/main/java/com/algorithmx/q_base/data/ai/AiModuleIntegrator.kt

```
L17: class BrainConfigProviderImpl @Inject constructor(
L32: class AiUsageLoggerImpl @Inject constructor(
```

app/src/main/java/com/algorithmx/q_base/data/ai/AiResponseEntity.kt

```
L6: data class AiResponseEntity(
```

app/src/main/java/com/algorithmx/q_base/data/ai/AiRepository.kt

```
L15: class AiRepository @Inject constructor(
L24: suspend fun generateCollection(
L98: suspend fun saveAsSet(
L118: suspend fun saveAsCollection(
L150: private suspend fun saveQuestionsToSet(questions:
List<com.algorithmx.q_base.core_ai.brain.models.AiQuestion>, setId: String, collectionName:
String) {
L191: suspend fun extractQuestionsFromText(
L265: suspend fun promoteAiResponseToDatabase(
L294: suspend fun assistQuestionEditing(stem: String, options: String = "", context: String =
""): Result<String> {
L308: suspend fun getAiAssistance(prompt: String): Result<String> {
L312: suspend fun getAiResponseById(responseId: String): AiResponseEntity? {
L316: private fun extractJsonFromResponse(response: String): String {
```

app/src/main/java/com/algorithmx/q_base/data/ai/BrainUsageDao.kt

```

L11: interface BrainUsageDao {
L13: suspend fun insertUsageRecord(record: BrainUsageEntity)
L16: fun getRecentUsage(limit: Int = 100): Flow<List<BrainUsageEntity>>
L19: fun getTotalSuccessfulTokens(): Flow<Int?>
L22: fun getTotalTokensForTask(taskId: BrainTask): Flow<Int?>
L25: suspend fun pruneOldRecords(olderThanMs: Long)
L28: suspend fun deleteAllBrainUsage()

```

app/src/main/java/com/algorithmx/q_base/data/sync/ChatManagerRepository.kt

```

L23: class ChatManagerRepository @Inject constructor(
L37: suspend fun addParticipantToRemote(chatId: String, userId: String) {
L41: suspend fun removeParticipantFromRemote(chatId: String, userId: String) {
L45: suspend fun promoteParticipantToAdminOnRemote(chatId: String, userId: String) {
L49: suspend fun demoteAdminOnRemote(chatId: String, userId: String) {
L53: suspend fun createChatOnRemote(chat: ChatEntity) {
L57: suspend fun getChatById(chatId: String): ChatEntity? {
L61: suspend fun syncUserChatsFromRemote() {
L126: suspend fun findExistingP2PChat(uid: String, userId: String): ChatEntity? {
L172: suspend fun ensureChatExistsLocally(chatId: String, senderId: String? = null) {
L198: suspend fun fetchAndSyncChatMetadata(chatId: String) {
L237: suspend fun deleteChatOnRemote(chatId: String) {
L241: fun deleteChatAndMessagesGlobally(chatId: String) {

```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncRepository.kt

```

L21: class MessageSyncRepository @Inject constructor(
L39: fun serializeWrappedKeys(map: Map<String, String>): String {
L45: fun deserializeWrappedKeys(jsonStr: String?): Map<String, String> {
L61: suspend fun acknowledgeMessageDelivery(

```

app/src/main/java/com/algorithmx/q_base/data/sync/OfflineActionEntity.kt

```

L8: data class OfflineActionEntity(

```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncIncomingGlobalExtensions.kt

```

L17: fun MessageSyncRepository.observeAllIncomingMessages(notificationHelper:
NotificationHelper): Flow<Unit> {

```

```
L205: suspend fun MessageSyncRepository.fetchAndSyncMessages(chatId: String) {
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncRequestExtensions.kt

```
L12: suspend fun CollectionSyncRepository.sendSyncRequest(targetUserId: String,
targetCollectionId: String) {
L34: fun CollectionSyncRepository.observeIncomingRequests(): Flow<List<SyncRequest>> =
callbackFlow {
L86: suspend fun CollectionSyncRepository.requestCollectionAccess(chatId: String,
collectionId: String) {
L107: fun CollectionSyncRepository.observeAccessRequests(chatId: String):
Flow<List<Map<String, Any>>> {
L155: suspend fun CollectionSyncRepository.grantCollectionAccess(chatId: String,
collectionId: String, requesterId: String) {
```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncOutgoingExtensions.kt

```
L11: suspend fun MessageSyncRepository.sendMessage(message: MessageEntity) {
L143: suspend fun MessageSyncRepository.flushQueue() {
L161: suspend fun MessageSyncRepository.clearChatMessagesOnRemote(chatId: String) {
```

app/src/main/java/com/algorithmx/q_base/data/sync/SyncRequest.kt

```
L6: data class SyncRequest(
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncPatchExtensions.kt

```
L15: suspend fun CollectionSyncRepository.applyCollectionMicroUpdate(payload: String) {
L128: suspend fun CollectionSyncRepository.broadcastCollectionMicroUpdate(chatId: String,
collectionId: String, diff: JSONObject) {
L168: suspend fun CollectionSyncRepository.sendCollectionPatch(chatId: String, collectionId:
String, op: String, data: JSONObject) {
L185: suspend fun CollectionSyncRepository.applyCollectionPatch(jsonString: String) {
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncRepository.kt

```
L23: class CollectionSyncRepository @Inject constructor(
```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncIncomingExtensions.kt

```
L14: fun MessageSyncRepository.observeAndSyncMessages(chatId: String): Flow<MessageEntity?> {
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncFileExtensions.kt

```
L19: suspend fun CollectionSyncRepository.uploadQuestionBankZip(zipFile: File): Pair<String, String> {
L39: suspend fun CollectionSyncRepository.deleteQuestionBankZip(fileId: String) {
L48: suspend fun CollectionSyncRepository.shareCollectionToGroup(chatId: String, collectionMetadata: Map<String, Any>) {
L165: suspend fun CollectionSyncRepository.acknowledgeCollectionDownload(collectionId: String) {
L203: fun CollectionSyncRepository.observeGroupLibrary(chatId: String): Flow<List<Map<String, Any>>> {
L235: private suspend fun CollectionSyncRepository.mapGroupLibrary(list: List<Map<String, Any>>): List<Map<String, Any>> {
```

app/src/main/java/com/algorithmx/q_base/data/sync/SyncRepository.kt

```
L18: class SyncRepository @Inject constructor(
L28: fun observeAndSyncMessages(chatId: String): Flow<MessageEntity?> {
L32: suspend fun sendMessage(message: MessageEntity) {
L36: suspend fun flushQueue() {
L40: suspend fun addParticipantToRemote(chatId: String, userId: String) {
L44: suspend fun removeParticipantFromRemote(chatId: String, userId: String) {
L48: suspend fun promoteParticipantToAdminOnRemote(chatId: String, userId: String) {
L52: suspend fun demoteAdminOnRemote(chatId: String, userId: String) {
L56: suspend fun createChatOnRemote(chat: ChatEntity) {
L60: fun observeAllIncomingMessages(notificationHelper: NotificationHelper): Flow<Unit> {
L64: suspend fun syncUserChatsFromRemote() {
L68: suspend fun findExistingP2PChat(uid: String, userId: String): ChatEntity? {
L72: suspend fun fetchAndSyncMessages(chatId: String) {
L76: suspend fun clearChatMessagesOnRemote(chatId: String) {
L80: suspend fun deleteChatOnRemote(chatId: String) {
L84: fun deleteChatAndMessagesGlobally(chatId: String) {
L88: suspend fun getChatById(chatId: String): ChatEntity? {
L93: suspend fun sendSessionInvite(
L103: suspend fun addSharedSessionToGroup(
L113: fun observeSharedSessions(chatId: String): Flow<List<Map<String, Any>>> {
L117: suspend fun sendSessionPatch(chatId: String, sessionId: String, op: String, data: JSONObject) {
L122: suspend fun sendSyncRequest(targetUserId: String, targetCollectionId: String) {
L126: fun observeIncomingRequests(): Flow<List<SyncRequest>> {
```

```

L130: suspend fun uploadQuestionBankZip(zipFile: File): Pair<String, String> {
L134: suspend fun deleteQuestionBankZip(fileId: String) {
L138: suspend fun shareCollectionToGroup(chatId: String, collectionMetadata: Map<String,
Any>) {
L142: suspend fun acknowledgeCollectionDownload(collectionId: String) {
L146: suspend fun applyCollectionMicroUpdate(payload: String) {
L150: suspend fun broadcastCollectionMicroUpdate(chatId: String, collectionId: String, diff:
JSONObject) {
L154: fun observeGroupLibrary(chatId: String): Flow<List<Map<String, Any>>> {
L158: suspend fun sendCollectionPatch(chatId: String, collectionId: String, op: String, data:
JSONObject) {
L162: suspend fun requestCollectionAccess(chatId: String, collectionId: String) {
L166: fun observeAccessRequests(chatId: String): Flow<List<Map<String, Any>>> {
L170: suspend fun grantCollectionAccess(chatId: String, collectionId: String, requesterId:
String) {
L175: suspend fun reportSession(sessionId: String, reason: String) {
L179: suspend fun reportQuestion(
L188: suspend fun reportGroup(group: ChatEntity, reason: String) {
L192: suspend fun reportUser(user: UserEntity, reason: String) {
L196: suspend fun reportCollection(collection: StudyCollection, reason: String) {
L200: suspend fun reportMessage(message: MessageEntity, reason: String) {

```

app/src/main/java/com/algorithmx/q_base/data/sync/UniversalQueueMa nager.kt

```

L16: class UniversalQueueManager @Inject constructor(
L22: suspend fun flushUniversalQueue() {
L56: private suspend fun processAction(action: OfflineActionEntity): Boolean {

```

app/src/main/java/com/algorithmx/q_base/data/sync/ActionQueueDao.k t

```

L6: interface ActionQueueDao {
L8: suspend fun insertAction(action: OfflineActionEntity)
L11: suspend fun getPendingActions(): List<OfflineActionEntity>
L14: suspend fun deleteAction(action: OfflineActionEntity)
L17: suspend fun updateAction(action: OfflineActionEntity)
L20: suspend fun clearAllActions()

```

app/src/main/java/com/algorithmx/q_base/data/sync/PatchEvent.kt

```

L6: data class PatchEvent(

```

app/src/main/java/com/algorithmx/q_base/data/sync/SessionSyncRepo

sitory.kt

```
L27: class SessionSyncRepository @Inject constructor(
L40: suspend fun sendSessionInvite(
L62: suspend fun addSharedSessionToGroup(
L115: fun observeSharedSessions(chatId: String): Flow<List<Map<String, Any>>> {
L157: suspend fun sendSessionPatch(chatId: String, sessionId: String, op: String, data:
JSONObject) {
L174: suspend fun applySessionPatch(jsonString: String) {
```

app/src/main/java/com/algorithmx/q_base/data/sync/ReportSyncRepository.kt

```
L20: class ReportSyncRepository @Inject constructor(
L29: suspend fun reportSession(sessionId: String, reason: String) {
L52: suspend fun reportQuestion(
L79: suspend fun reportGroup(group: ChatEntity, reason: String) {
L83: suspend fun reportUser(user: UserEntity, reason: String) {
L103: suspend fun reportCollection(collection: StudyCollection, reason: String) {
L123: suspend fun reportMessage(message: MessageEntity, reason: String) {
```

app/src/main/java/com/algorithmx/q_base/data/collections/ExploreRepository.kt

```
L15: class ExploreRepository @Inject constructor(
L22: fun getCurrentUser(userId: String): Flow<UserEntity?> = userDao.getCurrentUser(userId)
L24: fun getStudyCollections(): Flow<List<StudyCollection>> =
collectionDao.getAllStudyCollections()
L26: fun getStudyCollectionsWithCount(): Flow<List<StudyCollectionWithCount>> =
L29: fun getStudyCollectionById(collectionId: String): Flow<StudyCollection?> =
collectionDao.getStudyCollectionById(collectionId)
L31: fun getSetsByStudyCollectionId(collectionId: String): Flow<List<QuestionSet>> =
collectionDao.getSetsByStudyCollectionId(collectionId)
L33: fun getLastSessionForStudyCollection(collectionId: String): Flow<StudySession?> =
sessionDao.getLastSessionForStudyCollection(collectionId)
L35: fun getQuestionsByStudyCollection(collection: String): Flow<List<Question>> =
L38: fun getQuestionsBySet(setId: String): Flow<List<Question>> =
collectionDao.getQuestionsForSet(setId)
L40: suspend fun getQuestionById(questionId: String): Question? =
L43: suspend fun getSessionById(sessionId: String): StudySession? =
sessionDao.getSessionById(sessionId)
L45: suspend fun updateSession(session: StudySession) = sessionDao.updateSession(session)
L47: fun getOptionsForQuestion(questionId: String): Flow<List<QuestionOption>> =
L50: fun getAnswerForQuestion(questionId: String): Flow<Answer?> =
L53: suspend fun updateQuestion(question: Question) {
L57: suspend fun reportProblem(report: ProblemReport) {
```

```

L61: fun getAllSets(): Flow<List<QuestionSet>> = sessionDao.getAllSets()
L63: fun getAllSessions(): Flow<List<StudySession>> = sessionDao.getAllSessions()
L65: fun getPinnedQuestions(): Flow<List<Question>> = questionDao.getPinnedQuestions()
L67: fun getQuestionCountByStudyCollection(collectionName: String): Flow<Int> =
L70: suspend fun addQuestionToSet(setId: String, questionId: String) {
L76: suspend fun addQuestionToSession(sessionId: String, questionId: String) {
L88: suspend fun saveSet(set: QuestionSet) {
L92: suspend fun saveAnswer(answer: Answer) {
L96: suspend fun updateStudyCollection(collection: StudyCollection) {
L100: suspend fun getStudyCollectionByIdOnce(collectionId: String): StudyCollection? {
L104: suspend fun getStudyCollectionByNameOnce(name: String): StudyCollection? {
L108: suspend fun getSetIdForQuestion(questionId: String): String? {
L112: suspend fun deleteStudyCollection(collectionId: String) {

```

app/src/main/java/com/algorithmx/q_base/data/collections/ProblemReport.kt

```

L21: data class ProblemReport(

```

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionVersionLedger.kt

```

L11: data class CollectionVersionLedgerEntity(
L18: interface CollectionVersionLedgerDao {
L20: suspend fun getLedgerForCollection(collectionId: String): CollectionVersionLedgerEntity?
L23: suspend fun insertLedger(ledger: CollectionVersionLedgerEntity)
L26: suspend fun deleteLedger(collectionId: String)

```

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionSet.kt

```

L23: data class QuestionSet(

```

app/src/main/java/com/algorithmx/q_base/data/collections/ImportRepository.kt

```

L20: class ImportRepository @Inject constructor(
L30: suspend fun recognizeTextFromImage(uri: Uri): Result<String> =
withContext(Dispatchers.IO) {
L41: suspend fun extractTextFromPdf(uri: Uri): Result<String> = withContext(Dispatchers.IO) {
L71: fun cleanRecognizedText(rawText: String): String {

```


app/src/main/java/com/algorithmx/q_base/data/collections/QuestionWithContent.kt

```
L6: data class QuestionWithContent(
```

app/src/main/java/com/algorithmx/q_base/data/collections/Answer.kt

```
L10: data class Answer(
```

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionWithSets.kt

```
L6: data class StudyCollectionWithSets(
```

app/src/main/java/com/algorithmx/q_base/data/collections/ProblemReportDao.kt

```
L7: interface ProblemReportDao {
L9: suspend fun insertReport(report: ProblemReport)
L12: fun getAllReports(): Flow<List<ProblemReport>>
L15: fun getReportsForQuestion(questionId: String): Flow<List<ProblemReport>>
```

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionDao.kt

```
L7: interface CollectionDao {
L9: fun getAllStudyCollections(): Flow<List<StudyCollection>>
L16: fun getAllStudyCollectionsWithCount(): Flow<List<StudyCollectionWithCount>>
L19: suspend fun getStudyCollectionCount(): Int
L22: fun getStudyCollectionById(collectionId: String): Flow<StudyCollection?>
L25: suspend fun getStudyCollectionByIdOnce(collectionId: String): StudyCollection?
L28: suspend fun getStudyCollectionByNameOnce(name: String): StudyCollection?
L31: fun getSetsByStudyCollectionId(collectionId: String): Flow<List<QuestionSet>>
L34: fun getSetsByStudyCollectionName(collectionName: String): Flow<List<QuestionSet>>
L41: fun getCategoriesByStudyCollectionId(collectionId: String): Flow<List<String>>
L48: fun getQuestionsForSet(setId: String): Flow<List<Question>>
L51: suspend fun getSetsByStudyCollectionIdOnce(collectionId: String): List<QuestionSet>
L58: suspend fun getQuestionsForSetOnce(setId: String): List<Question>
L61: suspend fun getCrossRefsForSetsBatch(setIds: List<String>): List<SetQuestionCrossRef>
L64: suspend fun insertStudyCollections(collections: List<StudyCollection>)
L67: suspend fun updateStudyCollection(collection: StudyCollection)
L70: suspend fun insertSets(sets: List<QuestionSet>)
L73: suspend fun insertCrossRefs(refs: List<SetQuestionCrossRef>)
```

```

L76: suspend fun updateStudyCollectionTimestamp(collectionId: String, timestamp: Long)
L79: suspend fun deleteStudyCollectionById(collectionId: String)
L82: suspend fun deleteAllStudyCollections()

```

app/src/main/java/com/algorithmx/q_base/data/collections/Question.kt

```

L18: data class Question(

```

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionExport.kt

```

L5: data class CollectionExport(

```

app/src/main/java/com/algorithmx/q_base/data/collections/SetWithQuestions.kt

```

L7: data class SetWithQuestions(

```

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionDao.kt

```

L7: interface QuestionDao {
L9: fun getQuestionsByStudyCollection(collection: String): Flow<List<Question>>
L12: fun getQuestionsByCategory(category: String): Flow<List<Question>>
L15: fun getQuestionsByTag(tag: String): Flow<List<Question>>
L18: fun getQuestionsByCategoryAndTag(category: String, tag: String): Flow<List<Question>>
L21: fun getOptionsForQuestion(questionId: String): Flow<List<QuestionOption>>
L24: fun getAnswerForQuestion(questionId: String): Flow<Answer?>
L27: suspend fun getOptionsForQuestionOnce(questionId: String): List<QuestionOption>
L30: suspend fun getAnswerForQuestionOnce(questionId: String): Answer?
L33: suspend fun getQuestionById(questionId: String): Question?
L36: suspend fun updateQuestion(question: Question)
L39: suspend fun insertQuestions(questions: List<Question>)
L42: suspend fun insertOptions(options: List<QuestionOption>)
L45: suspend fun insertAnswers(answers: List<Answer>)
L48: suspend fun insertSet(set: QuestionSet)
L51: suspend fun insertQuestion(question: Question)
L54: suspend fun insertOption(option: QuestionOption)
L57: suspend fun insertAnswer(answer: Answer)
L60: suspend fun insertSetQuestionCrossRef(crossRef: SetQuestionCrossRef)
L63: fun getQuestionCountFlow(): Flow<Int>
L71: fun getUserCreatedQuestionCount(): Flow<Int>
L79: fun getSharedQuestionCount(): Flow<Int>
L82: suspend fun getQuestionCount(): Int

```

```

L85: fun getPinnedQuestions(): Flow<List<Question>>
L89: suspend fun getSetWithContent(setId: String): SetWithQuestions?
L92: fun getQuestionCountByStudyCollection(collectionName: String): Flow<Int>
L95: suspend fun getSetIdForQuestion(questionId: String): String?
L98: suspend fun deleteOptionsForQuestion(questionId: String)
L101: suspend fun deleteSetById(setId: String)
L104: suspend fun deleteSetsByIds(setIds: List<String>)
L107: suspend fun deleteCrossRefsForSets(setIds: List<String>)
L110: suspend fun removeQuestionFromSet(setId: String, questionId: String)
L113: suspend fun deleteQuestionById(questionId: String)
L116: suspend fun deleteAllQuestions()
L119: suspend fun deleteAllOptions()
L122: suspend fun deleteAllAnswers()
L125: suspend fun deleteAllCrossRefs()

```

app/src/main/java/com/algorithmx/q_base/data/collections/MockExport.kt

```

L5: data class QuestionExport(
L12: data class MockExport(

```

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionOption.kt

```

L23: data class QuestionOption(

```

app/src/main/java/com/algorithmx/q_base/data/collections/StudyCollection.kt

```

L10: data class StudyCollection(
L37: data class StudyCollectionWithCount(

```

app/src/main/java/com/algorithmx/q_base/data/collections/SetQuestionCrossRef.kt

```

L32: data class SetQuestionCrossRef(

```

app/src/main/java/com/algorithmx/q_base/util/NotificationHelper.kt

```

L21: class NotificationHelper @Inject constructor(
L30: fun createNotificationChannels() {
L55: fun showMessageNotification(chatId: String, senderName: String, message: String) {

```

```
L87: fun showSessionNotification(sessionId: String, title: String, description: String) {
```

app/src/main/java/com/algorithmx/q_base/util/NetworkMonitor.kt

```
L21: class NetworkMonitor @Inject constructor(  
L32: fun currentConnectivity(): Boolean {
```

app/src/main/java/com/algorithmx/q_base/ui/navigation/Screen.kt

```
L7: sealed class Screen : NavKey {
```

app/src/main/java/com/algorithmx/q_base/ui/navigation/Navigator.kt

```
L8: class Navigator(val state: NavigationState) {  
L9: private fun normalizeRoute(route: NavKey): NavKey = when (route) {  
L14: private fun findTopLevelMatch(route: NavKey): NavKey? =  
L19: private fun resetStack(root: NavKey, stack:  
androidx.navigation3.runtime.NavBackStack<NavKey>) {  
L24: fun navigate(route: NavKey) {  
L56: fun resetTo(route: NavKey) {  
L78: fun goBack() {
```

app/src/main/java/com/algorithmx/q_base/ui/navigation/NavigationState.kt

```
L27: fun rememberNavigationState(  
L83: class NavigationState(  
L98: fun NavigationState.toEntries()
```

app/src/main/java/com/algorithmx/q_base/ui/navigation/AppEntryProvider.kt

```
L16: fun rememberAppEntryProvider(navigator: Navigator) = remember(navigator) {
```

app/src/main/java/com/algorithmx/q_base/ui/navigation/AppEntryWrappers.kt

```
L20: fun ExplorePagerWrapper(key: Screen.ExplorePager, navigator: Navigator) {  
L81: fun CollectionOverviewWrapper(key: Screen.CollectionOverview, navigator: Navigator) {  
L123: fun PinnedQuestionsWrapper(navigator: Navigator) {  
L147: fun ExploreSetWrapper(key: Screen.ExploreSet, navigator: Navigator) {  
L193: fun SessionsWrapper(navigator: Navigator) {
```

```

L220: fun NewSessionWizardWrapper(navigator: Navigator) {
L238: fun ActiveSessionWrapper(key: Screen.ActiveSession, navigator: Navigator) {
L253: fun SessionResultsWrapper(key: Screen.SessionResults, navigator: Navigator) {
L267: fun ChatDetailWrapper(key: Screen.ChatDetail, navigator: Navigator) {
L294: fun ContactOverviewWrapper(key: Screen.ContactOverview, navigator: Navigator) {
L308: fun GroupOverviewWrapper(key: Screen.GroupOverview, navigator: Navigator) {
L322: fun ProfileWrapper(navigator: Navigator) {

```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModel.kt

```

L20: data class ExploreQuestionState(
L32: class ExploreViewModel @Inject constructor(
L112: fun resetQuestionStates() {
L141: fun loadQuestionsByStudyCollection(collectionId: String) {
L156: fun loadQuestionsBySet(setId: String) {
L166: private suspend fun checkIsEditable(collection: StudyCollection?): Boolean {
L175: fun loadPinnedQuestions() {
L191: fun updateCollectionAdminOnly(collectionId: String, isAdminOnly: Boolean) {
L213: fun loadCollectionOverview(collectionId: String) {
L246: fun updateSessionProgress(sessionId: String, index: Int) {
L254: fun loadQuestionDetails(index: Int) {
L272: fun selectOption(index: Int, optionLetter: String) {
L309: fun revealAnswer(index: Int) {
L317: fun togglePin(index: Int) {

```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModelSetExtensions.kt

```

L11: fun ExploreViewModel.toggleSetSelection(setId: String) {
L22: fun ExploreViewModel.clearSelection() {
L27: fun ExploreViewModel.deleteCollectionSet(setId: String) {
L34: suspend fun ExploreViewModel.getSetIdForQuestion(questionId: String): String? {
L38: fun ExploreViewModel.deleteSelectedSets() {
L50: fun ExploreViewModel.addQuestionToSet(index: Int, setId: String) {
L72: fun ExploreViewModel.addQuestionToSession(index: Int, sessionId: String) {
L94: fun ExploreViewModel.createSet(title: String, description: String, collectionId: String) {
L110: fun ExploreViewModel.deleteQuestion(index: Int) {
L137: fun ExploreViewModel.deleteQuestionFromSet(index: Int, setId: String) {

```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModelAiExtensions.kt

```

L9: fun ExploreViewModel.askAi(index: Int, mode: String = "EXPLAIN") {

```

```
L37: fun ExploreViewModel.askAiAboutCollection(collection: StudyCollection) {
L56: fun ExploreViewModel.clearCollectionAiResponse() {
L60: fun ExploreViewModel.clearAiResponse(index: Int) {
L66: fun ExploreViewModel.saveAiResponseToQuestion(index: Int) {
```

app/src/main/java/com/algorithmx/q_base/ui/explore/PinnedQuestionsScreen.kt

```
L29: fun PinnedQuestionsScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreScreens.kt

```
L45: fun ExploreQuestionPagerScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/explore/UnifiedExploreScreen.kt

```
L37: fun UnifiedExploreScreen(
L172: fun MasterCollectionListItem(
L256: fun EmptyLibraryView(modifier: Modifier = Modifier) {
```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModelReportExtensions.kt

```
L10: fun ExploreViewModel.reportCollectionToGroup(collection: StudyCollection, reason:
String) {
L32: fun ExploreViewModel.reportProblem(index: Int, explanation: String) {
L62: fun ExploreViewModel.reportCollection(collection: StudyCollection, reason: String) {
L79: fun ExploreViewModel.deleteStudyCollection(collectionId: String) {
L92: fun ExploreViewModel.reportSet(setId: String, reason: String) {
```

app/src/main/java/com/algorithmx/q_base/ui/explore/CollectionOverviewScreen.kt

```
L39: fun CollectionOverviewScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/explore/CollectionOverviewComponents.kt

```
L21: fun StatCard(
```

```
L44: fun SetItem(
```

app/src/main/java/com/algorithmx/q_base/ui/state/AppAccessState.kt

```
L3: sealed interface AppAccessState {
L4: data object RestoringSession : AppAccessState
L5: data object OnlineReady : AppAccessState
L6: data object SignedInOffline : AppAccessState
L7: data object GuestOnline : AppAccessState
L8: data object OfflineGuest : AppAccessState
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/NewSessionWizardScreen.kt

```
L26: fun NewSessionWizardScreen(
L140: fun EmptyCollectionsView() {
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionsScreens.kt

```
L51: fun SessionsListScreen(
L176: fun AnimatedSessionItem(index: Int, content: @Composable () -> Unit) {
L192: fun CategoryChip(name: String) {
L220: fun SessionListItemExpressive(
L319: fun EmptySessionsView() {
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionWizardSteps.kt

```
L27: fun CategoryStep(
L75: fun QuestionSelectionStep(
L182: fun ConfigurationStep(
L284: fun ConfigToggle(
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/ActiveSessionViewModel.kt

```
L25: sealed class SessionNavEvent {
L26: data class NavigateToResults(val sessionId: String) : SessionNavEvent()
L29: data class NavigatorDot(
L36: class ActiveSessionViewModel @Inject constructor(
L116: fun setSessionId(id: String, chatId: String? = null) {
```

```

L128: fun getSessionId(): String = _sessionId
L130: private fun loadSessionData() {
L156: private fun startTimer() {
L184: private fun loadAttempts() {
L195: fun navigateToQuestion(index: Int) {
L205: private fun loadQuestion(questionId: String) {
L216: fun onAnswerSelected(optionLetter: String) {
L257: fun toggleFlag() {
L264: private fun updateAttempt(attempt: SessionAttempt) {
L290: fun askAi(mode: String = "EXPLAIN") {
L309: fun clearAiResponse() {
L313: fun saveAiResponseToQuestion() {
L331: fun submitSession() {
L366: fun reportSession(reason: String) {
L380: fun reportQuestion(reason: String) {

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/ActiveSessionScreen.kt

```

L56: fun ActiveSessionScreen(

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionsViewModel.kt

```

L20: class SessionsViewModel @Inject constructor(
L96: fun onSearchQueryChange(query: String) {
L100: fun setWizardStep(step: Int) {
L104: fun selectCollection(name: String) {
L114: fun toggleQuestionSelection(id: String) {
L121: fun selectAllQuestions() {
L125: fun deselectAllQuestions() {
L129: fun selectRandomQuestions(count: Int) {
L140: fun setOrder(order: String) { _sessionOrder.value = order }
L141: fun setTimingType(type: String) { _timingType.value = type }
L142: fun setTimeLimit(seconds: Int) { _timeLimitSeconds.value = seconds }
L143: fun setSessionIsAdminOnly(value: Boolean) { _sessionIsAdminOnly.value = value }
L145: fun launchSession(title: String) {
L163: fun resetWizard() {
L174: fun toggleSessionSelection(sessionId: String) {
L185: fun clearSessionSelection() {
L190: fun deleteSelectedSessions() {
L200: fun reportSession(sessionId: String, reason: String) {

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionResultsViewModel.kt


```

L20: data class ReviewState(
L27: sealed class ResultsUiState {
L28: object Loading : ResultsUiState()
L29: data class Success(val session: StudySession?, val attempts: List<SessionAttempt>, val
score: Float) : ResultsUiState()
L33: class SessionResultsViewModel @Inject constructor(
L66: fun initSession(id: String) {
L72: private fun loadResults() {
L104: fun updateSessionAdminOnly(sessionId: String, isAdminOnly: Boolean) {
L128: fun selectQuestionForReview(attempt: SessionAttempt) {
L143: fun clearReview() {
L147: fun reportCurrentSession(reason: String) {

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionResultsScreen.kt

```

L39: fun SessionResultsScreen(
L162: fun ResultsContent(
L334: fun AnimatedAttemptDot(

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/components/MasterNavigator.kt

```

L21: fun MasterNavigator(

```

app/src/main/java/com/algorithmx/q_base/ui/settings/AiBrainManagerScreen.kt

```

L22: fun AiBrainManagerScreen(

```

app/src/main/java/com/algorithmx/q_base/ui/settings/SecureBackupViewModel.kt

```

L14: data class SecureBackupState(
L22: class SecureBackupViewModel @Inject constructor(
L34: fun checkBackupStatus() {
L43: fun setupBackup(passphrase: String) {
L64: fun restoreBackup(passphrase: String) {
L80: fun clearState() {

```

app/src/main/java/com/algorithmx/q_base/ui/settings/SettingsScreen.kt

```
L34: fun SettingsScreen(
L58: fun SettingsContent(
```

app/src/main/java/com/algorithmx/q_base/ui/settings/ProfileViewModel. kt

```
L23: data class UserStats(
L31: class ProfileViewModel @Inject constructor(
L82: private fun loadUser() {
L96: private fun loadBackupStatus() {
L110: private fun loadStats() {
L130: private suspend fun tryUpdateProfile(updatedProfile: UserProfile) {
L142: fun updateDisplayName(newName: String) {
L160: fun updateIntro(newIntro: String) {
L178: fun updateProfilePictureUrl(url: String) {
L196: fun togglePhotoVisibility(isVisible: Boolean) {
L214: fun signOut(clearCollections: Boolean, onComplete: () -> Unit) {
```

app/src/main/java/com/algorithmx/q_base/ui/settings/ProfileComponent ts.kt

```
L40: data class AvatarTemplate(
L59: fun Modifier.bounceClick(onClick: () -> Unit = {}) = composed {
L91: fun ProfileParallaxHeader(
```

app/src/main/java/com/algorithmx/q_base/ui/settings/SettingsViewMod el.kt

```
L25: class SettingsViewModel @Inject constructor(
L44: fun updateModel(newModel: String) {
L56: fun updateSystemInstruction(instruction: String) {
L67: fun saveTaskConfig(task: BrainTask, config: TaskConfig) {
L73: fun updateNotifications(enabled: Boolean) {
L79: fun updateTheme(mode: String) {
L85: fun clearAllData(onComplete: () -> Unit) {
L94: private fun calculateDbSize(): Double {
```

app/src/main/java/com/algorithmx/q_base/ui/settings/AppThemeScreen .kt

```
L26: fun AppThemeScreen(
L85: data class ThemeOption(val id: String, val title: String, val subtitle: String)
L88: fun ThemeCard(
```

app/src/main/java/com/algorithmx/q_base/ui/settings/SecureBackupDialog.kt

```
L16: fun SecureBackupDialog(
```

app/src/main/java/com/algorithmx/q_base/ui/settings/ProfileScreen.kt

```
L35: fun ProfileScreen(
L74: fun ProfileContent(
L290: fun ProfileContentPreview() {
```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/ProfileAvatar.kt

```
L29: fun ProfileAvatar(
```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/ProfileRowComponents.kt

```
L19: fun ProfileCardSection(
L54: fun ProfilePropertyRow(
L113: fun ProfilePropertyToggleRow(
```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/SettingsComponents.kt

```
L18: fun SettingsSection(
L31: fun SettingsSectionHeader(title: String) {
L44: fun SettingsToggleCard(
L81: fun SettingsCard(
L117: fun UsageStatsCard(requests: Int, tokens: Int) {
```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/ProfileStatsComponents.kt

```
L28: fun ProfileAchievementsProperty(stats: UserStats) {
L63: fun BadgeBadge(
L134: fun StatCard(
```

app/src/main/java/com/algorithmx/q_base/ui/theme/Theme.kt

```
L98: fun QbaseTheme(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ContactOverviewScreen.kt

```
L34: fun ContactOverviewScreen(
L196: fun ActionButton(
L221: fun SettingsItem(
L260: fun ReportDialog(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatDetailScreen.kt

```
L27: fun ChatDetailScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/GroupOverviewScreen.kt

```
L35: fun GroupOverviewScreen(
L334: fun ParticipantItem(user: UserEntity, isAdmin: Boolean, onClick: () -> Unit = {}) {
```

app/src/main/java/com/algorithmx/q_base/ui/chat/NewChatScreen.kt

```
L10: fun NewChatScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModelSharingExtensions.kt

```
L10: fun ChatViewModel.addSharedCollection(jsonPayload: String) {
L27: fun ChatViewModel.importSharedCollection(payload: String) {
L80: fun ChatViewModel.shareCollection(chatId: String, collectionId: String) {
L132: fun ChatViewModel.resendCollection(collectionId: String) {
L176: fun ChatViewModel.shareSession(chatId: String, sessionId: String) {
L217: fun ChatViewModel.joinSession(sessionIdOrPayload: String, onSessionImported: (String)
-> Unit) {
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatListScreen.kt

```
L44: fun ChatListScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/BlockedListScreen.kt

```
L26: fun BlockedListScreen(
L71: fun BlockedChatItem(
L129: fun EmptyBlockedView(modifier: Modifier = Modifier) {
```

app/src/main/java/com/algorithmx/q_base/ui/chat/AddParticipantDialog.kt

```
L23: fun AddParticipantDialog(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/NewGroupScreen.kt

```
L29: fun NewGroupScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatModels.kt

```
L10: data class ChatUiModel(
L20: data class ChatListState(
L29: data class ChatDetailState(
L40: sealed class ChatNavEvent {
L41: data class NavigateToChatDetail(val chatId: String) : ChatNavEvent()
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModel.kt

```
L34: class ChatViewModel @Inject constructor(
L72: fun canSendToChat(chatId: String): Flow<Boolean> {
L95: fun requestAccess(collectionId: String) {
L107: fun grantAccess(collectionId: String, requesterId: String) {
L137: fun toggleLibraryMode(enabled: Boolean) {
L176: fun toggleChatSelection(chatId: String) {
L188: fun clearSelection() {
L193: fun deleteSelectedChats() {
L348: fun syncChatsFromRemote() {
L361: fun setChatId(chatId: String) {
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ContactSelector.kt

```
L38: fun ContactSelector(
L301: fun UserItem(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModelAdminExtensions.kt

```

L9: fun ChatViewModel.addParticipant(chatId: String, userId: String) {
L48: fun ChatViewModel.removeParticipant(chatId: String, userId: String) {
L86: fun ChatViewModel.promoteParticipantToAdmin(chatId: String, userId: String) {
L109: fun ChatViewModel.demoteAdmin(chatId: String, userId: String) {
L136: fun ChatViewModel.leaveGroup(chatId: String) {
L156: fun ChatViewModel.reportGroup(chatId: String, reason: String) {
L170: fun ChatViewModel.reportUser(userId: String, reason: String) {
L183: fun ChatViewModel.reportMessage(message: MessageEntity, reason: String) {
L194: fun ChatViewModel.toggleMute(chatId: String, isMuted: Boolean) {
L203: fun ChatViewModel.toggleBlock(chatId: String, isBlocked: Boolean) {
L212: fun ChatViewModel.deleteChat(chatId: String) {
L216: fun ChatViewModel.clearChatMessages(chatId: String) {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModelMessageExtensions.kt

```

L9: fun ChatViewModel.startNewChat(userId: String, userName: String) {
L54: fun ChatViewModel.startNewGroup(participantIds: List<String>, groupName: String) {
L77: fun ChatViewModel.startAiChat() {
L81: fun ChatViewModel.sendMessage(chatId: String, text: String, type: String = "TEXT",
senderId: String = currentUserId) {
L130: private fun ChatViewModel.handleAiChatResponse(chatId: String, userMessage: String) {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/ContactSelectorViewModel.kt

```

L13: data class ContactSelectorState(
L21: class ContactSelectorViewModel @Inject constructor(
L33: private fun loadLocalContacts() {
L41: fun searchByFriendCode(code: String, excludedUserId: String? = null) {
L93: fun clearSearchResult() {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatItem.kt

```

L24: fun AnimatedChatItem(
L49: fun ChatItem(

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/MessageBubble.kt

```

L43: fun AnimatedMessageItem(
L82: fun MessageBubble(

```

```

L177: private fun AIHeader(isAiLoading: Boolean) {
L210: private fun SenderAvatar(avatarUrl: String?, onClick: () -> Unit) {
L240: private fun SenderNameLabel(name: String, onClick: () -> Unit) {
L253: private fun MessageContent(
L324: fun MessageBubblePreview() {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/EmptyConnectView.kt

```

L15: fun EmptyConnectView(modifier: Modifier = Modifier) {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatDetailDialogs.kt

```

L23: fun SessionPickerSheet(
L85: fun CollectionPickerSheet(
L152: fun ChatDetailConfirmDialogs(

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/SharedLibraryView.kt

```

L27: fun SharedLibraryView(
L94: fun CollectionsTabContent(
L151: fun SessionsTabContent(
L183: fun LibraryEmptyState(message: String) {
L199: fun LibraryHeader(title: String, description: String) {
L207: fun SharedSessionCard(title: String, timestamp: Long, onJoin: () -> Unit) {
L231: fun PendingRequestsSection(accessRequests: List<Map<String, Any>>, onGrantAccess:
(String, String) -> Unit) {
L245: fun SharedCollectionCard(
L375: fun AccessRequestItem(
L412: fun SharedLibraryViewPreview() {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatDetailHelpers.kt

```

L9: fun accessStateLabel(state: AppAccessState): String = when (state) {
L17: fun formatDateRelatively(timestamp: Long): String {
L28: private fun isSameDay(cal1: Calendar, cal2: Calendar): Boolean {
L33: private fun isYesterday(now: Calendar, date: Calendar): Boolean {

```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/GuestCo

nnectView.kt

```
L17: fun GuestConnectView(modifier: Modifier = Modifier) {
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatDetailComponents.kt

```
L30: fun DateHeader(date: String) {
L53: fun SystemMessageItem(text: String) {
L76: fun ChatDetailTopBar(
L213: fun ChatDetailBottomBar(
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/SpecialBubbleContents.kt

```
L23: fun CollectionBubbleContent(
L64: fun SessionBubbleContent(payload: String, onJoin: (String) -> Unit, isMine: Boolean) {
L94: fun FileTransferBubbleContent(
L144: fun DecryptionErrorContent(status: String, isMine: Boolean, onDeleteChat: () -> Unit) {
L183: fun MessageTimestampAndStatus(timeString: String, isMine: Boolean, status: String) {
```

app/src/main/java/com/algorithmx/q_base/ui/auth/AuthViewModel.kt

```
L15: data class AuthState(
L24: class AuthViewModel @Inject constructor(
L32: fun signIn(email: String, pass: String) {
L54: fun signUp(email: String, pass: String, username: String, photoUrl: String? = null) {
L76: fun signInWithGoogle(activity: androidx.activity.ComponentActivity) {
L93: fun onGoogleSignInSuccess(user: AppwriteUser) {
L105: fun clearError() {
```

app/src/main/java/com/algorithmx/q_base/ui/auth/SignupScreen.kt

```
L38: fun SignupScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/auth/LoginScreen.kt

```
L35: fun LoginScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/ai/AiGenerationScreen.kt


```
L20: fun AiGenerationScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/ai/AiViewModel.kt

```
L16: sealed class AiUiState {
L17: object Idle : AiUiState()
L18: object Loading : AiUiState()
L19: data class Success(val message: String) : AiUiState()
L20: data class Error(val message: String) : AiUiState()
L24: class AiViewModel @Inject constructor(
L37: fun generateCollection(
L72: fun promoteResponse(targetCollectionId: String? = null, targetCollectionName: String? =
null) {
L86: fun resetState() {
```

app/src/main/java/com/algorithmx/q_base/ui/home/HomeScreen.kt

```
L40: fun HomeScreen(
L195: fun QuickActionCard(
L230: fun HomeCategoryCard(
L303: fun AnimatedHomeItem(
L324: fun PinnedQuestionItem(
L371: fun EmptyHomeView(onNavigate: () -> Unit) {
```

app/src/main/java/com/algorithmx/q_base/ui/home/HomeViewModel.kt

```
L20: class HomeViewModel @Inject constructor(
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Extraction WizardSecondScreen.kt

```
L24: fun ExtractionWizardSecondScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/QuestionEditorScreen.kt

```
L24: fun QuestionEditorScreen(
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Common WizardThirdScreen.kt

```
L26: fun WaitingView(message: String) {
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ManualBuilderViewModel.kt

```
L18: class ManualBuilderViewModel @Inject constructor(
L31: fun initialize(targetId: String?, name: String? = null) {
L61: private suspend fun createNewCollectionAndSet(name: String? = null) {
L77: private suspend fun createNewSet(collectionId: String, title: String) {
L90: private fun observeQuestions(setId: String) {
L96: fun getTargetSetId(): String? = _targetSetId.value
L98: private fun getCurrentDate(): String {
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/CommonWizardSecondScreen.kt

```
L17: fun ImportConfigView(onProceed: (List<String>, String) -> Unit) {
L82: fun GenerateConfigView(onProceed: (ExtractionConfigData) -> Unit) {
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ImportViewModel.kt

```
L23: data class ExtractionConfigData(
L43: sealed class ImportStep {
L44: data object NameAndDestination : ImportStep()
L45: data object ChooseMethod : ImportStep()
L46: data object MediaInput : ImportStep()
L47: data class Configure(val mode: String) : ImportStep() // "IMPORT" or "GENERATE"
L48: data class Processing(val message: String = "AI is structuring your questions...") :
ImportStep()
L49: data class Review(val questionCount: Int, val responseId: String) : ImportStep()
L50: data class Error(val message: String) : ImportStep()
L53: data object ExtractionIngest : ImportStep()
L54: data class ExtractionOverview(val responseId: String, val response:
com.algorithmx.q_base.core_ai.brain.models.AiCollectionResponse) : ImportStep()
L57: data class Extracting(val source: String) : ImportStep()
L58: data class Editing(val extractedText: String) : ImportStep()
L59: data class Config(val extractedText: String, val targetId: String? = null) :
ImportStep()
L60: data class Preview(val responseId: String, val response:
com.algorithmx.q_base.core_ai.brain.models.AiCollectionResponse) : ImportStep()
L61: data class Complete(val message: String) : ImportStep()
L65: class ImportViewModel @Inject constructor(
L116: fun togglePaperType(type: String) {
L142: fun setInitialSource(source: String?, targetId: String? = null) {
L153: private fun loadCollections() {
L161: fun navigateTo(step: ImportStep) {
L171: fun selectCategory(categoryId: String?) {
```

```

L175: fun updateNewCollectionName(name: String) {
L179: fun updateNewCollectionDescription(desc: String) {
L183: fun updateCustomInstructions(instructions: String) {
L187: fun selectMethod(method: String) {
L191: fun onImagePicked(uri: Uri) {
L199: fun onPdfPicked(uri: Uri) {
L207: fun onRawTextUpdated(text: String) {
L211: private fun handleExtractionResult(result: Result<String>) {
L220: fun startDirectImport(types: List<String>, instructions: String) {
L238: fun startAiGeneration(config: ExtractionConfigData) {
L256: private fun handleGenerationResult(result: Result<String>) {
L274: fun promoteResponse(responseId: String, customName: String? = null, onFinish:
(String, String?) -> Unit) {
L295: fun addPdf(uri: Uri) {
L321: fun addOcr(uri: Uri) {
L346: fun addClipboard(text: String) {
L359: fun removeDoc(id: String) {
L364: fun startPaperExtraction() {
L401: fun handleRetry() {
L409: fun reset() {
L435: fun currentStepNumber(): Int = when (val s = _uiState.value) {
L453: fun totalSteps(): Int = 5

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Extraction WizardThirdScreen.kt

```

L21: fun ExtractionWizardThirdScreen(

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ManualBuilderScreen.kt

```

L29: fun ManualBuilderScreen(
L131: fun ManualQuestionItem(

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ImportWizardScreen.kt

```

L20: fun ImportWizardScreen(

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Extraction WizardFirstScreen.kt

```

L22: data class ExtractedDocumentCard(

```

```
L31: fun ExtractionWizardFirstScreen(
L243: fun ExtractedDocItem(
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/QuestionEditorViewModel.kt

```
L15: data class QuestionEditorState(
L29: class QuestionEditorViewModel @Inject constructor(
L41: fun init(questionId: String?, setId: String) {
L70: fun updateStem(stem: String) {
L74: fun updateOption(letter: String, text: String) {
L81: fun updateCorrectAnswer(answer: String) {
L85: fun updateExplanation(explanation: String) {
L89: fun updateReferences(refs: String) {
L93: fun getAiAssist() {
L107: fun generateAiExplanation() {
L129: fun applyAiExplanation() {
L137: fun discardAiExplanation() {
L141: fun clearAiSuggestions() {
L145: fun saveQuestion() {
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/CommonWizardFourthScreen.kt

```
L26: fun ReviewView(
L227: fun ErrorView(message: String, onRetry: () -> Unit) {
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ExtractionWizardFourthScreen.kt

```
L27: fun ExtractionWizardFourthScreen(
L281: fun CountBadge(label: String, count: Int, color: Color, modifier: Modifier = Modifier)
{
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/CommonWizardFirstScreen.kt

```
L26: fun CommonWizardFirstScreen(
L214: fun SmallSourceButton(icon: ImageVector, title: String, color: Color, modifier:
Modifier = Modifier, onClick: () -> Unit) {
```

app/src/main/java/com/algorithmx/q_base/ui/components/question/Que

stionHeader.kt

```
L35: fun QuestionHeader(
L246: fun QuestionHeaderPreview() {
```

app/src/main/java/com/algorithmx/q_base/ui/components/question/QuestionViewer.kt

```
L20: fun QuestionViewer(
L151: fun QuestionViewerPreview() {
```

app/src/main/java/com/algorithmx/q_base/ui/components/question/TrueFalseToggle.kt

```
L15: fun TrueFalseToggle(
```

app/src/main/java/com/algorithmx/q_base/ui/components/question/OptionsList.kt

```
L29: fun OptionsList(
L341: fun OptionsListPreview() {
```

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/ReportDialog.kt

```
L13: fun ReportDialog(
```

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/ProfileIconButton.kt

```
L24: fun ProfileIconButton(
```

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/AiConfigSelector.kt

```
L16: fun AiConfigSelector(
```

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/Co

mmonComponents.kt

```
L32: fun UnifiedTopAppBar(
L125: private fun AppAccessStateBadge(appAccessState: AppAccessState) {
L150: fun SessionCard(
L196: fun SessionListItem(
L230: fun SectionHeader(
L272: fun SessionCardPreview() {
L289: fun SessionListItemPreview() {
L308: fun SectionHeaderPreview() {
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/BrainConfigProvider.kt

```
L5: interface BrainConfigProvider {
L6: suspend fun getApiKey(provider: BrainProvider): String
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/BrainDataStoreManager.kt

```
L24: class BrainDataStoreManager @Inject constructor(
L29: private object PreferencesKeys {
L73: suspend fun markSeedAsApplied() {
L79: suspend fun resetSeedFlag() {
L85: suspend fun saveEngineConfiguration(
L99: suspend fun incrementUsageStats(tokens: Int) {
L108: suspend fun saveThemeMode(mode: String) {
L114: suspend fun saveNotificationsEnabled(enabled: Boolean) {
L120: suspend fun saveTaskConfig(task: BrainTask, config: TaskConfig) {
L135: suspend fun setMasterAiFreeze(freeze: Boolean) {
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/AiUsageLogger.kt

```
L6: interface AiUsageLogger {
L7: suspend fun logUsage(
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/CommonAiService.kt

```
L13: class CommonAiService @Inject constructor(
L22: suspend fun generateNoteStructure(
L58: suspend fun generateBlocksForTopic(
```

```
L73: private fun constructGenerationPrompt(
L104: private fun extractJsonFromResponse(response: String): String {
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/AiBrainManager.kt

```
L24: class AiBrainManager @Inject constructor(
L40: private suspend fun buildBrain(modelName: String): AiBrain? {
L67: suspend fun askBrain(task: BrainTask, prompt: String): Result<String> {
L131: suspend fun streamFromBrain(task: BrainTask, prompt: String): Flow<String> {
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/BrainTask.kt

```
L3: enum class BrainTask(val displayName: String) {
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/AiResponseModels.kt

```
L6: data class AiQuestion(
L15: data class AiOption(
L22: data class AiAnswer(
L29: data class AiCollectionResponse(
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/AiModels.kt

```
L6: enum class BlockType {
L16: data class AiGeneratedBlock(
L22: data class AiGeneratedTab(
L27: data class NoteContext(
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/BrainModels.kt

```
L10: data class BrainConfig(
L17: data class TaskConfig(
L24: data class StoredBrainConfig(
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/di/AiCoreModule.kt

e.kt

```
L16: object AiCoreModule {  
L20: fun provideAiBrainManager(  
L30: fun provideCommonAiService(aiBrainManager: AiBrainManager): CommonAiService {
```