

FULL PROJECT DECLARATIONS

This file lists declaration lines (classes, interfaces, enums, objects, and functions) found across the project.

Q_base appwrite/app_write.py

```
L316: def wait_for_attributes(db_id, collection_id):    Function `wait_for_attributes`
utility or script function.
L336: def setup_database():    Function `setup_database`  Sets or updates a value.
```

Q_base appwrite/encrypt_and_sync_keys.py

```
L21: def get_global_decryption_key():    Function `get_global_decryption_key`  Returns or
fetches data.
L29: def encrypt_global_key(plain_text: str) -> str:    Function `encrypt_global_key`
Encrypts data.
L42: def main():    Function `main`  Entry point / main routine.
```

Q_base appwrite/verify_appwrite_readiness.py

```
L22: def check_readiness():    Function `check_readiness`  utility or script function.
```

Q_base appwrite/create_global_keys_doc.py

```
L24: def init_global_keys_doc():    Function `init_global_keys_doc`  Initialisation routine.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/typing_extensions.py

```
L167: class _Sentinel:    Class (`_Sentinel`)  component used by the app (see file context:
None).
L168: def __repr__(self):    Function `__repr__`  utility or script function.
L177: def _should_collect_from_parameters(t):    Function `_should_collect_from_parameters`
utility or script function.
L182: def _should_collect_from_parameters(t):    Function `_should_collect_from_parameters`
utility or script function.
L202: class _AnyMeta(type):    Class (`_AnyMeta`)  component used by the app (see file
context: None).
L203: def __instancecheck__(self, obj):    Function `__instancecheck__`  utility or script
```

```

function.
L208: def __repr__(self):  Function `__repr__`  utility or script function.
L213: class Any(metaclass=_AnyMeta):  Class (`Any`)  component used by the app (see file
context: None).
L222: def __new__(cls, *args, **kwargs):  Function `__new__`  utility or script function.
L233: class _SpecialForm(typing._Final, _root=True):  Class (`_SpecialForm`)  component used
by the app (see file context: None).
L236: def __init__(self, getitem):  Function `__init__`  utility or script function.
L241: def __getattr__(self, item):  Function `__getattr__`  utility or script function.
L247: def __mro_entries__(self, bases):  Function `__mro_entries__`  utility or script
function.
L250: def __repr__(self):  Function `__repr__`  utility or script function.
L253: def __reduce__(self):  Function `__reduce__`  utility or script function.
L256: def __call__(self, *args, **kws):  Function `__call__`  utility or script function.
L259: def __or__(self, other):  Function `__or__`  utility or script function.
L262: def __ror__(self, other):  Function `__ror__`  utility or script function.
L265: def __instancecheck__(self, obj):  Function `__instancecheck__`  utility or script
function.
L268: def __subclasscheck__(self, cls):  Function `__subclasscheck__`  utility or script
function.
L272: def __getitem__(self, parameters):  Function `__getitem__`  utility or script
function.
L279: class _ExtensionsSpecialForm(typing._SpecialForm, _root=True):  Class
(`_ExtensionsSpecialForm`)  component used by the app (see file context: None).
L280: def __repr__(self):  Function `__repr__`  utility or script function.
L293: def final(f):  Function `final`  utility or script function.
L298: class Base:  Class (`Base`)  component used by the app (see file context: None).
L300: def done(self) -> None:  Function `done`  utility or script function.
L302: class Sub(Base):  Class (`Sub`)  component used by the app (see file context: None).
L303: def done(self) -> None:  # Error reported by type checker  Function `done`  utility or
script function.
L306: class Leaf:  Class (`Leaf`)  component used by the app (see file context: None).
L308: class Other(Leaf):  # Error reported by type checker  Class (`Other`)  component used
by the app (see file context: None).
L328: def disjoint_base(cls):  Function `disjoint_base`  utility or script function.
L337: class Disjoint1: pass  Class (`Disjoint1`)  component used by the app (see file
context: None).
L340: class Disjoint2: pass  Class (`Disjoint2`)  component used by the app (see file
context: None).
L342: class Disjoint3(Disjoint1, Disjoint2): pass  # Type checker error  Class (`Disjoint3`)
component used by the app (see file context: None).
L352: def IntVar(name):  Function `IntVar`  utility or script function.
L361: def _flatten_literal_params(parameters):  Function `_flatten_literal_params`  utility
or script function.
L371: def _value_and_type_iter(params):  Function `_value_and_type_iter`  utility or script
function.
L375: class _LiteralGenericAlias(typing._GenericAlias, _root=True):  Class
(`_LiteralGenericAlias`)  component used by the app (see file context: None).
L376: def __eq__(self, other):  Function `__eq__`  utility or script function.
L383: def __hash__(self):  Function `__hash__`  utility or script function.
L386: class _LiteralForm(_ExtensionsSpecialForm, _root=True):  Class (`_LiteralForm`)

```

```

component used by the app (see file context: None).
L387: def __init__(self, doc: str):    Function `__init__`    utility or script function.
L391: def __getitem__(self, parameters):    Function `__getitem__`    utility or script
function.
L444: def overload(func):    Function `overload`    utility or script function.
L451: def utf8(value: None) -> None: ...    Function `utf8`    utility or script function.
L453: def utf8(value: bytes) -> bytes: ...    Function `utf8`    utility or script function.
L455: def utf8(value: str) -> bytes: ...    Function `utf8`    utility or script function.
L462: def utf8(value: None) -> None: ...    Function `utf8`    utility or script function.
L464: def utf8(value: bytes) -> bytes: ...    Function `utf8`    utility or script function.
L466: def utf8(value: str) -> bytes: ...    Function `utf8`    utility or script function.
L467: def utf8(value):    Function `utf8`    utility or script function.
L484: def get_overloads(func):    Function `get_overloads`    Returns or fetches data.
L495: def clear_overloads():    Function `clear_overloads`    utility or script function.
L522: def _is_dunder(attr):    Function `_is_dunder`    utility or script function.
L526: class _SpecialGenericAlias(typing._SpecialGenericAlias, _root=True):    Class
(`_SpecialGenericAlias`)    component used by the app (see file context: None).
L527: def __init__(self, origin, nparams, *, inst=True, name=None, defaults=()):    Function
`__init__`    utility or script function.
L531: def __setattr__(self, attr, val):    Function `__setattr__`    utility or script function.
L539: def __getitem__(self, params):    Function `__getitem__`    utility or script function.
L603: def _get_protocol_attrs(cls):    Function `_get_protocol_attrs`    utility or script
function.
L615: def _caller(depth=1, default='__main__'):    Function `_caller`    utility or script
function.
L633: def _allow_reckless_class_checks(depth=2):    Function `_allow_reckless_class_checks`
utility or script function.
L640: def _no_init(self, *args, **kwargs):    Function `_no_init`    utility or script function.
L644: def _type_check_issubclass_arg_1(arg):    Function `_type_check_issubclass_arg_1`
utility or script function.
L663: class _ProtocolMeta(type(typing.Protocol)):    Class (`_ProtocolMeta`)    component used
by the app (see file context: None).
L670: def __new__(mcls, name, bases, namespace, **kwargs):    Function `__new__`    utility or
script function.
L686: def __init__(cls, *args, **kwargs):    Function `__init__`    utility or script function.
L691: def __subclasscheck__(cls, other):    Function `__subclasscheck__`    utility or script
function.
L717: def __instancecheck__(cls, instance):    Function `__instancecheck__`    utility or script
function.
L749: def __eq__(cls, other):    Function `__eq__`    utility or script function.
L760: def __hash__(cls) -> int:    Function `__hash__`    utility or script function.
L764: def _proto_hook(cls, other):    Function `_proto_hook`    utility or script function.
L788: class Protocol(typing.Generic, metaclass=_ProtocolMeta):    Class (`Protocol`)
component used by the app (see file context: None).
L794: def __init_subclass__(cls, *args, **kwargs):    Function `__init_subclass__`    utility or
script function.
L814: def runtime_checkable(cls):    Function `runtime_checkable`    utility or script function.
L825: class Closable(Protocol):    Class (`Closable`)    component used by the app (see file
context: None).
L826: def close(self): ...    Function `close`    utility or script function.
L882: class SupportsInt(Protocol):    Class (`SupportsInt`)    component used by the app (see

```

```

file context: None).
L887: def __int__(self) -> int:    Function `__int__`    utility or script function.
L891: class SupportsFloat(Protocol):    Class (`SupportsFloat`)    component used by the app
(see file context: None).
L896: def __float__(self) -> float:    Function `__float__`    utility or script function.
L900: class SupportsComplex(Protocol):    Class (`SupportsComplex`)    component used by the app
(see file context: None).
L905: def __complex__(self) -> complex:    Function `__complex__`    utility or script function.
L909: class SupportsBytes(Protocol):    Class (`SupportsBytes`)    component used by the app
(see file context: None).
L914: def __bytes__(self) -> bytes:    Function `__bytes__`    utility or script function.
L918: class SupportsIndex(Protocol):    Class (`SupportsIndex`)    component used by the app
(see file context: None).
L922: def __index__(self) -> int:    Function `__index__`    utility or script function.
L926: class SupportsAbs(Protocol[T_co]):    Class (`SupportsAbs`)    component used by the app
(see file context: None).
L933: def __abs__(self) -> T_co:    Function `__abs__`    utility or script function.
L937: class SupportsRound(Protocol[T_co]):    Class (`SupportsRound`)    component used by the app
(see file context: None).
L944: def __round__(self, ndigits: int = 0) -> T_co:    Function `__round__`    utility or
script function.
L953: class Reader(Protocol[T_co]):    Class (`Reader`)    component used by the app (see file
context: None).
L962: def read(self, size: int = ..., /) -> T_co:    Function `read`    utility or script
function.
L970: class Writer(Protocol[T_contra]):    Class (`Writer`)    component used by the app (see
file context: None).
L979: def write(self, data: T_contra, /) -> int:    Function `write`    utility or script
function.
L988: class SingletonMeta(type):    Class (`SingletonMeta`)    component used by the app (see
file context: None).
L989: def __setattr__(cls, attr, value):    Function `__setattr__`    utility or script
function.
L999: class NoDefaultType(metaclass=SingletonMeta):    Class (`NoDefaultType`)    component used
by the app (see file context: None).
L1004: def __new__(cls):    Function `__new__`    utility or script function.
L1007: def __repr__(self):    Function `__repr__`    utility or script function.
L1010: def __reduce__(self):    Function `__reduce__`    utility or script function.
L1019: class NoExtraItemsType(metaclass=SingletonMeta):    Class (`NoExtraItemsType`)
component used by the app (see file context: None).
L1024: def __new__(cls):    Function `__new__`    utility or script function.
L1027: def __repr__(self):    Function `__repr__`    utility or script function.
L1030: def __reduce__(self):    Function `__reduce__`    utility or script function.
L1062: def _get_typeddict_qualifiers(annotation_type):    Function `_get_typeddict_qualifiers`
utility or script function.
L1083: class _TypedDictMeta(type):    Class (`_TypedDictMeta`)    component used by the app (see
file context: None).
L1085: def __new__(cls, name, bases, ns, *, total=True, closed=None,    Function `__new__`
utility or script function.
L1203: def __annotate__(format):    Function `__annotate__`    utility or script function.
L1245: def __subclasscheck__(cls, other):    Function `__subclasscheck__`    utility or script

```

```

function.
L1253: def _create_typeddict( Function `_create_typeddict` utility or script function.
L1315: class _TypedDictSpecialForm(_SpecialForm, _root=True): Class
(`_TypedDictSpecialForm`) component used by the app (see file context: None).
L1316: def __call__( Function `__call__` utility or script function.
L1337: def __mro_entries__(self, bases): Function `__mro_entries__` utility or script
function.
L1341: def TypedDict(self, args): Function `TypedDict` utility or script function.
L1351: class Point2D(TypedDict): Class (`Point2D`) component used by the app (see file
context: None).
L1370: class Point2D(TypedDict, total=False): Class (`Point2D`) component used by the app
(see file context: None).
L1377: class body be required. Class (`body`) component used by the app (see file context:
None).
L1382: class Point2D(TypedDict): Class (`Point2D`) component used by the app (see file
context: None).
L1405: def is_typeddict(tp): Function `is_typeddict` utility or script function.
L1409: class Film(TypedDict): Class (`Film`) component used by the app (see file context:
None).
L1423: def assert_type(val, typ, /): Function `assert_type` utility or script function.
L1429: def greet(name: str) -> None: Function `greet` utility or script function.
L1443: def _strip_extras(t): Function `_strip_extras` utility or script function.
L1467: def get_type_hints(obj, globalns=None, localns=None, include_extras=False): Function
`get_type_hints` Returns or fetches data.
L1511: def _could_be_inserted_optional(t): Function `_could_be_inserted_optional` utility
or script function.
L1521: def _clean_optional(obj, hints, globalns=None, localns=None): Function
`_clean_optional` utility or script function.
L1581: def get_origin(tp): Function `get_origin` Returns or fetches data.
L1605: def get_args(tp): Function `get_args` Returns or fetches data.
L1632: def TypeAlias(self, parameters): Function `TypeAlias` utility or script function.
L1646: def _set_default(type_param, default): Function `_set_default` utility or script
function.
L1651: def _set_module(typevarlike): Function `_set_module` utility or script function.
L1658: class _DefaultMixin: Class (`_DefaultMixin`) component used by the app (see file
context: None).
L1666: class _TypeVarLikeMeta(type): Class (`_TypeVarLikeMeta`) component used by the app
(see file context: None).
L1667: def __instancecheck__(cls, __instance: Any) -> bool: Function `__instancecheck__`
utility or script function.
L1675: class TypeVar(metaclass=_TypeVarLikeMeta): Class (`TypeVar`) component used by the
app (see file context: None).
L1680: def __new__(cls, name, *constraints, bound=None, Function `__new__` utility or
script function.
L1698: def _tvar_prepare_subst(alias, args): Function `_tvar_prepare_subst` utility or
script function.
L1709: def __init_subclass__(cls) -> None: Function `__init_subclass__` utility or script
function.
L1719: class _Immutable: Class (`_Immutable`) component used by the app (see file context:
None).
L1723: def __copy__(self): Function `__copy__` utility or script function.

```

```

L1726: def __deepcopy__(self, memo):    Function `__deepcopy__` utility or script function.
L1729: class ParamSpecArgs(_Immutable):  Class (`ParamSpecArgs`) component used by the app
(see file context: None).
L1741: def __init__(self, origin):    Function `__init__` utility or script function.
L1744: def __repr__(self):    Function `__repr__` utility or script function.
L1747: def __eq__(self, other):    Function `__eq__` utility or script function.
L1752: class ParamSpecKwargs(_Immutable):  Class (`ParamSpecKwargs`) component used by the
app (see file context: None).
L1764: def __init__(self, origin):    Function `__init__` utility or script function.
L1767: def __repr__(self):    Function `__repr__` utility or script function.
L1770: def __eq__(self, other):    Function `__eq__` utility or script function.
L1783: class ParamSpec(metaclass=_TypeVarLikeMeta):  Class (`ParamSpec`) component used by
the app (see file context: None).
L1788: def __new__(cls, name, *, bound=None,    Function `__new__` utility or script
function.
L1806: def _paramspec_prepare_subst(alias, args):    Function `_paramspec_prepare_subst`
utility or script function.
L1825: def __init_subclass__(cls) -> None:    Function `__init_subclass__` utility or script
function.
L1832: class ParamSpec(list, _DefaultMixin):  Class (`ParamSpec`) component used by the app
(see file context: None).
L1851: def add_logging(f: Callable[P, T]) -> Callable[P, T]:    Function `add_logging`
utility or script function.
L1853: def inner(*args: P.args, **kwargs: P.kwargs) -> T:    Function `inner` utility or
script function.
L1859: def add_two(x: float, y: float) -> float:    Function `add_two` utility or script
function.
L1883: def args(self):    Function `args` utility or script function.
L1887: def kwargs(self):    Function `kwargs` utility or script function.
L1890: def __init__(self, name, *, bound=None, covariant=False, contravariant=False,
Function `__init__` utility or script function.
L1908: def __repr__(self):    Function `__repr__` utility or script function.
L1919: def __hash__(self):    Function `__hash__` utility or script function.
L1922: def __eq__(self, other):    Function `__eq__` utility or script function.
L1925: def __reduce__(self):    Function `__reduce__` utility or script function.
L1929: def __call__(self, *args, **kwargs):    Function `__call__` utility or script
function.
L1939: def _type_convert(arg, module=None, *, allow_special_forms=False):    Function
`_type_convert` utility or script function.
L1953: class _ConcatenateGenericAlias(list):  Class (`_ConcatenateGenericAlias`) component
used by the app (see file context: None).
L1958: def __init__(self, origin, args):    Function `__init__` utility or script function.
L1963: def __repr__(self):    Function `__repr__` utility or script function.
L1968: def __hash__(self):    Function `__hash__` utility or script function.
L1972: def __call__(self, *args, **kwargs):    Function `__call__` utility or script
function.
L1976: def __parameters__(self):    Function `__parameters__` utility or script function.
L1982: def copy_with(self, params):    Function `copy_with` utility or script function.
L1993: def __getitem__(self, args):    Function `__getitem__` utility or script function.
L2076: class _ConcatenateGenericAlias(typing._ConcatenateGenericAlias, _root=True):  Class
(`_ConcatenateGenericAlias`) component used by the app (see file context: None).

```

```

L2080: def copy_with(self, params):    Function `copy_with` utility or script function.
L2090: def __getitem__(self, args):    Function `__getitem__` utility or script function.
L2098: class _EllipsisDummy: ...      Class (`_EllipsisDummy`) component used by the app (see
file context: None).
L2102: def _create_concatenate_alias(origin, parameters):    Function
`_create_concatenate_alias` utility or script function.
L2127: def _concatenate_getitem(self, parameters):    Function `_concatenate_getitem` utility
or script function.
L2148: def Concatenate(self, parameters):    Function `Concatenate` utility or script
function.
L2168: def TypeGuard(self, parameters):    Function `TypeGuard` utility or script function.
L2192: def is_str(val: Union[str, float]):    Function `is_str` utility or script function.
L2221: def TypeIs(self, parameters):    Function `TypeIs` utility or script function.
L2246: def is_awaitable(val: object) -> TypeIs[Awaitable[Any]]:    Object (singleton).
L2249: def f(val: Union[int, Awaitable[int]]) -> int:    Function `f` utility or script
function.
L2267: class _TypeFormForm(_ExtensionsSpecialForm, _root=True):    Class (`_TypeFormForm`)
component used by the app (see file context: None).
L2270: def __call__(self, obj, /):    Function `__call__` utility or script function.
L2274: def TypeForm(self, parameters):    Function `TypeForm` utility or script function.
L2286: def cast[T](typ: TypeForm[T], value: Any) -> T: ...    Function `cast` utility or
script function.
L2302: def LiteralString(self, params):    Function `LiteralString` utility or script
function.
L2309: def query(sql: LiteralString) -> ...:    Function `query` utility or script function.
L2325: def Self(self, params):    Function `Self` utility or script function.
L2332: class ReturnsSelf:    Class (`ReturnsSelf`) component used by the app (see file
context: None).
L2333: def parse(self, data: bytes) -> Self:    Function `parse` utility or script function.
L2346: def Never(self, params):    Function `Never` utility or script function.
L2354: def never_call_me(arg: Never) -> None:    Function `never_call_me` utility or script
function.
L2357: def int_or_str(arg: int | str) -> None:    Function `int_or_str` utility or script
function.
L2377: def Required(self, parameters):    Function `Required` utility or script function.
L2381: class Movie(TypedDict, total=False):    Class (`Movie`) component used by the app (see
file context: None).
L2397: def NotRequired(self, parameters):    Function `NotRequired` utility or script
function.
L2401: class Movie(TypedDict):    Class (`Movie`) component used by the app (see file
context: None).
L2418: def ReadOnly(self, parameters):    Function `ReadOnly` utility or script function.
L2423: class Movie(TypedDict):    Class (`Movie`) component used by the app (see file
context: None).
L2427: def mutate_movie(m: Movie) -> None:    Function `mutate_movie` utility or script
function.
L2452: class Bar(Generic[Unpack[Ts]]): ...    Class (`Bar`) component used by the app (see
file context: None).
L2459: class Bar(Generic[*Ts]): ...    Class (`Bar`) component used by the app (see file
context: None).
L2464: class Movie(TypedDict):    Class (`Movie`) component used by the app (see file

```



```

context: None).
L2470: def foo(**kwargs: Unpack[Movie]): ...    Function `foo` utility or script function.
L2484: def _is_unpack(obj):    Function `_is_unpack` utility or script function.
L2488: class _UnpackSpecialForm(_ExtensionsSpecialForm, _root=True):    Class
(`_UnpackSpecialForm`) component used by the app (see file context: None).
L2489: def __init__(self, getitem):    Function `__init__` utility or script function.
L2493: class _UnpackAlias(typing._GenericAlias, _root=True):    Class (`_UnpackAlias`)
component used by the app (see file context: None).
L2499: def __typing_unpacked_tuple_args__(self):    Function `__typing_unpacked_tuple_args__`
utility or script function.
L2510: def __typing_is_unpacked_typevartuple__(self):    Function
`__typing_is_unpacked_typevartuple__` utility or script function.
L2515: def __getitem__(self, args):    Function `__getitem__` utility or script function.
L2521: def Unpack(self, parameters):    Function `Unpack` utility or script function.
L2525: def _is_unpack(obj):    Function `_is_unpack` utility or script function.
L2529: def _unpack_args(*args):    Function `_unpack_args` utility or script function.
L2546: class TypeVarTuple(metaclass=_TypeVarLikeMeta):    Class (`TypeVarTuple`) component
used by the app (see file context: None).
L2551: def __new__(cls, name, *, default=NoDefault):    Function `__new__` utility or script
function.
L2556: def _typevartuple_prepare_subst(alias, args):    Function `_typevartuple_prepare_subst`
utility or script function.
L2604: def __init_subclass__(self, *args, **kws):    Function `__init_subclass__` utility or
script function.
L2608: class TypeVarTuple(_DefaultMixin):    Class (`TypeVarTuple`) component used by the app
(see file context: None).
L2622: class Array(Generic[*Ts]): ...    Class (`Array`) component used by the app (see file
context: None).
L2636: class Array(Generic[*Ts]):    Class (`Array`) component used by the app (see file
context: None).
L2638: def __init__(self, shape: Tuple[*Ts]):    Function `__init__` utility or script
function.
L2641: def get_shape(self) -> Tuple[*Ts]:    Function `get_shape` Returns or fetches data.
L2655: def __iter__(self):    Function `__iter__` utility or script function.
L2658: def __init__(self, name, *, default=NoDefault):    Function `__init__` utility or
script function.
L2669: def __repr__(self):    Function `__repr__` utility or script function.
L2672: def __hash__(self):    Function `__hash__` utility or script function.
L2675: def __eq__(self, other):    Function `__eq__` utility or script function.
L2678: def __reduce__(self):    Function `__reduce__` utility or script function.
L2681: def __init_subclass__(self, *args, **kws):    Function `__init_subclass__` utility or
script function.
L2689: def reveal_type(obj: T, /) -> T:    Function `reveal_type` utility or script function.
L2718: def assert_never(arg: Never, /) -> Never:    Function `assert_never` utility or script
function.
L2723: def int_or_str(arg: int | str) -> None:    Function `int_or_str` utility or script
function.
L2749: def dataclass_transform(    Function `dataclass_transform` utility or script function.
L2772: def create_model(cls: type[_T]) -> type[_T]:    Function `create_model` Creates a
resource or document.
L2777: class CustomerModel:    Class (`CustomerModel`) component used by the app (see file

```



```

context: None).
L2783: class ModelBase: ... Class (`ModelBase`) component used by the app (see file
context: None).
L2785: class CustomerModel(ModelBase): Class (`CustomerModel`) component used by the app
(see file context: None).
L2791: class ModelMeta(type): ... Class (`ModelMeta`) component used by the app (see file
context: None).
L2793: class ModelBase(metaclass=ModelMeta): ... Class (`ModelBase`) component used by the
app (see file context: None).
L2795: class CustomerModel(ModelBase): Class (`CustomerModel`) component used by the app
(see file context: None).
L2822: def decorator(cls_or_fn): Function `decorator` utility or script function.
L2840: def override(arg: _F, /) -> _F: Function `override` utility or script function.
L2845: class Base: Class (`Base`) component used by the app (see file context: None).
L2846: def method(self) -> None: Function `method` utility or script function.
L2849: class Child(Base): Class (`Child`) component used by the app (see file context:
None).
L2851: def method(self) -> None: Function `method` utility or script function.
L2883: class deprecated: Class (`deprecated`) component used by the app (see file context:
None).
L2892: class A: Class (`A`) component used by the app (see file context: None).
L2896: def f(): Function `f` utility or script function.
L2901: def g(x: int) -> int: ... Function `g` utility or script function.
L2903: def g(x: str) -> int: ... Function `g` utility or script function.
L2925: def __init__( Function `__init__` utility or script function.
L2942: def __call__(self, arg: _T, /) -> _T: Function `__call__` utility or script
function.
L2958: def __new__(cls, /, *args, **kwargs): Function `__new__` utility or script
function.
L2978: def __init_subclass__(*args, **kwargs): Function `__init_subclass__` utility or
script function.
L2987: def __init_subclass__(*args, **kwargs): Function `__init_subclass__` utility or
script function.
L3002: def wrapper(*args, **kwargs): Function `wrapper` utility or script function.
L3023: def _is_param_expr(arg): Function `_is_param_expr` utility or script function.
L3028: def _is_param_expr(arg): Function `_is_param_expr` utility or script function.
L3049: def _check_generic(cls, parameters, elen=marker): Function `_check_generic`
utility or script function.
L3105: def _check_generic(cls, parameters, elen): Function `_check_generic` utility or
script function.
L3143: def _has_generic_or_protocol_as_origin() -> bool: Function
`_has_generic_or_protocol_as_origin` utility or script function.
L3165: def _is_unpacked_typevar_tuple(x) -> bool: Function `_is_unpacked_typevar_tuple`
utility or script function.
L3178: def _collect_type_vars(types, typevar_types=None): Function `_collect_type_vars`
utility or script function.
L3228: def _collect_parameters(args): Function `_collect_parameters` utility or script
function.
L3296: def _make_nmtuple(name, types, module, defaults=()): Function `_make_nmtuple`
utility or script function.
L3308: class _NamedTupleMeta(type): Class (`_NamedTupleMeta`) component used by the app

```

```

(see file context: None).
L3309: def __new__(cls, typename, bases, ns):    Function `__new__`    utility or script
function.
L3381: def _namedtuple_mro_entries(bases):    Function `_namedtuple_mro_entries`    utility or
script function.
L3385: def NamedTuple(typename, fields=_marker, /, **kwargs):    Function `NamedTuple`
utility or script function.
L3390: class Employee(NamedTuple):    Class (`Employee`)    component used by the app (see file
context: None).
L3456: class Buffer(abc.ABC):    # noqa: B024    Class (`Buffer`)    component used by the app
(see file context: None).
L3486: def get_original_bases(cls, /):    Function `get_original_bases`    Returns or fetches
data.
L3495: class Foo(Generic[T]): ...    Class (`Foo`)    component used by the app (see file
context: None).
L3496: class Bar(Foo[int], float): ...    Class (`Bar`)    component used by the app (see file
context: None).
L3497: class Baz(list[str]): ...    Class (`Baz`)    component used by the app (see file
context: None).
L3521: class NewType:    Class (`NewType`)    component used by the app (see file context:
None).
L3527: def name_by_id(user_id: UserId) -> str:    Function `name_by_id`    utility or script
function.
L3535: def __call__(self, obj, /):    Function `__call__`    utility or script function.
L3538: def __init__(self, name, tp):    Function `__init__`    utility or script function.
L3548: def __mro_entries__(self, bases):    Function `__mro_entries__`    utility or script
function.
L3553: class Dummy:    Class (`Dummy`)    component used by the app (see file context: None).
L3554: def __init_subclass__(cls):    Function `__init_subclass__`    utility or script
function.
L3564: def __repr__(self):    Function `__repr__`    utility or script function.
L3567: def __reduce__(self):    Function `__reduce__`    utility or script function.
L3575: def __or__(self, other):    Function `__or__`    utility or script function.
L3578: def __ror__(self, other):    Function `__ror__`    utility or script function.
L3590: def _is_unionable(obj):    Function `_is_unionable`    utility or script function.
L3601: def _is_unionable(obj):    Function `_is_unionable`    utility or script function.
L3629: class _TypeAliasGenericAlias(typing._GenericAlias, _root=True):    Class
(`_TypeAliasGenericAlias`)    component used by the app (see file context: None).
L3630: def __getattr__(self, attr):    Function `__getattr__`    utility or script function.
L3636: class TypeAliasType:    Class (`TypeAliasType`)    component used by the app (see file
context: None).
L3664: def __init__(self, name: str, value, *, type_params=()):    Function `__init__`
utility or script function.
L3701: def __setattr__(self, name: str, value: object, /) -> None:    Object (singleton).
L3706: def __delattr__(self, name: str, /) -> Never:    Function `__delattr__`    utility or
script function.
L3709: def _raise_attribute_error(self, name: str) -> Never:    Function
`_raise_attribute_error`    utility or script function.
L3723: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L3727: def _check_single_param(self, param, recursion=0):    Function `_check_single_param`
utility or script function.

```

```

L3741: def _check_parameters(self, parameters):    Function `_check_parameters` utility or
script function.
L3753: def __getitem__(self, parameters):    Function `__getitem__` utility or script
function.
L3770: def __reduce__(self):    Function `__reduce__` utility or script function.
L3773: def __init_subclass__(cls, *args, **kwargs):    Function `__init_subclass__` utility
or script function.
L3780: def __call__(self):    Function `__call__` utility or script function.
L3785: def __or__(self, right):    Function `__or__` utility or script function.
L3792: def __ror__(self, left):    Function `__ror__` utility or script function.
L3802: def is_protocol(tp: type, /) -> bool:    Function `is_protocol` utility or script
function.
L3823: def get_protocol_members(tp: type, /) -> typing.FrozenSet[str]:    Function
`get_protocol_members` Returns or fetches data.
L3847: class Doc:    Class (`Doc`) component used by the app (see file context: None).
L3864: def __init__(self, documentation: str, /) -> None:    Function `__init__` utility or
script function.
L3867: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L3870: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L3873: def __eq__(self, other: object) -> bool:    Object (singleton).
L3901: class Format(enum.IntEnum):    Class (`Format`) component used by the app (see file
context: None).
L3909: def get_annotations(obj, *, globals=None, locals=None, eval_str=False,    Function
`get_annotations` Returns or fetches data.
L4043: def _eval_with_owner(    Function `_eval_with_owner` utility or script function.
L4121: def evaluate_forward_ref(    Function `evaluate_forward_ref` utility or script
function.
L4210: class Sentinel:    Class (`Sentinel`) component used by the app (see file context:
None).
L4219: def __init__(    Function `__init__` utility or script function.
L4227: def __repr__(self):    Function `__repr__` utility or script function.
L4233: def __call__(self, *args, **kwargs):    Function `__call__` utility or script
function.
L4238: def __or__(self, other):    Function `__or__` utility or script function.
L4241: def __ror__(self, other):    Function `__ror__` utility or script function.
L4244: def __getstate__(self):    Function `__getstate__` utility or script function.
L4251: def type_repr(value):    Function `type_repr` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/_collections.py

```

L15: class HasGettableStringKeys(Protocol):    Class (`HasGettableStringKeys`) component used
by the app (see file context: None).
L16: def keys(self) -> typing.Iterator[str]: ...    Function `keys` utility or script
function.
L18: def __getitem__(self, key: str) -> str: ...    Function `__getitem__` utility or script
function.
L39: class _Sentinel(Enum):    Class (`_Sentinel`) component used by the app (see file

```

```

context: None).
L43: def ensure_can_construct_http_header_dict(    Function
`ensure_can_construct_http_header_dict` utility or script function.
L63: class RecentlyUsedContainer(typing.Generic[_KT, _VT], typing.MutableMapping[_KT, _VT]):
    Class (`RecentlyUsedContainer`) component used by the app (see file context: None).
L82: def __init__(    Function `__init__` utility or script function.
L93: def __getitem__(self, key: _KT) -> _VT:    Function `__getitem__` utility or script
function.
L100: def __setitem__(self, key: _KT, value: _VT) -> None:    Function `__setitem__` utility
or script function.
L125: def __delitem__(self, key: _KT) -> None:    Function `__delitem__` utility or script
function.
L132: def __len__(self) -> int:    Function `__len__` utility or script function.
L136: def __iter__(self) -> typing.NoReturn:    Function `__iter__` utility or script
function.
L141: def clear(self) -> None:    Function `clear` utility or script function.
L151: def keys(self) -> set[_KT]: # type: ignore[override]    Function `keys` utility or
script function.
L156: class HTTPHeaderDictItemView(set[tuple[str, str]]):    Class (`HTTPHeaderDictItemView`)
component used by the app (see file context: None).
L187: def __init__(self, headers: HTTPHeaderDict) -> None:    Function `__init__` utility or
script function.
L190: def __len__(self) -> int:    Function `__len__` utility or script function.
L193: def __iter__(self) -> typing.Iterator[tuple[str, str]]:    Function `__iter__` utility
or script function.
L196: def __contains__(self, item: object) -> bool:    Object (singleton).
L204: class HTTPHeaderDict(typing.MutableMapping[str, str]):    Class (`HTTPHeaderDict`)
component used by the app (see file context: None).
L240: def __init__(self, headers: ValidHTTPHeaderSource | None = None, **kwargs: str):
Function `__init__` utility or script function.
L251: def __setitem__(self, key: str, val: str) -> None:    Function `__setitem__` utility or
script function.
L257: def __getitem__(self, key: str) -> str:    Function `__getitem__` utility or script
function.
L263: def __delitem__(self, key: str) -> None:    Function `__delitem__` utility or script
function.
L268: def __contains__(self, key: object) -> bool:    Object (singleton).
L275: def setdefault(self, key: str, default: str = "") -> str:    Function `setdefault` Sets
or updates a value.
L278: def __eq__(self, other: object) -> bool:    Object (singleton).
L289: def __ne__(self, other: object) -> bool:    Object (singleton).
L292: def __len__(self) -> int:    Function `__len__` utility or script function.
L295: def __iter__(self) -> typing.Iterator[str]:    Function `__iter__` utility or script
function.
L300: def discard(self, key: str) -> None:    Function `discard` utility or script function.
L306: def add(self, key: str, val: str, *, combine: bool = False) -> None:    Function `add`
utility or script function.
L341: def extend(self, *args: ValidHTTPHeaderSource, **kwargs: str) -> None:    Function
`extend` utility or script function.
L374: def getlist(self, key: str) -> list[str]: ...    Function `getlist` Returns or fetches
data.

```

```

L377: def getlist(self, key: str, default: _DT) -> list[str] | _DT: ...    Function `getlist`
Returns or fetches data.
L379: def getlist(    Function `getlist`    Returns or fetches data.
L399: def _prepare_for_method_change(self) -> Self:    Function `_prepare_for_method_change`
utility or script function.
L425: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L428: def _copy_from(self, other: HTTPHeaderDict) -> None:    Function `_copy_from`    utility
or script function.
L433: def copy(self) -> Self:    Function `copy`    utility or script function.
L438: def iteritems(self) -> typing.Iterator[tuple[str, str]]:    Function `iteritems`
utility or script function.
L445: def itermerged(self) -> typing.Iterator[tuple[str, str]]:    Function `itermerged`
utility or script function.
L451: def items(self) -> HTTPHeaderDictItemView: # type: ignore[override]    Function `items`
utility or script function.
L454: def _has_value_for_header(self, header_name: str, potential_value: str) -> bool:
Function `_has_value_for_header`    utility or script function.
L459: def __ior__(self, other: object) -> HTTPHeaderDict:    Object (singleton).
L468: def __or__(self, other: object) -> Self:    Object (singleton).
L478: def __ror__(self, other: object) -> Self:    Object (singleton).

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/fields.py

```

L15: def guess_content_type(    Function `guess_content_type`    utility or script function.
L31: def format_header_param_rfc2231(name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`format_header_param_rfc2231`    utility or script function.
L79: def format_multipart_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
Function `format_multipart_header_param`    utility or script function.
L117: def format_header_param_html5(name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`format_header_param_html5`    utility or script function.
L135: def format_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`format_header_param`    utility or script function.
L153: class RequestField:    Class (`RequestField`)    component used by the app (see file
context: None).
L171: def __init__(    Function `__init__`    utility or script function.
L200: def from_tuples(    Function `from_tuples`    utility or script function.
L244: def _render_part(self, name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`_render_part`    utility or script function.
L260: def _render_parts(    Function `_render_parts`    utility or script function.
L291: def render_headers(self) -> str:    Function `render_headers`    utility or script
function.
L310: def make_multipart(    Function `make_multipart`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/connection.py

```

L37: class BaseSSLError(BaseException): # type: ignore[no-redef] Class (`BaseSSLError`)
component used by the app (see file context: None).
L82: class HTTPConnection(_HTTPConnection): Class (`HTTPConnection`) component used by the
app (see file context: None).
L132: def __init__( Function `__init__` utility or script function.
L163: def __str__(self) -> str: Function `__str__` utility or script function.
L166: def __repr__(self) -> str: Function `__repr__` utility or script function.
L170: def host(self) -> str: Function `host` utility or script function.
L189: def host(self, value: str) -> None: Function `host` utility or script function.
L198: def _new_conn(self) -> socket.socket: Function `_new_conn` utility or script
function.
L227: def set_tunnel( Function `set_tunnel` Sets or updates a value.
L244: def _wrap_ipv6(self, ip: bytes) -> bytes: Function `_wrap_ipv6` utility or script
function.
L253: def _tunnel(self) -> None: Function `_tunnel` utility or script function.
L296: def _tunnel(self) -> None: # noqa: F811 Function `_tunnel` utility or script
function.
L330: def connect(self) -> None: Function `connect` utility or script function.
L348: def is_closed(self) -> bool: Function `is_closed` utility or script function.
L352: def is_connected(self) -> bool: Function `is_connected` utility or script function.
L358: def has_connected_to_proxy(self) -> bool: Function `has_connected_to_proxy` utility
or script function.
L362: def proxy_is_forwarding(self) -> bool: Function `proxy_is_forwarding` utility or
script function.
L369: def proxy_is_tunneling(self) -> bool: Function `proxy_is_tunneling` utility or
script function.
L375: def close(self) -> None: Function `close` utility or script function.
L390: def putrequest( Function `putrequest` utility or script function.
L410: def putheader(self, header: str, *values: str) -> None: # type: ignore[override]
Function `putheader` utility or script function.
L424: def request( # type: ignore[override] Function `request` utility or script
function.
L521: def request_chunked( Function `request_chunked` utility or script function.
L540: def getresponse( # type: ignore[override] Function `getresponse` Returns or fetches
data.
L603: class HTTPSConnection(HTTPConnection): Class (`HTTPSConnection`) component used by
the app (see file context: None).
L621: def __init__( Function `__init__` utility or script function.
L683: def set_cert( Function `set_cert` Sets or updates a value.
L724: def connect(self) -> None: Function `connect` utility or script function.
L861: def _connect_tls_proxy(self, hostname: str, sock: socket.socket) -> ssl.SSLSocket:
Function `_connect_tls_proxy` utility or script function.
L891: class _WrappedAndVerifiedSocket(typing.NamedTuple): Class
(`_WrappedAndVerifiedSocket`) component used by the app (see file context: None).
L901: def _ssl_wrap_socket_and_match_hostname( Function
`_ssl_wrap_socket_and_match_hostname` utility or script function.
L1026: def _match_hostname( Function `_match_hostname` utility or script function.
L1052: def _wrap_proxy_error(err: Exception, proxy_scheme: str | None) -> ProxyError:
Function `_wrap_proxy_error` utility or script function.
L1077: def _get_default_user_agent() -> str: Function `_get_default_user_agent` utility or
script function.

```

```
L1081: class DummyConnection:    Class (`DummyConnection`)    component used by the app (see
file context: None).
L1092: def _url_from_connection(    Function `_url_from_connection`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/response.py

```
L54: class ContentDecoder:    Class (`ContentDecoder`)    component used by the app (see file
context: None).
L55: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L59: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L62: def flush(self) -> bytes:    Function `flush`    utility or script function.
L66: class DeflateDecoder(ContentDecoder):    Class (`DeflateDecoder`)    component used by the
app (see file context: None).
L67: def __init__(self) -> None:    Function `__init__`    utility or script function.
L73: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L116: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L121: def flush(self) -> bytes:    Function `flush`    utility or script function.
L125: class GzipDecoderState:    Class (`GzipDecoderState`)    component used by the app (see
file context: None).
L131: class GzipDecoder(ContentDecoder):    Class (`GzipDecoder`)    component used by the app
(see file context: None).
L132: def __init__(self) -> None:    Function `__init__`    utility or script function.
L137: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L188: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L191: def flush(self) -> bytes:    Function `flush`    utility or script function.
L197: class BrotliDecoder(ContentDecoder):    Class (`BrotliDecoder`)    component used by the
app (see file context: None).
L201: def __init__(self) -> None:    Function `__init__`    utility or script function.
L209: def _decompress(self, data: bytes, output_buffer_limit: int = -1) -> bytes:    Function
`_decompress`    utility or script function.
L212: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L228: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L234: def flush(self) -> bytes:    Function `flush`    utility or script function.
L250: class ZstdDecoder(ContentDecoder):    Class (`ZstdDecoder`)    component used by the app
(see file context: None).
L251: def __init__(self) -> None:    Function `__init__`    utility or script function.
L254: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
```



```

L289: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail` utility or
script function.
L294: def flush(self) -> bytes:    Function `flush` utility or script function.
L300: class MultiDecoder(ContentDecoder):    Class (`MultiDecoder`) component used by the app
(see file context: None).
L313: def __init__(self, modes: str) -> None:    Function `__init__` utility or script
function.
L322: def flush(self) -> bytes:    Function `flush` utility or script function.
L325: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress` utility or script function.
L352: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail` utility or
script function.
L356: def _get_decoder(mode: str) -> ContentDecoder:    Function `_get_decoder` utility or
script function.
L374: class BytesQueueBuffer:    Class (`BytesQueueBuffer`) component used by the app (see
file context: None).
L388: def __init__(self) -> None:    Function `__init__` utility or script function.
L392: def __len__(self) -> int:    Function `__len__` utility or script function.
L395: def put(self, data: bytes) -> None:    Function `put` utility or script function.
L399: def get(self, n: int) -> bytes:    Function `get` Returns or fetches data.
L434: def get_all(self) -> bytes:    Function `get_all` Returns or fetches data.
L451: class BaseHTTPResponse(io.IOBase):    Class (`BaseHTTPResponse`) component used by the
app (see file context: None).
L466: def __init__(self) -> None:    Function `__init__` utility or script function.
L501: def get_redirect_location(self) -> str | None | typing.Literal[False]:    Function
`get_redirect_location` Returns or fetches data.
L514: def data(self) -> bytes:    Function `data` utility or script function.
L517: def json(self) -> typing.Any:    Function `json` utility or script function.
L539: def url(self) -> str | None:    Function `url` utility or script function.
L543: def url(self, url: str | None) -> None:    Function `url` utility or script function.
L547: def connection(self) -> BaseHTTPConnection | None:    Function `connection` utility or
script function.
L551: def retries(self) -> Retry | None:    Function `retries` utility or script function.
L555: def retries(self, retries: Retry | None) -> None:    Function `retries` utility or
script function.
L561: def stream(self) -> None:    Function `stream` utility or script function.
L566: def read(self) -> bytes:    Function `read` utility or script function.
L574: def read1(self) -> bytes:    Function `read1` utility or script function.
L581: def read_chunked(self) -> None:    Function `read_chunked` utility or script function.
L588: def release_conn(self) -> None:    Function `release_conn` utility or script function.
L591: def drain_conn(self) -> None:    Function `drain_conn` utility or script function.
L594: def shutdown(self) -> None:    Function `shutdown` utility or script function.
L597: def close(self) -> None:    Function `close` utility or script function.
L600: def _init_decoder(self) -> None:    Function `_init_decoder` utility or script
function.
L619: def _decode(self) -> bytes:    Function `_decode` utility or script function.
L656: def _flush_decoder(self) -> bytes:    Function `_flush_decoder` utility or script
function.
L666: def readinto(self, b: bytearray | memoryview[int]) -> int:    Function `readinto`
utility or script function.
L675: def getheaders(self) -> HTTPHeaderDict:    Function `getheaders` Returns or fetches

```

```

data.
L678: def getheader(self, name: str, default: str | None = None) -> str | None:    Function
`getheader` Returns or fetches data.
L682: def info(self) -> HTTPHeaderDict:    Function `info` utility or script function.
L685: def geturl(self) -> str | None:    Function `geturl` Returns or fetches data.
L689: class HTTPResponse(BaseHTTPResponse):    Class (`HTTPResponse`) component used by the
app (see file context: None).
L695: class is also compatible with the Python standard library's :mod:`io`    Class (`is`)
component used by the app (see file context: None).
L722: def __init__(    Function `__init__` utility or script function.
L787: def release_conn(self) -> None:    Function `release_conn` utility or script function.
L794: def drain_conn(self) -> None:    Function `drain_conn` utility or script function.
L811: def data(self) -> bytes:    Function `data` utility or script function.
L822: def connection(self) -> HTTPConnection | None:    Function `connection` utility or
script function.
L825: defisclosed(self) -> bool:    Function `isclosed` utility or script function.
L828: def tell(self) -> int:    Function `tell` utility or script function.
L836: def _init_length(self, request_method: str | None) -> int | None:    Function
`_init_length` utility or script function.
L893: def _error_catcher(self) -> typing.Generator[None]:    Function `_error_catcher`
utility or script function.
L954: def _fp_read(    Function `_fp_read` utility or script function.
L1007: def _raw_read(    Function `_raw_read` utility or script function.
L1059: def read(    Function `read` utility or script function.
L1167: def read1(    Function `read1` utility or script function.
L1238: def stream(    Function `stream` utility or script function.
L1273: def readable(self) -> bool:    Function `readable` utility or script function.
L1276: def shutdown(self) -> None:    Function `shutdown` utility or script function.
L1285: def close(self) -> None:    Function `close` utility or script function.
L1298: def closed(self) -> bool:    Function `closed` utility or script function.
L1310: def fileno(self) -> int:    Function `fileno` utility or script function.
L1321: def flush(self) -> None:    Function `flush` utility or script function.
L1329: def supports_chunked_reads(self) -> bool:    Function `supports_chunked_reads` utility
or script function.
L1338: def _update_chunk_length(self) -> None:    Function `_update_chunk_length` utility or
script function.
L1356: def _handle_chunk(self, amt: int | None) -> bytes:    Function `_handle_chunk` utility
or script function.
L1378: def read_chunked(    Function `read_chunked` utility or script function.
L1466: def url(self) -> str | None:    Function `url` utility or script function.
L1475: def url(self, url: str | None) -> None:    Function `url` utility or script function.
L1478: def __iter__(self) -> typing.Iterator[bytes]:    Function `__iter__` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/exceptions.py

```

L18: class HTTPError(Exception):    Class (`HTTPError`) component used by the app (see file

```

```

context: None).
L22: class HTTPWarning(Warning):    Class (`HTTPWarning`)    component used by the app (see file
context: None).
L29: class PoolError(HTTPError):    Class (`PoolError`)    component used by the app (see file
context: None).
L32: def __init__(self, pool: ConnectionPool, message: str) -> None:    Function `__init__`
utility or script function.
L37: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L42: class RequestError(PoolError):    Class (`RequestError`)    component used by the app (see
file context: None).
L45: def __init__(self, pool: ConnectionPool, url: str | None, message: str) -> None:
Function `__init__`    utility or script function.
L49: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L54: class SSLError(HTTPError):    Class (`SSLError`)    component used by the app (see file
context: None).
L58: class ProxyError(HTTPError):    Class (`ProxyError`)    component used by the app (see file
context: None).
L64: def __init__(self, message: str, error: Exception) -> None:    Function `__init__`
utility or script function.
L69: class DecodeError(HTTPError):    Class (`DecodeError`)    component used by the app (see
file context: None).
L73: class ProtocolError(HTTPError):    Class (`ProtocolError`)    component used by the app
(see file context: None).
L84: class MaxRetryError(RequestError):    Class (`MaxRetryError`)    component used by the app
(see file context: None).
L95: def __init__(    Function `__init__`    utility or script function.
L104: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L109: class HostChangedError(RequestError):    Class (`HostChangedError`)    component used by
the app (see file context: None).
L112: def __init__(    Function `__init__`    utility or script function.
L120: class TimeoutStateError(HTTPError):    Class (`TimeoutStateError`)    component used by
the app (see file context: None).
L124: class TimeoutError(HTTPError):    Class (`TimeoutError`)    component used by the app (see
file context: None).
L132: class ReadTimeoutError(TimeoutError, RequestError):    Class (`ReadTimeoutError`)
component used by the app (see file context: None).
L138: class ConnectTimeoutError(TimeoutError):    Class (`ConnectTimeoutError`)    component
used by the app (see file context: None).
L142: class NewConnectionError(ConnectTimeoutError, HTTPError):    Class
(`NewConnectionError`)    component used by the app (see file context: None).
L145: def __init__(self, conn: HTTPConnection, message: str) -> None:    Function `__init__`
utility or script function.
L150: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L155: def pool(self) -> HTTPConnection:    Function `pool`    utility or script function.
L166: class NameResolutionError(NewConnectionError):    Class (`NameResolutionError`)
component used by the app (see file context: None).
L169: def __init__(self, host: str, conn: HTTPConnection, reason: socket.gaierror):

```

```

Function `__init__` utility or script function.
L175: def __reduce__(self) -> _TYPE_REDUCE_RESULT: Function `__reduce__` utility or script
function.
L180: class EmptyPoolError(PoolError): Class (`EmptyPoolError`) component used by the app
(see file context: None).
L184: class FullPoolError(PoolError): Class (`FullPoolError`) component used by the app
(see file context: None).
L188: class ClosedPoolError(PoolError): Class (`ClosedPoolError`) component used by the
app (see file context: None).
L192: class LocationValueError(ValueError, HTTPError): Class (`LocationValueError`)
component used by the app (see file context: None).
L196: class LocationParseError(LocationValueError): Class (`LocationParseError`) component
used by the app (see file context: None).
L199: def __init__(self, location: str) -> None: Function `__init__` utility or script
function.
L206: class URLSchemeUnknown(LocationValueError): Class (`URLSchemeUnknown`) component
used by the app (see file context: None).
L209: def __init__(self, scheme: str): Function `__init__` utility or script function.
L216: class ResponseError(HTTPError): Class (`ResponseError`) component used by the app
(see file context: None).
L223: class SecurityWarning(HTTPWarning): Class (`SecurityWarning`) component used by the
app (see file context: None).
L227: class InsecureRequestWarning(SecurityWarning): Class (`InsecureRequestWarning`)
component used by the app (see file context: None).
L231: class NotOpenSSLWarning(SecurityWarning): Class (`NotOpenSSLWarning`) component used
by the app (see file context: None).
L235: class SystemTimeWarning(SecurityWarning): Class (`SystemTimeWarning`) component used
by the app (see file context: None).
L239: class InsecurePlatformWarning(SecurityWarning): Class (`InsecurePlatformWarning`)
component used by the app (see file context: None).
L243: class DependencyWarning(HTTPWarning): Class (`DependencyWarning`) component used by
the app (see file context: None).
L250: class ResponseNotChunked(ProtocolError, ValueError): Class (`ResponseNotChunked`)
component used by the app (see file context: None).
L254: class BodyNotHttpLibCompatible(HTTPError): Class (`BodyNotHttpLibCompatible`)
component used by the app (see file context: None).
L261: class IncompleteRead(HTTPError, httplib_IncompleteRead): Class (`IncompleteRead`)
component used by the app (see file context: None).
L272: def __init__(self, partial: int, expected: int) -> None: Function `__init__` utility
or script function.
L276: def __repr__(self) -> str: Function `__repr__` utility or script function.
L283: class InvalidChunkLength(HTTPError, httplib_IncompleteRead): Class
(`InvalidChunkLength`) component used by the app (see file context: None).
L286: def __init__(self, response: HTTPResponse, length: bytes) -> None: Function
`__init__` utility or script function.
L292: def __repr__(self) -> str: Function `__repr__` utility or script function.
L299: class InvalidHeader(HTTPError): Class (`InvalidHeader`) component used by the app
(see file context: None).
L303: class ProxySchemeUnknown(AssertionError, URLSchemeUnknown): Class
(`ProxySchemeUnknown`) component used by the app (see file context: None).
L308: def __init__(self, scheme: str | None) -> None: Function `__init__` utility or

```

script function.

L320: class ProxySchemeUnsupported(ValueError): Class (`ProxySchemeUnsupported`) component used by the app (see file context: None).

L324: class HeaderParsingError(HTTPError): Class (`HeaderParsingError`) component used by the app (see file context: None).

L327: def __init__(Function `\_\_init\_\_` utility or script function.

L334: class UnrewindableBodyError(HTTPError): Class (`UnrewindableBodyError`) component used by the app (see file context: None).

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/_request_methods.py

L20: class RequestMethods: Class (`RequestMethods`) component used by the app (see file context: None).

L51: def __init__(self, headers: typing.Mapping[str, str] | None = None) -> None: Function `\_\_init\_\_` utility or script function.

L54: def urlopen(Function `urlopen` utility or script function.

L69: def request(Function `request` utility or script function.

L147: def request_encode_url(Function `request\_encode\_url` utility or script function.

L184: def request_encode_body(Function `request\_encode\_body` utility or script function.

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/__init__.py

L74: def add_stderr_logger(Function `add\_stderr\_logger` utility or script function.

L107: def disable_warnings(category: type[Warning] = exceptions.HTTPWarning) -> None: Function `disable\_warnings` utility or script function.

L117: def request(Function `request` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/poolmanager.py

L56: class PoolKey(typing.NamedTuple): Class (`PoolKey`) component used by the app (see file context: None).

L95: def _default_key_normalizer(Function `\_default\_key\_normalizer` utility or script function.

L162: class PoolManager(RequestMethods): Manager (`PoolManager`) orchestration/utility for managing resources or behaviors.

L199: def __init__(Function `\_\_init\_\_` utility or script function.

L230: def __enter__(self) -> Self: Function `\_\_enter\_\_` utility or script function.

L233: def __exit__(Function `\_\_exit\_\_` utility or script function.

L243: def _new_pool(Function `\_new\_pool` utility or script function.

```

L281: def clear(self) -> None:    Function `clear`    utility or script function.
L290: def connection_from_host(    Function `connection_from_host`    utility or script
function.
L319: def connection_from_context(    Function `connection_from_context`    utility or script
function.
L344: def connection_from_pool_key(    Function `connection_from_pool_key`    utility or script
function.
L370: def connection_from_url(    Function `connection_from_url`    utility or script function.
L388: def _merge_pool_kwargs(    Function `_merge_pool_kwargs`    utility or script function.
L410: def _proxy_requires_url_absolute_form(self, parsed_url: Url) -> bool:    Function
`_proxy_requires_url_absolute_form`    utility or script function.
L423: def urlopen( # type: ignore[override]    Function `urlopen`    utility or script
function.
L506: class ProxyManager(PoolManager):    Manager (`ProxyManager`)    orchestration/utility for
managing resources or behaviors.
L563: def __init__(    Function `__init__`    utility or script function.
L604: def connection_from_host(    Function `connection_from_host`    utility or script
function.
L620: def _set_proxy_headers(    Function `_set_proxy_headers`    utility or script function.
L637: def urlopen( # type: ignore[override]    Function `urlopen`    utility or script
function.
L652: def proxy_from_url(url: str, **kw: typing.Any) -> ProxyManager:    Function
`proxy_from_url`    utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/filepost.py

```

L22: def choose_boundary() -> str:    Function `choose_boundary`    utility or script function.
L29: def iter_field_objects(fields: _TYPE_FIELDS) -> typing.Iterable[RequestField]:
Function `iter_field_objects`    utility or script function.
L51: def encode_multipart_formdata(    Function `encode_multipart_formdata`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/_base_connection.py

```

L14: class ProxyConfig(typing.NamedTuple):    Class (`ProxyConfig`)    component used by the app
(see file context: None).
L21: class _ResponseOptions(typing.NamedTuple):    Class (`_ResponseOptions`)    component used
by the app (see file context: None).
L37: class BaseHTTPConnection(Protocol):    Class (`BaseHTTPConnection`)    component used by
the app (see file context: None).
L56: def __init__(    Function `__init__`    utility or script function.
L69: def set_tunnel(    Function `set_tunnel`    Sets or updates a value.
L77: def connect(self) -> None: ...    Function `connect`    utility or script function.

```

```

L79: def request(    Function `request`    utility or script function.
L95: def getresponse(self) -> BaseHTTPResponse: ...    Function `getresponse`    Returns or
fetches data.
L97: def close(self) -> None: ...    Function `close`    utility or script function.
L100: def is_closed(self) -> bool:    Function `is_closed`    utility or script function.
L107: def is_connected(self) -> bool:    Function `is_connected`    utility or script function.
L111: def has_connected_to_proxy(self) -> bool:    Function `has_connected_to_proxy`    utility
or script function.
L117: class BaseHTTPSConnection(BaseHTTPConnection, Protocol):    Class
(`BaseHTTPSConnection`)    component used by the app (see file context: None).
L142: def __init__(    Function `__init__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/connectionpool.py

```

L67: class ConnectionPool:    Class (`ConnectionPool`)    component used by the app (see file
context: None).
L81: def __init__(self, host: str, port: int | None = None) -> None:    Function `__init__`
utility or script function.
L94: def __str__(self) -> str:    Function `__str__`    utility or script function.
L97: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L100: def __exit__(    Function `__exit__`    utility or script function.
L110: def close(self) -> None:    Function `close`    utility or script function.
L120: class HTTPConnectionPool(ConnectionPool, RequestMethods):    Class
(`HTTPConnectionPool`)    component used by the app (see file context: None).
L175: def __init__(    Function `__init__`    utility or script function.
L236: def _new_conn(self) -> BaseHTTPConnection:    Function `_new_conn`    utility or script
function.
L256: def _get_conn(self, timeout: float | None = None) -> BaseHTTPConnection:    Function
`_get_conn`    utility or script function.
L294: def _put_conn(self, conn: BaseHTTPConnection | None) -> None:    Function `_put_conn`
utility or script function.
L337: def _validate_conn(self, conn: BaseHTTPConnection) -> None:    Function `_validate_conn`
utility or script function.
L342: def _prepare_proxy(self, conn: BaseHTTPConnection) -> None:    Function `_prepare_proxy`
utility or script function.
L346: def _get_timeout(self, timeout: _TYPE_TIMEOUT) -> Timeout:    Function `_get_timeout`
utility or script function.
L358: def _raise_timeout(    Function `_raise_timeout`    utility or script function.
L377: def _make_request(    Function `_make_request`    utility or script function.
L558: def close(self) -> None:    Function `close`    utility or script function.
L570: def is_same_host(self, url: str) -> bool:    Function `is_same_host`    utility or script
function.
L592: def urlopen( # type: ignore[override]    Function `urlopen`    utility or script
function.
L976: class HTTPSConnectionPool(HTTPConnectionPool):    Class (`HTTPSConnectionPool`)
component used by the app (see file context: None).
L993: def __init__(    Function `__init__`    utility or script function.

```



```

L1042: def _prepare_proxy(self, conn: HTTPSConnection) -> None: # type: ignore[override]
Function `_prepare_proxy` utility or script function.
L1057: def _new_conn(self) -> BaseHTTPConnection: Function `_new_conn` utility or script
function.
L1098: def _validate_conn(self, conn: BaseHTTPConnection) -> None: Function
`_validate_conn` utility or script function.
L1121: def connection_from_url(url: str, **kw: typing.Any) -> HTTPConnectionPool: Function
`connection_from_url` utility or script function.
L1151: def _normalize_host(host: None, scheme: str | None) -> None: ... Function
`_normalize_host` utility or script function.
L1155: def _normalize_host(host: str, scheme: str | None) -> str: ... Function
`_normalize_host` utility or script function.
L1158: def _normalize_host(host: str | None, scheme: str | None) -> str | None: Function
`_normalize_host` utility or script function.
L1176: def _url_from_pool( Function `_url_from_pool` utility or script function.
L1183: def _close_pool_connections(pool: queue.LifoQueue[typing.Any]) -> None: Function
`_close_pool_connections` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/timeout.py

```

L14: class _TYPE_DEFAULT(Enum): Class (`_TYPE_DEFAULT`) component used by the app (see
file context: None).
L25: class Timeout: Class (`Timeout`) component used by the app (see file context: None).
L109: def __init__( Function `__init__` utility or script function.
L120: def __repr__(self) -> str: Function `__repr__` utility or script function.
L127: def resolve_default_timeout(timeout: _TYPE_TIMEOUT) -> float | None: Function
`resolve_default_timeout` utility or script function.
L131: def _validate_timeout(cls, value: _TYPE_TIMEOUT, name: str) -> _TYPE_TIMEOUT:
Function `_validate_timeout` utility or script function.
L173: def from_float(cls, timeout: _TYPE_TIMEOUT) -> Timeout: Function `from_float`
utility or script function.
L188: def clone(self) -> Timeout: Function `clone` utility or script function.
L202: def start_connect(self) -> float: Function `start_connect` utility or script
function.
L213: def get_connect_duration(self) -> float: Function `get_connect_duration` Returns or
fetches data.
L228: def connect_timeout(self) -> _TYPE_TIMEOUT: Function `connect_timeout` utility or
script function.
L246: def read_timeout(self) -> float | None: Function `read_timeout` utility or script
function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/retry.py

```

L33: class RequestHistory(typing.NamedTuple): Class (`RequestHistory`) component used by
the app (see file context: None).

```

```

L41: class Retry:    Class (`Retry`) component used by the app (see file context: None).
L219: def __init__(    Function `__init__` utility or script function.
L266: def new(self, **kw: typing.Any) -> Self:    Function `new` utility or script function.
L291: def from_int(    Function `from_int` utility or script function.
L309: def get_backoff_time(self) -> float:    Function `get_backoff_time` Returns or fetches
data.
L328: def parse_retry_after(self, retry_after: str) -> float:    Function `parse_retry_after`
utility or script function.
L349: def get_retry_after(self, response: BaseHTTPResponse) -> float | None:    Function
`get_retry_after` Returns or fetches data.
L359: def sleep_for_retry(self, response: BaseHTTPResponse) -> bool:    Function
`sleeo_for_retry` utility or script function.
L367: def _sleep_backoff(self) -> None:    Function `_sleep_backoff` utility or script
function.
L373: def sleep(self, response: BaseHTTPResponse | None = None) -> None:    Function `sleep`
utility or script function.
L389: def _is_connection_error(self, err: Exception) -> bool:    Function
`_is_connection_error` utility or script function.
L397: def _is_read_error(self, err: Exception) -> bool:    Function `_is_read_error` utility
or script function.
L403: def _is_method_retryable(self, method: str) -> bool:    Function `_is_method_retryable`
utility or script function.
L411: def is_retry(    Function `is_retry` utility or script function.
L433: def is_exhausted(self) -> bool:    Function `is_exhausted` utility or script function.
L452: def increment(    Function `increment` utility or script function.
L549: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/wait.py

```

L33: def select_wait_for_socket(    Function `select_wait_for_socket` utility or script
function.
L57: def poll_wait_for_socket(    Function `poll_wait_for_socket` utility or script function.
L74: def do_poll(t: float | None) -> list[tuple[int, int]]:    Function `do_poll` utility or
script function.
L82: def _have_working_poll() -> bool:    Function `_have_working_poll` utility or script
function.
L95: def wait_for_socket(    Function `wait_for_socket` utility or script function.
L113: def wait_for_read(sock: socket.socket, timeout: float | None = None) -> bool:
Function `wait_for_read` utility or script function.
L120: def wait_for_write(sock: socket.socket, timeout: float | None = None) -> bool:
Function `wait_for_write` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/connection.py

```

L15: def is_connection_dropped(conn: BaseHTTPConnection) -> bool:    # Platform-specific

```

```

Function `is_connection_dropped` utility or script function.
L27: def create_connection( Function `create_connection` Creates a resource or document.
L93: def _set_socket_options( Function `_set_socket_options` utility or script function.
L103: def allowed_gai_family() -> socket.AddressFamily: Function `allowed_gai_family`
utility or script function.
L114: def _has_ipv6(host: str) -> bool: Function `_has_ipv6` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/url.py

```

L80: class Url( Class (`Url`) component used by the app (see file context: None).
L100: def __new__( # type: ignore[no-unttyped-def] Function `__new__` utility or script
function.
L117: def hostname(self) -> str | None: Function `hostname` utility or script function.
L122: def request_uri(self) -> str: Function `request_uri` utility or script function.
L132: def authority(self) -> str | None: Function `authority` utility or script function.
L148: def netloc(self) -> str | None: Function `netloc` utility or script function.
L162: def url(self) -> str: Function `url` utility or script function.
L209: def __str__(self) -> str: Function `__str__` utility or script function.
L214: def _encode_invalid_chars( Function `_encode_invalid_chars` utility or script
function.
L221: def _encode_invalid_chars( Function `_encode_invalid_chars` utility or script
function.
L227: def _encode_invalid_chars( Function `_encode_invalid_chars` utility or script
function.
L263: def _remove_path_dot_segments(path: str) -> str: Function `_remove_path_dot_segments`
utility or script function.
L294: def _normalize_host(host: None, scheme: str | None) -> None: ... Function
`_normalize_host` utility or script function.
L298: def _normalize_host(host: str, scheme: str | None) -> str: ... Function
`_normalize_host` utility or script function.
L301: def _normalize_host(host: str | None, scheme: str | None) -> str | None: Function
`_normalize_host` utility or script function.
L330: def _idna_encode(name: str) -> bytes: Function `_idna_encode` utility or script
function.
L349: def _encode_target(target: str) -> str: Function `_encode_target` utility or script
function.
L367: def parse_url(url: str) -> Url: Function `parse_url` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/response.py

```

L9: def is_fp_closed(obj: object) -> bool: Object (singleton).
L40: def assert_header_parsing(headers: httplib.HTTPMessage) -> None: Function
`assert_header_parsing` utility or script function.
L91: def is_response_to_head(response: httplib.HTTPResponse) -> bool: Function
`is_response_to_head` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/ssltransport.py

```

L22: class SSLTransport:    Class (`SSLTransport`)    component used by the app (see file
context: None).
L34: def _validate_ssl_context_for_tls_in_tls(ssl_context: ssl.SSLContext) -> None:
Function `_validate_ssl_context_for_tls_in_tls`    utility or script function.
L49: def __init__(    Function `__init__`    utility or script function.
L72: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L75: def __exit__(self, *_: typing.Any) -> None:    Function `__exit__`    utility or script
function.
L78: def fileno(self) -> int:    Function `fileno`    utility or script function.
L81: def read(self, len: int = 1024, buffer: typing.Any | None = None) -> int | bytes:
Function `read`    utility or script function.
L84: def recv(self, buflen: int = 1024, flags: int = 0) -> int | bytes:    Function `recv`
utility or script function.
L89: def recv_into(    Function `recv_into`    utility or script function.
L101: def sendall(self, data: bytes, flags: int = 0) -> None:    Function `sendall`    utility
or script function.
L111: def send(self, data: bytes, flags: int = 0) -> int:    Function `send`    utility or
script function.
L116: def makefile(    Function `makefile`    utility or script function.
L168: def unwrap(self) -> None:    Function `unwrap`    utility or script function.
L171: def close(self) -> None:    Function `close`    utility or script function.
L175: def getpeercert(    Function `getpeercert`    Returns or fetches data.
L180: def getpeercert(self, binary_form: typing.Literal[True]) -> bytes | None: ...
Function `getpeercert`    Returns or fetches data.
L182: def getpeercert(self, binary_form: bool = False) -> _TYPE_PEER_CERT_RET:    Function
`getpeercert`    Returns or fetches data.
L185: def version(self) -> str | None:    Function `version`    utility or script function.
L188: def cipher(self) -> tuple[str, str, int] | None:    Function `cipher`    utility or script
function.
L191: def selected_alpn_protocol(self) -> str | None:    Function `selected_alpn_protocol`
utility or script function.
L194: def shared_ciphers(self) -> list[tuple[str, str, int]] | None:    Function
`shared_ciphers`    utility or script function.
L197: def compression(self) -> str | None:    Function `compression`    utility or script
function.
L200: def settimeout(self, value: float | None) -> None:    Function `settimeout`    Sets or
updates a value.
L203: def gettimeout(self) -> float | None:    Function `gettimeout`    Returns or fetches data.
L206: def _decref_socketios(self) -> None:    Function `_decref_socketios`    utility or script
function.
L209: def _wrap_ssl_read(self, len: int, buffer: bytearray | None = None) -> int | bytes:
Function `_wrap_ssl_read`    utility or script function.
L220: def _ssl_io_loop(self, func: typing.Callable[[], None]) -> None: ...    Function
`_ssl_io_loop`    utility or script function.
L224: def _ssl_io_loop(self, func: typing.Callable[[bytes], int], arg1: bytes) -> int: ...
Function `_ssl_io_loop`    utility or script function.

```

```
L228: def _ssl_io_loop(    Function `_ssl_io_loop`    utility or script function.
L235: def _ssl_io_loop(    Function `_ssl_io_loop`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/ssl_match_host name.py

```
L20: class CertificateError(ValueError):    Class (`CertificateError`)    component used by the
app (see file context: None).
L24: def _dnsname_match(    Function `_dnsname_match`    utility or script function.
L80: def _ipaddress_match(ipname: str, host_ip: IPv4Address | IPv6Address) -> bool:
Function `_ipaddress_match`    utility or script function.
L95: def match_hostname(    Function `match_hostname`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/proxy.py

```
L11: def connection_requires_http_tunnel(    Function `connection_requires_http_tunnel`
utility or script function.
```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/ssl_.py

```
L30: def _is_has_never_check_common_name_reliable(    Function
`_is_has_never_check_common_name_reliable`    utility or script function.
L46: class _TYPE_PEER_CERT_RET_DICT(TypedDict, total=False):    Class
(`_TYPE_PEER_CERT_RET_DICT`)    component used by the app (see file context: None).
L107: def assert_fingerprint(cert: bytes | None, fingerprint: str) -> None:    Function
`assert_fingerprint`    utility or script function.
L141: def resolve_cert_reqs(candidate: None | int | str) -> VerifyMode:    Function
`resolve_cert_reqs`    utility or script function.
L164: def resolve_ssl_version(candidate: None | int | str) -> int:    Function
`resolve_ssl_version`    utility or script function.
L180: def create_urllib3_context(    Function `create_urllib3_context`    Creates a resource or
document.
L328: def ssl_wrap_socket(    Function `ssl_wrap_socket`    utility or script function.
L346: def ssl_wrap_socket(    Function `ssl_wrap_socket`    utility or script function.
L363: def ssl_wrap_socket(    Function `ssl_wrap_socket`    utility or script function.
L437: def is_ipaddress(hostname: str | bytes) -> bool:    Function `is_ipaddress`    utility or
script function.
L450: def _is_key_file_encrypted(key_file: str) -> bool:    Function `_is_key_file_encrypted`
utility or script function.
L461: def _ssl_wrap_socket_impl(    Function `_ssl_wrap_socket_impl`    utility or script
```

```
function.
```

Q_base appwrite/.venv/lib/python3.12/site-packages/urllib3/util/util.py

```
L7: def to_bytes(    Function `to_bytes`    utility or script function.
L19: def to_str(    Function `to_str`    utility or script function.
L31: def reraise(    Function `reraise`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/util/request.py

```
L44: class _TYPE_FAILEDTELL(Enum):    AI-related component (`_TYPE_FAILEDTELL`)    coordinates
AI/LLM interactions.
L60: def make_headers(    Function `make_headers`    utility or script function.
L142: def set_file_position(    Function `set_file_position`    Sets or updates a value.
L162: def rewind_body(body: typing.IO[typing.AnyStr], body_pos: _TYPE_BODY_POSITION) -> None:
    Function `rewind_body`    utility or script function.
L192: class ChunksAndContentLength(typing.NamedTuple):    Class (`ChunksAndContentLength`)
component used by the app (see file context: None).
L197: def body_to_chunks(    Function `body_to_chunks`    utility or script function.
L230: def chunk_readable() -> typing.Iterable[bytes]:    Function `chunk_readable`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/http2/connection.py

```
L29: def _is_legal_header_name(name: bytes) -> bool:    Function `_is_legal_header_name`
utility or script function.
L44: def _is_illegal_header_value(value: bytes) -> bool:    Function
`_is_illegal_header_value`    utility or script function.
L54: class _LockedObject(typing.Generic[T]):    Class (`_LockedObject`)    component used by the
app (see file context: None).
L68: def __init__(self, obj: T):    Function `__init__`    utility or script function.
L72: def __enter__(self) -> T:    Function `__enter__`    utility or script function.
L76: def __exit__(    Function `__exit__`    utility or script function.
L85: class HTTP2Connection(HTTPSPConnection):    Class (`HTTP2Connection`)    component used by
the app (see file context: None).
L86: def __init__(    Function `__init__`    utility or script function.
L101: def _new_h2_conn(self) -> _LockedObject[h2.connection.H2Connection]:    Function
`_new_h2_conn`    utility or script function.
L105: def connect(self) -> None:    Function `connect`    utility or script function.
L112: def putrequest(    # type: ignore[override]    Function `putrequest`    utility or script
function.
```

```

L143: def putheader(self, header: str | bytes, *values: str | bytes) -> None: # type:
ignore[override]    Function `putheader`    utility or script function.
L156: def endheaders(self, message_body: typing.Any = None) -> None: # type:
ignore[override]    Function `endheaders`    utility or script function.
L170: def send(self, data: typing.Any) -> None:    Function `send`    utility or script
function.
L215: def set_tunnel(    Function `set_tunnel`    Sets or updates a value.
L226: def getresponse( # type: ignore[override]    Function `getresponse`    Returns or fetches
data.
L268: def request( # type: ignore[override]    Function `request`    utility or script
function.
L307: def close(self) -> None:    Function `close`    utility or script function.
L324: class HTTP2Response(BaseHTTPResponse):    Class (`HTTP2Response`)    component used by the
app (see file context: None).
L326: def __init__(    Function `__init__`    utility or script function.
L349: def data(self) -> bytes:    Function `data`    utility or script function.
L352: def get_redirect_location(self) -> None:    Function `get_redirect_location`    Returns or
fetches data.
L355: def close(self) -> None:    Function `close`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/http2/__init__.py

```

L15: def inject_into_urllib3() -> None:    Function `inject_into_urllib3`    utility or script
function.
L43: def extract_from_urllib3() -> None:    Function `extract_from_urllib3`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/http2/probe.py

```

L6: class _HTTP2ProbeCache:    Class (`_HTTP2ProbeCache`)    component used by the app (see file
context: None).
L13: def __init__(self) -> None:    Function `__init__`    utility or script function.
L18: def acquire_and_get(self, host: str, port: int) -> bool | None:    Function
`acquire_and_get`    utility or script function.
L51: def set_and_release(    Function `set_and_release`    Sets or updates a value.
L65: def _values(self) -> dict[tuple[str, int], bool | None]:    Function `_values`    utility
or script function.
L70: def _reset(self) -> None:    Function `_reset`    utility or script function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/urllib3/contrib/pyopenssl.p y

```

L150: class UnsupportedExtension(Exception): # type: ignore[no-redef] Class
(`UnsupportedExtension`) component used by the app (see file context: None).
L138: def inject_into_urllib3() -> None: Function `inject_into_urllib3` utility or script
function.
L149: def extract_from_urllib3() -> None: Function `extract_from_urllib3` utility or
script function.
L158: def _validate_dependencies_met() -> None: Function `_validate_dependencies_met`
utility or script function.
L184: def _dnsname_to_stdlib(name: str) -> str | None: Function `_dnsname_to_stdlib`
utility or script function.
L198: def idna_encode(name: str) -> bytes | None: Function `idna_encode` utility or script
function.
L225: def get_subj_alt_name(peer_cert: X509) -> list[tuple[str, str]]: Function
`get_subj_alt_name` Returns or fetches data.
L273: class WrappedSocket: Class (`WrappedSocket`) component used by the app (see file
context: None).
L276: def __init__( Function `_init__` utility or script function.
L288: def fileno(self) -> int: Function `fileno` utility or script function.
L292: def _decref_socketios(self) -> None: Function `_decref_socketios` utility or script
function.
L298: def recv(self, *args: typing.Any, **kwargs: typing.Any) -> bytes: Function `recv`
utility or script function.
L323: def recv_into(self, *args: typing.Any, **kwargs: typing.Any) -> int: Function
`recv_into` utility or script function.
L346: def settimeout(self, timeout: float) -> None: Function `settimeout` Sets or updates
a value.
L349: def _send_until_done(self, data: bytes) -> int: Function `_send_until_done` utility
or script function.
L360: def sendall(self, data: bytes) -> None: Function `sendall` utility or script
function.
L368: def shutdown(self, how: int) -> None: Function `shutdown` utility or script
function.
L374: def close(self) -> None: Function `close` utility or script function.
L379: def _real_close(self) -> None: Function `_real_close` utility or script function.
L385: def getpeercert( Function `getpeercert` Returns or fetches data.
L401: def version(self) -> str: Function `version` utility or script function.
L404: def selected_alpn_protocol(self) -> str | None: Function `selected_alpn_protocol`
utility or script function.
L412: class PyOpenSSLContext: Class (`PyOpenSSLContext`) component used by the app (see
file context: None).
L419: def __init__(self, protocol: int) -> None: Function `_init__` utility or script
function.
L429: def options(self) -> int: Function `options` utility or script function.
L433: def options(self, value: int) -> None: Function `options` utility or script
function.
L438: def verify_flags(self) -> int: Function `verify_flags` utility or script function.

```

```

L442: def verify_flags(self, value: int) -> None:    Function `verify_flags` utility or
script function.
L447: def verify_mode(self) -> int:    Function `verify_mode` utility or script function.
L451: def verify_mode(self, value: ssl.VerifyMode) -> None:    Function `verify_mode` utility
or script function.
L454: def set_default_verify_paths(self) -> None:    Function `set_default_verify_paths` Sets
or updates a value.
L457: def set_ciphers(self, ciphers: bytes | str) -> None:    Function `set_ciphers` Sets or
updates a value.
L462: def load_verify_locations(    Function `load_verify_locations` Loads data from storage
or remote.
L479: def load_cert_chain(    Function `load_cert_chain` Loads data from storage or remote.
L495: def set_alpn_protocols(self, protocols: list[bytes | str]) -> None:    Function
`set_alpn_protocols` Sets or updates a value.
L499: def wrap_socket(    Function `wrap_socket` utility or script function.
L530: def _set_ctx_options(self) -> None:    Function `_set_ctx_options` utility or script
function.
L538: def minimum_version(self) -> int:    Function `minimum_version` utility or script
function.
L542: def minimum_version(self, minimum_version: int) -> None:    Function `minimum_version`
utility or script function.
L547: def maximum_version(self) -> int:    Function `maximum_version` utility or script
function.
L551: def maximum_version(self, maximum_version: int) -> None:    Function `maximum_version`
utility or script function.
L556: def _verify_callback(    Function `_verify_callback` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/socks.py

```

L75: class _TYPE SOCKS_OPTIONS(typing.TypedDict):    Class (`_TYPE SOCKS_OPTIONS`) component
used by the app (see file context: None).
L84: class SOCKSConnection(HTTPConnection):    Class (`SOCKSConnection`) component used by
the app (see file context: None).
L89: def __init__(    Function `__init__` utility or script function.
L98: def _new_conn(self) -> socks.socksocket:    Function `_new_conn` utility or script
function.
L161: class SOCKSHTTPConnection(SOCKSConnection, HTTPConnection):    Class
(`SOCKSHTTPConnection`) component used by the app (see file context: None).
L165: class SOCKSHTTPConnectionPool(HTTPConnectionPool):    Class (`SOCKSHTTPConnectionPool`)
component used by the app (see file context: None).
L169: class SOCKSHTTPConnectionPool(HTTPConnectionPool):    Class
(`SOCKSHTTPConnectionPool`) component used by the app (see file context: None).
L173: class SOCKSProxyManager(PoolManager):    Manager (`SOCKSProxyManager`)
orchestration/utility for managing resources or behaviors.
L184: def __init__(    Function `__init__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/fetch.py

```

L71: class _RequestError(Exception):    Class (`_RequestError`) component used by the app
(see file context: None).
L72: def __init__(    Function `__init__` utility or script function.
L85: class _StreamingError(_RequestError):    Class (`_StreamingError`) component used by the
app (see file context: None).
L89: class _TimeoutError(_RequestError):    Class (`_TimeoutError`) component used by the app
(see file context: None).
L93: def _obj_from_dict(dict_val: dict[str, Any]) -> JsProxy:    Function `_obj_from_dict`
utility or script function.
L97: class _ReadStream(io.RawIOBase):    Class (`_ReadStream`) component used by the app (see
file context: None).
L98: def __init__(    Function `__init__` utility or script function.
L118: def __del__(self) -> None:    Function `__del__` utility or script function.
L122: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L127: def closed(self) -> bool:    Function `closed` utility or script function.
L130: def close(self) -> None:    Function `close` utility or script function.
L144: def readable(self) -> bool:    Function `readable` utility or script function.
L147: def writable(self) -> bool:    Function `writable` utility or script function.
L150: def seekable(self) -> bool:    Function `seekable` utility or script function.
L153: def readinto(self, byte_obj: Buffer) -> int:    Function `readinto` utility or script
function.
L200: class _StreamingFetcher:    Class (`_StreamingFetcher`) component used by the app (see
file context: None).
L201: def __init__(self) -> None:    Function `__init__` utility or script function.
L214: def promise_resolver(js_resolve_fn: JsProxy, js_reject_fn: JsProxy) -> None:    Function
`promise_resolver` utility or script function.
L215: def onMsg(e: JsProxy) -> None:    Function `onMsg` utility or script function.
L219: def onErr(e: JsProxy) -> None:    Function `onErr` utility or script function.
L229: def send(self, request: EmscriptenRequest) -> EmscriptenResponse:    Function `send`
utility or script function.
L302: class _JSPiReadStream(io.RawIOBase):    Class (`_JSPiReadStream`) component used by the
app (see file context: None).
L324: def __init__(    Function `__init__` utility or script function.
L342: def __del__(self) -> None:    Function `__del__` utility or script function.
L346: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L351: def closed(self) -> bool:    Function `closed` utility or script function.
L354: def close(self) -> None:    Function `close` utility or script function.
L367: def readable(self) -> bool:    Function `readable` utility or script function.
L370: def writable(self) -> bool:    Function `writable` utility or script function.
L373: def seekable(self) -> bool:    Function `seekable` utility or script function.
L376: def _get_next_buffer(self) -> bool:    Function `_get_next_buffer` utility or script
function.
L392: def readinto(self, byte_obj: Buffer) -> int:    Function `readinto` utility or script
function.
L410: def is_in_browser_main_thread() -> bool:    Function `is_in_browser_main_thread`

```

utility or script function.

L414: def is_cross_origin_isolated() -> bool: Function `is\_cross\_origin\_isolated` utility or script function.

L418: def is_in_node() -> bool: Function `is\_in\_node` utility or script function.

L427: def is_worker_available() -> bool: Function `is\_worker\_available` utility or script function.

L449: def send_streaming_request(request: EmscriptenRequest) -> EmscriptenResponse | None: Function `send\_streaming\_request` utility or script function.

L469: def _show_timeout_warning() -> None: Function `\_show\_timeout\_warning` utility or script function.

L480: def _show_streaming_warning() -> None: Function `\_show\_streaming\_warning` utility or script function.

L499: def send_request(request: EmscriptenRequest) -> EmscriptenResponse: Function `send\_request` utility or script function.

L548: def send_jspi_request(Function `send\_jspi\_request` utility or script function.

L626: def _run_sync_with_timeout(Function `\_run\_sync\_with\_timeout` utility or script function.

L680: def has_jspi() -> bool: Function `has\_jspi` utility or script function.

L699: def _is_node_js() -> bool: Function `\_is\_node\_js` utility or script function.

L714: def streaming_ready() -> bool | None: Function `streaming\_ready` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/connection.py

L25: class EmscriptenHTTPConnection: Class (`EmscriptenHTTPConnection`) component used by the app (see file context: None).

L46: def __init__(Function `\_\_init\_\_` utility or script function.

L73: def set_tunnel(Function `set\_tunnel` Sets or updates a value.

L82: def connect(self) -> None: Function `connect` utility or script function.

L85: def request(Function `request` utility or script function.

L129: def getresponse(self) -> BaseHTTPResponse: Function `getresponse` Returns or fetches data.

L139: def close(self) -> None: Function `close` utility or script function.

L144: def is_closed(self) -> bool: Function `is\_closed` utility or script function.

L152: def is_connected(self) -> bool: Function `is\_connected` utility or script function.

L157: def has_connected_to_proxy(self) -> bool: Function `has\_connected\_to\_proxy` utility or script function.

L165: class EmscriptenHTTPSConnection(EmscriptenHTTPConnection): Class (`EmscriptenHTTPSConnection`) component used by the app (see file context: None).

L182: def __init__(Function `\_\_init\_\_` utility or script function.

L242: def set_cert(Function `set\_cert` Sets or updates a value.

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/response.py

```

L23: class EmscriptenResponse:    Class (`EmscriptenResponse`)    component used by the app (see
file context: None).
L30: class EmscriptenHttpResponseWrapper(BaseHTTPResponse):    Class
(`EmscriptenHttpResponseWrapper`)    component used by the app (see file context: None).
L31: def __init__(    Function `__init__`    utility or script function.
L57: def url(self) -> str | None:    Function `url`    utility or script function.
L61: def url(self, url: str | None) -> None:    Function `url`    utility or script function.
L65: def connection(self) -> BaseHTTPConnection | BaseHTTPSConnection | None:    Function
`connection`    utility or script function.
L69: def retries(self) -> Retry | None:    Function `retries`    utility or script function.
L73: def retries(self, retries: Retry | None) -> None:    Function `retries`    utility or
script function.
L77: def stream(    Function `stream`    utility or script function.
L103: def _init_length(self, request_method: str | None) -> int | None:    Function
`_init_length`    utility or script function.
L140: def read(    Function `read`    utility or script function.
L180: def read_chunked(    Function `read_chunked`    utility or script function.
L192: def release_conn(self) -> None:    Function `release_conn`    utility or script function.
L199: def drain_conn(self) -> None:    Function `drain_conn`    utility or script function.
L203: def data(self) -> bytes:    Function `data`    utility or script function.
L209: def json(self) -> typing.Any:    Function `json`    utility or script function.
L230: def close(self) -> None:    Function `close`    utility or script function.
L240: def _error_catcher(self) -> typing.Generator[None]:    Function `_error_catcher`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/ __init__.py

```

L9: def inject_into_urllib3() -> None:    Function `inject_into_urllib3`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/urllib3/contrib/emscripten/ request.py

```

L9: class EmscriptenRequest:    Class (`EmscriptenRequest`)    component used by the app (see
file context: None).
L18: def set_header(self, name: str, value: str) -> None:    Function `set_header`    Sets or

```

updates a value.

L21: def set_body(self, body: _TYPE_BODY | None) -> None: Function `set\_body` Sets or updates a value.

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/compat.py

L6: def ToASCII(label: str) -> bytes: Function `ToASCII` utility or script function.

L19: def ToUnicode(label: Union[bytes, bytearray]) -> str: Function `ToUnicode` utility or script function.

L32: def nameprep(s: Any) -> None: Function `nameprep` utility or script function.

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/idnadata.py

L109: def joining_types() -> Dict[int, int]: Function `joining\_types` utility or script function.

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/core.py

L27: class IDNAError(UnicodeError): Class (`IDNAError`) component used by the app (see file context: None).

L33: class IDNABidiError(IDNAError): Class (`IDNABidiError`) component used by the app (see file context: None).

L39: class InvalidCodepoint(IDNAError): Class (`InvalidCodepoint`) component used by the app (see file context: None).

L45: class InvalidCodepointContext(IDNAError): Class (`InvalidCodepointContext`) component used by the app (see file context: None).

L51: def _combining_class(cp: int) -> int: Function `\_combining\_class` utility or script function.

L58: def _is_script(cp: str, script: str) -> bool: Function `\_is\_script` utility or script function.

L62: def _punycode(s: str) -> bytes: Function `\_punycode` utility or script function.

L66: def _unot(s: int) -> str: Function `\_unot` utility or script function.

L70: def valid_label_length(label: Union[bytes, str]) -> bool: Function `valid\_label\_length` utility or script function.

L85: def valid_string_length(domain: Union[bytes, str], trailing_dot: bool) -> bool: Function `valid\_string\_length` utility or script function.

L99: def check_bidi(label: str, check_ltr: bool = False) -> bool: Function `check\_bidi` utility or script function.

L173: def check_initial_combiner(label: str) -> bool: Function `check\_initial\_combiner` utility or script function.

L188: def check_hyphen_ok(label: str) -> bool: Function `check\_hyphen\_ok` utility or script function.

L206: def check_nfc(label: str) -> None: Function `check\_nfc` utility or script function.

L216: def valid_contextj(label: str, pos: int) -> bool: Function `valid\_contextj` utility

or script function.

L270: def valid_contexto(label: str, pos: int, exception: bool = False) -> bool: Function
`valid\_contexto` utility or script function.

L316: def check_label(label: Union[str, bytes, bytearray]) -> None: Function `check\_label`
utility or script function.

L373: def alabel(label: str) -> bytes: Function `alabel` utility or script function.

L404: def ulabel(label: Union[str, bytes, bytearray]) -> str: Function `ulabel` utility or
script function.

L445: def uts46_remap(domain: str, std3_rules: bool = True, transitional: bool = False) ->
str: Function `uts46\_remap` utility or script function.

L500: def encode(Function `encode` utility or script function.

L570: def decode(Function `decode` utility or script function.

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/codec.py

L7: class Codec(codecs.Codec): Class (`Codec`) component used by the app (see file
context: None).

L18: def encode(self, data: str, errors: str = "strict") -> Tuple[bytes, int]: # ty:
ignore[invalid-method-override] Function `encode` utility or script function.

L27: def decode(self, data: bytes, errors: str = "strict") -> Tuple[str, int]: # ty:
ignore[invalid-method-override] Function `decode` utility or script function.

L37: class IncrementalEncoder(codecs.BufferedIncrementalEncoder): Class
(`IncrementalEncoder`) component used by the app (see file context: None).

L49: def _buffer_encode(self, data: str, errors: str, final: bool) -> Tuple[bytes, int]: #
ty: ignore[invalid-method-override] Function `\_buffer\_encode` utility or script function.

L82: class IncrementalDecoder(codecs.BufferedIncrementalDecoder): Class
(`IncrementalDecoder`) component used by the app (see file context: None).

L92: def _buffer_decode(self, data: Any, errors: str, final: bool) -> Tuple[str, int]: # ty:
ignore[invalid-method-override] Function `\_buffer\_decode` utility or script function.

L127: class StreamWriter(Codec, codecs.StreamWriter): Class (`StreamWriter`) component
used by the app (see file context: None).

L131: class StreamReader(Codec, codecs.StreamReader): Class (`StreamReader`) component
used by the app (see file context: None).

L135: def search_function(name: str) -> Optional[codecs.CodecInfo]: Function
`search\_function` utility or script function.

Q_base appwrite/.venv/lib/python3.12/site-packages/idna/intranges.py

L12: def intranges_from_list(list_: List[int]) -> Tuple[int, ...]: Function
`intranges\_from\_list` utility or script function.

L33: def _encode_range(start: int, end: int) -> int: Function `\_encode\_range` utility or
script function.

L37: def _decode_range(r: int) -> Tuple[int, int]: Function `\_decode\_range` utility or
script function.

L41: def intranges_contain(int_: int, ranges: Tuple[int, ...]) -> bool: Function
`intranges\_contain` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_elffile.py

```

L18: class ELFInvalid(ValueError):    Class (`ELFInvalid`)    component used by the app (see
file context: None).
L22: class EIClass(enum.IntEnum):    Class (`EIClass`)    component used by the app (see file
context: None).
L27: class EIData(enum.IntEnum):    Class (`EIData`)    component used by the app (see file
context: None).
L32: class EMachine(enum.IntEnum):    Class (`EMachine`)    component used by the app (see file
context: None).
L40: class ELFFile:    Class (`ELFFile`)    component used by the app (see file context: None).
L45: def __init__(self, f: IO[bytes]) -> None:    Function `__init__`    utility or script
function.
L90: def _read(self, fmt: str) -> tuple[int, ...]:    Function `_read`    utility or script
function.
L94: def interpreter(self) -> str | None:    Function `interpreter`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_manylinux.py

```

L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:    Function
`_parse_elf`    utility or script function.
L40: def _is_linux_armhf(executable: str) -> bool:    Function `_is_linux_armhf`    utility or
script function.
L55: def _is_linux_i686(executable: str) -> bool:    Function `_is_linux_i686`    utility or
script function.
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:    Function
`_have_compatible_abi`    utility or script function.
L81: class _GLibCVersion(NamedTuple):    Class (`_GLibCVersion`)    component used by the app
(see file context: None).
L86: def _glibc_version_string_confstr() -> str | None:    Function
`_glibc_version_string_confstr`    utility or script function.
L105: def _glibc_version_string_ctypes() -> str | None:    Function
`_glibc_version_string_ctypes`    utility or script function.
L149: def _glibc_version_string() -> str | None:    Function `_glibc_version_string`    utility
or script function.
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:    Function
`_parse_glibc_version`    utility or script function.
L174: def _get_glibc_version() -> _GLibCVersion:    Function `_get_glibc_version`    utility or
script function.
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:    Function
`_is_compatible`    utility or script function.
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/direct_url.py

```

L27: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L34: class _FromMappingProtocol(Protocol): # pragma: no cover    Class
(`_FromMappingProtocol`)    component used by the app (see file context: None).
L36: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict`    utility
or script function.
L42: def _json_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_json_dict_factory`    utility or script function.
L46: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get`    utility or script function.
L59: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required`    utility or script function.
L66: def _get_object(    Function `_get_object`    utility or script function.
L83: def _strip_auth_from_netloc(netloc: str, safe_user_passwords: Collection[str]) -> str:
Function `_strip_auth_from_netloc`    utility or script function.
L94: def _strip_url(url: str, safe_user_passwords: Collection[str]) -> str:    Function
`_strip_url`    utility or script function.
L112: class DirectUrlValidationError(Exception):    Class (`DirectUrlValidationError`)
component used by the app (see file context: None).
L118: def __init__(    Function `__init__`    utility or script function.
L136: def __str__(self) -> str:    Function `__str__`    utility or script function.
L142: class _DirectUrlRequiredKeyError(DirectUrlValidationError):    Class
(`_DirectUrlRequiredKeyError`)    component used by the app (see file context: None).
L143: def __init__(self, key: str) -> None:    Function `__init__`    utility or script
function.
L148: class VcsInfo:    Class (`VcsInfo`)    component used by the app (see file context: None).
L153: def __init__(    Function `__init__`    utility or script function.
L165: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L175: class ArchiveInfo:    Class (`ArchiveInfo`)    component used by the app (see file
context: None).
L178: def __init__(    Function `__init__`    utility or script function.
L186: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L221: class DirInfo:    Class (`DirInfo`)    component used by the app (see file context: None).
L224: def __init__(    Function `__init__`    utility or script function.
L232: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L239: class DirectUrl:    Class (`DirectUrl`)    component used by the app (see file context:
None).
L248: def __init__(    Function `__init__`    utility or script function.
L264: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L289: def from_dict(cls, d: Mapping[str, Any], /) -> Self:    Function `from_dict`    utility or
script function.
L293: def to_dict(    Function `to_dict`    utility or script function.
L320: def validate(self) -> None:    Function `validate`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/metadata.py

```

L40: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L44: class InvalidMetadata(ValueError):    Class (`InvalidMetadata`)    component used by the
app (see file context: None).
L50: def __init__(self, field: str, message: str) -> None:    Function `__init__`    utility or
script function.
L59: class RawMetadata(TypedDict, total=False):    Class (`RawMetadata`)    component used by
the app (see file context: None).
L178: def _parse_keywords(data: str) -> list[str]:    Function `_parse_keywords`    utility or
script function.
L183: def _parse_project_urls(data: list[str]) -> dict[str, str]:    Function
`_parse_project_urls`    utility or script function.
L222: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:    Function
`_get_payload`    utility or script function.
L291: class RFC822Policy(email.policy.EmailPolicy):    Class (`RFC822Policy`)    component used
by the app (see file context: None).
L301: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:    Function
`header_store_parse`    utility or script function.
L308: class RFC822Message(email.message.EmailMessage):    Class (`RFC822Message`)    component
used by the app (see file context: None).
L315: def __init__(self) -> None:    Function `__init__`    utility or script function.
L318: def as_bytes(    Function `as_bytes`    utility or script function.
L329: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
Function `parse_email`    utility or script function.
L520: class _Validator(Generic[T]):    Class (`_Validator`)    component used by the app (see
file context: None).
L534: def __init__(    Function `__init__`    utility or script function.
L541: def __set_name__(self, _owner: Metadata, name: str) -> None:    Function `__set_name__`
utility or script function.
L545: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:    Function
`__get__`    utility or script function.
L572: def _invalid_metadata(    Function `_invalid_metadata`    utility or script function.
L581: def _process_metadata_version(self, value: str) -> _MetadataVersion:    Function
`_process_metadata_version`    utility or script function.
L587: def _process_name(self, value: str) -> str:    Function `_process_name`    utility or
script function.
L600: def _process_version(self, value: str) -> version_module.Version:    Function
`_process_version`    utility or script function.
L610: def _process_summary(self, value: str) -> str:    Function `_process_summary`    utility
or script function.
L616: def _process_description_content_type(self, value: str) -> str:    Function
`_process_description_content_type`    utility or script function.
L648: def _process_dynamic(self, value: list[str]) -> list[str]:    Function
`_process_dynamic`    utility or script function.
L660: def _process_provides_extra(    Function `_process_provides_extra`    utility or script
function.
L675: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:    Function

```

```

`_process_requires_python` utility or script function.
L683: def _process_requires_dist( Function `_process_requires_dist` utility or script
function.
L698: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
Function `_process_license_expression` utility or script function.
L706: def _process_license_files(self, value: list[str]) -> list[str]: Function
`_process_license_files` utility or script function.
L732: def _process_import_names(self, value: list[str]) -> list[str]: Function
`_process_import_names` utility or script function.
L757: class Metadata: Class (`Metadata`) component used by the app (see file context:
None).
L769: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata: Function
`from_raw` utility or script function.
L823: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
Function `from_email` utility or script function.
L932: def as_rfc822(self) -> RFC822Message: Function `as_rfc822` utility or script
function.
L940: def _write_metadata(self, message: RFC822Message) -> None: Function `_write_metadata`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/markers.py

```

L30: def __dir__() -> list[str]: Function `__dir__` utility or script function.
L54: class InvalidMarker(ValueError): Class (`InvalidMarker`) component used by the app
(see file context: None).
L62: class UndefinedComparison(ValueError): Class (`UndefinedComparison`) component used
by the app (see file context: None).
L71: class UndefinedEnvironmentName(ValueError): Class (`UndefinedEnvironmentName`)
component used by the app (see file context: None).
L75: class Environment(TypedDict): Class (`Environment`) component used by the app (see
file context: None).
L152: def _normalize_extras( Function `_normalize_extras` utility or script function.
L168: def _normalize_extra_values(results: MarkerList) -> MarkerList: Function
`_normalize_extra_values` utility or script function.
L176: def _format_marker( Function `_format_marker` utility or script function.
L216: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
Function `_eval_op` utility or script function.
L233: def _normalize( Function `_normalize` utility or script function.
L254: def _evaluate_markers( Function `_evaluate_markers` utility or script function.
L287: def _format_full_version(info: sys._version_info) -> str: Function
`_format_full_version` utility or script function.
L295: def default_environment() -> Environment: Function `default_environment` utility or
script function.
L317: class Marker: Class (`Marker`) component used by the app (see file context: None).
L339: def __init__(self, marker: str) -> None: Function `__init__` utility or script
function.
L370: def _from_markers(cls, markers: MarkerList) -> Marker: Function `_from_markers`

```

utility or script function.

```
L379: def __str__(self) -> str:    Function `__str__`    utility or script function.
L382: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L385: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L388: def __eq__(self, other: object) -> bool:    Object (singleton).
L394: def __getstate__(self) -> str:    Function `__getstate__`    utility or script function.
L399: def __setstate__(self, state: object) -> None:    Object (singleton).
L423: def __and__(self, other: Marker) -> Marker:    Function `__and__`    utility or script
function.
L428: def __or__(self, other: Marker) -> Marker:    Function `__or__`    utility or script
function.
L433: def evaluate(    Function `evaluate`    utility or script function.
L482: def _repair_python_full_version(    Function `_repair_python_full_version`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/specifiers.py

```
L48: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L52: def _validate_spec(spec: object, /) -> TypeGuard[tuple[str, str]]:    Object (singleton).
L61: def _validate_pre(pre: object, /) -> TypeGuard[bool | None]:    Object (singleton).
L74: def _trim_release(release: tuple[int, ...]) -> tuple[int, ...]:    Function
`_trim_release`    utility or script function.
L82: class _BoundaryKind(enum.Enum):    Class (`_BoundaryKind`)    component used by the app
(see file context: None).
L90: class _BoundaryVersion:    Class (`_BoundaryVersion`)    component used by the app (see
file context: None).
L113: def __init__(self, version: Version, kind: _BoundaryKind) -> None:    Function
`__init__`    utility or script function.
L118: def _is_family(self, other: Version) -> bool:    Function `_is_family`    utility or
script function.
L133: def __eq__(self, other: object) -> bool:    Object (singleton).
L138: def __lt__(self, other: _BoundaryVersion | Version) -> bool:    Function `__lt__`
utility or script function.
L145: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L148: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L153: class _LowerBound:    Class (`_LowerBound`)    component used by the app (see file
context: None).
L163: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:    Function
`__init__`    utility or script function.
L167: def __eq__(self, other: object) -> bool:    Object (singleton).
L172: def __lt__(self, other: _LowerBound) -> bool:    Function `__lt__`    utility or script
function.
L185: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L188: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L194: class _UpperBound:    Class (`_UpperBound`)    component used by the app (see file
context: None).
L204: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:    Function
```

```

`__init__` utility or script function.
L208: def __eq__(self, other: object) -> bool: Object (singleton).
L213: def __lt__(self, other: _UpperBound) -> bool: Function `__lt__` utility or script
function.
L226: def __hash__(self) -> int: Function `__hash__` utility or script function.
L229: def __repr__(self) -> str: Function `__repr__` utility or script function.
L246: def _range_is_empty(lower: _LowerBound, upper: _UpperBound) -> bool: Function
`_range_is_empty` utility or script function.
L255: def _intersect_ranges( Function `_intersect_ranges` utility or script function.
L281: def _next_prefix_dev0(version: Version) -> Version: Function `_next_prefix_dev0`
utility or script function.
L287: def _base_dev0(version: Version) -> Version: Function `_base_dev0` utility or script
function.
L292: def _coerce_version(version: UnparsedVersion) -> Version | None: Function
`_coerce_version` utility or script function.
L301: def _public_version(version: Version) -> Version: Function `_public_version` utility
or script function.
L307: def _post_base(version: Version) -> Version: Function `_post_base` utility or script
function.
L315: def _earliest_prerelease(version: Version) -> Version: Function
`_earliest_prerelease` utility or script function.
L323: def _nearest_non_prerelease( Function `_nearest_non_prerelease` utility or script
function.
L344: class InvalidSpecifier(ValueError): Class (`InvalidSpecifier`) component used by the
app (see file context: None).
L356: class BaseSpecifier(metaclass=abc.ABCMeta): Class (`BaseSpecifier`) component used
by the app (see file context: None).
L361: def _str(self) -> str: Function `_str` utility or script function.
L366: def __str__(self) -> str: Function `__str__` utility or script function.
L373: def __hash__(self) -> int: Function `__hash__` utility or script function.
L379: def __eq__(self, other: object) -> bool: Object (singleton).
L389: def prereleases(self) -> bool | None: Function `prereleases` utility or script
function.
L397: def prereleases(self, value: bool) -> None: Function `prereleases` utility or script
function.
L404: def contains(self, item: str, prereleases: bool | None = None) -> bool: Function
`contains` utility or script function.
L410: def filter( Function `filter` utility or script function.
L418: def filter( Function `filter` utility or script function.
L426: def filter( Function `filter` utility or script function.
L438: class Specifier(BaseSpecifier): Class (`Specifier`) component used by the app (see
file context: None).
L573: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None: Function
`__init__` utility or script function.
L611: def _get_spec_version(self, version: str) -> Version | None: Function
`_get_spec_version` utility or script function.
L623: def _require_spec_version(self, version: str) -> Version: Function
`_require_spec_version` utility or script function.
L633: def _to_ranges(self) -> Sequence[_VersionRange]: Function `_to_ranges` utility or
script function.
L657: def _wildcard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]: Function

```

```

`_wildcard_ranges` utility or script function.
L670: def _standard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]: Function
`_standard_ranges` utility or script function.
L733: def prereleases(self) -> bool | None: Function `prereleases` utility or script
function.
L761: def prereleases(self, value: bool | None) -> None: Function `prereleases` utility or
script function.
L764: def __getstate__(self) -> tuple[tuple[str, str], bool | None]: Function
`__getstate__` utility or script function.
L770: def __setstate__(self, state: object) -> None: Object (singleton).
L805: def operator(self) -> str: Function `operator` utility or script function.
L814: def version(self) -> str: Function `version` utility or script function.
L822: def __repr__(self) -> str: Function `__repr__` utility or script function.
L840: def __str__(self) -> str: Function `__str__` utility or script function.
L851: def _canonical_spec(self) -> tuple[str, str]: Function `_canonical_spec` utility or
script function.
L864: def __hash__(self) -> int: Function `__hash__` utility or script function.
L867: def __eq__(self, other: object) -> bool: Object (singleton).
L896: def _get_operator(self, op: str) -> CallableOperator: Function `_get_operator`
utility or script function.
L902: def _compare_compatible(self, prospective: Version, spec: str) -> bool: Function
`_compare_compatible` utility or script function.
L922: def _get_wildcard_split(self, spec: str) -> tuple[list[str], int]: Function
`_get_wildcard_split` utility or script function.
L938: def _compare_equal(self, prospective: Version, spec: str) -> bool: Function
`_compare_equal` utility or script function.
L974: def _compare_not_equal(self, prospective: Version, spec: str) -> bool: Function
`_compare_not_equal` utility or script function.
L977: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool: Function
`_compare_less_than_equal` utility or script function.
L983: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
Function `_compare_greater_than_equal` utility or script function.
L989: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool: Function
`_compare_less_than` utility or script function.
L1014: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
Function `_compare_greater_than` utility or script function.
L1046: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
Function `_compare_arbitrary` utility or script function.
L1049: def __contains__(self, item: str | Version) -> bool: Function `__contains__`
utility or script function.
L1070: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
Function `contains` utility or script function.
L1098: def filter( Function `filter` utility or script function.
L1106: def filter( Function `filter` utility or script function.
L1113: def filter( Function `filter` utility or script function.
L1198: def _pep440_filter_prereleases( Function `_pep440_filter_prereleases` utility or
script function.
L1240: def _version_split(version: str) -> list[str]: Function `_version_split` utility or
script function.
L1262: def _version_join(components: list[str]) -> str: Function `_version_join` utility
or script function.

```



```

L1273: def _is_not_suffix(segment: str) -> bool:    Function `_is_not_suffix` utility or
script function.
L1279: def _numeric_prefix_len(split: list[str]) -> int:    Function `_numeric_prefix_len`
utility or script function.
L1293: def _left_pad(split: list[str], target_numeric_len: int) -> list[str]:    Function
`_left_pad` utility or script function.
L1307: def _operator_cost(op_entry: tuple[CallableOperator, str, str]) -> int:    Function
`_operator_cost` utility or script function.
L1334: class SpecifierSet(BaseSpecifier):    Class (`SpecifierSet`) component used by the app
(see file context: None).
L1362: def __init__(    Function `__init__` utility or script function.
L1407: def _canonical_specs(self) -> tuple[Specifier, ...]:    Function `_canonical_specs`
utility or script function.
L1417: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L1437: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility
or script function.
L1441: def __getstate__(self) -> tuple[tuple[Specifier, ...], bool | None]:    Function
`__getstate__` utility or script function.
L1447: def __setstate__(self, state: object) -> None:    Object (singleton).
L1504: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L1525: def __str__(self) -> str:    Function `__str__` utility or script function.
L1538: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L1541: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:    Function `__and__`
utility or script function.
L1574: def __eq__(self, other: object) -> bool:    Object (singleton).
L1600: def __len__(self) -> int:    Function `__len__` utility or script function.
L1604: def __iter__(self) -> Iterator[Specifier]:    Function `__iter__` utility or script
function.
L1614: def _get_ranges(self) -> Sequence[_VersionRange]:    Function `_get_ranges` utility or
script function.
L1636: def is_unsatisfiable(self) -> bool:    Function `is_unsatisfiable` utility or script
function.
L1669: def _check_prerelease_only_ranges(self) -> bool:    Function
`_check_prerelease_only_ranges` utility or script function.
L1682: def _check_arbitrary_unsatisfiable(self) -> bool:    Function
`_check_arbitrary_unsatisfiable` utility or script function.
L1721: def __contains__(self, item: UnparsedVersion) -> bool:    Function `__contains__`
utility or script function.
L1742: def contains(    Function `contains` utility or script function.
L1788: def filter(    Function `filter` utility or script function.
L1796: def filter(    Function `filter` utility or script function.
L1803: def filter(    Function `filter` utility or script function.
L1899: def _filter_versions(    Function `_filter_versions` utility or script function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/packaging/dependency_gr

oups.py

```

L19: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L28: class DuplicateGroupNames(ValueError):    Class (`DuplicateGroupNames`)    component used
by the app (see file context: None).
L34: class CyclicDependencyGroup(ValueError):    Class (`CyclicDependencyGroup`)    component
used by the app (see file context: None).
L39: def __init__(self, requested_group: str, group: str, include_group: str) -> None:
Function `__init__`    utility or script function.
L57: class InvalidDependencyGroupObject(ValueError):    Class (`InvalidDependencyGroupObject`)
component used by the app (see file context: None).
L69: class DependencyGroupInclude:    Class (`DependencyGroupInclude`)    component used by the
app (see file context: None).
L72: def __init__(self, include_group: str) -> None:    Function `__init__`    utility or script
function.
L80: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L84: class DependencyGroupResolver:    Class (`DependencyGroupResolver`)    component used by
the app (see file context: None).
L96: def __init__(    Function `__init__`    utility or script function.
L115: def lookup(self, group: str) -> tuple[Requirement | DependencyGroupInclude, ...]:
Function `lookup`    utility or script function.
L129: def resolve(self, group: str) -> tuple[Requirement, ...]:    Function `resolve`    utility
or script function.
L142: def _resolve(    Function `_resolve`    utility or script function.
L200: def _parse_group(    Function `_parse_group`    utility or script function.
L255: def resolve_dependency_groups(    Function `resolve_dependency_groups`    utility or
script function.
L277: def _normalize_name(name: str) -> str:    Function `_normalize_name`    utility or script
function.
L281: def _normalize_group_names(    Function `_normalize_group_names`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_tokenizer.py

```

L12: class Token:    Class (`Token`)    component used by the app (see file context: None).
L18: class ParserSyntaxError(Exception):    Class (`ParserSyntaxError`)    component used by the
app (see file context: None).
L21: def __init__(    Function `__init__`    utility or script function.
L34: def __str__(self) -> str:    Function `__str__`    utility or script function.
L91: class Tokenizer:    Class (`Tokenizer`)    component used by the app (see file context:
None).
L98: def __init__(    Function `__init__`    utility or script function.
L109: def consume(self, name: str) -> None:    Function `consume`    utility or script function.
L114: def check(self, name: str, *, peek: bool = False) -> bool:    Function `check`    utility
or script function.
L135: def expect(self, name: str, *, expected: str) -> Token:    Function `expect`    utility or

```

```

script function.
L144: def read(self) -> Token:    Function `read`    utility or script function.
L154: def raise_syntax_error(    Function `raise_syntax_error`    utility or script function.
L173: def enclosing_tokens(    Function `enclosing_tokens`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_parser.py

```

L15: class Node:    Class (`Node`)    component used by the app (see file context: None).
L18: def __init__(self, value: str) -> None:    Function `__init__`    utility or script
function.
L21: def __str__(self) -> str:    Function `__str__`    utility or script function.
L24: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L27: def serialize(self) -> str:    Function `serialize`    utility or script function.
L30: def __getstate__(self) -> str:    Function `__getstate__`    utility or script function.
L34: def _restore_value(self, value: object) -> None:    Object (singleton).
L41: def __setstate__(self, state: object) -> None:    Object (singleton).
L59: class Variable(Node):    Class (`Variable`)    component used by the app (see file context:
None).
L62: def serialize(self) -> str:    Function `serialize`    utility or script function.
L66: class Value(Node):    Class (`Value`)    component used by the app (see file context:
None).
L69: def serialize(self) -> str:    Function `serialize`    utility or script function.
L73: class Op(Node):    Class (`Op`)    component used by the app (see file context: None).
L76: def serialize(self) -> str:    Function `serialize`    utility or script function.
L87: class ParsedRequirement(NamedTuple):    Class (`ParsedRequirement`)    component used by
the app (see file context: None).
L98: def parse_requirement(source: str) -> ParsedRequirement:    Function `parse_requirement`
utility or script function.
L102: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:    Function
`_parse_requirement`    utility or script function.
L123: def _parse_requirement_details(    Function `_parse_requirement_details`    utility or
script function.
L176: def _parse_requirement_marker(    Function `_parse_requirement_marker`    utility or
script function.
L197: def _parse_extras(tokenizer: Tokenizer) -> list[str]:    Function `_parse_extras`
utility or script function.
L216: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:    Function
`_parse_extras_list`    utility or script function.
L243: def _parse_specifier(tokenizer: Tokenizer) -> str:    Function `_parse_specifier`
utility or script function.
L260: def _parse_version_many(tokenizer: Tokenizer) -> str:    Function `_parse_version_many`
utility or script function.
L292: def parse_marker(source: str) -> MarkerList:    Function `parse_marker`    utility or
script function.
L296: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:    Function
`_parse_full_marker`    utility or script function.
L302: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:    Function `_parse_marker`

```

```

utility or script function.
L314: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:    Function
`_parse_marker_atom` utility or script function.
L336: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:    Function
`_parse_marker_item` utility or script function.
L350: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar:    # noqa: RET503    Function
`_parse_marker_var` utility or script function.
L364: def process_env_var(env_var: str) -> Variable:    Function `process_env_var` utility or
script function.
L371: def process_python_str(python_str: str) -> Value:    Function `process_python_str`
utility or script function.
L376: def _parse_marker_op(tokenizer: Tokenizer) -> Op:    Function `_parse_marker_op`
utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/packaging/utils.py

```

L27: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L39: class InvalidName(ValueError):    Class (`InvalidName`) component used by the app (see
file context: None).
L45: class InvalidWheelFilename(ValueError):    Class (`InvalidWheelFilename`) component used
by the app (see file context: None).
L51: class InvalidSdistFilename(ValueError):    Class (`InvalidSdistFilename`) component used
by the app (see file context: None).
L66: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
Function `canonicalize_name` utility or script function.
L103: def is_normalized_name(name: str) -> bool:    Function `is_normalized_name` utility or
script function.
L119: def canonicalize_version(    Function `canonicalize_version` utility or script
function.
L157: def parse_wheel_filename(    Function `parse_wheel_filename` utility or script
function.
L249: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:    Function
`parse_sdist_filename` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/version.py

```

L37: def _deprecated(message: str) -> object:    Object (singleton).
L38: def decorator(func: Callable[[...], object]) -> object:    Object (singleton).
L40: def wrapper(*args: object, **kwargs: object) -> object:    Object (singleton).
L66: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L81: class _VersionReplace(TypedDict, total=False):    Class (`_VersionReplace`) component
used by the app (see file context: None).
L90: def normalize_pre(letter: str, /) -> str:    Function `normalize_pre` utility or script
function.
L111: def parse(version: str) -> Version:    Function `parse` utility or script function.

```

```

L125: class InvalidVersion(ValueError):  Class (`InvalidVersion`) component used by the app
(see file context: None).
L135: class _BaseVersion:  Class (`_BaseVersion`) component used by the app (see file
context: None).
L144: def _key(self) -> tuple[Any, ...]: ...  Function `_key` utility or script function.
L146: def __hash__(self) -> int:  Function `__hash__` utility or script function.
L152: def __lt__(self, other: _BaseVersion) -> bool:  Function `__lt__` utility or script
function.
L158: def __le__(self, other: _BaseVersion) -> bool:  Function `__le__` utility or script
function.
L164: def __eq__(self, other: object) -> bool:  Object (singleton).
L170: def __ge__(self, other: _BaseVersion) -> bool:  Function `__ge__` utility or script
function.
L176: def __gt__(self, other: _BaseVersion) -> bool:  Function `__gt__` utility or script
function.
L182: def __ne__(self, other: object) -> bool:  Object (singleton).
L266: def _validate_epoch(value: object, /) -> int:  Object (singleton).
L274: def _validate_release(value: object, /) -> tuple[int, ...]:  Object (singleton).
L286: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
Object (singleton).
L299: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:  Object
(singleton).
L308: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:  Object
(singleton).
L317: def _validate_local(value: object, /) -> LocalType | None:  Object (singleton).
L327: class _Version(NamedTuple):  Class (`_Version`) component used by the app (see file
context: None).
L336: class Version(_BaseVersion):  Class (`Version`) component used by the app (see file
context: None).
L404: def __init__(self, version: str) -> None:  Function `__init__` utility or script
function.
L455: def from_parts(  Function `from_parts` utility or script function.
L501: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:  Function
`__replace__` utility or script function.
L560: def _key(self) -> CmpKey:  Function `_key` utility or script function.
L574: def __hash__(self) -> int:  Function `__hash__` utility or script function.
L592: def __lt__(self, other: _BaseVersion) -> bool:  Function `__lt__` utility or script
function.
L619: def __le__(self, other: _BaseVersion) -> bool:  Function `__le__` utility or script
function.
L646: def __eq__(self, other: object) -> bool:  Object (singleton).
L673: def __ge__(self, other: _BaseVersion) -> bool:  Function `__ge__` utility or script
function.
L700: def __gt__(self, other: _BaseVersion) -> bool:  Function `__gt__` utility or script
function.
L727: def __ne__(self, other: object) -> bool:  Object (singleton).
L754: def __getstate__(  Function `__getstate__` utility or script function.
L776: def __setstate__(self, state: object) -> None:  Object (singleton).
L823: def _version(self) -> _Version:  Function `_version` utility or script function.
L830: def _version(self, value: _Version) -> None:  Function `_version` utility or script
function.

```

```

L840: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L848: def __str__(self) -> str:    Function `__str__` utility or script function.
L880: def _str(self) -> str:    Function `_str` utility or script function.
L885: def epoch(self) -> int:    Function `epoch` utility or script function.
L896: def release(self) -> tuple[int, ...]:    Function `release` utility or script function.
L912: def pre(self) -> tuple[Literal["a", "b", "rc"], int] | None:    Function `pre` utility
or script function.
L927: def post(self) -> int | None:    Function `post` utility or script function.
L938: def dev(self) -> int | None:    Function `dev` utility or script function.
L949: def local(self) -> str | None:    Function `local` utility or script function.
L963: def public(self) -> str:    Function `public` utility or script function.
L979: def base_version(self) -> str:    Function `base_version` utility or script function.
L1000: def is_prerelease(self) -> bool:    Function `is_prerelease` utility or script
function.
L1017: def is_postrelease(self) -> bool:    Function `is_postrelease` utility or script
function.
L1028: def is_devrelease(self) -> bool:    Function `is_devrelease` utility or script
function.
L1039: def major(self) -> int:    Function `major` utility or script function.
L1048: def minor(self) -> int:    Function `minor` utility or script function.
L1059: def micro(self) -> int:    Function `micro` utility or script function.
L1070: class _TrimmedRelease(Version):    Class (`_TrimmedRelease`) component used by the app
(see file context: None).
L1073: def __init__(self, version: str | Version) -> None:    Function `__init__` utility or
script function.
L1086: def release(self) -> tuple[int, ...]:    Function `release` utility or script
function.
L1104: def _parse_letter_version(    Function `_parse_letter_version` utility or script
function.
L1131: def _parse_local_version(local: str | None) -> LocalType | None:    Function
`_parse_local_version` utility or script function.
L1157: def _cmpkey(    Function `_cmpkey` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_structures.py

```

L18: class InfinityType:    Class (`InfinityType`) component used by the app (see file
context: None).
L21: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L25: class NegativeInfinityType:    Class (`NegativeInfinityType`) component used by the app
(see file context: None).
L28: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/packaging/tags.py

```

L54: def __dir__() -> list[str]:    Function `__dir__` utility or script function.

```

```

L75: def _compute_32_bit_interpreter() -> bool:    Function `_compute_32_bit_interpreter`
utility or script function.
L82: class UnsortedTagsError(ValueError):    Class (`UnsortedTagsError`) component used by
the app (see file context: None).
L88: class Tag:    Class (`Tag`) component used by the app (see file context: None).
L108: def __init__(self, interpreter: str, abi: str, platform: str) -> None:    Function
`__init__` utility or script function.
L128: def interpreter(self) -> str:    Function `interpreter` utility or script function.
L137: def abi(self) -> str:    Function `abi` utility or script function.
L144: def platform(self) -> str:    Function `platform` utility or script function.
L150: def __eq__(self, other: object) -> bool:    Object (singleton).
L161: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L164: def __str__(self) -> str:    Function `__str__` utility or script function.
L167: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L170: def __getstate__(self) -> tuple[str, str, str]:    Function `__getstate__` utility or
script function.
L175: def __setstate__(self, state: object) -> None:    Object (singleton).
L203: def parse_tag(tag: str, *, validate_order: bool = False) -> frozenset[Tag]:    Function
`parse_tag` utility or script function.
L240: def _get_config_var(name: str, warn: bool = False) -> int | str | None:    Function
`_get_config_var` utility or script function.
L249: def _normalize_string(string: str) -> str:    Function `_normalize_string` utility or
script function.
L253: def _is_threaded_cpython(abis: list[str]) -> bool:    Function `_is_threaded_cpython`
utility or script function.
L269: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3_applies` utility or script function.
L279: def _abi3t_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3t_applies` utility or script function.
L292: def _cpython_abis(py_version: PythonVersion, warn: bool = False) -> list[str]:
Function `_cpython_abis` utility or script function.
L325: def cpython_tags(    Function `cpython_tags` utility or script function.
L404: def _generic_abi() -> list[str]:    Function `_generic_abi` utility or script function.
L445: def generic_tags(    Function `generic_tags` utility or script function.
L486: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:    Function
`_py_interpreter_range` utility or script function.
L501: def compatible_tags(    Function `compatible_tags` utility or script function.
L536: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:    Function
`_mac_arch` utility or script function.
L546: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:    Function
`_mac_binary_formats` utility or script function.
L578: def mac_platforms(    Function `mac_platforms` utility or script function.
L667: def ios_platforms(    Function `ios_platforms` utility or script function.
L729: def android_platforms(    Function `android_platforms` utility or script function.
L766: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:    Function
`_linux_platforms` utility or script function.
L785: def _emscripten_platforms() -> Iterator[str]:    Function `_emscripten_platforms`
utility or script function.
L794: def _generic_platforms() -> Iterator[str]:    Function `_generic_platforms` utility or
script function.
L798: def platform_tags() -> Iterator[str]:    Function `platform_tags` utility or script

```



```

function.
L816: def interpreter_name() -> str:    Function `interpreter_name`    utility or script
function.
L829: def interpreter_version(*, warn: bool = False) -> str:    Function `interpreter_version`
utility or script function.
L841: def _version_nodot(version: PythonVersion) -> str:    Function `_version_nodot`    utility
or script function.
L845: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:    Function `sys_tags`    utility or
script function.
L889: def create_compatible_tags_selector(    Function `create_compatible_tags_selector`
Creates a resource or document.
L919: def selector(    Function `selector`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/errors.py

```

L11: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L19: class ExceptionGroup(Exception):    Class (`ExceptionGroup`)    component used by the app
(see file context: None).
L29: def __init__(self, message: str, exceptions: list[Exception]) -> None:    Function
`__init__`    utility or script function.
L33: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L38: class _ErrorCollector:    Class (`_ErrorCollector`)    component used by the app (see file
context: None).
L59: def finalize(self, msg: str) -> None:    Function `finalize`    utility or script function.
L65: def on_exit(self, msg: str) -> typing.Generator[_ErrorCollector, None, None]:    Function
`on_exit`    utility or script function.
L75: def collect(self, *err_cls: type[Exception]) -> typing.Generator[None, None, None]:
Function `collect`    utility or script function.
L89: def error(    Function `error`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/_musllinux.py

```

L18: class _MuslVersion(NamedTuple):    Class (`_MuslVersion`)    component used by the app (see
file context: None).
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:    Function
`_parse_musl_version`    utility or script function.
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:    Function
`_get_musl_version`    utility or script function.
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/requirements.py

```

L20: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L24: class InvalidRequirement(ValueError):    Class (`InvalidRequirement`)    component used by
the app (see file context: None).
L30: class Requirement:    Class (`Requirement`)    component used by the app (see file context:
None).
L53: def __init__(self, requirement_string: str) -> None:    Function `__init__`    utility or
script function.
L68: def _iter_parts(self, name: str) -> Iterator[str]:    Function `_iter_parts`    utility or
script function.
L86: def __getstate__(self) -> str:    Function `__getstate__`    utility or script function.
L91: def __setstate__(self, state: object) -> None:    Object (singleton).
L110: def __str__(self) -> str:    Function `__str__`    utility or script function.
L113: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L116: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L119: def __eq__(self, other: object) -> bool:    Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/pylock.py

```

L54: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L62: class _FromMappingProtocol(Protocol):    # pragma: no cover    Class
(`_FromMappingProtocol`)    component used by the app (see file context: None).
L64: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict`    utility
or script function.
L73: def is_valid_pylock_path(path: Path) -> bool:    Function `is_valid_pylock_path`    utility
or script function.
L78: def _toml_key(key: str) -> str:    Function `_toml_key`    utility or script function.
L82: def _toml_value(key: str, value: Any) -> Any:    # noqa: ANN401    Function `_toml_value`
utility or script function.
L90: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_toml_dict_factory`    utility or script function.
L98: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get`    utility or script function.
L111: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required`    utility or script function.
L118: def _get_sequence(    Function `_get_sequence`    utility or script function.
L140: def _get_as(    Function `_get_as`    utility or script function.
L159: def _get_required_as(    Function `_get_required_as`    utility or script function.
L172: def _get_sequence_as(    Function `_get_sequence_as`    utility or script function.
L191: def _get_object(    Function `_get_object`    utility or script function.
L203: def _get_sequence_of_objects(    Function `_get_sequence_of_objects`    utility or script
function.

```

```

L219: def _get_required_sequence_of_objects(    Function `_get_required_sequence_of_objects`
utility or script function.
L229: def _validate_normalized_name(name: str) -> NormalizedName:    Function
`_validate_normalized_name` utility or script function.
L236: def _validate_path_url(path: str | None, url: str | None) -> None:    Function
`_validate_path_url` utility or script function.
L241: def _path_name(path: str | None) -> str | None:    Function `_path_name` utility or
script function.
L254: def _url_name(url: str | None) -> str | None:    Function `_url_name` utility or script
function.
L261: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:    Function
`_validate_hashes` utility or script function.
L269: class PylockValidationError(Exception):    Class (`PylockValidationError`) component
used by the app (see file context: None).
L275: def __init__(    Function `__init__` utility or script function.
L293: def __str__(self) -> str:    Function `__str__` utility or script function.
L299: class _PylockRequiredKeyError(PylockValidationError):    Class
(`_PylockRequiredKeyError`) component used by the app (see file context: None).
L300: def __init__(self, key: str) -> None:    Function `__init__` utility or script
function.
L304: class PylockUnsupportedVersionError(PylockValidationError):    Class
(`PylockUnsupportedVersionError`) component used by the app (see file context: None).
L308: class PylockSelectError(Exception):    Class (`PylockSelectError`) component used by
the app (see file context: None).
L313: class PackageVcs:    Class (`PackageVcs`) component used by the app (see file context:
None).
L321: def __init__(    Function `__init__` utility or script function.
L340: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L354: class PackageDirectory:    Class (`PackageDirectory`) component used by the app (see
file context: None).
L359: def __init__(    Function `__init__` utility or script function.
L372: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L381: class PackageArchive:    Class (`PackageArchive`) component used by the app (see file
context: None).
L389: def __init__(    Function `__init__` utility or script function.
L408: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L422: class PackageSdist:    Class (`PackageSdist`) component used by the app (see file
context: None).
L430: def __init__(    Function `__init__` utility or script function.
L449: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L462: def filename(self) -> str:    Function `filename` utility or script function.
L471: class PackageWheel:    Class (`PackageWheel`) component used by the app (see file
context: None).
L479: def __init__(    Function `__init__` utility or script function.
L498: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L511: def filename(self) -> str:    Function `filename` utility or script function.

```

```

L520: class Package:    Class (`Package`) component used by the app (see file context: None).
L535: def __init__(    Function `__init__` utility or script function.
L568: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L649: def is_direct(self) -> bool:    Function `is_direct` utility or script function.
L654: class Pylock:    Class (`Pylock`) component used by the app (see file context: None).
L667: def __init__(    Function `__init__` utility or script function.
L692: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L715: def from_dict(cls, d: Mapping[str, Any], /) -> Self:    Function `from_dict` utility or
script function.
L723: def to_dict(self) -> Mapping[str, Any]:    Function `to_dict` utility or script
function.
L727: def validate(self) -> None:    Function `validate` utility or script function.
L733: def select(    Function `select` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):    Class (`SPDXLicense`) component used by the app (see
file context: None).
L10: class SPDXException(TypedDict):    Class (`SPDXException`) component used by the app
(see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/packaging/licenses/__init___.py

```

L47: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L60: class InvalidLicenseExpression(ValueError):    Class (`InvalidLicenseExpression`)
component used by the app (see file context: None).
L71: def canonicalize_license_expression(    Function `canonicalize_license_expression`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/__pip-runner__.py

```

L15: def version_str(version):    # type: ignore    Function `version_str` utility or script
function.
L36: class PipImportRedirectingFinder:    Class (`PipImportRedirectingFinder`) component used

```

by the app (see file context: None).

```
L38: def find_spec(self, fullname, path=None, target=None): # type: ignore    Function
`find_spec`    utility or script function.
```

Q_base appwrite/.venv/lib/python3.12/site-packages/pip/__init__.py

```
L6: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main
routine.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/pyproject.py

```
L18: def _is_list_of_str(obj: Any) -> bool:    Function `_is_list_of_str`    utility or script
function.
```

```
L22: def make_pyproject_path(unpacked_source_directory: str) -> str:    Function
`make_pyproject_path`    utility or script function.
```

```
L31: def load_pyproject_toml(    Function `load_pyproject_toml`    Loads data from storage or
remote.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/build_env.py

```
L44: class ExtraEnviron(TypedDict, total=False):    Class (`ExtraEnviron`)    component used by
the app (see file context: None).
```

```
L51: def _dedup(a: str, b: str) -> tuple[str] | tuple[str, str]:    Function `_dedup`    utility
or script function.
```

```
L55: class _Prefix:    Class (`_Prefix`)    component used by the app (see file context: None).
```

```
L56: def __init__(self, path: str) -> None:    Function `__init__`    utility or script
function.
```

```
L64: def get_runnable_pip() -> str:    Function `get_runnable_pip`    Returns or fetches data.
```

```
L80: def _get_system_sitepackages() -> set[str]:    Function `_get_system_sitepackages`
utility or script function.
```

```
L100: class BuildEnvironmentInstaller(Protocol):    Class (`BuildEnvironmentInstaller`)
component used by the app (see file context: None).
```

```
L106: def install(    Function `install`    utility or script function.
```

```
L116: class SubprocessBuildEnvironmentInstaller:    Class
(`SubprocessBuildEnvironmentInstaller`)    component used by the app (see file context: None).
```

```
L121: def __init__(    Function `__init__`    utility or script function.
```

```
L131: def _deprecation_constraint_check(self) -> None:    Function
`_deprecation_constraint_check`    utility or script function.
```

```
L160: def install(    Function `install`    utility or script function.
```

```
L266: class InprocessBuildEnvironmentInstaller:    Class
(`InprocessBuildEnvironmentInstaller`)    component used by the app (see file context: None).
```

```

L280: def __init__(    Function `__init__`    utility or script function.
L320: def install(    Function `install`    utility or script function.
L372: def _install_impl(self, requirements: Iterable[str], prefix: _Prefix) -> None:
Function `_install_impl`    utility or script function.
L413: def _make_resolver(self) -> BaseResolver:    Function `_make_resolver`    utility or
script function.
L437: class BuildEnvironment:    Class (`BuildEnvironment`)    component used by the app (see
file context: None).
L440: def __init__(self, installer: BuildEnvironmentInstaller) -> None:    Function `__init__`
utility or script function.
L495: def __enter__(self) -> None:    Function `__enter__`    utility or script function.
L516: def __exit__(    Function `__exit__`    utility or script function.
L528: def check_requirements(    Function `check_requirements`    utility or script function.
L562: def install_requirements(    Function `install_requirements`    utility or script
function.
L578: class NoOpBuildEnvironment(BuildEnvironment):    Class (`NoOpBuildEnvironment`)
component used by the app (see file context: None).
L581: def __init__(self) -> None:    Function `__init__`    utility or script function.
L584: def __enter__(self) -> None:    Function `__enter__`    utility or script function.
L587: def __exit__(    Function `__exit__`    utility or script function.
L595: def cleanup(self) -> None:    Function `cleanup`    utility or script function.
L598: def install_requirements(    Function `install_requirements`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/configuration.py

```

L53: def _normalize_name(name: str) -> str:    Function `_normalize_name`    utility or script
function.
L60: def _disassemble_key(name: str) -> list[str]:    Function `_disassemble_key`    utility or
script function.
L70: def get_configuration_files() -> dict[Kind, list[str]]:    Function
`get_configuration_files`    Returns or fetches data.
L89: class Configuration:    Class (`Configuration`)    component used by the app (see file
context: None).
L103: def __init__(self, isolated: bool, load_only: Kind | None = None) -> None:    Function
`__init__`    utility or script function.
L124: def load(self) -> None:    Function `load`    Loads data from storage or remote.
L130: def get_file_to_edit(self) -> str | None:    Function `get_file_to_edit`    Returns or
fetches data.
L139: def items(self) -> Iterable[tuple[str, Any]]:    Function `items`    utility or script
function.
L145: def get_value(self, key: str) -> Any:    Function `get_value`    Returns or fetches data.
L160: def set_value(self, key: str, value: Any) -> None:    Function `set_value`    Sets or
updates a value.
L180: def unset_value(self, key: str) -> None:    Function `unset_value`    utility or script

```

```

function.
L214: def save(self) -> None:    Function `save`    Saves data to storage or remote.
L238: def _ensure_have_load_only(self) -> None:    Function `_ensure_have_load_only`    utility
or script function.
L244: def _dictionary(self) -> dict[str, dict[str, Any]]:    Function `_dictionary`    utility
or script function.
L255: def _load_config_files(self) -> None:    Function `_load_config_files`    utility or
script function.
L278: def _load_file(self, variant: Kind, fname: str) -> RawConfigParser:    Function
`_load_file`    utility or script function.
L289: def _construct_parser(self, fname: str) -> RawConfigParser:    Function
`_construct_parser`    utility or script function.
L310: def _load_environment_vars(self) -> None:    Function `_load_environment_vars`    utility
or script function.
L317: def _normalized_keys(    Function `_normalized_keys`    utility or script function.
L331: def get_environ_vars(self) -> Iterable[tuple[str, str]]:    Function `get_environ_vars`
Returns or fetches data.
L340: def iter_config_files(self) -> Iterable[tuple[Kind, list[str]]]:    Function
`iter_config_files`    utility or script function.
L372: def get_values_in_config(self, variant: Kind) -> dict[str, Any]:    Function
`get_values_in_config`    Returns or fetches data.
L376: def _get_parser_to_modify(self) -> tuple[str, RawConfigParser]:    Function
`_get_parser_to_modify`    utility or script function.
L390: def _mark_as_modified(self, fname: str, parser: RawConfigParser) -> None:    Function
`_mark_as_modified`    utility or script function.
L395: def __repr__(self) -> str:    Function `__repr__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/wheel_builder
.py

```

L34: def _contains_egg_info(s: str) -> bool:    Function `_contains_egg_info`    utility or
script function.
L42: def _should_cache(    Function `_should_cache`    utility or script function.
L73: def _get_cache_dir(    Function `_get_cache_dir`    utility or script function.
L89: def _verify_one(req: InstallRequirement, wheel_path: str) -> None:    Function
`_verify_one`    utility or script function.
L118: def _build_one(    Function `_build_one`    utility or script function.
L152: def _build_one_inside_env(    Function `_build_one_inside_env`    utility or script
function.
L204: def build(    Function `build`    Constructs or prepares an object.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/exceptions.py


```

L44: def _is_kebab_case(s: str) -> bool:    Function `_is_kebab_case` utility or script
function.
L48: def _prefix_with_indent(    Function `_prefix_with_indent` utility or script function.
L65: class PipError(Exception):    Class (`PipError`) component used by the app (see file
context: None).
L69: class DiagnosticPipError(PipError):    Class (`DiagnosticPipError`) component used by
the app (see file context: None).
L82: def __init__(    Function `__init__` utility or script function.
L112: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L123: def __rich_console__(    Function `__rich_console__` utility or script function.
L187: class ConfigurationError(PipError):    Class (`ConfigurationError`) component used by
the app (see file context: None).
L191: class InstallationError(PipError):    Class (`InstallationError`) component used by the
app (see file context: None).
L195: class FailedToPrepareCandidate(InstallationError):    Class (`FailedToPrepareCandidate`)
component used by the app (see file context: None).
L203: def __init__(    Function `__init__` utility or script function.
L212: class MissingPyProjectBuildRequires(DiagnosticPipError):    Class
(`MissingPyProjectBuildRequires`) component used by the app (see file context: None).
L217: def __init__(self, *, package: str) -> None:    Function `__init__` utility or script
function.
L229: class InvalidPyProjectBuildRequires(DiagnosticPipError):    Class
(`InvalidPyProjectBuildRequires`) component used by the app (see file context: None).
L234: def __init__(self, *, package: str, reason: str) -> None:    Function `__init__`
utility or script function.
L246: class NoneMetadataError(PipError):    Class (`NoneMetadataError`) component used by the
app (see file context: None).
L255: def __init__(    Function `__init__` utility or script function.
L268: def __str__(self) -> str:    Function `__str__` utility or script function.
L274: class UserInstallationInvalid(InstallationError):    Class (`UserInstallationInvalid`)
component used by the app (see file context: None).
L277: def __str__(self) -> str:    Function `__str__` utility or script function.
L281: class InvalidSchemeCombination(InstallationError):    Class (`InvalidSchemeCombination`)
component used by the app (see file context: None).
L282: def __str__(self) -> str:    Function `__str__` utility or script function.
L287: class DistributionNotFound(InstallationError):    Class (`DistributionNotFound`)
component used by the app (see file context: None).
L291: class RequirementsFileParseError(InstallationError):    Class
(`RequirementsFileParseError`) component used by the app (see file context: None).
L295: class BestVersionAlreadyInstalled(PipError):    Class (`BestVersionAlreadyInstalled`)
component used by the app (see file context: None).
L300: class BadCommand(PipError):    Class (`BadCommand`) component used by the app (see file
context: None).
L304: class CommandError(PipError):    Class (`CommandError`) component used by the app (see
file context: None).
L308: class PreviousBuildDirError(PipError):    Class (`PreviousBuildDirError`) component
used by the app (see file context: None).
L312: class NetworkConnectionError(PipError):    Class (`NetworkConnectionError`) component
used by the app (see file context: None).
L315: def __init__(    Function `__init__` utility or script function.
L336: def __str__(self) -> str:    Function `__str__` utility or script function.

```

```

L340: class InvalidWheelFilename(InstallationError):  Class (`InvalidWheelFilename`)
component used by the app (see file context: None).
L344: class UnsupportedWheel(InstallationError):  Class (`UnsupportedWheel`) component used
by the app (see file context: None).
L348: class InvalidWheel(InstallationError):  Class (`InvalidWheel`) component used by the
app (see file context: None).
L351: def __init__(self, location: str, name: str):  Function `__init__` utility or script
function.
L355: def __str__(self) -> str:  Function `__str__` utility or script function.
L359: class MetadataInconsistent(InstallationError):  Class (`MetadataInconsistent`)
component used by the app (see file context: None).
L367: def __init__(  Function `__init__` utility or script function.
L375: def __str__(self) -> str:  Function `__str__` utility or script function.
L382: class MetadataInvalid(InstallationError):  Class (`MetadataInvalid`) component used
by the app (see file context: None).
L385: def __init__(self, ireq: InstallRequirement, error: str) -> None:  Function `__init__`
utility or script function.
L389: def __str__(self) -> str:  Function `__str__` utility or script function.
L393: class InstallationSubprocessError(DiagnosticPipError, InstallationError):  Class
(`InstallationSubprocessError`) component used by the app (see file context: None).
L398: def __init__(  Function `__init__` utility or script function.
L430: def __str__(self) -> str:  Function `__str__` utility or script function.
L434: class MetadataGenerationFailed(DiagnosticPipError, InstallationError):  Class
(`MetadataGenerationFailed`) component used by the app (see file context: None).
L437: def __init__(  Function `__init__` utility or script function.
L449: def __str__(self) -> str:  Function `__str__` utility or script function.
L453: class HashErrors(InstallationError):  Class (`HashErrors`) component used by the app
(see file context: None).
L456: def __init__(self) -> None:  Function `__init__` utility or script function.
L459: def append(self, error: HashError) -> None:  Function `append` utility or script
function.
L462: def __str__(self) -> str:  Function `__str__` utility or script function.
L472: def __bool__(self) -> bool:  Function `__bool__` utility or script function.
L476: class HashError(InstallationError):  Class (`HashError`) component used by the app
(see file context: None).
L497: def body(self) -> str:  Function `body` utility or script function.
L509: def __str__(self) -> str:  Function `__str__` utility or script function.
L512: def _requirement_name(self) -> str:  Function `_requirement_name` utility or script
function.
L522: class VcsHashUnsupported(HashError):  Class (`VcsHashUnsupported`) component used by
the app (see file context: None).
L533: class DirectoryUrlHashUnsupported(HashError):  Class (`DirectoryUrlHashUnsupported`)
component used by the app (see file context: None).
L544: class HashMissing(HashError):  Class (`HashMissing`) component used by the app (see
file context: None).
L558: def __init__(self, gotten_hash: str) -> None:  Function `__init__` utility or script
function.
L565: def body(self) -> str:  Function `body` utility or script function.
L586: class HashUnpinned(HashError):  Class (`HashUnpinned`) component used by the app (see
file context: None).
L597: class HashMismatch(HashError):  Class (`HashMismatch`) component used by the app (see

```

```

file context: None).
L615: def __init__(self, allowed: dict[str, list[str]], gots: dict[str, _Hash]) -> None:
Function `__init__` utility or script function.
L625: def body(self) -> str: Function `body` utility or script function.
L628: def _hash_comparison(self) -> str: Function `_hash_comparison` utility or script
function.
L640: def hash_then_or(hash_name: str) -> chain[str]: Function `hash_then_or` utility or
script function.
L655: class UnsupportedPythonVersion(InstallationError): Class (`UnsupportedPythonVersion`)
component used by the app (see file context: None).
L660: class ConfigurationFileCouldNotBeLoaded(ConfigurationError): Class
(`ConfigurationFileCouldNotBeLoaded`) component used by the app (see file context: None).
L663: def __init__( Function `__init__` utility or script function.
L674: def __str__(self) -> str: Function `__str__` utility or script function.
L690: class ExternallyManagedEnvironment(DiagnosticPipError): Class
(`ExternallyManagedEnvironment`) component used by the app (see file context: None).
L702: def __init__(self, error: str | None) -> None: Function `__init__` utility or script
function.
L720: def _iter_externally_managed_error_keys() -> Iterator[str]: Function
`_iter_externally_managed_error_keys` utility or script function.
L742: def from_config( Function `from_config` utility or script function.
L763: class UninstallMissingRecord(DiagnosticPipError): Class (`UninstallMissingRecord`)
component used by the app (see file context: None).
L766: def __init__(self, *, distribution: BaseDistribution) -> None: Function `__init__`
utility or script function.
L790: class LegacyDistutilsInstall(DiagnosticPipError): Class (`LegacyDistutilsInstall`)
component used by the app (see file context: None).
L793: def __init__(self, *, distribution: BaseDistribution) -> None: Function `__init__`
utility or script function.
L805: class InvalidInstalledPackage(DiagnosticPipError): Class (`InvalidInstalledPackage`)
component used by the app (see file context: None).
L808: def __init__( Function `__init__` utility or script function.
L835: class IncompleteDownloadError(DiagnosticPipError): Class (`IncompleteDownloadError`)
component used by the app (see file context: None).
L841: def __init__(self, download: _FileDownload) -> None: Function `__init__` utility or
script function.
L869: class ResolutionTooDeepError(DiagnosticPipError): Class (`ResolutionTooDeepError`)
component used by the app (see file context: None).
L874: def __init__(self) -> None: Function `__init__` utility or script function.
L889: class InstallWheelBuildError(DiagnosticPipError): Class (`InstallWheelBuildError`)
component used by the app (see file context: None).
L892: def __init__(self, failed: list[InstallRequirement]) -> None: Function `__init__`
utility or script function.
L903: class InvalidEggFragment(DiagnosticPipError): Android UI component
(`InvalidEggFragment`) activity/fragment presenting screens to the user.
L906: def __init__(self, link: Link, fragment: str) -> None: Function `__init__` utility
or script function.
L926: class BuildDependencyInstallError(DiagnosticPipError): Class
(`BuildDependencyInstallError`) component used by the app (see file context: None).
L931: def __init__( Function `__init__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/__init__.py

```
L10: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main routine.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cache.py

```
L27: def _hash_dict(d: dict[str, str]) -> str:    Function `_hash_dict`    utility or script function.
L33: class Cache:    Class (`Cache`)    component used by the app (see file context: None).
L39: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script function.
L44: def _get_cache_path_parts(self, link: Link) -> list[str]:    Function `_get_cache_path_parts`    utility or script function.
L77: def _get_candidates(self, link: Link, canonical_package_name: str) -> list[Any]:    Function `_get_candidates`    utility or script function.
L87: def get_path_for_link(self, link: Link) -> str:    Function `get_path_for_link`    Returns or fetches data.
L91: def get(    Function `get`    Returns or fetches data.
L103: class SimpleWheelCache(Cache):    Class (`SimpleWheelCache`)    component used by the app (see file context: None).
L106: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script function.
L109: def get_path_for_link(self, link: Link) -> str:    Function `get_path_for_link`    Returns or fetches data.
L129: def get(    Function `get`    Returns or fetches data.
L173: class EphemWheelCache(SimpleWheelCache):    Class (`EphemWheelCache`)    component used by the app (see file context: None).
L176: def __init__(self) -> None:    Function `__init__`    utility or script function.
L185: class CacheEntry:    Class (`CacheEntry`)    component used by the app (see file context: None).
L186: def __init__(    Function `__init__`    utility or script function.
L209: class WheelCache(Cache):    Class (`WheelCache`)    component used by the app (see file context: None).
L216: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script function.
L221: def get_path_for_link(self, link: Link) -> str:    Function `get_path_for_link`    Returns or fetches data.
L224: def get_ephem_path_for_link(self, link: Link) -> str:    Function `_get_ephem_path_for_link`    Returns or fetches data.
L227: def get(    Function `get`    Returns or fetches data.
L238: def get_cache_entry(    Function `get_cache_entry`    Returns or fetches data.
L267: def record_download_origin(cache_dir: str, download_info: DirectUrl) -> None:    Function `record_download_origin`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/self_outdated_check.py

```

L47: def _get_statefile_name(key: str) -> str:    Function `_get_statefile_name`    utility or
script function.
L53: class SelfCheckState:    Class (`SelfCheckState`)    component used by the app (see file
context: None).
L54: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script
function.
L72: def key(self) -> str:    Function `key`    utility or script function.
L75: def get(self, current_time: datetime.datetime) -> str | None:    Function `get`    Returns
or fetches data.
L94: def set(self, pypi_version: str, current_time: datetime.datetime) -> None:    Function
`set`    Sets or updates a value.
L133: class UpgradePrompt:    Class (`UpgradePrompt`)    component used by the app (see file
context: None).
L137: def __rich__(self) -> Group:    Function `__rich__`    utility or script function.
L157: def _get_current_remote_pip_version(    Function `_get_current_remote_pip_version`
utility or script function.
L185: def _compute_upgrade_prompt(    Function `_compute_upgrade_prompt`    utility or script
function.
L206: def pip_self_version_check_fetch(    Function `pip_self_version_check_fetch`    utility or
script function.
L243: def pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
Function `pip_self_version_check_emit`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/main.py

```

L4: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main
routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/list.py

```

L27: class _DistWithLatestInfo(BaseDistribution):    Class (`_DistWithLatestInfo`)    component
used by the app (see file context: None).
L43: class ListCommand(IndexGroupCommand):    Class (`ListCommand`)    component used by the app
(see file context: None).
L54: def add_options(self) -> None:    Function `add_options`    utility or script function.

```

```

L140: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check` utility or script function.
L147: def _build_package_finder( Function `_build_package_finder` utility or script
function.
L170: def run(self, options: Values, args: list[str]) -> int: Function `run` utility or
script function.
L213: def get_outdated( Function `_get_outdated` Returns or fetches data.
L222: def get_uptodate( Function `_get_uptodate` Returns or fetches data.
L231: def get_not_required( Function `_get_not_required` Returns or fetches data.
L245: def iter_packages_latest_infos( Function `_iter_packages_latest_infos` utility or
script function.
L251: def latest_info( Function `_latest_info` utility or script function.
L282: def output_package_listing( Function `_output_package_listing` utility or script
function.
L305: def output_package_listing_columns( Function `_output_package_listing_columns`
utility or script function.
L322: def format_for_columns( Function `_format_for_columns` utility or script function.
L335: def wheel_build_tag(dist: BaseDistribution) -> str | None: Function `_wheel_build_tag`
utility or script function.
L382: def format_for_json(packages: _ProcessedDists, options: Values) -> str: Function
`format_for_json` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/install.py

```

L91: def _prevent_import_hook(name: str, args: tuple[Any, ...]) -> None: Function
`_prevent_import_hook` utility or script function.
L109: def _eagerly_import_modules() -> None: Function `_eagerly_import_modules` utility or
script function.
L120: def _prevent_further_imports() -> None: Function `_prevent_further_imports` utility
or script function.
L134: def _arg_refers_to_pip(arg: str) -> bool: Function `_arg_refers_to_pip` utility or
script function.
L142: class InstallCommand(RequirementCommand): Class (`InstallCommand`) component used by
the app (see file context: None).
L162: def add_options(self) -> None: Function `_add_options` utility or script function.
L358: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check` utility or script function.
L369: def run(self, options: Values, args: list[str]) -> int: Function `run` utility or
script function.
L604: def _handle_target_dir( Function `_handle_target_dir` utility or script function.
L658: def _determine_conflicts( Function `_determine_conflicts` utility or script
function.
L670: def _warn_about_conflicts( Function `_warn_about_conflicts` utility or script
function.
L721: def installed_packages_summary( Function `_installed_packages_summary` utility or

```

```

script function.
L745: def get_lib_location_guesses(    Function `get_lib_location_guesses`    Returns or fetches
data.
L763: def site_packages_writable(root: str | None, isolated: bool) -> bool:    Function
`site_packages_writable`    utility or script function.
L770: def decide_user_install(    Function `decide_user_install`    utility or script function.
L839: def create_os_error_message(    Function `create_os_error_message`    Creates a resource
or document.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/lock.py

```

L26: class LockCommand(RequirementCommand):    Class (`LockCommand`)    component used by the
app (see file context: None).
L48: def add_options(self) -> None:    Function `add_options`    utility or script function.
L95: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/uninstall.py

```

L25: class UninstallCommand(Command, SessionCommandMixin):    Class (`UninstallCommand`)
component used by the app (see file context: None).
L40: def add_options(self) -> None:    Function `add_options`    utility or script function.
L64: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/index.py

```

L30: class IndexCommand(IndexGroupCommand):    Class (`IndexCommand`)    component used by the
app (see file context: None).
L40: def add_options(self) -> None:    Function `add_options`    utility or script function.
L60: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map`    utility or script function.
L65: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

```

L89: def _build_package_finder(    Function `_build_package_finder`    utility or script
function.
L116: def get_available_package_versions(self, options: Values, args: list[Any]) -> None:
Function `get_available_package_versions`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/d ebug.py

```

L28: def show_value(name: str, value: Any) -> None:    Function `show_value`    utility or
script function.
L32: def show_sys_implementation() -> None:    Function `show_sys_implementation`    utility or
script function.
L39: def create_vendor_txt_map() -> dict[str, str]:    Function `create_vendor_txt_map`
Creates a resource or document.
L51: def get_module_from_module_name(module_name: str) -> ModuleType | None:    Function
`get_module_from_module_name`    Returns or fetches data.
L62: def get_vendor_version_from_module(module_name: str) -> str | None:    Function
`get_vendor_version_from_module`    Returns or fetches data.
L77: def show_actual_vendor_versions(vendor_txt_versions: dict[str, str]) -> None:    Function
`show_actual_vendor_versions`    utility or script function.
L98: def show_vendor_versions() -> None:    Function `show_vendor_versions`    utility or script
function.
L106: def show_tags(options: Values) -> None:    Function `show_tags`    utility or script
function.
L136: def ca_bundle_info(config: Configuration) -> str:    Function `ca_bundle_info`    utility
or script function.
L153: class DebugCommand(Command):    Class (`DebugCommand`)    component used by the app (see
file context: None).
L162: def add_options(self) -> None:    Function `add_options`    utility or script function.
L167: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/h elp.py

```

L8: class HelpCommand(Command):    Class (`HelpCommand`)    component used by the app (see file
context: None).
L15: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/freeze.py

```

L11: def _should_suppress_build_backends() -> bool:    Function
`_should_suppress_build_backends` utility or script function.
L15: def _dev_pkgs() -> set[str]:    Function `_dev_pkgs` utility or script function.
L24: class FreezeCommand(Command):    Class (`FreezeCommand`) component used by the app (see
file context: None).
L35: def add_options(self) -> None:    Function `add_options` utility or script function.
L87: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/configuration.py

```

L24: class ConfigurationCommand(Command):    Class (`ConfigurationCommand`) component used by
the app (see file context: None).
L60: def add_options(self) -> None:    Function `add_options` utility or script function.
L98: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map` utility or script function.
L108: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L146: def _determine_file(self, options: Values, need_value: bool) -> Kind | None:    Function
`_determine_file` utility or script function.
L176: def list_values(self, options: Values, args: list[str]) -> None:    Function
`list_values` utility or script function.
L183: def get_name(self, options: Values, args: list[str]) -> None:    Function `get_name`
Returns or fetches data.
L189: def set_name_value(self, options: Values, args: list[str]) -> None:    Function
`set_name_value` Sets or updates a value.
L195: def unset_name(self, options: Values, args: list[str]) -> None:    Function `unset_name`
utility or script function.
L201: def list_config_values(self, options: Values, args: list[str]) -> None:    Function
`list_config_values` utility or script function.
L217: def print_config_file_values(self, variant: Kind, fname: str) -> None:    Function
`print_config_file_values` utility or script function.
L225: def print_env_var_values(self) -> None:    Function `print_env_var_values` utility or
script function.
L233: def open_in_editor(self, options: Values, args: list[str]) -> None:    Function
`open_in_editor` utility or script function.
L255: def _get_n_args(self, args: list[str], example: str, n: int) -> Any:    Function
`_get_n_args` utility or script function.
L269: def _save_configuration(self) -> None:    Function `_save_configuration` utility or

```

```
script function.
L280: def _determine_editor(self, options: Values) -> str:    Function `_determine_editor`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/se arch.py

```
L26: class TransformedHit(TypedDict):    Class (`TransformedHit`)    component used by the app
(see file context: None).
L35: class SearchCommand(Command, SessionCommandMixin):    Class (`SearchCommand`)    component
used by the app (see file context: None).
L42: def add_options(self) -> None:    Function `add_options`    utility or script function.
L54: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L70: def search(self, query: list[str], options: Values) -> list[dict[str, str]]:    Function
`search`    utility or script function.
L88: def transform_hits(hits: list[dict[str, str]]) -> list[TransformedHit]:    Function
`transform_hits`    utility or script function.
L116: def print_dist_installation_info(latest: str, dist: BaseDistribution | None) -> None:
Function `print_dist_installation_info`    utility or script function.
L133: def get_installed_distribution(name: str) -> BaseDistribution | None:    Function
`get_installed_distribution`    Returns or fetches data.
L138: def print_results(    Function `print_results`    utility or script function.
L177: def highest_version(versions: list[str]) -> str:    Function `highest_version`    utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/__ init__.py

```
L116: def create_command(name: str, **kwargs: Any) -> Command:    Function `create_command`
Creates a resource or document.
L128: def get_similar_commands(name: str) -> str | None:    Function `get_similar_commands`
Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/ca che.py

```

L16: class CacheCommand(Command):    Class (`CacheCommand`)    component used by the app (see
file context: None).
L40: def add_options(self) -> None:    Function `add_options`    utility or script function.
L52: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map`    utility or script function.
L61: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L87: def get_cache_dir(self, options: Values, args: list[str]) -> None:    Function
`get_cache_dir`    Returns or fetches data.
L93: def get_cache_info(self, options: Values, args: list[str]) -> None:    Function
`get_cache_info`    Returns or fetches data.
L135: def list_cache_items(self, options: Values, args: list[str]) -> None:    Function
`list_cache_items`    utility or script function.
L150: def format_for_human(self, files: list[str]) -> None:    Function `format_for_human`
utility or script function.
L163: def format_for_abspath(self, files: list[str]) -> None:    Function `format_for_abspath`
utility or script function.
L167: def remove_cache_items(self, options: Values, args: list[str]) -> None:    Function
`remove_cache_items`    utility or script function.
L218: def purge_cache(self, options: Values, args: list[str]) -> None:    Function
`purge_cache`    utility or script function.
L224: def _cache_dir(self, options: Values, subdir: str) -> str:    Function `_cache_dir`
utility or script function.
L227: def _find_http_files(self, options: Values) -> list[str]:    Function `_find_http_files`
utility or script function.
L234: def _find_wheels(self, options: Values, pattern: str) -> list[str]:    Function
`_find_wheels`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/c ompletion.py

```

L81: class CompletionCommand(Command):    Class (`CompletionCommand`)    component used by the
app (see file context: None).
L86: def add_options(self) -> None:    Function `add_options`    utility or script function.
L122: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/s how.py

```

L20: def normalize_project_url_label(label: str) -> str:    Function
`normalize_project_url_label`    utility or script function.

```

```

L27: class ShowCommand(Command):    Class (`ShowCommand`)    component used by the app (see file
context: None).
L38: def add_options(self) -> None:    Function `add_options`    utility or script function.
L50: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L64: class _PackageInfo(NamedTuple):    Class (`_PackageInfo`)    component used by the app (see
file context: None).
L85: def search_packages_info(query: list[str]) -> Generator[_PackageInfo, None, None]:
Function `search_packages_info`    utility or script function.
L102: def _get_requiring_packages(current_dist: BaseDistribution) -> Iterator[str]:
Function `_get_requiring_packages`    utility or script function.
L178: def print_results(    Function `print_results`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/h
ash.py**

```

L14: class HashCommand(Command):    Class (`HashCommand`)    component used by the app (see file
context: None).
L25: def add_options(self) -> None:    Function `add_options`    utility or script function.
L39: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L52: def _hash_of_file(path: str, algorithm: str) -> str:    Function `_hash_of_file`    utility
or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/d
ownload.py**

```

L16: class DownloadCommand(RequirementCommand):    Class (`DownloadCommand`)    component used
by the app (see file context: None).
L36: def add_options(self) -> None:    Function `add_options`    utility or script function.
L78: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/in
spect.py**

```

L19: class InspectCommand(Command):    Class (`InspectCommand`)    component used by the app

```

```
(see file context: None).
L28: def add_options(self) -> None:    Function `add_options`    utility or script function.
L48: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L65: def _dist_to_dict(self, dist: BaseDistribution) -> dict[str, Any]:    Function
`_dist_to_dict`    utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/c
heck.py**

```
L18: class CheckCommand(Command):    Class (`CheckCommand`)    component used by the app (see
file context: None).
L25: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/commands/w
heel.py**

```
L22: class WheelCommand(RequirementCommand):    Class (`WheelCommand`)    component used by the
app (see file context: None).
L42: def add_options(self) -> None:    Function `add_options`    utility or script function.
L94: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/link.p
y**

```
L40: class LinkHash:    Class (`LinkHash`)    component used by the app (see file context:
None).
L64: def __post_init__(self) -> None:    Function `__post_init__`    utility or script function.
L69: def find_hash_url_fragment(cls, url: str) -> LinkHash | None:    Function
`find_hash_url_fragment`    utility or script function.
L77: def as_dict(self) -> dict[str, str]:    Function `as_dict`    utility or script function.
L80: def as_hashes(self) -> Hashes:    Function `as_hashes`    utility or script function.
L84: def is_hash_allowed(self, hashes: Hashes | None) -> bool:    Function `is_hash_allowed`
utility or script function.
L94: class MetadataFile:    Class (`MetadataFile`)    component used by the app (see file
```

```

context: None).
L99: def __post_init__(self) -> None:    Function `__post_init__`    utility or script function.
L104: def supported_hashes(hashes: dict[str, str] | None) -> dict[str, str] | None:
Function `supported_hashes`    utility or script function.
L115: def _clean_url_path_part(part: str) -> str:    Function `_clean_url_path_part`    utility
or script function.
L123: def _clean_file_url_path(part: str) -> str:    Function `_clean_file_url_path`    utility
or script function.
L144: def _clean_url_path(path: str, is_local_path: bool) -> str:    Function
`_clean_url_path`    utility or script function.
L166: def _ensure_quoted_url(url: str) -> str:    Function `_ensure_quoted_url`    utility or
script function.
L185: def _absolute_link_url(base_url: str, url: str) -> str:    Function `_absolute_link_url`
utility or script function.
L197: class Link:    Class (`Link`)    component used by the app (see file context: None).
L214: def __init__(    Function `__init__`    utility or script function.
L283: def from_json(    Function `from_json`    utility or script function.
L340: def from_element(    Function `from_element`    utility or script function.
L391: def __str__(self) -> str:    Function `__str__`    utility or script function.
L401: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L404: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L407: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L412: def __lt__(self, other: Any) -> bool:    Function `__lt__`    utility or script function.
L418: def url(self) -> str:    Function `url`    utility or script function.
L422: def redacted_url(self) -> str:    Function `redacted_url`    utility or script function.
L426: def filename(self) -> str:    Function `filename`    utility or script function.
L440: def file_path(self) -> str:    Function `file_path`    utility or script function.
L444: def scheme(self) -> str:    Function `scheme`    utility or script function.
L448: def netloc(self) -> str:    Function `netloc`    utility or script function.
L455: def path(self) -> str:    Function `path`    utility or script function.
L458: def splitext(self) -> tuple[str, str]:    Function `splitext`    utility or script
function.
L462: def ext(self) -> str:    Function `ext`    utility or script function.
L466: def url_without_fragment(self) -> str:    Function `url_without_fragment`    utility or
script function.
L477: def _egg_fragment(self) -> str | None:    Function `_egg_fragment`    utility or script
function.
L493: def subdirectory_fragment(self) -> str | None:    Function `subdirectory_fragment`
utility or script function.
L499: def metadata_link(self) -> Link | None:    Function `metadata_link`    utility or script
function.
L508: def as_hashes(self) -> Hashes:    Function `as_hashes`    utility or script function.
L512: def hash(self) -> str | None:    Function `hash`    utility or script function.
L516: def hash_name(self) -> str | None:    Function `hash_name`    utility or script function.
L520: def show_url(self) -> str:    Function `show_url`    utility or script function.
L524: def is_file(self) -> bool:    Function `is_file`    utility or script function.
L527: def is_existing_dir(self) -> bool:    Function `is_existing_dir`    utility or script
function.
L531: def is_wheel(self) -> bool:    Function `is_wheel`    utility or script function.
L535: def is_vcs(self) -> bool:    Function `is_vcs`    utility or script function.
L541: def is_yanked(self) -> bool:    Function `is_yanked`    utility or script function.

```

```

L545: def has_hash(self) -> bool:    Function `has_hash` utility or script function.
L548: def is_hash_allowed(self, hashes: Hashes | None) -> bool:    Function `is_hash_allowed`
utility or script function.
L557: class _CleanResult(NamedTuple):    Class (`_CleanResult`) component used by the app
(see file context: None).
L589: def _clean_link(link: Link) -> _CleanResult:    Function `_clean_link` utility or
script function.
L616: def links_equivalent(link1: Link, link2: Link) -> bool:    Function `links_equivalent`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/candidate.py

```

L10: class InstallationCandidate:    Class (`InstallationCandidate`) component used by the
app (see file context: None).
L17: def __init__(self, name: str, version: str, link: Link) -> None:    Function `__init__`
utility or script function.
L22: def __str__(self) -> str:    Function `__str__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/direct_url.py

```

L30: class DirectUrl(PackagingDirectUrl):    Class (`DirectUrl`) component used by the app
(see file context: None).
L31: def to_dict_compat(self) -> dict[str, Any]:    Function `to_dict_compat` utility or
script function.
L35: def from_json(cls, s: str) -> DirectUrl:    Function `from_json` utility or script
function.
L38: def to_json(self) -> str:    Function `to_json` utility or script function.
L41: def is_local_editable(self) -> bool:    Function `is_local_editable` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/index.py

```

L4: class PackageIndex:    Class (`PackageIndex`) component used by the app (see file
context: None).

```

```
L9: def __init__(self, url: str, file_storage_domain: str) -> None:    Function `__init__`
utility or script function.
L21: def _url_for_path(self, path: str) -> str:    Function `_url_for_path`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/search_scope.py

```
L18: class SearchScope:    Class (`SearchScope`)    component used by the app (see file context:
None).
L28: def create(    Function `create`    Creates a resource or document.
L69: def get_formatted_locations(self) -> str:    Function `get_formatted_locations`    Returns
or fetches data.
L104: def get_index_urls_locations(self, project_name: str) -> list[str]:    Function
`get_index_urls_locations`    Returns or fetches data.
L111: def mkurl_pypi_url(url: str) -> str:    Function `mkurl_pypi_url`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/format_control.py

```
L8: class FormatControl:    Class (`FormatControl`)    component used by the app (see file
context: None).
L13: def __init__(    Function `__init__`    utility or script function.
L26: def __eq__(self, other: object) -> bool:    Object (singleton).
L35: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L39: def handle_mutual_excludes(value: str, target: set[str], other: set[str]) -> None:
Function `handle_mutual_excludes`    utility or script function.
L61: def get_allowed_formats(self, canonical_name: str) -> frozenset[str]:    Function
`get_allowed_formats`    Returns or fetches data.
L73: def disallow_binaries(self) -> None:    Function `disallow_binaries`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/target_python.py

```
L11: class TargetPython:    Class (`TargetPython`)    component used by the app (see file
```



```

context: None).
L28: def __init__(    Function `__init__`    utility or script function.
L69: def format_given(self) -> str:    Function `format_given`    utility or script function.
L89: def get_sorted_tags(self) -> list[Tag]:    Function `get_sorted_tags`    Returns or fetches
data.
L114: def get_unsorted_tags(self) -> set[Tag]:    Function `get_unsorted_tags`    Returns or
fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/installation_report.py

```

L10: class InstallationReport:    Class (`InstallationReport`)    component used by the app (see
file context: None).
L11: def __init__(self, install_requirements: Sequence[InstallRequirement]):    Function
`__init__`    utility or script function.
L15: def _install_req_to_dict(cls, ireq: InstallRequirement) -> dict[str, Any]:    Function
`_install_req_to_dict`    utility or script function.
L43: def to_dict(self) -> dict[str, Any]:    Function `to_dict`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/selection_prefs.py

```

L10: class SelectionPreferences:    Class (`SelectionPreferences`)    component used by the app
(see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/scheme.py

```

L14: class Scheme:    Class (`Scheme`)    component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/wheel.py

```

L18: class Wheel:    Class (`Wheel`) component used by the app (see file context: None).
L21: def __init__(self, filename: str) -> None:    Function `__init__` utility or script
function.
L32: def get_formatted_file_tags(self) -> list[str]:    Function `get_formatted_file_tags`
Returns or fetches data.
L36: def support_index_min(self, tags: list[Tag]) -> int:    Function `support_index_min`
utility or script function.
L54: def find_most_preferred_tag(    Function `find_most_preferred_tag` utility or script
function.
L75: def supported(self, tags: Iterable[Tag]) -> bool:    Function `supported` utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/models/releas
e_control.py**

```

L11: class ReleaseControl:    Class (`ReleaseControl`) component used by the app (see file
context: None).
L20: def handle_mutual_excludes(    Function `handle_mutual_excludes` utility or script
function.
L59: def get_ordered_args(self) -> list[tuple[str, str]]:    Function `get_ordered_args`
Returns or fetches data.
L74: def allows_prereleases(self, canonical_name: NormalizedName) -> bool | None:    Function
`allows_prereleases` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/compat.
py**

```

L16: def has_tls() -> bool:    Function `has_tls` utility or script function.
L29: def get_path_uid(path: str) -> int:    Function `get_path_uid` Returns or fetches data.
L62: def open_text_resource(    Function `open_text_resource` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/entrypoi
nts.py**

```

L24: def _wrapper(args: list[str] | None = None) -> int:    Function `_wrapper` utility or
script function.
L47: def get_best_invocation_for_this_pip() -> str:    Function

```

```
`get_best_invocation_for_this_pip` Returns or fetches data.
L74: def get_best_invocation_for_this_python() -> str:    Function
`get_best_invocation_for_this_python` Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/datetime.py

```
L7: def today_is_later_than(year: int, month: int, day: int) -> bool:    Function
`today_is_later_than` utility or script function.
L14: def parse_iso_datetime(isodate: str) -> datetime.datetime:    Function
`parse_iso_datetime` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/urls.py

```
L9: def path_to_url(path: str) -> str:    Function `path_to_url` utility or script function.
L19: def url_to_path(url: str) -> str:    Function `url_to_path` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/_jaraco_text.py

```
L36: def _nonblank(str):    Function `_nonblank` utility or script function.
L41: def yield_lines(iterable):    Function `yield_lines` utility or script function.
L60: def _(text):    Function `_` utility or script function.
L64: def drop_comment(line):    Function `drop_comment` utility or script function.
L79: def join_continuation(lines):    Function `join_continuation` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/appdirs.py

```
L15: def user_cache_dir(appname: str) -> str:    Function `user_cache_dir` utility or script function.
L19: def _macos_user_config_dir(appname: str, roaming: bool = True) -> str:    Function
`_macos_user_config_dir` utility or script function.
```

```
L33: def user_config_dir(appname: str, roaming: bool = True) -> str:    Function
`user_config_dir` utility or script function.
L42: def site_config_dirs(appname: str) -> list[str]:    Function `site_config_dirs` utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/filesystem.py

```
L19: def check_path_owner(path: str) -> bool:    Function `check_path_owner` utility or
script function.
L47: def adjacent_tmp_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
Function `adjacent_tmp_file` utility or script function.
L76: def test_writable_dir(path: str) -> bool:    Function `test_writable_dir` utility or
script function.
L94: def _test_writable_dir_win(path: str) -> bool:    Function `_test_writable_dir_win`
utility or script function.
L122: def find_files(path: str, pattern: str) -> list[str]:    Function `find_files` utility
or script function.
L132: def file_size(path: str) -> int | float:    Function `file_size` utility or script
function.
L139: def format_file_size(path: str) -> str:    Function `format_file_size` utility or
script function.
L143: def directory_size(path: str) -> int | float:    Function `directory_size` utility or
script function.
L152: def format_directory_size(path: str) -> str:    Function `format_directory_size`
utility or script function.
L156: def copy_directory_permissions(directory: str, target_file: BinaryIO) -> None:
Function `copy_directory_permissions` utility or script function.
L168: def _subdirs_without_generic(    Function `_subdirs_without_generic` utility or script
function.
L192: def subdirs_without_files(path: str) -> Generator[Path]:    Function
`subdirs_without_files` utility or script function.
L197: def subdirs_without_wheels(path: str) -> Generator[Path]:    Function
`subdirs_without_wheels` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/retry.py

```
L14: def retry(    Function `retry` utility or script function.
L28: def wrapper(func: Callable[P, T]) -> Callable[P, T]:    Function `wrapper` utility or
script function.
L31: def retry_wrapped(*args: P.args, **kwargs: P.kwargs) -> T:    Function `retry_wrapped`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/logging.py

```

L40: class BrokenStdoutLoggingError(Exception):    Class (`BrokenStdoutLoggingError`)
component used by the app (see file context: None).
L46: def _is_broken_pipe_error(exc_class: type[BaseException], exc: BaseException) -> bool:
Function `_is_broken_pipe_error` utility or script function.
L60: def capture_logging() -> Generator[StringIO, None, None]:    Function `capture_logging`
utility or script function.
L92: def indent_log(num: int = 2) -> Generator[None, None, None]:    Function `indent_log`
utility or script function.
L106: def get_indentation() -> int:    Function `get_indentation` Returns or fetches data.
L110: class IndentingFormatter(logging.Formatter):    Class (`IndentingFormatter`) component
used by the app (see file context: None).
L113: def __init__(    Function `__init__` utility or script function.
L128: def get_message_start(self, formatted: str, levelno: int) -> str:    Function
`get_message_start` Returns or fetches data.
L144: def format(self, record: logging.LogRecord) -> str:    Function `format` utility or
script function.
L162: class IndentedRenderable:    Class (`IndentedRenderable`) component used by the app
(see file context: None).
L166: def __rich_console__(    Function `__rich_console__` utility or script function.
L177: class PipConsole(Console):    Class (`PipConsole`) component used by the app (see file
context: None).
L178: def on_broken_pipe(self) -> None:    Function `on_broken_pipe` utility or script
function.
L184: def get_console(*, stderr: bool = False) -> Console:    Function `get_console` Returns
or fetches data.
L193: class RichPipStreamHandler(RichHandler):    Class (`RichPipStreamHandler`) component
used by the app (see file context: None).
L196: def __init__(self, console: Console) -> None:    Function `__init__` utility or script
function.
L206: def emit(self, record: logging.LogRecord) -> None:    Function `emit` utility or script
function.
L234: def handleError(self, record: logging.LogRecord) -> None:    Function `handleError`
utility or script function.
L253: class BetterRotatingFileHandler(logging.handlers.RotatingFileHandler):    Class
(`BetterRotatingFileHandler`) component used by the app (see file context: None).
L254: def _open(self) -> TextIOWrapper:    Function `_open` utility or script function.
L259: class MaxLevelFilter(Filter):    Class (`MaxLevelFilter`) component used by the app
(see file context: None).
L260: def __init__(self, level: int) -> None:    Function `__init__` utility or script
function.
L263: def filter(self, record: logging.LogRecord) -> bool:    Function `filter` utility or
script function.
L267: class ExcludeLoggerFilter(Filter):    Class (`ExcludeLoggerFilter`) component used by
the app (see file context: None).
L272: def filter(self, record: logging.LogRecord) -> bool:    Function `filter` utility or

```

```
script function.
L278: def setup_logging(verbosity: int, no_color: bool, user_log_file: str | None) -> int:
Function `setup_logging` Sets or updates a value.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/unpacking.py

```
L45: def current_umask() -> int:    Function `current_umask`    utility or script function.
L52: def split_leading_dir(path: str) -> list[str]:    Function `split_leading_dir`    utility
or script function.
L64: def has_leading_dir(paths: Iterable[str]) -> bool:    Function `has_leading_dir`    utility
or script function.
L79: def is_within_directory(directory: str, target: str) -> bool:    Function
`is_within_directory`    utility or script function.
L90: def _get_default_mode_plus_executable() -> int:    Function
`_get_default_mode_plus_executable`    utility or script function.
L94: def set_extracted_file_to_default_mode_plus_executable(path: str) -> None:    Function
`set_extracted_file_to_default_mode_plus_executable`    Sets or updates a value.
L102: def zip_item_is_executable(info: ZipInfo) -> bool:    Function `zip_item_is_executable`
utility or script function.
L109: def unzip_file(filename: str, location: str, flatten: bool = True) -> None:    Function
`unzip_file`    utility or script function.
L155: def untar_file(filename: str, location: str) -> None:    Function `untar_file`    utility
or script function.
L206: def pip_filter(member: tarfile.TarInfo, path: str) -> tarfile.TarInfo:    Function
`pip_filter`    utility or script function.
L251: def is_symlink_target_in_tar(tar: tarfile.TarFile, tarinfo: tarfile.TarInfo) -> bool:
Function `is_symlink_target_in_tar`    utility or script function.
L265: def _untar_without_filter(    Function `_untar_without_filter`    utility or script
function.
L334: def unpack_file(    Function `unpack_file`    utility or script function.
L348: def _unzip() -> None:    Function `_unzip`    utility or script function.
L351: def _untar() -> None:    Function `_untar`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/subprocess.py

```
L20: def make_command(*args: str | HiddenText | CommandArgs) -> CommandArgs:    Function
`make_command`    utility or script function.
L37: def format_command_args(args: list[str] | CommandArgs) -> str:    Function
`format_command_args`    utility or script function.
L52: def reveal_command_args(args: list[str] | CommandArgs) -> list[str]:    Function
```

```

`reveal_command_args` utility or script function.
L59: def call_subprocess(    Function `call_subprocess` utility or script function.
L227: def runner_with_spinner_message(message: str) -> Callable[..., None]:    Function
`runner_with_spinner_message` utility or script function.
L234: def runner(    Function `runner` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/compatibility_tags.py

```

L23: def version_info_to_nodot(version_info: tuple[int, ...]) -> str:    Function
`version_info_to_nodot` utility or script function.
L28: def _mac_platforms(arch: str) -> list[str]:    Function `_mac_platforms` utility or
script function.
L48: def _ios_platforms(arch: str) -> list[str]:    Function `_ios_platforms` utility or
script function.
L68: def _android_platforms(arch: str) -> list[str]:    Function `_android_platforms` utility
or script function.
L78: def _custom_manylinux_platforms(arch: str) -> list[str]:    Function
`_custom_manylinux_platforms` utility or script function.
L99: def _get_custom_platforms(arch: str) -> list[str]:    Function `_get_custom_platforms`
utility or script function.
L114: def _expand_allowed_platforms(platforms: list[str] | None) -> list[str] | None:
Function `_expand_allowed_platforms` utility or script function.
L131: def _get_python_version(version: str) -> PythonVersion:    Function
`_get_python_version` utility or script function.
L138: def _get_custom_interpreter(    Function `_get_custom_interpreter` utility or script
function.
L148: def get_supported(    Function `get_supported` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/glibc.py

```

L7: def glibc_version_string() -> str | None:    Function `glibc_version_string` utility or
script function.
L12: def glibc_version_string_confstr() -> str | None:    Function
`glibc_version_string_confstr` utility or script function.
L32: def glibc_version_string_ctypes() -> str | None:    Function
`glibc_version_string_ctypes` utility or script function.
L92: def libc_ver() -> tuple[str, str]:    Function `libc_ver` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/virtualenv.py

```
L15: def _running_under_venv() -> bool:    Function `_running_under_venv` utility or script
function.
L23: def _running_under_legacy_virtualenv() -> bool:    Function
`_running_under_legacy_virtualenv` utility or script function.
L32: def running_under_virtualenv() -> bool:    Function `running_under_virtualenv` utility
or script function.
L37: def _get_pyvenv_cfg_lines() -> list[str] | None:    Function `_get_pyvenv_cfg_lines`
utility or script function.
L52: def _no_global_under_venv() -> bool:    Function `_no_global_under_venv` utility or
script function.
L81: def _no_global_under_legacy_virtualenv() -> bool:    Function
`_no_global_under_legacy_virtualenv` utility or script function.
L95: def virtualenv_no_global() -> bool:    Function `virtualenv_no_global` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/deprecation.py

```
L18: class PipDeprecationWarning(Warning):    Class (`PipDeprecationWarning`) component used
by the app (see file context: None).
L26: def _showwarning(    Function `_showwarning` utility or script function.
L49: def install_warning_logger() -> None:    Function `install_warning_logger` utility or
script function.
L60: def deprecated(    Function `deprecated` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/filetypes.py

```
L19: def is_archive_file(name: str) -> bool:    Function `is_archive_file` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/egg_link.py


```

L19: def _egg_link_names(raw_name: str) -> list[str]:    Function `_egg_link_names` utility
or script function.
L34: def egg_link_path_from_sys_path(raw_name: str) -> str | None:    Function
`egg_link_path_from_sys_path` utility or script function.
L47: def egg_link_path_from_location(raw_name: str) -> str | None:    Function
`egg_link_path_from_location` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/hashe.p
y**

```

L24: class Hashes:    Class (`Hashes`) component used by the app (see file context: None).
L30: def __init__(self, hashes: dict[str, list[str]] | None = None) -> None:    Function
`__init__` utility or script function.
L42: def __and__(self, other: Hashes) -> Hashes:    Function `__and__` utility or script
function.
L62: def digest_count(self) -> int:    Function `digest_count` utility or script function.
L65: def is_hash_allowed(self, hash_name: str, hex_digest: str) -> bool:    Function
`is_hash_allowed` utility or script function.
L69: def check_against_chunks(self, chunks: Iterable[bytes]) -> None:    Function
`check_against_chunks` utility or script function.
L92: def _raise(self, gots: dict[str, _Hash]) -> NoReturn:    Function `_raise` utility or
script function.
L95: def check_against_file(self, file: BinaryIO) -> None:    Function `check_against_file`
utility or script function.
L103: def check_against_path(self, path: str) -> None:    Function `check_against_path`
utility or script function.
L107: def has_one_of(self, hashes: Mapping[str, str]) -> bool:    Function `has_one_of`
utility or script function.
L114: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L118: def __eq__(self, other: object) -> bool:    Object (singleton).
L123: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L135: class MissingHashes(Hashes):    Class (`MissingHashes`) component used by the app (see
file context: None).
L143: def __init__(self) -> None:    Function `__init__` utility or script function.
L149: def _raise(self, gots: dict[str, _Hash]) -> NoReturn:    Function `_raise` utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/temp_dir
.py**

```

L38: def global_tempdir_manager() -> Generator[None, None, None]:    Function
`global_tempdir_manager` utility or script function.

```

```

L48: class TempDirectoryTypeRegistry:  Class (`TempDirectoryTypeRegistry`)  component used
by the app (see file context: None).
L51: def __init__(self) -> None:  Function `__init__`  utility or script function.
L54: def set_delete(self, kind: str, value: bool) -> None:  Function `set_delete`  Sets or
updates a value.
L60: def get_delete(self, kind: str) -> bool:  Function `get_delete`  Returns or fetches
data.
L71: def tempdir_registry() -> Generator[TempDirectoryTypeRegistry, None, None]:  Function
`tempdir_registry`  utility or script function.
L84: class _Default:  Class (`_Default`)  component used by the app (see file context:
None).
L91: class TempDirectory:  Class (`TempDirectory`)  component used by the app (see file
context: None).
L112: def __init__(  Function `__init__`  utility or script function.
L148: def path(self) -> str:  Function `path`  utility or script function.
L152: def __repr__(self) -> str:  Function `__repr__`  utility or script function.
L155: def __enter__(self: _T) -> _T:  Function `__enter__`  utility or script function.
L158: def __exit__(self, exc: Any, value: Any, tb: Any) -> None:  Function `__exit__`
utility or script function.
L169: def _create(self, kind: str) -> str:  Function `_create`  utility or script function.
L179: def cleanup(self) -> None:  Function `cleanup`  utility or script function.
L187: def onerror(  Function `onerror`  utility or script function.
L224: class AdjacentTempDirectory(TempDirectory):  Class (`AdjacentTempDirectory`)
component used by the app (see file context: None).
L246: def __init__(self, original: str, delete: bool | None = None) -> None:  Function
`__init__`  utility or script function.
L251: def _generate_names(cls, name: str) -> Generator[str, None, None]:  Function
`_generate_names`  utility or script function.
L276: def _create(self, kind: str) -> str:  Function `_create`  utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utis/pylock.p
y**

```

L32: def _pylock_package_from_install_requirement(  Function
`_pylock_package_from_install_requirement`  utility or script function.
L116: def pylock_from_install_requirements(  Function `pylock_from_install_requirements`
utility or script function.
L135: def _is_url(s: str) -> bool:  Function `_is_url`  utility or script function.
L139: def is_valid_pylock_filename(filename: str) -> bool:  Function
`is_valid_pylock_filename`  utility or script function.
L147: def _package_dist_url(  Function `_package_dist_url`  utility or script function.
L177: def package_vcs_requirement_url(  Function `package_vcs_requirement_url`  utility or
script function.
L192: def package_archive_requirement_url(  Function `package_archive_requirement_url`
utility or script function.
L208: def package_directory_requirement_url(  Function `package_directory_requirement_url`

```

```

utility or script function.
L227: def package_sdist_requirement_url(    Function `package_sdist_requirement_url`    utility
or script function.
L233: def package_wheel_requirement_url(    Function `package_wheel_requirement_url`    utility
or script function.
L239: def _get_pylock_path_or_url_content(path_or_url: str, session: PipSession) -> str:
Function `_get_pylock_path_or_url_content`    utility or script function.
L255: def select_from_pylock_path_or_url(    Function `select_from_pylock_path_or_url`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/wheel.py

```

L18: def parse_wheel(wheel_zip: ZipFile, name: str) -> tuple[str, Message]:    Function
`parse_wheel`    utility or script function.
L36: def wheel_dist_info_dir(source: ZipFile, name: str) -> str:    Function
`wheel_dist_info_dir`    utility or script function.
L67: def read_wheel_metadata_file(source: ZipFile, path: str) -> bytes:    Function
`read_wheel_metadata_file`    utility or script function.
L76: def wheel_metadata(source: ZipFile, dist_info_dir: str) -> Message:    Function
`wheel_metadata`    utility or script function.
L95: def wheel_version(wheel_data: Message) -> tuple[int, ...]:    Function `wheel_version`
utility or script function.
L111: def check_compatibility(version: tuple[int, ...], name: str) -> None:    Function
`check_compatibility`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/misc.py

```

L70: def get_pip_version() -> str:    Function `get_pip_version`    Returns or fetches data.
L77: def normalize_version_info(py_version_info: tuple[int, ...]) -> tuple[int, int, int]:
Function `normalize_version_info`    utility or script function.
L96: def ensure_dir(path: str) -> None:    Function `ensure_dir`    utility or script function.
L106: def get_prog() -> str:    Function `get_prog`    Returns or fetches data.
L120: def rmtree(dir: str, ignore_errors: bool = False, onexc: OnExc | None = None) -> None:
Function `rmtree`    utility or script function.
L133: def _onerror_ignore(*args: Any) -> None:    Function `_onerror_ignore`    utility or
script function.
L137: def _onerror_reraise(*args: Any) -> None:    Function `_onerror_reraise`    utility or
script function.
L141: def rmtree_errorhandler(    Function `rmtree_errorhandler`    utility or script function.
L182: def display_path(path: str) -> str:    Function `display_path`    utility or script
function.
L193: def backup_dir(dir: str, ext: str = ".bak") -> str:    Function `backup_dir`    utility or
script function.

```

```

L204: def ask_path_exists(message: str, options: Iterable[str]) -> str:    Function
`ask_path_exists` utility or script function.
L211: def _check_no_input(message: str) -> None:    Function `_check_no_input` utility or
script function.
L219: def ask(message: str, options: Iterable[str]) -> str:    Function `ask` utility or
script function.
L234: def ask_input(message: str) -> str:    Function `ask_input` utility or script function.
L240: def ask_password(message: str) -> str:    Function `ask_password` utility or script
function.
L246: def strtobool(val: str) -> int:    Function `strtobool` utility or script function.
L262: def format_size(bytes: float) -> str:    Function `format_size` utility or script
function.
L273: def tabulate(rows: Iterable[Iterable[Any]]) -> tuple[list[str], list[int]]:    Function
`tabulate` utility or script function.
L287: def is_installable_dir(path: str) -> bool:    Function `is_installable_dir` utility or
script function.
L304: def read_chunks(    Function `read_chunks` utility or script function.
L315: def normalize_path(path: str, resolve_symlinks: bool = True) -> str:    Function
`normalize_path` utility or script function.
L328: def splitext(path: str) -> tuple[str, str]:    Function `splitext` utility or script
function.
L337: def renames(old: str, new: str) -> None:    Function `renames` utility or script
function.
L354: def is_local(path: str) -> bool:    Function `is_local` utility or script function.
L368: def write_output(msg: Any, *args: Any) -> None:    Function `write_output` utility or
script function.
L372: class StreamWrapper(StringIO):    Class (`StreamWrapper`) component used by the app
(see file context: None).
L376: def from_stream(cls, orig_stream: TextIO) -> StreamWrapper:    Function `from_stream`
utility or script function.
L384: def encoding(self) -> str:    # type: ignore    Function `encoding` utility or script
function.
L389: def enum(*sequential: Any, **named: Any) -> type[Any]:    Function `enum` utility or
script function.
L396: def build_netloc(host: str, port: int | None) -> str:    Function `build_netloc`
Constructs or prepares an object.
L408: def build_url_from_netloc(netloc: str, scheme: str = "https") -> str:    Function
`build_url_from_netloc` Constructs or prepares an object.
L418: def parse_netloc(netloc: str) -> tuple[str | None, int | None]:    Function
`parse_netloc` utility or script function.
L427: def split_auth_from_netloc(netloc: str) -> NetlocTuple:    Function
`split_auth_from_netloc` utility or script function.
L456: def redact_netloc(netloc: str) -> str:    Function `redact_netloc` utility or script
function.
L476: def _transform_url(    Function `_transform_url` utility or script function.
L496: def _get_netloc(netloc: str) -> NetlocTuple:    Function `_get_netloc` utility or
script function.
L500: def _redact_netloc(netloc: str) -> tuple[str]:    Function `_redact_netloc` utility or
script function.
L504: def split_auth_netloc_from_url(    Function `split_auth_netloc_from_url` utility or
script function.

```

```

L516: def remove_auth_from_url(url: str) -> str:    Function `remove_auth_from_url` utility
or script function.
L523: def redact_auth_from_url(url: str) -> str:    Function `redact_auth_from_url` utility
or script function.
L528: def redact_auth_from_requirement(req: Requirement) -> str:    Function
`redact_auth_from_requirement` utility or script function.
L536: class HiddenText:    Class (`HiddenText`) component used by the app (see file context:
None).
L540: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L543: def __str__(self) -> str:    Function `__str__` utility or script function.
L546: def __eq__(self, other: object) -> bool:    Object (singleton).
L560: def hide_value(value: str) -> HiddenText:    Function `hide_value` utility or script
function.
L564: def hide_url(url: str) -> HiddenText:    Function `hide_url` utility or script
function.
L569: def protect_pip_from_modification_on_windows(modifying_pip: bool) -> None:    Function
`protect_pip_from_modification_on_windows` utility or script function.
L595: def check_externally_managed() -> None:    Function `check_externally_managed` utility
or script function.
L610: def is_console_interactive() -> bool:    Function `is_console_interactive` utility or
script function.
L615: def hash_file(path: str, blocksize: int = 1 << 20) -> tuple[Any, int]:    Function
`hash_file` utility or script function.
L627: def pairwise(iterable: Iterable[Any]) -> Iterator[tuple[Any, Any]]:    Function
`pairwise` utility or script function.
L638: def partition(    Function `partition` utility or script function.
L651: class ConfiguredBuildBackendHookCaller(BuildBackendHookCaller):    Class
(`ConfiguredBuildBackendHookCaller`) component used by the app (see file context: None).
L652: def __init__(    Function `__init__` utility or script function.
L666: def build_wheel(    Function `build_wheel` Constructs or prepares an object.
L677: def build_sdist(    Function `build_sdist` Constructs or prepares an object.
L685: def build_editable(    Function `build_editable` Constructs or prepares an object.
L696: def get_requires_for_build_wheel(    Function `get_requires_for_build_wheel` Returns or
fetches data.
L702: def get_requires_for_build_sdist(    Function `get_requires_for_build_sdist` Returns or
fetches data.
L708: def get_requires_for_build_editable(    Function `get_requires_for_build_editable`
Returns or fetches data.
L714: def prepare_metadata_for_build_wheel(    Function `prepare_metadata_for_build_wheel`
utility or script function.
L727: def prepare_metadata_for_build_editable(    Function
`prepare_metadata_for_build_editable` utility or script function.
L741: def warn_if_run_as_root() -> None:    Function `warn_if_run_as_root` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utls/direct_ur

I_helpers.py

```
L19: def direct_url_as_pep440_direct_reference(direct_url: DirectUrl, name: str) -> str:
Function `direct_url_as_pep440_direct_reference` utility or script function.
L36: def direct_url_for_editable(source_dir: str) -> DirectUrl: Function
`direct_url_for_editable` utility or script function.
L43: def direct_url_from_link( Function `direct_url_from_link` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/packaging.py

```
L13: def check_requires_python( Function `check_requires_python` utility or script
function.
L37: def get_requirement(req_string: str) -> Requirement: Function `get_requirement`
Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/utils/_log.py

```
L16: class VerboseLogger(logging.Logger): Class (`VerboseLogger`) component used by the
app (see file context: None).
L22: def verbose(self, msg: str, *args: Any, **kwargs: Any) -> None: Function `verbose`
utility or script function.
L26: def getLogger(name: str) -> VerboseLogger: Function `getLogger` Returns or fetches
data.
L31: def init_logging() -> None: Function `init_logging` Initialisation routine.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/freeze.py

```
L25: class _EditableInfo(NamedTuple): Class (`_EditableInfo`) component used by the app
(see file context: None).
L30: def freeze( Function `freeze` utility or script function.
L151: def _format_as_name_version(dist: BaseDistribution) -> str: Function
`_format_as_name_version` utility or script function.
L161: def _get_editable_info(dist: BaseDistribution) -> _EditableInfo: Function
`_get_editable_info` utility or script function.
L228: class FrozenRequirement: Class (`FrozenRequirement`) component used by the app (see
```

```

file context: None).
L235: def canonical_name(self) -> NormalizedName:    Function `canonical_name`    utility or
script function.
L239: def from_dist(cls, dist: BaseDistribution) -> FrozenRequirement:    Function `from_dist`
utility or script function.
L255: def __str__(self) -> str:    Function `__str__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/prepare.py

```

L65: def _get_prepared_distribution(    Function `_get_prepared_distribution`    utility or
script function.
L83: def unpack_vcs_link(link: Link, location: str, verbosity: int) -> None:    Function
`unpack_vcs_link`    utility or script function.
L90: class File:    Class (`File`)    component used by the app (see file context: None).
L94: def __post_init__(self) -> None:    Function `__post_init__`    utility or script function.
L104: def get_http_url(    Function `get_http_url`    Returns or fetches data.
L128: def get_file_url(    Function `get_file_url`    Returns or fetches data.
L152: def unpack_url(    Function `unpack_url`    utility or script function.
L195: def _check_download_dir(    Function `_check_download_dir`    utility or script function.
L225: class RequirementPreparer:    Class (`RequirementPreparer`)    component used by the app
(see file context: None).
L228: def __init__(    Function `__init__`    utility or script function.
L288: def _log_preparing_link(self, req: InstallRequirement) -> None:    Function
`_log_preparing_link`    utility or script function.
L315: def _ensure_link_req_src_dir(    Function `_ensure_link_req_src_dir`    utility or script
function.
L338: def _get_linked_req_hashes(self, req: InstallRequirement) -> Hashes:    Function
`_get_linked_req_hashes`    utility or script function.
L370: def _fetch_metadata_only(    Function `_fetch_metadata_only`    utility or script
function.
L389: def _fetch_metadata_using_link_data_attr(    Function
`_fetch_metadata_using_link_data_attr`    utility or script function.
L430: def _fetch_metadata_using_lazy_wheel(    Function `_fetch_metadata_using_lazy_wheel`
utility or script function.
L459: def _complete_partial_requirements(    Function `_complete_partial_requirements`
utility or script function.
L500: def prepare_linked_requirement(    Function `prepare_linked_requirement`    utility or
script function.
L544: def prepare_linked_requirements_more(    Function `prepare_linked_requirements_more`
utility or script function.
L574: def _prepare_linked_requirement(    Function `_prepare_linked_requirement`    utility or
script function.
L670: def save_linked_requirement(self, req: InstallRequirement) -> None:    Function
`save_linked_requirement`    Saves data to storage or remote.
L696: def prepare_editable_requirement(    Function `prepare_editable_requirement`    utility or

```

```
script function.
L729: def prepare_installed_requirement(    Function `prepare_installed_requirement`    utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/ch eck.py

```
L28: class PackageDetails(NamedTuple):    Class (`PackageDetails`)    component used by the app
(see file context: None).
L44: def create_package_set_from_installed() -> tuple[PackageSet, bool]:    Function
`create_package_set_from_installed`    Creates a resource or document.
L61: def check_package_set(    Function `check_package_set`    utility or script function.
L106: def check_install_conflicts(to_install: list[InstallRequirement]) -> ConflictDetails:
Function `check_install_conflicts`    utility or script function.
L126: def check_unsupported(    Function `check_unsupported`    utility or script function.
L142: def _simulate_installation_of(    Function `_simulate_installation_of`    utility or
script function.
L161: def _create_whitelist(    Function `_create_whitelist`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/operations/in stall/wheel.py

```
L57: class File(Protocol):    Class (`File`)    component used by the app (see file context:
None).
L62: def save(self) -> None:    Function `save`    Saves data to storage or remote.
L72: def rehash(path: str, blocksize: int = 1 << 20) -> tuple[str, str]:    Function `rehash`
utility or script function.
L79: def csv_io_kwargs(mode: str) -> dict[str, Any]:    Function `csv_io_kwargs`    utility or
script function.
L86: def fix_script(path: str) -> bool:    Function `fix_script`    utility or script function.
L106: def wheel_root_is_purelib(metadata: Message) -> bool:    Function
`wheel_root_is_purelib`    utility or script function.
L110: def get_entrypoints(dist: BaseDistribution) -> tuple[dict[str, str], dict[str, str]]:
Function `get_entrypoints`    Returns or fetches data.
L121: def message_about_scripts_not_on_PATH(scripts: Sequence[str]) -> str | None:    Function
`message_about_scripts_not_on_PATH`    utility or script function.
L193: def _normalized_outrows(    Function `_normalized_outrows`    utility or script function.
L219: def _record_to_fs_path(record_path: RecordPath, lib_dir: str) -> str:    Function
`_record_to_fs_path`    utility or script function.
L223: def _fs_to_record_path(path: str, lib_dir: str) -> RecordPath:    Function
`_fs_to_record_path`    utility or script function.
L233: def get_csv_rows_for_installed(    Function `get_csv_rows_for_installed`    Returns or
```



```

fetches data.
L265: def get_console_script_specs(console: dict[str, str]) -> list[str]:    Function
`get_console_script_specs` Returns or fetches data.
L340: class ZipBackedFile:    Class (`ZipBackedFile`) component used by the app (see file
context: None).
L341: def __init__(    Function `__init__` utility or script function.
L349: def _getinfo(self) -> ZipInfo:    Function `_getinfo` utility or script function.
L352: def save(self) -> None:    Function `save` Saves data to storage or remote.
L378: class ScriptFile:    Class (`ScriptFile`) component used by the app (see file context:
None).
L379: def __init__(self, file: File) -> None:    Function `__init__` utility or script
function.
L385: def save(self) -> None:    Function `save` Saves data to storage or remote.
L390: class MissingCallableSuffix(InstallationError):    Class (`MissingCallableSuffix`)
component used by the app (see file context: None).
L391: def __init__(self, entry_point: str) -> None:    Function `__init__` utility or script
function.
L400: def _raise_for_invalid_entrypoint(specification: str) -> None:    Function
`_raise_for_invalid_entrypoint` utility or script function.
L406: class PipScriptMaker(ScriptMaker):    Class (`PipScriptMaker`) component used by the
app (see file context: None).
L419: def make(    Function `make` utility or script function.
L426: def _install_wheel( # noqa: C901, PLR0915 function is too long    Function
`_install_wheel` utility or script function.
L466: def record_installed(    Function `record_installed` utility or script function.
L475: def is_dir_path(path: RecordPath) -> bool:    Function `is_dir_path` utility or script
function.
L478: def assert_no_path_traversal(dest_dir_path: str, target_path: str) -> None:    Function
`assert_no_path_traversal` utility or script function.
L488: def root_scheme_file_maker(    Function `root_scheme_file_maker` utility or script
function.
L491: def make_root_scheme_file(record_path: RecordPath) -> File:    Function
`make_root_scheme_file` utility or script function.
L499: def data_scheme_file_maker(    Function `data_scheme_file_maker` utility or script
function.
L504: def make_data_scheme_file(record_path: RecordPath) -> File:    Function
`make_data_scheme_file` utility or script function.
L533: def is_data_scheme_path(path: RecordPath) -> bool:    Function `is_data_scheme_path`
utility or script function.
L543: def is_script_scheme_path(path: RecordPath) -> bool:    Function `is_script_scheme_path`
utility or script function.
L562: def is_entrypoint_wrapper(file: File) -> bool:    Function `is_entrypoint_wrapper`
utility or script function.
L597: def pyc_source_file_paths() -> Generator[str, None, None]:    Function
`pyc_source_file_paths` utility or script function.
L610: def pyc_output_path(path: str) -> str:    Function `pyc_output_path` utility or script
function.
L666: def _generate_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
Function `_generate_file` utility or script function.
L716: def req_error_context(req_description: str) -> Generator[None, None, None]:    Function
`req_error_context` utility or script function.

```

```
L724: def install_wheel(    Function `install_wheel`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/_distutils.py

```
L136: def distutils_scheme(    Function `distutils_scheme`    utility or script function.
L116: def get_scheme(    Function `get_scheme`    Returns or fetches data.
L151: def get_bin_prefix() -> str:    Function `get_bin_prefix`    Returns or fetches data.
L168: def get_purelib() -> str:    Function `get_purelib`    Returns or fetches data.
L172: def get_platlib() -> str:    Function `get_platlib`    Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/base.py

```
L20: def get_major_minor_version() -> str:    Function `get_major_minor_version`    Returns or
fetches data.
L28: def change_root(new_root: str, pathname: str) -> str:    Function `change_root`    utility
or script function.
L56: def get_src_prefix() -> str:    Function `get_src_prefix`    Returns or fetches data.
L81: def is_osx_framework() -> bool:    Function `is_osx_framework`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/_init_.py

```
L45: def _should_use_sysconfig() -> bool:    Function `_should_use_sysconfig`    utility or
script function.
L75: def _looks_like_bpo_44860() -> bool:    Function `_looks_like_bpo_44860`    utility or
script function.
L89: def _looks_like_red_hat_patched_platlib_purelib(scheme: dict[str, str]) -> bool:
Function `_looks_like_red_hat_patched_platlib_purelib`    utility or script function.
L100: def _looks_like_red_hat_lib() -> bool:    Function `_looks_like_red_hat_lib`    utility or
script function.
L115: def _looks_like_debian_scheme() -> bool:    Function `_looks_like_debian_scheme`
utility or script function.
L123: def _looks_like_red_hat_scheme() -> bool:    Function `_looks_like_red_hat_scheme`
utility or script function.
```

```

L143: def _looks_like_slackware_scheme() -> bool:    Function `_looks_like_slackware_scheme`
utility or script function.
L159: def _looks_like_msys2_mingw_scheme() -> bool:    Function
`_looks_like_msys2_mingw_scheme` utility or script function.
L177: def _warn_mismatched(old: pathlib.Path, new: pathlib.Path, *, key: str) -> None:
Function `_warn_mismatched` utility or script function.
L187: def _warn_if_mismatch(old: pathlib.Path, new: pathlib.Path, *, key: str) -> bool:
Function `_warn_if_mismatch` utility or script function.
L195: def _log_context(    Function `_log_context` utility or script function.
L213: def get_scheme(    Function `get_scheme` Returns or fetches data.
L379: def get_bin_prefix() -> str:    Function `get_bin_prefix` Returns or fetches data.
L390: def get_bin_user() -> str:    Function `get_bin_user` Returns or fetches data.
L394: def _looks_like_deb_system_dist_packages(value: str) -> bool:    Function
`_looks_like_deb_system_dist_packages` utility or script function.
L411: def get_purelib() -> str:    Function `get_purelib` Returns or fetches data.
L425: def get_platlib() -> str:    Function `get_platlib` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/locations/_sysconfig.py

```

L33: def _should_use_osx_framework_prefix() -> bool:    Function
`_should_use_osx_framework_prefix` utility or script function.
L59: def _infer_prefix() -> str:    Function `_infer_prefix` utility or script function.
L90: def _infer_user() -> str:    Function `_infer_user` utility or script function.
L105: def _infer_home() -> str:    Function `_infer_home` utility or script function.
L128: def get_scheme(    Function `get_scheme` Returns or fetches data.
L206: def get_bin_prefix() -> str:    Function `get_bin_prefix` Returns or fetches data.
L213: def get_purelib() -> str:    Function `get_purelib` Returns or fetches data.
L217: def get_platlib() -> str:    Function `get_platlib` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/base.py

```

L44: class BaseEntryPoint(Protocol):    Class (`BaseEntryPoint`) component used by the app
(see file context: None).
L46: def name(self) -> str:    Function `name` utility or script function.
L50: def value(self) -> str:    Function `value` utility or script function.
L54: def group(self) -> str:    Function `group` utility or script function.
L58: def _convert_installed_files_path(    Function `_convert_installed_files_path` utility
or script function.
L88: class RequiresEntry(NamedTuple):    Class (`RequiresEntry`) component used by the app
(see file context: None).

```

```

L94: class BaseDistribution(Protocol):    Class (`BaseDistribution`) component used by the
app (see file context: None).
L96: def from_directory(cls, directory: str) -> BaseDistribution:    Function `from_directory`
utility or script function.
L104: def from_metadata_file_contents(    Function `from_metadata_file_contents` utility or
script function.
L122: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:    Function
`from_wheel` utility or script function.
L135: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L138: def __str__(self) -> str:    Function `__str__` utility or script function.
L142: def location(self) -> str | None:    Function `location` utility or script function.
L156: def editable_project_location(self) -> str | None:    Function
`editable_project_location` utility or script function.
L178: def installed_location(self) -> str | None:    Function `installed_location` utility or
script function.
L191: def info_location(self) -> str | None:    Function `info_location` utility or script
function.
L207: def installed_by_distutils(self) -> bool:    Function `installed_by_distutils` utility
or script function.
L220: def installed_as_egg(self) -> bool:    Function `installed_as_egg` utility or script
function.
L234: def installed_with_setuptools_egg_info(self) -> bool:    Function
`installed_with_setuptools_egg_info` utility or script function.
L252: def installed_with_dist_info(self) -> bool:    Function `installed_with_dist_info`
utility or script function.
L268: def canonical_name(self) -> NormalizedName:    Function `canonical_name` utility or
script function.
L272: def version(self) -> Version:    Function `version` utility or script function.
L276: def raw_version(self) -> str:    Function `raw_version` utility or script function.
L280: def setuptools_filename(self) -> str:    Function `setuptools_filename` Sets or updates
a value.
L288: def direct_url(self) -> DirectUrl | None:    Function `direct_url` utility or script
function.
L314: def installer(self) -> str:    Function `installer` utility or script function.
L326: def requested(self) -> bool:    Function `requested` utility or script function.
L330: def editable(self) -> bool:    Function `editable` utility or script function.
L334: def local(self) -> bool:    Function `local` utility or script function.
L344: def in_usersite(self) -> bool:    Function `in_usersite` utility or script function.
L350: def in_site_packages(self) -> bool:    Function `in_site_packages` utility or script
function.
L355: def is_file(self, path: InfoPath) -> bool:    Function `is_file` utility or script
function.
L359: def iter_distutils_script_names(self) -> Iterator[str]:    Function
`iter_distutils_script_names` utility or script function.
L367: def read_text(self, path: InfoPath) -> str:    Function `read_text` utility or script
function.
L376: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:    Function `iter_entry_points`
utility or script function.
L379: def _metadata_impl(self) -> email.message.Message:    Function `_metadata_impl` utility
or script function.
L383: def metadata(self) -> email.message.Message:    Function `metadata` utility or script

```

```

function.
L396: def metadata_dict(self) -> dict[str, Any]:    Function `metadata_dict`    utility or
script function.
L407: def metadata_version(self) -> str | None:    Function `metadata_version`    utility or
script function.
L412: def raw_name(self) -> str:    Function `raw_name`    utility or script function.
L419: def requires_python(self) -> SpecifierSet:    Function `requires_python`    utility or
script function.
L437: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
Function `iter_dependencies`    utility or script function.
L445: def iter_raw_dependencies(self) -> Iterable[str]:    Function `iter_raw_dependencies`
utility or script function.
L449: def iter_provided_extras(self) -> Iterable[NormalizedName]:    Function
`iter_provided_extras`    utility or script function.
L461: def _iter_declared_entries_from_record(self) -> Iterator[str] | None:    Function
`_iter_declared_entries_from_record`    utility or script function.
L469: def _iter_declared_entries_from_legacy(self) -> Iterator[str] | None:    Function
`_iter_declared_entries_from_legacy`    utility or script function.
L490: def iter_declared_entries(self) -> Iterator[str] | None:    Function
`iter_declared_entries`    utility or script function.
L506: def _iter_requires_txt_entries(self) -> Iterator[RequiresEntry]:    Function
`_iter_requires_txt_entries`    utility or script function.
L531: def _iter_egg_info_extras(self) -> Iterable[str]:    Function `_iter_egg_info_extras`
utility or script function.
L541: def _iter_egg_info_dependencies(self) -> Iterable[str]:    Function
`_iter_egg_info_dependencies`    utility or script function.
L569: def _add_egg_info_requires(self, metadata: email.message.Message) -> None:    Function
`_add_egg_info_requires`    utility or script function.
L579: class BaseEnvironment:    Class (`BaseEnvironment`)    component used by the app (see file
context: None).
L583: def default(cls) -> BaseEnvironment:    Function `default`    utility or script function.
L587: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:    Function
`from_paths`    utility or script function.
L590: def get_distribution(self, name: str) -> BaseDistribution | None:    Function
`get_distribution`    Returns or fetches data.
L598: def _iter_distributions(self) -> Iterator[BaseDistribution]:    Function
`_iter_distributions`    utility or script function.
L607: def iter_all_distributions(self) -> Iterator[BaseDistribution]:    Function
`iter_all_distributions`    utility or script function.
L628: def iter_installed_distributions(    Function `iter_installed_distributions`    utility or
script function.
L664: class Wheel(Protocol):    Class (`Wheel`)    component used by the app (see file context:
None).
L667: def as_zipfile(self) -> zipfile.ZipFile:    Function `as_zipfile`    utility or script
function.
L671: class FilesystemWheel(Wheel):    Class (`FilesystemWheel`)    component used by the app
(see file context: None).
L672: def __init__(self, location: str) -> None:    Function `__init__`    utility or script
function.
L675: def as_zipfile(self) -> zipfile.ZipFile:    Function `as_zipfile`    utility or script
function.

```

```

L679: class MemoryWheel(Wheel):    Class (`MemoryWheel`)    component used by the app (see file
context: None).
L680: def __init__(self, location: str, stream: IO[bytes]) -> None:    Function `__init__`
utility or script function.
L684: def as_zipfile(self) -> zipfile.ZipFile:    Function `as_zipfile`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/_json.py

```

L40: def json_name(field: str) -> str:    Function `json_name`    utility or script function.
L44: def msg_to_json(msg: Message) -> dict[str, Any]:    Function `msg_to_json`    utility or
script function.
L47: def sanitise_header(h: Header | str) -> str:    Function `sanitise_header`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/_init_.py

```

L30: def _should_use_importlib_metadata() -> bool:    Function
`_should_use_importlib_metadata`    utility or script function.
L63: def _emit_pkg_resources_deprecation_if_needed() -> None:    Function
`_emit_pkg_resources_deprecation_if_needed`    utility or script function.
L88: class Backend(Protocol):    Class (`Backend`)    component used by the app (see file
context: None).
L95: def select_backend() -> Backend:    Function `select_backend`    utility or script
function.
L108: def get_default_environment() -> BaseEnvironment:    Function `get_default_environment`
Returns or fetches data.
L118: def get_environment(paths: list[str] | None) -> BaseEnvironment:    Function
`get_environment`    Returns or fetches data.
L128: def get_directory_distribution(directory: str) -> BaseDistribution:    Function
`get_directory_distribution`    Returns or fetches data.
L137: def get_wheel_distribution(    Function `get_wheel_distribution`    Returns or fetches
data.
L150: def get_metadata_distribution(    Function `get_metadata_distribution`    Returns or
fetches data.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pip/_internal/metadata/pkg_resources.py

```

L39: class EntryPoint(NamedTuple):    Class (`EntryPoint`)    component used by the app (see
file context: None).
L45: class InMemoryMetadata:    Class (`InMemoryMetadata`)    component used by the app (see
file context: None).
L51: def __init__(self, metadata: Mapping[str, bytes], wheel_name: str) -> None:    Function
`__init__`    utility or script function.
L55: def has_metadata(self, name: str) -> bool:    Function `has_metadata`    utility or script
function.
L58: def get_metadata(self, name: str) -> str:    Function `get_metadata`    Returns or fetches
data.
L67: def get_metadata_lines(self, name: str) -> Iterable[str]:    Function
`get_metadata_lines`    Returns or fetches data.
L70: def metadata_isdir(self, name: str) -> bool:    Function `metadata_isdir`    utility or
script function.
L73: def metadata_listdir(self, name: str) -> list[str]:    Function `metadata_listdir`
utility or script function.
L76: def run_script(self, script_name: str, namespace: str) -> None:    Function `run_script`
utility or script function.
L80: class Distribution(BaseDistribution):    Class (`Distribution`)    component used by the
app (see file context: None).
L81: def __init__(self, dist: pkg_resources.Distribution) -> None:    Function `__init__`
utility or script function.
L88: def _extra_mapping(self) -> Mapping[NormalizedName, str]:    Function `_extra_mapping`
utility or script function.
L97: def from_directory(cls, directory: str) -> BaseDistribution:    Function `from_directory`
utility or script function.
L117: def from_metadata_file_contents(    Function `from_metadata_file_contents`    utility or
script function.
L134: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:    Function
`from_wheel`    utility or script function.
L155: def location(self) -> str | None:    Function `location`    utility or script function.
L159: def installed_location(self) -> str | None:    Function `installed_location`    utility or
script function.
L170: def info_location(self) -> str | None:    Function `info_location`    utility or script
function.
L174: def installed_by_distutils(self) -> bool:    Function `installed_by_distutils`    utility
or script function.
L184: def canonical_name(self) -> NormalizedName:    Function `canonical_name`    utility or
script function.
L188: def version(self) -> Version:    Function `version`    utility or script function.
L192: def raw_version(self) -> str:    Function `raw_version`    utility or script function.
L195: def is_file(self, path: InfoPath) -> bool:    Function `is_file`    utility or script
function.
L198: def iter_distutils_script_names(self) -> Iterator[str]:    Function
`iter_distutils_script_names`    utility or script function.
L201: def read_text(self, path: InfoPath) -> str:    Function `read_text`    utility or script

```

```

function.
L210: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:    Function `iter_entry_points`
    utility or script function.
L216: def _metadata_impl(self) -> email.message.Message:    Function `_metadata_impl`    utility
    or script function.
L238: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
    Function `iter_dependencies`    utility or script function.
L246: def iter_provided_extras(self) -> Iterable[NormalizedName]:    Function
    `iter_provided_extras`    utility or script function.
L250: class Environment(BaseEnvironment):    Class (`Environment`)    component used by the app
    (see file context: None).
L251: def __init__(self, ws: pkg_resources.WorkingSet) -> None:    Function `__init__`
    utility or script function.
L255: def default(cls) -> BaseEnvironment:    Function `default`    utility or script function.
L259: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:    Function
    `from_paths`    utility or script function.
L262: def _iter_distributions(self) -> Iterator[BaseDistribution]:    Function
    `_iter_distributions`    utility or script function.
L266: def _search_distribution(self, name: str) -> BaseDistribution | None:    Function
    `_search_distribution`    utility or script function.
L278: def get_distribution(self, name: str) -> BaseDistribution | None:    Function
    `get_distribution`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_compat.py

```

L10: class BadMetadata(ValueError):    Class (`BadMetadata`)    component used by the app (see
    file context: None).
L11: def __init__(self, dist: importlib.metadata.Distribution, *, reason: str) -> None:
    Function `__init__`    utility or script function.
L15: def __str__(self) -> str:    Function `__str__`    utility or script function.
L19: class BasePath(Protocol):    Class (`BasePath`)    component used by the app (see file
    context: None).
L31: def name(self) -> str:    Function `name`    utility or script function.
L35: def parent(self) -> BasePath:    Function `parent`    utility or script function.
L39: def get_info_location(d: importlib.metadata.Distribution) -> BasePath | None:    Function
    `get_info_location`    Returns or fetches data.
L51: def parse_name_and_version_from_info_directory(    Function
    `parse_name_and_version_from_info_directory`    utility or script function.
L75: def get_dist_canonical_name(dist: importlib.metadata.Distribution) -> NormalizedName:
    Function `get_dist_canonical_name`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_compat.py

ortlib/_envs.py

```

L28: def _looks_like_wheel(location: str) -> bool:    Function `_looks_like_wheel` utility or
script function.
L40: class _DistributionFinder:    Class (`_DistributionFinder`) component used by the app
(see file context: None).
L55: def __init__(self) -> None:    Function `__init__` utility or script function.
L58: def _find_impl(self, location: str) -> Iterator[FoundResult]:    Function `_find_impl`
utility or script function.
L79: def find(self, location: str) -> Iterator[BaseDistribution]:    Function `find` utility
or script function.
L91: def find_legacy_editables(self, location: str) -> Iterator[BaseDistribution]:    Function
`find_legacy_editables` utility or script function.
L116: class Environment(BaseEnvironment):    Class (`Environment`) component used by the app
(see file context: None).
L117: def __init__(self, paths: Sequence[str]) -> None:    Function `__init__` utility or
script function.
L121: def default(cls) -> BaseEnvironment:    Function `default` utility or script function.
L125: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:    Function
`from_paths` utility or script function.
L130: def _iter_distributions(self) -> Iterator[BaseDistribution]:    Function
`_iter_distributions` utility or script function.
L136: def get_distribution(self, name: str) -> BaseDistribution | None:    Function
`get_distribution` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/metadata/imp

ortlib/_dists.py

```

L38: class WheelDistribution(importlib.metadata.Distribution):    Class (`WheelDistribution`)
component used by the app (see file context: None).
L49: def __init__(    Function `__init__` utility or script function.
L58: def from_zipfile(    Function `from_zipfile` utility or script function.
L77: def iterdir(self, path: InfoPath) -> Iterator[pathlib.PurePosixPath]:    Function
`iterdir` utility or script function.
L83: def read_text(self, filename: str) -> str | None:    Function `read_text` utility or
script function.
L96: def locate_file(self, path: str | PathLike[str]) -> pathlib.Path:    Function
`locate_file` utility or script function.
L102: class Distribution(BaseDistribution):    Class (`Distribution`) component used by the
app (see file context: None).
L103: def __init__(    Function `__init__` utility or script function.
L114: def from_directory(cls, directory: str) -> BaseDistribution:    Function
`from_directory` utility or script function.
L120: def from_metadata_file_contents(    Function `from_metadata_file_contents` utility or
script function.

```

```

L137: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:    Function
`from_wheel` utility or script function.
L146: def location(self) -> str | None:    Function `location` utility or script function.
L152: def info_location(self) -> str | None:    Function `info_location` utility or script
function.
L158: def installed_location(self) -> str | None:    Function `installed_location` utility or
script function.
L164: def canonical_name(self) -> NormalizedName:    Function `canonical_name` utility or
script function.
L168: def version(self) -> Version:    Function `version` utility or script function.
L179: def raw_version(self) -> str:    Function `raw_version` utility or script function.
L182: def is_file(self, path: InfoPath) -> bool:    Function `is_file` utility or script
function.
L185: def iter_distutils_script_names(self) -> Iterator[str]:    Function
`iter_distutils_script_names` utility or script function.
L194: def read_text(self, path: InfoPath) -> str:    Function `read_text` utility or script
function.
L200: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:    Function `iter_entry_points`
utility or script function.
L204: def _metadata_impl(self) -> email.message.Message:    Function `_metadata_impl` utility
or script function.
L218: def iter_provided_extras(self) -> Iterable[NormalizedName]:    Function
`iter_provided_extras` utility or script function.
L224: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
Function `iter_dependencies` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_install.py

```

L62: class InstallRequirement:    Class (`InstallRequirement`) component used by the app (see
file context: None).
L69: def __init__(    Function `__init__` utility or script function.
L191: def __str__(self) -> str:    Function `__str__` utility or script function.
L215: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L221: def format_debug(self) -> str:    Function `format_debug` utility or script function.
L234: def name(self) -> str | None:    Function `name` utility or script function.
L240: def supports_pyproject_editable(self) -> bool:    Function `supports_pyproject_editable`
utility or script function.
L250: def specifier(self) -> SpecifierSet:    Function `specifier` utility or script
function.
L255: def is_direct(self) -> bool:    Function `is_direct` utility or script function.
L260: def is_pinned(self) -> bool:    Function `is_pinned` utility or script function.
L269: def match_markers(self, extras_requested: Iterable[str] | None = None) -> bool:
Function `match_markers` utility or script function.
L282: def has_hash_options(self) -> bool:    Function `has_hash_options` utility or script
function.

```

```

L291: def hashes(self, trust_internet: bool = True) -> Hashes:    Function `hashes` utility
or script function.
L318: def from_path(self) -> str | None:    Function `from_path` utility or script function.
L333: def ensure_build_location(    Function `ensure_build_location` utility or script
function.
L376: def _set_requirement(self) -> None:    Function `_set_requirement` utility or script
function.
L398: def warn_on_mismatching_name(self) -> None:    Function `warn_on_mismatching_name`
utility or script function.
L416: def check_if_exists(self, use_user_site: bool) -> None:    Function `check_if_exists`
utility or script function.
L455: def is_wheel(self) -> bool:    Function `is_wheel` utility or script function.
L461: def is_wheel_from_cache(self) -> bool:    Function `is_wheel_from_cache` utility or
script function.
L468: def unpacked_source_directory(self) -> str:    Function `unpacked_source_directory`
utility or script function.
L475: def setup_py_path(self) -> str:    Function `setup_py_path` Sets or updates a value.
L482: def pyproject_toml_path(self) -> str:    Function `pyproject_toml_path` utility or
script function.
L486: def load_pyproject_toml(self) -> None:    Function `load_pyproject_toml` Loads data
from storage or remote.
L506: def editable_sanity_check(self) -> None:    Function `editable_sanity_check` utility or
script function.
L519: def prepare_metadata(self) -> None:    Function `prepare_metadata` utility or script
function.
L555: def metadata(self) -> Any:    Function `metadata` utility or script function.
L561: def set_dist(self, distribution: BaseDistribution) -> None:    Function `set_dist` Sets
or updates a value.
L564: def get_dist(self) -> BaseDistribution:    Function `get_dist` Returns or fetches data.
L580: def assert_source_matches_version(self) -> None:    Function
`assert_source_matches_version` utility or script function.
L598: def ensure_has_source_dir(    Function `ensure_has_source_dir` utility or script
function.
L620: def needs_unpacked_archive(self, archive_source: Path) -> None:    Function
`needs_unpacked_archive` utility or script function.
L624: def ensure_pristine_source_checkout(self) -> None:    Function
`ensure_pristine_source_checkout` utility or script function.
L642: def update_editable(self) -> None:    Function `update_editable` utility or script
function.
L662: def uninstall(    Function `uninstall` utility or script function.
L688: def _get_archive_name(self, path: str, parentdir: str, rootdir: str) -> str:    Function
`_get_archive_name` utility or script function.
L689: def _clean_zip_name(name: str, prefix: str) -> str:    Function `_clean_zip_name`
utility or script function.
L702: def archive(self, build_dir: str | None) -> None:    Function `archive` utility or
script function.
L769: def install(    Function `install` utility or script function.
L804: def check_invalid_constraint_type(req: InstallRequirement) -> str:    Function
`check_invalid_constraint_type` utility or script function.
L832: def _has_option(options: Values, reqs: list[InstallRequirement], option: str) -> bool:
Function `_has_option` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/pep723.py

```
L9: class PEP723Exception(ValueError):    Class (`PEP723Exception`) component used by the app
(see file context: None).
L12: def __init__(self, msg: str) -> None:    Function `__init__` utility or script function.
L16: def pep723_metadata(scriptfile: str) -> dict[str, Any]:    Function `pep723_metadata`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_set.py

```
L11: class RequirementSet:    Class (`RequirementSet`) component used by the app (see file
context: None).
L12: def __init__(self, check_supported_wheels: bool = True) -> None:    Function `__init__`
utility or script function.
L20: def __str__(self) -> str:    Function `__str__` utility or script function.
L27: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L40: def add_unnamed_requirement(self, install_req: InstallRequirement) -> None:    Function
`add_unnamed_requirement` utility or script function.
L44: def add_named_requirement(self, install_req: InstallRequirement) -> None:    Function
`add_named_requirement` utility or script function.
L50: def has_requirement(self, name: str) -> bool:    Function `has_requirement` utility or
script function.
L58: def get_requirement(self, name: str) -> InstallRequirement:    Function `get_requirement`
Returns or fetches data.
L67: def all_requirements(self) -> list[InstallRequirement]:    Function `all_requirements`
utility or script function.
L71: def requirements_to_install(self) -> list[InstallRequirement]:    Function
`requirements_to_install` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/__init__.py

```
L26: class InstallationResult:    Class (`InstallationResult`) component used by the app (see
file context: None).
L30: def _validate_requirements(    Function `_validate_requirements` utility or script
function.
L38: def install_given_reqs(    Function `install_given_reqs` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/constructors.py

```

L58: def _strip_extras(path: str) -> tuple[str, str | None]:    Function `_strip_extras`
utility or script function.
L70: def convert_extras(extras: str | None) -> set[str]:    Function `convert_extras` utility
or script function.
L76: def _set_requirement_extras(req: Requirement, new_extras: set[str]) -> Requirement:
Function `_set_requirement_extras` utility or script function.
L101: def _parse_direct_url_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
Function `_parse_direct_url_editable` utility or script function.
L119: def _parse_pip_syntax_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
Function `_parse_pip_syntax_editable` utility or script function.
L148: def parse_editable(editable_req: str) -> tuple[str | None, str, set[str]]:    Function
`parse_editable` utility or script function.
L182: def check_first_requirement_in_file(filename: str) -> None:    Function
`check_first_requirement_in_file` utility or script function.
L210: def deduce_helpful_msg(req: str) -> str:    Function `deduce_helpful_msg` utility or
script function.
L236: class RequirementParts:    Class (`RequirementParts`) component used by the app (see
file context: None).
L243: def parse_req_from_editable(editable_req: str) -> RequirementParts:    Function
`parse_req_from_editable` utility or script function.
L262: def install_req_from_editable(    Function `install_req_from_editable` utility or
script function.
L292: def _looks_like_path(name: str) -> bool:    Function `_looks_like_path` utility or
script function.
L311: def _get_url_from_path(path: str, name: str) -> str | None:    Function
`_get_url_from_path` utility or script function.
L345: def parse_req_from_line(name: str, line_source: str | None) -> RequirementParts:
Function `parse_req_from_line` utility or script function.
L393: def with_source(text: str) -> str:    Function `with_source` utility or script
function.
L398: def _parse_req_string(req_as_string: str) -> Requirement:    Function
`_parse_req_string` utility or script function.
L424: def install_req_from_line(    Function `install_req_from_line` utility or script
function.
L457: def install_req_from_req_string(    Function `install_req_from_req_string` utility or
script function.
L493: def install_req_from_parsed_requirement(    Function
`install_req_from_parsed_requirement` utility or script function.
L525: def install_req_from_link_and_ireq(    Function `install_req_from_link_and_ireq`
utility or script function.
L541: def install_req_drop_extras(ireq: InstallRequirement) -> InstallRequirement:    Function
`install_req_drop_extras` utility or script function.
L565: def install_req_extend_extras(    Function `install_req_extend_extras` utility or
script function.
L583: def _pylock_hashes_to_hash_options(hashes: Mapping[str, str]) -> dict[str, list[str]]:

```

```
Function `_pylock_hashes_to_hash_options` utility or script function.
L587: def install_req_from_pylock_package( Function `_install_req_from_pylock_package`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_file.py

```
L105: class ParsedRequirement: Class (`ParsedRequirement`) component used by the app (see
file context: None).
L115: class ParsedLine: Class (`ParsedLine`) component used by the app (see file context:
None).
L123: def is_editable(self) -> bool: Function `_is_editable` utility or script function.
L127: def requirement(self) -> str | None: Function `_requirement` utility or script
function.
L136: def parse_requirements( Function `_parse_requirements` utility or script function.
L163: def preprocess(content: str) -> ReqFileLines: Function `_preprocess` utility or
script function.
L175: def handle_requirement_line( Function `_handle_requirement_line` utility or script
function.
L209: def handle_option_line( Function `_handle_option_line` utility or script function.
L287: def handle_line( Function `_handle_line` utility or script function.
L331: class RequirementsFileParser: Class (`RequirementsFileParser`) component used by the
app (see file context: None).
L332: def __init__( Function `__init__` utility or script function.
L340: def parse( Function `_parse` utility or script function.
L348: def _parse_and_recurse( Function `_parse_and_recurse` utility or script function.
L400: def _parse_file( Function `_parse_file` utility or script function.
L424: def get_line_parser(finder: PackageFinder | None) -> LineParser: Function
`get_line_parser` Returns or fetches data.
L425: def parse_line(line: str) -> tuple[str, Values]: Function `_parse_line` utility or
script function.
L449: def break_args_options(line: str) -> tuple[str, str]: Function `_break_args_options`
utility or script function.
L466: class OptionParsingError(Exception): Class (`OptionParsingError`) component used by
the app (see file context: None).
L467: def __init__(self, msg: str) -> None: Function `__init__` utility or script
function.
L471: def build_parser() -> optparse.OptionParser: Function `_build_parser` Constructs or
prepares an object.
L484: def parser_exit(self: Any, msg: str) -> NoReturn: Function `_parser_exit` utility or
script function.
L494: def join_lines(lines_enum: ReqFileLines) -> ReqFileLines: Function `_join_lines`
utility or script function.
L525: def ignore_comments(lines_enum: ReqFileLines) -> ReqFileLines: Function
`ignore_comments` utility or script function.
L536: def expand_env_variables(lines_enum: ReqFileLines) -> ReqFileLines: Function
```

```
`expand_env_variables` utility or script function.
L563: def get_file_content( Function `get_file_content` Returns or fetches data.
L596: def _decode_req_file(data: bytes, url: str) -> str: Function `_decode_req_file`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_dependency_group.py

```
L11: def parse_dependency_groups(groups: list[tuple[str, str]]) -> list[str]: Function
`parse_dependency_groups` utility or script function.
L21: def _resolve_all_groups( Function `_resolve_all_groups` utility or script function.
L41: def _build_resolvers(paths: Iterable[str]) -> dict[str, Any]: Function
`_build_resolvers` utility or script function.
L72: def _load_pyproject(path: str) -> dict[str, Any]: Function `_load_pyproject` utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/req/req_uninstall.py

```
L24: def _script_names( Function `_script_names` utility or script function.
L43: def _unique( Function `_unique` utility or script function.
L47: def unique(*args: Any, **kw: Any) -> Generator[Any, None, None]: Function `unique`
utility or script function.
L58: def uninstallation_paths(dist: BaseDistribution) -> Generator[str, None, None]:
Function `uninstallation_paths` utility or script function.
L91: def compact(paths: Iterable[str]) -> set[str]: Function `compact` utility or script
function.
L110: def compress_for_rename(paths: Iterable[str]) -> set[str]: Function
`compress_for_rename` utility or script function.
L121: def norm_join(*a: str) -> str: Function `norm_join` utility or script function.
L144: def compress_for_output_listing(paths: Iterable[str]) -> tuple[set[str], set[str]]:
Function `compress_for_output_listing` utility or script function.
L193: class StashedUninstallPathSet: Class (`StashedUninstallPathSet`) component used by
the app (see file context: None).
L197: def __init__(self) -> None: Function `__init__` utility or script function.
L205: def _get_directory_stash(self, path: str) -> str: Function `_get_directory_stash`
utility or script function.
L219: def _get_file_stash(self, path: str) -> str: Function `_get_file_stash` utility or
script function.
L246: def stash(self, path: str) -> str: Function `stash` utility or script function.
L267: def commit(self) -> None: Function `commit` utility or script function.
L274: def rollback(self) -> None: Function `rollback` utility or script function.
```

```

L294: def can_rollback(self) -> bool:    Function `can_rollback` utility or script function.
L298: class UninstallPathSet:    Class (`UninstallPathSet`) component used by the app (see
file context: None).
L302: def __init__(self, dist: BaseDistribution) -> None:    Function `__init__` utility or
script function.
L313: def _permitted(self, path: str) -> bool:    Function `_permitted` utility or script
function.
L324: def add(self, path: str) -> None:    Function `add` utility or script function.
L343: def add_pth(self, pth_file: str, entry: str) -> None:    Function `add_pth` utility or
script function.
L352: def remove(self, auto_confirm: bool = False, verbose: bool = False) -> None:    Function
`remove` utility or script function.
L381: def _allowed_to_proceed(self, verbose: bool) -> bool:    Function `_allowed_to_proceed`
utility or script function.
L384: def _display(msg: str, paths: Iterable[str]) -> None:    Function `_display` utility or
script function.
L409: def rollback(self) -> None:    Function `rollback` utility or script function.
L422: def commit(self) -> None:    Function `commit` utility or script function.
L427: def from_dist(cls, dist: BaseDistribution) -> UninstallPathSet:    Function `from_dist`
utility or script function.
L568: def iter_scripts_to_remove(    Function `iter_scripts_to_remove` utility or script
function.
L584: class UninstallPthEntries:    Class (`UninstallPthEntries`) component used by the app
(see file context: None).
L585: def __init__(self, pth_file: str) -> None:    Function `__init__` utility or script
function.
L590: def add(self, entry: str) -> None:    Function `add` utility or script function.
L605: def remove(self) -> None:    Function `remove` utility or script function.
L632: def rollback(self) -> bool:    Function `rollback` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/base.py

```

L11: class BaseResolver:    Class (`BaseResolver`) component used by the app (see file
context: None).
L12: def resolve(    Function `resolve` utility or script function.
L17: def get_installation_order(    Function `get_installation_order` Returns or fetches
data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/base.py


```

L18: def format_name(project: NormalizedName, extras: frozenset[NormalizedName]) -> str:
Function `format_name` utility or script function.
L26: class Constraint: Class (`Constraint`) component used by the app (see file context:
None).
L33: def empty(cls) -> Constraint: Function `empty` utility or script function.
L37: def from_ireq(cls, ireq: InstallRequirement) -> Constraint: Function `from_ireq`
utility or script function.
L47: def __bool__(self) -> bool: Function `__bool__` utility or script function.
L50: def __and__(self, other: InstallRequirement) -> Constraint: Function `__and__`
utility or script function.
L69: def is_satisfied_by(self, candidate: Candidate) -> bool: Function `is_satisfied_by`
utility or script function.
L78: def format_for_error(self) -> str: Function `format_for_error` utility or script
function.
L85: class Requirement: Class (`Requirement`) component used by the app (see file context:
None).
L87: def project_name(self) -> NormalizedName: Function `project_name` utility or script
function.
L97: def name(self) -> str: Function `name` utility or script function.
L105: def is_satisfied_by(self, candidate: Candidate) -> bool: Function `is_satisfied_by`
utility or script function.
L108: def get_candidate_lookup(self) -> CandidateLookup: Function `get_candidate_lookup`
Returns or fetches data.
L111: def format_for_error(self) -> str: Function `format_for_error` utility or script
function.
L115: def _match_link(link: Link, candidate: Candidate) -> bool: Function `_match_link`
utility or script function.
L121: class Candidate: Class (`Candidate`) component used by the app (see file context:
None).
L123: def project_name(self) -> NormalizedName: Function `project_name` utility or script
function.
L133: def name(self) -> str: Function `name` utility or script function.
L142: def version(self) -> Version: Function `version` utility or script function.
L146: def is_installed(self) -> bool: Function `is_installed` utility or script function.
L150: def is_editable(self) -> bool: Function `is_editable` utility or script function.
L154: def source_link(self) -> Link | None: Function `source_link` utility or script
function.
L157: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L160: def get_install_requirement(self) -> InstallRequirement | None: Function
`get_install_requirement` Returns or fetches data.
L163: def format_for_error(self) -> str: Function `format_for_error` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/resolver.py**

```

L41: class Resolver(BaseResolver):  Class (`Resolver`) component used by the app (see file
context: None).
L44: def __init__(  Function `__init__` utility or script function.
L76: def resolve(  Function `resolve` utility or script function.
L186: def get_installation_order(  Function `get_installation_order` Returns or fetches
data.
L218: def get_topological_weights(  Function `get_topological_weights` Returns or fetches
data.
L249: def visit(node: str | None) -> None:  Function `visit` utility or script function.
L321: def _req_set_item_sorter(  Function `_req_set_item_sorter` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/reporter.py**

```

L15: class PipReporter(BaseReporter[Requirement, Candidate, str]):  Class (`PipReporter`)
component used by the app (see file context: None).
L16: def __init__(self, constraints: Mapping[str, Constraint] | None = None) -> None:
Function `__init__` utility or script function.
L39: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:  Function
`rejecting_candidate` utility or script function.
L73: class PipDebuggingReporter(BaseReporter[Requirement, Candidate, str]):  Class
(`PipDebuggingReporter`) component used by the app (see file context: None).
L76: def starting(self) -> None:  Function `starting` utility or script function.
L79: def starting_round(self, index: int) -> None:  Function `starting_round` utility or
script function.
L82: def ending_round(self, index: int, state: Any) -> None:  Function `ending_round`
utility or script function.
L86: def ending(self, state: Any) -> None:  Function `ending` utility or script function.
L89: def adding_requirement(  Function `adding_requirement` utility or script function.
L94: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:  Function
`rejecting_candidate` utility or script function.
L97: def pinning(self, candidate: Candidate) -> None:  Function `pinning` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/candidates.py**

```

L48: def as_base_candidate(candidate: Candidate) -> BaseCandidate | None:  Function
`as_base_candidate` utility or script function.
L60: def make_install_req_from_link(  Function `make_install_req_from_link` utility or
script function.

```

```

L90: def make_install_req_from_editable(    Function `make_install_req_from_editable`    utility
or script function.
L112: def _make_install_req_from_dist(    Function `_make_install_req_from_dist`    utility or
script function.
L134: class _InstallRequirementBackedCandidate(Candidate):    Class
(`_InstallRequirementBackedCandidate`)    component used by the app (see file context: None).
L140: class exposes appropriate information to the resolver.    Class (`exposes`)    component
used by the app (see file context: None).
L153: def __init__(    Function `__init__`    utility or script function.
L171: def __str__(self) -> str:    Function `__str__`    utility or script function.
L174: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L177: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L184: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L190: def source_link(self) -> Link | None:    Function `source_link`    utility or script
function.
L194: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L201: def name(self) -> str:    Function `name`    utility or script function.
L205: def version(self) -> Version:    Function `version`    utility or script function.
L210: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L217: def _prepare_distribution(self) -> BaseDistribution:    Function `_prepare_distribution`
utility or script function.
L220: def _check_metadata_consistency(self, dist: BaseDistribution) -> None:    Function
`_check_metadata_consistency`    utility or script function.
L244: def _prepare(self) -> BaseDistribution:    Function `_prepare`    utility or script
function.
L271: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies`    utility or script function.
L279: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement`    Returns or fetches data.
L283: class LinkCandidate(_InstallRequirementBackedCandidate):    Class (`LinkCandidate`)
component used by the app (see file context: None).
L286: def __init__(    Function `__init__`    utility or script function.
L335: def _prepare_distribution(self) -> BaseDistribution:    Function `_prepare_distribution`
utility or script function.
L340: class EditableCandidate(_InstallRequirementBackedCandidate):    Class
(`EditableCandidate`)    component used by the app (see file context: None).
L343: def __init__(    Function `__init__`    utility or script function.
L360: def _prepare_distribution(self) -> BaseDistribution:    Function `_prepare_distribution`
utility or script function.
L364: class AlreadyInstalledCandidate(Candidate):    Class (`AlreadyInstalledCandidate`)
component used by the app (see file context: None).
L368: def __init__(    Function `__init__`    utility or script function.
L386: def __str__(self) -> str:    Function `__str__`    utility or script function.
L389: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L392: def __eq__(self, other: object) -> bool:    Object (singleton).
L397: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L401: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L405: def name(self) -> str:    Function `name`    utility or script function.

```

```

L409: def version(self) -> Version:    Function `version` utility or script function.
L415: def is_editable(self) -> bool:    Function `is_editable` utility or script function.
L418: def format_for_error(self) -> str:  Function `format_for_error` utility or script
function.
L421: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L431: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.
L435: class ExtrasCandidate(Candidate):    Class (`ExtrasCandidate`) component used by the
app (see file context: None).
L460: def __init__(    Function `__init__` utility or script function.
L479: def __str__(self) -> str:    Function `__str__` utility or script function.
L483: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L486: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L489: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L495: def project_name(self) -> NormalizedName:    Function `project_name` utility or script
function.
L499: def name(self) -> str:    Function `name` utility or script function.
L504: def version(self) -> Version:    Function `version` utility or script function.
L507: def format_for_error(self) -> str:    Function `format_for_error` utility or script
function.
L513: def is_installed(self) -> bool:    Function `is_installed` utility or script function.
L517: def is_editable(self) -> bool:    Function `is_editable` utility or script function.
L521: def source_link(self) -> Link | None:    Function `source_link` utility or script
function.
L524: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L552: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.
L559: class RequiresPythonCandidate(Candidate):    Class (`RequiresPythonCandidate`)
component used by the app (see file context: None).
L563: def __init__(self, py_version_info: tuple[int, ...] | None) -> None:    Function
`__init__` utility or script function.
L574: def __str__(self) -> str:    Function `__str__` utility or script function.
L577: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L581: def project_name(self) -> NormalizedName:    Function `project_name` utility or script
function.
L585: def name(self) -> str:    Function `name` utility or script function.
L589: def version(self) -> Version:    Function `version` utility or script function.
L592: def format_for_error(self) -> str:    Function `format_for_error` utility or script
function.
L595: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L598: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pip/_internal/resolution/res

olvelib/provider.py

```

L56: def _get_with_identifier(    Function `_get_with_identifier`    utility or script function.
L81: class PipProvider(_ProviderBase):    Class (`PipProvider`)    component used by the app
(see file context: None).
L92: def __init__(    Function `__init__`    utility or script function.
L109: def constraints(self) -> dict[str, Constraint]:    Function `constraints`    utility or
script function.
L117: def identify(self, requirement_or_candidate: Requirement | Candidate) -> str:
Function `identify`    utility or script function.
L120: def narrow_requirement_selection(    Function `narrow_requirement_selection`    utility or
script function.
L176: def get_preference(    Function `get_preference`    Returns or fetches data.
L256: def find_matches(    Function `find_matches`    utility or script function.
L262: def _eligible_for_upgrade(identifier: str) -> bool:    Function `_eligible_for_upgrade`
utility or script function.
L300: def is_satisfied_by(requirement: Requirement, candidate: Candidate) -> bool:    Function
`is_satisfied_by`    utility or script function.
L303: def get_dependencies(self, candidate: Candidate) -> Iterable[Requirement]:    Function
`get_dependencies`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res olvelib/factory.py

```

L74: class ConflictCause(Protocol):    Class (`ConflictCause`)    component used by the app (see
file context: None).
L85: class CollectedRootRequirements(NamedTuple):    Class (`CollectedRootRequirements`)
component used by the app (see file context: None).
L91: class Factory:    Class (`Factory`)    component used by the app (see file context: None).
L92: def __init__(    Function `__init__`    utility or script function.
L132: def force_reinstall(self) -> bool:    Function `force_reinstall`    utility or script
function.
L135: def _fail_if_link_is_unsupported_wheel(self, link: Link) -> None:    Function
`_fail_if_link_is_unsupported_wheel`    utility or script function.
L144: def _make_extras_candidate(    Function `_make_extras_candidate`    utility or script
function.
L159: def _make_candidate_from_dist(    Function `_make_candidate_from_dist`    utility or
script function.
L174: def _make_candidate_from_link(    Function `_make_candidate_from_link`    utility or
script function.
L189: def _make_base_candidate_from_link(    Function `_make_base_candidate_from_link`
utility or script function.
L246: def _get_locked_installation_candidate(    Function `_get_locked_installation_candidate`
utility or script function.
L271: def _iter_found_candidates(    Function `_iter_found_candidates`    utility or script

```

```

function.
L308: def _get_installed_candidate() -> Candidate | None:    Function
`_get_installed_candidate` utility or script function.
L337: def iter_index_candidate_infos() -> Iterator[IndexCandidateInfo]:    Function
`iter_index_candidate_infos` utility or script function.
L358: def is_pinned(specifier: SpecifierSet) -> bool:    Function `is_pinned` utility or
script function.
L392: def _iter_explicit_candidates_from_base(    Function
`_iter_explicit_candidates_from_base` utility or script function.
L414: def _iter_candidates_from_constraints(    Function `_iter_candidates_from_constraints`
utility or script function.
L448: def find_candidates(    Function `find_candidates` utility or script function.
L525: def _make_requirements_from_install_req(    Function
`_make_requirements_from_install_req` utility or script function.
L578: def collect_root_requirements(    Function `collect_root_requirements` utility or
script function.
L620: def make_requirement_from_candidate(    Function `make_requirement_from_candidate`
utility or script function.
L625: def make_requirements_from_spec(    Function `make_requirements_from_spec` utility or
script function.
L643: def make_requires_python_requirement(    Function `make_requires_python_requirement`
utility or script function.
L654: def get_wheel_cache_entry(self, link: Link, name: str | None) -> CacheEntry | None:
Function `get_wheel_cache_entry` Returns or fetches data.
L671: def get_dist_to_uninstall(self, candidate: Candidate) -> BaseDistribution | None:
Function `get_dist_to_uninstall` Returns or fetches data.
L699: def _report_requires_python_error(    Function `_report_requires_python_error` utility
or script function.
L721: def _report_single_requirement_conflict(    Function
`_report_single_requirement_conflict` utility or script function.
L783: def _has_any_candidates(self, project_name: str) -> bool:    Function
`_has_any_candidates` utility or script function.
L798: def get_installation_error(    Function `get_installation_error` Returns or fetches
data.
L834: def text_join(parts: list[str]) -> str:    Function `text_join` utility or script
function.
L840: def describe_trigger(parent: Candidate) -> str:    Function `describe_trigger` utility
or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/requirements.py**

```

L14: class ExplicitRequirement(Requirement):    Class (`ExplicitRequirement`) component used
by the app (see file context: None).
L15: def __init__(self, candidate: Candidate) -> None:    Function `__init__` utility or
script function.

```

```

L18: def __str__(self) -> str:    Function `__str__`    utility or script function.
L21: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L24: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L27: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L33: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L38: def name(self) -> str:    Function `name`    utility or script function.
L42: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L45: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L48: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L52: class SpecifierRequirement(Requirement):    Class (`SpecifierRequirement`)    component
used by the app (see file context: None).
L53: def __init__(self, ireq: InstallRequirement) -> None:    Function `__init__`    utility or
script function.
L61: def _equal(self) -> str:    Function `_equal`    utility or script function.
L68: def __str__(self) -> str:    Function `__str__`    utility or script function.
L71: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L74: def __eq__(self, other: object) -> bool:    Object (singleton).
L79: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L87: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L92: def name(self) -> str:    Function `name`    utility or script function.
L95: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L108: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L111: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L124: class SpecifierWithoutExtrasRequirement(SpecifierRequirement):    Class
(`SpecifierWithoutExtrasRequirement`)    component used by the app (see file context: None).
L130: def __init__(self, ireq: InstallRequirement) -> None:    Function `__init__`    utility or
script function.
L138: def _equal(self) -> str:    Function `_equal`    utility or script function.
L145: def __eq__(self, other: object) -> bool:    Object (singleton).
L150: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L158: class RequiresPythonRequirement(Requirement):    Class (`RequiresPythonRequirement`)
component used by the app (see file context: None).
L161: def __init__(self, specifier: SpecifierSet, match: Candidate) -> None:    Function
`__init__`    utility or script function.
L173: def __str__(self) -> str:    Function `__str__`    utility or script function.
L176: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L179: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L186: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L195: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L199: def name(self) -> str:    Function `name`    utility or script function.
L202: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.

```

```

L205: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L208: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L216: class UnsatisfiableRequirement(Requirement):    Class (`UnsatisfiableRequirement`)
component used by the app (see file context: None).
L219: def __init__(self, name: NormalizedName) -> None:    Function `__init__`    utility or
script function.
L222: def __str__(self) -> str:    Function `__str__`    utility or script function.
L225: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L228: def __eq__(self, other: object) -> bool:    Object (singleton).
L233: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L237: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L241: def name(self) -> str:    Function `name`    utility or script function.
L244: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L247: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L250: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/res
olvelib/found_candidates.py**

```

L28: def _iter_built(infos: Iterator[IndexCandidateInfo]) -> Iterator[Candidate]:    Function
`_iter_built`    utility or script function.
L59: def _iter_built_with_prepended(    Function `_iter_built_with_prepended`    utility or
script function.
L81: def _iter_built_with_inserted(    Function `_iter_built_with_inserted`    utility or script
function.
L113: class FoundCandidates(Sequence[Candidate]):    Class (`FoundCandidates`)    component used
by the app (see file context: None).
L122: def __init__(    Function `__init__`    utility or script function.
L135: def __getitem__(self, index: Any) -> Any:    Function `__getitem__`    utility or script
function.
L141: def __iter__(self) -> Iterator[Candidate]:    Function `__iter__`    utility or script
function.
L151: def __len__(self) -> int:    Function `__len__`    utility or script function.
L157: def __bool__(self) -> bool:    Function `__bool__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/resolution/leg

acy/resolver.py

```

L58: def _check_dist_requires_python(    Function `_check_dist_requires_python`    utility or
script function.
L112: class Resolver(BaseResolver):    Class (`Resolver`)    component used by the app (see file
context: None).
L119: def __init__(    Function `__init__`    utility or script function.
L157: def resolve(    Function `resolve`    utility or script function.
L194: def _add_requirement_to_set(    Function `_add_requirement_to_set`    utility or script
function.
L309: def _is_upgrade_allowed(self, req: InstallRequirement) -> bool:    Function
`_is_upgrade_allowed`    utility or script function.
L318: def _set_req_to_reinstall(self, req: InstallRequirement) -> None:    Function
`_set_req_to_reinstall`    utility or script function.
L329: def _check_skip_installed(self, req_to_install: InstallRequirement) -> str | None:
Function `_check_skip_installed`    utility or script function.
L381: def _find_requirement_link(self, req: InstallRequirement) -> Link | None:    Function
`_find_requirement_link`    utility or script function.
L403: def _populate_link(self, req: InstallRequirement) -> None:    Function `_populate_link`
utility or script function.
L442: def _get_dist_for(self, req: InstallRequirement) -> BaseDistribution:    Function
`_get_dist_for`    utility or script function.
L488: def _resolve_one(    Function `_resolve_one`    utility or script function.
L517: def add_req(subreq: Requirement, extras_requested: Iterable[str]) -> None:    Function
`add_req`    utility or script function.
L571: def get_installation_order(    Function `get_installation_order`    Returns or fetches
data.
L586: def schedule(req: InstallRequirement) -> None:    Function `schedule`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/index/collecto r.py

```

L46: def _match_vcs_scheme(url: str) -> str | None:    Function `_match_vcs_scheme`    utility
or script function.
L57: class _NotAPIContent(Exception):    Class (`_NotAPIContent`)    component used by the app
(see file context: None).
L58: def __init__(self, content_type: str, request_desc: str) -> None:    Function `__init__`
utility or script function.
L64: def _ensure_api_header(response: Response) -> None:    Function `_ensure_api_header`
utility or script function.
L86: class _NotHTTP(Exception):    Class (`_NotHTTP`)    component used by the app (see file
context: None).
L90: def _ensure_api_response(url: str, session: PipSession) -> None:    Function
`_ensure_api_response`    utility or script function.

```

```

L108: def _get_simple_response(url: str, session: PipSession) -> Response:    Function
`_get_simple_response` utility or script function.
L171: def _get_encoding_from_headers(headers: ResponseHeaders) -> str | None:    Function
`_get_encoding_from_headers` utility or script function.
L182: class CacheablePageContent:    Class (`CacheablePageContent`) component used by the app
(see file context: None).
L183: def __init__(self, page: IndexContent) -> None:    Function `__init__` utility or
script function.
L187: def __eq__(self, other: object) -> bool:    Object (singleton).
L190: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L194: class ParseLinks(Protocol):    Class (`ParseLinks`) component used by the app (see file
context: None).
L195: def __call__(self, page: IndexContent) -> Iterable[Link]: ...    Function `__call__`
utility or script function.
L198: def with_cached_index_content(fn: ParseLinks) -> ParseLinks:    Function
`with_cached_index_content` utility or script function.
L206: def wrapper(cacheable_page: CacheablePageContent) -> list[Link]:    Function `wrapper`
utility or script function.
L210: def wrapper_wrapper(page: IndexContent) -> list[Link]:    Function `wrapper_wrapper`
utility or script function.
L219: def parse_links(page: IndexContent) -> Iterable[Link]:    Function `parse_links`
utility or script function.
L248: class IndexContent:    Class (`IndexContent`) component used by the app (see file
context: None).
L264: def __str__(self) -> str:    Function `__str__` utility or script function.
L268: class HTMLLinkParser(HTMLParser):    Class (`HTMLLinkParser`) component used by the app
(see file context: None).
L274: def __init__(self, url: str) -> None:    Function `__init__` utility or script
function.
L281: def handle_starttag(self, tag: str, attrs: list[tuple[str, str | None]]) -> None:
Function `handle_starttag` utility or script function.
L289: def get_href(self, attrs: list[tuple[str, str | None]]) -> str | None:    Function
`get_href` Returns or fetches data.
L296: def _handle_get_simple_fail(    Function `_handle_get_simple_fail` utility or script
function.
L306: def _make_index_content(    Function `_make_index_content` utility or script function.
L319: def _get_index_content(link: Link, *, session: PipSession) -> IndexContent | None:
Function `_get_index_content` utility or script function.
L379: class CollectedSources(NamedTuple):    Class (`CollectedSources`) component used by the
app (see file context: None).
L384: class LinkCollector:    Class (`LinkCollector`) component used by the app (see file
context: None).
L392: def __init__(    Function `__init__` utility or script function.
L401: def create(    Function `create` Creates a resource or document.
L435: def find_links(self) -> list[str]:    Function `find_links` utility or script function.
L438: def fetch_response(self, location: Link) -> IndexContent | None:    Function
`fetch_response` utility or script function.
L444: def collect_sources(    Function `collect_sources` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/index/source s.py

```

L31: class LinkSource:    Class (`LinkSource`) component used by the app (see file context:
None).
L33: def link(self) -> Link | None:    Function `link` utility or script function.
L37: def page_candidates(self) -> FoundCandidates:    Function `page_candidates` utility or
script function.
L41: def file_links(self) -> FoundLinks:    Function `file_links` utility or script function.
L46: def _is_html_file(file_url: str) -> bool:    Function `_is_html_file` utility or script
function.
L50: class _FlatDirectoryToUrls:    Class (`_FlatDirectoryToUrls`) component used by the app
(see file context: None).
L53: def __init__(self, path: str) -> None:    Function `__init__` utility or script
function.
L59: def _scan_directory(self) -> None:    Function `_scan_directory` utility or script
function.
L83: def page_candidates(self) -> list[str]:    Function `page_candidates` utility or script
function.
L90: def project_name_to_urls(self) -> dict[str, list[str]]:    Function
`project_name_to_urls` utility or script function.
L97: class _FlatDirectorySource(LinkSource):    Class (`_FlatDirectorySource`) component used
by the app (see file context: None).
L108: def __init__(    Function `__init__` utility or script function.
L125: def link(self) -> Link | None:    Function `link` utility or script function.
L128: def page_candidates(self) -> FoundCandidates:    Function `page_candidates` utility or
script function.
L132: def file_links(self) -> FoundLinks:    Function `file_links` utility or script
function.
L137: class _LocalFileSource(LinkSource):    Class (`_LocalFileSource`) component used by the
app (see file context: None).
L147: def __init__(    Function `__init__` utility or script function.
L156: def link(self) -> Link | None:    Function `link` utility or script function.
L159: def page_candidates(self) -> FoundCandidates:    Function `page_candidates` utility or
script function.
L164: def file_links(self) -> FoundLinks:    Function `file_links` utility or script
function.
L170: class _RemoteFileSource(LinkSource):    Class (`_RemoteFileSource`) component used by
the app (see file context: None).
L179: def __init__(    Function `__init__` utility or script function.
L190: def link(self) -> Link | None:    Function `link` utility or script function.
L193: def page_candidates(self) -> FoundCandidates:    Function `page_candidates` utility or
script function.
L198: def file_links(self) -> FoundLinks:    Function `file_links` utility or script
function.
L202: class _IndexDirectorySource(LinkSource):    Class (`_IndexDirectorySource`) component
used by the app (see file context: None).
L209: def __init__(    Function `__init__` utility or script function.

```

```

L218: def link(self) -> Link | None:    Function `link`    utility or script function.
L221: def page_candidates(self) -> FoundCandidates:    Function `page_candidates`    utility or
script function.
L224: def file_links(self) -> FoundLinks:    Function `file_links`    utility or script
function.
L228: def build_source(    Function `build_source`    Constructs or prepares an object.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/index/packag e_finder.py

```

L63: def _check_link_requires_python(    Function `_check_link_requires_python`    utility or
script function.
L110: class LinkType(enum.Enum):    Class (`LinkType`)    component used by the app (see file
context: None).
L122: class LinkEvaluator:    Class (`LinkEvaluator`)    component used by the app (see file
context: None).
L133: def __init__(    Function `__init__`    utility or script function.
L172: def evaluate_link(self, link: Link) -> tuple[LinkType, str]:    Function `evaluate_link`
utility or script function.
L283: def get_version_sort_key(v: str) -> tuple[int, ...]:    Function `get_version_sort_key`
Returns or fetches data.
L300: def filter_unallowed_hashes(    Function `filter_unallowed_hashes`    utility or script
function.
L375: class CandidatePreferences:    Class (`CandidatePreferences`)    component used by the app
(see file context: None).
L386: class BestCandidateResult:    Class (`BestCandidateResult`)    component used by the app
(see file context: None).
L402: def __post_init__(self) -> None:    Function `__post_init__`    utility or script
function.
L411: class CandidateEvaluator:    Class (`CandidateEvaluator`)    component used by the app
(see file context: None).
L418: def create(    Function `create`    Creates a resource or document.
L453: def __init__(    Function `__init__`    utility or script function.
L479: def get_applicable_candidates(    Function `get_applicable_candidates`    Returns or
fetches data.
L518: def _sort_key(self, candidate: InstallationCandidate) -> CandidateSortingKey:
Function `_sort_key`    utility or script function.
L583: def sort_best_candidate(    Function `sort_best_candidate`    utility or script function.
L596: def compute_best_candidate(    Function `compute_best_candidate`    utility or script
function.
L614: class PackageFinder:    Class (`PackageFinder`)    component used by the app (see file
context: None).
L621: def __init__(    Function `__init__`    utility or script function.
L672: def create(    Function `create`    Creates a resource or document.
L708: def target_python(self) -> TargetPython:    Function `target_python`    utility or script
function.

```

```

L712: def search_scope(self) -> SearchScope:    Function `search_scope` utility or script
function.
L716: def search_scope(self, search_scope: SearchScope) -> None:    Function `search_scope`
utility or script function.
L720: def find_links(self) -> list[str]:    Function `find_links` utility or script function.
L724: def index_urls(self) -> list[str]:    Function `index_urls` utility or script function.
L728: def proxy(self) -> str | None:    Function `proxy` utility or script function.
L732: def trusted_hosts(self) -> Iterable[str]:    Function `trusted_hosts` utility or script
function.
L737: def custom_cert(self) -> str | None:    Function `custom_cert` utility or script
function.
L745: def client_cert(self) -> str | None:    Function `client_cert` utility or script
function.
L751: def release_control(self) -> ReleaseControl | None:    Function `release_control`
utility or script function.
L754: def set_release_control(self, release_control: ReleaseControl) -> None:    Function
`set_release_control` Sets or updates a value.
L758: def prefer_binary(self) -> bool:    Function `prefer_binary` utility or script
function.
L761: def set_prefer_binary(self) -> None:    Function `set_prefer_binary` Sets or updates a
value.
L765: def uploaded_prior_to(self) -> datetime.datetime | None:    Function `uploaded_prior_to`
utility or script function.
L768: def requires_python_skipped_reasons(self) -> list[str]:    Function
`requires_python_skipped_reasons` utility or script function.
L771: def make_link_evaluator(self, project_name: str) -> LinkEvaluator:    Function
`make_link_evaluator` utility or script function.
L785: def _sort_links(self, links: Iterable[Link]) -> list[Link]:    Function `_sort_links`
utility or script function.
L801: def _log_skipped_link(self, link: Link, result: LinkType, detail: str) -> None:
Function `_log_skipped_link` utility or script function.
L808: def get_install_candidate(    Function `get_install_candidate` Returns or fetches data.
L833: def evaluate_links(    Function `evaluate_links` utility or script function.
L847: def process_project_url(    Function `process_project_url` utility or script function.
L868: def find_all_candidates(self, project_name: str) -> list[InstallationCandidate]:
Function `find_all_candidates` utility or script function.
L925: def make_candidate_evaluator(    Function `make_candidate_evaluator` utility or script
function.
L942: def find_best_candidate(    Function `find_best_candidate` utility or script function.
L971: def find_requirement(    Function `find_requirement` utility or script function.
L995: def _format_versions(cand_iter: Iterable[InstallationCandidate]) -> str:    Function
`_format_versions` utility or script function.
L1030: def _should_install_candidate(    Function `_should_install_candidate` utility or
script function.
L1072: def _find_name_version_sep(fragment: str, canonical_name: str) -> int:    Function
`_find_name_version_sep` utility or script function.
L1098: def _extract_version_from_fragment(fragment: str, canonical_name: str) -> str | None:
Function `_extract_version_from_fragment` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/lazy_wheel.py

```

L22: class HTTPRangeRequestUnsupported(Exception):    Class (`HTTPRangeRequestUnsupported`)
component used by the app (see file context: None).
L26: def dist_from_wheel_url(    Function `dist_from_wheel_url`    utility or script function.
L45: class LazyZipOverHTTP:    Class (`LazyZipOverHTTP`)    component used by the app (see file
context: None).
L54: def __init__(    Function `__init__`    utility or script function.
L71: def mode(self) -> str:    Function `mode`    utility or script function.
L76: def name(self) -> str:    Function `name`    utility or script function.
L80: def seekable(self) -> bool:    Function `seekable`    utility or script function.
L84: def close(self) -> None:    Function `close`    utility or script function.
L89: def closed(self) -> bool:    Function `closed`    utility or script function.
L93: def read(self, size: int = -1) -> bytes:    Function `read`    utility or script function.
L107: def readable(self) -> bool:    Function `readable`    utility or script function.
L111: def seek(self, offset: int, whence: int = 0) -> int:    Function `seek`    utility or
script function.
L121: def tell(self) -> int:    Function `tell`    utility or script function.
L125: def truncate(self, size: int | None = None) -> int:    Function `truncate`    utility or
script function.
L135: def writable(self) -> bool:    Function `writable`    utility or script function.
L139: def __enter__(self) -> LazyZipOverHTTP:    Function `__enter__`    utility or script
function.
L143: def __exit__(self, *exc: Any) -> None:    Function `__exit__`    utility or script
function.
L147: def _stay(self) -> Generator[None, None, None]:    Function `_stay`    utility or script
function.
L158: def _check_zip(self) -> None:    Function `_check_zip`    utility or script function.
L173: def _stream_response(    Function `_stream_response`    utility or script function.
L183: def _merge(    Function `_merge`    utility or script function.
L205: def _download(self, start: int, end: int) -> None:    Function `_download`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/session.py

```

L98: def looks_like_ci() -> bool:    Function `looks_like_ci`    utility or script function.
L109: def user_agent() -> str:    Function `user_agent`    utility or script function.
L210: class LocalFSAdapter(BaseAdapter):    Class (`LocalFSAdapter`)    component used by the
app (see file context: None).
L211: def send(    Function `send`    utility or script function.
L251: def close(self) -> None:    Function `close`    utility or script function.

```

```

L255: class _SSLContextAdapterMixin:  Class (`_SSLContextAdapterMixin`) component used by
the app (see file context: None).
L263: def __init__(  Function `__init__` utility or script function.
L272: def init_poolmanager(  Function `init_poolmanager` Initialisation routine.
L288: def proxy_manager_for(self, proxy: str, **proxy_kwargs: Any) -> ProxyManager:
Function `proxy_manager_for` utility or script function.
L296: class HTTPAdapter(_SSLContextAdapterMixin, _BaseHTTPAdapter):  Class (`HTTPAdapter`)
component used by the app (see file context: None).
L300: class CacheControlAdapter(_SSLContextAdapterMixin, _BaseCacheControlAdapter):  Class
(`CacheControlAdapter`) component used by the app (see file context: None).
L304: class InsecureHTTPAdapter(HTTPAdapter):  Class (`InsecureHTTPAdapter`) component used
by the app (see file context: None).
L305: def cert_verify(  Function `cert_verify` utility or script function.
L315: class InsecureCacheControlAdapter(CacheControlAdapter):  Class
(`InsecureCacheControlAdapter`) component used by the app (see file context: None).
L316: def cert_verify(  Function `cert_verify` utility or script function.
L326: class PipSession(requests.Session):  Class (`PipSession`) component used by the app
(see file context: None).
L329: def __init__(  Function `__init__` utility or script function.
L413: def update_index_urls(self, new_index_urls: list[str]) -> None:  Function
`update_index_urls` utility or script function.
L420: def add_trusted_host(  Function `add_trusted_host` utility or script function.
L453: def iter_secure_origins(self) -> Generator[SecureOrigin, None, None]:  Function
`iter_secure_origins` utility or script function.
L458: def is_secure_origin(self, location: Link) -> bool:  Function `is_secure_origin`
utility or script function.
L525: def request(self, method: str, url: str, *args: Any, **kwargs: Any) -> Response:  #
type: ignore[override]  Function `request` utility or script function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pip/_internal/network/cache e.py

```

L24: def is_from_cache(response: Response) -> bool:  Function `is_from_cache` utility or
script function.
L29: def suppressed_cache_errors() -> Generator[None, None, None]:  Function
`suppressed_cache_errors` utility or script function.
L39: class SafeFileCache(SeparateBodyBaseCache):  Class (`SafeFileCache`) component used by
the app (see file context: None).
L57: def __init__(self, directory: str) -> None:  Function `__init__` utility or script
function.
L62: def _get_cache_path(self, name: str) -> str:  Function `_get_cache_path` utility or
script function.
L70: def get(self, key: str) -> bytes | None:  Function `get` Returns or fetches data.
L80: def _write_to_file(self, path: str, writer_func: Callable[[BinaryIO], Any]) -> None:
Function `_write_to_file` utility or script function.
L93: def _write(self, path: str, data: bytes) -> None:  Function `_write` utility or script

```

```

function.
L96: def _write_from_io(self, path: str, source_file: BinaryIO) -> None:    Function
`_write_from_io` utility or script function.
L99: def set(    Function `set` Sets or updates a value.
L105: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L112: def get_body(self, key: str) -> BinaryIO | None:    Function `get_body` Returns or
fetches data.
L121: def set_body(self, key: str, body: bytes) -> None:    Function `set_body` Sets or
updates a value.
L125: def set_body_from_io(self, key: str, body_file: BinaryIO) -> None:    Function
`set_body_from_io` Sets or updates a value.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/utls.py

```

L31: def raise_for_status(resp: Response) -> None:    Function `raise_for_status` utility or
script function.
L59: def response_chunks(    Function `response_chunks` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/xmlrpc.py

```

L20: class PipXmlrpcTransport(xmlrpc.client.Transport):    Class (`PipXmlrpcTransport`)
component used by the app (see file context: None).
L25: def __init__(    Function `__init__` utility or script function.
L33: def request(    Function `request` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/auth.py

```

L44: class Credentials(NamedTuple):    Class (`Credentials`) component used by the app (see
file context: None).
L50: class KeyRingBaseProvider(ABC):    Class (`KeyRingBaseProvider`) component used by the
app (see file context: None).
L56: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None: ...
Function `get_auth_info` Returns or fetches data.
L59: def save_auth_info(self, url: str, username: str, password: str) -> None: ...    Function

```



```

`save_auth_info` Saves data to storage or remote.
L62: class KeyRingNullProvider(KeyRingBaseProvider):    Class (`KeyRingNullProvider`)
component used by the app (see file context: None).
L67: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:    Function
`get_auth_info` Returns or fetches data.
L70: def save_auth_info(self, url: str, username: str, password: str) -> None:    Function
`save_auth_info` Saves data to storage or remote.
L74: class KeyRingPythonProvider(KeyRingBaseProvider):    Class (`KeyRingPythonProvider`)
component used by the app (see file context: None).
L79: def __init__(self) -> None:    Function `__init__` utility or script function.
L84: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:    Function
`get_auth_info` Returns or fetches data.
L102: def save_auth_info(self, url: str, username: str, password: str) -> None:    Function
`save_auth_info` Saves data to storage or remote.
L106: class KeyRingCliProvider(KeyRingBaseProvider):    Class (`KeyRingCliProvider`)
component used by the app (see file context: None).
L117: def __init__(self, cmd: str) -> None:    Function `__init__` utility or script
function.
L120: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:    Function
`get_auth_info` Returns or fetches data.
L129: def save_auth_info(self, url: str, username: str, password: str) -> None:    Function
`save_auth_info` Saves data to storage or remote.
L132: def _get_password(self, service_name: str, username: str) -> str | None:    Function
`_get_password` utility or script function.
L150: def _set_password(self, service_name: str, username: str, password: str) -> None:
Function `_set_password` utility or script function.
L166: def get_keyring_provider(provider: str) -> KeyRingBaseProvider:    Function
`get_keyring_provider` Returns or fetches data.
L191: def PATH_as_shutil_which_determines_it() -> str:    Function
`PATH_as_shutil_which_determines_it` utility or script function.
L227: class MultiDomainBasicAuth(AuthBase):    Authentication component
(`MultiDomainBasicAuth`) handles user authentication flows.
L228: def __init__(    Function `__init__` utility or script function.
L246: def keyring_provider(self) -> KeyRingBaseProvider:    Function `keyring_provider`
utility or script function.
L250: def keyring_provider(self, provider: str) -> None:    Function `keyring_provider`
utility or script function.
L258: def use_keyring(self) -> bool:    Function `use_keyring` utility or script function.
L264: def _get_keyring_auth(    Function `_get_keyring_auth` utility or script function.
L290: def _get_index_url(self, url: str) -> str | None:    Function `_get_index_url` utility
or script function.
L340: def _get_new_credentials(    Function `_get_new_credentials` utility or script
function.
L397: def _get_url_and_credentials(    Function `_get_url_and_credentials` utility or script
function.
L445: def __call__(self, req: PreparedRequest) -> PreparedRequest:    Function `__call__`
utility or script function.
L463: def _prompt_for_password(self, netloc: str) -> tuple[str | None, str | None, bool]:
Function `_prompt_for_password` utility or script function.
L475: def _should_save_password_to_keyring(self) -> bool:    Function
`_should_save_password_to_keyring` utility or script function.

```

```

L484: def handle_401(self, resp: Response, **kwargs: Any) -> Response:    Function
`handle_401` utility or script function.
L547: def warn_on_401(self, resp: Response, **kwargs: Any) -> None:    Function `warn_on_401`
utility or script function.
L555: def save_credentials(self, resp: Response, **kwargs: Any) -> None:    Function
`save_credentials` Saves data to storage or remote.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/network/download.py

```

L31: def _get_http_response_size(resp: Response) -> int | None:    Function
`_get_http_response_size` utility or script function.
L38: def _get_http_response_etag_or_last_modified(resp: Response) -> str | None:    Function
`_get_http_response_etag_or_last_modified` utility or script function.
L46: def _log_download(    Function `_log_download` utility or script function.
L97: def sanitize_content_filename(filename: str) -> str:    Function
`sanitize_content_filename` utility or script function.
L104: def parse_content_disposition(content_disposition: str, default_filename: str) -> str:
Function `_parse_content_disposition` utility or script function.
L119: def _get_http_response_filename(resp: Response, link: Link) -> str:    Function
`_get_http_response_filename` utility or script function.
L141: class _FileDownload:    Class (`_FileDownload`) component used by the app (see file
context: None).
L150: def is_incomplete(self) -> bool:    Function `is_incomplete` utility or script
function.
L153: def write_chunk(self, data: bytes) -> None:    Function `write_chunk` utility or script
function.
L157: def reset_file(self) -> None:    Function `reset_file` utility or script function.
L164: class Downloader:    Class (`Downloader`) component used by the app (see file context:
None).
L165: def __init__(    Function `__init__` utility or script function.
L177: def batch(    Function `batch` utility or script function.
L185: def __call__(self, link: Link, location: str) -> tuple[str, str]:    Function `__call__`
utility or script function.
L200: def _process_response(self, download: _FileDownload, resp: Response) -> None:
Function `_process_response` utility or script function.
L219: def _attempt_resumes_or_redownloads(    Function `_attempt_resumes_or_redownloads`
utility or script function.
L259: def _cache_resumed_download(    Function `_cache_resumed_download` utility or script
function.
L315: def _http_get_resume(    Function `_http_get_resume` utility or script function.
L329: def _http_get(self, link: Link, headers: Mapping[str, str] = HEADERS) -> Response:
Function `_http_get` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/parser.py

```

L27: class PrettyHelpFormatter(optparse.IndentedHelpFormatter):    Class
(`PrettyHelpFormatter`) component used by the app (see file context: None).
L41: def __init__(self, *args: Any, **kwargs: Any) -> None:    Function `__init__` utility or
script function.
L48: def format_option_strings(self, option: optparse.Option) -> str:    Function
`format_option_strings` utility or script function.
L66: def format_option(self, option: optparse.Option) -> str:    Function `format_option`
utility or script function.
L96: def format_heading(self, heading: str) -> str:    Function `format_heading` utility or
script function.
L101: def format_usage(self, usage: str) -> str:    Function `format_usage` utility or script
function.
L110: def format_description(self, description: str | None) -> str:    Function
`format_description` utility or script function.
L129: def format_epilog(self, epilog: str | None) -> str:    Function `format_epilog` utility
or script function.
L136: def expand_default(self, option: optparse.Option) -> str:    Function `expand_default`
utility or script function.
L143: def indent_lines(self, text: str, indent: str) -> str:    Function `indent_lines`
utility or script function.
L148: class UpdatingDefaultsHelpFormatter(PrettyHelpFormatter):    Class
(`UpdatingDefaultsHelpFormatter`) component used by the app (see file context: None).
L157: def expand_default(self, option: optparse.Option) -> str:    Function `expand_default`
utility or script function.
L180: class CustomOptionParser(optparse.OptionParser):    Class (`CustomOptionParser`)
component used by the app (see file context: None).
L181: def insert_option_group(    Function `insert_option_group` utility or script function.
L193: def option_list_all(self) -> list[optparse.Option]:    Function `option_list_all`
utility or script function.
L202: class ConfigOptionParser(CustomOptionParser):    Class (`ConfigOptionParser`) component
used by the app (see file context: None).
L206: def __init__(    Function `__init__` utility or script function.
L219: def check_default(self, option: optparse.Option, key: str, val: Any) -> Any:    Function
`check_default` utility or script function.
L226: def _get_ordered_configuration_items(    Function `_get_ordered_configuration_items`
utility or script function.
L257: def _update_defaults(self, defaults: dict[str, Any]) -> dict[str, Any]:    Function
`_update_defaults` utility or script function.
L321: def get_default_values(self) -> optparse.Values:    Function `get_default_values`
Returns or fetches data.
L343: def error(self, msg: str) -> NoReturn:    Function `error` utility or script function.
L347: def print_help(self, file: Any = None) -> None:    Function `print_help` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/main_parser.py

```

L21: def create_main_parser() -> ConfigOptionParser:    Function `create_main_parser`    Creates
a resource or document.
L52: def identify_python_interpreter(python: str) -> str | None:    Function
`identify_python_interpreter`    utility or script function.
L71: def parse_command(args: list[str]) -> tuple[str, list[str]]:    Function `parse_command`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/progress_bar.py

```

L33: def _rich_download_progress_bar(    Function `_rich_download_progress_bar`    utility or
script function.
L75: def _rich_install_progress_bar(    Function `_rich_install_progress_bar`    utility or
script function.
L97: def _raw_progress_bar(    Function `_raw_progress_bar`    utility or script function.
L103: def write_progress(current: int, total: int) -> None:    Function `write_progress`
utility or script function.
L120: def get_download_progress_renderer(    Function `get_download_progress_renderer`
Returns or fetches data.
L144: def get_install_progress_renderer(    Function `get_install_progress_renderer`    Returns
or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/autocompletion.py

```

L17: def autocomplete() -> None:    Function `autocomplete`    utility or script function.
L132: def get_path_completion_type(    Function `get_path_completion_type`    Returns or fetches
data.
L156: def auto_complete_paths(current: str, completion_type: str) -> Iterable[str]:
Function `auto_complete_paths`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/req_comm

and.py

```

L64: def should_ignore_regular_constraints(options: Values) -> bool:    Function
`should_ignore_regular_constraints` utility or script function.
L84: def with_cleanup(    Function `with_cleanup` utility or script function.
L91: def configure_tempdir_registry(registry: TempDirectoryTypeRegistry) -> None:    Function
`configure_tempdir_registry` utility or script function.
L95: def wrapper(self: _CommandT, options: Values, args: list[str]) -> int:    Function
`wrapper` utility or script function.
L112: def parse_constraint_files(    Function `parse_constraint_files` utility or script
function.
L137: class RequirementCommand(IndexGroupCommand):    Class (`RequirementCommand`) component
used by the app (see file context: None).
L138: def __init__(self, *args: Any, **kw: Any) -> None:    Function `__init__` utility or
script function.
L145: def determine_resolver_variant(options: Values) -> str:    Function
`determine_resolver_variant` utility or script function.
L153: def make_requirement_preparer(    Function `make_requirement_preparer` utility or
script function.
L234: def make_resolver(    Function `make_resolver` utility or script function.
L290: def get_requirements(    Function `get_requirements` Returns or fetches data.
L435: def trace_basic_info(finder: PackageFinder) -> None:    Function `trace_basic_info`
utility or script function.
L445: def _build_package_finder(    Function `_build_package_finder` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/index_com
mand.py**

```

L36: def _create_truststore_ssl_context() -> SSLContext | None:    Function
`_create_truststore_ssl_context` utility or script function.
L54: class SessionCommandMixin(CommandContextMixin):    Class (`SessionCommandMixin`)
component used by the app (see file context: None).
L59: def __init__(self) -> None:    Function `__init__` utility or script function.
L64: def _get_index_urls(cls, options: Values) -> list[str] | None:    Function
`_get_index_urls` utility or script function.
L77: def get_default_session(self, options: Values) -> PipSession:    Function
`get_default_session` Returns or fetches data.
L87: def _build_session(    Function `_build_session` utility or script function.
L140: def _pip_self_version_check_fetch(    Function `_pip_self_version_check_fetch` utility
or script function.
L148: def _pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
Function `_pip_self_version_check_emit` utility or script function.
L154: class IndexGroupCommand(Command, SessionCommandMixin):    Class (`IndexGroupCommand`)
component used by the app (see file context: None).

```

```
L161: def should_exclude_prerelease(    Function `should_exclude_prerelease`    utility or
script function.
L179: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/cmdoption s.py

```
L42: def raise_option_error(parser: OptionParser, option: Option, msg: str) -> None:
Function `raise_option_error`    utility or script function.
L56: def make_option_group(group: dict[str, Any], parser: ConfigOptionParser) -> OptionGroup:
    Function `make_option_group`    utility or script function.
L68: def check_dist_restriction(options: Values, check_target: bool = False) -> None:
Function `check_dist_restriction`    utility or script function.
L116: def check_build_constraints(options: Values) -> None:    Function
`check_build_constraints`    utility or script function.
L139: def _path_option_check(option: Option, opt: str, value: str) -> str:    Function
`_path_option_check`    utility or script function.
L143: def _package_name_option_check(option: Option, opt: str, value: str) -> str:    Function
`_package_name_option_check`    utility or script function.
L147: class PipOption(Option):    Class (`PipOption`)    component used by the app (see file
context: None).
L348: def exists_action() -> Option:    Function `exists_action`    utility or script function.
L403: def extra_index_url() -> Option:    Function `extra_index_url`    utility or script
function.
L426: def find_links() -> Option:    Function `find_links`    utility or script function.
L442: def _handle_uploaded_prior_to(    Function `_handle_uploaded_prior_to`    utility or
script function.
L487: def uploaded_prior_to() -> Option:    Function `uploaded_prior_to`    utility or script
function.
L506: def trusted_host() -> Option:    Function `trusted_host`    utility or script function.
L518: def constraints() -> Option:    Function `constraints`    utility or script function.
L531: def build_constraints() -> Option:    Function `build_constraints`    Constructs or
prepares an object.
L546: def requirements() -> Option:    Function `requirements`    utility or script function.
L563: def requirements_from_scripts() -> Option:    Function `requirements_from_scripts`
utility or script function.
L575: def editable() -> Option:    Function `editable`    utility or script function.
L590: def _handle_src(option: Option, opt_str: str, value: str, parser: OptionParser) ->
None:    Function `_handle_src`    utility or script function.
L613: def _get_format_control(values: Values, option: Option) -> Any:    Function
`_get_format_control`    utility or script function.
L618: def _handle_no_binary(    Function `_handle_no_binary`    utility or script function.
L629: def _handle_only_binary(    Function `_handle_only_binary`    utility or script function.
L640: def no_binary() -> Option:    Function `no_binary`    utility or script function.
L658: def only_binary() -> Option:    Function `only_binary`    utility or script function.
```

```

L676: def _get_release_control(values: Values, option: Option) -> Any:    Function
`_get_release_control` utility or script function.
L681: def _handle_all_releases(    Function `_handle_all_releases` utility or script
function.
L693: def _handle_only_final(    Function `_handle_only_final` utility or script function.
L705: def all_releases() -> Option:    Function `all_releases` utility or script function.
L723: def only_final() -> Option:    Function `only_final` utility or script function.
L740: def check_release_control_exclusive(options: Values) -> None:    Function
`check_release_control_exclusive` utility or script function.
L772: def _convert_python_version(value: str) -> tuple[tuple[int, ...], str | None]:
Function `_convert_python_version` utility or script function.
L801: def _handle_python_version(    Function `_handle_python_version` utility or script
function.
L870: def add_target_python_options(cmd_opts: OptionGroup) -> None:    Function
`add_target_python_options` utility or script function.
L877: def make_target_python(options: Values) -> TargetPython:    Function
`make_target_python` utility or script function.
L888: def prefer_binary() -> Option:    Function `prefer_binary` utility or script function.
L912: def _handle_no_cache_dir(    Function `_handle_no_cache_dir` utility or script
function.
L961: def _handle_dependency_group(    Function `_handle_dependency_group` utility or script
function.
L1040: def _handle_config_settings(    Function `_handle_config_settings` utility or script
function.
L1118: def _handle_merge_hash(    Function `_handle_merge_hash` utility or script function.
L1179: def check_list_path_option(options: Values) -> None:    Function
`check_list_path_option` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/base_command.py

```

L48: class Command(CommandContextMixin):    Class (`Command`) component used by the app (see
file context: None).
L52: def __init__(self, name: str, summary: str, isolated: bool = False) -> None:    Function
`__init__` utility or script function.
L82: def add_options(self) -> None:    Function `add_options` utility or script function.
L86: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check` utility or script function.
L96: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L99: def _run_wrapper(self, level_number: int, options: Values, args: list[str]) -> int:
Function `_run_wrapper` utility or script function.
L100: def _inner_run() -> int:    Function `_inner_run` utility or script function.
L161: def parse_args(self, args: list[str]) -> tuple[Values, list[str]]:    Function
`parse_args` utility or script function.
L165: def main(self, args: list[str]) -> int:    Function `main` Entry point / main routine.

```

```
L172: def _main(self, args: list[str]) -> int:    Function `_main` utility or script
function.
L260: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/command_ context.py

```
L8: class CommandContextMixin:    Class (`CommandContextMixin`) component used by the app
(see file context: None).
L9: def __init__(self) -> None:    Function `__init__` utility or script function.
L15: def main_context(self) -> Generator[None, None, None]:    Function `main_context` Entry
point / main routine.
L25: def enter_context(self, context_provider: AbstractContextManager[_T]) -> _T:    Function
`enter_context` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/spinners.p y

```
L30: class SpinnerInterface:    Class (`SpinnerInterface`) component used by the app (see
file context: None).
L31: def spin(self) -> None:    Function `spin` utility or script function.
L34: def finish(self, final_status: str) -> None:    Function `finish` utility or script
function.
L38: class InteractiveSpinner(SpinnerInterface):    Class (`InteractiveSpinner`) component
used by the app (see file context: None).
L39: def __init__(    Function `__init__` utility or script function.
L59: def _write(self, status: str) -> None:    Function `_write` utility or script function.
L71: def spin(self) -> None:    Function `spin` utility or script function.
L78: def finish(self, final_status: str) -> None:    Function `finish` utility or script
function.
L91: class NonInteractiveSpinner(SpinnerInterface):    Class (`NonInteractiveSpinner`)
component used by the app (see file context: None).
L92: def __init__(self, message: str, min_update_interval_seconds: float = 60.0) -> None:
Function `__init__` utility or script function.
L98: def _update(self, status: str) -> None:    Function `_update` utility or script
function.
L103: def spin(self) -> None:    Function `spin` utility or script function.
L110: def finish(self, final_status: str) -> None:    Function `finish` utility or script
function.
L117: class RateLimiter:    Class (`RateLimiter`) component used by the app (see file
context: None).
```



```

L118: def __init__(self, min_update_interval_seconds: float) -> None:    Function `__init__`
utility or script function.
L122: def ready(self) -> bool:    Function `ready`    utility or script function.
L127: def reset(self) -> None:    Function `reset`    utility or script function.
L132: def open_spinner(message: str) -> Generator[SpinnerInterface, None, None]:    Function
`open_spinner`    utility or script function.
L155: class _PipRichSpinner:    Class (`_PipRichSpinner`)    component used by the app (see file
context: None).
L163: def __init__(self, label: str) -> None:    Function `__init__`    utility or script
function.
L170: def __rich_console__(    Function `__rich_console__`    utility or script function.
L175: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L181: def render(self) -> RenderableType:    Function `render`    utility or script function.
L187: def finish(self, status: str) -> None:    Function `finish`    utility or script function.
L194: def open_rich_spinner(label: str, console: Console | None = None) -> Generator[None]:
Function `open_rich_spinner`    utility or script function.
L220: def hidden_cursor(file: IO[str]) -> Generator[None, None, None]:    Function
`hidden_cursor`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/cli/main.py

```

L41: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main
routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/base.py

```

L13: class AbstractDistribution(metaclass=abc.ABCMeta):    Class (`AbstractDistribution`)
component used by the app (see file context: None).
L32: def __init__(self, req: InstallRequirement) -> None:    Function `__init__`    utility or
script function.
L37: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`    Constructs or
prepares an object.
L45: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`    Returns or fetches data.
L49: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`    utility
or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/i

nstalled.py

```
L12: class InstalledDistribution(AbstractDistribution):    Class (`InstalledDistribution`)
component used by the app (see file context: None).
L20: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`    Constructs or
prepares an object.
L23: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`    Returns or fetches data.
L27: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`    utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/ sdist.py

```
L19: class SourceDistribution(AbstractDistribution):    Class (`SourceDistribution`)
component used by the app (see file context: None).
L27: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`    Constructs or
prepares an object.
L32: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`    Returns or fetches data.
L35: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`    utility
or script function.
L73: def _prepare_build_backend(    Function `_prepare_build_backend`    utility or script
function.
L101: def _get_build_requires_wheel(self) -> Iterable[str]:    Function
`_get_build_requires_wheel`    utility or script function.
L109: def _get_build_requires_editable(self) -> Iterable[str]:    Function
`_get_build_requires_editable`    utility or script function.
L119: def _install_build_reqs(    Function `_install_build_reqs`    utility or script function.
L140: def _raise_conflicts(    Function `_raise_conflicts`    utility or script function.
L157: def _raise_missing_reqs(self, missing: set[str]) -> None:    Function
`_raise_missing_reqs`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/ __init__.py

```
L7: def make_distribution_for_install_requirement(    Function
`make_distribution_for_install_requirement`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/distributions/wheel.py

```

L18: class WheelDistribution(AbstractDistribution):    Class (`WheelDistribution`) component
used by the app (see file context: None).
L25: def build_tracker_id(self) -> str | None:    Function `build_tracker_id` Constructs or
prepares an object.
L28: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution` Returns or fetches data.
L38: def prepare_distribution_metadata(    Function `prepare_distribution_metadata` utility
or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/versioncontrol.py

```

L45: def is_url(name: str) -> bool:    Function `is_url` utility or script function.
L55: def make_vcs_requirement_url(    Function `make_vcs_requirement_url` utility or script
function.
L74: def find_path_to_project_root_from_repo_root(    Function
`find_path_to_project_root_from_repo_root` utility or script function.
L103: class RemoteNotFoundError(Exception):    Class (`RemoteNotFoundError`) component used
by the app (see file context: None).
L107: class RemoteNotValidError(Exception):    Class (`RemoteNotValidError`) component used
by the app (see file context: None).
L108: def __init__(self, url: str):    Function `__init__` utility or script function.
L114: class RevOptions:    Class (`RevOptions`) component used by the app (see file context:
None).
L130: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L134: def arg_rev(self) -> str | None:    Function `arg_rev` utility or script function.
L140: def to_args(self) -> CommandArgs:    Function `to_args` utility or script function.
L152: def to_display(self) -> str:    Function `to_display` utility or script function.
L158: def make_new(self, rev: str) -> RevOptions:    Function `make_new` utility or script
function.
L168: class VcsSupport:    Class (`VcsSupport`) component used by the app (see file context:
None).
L172: def __init__(self) -> None:    Function `__init__` utility or script function.
L178: def __iter__(self) -> Iterator[str]:    Function `__iter__` utility or script function.
L182: def backends(self) -> list[VersionControl]:    Function `backends` utility or script
function.
L186: def dirnames(self) -> list[str]:    Function `dirnames` utility or script function.
L190: def all_schemes(self) -> list[str]:    Function `all_schemes` utility or script
function.
L196: def register(self, cls: type[VersionControl]) -> None:    Function `register` utility

```

or script function.

L204: def unregister(self, name: str) -> None: Function `unregister` utility or script function.

L208: def get_backend_for_dir(self, location: str) -> VersionControl | None: Function `get\_backend\_for\_dir` Returns or fetches data.

L231: def get_backend_for_scheme(self, scheme: str) -> VersionControl | None: Function `get\_backend\_for\_scheme` Returns or fetches data.

L240: def get_backend(self, name: str) -> VersionControl | None: Function `get\_backend` Returns or fetches data.

L251: class VersionControl: Class (`VersionControl`) component used by the app (see file context: None).

L262: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool: Function `should\_add\_vcs\_url\_prefix` utility or script function.

L270: def get_subdirectory(cls, location: str) -> str | None: Function `get\_subdirectory` Returns or fetches data.

L278: def get_requirement_revision(cls, repo_dir: str) -> str: Function `get\_requirement\_revision` Returns or fetches data.

L285: def get_src_requirement(cls, repo_dir: str, project_name: str) -> str: Function `get\_src\_requirement` Returns or fetches data.

L309: def get_base_rev_args(rev: str) -> list[str]: Function `get\_base\_rev\_args` Returns or fetches data.

L318: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool: Function `is\_immutable\_rev\_checkout` utility or script function.

L332: def make_rev_options(Function `make\_rev\_options` utility or script function.

L345: def _is_local_repository(cls, repo: str) -> bool: Function `\_is\_local\_repository` utility or script function.

L354: def get_netloc_and_auth(Function `get\_netloc\_and\_auth` Returns or fetches data.

L375: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]: Function `get\_url\_rev\_and\_auth` Returns or fetches data.

L406: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs: Function `make\_rev\_args` utility or script function.

L412: def get_url_rev_options(self, url: HiddenText) -> tuple[HiddenText, RevOptions]: Function `get\_url\_rev\_options` Returns or fetches data.

L428: def normalize_url(url: str) -> str: Function `normalize\_url` utility or script function.

L436: def compare_urls(cls, url1: str, url2: str) -> bool: Function `compare\_urls` utility or script function.

L442: def fetch_new(Function `fetch\_new` utility or script function.

L456: def switch(Function `switch` utility or script function.

L471: def update(Function `update` utility or script function.

L487: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool: Function `is\_commit\_id\_equal` utility or script function.

L497: def obtain(self, dest: str, url: HiddenText, verbosity: int) -> None: Function `obtain` utility or script function.

L586: def unpack(self, location: str, url: HiddenText, verbosity: int) -> None: Function `unpack` utility or script function.

L599: def get_remote_url(cls, location: str) -> str: Function `get\_remote\_url` Returns or fetches data.

L609: def get_revision(cls, location: str) -> str: Function `get\_revision` Returns or fetches data.

L616: def run_command(Function `run\_command` utility or script function.

```
L674: def is_repository_directory(cls, path: str) -> bool:    Function
`is_repository_directory` utility or script function.
L682: def get_repository_root(cls, location: str) -> str | None:    Function
`get_repository_root` Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/subversion.py

```
L31: class Subversion(VersionControl):    Class (`Subversion`) component used by the app (see
file context: None).
L38: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:    Function
`should_add_vcs_url_prefix` utility or script function.
L42: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L46: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L75: def get_netloc_and_auth(    Function `get_netloc_and_auth` Returns or fetches data.
L90: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
`get_url_rev_and_auth` Returns or fetches data.
L98: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
Function `make_rev_args` utility or script function.
L108: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L132: def _get_svn_url_rev(cls, location: str) -> tuple[str | None, int]:    Function
`_get_svn_url_rev` utility or script function.
L182: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L186: def __init__(self, use_interactive: bool | None = None) -> None:    Function `__init__`
utility or script function.
L200: def call_vcs_version(self) -> tuple[int, ...]:    Function `call_vcs_version` utility
or script function.
L228: def get_vcs_version(self) -> tuple[int, ...]:    Function `get_vcs_version` Returns or
fetches data.
L248: def get_remote_call_options(self) -> CommandArgs:    Function `get_remote_call_options`
Returns or fetches data.
L279: def fetch_new(    Function `fetch_new` utility or script function.
L303: def switch(    Function `switch` utility or script function.
L319: def update(    Function `update` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/bazaar.py

```
L19: class Bazaar(VersionControl):    Class (`Bazaar`) component used by the app (see file
```

```

context: None).
L34: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L37: def fetch_new(    Function `fetch_new` utility or script function.
L58: def switch(    Function `switch` utility or script function.
L67: def update(    Function `update` utility or script function.
L92: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
`get_url_rev_and_auth` Returns or fetches data.
L100: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L115: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L125: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/mercurial.py

```

L21: class Mercurial(VersionControl):    Class (`Mercurial`) component used by the app (see
file context: None).
L34: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L37: def fetch_new(    Function `fetch_new` utility or script function.
L61: def switch(    Function `switch` utility or script function.
L86: def update(    Function `update` utility or script function.
L103: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L115: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L128: def get_requirement_revision(cls, location: str) -> str:    Function
`get_requirement_revision` Returns or fetches data.
L142: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L147: def get_subdirectory(cls, location: str) -> str | None:    Function `get_subdirectory`
Returns or fetches data.
L161: def get_repository_root(cls, location: str) -> str | None:    Function
`get_repository_root` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_internal/vcs/git.py

```

L58: def looks_like_hash(sha: str) -> bool:    Function `looks_like_hash` utility or script
function.

```

```

L62: class Git(VersionControl):    Class (`Git`) component used by the app (see file context:
None).
L79: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L83: def run_command(cls, *args: Any, **kwargs: Any) -> str:    Function `run_command`
utility or script function.
L91: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:    Function
`is_immutable_rev_checkout` utility or script function.
L105: def get_git_version(self) -> tuple[int, ...]:    Function `get_git_version` Returns or
fetches data.
L119: def get_current_branch(cls, location: str) -> str | None:    Function
`get_current_branch` Returns or fetches data.
L144: def get_revision_sha(cls, dest: str, rev: str) -> tuple[str | None, bool]:    Function
`get_revision_sha` Returns or fetches data.
L190: def _should_fetch(cls, dest: str, rev: str) -> bool:    Function `_should_fetch`
utility or script function.
L213: def resolve_revision(    Function `resolve_revision` utility or script function.
L259: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L273: def fetch_new(    Function `fetch_new` utility or script function.
L336: def switch(    Function `switch` utility or script function.
L358: def update(    Function `update` utility or script function.
L389: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L419: def _git_remote_to_pip_url(url: str) -> str:    Function `_git_remote_to_pip_url`
utility or script function.
L450: def has_commit(cls, location: str, rev: str) -> bool:    Function `has_commit` utility
or script function.
L466: def get_revision(cls, location: str, rev: str | None = None) -> str:    Function
`get_revision` Returns or fetches data.
L478: def get_subdirectory(cls, location: str) -> str | None:    Function `get_subdirectory`
Returns or fetches data.
L496: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
`get_url_rev_and_auth` Returns or fetches data.
L527: def update_submodules(cls, location: str, verbosity: int = 0) -> None:    Function
`update_submodules` utility or script function.
L541: def get_repository_root(cls, location: str) -> str | None:    Function
`get_repository_root` Returns or fetches data.
L566: def should_add_vcs_url_prefix(repo_url: str) -> bool:    Function
`should_add_vcs_url_prefix` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/__init__.py

```

L29: def vendored(modulename):    Function `vendored` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/tomli_w/_write
r.py**

```

L133: class Context:    Class (`Context`)    component used by the app (see file context: None).
L134: def __init__(self, allow_multiline: bool, indent: int):    Function `__init__`    utility
or script function.
L143: def dump(    Function `dump`    utility or script function.
L156: def dumps(    Function `dumps`    utility or script function.
L163: def gen_table_chunks(    Function `gen_table_chunks`    utility or script function.
L100: def format_literal(obj: object, ctx: Context, *, nest_level: int = 0) -> str:    Object
(singleton).
L126: def format_decimal(obj: Decimal) -> str:    Function `format_decimal`    utility or script
function.
L135: def format_inline_table(obj: Mapping, ctx: Context) -> str:    Function
`format_inline_table`    utility or script function.
L156: def format_inline_array(obj: tuple | list, ctx: Context, nest_level: int) -> str:
Function `format_inline_array`    utility or script function.
L171: def format_key_part(part: str) -> str:    Function `format_key_part`    utility or script
function.
L185: def format_string(s: str, *, allow_multiline: bool) -> str:    Function `format_string`
utility or script function.
L215: def is_aot(obj: Any) -> bool:    Function `is_aot`    utility or script function.
L225: def is_suitable_inline_table(obj: Mapping, ctx: Context) -> bool:    Function
`is_suitable_inline_table`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_collec
tions.py**

```

L15: class HasGettableStringKeys(Protocol):    Class (`HasGettableStringKeys`)    component used
by the app (see file context: None).
L16: def keys(self) -> typing.Iterator[str]: ...    Function `keys`    utility or script
function.
L18: def __getitem__(self, key: str) -> str: ...    Function `__getitem__`    utility or script
function.
L39: class _Sentinel(Enum):    Class (`_Sentinel`)    component used by the app (see file
context: None).
L43: def ensure_can_construct_http_header_dict(    Function
`ensure_can_construct_http_header_dict`    utility or script function.
L63: class RecentlyUsedContainer(typing.Generic[_KT, _VT], typing.MutableMapping[_KT, _VT]):
Class (`RecentlyUsedContainer`)    component used by the app (see file context: None).
L82: def __init__(    Function `__init__`    utility or script function.
L93: def __getitem__(self, key: _KT) -> _VT:    Function `__getitem__`    utility or script
function.

```



```

L100: def __setitem__(self, key: _KT, value: _VT) -> None:    Function `__setitem__` utility
or script function.
L125: def __delitem__(self, key: _KT) -> None:    Function `__delitem__` utility or script
function.
L132: def __len__(self) -> int:    Function `__len__` utility or script function.
L136: def __iter__(self) -> typing.NoReturn:    Function `__iter__` utility or script
function.
L141: def clear(self) -> None:    Function `clear` utility or script function.
L151: def keys(self) -> set[_KT]:    # type: ignore[override]    Function `keys` utility or
script function.
L156: class HTTPHeaderDictItemView(set[tuple[str, str]]):    Class (`HTTPHeaderDictItemView`)
component used by the app (see file context: None).
L187: def __init__(self, headers: HTTPHeaderDict) -> None:    Function `__init__` utility or
script function.
L190: def __len__(self) -> int:    Function `__len__` utility or script function.
L193: def __iter__(self) -> typing.Iterator[tuple[str, str]]:    Function `__iter__` utility
or script function.
L196: def __contains__(self, item: object) -> bool:    Object (singleton).
L204: class HTTPHeaderDict(typing.MutableMapping[str, str]):    Class (`HTTPHeaderDict`)
component used by the app (see file context: None).
L240: def __init__(self, headers: ValidHTTPHeaderSource | None = None, **kwargs: str):
Function `__init__` utility or script function.
L251: def __setitem__(self, key: str, val: str) -> None:    Function `__setitem__` utility or
script function.
L257: def __getitem__(self, key: str) -> str:    Function `__getitem__` utility or script
function.
L263: def __delitem__(self, key: str) -> None:    Function `__delitem__` utility or script
function.
L268: def __contains__(self, key: object) -> bool:    Object (singleton).
L275: def setdefault(self, key: str, default: str = "") -> str:    Function `setdefault` Sets
or updates a value.
L278: def __eq__(self, other: object) -> bool:    Object (singleton).
L289: def __ne__(self, other: object) -> bool:    Object (singleton).
L292: def __len__(self) -> int:    Function `__len__` utility or script function.
L295: def __iter__(self) -> typing.Iterator[str]:    Function `__iter__` utility or script
function.
L300: def discard(self, key: str) -> None:    Function `discard` utility or script function.
L306: def add(self, key: str, val: str, *, combine: bool = False) -> None:    Function `add`
utility or script function.
L341: def extend(self, *args: ValidHTTPHeaderSource, **kwargs: str) -> None:    Function
`extend` utility or script function.
L375: def getlist(self, key: str) -> list[str]: ...    Function `getlist` Returns or fetches
data.
L378: def getlist(self, key: str, default: _DT) -> list[str] | _DT: ...    Function `getlist`
Returns or fetches data.
L380: def getlist(    Function `getlist` Returns or fetches data.
L400: def _prepare_for_method_change(self) -> Self:    Function `_prepare_for_method_change`
utility or script function.
L426: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L429: def _copy_from(self, other: HTTPHeaderDict) -> None:    Function `_copy_from` utility
or script function.

```

```

L434: def copy(self) -> Self:    Function `copy`    utility or script function.
L439: def iteritems(self) -> typing.Iterator[tuple[str, str]]:    Function `iteritems`
utility or script function.
L446: def itermerged(self) -> typing.Iterator[tuple[str, str]]:    Function `itermerged`
utility or script function.
L452: def items(self) -> HTTPHeaderDictItemView:    # type: ignore[override]    Function `items`
utility or script function.
L455: def _has_value_for_header(self, header_name: str, potential_value: str) -> bool:
Function `_has_value_for_header`    utility or script function.
L460: def __ior__(self, other: object) -> HTTPHeaderDict:    Object (singleton).
L469: def __or__(self, other: object) -> Self:    Object (singleton).
L479: def __ror__(self, other: object) -> Self:    Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/fields.py

```

L15: def guess_content_type(    Function `guess_content_type`    utility or script function.
L31: def format_header_param_rfc2231(name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`format_header_param_rfc2231`    utility or script function.
L79: def format_multipart_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
Function `format_multipart_header_param`    utility or script function.
L117: def format_header_param_html5(name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`format_header_param_html5`    utility or script function.
L135: def format_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`format_header_param`    utility or script function.
L153: class RequestField:    Class (`RequestField`)    component used by the app (see file
context: None).
L171: def __init__(    Function `__init__`    utility or script function.
L200: def from_tuples(    Function `from_tuples`    utility or script function.
L244: def _render_part(self, name: str, value: _TYPE_FIELD_VALUE) -> str:    Function
`_render_part`    utility or script function.
L260: def _render_parts(    Function `_render_parts`    utility or script function.
L291: def render_headers(self) -> str:    Function `render_headers`    utility or script
function.
L310: def make_multipart(    Function `make_multipart`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connection.py

```

L37: class BaseSSLError(BaseException):    # type: ignore[no-redef]    Class (`BaseSSLError`)
component used by the app (see file context: None).
L82: class HTTPConnection(_HTTPConnection):    Class (`HTTPConnection`)    component used by the

```

```

app (see file context: None).
L132: def __init__(    Function `__init__`    utility or script function.
L163: def __str__(self) -> str:    Function `__str__`    utility or script function.
L166: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L170: def host(self) -> str:    Function `host`    utility or script function.
L189: def host(self, value: str) -> None:    Function `host`    utility or script function.
L198: def _new_conn(self) -> socket.socket:    Function `_new_conn`    utility or script
function.
L227: def set_tunnel(    Function `set_tunnel`    Sets or updates a value.
L244: def _wrap_ipv6(self, ip: bytes) -> bytes:    Function `_wrap_ipv6`    utility or script
function.
L253: def _tunnel(self) -> None:    Function `_tunnel`    utility or script function.
L296: def _tunnel(self) -> None:    # noqa: F811    Function `_tunnel`    utility or script
function.
L330: def connect(self) -> None:    Function `connect`    utility or script function.
L348: def is_closed(self) -> bool:    Function `is_closed`    utility or script function.
L352: def is_connected(self) -> bool:    Function `is_connected`    utility or script function.
L358: def has_connected_to_proxy(self) -> bool:    Function `has_connected_to_proxy`    utility
or script function.
L362: def proxy_is_forwarding(self) -> bool:    Function `proxy_is_forwarding`    utility or
script function.
L369: def proxy_is_tunneling(self) -> bool:    Function `proxy_is_tunneling`    utility or
script function.
L375: def close(self) -> None:    Function `close`    utility or script function.
L390: def putrequest(    Function `putrequest`    utility or script function.
L410: def putheader(self, header: str, *values: str) -> None:    # type: ignore[override]
Function `putheader`    utility or script function.
L424: def request(    # type: ignore[override]    Function `request`    utility or script
function.
L521: def request_chunked(    Function `request_chunked`    utility or script function.
L540: def getresponse(    # type: ignore[override]    Function `getresponse`    Returns or fetches
data.
L603: class HTTPConnection(HTTPConnection):    Class (`HTTPConnection`)    component used by
the app (see file context: None).
L621: def __init__(    Function `__init__`    utility or script function.
L683: def set_cert(    Function `set_cert`    Sets or updates a value.
L724: def connect(self) -> None:    Function `connect`    utility or script function.
L861: def _connect_tls_proxy(self, hostname: str, sock: socket.socket) -> ssl.SSLSocket:
Function `_connect_tls_proxy`    utility or script function.
L891: class _WrappedAndVerifiedSocket(typing.NamedTuple):    Class
(`_WrappedAndVerifiedSocket`)    component used by the app (see file context: None).
L901: def _ssl_wrap_socket_and_match_hostname(    Function
`_ssl_wrap_socket_and_match_hostname`    utility or script function.
L1026: def _match_hostname(    Function `_match_hostname`    utility or script function.
L1052: def _wrap_proxy_error(err: Exception, proxy_scheme: str | None) -> ProxyError:
Function `_wrap_proxy_error`    utility or script function.
L1077: def _get_default_user_agent() -> str:    Function `_get_default_user_agent`    utility or
script function.
L1081: class DummyConnection:    Class (`DummyConnection`)    component used by the app (see
file context: None).
L1092: def _url_from_connection(    Function `_url_from_connection`    utility or script

```

```
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/responses.py

```
L48: class ContentDecoder:    Class (`ContentDecoder`)    component used by the app (see file
context: None).
L49: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L53: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L56: def flush(self) -> bytes:    Function `flush`    utility or script function.
L60: class DeflateDecoder(ContentDecoder):    Class (`DeflateDecoder`)    component used by the
app (see file context: None).
L61: def __init__(self) -> None:    Function `__init__`    utility or script function.
L67: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L110: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L115: def flush(self) -> bytes:    Function `flush`    utility or script function.
L119: class GzipDecoderState:    Class (`GzipDecoderState`)    component used by the app (see
file context: None).
L125: class GzipDecoder(ContentDecoder):    Class (`GzipDecoder`)    component used by the app
(see file context: None).
L126: def __init__(self) -> None:    Function `__init__`    utility or script function.
L131: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L182: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L185: def flush(self) -> bytes:    Function `flush`    utility or script function.
L191: class BrotliDecoder(ContentDecoder):    Class (`BrotliDecoder`)    component used by the
app (see file context: None).
L195: def __init__(self) -> None:    Function `__init__`    utility or script function.
L203: def _decompress(self, data: bytes, output_buffer_limit: int = -1) -> bytes:    Function
`_decompress`    utility or script function.
L206: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L222: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L228: def flush(self) -> bytes:    Function `flush`    utility or script function.
L244: class ZstdDecoder(ContentDecoder):    Class (`ZstdDecoder`)    component used by the app
(see file context: None).
L245: def __init__(self) -> None:    Function `__init__`    utility or script function.
L248: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L283: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
```

```

script function.
L288: def flush(self) -> bytes:    Function `flush`    utility or script function.
L294: class MultiDecoder(ContentDecoder):    Class (`MultiDecoder`)    component used by the app
(see file context: None).
L307: def __init__(self, modes: str) -> None:    Function `__init__`    utility or script
function.
L316: def flush(self) -> bytes:    Function `flush`    utility or script function.
L319: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L346: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L350: def _get_decoder(mode: str) -> ContentDecoder:    Function `_get_decoder`    utility or
script function.
L368: class BytesQueueBuffer:    Class (`BytesQueueBuffer`)    component used by the app (see
file context: None).
L382: def __init__(self) -> None:    Function `__init__`    utility or script function.
L386: def __len__(self) -> int:    Function `__len__`    utility or script function.
L389: def put(self, data: bytes) -> None:    Function `put`    utility or script function.
L393: def get(self, n: int) -> bytes:    Function `get`    Returns or fetches data.
L428: def get_all(self) -> bytes:    Function `get_all`    Returns or fetches data.
L445: class BaseHTTPResponse(io.IOBase):    Class (`BaseHTTPResponse`)    component used by the
app (see file context: None).
L460: def __init__(    Function `__init__`    utility or script function.
L495: def get_redirect_location(self) -> str | None | typing.Literal[False]:    Function
`get_redirect_location`    Returns or fetches data.
L508: def data(self) -> bytes:    Function `data`    utility or script function.
L511: def json(self) -> typing.Any:    Function `json`    utility or script function.
L533: def url(self) -> str | None:    Function `url`    utility or script function.
L537: def url(self, url: str | None) -> None:    Function `url`    utility or script function.
L541: def connection(self) -> BaseHTTPConnection | None:    Function `connection`    utility or
script function.
L545: def retries(self) -> Retry | None:    Function `retries`    utility or script function.
L549: def retries(self, retries: Retry | None) -> None:    Function `retries`    utility or
script function.
L555: def stream(    Function `stream`    utility or script function.
L560: def read(    Function `read`    utility or script function.
L568: def read1(    Function `read1`    utility or script function.
L575: def read_chunked(    Function `read_chunked`    utility or script function.
L582: def release_conn(self) -> None:    Function `release_conn`    utility or script function.
L585: def drain_conn(self) -> None:    Function `drain_conn`    utility or script function.
L588: def shutdown(self) -> None:    Function `shutdown`    utility or script function.
L591: def close(self) -> None:    Function `close`    utility or script function.
L594: def _init_decoder(self) -> None:    Function `_init_decoder`    utility or script
function.
L613: def _decode(    Function `_decode`    utility or script function.
L650: def _flush_decoder(self) -> bytes:    Function `_flush_decoder`    utility or script
function.
L660: def readinto(self, b: bytearray) -> int:    Function `readinto`    utility or script
function.
L669: def getheaders(self) -> HTTPHeaderDict:    Function `getheaders`    Returns or fetches
data.

```

```

L672: def getheader(self, name: str, default: str | None = None) -> str | None:    Function
`getheader` Returns or fetches data.
L676: def info(self) -> HTTPHeaderDict:    Function `info` utility or script function.
L679: def geturl(self) -> str | None:    Function `geturl` Returns or fetches data.
L683: class HTTPResponse(BaseHTTPResponse):    Class (`HTTPResponse`) component used by the
app (see file context: None).
L689: class is also compatible with the Python standard library's :mod:`io`    Class (`is`)
component used by the app (see file context: None).
L716: def __init__(    Function `__init__` utility or script function.
L780: def release_conn(self) -> None:    Function `release_conn` utility or script function.
L787: def drain_conn(self) -> None:    Function `drain_conn` utility or script function.
L803: def data(self) -> bytes:    Function `data` utility or script function.
L814: def connection(self) -> HTTPConnection | None:    Function `connection` utility or
script function.
L817: defisclosed(self) -> bool:    Function `isclosed` utility or script function.
L820: def tell(self) -> int:    Function `tell` utility or script function.
L828: def _init_length(self, request_method: str | None) -> int | None:    Function
`_init_length` utility or script function.
L885: def _error_catcher(self) -> typing.Generator[None]:    Function `_error_catcher`
utility or script function.
L950: def _fp_read(    Function `_fp_read` utility or script function.
L1007: def _raw_read(    Function `_raw_read` utility or script function.
L1059: def read(    Function `read` utility or script function.
L1155: def read1(    Function `read1` utility or script function.
L1225: def stream(    Function `stream` utility or script function.
L1257: def readable(self) -> bool:    Function `readable` utility or script function.
L1260: def shutdown(self) -> None:    Function `shutdown` utility or script function.
L1269: def close(self) -> None:    Function `close` utility or script function.
L1282: def closed(self) -> bool:    Function `closed` utility or script function.
L1294: def fileno(self) -> int:    Function `fileno` utility or script function.
L1305: def flush(self) -> None:    Function `flush` utility or script function.
L1313: def supports_chunked_reads(self) -> bool:    Function `supports_chunked_reads` utility
or script function.
L1322: def _update_chunk_length(self) -> None:    Function `_update_chunk_length` utility or
script function.
L1340: def _handle_chunk(self, amt: int | None) -> bytes:    Function `_handle_chunk` utility
or script function.
L1362: def read_chunked(    Function `read_chunked` utility or script function.
L1447: def url(self) -> str | None:    Function `url` utility or script function.
L1456: def url(self, url: str | None) -> None:    Function `url` utility or script function.
L1459: def __iter__(self) -> typing.Iterator[bytes]:    Function `__iter__` utility or script
function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pip/_vendor/urllib3/exceptions.py

```

L18: class HTTPError(Exception):    Class (`HTTPError`)    component used by the app (see file
context: None).
L22: class HTTPWarning(Warning):    Class (`HTTPWarning`)    component used by the app (see file
context: None).
L29: class PoolError(HTTPError):    Class (`PoolError`)    component used by the app (see file
context: None).
L32: def __init__(self, pool: ConnectionPool, message: str) -> None:    Function `__init__`
utility or script function.
L37: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L42: class RequestError(PoolError):    Class (`RequestError`)    component used by the app (see
file context: None).
L45: def __init__(self, pool: ConnectionPool, url: str | None, message: str) -> None:
Function `__init__`    utility or script function.
L49: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L54: class SSLError(HTTPError):    Class (`SSLError`)    component used by the app (see file
context: None).
L58: class ProxyError(HTTPError):    Class (`ProxyError`)    component used by the app (see file
context: None).
L64: def __init__(self, message: str, error: Exception) -> None:    Function `__init__`
utility or script function.
L69: class DecodeError(HTTPError):    Class (`DecodeError`)    component used by the app (see
file context: None).
L73: class ProtocolError(HTTPError):    Class (`ProtocolError`)    component used by the app
(see file context: None).
L84: class MaxRetryError(RequestError):    Class (`MaxRetryError`)    component used by the app
(see file context: None).
L95: def __init__(    Function `__init__`    utility or script function.
L104: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L109: class HostChangedError(RequestError):    Class (`HostChangedError`)    component used by
the app (see file context: None).
L112: def __init__(    Function `__init__`    utility or script function.
L120: class TimeoutStateError(HTTPError):    Class (`TimeoutStateError`)    component used by
the app (see file context: None).
L124: class TimeoutError(HTTPError):    Class (`TimeoutError`)    component used by the app (see
file context: None).
L132: class ReadTimeoutError(TimeoutError, RequestError):    Class (`ReadTimeoutError`)
component used by the app (see file context: None).
L138: class ConnectTimeoutError(TimeoutError):    Class (`ConnectTimeoutError`)    component
used by the app (see file context: None).
L142: class NewConnectionError(ConnectTimeoutError, HTTPError):    Class
(`NewConnectionError`)    component used by the app (see file context: None).
L145: def __init__(self, conn: HTTPConnection, message: str) -> None:    Function `__init__`
utility or script function.
L150: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L155: def pool(self) -> HTTPConnection:    Function `pool`    utility or script function.
L166: class NameResolutionError(NewConnectionError):    Class (`NameResolutionError`)
component used by the app (see file context: None).

```



```

L169: def __init__(self, host: str, conn: HTTPConnection, reason: socket.gaierror):
Function `__init__` utility or script function.
L175: def __reduce__(self) -> _TYPE_REDUCE_RESULT: Function `__reduce__` utility or script
function.
L180: class EmptyPoolError(PoolError): Class (`EmptyPoolError`) component used by the app
(see file context: None).
L184: class FullPoolError(PoolError): Class (`FullPoolError`) component used by the app
(see file context: None).
L188: class ClosedPoolError(PoolError): Class (`ClosedPoolError`) component used by the
app (see file context: None).
L192: class LocationValueError(ValueError, HTTPError): Class (`LocationValueError`)
component used by the app (see file context: None).
L196: class LocationParseError(LocationValueError): Class (`LocationParseError`) component
used by the app (see file context: None).
L199: def __init__(self, location: str) -> None: Function `__init__` utility or script
function.
L206: class URLSchemeUnknown(LocationValueError): Class (`URLSchemeUnknown`) component
used by the app (see file context: None).
L209: def __init__(self, scheme: str): Function `__init__` utility or script function.
L216: class ResponseError(HTTPError): Class (`ResponseError`) component used by the app
(see file context: None).
L223: class SecurityWarning(HTTPWarning): Class (`SecurityWarning`) component used by the
app (see file context: None).
L227: class InsecureRequestWarning(SecurityWarning): Class (`InsecureRequestWarning`)
component used by the app (see file context: None).
L231: class NotOpenSSLWarning(SecurityWarning): Class (`NotOpenSSLWarning`) component used
by the app (see file context: None).
L235: class SystemTimeWarning(SecurityWarning): Class (`SystemTimeWarning`) component used
by the app (see file context: None).
L239: class InsecurePlatformWarning(SecurityWarning): Class (`InsecurePlatformWarning`)
component used by the app (see file context: None).
L243: class DependencyWarning(HTTPWarning): Class (`DependencyWarning`) component used by
the app (see file context: None).
L250: class ResponseNotChunked(ProtocolError, ValueError): Class (`ResponseNotChunked`)
component used by the app (see file context: None).
L254: class BodyNotHttpLibCompatible(HTTPError): Class (`BodyNotHttpLibCompatible`)
component used by the app (see file context: None).
L261: class IncompleteRead(HTTPError, httplib_IncompleteRead): Class (`IncompleteRead`)
component used by the app (see file context: None).
L272: def __init__(self, partial: int, expected: int) -> None: Function `__init__` utility
or script function.
L276: def __repr__(self) -> str: Function `__repr__` utility or script function.
L283: class InvalidChunkLength(HTTPError, httplib_IncompleteRead): Class
(`InvalidChunkLength`) component used by the app (see file context: None).
L286: def __init__(self, response: HTTPResponse, length: bytes) -> None: Function
`__init__` utility or script function.
L292: def __repr__(self) -> str: Function `__repr__` utility or script function.
L299: class InvalidHeader(HTTPError): Class (`InvalidHeader`) component used by the app
(see file context: None).
L303: class ProxySchemeUnknown(AssertionError, URLSchemeUnknown): Class
(`ProxySchemeUnknown`) component used by the app (see file context: None).

```



```

L308: def __init__(self, scheme: str | None) -> None:    Function `__init__` utility or
script function.
L320: class ProxySchemeUnsupported(ValueError):    Class (`ProxySchemeUnsupported`) component
used by the app (see file context: None).
L324: class HeaderParsingError(HTTPError):    Class (`HeaderParsingError`) component used by
the app (see file context: None).
L327: def __init__(    Function `__init__` utility or script function.
L334: class UnrewindableBodyError(HTTPError):    Class (`UnrewindableBodyError`) component
used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_request_methods.py

```

L20: class RequestMethods:    Class (`RequestMethods`) component used by the app (see file
context: None).
L51: def __init__(self, headers: typing.Mapping[str, str] | None = None) -> None:    Function
`__init__` utility or script function.
L54: def urlopen(    Function `urlopen` utility or script function.
L69: def request(    Function `request` utility or script function.
L147: def request_encode_url(    Function `request_encode_url` utility or script function.
L184: def request_encode_body(    Function `request_encode_body` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/__init__.py

```

L74: def add_stderr_logger(    Function `add_stderr_logger` utility or script function.
L107: def disable_warnings(category: type[Warning] = exceptions.HTTPWarning) -> None:
Function `disable_warnings` utility or script function.
L117: def request(    Function `request` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/poolmanager.py

```

L56: class PoolKey(typing.NamedTuple):    Class (`PoolKey`) component used by the app (see
file context: None).
L95: def _default_key_normalizer(    Function `_default_key_normalizer` utility or script
function.

```

```

L162: class PoolManager(RequestMethods):  Manager (`PoolManager`)  orchestration/utility for
managing resources or behaviors.
L199: def __init__(  Function `__init__`  utility or script function.
L230: def __enter__(self) -> Self:  Function `__enter__`  utility or script function.
L233: def __exit__(  Function `__exit__`  utility or script function.
L243: def _new_pool(  Function `_new_pool`  utility or script function.
L281: def clear(self) -> None:  Function `clear`  utility or script function.
L290: def connection_from_host(  Function `connection_from_host`  utility or script
function.
L319: def connection_from_context(  Function `connection_from_context`  utility or script
function.
L344: def connection_from_pool_key(  Function `connection_from_pool_key`  utility or script
function.
L370: def connection_from_url(  Function `connection_from_url`  utility or script function.
L388: def _merge_pool_kwargs(  Function `_merge_pool_kwargs`  utility or script function.
L410: def _proxy_requires_url_absolute_form(self, parsed_url: Url) -> bool:  Function
`_proxy_requires_url_absolute_form`  utility or script function.
L423: def urlopen( # type: ignore[override]  Function `urlopen`  utility or script
function.
L506: class ProxyManager(PoolManager):  Manager (`ProxyManager`)  orchestration/utility for
managing resources or behaviors.
L561: def __init__(  Function `__init__`  utility or script function.
L602: def connection_from_host(  Function `connection_from_host`  utility or script
function.
L618: def _set_proxy_headers(  Function `_set_proxy_headers`  utility or script function.
L635: def urlopen( # type: ignore[override]  Function `urlopen`  utility or script
function.
L650: def proxy_from_url(url: str, **kw: typing.Any) -> ProxyManager:  Function
`proxy_from_url`  utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/filepost
.py**

```

L22: def choose_boundary() -> str:  Function `choose_boundary`  utility or script function.
L29: def iter_field_objects(fields: _TYPE_FIELDS) -> typing.Iterable[RequestField]:
Function `iter_field_objects`  utility or script function.
L51: def encode_multipart_formdata(  Function `encode_multipart_formdata`  utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_base_
connection.py**

```

L12: class ProxyConfig(typing.NamedTuple):  Class (`ProxyConfig`) component used by the app
(see file context: None).
L19: class _ResponseOptions(typing.NamedTuple):  Class (`_ResponseOptions`) component used
by the app (see file context: None).
L35: class BaseHTTPConnection(Protocol):  Class (`BaseHTTPConnection`) component used by
the app (see file context: None).
L54: def __init__(  Function `__init__` utility or script function.
L67: def set_tunnel(  Function `set_tunnel` Sets or updates a value.
L75: def connect(self) -> None: ...  Function `connect` utility or script function.
L77: def request(  Function `request` utility or script function.
L93: def getresponse(self) -> BaseHTTPResponse: ...  Function `getresponse` Returns or
fetches data.
L95: def close(self) -> None: ...  Function `close` utility or script function.
L98: def is_closed(self) -> bool:  Function `is_closed` utility or script function.
L105: def is_connected(self) -> bool:  Function `is_connected` utility or script function.
L109: def has_connected_to_proxy(self) -> bool:  Function `has_connected_to_proxy` utility
or script function.
L115: class BaseHTTPSConnection(BaseHTTPConnection, Protocol):  Class
(`BaseHTTPSConnection`) component used by the app (see file context: None).
L140: def __init__(  Function `__init__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connectionpool.py

```

L67: class ConnectionPool:  Class (`ConnectionPool`) component used by the app (see file
context: None).
L81: def __init__(self, host: str, port: int | None = None) -> None:  Function `__init__`
utility or script function.
L94: def __str__(self) -> str:  Function `__str__` utility or script function.
L97: def __enter__(self) -> Self:  Function `__enter__` utility or script function.
L100: def __exit__(  Function `__exit__` utility or script function.
L110: def close(self) -> None:  Function `close` utility or script function.
L120: class HTTPConnectionPool(ConnectionPool, RequestMethods):  Class
(`HTTPConnectionPool`) component used by the app (see file context: None).
L175: def __init__(  Function `__init__` utility or script function.
L236: def _new_conn(self) -> BaseHTTPConnection:  Function `_new_conn` utility or script
function.
L256: def _get_conn(self, timeout: float | None = None) -> BaseHTTPConnection:  Function
`_get_conn` utility or script function.
L294: def _put_conn(self, conn: BaseHTTPConnection | None) -> None:  Function `_put_conn`
utility or script function.
L337: def _validate_conn(self, conn: BaseHTTPConnection) -> None:  Function `_validate_conn`
utility or script function.
L342: def _prepare_proxy(self, conn: BaseHTTPConnection) -> None:  Function `_prepare_proxy`
utility or script function.
L346: def _get_timeout(self, timeout: _TYPE_TIMEOUT) -> Timeout:  Function `_get_timeout`

```

```

utility or script function.
L358: def _raise_timeout(    Function `_raise_timeout`    utility or script function.
L377: def _make_request(    Function `_make_request`    utility or script function.
L558: def close(self) -> None:    Function `close`    utility or script function.
L570: def is_same_host(self, url: str) -> bool:    Function `is_same_host`    utility or script
function.
L592: def urlopen(    # type: ignore[override]    Function `urlopen`    utility or script
function.
L963: class HTTPSConnectionPool(HTTPConnectionPool):    Class (`HTTPSConnectionPool`)
component used by the app (see file context: None).
L980: def __init__(    Function `__init__`    utility or script function.
L1029: def _prepare_proxy(self, conn: HTTPSConnection) -> None:    # type: ignore[override]
Function `_prepare_proxy`    utility or script function.
L1044: def _new_conn(self) -> BaseHTTPConnection:    Function `_new_conn`    utility or script
function.
L1085: def _validate_conn(self, conn: BaseHTTPConnection) -> None:    Function
`_validate_conn`    utility or script function.
L1108: def connection_from_url(url: str, **kw: typing.Any) -> HTTPConnectionPool:    Function
`connection_from_url`    utility or script function.
L1138: def _normalize_host(host: None, scheme: str | None) -> None: ...    Function
`_normalize_host`    utility or script function.
L1142: def _normalize_host(host: str, scheme: str | None) -> str: ...    Function
`_normalize_host`    utility or script function.
L1145: def _normalize_host(host: str | None, scheme: str | None) -> str | None:    Function
`_normalize_host`    utility or script function.
L1163: def _url_from_pool(    Function `_url_from_pool`    utility or script function.
L1170: def _close_pool_connections(pool: queue.LifoQueue[typing.Any]) -> None:    Function
`_close_pool_connections`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/timeout.py

```

L14: class _TYPE_DEFAULT(Enum):    Class (`_TYPE_DEFAULT`)    component used by the app (see
file context: None).
L25: class Timeout:    Class (`Timeout`)    component used by the app (see file context: None).
L109: def __init__(    Function `__init__`    utility or script function.
L120: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L127: def resolve_default_timeout(timeout: _TYPE_TIMEOUT) -> float | None:    Function
`resolve_default_timeout`    utility or script function.
L131: def _validate_timeout(cls, value: _TYPE_TIMEOUT, name: str) -> _TYPE_TIMEOUT:
Function `_validate_timeout`    utility or script function.
L173: def from_float(cls, timeout: _TYPE_TIMEOUT) -> Timeout:    Function `from_float`
utility or script function.
L188: def clone(self) -> Timeout:    Function `clone`    utility or script function.
L202: def start_connect(self) -> float:    Function `start_connect`    utility or script
function.

```

```

L213: def get_connect_duration(self) -> float:    Function `get_connect_duration` Returns or
fetches data.
L228: def connect_timeout(self) -> _TYPE_TIMEOUT:    Function `connect_timeout` utility or
script function.
L246: def read_timeout(self) -> float | None:    Function `read_timeout` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/retry.py

```

L33: class RequestHistory(typing.NamedTuple):    Class (`RequestHistory`) component used by
the app (see file context: None).
L41: class Retry:    Class (`Retry`) component used by the app (see file context: None).
L211: def __init__(    Function `__init__` utility or script function.
L258: def new(self, **kw: typing.Any) -> Self:    Function `new` utility or script function.
L283: def from_int(    Function `from_int` utility or script function.
L301: def get_backoff_time(self) -> float:    Function `get_backoff_time` Returns or fetches
data.
L320: def parse_retry_after(self, retry_after: str) -> float:    Function `parse_retry_after`
utility or script function.
L341: def get_retry_after(self, response: BaseHTTPResponse) -> float | None:    Function
`get_retry_after` Returns or fetches data.
L351: def sleep_for_retry(self, response: BaseHTTPResponse) -> bool:    Function
`sleeper_for_retry` utility or script function.
L359: def _sleep_backoff(self) -> None:    Function `_sleep_backoff` utility or script
function.
L365: def sleep(self, response: BaseHTTPResponse | None = None) -> None:    Function `sleep`
utility or script function.
L381: def _is_connection_error(self, err: Exception) -> bool:    Function
`_is_connection_error` utility or script function.
L389: def _is_read_error(self, err: Exception) -> bool:    Function `_is_read_error` utility
or script function.
L395: def _is_method_retryable(self, method: str) -> bool:    Function `_is_method_retryable`
utility or script function.
L403: def is_retry(    Function `is_retry` utility or script function.
L425: def is_exhausted(self) -> bool:    Function `is_exhausted` utility or script function.
L444: def increment(    Function `increment` utility or script function.
L541: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/wait.py

```

L33: def select_wait_for_socket(    Function `select_wait_for_socket`    utility or script
function.
L57: def poll_wait_for_socket(    Function `poll_wait_for_socket`    utility or script function.
L74: def do_poll(t: float | None) -> list[tuple[int, int]]:    Function `do_poll`    utility or
script function.
L82: def _have_working_poll() -> bool:    Function `_have_working_poll`    utility or script
function.
L95: def wait_for_socket(    Function `wait_for_socket`    utility or script function.
L113: def wait_for_read(sock: socket.socket, timeout: float | None = None) -> bool:
Function `wait_for_read`    utility or script function.
L120: def wait_for_write(sock: socket.socket, timeout: float | None = None) -> bool:
Function `wait_for_write`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/connection.py

```

L15: def is_connection_dropped(conn: BaseHTTPConnection) -> bool:    # Platform-specific
Function `is_connection_dropped`    utility or script function.
L27: def create_connection(    Function `create_connection`    Creates a resource or document.
L93: def _set_socket_options(    Function `_set_socket_options`    utility or script function.
L103: def allowed_gai_family() -> socket.AddressFamily:    Function `allowed_gai_family`
utility or script function.
L114: def _has_ipv6(host: str) -> bool:    Function `_has_ipv6`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/url.py

```

L80: class Url(    Class (`Url`)    component used by the app (see file context: None).
L100: def __new__(    # type: ignore[no-untyped-def]    Function `__new__`    utility or script
function.
L117: def hostname(self) -> str | None:    Function `hostname`    utility or script function.
L122: def request_uri(self) -> str:    Function `request_uri`    utility or script function.
L132: def authority(self) -> str | None:    Function `authority`    utility or script function.
L148: def netloc(self) -> str | None:    Function `netloc`    utility or script function.
L162: def url(self) -> str:    Function `url`    utility or script function.
L209: def __str__(self) -> str:    Function `__str__`    utility or script function.
L214: def _encode_invalid_chars(    Function `_encode_invalid_chars`    utility or script
function.
L221: def _encode_invalid_chars(    Function `_encode_invalid_chars`    utility or script
function.
L227: def _encode_invalid_chars(    Function `_encode_invalid_chars`    utility or script
function.

```

```

L263: def _remove_path_dot_segments(path: str) -> str:    Function `_remove_path_dot_segments`
        utility or script function.
L294: def _normalize_host(host: None, scheme: str | None) -> None: ...    Function
        `_normalize_host` utility or script function.
L298: def _normalize_host(host: str, scheme: str | None) -> str: ...    Function
        `_normalize_host` utility or script function.
L301: def _normalize_host(host: str | None, scheme: str | None) -> str | None:    Function
        `_normalize_host` utility or script function.
L330: def _idna_encode(name: str) -> bytes:    Function `_idna_encode` utility or script
        function.
L349: def _encode_target(target: str) -> str:    Function `_encode_target` utility or script
        function.
L367: def parse_url(url: str) -> Url:    Function `parse_url` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/response.py

```

L9: def is_fp_closed(obj: object) -> bool:    Object (singleton).
L40: def assert_header_parsing(headers: httplib.HTTPMessage) -> None:    Function
        `assert_header_parsing` utility or script function.
L91: def is_response_to_head(response: httplib.HTTPResponse) -> bool:    Function
        `is_response_to_head` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssltransport.py

```

L22: class SSLTransport:    Class (`SSLTransport`) component used by the app (see file
        context: None).
L34: def _validate_ssl_context_for_tls_in_tls(ssl_context: ssl.SSLContext) -> None:
        Function `_validate_ssl_context_for_tls_in_tls` utility or script function.
L49: def __init__(    Function `__init__` utility or script function.
L72: def __enter__(self) -> Self:    Function `__enter__` utility or script function.
L75: def __exit__(self, *_: typing.Any) -> None:    Function `__exit__` utility or script
        function.
L78: def fileno(self) -> int:    Function `fileno` utility or script function.
L81: def read(self, len: int = 1024, buffer: typing.Any | None = None) -> int | bytes:
        Function `read` utility or script function.
L84: def recv(self, buflen: int = 1024, flags: int = 0) -> int | bytes:    Function `recv`
        utility or script function.
L89: def recv_into(    Function `recv_into` utility or script function.
L101: def sendall(self, data: bytes, flags: int = 0) -> None:    Function `sendall` utility
        or script function.

```

```

L111: def send(self, data: bytes, flags: int = 0) -> int:    Function `send` utility or
script function.
L116: def makefile(    Function `makefile` utility or script function.
L168: def unwrap(self) -> None:    Function `unwrap` utility or script function.
L171: def close(self) -> None:    Function `close` utility or script function.
L175: def getpeercert(    Function `getpeercert` Returns or fetches data.
L180: def getpeercert(self, binary_form: typing.Literal[True]) -> bytes | None: ...
Function `getpeercert` Returns or fetches data.
L182: def getpeercert(self, binary_form: bool = False) -> _TYPE_PEER_CERT_RET:    Function
`getpeercert` Returns or fetches data.
L185: def version(self) -> str | None:    Function `version` utility or script function.
L188: def cipher(self) -> tuple[str, str, int] | None:    Function `cipher` utility or script
function.
L191: def selected_alpn_protocol(self) -> str | None:    Function `selected_alpn_protocol`
utility or script function.
L194: def shared_ciphers(self) -> list[tuple[str, str, int]] | None:    Function
`shared_ciphers` utility or script function.
L197: def compression(self) -> str | None:    Function `compression` utility or script
function.
L200: def settimeout(self, value: float | None) -> None:    Function `settimeout` Sets or
updates a value.
L203: def gettimeout(self) -> float | None:    Function `gettimeout` Returns or fetches data.
L206: def _decref_socketios(self) -> None:    Function `_decref_socketios` utility or script
function.
L209: def _wrap_ssl_read(self, len: int, buffer: bytearray | None = None) -> int | bytes:
Function `_wrap_ssl_read` utility or script function.
L220: def _ssl_io_loop(self, func: typing.Callable[[], None]) -> None: ...    Function
`_ssl_io_loop` utility or script function.
L224: def _ssl_io_loop(self, func: typing.Callable[[bytes], int], arg1: bytes) -> int: ...
Function `_ssl_io_loop` utility or script function.
L228: def _ssl_io_loop(    Function `_ssl_io_loop` utility or script function.
L235: def _ssl_io_loop(    Function `_ssl_io_loop` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl
_match_hostname.py**

```

L20: class CertificateError(ValueError):    Class (`CertificateError`) component used by the
app (see file context: None).
L24: def _dnsname_match(    Function `_dnsname_match` utility or script function.
L80: def _ipaddress_match(ipname: str, host_ip: IPv4Address | IPv6Address) -> bool:
Function `_ipaddress_match` utility or script function.
L95: def match_hostname(    Function `_match_hostname` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/proxy.py

```
L11: def connection_requires_http_tunnel(    Function `connection_requires_http_tunnel`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl_.py

```
L30: def _is_bpo_43522_fixed(    Function `_is_bpo_43522_fixed`    utility or script function.
L56: def _is_has_never_check_common_name_reliable(    Function
`_is_has_never_check_common_name_reliable`    utility or script function.
L84: class _TYPE_PEER_CERT_RET_DICT(TypedDict, total=False):    Class
(`_TYPE_PEER_CERT_RET_DICT`)    component used by the app (see file context: None).
L152: def assert_fingerprint(cert: bytes | None, fingerprint: str) -> None:    Function
`assert_fingerprint`    utility or script function.
L186: def resolve_cert_reqs(candidate: None | int | str) -> VerifyMode:    Function
`resolve_cert_reqs`    utility or script function.
L209: def resolve_ssl_version(candidate: None | int | str) -> int:    Function
`resolve_ssl_version`    utility or script function.
L225: def create_urllib3_context(    Function `create_urllib3_context`    Creates a resource or
document.
L378: def ssl_wrap_socket(    Function `ssl_wrap_socket`    utility or script function.
L396: def ssl_wrap_socket(    Function `ssl_wrap_socket`    utility or script function.
L413: def ssl_wrap_socket(    Function `ssl_wrap_socket`    utility or script function.
L487: def is_ipaddress(hostname: str | bytes) -> bool:    Function `is_ipaddress`    utility or
script function.
L500: def _is_key_file_encrypted(key_file: str) -> bool:    Function `_is_key_file_encrypted`
utility or script function.
L511: def _ssl_wrap_socket_impl(    Function `_ssl_wrap_socket_impl`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/util.py

```
L7: def to_bytes(    Function `to_bytes`    utility or script function.
L19: def to_str(    Function `to_str`    utility or script function.
L31: def reraise(    Function `reraise`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/request.py

```

L35: class _TYPE_FAILEDTELL(Enum):    AI-related component (`_TYPE_FAILEDTELL`) coordinates
AI/LLM interactions.
L51: def make_headers(    Function `make_headers` utility or script function.
L133: def set_file_position(    Function `set_file_position` Sets or updates a value.
L153: def rewind_body(body: typing.IO[typing.AnyStr], body_pos: _TYPE_BODY_POSITION) -> None:
    Function `rewind_body` utility or script function.
L183: class ChunksAndContentLength(typing.NamedTuple):    Class (`ChunksAndContentLength`)
component used by the app (see file context: None).
L188: def body_to_chunks(    Function `body_to_chunks` utility or script function.
L221: def chunk_readable() -> typing.Iterable[bytes]:    Function `chunk_readable` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/connection.py

```

L29: def _is_legal_header_name(name: bytes) -> bool:    Function `_is_legal_header_name`
utility or script function.
L44: def _is_illegal_header_value(value: bytes) -> bool:    Function
`_is_illegal_header_value` utility or script function.
L54: class _LockedObject(typing.Generic[T]):    Class (`_LockedObject`) component used by the
app (see file context: None).
L68: def __init__(self, obj: T):    Function `__init__` utility or script function.
L72: def __enter__(self) -> T:    Function `__enter__` utility or script function.
L76: def __exit__(    Function `__exit__` utility or script function.
L85: class HTTP2Connection(HTTPSPConnection):    Class (`HTTP2Connection`) component used by
the app (see file context: None).
L86: def __init__(    Function `__init__` utility or script function.
L101: def _new_h2_conn(self) -> _LockedObject[h2.connection.H2Connection]:    Function
`_new_h2_conn` utility or script function.
L105: def connect(self) -> None:    Function `connect` utility or script function.
L112: def putrequest(    # type: ignore[override]    Function `putrequest` utility or script
function.
L143: def putheader(self, header: str | bytes, *values: str | bytes) -> None:    # type:
ignore[override]    Function `putheader` utility or script function.
L156: def endheaders(self, message_body: typing.Any = None) -> None:    # type:
ignore[override]    Function `endheaders` utility or script function.
L170: def send(self, data: typing.Any) -> None:    Function `send` utility or script
function.
L215: def set_tunnel(    Function `set_tunnel` Sets or updates a value.
L226: def getresponse(    # type: ignore[override]    Function `getresponse` Returns or fetches

```

```

data.
L268: def request( # type: ignore[override]    Function `request`    utility or script
function.
L307: def close(self) -> None:    Function `close`    utility or script function.
L324: class HTTP2Response(BaseHTTPResponse):    Class (`HTTP2Response`)    component used by the
app (see file context: None).
L326: def __init__(    Function `__init__`    utility or script function.
L349: def data(self) -> bytes:    Function `data`    utility or script function.
L352: def get_redirect_location(self) -> None:    Function `get_redirect_location`    Returns or
fetches data.
L355: def close(self) -> None:    Function `close`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/_init__.py

```

L15: def inject_into_urllib3() -> None:    Function `inject_into_urllib3`    utility or script
function.
L43: def extract_from_urllib3() -> None:    Function `extract_from_urllib3`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/probe.py

```

L6: class _HTTP2ProbeCache:    Class (`_HTTP2ProbeCache`)    component used by the app (see file
context: None).
L13: def __init__(self) -> None:    Function `__init__`    utility or script function.
L18: def acquire_and_get(self, host: str, port: int) -> bool | None:    Function
`acquire_and_get`    utility or script function.
L51: def set_and_release(    Function `set_and_release`    Sets or updates a value.
L65: def _values(self) -> dict[tuple[str, int], bool | None]:    Function `_values`    utility
or script function.
L70: def _reset(self) -> None:    Function `_reset`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/pyopenssl.py

```

L50: class UnsupportedExtension(Exception):    # type: ignore[no-redef]    Class

```

```
(`UnsupportedExtension`) component used by the app (see file context: None).
L139: def inject_into_urllib3() -> None: Function `inject_into_urllib3` utility or script
function.
L150: def extract_from_urllib3() -> None: Function `extract_from_urllib3` utility or
script function.
L159: def _validate_dependencies_met() -> None: Function `_validate_dependencies_met`
utility or script function.
L185: def _dnsname_to_stdlib(name: str) -> str | None: Function `_dnsname_to_stdlib`
utility or script function.
L199: def idna_encode(name: str) -> bytes | None: Function `idna_encode` utility or script
function.
L226: def get_subj_alt_name(peer_cert: X509) -> list[tuple[str, str]]: Function
`get_subj_alt_name` Returns or fetches data.
L274: class WrappedSocket: Class (`WrappedSocket`) component used by the app (see file
context: None).
L277: def __init__( Function `_init__` utility or script function.
L289: def fileno(self) -> int: Function `fileno` utility or script function.
L293: def _decref_socketios(self) -> None: Function `_decref_socketios` utility or script
function.
L299: def recv(self, *args: typing.Any, **kwargs: typing.Any) -> bytes: Function `recv`
utility or script function.
L324: def recv_into(self, *args: typing.Any, **kwargs: typing.Any) -> int: Function
`recv_into` utility or script function.
L347: def settimeout(self, timeout: float) -> None: Function `settimeout` Sets or updates
a value.
L350: def _send_until_done(self, data: bytes) -> int: Function `_send_until_done` utility
or script function.
L361: def sendall(self, data: bytes) -> None: Function `sendall` utility or script
function.
L369: def shutdown(self, how: int) -> None: Function `shutdown` utility or script
function.
L375: def close(self) -> None: Function `close` utility or script function.
L380: def _real_close(self) -> None: Function `_real_close` utility or script function.
L386: def getpeercert( Function `getpeercert` Returns or fetches data.
L402: def version(self) -> str: Function `version` utility or script function.
L405: def selected_alpn_protocol(self) -> str | None: Function `selected_alpn_protocol`
utility or script function.
L413: class PyOpenSSLContext: Class (`PyOpenSSLContext`) component used by the app (see
file context: None).
L420: def __init__(self, protocol: int) -> None: Function `_init__` utility or script
function.
L430: def options(self) -> int: Function `options` utility or script function.
L434: def options(self, value: int) -> None: Function `options` utility or script
function.
L439: def verify_flags(self) -> int: Function `verify_flags` utility or script function.
L443: def verify_flags(self, value: int) -> None: Function `verify_flags` utility or
script function.
L448: def verify_mode(self) -> int: Function `verify_mode` utility or script function.
L452: def verify_mode(self, value: ssl.VerifyMode) -> None: Function `verify_mode` utility
or script function.
L455: def set_default_verify_paths(self) -> None: Function `set_default_verify_paths` Sets
```

```

or updates a value.
L458: def set_ciphers(self, ciphers: bytes | str) -> None:    Function `set_ciphers` Sets or
updates a value.
L463: def load_verify_locations(    Function `load_verify_locations` Loads data from storage
or remote.
L480: def load_cert_chain(    Function `load_cert_chain` Loads data from storage or remote.
L496: def set_alpn_protocols(self, protocols: list[bytes | str]) -> None:    Function
`set_alpn_protocols` Sets or updates a value.
L500: def wrap_socket(    Function `wrap_socket` utility or script function.
L531: def _set_ctx_options(self) -> None:    Function `_set_ctx_options` utility or script
function.
L539: def minimum_version(self) -> int:    Function `minimum_version` utility or script
function.
L543: def minimum_version(self, minimum_version: int) -> None:    Function `minimum_version`
utility or script function.
L548: def maximum_version(self) -> int:    Function `maximum_version` utility or script
function.
L552: def maximum_version(self, maximum_version: int) -> None:    Function `maximum_version`
utility or script function.
L557: def _verify_callback(    Function `_verify_callback` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/socks.py

```

L75: class _TYPE SOCKS_OPTIONS(typing.TypedDict):    Class (`_TYPE SOCKS_OPTIONS`) component
used by the app (see file context: None).
L84: class SOCKSConnection(HTTPConnection):    Class (`SOCKSConnection`) component used by
the app (see file context: None).
L89: def __init__(    Function `__init__` utility or script function.
L98: def _new_conn(self) -> socks.socksocket:    Function `_new_conn` utility or script
function.
L161: class SOCKSHTTPSConnection(SOCKSConnection, HTTPSConnection):    Class
(`SOCKSHTTPSConnection`) component used by the app (see file context: None).
L165: class SOCKSHTTPSConnectionPool(HTTPConnectionPool):    Class (`SOCKSHTTPSConnectionPool`)
component used by the app (see file context: None).
L169: class SOCKSHTTPSConnectionPool(HTTPSConnectionPool):    Class
(`SOCKSHTTPSConnectionPool`) component used by the app (see file context: None).
L173: class SOCKSProxyManager(PoolManager):    Manager (`SOCKSProxyManager`)
orchestration/utility for managing resources or behaviors.
L184: def __init__(    Function `__init__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/

emscripten/fetch.py

```

L71: class _RequestError(Exception):    Class (`_RequestError`) component used by the app
(see file context: None).
L72: def __init__(    Function `__init__` utility or script function.
L85: class _StreamingError(_RequestError):    Class (`_StreamingError`) component used by the
app (see file context: None).
L89: class _TimeoutError(_RequestError):    Class (`_TimeoutError`) component used by the app
(see file context: None).
L93: def _obj_from_dict(dict_val: dict[str, Any]) -> JsProxy:    Function `_obj_from_dict`
utility or script function.
L97: class _ReadStream(io.RawIOBase):    Class (`_ReadStream`) component used by the app (see
file context: None).
L98: def __init__(    Function `__init__` utility or script function.
L118: def __del__(self) -> None:    Function `__del__` utility or script function.
L122: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L127: def closed(self) -> bool:    Function `closed` utility or script function.
L130: def close(self) -> None:    Function `close` utility or script function.
L144: def readable(self) -> bool:    Function `readable` utility or script function.
L147: def writable(self) -> bool:    Function `writable` utility or script function.
L150: def seekable(self) -> bool:    Function `seekable` utility or script function.
L153: def readinto(self, byte_obj: Buffer) -> int:    Function `readinto` utility or script
function.
L200: class _StreamingFetcher:    Class (`_StreamingFetcher`) component used by the app (see
file context: None).
L201: def __init__(self) -> None:    Function `__init__` utility or script function.
L214: def promise_resolver(js_resolve_fn: JsProxy, js_reject_fn: JsProxy) -> None:    Function
`promise_resolver` utility or script function.
L215: def onMsg(e: JsProxy) -> None:    Function `onMsg` utility or script function.
L219: def onErr(e: JsProxy) -> None:    Function `onErr` utility or script function.
L229: def send(self, request: EmscriptenRequest) -> EmscriptenResponse:    Function `send`
utility or script function.
L302: class _JSPiReadStream(io.RawIOBase):    Class (`_JSPiReadStream`) component used by the
app (see file context: None).
L324: def __init__(    Function `__init__` utility or script function.
L342: def __del__(self) -> None:    Function `__del__` utility or script function.
L346: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L351: def closed(self) -> bool:    Function `closed` utility or script function.
L354: def close(self) -> None:    Function `close` utility or script function.
L367: def readable(self) -> bool:    Function `readable` utility or script function.
L370: def writable(self) -> bool:    Function `writable` utility or script function.
L373: def seekable(self) -> bool:    Function `seekable` utility or script function.
L376: def _get_next_buffer(self) -> bool:    Function `_get_next_buffer` utility or script
function.
L392: def readinto(self, byte_obj: Buffer) -> int:    Function `readinto` utility or script
function.
L410: def is_in_browser_main_thread() -> bool:    Function `is_in_browser_main_thread`
utility or script function.
L414: def is_cross_origin_isolated() -> bool:    Function `is_cross_origin_isolated` utility
or script function.

```

```

L418: def is_in_node() -> bool:    Function `is_in_node` utility or script function.
L427: def is_worker_available() -> bool:    Function `is_worker_available` utility or script
function.
L449: def send_streaming_request(request: EmscriptenRequest) -> EmscriptenResponse | None:
Function `send_streaming_request` utility or script function.
L469: def _show_timeout_warning() -> None:    Function `_show_timeout_warning` utility or
script function.
L480: def _show_streaming_warning() -> None:    Function `_show_streaming_warning` utility or
script function.
L499: def send_request(request: EmscriptenRequest) -> EmscriptenResponse:    Function
`send_request` utility or script function.
L548: def send_jspi_request(    Function `send_jspi_request` utility or script function.
L626: def _run_sync_with_timeout(    Function `_run_sync_with_timeout` utility or script
function.
L680: def has_jspi() -> bool:    Function `has_jspi` utility or script function.
L699: def _is_node_js() -> bool:    Function `_is_node_js` utility or script function.
L714: def streaming_ready() -> bool | None:    Function `streaming_ready` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/connection.py

```

L25: class EmscriptenHTTPConnection:    Class (`EmscriptenHTTPConnection`) component used by
the app (see file context: None).
L46: def __init__(    Function `__init__` utility or script function.
L73: def set_tunnel(    Function `set_tunnel` Sets or updates a value.
L82: def connect(self) -> None:    Function `connect` utility or script function.
L85: def request(    Function `request` utility or script function.
L129: def getresponse(self) -> BaseHTTPResponse:    Function `getresponse` Returns or fetches
data.
L139: def close(self) -> None:    Function `close` utility or script function.
L144: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L152: def is_connected(self) -> bool:    Function `is_connected` utility or script function.
L157: def has_connected_to_proxy(self) -> bool:    Function `has_connected_to_proxy` utility
or script function.
L165: class EmscriptenHTTPSConnection(EmscriptenHTTPConnection):    Class
(`EmscriptenHTTPSConnection`) component used by the app (see file context: None).
L182: def __init__(    Function `__init__` utility or script function.
L242: def set_cert(    Function `set_cert` Sets or updates a value.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/response.py

```

L23: class EmscriptenResponse:    Class (`EmscriptenResponse`)    component used by the app (see
file context: None).
L30: class EmscriptenHttpResponseWrapper(BaseHTTPResponse):    Class
(`EmscriptenHttpResponseWrapper`)    component used by the app (see file context: None).
L31: def __init__(    Function `__init__`    utility or script function.
L56: def url(self) -> str | None:    Function `url`    utility or script function.
L60: def url(self, url: str | None) -> None:    Function `url`    utility or script function.
L64: def connection(self) -> BaseHTTPConnection | BaseHTTPSPConnection | None:    Function
`connection`    utility or script function.
L68: def retries(self) -> Retry | None:    Function `retries`    utility or script function.
L72: def retries(self, retries: Retry | None) -> None:    Function `retries`    utility or
script function.
L76: def stream(    Function `stream`    utility or script function.
L102: def _init_length(self, request_method: str | None) -> int | None:    Function
`_init_length`    utility or script function.
L139: def read(    Function `read`    utility or script function.
L176: def read_chunked(    Function `read_chunked`    utility or script function.
L188: def release_conn(self) -> None:    Function `release_conn`    utility or script function.
L195: def drain_conn(self) -> None:    Function `drain_conn`    utility or script function.
L199: def data(self) -> bytes:    Function `data`    utility or script function.
L205: def json(self) -> typing.Any:    Function `json`    utility or script function.
L226: def close(self) -> None:    Function `close`    utility or script function.
L236: def _error_catcher(self) -> typing.Generator[None]:    Function `_error_catcher`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/
emscripten/__init__.py

```

L9: def inject_into_urllib3() -> None:    Function `inject_into_urllib3`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/
emscripten/request.py

```

L9: class EmscriptenRequest:    Class (`EmscriptenRequest`)    component used by the app (see
file context: None).
L18: def set_header(self, name: str, value: str) -> None:    Function `set_header`    Sets or
updates a value.
L21: def set_body(self, body: _TYPE_BODY | None) -> None:    Function `set_body`    Sets or
updates a value.

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/providers.py

```
L17: class Preference(Protocol):    Class (`Preference`) component used by the app (see file
context: None).
L18: def __lt__(self, __other: Any) -> bool: ...    Function `__lt__` utility or script
function.
L21: class AbstractProvider(Generic[RT, CT, KT]):    Class (`AbstractProvider`) component
used by the app (see file context: None).
L24: def identify(self, requirement_or_candidate: RT | CT) -> KT:    Function `identify`
utility or script function.
L33: def get_preference(    Function `get_preference` Returns or fetches data.
L92: def find_matches(    Function `find_matches` utility or script function.
L127: def is_satisfied_by(self, requirement: RT, candidate: CT) -> bool:    Function
`is_satisfied_by` utility or script function.
L138: def get_dependencies(self, candidate: CT) -> Iterable[RT]:    Function
`get_dependencies` Returns or fetches data.
L146: def narrow_requirement_selection(    Function `narrow_requirement_selection` utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/structs.py

```
L27: class RequirementInformation(NamedTuple, Generic[RT, CT]):    Class
(`RequirementInformation`) component used by the app (see file context: None).
L31: class State(NamedTuple, Generic[RT, CT, KT]):    Class (`State`) component used by the
app (see file context: None).
L45: class DirectedGraph(Generic[KT]):    Class (`DirectedGraph`) component used by the app
(see file context: None).
L48: def __init__(self) -> None:    Function `__init__` utility or script function.
L53: def __iter__(self) -> Iterator[KT]:    Function `__iter__` utility or script function.
L56: def __len__(self) -> int:    Function `__len__` utility or script function.
L59: def __contains__(self, key: KT) -> bool:    Function `__contains__` utility or script
function.
L62: def copy(self) -> DirectedGraph[KT]:    Function `copy` utility or script function.
L70: def add(self, key: KT) -> None:    Function `add` utility or script function.
L78: def remove(self, key: KT) -> None:    Function `remove` utility or script function.
L86: def connected(self, f: KT, t: KT) -> bool:    Function `connected` utility or script
function.
L89: def connect(self, f: KT, t: KT) -> None:    Function `connect` utility or script
function.
L99: def iter_edges(self) -> Iterator[tuple[KT, KT]]:    Function `iter_edges` utility or
script function.
```

```

L104: def iter_children(self, key: KT) -> Iterator[KT]:    Function `iter_children` utility
or script function.
L107: def iter_parents(self, key: KT) -> Iterator[KT]:    Function `iter_parents` utility or
script function.
L111: class IteratorMapping(Mapping[KT, Iterator[CT]], Generic[RT, CT, KT]):    Class
(`IteratorMapping`) component used by the app (see file context: None).
L112: def __init__(    Function `__init__` utility or script function.
L122: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L129: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L132: def __contains__(self, key: object) -> bool:    Object (singleton).
L135: def __getitem__(self, k: KT) -> Iterator[CT]:    Function `__getitem__` utility or
script function.
L142: def __iter__(self) -> Iterator[KT]:    Function `__iter__` utility or script function.
L146: def __len__(self) -> int:    Function `__len__` utility or script function.
L151: class _FactoryIterableView(Iterable[RT]):    Class (`_FactoryIterableView`) component
used by the app (see file context: None).
L160: def __init__(self, factory: Callable[[], Iterable[RT]]) -> None:    Function `__init__`
utility or script function.
L164: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L167: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L174: def __iter__(self) -> Iterator[RT]:    Function `__iter__` utility or script function.
L180: class _SequenceIterableView(Iterable[RT]):    Class (`_SequenceIterableView`) component
used by the app (see file context: None).
L187: def __init__(self, sequence: Sequence[RT]):    Function `__init__` utility or script
function.
L190: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L193: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L196: def __iter__(self) -> Iterator[RT]:    Function `__iter__` utility or script function.
L200: def build_iter_view(matches: Matches[CT]) -> Iterable[CT]:    Function `build_iter_view`
Constructs or prepares an object.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/reports.py

```

L11: class BaseReporter(Generic[RT, CT, KT]):    Class (`BaseReporter`) component used by the
app (see file context: None).
L14: def starting(self) -> None:    Function `starting` utility or script function.
L17: def starting_round(self, index: int) -> None:    Function `starting_round` utility or
script function.
L23: def ending_round(self, index: int, state: State[RT, CT, KT]) -> None:    Function
`ending_round` utility or script function.
L30: def ending(self, state: State[RT, CT, KT]) -> None:    Function `ending` utility or
script function.
L33: def adding_requirement(self, requirement: RT, parent: CT | None) -> None:    Function
`adding_requirement` utility or script function.
L43: def resolving_conflicts(    Function `resolving_conflicts` utility or script function.

```

```
L51: def rejecting_candidate(self, criterion: Criterion[RT, CT], candidate: CT) -> None:
Function `rejecting_candidate` utility or script function.
L54: def pinning(self, candidate: CT) -> None: Function `pinning` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/resolution.py

```
L38: def _build_result(state: State[RT, CT, KT]) -> Result[RT, CT, KT]: Function
`_build_result` utility or script function.
L68: class Resolution(Generic[RT, CT, KT]): Class (`Resolution`) component used by the app
(see file context: None).
L75: def __init__( Function `__init__` utility or script function.
L90: def state(self) -> State[RT, CT, KT]: Function `state` utility or script function.
L96: def _push_new_state(self) -> None: Function `_push_new_state` utility or script
function.
L110: def _add_to_criteria( Function `_add_to_criteria` utility or script function.
L154: def _remove_information_from_criteria( Function `_remove_information_from_criteria`
utility or script function.
L181: def _get_preference(self, name: KT) -> Preference: Function `_get_preference`
utility or script function.
L196: def _is_current_pin_satisfying( Function `_is_current_pin_satisfying` utility or
script function.
L208: def _get_updated_criteria(self, candidate: CT) -> dict[KT, Criterion[RT, CT]]:
Function `_get_updated_criteria` utility or script function.
L214: def _attempt_to_pin_criterion(self, name: KT) -> list[Criterion[RT, CT]]: Function
`_attempt_to_pin_criterion` utility or script function.
L251: def _patch_criteria( Function `_patch_criteria` utility or script function.
L286: def _save_state(self) -> None: Function `_save_state` utility or script function.
L298: def _rollback_states(self) -> None: Function `_rollback_states` utility or script
function.
L305: def _backjump(self, causes: list[RequirementInformation[RT, CT]]) -> bool: Function
`_backjump` utility or script function.
L412: def _extract_causes( Function `_extract_causes` utility or script function.
L418: def resolve(self, requirements: Iterable[RT], max_rounds: int) -> State[RT, CT, KT]:
Function `resolve` utility or script function.
L563: class Resolver(AbstractResolver[RT, CT, KT]): Class (`Resolver`) component used by
the app (see file context: None).
L568: def resolve( # type: ignore[override] Function `resolve` utility or script
function.
L605: def _has_route_to_root( Function `_has_route_to_root` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/res

olvers/exceptions.py

```

L11: class ResolverException(Exception):    Class (`ResolverException`) component used by the
app (see file context: None).
L19: class RequirementsConflicted(ResolverException, Generic[RT, CT]):    Class
(`RequirementsConflicted`) component used by the app (see file context: None).
L20: def __init__(self, criterion: Criterion[RT, CT]) -> None:    Function `__init__` utility
or script function.
L24: def __str__(self) -> str:    Function `__str__` utility or script function.
L30: class InconsistentCandidate(ResolverException, Generic[RT, CT]):    Class
(`InconsistentCandidate`) component used by the app (see file context: None).
L31: def __init__(self, candidate: CT, criterion: Criterion[RT, CT]):    Function `__init__`
utility or script function.
L36: def __str__(self) -> str:    Function `__str__` utility or script function.
L43: class ResolutionError(ResolverException):    Class (`ResolutionError`) component used by
the app (see file context: None).
L47: class ResolutionImpossible(ResolutionError, Generic[RT, CT]):    Class
(`ResolutionImpossible`) component used by the app (see file context: None).
L48: def __init__(self, causes: Collection[RequirementInformation[RT, CT]]):    Function
`__init__` utility or script function.
L54: class ResolutionTooDeep(ResolutionError):    Class (`ResolutionTooDeep`) component used
by the app (see file context: None).
L55: def __init__(self, round_count: int) -> None:    Function `__init__` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/abstract.py

```

L13: class Result(NamedTuple, Generic[RT, CT, KT]):    Class (`Result`) component used by the
app (see file context: None).
L22: class AbstractResolver(Generic[RT, CT, KT]):    Class (`AbstractResolver`) component
used by the app (see file context: None).
L27: def __init__(    Function `__init__` utility or script function.
L35: def resolve(self, requirements: Iterable[RT], **kwargs: Any) -> Result[RT, CT, KT]:
Function `resolve` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/criterion.py

```

L8: class Criterion(Generic[RT, CT]):    Class (`Criterion`) component used by the app (see
file context: None).

```

```

L28: def __init__(    Function `__init__`    utility or script function.
L38: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L44: def iter_requirement(self) -> Iterator[RT]:    Function `iter_requirement`    utility or
script function.
L47: def iter_parent(self) -> Iterator[CT | None]:    Function `iter_parent`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/compat.py

```

L6: def ToASCII(label: str) -> bytes:    Function `ToASCII`    utility or script function.
L10: def ToUnicode(label: Union[bytes, bytearray]) -> str:    Function `ToUnicode`    utility or
script function.
L14: def nameprep(s: Any) -> None:    Function `nameprep`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/core.py

```

L14: class IDNAError(UnicodeError):    Class (`IDNAError`)    component used by the app (see
file context: None).
L20: class IDNABidiError(IDNAError):    Class (`IDNABidiError`)    component used by the app
(see file context: None).
L26: class InvalidCodepoint(IDNAError):    Class (`InvalidCodepoint`)    component used by the
app (see file context: None).
L32: class InvalidCodepointContext(IDNAError):    Class (`InvalidCodepointContext`)    component
used by the app (see file context: None).
L38: def _combining_class(cp: int) -> int:    Function `_combining_class`    utility or script
function.
L46: def _is_script(cp: str, script: str) -> bool:    Function `_is_script`    utility or script
function.
L50: def _punycode(s: str) -> bytes:    Function `_punycode`    utility or script function.
L54: def _unot(s: int) -> str:    Function `_unot`    utility or script function.
L58: def valid_label_length(label: Union[bytes, str]) -> bool:    Function
`valid_label_length`    utility or script function.
L64: def valid_string_length(label: Union[bytes, str], trailing_dot: bool) -> bool:
Function `valid_string_length`    utility or script function.
L70: def check_bidi(label: str, check_ltr: bool = False) -> bool:    Function `check_bidi`
utility or script function.
L140: def check_initial_combiner(label: str) -> bool:    Function `check_initial_combiner`
utility or script function.
L146: def check_hyphen_ok(label: str) -> bool:    Function `check_hyphen_ok`    utility or
script function.
L154: def check_nfc(label: str) -> None:    Function `check_nfc`    utility or script function.

```

```

L159: def valid_contextj(label: str, pos: int) -> bool:    Function `valid_contextj` utility
or script function.
L203: def valid_contexto(label: str, pos: int, exception: bool = False) -> bool:    Function
`valid_contexto` utility or script function.
L245: def check_label(label: Union[str, bytes, bytearray]) -> None:    Function `check_label`
utility or script function.
L284: def alabel(label: str) -> bytes:    Function `alabel` utility or script function.
L303: def ulabel(label: Union[str, bytes, bytearray]) -> str:    Function `ulabel` utility or
script function.
L332: def uts46_remap(domain: str, std3_rules: bool = True, transitional: bool = False) ->
str:    Function `uts46_remap` utility or script function.
L366: def encode(    Function `encode` utility or script function.
L405: def decode(    Function `decode` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/codec.py

```

L10: class Codec(codecs.Codec):    Class (`Codec`) component used by the app (see file
context: None).
L11: def encode(self, data: str, errors: str = "strict") -> Tuple[bytes, int]:    Function
`encode` utility or script function.
L20: def decode(self, data: bytes, errors: str = "strict") -> Tuple[str, int]:    Function
`decode` utility or script function.
L30: class IncrementalEncoder(codecs.BufferedIncrementalEncoder):    Class
(`IncrementalEncoder`) component used by the app (see file context: None).
L31: def _buffer_encode(self, data: str, errors: str, final: bool) -> Tuple[bytes, int]:
Function `_buffer_encode` utility or script function.
L64: class IncrementalDecoder(codecs.BufferedIncrementalDecoder):    Class
(`IncrementalDecoder`) component used by the app (see file context: None).
L65: def _buffer_decode(self, data: Any, errors: str, final: bool) -> Tuple[str, int]:
Function `_buffer_decode` utility or script function.
L100: class StreamWriter(Codec, codecs.StreamWriter):    Class (`StreamWriter`) component
used by the app (see file context: None).
L104: class StreamReader(Codec, codecs.StreamReader):    Class (`StreamReader`) component
used by the app (see file context: None).
L108: def search_function(name: str) -> Optional[codecs.CodecInfo]:    Function
`search_function` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/intranges.py

```

L12: def intranges_from_list(list_: List[int]) -> Tuple[int, ...]:    Function
`intranges_from_list` utility or script function.

```

```

L34: def _encode_range(start: int, end: int) -> int:    Function `_encode_range` utility or
script function.
L38: def _decode_range(r: int) -> Tuple[int, int]:    Function `_decode_range` utility or
script function.
L42: def intranges_contain(int_: int, ranges: Tuple[int, ...]) -> bool:    Function
`intranges_contain` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/idna/uts46dat
a.py**

```

L12: def _seg_0() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_0`
utility or script function.
L117: def _seg_1() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_1`
utility or script function.
L222: def _seg_2() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_2`
utility or script function.
L327: def _seg_3() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_3`
utility or script function.
L432: def _seg_4() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_4`
utility or script function.
L537: def _seg_5() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_5`
utility or script function.
L642: def _seg_6() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_6`
utility or script function.
L747: def _seg_7() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_7`
utility or script function.
L852: def _seg_8() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_8`
utility or script function.
L957: def _seg_9() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_9`
utility or script function.
L1062: def _seg_10() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_10` utility or script function.
L1167: def _seg_11() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_11` utility or script function.
L1272: def _seg_12() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_12` utility or script function.
L1377: def _seg_13() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_13` utility or script function.
L1482: def _seg_14() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_14` utility or script function.
L1587: def _seg_15() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_15` utility or script function.
L1692: def _seg_16() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_16` utility or script function.
L1797: def _seg_17() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function
`_seg_17` utility or script function.

```

```

L1902: def _seg_18() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_18` utility or script function.
L2007: def _seg_19() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_19` utility or script function.
L2112: def _seg_20() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_20` utility or script function.
L2217: def _seg_21() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_21` utility or script function.
L2322: def _seg_22() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_22` utility or script function.
L2427: def _seg_23() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_23` utility or script function.
L2532: def _seg_24() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_24` utility or script function.
L2637: def _seg_25() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_25` utility or script function.
L2742: def _seg_26() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_26` utility or script function.
L2847: def _seg_27() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_27` utility or script function.
L2952: def _seg_28() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_28` utility or script function.
L3057: def _seg_29() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_29` utility or script function.
L3162: def _seg_30() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_30` utility or script function.
L3267: def _seg_31() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_31` utility or script function.
L3372: def _seg_32() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_32` utility or script function.
L3477: def _seg_33() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_33` utility or script function.
L3582: def _seg_34() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_34` utility or script function.
L3687: def _seg_35() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_35` utility or script function.
L3792: def _seg_36() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_36` utility or script function.
L3897: def _seg_37() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_37` utility or script function.
L4002: def _seg_38() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_38` utility or script function.
L4107: def _seg_39() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_39` utility or script function.
L4212: def _seg_40() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_40` utility or script function.
L4317: def _seg_41() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_41` utility or script function.
L4422: def _seg_42() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_42` utility or script function.
L4527: def _seg_43() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function

```



```

`_seg_43` utility or script function.
L4632: def _seg_44() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_44` utility or script function.
L4737: def _seg_45() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_45` utility or script function.
L4842: def _seg_46() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_46` utility or script function.
L4947: def _seg_47() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_47` utility or script function.
L5052: def _seg_48() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_48` utility or script function.
L5157: def _seg_49() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_49` utility or script function.
L5262: def _seg_50() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_50` utility or script function.
L5367: def _seg_51() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_51` utility or script function.
L5472: def _seg_52() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_52` utility or script function.
L5577: def _seg_53() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_53` utility or script function.
L5682: def _seg_54() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_54` utility or script function.
L5787: def _seg_55() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_55` utility or script function.
L5892: def _seg_56() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_56` utility or script function.
L5997: def _seg_57() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_57` utility or script function.
L6102: def _seg_58() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_58` utility or script function.
L6207: def _seg_59() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_59` utility or script function.
L6312: def _seg_60() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_60` utility or script function.
L6417: def _seg_61() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_61` utility or script function.
L6522: def _seg_62() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_62` utility or script function.
L6627: def _seg_63() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_63` utility or script function.
L6732: def _seg_64() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_64` utility or script function.
L6837: def _seg_65() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_65` utility or script function.
L6942: def _seg_66() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_66` utility or script function.
L7047: def _seg_67() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_67` utility or script function.
L7152: def _seg_68() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_68` utility or script function.

```

```

L7257: def _seg_69() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_69` utility or script function.
L7362: def _seg_70() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_70` utility or script function.
L7467: def _seg_71() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_71` utility or script function.
L7572: def _seg_72() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_72` utility or script function.
L7677: def _seg_73() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_73` utility or script function.
L7782: def _seg_74() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_74` utility or script function.
L7887: def _seg_75() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_75` utility or script function.
L7992: def _seg_76() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_76` utility or script function.
L8097: def _seg_77() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_77` utility or script function.
L8202: def _seg_78() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_78` utility or script function.
L8307: def _seg_79() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_79` utility or script function.
L8412: def _seg_80() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_80` utility or script function.
L8517: def _seg_81() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_81` utility or script function.
L8622: def _seg_82() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_82` utility or script function.
L8727: def _seg_83() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_83` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_elf
file.py**

```

L18: class ELFInvalid(ValueError): Class (`ELFInvalid`) component used by the app (see
file context: None).
L22: class EIClass(enum.IntEnum): Class (`EIClass`) component used by the app (see file
context: None).
L27: class EIData(enum.IntEnum): Class (`EIData`) component used by the app (see file
context: None).
L32: class EMachine(enum.IntEnum): Class (`EMachine`) component used by the app (see file
context: None).
L40: class ELFFile: Class (`ELFFile`) component used by the app (see file context: None).
L45: def __init__(self, f: IO[bytes]) -> None: Function `__init__` utility or script
function.
L90: def _read(self, fmt: str) -> tuple[int, ...]: Function `_read` utility or script

```

```
function.
L94: def interpreter(self) -> str | None:    Function `interpreter` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_manylinux.py

```
L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:    Function
`_parse_elf` utility or script function.
L40: def _is_linux_armhf(executable: str) -> bool:    Function `_is_linux_armhf` utility or
script function.
L55: def _is_linux_i686(executable: str) -> bool:    Function `_is_linux_i686` utility or
script function.
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:    Function
`_have_compatible_abi` utility or script function.
L81: class _GLibCVersion(NamedTuple):    Class (`_GLibCVersion`) component used by the app
(see file context: None).
L86: def _glibc_version_string_confstr() -> str | None:    Function
`_glibc_version_string_confstr` utility or script function.
L105: def _glibc_version_string_ctypes() -> str | None:    Function
`_glibc_version_string_ctypes` utility or script function.
L149: def _glibc_version_string() -> str | None:    Function `_glibc_version_string` utility
or script function.
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:    Function
`_parse_glibc_version` utility or script function.
L174: def _get_glibc_version() -> _GLibCVersion:    Function `_get_glibc_version` utility or
script function.
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:    Function
`_is_compatible` utility or script function.
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/direct_url.py

```
L27: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L34: class _FromMappingProtocol(Protocol):    # pragma: no cover    Class
(`_FromMappingProtocol`) component used by the app (see file context: None).
L36: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict` utility
or script function.
L42: def _json_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_json_dict_factory` utility or script function.
```

```

L46: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get` utility or script function.
L59: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required` utility or script function.
L66: def _get_object( Function `_get_object` utility or script function.
L83: def _strip_auth_from_netloc(netloc: str, safe_user_passwords: Collection[str]) -> str:
Function `_strip_auth_from_netloc` utility or script function.
L94: def _strip_url(url: str, safe_user_passwords: Collection[str]) -> str: Function
`_strip_url` utility or script function.
L112: class DirectUrlValidationError(Exception): Class (`DirectUrlValidationError`)
component used by the app (see file context: None).
L118: def __init__( Function `__init__` utility or script function.
L136: def __str__(self) -> str: Function `__str__` utility or script function.
L142: class _DirectUrlRequiredKeyError(DirectUrlValidationError): Class
(`_DirectUrlRequiredKeyError`) component used by the app (see file context: None).
L143: def __init__(self, key: str) -> None: Function `__init__` utility or script
function.
L148: class VcsInfo: Class (`VcsInfo`) component used by the app (see file context: None).
L153: def __init__( Function `__init__` utility or script function.
L165: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L175: class ArchiveInfo: Class (`ArchiveInfo`) component used by the app (see file
context: None).
L178: def __init__( Function `__init__` utility or script function.
L186: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L221: class DirInfo: Class (`DirInfo`) component used by the app (see file context: None).
L224: def __init__( Function `__init__` utility or script function.
L232: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L239: class DirectUrl: Class (`DirectUrl`) component used by the app (see file context:
None).
L248: def __init__( Function `__init__` utility or script function.
L264: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L289: def from_dict(cls, d: Mapping[str, Any], /) -> Self: Function `from_dict` utility or
script function.
L293: def to_dict( Function `to_dict` utility or script function.
L320: def validate(self) -> None: Function `validate` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/me
tadata.py**

```

L40: def __dir__() -> list[str]: Function `__dir__` utility or script function.
L44: class InvalidMetadata(ValueError): Class (`InvalidMetadata`) component used by the
app (see file context: None).

```

```

L50: def __init__(self, field: str, message: str) -> None:    Function `__init__`    utility or
script function.
L59: class RawMetadata(TypedDict, total=False):    Class (`RawMetadata`)    component used by
the app (see file context: None).
L178: def _parse_keywords(data: str) -> list[str]:    Function `_parse_keywords`    utility or
script function.
L183: def _parse_project_urls(data: list[str]) -> dict[str, str]:    Function
`_parse_project_urls`    utility or script function.
L222: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:    Function
`_get_payload`    utility or script function.
L291: class RFC822Policy(email.policy.EmailPolicy):    Class (`RFC822Policy`)    component used
by the app (see file context: None).
L301: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:    Function
`header_store_parse`    utility or script function.
L308: class RFC822Message(email.message.EmailMessage):    Class (`RFC822Message`)    component
used by the app (see file context: None).
L315: def __init__(self) -> None:    Function `__init__`    utility or script function.
L318: def as_bytes(    Function `as_bytes`    utility or script function.
L329: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
Function `parse_email`    utility or script function.
L520: class _Validator(Generic[T]):    Class (`_Validator`)    component used by the app (see
file context: None).
L534: def __init__(    Function `__init__`    utility or script function.
L541: def __set_name__(self, _owner: Metadata, name: str) -> None:    Function `__set_name__`
utility or script function.
L545: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:    Function
`__get__`    utility or script function.
L572: def _invalid_metadata(    Function `_invalid_metadata`    utility or script function.
L581: def _process_metadata_version(self, value: str) -> _MetadataVersion:    Function
`_process_metadata_version`    utility or script function.
L587: def _process_name(self, value: str) -> str:    Function `_process_name`    utility or
script function.
L600: def _process_version(self, value: str) -> version_module.Version:    Function
`_process_version`    utility or script function.
L610: def _process_summary(self, value: str) -> str:    Function `_process_summary`    utility
or script function.
L616: def _process_description_content_type(self, value: str) -> str:    Function
`_process_description_content_type`    utility or script function.
L648: def _process_dynamic(self, value: list[str]) -> list[str]:    Function
`_process_dynamic`    utility or script function.
L660: def _process_provides_extra(    Function `_process_provides_extra`    utility or script
function.
L675: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:    Function
`_process_requires_python`    utility or script function.
L683: def _process_requires_dist(    Function `_process_requires_dist`    utility or script
function.
L698: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
Function `_process_license_expression`    utility or script function.
L706: def _process_license_files(self, value: list[str]) -> list[str]:    Function
`_process_license_files`    utility or script function.
L732: def _process_import_names(self, value: list[str]) -> list[str]:    Function

```

```

`_process_import_names` utility or script function.
L757: class Metadata: Class (`Metadata`) component used by the app (see file context:
None).
L769: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata: Function
`from_raw` utility or script function.
L823: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
Function `from_email` utility or script function.
L932: def as_rfc822(self) -> RFC822Message: Function `as_rfc822` utility or script
function.
L940: def _write_metadata(self, message: RFC822Message) -> None: Function `_write_metadata`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/markers.py

```

L30: def __dir__() -> list[str]: Function `__dir__` utility or script function.
L54: class InvalidMarker(ValueError): Class (`InvalidMarker`) component used by the app
(see file context: None).
L62: class UndefinedComparison(ValueError): Class (`UndefinedComparison`) component used
by the app (see file context: None).
L71: class UndefinedEnvironmentName(ValueError): Class (`UndefinedEnvironmentName`)
component used by the app (see file context: None).
L75: class Environment(TypedDict): Class (`Environment`) component used by the app (see
file context: None).
L152: def _normalize_extras( Function `_normalize_extras` utility or script function.
L168: def _normalize_extra_values(results: MarkerList) -> MarkerList: Function
`_normalize_extra_values` utility or script function.
L176: def _format_marker( Function `_format_marker` utility or script function.
L216: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
Function `_eval_op` utility or script function.
L233: def _normalize( Function `_normalize` utility or script function.
L254: def _evaluate_markers( Function `_evaluate_markers` utility or script function.
L287: def _format_full_version(info: sys._version_info) -> str: Function
`_format_full_version` utility or script function.
L295: def default_environment() -> Environment: Function `default_environment` utility or
script function.
L317: class Marker: Class (`Marker`) component used by the app (see file context: None).
L339: def __init__(self, marker: str) -> None: Function `__init__` utility or script
function.
L370: def _from_markers(cls, markers: MarkerList) -> Marker: Function `_from_markers`
utility or script function.
L379: def __str__(self) -> str: Function `__str__` utility or script function.
L382: def __repr__(self) -> str: Function `__repr__` utility or script function.
L385: def __hash__(self) -> int: Function `__hash__` utility or script function.
L388: def __eq__(self, other: object) -> bool: Object (singleton).
L394: def __getstate__(self) -> str: Function `__getstate__` utility or script function.

```

```

L399: def __setstate__(self, state: object) -> None:    Object (singleton).
L423: def __and__(self, other: Marker) -> Marker:    Function `__and__` utility or script
function.
L428: def __or__(self, other: Marker) -> Marker:    Function `__or__` utility or script
function.
L433: def evaluate(    Function `evaluate` utility or script function.
L482: def _repair_python_full_version(    Function `_repair_python_full_version` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/specifiers.py

```

L48: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L52: def _validate_spec(spec: object, /) -> TypeGuard[tuple[str, str]]:    Object (singleton).
L61: def _validate_pre(pre: object, /) -> TypeGuard[bool | None]:    Object (singleton).
L74: def _trim_release(release: tuple[int, ...]) -> tuple[int, ...]:    Function
`_trim_release` utility or script function.
L82: class _BoundaryKind(enum.Enum):    Class (`_BoundaryKind`) component used by the app
(see file context: None).
L90: class _BoundaryVersion:    Class (`_BoundaryVersion`) component used by the app (see
file context: None).
L113: def __init__(self, version: Version, kind: _BoundaryKind) -> None:    Function
`__init__` utility or script function.
L118: def _is_family(self, other: Version) -> bool:    Function `_is_family` utility or
script function.
L133: def __eq__(self, other: object) -> bool:    Object (singleton).
L138: def __lt__(self, other: _BoundaryVersion | Version) -> bool:    Function `__lt__`
utility or script function.
L145: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L148: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L153: class _LowerBound:    Class (`_LowerBound`) component used by the app (see file
context: None).
L163: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:    Function
`__init__` utility or script function.
L167: def __eq__(self, other: object) -> bool:    Object (singleton).
L172: def __lt__(self, other: _LowerBound) -> bool:    Function `__lt__` utility or script
function.
L185: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L188: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L194: class _UpperBound:    Class (`_UpperBound`) component used by the app (see file
context: None).
L204: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:    Function
`__init__` utility or script function.
L208: def __eq__(self, other: object) -> bool:    Object (singleton).
L213: def __lt__(self, other: _UpperBound) -> bool:    Function `__lt__` utility or script
function.

```



```

L226: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L229: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L246: def _range_is_empty(lower: _LowerBound, upper: _UpperBound) -> bool:    Function
`_range_is_empty` utility or script function.
L255: def _intersect_ranges(    Function `_intersect_ranges` utility or script function.
L281: def _next_prefix_dev0(version: Version) -> Version:    Function `_next_prefix_dev0`
utility or script function.
L287: def _base_dev0(version: Version) -> Version:    Function `_base_dev0` utility or script
function.
L292: def _coerce_version(version: UnparsedVersion) -> Version | None:    Function
`_coerce_version` utility or script function.
L301: def _public_version(version: Version) -> Version:    Function `_public_version` utility
or script function.
L307: def _post_base(version: Version) -> Version:    Function `_post_base` utility or script
function.
L315: def _earliest_prerelease(version: Version) -> Version:    Function
`_earliest_prerelease` utility or script function.
L323: def _nearest_non_prerelease(    Function `_nearest_non_prerelease` utility or script
function.
L344: class InvalidSpecifier(ValueError):    Class (`InvalidSpecifier`) component used by the
app (see file context: None).
L356: class BaseSpecifier(metaclass=abc.ABCMeta):    Class (`BaseSpecifier`) component used
by the app (see file context: None).
L361: def _str(self) -> str:    Function `_str` utility or script function.
L366: def __str__(self) -> str:    Function `__str__` utility or script function.
L373: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L379: def __eq__(self, other: object) -> bool:    Object (singleton).
L389: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L397: def prereleases(self, value: bool) -> None:    Function `prereleases` utility or script
function.
L404: def contains(self, item: str, prereleases: bool | None = None) -> bool:    Function
`contains` utility or script function.
L410: def filter(    Function `filter` utility or script function.
L418: def filter(    Function `filter` utility or script function.
L426: def filter(    Function `filter` utility or script function.
L438: class Specifier(BaseSpecifier):    Class (`Specifier`) component used by the app (see
file context: None).
L573: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:    Function
`__init__` utility or script function.
L611: def _get_spec_version(self, version: str) -> Version | None:    Function
`_get_spec_version` utility or script function.
L623: def _require_spec_version(self, version: str) -> Version:    Function
`_require_spec_version` utility or script function.
L633: def _to_ranges(self) -> Sequence[_VersionRange]:    Function `_to_ranges` utility or
script function.
L657: def _wildcard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:    Function
`_wildcard_ranges` utility or script function.
L670: def _standard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:    Function
`_standard_ranges` utility or script function.
L733: def prereleases(self) -> bool | None:    Function `prereleases` utility or script

```



```

function.
L761: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility or
script function.
L764: def __getstate__(self) -> tuple[tuple[str, str], bool | None]:    Function
`__getstate__` utility or script function.
L770: def __setstate__(self, state: object) -> None:    Object (singleton).
L805: def operator(self) -> str:    Function `operator` utility or script function.
L814: def version(self) -> str:    Function `version` utility or script function.
L822: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L840: def __str__(self) -> str:    Function `__str__` utility or script function.
L851: def _canonical_spec(self) -> tuple[str, str]:    Function `_canonical_spec` utility or
script function.
L864: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L867: def __eq__(self, other: object) -> bool:    Object (singleton).
L896: def _get_operator(self, op: str) -> CallableOperator:    Function `_get_operator`
utility or script function.
L902: def _compare_compatible(self, prospective: Version, spec: str) -> bool:    Function
`_compare_compatible` utility or script function.
L922: def _get_wildcard_split(self, spec: str) -> tuple[list[str], int]:    Function
`_get_wildcard_split` utility or script function.
L938: def _compare_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_equal` utility or script function.
L974: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_not_equal` utility or script function.
L977: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_less_than_equal` utility or script function.
L983: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
Function `_compare_greater_than_equal` utility or script function.
L989: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:    Function
`_compare_less_than` utility or script function.
L1014: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
Function `_compare_greater_than` utility or script function.
L1046: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
Function `_compare_arbitrary` utility or script function.
L1049: def __contains__(self, item: str | Version) -> bool:    Function `__contains__`
utility or script function.
L1070: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
Function `contains` utility or script function.
L1098: def filter(    Function `filter` utility or script function.
L1106: def filter(    Function `filter` utility or script function.
L1113: def filter(    Function `filter` utility or script function.
L1198: def _pep440_filter_prereleases(    Function `_pep440_filter_prereleases` utility or
script function.
L1240: def _version_split(version: str) -> list[str]:    Function `_version_split` utility or
script function.
L1262: def _version_join(components: list[str]) -> str:    Function `_version_join` utility
or script function.
L1273: def _is_not_suffix(segment: str) -> bool:    Function `_is_not_suffix` utility or
script function.
L1279: def _numeric_prefix_len(split: list[str]) -> int:    Function `_numeric_prefix_len`
utility or script function.

```

```

L1293: def _left_pad(split: list[str], target_numeric_len: int) -> list[str]:    Function
`_left_pad` utility or script function.
L1307: def _operator_cost(op_entry: tuple[CallableOperator, str, str]) -> int:    Function
`_operator_cost` utility or script function.
L1334: class SpecifierSet(BaseSpecifier):    Class (`SpecifierSet`) component used by the app
(see file context: None).
L1362: def __init__(    Function `__init__` utility or script function.
L1407: def _canonical_specs(self) -> tuple[Specifier, ...]:    Function `_canonical_specs`
utility or script function.
L1417: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L1437: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility
or script function.
L1441: def __getstate__(self) -> tuple[tuple[Specifier, ...], bool | None]:    Function
`__getstate__` utility or script function.
L1447: def __setstate__(self, state: object) -> None:    Object (singleton).
L1504: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L1525: def __str__(self) -> str:    Function `__str__` utility or script function.
L1538: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L1541: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:    Function `__and__`
utility or script function.
L1574: def __eq__(self, other: object) -> bool:    Object (singleton).
L1600: def __len__(self) -> int:    Function `__len__` utility or script function.
L1604: def __iter__(self) -> Iterator[Specifier]:    Function `__iter__` utility or script
function.
L1614: def _get_ranges(self) -> Sequence[_VersionRange]:    Function `_get_ranges` utility or
script function.
L1636: def is_unsatisfiable(self) -> bool:    Function `is_unsatisfiable` utility or script
function.
L1669: def _check_prerelease_only_ranges(self) -> bool:    Function
`_check_prerelease_only_ranges` utility or script function.
L1682: def _check_arbitrary_unsatisfiable(self) -> bool:    Function
`_check_arbitrary_unsatisfiable` utility or script function.
L1721: def __contains__(self, item: UnparsedVersion) -> bool:    Function `__contains__`
utility or script function.
L1742: def contains(    Function `contains` utility or script function.
L1788: def filter(    Function `filter` utility or script function.
L1796: def filter(    Function `filter` utility or script function.
L1803: def filter(    Function `filter` utility or script function.
L1899: def _filter_versions(    Function `_filter_versions` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/de
pendency_groups.py**

```

L19: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L28: class DuplicateGroupNames(ValueError):    Class (`DuplicateGroupNames`) component used

```

by the app (see file context: None).

L34: class CyclicDependencyGroup(ValueError): Class (`CyclicDependencyGroup`) component used by the app (see file context: None).

L39: def __init__(self, requested_group: str, group: str, include_group: str) -> None: Function `\_\_init\_\_` utility or script function.

L57: class InvalidDependencyGroupObject(ValueError): Class (`InvalidDependencyGroupObject`) component used by the app (see file context: None).

L69: class DependencyGroupInclude: Class (`DependencyGroupInclude`) component used by the app (see file context: None).

L72: def __init__(self, include_group: str) -> None: Function `\_\_init\_\_` utility or script function.

L80: def __repr__(self) -> str: Function `\_\_repr\_\_` utility or script function.

L84: class DependencyGroupResolver: Class (`DependencyGroupResolver`) component used by the app (see file context: None).

L96: def __init__(self) -> None: Function `\_\_init\_\_` utility or script function.

L115: def lookup(self, group: str) -> tuple[Requirement | DependencyGroupInclude, ...]: Function `lookup` utility or script function.

L129: def resolve(self, group: str) -> tuple[Requirement, ...]: Function `resolve` utility or script function.

L142: def _resolve(self, group: str) -> tuple[Requirement, ...]: Function `\_resolve` utility or script function.

L200: def _parse_group(self, group: str) -> tuple[Requirement, ...]: Function `\_parse\_group` utility or script function.

L255: def resolve_dependency_groups(self, groups: list[str]) -> tuple[Requirement, ...]: Function `resolve\_dependency\_groups` utility or script function.

L277: def _normalize_name(self, name: str) -> str: Function `\_normalize\_name` utility or script function.

L281: def _normalize_group_names(self, groups: list[str]) -> list[str]: Function `\_normalize\_group\_names` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_tokenizer.py

L12: class Token: Class (`Token`) component used by the app (see file context: None).

L18: class ParserSyntaxError(Exception): Class (`ParserSyntaxError`) component used by the app (see file context: None).

L21: def __init__(self, token: Token) -> None: Function `\_\_init\_\_` utility or script function.

L34: def __str__(self) -> str: Function `\_\_str\_\_` utility or script function.

L91: class Tokenizer: Class (`Tokenizer`) component used by the app (see file context: None).

L98: def __init__(self, input: str) -> None: Function `\_\_init\_\_` utility or script function.

L109: def consume(self) -> Token: Function `consume` utility or script function.

L114: def check(self, name: str, *, peek: bool = False) -> bool: Function `check` utility or script function.

L135: def expect(self, name: str, *, expected: str) -> Token: Function `expect` utility or script function.

L144: def read(self) -> Token: Function `read` utility or script function.

L154: def raise_syntax_error(self, message: str) -> None: Function `raise\_syntax\_error` utility or script function.

```
L173: def enclosing_tokens(    Function `enclosing_tokens`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_parser.py

```
L15: class Node:    Class (`Node`)    component used by the app (see file context: None).
L18: def __init__(self, value: str) -> None:    Function `__init__`    utility or script
function.
L21: def __str__(self) -> str:    Function `__str__`    utility or script function.
L24: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L27: def serialize(self) -> str:    Function `serialize`    utility or script function.
L30: def __getstate__(self) -> str:    Function `__getstate__`    utility or script function.
L34: def _restore_value(self, value: object) -> None:    Object (singleton).
L41: def __setstate__(self, state: object) -> None:    Object (singleton).
L59: class Variable(Node):    Class (`Variable`)    component used by the app (see file context:
None).
L62: def serialize(self) -> str:    Function `serialize`    utility or script function.
L66: class Value(Node):    Class (`Value`)    component used by the app (see file context:
None).
L69: def serialize(self) -> str:    Function `serialize`    utility or script function.
L73: class Op(Node):    Class (`Op`)    component used by the app (see file context: None).
L76: def serialize(self) -> str:    Function `serialize`    utility or script function.
L87: class ParsedRequirement(NamedTuple):    Class (`ParsedRequirement`)    component used by
the app (see file context: None).
L98: def parse_requirement(source: str) -> ParsedRequirement:    Function `parse_requirement`
utility or script function.
L102: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:    Function
`_parse_requirement`    utility or script function.
L123: def _parse_requirement_details(    Function `_parse_requirement_details`    utility or
script function.
L176: def _parse_requirement_marker(    Function `_parse_requirement_marker`    utility or
script function.
L197: def _parse_extras(tokenizer: Tokenizer) -> list[str]:    Function `_parse_extras`
utility or script function.
L216: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:    Function
`_parse_extras_list`    utility or script function.
L243: def _parse_specifier(tokenizer: Tokenizer) -> str:    Function `_parse_specifier`
utility or script function.
L260: def _parse_version_many(tokenizer: Tokenizer) -> str:    Function `_parse_version_many`
utility or script function.
L292: def parse_marker(source: str) -> MarkerList:    Function `parse_marker`    utility or
script function.
L296: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:    Function
`_parse_full_marker`    utility or script function.
L302: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:    Function `_parse_marker`
utility or script function.
```

```

L314: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:    Function
`_parse_marker_atom` utility or script function.
L336: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:    Function
`_parse_marker_item` utility or script function.
L350: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar:    # noqa: RET503    Function
`_parse_marker_var` utility or script function.
L364: def process_env_var(env_var: str) -> Variable:    Function `process_env_var` utility or
script function.
L371: def process_python_str(python_str: str) -> Value:    Function `process_python_str`
utility or script function.
L376: def _parse_marker_op(tokenizer: Tokenizer) -> Op:    Function `_parse_marker_op`
utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/util
s.py**

```

L27: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L39: class InvalidName(ValueError):    Class (`InvalidName`) component used by the app (see
file context: None).
L45: class InvalidWheelFilename(ValueError):    Class (`InvalidWheelFilename`) component used
by the app (see file context: None).
L51: class InvalidSdistFilename(ValueError):    Class (`InvalidSdistFilename`) component used
by the app (see file context: None).
L66: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
Function `canonicalize_name` utility or script function.
L103: def is_normalized_name(name: str) -> bool:    Function `is_normalized_name` utility or
script function.
L119: def canonicalize_version(    Function `canonicalize_version` utility or script
function.
L157: def parse_wheel_filename(    Function `parse_wheel_filename` utility or script
function.
L249: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:    Function
`parse_sdist_filename` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/ver
sion.py**

```

L37: def _deprecated(message: str) -> object:    Object (singleton).
L38: def decorator(func: Callable[[...], object]) -> object:    Object (singleton).
L40: def wrapper(*args: object, **kwargs: object) -> object:    Object (singleton).
L66: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L81: class _VersionReplace(TypedDict, total=False):    Class (`_VersionReplace`) component

```

```

used by the app (see file context: None).
L90: def normalize_pre(letter: str, /) -> str:    Function `normalize_pre`    utility or script
function.
L111: def parse(version: str) -> Version:    Function `parse`    utility or script function.
L125: class InvalidVersion(ValueError):    Class (`InvalidVersion`)    component used by the app
(see file context: None).
L135: class _BaseVersion:    Class (`_BaseVersion`)    component used by the app (see file
context: None).
L144: def _key(self) -> tuple[Any, ...]: ...    Function `_key`    utility or script function.
L146: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L152: def __lt__(self, other: _BaseVersion) -> bool:    Function `__lt__`    utility or script
function.
L158: def __le__(self, other: _BaseVersion) -> bool:    Function `__le__`    utility or script
function.
L164: def __eq__(self, other: object) -> bool:    Object (singleton).
L170: def __ge__(self, other: _BaseVersion) -> bool:    Function `__ge__`    utility or script
function.
L176: def __gt__(self, other: _BaseVersion) -> bool:    Function `__gt__`    utility or script
function.
L182: def __ne__(self, other: object) -> bool:    Object (singleton).
L266: def _validate_epoch(value: object, /) -> int:    Object (singleton).
L274: def _validate_release(value: object, /) -> tuple[int, ...]:    Object (singleton).
L286: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
Object (singleton).
L299: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:    Object
(singleton).
L308: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:    Object
(singleton).
L317: def _validate_local(value: object, /) -> LocalType | None:    Object (singleton).
L327: class _Version(NamedTuple):    Class (`_Version`)    component used by the app (see file
context: None).
L336: class Version(_BaseVersion):    Class (`Version`)    component used by the app (see file
context: None).
L404: def __init__(self, version: str) -> None:    Function `__init__`    utility or script
function.
L455: def from_parts(    Function `from_parts`    utility or script function.
L501: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:    Function
`__replace__`    utility or script function.
L560: def _key(self) -> CmpKey:    Function `_key`    utility or script function.
L574: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L592: def __lt__(self, other: _BaseVersion) -> bool:    Function `__lt__`    utility or script
function.
L619: def __le__(self, other: _BaseVersion) -> bool:    Function `__le__`    utility or script
function.
L646: def __eq__(self, other: object) -> bool:    Object (singleton).
L673: def __ge__(self, other: _BaseVersion) -> bool:    Function `__ge__`    utility or script
function.
L700: def __gt__(self, other: _BaseVersion) -> bool:    Function `__gt__`    utility or script
function.
L727: def __ne__(self, other: object) -> bool:    Object (singleton).
L754: def __getstate__(    Function `__getstate__`    utility or script function.

```

```

L776: def __setstate__(self, state: object) -> None:    Object (singleton).
L823: def _version(self) -> _Version:    Function `_version` utility or script function.
L830: def _version(self, value: _Version) -> None:    Function `_version` utility or script
function.
L840: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L848: def __str__(self) -> str:    Function `__str__` utility or script function.
L880: def _str(self) -> str:    Function `_str` utility or script function.
L885: def epoch(self) -> int:    Function `epoch` utility or script function.
L896: def release(self) -> tuple[int, ...]:    Function `release` utility or script function.
L912: def pre(self) -> tuple[Literal["a", "b", "rc"], int] | None:    Function `pre` utility
or script function.
L927: def post(self) -> int | None:    Function `post` utility or script function.
L938: def dev(self) -> int | None:    Function `dev` utility or script function.
L949: def local(self) -> str | None:    Function `local` utility or script function.
L963: def public(self) -> str:    Function `public` utility or script function.
L979: def base_version(self) -> str:    Function `base_version` utility or script function.
L1000: def is_prerelease(self) -> bool:    Function `is_prerelease` utility or script
function.
L1017: def is_postrelease(self) -> bool:    Function `is_postrelease` utility or script
function.
L1028: def is_devrelease(self) -> bool:    Function `is_devrelease` utility or script
function.
L1039: def major(self) -> int:    Function `major` utility or script function.
L1048: def minor(self) -> int:    Function `minor` utility or script function.
L1059: def micro(self) -> int:    Function `micro` utility or script function.
L1070: class _TrimmedRelease(_Version):    Class (`_TrimmedRelease`) component used by the app
(see file context: None).
L1073: def __init__(self, version: str | _Version) -> None:    Function `__init__` utility or
script function.
L1086: def release(self) -> tuple[int, ...]:    Function `release` utility or script
function.
L1104: def _parse_letter_version(    Function `_parse_letter_version` utility or script
function.
L1131: def _parse_local_version(local: str | None) -> LocalType | None:    Function
`_parse_local_version` utility or script function.
L1157: def _cmpkey(    Function `_cmpkey` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_structures.py

```

L18: class InfinityType:    Class (`InfinityType`) component used by the app (see file
context: None).
L21: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L25: class NegativeInfinityType:    Class (`NegativeInfinityType`) component used by the app
(see file context: None).
L28: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/tag s.py

```

L54: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L75: def _compute_32_bit_interpreter() -> bool:    Function `_compute_32_bit_interpreter`
utility or script function.
L82: class UnsortedTagsError(ValueError):    Class (`UnsortedTagsError`)    component used by
the app (see file context: None).
L88: class Tag:    Class (`Tag`)    component used by the app (see file context: None).
L108: def __init__(self, interpreter: str, abi: str, platform: str) -> None:    Function
`__init__`    utility or script function.
L128: def interpreter(self) -> str:    Function `interpreter`    utility or script function.
L137: def abi(self) -> str:    Function `abi`    utility or script function.
L144: def platform(self) -> str:    Function `platform`    utility or script function.
L150: def __eq__(self, other: object) -> bool:    Object (singleton).
L161: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L164: def __str__(self) -> str:    Function `__str__`    utility or script function.
L167: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L170: def __getstate__(self) -> tuple[str, str, str]:    Function `__getstate__`    utility or
script function.
L175: def __setstate__(self, state: object) -> None:    Object (singleton).
L203: def parse_tag(tag: str, *, validate_order: bool = False) -> frozenset[Tag]:    Function
`parse_tag`    utility or script function.
L240: def _get_config_var(name: str, warn: bool = False) -> int | str | None:    Function
`_get_config_var`    utility or script function.
L249: def _normalize_string(string: str) -> str:    Function `_normalize_string`    utility or
script function.
L253: def _is_threaded_cpython(abis: list[str]) -> bool:    Function `_is_threaded_cpython`
utility or script function.
L269: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3_applies`    utility or script function.
L279: def _abi3t_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3t_applies`    utility or script function.
L292: def _cpython_abis(py_version: PythonVersion, warn: bool = False) -> list[str]:
Function `_cpython_abis`    utility or script function.
L325: def cpython_tags(    Function `cpython_tags`    utility or script function.
L404: def _generic_abi() -> list[str]:    Function `_generic_abi`    utility or script function.
L445: def generic_tags(    Function `generic_tags`    utility or script function.
L486: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:    Function
`_py_interpreter_range`    utility or script function.
L501: def compatible_tags(    Function `compatible_tags`    utility or script function.
L536: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:    Function
`_mac_arch`    utility or script function.
L546: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:    Function
`_mac_binary_formats`    utility or script function.
L578: def mac_platforms(    Function `mac_platforms`    utility or script function.
L667: def ios_platforms(    Function `ios_platforms`    utility or script function.
L729: def android_platforms(    Function `android_platforms`    utility or script function.

```



```

L766: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:    Function
`_linux_platforms`    utility or script function.
L785: def _emscripten_platforms() -> Iterator[str]:    Function `_emscripten_platforms`
utility or script function.
L794: def _generic_platforms() -> Iterator[str]:    Function `_generic_platforms`    utility or
script function.
L798: def platform_tags() -> Iterator[str]:    Function `platform_tags`    utility or script
function.
L816: def interpreter_name() -> str:    Function `interpreter_name`    utility or script
function.
L829: def interpreter_version(*, warn: bool = False) -> str:    Function `interpreter_version`
utility or script function.
L841: def _version_nodot(version: PythonVersion) -> str:    Function `_version_nodot`    utility
or script function.
L845: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:    Function `sys_tags`    utility or
script function.
L889: def create_compatible_tags_selector(    Function `create_compatible_tags_selector`
Creates a resource or document.
L919: def selector(    Function `selector`    utility or script function.

```

Q_base

**appwrite/venv/lib/python3.12/site-packages/pip/_vendor/packaging/err
ors.py**

```

L11: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L19: class ExceptionGroup(Exception):    Class (`ExceptionGroup`)    component used by the app
(see file context: None).
L29: def __init__(self, message: str, exceptions: list[Exception]) -> None:    Function
`__init__`    utility or script function.
L33: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L38: class _ErrorCollector:    Class (`_ErrorCollector`)    component used by the app (see file
context: None).
L59: def finalize(self, msg: str) -> None:    Function `finalize`    utility or script function.
L65: def on_exit(self, msg: str) -> typing.Generator[_ErrorCollector, None, None]:    Function
`on_exit`    utility or script function.
L75: def collect(self, *err_cls: type[Exception]) -> typing.Generator[None, None, None]:
Function `collect`    utility or script function.
L89: def error(    Function `error`    utility or script function.

```

Q_base

**appwrite/venv/lib/python3.12/site-packages/pip/_vendor/packaging/_m
usllinux.py**

```

L18: class _MuslVersion(NamedTuple):    Class (`_MuslVersion`)    component used by the app (see

```

```

file context: None).
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:    Function
`_parse_musl_version` utility or script function.
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:    Function
`_get_musl_version` utility or script function.
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/requirements.py

```

L20: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L24: class InvalidRequirement(ValueError):    Class (`InvalidRequirement`) component used by
the app (see file context: None).
L30: class Requirement:    Class (`Requirement`) component used by the app (see file context:
None).
L53: def __init__(self, requirement_string: str) -> None:    Function `__init__` utility or
script function.
L68: def _iter_parts(self, name: str) -> Iterator[str]:    Function `_iter_parts` utility or
script function.
L86: def __getstate__(self) -> str:    Function `__getstate__` utility or script function.
L91: def __setstate__(self, state: object) -> None:    Object (singleton).
L110: def __str__(self) -> str:    Function `__str__` utility or script function.
L113: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L116: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L119: def __eq__(self, other: object) -> bool:    Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/pylock.py

```

L54: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L62: class _FromMappingProtocol(Protocol):    # pragma: no cover    Class
(`_FromMappingProtocol`) component used by the app (see file context: None).
L64: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict` utility
or script function.
L73: def is_valid_pylock_path(path: Path) -> bool:    Function `is_valid_pylock_path` utility
or script function.
L78: def _toml_key(key: str) -> str:    Function `_toml_key` utility or script function.
L82: def _toml_value(key: str, value: Any) -> Any:    # noqa: ANN401    Function `_toml_value`
utility or script function.
L90: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_toml_dict_factory` utility or script function.

```

```

L98: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get` utility or script function.
L111: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required` utility or script function.
L118: def _get_sequence( Function `_get_sequence` utility or script function.
L140: def _get_as( Function `_get_as` utility or script function.
L159: def _get_required_as( Function `_get_required_as` utility or script function.
L172: def _get_sequence_as( Function `_get_sequence_as` utility or script function.
L191: def _get_object( Function `_get_object` utility or script function.
L203: def _get_sequence_of_objects( Function `_get_sequence_of_objects` utility or script
function.
L219: def _get_required_sequence_of_objects( Function `_get_required_sequence_of_objects`
utility or script function.
L229: def _validate_normalized_name(name: str) -> NormalizedName: Function
`_validate_normalized_name` utility or script function.
L236: def _validate_path_url(path: str | None, url: str | None) -> None: Function
`_validate_path_url` utility or script function.
L241: def _path_name(path: str | None) -> str | None: Function `_path_name` utility or
script function.
L254: def _url_name(url: str | None) -> str | None: Function `_url_name` utility or script
function.
L261: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]: Function
`_validate_hashes` utility or script function.
L269: class PylockValidationError(Exception): Class (`PylockValidationError`) component
used by the app (see file context: None).
L275: def __init__( Function `__init__` utility or script function.
L293: def __str__(self) -> str: Function `__str__` utility or script function.
L299: class _PylockRequiredKeyError(PylockValidationError): Class
(`_PylockRequiredKeyError`) component used by the app (see file context: None).
L300: def __init__(self, key: str) -> None: Function `__init__` utility or script
function.
L304: class PylockUnsupportedVersionError(PylockValidationError): Class
(`PylockUnsupportedVersionError`) component used by the app (see file context: None).
L308: class PylockSelectError(Exception): Class (`PylockSelectError`) component used by
the app (see file context: None).
L313: class PackageVcs: Class (`PackageVcs`) component used by the app (see file context:
None).
L321: def __init__( Function `__init__` utility or script function.
L340: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L354: class PackageDirectory: Class (`PackageDirectory`) component used by the app (see
file context: None).
L359: def __init__( Function `__init__` utility or script function.
L372: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L381: class PackageArchive: Class (`PackageArchive`) component used by the app (see file
context: None).
L389: def __init__( Function `__init__` utility or script function.
L408: def _from_dict(cls, d: Mapping[str, Any]) -> Self: Function `_from_dict` utility or
script function.
L422: class PackageSdist: Class (`PackageSdist`) component used by the app (see file

```

```

context: None).
L430: def __init__(    Function `__init__`    utility or script function.
L449: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L462: def filename(self) -> str:    Function `filename`    utility or script function.
L471: class PackageWheel:    Class (`PackageWheel`)    component used by the app (see file
context: None).
L479: def __init__(    Function `__init__`    utility or script function.
L498: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L511: def filename(self) -> str:    Function `filename`    utility or script function.
L520: class Package:    Class (`Package`)    component used by the app (see file context: None).
L535: def __init__(    Function `__init__`    utility or script function.
L568: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L649: def is_direct(self) -> bool:    Function `is_direct`    utility or script function.
L654: class Pylock:    Class (`Pylock`)    component used by the app (see file context: None).
L667: def __init__(    Function `__init__`    utility or script function.
L692: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L715: def from_dict(cls, d: Mapping[str, Any], /) -> Self:    Function `from_dict`    utility or
script function.
L723: def to_dict(self) -> Mapping[str, Any]:    Function `to_dict`    utility or script
function.
L727: def validate(self) -> None:    Function `validate`    utility or script function.
L733: def select(    Function `select`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):    Class (`SPDXLicense`)    component used by the app (see
file context: None).
L10: class SPDXException(TypedDict):    Class (`SPDXException`)    component used by the app
(see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/__init__.py

```

L47: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L60: class InvalidLicenseExpression(ValueError):    Class (`InvalidLicenseExpression`)
component used by the app (see file context: None).
L71: def canonicalize_license_expression(    Function `canonicalize_license_expression`

```

utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_impl.py

```

L16: class SubprocessRunner(Protocol):    Class (`SubprocessRunner`) component used by the
app (see file context: None).
L19: def __call__(    Function `__call__` utility or script function.
L28: def write_json(obj: Mapping[str, Any], path: str, **kwargs) -> None:    Function
`write_json` utility or script function.
L33: def read_json(path: str) -> Mapping[str, Any]:    Function `read_json` utility or script
function.
L38: class BackendUnavailable(Exception):    Class (`BackendUnavailable`) component used by
the app (see file context: None).
L41: def __init__(    Function `__init__` utility or script function.
L55: class HookMissing(Exception):    Class (`HookMissing`) component used by the app (see
file context: None).
L58: def __init__(self, hook_name: str) -> None:    Function `__init__` utility or script
function.
L63: class UnsupportedOperation(Exception):    Class (`UnsupportedOperation`) component used
by the app (see file context: None).
L66: def __init__(self, traceback: str) -> None:    Function `__init__` utility or script
function.
L70: def default_subprocess_runner(    Function `default_subprocess_runner` utility or script
function.
L86: def quiet_subprocess_runner(    Function `quiet_subprocess_runner` utility or script
function.
L102: def norm_and_check(source_tree: str, requested: str) -> str:    Function
`norm_and_check` utility or script function.
L126: class BuildBackendHookCaller:    Class (`BuildBackendHookCaller`) component used by the
app (see file context: None).
L129: def __init__(    Function `__init__` utility or script function.
L159: def subprocess_runner(self, runner: "SubprocessRunner") -> Iterator[None]:    Function
`subprocess_runner` utility or script function.
L178: def _supported_features(self) -> Sequence[str]:    Function `_supported_features`
utility or script function.
L182: def get_requires_for_build_wheel(    Function `get_requires_for_build_wheel` Returns or
fetches data.
L200: def prepare_metadata_for_build_wheel(    Function `prepare_metadata_for_build_wheel`
utility or script function.
L233: def build_wheel(    Function `build_wheel` Constructs or prepares an object.
L265: def get_requires_for_build_editable(    Function `get_requires_for_build_editable`
Returns or fetches data.
L283: def prepare_metadata_for_build_editable(    Function
`prepare_metadata_for_build_editable` utility or script function.
L315: def build_editable(    Function `build_editable` Constructs or prepares an object.

```

```

L348: def get_requires_for_build_sdist(    Function `get_requires_for_build_sdist` Returns or
fetches data.
L360: def build_sdist(    Function `build_sdist` Constructs or prepares an object.
L378: def _call_hook(self, hook_name: str, kwargs: Mapping[str, Any]) -> Any:    Function
`_call_hook` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/_in_process.py

```

L31: def write_json(obj, path, **kwargs):    Function `write_json` utility or script
function.
L36: def read_json(path):    Function `read_json` utility or script function.
L41: class BackendUnavailable(Exception):    Class (`BackendUnavailable`) component used by
the app (see file context: None).
L44: def __init__(self, message, traceback=None):    Function `__init__` utility or script
function.
L50: class HookMissing(Exception):    Class (`HookMissing`) component used by the app (see
file context: None).
L53: def __init__(self, hook_name=None):    Function `__init__` utility or script function.
L58: def _build_backend():    Function `_build_backend` utility or script function.
L81: class _BackendPathFinder:    Class (`_BackendPathFinder`) component used by the app (see
file context: None).
L89: def __init__(self, backend_path, backend_module):    Function `__init__` utility or
script function.
L94: def find_spec(self, fullname, _path, _target=None):    Function `find_spec` utility or
script function.
L111: def find_distributions(self, context=None):    Function `find_distributions` utility or
script function.
L119: def _supported_features():    Function `_supported_features` utility or script
function.
L132: def get_requires_for_build_wheel(config_settings):    Function
`get_requires_for_build_wheel` Returns or fetches data.
L146: def get_requires_for_build_editable(config_settings):    Function
`get_requires_for_build_editable` Returns or fetches data.
L160: def prepare_metadata_for_build_wheel(    Function `prepare_metadata_for_build_wheel`
utility or script function.
L184: def prepare_metadata_for_build_editable(    Function
`prepare_metadata_for_build_editable` utility or script function.
L215: def _dist_info_files(whl_zip):    Function `_dist_info_files` utility or script
function.
L227: def _get_wheel_metadata_from_wheel(whl_basename, metadata_directory, config_settings):
    Function `_get_wheel_metadata_from_wheel` utility or script function.
L245: def _find_already_built_wheel(metadata_directory):    Function
`_find_already_built_wheel` utility or script function.
L268: def build_wheel(wheel_directory, config_settings, metadata_directory=None):    Function
`build_wheel` Constructs or prepares an object.

```

```

L285: def build_editable(wheel_directory, config_settings, metadata_directory=None):
Function `build_editable` Constructs or prepares an object.
L306: def get_requires_for_build_sdist(config_settings): Function
`get_requires_for_build_sdist` Returns or fetches data.
L320: class _DummyException(Exception): Class (`_DummyException`) component used by the
app (see file context: None).
L324: class GotUnsupportedOperation(Exception): Class (`GotUnsupportedOperation`)
component used by the app (see file context: None).
L327: def __init__(self, traceback): Function `__init__` utility or script function.
L331: def build_sdist(sdist_directory, config_settings): Function `build_sdist` Constructs
or prepares an object.
L353: def main(): Function `main` Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/__init__.py

```

L13: def _in_proc_script_path(): Function `_in_proc_script_path` utility or script
function.
L18: def _in_proc_script_path(): Function `_in_proc_script_path` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_ssl_constants.py

```

L28: def _set_ssl_context_verify_mode( Function `_set_ssl_context_verify_mode` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_windows.py

```

L39: class CERT_CONTEXT(Structure): Class (`CERT_CONTEXT`) component used by the app (see
file context: None).
L53: class CERT_ENHKEY_USAGE(Structure): Class (`CERT_ENHKEY_USAGE`) component used by the
app (see file context: None).
L63: class CERT_USAGE_MATCH(Structure): Class (`CERT_USAGE_MATCH`) component used by the
app (see file context: None).
L70: class CERT_CHAIN_PARA(Structure): AI-related component (`CERT_CHAIN_PARA`)

```

```

coordinates AI/LLM interactions.
L90: class CERT_TRUST_STATUS(Structure):    Class (`CERT_TRUST_STATUS`)    component used by the
app (see file context: None).
L97: class CERT_CHAIN_ELEMENT(Structure):    AI-related component (`CERT_CHAIN_ELEMENT`)
coordinates AI/LLM interactions.
L112: class CERT_SIMPLE_CHAIN(Structure):    AI-related component (`CERT_SIMPLE_CHAIN`)
coordinates AI/LLM interactions.
L127: class CERT_CHAIN_CONTEXT(Structure):    AI-related component (`CERT_CHAIN_CONTEXT`)
coordinates AI/LLM interactions.
L144: class SSL_EXTRA_CERT_CHAIN_POLICY_PARA(Structure):    AI-related component
(`SSL_EXTRA_CERT_CHAIN_POLICY_PARA`)    coordinates AI/LLM interactions.
L153: class CERT_CHAIN_POLICY_PARA(Structure):    AI-related component
(`CERT_CHAIN_POLICY_PARA`)    coordinates AI/LLM interactions.
L164: class CERT_CHAIN_POLICY_STATUS(Structure):    AI-related component
(`CERT_CHAIN_POLICY_STATUS`)    coordinates AI/LLM interactions.
L177: class CERT_CHAIN_ENGINE_CONFIG(Structure):    AI-related component
(`CERT_CHAIN_ENGINE_CONFIG`)    coordinates AI/LLM interactions.
L238: def _handle_win_error(result: bool, _: Any, args: Any) -> Any:    Function
`_handle_win_error`    utility or script function.
L323: def _verify_peercerts_impl(    Function `_verify_peercerts_impl`    utility or script
function.
L415: def _get_and_verify_cert_chain(    Function `_get_and_verify_cert_chain`    utility or
script function.
L505: def _verify_using_custom_ca_certs(    Function `_verify_using_custom_ca_certs`    utility
or script function.
L558: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:    Function
`_configure_context`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_api.py

```

L34: def inject_into_ssl() -> None:    Function `inject_into_ssl`    utility or script function.
L66: def extract_from_ssl() -> None:    Function `extract_from_ssl`    utility or script
function.
L77: class SSLContext(_truststore_SSLContext_super_class):    # type: ignore[misc]    Class
(`SSLContext`)    component used by the app (see file context: None).
L81: def __class__(self) -> type:    Function `__class__`    utility or script function.
L87: def __init__(self, protocol: int = None) -> None:    # type: ignore[assignment]    Function
`__init__`    utility or script function.
L91: class TruststoreSSLObject(ssl.SSLObject):    Class (`TruststoreSSLObject`)    component
used by the app (see file context: None).
L96: def do_handshake(self) -> None:    Function `do_handshake`    utility or script function.
L103: def wrap_socket(    Function `wrap_socket`    utility or script function.
L136: def wrap_bio(    Function `wrap_bio`    utility or script function.
L154: def load_verify_locations(    Function `load_verify_locations`    Loads data from storage
or remote.

```



```

L164: def load_cert_chain(    Function `load_cert_chain`  Loads data from storage or remote.
L174: def load_default_certs(    Function `load_default_certs`  Loads data from storage or
remote.
L179: def set_alpn_protocols(self, alpn_protocols: typing.Iterable[str]) -> None:    Function
`set_alpn_protocols`  Sets or updates a value.
L182: def set_npn_protocols(self, npn_protocols: typing.Iterable[str]) -> None:    Function
`set_npn_protocols`  Sets or updates a value.
L185: def set_ciphers(self, __cipherlist: str) -> None:    Function `set_ciphers`  Sets or
updates a value.
L188: def get_ciphers(self) -> typing.Any:    Function `get_ciphers`  Returns or fetches data.
L191: def session_stats(self) -> dict[str, int]:    Function `session_stats`  utility or
script function.
L194: def cert_store_stats(self) -> dict[str, int]:    Function `cert_store_stats`  utility or
script function.
L197: def set_default_verify_paths(self) -> None:    Function `set_default_verify_paths`  Sets
or updates a value.
L201: def get_ca_certs(    Function `get_ca_certs`  Returns or fetches data.
L206: def get_ca_certs(self, binary_form: typing.Literal[True] = ...) -> list[bytes]: ...
Function `get_ca_certs`  Returns or fetches data.
L209: def get_ca_certs(self, binary_form: bool = ...) -> typing.Any: ...    Function
`get_ca_certs`  Returns or fetches data.
L211: def get_ca_certs(self, binary_form: bool = False) -> list[typing.Any] | list[bytes]:
Function `get_ca_certs`  Returns or fetches data.
L215: def check_hostname(self) -> bool:    Function `check_hostname`  utility or script
function.
L219: def check_hostname(self, value: bool) -> None:    Function `check_hostname`  utility or
script function.
L223: def hostname_checks_common_name(self) -> bool:    Function `hostname_checks_common_name`
utility or script function.
L227: def hostname_checks_common_name(self, value: bool) -> None:    Function
`hostname_checks_common_name`  utility or script function.
L231: def keylog_filename(self) -> str:    Function `keylog_filename`  utility or script
function.
L235: def keylog_filename(self, value: str) -> None:    Function `keylog_filename`  utility or
script function.
L239: def maximum_version(self) -> ssl.TLSVersion:    Function `maximum_version`  utility or
script function.
L243: def maximum_version(self, value: ssl.TLSVersion) -> None:    Function `maximum_version`
utility or script function.
L249: def minimum_version(self) -> ssl.TLSVersion:    Function `minimum_version`  utility or
script function.
L253: def minimum_version(self, value: ssl.TLSVersion) -> None:    Function `minimum_version`
utility or script function.
L259: def options(self) -> ssl.Options:    Function `options`  utility or script function.
L263: def options(self, value: ssl.Options) -> None:    Function `options`  utility or script
function.
L269: def post_handshake_auth(self) -> bool:    Function `post_handshake_auth`  utility or
script function.
L273: def post_handshake_auth(self, value: bool) -> None:    Function `post_handshake_auth`
utility or script function.
L277: def protocol(self) -> ssl._SSLMethod:    Function `protocol`  utility or script

```

```

function.
L281: def security_level(self) -> int:    Function `security_level` utility or script
function.
L285: def verify_flags(self) -> ssl.VerifyFlags:    Function `verify_flags` utility or script
function.
L289: def verify_flags(self, value: ssl.VerifyFlags) -> None:    Function `verify_flags`
utility or script function.
L295: def verify_mode(self) -> ssl.VerifyMode:    Function `verify_mode` utility or script
function.
L299: def verify_mode(self, value: ssl.VerifyMode) -> None:    Function `verify_mode` utility
or script function.
L310: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:    Function
`_get_unverified_chain_bytes` utility or script function.
L319: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:    Function
`_get_unverified_chain_bytes` utility or script function.
L324: def _verify_peercerts(    Function `_verify_peercerts` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_openssl.py

```

L25: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:    Function
`_configure_context` utility or script function.
L51: def _capath_contains_certs(capath: str) -> bool:    Function `_capath_contains_certs`
utility or script function.
L61: def _verify_peercerts_impl(    Function `_verify_peercerts_impl` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_macos.py

```

L31: def _load_cdll(name: str, macos10_16_path: str) -> CDLL:    Function `_load_cdll`
utility or script function.
L223: def _handle_osstatus(result: OSStatus, _: typing.Any, args: typing.Any) -> typing.Any:
Function `_handle_osstatus` utility or script function.
L283: class CFConst:    Class (`CFConst`) component used by the app (see file context: None).
L294: def _bytes_to_cf_data_ref(value: bytes) -> CFDataRef:    # type: ignore[valid-type]
Function `_bytes_to_cf_data_ref` utility or script function.
L300: def _bytes_to_cf_string(value: bytes) -> CFString:    Function `_bytes_to_cf_string`
utility or script function.
L314: def _cf_string_ref_to_str(cf_string_ref: CFStringRef) -> str | None:    # type:
ignore[valid-type]    Function `_cf_string_ref_to_str` utility or script function.
L337: def _der_certs_to_cf_cert_array(certs: list[bytes]) -> CFMutableArrayRef:    # type:

```

```

ignore[valid-type]    Function `_der_certs_to_cf_cert_array` utility or script function.
L368: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:    Function
`_configure_context` utility or script function.
L380: def _verify_peer certs_impl(    Function `_verify_peer certs_impl` utility or script
function.
L469: def _verify_peer certs_impl_macos_10_13(    Function `_verify_peer certs_impl_macos_10_13`
utility or script function.
L513: def _verify_peer certs_impl_macos_10_14(    Function `_verify_peer certs_impl_macos_10_14`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/certifi/core.py

```

L10: def exit_cacert_ctx() -> None:    Function `exit_cacert_ctx` utility or script function.
L21: def where() -> str:    Function `where` utility or script function.
L46: def contents() -> str:    Function `contents` utility or script function.
L56: def where() -> str:    Function `where` utility or script function.
L82: def contents() -> str:    Function `contents` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/console.py

```

L40: def reset_color():    Function `reset_color` utility or script function.
L44: def colorize(color_key, text):    Function `colorize` utility or script function.
L48: def ansiformat(attr, text):    Function `ansiformat` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexer.py

```

L37: class LexerMeta(type):    Class (`LexerMeta`) component used by the app (see file
context: None).
L43: def __new__(mcs, name, bases, d):    Function `__new__` utility or script function.
L49: class Lexer(metaclass=LexerMeta):    Class (`Lexer`) component used by the app (see file
context: None).
L145: def __init__(self, **options):    Function `__init__` utility or script function.
L156: def __init__(self, **options):    Function `__init__` utility or script function.
L175: def __repr__(self):    Function `__repr__` utility or script function.
L181: def add_filter(self, filter_, **options):    Function `add_filter` utility or script
function.

```

```

L189: def analyse_text(text):    Function `analyse_text` utility or script function.
L206: def _preprocess_lexer_input(self, text):    Function `_preprocess_lexer_input` utility
or script function.
L255: def get_tokens(self, text, unfiltered=False):    Function `get_tokens` Returns or
fetches data.
L271: def streamer():    Function `streamer` utility or script function.
L279: def get_tokens_unprocessed(self, text):    Function `get_tokens_unprocessed` Returns or
fetches data.
L291: class DelegatingLexer(Lexer):    Class (`DelegatingLexer`) component used by the app
(see file context: None).
L301: def __init__(self, _root_lexer, _language_lexer, _needle=Other, **options):    Function
`__init__` utility or script function.
L307: def get_tokens_unprocessed(self, text):    Function `get_tokens_unprocessed` Returns or
fetches data.
L330: class include(str):    # pylint: disable=invalid-name    Class (`include`) component used
by the app (see file context: None).
L337: class _inherit:    Class (`_inherit`) component used by the app (see file context:
None).
L341: def __repr__(self):    Function `__repr__` utility or script function.
L347: class combined(tuple):    # pylint: disable=invalid-name    Class (`combined`) component
used by the app (see file context: None).
L352: def __new__(cls, *args):    Function `__new__` utility or script function.
L355: def __init__(self, *args):    Function `__init__` utility or script function.
L360: class _PseudoMatch:    Class (`_PseudoMatch`) component used by the app (see file
context: None).
L365: def __init__(self, start, text):    Function `__init__` utility or script function.
L369: def start(self, arg=None):    Function `start` utility or script function.
L372: def end(self, arg=None):    Function `end` utility or script function.
L375: def group(self, arg=None):    Function `group` utility or script function.
L380: def groups(self):    Function `groups` utility or script function.
L383: def groupdict(self):    Function `groupdict` utility or script function.
L387: def bygroups(*args):    Function `bygroups` utility or script function.
L391: def callback(lexer, match, ctx=None):    Function `callback` utility or script
function.
L413: class _This:    Class (`_This`) component used by the app (see file context: None).
L422: def using(_other, **kwargs):    Function `using` utility or script function.
L444: def callback(lexer, match, ctx=None):    Function `callback` utility or script
function.
L459: def callback(lexer, match, ctx=None):    Function `callback` utility or script
function.
L472: class default:    Class (`default`) component used by the app (see file context: None).
L480: def __init__(self, state):    Function `__init__` utility or script function.
L484: class words(Future):    Class (`words`) component used by the app (see file context:
None).
L491: def __init__(self, words, prefix='', suffix=''):    Function `__init__` utility or
script function.
L496: def get(self):    Function `get` Returns or fetches data.
L500: class RegexLexerMeta(LexerMeta):    Class (`RegexLexerMeta`) component used by the app
(see file context: None).
L506: def _process_regex(cls, regex, rflags, state):    Function `_process_regex` utility or
script function.

```

```

L512: def _process_token(cls, token):    Function `_process_token` utility or script
function.
L518: def _process_new_state(cls, new_state, unprocessed, processed):    Function
`_process_new_state` utility or script function.
L553: def _process_state(cls, unprocessed, processed, state):    Function `_process_state`
utility or script function.
L596: def process_tokendef(cls, name, tokendefs=None):    Function `process_tokendef` utility
or script function.
L604: def get_tokendefs(cls):    Function `get_tokendefs` Returns or fetches data.
L653: def __call__(cls, *args, **kwds):    Function `__call__` utility or script function.
L667: class RegexLexer(Lexer, metaclass=RegexLexerMeta):    Class (`RegexLexer`) component
used by the app (see file context: None).
L702: def get_tokens_unprocessed(self, text, stack=('root',)):    Function
`get_tokens_unprocessed` Returns or fetches data.
L764: class LexerContext:    Class (`LexerContext`) component used by the app (see file
context: None).
L769: def __init__(self, text, pos, stack=None, end=None):    Function `__init__` utility or
script function.
L775: def __repr__(self):    Function `__repr__` utility or script function.
L779: class ExtendedRegexLexer(RegexLexer):    Class (`ExtendedRegexLexer`) component used by
the app (see file context: None).
L784: def get_tokens_unprocessed(self, text=None, context=None):    Function
`get_tokens_unprocessed` Returns or fetches data.
L851: def do_insertions(insertions, tokens):    Function `do_insertions` utility or script
function.
L915: class ProfilingRegexLexerMeta(RegexLexerMeta):    Class (`ProfilingRegexLexerMeta`)
component used by the app (see file context: None).
L918: def _process_regex(cls, regex, rflags, state):    Function `_process_regex` utility or
script function.
L926: def match_func(text, pos, endpos=sys.maxsize):    Function `match_func` utility or
script function.
L937: class ProfilingRegexLexer(RegexLexer, metaclass=ProfilingRegexLexerMeta):    Class
(`ProfilingRegexLexer`) component used by the app (see file context: None).
L943: def get_tokens_unprocessed(self, text, stack=('root',)):    Function
`get_tokens_unprocessed` Returns or fetches data.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/reg
exopt.py**

```

L22: def make_charset(letters):    Function `make_charset` utility or script function.
L26: def regex_opt_inner(strings, open_paren):    Function `regex_opt_inner` utility or
script function.
L82: def regex_opt(strings, prefix='', suffix=''):    Function `regex_opt` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/token.py

```

L12: class _TokenType(tuple):    Class (`_TokenType`) component used by the app (see file
context: None).
L15: def split(self):    Function `split` utility or script function.
L24: def __init__(self, *args):    Function `__init__` utility or script function.
L28: def __contains__(self, val):    Function `__contains__` utility or script function.
L34: def __getattr__(self, val):    Function `__getattr__` utility or script function.
L43: def __repr__(self):    Function `__repr__` utility or script function.
L46: def __copy__(self):    Function `__copy__` utility or script function.
L50: def __deepcopy__(self, memo):    Function `__deepcopy__` utility or script function.
L85: def is_token_subtype(ttype, other):    Function `is_token_subtype` utility or script
function.
L94: def string_to_tokentype(s):    Function `string_to_tokentype` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/modelfile.py

```

L22: def get_filetype_from_line(l): # noqa: E741    Function `get_filetype_from_line` Returns
or fetches data.
L28: def get_filetype_from_buffer(buf, max_lines=5):    Function `get_filetype_from_buffer`
Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/sphinxext.py

```

L60: class PygmentsDoc(Directive):    Class (`PygmentsDoc`) component used by the app (see
file context: None).
L71: def run(self):    Function `run` utility or script function.
L90: def document_lexers_overview(self):    Function `document_lexers_overview` utility or
script function.
L101: def format_link(name, url):    Function `format_link` utility or script function.
L121: def write_row(*columns):    Function `write_row` utility or script function.
L132: def write_seperator():    Function `write_seperator` utility or script function.
L150: def document_lexers(self):    Function `document_lexers` utility or script function.
L215: def document_formatters(self):    Function `document_formatters` utility or script
function.

```

```
L233: def document_filters(self):    Function `document_filters` utility or script function.
L246: def setup(app):    Function `setup` Sets or updates a value.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/__init__.py

```
L35: def lex(code, lexer):    Function `lex` utility or script function.
L52: def format(tokens, formatter, outfile=None):    # pylint: disable=redefined-builtin
Function `format` utility or script function.
L77: def highlight(code, lexer, formatter, outfile=None):    Function `highlight` utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/unistring.py

```
L82: def combine(*args):    Function `combine` utility or script function.
L86: def allexcept(*args):    Function `allexcept` utility or script function.
L93: def _handle_runs(char_list):    # pragma: no cover    Function `_handle_runs` utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/style.py

```
L58: class StyleMeta(type):    Class (`StyleMeta`) component used by the app (see file
context: None).
L60: def __new__(mcs, name, bases, dct):    Function `__new__` utility or script function.
L66: def colorformat(text):    Function `colorformat` utility or script function.
L126: def style_for_token(cls, token):    Function `style_for_token` utility or script
function.
L156: def list_styles(cls):    Function `list_styles` utility or script function.
L159: def styles_token(cls, ttype):    Function `styles_token` utility or script function.
L162: def __iter__(cls):    Function `__iter__` utility or script function.
L166: def __len__(cls):    Function `__len__` utility or script function.
L170: class Style(metaclass=StyleMeta):    Class (`Style`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filter.py

```

L12: def apply_filters(stream, filters, lexer=None):    Function `apply_filters` utility or
script function.
L18: def _apply(filter_, stream):    Function `_apply` utility or script function.
L25: def simplefilter(f):    Function `simplefilter` utility or script function.
L30: def lowercase(self, lexer, stream, options):    Function `lowercase` utility or script
function.
L41: class Filter:    Class (`Filter`) component used by the app (see file context: None).
L47: def __init__(self, **options):    Function `__init__` utility or script function.
L50: def filter(self, lexer, stream):    Function `filter` utility or script function.
L54: class FunctionFilter(Filter):    Class (`FunctionFilter`) component used by the app (see
file context: None).
L63: def __init__(self, **options):    Function `__init__` utility or script function.
L68: def filter(self, lexer, stream):    Function `filter` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/scanner.py

```

L20: class EndOfText(RuntimeError):    Class (`EndOfText`) component used by the app (see
file context: None).
L27: class Scanner:    Class (`Scanner`) component used by the app (see file context: None).
L35: def __init__(self, text, flags=0):    Function `__init__` utility or script function.
L49: def eos(self):    Function `eos` utility or script function.
L54: def check(self, pattern):    Function `check` utility or script function.
L66: def test(self, pattern):    Function `test` utility or script function.
L72: def scan(self, pattern):    Function `scan` utility or script function.
L95: def get_char(self):    Function `get_char` Returns or fetches data.
L99: def __repr__(self):    Function `__repr__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/util.py

```

L30: class ClassNotFound(ValueError):    Class (`ClassNotFound`) component used by the app
(see file context: None).
L34: class OptionError(Exception):    Class (`OptionError`) component used by the app (see
file context: None).
L40: def get_choice_opt(options, optname, allowed, default=None, normcase=False):    Function

```



```

`get_choice_opt` Returns or fetches data.
L53: def get_bool_opt(options, optname, default=None):    Function `get_bool_opt` Returns or
fetches data.
L82: def get_int_opt(options, optname, default=None):    Function `get_int_opt` Returns or
fetches data.
L94: def get_list_opt(options, optname, default=None):    Function `get_list_opt` Returns or
fetches data.
L110: def docstring_headline(obj):    Function `docstring_headline` utility or script
function.
L122: def make_analysator(f):    Function `make_analysator` utility or script function.
L124: def text_analyse(text):    Function `text_analyse` utility or script function.
L139: def shebang_matches(text, regex):    Function `shebang_matches` utility or script
function.
L184: def doctype_matches(text, regex):    Function `doctype_matches` utility or script
function.
L197: def html_doctype_matches(text):    Function `html_doctype_matches` utility or script
function.
L205: def looks_like_xml(text):    Function `looks_like_xml` utility or script function.
L221: def surrogatepair(c):    Function `surrogatepair` utility or script function.
L230: def format_lines(var_name, seq, raw=False, indent_level=0):    Function `format_lines`
utility or script function.
L249: def duplicates_removed(it, already_seen=()):    Function `duplicates_removed` utility
or script function.
L265: class Future:    Class (`Future`) component used by the app (see file context: None).
L271: def get(self):    Function `get` Returns or fetches data.
L275: def guess_decode(text):    Function `guess_decode` utility or script function.
L296: def guess_decode_from_terminal(text, term):    Function `guess_decode_from_terminal`
utility or script function.
L313: def terminal_encoding(term):    Function `terminal_encoding` utility or script
function.
L321: class UnclosingTextIOWrapper(TextIOWrapper):    Class (`UnclosingTextIOWrapper`)
component used by the app (see file context: None).
L323: def close(self):    Function `close` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatter.py

```

L19: def _lookup_style(style):    Function `_lookup_style` utility or script function.
L25: class Formatter:    Class (`Formatter`) component used by the app (see file context:
None).
L83: def __init__(self, **options):    Function `__init__` utility or script function.
L99: def get_style_defs(self, arg=''):    Function `get_style_defs` Returns or fetches data.
L114: def format(self, tokensource, outfile):    Function `format` utility or script
function.
L128: def __class_getitem__(cls, name):    Function `__class_getitem__` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/plu
gin.py**

```

L43: def iter_entry_points(group_name):    Function `iter_entry_points` utility or script
function.
L55: def find_plugin_lexers():    Function `find_plugin_lexers` utility or script function.
L60: def find_plugin_formatters():    Function `find_plugin_formatters` utility or script
function.
L65: def find_plugin_styles():    Function `find_plugin_styles` utility or script function.
L70: def find_plugin_filters():    Function `find_plugin_filters` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filte
rs/__init__.py**

```

L22: def find_filter_class(filtername):    Function `find_filter_class` utility or script
function.
L32: def get_filter_by_name(filtername, **options):    Function `get_filter_by_name` Returns
or fetches data.
L45: def get_all_filters():    Function `get_all_filters` Returns or fetches data.
L52: def _replace_special(ttype, value, regex, specialttype,    Function `_replace_special`
utility or script function.
L65: class CodeTagFilter(Filter):    Class (`CodeTagFilter`) component used by the app (see
file context: None).
L78: def __init__(self, **options):    Function `__init__` utility or script function.
L86: def filter(self, lexer, stream):    Function `filter` utility or script function.
L97: class SymbolFilter(Filter):    Class (`SymbolFilter`) component used by the app (see
file context: None).
L673: def __init__(self, **options):    Function `__init__` utility or script function.
L679: def filter(self, lexer, stream):    Function `filter` utility or script function.
L687: class KeywordCaseFilter(Filter):    Class (`KeywordCaseFilter`) component used by the
app (see file context: None).
L701: def __init__(self, **options):    Function `__init__` utility or script function.
L707: def filter(self, lexer, stream):    Function `filter` utility or script function.
L715: class NameHighlightFilter(Filter):    Class (`NameHighlightFilter`) component used by
the app (see file context: None).
L739: def __init__(self, **options):    Function `__init__` utility or script function.
L748: def filter(self, lexer, stream):    Function `filter` utility or script function.
L756: class ErrorToken(Exception):    Class (`ErrorToken`) component used by the app (see
file context: None).
L760: class RaiseOnErrorTokenFilter(Filter):    Class (`RaiseOnErrorTokenFilter`) component
used by the app (see file context: None).
L772: def __init__(self, **options):    Function `__init__` utility or script function.
L782: def filter(self, lexer, stream):    Function `filter` utility or script function.

```

```

L789: class VisibleWhitespaceFilter(Filter):  Class (`VisibleWhitespaceFilter`) component
used by the app (see file context: None).
L819: def __init__(self, **options):  Function `__init__` utility or script function.
L836: def filter(self, lexer, stream):  Function `filter` utility or script function.
L843: def replacefunc(wschar):  Function `replacefunc` utility or script function.
L868: class GobbleFilter(Filter):  Class (`GobbleFilter`) component used by the app (see
file context: None).
L882: def __init__(self, **options):  Function `__init__` utility or script function.
L886: def gobble(self, value, left):  Function `gobble` utility or script function.
L892: def filter(self, lexer, stream):  Function `filter` utility or script function.
L907: class TokenMergeFilter(Filter):  Class (`TokenMergeFilter`) component used by the app
(see file context: None).
L913: def __init__(self, **options):  Function `__init__` utility or script function.
L916: def filter(self, lexer, stream):  Function `filter` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/python.py

```

L25: class PythonLexer(RegexLexer):  Class (`PythonLexer`) component used by the app (see
file context: None).
L65: def innerstring_rules(ttype):  Function `innerstring_rules` utility or script
function.
L85: def fstring_rules(ttype):  Function `fstring_rules` utility or script function.
L408: def analyse_text(text):  Function `analyse_text` utility or script function.
L416: class Python2Lexer(RegexLexer):  Class (`Python2Lexer`) component used by the app
(see file context: None).
L433: def innerstring_rules(ttype):  Function `innerstring_rules` utility or script
function.
L635: def analyse_text(text):  Function `analyse_text` utility or script function.
L639: class _PythonConsoleLexerBase(RegexLexer):  Class (`_PythonConsoleLexerBase`)
component used by the app (see file context: None).
L676: class PythonConsoleLexer(DelegatingLexer):  Class (`PythonConsoleLexer`) component
used by the app (see file context: None).
L706: def __init__(self, **options):  Function `__init__` utility or script function.
L719: class _ReplaceInnerCode(DelegatingLexer):  Class (`_ReplaceInnerCode`) component used
by the app (see file context: None).
L720: def __init__(self, **options):  Function `__init__` utility or script function.
L725: class PythonTracebackLexer(RegexLexer):  Class (`PythonTracebackLexer`) component
used by the app (see file context: None).
L782: class Python2TracebackLexer(RegexLexer):  Class (`Python2TracebackLexer`) component
used by the app (see file context: None).
L830: class CythonLexer(RegexLexer):  Class (`CythonLexer`) component used by the app (see
file context: None).
L1009: class DgLexer(RegexLexer):  Class (`DgLexer`) component used by the app (see file
context: None).
L1108: class NumPyLexer(PythonLexer):  Class (`NumPyLexer`) component used by the app (see

```

```

file context: None).
L1189: def get_tokens_unprocessed(self, text):    Function `get_tokens_unprocessed` Returns
or fetches data.
L1197: def analyse_text(text):    Function `analyse_text` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/_init__.py

```

L35: def _fn_matches(fn, glob):    Function `_fn_matches` utility or script function.
L43: def _load_lexers(module_name):    Function `_load_lexers` utility or script function.
L51: def get_all_lexers(plugins=True):    Function `get_all_lexers` Returns or fetches data.
L65: def find_lexer_class(name):    Function `find_lexer_class` utility or script function.
L83: def find_lexer_class_by_name(_alias):    Function `find_lexer_class_by_name` utility or
script function.
L110: def get_lexer_by_name(_alias, **options):    Function `get_lexer_by_name` Returns or
fetches data.
L135: def load_lexer_from_file(filename, lexername="CustomLexer", **options):    Function
`load_lexer_from_file` Loads data from storage or remote.
L169: def find_lexer_class_for_filename(_fn, code=None):    Function
`find_lexer_class_for_filename` utility or script function.
L194: def get_rating(info):    Function `get_rating` Returns or fetches data.
L212: def get_lexer_for_filename(_fn, code=None, **options):    Function
`get_lexer_for_filename` Returns or fetches data.
L231: def get_lexer_for_mimetype(_mime, **options):    Function `get_lexer_for_mimetype`
Returns or fetches data.
L250: def _iter_lexerclasses(plugins=True):    Function `_iter_lexerclasses` utility or
script function.
L261: def guess_lexer_for_filename(_fn, _text, **options):    Function
`guess_lexer_for_filename` utility or script function.
L292: def type_sort(t):    Function `type_sort` utility or script function.
L304: def guess_lexer(_text, **options):    Function `guess_lexer` utility or script
function.
L308: class is called with the text as argument, and the lexer which returned the    Class
(`is`) component used by the app (see file context: None).
L343: class _automodule(types.ModuleType):    Class (`_automodule`) component used by the app
(see file context: None).
L346: def __getattr__(self, name):    Function `__getattr__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/styles/_init__.py

```

L24: def get_style_by_name(name):    Function `get_style_by_name` Returns or fetches data.

```

```
L56: def get_all_styles():    Function `get_all_styles` Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatters/__init__.py

```
L28: def _fn_matches(fn, glob):    Function `_fn_matches` utility or script function.
L36: def _load_formatters(module_name):    Function `_load_formatters` utility or script
function.
L44: def get_all_formatters():    Function `get_all_formatters` Returns or fetches data.
L55: def find_formatter_class(alias):    Function `find_formatter_class` utility or script
function.
L70: def get_formatter_by_name(_alias, **options):    Function `get_formatter_by_name`
Returns or fetches data.
L84: def load_formatter_from_file(filename, formattername="CustomFormatter", **options):
Function `load_formatter_from_file` Loads data from storage or remote.
L118: def get_formatter_for_filename(fn, **options):    Function `get_formatter_for_filename`
Returns or fetches data.
L140: class _automodule(types.ModuleType):    Class (`_automodule`) component used by the app
(see file context: None).
L143: def __getattr__(self, name):    Function `__getattr__` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distro/distro.py

```
L61: class VersionDict(TypedDict):    Class (`VersionDict`) component used by the app (see
file context: None).
L67: class InfoDict(TypedDict):    Class (`InfoDict`) component used by the app (see file
context: None).
L160: def linux_distribution(full_distribution_name: bool = True) -> Tuple[str, str, str]:
Function `linux_distribution` utility or script function.
L203: def id() -> str:    Function `id` utility or script function.
L287: def name(pretty: bool = False) -> str:    Function `name` utility or script function.
L326: def version(pretty: bool = False, best: bool = False) -> str:    Function `version`
utility or script function.
L374: def version_parts(best: bool = False) -> Tuple[str, str, str]:    Function
`version_parts` utility or script function.
L391: def major_version(best: bool = False) -> str:    Function `major_version` utility or
script function.
L404: def minor_version(best: bool = False) -> str:    Function `minor_version` utility or
script function.
L417: def build_number(best: bool = False) -> str:    Function `build_number` Constructs or
prepares an object.
```

```

L430: def like() -> str:    Function `like`    utility or script function.
L447: def codename() -> str:    Function `codename`    utility or script function.
L471: def info(pretty: bool = False, best: bool = False) -> InfoDict:    Function `info`
utility or script function.
L515: def os_release_info() -> Dict[str, str]:    Function `os_release_info`    utility or
script function.
L525: def lsb_release_info() -> Dict[str, str]:    Function `lsb_release_info`    utility or
script function.
L536: def distro_release_info() -> Dict[str, str]:    Function `distro_release_info`    utility
or script function.
L546: def uname_info() -> Dict[str, str]:    Function `uname_info`    utility or script
function.
L554: def os_release_attr(attribute: str) -> str:    Function `os_release_attr`    utility or
script function.
L573: def lsb_release_attr(attribute: str) -> str:    Function `lsb_release_attr`    utility or
script function.
L593: def distro_release_attr(attribute: str) -> str:    Function `distro_release_attr`
utility or script function.
L612: def uname_attr(attribute: str) -> str:    Function `uname_attr`    utility or script
function.
L633: class cached_property:    # type: ignore    Class (`cached_property`)    component used by
the app (see file context: None).
L639: def __init__(self, f: Callable[[Any], Any]) -> None:    Function `__init__`    utility or
script function.
L643: def __get__(self, obj: Any, owner: Type[Any]) -> Any:    Function `__get__`    utility or
script function.
L649: class LinuxDistribution:    Class (`LinuxDistribution`)    component used by the app (see
file context: None).
L667: def __init__(    Function `__init__`    utility or script function.
L800: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L817: def linux_distribution(    Function `linux_distribution`    utility or script function.
L833: def id(self) -> str:    Function `id`    utility or script function.
L839: def normalize(distro_id: str, table: Dict[str, str]) -> str:    Function `normalize`
utility or script function.
L861: def name(self, pretty: bool = False) -> str:    Function `name`    utility or script
function.
L884: def version(self, pretty: bool = False, best: bool = False) -> str:    Function
`version`    utility or script function.
L926: def version_parts(self, best: bool = False) -> Tuple[str, str, str]:    Function
`version_parts`    utility or script function.
L942: def major_version(self, best: bool = False) -> str:    Function `major_version`    utility
or script function.
L950: def minor_version(self, best: bool = False) -> str:    Function `minor_version`    utility
or script function.
L958: def build_number(self, best: bool = False) -> str:    Function `build_number`
Constructs or prepares an object.
L966: def like(self) -> str:    Function `like`    utility or script function.
L974: def codename(self) -> str:    Function `codename`    utility or script function.
L991: def info(self, pretty: bool = False, best: bool = False) -> InfoDict:    Function `info`
utility or script function.
L1010: def os_release_info(self) -> Dict[str, str]:    Function `os_release_info`    utility or

```

```

script function.
L1019: def lsb_release_info(self) -> Dict[str, str]:    Function `lsb_release_info` utility
or script function.
L1029: def distro_release_info(self) -> Dict[str, str]:    Function `distro_release_info`
utility or script function.
L1039: def uname_info(self) -> Dict[str, str]:    Function `uname_info` utility or script
function.
L1048: def oslevel_info(self) -> str:    Function `oslevel_info` utility or script function.
L1054: def os_release_attr(self, attribute: str) -> str:    Function `os_release_attr`
utility or script function.
L1063: def lsb_release_attr(self, attribute: str) -> str:    Function `lsb_release_attr`
utility or script function.
L1072: def distro_release_attr(self, attribute: str) -> str:    Function `distro_release_attr`
utility or script function.
L1081: def uname_attr(self, attribute: str) -> str:    Function `uname_attr` utility or
script function.
L1091: def _os_release_info(self) -> Dict[str, str]:    Function `_os_release_info` utility
or script function.
L1104: def _parse_os_release_content(lines: TextIO) -> Dict[str, str]:    Function
`_parse_os_release_content` utility or script function.
L1154: def _lsb_release_info(self) -> Dict[str, str]:    Function `_lsb_release_info` utility
or script function.
L1173: def _parse_lsb_release_content(lines: Iterable[str]) -> Dict[str, str]:    Function
`_parse_lsb_release_content` utility or script function.
L1197: def _uname_info(self) -> Dict[str, str]:    Function `_uname_info` utility or script
function.
L1209: def _oslevel_info(self) -> str:    Function `_oslevel_info` utility or script
function.
L1219: def _debian_version(self) -> str:    Function `_debian_version` utility or script
function.
L1229: def _parse_uname_content(lines: Sequence[str]) -> Dict[str, str]:    Function
`_parse_uname_content` utility or script function.
L1248: def _to_str(bytestring: bytes) -> str:    Function `_to_str` utility or script
function.
L1253: def _distro_release_info(self) -> Dict[str, str]:    Function `_distro_release_info`
utility or script function.
L1311: def _parse_distro_release_file(self, filepath: str) -> Dict[str, str]:    Function
`_parse_distro_release_file` utility or script function.
L1334: def _parse_distro_release_content(line: str) -> Dict[str, str]:    Function
`_parse_distro_release_content` utility or script function.
L1362: def main() -> None:    Function `main` Entry point / main routine.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/com
pat.py**

```

L29: def _resolve_char_detection():    Function `_resolve_char_detection` utility or script

```

```
function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/hook
s.py**

```
L16: def default_hooks():    Function `default_hooks`    utility or script function.
L23: def dispatch_hook(key, hooks, hook_data, **kwargs):    Function `dispatch_hook`    utility
or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/mod
els.py**

```
L86: class RequestEncodingMixin:    Class (`RequestEncodingMixin`)    component used by the app
(see file context: None).
L88: def path_url(self):    Function `path_url`    utility or script function.
L109: def _encode_params(data):    Function `_encode_params`    utility or script function.
L139: def _encode_files(files, data):    Function `_encode_files`    utility or script function.
L208: class RequestHooksMixin:    Class (`RequestHooksMixin`)    component used by the app (see
file context: None).
L209: def register_hook(self, event, hook):    Function `register_hook`    utility or script
function.
L220: def deregister_hook(self, event, hook):    Function `deregister_hook`    utility or script
function.
L232: class Request(RequestHooksMixin):    Class (`Request`)    component used by the app (see
file context: None).
L260: def __init__(    Function `__init__`    utility or script function.
L294: def __repr__(self):    Function `__repr__`    utility or script function.
L297: def prepare(self):    Function `prepare`    utility or script function.
L315: class PreparedRequest(RequestEncodingMixin, RequestHooksMixin):    Class
(`PreparedRequest`)    component used by the app (see file context: None).
L336: def __init__(self):    Function `__init__`    utility or script function.
L353: def prepare(    Function `prepare`    utility or script function.
L381: def __repr__(self):    Function `__repr__`    utility or script function.
L384: def copy(self):    Function `copy`    utility or script function.
L395: def prepare_method(self, method):    Function `prepare_method`    utility or script
function.
L402: def _get_idna_encoded_host(host):    Function `_get_idna_encoded_host`    utility or
script function.
L411: def prepare_url(self, url, params):    Function `prepare_url`    utility or script
function.
L485: def prepare_headers(self, headers):    Function `prepare_headers`    utility or script
function.
```



```

L496: def prepare_body(self, data, files, json=None):    Function `prepare_body` utility or
script function.
L574: def prepare_content_length(self, body):    Function `prepare_content_length` utility or
script function.
L590: def prepare_auth(self, auth, url=""):    Function `prepare_auth` utility or script
function.
L612: def prepare_cookies(self, cookies):    Function `prepare_cookies` utility or script
function.
L632: def prepare_hooks(self, hooks):    Function `prepare_hooks` utility or script function.
L642: class Response:    Class (`Response`) component used by the app (see file context:
None).
L660: def __init__(self):    Function `__init__` utility or script function.
L707: def __enter__(self):    Function `__enter__` utility or script function.
L710: def __exit__(self, *args):    Function `__exit__` utility or script function.
L713: def __getstate__(self):    Function `__getstate__` utility or script function.
L721: def __setstate__(self, state):    Function `__setstate__` utility or script function.
L729: def __repr__(self):    Function `__repr__` utility or script function.
L732: def __bool__(self):    Function `__bool__` utility or script function.
L742: def __nonzero__(self):    Function `__nonzero__` utility or script function.
L752: def __iter__(self):    Function `__iter__` utility or script function.
L757: def ok(self):    Function `ok` utility or script function.
L772: def is_redirect(self):    Function `is_redirect` utility or script function.
L779: def is_permanent_redirect(self):    Function `is_permanent_redirect` utility or script
function.
L787: def next(self):    Function `next` utility or script function.
L792: def apparent_encoding(self):    Function `apparent_encoding` utility or script
function.
L801: def iter_content(self, chunk_size=1, decode_unicode=False):    Function `iter_content`
utility or script function.
L818: def generate():    Function `generate` Generates content (often AI-generated).
L859: def iter_lines(    Function `iter_lines` utility or script function.
L893: def content(self):    Function `content` utility or script function.
L912: def text(self):    Function `text` utility or script function.
L949: def json(self, **kwargs):    Function `json` utility or script function.
L985: def links(self):    Function `links` utility or script function.
L1001: def raise_for_status(self):    Function `raise_for_status` utility or script function.
L1030: def close(self):    Function `close` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/help.py

```

L27: def _implementation():    Function `_implementation` utility or script function.
L59: def info():    Function `info` utility or script function.
L118: def main():    Function `main` Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/api.py

```

L14: def request(method, url, **kwargs):    Function `request` utility or script function.
L62: def get(url, params=None, **kwargs):    Function `get` Returns or fetches data.
L76: def options(url, **kwargs):    Function `options` utility or script function.
L88: def head(url, **kwargs):    Function `head` utility or script function.
L103: def post(url, data=None, json=None, **kwargs):    Function `post` utility or script
function.
L118: def put(url, data=None, **kwargs):    Function `put` utility or script function.
L133: def patch(url, data=None, **kwargs):    Function `patch` utility or script function.
L148: def delete(url, **kwargs):    Function `delete` Deletes a resource.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/exceptions.py

```

L13: class RequestException(IOError):    Class (`RequestException`) component used by the app
(see file context: None).
L18: def __init__(self, *args, **kwargs):    Function `__init__` utility or script function.
L28: class InvalidJSONError(RequestException):    Class (`InvalidJSONError`) component used
by the app (see file context: None).
L32: class JSONDecodeError(InvalidJSONError, CompatJSONDecodeError):    Class
(`JSONDecodeError`) component used by the app (see file context: None).
L35: def __init__(self, *args, **kwargs):    Function `__init__` utility or script function.
L45: def __reduce__(self):    Function `__reduce__` utility or script function.
L56: class HTTPError(RequestException):    Class (`HTTPError`) component used by the app (see
file context: None).
L60: class ConnectionError(RequestException):    Class (`ConnectionError`) component used by
the app (see file context: None).
L64: class ProxyError(ConnectionError):    Class (`ProxyError`) component used by the app
(see file context: None).
L68: class SSLError(ConnectionError):    Class (`SSLError`) component used by the app (see
file context: None).
L72: class Timeout(RequestException):    Class (`Timeout`) component used by the app (see
file context: None).
L81: class ConnectTimeout(ConnectionError, Timeout):    Class (`ConnectTimeout`) component
used by the app (see file context: None).
L88: class ReadTimeout(Timeout):    Class (`ReadTimeout`) component used by the app (see file
context: None).
L92: class URLRequired(RequestException):    Class (`URLRequired`) component used by the app
(see file context: None).
L96: class TooManyRedirects(RequestException):    Class (`TooManyRedirects`) component used
by the app (see file context: None).

```

```

L100: class MissingSchema(RequestException, ValueError):    Class (`MissingSchema`) component
used by the app (see file context: None).
L104: class InvalidSchema(RequestException, ValueError):    Class (`InvalidSchema`) component
used by the app (see file context: None).
L108: class InvalidURL(RequestException, ValueError):    Class (`InvalidURL`) component used
by the app (see file context: None).
L112: class InvalidHeader(RequestException, ValueError):    Class (`InvalidHeader`) component
used by the app (see file context: None).
L116: class InvalidProxyURL(InvalidURL):    Class (`InvalidProxyURL`) component used by the
app (see file context: None).
L120: class ChunkedEncodingError(RequestException):    Class (`ChunkedEncodingError`)
component used by the app (see file context: None).
L124: class ContentDecodingError(RequestException, BaseHTTPError):    Class
(`ContentDecodingError`) component used by the app (see file context: None).
L128: class StreamConsumedError(RequestException, TypeError):    Class (`StreamConsumedError`)
component used by the app (see file context: None).
L132: class RetryError(RequestException):    Class (`RetryError`) component used by the app
(see file context: None).
L136: class UnrewindableBodyError(RequestException):    Class (`UnrewindableBodyError`)
component used by the app (see file context: None).
L143: class RequestsWarning(Warning):    Class (`RequestsWarning`) component used by the app
(see file context: None).
L147: class FileModeWarning(RequestsWarning, DeprecationWarning):    Class (`FileModeWarning`)
component used by the app (see file context: None).
L151: class RequestsDependencyWarning(RequestsWarning):    Class (`RequestsDependencyWarning`)
component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/__init__.py

```

L51: def check_compatibility(urllib3_version, chardet_version, charset_normalizer_version):
Function `check_compatibility` utility or script function.
L83: def _check_cryptography(cryptography_version):    Function `_check_cryptography` utility
or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/sessions.py

```

L62: def merge_setting(request_setting, session_setting, dict_class=OrderedDict):    Function
`merge_setting` utility or script function.
L92: def merge_hooks(request_hooks, session_hooks, dict_class=OrderedDict):    Function
`merge_hooks` utility or script function.

```

```

L107: class SessionRedirectMixin:  Class (`SessionRedirectMixin`) component used by the app
(see file context: None).
L108: def get_redirect_target(self, resp):  Function `get_redirect_target` Returns or
fetches data.
L128: def should_strip_auth(self, old_url, new_url):  Function `should_strip_auth` utility
or script function.
L160: def resolve_redirects(  Function `resolve_redirects` utility or script function.
L283: def rebuild_auth(self, prepared_request, response):  Function `rebuild_auth` utility
or script function.
L303: def rebuild_proxies(self, prepared_request, proxies):  Function `rebuild_proxies`
utility or script function.
L334: def rebuild_method(self, prepared_request, response):  Function `rebuild_method`
utility or script function.
L357: class Session(SessionRedirectMixin):  Class (`Session`) component used by the app
(see file context: None).
L391: def __init__(self):  Function `__init__` utility or script function.
L454: def __enter__(self):  Function `__enter__` utility or script function.
L457: def __exit__(self, *args):  Function `__exit__` utility or script function.
L460: def prepare_request(self, request):  Function `prepare_request` utility or script
function.
L503: def request(  Function `request` utility or script function.
L596: def get(self, url, **kwargs):  Function `get` Returns or fetches data.
L607: def options(self, url, **kwargs):  Function `options` utility or script function.
L618: def head(self, url, **kwargs):  Function `head` utility or script function.
L629: def post(self, url, data=None, json=None, **kwargs):  Function `post` utility or
script function.
L642: def put(self, url, data=None, **kwargs):  Function `put` utility or script function.
L654: def patch(self, url, data=None, **kwargs):  Function `patch` utility or script
function.
L666: def delete(self, url, **kwargs):  Function `delete` Deletes a resource.
L676: def send(self, request, **kwargs):  Function `send` utility or script function.
L753: def merge_environment_settings(self, url, proxies, stream, verify, cert):  Function
`merge_environment_settings` utility or script function.
L784: def get_adapter(self, url):  Function `get_adapter` Returns or fetches data.
L797: def close(self):  Function `close` utility or script function.
L802: def mount(self, prefix, adapter):  Function `mount` utility or script function.
L813: def __getstate__(self):  Function `__getstate__` utility or script function.
L817: def __setstate__(self, state):  Function `__setstate__` utility or script function.
L822: def session():  Function `session` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/utls.py

```

L76: def proxy_bypass_registry(host):  Function `proxy_bypass_registry` utility or script
function.
L114: def proxy_bypass(host):  # noqa  Function `proxy_bypass` utility or script function.

```

```

L126: def dict_to_sequence(d):    Function `dict_to_sequence` utility or script function.
L135: def super_len(o):    Function `super_len` utility or script function.
L206: def get_netrc_auth(url, raise_errors=False):    Function `get_netrc_auth` Returns or
fetches data.
L250: def guess_filename(obj):    Function `guess_filename` utility or script function.
L257: def extract_zipped_paths(path):    Function `extract_zipped_paths` utility or script
function.
L296: def atomic_open(filename):    Function `atomic_open` utility or script function.
L308: def from_key_val_list(value):    Function `from_key_val_list` utility or script
function.
L335: def to_key_val_list(value):    Function `to_key_val_list` utility or script function.
L365: def parse_list_header(value):    Function `parse_list_header` utility or script
function.
L397: def parse_dict_header(value):    Function `parse_dict_header` utility or script
function.
L432: def unquote_header_value(value, is_filename=False):    Function `unquote_header_value`
utility or script function.
L457: def dict_from_cookiejar(cj):    Function `dict_from_cookiejar` utility or script
function.
L468: def add_dict_to_cookiejar(cj, cookie_dict):    Function `add_dict_to_cookiejar` utility
or script function.
L479: def get_encodings_from_content(content):    Function `get_encodings_from_content`
Returns or fetches data.
L504: def _parse_content_type_header(header):    Function `_parse_content_type_header`
utility or script function.
L526: def get_encoding_from_headers(headers):    Function `get_encoding_from_headers` Returns
or fetches data.
L551: def stream_decode_response_unicode(iterator, r):    Function
`stream_decode_response_unicode` utility or script function.
L568: def iter_slices(string, slice_length):    Function `iter_slices` utility or script
function.
L578: def get_unicode_from_response(r):    Function `get_unicode_from_response` Returns or
fetches data.
L623: def unquote_unreserved(uri):    Function `unquote_unreserved` utility or script
function.
L647: def requote_uri(uri):    Function `requote_uri` utility or script function.
L669: def address_in_network(ip, net):    Function `address_in_network` utility or script
function.
L684: def dotted_netmask(mask):    Function `dotted_netmask` utility or script function.
L695: def is_ipv4_address(string_ip):    Function `is_ipv4_address` utility or script
function.
L706: def is_valid_cidr(string_network):    Function `is_valid_cidr` utility or script
function.
L731: def set_environ(env_name, value):    Function `set_environ` Sets or updates a value.
L752: def should_bypass_proxies(url, no_proxy):    Function `should_bypass_proxies` utility
or script function.
L761: def get_proxy(key):    Function `get_proxy` Returns or fetches data.
L813: def get_environ_proxies(url, no_proxy=None):    Function `get_environ_proxies` Returns
or fetches data.
L825: def select_proxy(url, proxies):    Function `select_proxy` utility or script function.
L851: def resolve_proxies(request, proxies, trust_env=True):    Function `resolve_proxies`

```

```

utility or script function.
L878: def default_user_agent(name="python-requests"):  Function `default_user_agent`
utility or script function.
L887: def default_headers():  Function `default_headers`  utility or script function.
L901: def parse_header_links(value):  Function `parse_header_links`  utility or script
function.
L944: def guess_json_utf(data):  Function `guess_json_utf`  utility or script function.
L976: def prepend_scheme_if_needed(url, new_scheme):  Function `prepend_scheme_if_needed`
utility or script function.
L1005: def get_auth_from_url(url):  Function `get_auth_from_url`  Returns or fetches data.
L1021: def check_header_validity(header):  Function `check_header_validity`  utility or
script function.
L1032: def _validate_header_part(header, header_part, header_validator_index):  Function
`_validate_header_part`  utility or script function.
L1051: def urldefragauth(url):  Function `urldefragauth`  utility or script function.
L1068: def rewind_body(prepared_request):  Function `rewind_body`  utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/_internal_utils.py

```

L26: def to_native_string(string, encoding="ascii"):  Function `to_native_string`  utility
or script function.
L39: def unicode_is_ascii(u_string):  Function `unicode_is_ascii`  utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/cookies.py

```

L23: class MockRequest:  Class (`MockRequest`)  component used by the app (see file context:
None).
L35: def __init__(self, request):  Function `__init__`  utility or script function.
L40: def get_type(self):  Function `get_type`  Returns or fetches data.
L43: def get_host(self):  Function `get_host`  Returns or fetches data.
L46: def get_origin_req_host(self):  Function `get_origin_req_host`  Returns or fetches
data.
L49: def get_full_url(self):  Function `get_full_url`  Returns or fetches data.
L69: def is_unverifiable(self):  Function `is_unverifiable`  utility or script function.
L72: def has_header(self, name):  Function `has_header`  utility or script function.
L75: def get_header(self, name, default=None):  Function `get_header`  Returns or fetches
data.
L78: def add_header(self, key, val):  Function `add_header`  utility or script function.

```

```

L84: def add_unredirected_header(self, name, value):  Function `add_unredirected_header`
utility or script function.
L87: def get_new_headers(self):  Function `get_new_headers`  Returns or fetches data.
L91: def unverifiable(self):  Function `unverifiable`  utility or script function.
L95: def origin_req_host(self):  Function `origin_req_host`  utility or script function.
L99: def host(self):  Function `host`  utility or script function.
L103: class MockResponse:  Class (`MockResponse`)  component used by the app (see file
context: None).
L110: def __init__(self, headers):  Function `__init__`  utility or script function.
L117: def info(self):  Function `info`  utility or script function.
L120: def getheaders(self, name):  Function `getheaders`  Returns or fetches data.
L124: def extract_cookies_to_jar(jar, request, response):  Function `extract_cookies_to_jar`
utility or script function.
L140: def get_cookie_header(jar, request):  Function `get_cookie_header`  Returns or fetches
data.
L151: def remove_cookie_by_name(cookiejar, name, domain=None, path=None):  Function
`remove_cookie_by_name`  utility or script function.
L170: class CookieConflictError(RuntimeError):  Class (`CookieConflictError`)  component
used by the app (see file context: None).
L176: class RequestsCookieJar(cookiejar.CookieJar, MutableMapping):  Class
(`RequestsCookieJar`)  component used by the app (see file context: None).
L194: def get(self, name, default=None, domain=None, path=None):  Function `get`  Returns or
fetches data.
L206: def set(self, name, value, **kwargs):  Function `set`  Sets or updates a value.
L225: def iterkeys(self):  Function `iterkeys`  utility or script function.
L234: def keys(self):  Function `keys`  utility or script function.
L242: def itervalues(self):  Function `itervalues`  utility or script function.
L251: def values(self):  Function `values`  utility or script function.
L259: def iteritems(self):  Function `iteritems`  utility or script function.
L268: def items(self):  Function `items`  utility or script function.
L277: def list_domains(self):  Function `list_domains`  utility or script function.
L285: def list_paths(self):  Function `list_paths`  utility or script function.
L293: def multiple_domains(self):  Function `multiple_domains`  utility or script function.
L306: def get_dict(self, domain=None, path=None):  Function `get_dict`  Returns or fetches
data.
L321: def __contains__(self, name):  Function `__contains__`  utility or script function.
L327: def __getitem__(self, name):  Function `__getitem__`  utility or script function.
L336: def __setitem__(self, name, value):  Function `__setitem__`  utility or script
function.
L343: def __delitem__(self, name):  Function `__delitem__`  utility or script function.
L349: def set_cookie(self, cookie, *args, **kwargs):  Function `set_cookie`  Sets or updates
a value.
L358: def update(self, other):  Function `update`  utility or script function.
L366: def _find(self, name, domain=None, path=None):  Function `_find`  utility or script
function.
L386: def _find_no_duplicates(self, name, domain=None, path=None):  Function
`_find_no_duplicates`  utility or script function.
L415: def __getstate__(self):  Function `__getstate__`  utility or script function.
L422: def __setstate__(self, state):  Function `__setstate__`  utility or script function.
L428: def copy(self):  Function `copy`  utility or script function.
L435: def get_policy(self):  Function `get_policy`  Returns or fetches data.

```

```

L440: def _copy_cookie_jar(jar):    Function `_copy_cookie_jar` utility or script function.
L455: def create_cookie(name, value, **kwargs):    Function `create_cookie` Creates a
resource or document.
L492: def morsel_to_cookie(morsel):    Function `morsel_to_cookie` utility or script
function.
L521: def cookiejar_from_dict(cookie_dict, cookiejar=None, overwrite=True):    Function
`cookiejar_from_dict` utility or script function.
L542: def merge_cookies(cookiejar, cookies):    Function `merge_cookies` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/auth.py

```

L25: def _basic_auth_str(username, password):    Function `_basic_auth_str` utility or script
function.
L69: class AuthBase:    Authentication component (`AuthBase`) handles user authentication
flows.
L72: def __call__(self, r):    Function `__call__` utility or script function.
L76: class HTTPBasicAuth(AuthBase):    Authentication component (`HTTPBasicAuth`) handles
user authentication flows.
L79: def __init__(self, username, password):    Function `__init__` utility or script
function.
L83: def __eq__(self, other):    Function `__eq__` utility or script function.
L91: def __ne__(self, other):    Function `__ne__` utility or script function.
L94: def __call__(self, r):    Function `__call__` utility or script function.
L99: class HTTPProxyAuth(HTTPBasicAuth):    Authentication component (`HTTPProxyAuth`)
handles user authentication flows.
L102: def __call__(self, r):    Function `__call__` utility or script function.
L107: class HTTPDigestAuth(AuthBase):    Authentication component (`HTTPDigestAuth`) handles
user authentication flows.
L110: def __init__(self, username, password):    Function `__init__` utility or script
function.
L116: def init_per_thread_state(self):    Function `init_per_thread_state` Initialisation
routine.
L126: def build_digest_header(self, method, url):    Function `build_digest_header`
Constructs or prepares an object.
L145: def md5_utf8(x):    Function `md5_utf8` utility or script function.
L153: def sha_utf8(x):    Function `sha_utf8` utility or script function.
L161: def sha256_utf8(x):    Function `sha256_utf8` utility or script function.
L169: def sha512_utf8(x):    Function `sha512_utf8` utility or script function.
L236: def handle_redirect(self, r, **kwargs):    Function `handle_redirect` utility or script
function.
L241: def handle_401(self, r, **kwargs):    Function `handle_401` utility or script function.
L285: def __call__(self, r):    Function `__call__` utility or script function.
L305: def __eq__(self, other):    Function `__eq__` utility or script function.
L313: def __ne__(self, other):    Function `__ne__` utility or script function.

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/adapters.py

```

L63: def SOCKSProxyManager(*args, **kwargs):    Function `SOCKSProxyManager` utility or
script function.
L77: def _urllib3_request_context(    Function `_urllib3_request_context` utility or script
function.
L114: class BaseAdapter:    Class (`BaseAdapter`) component used by the app (see file
context: None).
L117: def __init__(self):    Function `__init__` utility or script function.
L120: def send(    Function `send` utility or script function.
L139: def close(self):    Function `close` utility or script function.
L144: class HTTPAdapter(BaseAdapter):    Class (`HTTPAdapter`) component used by the app (see
file context: None).
L179: def __init__(    Function `__init__` utility or script function.
L201: def __getstate__(self):    Function `__getstate__` utility or script function.
L204: def __setstate__(self, state):    Function `__setstate__` utility or script function.
L217: def init_poolmanager(    Function `init_poolmanager` Initialisation routine.
L243: def proxy_manager_for(self, proxy, **proxy_kwargs):    Function `proxy_manager_for`
utility or script function.
L281: def cert_verify(self, conn, url, verify, cert):    Function `cert_verify` utility or
script function.
L337: def build_response(self, req, resp):    Function `build_response` Constructs or
prepares an object.
L374: def build_connection_pool_key_attributes(self, request, verify, cert=None):    Function
`build_connection_pool_key_attributes` Constructs or prepares an object.
L424: def get_connection_with_tls_context(self, request, verify, proxies=None, cert=None):
Function `get_connection_with_tls_context` Returns or fetches data.
L473: def get_connection(self, url, proxies=None):    Function `get_connection` Returns or
fetches data.
L514: def close(self):    Function `close` utility or script function.
L524: def request_url(self, request, proxies):    Function `request_url` utility or script
function.
L556: def add_headers(self, request, **kwargs):    Function `add_headers` utility or script
function.
L570: def proxy_headers(self, proxy):    Function `proxy_headers` utility or script function.
L591: def send(    Function `send` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/structures.py

```

L13: class CaseInsensitiveDict(MutableMapping):    Class (`CaseInsensitiveDict`) component
used by the app (see file context: None).

```

```

L40: def __init__(self, data=None, **kwargs):    Function `__init__` utility or script
function.
L46: def __setitem__(self, key, value):    Function `__setitem__` utility or script function.
L51: def __getitem__(self, key):    Function `__getitem__` utility or script function.
L54: def __delitem__(self, key):    Function `__delitem__` utility or script function.
L57: def __iter__(self):    Function `__iter__` utility or script function.
L60: def __len__(self):    Function `__len__` utility or script function.
L63: def lower_items(self):    Function `lower_items` utility or script function.
L67: def __eq__(self, other):    Function `__eq__` utility or script function.
L76: def copy(self):    Function `copy` utility or script function.
L79: def __repr__(self):    Function `__repr__` utility or script function.
L83: class LookupDict(dict):    Class (`LookupDict`) component used by the app (see file
context: None).
L86: def __init__(self, name=None):    Function `__init__` utility or script function.
L90: def __repr__(self):    Function `__repr__` utility or script function.
L93: def __getitem__(self, key):    Function `__getitem__` utility or script function.
L98: def get(self, key, default=None):    Function `get` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/requests/status_codes.py

```

L109: def __init__():    Function `__init__` utility or script function.
L116: def doc(code):    Function `doc` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/unix.py

```

L18: def getuid() -> NoReturn:    Function `getuid` Returns or fetches data.
L26: class Unix(PlatformDirsABC):    # noqa: PLR0904    Class (`Unix`) component used by the
app (see file context: None).
L40: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L51: def _site_data_dirs(self) -> list[str]:    Function `_site_data_dirs` utility or script
function.
L58: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L71: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L82: def _site_config_dirs(self) -> list[str]:    Function `_site_config_dirs` utility or
script function.
L89: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L102: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.

```

```

L113: def site_cache_dir(self) -> str:    Function `site_cache_dir`  utility or script
function.
L118: def user_state_dir(self) -> str:    Function `user_state_dir`  utility or script
function.
L129: def user_log_dir(self) -> str:     Function `user_log_dir`   utility or script function.
L138: def user_documents_dir(self) -> str:  Function `user_documents_dir` utility or script
function.
L143: def user_downloads_dir(self) -> str:  Function `user_downloads_dir` utility or script
function.
L148: def user_pictures_dir(self) -> str:   Function `user_pictures_dir` utility or script
function.
L153: def user_videos_dir(self) -> str:    Function `user_videos_dir`  utility or script
function.
L158: def user_music_dir(self) -> str:     Function `user_music_dir`   utility or script
function.
L163: def user_desktop_dir(self) -> str:    Function `user_desktop_dir` utility or script
function.
L168: def user_runtime_dir(self) -> str:    Function `user_runtime_dir` utility or script
function.
L188: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.
L210: def site_data_path(self) -> Path:    Function `site_data_path`  utility or script
function.
L215: def site_config_path(self) -> Path:   Function `site_config_path` utility or script
function.
L220: def site_cache_path(self) -> Path:    Function `site_cache_path` utility or script
function.
L224: def iter_config_dirs(self) -> Iterator[str]: Function `iter_config_dirs` utility or
script function.
L229: def iter_data_dirs(self) -> Iterator[str]: Function `iter_data_dirs` utility or
script function.
L235: def _get_user_media_dir(env_var: str, fallback_tilde_path: str) -> str:  Function
`_get_user_media_dir`  utility or script function.
L245: def _get_user_dirs_folder(key: str) -> str | None:  Function `_get_user_dirs_folder`
utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/_
_main__.py**

```

L26: def main() -> None:    Function `main`  Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/a

pi.py

```

L15: class PlatformDirsABC(ABC): # noqa: PLR0904    Class (`PlatformDirsABC`) component used
by the app (see file context: None).
L18: def __init__( # noqa: PLR0913, PLR0917    Function `__init__` utility or script
function.
L81: def _append_app_name_and_version(self, *base: str) -> str:    Function
`_append_app_name_and_version` utility or script function.
L91: def _optionally_create_directory(self, path: str) -> None:    Function
`_optionally_create_directory` utility or script function.
L95: def _first_item_as_path_if_multipath(self, directory: str) -> Path:    Function
`_first_item_as_path_if_multipath` utility or script function.
L103: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L108: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L113: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L118: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L123: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L128: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L133: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script
function.
L138: def user_log_dir(self) -> str:    Function `user_log_dir` utility or script function.
L143: def user_documents_dir(self) -> str:    Function `user_documents_dir` utility or script
function.
L148: def user_downloads_dir(self) -> str:    Function `user_downloads_dir` utility or script
function.
L153: def user_pictures_dir(self) -> str:    Function `user_pictures_dir` utility or script
function.
L158: def user_videos_dir(self) -> str:    Function `user_videos_dir` utility or script
function.
L163: def user_music_dir(self) -> str:    Function `user_music_dir` utility or script
function.
L168: def user_desktop_dir(self) -> str:    Function `user_desktop_dir` utility or script
function.
L173: def user_runtime_dir(self) -> str:    Function `user_runtime_dir` utility or script
function.
L178: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.
L182: def user_data_path(self) -> Path:    Function `user_data_path` utility or script
function.
L187: def site_data_path(self) -> Path:    Function `site_data_path` utility or script
function.
L192: def user_config_path(self) -> Path:    Function `user_config_path` utility or script
function.
L197: def site_config_path(self) -> Path:    Function `site_config_path` utility or script
function.
L202: def user_cache_path(self) -> Path:    Function `user_cache_path` utility or script

```

```

function.
L207: def site_cache_path(self) -> Path:    Function `site_cache_path`  utility or script
function.
L212: def user_state_path(self) -> Path:    Function `user_state_path`  utility or script
function.
L217: def user_log_path(self) -> Path:     Function `user_log_path`   utility or script
function.
L222: def user_documents_path(self) -> Path:  Function `user_documents_path` utility or
script function.
L227: def user_downloads_path(self) -> Path:  Function `user_downloads_path` utility or
script function.
L232: def user_pictures_path(self) -> Path:   Function `user_pictures_path` utility or
script function.
L237: def user_videos_path(self) -> Path:    Function `user_videos_path` utility or script
function.
L242: def user_music_path(self) -> Path:     Function `user_music_path` utility or script
function.
L247: def user_desktop_path(self) -> Path:   Function `user_desktop_path` utility or script
function.
L252: def user_runtime_path(self) -> Path:   Function `user_runtime_path` utility or script
function.
L257: def site_runtime_path(self) -> Path:   Function `site_runtime_path` utility or script
function.
L261: def iter_config_dirs(self) -> Iterator[str]: Function `iter_config_dirs` utility or
script function.
L266: def iter_data_dirs(self) -> Iterator[str]: Function `iter_data_dirs` utility or
script function.
L271: def iter_cache_dirs(self) -> Iterator[str]: Function `iter_cache_dirs` utility or
script function.
L276: def iter_runtime_dirs(self) -> Iterator[str]: Function `iter_runtime_dirs` utility
or script function.
L281: def iter_config_paths(self) -> Iterator[Path]: Function `iter_config_paths` utility
or script function.
L286: def iter_data_paths(self) -> Iterator[Path]: Function `iter_data_paths` utility or
script function.
L291: def iter_cache_paths(self) -> Iterator[Path]: Function `iter_cache_paths` utility or
script function.
L296: def iter_runtime_paths(self) -> Iterator[Path]: Function `iter_runtime_paths`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/_init__.py

```

L30: def _set_platform_dir_class() -> type[PlatformDirsABC]:    Function
`_set_platform_dir_class` utility or script function.
L53: def user_data_dir(    Function `user_data_dir` utility or script function.

```

```

L77: def site_data_dir(    Function `site_data_dir`    utility or script function.
L101: def user_config_dir(    Function `user_config_dir`    utility or script function.
L125: def site_config_dir(    Function `site_config_dir`    utility or script function.
L149: def user_cache_dir(    Function `user_cache_dir`    utility or script function.
L173: def site_cache_dir(    Function `site_cache_dir`    utility or script function.
L197: def user_state_dir(    Function `user_state_dir`    utility or script function.
L221: def user_log_dir(    Function `user_log_dir`    utility or script function.
L245: def user_documents_dir() -> str:    Function `user_documents_dir`    utility or script
function.
L250: def user_downloads_dir() -> str:    Function `user_downloads_dir`    utility or script
function.
L255: def user_pictures_dir() -> str:    Function `user_pictures_dir`    utility or script
function.
L260: def user_videos_dir() -> str:    Function `user_videos_dir`    utility or script function.
L265: def user_music_dir() -> str:    Function `user_music_dir`    utility or script function.
L270: def user_desktop_dir() -> str:    Function `user_desktop_dir`    utility or script
function.
L275: def user_runtime_dir(    Function `user_runtime_dir`    utility or script function.
L299: def site_runtime_dir(    Function `site_runtime_dir`    utility or script function.
L323: def user_data_path(    Function `user_data_path`    utility or script function.
L347: def site_data_path(    Function `site_data_path`    utility or script function.
L371: def user_config_path(    Function `user_config_path`    utility or script function.
L395: def site_config_path(    Function `site_config_path`    utility or script function.
L419: def site_cache_path(    Function `site_cache_path`    utility or script function.
L443: def user_cache_path(    Function `user_cache_path`    utility or script function.
L467: def user_state_path(    Function `user_state_path`    utility or script function.
L491: def user_log_path(    Function `user_log_path`    utility or script function.
L515: def user_documents_path() -> Path:    Function `user_documents_path`    utility or script
function.
L520: def user_downloads_path() -> Path:    Function `user_downloads_path`    utility or script
function.
L525: def user_pictures_path() -> Path:    Function `user_pictures_path`    utility or script
function.
L530: def user_videos_path() -> Path:    Function `user_videos_path`    utility or script
function.
L535: def user_music_path() -> Path:    Function `user_music_path`    utility or script
function.
L540: def user_desktop_path() -> Path:    Function `user_desktop_path`    utility or script
function.
L545: def user_runtime_path(    Function `user_runtime_path`    utility or script function.
L569: def site_runtime_path(    Function `site_runtime_path`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/android.py

```

L14: class Android(PlatformDirsABC):    Class (`Android`)    component used by the app (see file

```

```

context: None).
L24: def user_data_dir(self) -> str:    Function `user_data_dir`  utility or script function.
L29: def site_data_dir(self) -> str:    Function `site_data_dir`  utility or script function.
L34: def user_config_dir(self) -> str:   Function `user_config_dir` utility or script
function.
L42: def site_config_dir(self) -> str:   Function `site_config_dir` utility or script
function.
L47: def user_cache_dir(self) -> str:    Function `user_cache_dir`  utility or script
function.
L52: def site_cache_dir(self) -> str:    Function `site_cache_dir`  utility or script
function.
L57: def user_state_dir(self) -> str:    Function `user_state_dir`  utility or script
function.
L62: def user_log_dir(self) -> str:      Function `user_log_dir`    utility or script function.
L73: def user_documents_dir(self) -> str: Function `user_documents_dir` utility or script
function.
L78: def user_downloads_dir(self) -> str: Function `user_downloads_dir` utility or script
function.
L83: def user_pictures_dir(self) -> str:  Function `user_pictures_dir` utility or script
function.
L88: def user_videos_dir(self) -> str:    Function `user_videos_dir`  utility or script
function.
L93: def user_music_dir(self) -> str:     Function `user_music_dir`   utility or script
function.
L98: def user_desktop_dir(self) -> str:   Function `user_desktop_dir` utility or script
function.
L103: def user_runtime_dir(self) -> str:   Function `user_runtime_dir` utility or script
function.
L114: def site_runtime_dir(self) -> str:   Function `site_runtime_dir` utility or script
function.
L120: def _android_folder() -> str | None: # noqa: C901    Function `_android_folder`
utility or script function.
L168: def _android_documents_folder() -> str:   Function `_android_documents_folder` utility
or script function.
L184: def _android_downloads_folder() -> str:   Function `_android_downloads_folder` utility
or script function.
L200: def _android_pictures_folder() -> str:   Function `_android_pictures_folder` utility
or script function.
L216: def _android_videos_folder() -> str:     Function `_android_videos_folder` utility or
script function.
L232: def _android_music_folder() -> str:      Function `_android_music_folder` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/
macos.py

```

L15: class MacOS(PlatformDirsABC):    Class (`MacOS`) component used by the app (see file
context: None).
L28: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L33: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L51: def site_data_path(self) -> Path:    Function `site_data_path` utility or script
function.
L56: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L61: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L66: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L71: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L89: def site_cache_path(self) -> Path:    Function `site_cache_path` utility or script
function.
L94: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script
function.
L99: def user_log_dir(self) -> str:    Function `user_log_dir` utility or script function.
L104: def user_documents_dir(self) -> str:    Function `user_documents_dir` utility or script
function.
L109: def user_downloads_dir(self) -> str:    Function `user_downloads_dir` utility or script
function.
L114: def user_pictures_dir(self) -> str:    Function `user_pictures_dir` utility or script
function.
L119: def user_videos_dir(self) -> str:    Function `user_videos_dir` utility or script
function.
L124: def user_music_dir(self) -> str:    Function `user_music_dir` utility or script
function.
L129: def user_desktop_dir(self) -> str:    Function `user_desktop_dir` utility or script
function.
L134: def user_runtime_dir(self) -> str:    Function `user_runtime_dir` utility or script
function.
L139: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/windows.py

```

L16: class Windows(PlatformDirsABC):    Class (`Windows`) component used by the app (see file
context: None).
L28: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L38: def _append_parts(self, path: str, *, opinion_value: str | None = None) -> str:
Function `_append_parts` utility or script function.
L54: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L60: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script

```



```

function.
L65: def site_config_dir(self) -> str:    Function `site_config_dir`    utility or script
function.
L70: def user_cache_dir(self) -> str:    Function `user_cache_dir`    utility or script
function.
L79: def site_cache_dir(self) -> str:    Function `site_cache_dir`    utility or script
function.
L85: def user_state_dir(self) -> str:    Function `user_state_dir`    utility or script
function.
L90: def user_log_dir(self) -> str:    Function `user_log_dir`    utility or script function.
L99: def user_documents_dir(self) -> str:    Function `user_documents_dir`    utility or script
function.
L104: def user_downloads_dir(self) -> str:    Function `user_downloads_dir`    utility or script
function.
L109: def user_pictures_dir(self) -> str:    Function `user_pictures_dir`    utility or script
function.
L114: def user_videos_dir(self) -> str:    Function `user_videos_dir`    utility or script
function.
L119: def user_music_dir(self) -> str:    Function `user_music_dir`    utility or script
function.
L124: def user_desktop_dir(self) -> str:    Function `user_desktop_dir`    utility or script
function.
L129: def user_runtime_dir(self) -> str:    Function `user_runtime_dir`    utility or script
function.
L138: def site_runtime_dir(self) -> str:    Function `site_runtime_dir`    utility or script
function.
L143: def get_win_folder_from_env_vars(csidl_name: str) -> str:    Function
`get_win_folder_from_env_vars`    Returns or fetches data.
L164: def get_win_folder_if_csidl_name_not_env_var(csidl_name: str) -> str | None:    Function
`get_win_folder_if_csidl_name_not_env_var`    Returns or fetches data.
L183: def get_win_folder_from_registry(csidl_name: str) -> str:    Function
`get_win_folder_from_registry`    Returns or fetches data.
L219: def get_win_folder_via_ctypes(csidl_name: str) -> str:    Function
`get_win_folder_via_ctypes`    Returns or fetches data.
L258: def _pick_get_win_folder() -> Callable[[str], str]:    Function `_pick_get_win_folder`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_parser.py

```

L77: class DEPRECATED_DEFAULT:    Class (`DEPRECATED_DEFAULT`)    component used by the app (see
file context: None).
L82: class TOMLDecodeError(ValueError):    Class (`TOMLDecodeError`)    component used by the
app (see file context: None).
L93: def __init__(    Function `__init__`    utility or script function.
L143: def load(__fp: IO[bytes], *, parse_float: ParseFloat = float) -> dict[str, Any]:

```

```

Function `load` Loads data from storage or remote.
L155: def loads(__s: str, *, parse_float: ParseFloat = float) -> dict[str, Any]: Function
`loads` Loads data from storage or remote.
L226: class Flags: Class (`Flags`) component used by the app (see file context: None).
L235: def __init__(self) -> None: Function `__init__` utility or script function.
L239: def add_pending(self, key: Key, flag: int) -> None: Function `add_pending` utility
or script function.
L242: def finalize_pending(self) -> None: Function `finalize_pending` utility or script
function.
L247: def unset_all(self, key: Key) -> None: Function `unset_all` utility or script
function.
L255: def set(self, key: Key, flag: int, *, recursive: bool) -> None: # noqa: A003
Function `set` Sets or updates a value.
L266: def is_(self, key: Key, flag: int) -> bool: Function `is_` utility or script
function.
L284: class NestedDict: Class (`NestedDict`) component used by the app (see file context:
None).
L285: def __init__(self) -> None: Function `__init__` utility or script function.
L289: def get_or_create_nest( Function `get_or_create_nest` Returns or fetches data.
L306: def append_nest_to_list(self, key: Key) -> None: Function `append_nest_to_list`
utility or script function.
L318: class Output: Class (`Output`) component used by the app (see file context: None).
L319: def __init__(self) -> None: Function `__init__` utility or script function.
L324: def skip_chars(src: str, pos: Pos, chars: Iterable[str]) -> Pos: Function
`skip_chars` utility or script function.
L333: def skip_until( Function `skip_until` utility or script function.
L355: def skip_comment(src: str, pos: Pos) -> Pos: Function `skip_comment` utility or
script function.
L367: def skip_comments_and_array_ws(src: str, pos: Pos) -> Pos: Function
`skip_comments_and_array_ws` utility or script function.
L376: def create_dict_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]: Function
`create_dict_rule` Creates a resource or document.
L396: def create_list_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]: Function
`create_list_rule` Creates a resource or document.
L419: def key_value_rule( Function `key_value_rule` utility or script function.
L453: def parse_key_value_pair( Function `parse_key_value_pair` utility or script
function.
L469: def parse_key(src: str, pos: Pos) -> tuple[Pos, Key]: Function `parse_key` utility
or script function.
L491: def parse_key_part(src: str, pos: Pos) -> tuple[Pos, str]: Function `parse_key_part`
utility or script function.
L507: def parse_one_line_basic_str(src: str, pos: Pos) -> tuple[Pos, str]: Function
`parse_one_line_basic_str` utility or script function.
L512: def parse_array( Function `parse_array` utility or script function.
L538: def parse_inline_table( Function `parse_inline_table` utility or script function.
L572: def parse_basic_str_escape( Function `parse_basic_str_escape` utility or script
function.
L601: def parse_basic_str_escape_multiline(src: str, pos: Pos) -> tuple[Pos, str]: Function
`parse_basic_str_escape_multiline` utility or script function.
L605: def parse_hex_char(src: str, pos: Pos, hex_len: int) -> tuple[Pos, str]: Function
`parse_hex_char` utility or script function.

```

```

L618: def parse_literal_str(src: str, pos: Pos) -> tuple[Pos, str]:    Function
`parse_literal_str` utility or script function.
L627: def parse_multiline_str(src: str, pos: Pos, *, literal: bool) -> tuple[Pos, str]:
Function `parse_multiline_str` utility or script function.
L658: def parse_basic_str(src: str, pos: Pos, *, multiline: bool) -> tuple[Pos, str]:
Function `parse_basic_str` utility or script function.
L690: def parse_value(    Function `parse_value` utility or script function.
L766: def is_unicode_scalar_value(codepoint: int) -> bool:    Function
`is_unicode_scalar_value` utility or script function.
L770: def make_safe_parse_float(parse_float: ParseFloat) -> ParseFloat:    Function
`make_safe_parse_float` utility or script function.
L782: def safe_parse_float(float_str: str) -> Any:    Function `safe_parse_float` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_re.py

```

L57: def match_to_datetime(match: re.Match[str]) -> datetime | date:    Function
`match_to_datetime` utility or script function.
L96: def cached_tz(hour_str: str, minute_str: str, sign_str: str) -> timezone:    Function
`cached_tz` utility or script function.
L106: def match_to_localtime(match: re.Match[str]) -> time:    Function `match_to_localtime`
utility or script function.
L112: def match_to_number(match: re.Match[str], parse_float: ParseFloat) -> Any:    Function
`match_to_number` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/exceptions.py

```

L1: class UnpackException(Exception):    Class (`UnpackException`) component used by the app
(see file context: None).
L10: class BufferFull(UnpackException):    Class (`BufferFull`) component used by the app
(see file context: None).
L14: class OutOfData(UnpackException):    Class (`OutOfData`) component used by the app (see
file context: None).
L18: class FormatError(ValueError, UnpackException):    Class (`FormatError`) component used
by the app (see file context: None).
L22: class StackError(ValueError, UnpackException):    Class (`StackError`) component used by
the app (see file context: None).
L30: class ExtraData(UnpackValueError):    Class (`ExtraData`) component used by the app (see
file context: None).
L37: def __init__(self, unpacked, extra):    Function `__init__` utility or script function.
L41: def __str__(self):    Function `__str__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/__init__.py

```

L20: def pack(o, stream, **kwargs):    Function `pack` utility or script function.
L30: def packb(o, **kwargs):    Function `packb` utility or script function.
L39: def unpack(stream, **kwargs):    Function `unpack` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/ext.py

```

L6: class ExtType(namedtuple("ExtType", "code data")):    Class (`ExtType`) component used by
the app (see file context: None).
L9: def __new__(cls, code, data):    Function `__new__` utility or script function.
L19: class Timestamp:    Class (`Timestamp`) component used by the app (see file context:
None).
L31: def __init__(self, seconds, nanoseconds=0):    Function `__init__` utility or script
function.
L53: def __repr__(self):    Function `__repr__` utility or script function.
L57: def __eq__(self, other):    Function `__eq__` utility or script function.
L63: def __ne__(self, other):    Function `__ne__` utility or script function.
L67: def __hash__(self):    Function `__hash__` utility or script function.
L71: def from_bytes(b):    Function `from_bytes` utility or script function.
L97: def to_bytes(self):    Function `to_bytes` utility or script function.
L119: def from_unix(unix_sec):    Function `from_unix` utility or script function.
L129: def to_unix(self):    Function `to_unix` utility or script function.
L138: def from_unix_nano(unix_ns):    Function `from_unix_nano` utility or script function.
L146: def to_unix_nano(self):    Function `to_unix_nano` utility or script function.
L154: def to_datetime(self):    Function `to_datetime` utility or script function.
L165: def from_datetime(dt):    Function `from_datetime` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/fallback.py

```

L13: class BytesIO:    Class (`BytesIO`) component used by the app (see file context: None).
L14: def __init__(self, s=b''):    Function `__init__` utility or script function.
L21: def write(self, s):    Function `write` utility or script function.
L28: def getvalue(self):    Function `getvalue` Returns or fetches data.
L36: def newlist_hint(size):    Function `newlist_hint` utility or script function.
L58: def _check_type_strict(obj, t, type=type, tuple=tuple):    Function `_check_type_strict`

```

utility or script function.

L65: def _get_data_from_buffer(obj): Function `\_get\_data\_from\_buffer` utility or script function.

L72: def unpackb(packed, **kwargs): Function `\_unpackb` utility or script function.

L130: class Unpacker: Class (`Unpacker`) component used by the app (see file context: None).

L226: def __init__(Function `\_\_\_init\_\_` utility or script function.

L318: def feed(self, next_bytes): Function `\_feed` utility or script function.

L334: def _consume(self): Function `\_consume` utility or script function.

L339: def _got_extradata(self): Function `\_got\_extradata` utility or script function.

L342: def _get_extradata(self): Function `\_get\_extradata` utility or script function.

L345: def read_bytes(self, n): Function `\_read\_bytes` utility or script function.

L350: def _read(self, n, raise_outofdata=True): Function `\_read` utility or script function.

L358: def _reserve(self, n, raise_outofdata=True): Function `\_reserve` utility or script function.

L392: def _read_header(self): Function `\_read\_header` utility or script function.

L488: def _unpack(self, execute=EX_CONSTRUCT): Function `\_unpack` utility or script function.

L562: def __iter__(self): Function `\_\_\_iter\_\_` utility or script function.

L565: def __next__(self): Function `\_\_\_next\_\_` utility or script function.

L578: def skip(self): Function `\_skip` utility or script function.

L582: def unpack(self): Function `\_unpack` utility or script function.

L590: def read_array_header(self): Function `\_read\_array\_header` utility or script function.

L595: def read_map_header(self): Function `\_read\_map\_header` utility or script function.

L600: def tell(self): Function `\_tell` utility or script function.

L604: class Packer: Class (`Packer`) component used by the app (see file context: None).

L653: def __init__(Function `\_\_\_init\_\_` utility or script function.

L676: def _pack(Function `\_pack` utility or script function.

L800: def pack(self, obj): Function `\_pack` utility or script function.

L811: def pack_map_pairs(self, pairs): Function `\_pack\_map\_pairs` utility or script function.

L818: def pack_array_header(self, n): Function `\_pack\_array\_header` utility or script function.

L827: def pack_map_header(self, n): Function `\_pack\_map\_header` utility or script function.

L836: def pack_ext_type(self, typecode, data): Function `\_pack\_ext\_type` utility or script function.

L865: def _pack_array_header(self, n): Function `\_pack\_array\_header` utility or script function.

L874: def _pack_map_header(self, n): Function `\_pack\_map\_header` utility or script function.

L883: def _pack_map_pairs(self, n, pairs, nest_limit=DEFAULT_RECURSE_LIMIT): Function `\_pack\_map\_pairs` utility or script function.

L889: def _pack_raw_header(self, n): Function `\_pack\_raw\_header` utility or script function.

L901: def _pack_bin_header(self, n): Function `\_pack\_bin\_header` utility or script function.

L913: def bytes(self): Function `\_bytes` utility or script function.

L917: def reset(self): Function `\_reset` utility or script function.

L924: def getbuffer(self): Function `\_getbuffer` Returns or fetches data.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/pkg_resources/____init____.py

```

L135: class _LoaderProtocol(Protocol):    Class (`_LoaderProtocol`) component used by the app
(see file context: None).
L136: def load_module(self, fullname: str, /) -> types.ModuleType: ...    Function
`load_module` Loads data from storage or remote.
L139: class _ZipLoaderModule(Protocol):    Dependency injection module (`_ZipLoaderModule`)
provides DI bindings.
L146: class PEP440Warning(RuntimeWarning):    Class (`PEP440Warning`) component used by the
app (see file context: None).
L159: def _declare_state(vartype: str, varname: str, initial_value: _T) -> _T:    Function
`_declare_state` utility or script function.
L164: def __getstate__() -> dict[str, Any]:    Function `__getstate__` utility or script
function.
L172: def __setstate__(state: dict[str, Any]) -> dict[str, Any]:    Function `__setstate__`
utility or script function.
L179: def _sget_dict(val):    Function `_sget_dict` utility or script function.
L183: def _sset_dict(key, ob, state):    Function `_sset_dict` utility or script function.
L188: def _sget_object(val):    Function `_sget_object` utility or script function.
L192: def _sset_object(key, ob, state):    Function `_sset_object` utility or script
function.
L199: def get_supported_platform():    Function `get_supported_platform` Returns or fetches
data.
L309: class ResolutionError(Exception):    Class (`ResolutionError`) component used by the
app (see file context: None).
L312: def __repr__(self):    Function `__repr__` utility or script function.
L316: class VersionConflict(ResolutionError):    Class (`VersionConflict`) component used by
the app (see file context: None).
L327: def dist(self) -> Distribution:    Function `dist` utility or script function.
L331: def req(self) -> Requirement:    Function `req` utility or script function.
L334: def report(self):    Function `report` utility or script function.
L337: def with_context(self, required_by: set[Distribution | str]):    Function `with_context`
utility or script function.
L348: class ContextualVersionConflict(VersionConflict):    Class (`ContextualVersionConflict`)
component used by the app (see file context: None).
L357: def required_by(self) -> set[str]:    Function `required_by` utility or script
function.
L361: class DistributionNotFound(ResolutionError):    Class (`DistributionNotFound`)
component used by the app (see file context: None).
L370: def req(self) -> Requirement:    Function `req` utility or script function.
L374: def requirers(self) -> set[str] | None:    Function `requirers` utility or script
function.
L378: def requirers_str(self):    Function `requirers_str` utility or script function.
L383: def report(self):    Function `report` utility or script function.
L386: def __str__(self):    Function `__str__` utility or script function.
L390: class UnknownExtra(ResolutionError):    Class (`UnknownExtra`) component used by the
app (see file context: None).

```

```

L404: def register_loader_type(    Function `register_loader_type`    utility or script
function.
L417: def get_provider(moduleOrReq: str) -> IResourceProvider: ...    Function `get_provider`
Returns or fetches data.
L419: def get_provider(moduleOrReq: Requirement) -> Distribution: ...    Function
`get_provider`    Returns or fetches data.
L420: def get_provider(moduleOrReq: str | Requirement) -> IResourceProvider | Distribution:
Function `get_provider`    Returns or fetches data.
L434: def _macos_vers():    Function `_macos_vers`    utility or script function.
L447: def _macos_arch(machine):    Function `_macos_arch`    utility or script function.
L451: def get_build_platform():    Function `get_build_platform`    Returns or fetches data.
L482: def compatible_platforms(provided: str | None, required: str | None):    Function
`compatible_platforms`    utility or script function.
L532: def get_distribution(dist: _DistributionT) -> _DistributionT: ...    Function
`get_distribution`    Returns or fetches data.
L534: def get_distribution(dist: _PkgReqType) -> Distribution: ...    Function
`get_distribution`    Returns or fetches data.
L535: def get_distribution(dist: Distribution | _PkgReqType) -> Distribution:    Function
`get_distribution`    Returns or fetches data.
L547: def load_entry_point(dist: _EPDistType, group: str, name: str) -> _ResolvedEntryPoint:
Function `load_entry_point`    Loads data from storage or remote.
L553: def get_entry_map(    Function `get_entry_map`    Returns or fetches data.
L557: def get_entry_map(dist: _EPDistType, group: str) -> dict[str, EntryPoint]: ...
Function `get_entry_map`    Returns or fetches data.
L558: def get_entry_map(dist: _EPDistType, group: str | None = None):    Function
`get_entry_map`    Returns or fetches data.
L563: def get_entry_info(dist: _EPDistType, group: str, name: str):    Function
`get_entry_info`    Returns or fetches data.
L568: class IMetadataProvider(Protocol):    Class (`IMetadataProvider`)    component used by the
app (see file context: None).
L569: def has_metadata(self, name: str) -> bool:    Function `has_metadata`    utility or script
function.
L572: def get_metadata(self, name: str) -> str:    Function `get_metadata`    Returns or fetches
data.
L575: def get_metadata_lines(self, name: str) -> Iterator[str]:    Function
`get_metadata_lines`    Returns or fetches data.
L581: def metadata_isdir(self, name: str) -> bool:    Function `metadata_isdir`    utility or
script function.
L584: def metadata_listdir(self, name: str) -> list[str]:    Function `metadata_listdir`
utility or script function.
L587: def run_script(self, script_name: str, namespace: dict[str, Any]) -> None:    Function
`run_script`    utility or script function.
L591: class IResourceProvider(IMetadataProvider, Protocol):    Class (`IResourceProvider`)
component used by the app (see file context: None).
L594: def get_resource_filename(    Function `get_resource_filename`    Returns or fetches data.
L601: def get_resource_stream(    Function `get_resource_stream`    Returns or fetches data.
L608: def get_resource_string(    Function `get_resource_string`    Returns or fetches data.
L615: def has_resource(self, resource_name: str) -> bool:    Function `has_resource`    utility
or script function.
L618: def resource_isdir(self, resource_name: str) -> bool:    Function `resource_isdir`
utility or script function.

```



```

L621: def resource_listdir(self, resource_name: str) -> list[str]:    Function
`resource_listdir` utility or script function.
L625: class WorkingSet:    Class (`WorkingSet`) component used by the app (see file context:
None).
L628: def __init__(self, entries: Iterable[str] | None = None):    Function `__init__`
utility or script function.
L643: def _build_master(cls):    Function `_build_master` utility or script function.
L663: def _build_from_requirements(cls, req_spec):    Function `_build_from_requirements`
utility or script function.
L684: def add_entry(self, entry: str):    Function `add_entry` utility or script function.
L699: def __contains__(self, dist: Distribution) -> bool:    Function `__contains__` utility
or script function.
L703: def find(self, req: Requirement) -> Distribution | None:    Function `find` utility or
script function.
L727: def iter_entry_points(self, group: str, name: str | None = None):    Function
`iter_entry_points` utility or script function.
L741: def run_script(self, requires: str, script_name: str):    Function `run_script` utility
or script function.
L749: def __iter__(self) -> Iterator[Distribution]:    Function `__iter__` utility or script
function.
L766: def add(    Function `add` utility or script function.
L805: def resolve(    Function `resolve` utility or script function.
L814: def resolve(    Function `resolve` utility or script function.
L824: def resolve(    Function `resolve` utility or script function.
L832: def resolve(    Function `resolve` utility or script function.
L906: def _resolve_dist(    Function `_resolve_dist` utility or script function.
L938: def find_plugins(    Function `find_plugins` utility or script function.
L946: def find_plugins(    Function `find_plugins` utility or script function.
L955: def find_plugins(    Function `find_plugins` utility or script function.
L962: def find_plugins(    Function `find_plugins` utility or script function.
L1052: def require(self, *requirements: _NestedStr):    Function `require` utility or script
function.
L1068: def subscribe(    Function `subscribe` utility or script function.
L1084: def _added_new(self, dist):    Function `_added_new` utility or script function.
L1088: def __getstate__(self):    Function `__getstate__` utility or script function.
L1097: def __setstate__(self, e_k_b_n_c):    Function `__setstate__` utility or script
function.
L1106: class _ReqExtras(Dict["Requirement", Tuple[str, ...]]):    Class (`_ReqExtras`)
component used by the app (see file context: None).
L1111: def markers_pass(self, req: Requirement, extras: tuple[str, ...] | None = None):
Function `markers_pass` utility or script function.
L1126: class Environment:    Class (`Environment`) component used by the app (see file
context: None).
L1129: def __init__(    Function `__init__` utility or script function.
L1156: def can_add(self, dist: Distribution):    Function `can_add` utility or script
function.
L1170: def remove(self, dist: Distribution):    Function `remove` utility or script function.
L1174: def scan(self, search_path: Iterable[str] | None = None):    Function `scan` utility
or script function.
L1189: def __getitem__(self, project_name: str) -> list[Distribution]:    Function
`__getitem__` utility or script function.

```



```

L1200: def add(self, dist: Distribution):    Function `add` utility or script function.
L1209: def best_match(    Function `best_match` utility or script function.
L1217: def best_match(    Function `best_match` utility or script function.
L1224: def best_match(    Function `best_match` utility or script function.
L1258: def obtain(    Function `obtain` utility or script function.
L1264: def obtain(    Function `obtain` utility or script function.
L1270: def obtain(    Function `obtain` utility or script function.
L1275: def obtain(    Function `obtain` utility or script function.
L1293: def __iter__(self) -> Iterator[str]:    Function `__iter__` utility or script
function.
L1299: def __iadd__(self, other: Distribution | Environment):    Function `__iadd__` utility
or script function.
L1311: def __add__(self, other: Distribution | Environment):    Function `__add__` utility or
script function.
L1323: class ExtractionError(RuntimeError):    Class (`ExtractionError`) component used by
the app (see file context: None).
L1343: class ResourceManager:    Manager (`ResourceManager`) orchestration/utility for
managing resources or behaviors.
L1348: def __init__(self):    Function `__init__` utility or script function.
L1351: def resource_exists(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_exists` utility or script function.
L1355: def resource_isdir(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_isdir` utility or script function.
L1359: def resource_filename(    Function `resource_filename` utility or script function.
L1367: def resource_stream(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_stream` utility or script function.
L1373: def resource_string(    Function `resource_string` utility or script function.
L1381: def resource_listdir(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_listdir` utility or script function.
L1385: def extraction_error(self) -> NoReturn:    Function `extraction_error` utility or
script function.
L1415: def get_cache_path(self, archive_name: str, names: Iterable[StrPath] = ()):    Function
`get_cache_path` Returns or fetches data.
L1441: def _warn_unsafe_extraction_path(path):    Function `_warn_unsafe_extraction_path`
utility or script function.
L1467: def postprocess(self, tempname: StrOrBytesPath, filename: StrOrBytesPath):    Function
`postprocess` utility or script function.
L1487: def set_extraction_path(self, path: str):    Function `set_extraction_path` Sets or
updates a value.
L1511: def cleanup_resources(self, force: bool = False) -> list[str]:    Function
`cleanup_resources` utility or script function.
L1526: def get_default_cache() -> str:    Function `get_default_cache` Returns or fetches
data.
L1535: def safe_name(name: str):    Function `safe_name` utility or script function.
L1543: def safe_version(version: str):    Function `safe_version` utility or script function.
L1555: def _forgiving_version(version):    Function `_forgiving_version` utility or script
function.
L1580: def _safe_segment(segment):    Function `_safe_segment` utility or script function.
L1587: def safe_extra(extra: str):    Function `safe_extra` utility or script function.
L1596: def to_filename(name: str):    Function `to_filename` utility or script function.
L1604: def invalid_marker(text: str):    Function `invalid_marker` utility or script

```

```

function.
L1618: def evaluate_marker(text: str, extra: str | None = None) -> bool:    Function
`evaluate_marker` utility or script function.
L1633: class NullProvider:    Class (`NullProvider`) component used by the app (see file
context: None).
L1640: def __init__(self, module: _ModuleLike):    Function `__init__` utility or script
function.
L1644: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
Function `get_resource_filename` Returns or fetches data.
L1647: def get_resource_stream(self, manager: ResourceManager, resource_name: str):
Function `get_resource_stream` Returns or fetches data.
L1650: def get_resource_string(    Function `get_resource_string` Returns or fetches data.
L1655: def has_resource(self, resource_name: str):    Function `has_resource` utility or
script function.
L1658: def _get_metadata_path(self, name):    Function `_get_metadata_path` utility or script
function.
L1661: def has_metadata(self, name: str) -> bool:    Function `has_metadata` utility or
script function.
L1668: def get_metadata(self, name: str):    Function `get_metadata` Returns or fetches data.
L1681: def get_metadata_lines(self, name: str) -> Iterator[str]:    Function
`get_metadata_lines` Returns or fetches data.
L1684: def resource_isdir(self, resource_name: str):    Function `resource_isdir` utility or
script function.
L1687: def metadata_isdir(self, name: str) -> bool:    Function `metadata_isdir` utility or
script function.
L1690: def resource_listdir(self, resource_name: str):    Function `resource_listdir` utility
or script function.
L1693: def metadata_listdir(self, name: str) -> list[str]:    Function `metadata_listdir`
utility or script function.
L1698: def run_script(self, script_name: str, namespace: dict[str, Any]):    Function
`run_script` utility or script function.
L1727: def _has(self, path) -> bool:    Function `_has` utility or script function.
L1732: def _isdir(self, path) -> bool:    Function `_isdir` utility or script function.
L1737: def _listdir(self, path) -> list[str]:    Function `_listdir` utility or script
function.
L1742: def _fn(self, base: str | None, resource_name: str):    Function `_fn` utility or
script function.
L1753: def _validate_resource_path(path):    Function `_validate_resource_path` utility or
script function.
L1827: def _get(self, path) -> bytes:    Function `_get` utility or script function.
L1839: def _parents(path):    Function `_parents` utility or script function.
L1850: class EggProvider(NullProvider):    Class (`EggProvider`) component used by the app
(see file context: None).
L1853: def __init__(self, module: _ModuleLike):    Function `__init__` utility or script
function.
L1857: def _setup_prefix(self):    Function `_setup_prefix` utility or script function.
L1864: def _set_egg(self, path: str):    Function `_set_egg` utility or script function.
L1870: class DefaultProvider(EggProvider):    Class (`DefaultProvider`) component used by the
app (see file context: None).
L1873: def _has(self, path) -> bool:    Function `_has` utility or script function.
L1876: def _isdir(self, path) -> bool:    Function `_isdir` utility or script function.

```

```

L1879: def _listdir(self, path):    Function `_listdir` utility or script function.
L1882: def get_resource_stream(self, manager: object, resource_name: str):    Object
(singleton).
L1885: def _get(self, path) -> bytes:    Function `_get` utility or script function.
L1890: def _register(cls):    Function `_register` utility or script function.
L1903: class EmptyProvider(NullProvider):    Class (`EmptyProvider`) component used by the
app (see file context: None).
L1911: def _get(self, path) -> bytes:    Function `_get` utility or script function.
L1914: def _listdir(self, path):    Function `_listdir` utility or script function.
L1917: def __init__(self):    Function `__init__` utility or script function.
L1924: class ZipManifests(Dict[str, "MemoizedZipManifests.manifest_mod"]):    Class
(`ZipManifests`) component used by the app (see file context: None).
L1931: def build(cls, path: str):    Function `build` Constructs or prepares an object.
L1952: class MemoizedZipManifests(ZipManifests):    Class (`MemoizedZipManifests`) component
used by the app (see file context: None).
L1957: class manifest_mod(NamedTuple):    Class (`manifest_mod`) component used by the app
(see file context: None).
L1961: def load(self, path: str) -> dict[str, zipfile.ZipInfo]:    # type: ignore[override] #
ZipManifests.load is a classmethod    Function `load` Loads data from storage or remote.
L1975: class ZipProvider(EggProvider):    Class (`ZipProvider`) component used by the app
(see file context: None).
L1983: def __init__(self, module: _ZipLoaderModule):    Function `__init__` utility or script
function.
L1987: def _zipinfo_name(self, fspath):    Function `_zipinfo_name` utility or script
function.
L1997: def _parts(self, zip_path):    Function `_parts` utility or script function.
L2006: def zipinfo(self):    Function `zipinfo` utility or script function.
L2009: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
Function `get_resource_filename` Returns or fetches data.
L2023: def _get_date_and_size(zip_stat):    Function `_get_date_and_size` utility or script
function.
L2032: def _extract_resource(self, manager: ResourceManager, zip_path) -> str:    # noqa: C901
Function `_extract_resource` utility or script function.
L2086: def _is_current(self, file_path, zip_path):    Function `_is_current` utility or
script function.
L2102: def _get_eager_resources(self):    Function `_get_eager_resources` utility or script
function.
L2111: def _index(self):    Function `_index` utility or script function.
L2128: def _has(self, fspath) -> bool:    Function `_has` utility or script function.
L2132: def _isdir(self, fspath) -> bool:    Function `_isdir` utility or script function.
L2135: def _listdir(self, fspath):    Function `_listdir` utility or script function.
L2138: def _eager_to_zip(self, resource_name: str):    Function `_eager_to_zip` utility or
script function.
L2141: def _resource_to_zip(self, resource_name: str):    Function `_resource_to_zip` utility
or script function.
L2148: class FileMetadata(EmptyProvider):    Class (`FileMetadata`) component used by the app
(see file context: None).
L2160: def __init__(self, path: StrPath):    Function `__init__` utility or script function.
L2163: def _get_metadata_path(self, name):    Function `_get_metadata_path` utility or script
function.
L2166: def has_metadata(self, name: str) -> bool:    Function `has_metadata` utility or

```

```

script function.
L2169: def get_metadata(self, name: str):    Function `get_metadata` Returns or fetches data.
L2178: def _warn_on_replacement(self, metadata):    Function `_warn_on_replacement` utility
or script function.
L2185: def get_metadata_lines(self, name: str) -> Iterator[str]:    Function
`get_metadata_lines` Returns or fetches data.
L2189: class PathMetadata(DefaultProvider):    Class (`PathMetadata`) component used by the
app (see file context: None).
L2209: def __init__(self, path: str, egg_info: str):    Function `__init__` utility or script
function.
L2214: class EggMetadata(ZipProvider):    Class (`EggMetadata`) component used by the app
(see file context: None).
L2217: def __init__(self, importer: zipimport.zipimporter):    Function `__init__` utility or
script function.
L2234: def register_finder(importer_type: type[_T], distribution_finder:
_DistFinderType[_T]):    Function `register_finder` utility or script function.
L2244: def find_distributions(path_item: str, only: bool = False):    Function
`find_distributions` utility or script function.
L2251: def find_eggs_in_zip(    Function `find_eggs_in_zip` utility or script function.
L2282: def find_nothing(    Function `find_nothing` utility or script function.
L2291: def find_on_path(importer: object | None, path_item, only=False):    Object
(singleton).
L2311: def dist_factory(path_item, entry, only):    Function `dist_factory` utility or script
function.
L2330: class NoDists:    Class (`NoDists`) component used by the app (see file context:
None).
L2339: def __bool__(self):    Function `__bool__` utility or script function.
L2342: def __call__(self, fullpath):    Function `__call__` utility or script function.
L2346: def safe_listdir(path: StrOrBytesPath):    Function `safe_listdir` utility or script
function.
L2362: def distributions_from_metadata(path: str):    Function `distributions_from_metadata`
utility or script function.
L2380: def non_empty_lines(path):    Function `non_empty_lines` utility or script function.
L2390: def resolve_egg_link(path):    Function `resolve_egg_link` utility or script function.
L2416: def register_namespace_handler(    Function `register_namespace_handler` utility or
script function.
L2424: def namespace_handler(importer, path_entry, moduleName, module):    Function
`namespace_handler` utility or script function.
L2436: def _handle_ns(packageName, path_item):    Function `_handle_ns` utility or script
function.
L2473: def _rebuild_mod_path(orig_path, package_name, module: types.ModuleType):    Function
`_rebuild_mod_path` utility or script function.
L2480: def safe_sys_path_index(entry):    Function `safe_sys_path_index` utility or script
function.
L2489: def position_in_sys_path(path):    Function `position_in_sys_path` utility or script
function.
L2507: def declare_namespace(packageName: str):    Function `declare_namespace` utility or
script function.
L2550: def fixup_namespace_packages(path_item: str, parent: str | None = None):    Function
`fixup_namespace_packages` utility or script function.
L2562: def file_ns_handler(    Function `file_ns_handler` utility or script function.

```

```

L2587: def null_ns_handler(    Function `null_ns_handler`    utility or script function.
L2600: def normalize_path(filename: StrPath) -> str: ...    Function `normalize_path`    utility
or script function.
L2602: def normalize_path(filename: BytesPath) -> bytes: ...    Function `normalize_path`
utility or script function.
L2603: def normalize_path(filename: StrOrBytesPath):    Function `normalize_path`    utility or
script function.
L2608: def _cygwin_patch(filename: StrOrBytesPath): # pragma: nocover    Function
`_cygwin_patch`    utility or script function.
L2623: def _normalize_cached(filename: StrPath) -> str: ...    Function `_normalize_cached`
utility or script function.
L2625: def _normalize_cached(filename: BytesPath) -> bytes: ...    Function
`_normalize_cached`    utility or script function.
L2626: def _normalize_cached(filename: StrOrBytesPath) -> str | bytes: ...    Function
`_normalize_cached`    utility or script function.
L2630: def _normalize_cached(filename):    Function `_normalize_cached`    utility or script
function.
L2634: def _is_egg_path(path):    Function `_is_egg_path`    utility or script function.
L2641: def _is_zip_egg(path):    Function `_is_zip_egg`    utility or script function.
L2649: def _is_unpacked_egg(path):    Function `_is_unpacked_egg`    utility or script function.
L2658: def _set_parent_ns(packageName):    Function `_set_parent_ns`    utility or script
function.
L2681: class EntryPoint:    Class (`EntryPoint`)    component used by the app (see file context:
None).
L2684: def __init__(    Function `__init__`    utility or script function.
L2700: def __str__(self):    Function `__str__`    utility or script function.
L2708: def __repr__(self):    Function `__repr__`    utility or script function.
L2712: def load(    Function `load`    Loads data from storage or remote.
L2719: def load(    Function `load`    Loads data from storage or remote.
L2725: def load(    Function `load`    Loads data from storage or remote.
L2747: def resolve(self) -> _ResolvedEntryPoint:    Function `resolve`    utility or script
function.
L2757: def require(    Function `require`    utility or script function.
L2785: def parse(cls, src: str, dist: Distribution | None = None):    Function `parse`
utility or script function.
L2805: def _parse_extras(cls, extras_spec):    Function `_parse_extras`    utility or script
function.
L2814: def parse_group(    Function `parse_group`    utility or script function.
L2832: def parse_map(    Function `parse_map`    utility or script function.
L2856: def _version_from_file(lines):    Function `_version_from_file`    utility or script
function.
L2862: def is_version_line(line):    Function `is_version_line`    utility or script function.
L2871: class Distribution:    Class (`Distribution`)    component used by the app (see file
context: None).
L2876: def __init__(    Function `__init__`    utility or script function.
L2896: def from_location(    Function `from_location`    utility or script function.
L2923: def _reload_version(self):    Function `_reload_version`    utility or script function.
L2927: def hashcmp(self):    Function `hashcmp`    utility or script function.
L2937: def __hash__(self):    Function `__hash__`    utility or script function.
L2940: def __lt__(self, other: Distribution):    Function `__lt__`    utility or script
function.

```

```

L2943: def __le__(self, other: Distribution):    Function `__le__`    utility or script
function.
L2946: def __gt__(self, other: Distribution):    Function `__gt__`    utility or script
function.
L2949: def __ge__(self, other: Distribution):    Function `__ge__`    utility or script
function.
L2952: def __eq__(self, other: object):    Object (singleton).
L2958: def __ne__(self, other: object):    Object (singleton).
L2966: def key(self):    Function `key`    utility or script function.
L2974: def parsed_version(self):    Function `parsed_version`    utility or script function.
L2988: def _forgiving_parsed_version(self):    Function `_forgiving_parsed_version`    utility
or script function.
L3014: def version(self):    Function `version`    utility or script function.
L3029: def _dep_map(self):    Function `_dep_map`    utility or script function.
L3041: def _filter_extras(dm: dict[str | None, list[Requirement]]):    Function
`_filter_extras`    utility or script function.
L3061: def _build_dep_map(self):    Function `_build_dep_map`    utility or script function.
L3068: def requires(self, extras: Iterable[str] = ()):    Function `requires`    utility or
script function.
L3082: def _get_metadata_path_for_display(self, name):    Function
`_get_metadata_path_for_display`    utility or script function.
L3099: def _get_metadata(self, name):    Function `_get_metadata`    utility or script function.
L3103: def _get_version(self):    Function `_get_version`    utility or script function.
L3107: def activate(self, path: list[str] | None = None, replace: bool = False):    Function
`activate`    utility or script function.
L3118: def egg_name(self):    Function `egg_name`    utility or script function.
L3130: def __repr__(self):    Function `__repr__`    utility or script function.
L3136: def __str__(self):    Function `__str__`    utility or script function.
L3144: def __getattr__(self, attr):    Function `__getattr__`    utility or script function.
L3150: def __dir__(self):    Function `__dir__`    utility or script function.
L3157: def from_filename(    Function `from_filename`    utility or script function.
L3167: def as_requirement(self):    Function `as_requirement`    utility or script function.
L3176: def load_entry_point(self, group: str, name: str) -> _ResolvedEntryPoint:    Function
`load_entry_point`    Loads data from storage or remote.
L3184: def get_entry_map(self, group: None = None) -> dict[str, dict[str, EntryPoint]]: ...
Function `get_entry_map`    Returns or fetches data.
L3186: def get_entry_map(self, group: str) -> dict[str, EntryPoint]: ...    Function
`get_entry_map`    Returns or fetches data.
L3187: def get_entry_map(self, group: str | None = None):    Function `get_entry_map`    Returns
or fetches data.
L3197: def get_entry_info(self, group: str, name: str):    Function `get_entry_info`    Returns
or fetches data.
L3202: def insert_on( # noqa: C901    Function `insert_on`    utility or script function.
L3275: def check_version_conflict(self):    Function `check_version_conflict`    utility or
script function.
L3301: def has_version(self):    Function `has_version`    utility or script function.
L3312: def clone(self, **kw: str | int | IResourceProvider | None):    Function `clone`
utility or script function.
L3322: def extras(self):    Function `extras`    utility or script function.
L3326: class EggInfoDistribution(Distribution):    Class (`EggInfoDistribution`)    component
used by the app (see file context: None).

```

```

L3327: def _reload_version(self):    Function `_reload_version` utility or script function.
L3345: class DistInfoDistribution(Distribution):    Class (`DistInfoDistribution`) component
used by the app (see file context: None).
L3355: def _parsed_pkg_info(self):    Function `_parsed_pkg_info` utility or script function.
L3365: def _dep_map(self):    Function `_dep_map` utility or script function.
L3372: def _compute_dependencies(self) -> dict[str | None, list[Requirement]]:    Function
`_compute_dependencies` utility or script function.
L3381: def reqs_for_extra(extra):    Function `reqs_for_extra` utility or script function.
L3405: def issue_warning(*args, **kw):    Function `issue_warning` utility or script
function.
L3418: def parse_requirements(strs: _NestedStr):    Function `parse_requirements` utility or
script function.
L3427: class RequirementParseError(_packaging_requirements.InvalidRequirement):    Class
(`RequirementParseError`) component used by the app (see file context: None).
L3431: class Requirement(_packaging_requirements.Requirement):    Class (`Requirement`)
component used by the app (see file context: None).
L3432: def __init__(self, requirement_string: str):    Function `__init__` utility or script
function.
L3450: def __eq__(self, other: object):    Object (singleton).
L3453: def __ne__(self, other):    Function `__ne__` utility or script function.
L3456: def __contains__(self, item: Distribution | str | tuple[str, ...]) -> bool:    Function
`__contains__` utility or script function.
L3468: def __hash__(self):    Function `__hash__` utility or script function.
L3471: def __repr__(self):    Function `__repr__` utility or script function.
L3475: def parse(s: str | Iterable[str]):    Function `parse` utility or script function.
L3480: def _always_object(classes):    Function `_always_object` utility or script function.
L3490: def _find_adapter(registry: Mapping[type, _AdapterT], ob: object) -> _AdapterT:
Object (singleton).
L3501: def ensure_directory(path: StrOrBytesPath):    Function `ensure_directory` utility or
script function.
L3507: def _bypass_ensure_directory(path):    Function `_bypass_ensure_directory` utility or
script function.
L3520: def split_sections(s: _NestedStr) -> Iterator[tuple[str | None, list[str]]]:
Function `split_sections` utility or script function.
L3546: def _mkstemp(*args, **kw):    Function `_mkstemp` utility or script function.
L3564: class PkgResourcesDeprecationWarning(Warning):    Class
(`PkgResourcesDeprecationWarning`) component used by the app (see file context: None).
L3577: def _read_utf8_with_fallback(file: str, fallback_encoding=_LOCALE_ENCODING) -> str:
Function `_read_utf8_with_fallback` utility or script function.
L3606: def _call_aside(f, *args, **kwargs):    Function `_call_aside` utility or script
function.
L3612: def _initialize(g=globals()):    Function `_initialize` utility or script function.
L3624: def _initialize_master_working_set():    Function `_initialize_master_working_set`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/

controller.py

```

L39: def parse_uri(uri: str) -> tuple[str, str, str, str, str]:    Function `parse_uri`
utility or script function.
L50: class CacheController:    Class (`CacheController`)    component used by the app (see file
context: None).
L53: def __init__(    Function `__init__`    utility or script function.
L66: def _urlnorm(cls, uri: str) -> str:    Function `_urlnorm`    utility or script function.
L86: def cache_url(cls, uri: str) -> str:    Function `cache_url`    utility or script function.
L89: def parse_cache_control(self, headers: Mapping[str, str]) -> dict[str, int | None]:
Function `parse_cache_control`    utility or script function.
L143: def _load_from_cache(self, request: PreparedRequest) -> HTTPResponse | None:    Function
`_load_from_cache`    utility or script function.
L169: def cached_request(self, request: PreparedRequest) -> HTTPResponse | Literal[False]:
Function `cached_request`    utility or script function.
L279: def conditional_headers(self, request: PreparedRequest) -> dict[str, str]:    Function
`conditional_headers`    utility or script function.
L294: def _cache_set(    Function `_cache_set`    utility or script function.
L324: def cache_response(    Function `cache_response`    utility or script function.
L471: def update_cached_response(    Function `update_cached_response`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/_cmd.py

```

L22: def setup_logging() -> None:    Function `setup_logging`    Sets or updates a value.
L28: def get_session() -> requests.Session:    Function `get_session`    Returns or fetches
data.
L40: def get_args() -> Namespace:    Function `get_args`    Returns or fetches data.
L46: def main() -> None:    Function `main`    Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/adapter.py

```

L26: class CacheControlAdapter(HTTPAdapter):    Class (`CacheControlAdapter`)    component used
by the app (see file context: None).
L29: def __init__(    Function `__init__`    utility or script function.
L50: def send(    Function `send`    utility or script function.
L80: def build_response(    # type: ignore[override]    Function `build_response`    Constructs or
prepares an object.
L137: def _update_chunk_length(    Function `_update_chunk_length`    utility or script

```



```
function.
L165: def close(self) -> None:    Function `close`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/ilewrapper.py

```
L15: class CallbackFileWrapper:    Class (`CallbackFileWrapper`)    component used by the app
(see file context: None).
L34: def __init__(    Function `__init__`    utility or script function.
L41: def __getattr__(self, name: str) -> Any:    Function `__getattr__`    utility or script
function.
L53: def __is_fp_closed(self) -> bool:    Function `__is_fp_closed`    utility or script
function.
L71: def _close(self) -> None:    Function `_close`    utility or script function.
L99: def read(self, amt: int | None = None) -> bytes:    Function `read`    utility or script
function.
L110: def _safe_read(self, amt: int) -> bytes:    Function `_safe_read`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/cache.py

```
L19: class BaseCache:    Class (`BaseCache`)    component used by the app (see file context:
None).
L20: def get(self, key: str) -> bytes | None:    Function `get`    Returns or fetches data.
L23: def set(    Function `set`    Sets or updates a value.
L28: def delete(self, key: str) -> None:    Function `delete`    Deletes a resource.
L31: def close(self) -> None:    Function `close`    utility or script function.
L35: class DictCache(BaseCache):    Class (`DictCache`)    component used by the app (see file
context: None).
L36: def __init__(self, init_dict: MutableMapping[str, bytes] | None = None) -> None:
Function `__init__`    utility or script function.
L40: def get(self, key: str) -> bytes | None:    Function `get`    Returns or fetches data.
L43: def set(    Function `set`    Sets or updates a value.
L49: def delete(self, key: str) -> None:    Function `delete`    Deletes a resource.
L55: class SeparateBodyBaseCache(BaseCache):    Class (`SeparateBodyBaseCache`)    component
used by the app (see file context: None).
L68: def set_body(self, key: str, body: bytes) -> None:    Function `set_body`    Sets or
updates a value.
L71: def get_body(self, key: str) -> IO[bytes] | None:    Function `get_body`    Returns or
fetches data.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
wrapper.py**

```
L20: def CacheControl(    Function `CacheControl`    utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/
heuristics.py**

```
L18: def expire_after(delta: timedelta, date: datetime | None = None) -> datetime:    Function
`expire_after`    utility or script function.
L23: def datetime_to_header(dt: datetime) -> str:    Function `datetime_to_header`    utility or
script function.
L27: class BaseHeuristic:    Class (`BaseHeuristic`)    component used by the app (see file
context: None).
L28: def warning(self, response: HTTPResponse) -> str | None:    Function `warning`    utility
or script function.
L39: def update_headers(self, response: HTTPResponse) -> dict[str, str]:    Function
`update_headers`    utility or script function.
L48: def apply(self, response: HTTPResponse) -> HTTPResponse:    Function `apply`    utility or
script function.
L60: class OneDayCache(BaseHeuristic):    Class (`OneDayCache`)    component used by the app
(see file context: None).
L66: def update_headers(self, response: HTTPResponse) -> dict[str, str]:    Function
`update_headers`    utility or script function.
L80: class ExpiresAfter(BaseHeuristic):    Class (`ExpiresAfter`)    component used by the app
(see file context: None).
L85: def __init__(self, **kw: Any) -> None:    Function `__init__`    utility or script
function.
L88: def update_headers(self, response: HTTPResponse) -> dict[str, str]:    Function
`update_headers`    utility or script function.
L92: def warning(self, response: HTTPResponse) -> str | None:    Function `warning`    utility
or script function.
L97: class LastModified(BaseHeuristic):    Class (`LastModified`)    component used by the app
(see file context: None).
L124: def update_headers(self, resp: HTTPResponse) -> dict[str, str]:    Function
`update_headers`    utility or script function.
L156: def warning(self, resp: HTTPResponse) -> str | None:    Function `warning`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/

serialize.py

```
L17: class Serializer:    Class (`Serializer`) component used by the app (see file context:
None).
L20: def dumps(    Function `dumps` utility or script function.
L62: def serialize(self, data: dict[str, Any]) -> bytes:    Function `serialize` utility or
script function.
L65: def loads(    Function `loads` Loads data from storage or remote.
L83: def prepare_response(    Function `prepare_response` utility or script function.
L135: def _loads_v4(    Function `_loads_v4` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/ caches/file_cache.py

```
L22: class _FileCacheMixin:    Class (`_FileCacheMixin`) component used by the app (see file
context: None).
L25: def __init__(    Function `__init__` utility or script function.
L55: def encode(x: str) -> str:    Function `encode` utility or script function.
L58: def _fn(self, name: str) -> str:    Function `_fn` utility or script function.
L65: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L74: def set(    Function `set` Sets or updates a value.
L80: def _write(self, path: str, data: bytes) -> None:    Function `_write` utility or script
function.
L98: def _delete(self, key: str, suffix: str) -> None:    Function `_delete` utility or
script function.
L107: class FileCache(_FileCacheMixin, BaseCache):    Class (`FileCache`) component used by
the app (see file context: None).
L113: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L117: class SeparateBodyFileCache(_FileCacheMixin, SeparateBodyBaseCache):    Class
(`SeparateBodyFileCache`) component used by the app (see file context: None).
L123: def get_body(self, key: str) -> IO[bytes] | None:    Function `get_body` Returns or
fetches data.
L130: def set_body(self, key: str, body: bytes) -> None:    Function `set_body` Sets or
updates a value.
L134: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L139: def url_to_file_path(url: str, filecache: FileCache) -> str:    Function
`url_to_file_path` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/ caches/redis_cache.py

```

L16: class RedisCache(BaseCache):    Class (`RedisCache`) component used by the app (see file
context: None).
L17: def __init__(self, conn: Redis[bytes]) -> None:    Function `__init__` utility or script
function.
L20: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L23: def set(    Function `set` Sets or updates a value.
L37: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L40: def clear(self) -> None:    Function `clear` utility or script function.
L46: def close(self) -> None:    Function `close` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/compat.py

```

L30: def quote(s):    Function `quote` utility or script function.
L93: class CertificateError(ValueError):    Class (`CertificateError`) component used by the
app (see file context: None).
L96: def _dnsname_match(dn, hostname, max_wildcards=1):    Function `_dnsname_match` utility
or script function.
L145: def match_hostname(cert, hostname):    Function `match_hostname` utility or script
function.
L192: class Container(object):    Object (singleton).
L197: def __init__(self, **kwargs):    Function `__init__` utility or script function.
L205: def which(cmd, mode=os.F_OK | os.X_OK, path=None):    Function `which` utility or
script function.
L219: def _access_check(fn, mode):    Function `_access_check` utility or script function.
L277: class ZipExtFile(BaseZipExtFile):    Class (`ZipExtFile`) component used by the app
(see file context: None).
L279: def __init__(self, base):    Function `__init__` utility or script function.
L282: def __enter__(self):    Function `__enter__` utility or script function.
L285: def __exit__(self, *exc_info):    Function `__exit__` utility or script function.
L289: class ZipFile(BaseZipFile):    Class (`ZipFile`) component used by the app (see file
context: None).
L291: def __enter__(self):    Function `__enter__` utility or script function.
L294: def __exit__(self, *exc_info):    Function `__exit__` utility or script function.
L298: def open(self, *args, **kwargs):    Function `open` utility or script function.
L307: def python_implementation():    Function `python_implementation` utility or script
function.
L325: def callable(obj):    Function `callable` utility or script function.
L345: def fsencode(filename):    Function `fsencode` utility or script function.
L354: def fsdecode(filename):    Function `fsdecode` utility or script function.
L371: def _get_normal_name(orig_enc):    Function `_get_normal_name` utility or script
function.
L382: def detect_encoding(readline):    Function `detect_encoding` utility or script
function.
L407: def read_or_stop():    Function `read_or_stop` utility or script function.
L413: def find_cookie(line):    Function `find_cookie` utility or script function.

```

```

L494: def _recursive_repr(fillvalue='...'):  Function `_recursive_repr` utility or script
function.
L500: def decorating_function(user_function):  Function `decorating_function` utility or
script function.
L503: def wrapper(self):  Function `wrapper` utility or script function.
L524: class ChainMap(MutableMapping):  Class (`ChainMap`) component used by the app (see
file context: None).
L537: def __init__(self, *maps):  Function `__init__` utility or script function.
L544: def __missing__(self, key):  Function `__missing__` utility or script function.
L547: def __getitem__(self, key):  Function `__getitem__` utility or script function.
L557: def get(self, key, default=None):  Function `get` Returns or fetches data.
L560: def __len__(self):  Function `__len__` utility or script function.
L564: def __iter__(self):  Function `__iter__` utility or script function.
L567: def __contains__(self, key):  Function `__contains__` utility or script function.
L570: def __bool__(self):  Function `__bool__` utility or script function.
L574: def __repr__(self):  Function `__repr__` utility or script function.
L579: def fromkeys(cls, iterable, *args):  Function `fromkeys` utility or script function.
L583: def copy(self):  Function `copy` utility or script function.
L589: def new_child(self):  # like Django's Context.push()  Function `new_child` utility or
script function.
L594: def parents(self):  # like Django's Context.pop()  Function `parents` utility or
script function.
L598: def __setitem__(self, key, value):  Function `__setitem__` utility or script
function.
L601: def __delitem__(self, key):  Function `__delitem__` utility or script function.
L608: def popitem(self):  Function `popitem` utility or script function.
L615: def pop(self, key, *args):  Function `pop` utility or script function.
L623: def clear(self):  Function `clear` utility or script function.
L632: def cache_from_source(path, debug_override=None):  Function `cache_from_source`
utility or script function.
L659: class OrderedDict(dict):  Class (`OrderedDict`) component used by the app (see file
context: None).
L672: def __init__(self, *args, **kwargs):  Function `__init__` utility or script function.
L689: def __setitem__(self, key, value, dict_setitem=dict.__setitem__):  Function
`__setitem__` utility or script function.
L699: def __delitem__(self, key, dict_delitem=dict.__delitem__):  Function `__delitem__`
utility or script function.
L708: def __iter__(self):  Function `__iter__` utility or script function.
L716: def __reversed__(self):  Function `__reversed__` utility or script function.
L724: def clear(self):  Function `clear` utility or script function.
L736: def popitem(self, last=True):  Function `popitem` utility or script function.
L761: def keys(self):  Function `keys` utility or script function.
L765: def values(self):  Function `values` utility or script function.
L769: def items(self):  Function `items` utility or script function.
L773: def iterkeys(self):  Function `iterkeys` utility or script function.
L777: def itervalues(self):  Function `itervalues` utility or script function.
L782: def iteritems(self):  Function `iteritems` utility or script function.
L787: def update(*args, **kwargs):  Function `update` utility or script function.
L822: def pop(self, key, default=__marker):  Function `pop` utility or script function.
L835: def setdefault(self, key, default=None):  Function `setdefault` Sets or updates a
value.

```

```

L842: def __repr__(self, _repr_running=None):    Function `__repr__` utility or script
function.
L857: def __reduce__(self):    Function `__reduce__` utility or script function.
L867: def copy(self):    Function `copy` utility or script function.
L872: def fromkeys(cls, iterable, value=None):    Function `fromkeys` utility or script
function.
L882: def __eq__(self, other):    Function `__eq__` utility or script function.
L892: def __ne__(self, other):    Function `__ne__` utility or script function.
L897: def viewkeys(self):    Function `viewkeys` utility or script function.
L901: def viewvalues(self):    Function `viewvalues` utility or script function.
L905: def viewitems(self):    Function `viewitems` utility or script function.
L915: def valid_ident(s):    Function `valid_ident` utility or script function.
L930: class ConvertingDict(dict):    Class (`ConvertingDict`) component used by the app (see
file context: None).
L933: def __getitem__(self, key):    Function `__getitem__` utility or script function.
L945: def get(self, key, default=None):    Function `get` Returns or fetches data.
L957: def pop(self, key, default=None):    Function `pop` utility or script function.
L967: class ConvertingList(list):    Class (`ConvertingList`) component used by the app (see
file context: None).
L970: def __getitem__(self, key):    Function `__getitem__` utility or script function.
L982: def pop(self, idx=-1):    Function `pop` utility or script function.
L991: class ConvertingTuple(tuple):    Class (`ConvertingTuple`) component used by the app
(see file context: None).
L994: def __getitem__(self, key):    Function `__getitem__` utility or script function.
L1004: class BaseConfigurator(object):    Object (singleton).
L1024: def __init__(self, config):    Function `__init__` utility or script function.
L1028: def resolve(self, s):    Function `resolve` utility or script function.
L1051: def ext_convert(self, value):    Function `ext_convert` utility or script function.
L1055: def cfg_convert(self, value):    Function `cfg_convert` utility or script function.
L1090: def convert(self, value):    Function `convert` utility or script function.
L1119: def configure_custom(self, config):    Function `configure_custom` utility or script
function.
L1133: def as_tuple(self, value):    Function `as_tuple` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/__init__
.py**

```

L12: class DistlibException(Exception):    Class (`DistlibException`) component used by the
app (see file context: None).
L20: class NullHandler(logging.Handler):    Class (`NullHandler`) component used by the app
(see file context: None).
L22: def handle(self, record):    Function `handle` utility or script function.
L25: def emit(self, record):    Function `emit` utility or script function.
L28: def createLock(self):    Function `createLock` Creates a resource or document.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/scripts.py

```

L71: def enquote_executable(executable):    Function `enquote_executable` utility or script
function.
L91: class ScriptMaker(object):    Object (singleton).
L100: def __init__(self, source_dir, target_dir, add_launchers=True, dry_run=False,
fileop=None):    Function `__init__` utility or script function.
L114: def _get_alternate_executable(self, executable, options):    Function
`_get_alternate_executable` utility or script function.
L123: def _is_shell(self, executable):    Function `_is_shell` utility or script function.
L135: def _fix_jython_executable(self, executable):    Function `_fix_jython_executable`
utility or script function.
L147: def _build_shebang(self, executable, post_interp):    Function `_build_shebang` utility
or script function.
L183: def _get_shebang(self, encoding, post_interp=b'', options=None):    Function
`_get_shebang` utility or script function.
L249: def _get_script_text(self, entry):    Function `_get_script_text` utility or script
function.
L255: def get_manifest(self, exename):    Function `get_manifest` Returns or fetches data.
L259: def _write_script(self, names, shebang, script_bytes, filenames, ext):    Function
`_write_script` utility or script function.
L316: def get_script_filenames(self, name):    Function `get_script_filenames` Returns or
fetches data.
L326: def _make_script(self, entry, filenames, options=None):    Function `_make_script`
utility or script function.
L342: def _copy_script(self, script, filenames):    Function `_copy_script` utility or script
function.
L393: def dry_run(self):    Function `dry_run` utility or script function.
L397: def dry_run(self, value):    Function `dry_run` utility or script function.
L404: def _get_launcher(self, kind):    Function `_get_launcher` utility or script function.
L419: def make(self, specification, options=None):    Function `make` utility or script
function.
L438: def make_multiple(self, specifications, options=None):    Function `make_multiple`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/resources.py

```

L27: class ResourceCache(Cache):    Class (`ResourceCache`) component used by the app (see
file context: None).
L28: def __init__(self, base=None):    Function `__init__` utility or script function.
L34: def is_stale(self, resource, path):    Function `is_stale` utility or script function.

```

```

L45: def get(self, resource):    Function `get`    Returns or fetches data.
L71: class ResourceBase(object):    Object (singleton).
L72: def __init__(self, finder, name):    Function `__init__`    utility or script function.
L77: class Resource(ResourceBase):    Class (`Resource`)    component used by the app (see file
context: None).
L85: def as_stream(self):    Function `as_stream`    utility or script function.
L95: def file_path(self):    Function `file_path`    utility or script function.
L102: def bytes(self):    Function `bytes`    utility or script function.
L106: def size(self):    Function `size`    utility or script function.
L110: class ResourceContainer(ResourceBase):    Class (`ResourceContainer`)    component used by
the app (see file context: None).
L114: def resources(self):    Function `resources`    utility or script function.
L118: class ResourceFinder(object):    Object (singleton).
L128: def __init__(self, module):    Function `__init__`    utility or script function.
L133: def _adjust_path(self, path):    Function `_adjust_path`    utility or script function.
L136: def _make_path(self, resource_name):    Function `_make_path`    utility or script
function.
L148: def _find(self, path):    Function `_find`    utility or script function.
L151: def get_cache_info(self, resource):    Function `get_cache_info`    Returns or fetches
data.
L154: def find(self, resource_name):    Function `find`    utility or script function.
L166: def get_stream(self, resource):    Function `get_stream`    Returns or fetches data.
L169: def get_bytes(self, resource):    Function `get_bytes`    Returns or fetches data.
L173: def get_size(self, resource):    Function `get_size`    Returns or fetches data.
L176: def get_resources(self, resource):    Function `get_resources`    Returns or fetches data.
L177: def allowed(f):    Function `allowed`    utility or script function.
L182: def is_container(self, resource):    Function `is_container`    utility or script
function.
L187: def iterator(self, resource_name):    Function `iterator`    utility or script function.
L208: class ZipResourceFinder(ResourceFinder):    Class (`ZipResourceFinder`)    component used
by the app (see file context: None).
L212: def __init__(self, module):    Function `__init__`    utility or script function.
L223: def _adjust_path(self, path):    Function `_adjust_path`    utility or script function.
L226: def _find(self, path):    Function `_find`    utility or script function.
L244: def get_cache_info(self, resource):    Function `get_cache_info`    Returns or fetches
data.
L249: def get_bytes(self, resource):    Function `get_bytes`    Returns or fetches data.
L252: def get_stream(self, resource):    Function `get_stream`    Returns or fetches data.
L255: def get_size(self, resource):    Function `get_size`    Returns or fetches data.
L259: def get_resources(self, resource):    Function `get_resources`    Returns or fetches data.
L274: def _is_directory(self, path):    Function `_is_directory`    utility or script function.
L306: def register_finder(loader, finder_maker):    Function `register_finder`    utility or
script function.
L313: def finder(package):    Function `finder`    utility or script function.
L341: def finder_for_path(path):    Function `finder_for_path`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/distlib/util.py


```

L54: def parse_marker(marker_string):  Function `parse_marker`  utility or script function.
L64: def marker_var(remaining):  Function `marker_var`  utility or script function.
L100: def marker_expr(remaining):  Function `marker_expr`  utility or script function.
L119: def marker_and(remaining):  Function `marker_and`  utility or script function.
L130: def marker(remaining):  Function `marker`  utility or script function.
L144: def parse_requirement(req):  Function `parse_requirement`  utility or script function.
L196: def get_versions(ver_remaining):  Function `get_versions`  Returns or fetches data.
L268: def get_resources_dests(resources_root, rules):  Function `get_resources_dests`
Returns or fetches data.
L271: def get_rel_path(root, path):  Function `get_rel_path`  Returns or fetches data.
L294: def in_venv():  Function `in_venv`  utility or script function.
L304: def get_executable():  Function `get_executable`  Returns or fetches data.
L322: def proceed(prompt, allowed_chars, error_prompt=None, default=None):  Function
`proceed`  utility or script function.
L338: def extract_by_key(d, keys):  Function `extract_by_key`  utility or script function.
L348: def read_exports(stream):  Function `read_exports`  utility or script function.
L368: def read_stream(cp, stream):  Function `read_stream`  utility or script function.
L395: def write_exports(exports, stream):  Function `write_exports`  utility or script
function.
L415: def tempdir():  Function `tempdir`  utility or script function.
L424: def chdir(d):  Function `chdir`  utility or script function.
L434: def socket_timeout(seconds=15):  Function `socket_timeout`  utility or script
function.
L443: class cached_property(object):  Object (singleton).
L445: def __init__(self, func):  Function `__init__`  utility or script function.
L450: def __get__(self, obj, cls=None):  Function `__get__`  utility or script function.
L459: def convert_path(pathname):  Function `convert_path`  utility or script function.
L486: class FileOperator(object):  Object (singleton).
L488: def __init__(self, dry_run=False):  Function `__init__`  utility or script function.
L493: def _init_record(self):  Function `_init_record`  utility or script function.
L498: def record_as_written(self, path):  Function `record_as_written`  utility or script
function.
L502: def newer(self, source, target):  Function `newer`  utility or script function.
L521: def copy_file(self, infile, outfile, check=True):  Function `copy_file`  utility or
script function.
L538: def copy_stream(self, instream, outfile, encoding=None):  Function `copy_stream`
utility or script function.
L553: def write_binary_file(self, path, data):  Function `write_binary_file`  utility or
script function.
L562: def write_text_file(self, path, data, encoding):  Function `write_text_file`  utility
or script function.
L565: def set_mode(self, bits, mask, files):  Function `set_mode`  Sets or updates a value.
L579: def ensure_dir(self, path):  Function `ensure_dir`  utility or script function.
L591: def byte_compile(self, path, optimize=False, force=False, prefix=None,
hashed_invalidation=False):  Function `byte_compile`  utility or script function.
L610: def ensure_removed(self, path):  Function `ensure_removed`  utility or script
function.
L631: def is_writable(self, path):  Function `is_writable`  utility or script function.
L643: def commit(self):  Function `commit`  utility or script function.
L653: def rollback(self):  Function `rollback`  utility or script function.
L672: def resolve(module_name, dotted_path):  Function `resolve`  utility or script

```

```

function.
L687: class ExportEntry(object):  Object (singleton).
L689: def __init__(self, name, prefix, suffix, flags):  Function `__init__`  utility or
script function.
L696: def value(self):  Function `value`  utility or script function.
L699: def __repr__(self):  # pragma: no cover  Function `__repr__`  utility or script
function.
L702: def __eq__(self, other):  Function `__eq__`  utility or script function.
L720: def get_export_entry(specification):  Function `get_export_entry`  Returns or fetches
data.
L751: def get_cache_base(suffix=None):  Function `get_cache_base`  Returns or fetches data.
L792: def path_to_cache_dir(path, use_abspath=True):  Function `path_to_cache_dir`  utility
or script function.
L809: def ensure_slash(s):  Function `ensure_slash`  utility or script function.
L815: def parse_credentials(netloc):  Function `parse_credentials`  utility or script
function.
L830: def get_process_umask():  Function `get_process_umask`  Returns or fetches data.
L836: def is_string_sequence(seq):  Function `is_string_sequence`  utility or script
function.
L852: def split_filename(filename, project_name=None):  Function `split_filename`  utility
or script function.
L882: def parse_name_and_version(p):  Function `parse_name_and_version`  utility or script
function.
L898: def get_extras(requested, available):  Function `get_extras`  Returns or fetches data.
L926: def _get_external_data(url):  Function `_get_external_data`  utility or script
function.
L950: def get_project_data(name):  Function `get_project_data`  Returns or fetches data.
L957: def get_package_data(name, version):  Function `get_package_data`  Returns or fetches
data.
L963: class Cache(object):  Object (singleton).
L970: def __init__(self, base):  Function `__init__`  utility or script function.
L984: def prefix_to_dir(self, prefix, use_abspath=True):  Function `prefix_to_dir`  utility
or script function.
L990: def clear(self):  Function `clear`  utility or script function.
L1007: class EventMixin(object):  Object (singleton).
L1012: def __init__(self):  Function `__init__`  utility or script function.
L1015: def add(self, event, subscriber, append=True):  Function `add`  utility or script
function.
L1035: def remove(self, event, subscriber):  Function `remove`  utility or script function.
L1047: def get_subscribers(self, event):  Function `get_subscribers`  Returns or fetches
data.
L1054: def publish(self, event, *args, **kwargs):  Function `publish`  utility or script
function.
L1080: class Sequencer(object):  Object (singleton).
L1082: def __init__(self):  Function `__init__`  utility or script function.
L1087: def add_node(self, node):  Function `add_node`  utility or script function.
L1090: def remove_node(self, node, edges=False):  Function `remove_node`  utility or script
function.
L1106: def add(self, pred, succ):  Function `add`  utility or script function.
L1111: def remove(self, pred, succ):  Function `remove`  utility or script function.
L1124: def is_step(self, step):  Function `is_step`  utility or script function.

```

```

L1127: def get_steps(self, final):  Function `get_steps` Returns or fetches data.
L1153: def strong_connections(self):  Function `strong_connections` utility or script
function.
L1163: def strongconnect(node):  Function `strongconnect` utility or script function.
L1205: def dot(self):  Function `dot` utility or script function.
L1224: def unarchive(archive_filename, dest_dir, format=None, check=True):  Function
`unarchive` utility or script function.
L1226: def check_path(path):  Function `check_path` utility or script function.
L1275: def extraction_filter(member, path):  Function `extraction_filter` utility or script
function.
L1292: def zip_dir(directory):  Function `zip_dir` utility or script function.
L1313: class Progress(object):  Object (singleton).
L1316: def __init__(self, minval=0, maxval=100):  Function `__init__` utility or script
function.
L1324: def update(self, curval):  Function `update` utility or script function.
L1334: def increment(self, incr):  Function `increment` utility or script function.
L1338: def start(self):  Function `start` utility or script function.
L1342: def stop(self):  Function `stop` utility or script function.
L1348: def maximum(self):  Function `maximum` utility or script function.
L1352: def percentage(self):  Function `percentage` utility or script function.
L1362: def format_duration(self, duration):  Function `format_duration` utility or script
function.
L1372: def ETA(self):  Function `ETA` utility or script function.
L1391: def speed(self):  Function `speed` utility or script function.
L1412: def iglob(path_glob):  Function `iglob` utility or script function.
L1423: def _iglob(path_glob):  Function `_iglob` utility or script function.
L1458: class HTTPSConnection(httplib.HTTPSConnection):  Class (`HTTPSConnection`) component
used by the app (see file context: None).
L1463: def connect(self):  Function `connect` utility or script function.
L1491: class HTTPSHandler(BaseHTTPSHandler):  Class (`HTTPSHandler`) component used by the
app (see file context: None).
L1493: def __init__(self, ca_certs, check_domain=True):  Function `__init__` utility or
script function.
L1498: def _conn_maker(self, *args, **kwargs):  Function `_conn_maker` utility or script
function.
L1514: def https_open(self, req):  Function `https_open` utility or script function.
L1533: class HTTPSOnlyHandler(HTTPSHandler, HTTPHandler):  Class (`HTTPSOnlyHandler`)
component used by the app (see file context: None).
L1535: def http_open(self, req):  Function `http_open` utility or script function.
L1543: class Transport(xmlrpclib.Transport):  Class (`Transport`) component used by the app
(see file context: None).
L1545: def __init__(self, timeout, use_datetime=0):  Function `__init__` utility or script
function.
L1549: def make_connection(self, host):  Function `make_connection` utility or script
function.
L1559: class SafeTransport(xmlrpclib.SafeTransport):  Class (`SafeTransport`) component
used by the app (see file context: None).
L1561: def __init__(self, timeout, use_datetime=0):  Function `__init__` utility or script
function.
L1565: def make_connection(self, host):  Function `make_connection` utility or script
function.

```

```

L1576: class ServerProxy(xmlrpclib.ServerProxy):  Class (`ServerProxy`)  component used by
the app (see file context: None).
L1578: def __init__(self, uri, **kwargs):  Function `__init__`  utility or script function.
L1601: def _csv_open(fn, mode, **kwargs):  Function `_csv_open`  utility or script function.
L1612: class CSVBase(object):  Object (singleton).
L1619: def __enter__(self):  Function `__enter__`  utility or script function.
L1622: def __exit__(self, *exc_info):  Function `__exit__`  utility or script function.
L1626: class CSVReader(CSVBase):  Class (`CSVReader`)  component used by the app (see file
context: None).
L1628: def __init__(self, **kwargs):  Function `__init__`  utility or script function.
L1639: def __iter__(self):  Function `__iter__`  utility or script function.
L1642: def next(self):  Function `next`  utility or script function.
L1653: class CSVWriter(CSVBase):  Class (`CSVWriter`)  component used by the app (see file
context: None).
L1655: def __init__(self, fn, **kwargs):  Function `__init__`  utility or script function.
L1659: def writerow(self, row):  Function `writerow`  utility or script function.
L1675: class Configurator(BaseConfigurator):  Class (`Configurator`)  component used by the
app (see file context: None).
L1680: def __init__(self, config, base=None):  Function `__init__`  utility or script
function.
L1684: def configure_custom(self, config):  Function `configure_custom`  utility or script
function.
L1686: def convert(o):  Function `convert`  utility or script function.
L1716: def __getitem__(self, key):  Function `__getitem__`  utility or script function.
L1722: def inc_convert(self, value):  Function `inc_convert`  utility or script function.
L1731: class SubprocessMixin(object):  Object (singleton).
L1736: def __init__(self, verbose=False, progress=None):  Function `__init__`  utility or
script function.
L1740: def reader(self, stream, context):  Function `reader`  utility or script function.
L1761: def run_command(self, cmd, **kwargs):  Function `run_command`  utility or script
function.
L1777: def normalize_name(name):  Function `normalize_name`  utility or script function.
L1794: class PyPIRCFile(object):  Object (singleton).
L1799: def __init__(self, fn=None, url=None):  Function `__init__`  utility or script
function.
L1805: def read(self):  Function `read`  utility or script function.
L1858: def update(self, username, password):  Function `update`  utility or script function.
L1871: def _load_pypirc(index):  Function `_load_pypirc`  utility or script function.
L1878: def _store_pypirc(index):  Function `_store_pypirc`  utility or script function.
L1888: def get_host_platform():  Function `get_host_platform`  Returns or fetches data.
L1978: def get_platform():  Function `get_platform`  Returns or fetches data.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_null_file.
py**

```

L5: class NullFile(IO[str]):  Class (`NullFile`)  component used by the app (see file

```

```

context: None).
L6: def close(self) -> None:    Function `close`    utility or script function.
L9: def isatty(self) -> bool:    Function `isatty`    utility or script function.
L12: def read(self, __n: int = 1) -> str:    Function `read`    utility or script function.
L15: def readable(self) -> bool:    Function `readable`    utility or script function.
L18: def readline(self, __limit: int = 1) -> str:    Function `readline`    utility or script
function.
L21: def readlines(self, __hint: int = 1) -> List[str]:    Function `readlines`    utility or
script function.
L24: def seek(self, __offset: int, __whence: int = 1) -> int:    Function `seek`    utility or
script function.
L27: def seekable(self) -> bool:    Function `seekable`    utility or script function.
L30: def tell(self) -> int:    Function `tell`    utility or script function.
L33: def truncate(self, __size: Optional[int] = 1) -> int:    Function `truncate`    utility or
script function.
L36: def writable(self) -> bool:    Function `writable`    utility or script function.
L39: def writelines(self, __lines: Iterable[str]) -> None:    Function `writelines`    utility
or script function.
L42: def __next__(self) -> str:    Function `__next__`    utility or script function.
L45: def __iter__(self) -> Iterator[str]:    Function `__iter__`    utility or script function.
L48: def __enter__(self) -> IO[str]:    Function `__enter__`    utility or script function.
L51: def __exit__(    Function `__exit__`    utility or script function.
L59: def write(self, text: str) -> int:    Function `write`    utility or script function.
L62: def flush(self) -> None:    Function `flush`    utility or script function.
L65: def fileno(self) -> int:    Function `fileno`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/segment.
py**

```

L35: class ControlType(IntEnum):    Class (`ControlType`)    component used by the app (see file
context: None).
L64: class Segment(NamedTuple):    Class (`Segment`)    component used by the app (see file
context: None).
L82: def cell_length(self) -> int:    Function `cell_length`    utility or script function.
L91: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.
L100: def __bool__(self) -> bool:    Function `__bool__`    utility or script function.
L105: def is_control(self) -> bool:    Function `is_control`    utility or script function.
L111: def _split_cells(cls, segment: "Segment", cut: int) -> Tuple["Segment", "Segment"]:
Function `_split_cells`    utility or script function.
L158: def split_cells(self, cut: int) -> Tuple["Segment", "Segment"]:    Function
`split_cells`    utility or script function.
L185: def line(cls) -> "Segment":    Function `line`    utility or script function.
L190: def apply_style(    Function `apply_style`    utility or script function.
L231: def filter_control(    Function `filter_control`    utility or script function.
L250: def split_lines(cls, segments: Iterable["Segment"]) -> Iterable[List["Segment"]]:

```

```

Function `split_lines` utility or script function.
L279: def split_and_crop_lines( Function `split_and_crop_lines` utility or script
function.
L326: def adjust_line_length( Function `adjust_line_length` utility or script function.
L371: def get_line_length(cls, line: List["Segment"]) -> int: Function `get_line_length`
Returns or fetches data.
L384: def get_shape(cls, lines: List[List["Segment"]]) -> Tuple[int, int]: Function
`get_shape` Returns or fetches data.
L398: def set_shape( Function `set_shape` Sets or updates a value.
L434: def align_top( Function `align_top` utility or script function.
L463: def align_bottom( Function `align_bottom` utility or script function.
L492: def align_middle( Function `align_middle` utility or script function.
L523: def simplify(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]: Function
`simplify` utility or script function.
L550: def strip_links(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]: Function
`strip_links` utility or script function.
L567: def strip_styles(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]: Function
`strip_styles` utility or script function.
L580: def remove_color(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]: Function
`remove_color` utility or script function.
L602: def divide( Function `divide` utility or script function.
L671: class Segments: Class (`Segments`) component used by the app (see file context:
None).
L680: def __init__(self, segments: Iterable[Segment], new_lines: bool = False) -> None:
Function `__init__` utility or script function.
L684: def __rich_console__( Function `__rich_console__` utility or script function.
L696: class SegmentLines: Class (`SegmentLines`) component used by the app (see file
context: None).
L697: def __init__(self, lines: Iterable[List[Segment]], new_lines: bool = False) -> None:
Function `__init__` utility or script function.
L708: def __rich_console__( Function `__rich_console__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/emoji.py

```

L18: class NoEmoji(Exception): Class (`NoEmoji`) component used by the app (see file
context: None).
L22: class Emoji(JupyterMixin): Class (`Emoji`) component used by the app (see file
context: None).
L27: def __init__( Function `__init__` utility or script function.
L53: def replace(cls, text: str) -> str: Function `replace` utility or script function.
L64: def __repr__(self) -> str: Function `__repr__` utility or script function.
L67: def __str__(self) -> str: Function `__str__` utility or script function.
L70: def __rich_console__( Function `__rich_console__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/styled.py

```

L11: class Styled:    Class (`Styled`)    component used by the app (see file context: None).
L19: def __init__(self, renderable: "RenderableType", style: "StyleType") -> None:    Function
`__init__`    utility or script function.
L23: def __rich_console__(    Function `__rich_console__`    utility or script function.
L31: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_log_render.py**

```

L14: class LogRender:    Class (`LogRender`)    component used by the app (see file context:
None).
L15: def __init__(    Function `__init__`    utility or script function.
L32: def __call__(    Function `__call__`    utility or script function.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/constrain.py**

```

L10: class Constrain(JupyterMixin):    Class (`Constrain`)    component used by the app (see
file context: None).
L18: def __init__(self, renderable: "RenderableType", width: Optional[int] = 80) -> None:
Function `__init__`    utility or script function.
L22: def __rich_console__(    Function `__rich_console__`    utility or script function.
L31: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/tree.py**

```

L14: class Tree(JupyterMixin):    Class (`Tree`)    component used by the app (see file context:
None).
L37: def __init__(    Function `__init__`    utility or script function.
L55: def add(    Function `add`    utility or script function.
L86: def __rich_console__(    Function `__rich_console__`    utility or script function.
L101: def make_guide(index: int, style: Style) -> Segment:    Function `make_guide`    utility
or script function.
L176: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L223: class Segment(NamedTuple):    Class (`Segment`)    component used by the app (see file

```

```
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/protocol.py

```
L10: def is_renderable(check_object: Any) -> bool:    Function `is_renderable` utility or
script function.
L19: def rich_cast(renderable: object) -> "RenderableType":    Object (singleton).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/syntax.py

```
L124: class SyntaxTheme(ABC):    Class (`SyntaxTheme`) component used by the app (see file
context: None).
L128: def get_style_for_token(self, token_type: TokenType) -> Style:    Function
`get_style_for_token` Returns or fetches data.
L133: def get_background_style(self) -> Style:    Function `get_background_style` Returns or
fetches data.
L138: class PygmentsSyntaxTheme(SyntaxTheme):    Class (`PygmentsSyntaxTheme`) component used
by the app (see file context: None).
L141: def __init__(self, theme: Union[str, Type[PygmentsStyle]]) -> None:    Function
`__init__` utility or script function.
L154: def get_style_for_token(self, token_type: TokenType) -> Style:    Function
`get_style_for_token` Returns or fetches data.
L176: def get_background_style(self) -> Style:    Function `get_background_style` Returns or
fetches data.
L180: class ANSISyntaxTheme(SyntaxTheme):    Class (`ANSISyntaxTheme`) component used by the
app (see file context: None).
L183: def __init__(self, style_map: Dict[TokenType, Style]) -> None:    Function `__init__`
utility or script function.
L189: def get_style_for_token(self, token_type: TokenType) -> Style:    Function
`get_style_for_token` Returns or fetches data.
L209: def get_background_style(self) -> Style:    Function `get_background_style` Returns or
fetches data.
L216: class _SyntaxHighlightRange(NamedTuple):    Class (`_SyntaxHighlightRange`) component
used by the app (see file context: None).
L229: class PaddingProperty:    Class (`PaddingProperty`) component used by the app (see file
context: None).
L232: def __get__(self, obj: Syntax, objtype: Type[Syntax]) -> Tuple[int, int, int, int]:
Function `__get__` utility or script function.
L236: def __set__(self, obj: Syntax, padding: PaddingDimensions) -> None:    Function
`__set__` utility or script function.
L240: class Syntax(JupyterMixin):    Class (`Syntax`) component used by the app (see file
```



```

context: None).
L265: def get_theme(cls, name: Union[str, SyntaxTheme]) -> SyntaxTheme:    Function
`get_theme` Returns or fetches data.
L276: def __init__(    Function `__init__` utility or script function.
L317: def from_path(    Function `from_path` utility or script function.
L380: def guess_lexer(cls, path: str, code: Optional[str] = None) -> str:    Function
`guess_lexer` utility or script function.
L421: def _get_base_style(self) -> Style:    Function `_get_base_style` utility or script
function.
L426: def _get_token_color(self, token_type: TokenType) -> Optional[Color]:    Function
`_get_token_color` utility or script function.
L439: def lexer(self) -> Optional[Lexer]:    Function `lexer` utility or script function.
L458: def default_lexer(self) -> Lexer:    Function `default_lexer` utility or script
function.
L467: def highlight(    Function `highlight` utility or script function.
L505: def line_tokenize() -> Iterable[Tuple[Any, str]]:    Function `line_tokenize` utility
or script function.
L514: def tokens_to_spans() -> Iterable[Tuple[str, Optional[Style]]]:    Function
`tokens_to_spans` utility or script function.
L552: def stylize_range(    Function `stylize_range` utility or script function.
L573: def _get_line_numbers_color(self, blend: float = 0.3) -> Color:    Function
`_get_line_numbers_color` utility or script function.
L589: def _numbers_column_width(self) -> int:    Function `_numbers_column_width` utility or
script function.
L599: def _get_number_styles(self, console: Console) -> Tuple[Style, Style, Style]:
Function `_get_number_styles` utility or script function.
L622: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L640: def __rich_console__(    Function `__rich_console__` utility or script function.
L649: def _get_syntax(    Function `_get_syntax` utility or script function.
L787: def _apply_stylized_ranges(self, text: Text) -> None:    Function
`_apply_stylized_ranges` utility or script function.
L820: def _process_code(self, code: str) -> Tuple[bool, str]:    Function `_process_code`
utility or script function.
L841: def _get_code_index_for_syntax_position(    Function
`_get_code_index_for_syntax_position` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_extension
n.py**

```

L4: def load_ipython_extension(ip: Any) -> None:    # pragma: no cover    Function
`load_ipython_extension` Loads data from storage or remote.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/control.py

```

L48: class Control:  Class (`Control`) component used by the app (see file context: None).
L58: def __init__(self, *codes: Union[ControlType, ControlCode]) -> None:  Function
`__init__` utility or script function.
L69: def bell(cls) -> "Control":  Function `bell` utility or script function.
L74: def home(cls) -> "Control":  Function `home` utility or script function.
L79: def move(cls, x: int = 0, y: int = 0) -> "Control":  Function `move` utility or script
function.
L91: def get_codes() -> Iterable[ControlCode]:  Function `get_codes` Returns or fetches
data.
L108: def move_to_column(cls, x: int, y: int = 0) -> "Control":  Function `move_to_column`
utility or script function.
L132: def move_to(cls, x: int, y: int) -> "Control":  Function `move_to` utility or script
function.
L145: def clear(cls) -> "Control":  Function `clear` utility or script function.
L150: def show_cursor(cls, show: bool) -> "Control":  Function `show_cursor` utility or
script function.
L155: def alt_screen(cls, enable: bool) -> "Control":  Function `alt_screen` utility or
script function.
L163: def title(cls, title: str) -> "Control":  Function `title` utility or script
function.
L171: def __str__(self) -> str:  Function `__str__` utility or script function.
L174: def __rich_console__(  Function `__rich_console__` utility or script function.
L181: def strip_control_codes(  Function `strip_control_codes` utility or script function.
L195: def escape_control_codes(  Function `escape_control_codes` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/status.py

```

L11: class Status(JupyterMixin):  Class (`Status`) component used by the app (see file
context: None).
L23: def __init__(  Function `__init__` utility or script function.
L45: def renderable(self) -> Spinner:  Function `renderable` utility or script function.
L49: def console(self) -> "Console":  Function `console` utility or script function.
L53: def update(  Function `update` utility or script function.
L85: def start(self) -> None:  Function `start` utility or script function.
L89: def stop(self) -> None:  Function `stop` utility or script function.
L93: def __rich__(self) -> RenderableType:  Function `__rich__` utility or script function.
L96: def __enter__(self) -> "Status":  Function `__enter__` utility or script function.
L100: def __exit__(  Function `__exit__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/color_triplet.py

```

L4: class ColorTriplet(NamedTuple):  Class (`ColorTriplet`)  component used by the app (see
file context: None).
L15: def hex(self) -> str:  Function `hex`  utility or script function.
L21: def rgb(self) -> str:  Function `rgb`  utility or script function.
L31: def normalized(self) -> Tuple[float, float, float]:  Function `normalized`  utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress.py

```

L64: class _TrackThread(Thread):  Class (`_TrackThread`)  component used by the app (see
file context: None).
L67: def __init__(self, progress: "Progress", task_id: "TaskID", update_period: float):
Function `__init__`  utility or script function.
L76: def run(self) -> None:  Function `run`  utility or script function.
L90: def __enter__(self) -> "_TrackThread":  Function `__enter__`  utility or script
function.
L94: def __exit__(  Function `__exit__`  utility or script function.
L104: def track(  Function `track`  utility or script function.
L182: class _Reader(RawIOBase, BinaryIO):  Class (`_Reader`)  component used by the app (see
file context: None).
L185: def __init__(  Function `__init__`  utility or script function.
L198: def __enter__(self) -> "_Reader":  Function `__enter__`  utility or script function.
L202: def __exit__(  Function `__exit__`  utility or script function.
L210: def __iter__(self) -> BinaryIO:  Function `__iter__`  utility or script function.
L213: def __next__(self) -> bytes:  Function `__next__`  utility or script function.
L219: def closed(self) -> bool:  Function `closed`  utility or script function.
L222: def fileno(self) -> int:  Function `fileno`  utility or script function.
L225: def isatty(self) -> bool:  Function `isatty`  utility or script function.
L229: def mode(self) -> str:  Function `mode`  utility or script function.
L233: def name(self) -> str:  Function `name`  utility or script function.
L236: def readable(self) -> bool:  Function `readable`  utility or script function.
L239: def seekable(self) -> bool:  Function `seekable`  utility or script function.
L242: def writable(self) -> bool:  Function `writable`  utility or script function.
L245: def read(self, size: int = -1) -> bytes:  Function `read`  utility or script function.
L250: def readinto(self, b: Union[bytearray, memoryview, mmap]):  # type:
ignore[no-untyped-def, override]  Function `readinto`  utility or script function.
L255: def readline(self, size: int = -1) -> bytes:  # type: ignore[override]  Function
`readline`  utility or script function.
L260: def readlines(self, hint: int = -1) -> List[bytes]:  Function `readlines`  utility or
script function.
L265: def close(self) -> None:  Function `close`  utility or script function.
L270: def seek(self, offset: int, whence: int = 0) -> int:  Function `seek`  utility or
script function.
L275: def tell(self) -> int:  Function `tell`  utility or script function.
L278: def write(self, s: Any) -> int:  Function `write`  utility or script function.

```

```

L281: def writelines(self, lines: Iterable[Any]) -> None:    Function `writelines` utility or
script function.
L285: class _ReadContext(ContextManager[_I], Generic[_I]):    Class (`_ReadContext`)
component used by the app (see file context: None).
L288: def __init__(self, progress: "Progress", reader: _I) -> None:    Function `__init__`
utility or script function.
L292: def __enter__(self) -> _I:    Function `__enter__` utility or script function.
L296: def __exit__(    Function `__exit__` utility or script function.
L306: def wrap_file(    Function `wrap_file` utility or script function.
L372: def open(    Function `open` utility or script function.
L397: def open(    Function `open` utility or script function.
L421: def open(    Function `open` utility or script function.
L507: class ProgressColumn(ABC):    Class (`ProgressColumn`) component used by the app (see
file context: None).
L512: def __init__(self, table_column: Optional[Column] = None) -> None:    Function
`__init__` utility or script function.
L517: def get_table_column(self) -> Column:    Function `get_table_column` Returns or fetches
data.
L521: def __call__(self, task: "Task") -> RenderableType:    Function `__call__` utility or
script function.
L545: def render(self, task: "Task") -> RenderableType:    Function `render` utility or
script function.
L549: class RenderableColumn(ProgressColumn):    Class (`RenderableColumn`) component used by
the app (see file context: None).
L556: def __init__(    Function `__init__` utility or script function.
L562: def render(self, task: "Task") -> RenderableType:    Function `render` utility or
script function.
L566: class SpinnerColumn(ProgressColumn):    Class (`SpinnerColumn`) component used by the
app (see file context: None).
L576: def __init__(    Function `__init__` utility or script function.
L592: def set_spinner(    Function `set_spinner` Sets or updates a value.
L607: def render(self, task: "Task") -> RenderableType:    Function `render` utility or
script function.
L616: class TextColumn(ProgressColumn):    Class (`TextColumn`) component used by the app
(see file context: None).
L619: def __init__(    Function `__init__` utility or script function.
L635: def render(self, task: "Task") -> Text:    Function `render` utility or script
function.
L646: class BarColumn(ProgressColumn):    Class (`BarColumn`) component used by the app (see
file context: None).
L657: def __init__(    Function `__init__` utility or script function.
L673: def render(self, task: "Task") -> ProgressBar:    Function `render` utility or script
function.
L688: class TimeElapsedColumn(ProgressColumn):    Class (`TimeElapsedColumn`) component used
by the app (see file context: None).
L691: def render(self, task: "Task") -> Text:    Function `render` utility or script
function.
L700: class TaskProgressColumn(TextColumn):    Class (`TaskProgressColumn`) component used by
the app (see file context: None).
L714: def __init__(    Function `__init__` utility or script function.
L737: def render_speed(cls, speed: Optional[float]) -> Text:    Function `render_speed`

```

```

utility or script function.
L756: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L772: class TimeRemainingColumn(ProgressColumn):    Class (`TimeRemainingColumn`)    component
used by the app (see file context: None).
L783: def __init__(    Function `__init__`    utility or script function.
L793: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L820: class FileSizeColumn(ProgressColumn):    Class (`FileSizeColumn`)    component used by the
app (see file context: None).
L823: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L829: class TotalFileSizeColumn(ProgressColumn):    Class (`TotalFileSizeColumn`)    component
used by the app (see file context: None).
L832: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L838: class MofNCompleteColumn(ProgressColumn):    Class (`MofNCompleteColumn`)    component
used by the app (see file context: None).
L850: def __init__(self, separator: str = "/", table_column: Optional[Column] = None):
Function `__init__`    utility or script function.
L854: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L865: class DownloadColumn(ProgressColumn):    Class (`DownloadColumn`)    component used by the
app (see file context: None).
L872: def __init__(    Function `__init__`    utility or script function.
L878: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L914: class TransferSpeedColumn(ProgressColumn):    Class (`TransferSpeedColumn`)    component
used by the app (see file context: None).
L917: def render(self, task: "Task") -> Text:    Function `render`    utility or script
function.
L926: class ProgressSample(NamedTuple):    Class (`ProgressSample`)    component used by the app
(see file context: None).
L936: class Task:    Class (`Task`)    component used by the app (see file context: None).
L983: def get_time(self) -> float:    Function `get_time`    Returns or fetches data.
L988: def started(self) -> bool:    Function `started`    utility or script function.
L993: def remaining(self) -> Optional[float]:    Function `remaining`    utility or script
function.
L1000: def elapsed(self) -> Optional[float]:    Function `elapsed`    utility or script
function.
L1009: def finished(self) -> bool:    Function `finished`    utility or script function.
L1014: def percentage(self) -> float:    Function `percentage`    utility or script function.
L1023: def speed(self) -> Optional[float]:    Function `speed`    utility or script function.
L1041: def time_remaining(self) -> Optional[float]:    Function `time_remaining`    utility or
script function.
L1054: def _reset(self) -> None:    Function `_reset`    utility or script function.
L1061: class Progress(JupyterMixin):    Class (`Progress`)    component used by the app (see
file context: None).
L1077: def __init__(    Function `__init__`    utility or script function.
L1114: def get_default_columns(cls) -> Tuple[ProgressColumn, ...]:    Function
`get_default_columns`    Returns or fetches data.

```

```

L1145: def console(self) -> Console:    Function `console` utility or script function.
L1149: def tasks(self) -> List[Task]:    Function `tasks` utility or script function.
L1155: def task_ids(self) -> List[TaskID]: Function `task_ids` utility or script function.
L1161: def finished(self) -> bool:      Function `finished` utility or script function.
L1168: def start(self) -> None:         Function `start` utility or script function.
L1173: def stop(self) -> None:         Function `stop` utility or script function.
L1179: def __enter__(self) -> Self:     Function `__enter__` utility or script function.
L1183: def __exit__(    Function `__exit__` utility or script function.
L1191: def track(    Function `track` utility or script function.
L1236: def wrap_file(    Function `wrap_file` utility or script function.
L1279: def open(    Function `open` utility or script function.
L1295: def open(    Function `open` utility or script function.
L1310: def open(    Function `open` utility or script function.
L1387: def start_task(self, task_id: TaskID) -> None:    Function `start_task` utility or
script function.
L1401: def stop_task(self, task_id: TaskID) -> None:    Function `stop_task` utility or
script function.
L1416: def update(    Function `update` utility or script function.
L1477: def reset(    Function `reset` utility or script function.
L1516: def advance(self, task_id: TaskID, advance: float = 1) -> None:    Function `advance`
utility or script function.
L1546: def refresh(self) -> None:      Function `refresh` utility or script function.
L1551: def get_renderable(self) -> RenderableType:    Function `get_renderable` Returns or
fetches data.
L1556: def get_renderables(self) -> Iterable[RenderableType]:    Function `get_renderables`
Returns or fetches data.
L1561: def make_tasks_table(self, tasks: Iterable[Task]) -> Table:    Function
`make_tasks_table` utility or script function.
L1594: def __rich__(self) -> RenderableType:    Function `__rich__` utility or script
function.
L1599: def add_task(    Function `add_task` utility or script function.
L1642: def remove_task(self, task_id: TaskID) -> None:    Function `remove_task` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/cells.py

```

L34: def cached_cell_len(text: str) -> int:    Function `cached_cell_len` utility or script
function.
L51: def cell_len(text: str, _cell_len: Callable[[str], int] = cached_cell_len) -> int:
Function `cell_len` utility or script function.
L68: def get_character_cell_size(character: str) -> int:    Function `get_character_cell_size`
Returns or fetches data.
L96: def set_cell_size(text: str, total: int) -> str:    Function `set_cell_size` Sets or
updates a value.
L131: def chop_cells(    Function `chop_cells` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/prompt.py

```

L11: class PromptError(Exception):    Class (`PromptError`)    component used by the app (see
file context: None).
L15: class InvalidResponse(PromptError):    Class (`InvalidResponse`)    component used by the
app (see file context: None).
L23: def __init__(self, message: TextType) -> None:    Function `__init__`    utility or script
function.
L26: def __rich__(self) -> TextType:    Function `__rich__`    utility or script function.
L30: class PromptBase(Generic[PromptType]):    Class (`PromptBase`)    component used by the app
(see file context: None).
L54: def __init__(    Function `__init__`    utility or script function.
L80: def ask(    Function `ask`    utility or script function.
L97: def ask(    Function `ask`    utility or script function.
L112: def ask(    Function `ask`    utility or script function.
L151: def render_default(self, default: DefaultType) -> Text:    Function `render_default`
utility or script function.
L162: def make_prompt(self, default: DefaultType) -> Text:    Function `make_prompt`    utility
or script function.
L194: def get_input(    Function `get_input`    Returns or fetches data.
L213: def check_choice(self, value: str) -> bool:    Function `check_choice`    utility or
script function.
L227: def process_response(self, value: str) -> PromptType:    Function `process_response`
utility or script function.
L258: def on_validate_error(self, value: str, error: InvalidResponse) -> None:    Function
`on_validate_error`    utility or script function.
L267: def pre_prompt(self) -> None:    Function `pre_prompt`    utility or script function.
L271: def __call__(self, *, stream: Optional[TextIO] = None) -> PromptType:    Function
`__call__`    utility or script function.
L275: def __call__(    Function `__call__`    utility or script function.
L280: def __call__(self, *, default: Any = ..., stream: Optional[TextIO] = None) -> Any:
Function `__call__`    utility or script function.
L304: class Prompt(PromptBase[str]):    Class (`Prompt`)    component used by the app (see file
context: None).
L316: class IntPrompt(PromptBase[int]):    Class (`IntPrompt`)    component used by the app (see
file context: None).
L328: class FloatPrompt(PromptBase[float]):    Class (`FloatPrompt`)    component used by the
app (see file context: None).
L340: class Confirm(PromptBase[bool]):    Class (`Confirm`)    component used by the app (see
file context: None).
L353: def render_default(self, default: DefaultType) -> Text:    Function `render_default`
utility or script function.
L358: def process_response(self, value: str) -> bool:    Function `process_response`    utility
or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/box.py

```

L10: class Box:    Class (`Box`)    component used by the app (see file context: None).
L27: def __init__(self, box: str, *, ascii: bool = False) -> None:    Function `__init__`
utility or script function.
L61: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L64: def __str__(self) -> str:    Function `__str__`    utility or script function.
L67: def substitute(self, options: "ConsoleOptions", safe: bool = True) -> "Box":    Function
`substitute`    utility or script function.
L85: def get_plain_headed_box(self) -> "Box":    Function `get_plain_headed_box`    Returns or
fetches data.
L95: def get_top(self, widths: Iterable[int]) -> str:    Function `get_top`    Returns or
fetches data.
L115: def get_row(    Function `get_row`    Returns or fetches data.
L164: def get_bottom(self, widths: Iterable[int]) -> str:    Function `get_bottom`    Returns or
fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/scope.py

```

L14: def render_scope(    Function `render_scope`    utility or script function.
L41: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:    Function `sort_items`
utility or script function.
L75: def test(foo: float, bar: float) -> None:    Function `test`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_emoji_replace.py

```

L12: def _emoji_replace(    Function `_emoji_replace`    utility or script function.
L23: def do_replace(match: Match[str]) -> str:    Function `do_replace`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/console.py

```

L79: class NoChange:    Class (`NoChange`)    component used by the app (see file context:
None).

```



```

L109: class ConsoleDimensions(NamedTuple):  Class (`ConsoleDimensions`)  component used by
the app (see file context: None).
L119: class ConsoleOptions:  Class (`ConsoleOptions`)  component used by the app (see file
context: None).
L149: def ascii_only(self) -> bool:  Function `ascii_only`  utility or script function.
L153: def copy(self) -> "ConsoleOptions":  Function `copy`  utility or script function.
L163: def update(  Function `update`  utility or script function.
L200: def update_width(self, width: int) -> "ConsoleOptions":  Function `update_width`
utility or script function.
L213: def update_height(self, height: int) -> "ConsoleOptions":  Function `update_height`
utility or script function.
L226: def reset_height(self) -> "ConsoleOptions":  Function `reset_height`  utility or
script function.
L236: def update_dimensions(self, width: int, height: int) -> "ConsoleOptions":  Function
`update_dimensions`  utility or script function.
L253: class RichCast(Protocol):  Class (`RichCast`)  component used by the app (see file
context: None).
L256: def __rich__(  Function `__rich__`  utility or script function.
L263: class ConsoleRenderable(Protocol):  Class (`ConsoleRenderable`)  component used by the
app (see file context: None).
L266: def __rich_console__(  Function `__rich_console__`  utility or script function.
L282: class CaptureError(Exception):  Class (`CaptureError`)  component used by the app (see
file context: None).
L286: class NewLine:  Class (`NewLine`)  component used by the app (see file context: None).
L289: def __init__(self, count: int = 1) -> None:  Function `__init__`  utility or script
function.
L292: def __rich_console__(  Function `__rich_console__`  utility or script function.
L298: class ScreenUpdate:  Class (`ScreenUpdate`)  component used by the app (see file
context: None).
L301: def __init__(self, lines: List[List[Segment]], x: int, y: int) -> None:  Function
`__init__`  utility or script function.
L306: def __rich_console__(  Function `__rich_console__`  utility or script function.
L316: class Capture:  Class (`Capture`)  component used by the app (see file context: None).
L324: def __init__(self, console: "Console") -> None:  Function `__init__`  utility or
script function.
L328: def __enter__(self) -> "Capture":  Function `__enter__`  utility or script function.
L332: def __exit__(  Function `__exit__`  utility or script function.
L340: def get(self) -> str:  Function `get`  Returns or fetches data.
L349: class ThemeContext:  Class (`ThemeContext`)  component used by the app (see file
context: None).
L352: def __init__(self, console: "Console", theme: Theme, inherit: bool = True) -> None:
Function `__init__`  utility or script function.
L357: def __enter__(self) -> "ThemeContext":  Function `__enter__`  utility or script
function.
L361: def __exit__(  Function `__exit__`  utility or script function.
L370: class PagerContext:  Class (`PagerContext`)  component used by the app (see file
context: None).
L373: def __init__(  Function `__init__`  utility or script function.
L385: def __enter__(self) -> "PagerContext":  Function `__enter__`  utility or script
function.
L389: def __exit__(  Function `__exit__`  utility or script function.

```

```

L409: class ScreenContext:  Class (`ScreenContext`)  component used by the app (see file
context: None).
L412: def __init__(  Function `__init__`  utility or script function.
L420: def update(  Function `update`  utility or script function.
L438: def __enter__(self) -> "ScreenContext":  Function `__enter__`  utility or script
function.
L444: def __exit__(  Function `__exit__`  utility or script function.
L456: class Group:  Class (`Group`)  component used by the app (see file context: None).
L464: def __init__(self, *renderables: "RenderableType", fit: bool = True) -> None:
Function `__init__`  utility or script function.
L470: def renderables(self) -> List["RenderableType"]:  Function `renderables`  utility or
script function.
L475: def __rich_measure__(  Function `__rich_measure__`  utility or script function.
L483: def __rich_console__(  Function `__rich_console__`  utility or script function.
L489: def group(fit: bool = True) -> Callable[..., Callable[..., Group]]:  Function `group`
utility or script function.
L496: def decorator(  Function `decorator`  utility or script function.
L502: def _replace(*args: Any, **kwargs: Any) -> Group:  Function `_replace`  utility or
script function.
L511: def _is_jupyter() -> bool:  # pragma: no cover  Function `_is_jupyter`  utility or
script function.
L542: class ConsoleThreadLocals(threading.local):  Class (`ConsoleThreadLocals`)  component
used by the app (see file context: None).
L550: class RenderHook(ABC):  Class (`RenderHook`)  component used by the app (see file
context: None).
L554: def process_renderables(  Function `process_renderables`  utility or script function.
L572: def get_windows_console_features() -> "WindowsConsoleFeatures":  # pragma: no cover
Function `get_windows_console_features`  Returns or fetches data.
L582: def detect_legacy_windows() -> bool:  Function `detect_legacy_windows`  utility or
script function.
L587: class Console:  Class (`Console`)  component used by the app (see file context: None).
L625: def __init__(  Function `__init__`  utility or script function.
L759: def __repr__(self) -> str:  Function `__repr__`  utility or script function.
L763: def file(self) -> IO[str]:  Function `file`  utility or script function.
L772: def file(self, new_file: IO[str]) -> None:  Function `file`  utility or script
function.
L777: def _buffer(self) -> List[Segment]:  Function `_buffer`  utility or script function.
L782: def _buffer_index(self) -> int:  Function `_buffer_index`  utility or script function.
L787: def _buffer_index(self, value: int) -> None:  Function `_buffer_index`  utility or
script function.
L791: def _theme_stack(self) -> ThemeStack:  Function `_theme_stack`  utility or script
function.
L795: def _detect_color_system(self) -> Optional[ColorSystem]:  Function
`_detect_color_system`  utility or script function.
L819: def _enter_buffer(self) -> None:  Function `_enter_buffer`  utility or script
function.
L823: def _exit_buffer(self) -> None:  Function `_exit_buffer`  utility or script function.
L828: def set_live(self, live: "Live") -> bool:  Function `set_live`  Sets or updates a
value.
L844: def clear_live(self) -> None:  Function `clear_live`  utility or script function.
L849: def push_render_hook(self, hook: RenderHook) -> None:  Function `push_render_hook`

```

utility or script function.

L858: def pop_render_hook(self) -> None: Function `pop\_render\_hook` utility or script function.

L863: def __enter__(self) -> "Console": Function `\_\_enter\_\_` utility or script function.

L868: def __exit__(self, exc_type: Any, exc_value: Any, traceback: Any) -> None: Function `\_\_exit\_\_` utility or script function.

L872: def begin_capture(self) -> None: Function `begin\_capture` utility or script function.

L876: def end_capture(self) -> str: Function `end\_capture` utility or script function.

L887: def push_theme(self, theme: Theme, *, inherit: bool = True) -> None: Function `push\_theme` utility or script function.

L898: def pop_theme(self) -> None: Function `pop\_theme` utility or script function.

L902: def use_theme(self, theme: Theme, *, inherit: bool = True) -> ThemeContext: Function `use\_theme` utility or script function.

L915: def color_system(self) -> Optional[str]: Function `color\_system` utility or script function.

L928: def encoding(self) -> str: Function `encoding` utility or script function.

L937: def is_terminal(self) -> bool: Function `is\_terminal` utility or script function.

L985: def is_dumb_terminal(self) -> bool: Function `is\_dumb\_terminal` utility or script function.

L997: def options(self) -> ConsoleOptions: Function `options` utility or script function.

L1011: def size(self) -> ConsoleDimensions: Function `size` utility or script function.

L1052: def size(self, new_size: Tuple[int, int]) -> None: Function `size` utility or script function.

L1063: def width(self) -> int: Function `width` utility or script function.

L1072: def width(self, width: int) -> None: Function `width` utility or script function.

L1081: def height(self) -> int: Function `height` utility or script function.

L1090: def height(self, height: int) -> None: Function `height` utility or script function.

L1098: def bell(self) -> None: Function `bell` utility or script function.

L1102: def capture(self) -> Capture: Function `capture` utility or script function.

L1119: def pager(Function `pager` utility or script function.

L1142: def line(self, count: int = 1) -> None: Function `line` utility or script function.

L1152: def clear(self, home: bool = True) -> None: Function `clear` utility or script function.

L1163: def status(Function `status` utility or script function.

L1196: def show_cursor(self, show: bool = True) -> bool: Function `show\_cursor` utility or script function.

L1207: def set_alt_screen(self, enable: bool = True) -> bool: Function `set\_alt\_screen` Sets or updates a value.

L1229: def is_alt_screen(self) -> bool: Function `is\_alt\_screen` utility or script function.

L1237: def set_window_title(self, title: str) -> bool: Function `set\_window\_title` Sets or updates a value.

L1269: def screen(Function `screen` utility or script function.

L1283: def measure(Function `measure` utility or script function.

L1300: def render(Function `render` utility or script function.

L1351: def render_lines(Function `render\_lines` utility or script function.

L1415: def render_str(Function `render\_str` utility or script function.

L1476: def get_style(Function `get\_style` Returns or fetches data.

L1506: def _collect_renderables(Function `\_collect\_renderables` utility or script

```

function.
L1539: def align_append(renderable: RenderableType) -> None:    Function `align_append`
utility or script function.
L1548: def check_text() -> None:    Function `check_text`    utility or script function.
L1585: def rule(    Function `rule`    utility or script function.
L1606: def control(self, *control: Control) -> None:    Function `control`    utility or script
function.
L1616: def out(    Function `out`    utility or script function.
L1648: def print(    Function `print`    utility or script function.
L1747: def print_json(    Function `print_json`    utility or script function.
L1808: def update_screen(    Function `update_screen`    utility or script function.
L1842: def update_screen_lines(    Function `update_screen_lines`    utility or script function.
L1862: def print_exception(    Function `print_exception`    utility or script function.
L1898: def _caller_frame_info(    Function `_caller_frame_info`    utility or script function.
L1932: def log(    Function `log`    utility or script function.
L2013: def on_broken_pipe(self) -> None:    Function `on_broken_pipe`    utility or script
function.
L2027: def _check_buffer(self) -> None:    Function `_check_buffer`    utility or script
function.
L2042: def _write_buffer(self) -> None:    Function `_write_buffer`    utility or script
function.
L2115: def _render_buffer(self, buffer: Iterable[Segment]) -> str:    Function
`_render_buffer`    utility or script function.
L2139: def input(    Function `input`    utility or script function.
L2173: def export_text(self, *, clear: bool = True, styles: bool = False) -> str:    Function
`export_text`    utility or script function.
L2205: def save_text(self, path: str, *, clear: bool = True, styles: bool = False) -> None:
Function `save_text`    Saves data to storage or remote.
L2219: def export_html(    Function `export_html`    utility or script function.
L2294: def save_html(    Function `save_html`    Saves data to storage or remote.
L2325: def export_svg(    Function `export_svg`    utility or script function.
L2356: def get_svg_style(style: Style) -> str:    Function `get_svg_style`    Returns or fetches
data.
L2416: def escape_text(text: str) -> str:    Function `escape_text`    utility or script
function.
L2420: def make_tag(    Function `make_tag`    utility or script function.
L2425: def stringify(value: object) -> str:    Object (singleton).
L2576: def save_svg(    Function `save_svg`    Saves data to storage or remote.
L2615: def _svg_hash(svg_main_code: str) -> str:    Function `_svg_hash`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/jupyter.py

```

L18: class JupyterRenderable:    Class (`JupyterRenderable`)    component used by the app (see
file context: None).
L21: def __init__(self, html: str, text: str) -> None:    Function `__init__`    utility or
script function.

```

```

L25: def _repr_mimebundle_( Function `_repr_mimebundle_` utility or script function.
L36: class JupyterMixin: Class (`JupyterMixin`) component used by the app (see file
context: None).
L41: def _repr_mimebundle_( Function `_repr_mimebundle_` utility or script function.
L59: def _render_segments(segments: Iterable[Segment]) -> str: Function `_render_segments`
utility or script function.
L60: def escape(text: str) -> str: Function `escape` utility or script function.
L84: def display(segments: Iterable[Segment], text: str) -> None: Function `display`
utility or script function.
L98: def print(*args: Any, **kwargs: Any) -> None: Function `print` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/abc.py

```

L4: class RichRenderable(ABC): Class (`RichRenderable`) component used by the app (see
file context: None).
L16: def __subclasshook__(cls, other: type) -> bool: Function `__subclasshook__` utility
or script function.
L28: class Foo: Class (`Foo`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress_bar.py

```

L18: class ProgressBar(JupyterMixin): Class (`ProgressBar`) component used by the app (see
file context: None).
L33: def __init__( Function `_init__` utility or script function.
L57: def __repr__(self) -> str: Function `__repr__` utility or script function.
L61: def percentage_completed(self) -> Optional[float]: Function `percentage_completed`
utility or script function.
L70: def _get_pulse_segments( Function `_get_pulse_segments` utility or script function.
L116: def update(self, completed: float, total: Optional[float] = None) -> None: Function
`update` utility or script function.
L126: def _render_pulse( Function `_render_pulse` utility or script function.
L156: def __rich_console__( Function `__rich_console__` utility or script function.
L200: def __rich_measure__( Function `__rich_measure__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/json.py

```

L9: class JSON: Class (`JSON`) component used by the app (see file context: None).

```

```
L25: def __init__(    Function `__init__`    utility or script function.
L54: def from_data(    Function `from_data`    utility or script function.
L101: def __rich__(self) -> Text:    Function `__rich__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/__main__.py

```
L18: class ColorBox:    Class (`ColorBox`)    component used by the app (see file context:
None).
L19: def __rich_console__(    Function `__rich_console__`    utility or script function.
L33: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L39: def make_test_card() -> Table:    Function `make_test_card`    utility or script function.
L90: def comparison(renderable1: RenderableType, renderable2: RenderableType) -> Table:
Function `comparison`    utility or script function.
L157: def iter_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:    Function `iter_last`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/measure.py

```
L11: class Measurement(NamedTuple):    Class (`Measurement`)    component used by the app (see
file context: None).
L20: def span(self) -> int:    Function `span`    utility or script function.
L24: def normalize(self) -> "Measurement":    Function `normalize`    utility or script
function.
L34: def with_maximum(self, width: int) -> "Measurement":    Function `with_maximum`    utility
or script function.
L46: def with_minimum(self, width: int) -> "Measurement":    Function `with_minimum`    utility
or script function.
L59: def clamp(    Function `clamp`    utility or script function.
L79: def get(    Function `get`    Returns or fetches data.
L125: def measure_renderables(    Function `measure_renderables`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/text.py

```
L47: class Span(NamedTuple):    Class (`Span`)    component used by the app (see file context:
None).
L57: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
```

```

L60: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L63: def split(self, offset: int) -> Tuple["Span", Optional["Span"]]:    Function `split`
utility or script function.
L76: def move(self, offset: int) -> "Span":    Function `move` utility or script function.
L88: def right_crop(self, offset: int) -> "Span":    Function `right_crop` utility or script
function.
L102: def extend(self, cells: int) -> "Span":    Function `extend` utility or script
function.
L118: class Text(JupyterMixin):    Class (`Text`) component used by the app (see file
context: None).
L144: def __init__(    Function `__init__` utility or script function.
L167: def __len__(self) -> int:    Function `__len__` utility or script function.
L170: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L173: def __str__(self) -> str:    Function `__str__` utility or script function.
L176: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L179: def __add__(self, other: Any) -> "Text":    Function `__add__` utility or script
function.
L186: def __eq__(self, other: object) -> bool:    Object (singleton).
L191: def __contains__(self, other: object) -> bool:    Object (singleton).
L198: def __getitem__(self, slice: Union[int, slice]) -> "Text":    Function `__getitem__`
utility or script function.
L199: def get_text_at(offset: int) -> "Text":    Function `get_text_at` Returns or fetches
data.
L225: def cell_len(self) -> int:    Function `cell_len` utility or script function.
L230: def markup(self) -> str:    Function `markup` utility or script function.
L260: def from_markup(    Function `from_markup` utility or script function.
L294: def from_ansi(    Function `from_ansi` utility or script function.
L332: def styled(    Function `styled` utility or script function.
L357: def assemble(    Function `assemble` utility or script function.
L403: def plain(self) -> str:    Function `plain` utility or script function.
L410: def plain(self, new_text: str) -> None:    Function `plain` utility or script function.
L421: def spans(self) -> List["Span"]:    Function `spans` utility or script function.
L426: def spans(self, spans: List["Span"]) -> None:    Function `spans` utility or script
function.
L430: def blank_copy(self, plain: str = "") -> "Text":    Function `blank_copy` utility or
script function.
L443: def copy(self) -> "Text":    Function `copy` utility or script function.
L457: def stylize(    Function `stylize` utility or script function.
L483: def stylize_before(    Function `stylize_before` utility or script function.
L509: def apply_meta(    Function `apply_meta` utility or script function.
L523: def on(self, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Text":
Function `on` utility or script function.
L543: def remove_suffix(self, suffix: str) -> None:    Function `remove_suffix` utility or
script function.
L552: def get_style_at_offset(self, console: "Console", offset: int) -> Style:    Function
`get_style_at_offset` Returns or fetches data.
L572: def extend_style(self, spaces: int) -> None:    Function `extend_style` utility or
script function.
L593: def highlight_regex(    Function `highlight_regex` utility or script function.
L633: def highlight_words(    Function `highlight_words` utility or script function.
L662: def rstrip(self) -> None:    Function `rstrip` utility or script function.

```

```

L666: def rstrip_end(self, size: int) -> None:    Function `rstrip_end` utility or script
function.
L680: def set_length(self, new_length: int) -> None:    Function `set_length` Sets or updates
a value.
L689: def __rich_console__(    Function `__rich_console__` utility or script function.
L708: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L720: def render(self, console: "Console", end: str = "") -> Iterable["Segment"]:    Function
`render` utility or script function.
L759: def get_current_style() -> Style:    Function `get_current_style` Returns or fetches
data.
L779: def join(self, lines: Iterable["Text"]) -> "Text":    Function `join` utility or script
function.
L791: def iter_text() -> Iterable["Text"]:    Function `iter_text` utility or script
function.
L818: def expand_tabs(self, tab_size: Optional[int] = None) -> None:    Function `expand_tabs`
utility or script function.
L860: def truncate(    Function `truncate` utility or script function.
L887: def _trim_spans(self) -> None:    Function `_trim_spans` utility or script function.
L901: def pad(self, count: int, character: str = " ") -> None:    Function `pad` utility or
script function.
L918: def pad_left(self, count: int, character: str = " ") -> None:    Function `pad_left`
utility or script function.
L934: def pad_right(self, count: int, character: str = " ") -> None:    Function `pad_right`
utility or script function.
L945: def align(self, align: AlignMethod, width: int, character: str = " ") -> None:
Function `align` utility or script function.
L965: def append(    Function `append` utility or script function.
L1009: def append_text(self, text: "Text") -> "Text":    Function `append_text` utility or
script function.
L1031: def append_tokens(    Function `append_tokens` utility or script function.
L1055: def copy_styles(self, text: "Text") -> None:    Function `copy_styles` utility or
script function.
L1063: def split(    Function `split` utility or script function.
L1092: def flatten_spans() -> Iterable[int]:    Function `flatten_spans` utility or script
function.
L1107: def divide(self, offsets: Iterable[int]) -> Lines:    Function `divide` utility or
script function.
L1186: def right_crop(self, amount: int = 1) -> None:    Function `right_crop` utility or
script function.
L1202: def wrap(    Function `wrap` utility or script function.
L1250: def fit(self, width: int) -> Lines:    Function `fit` utility or script function.
L1266: def detect_indentation(self) -> int:    Function `detect_indentation` utility or
script function.
L1287: def with_indent_guides(    Function `with_indent_guides` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/live.py


```

L22: class _RefreshThread(Thread):    Class (`_RefreshThread`) component used by the app (see
file context: None).
L25: def __init__(self, live: "Live", refresh_per_second: float) -> None:    Function
`__init__` utility or script function.
L31: def stop(self) -> None:    Function `stop` utility or script function.
L34: def run(self) -> None:    Function `run` utility or script function.
L41: class Live(JupyterMixin, RenderHook):    Class (`Live`) component used by the app (see
file context: None).
L57: def __init__(    Function `__init__` utility or script function.
L99: def is_started(self) -> bool:    Function `is_started` utility or script function.
L103: def get_renderable(self) -> RenderableType:    Function `get_renderable` Returns or
fetches data.
L111: def start(self, refresh: bool = False) -> None:    Function `start` utility or script
function.
L145: def stop(self) -> None:    Function `stop` utility or script function.
L179: def __enter__(self) -> Self:    Function `__enter__` utility or script function.
L183: def __exit__(    Function `__exit__` utility or script function.
L191: def _enable_redirect_io(self) -> None:    Function `_enable_redirect_io` utility or
script function.
L201: def _disable_redirect_io(self) -> None:    Function `_disable_redirect_io` utility or
script function.
L211: def renderable(self) -> RenderableType:    Function `renderable` utility or script
function.
L226: def update(self, renderable: RenderableType, *, refresh: bool = False) -> None:
Function `update` utility or script function.
L240: def refresh(self) -> None:    Function `refresh` utility or script function.
L274: def process_renderables(    Function `process_renderables` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/bar.py

```

L17: class Bar(JupyterMixin):    Class (`Bar`) component used by the app (see file context:
None).
L29: def __init__(    Function `__init__` utility or script function.
L45: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L48: def __rich_console__(    Function `__rich_console__` utility or script function.
L86: def __rich_measure__(    Function `__rich_measure__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/logging.py

```

L18: class RichHandler(Handler):    Class (`RichHandler`) component used by the app (see file
context: None).

```

```

L65: def __init__(    Function `__init__`    utility or script function.
L117: def get_level_text(self, record: LogRecord) -> Text:    Function `get_level_text`
Returns or fetches data.
L132: def emit(self, record: LogRecord) -> None:    Function `emit`    utility or script
function.
L182: def render_message(self, record: LogRecord, message: str) -> "ConsoleRenderable":
Function `render_message`    utility or script function.
L207: def render(    Function `render`    utility or script function.
L283: def divide() -> None:    Function `divide`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/rule.py

```

L12: class Rule(JupyterMixin):    Class (`Rule`)    component used by the app (see file context:
None).
L23: def __init__(    Function `__init__`    utility or script function.
L46: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L49: def __rich_console__(    Function `__rich_console__`    utility or script function.
L105: def _rule_line(self, chars_len: int, width: int) -> Text:    Function `_rule_line`
utility or script function.
L111: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/pretty.py

```

L60: def _is_attr_object(obj: Any) -> bool:    Function `_is_attr_object`    utility or script
function.
L65: def _get_attr_fields(obj: Any) -> Sequence["_attr_module.Attribute[Any]"]:    Function
`_get_attr_fields`    utility or script function.
L70: def _is_dataclass_repr(obj: object) -> bool:    Object (singleton).
L93: def _has_default_namedtuple_repr(obj: object) -> bool:    Object (singleton).
L113: def _ipy_display_hook(    Function `_ipy_display_hook`    utility or script function.
L161: def _safe_isinstance(    Function `_safe_isinstance`    utility or script function.
L171: def install(    Function `install`    utility or script function.
L200: def display_hook(value: Any) -> None:    Function `display_hook`    utility or script
function.
L230: class RichFormatter(BaseFormatter):    # type: ignore[misc]    Class (`RichFormatter`)
component used by the app (see file context: None).
L233: def __call__(self, value: Any) -> Any:    Function `__call__`    utility or script
function.
L253: class Pretty(JupyterMixin):    Class (`Pretty`)    component used by the app (see file
context: None).
L273: def __init__(    Function `__init__`    utility or script function.
L304: def __rich_console__(    Function `__rich_console__`    utility or script function.
L339: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

```

L357: def _get_braces_for_defaultdict(_object: DefaultDict[Any, Any]) -> Tuple[str, str, str]:
    Function `_get_braces_for_defaultdict` utility or script function.
L365: def _get_braces_for_deque(_object: Deque[Any]) -> Tuple[str, str, str]:
    Function `_get_braces_for_deque` utility or script function.
L375: def _get_braces_for_array(_object: "array[Any]") -> Tuple[str, str, str]:
    Function `_get_braces_for_array` utility or script function.
L398: def is_expandable(obj: Any) -> bool:
    Function `is_expandable` utility or script function.
L409: class Node:
    Class (`Node`) component used by the app (see file context: None).
L424: def iter_tokens(self) -> Iterable[str]:
    Function `iter_tokens` utility or script function.
L446: def check_length(self, start_length: int, max_length: int) -> bool:
    Function `check_length` utility or script function.
L463: def __str__(self) -> str:
    Function `__str__` utility or script function.
L467: def render(
    Function `render` utility or script function.
L494: class _Line:
    Class (`_Line`) component used by the app (see file context: None).
L507: def expandable(self) -> bool:
    Function `expandable` utility or script function.
L511: def check_length(self, max_length: int) -> bool:
    Function `check_length` utility or script function.
L519: def expand(self, indent_size: int) -> Iterable["_Line"]:
    Function `expand` utility or script function.
L552: def __str__(self) -> str:
    Function `__str__` utility or script function.
L561: def _is_namedtuple(obj: Any) -> bool:
    Function `_is_namedtuple` utility or script function.
L580: def traverse(
    Function `traverse` utility or script function.
L601: def to_repr(obj: Any) -> str:
    Function `to_repr` utility or script function.
L621: def _traverse(obj: Any, root: bool = False, depth: int = 0) -> Node:
    Function `_traverse` utility or script function.
L633: def iter_rich_args(rich_args: Any) -> Iterable[Union[Any, Tuple[str, Any]]]:
    Function `iter_rich_args` utility or script function.
L731: def iter_attrs() -> (
    Function `iter_attrs` utility or script function.
L878: def pretty_repr(
    Function `pretty_repr` utility or script function.
L918: def pprint(
    Function `pprint` utility or script function.
L957: class BrokenRepr:
    Class (`BrokenRepr`) component used by the app (see file context: None).
L958: def __repr__(self) -> str:
    Function `__repr__` utility or script function.
L964: class StockKeepingUnit(NamedTuple):
    Class (`StockKeepingUnit`) component used by the app (see file context: None).
L1012: class Thing:
    Class (`Thing`) component used by the app (see file context: None).
L1013: def __repr__(self) -> str:
    Function `__repr__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/panel.py

```

L17: class Panel(JupyterMixin):
    Class (`Panel`) component used by the app (see file context: None).
L40: def __init__(
    Function `__init__` utility or script function.
L74: def fit(
    Function `fit` utility or script function.

```

```

L110: def _title(self) -> Optional[Text]:    Function `_title` utility or script function.
L126: def _subtitle(self) -> Optional[Text]:  Function `_subtitle` utility or script
function.
L141: def __rich_console__(    Function `__rich_console__` utility or script function.
L159: def align_text(    Function `align_text` utility or script function.
L277: def __rich_measure__(    Function `__rich_measure__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows_renderer.py

```

L7: def legacy_windows_render(buffer: Iterable[Segment], term: LegacyWindowsTerm) -> None:
Function `legacy_windows_render` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_fileno.py

```

L6: def get_fileno(file_like: IO[str]) -> int | None:    Function `get_fileno` Returns or
fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/palette.py

```

L11: class Palette:    Class (`Palette`) component used by the app (see file context: None).
L14: def __init__(self, colors: Sequence[Tuple[int, int, int]]):    Function `__init__`
utility or script function.
L17: def __getitem__(self, number: int) -> ColorTriplet:    Function `__getitem__` utility or
script function.
L20: def __rich__(self) -> "Table":    Function `__rich__` utility or script function.
L45: def match(self, color: Tuple[int, int, int]) -> int:    Function `match` utility or
script function.
L58: def get_color_distance(index: int) -> float:    Function `get_color_distance` Returns or
fetches data.
L83: class ColorBox:    Class (`ColorBox`) component used by the app (see file context:
None).
L84: def __rich_console__(    Function `__rich_console__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/pager.py

```

L5: class Pager(ABC):    Class (`Pager`)    component used by the app (see file context: None).
L9: def show(self, content: str) -> None:    Function `show`    utility or script function.
L17: class SystemPager(Pager):    Class (`SystemPager`)    component used by the app (see file
context: None).
L20: def _pager(self, content: str) -> Any:    # pragma: no cover    Function `_pager`    utility
or script function.
L23: def show(self, content: str) -> None:    Function `show`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/repr.py

```

L23: class ReprError(Exception):    Class (`ReprError`)    component used by the app (see file
context: None).
L28: def auto(cls: Optional[Type[T]]) -> Type[T]:    Function `auto`    utility or script
function.
L33: def auto(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:    Function `auto`
utility or script function.
L37: def auto(    Function `auto`    utility or script function.
L42: def do_replace(cls: Type[T], angular: Optional[bool] = None) -> Type[T]:    Function
`do_replace`    utility or script function.
L43: def auto_repr(self: T) -> str:    Function `auto_repr`    utility or script function.
L68: def auto_rich_repr(self: Type[T]) -> Result:    Function `auto_rich_repr`    utility or
script function.
L105: def rich_repr(cls: Optional[Type[T]]) -> Type[T]:    Function `rich_repr`    utility or
script function.
L110: def rich_repr(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:    Function
`rich_repr`    utility or script function.
L114: def rich_repr(    Function `rich_repr`    utility or script function.
L126: class Foo:    Class (`Foo`)    component used by the app (see file context: None).
L127: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/columns.py

```

L16: class Columns(JupyterMixin):    Class (`Columns`)    component used by the app (see file
context: None).
L31: def __init__(    Function `__init__`    utility or script function.
L54: def add_renderable(self, renderable: RenderableType) -> None:    Function
`add_renderable`    utility or script function.
L62: def __rich_console__(    Function `__rich_console__`    utility or script function.
L86: def iter_renderables(    Function `iter_renderables`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/ansi.py

```

L20: class _AnsiToken(NamedTuple):    Class (`_AnsiToken`)    component used by the app (see
file context: None).
L28: def _ansi_tokenize(ansi_text: str) -> Iterable[_AnsiToken]:    Function `_ansi_tokenize`
utility or script function.
L120: class AnsiDecoder:    Class (`AnsiDecoder`)    component used by the app (see file
context: None).
L123: def __init__(self) -> None:    Function `__init__`    utility or script function.
L126: def decode(self, terminal_text: str) -> Iterable[Text]:    Function `decode`    utility or
script function.
L138: def decode_line(self, line: str) -> Text:    Function `decode_line`    utility or script
function.
L224: def read(fd: int) -> bytes:    Function `read`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/live_render.py

```

L14: class LiveRender:    Class (`LiveRender`)    component used by the app (see file context:
None).
L22: def __init__(    Function `__init__`    utility or script function.
L33: def set_renderable(self, renderable: RenderableType) -> None:    Function
`set_renderable`    Sets or updates a value.
L41: def position_cursor(self) -> Control:    Function `position_cursor`    utility or script
function.
L62: def restore_cursor(self) -> Control:    Function `restore_cursor`    utility or script
function.
L76: def __rich_console__(    Function `__rich_console__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/padding.py

```

L19: class Padding(JupyterMixin):    Class (`Padding`)    component used by the app (see file
context: None).
L33: def __init__(    Function `__init__`    utility or script function.
L47: def indent(cls, renderable: "RenderableType", level: int) -> "Padding":    Function
`indent`    utility or script function.
L61: def unpack(pad: "PaddingDimensions") -> Tuple[int, int, int, int]:    Function `unpack`
utility or script function.

```

```
L76: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L79: def __rich_console__(    Function `__rich_console__`    utility or script function.
L125: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_timer.py

```
L13: def timer(subject: str = "time") -> Generator[None, None, None]:    Function `timer`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/align.py

```
L17: class Align(JupyterMixin):    Class (`Align`)    component used by the app (see file
context: None).
L33: def __init__(    Function `__init__`    utility or script function.
L60: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L64: def left(    Function `left`    utility or script function.
L86: def center(    Function `center`    utility or script function.
L108: def right(    Function `right`    utility or script function.
L129: def __rich_console__(    Function `__rich_console__`    utility or script function.
L147: def generate_segments() -> Iterable[Segment]:    Function `generate_segments`    Generates
content (often AI-generated).
L192: def blank_lines(count: int) -> Iterable[Segment]:    Function `blank_lines`    utility or
script function.
L221: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L228: class VerticalCenter(JupyterMixin):    Class (`VerticalCenter`)    component used by the
app (see file context: None).
L240: def __init__(    Function `__init__`    utility or script function.
L248: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L251: def __rich_console__(    Function `__rich_console__`    utility or script function.
L265: def blank_lines(count: int) -> Iterable[Segment]:    Function `blank_lines`    utility or
script function.
L278: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/__init__.py

```
L23: def get_console() -> "Console":    Function `get_console`    Returns or fetches data.
L39: def reconfigure(*args: Any, **kwargs: Any) -> None:    Function `reconfigure`    utility or
script function.
```

```
L53: def print(    Function `print`    utility or script function.
L77: def print_json(    Function `print_json`    utility or script function.
L120: def inspect(    Function `inspect`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_inspect.py

```
L15: def _first_paragraph(doc: str) -> str:    Function `_first_paragraph`    utility or script
function.
L21: class Inspect(JupyterMixin):    Class (`Inspect`)    component used by the app (see file
context: None).
L37: def __init__(    Function `__init__`    utility or script function.
L64: def _make_title(self, obj: Any) -> Text:    Function `_make_title`    utility or script
function.
L74: def __rich__(self) -> Panel:    Function `__rich__`    utility or script function.
L82: def _get_signature(self, name: str, obj: Any) -> Optional[Text]:    Function
`_get_signature`    utility or script function.
L121: def _render(self) -> Iterable[RenderableType]:    Function `_render`    utility or script
function.
L124: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:    Function `sort_items`
utility or script function.
L128: def safe_getattr(attr_name: str) -> Tuple[Any, Any]:    Function `safe_getattr`    utility
or script function.
L214: def _get_formatted_doc(self, object_: Any) -> Optional[str]:    Function
`_get_formatted_doc`    utility or script function.
L236: def get_object_types_mro(obj: Union[object, Type[Any]]) -> Tuple[type, ...]:    Object
(singleton).
L245: def get_object_types_mro_as_strings(obj: object) -> Collection[str]:    Object
(singleton).
L258: def is_object_one_of_types(    Function `is_object_one_of_types`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_loop.py

```
L6: def loop_first(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:    Function `loop_first`
utility or script function.
L18: def loop_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:    Function `loop_last`
utility or script function.
L31: def loop_first_last(values: Iterable[T]) -> Iterable[Tuple[bool, bool, T]]:    Function
`loop_first_last`    utility or script function.
```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/screen.py

```

L18: class Screen:    Class (`Screen`)    component used by the app (see file context: None).
L28: def __init__(    Function `__init__`    utility or script function.
L40: def __rich_console__(    Function `__rich_console__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows.py

```

L6: class WindowsConsoleFeatures:    Class (`WindowsConsoleFeatures`)    component used by the
app (see file context: None).
L34: def get_windows_console_features() -> WindowsConsoleFeatures:    Function
`get_windows_console_features`    Returns or fetches data.
L40: def get_windows_console_features() -> WindowsConsoleFeatures:    Function
`get_windows_console_features`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/highlighter.py

```

L8: def _combine_regex(*regexes: str) -> str:    Function `_combine_regex`    utility or script
function.
L17: class Highlighter(ABC):    Class (`Highlighter`)    component used by the app (see file
context: None).
L20: def __call__(self, text: Union[str, Text]) -> Text:    Function `__call__`    utility or
script function.
L42: def highlight(self, text: Text) -> None:    Function `highlight`    utility or script
function.
L50: class NullHighlighter(Highlighter):    Class (`NullHighlighter`)    component used by the
app (see file context: None).
L57: def highlight(self, text: Text) -> None:    Function `highlight`    utility or script
function.
L61: class RegexHighlighter(Highlighter):    Class (`RegexHighlighter`)    component used by the
app (see file context: None).
L67: def highlight(self, text: Text) -> None:    Function `highlight`    utility or script
function.
L80: class ReprHighlighter(RegexHighlighter):    Class (`ReprHighlighter`)    component used by
the app (see file context: None).
L106: class JSONHighlighter(RegexHighlighter):    Class (`JSONHighlighter`)    component used by
the app (see file context: None).

```

```
L123: def highlight(self, text: Text) -> None:    Function `highlight` utility or script
function.
L143: class ISO8601Highlighter(RegexHighlighter):    Class (`ISO8601Highlighter`) component
used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_wrap.py

```
L12: def words(text: str) -> Iterable[tuple[int, int, str]]:    Function `words` utility or
script function.
L26: def divide_line(text: str, width: int, fold: bool = True) -> list[int]:    Function
`divide_line` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/spinner.py

```
L13: class Spinner:    Class (`Spinner`) component used by the app (see file context: None).
L26: def __init__(    Function `__init__` utility or script function.
L50: def __rich_console__(    Function `__rich_console__` utility or script function.
L55: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L61: def render(self, time: float) -> "RenderableType":    Function `render` utility or
script function.
L95: def update(    Function `update` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/style.py

```
L21: class _Bit:    Class (`_Bit`) component used by the app (see file context: None).
L26: def __init__(self, bit_no: int) -> None:    Function `__init__` utility or script
function.
L29: def __get__(self, obj: "Style", objtype: Type["Style"]) -> Optional[bool]:    Function
`__get__` utility or script function.
L36: class Style:    Class (`Style`) component used by the app (see file context: None).
L127: def __init__(    Function `__init__` utility or script function.
L151: def _make_color(color: Union[Color, str]) -> Color:    Function `_make_color` utility
or script function.
L204: def null(cls) -> "Style":    Function `null` utility or script function.
L209: def from_color(    Function `from_color` utility or script function.
L233: def from_meta(cls, meta: Optional[Dict[str, Any]]) -> "Style":    Function `from_meta`
utility or script function.
L254: def on(cls, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Style":
```

```

Function `on` utility or script function.
L286: def link_id(self) -> str:    Function `link_id` utility or script function.
L290: def __str__(self) -> str:    Function `__str__` utility or script function.
L336: def __bool__(self) -> bool:  Function `__bool__` utility or script function.
L340: def _make_ansi_codes(self, color_system: ColorSystem) -> str:    Function
`_make_ansi_codes` utility or script function.
L385: def normalize(cls, style: str) -> str:    Function `normalize` utility or script
function.
L401: def pick_first(cls, *values: Optional[StyleType]) -> StyleType:    Function `pick_first`
utility or script function.
L408: def __rich_repr__(self) -> Result:    Function `__rich_repr__` utility or script
function.
L427: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L432: def __ne__(self, other: Any) -> bool:    Function `__ne__` utility or script function.
L437: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L444: def color(self) -> Optional[Color]:    Function `color` utility or script function.
L449: def bgcolor(self) -> Optional[Color]:    Function `bgcolor` utility or script function.
L454: def link(self) -> Optional[str]:    Function `link` utility or script function.
L459: def transparent_background(self) -> bool:    Function `transparent_background` utility
or script function.
L464: def background_style(self) -> "Style":    Function `background_style` utility or script
function.
L469: def meta(self) -> Dict[str, Any]:    Function `meta` utility or script function.
L474: def without_color(self) -> "Style":    Function `without_color` utility or script
function.
L494: def parse(cls, style_definition: str) -> "Style":    Function `parse` utility or script
function.
L560: def get_html_style(self, theme: Optional[TerminalTheme] = None) -> str:    Function
`get_html_style` Returns or fetches data.
L597: def combine(cls, styles: Iterable["Style"]) -> "Style":    Function `combine` utility
or script function.
L610: def chain(cls, *styles: "Style") -> "Style":    Function `chain` utility or script
function.
L622: def copy(self) -> "Style":    Function `copy` utility or script function.
L645: def clear_meta_and_links(self) -> "Style":    Function `clear_meta_and_links` utility
or script function.
L667: def update_link(self, link: Optional[str] = None) -> "Style":    Function `update_link`
utility or script function.
L690: def render(    Function `render` utility or script function.
L716: def test(self, text: Optional[str] = None) -> None:    Function `test` utility or
script function.
L729: def _add(self, style: Optional["Style"]) -> "Style":    Function `_add` utility or
script function.
L753: def __add__(self, style: Optional["Style"]) -> "Style":    Function `__add__` utility
or script function.
L761: class StyleStack:    Class (`StyleStack`) component used by the app (see file context:
None).
L766: def __init__(self, default_style: "Style") -> None:    Function `__init__` utility or
script function.
L769: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L773: def current(self) -> Style:    Function `current` utility or script function.

```

```
L777: def push(self, style: Style) -> None:    Function `push`    utility or script function.
L785: def pop(self) -> Style:    Function `pop`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/theme.py

```
L8: class Theme:    Class (`Theme`)    component used by the app (see file context: None).
L18: def __init__(    Function `__init__`    utility or script function.
L31: def config(self) -> str:    Function `config`    utility or script function.
L39: def from_file(    Function `from_file`    utility or script function.
L59: def read(    Function `read`    utility or script function.
L76: class ThemeStackError(Exception):    Class (`ThemeStackError`)    component used by the app
(see file context: None).
L80: class ThemeStack:    Class (`ThemeStack`)    component used by the app (see file context:
None).
L87: def __init__(self, theme: Theme) -> None:    Function `__init__`    utility or script
function.
L91: def push_theme(self, theme: Theme, inherit: bool = True) -> None:    Function
`push_theme`    utility or script function.
L105: def pop_theme(self) -> None:    Function `pop_theme`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/terminal_theme.py

```
L9: class TerminalTheme:    Class (`TerminalTheme`)    component used by the app (see file
context: None).
L20: def __init__(    Function `__init__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/layout.py

```
L32: class LayoutRender(NamedTuple):    Class (`LayoutRender`)    component used by the app (see
file context: None).
L43: class LayoutError(Exception):    Class (`LayoutError`)    component used by the app (see
file context: None).
L47: class NoSplitter(LayoutError):    Class (`NoSplitter`)    component used by the app (see
file context: None).
L51: class _Placeholder:    Class (`_Placeholder`)    component used by the app (see file
context: None).
L56: def __init__(self, layout: "Layout", style: StyleType = "") -> None:    Function
`__init__`    utility or script function.
```

```

L60: def __rich_console__(    Function `__rich_console__` utility or script function.
L80: class Splitter(ABC):    Class (`Splitter`) component used by the app (see file context:
None).
L86: def get_tree_icon(self) -> str:    Function `get_tree_icon` Returns or fetches data.
L90: def divide(    Function `divide` utility or script function.
L101: class RowSplitter(Splitter):    Class (`RowSplitter`) component used by the app (see
file context: None).
L106: def get_tree_icon(self) -> str:    Function `get_tree_icon` Returns or fetches data.
L109: def divide(    Function `divide` utility or script function.
L121: class ColumnSplitter(Splitter):    Class (`ColumnSplitter`) component used by the app
(see file context: None).
L126: def get_tree_icon(self) -> str:    Function `get_tree_icon` Returns or fetches data.
L129: def divide(    Function `divide` utility or script function.
L142: class Layout:    Class (`Layout`) component used by the app (see file context: None).
L156: def __init__(    Function `__init__` utility or script function.
L177: def __rich_repr__(self) -> Result:    Function `__rich_repr__` utility or script
function.
L184: def renderable(self) -> RenderableType:    Function `renderable` utility or script
function.
L189: def children(self) -> List["Layout"]:    Function `children` utility or script
function.
L194: def map(self) -> RenderMap:    Function `map` Maps or converts between representations.
L198: def get(self, name: str) -> Optional["Layout"]:    Function `get` Returns or fetches
data.
L216: def __getitem__(self, name: str) -> "Layout":    Function `__getitem__` utility or
script function.
L223: def tree(self) -> "Tree":    Function `tree` utility or script function.
L229: def summary(layout: "Layout") -> Table:    Function `summary` utility or script
function.
L248: def recurse(tree: "Tree", layout: "Layout") -> None:    Function `recurse` utility or
script function.
L261: def split(    Function `split` utility or script function.
L286: def add_split(self, *layouts: Union["Layout", RenderableType]) -> None:    Function
`add_split` utility or script function.
L299: def split_row(self, *layouts: Union["Layout", RenderableType]) -> None:    Function
`split_row` utility or script function.
L307: def split_column(self, *layouts: Union["Layout", RenderableType]) -> None:    Function
`split_column` utility or script function.
L315: def unsplit(self) -> None:    Function `unsplit` utility or script function.
L319: def update(self, renderable: RenderableType) -> None:    Function `update` utility or
script function.
L328: def refresh_screen(self, console: "Console", layout_name: str) -> None:    Function
`refresh_screen` utility or script function.
L345: def _make_region_map(self, width: int, height: int) -> RegionMap:    Function
`_make_region_map` utility or script function.
L366: def render(self, console: Console, options: ConsoleOptions) -> RenderMap:    Function
`render` utility or script function.
L395: def __rich_console__(    Function `__rich_console__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/diagnose.py

```
L10: def report() -> None: # pragma: no cover    Function `report`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_pick.py

```
L4: def pick_bool(*values: Optional[bool]) -> bool:    Function `pick_bool`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_win32_console.py

```
L29: class LegacyWindowsError(Exception):    Class (`LegacyWindowsError`)    component used by
the app (see file context: None).
L33: class WindowsCoordinates(NamedTuple):    Class (`WindowsCoordinates`)    component used by
the app (see file context: None).
L44: def from_param(cls, value: "WindowsCoordinates") -> COORD:    Function `from_param`
utility or script function.
L57: class CONSOLE_SCREEN_BUFFER_INFO(Structure):    Class (`CONSOLE_SCREEN_BUFFER_INFO`)
component used by the app (see file context: None).
L67: class CONSOLE_CURSOR_INFO(ctypes.Structure):    Class (`CONSOLE_CURSOR_INFO`)    component
used by the app (see file context: None).
L78: def GetStdHandle(handle: int = STDOUT) -> wintypes.HANDLE:    Function `GetStdHandle`
utility or script function.
L95: def GetConsoleMode(std_handle: wintypes.HANDLE) -> int:    Function `GetConsoleMode`
utility or script function.
L128: def FillConsoleOutputCharacter(    Function `FillConsoleOutputCharacter`    utility or
script function.
L169: def FillConsoleOutputAttribute(    Function `FillConsoleOutputAttribute`    utility or
script function.
L204: def SetConsoleTextAttribute(    Function `SetConsoleTextAttribute`    utility or script
function.
L228: def GetConsoleScreenBufferInfo(    Function `GetConsoleScreenBufferInfo`    utility or
script function.
L252: def SetConsoleCursorPosition(    Function `SetConsoleCursorPosition`    utility or script
function.
L275: def GetConsoleCursorInfo(    Function `GetConsoleCursorInfo`    utility or script
```

```

function.
L299: def SetConsoleCursorInfo(    Function `SetConsoleCursorInfo`    utility or script
function.
L319: def SetConsoleTitle(title: str) -> bool:    Function `SetConsoleTitle`    utility or
script function.
L331: class LegacyWindowsTerm:    Class (`LegacyWindowsTerm`)    component used by the app (see
file context: None).
L362: def __init__(self, file: "IO[str]") -> None:    Function `__init__`    utility or script
function.
L377: def cursor_position(self) -> WindowsCoordinates:    Function `cursor_position`    utility
or script function.
L387: def screen_size(self) -> WindowsCoordinates:    Function `screen_size`    utility or
script function.
L396: def write_text(self, text: str) -> None:    Function `write_text`    utility or script
function.
L405: def write_styled(self, text: str, style: Style) -> None:    Function `write_styled`
utility or script function.
L444: def move_cursor_to(self, new_position: WindowsCoordinates) -> None:    Function
`move_cursor_to`    utility or script function.
L454: def erase_line(self) -> None:    Function `erase_line`    utility or script function.
L470: def erase_end_of_line(self) -> None:    Function `erase_end_of_line`    utility or script
function.
L484: def erase_start_of_line(self) -> None:    Function `erase_start_of_line`    utility or
script function.
L493: def move_cursor_up(self) -> None:    Function `move_cursor_up`    utility or script
function.
L503: def move_cursor_down(self) -> None:    Function `move_cursor_down`    utility or script
function.
L514: def move_cursor_forward(self) -> None:    Function `move_cursor_forward`    utility or
script function.
L526: def move_cursor_to_column(self, column: int) -> None:    Function
`move_cursor_to_column`    utility or script function.
L535: def move_cursor_backward(self) -> None:    Function `move_cursor_backward`    utility or
script function.
L547: def hide_cursor(self) -> None:    Function `hide_cursor`    utility or script function.
L553: def show_cursor(self) -> None:    Function `show_cursor`    utility or script function.
L559: def set_title(self, title: str) -> None:    Function `set_title`    Sets or updates a
value.
L568: def _get_cursor_size(self) -> int:    Function `_get_cursor_size`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/color.py

```

L21: class ColorSystem(IntEnum):    Class (`ColorSystem`)    component used by the app (see file
context: None).
L29: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L32: def __str__(self) -> str:    Function `__str__`    utility or script function.

```

```

L36: class ColorType(IntEnum):    Class (`ColorType`)    component used by the app (see file
context: None).
L45: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L288: class ColorParseError(Exception):    Class (`ColorParseError`)    component used by the
app (see file context: None).
L303: class Color(NamedTuple):    Class (`Color`)    component used by the app (see file
context: None).
L315: def __rich__(self) -> "Text":    Function `__rich__`    utility or script function.
L326: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.
L333: def system(self) -> ColorSystem:    Function `system`    utility or script function.
L340: def is_system_defined(self) -> bool:    Function `is_system_defined`    utility or script
function.
L345: def is_default(self) -> bool:    Function `is_default`    utility or script function.
L349: def get_truecolor(    Function `get_truecolor`    Returns or fetches data.
L381: def from_ansi(cls, number: int) -> "Color":    Function `from_ansi`    utility or script
function.
L397: def from_triplet(cls, triplet: "ColorTriplet") -> "Color":    Function `from_triplet`
utility or script function.
L409: def from_rgb(cls, red: float, green: float, blue: float) -> "Color":    Function
`from_rgb`    utility or script function.
L423: def default(cls) -> "Color":    Function `default`    utility or script function.
L433: def parse(cls, color: str) -> "Color":    Function `parse`    utility or script function.
L485: def get_ansi_codes(self, foreground: bool = True) -> Tuple[str, ...]:    Function
`get_ansi_codes`    Returns or fetches data.
L513: def downgrade(self, system: ColorSystem) -> "Color":    Function `downgrade`    utility or
script function.
L571: def parse_rgb_hex(hex_color: str) -> ColorTriplet:    Function `parse_rgb_hex`    utility
or script function.
L580: def blend_rgb(    Function `blend_rgb`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/traceback
.py

```

L55: def _iter_syntax_lines(    Function `_iter_syntax_lines`    utility or script function.
L83: def install(    Function `install`    utility or script function.
L134: def excepthook(    Function `excepthook`    utility or script function.
L159: def ipy_excepthook_closure(ip: Any) -> None:    # pragma: no cover    Function
`ipy_excepthook_closure`    utility or script function.
L163: def ipy_show_traceback(*args: Any, **kwargs: Any) -> None:    Function
`ipy_show_traceback`    utility or script function.
L169: def ipy_display_traceback(    Function `ipy_display_traceback`    utility or script
function.
L215: class Frame:    Class (`Frame`)    component used by the app (see file context: None).
L225: class _SyntaxError:    Class (`_SyntaxError`)    component used by the app (see file
context: None).

```



```

L235: class Stack:    Class (`Stack`)    component used by the app (see file context: None).
L247: class Trace:    Class (`Trace`)    component used by the app (see file context: None).
L251: class PathHighlighter(RegexHighlighter):    Class (`PathHighlighter`)    component used by
the app (see file context: None).
L255: class Traceback:    Class (`Traceback`)    component used by the app (see file context:
None).
L286: def __init__(    Function `__init__`    utility or script function.
L340: def from_exception(    Function `from_exception`    utility or script function.
L413: def extract(    Function `extract`    utility or script function.
L454: def safe_str(_object: Any) -> str:    Function `safe_str`    utility or script function.
L502: def get_locals(    Function `get_locals`    Returns or fetches data.
L603: def __rich_console__(    Function `__rich_console__`    utility or script function.
L635: def render_stack(stack: Stack, last: bool) -> RenderResult:    Function `render_stack`
utility or script function.
L706: def _render_syntax_error(self, syntax_error: _SyntaxError) -> RenderResult:    Function
`_render_syntax_error`    utility or script function.
L729: def _guess_lexer(cls, filename: str, code: str) -> str:    Function `_guess_lexer`
utility or script function.
L745: def _render_stack(self, stack: Stack) -> RenderResult:    Function `_render_stack`
utility or script function.
L749: def render_locals(frame: Frame) -> Iterable[ConsoleRenderable]:    Function
`render_locals`    utility or script function.
L877: def bar(    Function `bar`    utility or script function.
L883: def foo(a: Any) -> None:    Function `foo`    utility or script function.
L896: def error() -> None:    Function `error`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/table.py

```

L39: class Column:    Class (`Column`)    component used by the app (see file context: None).
L117: def copy(self) -> "Column":    Function `copy`    utility or script function.
L122: def cells(self) -> Iterable["RenderableType"]:    Function `cells`    utility or script
function.
L127: def flexible(self) -> bool:    Function `flexible`    utility or script function.
L133: class Row:    Class (`Row`)    component used by the app (see file context: None).
L143: class _Cell(NamedTuple):    Class (`_Cell`)    component used by the app (see file
context: None).
L154: class Table(JupyterMixin):    Class (`Table`)    component used by the app (see file
context: None).
L189: def __init__(    Function `__init__`    utility or script function.
L254: def grid(    Function `grid`    utility or script function.
L287: def expand(self) -> bool:    Function `expand`    utility or script function.
L292: def expand(self, expand: bool) -> None:    Function `expand`    utility or script
function.
L297: def _extra_width(self) -> int:    Function `_extra_width`    utility or script function.
L307: def row_count(self) -> int:    Function `row_count`    utility or script function.
L311: def get_row_style(self, console: "Console", index: int) -> StyleType:    Function
`get_row_style`    Returns or fetches data.

```

```

L321: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L355: def padding(self) -> Tuple[int, int, int, int]:    Function `padding`    utility or script
function.
L360: def padding(self, padding: PaddingDimensions) -> "Table":    Function `padding`    utility
or script function.
L365: def add_column(    Function `add_column`    utility or script function.
L423: def add_row(    Function `add_row`    utility or script function.
L441: def add_cell(column: Column, renderable: "RenderableType") -> None:    Function
`add_cell`    utility or script function.
L470: def add_section(self) -> None:    Function `add_section`    utility or script function.
L476: def __rich_console__(    Function `__rich_console__`    utility or script function.
L497: def render_annotation(    Function `render_annotation`    utility or script function.
L523: def _calculate_column_widths(    Function `_calculate_column_widths`    utility or script
function.
L588: def _collapse_widths(    Function `_collapse_widths`    utility or script function.
L626: def _get_cells(    Function `_get_cells`    utility or script function.
L641: def get_padding(first_row: bool, last_row: bool) -> Tuple[int, int, int, int]:
Function `get_padding`    Returns or fetches data.
L699: def _get_padding_width(self, column_index: int) -> int:    Function `_get_padding_width`
utility or script function.
L707: def _measure_column(    Function `_measure_column`    utility or script function.
L747: def _render(    Function `_render`    utility or script function.
L839: def align_cell(    Function `align_cell`    utility or script function.
L967: def header(text: str) -> None:    Function `header`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/errors.py

```

L1: class ConsoleError(Exception):    Class (`ConsoleError`)    component used by the app (see
file context: None).
L5: class StyleError(Exception):    Class (`StyleError`)    component used by the app (see file
context: None).
L9: class StyleSyntaxError(ConsoleError):    Class (`StyleSyntaxError`)    component used by the
app (see file context: None).
L13: class MissingStyle(StyleError):    Class (`MissingStyle`)    component used by the app (see
file context: None).
L17: class StyleStackError(ConsoleError):    Class (`StyleStackError`)    component used by the
app (see file context: None).
L21: class NotRenderableError(ConsoleError):    Class (`NotRenderableError`)    component used
by the app (see file context: None).
L25: class MarkupError(ConsoleError):    Class (`MarkupError`)    component used by the app (see
file context: None).
L29: class LiveError(ConsoleError):    Class (`LiveError`)    component used by the app (see
file context: None).
L33: class NoAltScreen(ConsoleError):    Class (`NoAltScreen`)    component used by the app (see
file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_stack.py

```

L6: class Stack(List[T]):    Class (`Stack`)    component used by the app (see file context:
None).
L10: def top(self) -> T:    Function `top`    utility or script function.
L14: def push(self, item: T) -> None:    Function `push`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/filesize.py

```

L18: def _to_str(    Function `_to_str`    utility or script function.
L43: def pick_unit_and_suffix(size: int, suffixes: List[str], base: int) -> Tuple[int, str]:
    Function `pick_unit_and_suffix`    utility or script function.
L52: def decimal(    Function `decimal`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/markup.py

```

L20: class Tag(NamedTuple):    Class (`Tag`)    component used by the app (see file context:
None).
L28: def __str__(self) -> str:    Function `__str__`    utility or script function.
L34: def markup(self) -> str:    Function `markup`    utility or script function.
L48: def escape(    Function `escape`    utility or script function.
L61: def escape_backslashes(match: Match[str]) -> str:    Function `escape_backslashes`
utility or script function.
L73: def _parse(markup: str) -> Iterable[Tuple[int, Optional[str], Optional[Tag]]]:
Function `_parse`    utility or script function.
L106: def render(    Function `render`    utility or script function.
L146: def pop_style(style_name: str) -> Tuple[int, Tag]:    Function `pop_style`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/region.py

```

L4: class Region(NamedTuple):    Class (`Region`)    component used by the app (see file
context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/container s.py

```

L30: class Renderables:    Class (`Renderables`) component used by the app (see file context:
None).
L33: def __init__(    Function `__init__` utility or script function.
L40: def __rich_console__(    Function `__rich_console__` utility or script function.
L46: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L59: def append(self, renderable: "RenderableType") -> None:    Function `append` utility or
script function.
L62: def __iter__(self) -> Iterable["RenderableType"]:    Function `__iter__` utility or
script function.
L66: class Lines:    Class (`Lines`) component used by the app (see file context: None).
L69: def __init__(self, lines: Iterable["Text"] = ()) -> None:    Function `__init__` utility
or script function.
L72: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L75: def __iter__(self) -> Iterator["Text"]:    Function `__iter__` utility or script
function.
L79: def __getitem__(self, index: int) -> "Text":    Function `__getitem__` utility or script
function.
L83: def __getitem__(self, index: slice) -> List["Text"]:    Function `__getitem__` utility
or script function.
L86: def __getitem__(self, index: Union[slice, int]) -> Union["Text", List["Text"]]:
Function `__getitem__` utility or script function.
L89: def __setitem__(self, index: int, value: "Text") -> "Lines":    Function `__setitem__`
utility or script function.
L93: def __len__(self) -> int:    Function `__len__` utility or script function.
L96: def __rich_console__(    Function `__rich_console__` utility or script function.
L102: def append(self, line: "Text") -> None:    Function `append` utility or script
function.
L105: def extend(self, lines: Iterable["Text"]) -> None:    Function `extend` utility or
script function.
L108: def pop(self, index: int = -1) -> "Text":    Function `pop` utility or script function.
L111: def justify(    Function `justify` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/_ratio.py

```

L6: class Edge(Protocol):    Class (`Edge`) component used by the app (see file context:
None).
L14: def ratio_resolve(total: int, edges: Sequence[Edge]) -> List[int]:    Function
`ratio_resolve` utility or script function.
L75: def ratio_reduce(    Function `ratio_reduce` utility or script function.
L107: def ratio_distribute(    Function `ratio_distribute` utility or script function.
L147: class E:    Class (`E`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pip/_vendor/rich/file_proxy.py

```

L11: class FileProxy(io.TextIOBase):    Class (`FileProxy`) component used by the app (see
file context: None).
L14: def __init__(self, console: "Console", file: IO[str]) -> None:    Function `__init__`
utility or script function.
L21: def rich_proxied_file(self) -> IO[str]:    Function `rich_proxied_file` utility or
script function.
L25: def __getattr__(self, name: str) -> Any:    Function `__getattr__` utility or script
function.
L28: def write(self, text: str) -> int:    Function `write` utility or script function.
L50: def flush(self) -> None:    Function `flush` utility or script function.
L56: def fileno(self) -> int:    Function `fileno` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/certifi/core.py

```

L10: def exit_cacert_ctx() -> None:    Function `exit_cacert_ctx` utility or script function.
L21: def where() -> str:    Function `where` utility or script function.
L46: def contents() -> str:    Function `contents` utility or script function.
L56: def where() -> str:    Function `where` utility or script function.
L82: def contents() -> str:    Function `contents` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic_core/__init__.py

```

L74: class ErrorDetails(_TypedDict):    Class (`ErrorDetails`) component used by the app (see
file context: None).
L100: class InitErrorDetails(_TypedDict):    Class (`InitErrorDetails`) component used by the
app (see file context: None).
L114: class ErrorTypeInfo(_TypedDict):    Class (`ErrorTypeInfo`) component used by the app
(see file context: None).
L133: class MultiHostHost(_TypedDict):    Class (`MultiHostHost`) component used by the app
(see file context: None).
L162: class Configuration(BaseModel):    Class (`Configuration`) component used by the app
(see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic_core/core_schem

a.py

```

L43: class CoreConfig(TypedDict, total=False):  Class (`CoreConfig`) component used by the
app (see file context: None).
L133: class SerializationInfo(Protocol[ContextT]):  Class (`SerializationInfo`) component
used by the app (see file context: None).
L137: def include(self) -> IncExCall:  Function `include` utility or script function.
L142: def exclude(self) -> IncExCall:  Function `exclude` utility or script function.
L147: def context(self) -> ContextT:  Function `context` utility or script function.
L152: def mode(self) -> Literal['python', 'json'] | str:  Function `mode` utility or script
function.
L157: def by_alias(self) -> bool:  Function `by_alias` utility or script function.
L162: def exclude_unset(self) -> bool:  Function `exclude_unset` utility or script
function.
L167: def exclude_defaults(self) -> bool:  Function `exclude_defaults` utility or script
function.
L172: def exclude_none(self) -> bool:  Function `exclude_none` utility or script function.
L177: def exclude_computed_fields(self) -> bool:  Function `exclude_computed_fields`
utility or script function.
L182: def serialize_as_any(self) -> bool:  Function `serialize_as_any` utility or script
function.
L187: def polymorphic_serialization(self) -> bool | None:  Function
`polymorphic_serialization` utility or script function.
L192: def round_trip(self) -> bool:  Function `round_trip` utility or script function.
L196: def mode_is_json(self) -> bool: ...  Function `mode_is_json` utility or script
function.
L198: def __str__(self) -> str: ...  Function `__str__` utility or script function.
L200: def __repr__(self) -> str: ...  Function `__repr__` utility or script function.
L203: class FieldSerializationInfo(SerializationInfo[ContextT], Protocol):  Class
(`FieldSerializationInfo`) component used by the app (see file context: None).
L207: def field_name(self) -> str:  Function `field_name` utility or script function.
L212: class ValidationInfo(Protocol[ContextT]):  Class (`ValidationInfo`) component used by
the app (see file context: None).
L216: def context(self) -> ContextT:  Function `context` utility or script function.
L221: def config(self) -> CoreConfig | None:  Function `config` utility or script function.
L226: def mode(self) -> Literal['python', 'json']:  Function `mode` utility or script
function.
L231: def data(self) -> dict[str, Any]:  Function `data` utility or script function.
L236: def field_name(self) -> str | None:  Function `field_name` utility or script
function.
L270: class SimpleSerSchema(TypedDict, total=False):  Class (`SimpleSerSchema`) component
used by the app (see file context: None).
L274: def simple_ser_schema(type: ExpectedSerializationTypes) -> SimpleSerSchema:  Function
`simple_ser_schema` utility or script function.
L310: class PlainSerializerFunctionSerSchema(TypedDict, total=False):  Class
(`PlainSerializerFunctionSerSchema`) component used by the app (see file context: None).
L319: def plain_serializer_function_ser_schema(  Function
`plain_serializer_function_ser_schema` utility or script function.
L351: class SerializerFunctionWrapHandler(Protocol):  # pragma: no cover  Class
(`SerializerFunctionWrapHandler`) component used by the app (see file context: None).

```

```

L352: def __call__(self, input_value: Any, index_key: int | str | None = None, /) -> Any: ...
    Function `__call__` utility or script function.
L371: class WrapSerializerFunctionSerSchema(TypedDict, total=False):    Class
(`WrapSerializerFunctionSerSchema`) component used by the app (see file context: None).
L381: def wrap_serializer_function_ser_schema(    Function
`wrap_serializer_function_ser_schema` utility or script function.
L416: class FormatSerSchema(TypedDict, total=False):    Class (`FormatSerSchema`) component
used by the app (see file context: None).
L422: def format_ser_schema(formatting_string: str, *, when_used: WhenUsed =
'json-unless-none') -> FormatSerSchema:    Function `format_ser_schema` utility or script
function.
L436: class ToStringSerSchema(TypedDict, total=False):    Class (`ToStringSerSchema`)
component used by the app (see file context: None).
L441: def to_string_ser_schema(*, when_used: WhenUsed = 'json-unless-none') ->
ToStringSerSchema:    Function `to_string_ser_schema` utility or script function.
L455: class ModelSerSchema(TypedDict, total=False):    Class (`ModelSerSchema`) component
used by the app (see file context: None).
L461: def model_ser_schema(cls: type[Any], schema: CoreSchema) -> ModelSerSchema:    Function
`model_ser_schema` utility or script function.
L482: class InvalidSchema(TypedDict, total=False):    Class (`InvalidSchema`) component used
by the app (see file context: None).
L491: def invalid_schema(ref: str | None = None, metadata: dict[str, Any] | None = None) ->
InvalidSchema:    Function `invalid_schema` utility or script function.
L503: class ComputedField(TypedDict, total=False):    Class (`ComputedField`) component used
by the app (see file context: None).
L512: def computed_field(    Function `computed_field` utility or script function.
L539: class AnySchema(TypedDict, total=False):    Class (`AnySchema`) component used by the
app (see file context: None).
L546: def any_schema(    Function `any_schema` utility or script function.
L568: class NoneSchema(TypedDict, total=False):    Class (`NoneSchema`) component used by the
app (see file context: None).
L575: def none_schema(    Function `none_schema` utility or script function.
L597: class BoolSchema(TypedDict, total=False):    Class (`BoolSchema`) component used by the
app (see file context: None).
L605: def bool_schema(    Function `bool_schema` utility or script function.
L631: class IntSchema(TypedDict, total=False):    Class (`IntSchema`) component used by the
app (see file context: None).
L644: def int_schema(    Function `int_schema` utility or script function.
L692: class FloatSchema(TypedDict, total=False):    Class (`FloatSchema`) component used by
the app (see file context: None).
L706: def float_schema(    Function `float_schema` utility or script function.
L757: class DecimalSchema(TypedDict, total=False):    Class (`DecimalSchema`) component used
by the app (see file context: None).
L773: def decimal_schema(    Function `decimal_schema` utility or script function.
L831: class ComplexSchema(TypedDict, total=False):    Class (`ComplexSchema`) component used
by the app (see file context: None).
L839: def complex_schema(    Function `complex_schema` utility or script function.
L873: class StringSchema(TypedDict, total=False):    Class (`StringSchema`) component used by
the app (see file context: None).
L889: def str_schema(    Function `str_schema` utility or script function.
L951: class BytesSchema(TypedDict, total=False):    Class (`BytesSchema`) component used by

```



```

the app (see file context: None).
L961: def bytes_schema(    Function `bytes_schema`    utility or script function.
L1000: class DateSchema(TypedDict, total=False):    Class (`DateSchema`)    component used by
the app (see file context: None).
L1016: def date_schema(    Function `date_schema`    utility or script function.
L1068: class TimeSchema(TypedDict, total=False):    Class (`TimeSchema`)    component used by
the app (see file context: None).
L1082: def time_schema(    Function `time_schema`    utility or script function.
L1134: class DatetimeSchema(TypedDict, total=False):    Class (`DatetimeSchema`)    component
used by the app (see file context: None).
L1152: def datetime_schema(    Function `datetime_schema`    utility or script function.
L1212: class TimedeltaSchema(TypedDict, total=False):    Class (`TimedeltaSchema`)    component
used by the app (see file context: None).
L1225: def timedelta_schema(    Function `timedelta_schema`    utility or script function.
L1274: class LiteralSchema(TypedDict, total=False):    Class (`LiteralSchema`)    component used
by the app (see file context: None).
L1282: def literal_schema(    Function `literal_schema`    utility or script function.
L1309: class EnumSchema(TypedDict, total=False):    Class (`EnumSchema`)    component used by
the app (see file context: None).
L1321: def enum_schema(    Function `enum_schema`    utility or script function.
L1339: class Color(Enum):    Class (`Color`)    component used by the app (see file context:
None).
L1372: class MissingSentinelSchema(TypedDict, total=False):    Class (`MissingSentinelSchema`)
component used by the app (see file context: None).
L1378: def missing_sentinel_schema(    Function `missing_sentinel_schema`    utility or script
function.
L1395: class IsInstanceSchema(TypedDict, total=False):    Class (`IsInstanceSchema`)
component used by the app (see file context: None).
L1404: def is_instance_schema(    Function `is_instance_schema`    utility or script function.
L1418: class A:    Class (`A`)    component used by the app (see file context: None).
L1438: class IsSubclassSchema(TypedDict, total=False):    Class (`IsSubclassSchema`)
component used by the app (see file context: None).
L1447: def is_subclass_schema(    Function `is_subclass_schema`    utility or script function.
L1461: class A:    Class (`A`)    component used by the app (see file context: None).
L1464: class B(A):    Class (`B`)    component used by the app (see file context: None).
L1484: class CallableSchema(TypedDict, total=False):    Class (`CallableSchema`)    component
used by the app (see file context: None).
L1491: def callable_schema(    Function `callable_schema`    utility or script function.
L1513: class UuidSchema(TypedDict, total=False):    Class (`UuidSchema`)    component used by
the app (see file context: None).
L1522: def uuid_schema(    Function `uuid_schema`    utility or script function.
L1535: class IncExSeqSerSchema(TypedDict, total=False):    Class (`IncExSeqSerSchema`)
component used by the app (see file context: None).
L1541: def filter_seq_schema(*, include: set[int] | None = None, exclude: set[int] | None =
None) -> IncExSeqSerSchema:    Function `filter_seq_schema`    utility or script function.
L1548: class ListSchema(TypedDict, total=False):    Class (`ListSchema`)    component used by
the app (see file context: None).
L1560: def list_schema(    Function `list_schema`    utility or script function.
L1606: def tuple_positional_schema(    Function `tuple_positional_schema`    utility or script
function.
L1655: def tuple_variable_schema(    Function `tuple_variable_schema`    utility or script

```



```

function.
L1699: class TupleSchema(TypedDict, total=False):  Class (`TupleSchema`) component used by
the app (see file context: None).
L1712: def tuple_schema(  Function `tuple_schema` utility or script function.
L1763: class SetSchema(TypedDict, total=False):  Class (`SetSchema`) component used by the
app (see file context: None).
L1775: def set_schema(  Function `set_schema` Sets or updates a value.
L1822: class FrozenSetSchema(TypedDict, total=False):  Class (`FrozenSetSchema`) component
used by the app (see file context: None).
L1834: def frozenset_schema(  Function `frozenset_schema` utility or script function.
L1881: class GeneratorSchema(TypedDict, total=False):  Class (`GeneratorSchema`) component
used by the app (see file context: None).
L1891: def generator_schema(  Function `generator_schema` utility or script function.
L1907: def gen() -> Iterator[int]:  Function `gen` utility or script function.
L1941: class IncExDictSerSchema(TypedDict, total=False):  Class (`IncExDictSerSchema`)
component used by the app (see file context: None).
L1947: def filter_dict_schema(*, include: IncExDict | None = None, exclude: IncExDict | None
= None) -> IncExDictSerSchema:  Function `filter_dict_schema` utility or script function.
L1954: class DictSchema(TypedDict, total=False):  Class (`DictSchema`) component used by
the app (see file context: None).
L1967: def dict_schema(  Function `dict_schema` utility or script function.
L2021: class NoInfoValidatorFunctionSchema(TypedDict):  Class
(`NoInfoValidatorFunctionSchema`) component used by the app (see file context: None).
L2030: class WithInfoValidatorFunctionSchema(TypedDict, total=False):  Class
(`WithInfoValidatorFunctionSchema`) component used by the app (see file context: None).
L2039: class _ValidatorFunctionSchema(TypedDict, total=False):  Class
(`_ValidatorFunctionSchema`) component used by the app (see file context: None).
L2047: class BeforeValidatorFunctionSchema(_ValidatorFunctionSchema, total=False):  Class
(`BeforeValidatorFunctionSchema`) component used by the app (see file context: None).
L2052: def no_info_before_validator_function(  Function `no_info_before_validator_function`
utility or script function.
L2067: def fn(v: bytes) -> str:  Function `fn` utility or script function.
L2098: def with_info_before_validator_function(  Function
`with_info_before_validator_function` utility or script function.
L2115: def fn(v: bytes, info: core_schema.ValidationInfo) -> str:  Function `fn` utility or
script function.
L2156: class AfterValidatorFunctionSchema(_ValidatorFunctionSchema, total=False):  Class
(`AfterValidatorFunctionSchema`) component used by the app (see file context: None).
L2160: def no_info_after_validator_function(  Function `no_info_after_validator_function`
utility or script function.
L2175: def fn(v: str) -> str:  Function `fn` utility or script function.
L2204: def with_info_after_validator_function(  Function
`with_info_after_validator_function` utility or script function.
L2220: def fn(v: str, info: core_schema.ValidationInfo) -> str:  Function `fn` utility or
script function.
L2259: class ValidatorFunctionWrapHandler(Protocol):  Class (`ValidatorFunctionWrapHandler`)
component used by the app (see file context: None).
L2260: def __call__(self, input_value: Any, outer_location: str | int | None = None, /) ->
Any:  # pragma: no cover  Function `__call__` utility or script function.
L2268: class NoInfoWrapValidatorFunctionSchema(TypedDict):  Class
(`NoInfoWrapValidatorFunctionSchema`) component used by the app (see file context: None).

```

```

L2277: class WithInfoWrapValidatorFunctionSchema(TypedDict, total=False):  Class
(`WithInfoWrapValidatorFunctionSchema`) component used by the app (see file context: None).
L2286: class WrapValidatorFunctionSchema(TypedDict, total=False):  Class
(`WrapValidatorFunctionSchema`) component used by the app (see file context: None).
L2296: def no_info_wrap_validator_function(  Function `no_info_wrap_validator_function`
utility or script function.
L2313: def fn(  Function `fn` utility or script function.
L2345: def with_info_wrap_validator_function(  Function `with_info_wrap_validator_function`
utility or script function.
L2363: def fn(  Function `fn` utility or script function.
L2404: class PlainValidatorFunctionSchema(TypedDict, total=False):  Class
(`PlainValidatorFunctionSchema`) component used by the app (see file context: None).
L2413: def no_info_plain_validator_function(  Function `no_info_plain_validator_function`
utility or script function.
L2427: def fn(v: str) -> str:  Function `fn` utility or script function.
L2453: def with_info_plain_validator_function(  Function
`with_info_plain_validator_function` utility or script function.
L2468: def fn(v: str, info: core_schema.ValidationInfo) -> str:  Function `fn` utility or
script function.
L2502: class WithDefaultSchema(TypedDict, total=False):  Class (`WithDefaultSchema`)
component used by the app (see file context: None).
L2516: def with_default_schema(  Function `with_default_schema` utility or script function.
L2572: class NullableSchema(TypedDict, total=False):  Class (`NullableSchema`) component
used by the app (see file context: None).
L2581: def nullable_schema(  Function `nullable_schema` utility or script function.
L2612: class UnionSchema(TypedDict, total=False):  Class (`UnionSchema`) component used by
the app (see file context: None).
L2627: def union_schema(  Function `union_schema` utility or script function.
L2678: class TaggedUnionSchema(TypedDict, total=False):  Class (`TaggedUnionSchema`)
component used by the app (see file context: None).
L2692: def tagged_union_schema(  Function `tagged_union_schema` utility or script function.
L2775: class ChainSchema(TypedDict, total=False):  Class (`ChainSchema`) component used by
the app (see file context: None).
L2783: def chain_schema(  Function `chain_schema` utility or script function.
L2796: def fn(v: str, info: core_schema.ValidationInfo) -> str:  Function `fn` utility or
script function.
L2817: class LaxOrStrictSchema(TypedDict, total=False):  Class (`LaxOrStrictSchema`)
component used by the app (see file context: None).
L2827: def lax_or_strict_schema(  Function `lax_or_strict_schema` utility or script
function.
L2842: def fn(v: str, info: core_schema.ValidationInfo) -> str:  Function `fn` utility or
script function.
L2881: class JsonOrPythonSchema(TypedDict, total=False):  Class (`JsonOrPythonSchema`)
component used by the app (see file context: None).
L2890: def json_or_python_schema(  Function `json_or_python_schema` utility or script
function.
L2938: class TypedDictField(TypedDict, total=False):  Class (`TypedDictField`) component
used by the app (see file context: None).
L2949: def typed_dict_field(  Function `typed_dict_field` utility or script function.
L2989: class TypedDictSchema(TypedDict, total=False):  Class (`TypedDictSchema`) component
used by the app (see file context: None).

```

```

L3006: def typed_dict_schema(    Function `typed_dict_schema`    utility or script function.
L3029: class MyTypedDict(TypedDict):    Class (`MyTypedDict`)    component used by the app (see
file context: None).
L3070: class ModelField(TypedDict, total=False):    Class (`ModelField`)    component used by
the app (see file context: None).
L3081: def model_field(    Function `model_field`    utility or script function.
L3121: class ModelFieldsSchema(TypedDict, total=False):    Class (`ModelFieldsSchema`)
component used by the app (see file context: None).
L3136: def model_fields_schema(    Function `model_fields_schema`    utility or script function.
L3193: class ModelSchema(TypedDict, total=False):    Class (`ModelSchema`)    component used by
the app (see file context: None).
L3211: def model_schema(    Function `model_schema`    utility or script function.
L3239: class MyModel:    Class (`MyModel`)    component used by the app (see file context:
None).
L3296: class DataclassField(TypedDict, total=False):    Class (`DataclassField`)    component
used by the app (see file context: None).
L3311: def dataclass_field(    Function `dataclass_field`    utility or script function.
L3368: class DataclassArgsSchema(TypedDict, total=False):    Class (`DataclassArgsSchema`)
component used by the app (see file context: None).
L3380: def dataclass_args_schema(    Function `dataclass_args_schema`    utility or script
function.
L3431: class DataclassSchema(TypedDict, total=False):    Class (`DataclassSchema`)    component
used by the app (see file context: None).
L3449: def dataclass_schema(    Function `dataclass_schema`    utility or script function.
L3508: class ArgumentsParameter(TypedDict, total=False):    Class (`ArgumentsParameter`)
component used by the app (see file context: None).
L3515: def arguments_parameter(    Function `arguments_parameter`    utility or script function.
L3548: class ArgumentsSchema(TypedDict, total=False):    Class (`ArgumentsSchema`)    component
used by the app (see file context: None).
L3561: def arguments_schema(    Function `arguments_schema`    utility or script function.
L3617: class ArgumentsV3Parameter(TypedDict, total=False):    Class (`ArgumentsV3Parameter`)
component used by the app (see file context: None).
L3631: def arguments_v3_parameter(    Function `arguments_v3_parameter`    utility or script
function.
L3669: class ArgumentsV3Schema(TypedDict, total=False):    Class (`ArgumentsV3Schema`)
component used by the app (see file context: None).
L3680: def arguments_v3_schema(    Function `arguments_v3_schema`    utility or script function.
L3731: class CallSchema(TypedDict, total=False):    Class (`CallSchema`)    component used by
the app (see file context: None).
L3742: def call_schema(    Function `call_schema`    utility or script function.
L3796: class CustomErrorSchema(TypedDict, total=False):    Class (`CustomErrorSchema`)
component used by the app (see file context: None).
L3807: def custom_error_schema(    Function `custom_error_schema`    utility or script function.
L3853: class JsonSchema(TypedDict, total=False):    Class (`JsonSchema`)    component used by
the app (see file context: None).
L3861: def json_schema(    Function `json_schema`    utility or script function.
L3881: class MyModel:    Class (`MyModel`)    component used by the app (see file context:
None).
L3907: class UrlSchema(TypedDict, total=False):    Class (`UrlSchema`)    component used by the
app (see file context: None).
L3921: def url_schema(    Function `url_schema`    utility or script function.

```

```

L3976: class MultiHostUrlSchema(TypedDict, total=False):  Class (`MultiHostUrlSchema`)
component used by the app (see file context: None).
L3990: def multi_host_url_schema(  Function `multi_host_url_schema`  utility or script
function.
L4045: class DefinitionsSchema(TypedDict, total=False):  Class (`DefinitionsSchema`)
component used by the app (see file context: None).
L4053: def definitions_schema(schema: CoreSchema, definitions: list[CoreSchema]) ->
DefinitionsSchema:  Function `definitions_schema`  utility or script function.
L4076: class DefinitionReferenceSchema(TypedDict, total=False):  Class
(`DefinitionReferenceSchema`)  component used by the app (see file context: None).
L4084: def definition_reference_schema(  Function `definition_reference_schema`  utility or
script function.
L4349: def _dict_not_none(**kwargs: Any) -> Any:  Function `_dict_not_none`  utility or
script function.
L4353: def iter_union_choices(union_schema: UnionSchema) -> Generator[CoreSchema]:  Function
`iter_union_choices`  utility or script function.
L4368: def field_before_validator_function(function: WithInfoValidatorFunction, field_name:
str, schema: CoreSchema, **kwargs):  Function `field_before_validator_function`  utility or
script function.
L4377: def general_before_validator_function(*args, **kwargs):  Function
`general_before_validator_function`  utility or script function.
L4386: def field_after_validator_function(function: WithInfoValidatorFunction, field_name:
str, schema: CoreSchema, **kwargs):  Function `field_after_validator_function`  utility or
script function.
L4395: def general_after_validator_function(*args, **kwargs):  Function
`general_after_validator_function`  utility or script function.
L4404: def field_wrap_validator_function(  Function `field_wrap_validator_function`  utility
or script function.
L4415: def general_wrap_validator_function(*args, **kwargs):  Function
`general_wrap_validator_function`  utility or script function.
L4424: def field_plain_validator_function(function: WithInfoValidatorFunction, field_name:
str, **kwargs):  Function `field_plain_validator_function`  utility or script function.
L4433: def general_plain_validator_function(*args, **kwargs):  Function
`general_plain_validator_function`  utility or script function.
L4452: def __getattr__(attr_name: str) -> object:  Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/functional_validators.py

```

L29: class AfterValidator:  Class (`AfterValidator`)  component used by the app (see file
context: None).
L46: class Model(BaseModel):  Class (`Model`)  component used by the app (see file context:
None).
L74: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:  Function `__get_pydantic_core_schema__`  utility or script
function.

```

```

L85: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:    Function
`_from_decorator` utility or script function.
L90: class BeforeValidator:    Class (`BeforeValidator`) component used by the app (see file
context: None).
L109: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L126: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__` utility or script
function.
L149: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:    Function
`_from_decorator` utility or script function.
L157: class PlainValidator:    Class (`PlainValidator`) component used by the app (see file
context: None).
L179: def validate(v: object) -> int:    Object (singleton).
L190: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L207: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__` utility or script
function.
L249: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:    Function
`_from_decorator` utility or script function.
L257: class WrapValidator:    Class (`WrapValidator`) component used by the app (see file
context: None).
L274: def validate_timestamp(v, handler):    Function `validate_timestamp` utility or script
function.
L286: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L299: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__` utility or script
function.
L324: def _from_decorator(cls, decorator:
_decorators.Decorator[_decorators.FieldValidatorDecoratorInfo]) -> Self:    Function
`_from_decorator` utility or script function.
L333: class _OnlyValueValidatorClsMethod(Protocol):    Class (`_OnlyValueValidatorClsMethod`)
component used by the app (see file context: None).
L334: def __call__(self, cls: Any, value: Any, /) -> Any: ...    Function `__call__` utility
or script function.
L336: class _V2ValidatorClsMethod(Protocol):    Class (`_V2ValidatorClsMethod`) component
used by the app (see file context: None).
L337: def __call__(self, cls: Any, value: Any, info: core_schema.ValidationInfo[Any], /) ->
Any: ...    Function `__call__` utility or script function.
L339: class _OnlyValueWrapValidatorClsMethod(Protocol):    Class
(`_OnlyValueWrapValidatorClsMethod`) component used by the app (see file context: None).
L340: def __call__(self, cls: Any, value: Any, handler:
core_schema.ValidatorFunctionWrapHandler, /) -> Any: ...    Function `__call__` utility or
script function.
L342: class _V2WrapValidatorClsMethod(Protocol):    Class (`_V2WrapValidatorClsMethod`)
component used by the app (see file context: None).

```

```

L343: def __call__(    Function `__call__`    utility or script function.
L378: def field_validator(    Function `field_validator`    utility or script function.
L389: def field_validator(    Function `field_validator`    utility or script function.
L400: def field_validator(    Function `field_validator`    utility or script function.
L409: def field_validator( # noqa: D417    Function `field_validator`    utility or script
function.
L432: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L437: def ensure_foobar(cls, v: Any):    Function `ensure_foobar`    utility or script function.
L497: def dec(    Function `dec`    utility or script function.
L521: class ModelWrapValidatorHandler(core_schema.ValidatorFunctionWrapHandler,
Protocol[_ModelTypeCo]):    Class (`ModelWrapValidatorHandler`)    component used by the app
(see file context: None).
L524: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L533: class ModelWrapValidatorWithoutInfo(Protocol[_ModelType]):    Class
(`ModelWrapValidatorWithoutInfo`)    component used by the app (see file context: None).
L538: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L550: class ModelWrapValidator(Protocol[_ModelType]):    Class (`ModelWrapValidator`)
component used by the app (see file context: None).
L553: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L566: class FreeModelBeforeValidatorWithoutInfo(Protocol):    Class
(`FreeModelBeforeValidatorWithoutInfo`)    component used by the app (see file context: None).
L571: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L581: class ModelBeforeValidatorWithoutInfo(Protocol):    Class
(`ModelBeforeValidatorWithoutInfo`)    component used by the app (see file context: None).
L586: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L597: class FreeModelBeforeValidator(Protocol):    Class (`FreeModelBeforeValidator`)
component used by the app (see file context: None).
L600: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L611: class ModelBeforeValidator(Protocol):    Class (`ModelBeforeValidator`)    component used
by the app (see file context: None).
L614: def __call__( # noqa: D102    Function `__call__`    utility or script function.
L642: def model_validator(    Function `model_validator`    utility or script function.
L651: def model_validator(    Function `model_validator`    utility or script function.
L660: def model_validator(    Function `model_validator`    utility or script function.
L668: def model_validator(    Function `model_validator`    utility or script function.
L683: class Square(BaseModel):    Class (`Square`)    component used by the app (see file
context: None).
L688: def verify_square(self) -> Self:    Function `verify_square`    utility or script
function.
L717: def dec(f: Any) -> _decorators.PydanticDescriptorProxy[Any]:    Function `dec`    utility
or script function.
L746: class InstanceOf:    Class (`InstanceOf`)    component used by the app (see file context:
None).
L753: class Foo:    Class (`Foo`)    component used by the app (see file context: None).
L756: class Bar(BaseModel):    Class (`Bar`)    component used by the app (see file context:
None).
L780: def __class_getitem__(cls, item: AnyType) -> AnyType:    Function `__class_getitem__`
utility or script function.
L784: def __get_pydantic_core_schema__(cls, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`    utility or script

```

```

function.
L811: class SkipValidation:    Class (`SkipValidation`)    component used by the app (see file
context: None).
L823: def __class_getitem__(cls, item: Any) -> Any:    Function `__class_getitem__`    utility
or script function.
L827: def __get_pydantic_core_schema__(cls, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`    utility or script
function.
L845: class ValidateAs:    Class (`ValidateAs`)    component used by the app (see file context:
None).
L859: class MyCls:    Class (`MyCls`)    component used by the app (see file context: None).
L860: def __init__(self, a: int) -> None:    Function `__init__`    utility or script function.
L863: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L866: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L880: def __init__(self, from_type: type[_FromTypeT], /, instantiation_hook:
Callable[[_FromTypeT], Any]) -> None:    Function `__init__`    utility or script function.
L884: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/alias_generators.py

```

L12: def to_pascal(snake: str) -> str:    Function `to_pascal`    utility or script function.
L25: def to_camel(snake: str) -> str:    Function `to_camel`    utility or script function.
L43: def to_snake(camel: str) -> str:    Function `to_snake`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_migration.py

```

L251: def getattr_migration(module: str) -> Callable[[str], Any]:    Function
`getattr_migration`    Returns or fetches data.
L264: def wrapper(name: str) -> object:    Object (singleton).

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/mypy.py

```

L111: def plugin(version: str) -> type[Plugin]:    Function `plugin`    utility or script
function.
L126: class PydanticPlugin(Plugin):    Class (`PydanticPlugin`)    component used by the app
(see file context: None).

```



```

L129: def __init__(self, options: Options) -> None:    Function `__init__`    utility or script
function.
L134: def get_base_class_hook(self, fullname: str) -> Callable[[ClassDefContext], None] |
None:    Function `get_base_class_hook`    Returns or fetches data.
L143: def get_metaclass_hook(self, fullname: str) -> Callable[[ClassDefContext], None] |
None:    Function `get_metaclass_hook`    Returns or fetches data.
L149: def get_method_hook(self, fullname: str) -> Callable[[MethodContext], Type] | None:
Function `get_method_hook`    Returns or fetches data.
L155: def get_dynamic_class_hook(self, fullname: str) -> Callable[[DynamicClassDefContext],
None] | None:    Function `get_dynamic_class_hook`    Returns or fetches data.
L161: def report_config_data(self, ctx: ReportConfigContext) -> dict[str, Any]:    Function
`report_config_data`    utility or script function.
L168: def _pydantic_model_class_maker_callback(self, ctx: ClassDefContext) -> None:
Function `_pydantic_model_class_maker_callback`    utility or script function.
L172: def _pydantic_model_metaclass_marker_callback(self, ctx: ClassDefContext) -> None:
Function `_pydantic_model_metaclass_marker_callback`    utility or script function.
L185: def _pydantic_create_model_callback(self, ctx: DynamicClassDefContext) -> None:
Function `_pydantic_create_model_callback`    utility or script function.
L213: class PydanticPluginConfig:    Class (`PydanticPluginConfig`)    component used by the app
(see file context: None).
L235: def __init__(self, options: Options) -> None:    Function `__init__`    utility or script
function.
L254: def to_data(self) -> dict[str, Any]:    Function `to_data`    utility or script function.
L259: def from_attributes_callback(ctx: MethodContext) -> Type:    Function
`from_attributes_callback`    utility or script function.
L285: class PydanticModelField:    Class (`PydanticModelField`)    component used by the app
(see file context: None).
L288: def __init__(    Function `__init__`    utility or script function.
L312: def to_argument(    Function `to_argument`    utility or script function.
L341: def expand_type(    Function `expand_type`    utility or script function.
L386: def to_var(    Function `to_var`    utility or script function.
L401: def serialize(self) -> JsonDict:    Function `serialize`    utility or script function.
L417: def deserialize(cls, info: TypeInfo, data: JsonDict, api:
SemanticAnalyzerPluginInterface) -> PydanticModelField:    Function `deserialize`    utility or
script function.
L423: def expand_typevar_from_subtype(self, sub_type: TypeInfo, api:
SemanticAnalyzerPluginInterface) -> None:    Function `expand_typevar_from_subtype`    utility
or script function.
L432: class PydanticModelClassVar:    Class (`PydanticModelClassVar`)    component used by the
app (see file context: None).
L441: def __init__(self, name):    Function `__init__`    utility or script function.
L445: def deserialize(cls, data: JsonDict) -> PydanticModelClassVar:    Function `deserialize`
utility or script function.
L450: def serialize(self) -> JsonDict:    Function `serialize`    utility or script function.
L457: class PydanticModelTransformer:    Class (`PydanticModelTransformer`)    component used by
the app (see file context: None).
L475: def __init__(    Function `__init__`    utility or script function.
L488: def transform(self) -> bool:    Function `transform`    utility or script function.
L524: def adjust_decorator_signatures(self) -> None:    Function `adjust_decorator_signatures`
utility or script function.
L551: def collect_config(self) -> ModelConfigData:    # noqa: C901 (ignore complexity)

```



```

Function `collect_config` utility or script function.
L627: def collect_fields_and_class_vars( Function `collect_fields_and_class_vars` utility
or script function.
L695: def _get_assignment_statements_from_if_statement(self, stmt: IfStmt) ->
Iterator[AssignmentStmt]: Function `_get_assignment_statements_from_if_statement` utility
or script function.
L702: def _get_assignment_statements_from_block(self, block: Block) ->
Iterator[AssignmentStmt]: Function `_get_assignment_statements_from_block` utility or
script function.
L709: def collect_field_or_class_var_from_stmt( # noqa C901 Function
`collect_field_or_class_var_from_stmt` utility or script function.
L846: def _infer_dataclass_attr_init_type(self, sym: SymbolTableNode, name: str, context:
Context) -> Type | None: Function `_infer_dataclass_attr_init_type` utility or script
function.
L884: def add_initializer( Function `add_initializer` utility or script function.
L941: def add_model_construct_method( Function `add_model_construct_method` utility or
script function.
L981: def set_frozen(self, fields: list[PydanticModelField], api:
SemanticAnalyzerPluginInterface, frozen: bool) -> None: Function `set_frozen` Sets or
updates a value.
L1006: def get_config_update(self, name: str, arg: Expression, lax_extra: bool = False) ->
ModelConfigData | None: Function `get_config_update` Returns or fetches data.
L1042: def get_has_default(stmt: AssignmentStmt) -> bool: Function `get_has_default`
Returns or fetches data.
L1064: def get_strict(stmt: AssignmentStmt) -> bool | None: Function `get_strict` Returns
or fetches data.
L1080: def get_alias_info(stmt: AssignmentStmt) -> tuple[str | None, bool]: Function
`get_alias_info` Returns or fetches data.
L1110: def is_field_frozen(stmt: AssignmentStmt) -> bool: Function `is_field_frozen`
utility or script function.
L1134: def get_field_arguments( Function `get_field_arguments` Returns or fetches data.
L1166: def should_init_forbid_extra(self, fields: list[PydanticModelField], config:
ModelConfigData) -> bool: Function `should_init_forbid_extra` utility or script function.
L1180: def is_dynamic_alias_present(fields: list[PydanticModelField], has_alias_generator:
bool) -> bool: Function `is_dynamic_alias_present` utility or script function.
L1194: class ChangeExplicitTypeOfAny(TypeTranslator): Class (`ChangeExplicitTypeOfAny`)
component used by the app (see file context: None).
L1197: def __init__(self, type_of_any: int) -> None: Function `__init__` utility or script
function.
L1201: def visit_any(self, t: AnyType) -> Type: # noqa: D102 Function `visit_any` utility
or script function.
L1208: class ModelConfigData: Class (`ModelConfigData`) component used by the app (see
file context: None).
L1211: def __init__( Function `__init__` utility or script function.
L1231: def get_values_dict(self) -> dict[str, Any]: Function `get_values_dict` Returns or
fetches data.
L1238: def update(self, config: ModelConfigData | None) -> None: Function `update` utility
or script function.
L1245: def setdefault(self, key: str, value: Any) -> None: Function `setdefault` Sets or
updates a value.
L1251: def is_root_model(info: TypeInfo) -> bool: Function `is_root_model` utility or

```

```

script function.
L1265: def error_from_attributes(model_name: str, api: CheckerPluginInterface, context:
Context) -> None:    Function `error_from_attributes`    utility or script function.
L1270: def error_invalid_config_value(name: str, api: SemanticAnalyzerPluginInterface,
context: Context) -> None:    Function `error_invalid_config_value`    utility or script
function.
L1275: def error_required_dynamic_aliases(api: SemanticAnalyzerPluginInterface, context:
Context) -> None:    Function `error_required_dynamic_aliases`    utility or script function.
L1283: def error_unexpected_behavior(    Function `error_unexpected_behavior`    utility or
script function.
L1294: def error_untyped_fields(api: SemanticAnalyzerPluginInterface, context: Context) ->
None:    Function `error_untyped_fields`    utility or script function.
L1299: def error_extra_fields_on_root_model(api: CheckerPluginInterface, context: Context) ->
None:    Function `error_extra_fields_on_root_model`    utility or script function.
L1304: def add_method(    Function `add_method`    utility or script function.
L1392: def parse_toml(config_file: str) -> dict[str, Any] | None:    Function `parse_toml`
utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/fields.py

```

L50: class _FromFieldInfoInputs(TypedDict, total=False):    Class (`_FromFieldInfoInputs`)
component used by the app (see file context: None).
L92: class _FieldInfoInputs(_FromFieldInfoInputs, total=False):    Class (`_FieldInfoInputs`)
component used by the app (see file context: None).
L98: class _FieldInfoAsDict(TypedDict, closed=True):    Class (`_FieldInfoAsDict`)    component
used by the app (see file context: None).
L106: class FieldInfo(_repr.Representation):    Class (`FieldInfo`)    component used by the app
(see file context: None).
L228: def __init__(self, **kwargs: Unpack[_FieldInfoInputs]) -> None:    Function `__init__`
utility or script function.
L291: def from_field(default: Any = PydanticUndefined, **kwargs:
Unpack[_FromFieldInfoInputs]) -> FieldInfo:    Function `from_field`    utility or script
function.
L310: class MyModel(pydantic.BaseModel):    Class (`MyModel`)    component used by the app (see
file context: None).
L319: def from_annotation(annotation: type[Any], *, _source: AnnotationSource =
AnnotationSource.ANY) -> FieldInfo:    Function `from_annotation`    utility or script function.
L327: class MyModel(pydantic.BaseModel):    Class (`MyModel`)    component used by the app (see
file context: None).
L341: class MyModel(pydantic.BaseModel):    Class (`MyModel`)    component used by the app (see
file context: None).
L379: def from_annotated_attribute(    Function `from_annotated_attribute`    utility or script
function.
L393: class MyModel(pydantic.BaseModel):    Class (`MyModel`)    component used by the app (see
file context: None).
L480: def _construct(cls, metadata: list[Any], **attr_overrides: Any) -> Self:    Function
`_construct`    utility or script function.
L486: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:

```

```

None).
L577: def merge_field_infos(*field_infos: FieldInfo, **overrides: Any) -> FieldInfo:
Function `merge_field_infos` utility or script function.
L643: def _from_dataclass_field(dc_field: DataclassField[Any]) -> FieldInfo: Function
`_from_dataclass_field` utility or script function.
L671: def _collect_metadata(kwarg: dict[str, Any]) -> list[Any]: Function
`_collect_metadata` utility or script function.
L700: def deprecation_message(self) -> str | None: Function `deprecation_message` utility
or script function.
L709: def default_factory_takes_validated_data(self) -> bool | None: Function
`default_factory_takes_validated_data` utility or script function.
L718: def get_default( Function `get_default` Returns or fetches data.
L723: def get_default(self, *, call_default_factory: Literal[False] = ...) -> Any: ...
Function `get_default` Returns or fetches data.
L725: def get_default(self, *, call_default_factory: bool = False, validated_data: dict[str,
Any] | None = None) -> Any: Function `get_default` Returns or fetches data.
L746: def is_required(self) -> bool: Function `is_required` utility or script function.
L754: def rebuild_annotation(self) -> Any: Function `rebuild_annotation` utility or script
function.
L773: def apply_typevars_map( Function `apply_typevars_map` utility or script function.
L801: def asdict(self) -> _FieldInfoAsDict: Function `asdict` utility or script function.
L816: def _copy(self) -> Self: Function `_copy` utility or script function.
L835: def __repr_args__(self) -> ReprArgs: Function `__repr_args__` utility or script
function.
L872: class _EmptyKwargs(TypedDict): Class (`_EmptyKwargs`) component used by the app (see
file context: None).
L925: def Field( Function `Field` utility or script function.
L965: def Field( Function `Field` utility or script function.
L1005: def Field( Function `Field` utility or script function.
L1048: def Field( # pyright: ignore[reportOverlappingOverload] Function `Field` utility
or script function.
L1088: def Field( Function `Field` utility or script function.
L1131: def Field( # No default set Function `Field` utility or script function.
L1169: def Field( # noqa: C901 Function `Field` utility or script function.
L1401: class ModelPrivateAttr(_repr.Representation): Class (`ModelPrivateAttr`) component
used by the app (see file context: None).
L1417: def __init__( Function `__init__` utility or script function.
L1432: def __getattr__(self, item: str) -> Any: Function `__getattr__` utility or script
function.
L1441: def __set_name__(self, cls: type[Any], name: str) -> None: Function `__set_name__`
utility or script function.
L1451: def default_factory_takes_validated_data(self) -> bool | None: Function
`default_factory_takes_validated_data` utility or script function.
L1460: def get_default( Function `get_default` Returns or fetches data.
L1465: def get_default(self, *, call_default_factory: Literal[False] = ...) -> Any: ...
Function `get_default` Returns or fetches data.
L1467: def get_default(self, *, call_default_factory: bool = False, validated_data: dict[str,
Any] | None = None) -> Any: Function `get_default` Returns or fetches data.
L1488: def __eq__(self, other: Any) -> bool: Function `__eq__` utility or script function.
L1498: def PrivateAttr( Function `PrivateAttr` utility or script function.
L1504: def PrivateAttr( Function `PrivateAttr` utility or script function.

```

```

L1510: def PrivateAttr(    Function `PrivateAttr`    utility or script function.
L1514: def PrivateAttr(    Function `PrivateAttr`    utility or script function.
L1553: class ComputedFieldInfo:    Class (`ComputedFieldInfo`)    component used by the app (see
file context: None).
L1587: def __copy__(self) -> Self:    Function `__copy__`    utility or script function.
L1606: def deprecation_message(self) -> str | None:    Function `deprecation_message`    utility
or script function.
L1614: def _update_from_config(self, config_wrapper: ConfigWrapper, name: str) -> None:
Function `_update_from_config`    utility or script function.
L1622: def _apply_alias_generator(self, alias_generator: Callable[[str], str] |
AliasGenerator, name: str) -> None:    Function `_apply_alias_generator`    utility or script
function.
L1654: def _wrapped_property_is_private(property_: cached_property | property) -> bool: #
type: ignore    Function `_wrapped_property_is_private`    utility or script function.
L1672: def computed_field(func: PropertyT, /) -> PropertyT: ...    Function `computed_field`
utility or script function.
L1676: def computed_field(    Function `computed_field`    utility or script function.
L1692: def computed_field(    Function `computed_field`    utility or script function.
L1718: class Rectangle(BaseModel):    Class (`Rectangle`)    component used by the app (see file
context: None).
L1724: def area(self) -> int:    Function `area`    utility or script function.
L1748: class Square(BaseModel):    Class (`Square`)    component used by the app (see file
context: None).
L1752: def area(self) -> float: # converted to a `property` by `computed_field`    Function
`area`    utility or script function.
L1756: def area(self, new_area: float) -> None:    Function `area`    utility or script
function.
L1760: def random_number(self) -> int:    Function `random_number`    utility or script
function.
L1786: class Parent(BaseModel):    Class (`Parent`)    component used by the app (see file
context: None).
L1791: class Child(Parent):    Class (`Child`)    component used by the app (see file context:
None).
L1794: def a(self) -> str:    Function `a`    utility or script function.
L1811: class Model(BaseModel):    Class (`Model`)    component used by the app (see file
context: None).
L1816: def _private_cached_property(self) -> int:    Function `_private_cached_property`
utility or script function.
L1821: def _private_property(self) -> int:    Function `_private_property`    utility or script
function.
L1854: def dec(f: Any) -> Any:    Function `dec`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/json_schema.py

```

L103: class PydanticJsonSchemaWarning(UserWarning):    Class (`PydanticJsonSchemaWarning`)
component used by the app (see file context: None).
L140: class _DefinitionsRemapping:    Class (`_DefinitionsRemapping`)    component used by the

```

```

app (see file context: None).
L145: def from_prioritized_choices(    Function `from_prioritized_choices`    utility or script
function.
L196: def remap_defs_ref(self, ref: DefsRef) -> DefsRef:    Function `remap_defs_ref`    utility
or script function.
L199: def remap_json_ref(self, ref: JsonRef) -> JsonRef:    Function `remap_json_ref`    utility
or script function.
L202: def remap_json_schema(self, schema: Any) -> Any:    Function `remap_json_schema`
utility or script function.
L225: class GenerateJsonSchema:    Class (`GenerateJsonSchema`)    component used by the app
(see file context: None).
L273: def __init__(    Function `__init__`    utility or script function.
L316: def _config(self) -> _config.ConfigWrapper:    Function `_config`    utility or script
function.
L320: def mode(self) -> JsonSchemaMode:    Function `mode`    utility or script function.
L326: def build_schema_type_to_method(    Function `build_schema_type_to_method`    Constructs
or prepares an object.
L352: def generate_definitions(    Function `generate_definitions`    Generates content (often
AI-generated).
L401: def generate(self, schema: CoreSchema, mode: JsonSchemaMode = 'validation') ->
JsonSchemaValue:    Function `generate`    Generates content (often AI-generated).
L450: def generate_inner(self, schema: CoreSchemaOrField) -> JsonSchemaValue:    # noqa: C901
Function `generate_inner`    Generates content (often AI-generated).
L472: def populate_defs(core_schema: CoreSchema, json_schema: JsonSchemaValue) ->
JsonSchemaValue:    Function `populate_defs`    utility or script function.
L486: def handler_func(schema_or_field: CoreSchemaOrField) -> JsonSchemaValue:    Function
`handler_func`    utility or script function.
L531: def js_updates_handler_func(    Function `js_updates_handler_func`    utility or script
function.
L542: def js_extra_handler_func(    Function `js_extra_handler_func`    utility or script
function.
L558: def new_handler_func(    Function `new_handler_func`    utility or script function.
L576: def new_handler_func(    Function `new_handler_func`    utility or script function.
L590: def sort(self, value: JsonSchemaValue, parent_key: str | None = None) ->
JsonSchemaValue:    Function `sort`    utility or script function.
L604: def _sort_recursive(self, value: Any, parent_key: str | None = None) -> Any:    Function
`_sort_recursive`    utility or script function.
L622: def invalid_schema(self, schema: core_schema.InvalidSchema) -> JsonSchemaValue:
Function `invalid_schema`    utility or script function.
L627: def any_schema(self, schema: core_schema.AnySchema) -> JsonSchemaValue:    Function
`any_schema`    utility or script function.
L638: def none_schema(self, schema: core_schema.NoneSchema) -> JsonSchemaValue:    Function
`none_schema`    utility or script function.
L649: def bool_schema(self, schema: core_schema.BoolSchema) -> JsonSchemaValue:    Function
`bool_schema`    utility or script function.
L660: def int_schema(self, schema: core_schema.IntSchema) -> JsonSchemaValue:    Function
`int_schema`    utility or script function.
L674: def float_schema(self, schema: core_schema.FloatSchema) -> JsonSchemaValue:    Function
`float_schema`    utility or script function.
L688: def decimal_schema(self, schema: core_schema.DecimalSchema) -> JsonSchemaValue:
Function `decimal_schema`    utility or script function.

```

```

L698: def get_decimal_pattern(schema: core_schema.DecimalSchema) -> str:    Function
`get_decimal_pattern` Returns or fetches data.
L763: def str_schema(self, schema: core_schema.StringSchema) -> JsonSchemaValue:    Function
`str_schema` utility or script function.
L779: def bytes_schema(self, schema: core_schema.BytesSchema) -> JsonSchemaValue:    Function
`bytes_schema` utility or script function.
L792: def date_schema(self, schema: core_schema.DateSchema) -> JsonSchemaValue:    Function
`date_schema` utility or script function.
L803: def time_schema(self, schema: core_schema.TimeSchema) -> JsonSchemaValue:    Function
`time_schema` utility or script function.
L814: def datetime_schema(self, schema: core_schema.DatetimeSchema) -> JsonSchemaValue:
Function `datetime_schema` utility or script function.
L825: def timedelta_schema(self, schema: core_schema.TimedeltaSchema) -> JsonSchemaValue:
Function `timedelta_schema` utility or script function.
L838: def literal_schema(self, schema: core_schema.LiteralSchema) -> JsonSchemaValue:
Function `literal_schema` utility or script function.
L870: def missing_sentinel_schema(self, schema: core_schema.MissingSentinelSchema) ->
JsonSchemaValue:    Function `missing_sentinel_schema` utility or script function.
L881: def enum_schema(self, schema: core_schema.EnumSchema) -> JsonSchemaValue:    Function
`enum_schema` utility or script function.
L917: def is_instance_schema(self, schema: core_schema.IsInstanceSchema) -> JsonSchemaValue:
Function `is_instance_schema` utility or script function.
L930: def is_subclass_schema(self, schema: core_schema.IsSubclassSchema) -> JsonSchemaValue:
Function `is_subclass_schema` utility or script function.
L944: def callable_schema(self, schema: core_schema.CallableSchema) -> JsonSchemaValue:
Function `callable_schema` utility or script function.
L957: def list_schema(self, schema: core_schema.ListSchema) -> JsonSchemaValue:    Function
`list_schema` utility or script function.
L973: def tuple_positional_schema(self, schema: core_schema.TupleSchema) -> JsonSchemaValue:
Function `tuple_positional_schema` utility or script function.
L984: def tuple_variable_schema(self, schema: core_schema.TupleSchema) -> JsonSchemaValue:
Function `tuple_variable_schema` utility or script function.
L993: def tuple_schema(self, schema: core_schema.TupleSchema) -> JsonSchemaValue:    Function
`tuple_schema` utility or script function.
L1028: def set_schema(self, schema: core_schema.SetSchema) -> JsonSchemaValue:    Function
`set_schema` Sets or updates a value.
L1039: def frozenset_schema(self, schema: core_schema.FrozensetSchema) -> JsonSchemaValue:
Function `frozenset_schema` utility or script function.
L1050: def _common_set_schema(self, schema: core_schema.SetSchema |
core_schema.FrozensetSchema) -> JsonSchemaValue:    Function `_common_set_schema` utility or
script function.
L1056: def generator_schema(self, schema: core_schema.GeneratorSchema) -> JsonSchemaValue:
Function `generator_schema` utility or script function.
L1070: def dict_schema(self, schema: core_schema.DictSchema) -> JsonSchemaValue:    Function
`dict_schema` utility or script function.
L1118: def function_before_schema(self, schema: core_schema.BeforeValidatorFunctionSchema) ->
JsonSchemaValue:    Function `function_before_schema` utility or script function.
L1132: def function_after_schema(self, schema: core_schema.AfterValidatorFunctionSchema) ->
JsonSchemaValue:    Function `function_after_schema` utility or script function.
L1143: def function_plain_schema(self, schema: core_schema.PlainValidatorFunctionSchema) ->
JsonSchemaValue:    Function `function_plain_schema` utility or script function.

```

```

L1159: def function_wrap_schema(self, schema: core_schema.WrapValidatorFunctionSchema) ->
JsonSchemaValue: Function `function_wrap_schema` utility or script function.
L1173: def default_schema(self, schema: core_schema.WithDefaultSchema) -> JsonSchemaValue:
Function `default_schema` utility or script function.
L1236: def get_default_value(self, schema: core_schema.WithDefaultSchema) -> Any: Function
`get_default_value` Returns or fetches data.
L1251: def nullable_schema(self, schema: core_schema.NullableSchema) -> JsonSchemaValue:
Function `nullable_schema` utility or script function.
L1268: def union_schema(self, schema: core_schema.UnionSchema) -> JsonSchemaValue: Function
`union_schema` utility or script function.
L1290: def get_union_of_schemas(self, schemas: list[JsonSchemaValue]) -> JsonSchemaValue:
Function `get_union_of_schemas` Returns or fetches data.
L1326: def tagged_union_schema(self, schema: core_schema.TaggedUnionSchema) ->
JsonSchemaValue: Function `tagged_union_schema` utility or script function.
L1363: def _extract_discriminator( Function `_extract_discriminator` utility or script
function.
L1408: def chain_schema(self, schema: core_schema.ChainSchema) -> JsonSchemaValue: Function
`chain_schema` utility or script function.
L1423: def lax_or_strict_schema(self, schema: core_schema.LaxOrStrictSchema) ->
JsonSchemaValue: Function `lax_or_strict_schema` utility or script function.
L1442: def json_or_python_schema(self, schema: core_schema.JsonOrPythonSchema) ->
JsonSchemaValue: Function `json_or_python_schema` utility or script function.
L1457: def typed_dict_schema(self, schema: core_schema.TypedDictSchema) -> JsonSchemaValue:
Function `typed_dict_schema` utility or script function.
L1509: def _name_required_computed_fields( Function `_name_required_computed_fields`
utility or script function.
L1514: def _named_required_fields_schema( Function `_named_required_fields_schema` utility
or script function.
L1539: def _get_alias_name(self, field: CoreSchemaField, name: str) -> str: Function
`_get_alias_name` utility or script function.
L1560: def typed_dict_field_schema(self, schema: core_schema.TypedDictField) ->
JsonSchemaValue: Function `typed_dict_field_schema` utility or script function.
L1571: def dataclass_field_schema(self, schema: core_schema.DataclassField) ->
JsonSchemaValue: Function `dataclass_field_schema` utility or script function.
L1582: def model_field_schema(self, schema: core_schema.ModelField) -> JsonSchemaValue:
Function `model_field_schema` utility or script function.
L1593: def computed_field_schema(self, schema: core_schema.ComputedField) -> JsonSchemaValue:
Function `computed_field_schema` utility or script function.
L1604: def model_schema(self, schema: core_schema.ModelSchema) -> JsonSchemaValue: Function
`model_schema` utility or script function.
L1625: def _update_class_schema(self, json_schema: JsonSchemaValue, cls: type[Any], config:
ConfigDict) -> None: Function `_update_class_schema` utility or script function.
L1706: def resolve_ref_schema(self, json_schema: JsonSchemaValue) -> JsonSchemaValue:
Function `resolve_ref_schema` utility or script function.
L1726: def model_fields_schema(self, schema: core_schema.ModelFieldsSchema) ->
JsonSchemaValue: Function `model_fields_schema` utility or script function.
L1749: def field_is_present(self, field: CoreSchemaField) -> bool: Function
`field_is_present` utility or script function.
L1767: def field_is_required( Function `field_is_required` utility or script function.
L1798: def dataclass_args_schema(self, schema: core_schema.DataclassArgsSchema) ->
JsonSchemaValue: Function `dataclass_args_schema` utility or script function.

```



```

L1816: def dataclass_schema(self, schema: core_schema.DataclassSchema) -> JsonSchemaValue:
Function `dataclass_schema` utility or script function.
L1836: def arguments_schema(self, schema: core_schema.ArgumentsSchema) -> JsonSchemaValue:
Function `arguments_schema` utility or script function.
L1872: def kw_arguments_schema( Function `kw_arguments_schema` utility or script function.
L1910: def p_arguments_schema( Function `p_arguments_schema` utility or script function.
L1953: def get_argument_name(self, argument: core_schema.ArgumentsParameter |
core_schema.ArgumentsV3Parameter) -> str: Function `get_argument_name` Returns or fetches
data.
L1971: def arguments_v3_schema(self, schema: core_schema.ArgumentsV3Schema) ->
JsonSchemaValue: Function `arguments_v3_schema` utility or script function.
L2010: def call_schema(self, schema: core_schema.CallSchema) -> JsonSchemaValue: Function
`call_schema` utility or script function.
L2021: def custom_error_schema(self, schema: core_schema.CustomErrorSchema) ->
JsonSchemaValue: Function `custom_error_schema` utility or script function.
L2032: def json_schema(self, schema: core_schema.JsonSchema) -> JsonSchemaValue: Function
`json_schema` utility or script function.
L2049: def url_schema(self, schema: core_schema.UrlSchema) -> JsonSchemaValue: Function
`url_schema` utility or script function.
L2062: def multi_host_url_schema(self, schema: core_schema.MultiHostUrlSchema) ->
JsonSchemaValue: Function `multi_host_url_schema` utility or script function.
L2076: def uuid_schema(self, schema: core_schema.UuidSchema) -> JsonSchemaValue: Function
`uuid_schema` utility or script function.
L2087: def definitions_schema(self, schema: core_schema.DefinitionsSchema) ->
JsonSchemaValue: Function `definitions_schema` utility or script function.
L2105: def definition_ref_schema(self, schema: core_schema.DefinitionReferenceSchema) ->
JsonSchemaValue: Function `definition_ref_schema` utility or script function.
L2118: def ser_schema( Function `ser_schema` utility or script function.
L2143: def complex_schema(self, schema: core_schema.ComplexSchema) -> JsonSchemaValue:
Function `complex_schema` utility or script function.
L2161: def get_title_from_name(self, name: str) -> str: Function `get_title_from_name`
Returns or fetches data.
L2172: def field_title_should_be_set(self, schema: CoreSchemaOrField) -> bool: Function
`field_title_should_be_set` utility or script function.
L2207: def normalize_name(self, name: str) -> str: Function `normalize_name` utility or
script function.
L2218: def get_defs_ref(self, core_mode_ref: CoreModeRef) -> DefsRef: Function
`get_defs_ref` Returns or fetches data.
L2266: def get_cache_defs_ref_schema(self, core_ref: CoreRef) -> tuple[DefsRef,
JsonSchemaValue]: Function `get_cache_defs_ref_schema` Returns or fetches data.
L2294: def handle_ref_overrides(self, json_schema: JsonSchemaValue) -> JsonSchemaValue:
Function `handle_ref_overrides` utility or script function.
L2321: def get_schema_from_definitions(self, json_ref: JsonRef) -> JsonSchemaValue | None:
Function `get_schema_from_definitions` Returns or fetches data.
L2332: def encode_default(self, dft: Any) -> Any: Function `encode_default` utility or
script function.
L2361: def update_with_validations( Function `update_with_validations` utility or script
function.
L2376: class ValidationsMapping: Class (`ValidationsMapping`) component used by the app
(see file context: None).
L2408: def get_flattened_anyof(self, schemas: list[JsonSchemaValue]) -> JsonSchemaValue:

```



```

Function `get_flattened_anyof` Returns or fetches data.
L2420: def get_json_ref_counts(self, json_schema: JsonSchemaValue) -> dict[JsonRef, int]:
Function `get_json_ref_counts` Returns or fetches data.
L2424: def _add_json_refs(schema: Any) -> None: Function `_add_json_refs` utility or
script function.
L2456: def handle_invalid_for_json_schema(self, schema: CoreSchemaOrField, error_info: str)
-> JsonSchemaValue: Function `handle_invalid_for_json_schema` utility or script function.
L2459: def emit_warning(self, kind: JsonSchemaWarningKind, detail: str) -> None: Function
`emit_warning` utility or script function.
L2465: def render_warning_message(self, kind: JsonSchemaWarningKind, detail: str) -> str |
None: Function `render_warning_message` utility or script function.
L2486: def _build_definitions_remapping(self) -> _DefinitionsRemapping: Function
`_build_definitions_remapping` utility or script function.
L2497: def _garbage_collect_definitions(self, schema: JsonSchemaValue) -> None: Function
`_garbage_collect_definitions` utility or script function.
L2518: def model_json_schema( Function `model_json_schema` utility or script function.
L2566: def models_json_schema( Function `models_json_schema` utility or script function.
L2631: def _deduplicate_schemas(schemas: Iterable[JsonDict]) -> list[JsonDict]: Function
`_deduplicate_schemas` utility or script function.
L2635: def _make_json_hashable(value: JsonValue) -> _HashableJsonValue: Function
`_make_json_hashable` utility or script function.
L2645: class WithJsonSchema: Class (`WithJsonSchema`) component used by the app (see file
context: None).
L2668: class Model(BaseModel): Class (`Model`) component used by the app (see file
context: None).
L2687: class Model(BaseModel): Class (`Model`) component used by the app (see file
context: None).
L2706: def __get_pydantic_json_schema__( Function `__get_pydantic_json_schema__` utility
or script function.
L2717: def __hash__(self) -> int: Function `__hash__` utility or script function.
L2721: class Examples: Class (`Examples`) component used by the app (see file context:
None).
L2733: def __init__( Function `__init__` utility or script function.
L2738: def __init__(self, examples: list[Any], mode: Literal['validation', 'serialization'] |
None = None) -> None: ... Function `__init__` utility or script function.
L2740: def __init__( Function `__init__` utility or script function.
L2752: def __get_pydantic_json_schema__( Function `__get_pydantic_json_schema__` utility
or script function.
L2791: def __hash__(self) -> int: Function `__hash__` utility or script function.
L2795: def _get_all_json_refs(item: Any) -> set[JsonRef]: Function `_get_all_json_refs`
utility or script function.
L2830: class SkipJsonSchema: Class (`SkipJsonSchema`) component used by the app (see file
context: None).
L2844: class Model(BaseModel): Class (`Model`) component used by the app (see file
context: None).
L2878: def __class_getitem__(cls, item: AnyType) -> AnyType: Function `__class_getitem__`
utility or script function.
L2881: def __get_pydantic_json_schema__( Function `__get_pydantic_json_schema__` utility
or script function.
L2886: def __hash__(self) -> int: Function `__hash__` utility or script function.
L2890: def _get_typed_dict_config(cls: type[Any] | None) -> ConfigDict: Function

```

```
`_get_typed_dict_config` utility or script function.
L2899: def _get_ser_schema_for_default_value(schema: CoreSchema) ->
core_schema.PlainSerializerFunctionSerSchema | None: Function
`_get_ser_schema_for_default_value` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/functional_serializers.py

```
L20: class PlainSerializer: Class (`PlainSerializer`) component used by the app (see file
context: None).
L35: class StudentModel(BaseModel): Class (`StudentModel`) component used by the app (see
file context: None).
L54: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema: Function `__get_pydantic_core_schema__` utility or script
function.
L90: class WrapSerializer: Class (`WrapSerializer`) component used by the app (see file
context: None).
L102: class EventDatetime(BaseModel): Class (`EventDatetime`) component used by the app
(see file context: None).
L106: def convert_to_utc(value: Any, handler, info) -> dict[str, datetime]: Function
`convert_to_utc` utility or script function.
L119: class EventModel(BaseModel): Class (`EventModel`) component used by the app (see
file context: None).
L157: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> core_schema.CoreSchema: Function `__get_pydantic_core_schema__` utility or script
function.
L209: def field_serializer( Function `field_serializer` utility or script function.
L221: def field_serializer( Function `field_serializer` utility or script function.
L232: def field_serializer( # noqa: D417 Function `field_serializer` utility or script
function.
L252: class StudentModel(BaseModel): Class (`StudentModel`) component used by the app (see
file context: None).
L257: def serialize_courses_in_order(self, courses: set[str]): Function
`serialize_courses_in_order` utility or script function.
L305: def dec(f: FieldSerializer) -> _decorators.PydanticDescriptorProxy[Any]: Function
`dec` utility or script function.
L346: def model_serializer(f: _ModelPlainSerializerT, /) -> _ModelPlainSerializerT: ...
Function `model_serializer` utility or script function.
L350: def model_serializer( Function `model_serializer` utility or script function.
L356: def model_serializer( Function `model_serializer` utility or script function.
L364: def model_serializer( Function `model_serializer` utility or script function.
L387: class TemperatureModel(BaseModel): Class (`TemperatureModel`) component used by the
app (see file context: None).
L392: def serialize_model(self): Function `serialize_model` utility or script function.
L428: def dec(f: ModelSerializer) -> _decorators.PydanticDescriptorProxy[Any]: Function
`dec` utility or script function.
```

```

L450: class SerializeAsAny:    Class (`SerializeAsAny`)    component used by the app (see file
context: None).
L456: def __class_getitem__(cls, item: Any) -> Any:    Function `__class_getitem__`    utility
or script function.
L459: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/networks.py

```

L71: class UrlConstraints:    Class (`UrlConstraints`)    component used by the app (see file
context: None).
L92: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L106: def defined_constraints(self) -> dict[str, Any]:    Function `defined_constraints`
utility or script function.
L110: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`    utility or script
function.
L126: class _BaseUrl:    Class (`_BaseUrl`)    component used by the app (see file context:
None).
L130: def __init__(self, url: str | _CoreUrl | _BaseUrl) -> None:    Function `__init__`
utility or script function.
L134: def scheme(self) -> str:    Function `scheme`    utility or script function.
L142: def username(self) -> str | None:    Function `username`    utility or script function.
L150: def password(self) -> str | None:    Function `password`    utility or script function.
L158: def host(self) -> str | None:    Function `host`    utility or script function.
L166: def unicode_host(self) -> str | None:    Function `unicode_host`    utility or script
function.
L177: def port(self) -> int | None:    Function `port`    utility or script function.
L185: def path(self) -> str | None:    Function `path`    utility or script function.
L193: def query(self) -> str | None:    Function `query`    utility or script function.
L200: def query_params(self) -> list[tuple[str, str]]:    Function `query_params`    utility or
script function.
L208: def fragment(self) -> str | None:    Function `fragment`    utility or script function.
L215: def unicode_string(self) -> str:    Function `unicode_string`    utility or script
function.
L223: def encoded_string(self) -> str:    Function `encoded_string`    utility or script
function.
L230: def __str__(self) -> str:    Function `__str__`    utility or script function.
L234: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L237: def __deepcopy__(self, memo: dict) -> Self:    Function `__deepcopy__`    utility or
script function.
L240: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L243: def __lt__(self, other: Any) -> bool:    Function `__lt__`    utility or script function.
L246: def __gt__(self, other: Any) -> bool:    Function `__gt__`    utility or script function.
L249: def __le__(self, other: Any) -> bool:    Function `__le__`    utility or script function.
L252: def __ge__(self, other: Any) -> bool:    Function `__ge__`    utility or script function.
L255: def __hash__(self) -> int:    Function `__hash__`    utility or script function.

```

```

L258: def __len__(self) -> int:    Function `__len__`    utility or script function.
L262: def build(    Function `build`    Constructs or prepares an object.
L303: def serialize_url(cls, url: Any, info: core_schema.SerializationInfo) -> str | Self:
Function `serialize_url`    utility or script function.
L313: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__`    utility or
script function.
L316: def wrap_val(v, h):    Function `wrap_val`    utility or script function.
L335: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__`    utility or
script function.
L346: class _BaseMultiHostUrl:    Class (`_BaseMultiHostUrl`)    component used by the app (see
file context: None).
L350: def __init__(self, url: str | _CoreMultiHostUrl | _BaseMultiHostUrl) -> None:
Function `__init__`    utility or script function.
L354: def scheme(self) -> str:    Function `scheme`    utility or script function.
L362: def path(self) -> str | None:    Function `path`    utility or script function.
L370: def query(self) -> str | None:    Function `query`    utility or script function.
L377: def query_params(self) -> list[tuple[str, str]]:    Function `query_params`    utility or
script function.
L385: def fragment(self) -> str | None:    Function `fragment`    utility or script function.
L392: def hosts(self) -> list[MultiHostHost]:    Function `hosts`    utility or script function.
L411: def encoded_string(self) -> str:    Function `encoded_string`    utility or script
function.
L418: def unicode_string(self) -> str:    Function `unicode_string`    utility or script
function.
L422: def __str__(self) -> str:    Function `__str__`    utility or script function.
L426: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L429: def __deepcopy__(self, memo: dict) -> Self:    Function `__deepcopy__`    utility or
script function.
L432: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L435: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L438: def __len__(self) -> int:    Function `__len__`    utility or script function.
L442: def build(    Function `build`    Constructs or prepares an object.
L489: def serialize_url(cls, url: Any, info: core_schema.SerializationInfo) -> str | Self:
Function `serialize_url`    utility or script function.
L499: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__`    utility or
script function.
L502: def wrap_val(v, h):    Function `wrap_val`    utility or script function.
L521: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__`    utility or
script function.
L533: def _build_type_adapter(cls: type[_BaseUrl | _BaseMultiHostUrl]) -> TypeAdapter:
Function `_build_type_adapter`    utility or script function.
L537: class AnyUrl(_BaseUrl):    Class (`AnyUrl`)    component used by the app (see file
context: None).
L562: class AnyHttpUrl(AnyUrl):    Class (`AnyHttpUrl`)    component used by the app (see file
context: None).
L572: class HttpUrl(AnyUrl):    Class (`HttpUrl`)    component used by the app (see file
context: None).
L582: class MyModel(BaseModel):    Class (`MyModel`)    component used by the app (see file
context: None).
L619: class MyModel(BaseModel):    Class (`MyModel`)    component used by the app (see file
context: None).

```

```

L653: class AnyWebsocketUrl(AnyUrl):    Class (`AnyWebsocketUrl`) component used by the app
(see file context: None).
L663: class WebsocketUrl(AnyUrl):    Class (`WebsocketUrl`) component used by the app (see
file context: None).
L674: class FileUrl(AnyUrl):    Class (`FileUrl`) component used by the app (see file
context: None).
L683: class FtpUrl(AnyUrl):    Class (`FtpUrl`) component used by the app (see file context:
None).
L693: class PostgresDsn(_BaseMultiHostUrl):    Class (`PostgresDsn`) component used by the
app (see file context: None).
L712: class MyModel(BaseModel):    Class (`MyModel`) component used by the app (see file
context: None).
L727: class MyDatabaseModel(BaseModel):    Database abstraction (`MyDatabaseModel`)
encapsulates DB access/setup.
L731: def check_db_name(cls, v):    Function `check_db_name` utility or script function.
L769: def host(self) -> str:    Function `host` utility or script function.
L774: class CockroachDsn(AnyUrl):    Class (`CockroachDsn`) component used by the app (see
file context: None).
L792: def host(self) -> str:    Function `host` utility or script function.
L797: class AmqpDsn(AnyUrl):    Class (`AmqpDsn`) component used by the app (see file
context: None).
L808: class RedisDsn(AnyUrl):    Class (`RedisDsn`) component used by the app (see file
context: None).
L825: def host(self) -> str:    Function `host` utility or script function.
L830: class MongoDsn(_BaseMultiHostUrl):    Class (`MongoDsn`) component used by the app (see
file context: None).
L859: class KafkaDsn(AnyUrl):    Class (`KafkaDsn`) component used by the app (see file
context: None).
L870: class NatsDsn(_BaseMultiHostUrl):    Class (`NatsDsn`) component used by the app (see
file context: None).
L884: class MySQLDsn(AnyUrl):    Class (`MySQLDsn`) component used by the app (see file
context: None).
L908: class MariaDBDsn(AnyUrl):    Class (`MariaDBDsn`) component used by the app (see file
context: None).
L922: class ClickHouseDsn(AnyUrl):    Class (`ClickHouseDsn`) component used by the app (see
file context: None).
L944: class SnowflakeDsn(AnyUrl):    Class (`SnowflakeDsn`) component used by the app (see
file context: None).
L958: def host(self) -> str:    Function `host` utility or script function.
L963: def import_email_validator() -> None:    Function `import_email_validator` utility or
script function.
L977: class EmailStr:    Class (`EmailStr`) component used by the app (see file context:
None).
L992: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L1001: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L1010: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1018: def _validate(cls, input_value: str, /) -> str:    Function `_validate` utility or
script function.

```

```

L1022: class NameEmail(_repr.Representation):    Class (`NameEmail`) component used by the
app (see file context: None).
L1041: class User(BaseModel):    Class (`User`) component used by the app (see file context:
None).
L1060: def __init__(self, name: str, email: str):    Function `__init__` utility or script
function.
L1064: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L1068: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1076: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L1097: def _validate(cls, input_value: Self | str, /) -> Self:    Function `_validate`
utility or script function.
L1104: def __str__(self) -> str:    Function `__str__` utility or script function.
L1121: class IPvAnyAddress:    Class (`IPvAnyAddress`) component used by the app (see file
context: None).
L1128: class IpModel(BaseModel):    Class (`IpModel`) component used by the app (see file
context: None).
L1153: def __new__(cls, value: Any) -> IPvAnyAddressType:    Function `__new__` utility or
script function.
L1166: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1174: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L1184: def _validate(cls, input_value: Any, /) -> IPvAnyAddressType:    Function `_validate`
utility or script function.
L1187: class IPvAnyInterface:    Class (`IPvAnyInterface`) component used by the app (see
file context: None).
L1192: def __new__(cls, value: NetworkType) -> IPvAnyInterfaceType:    Function `__new__`
utility or script function.
L1205: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1213: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L1223: def _validate(cls, input_value: NetworkType, /) -> IPvAnyInterfaceType:    Function
`_validate` utility or script function.
L1226: class IPvAnyNetwork:    Class (`IPvAnyNetwork`) component used by the app (see file
context: None).
L1231: def __new__(cls, value: NetworkType) -> IPvAnyNetworkType:    Function `__new__`
utility or script function.
L1246: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1254: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L1264: def _validate(cls, input_value: NetworkType, /) -> IPvAnyNetworkType:    Function
`_validate` utility or script function.
L1268: def _build_pretty_email_regex() -> re.Pattern[str]:    Function
`_build_pretty_email_regex` utility or script function.
L1284: def validate_email(value: str) -> tuple[str, str]:    Function `validate_email`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/type_adapter.py

```

L44: def _getattr_no_parents(obj: Any, attribute: str) -> Any:    Function
`_getattr_no_parents` utility or script function.
L59: def _type_has_config(type_: Any) -> bool:    Function `_type_has_config` utility or
script function.
L70: class TypeAdapter(Generic[T]):    Class (`TypeAdapter`) component used by the app (see
file context: None).
L174: def __init__(    Function `__init__` utility or script function.
L187: def __init__(    Function `__init__` utility or script function.
L196: def __init__(    Function `__init__` utility or script function.
L252: def _fetch_parent_frame(self) -> FrameType | None:    Function `_fetch_parent_frame`
utility or script function.
L263: def _init_core_attrs(    Function `_init_core_attrs` utility or script function.
L336: def _defer_build(self) -> bool:    Function `_defer_build` utility or script function.
L343: def _model_config(self) -> ConfigDict | None:    Function `_model_config` utility or
script function.
L349: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L352: def rebuild(    Function `rebuild` utility or script function.
L398: def validate_python(    Function `validate_python` utility or script function.
L452: def validate_json(    Function `validate_json` utility or script function.
L502: def validate_strings(    Function `validate_strings` utility or script function.
L549: def get_default_value(self, *, strict: bool | None = None, context: Any | None = None)
-> Some[T] | None:    Function `get_default_value` Returns or fetches data.
L561: def dump_python(    Function `dump_python` utility or script function.
L625: def dump_json(    Function `dump_json` utility or script function.
L696: def json_schema(    Function `json_schema` utility or script function.
L736: def json_schemas(    Function `json_schemas` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/validate_call_decorator.py

```

L24: def _check_function_type(function: object) -> None:    Object (singleton).
L73: def validate_call(    Function `validate_call` utility or script function.
L79: def validate_call(func: AnyCallableT, /) -> AnyCallableT: ...    Function `validate_call`
utility or script function.
L82: def validate_call(    Function `validate_call` utility or script function.
L106: def validate(function: AnyCallableT) -> AnyCallableT:    Function `validate` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/dataclasses.py

```

L133: def dataclass(    Function `dataclass`    utility or script function.
L150: def dataclass(    Function `dataclass`    utility or script function.
L169: def dataclass(    Function `dataclass`    utility or script function.
L184: def dataclass(    Function `dataclass`    utility or script function.
L199: def dataclass(    Function `dataclass`    utility or script function.
L153: def create_dataclass(cls: type[Any]) -> type[PydanticDataclass]:    Function
`create_dataclass`    Creates a resource or document.
L255: def validated_setattr(instance: PydanticDataclass, name: str, value: Any, /) -> None:
Function `validated_setattr`    utility or script function.
L281: def _dataclass_getstate(self: Any) -> list[Any]:    Function `_dataclass_getstate`
utility or script function.
L284: def _dataclass_setstate(self: Any, state: list[Any]) -> None:    Function
`_dataclass_setstate`    utility or script function.
L316: def _pydantic_fields_complete(cls: type[PydanticDataclass]) -> bool:    Function
`_pydantic_fields_complete`    utility or script function.
L330: def _call_initvar(*args: Any, **kwargs: Any) -> NoReturn:    Function `_call_initvar`
utility or script function.
L340: def rebuild_dataclass(    Function `rebuild_dataclass`    utility or script function.
L401: def is_pydantic_dataclass(class_: type[Any], /) -> TypeGuard[type[PydanticDataclass]]:
Function `is_pydantic_dataclass`    utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/config.py

```

L136: class ConfigDict(TypedDict, total=False):    Class (`ConfigDict`)    component used by the
app (see file context: None).
L173: class User(BaseModel):    Class (`User`)    component used by the app (see file context:
None).
L192: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L114: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L129: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L162: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L209: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L244: class SomeEnum(Enum):    Class (`SomeEnum`)    component used by the app (see file
context: None).
L249: class SomeModel(BaseModel):    Class (`SomeModel`)    component used by the app (see file
context: None).
L278: class User(BaseModel):    Class (`User`)    component used by the app (see file context:
None).
L297: class User(BaseModel, validate_assignment=True):    # (1)!    Class (`User`)    component
used by the app (see file context: None).
L327: class Pet:    Class (`Pet`)    component used by the app (see file context: None).

```



```

L328: def __init__(self, name: str):    Function `__init__` utility or script function.
L331: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L399: class Voice(BaseModel):    Class (`Voice`) component used by the app (see file context:
None).
L419: class Athlete(BaseModel):    Class (`Athlete`) component used by the app (see file
context: None).
L444: class without an annotation and has a type that is not in this tuple (or otherwise
recognized by Class (`without`) component used by the app (see file context: None).
L479: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L512: class User(BaseModel, revalidate_instances='never'): # (1)!    Class (`User`)
component used by the app (see file context: None).
L515: class Transaction(BaseModel):    Class (`Transaction`) component used by the app (see
file context: None).
L536: class User(BaseModel, revalidate_instances='subclass-instances'):    Class (`User`)
component used by the app (see file context: None).
L539: class SubUser(User):    Class (`SubUser`) component used by the app (see file context:
None).
L542: class Transaction(BaseModel):    Class (`Transaction`) component used by the app (see
file context: None).
L683: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L706: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L738: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L765: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L784: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L839: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L885: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L898: class ForceInputModel(Model):    Class (`ForceInputModel`) component used by the app
(see file context: None).
L936: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L949: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L979: class Model(BaseModel):    Class (`Model`) component used by the app (see file context:
None).
L1025: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1088: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1124: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1167: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).

```

```

L1196: class Model(BaseModel):  Class (`Model`)  component used by the app (see file
context: None).
L1221: def with_config(*, config: ConfigDict) -> Callable[[_TypeT], _TypeT]: ...  Function
`with_config`  utility or script function.
L1225: def with_config(config: ConfigDict, /) -> Callable[[_TypeT], _TypeT]: ...  Function
`with_config`  utility or script function.
L1229: def with_config(**config: Unpack[ConfigDict]) -> Callable[[_TypeT], _TypeT]: ...
Function `with_config`  utility or script function.
L1232: def with_config(config: ConfigDict | None = None, /, **kwargs: Any) ->
Callable[[_TypeT], _TypeT]:  Function `with_config`  utility or script function.
L1249: class TD(TypedDict):  Class (`TD`)  component used by the app (see file context:
None).
L1279: def inner(class_: _TypeT, /) -> _TypeT:  Function `inner`  utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/__init__.py

```

L425: def __getattr__(attr_name: str) -> object:  Object (singleton).
L455: def __dir__() -> list[str]:  Function `__dir__`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/version.py

```

L25: def version_short() -> str:  Function `version_short`  utility or script function.
L33: def version_info() -> str:  Function `version_info`  utility or script function.
L77: def check_pydantic_core_version() -> bool:  Function `check_pydantic_core_version`
utility or script function.
L82: def _ensure_pydantic_core_version() -> None:  # pragma: no cover  Function
`_ensure_pydantic_core_version`  utility or script function.
L101: def parse_mypy_version(version: str) -> tuple[int, int, int]:  Function
`parse_mypy_version`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/aliases.py

```

L16: class AliasPath:  Class (`AliasPath`)  component used by the app (see file context:
None).
L28: def __init__(self, first_arg: str, *args: str | int) -> None:  Function `__init__`
utility or script function.
L31: def convert_to_aliases(self) -> list[str | int]:  Function `convert_to_aliases`
utility or script function.

```

```

L39: def search_dict_for_path(self, d: dict) -> Any:    Function `search_dict_for_path`
utility or script function.
L58: class AliasChoices:    Class (`AliasChoices`)    component used by the app (see file
context: None).
L70: def __init__(self, first_choice: str | AliasPath, *choices: str | AliasPath) -> None:
Function `__init__`    utility or script function.
L73: def convert_to_aliases(self) -> list[list[str | int]]:    Function `convert_to_aliases`
utility or script function.
L89: class AliasGenerator:    Class (`AliasGenerator`)    component used by the app (see file
context: None).
L105: def _generate_alias(    Function `_generate_alias`    utility or script function.
L125: def generate_aliases(self, field_name: str) -> tuple[str | None, str | AliasPath |
AliasChoices | None, str | None]:    Function `generate_aliases`    Generates content (often
AI-generated).

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/types.py

```

L116: class Strict(_fields.PydanticMetadata, BaseMetadata):    Class (`Strict`)    component
used by the app (see file context: None).
L138: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L150: def conint(    Function `conint`    utility or script function.
L173: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L183: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L203: class ConstrainedExample(BaseModel):    Class (`ConstrainedExample`)    component used by
the app (see file context: None).
L243: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L274: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L305: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L336: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L367: class StrictIntModel(BaseModel):    Class (`StrictIntModel`)    component used by the app
(see file context: None).
L386: class AllowInfNan(_fields.PydanticMetadata):    Class (`AllowInfNan`)    component used by
the app (see file context: None).
L406: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L410: def confloat(    Function `confloat`    utility or script function.
L434: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L444: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L465: class ConstrainedExample(BaseModel):    Class (`ConstrainedExample`)    component used by
the app (see file context: None).
L505: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:

```

```

None).
L536: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L567: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L598: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L629: class StrictFloatModel(BaseModel):    Class (`StrictFloatModel`)    component used by the
app (see file context: None).
L649: class Model(BaseModel):    Class (`Model`)    component used by the app (see file context:
None).
L662: def conbytes(    Function `conbytes`    utility or script function.
L693: class StringConstraints(annotated_types.GroupedMetadata):    Class (`StringConstraints`)
component used by the app (see file context: None).
L729: def __iter__(self) -> Iterator[BaseMetadata]:    Function `__iter__`    utility or script
function.
L752: def constr(    Function `constr`    utility or script function.
L777: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L787: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L801: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L845: def conset(    Function `conset`    utility or script function.
L861: def confrozenset(    Function `confrozenset`    utility or script function.
L880: def conlist(    Function `conlist`    utility or script function.
L919: class ImportString:    Class (`ImportString`)    component used by the app (see file
context: None).
L935: class ImportThings(BaseModel):    Class (`ImportThings`)    component used by the app (see
file context: None).
L963: class ImportThingsDefaultPyObj(BaseModel):    Class (`ImportThingsDefaultPyObj`)
component used by the app (see file context: None).
L967: class ImportThingsDefaultString(BaseModel):    Class (`ImportThingsDefaultString`)
component used by the app (see file context: None).
L975: class ImportThingsMissingValidateDefault(BaseModel):    Class
(`ImportThingsMissingValidateDefault`)    component used by the app (see file context: None).
L987: class ImportThings(BaseModel):    Class (`ImportThings`)    component used by the app (see
file context: None).
L1000: def __class_getitem__(cls, item: AnyType) -> AnyType:    Function `__class_getitem__`
utility or script function.
L1004: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__`    utility
or script function.
L1019: def __get_pydantic_json_schema__(cls, cs: CoreSchema, handler: GetJsonSchemaHandler)
-> JsonSchemaValue:    Function `__get_pydantic_json_schema__`    utility or script function.
L1023: def _serialize(v: Any) -> str:    Function `_serialize`    utility or script function.
L1039: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L1046: def condecimal(    Function `condecimal`    utility or script function.
L1072: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).
L1083: class Foo(BaseModel):    Class (`Foo`)    component used by the app (see file context:
None).

```

```

L1105: class ConstrainedExample(BaseModel):    Class (`ConstrainedExample`) component used by
the app (see file context: None).
L1144: class UuidVersion:    Class (`UuidVersion`) component used by the app (see file
context: None).
L1165: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1173: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__` utility or script
function.
L1179: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L1191: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1205: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1219: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1233: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1247: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1261: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1275: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1286: class PathType:    Class (`PathType`) component used by the app (see file context:
None).
L1289: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility
or script function.
L1297: def __get_pydantic_core_schema__(self, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__` utility or script
function.
L1311: def validate_file(path: Path, _: core_schema.ValidationInfo) -> Path:    Function
`validate_file` utility or script function.
L1318: def validate_socket(path: Path, _: core_schema.ValidationInfo) -> Path:    Function
`validate_socket` utility or script function.
L1325: def validate_directory(path: Path, _: core_schema.ValidationInfo) -> Path:    Function
`validate_directory` utility or script function.
L1332: def validate_new(path: Path, _: core_schema.ValidationInfo) -> Path:    Function
`validate_new` utility or script function.
L1340: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L1352: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1394: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L1442: class Json:    Class (`Json`) component used by the app (see file context: None).
L1453: class AnyJsonModel(BaseModel):    Class (`AnyJsonModel`) component used by the app
(see file context: None).
L1456: class ConstrainedJsonModel(BaseModel):    Class (`ConstrainedJsonModel`) component
used by the app (see file context: None).
L1503: class ConstrainedJsonModel(BaseModel):    Class (`ConstrainedJsonModel`) component
used by the app (see file context: None).

```

```

L1516: def __class_getitem__(cls, item: AnyType) -> AnyType:    Function `__class_getitem__`
utility or script function.
L1520: def __get_pydantic_core_schema__(cls, source: Any, handler: GetCoreSchemaHandler) ->
core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`    utility or script
function.
L1526: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L1529: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L1532: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L1542: class _SecretBase(Generic[SecretType]):    Class (`_SecretBase`)    component used by the
app (see file context: None).
L1543: def __init__(self, secret_value: SecretType) -> None:    Function `__init__`    utility
or script function.
L1546: def get_secret_value(self) -> SecretType:    Function `get_secret_value`    Returns or
fetches data.
L1554: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L1557: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L1560: def __str__(self) -> str:    Function `__str__`    utility or script function.
L1563: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L1566: def _display(self) -> str | bytes:    Function `_display`    utility or script function.
L1570: def _serialize_secret(value: Secret[SecretType], info: core_schema.SerializationInfo)
-> str | Secret[SecretType]:    Function `_serialize_secret`    utility or script function.
L1577: class Secret(_SecretBase[SecretType]):    Class (`Secret`)    component used by the app
(see file context: None).
L1591: class Model(BaseModel):    Class (`Model`)    component used by the app (see file
context: None).
L1612: class SecretDate(Secret[date]):    Class (`SecretDate`)    component used by the app (see
file context: None).
L1613: def _display(self) -> str:    Function `_display`    utility or script function.
L1616: class Model(BaseModel):    Class (`Model`)    component used by the app (see file
context: None).
L1642: class Model(BaseModel):    Class (`Model`)    component used by the app (see file
context: None).
L1683: def _display(self) -> str | bytes:    Function `_display`    utility or script function.
L1687: def __get_pydantic_core_schema__(cls, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`
utility or script function.
L1707: def validate_secret_value(value, handler) -> Secret[SecretType]:    Function
`validate_secret_value`    utility or script function.
L1737: def _secret_display(value: SecretType) -> str:    # type: ignore    Function
`_secret_display`    utility or script function.
L1741: def _serialize_secret_field(    Function `_serialize_secret_field`    utility or script
function.
L1752: class _SecretField(_SecretBase[SecretType]):    Class (`_SecretField`)    component used
by the app (see file context: None).
L1757: def __get_pydantic_core_schema__(cls, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`
utility or script function.
L1758: def get_json_schema(_core_schema: core_schema.CoreSchema, handler:
GetJsonSchemaHandler) -> JsonSchemaValue:    Function `get_json_schema`    Returns or fetches
data.
L1768: def get_secret_schema(strict: bool) -> CoreSchema:    Function `get_secret_schema`

```

Returns or fetches data.

L1807: class SecretStr(_SecretField[str]): Class (`SecretStr`) component used by the app (see file context: None).

L1816: class User(BaseModel): Class (`User`) component used by the app (see file context: None).

L1839: class Model(BaseModel): Class (`Model`) component used by the app (see file context: None).

L1844: def dump_secret(self, v): Function `dump\_secret` utility or script function.

L1867: def __len__(self) -> int: Function `\_\_len\_\_` utility or script function.

L1870: def _display(self) -> str: Function `\_display` utility or script function.

L1874: class SecretBytes(_SecretField[bytes]): Class (`SecretBytes`) component used by the app (see file context: None).

L1884: class User(BaseModel): Class (`User`) component used by the app (see file context: None).

L1900: def __len__(self) -> int: Function `\_\_len\_\_` utility or script function.

L1903: def _display(self) -> bytes: Function `\_display` utility or script function.

L1910: class PaymentCardBrand(str, Enum): Class (`PaymentCardBrand`) component used by the app (see file context: None).

L1916: def __str__(self) -> str: Function `\_\_str\_\_` utility or script function.

L1925: class PaymentCardNumber(str): Class (`PaymentCardNumber`) component used by the app (see file context: None).

L1935: def __init__(self, card_number: str): Function `\_\_init\_\_` utility or script function.

L1945: def __get_pydantic_core_schema__(cls, source: type[Any], handler: GetCoreSchemaHandler) -> core_schema.CoreSchema: Function `\_\_get\_pydantic\_core\_schema\_\_` utility or script function.

L1954: def validate(cls, input_value: str, /, _: core_schema.ValidationInfo) -> PaymentCardNumber: Function `validate` utility or script function.

L1959: def masked(self) -> str: Function `masked` utility or script function.

L1969: def validate_digits(cls, card_number: str) -> None: Function `validate\_digits` utility or script function.

L1975: def validate_luhn_check_digit(cls, card_number: str) -> str: Function `validate\_luhn\_check\_digit` utility or script function.

L1993: def validate_brand(card_number: str) -> PaymentCardBrand: Function `validate\_brand` utility or script function.

L2031: class ByteSize(int): Class (`ByteSize`) component used by the app (see file context: None).

L2047: class MyModel(BaseModel): Class (`MyModel`) component used by the app (see file context: None).

L2102: def __get_pydantic_core_schema__(cls, source: type[Any], handler: GetCoreSchemaHandler) -> core_schema.CoreSchema: Function `\_\_get\_pydantic\_core\_schema\_\_` utility or script function.

L2119: def _validate(cls, input_value: Any, /, _: core_schema.ValidationInfo) -> ByteSize: Function `\_validate` utility or script function.

L2140: def human_readable(self, decimal: bool = False, separator: str = '') -> str: Function `human\_readable` utility or script function.

L2171: def to(self, unit: str) -> float: Function `to` utility or script function.

L2194: def _check_annotated_type(annotated_type: str, expected_type: str, annotation: str) -> None: Function `\_check\_annotated\_type` utility or script function.

L2204: class PastDate: Class (`PastDate`) component used by the app (see file context: None).


```

L2208: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L2220: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L2223: class FutureDate:    Class (`FutureDate`) component used by the app (see file context:
None).
L2227: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L2239: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L2243: def conddate(    Function `conddate` utility or script function.
L2280: class AwareDatetime:    Class (`AwareDatetime`) component used by the app (see file
context: None).
L2284: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L2296: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L2299: class NaiveDatetime:    Class (`NaiveDatetime`) component used by the app (see file
context: None).
L2303: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L2315: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L2318: class PastDatetime:    Class (`PastDatetime`) component used by the app (see file
context: None).
L2322: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L2334: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L2337: class FutureDatetime:    Class (`FutureDatetime`) component used by the app (see file
context: None).
L2341: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility
or script function.
L2353: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L2360: class EncoderProtocol(Protocol):    Class (`EncoderProtocol`) component used by the
app (see file context: None).
L2364: def decode(cls, data: bytes) -> bytes:    Function `decode` utility or script
function.
L2376: def encode(cls, value: bytes) -> bytes:    Function `encode` utility or script
function.
L2388: def get_json_format(cls) -> str:    Function `get_json_format` Returns or fetches
data.
L2397: class Base64Encoder(EncoderProtocol):    Class (`Base64Encoder`) component used by the
app (see file context: None).
L2401: def decode(cls, data: bytes) -> bytes:    Function `decode` utility or script
function.
L2416: def encode(cls, value: bytes) -> bytes:    Function `encode` utility or script
function.
L2428: def get_json_format(cls) -> Literal['base64']:    Function `get_json_format` Returns
or fetches data.
L2437: class Base64UrlEncoder(EncoderProtocol):    Class (`Base64UrlEncoder`) component used
by the app (see file context: None).
L2441: def decode(cls, data: bytes) -> bytes:    Function `decode` utility or script
function.
L2456: def encode(cls, value: bytes) -> bytes:    Function `encode` utility or script
function.

```



```

L2468: def get_json_format(cls) -> Literal['base64url']:    Function `get_json_format`
Returns or fetches data.
L2478: class EncodedBytes:    Class (`EncodedBytes`)    component used by the app (see file
context: None).
L2488: class MyEncoder(EncoderProtocol):    Class (`MyEncoder`)    component used by the app
(see file context: None).
L2490: def decode(cls, data: bytes) -> bytes:    Function `decode`    utility or script
function.
L2496: def encode(cls, value: bytes) -> bytes:    Function `encode`    utility or script
function.
L2500: def get_json_format(cls) -> str:    Function `get_json_format`    Returns or fetches
data.
L2505: class Model(BaseModel):    Class (`Model`)    component used by the app (see file
context: None).
L2534: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__`    utility
or script function.
L2541: def __get_pydantic_core_schema__(self, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`
utility or script function.
L2550: def decode(self, data: bytes, _: core_schema.ValidationInfo) -> bytes:    Function
`decode`    utility or script function.
L2561: def encode(self, value: bytes) -> bytes:    Function `encode`    utility or script
function.
L2572: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L2577: class EncodedStr:    Class (`EncodedStr`)    component used by the app (see file context:
None).
L2587: class MyEncoder(EncoderProtocol):    Class (`MyEncoder`)    component used by the app
(see file context: None).
L2589: def decode(cls, data: bytes) -> bytes:    Function `decode`    utility or script
function.
L2595: def encode(cls, value: bytes) -> bytes:    Function `encode`    utility or script
function.
L2599: def get_json_format(cls) -> str:    Function `get_json_format`    Returns or fetches
data.
L2604: class Model(BaseModel):    Class (`Model`)    component used by the app (see file
context: None).
L2633: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__`    utility
or script function.
L2640: def __get_pydantic_core_schema__(self, source: type[Any], handler:
GetCoreSchemaHandler) -> core_schema.CoreSchema:    Function `__get_pydantic_core_schema__`
utility or script function.
L2649: def decode_str(self, data: str, _: core_schema.ValidationInfo) -> str:    Function
`decode_str`    utility or script function.
L2660: def encode_str(self, value: str) -> str:    Function `encode_str`    utility or script
function.
L2671: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L2698: class LegacyBase64Encoder(EncoderProtocol):    Class (`LegacyBase64Encoder`)    component
used by the app (see file context: None).
L2700: def decode(cls, data: bytes) -> bytes:    Function `decode`    utility or script
function.
L2711: def encode(cls, value: bytes) -> bytes:    Function `encode`    utility or script

```

```

function.
L2715: def get_json_format(cls) -> Literal['base64']:    Function `get_json_format` Returns
or fetches data.
L2725: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L2772: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L2811: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L2832: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L2847: class GetPydanticSchema:    Class (`GetPydanticSchema`) component used by the app (see
file context: None).
L2864: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L2881: def __getattr__(self, item: str) -> Any:    Function `__getattr__` utility or script
function.
L2894: class Tag:    Class (`Tag`) component used by the app (see file context: None).
L2912: class Pie(BaseModel):    Class (`Pie`) component used by the app (see file context:
None).
L2916: class ApplePie(Pie):    Class (`ApplePie`) component used by the app (see file
context: None).
L2919: class PumpkinPie(Pie):    Class (`PumpkinPie`) component used by the app (see file
context: None).
L2922: def get_discriminator_value(v: Any) -> str:    Function `get_discriminator_value`
Returns or fetches data.
L2927: class ThanksgivingDinner(BaseModel):    Class (`ThanksgivingDinner`) component used by
the app (see file context: None).
L2971: def __get_pydantic_core_schema__(self, source_type: Any, handler:
GetCoreSchemaHandler) -> CoreSchema:    Function `__get_pydantic_core_schema__` utility or
script function.
L2979: class Discriminator:    Class (`Discriminator`) component used by the app (see file
context: None).
L2999: class Pie(BaseModel):    Class (`Pie`) component used by the app (see file context:
None).
L3003: class ApplePie(Pie):    Class (`ApplePie`) component used by the app (see file
context: None).
L3006: class PumpkinPie(Pie):    Class (`PumpkinPie`) component used by the app (see file
context: None).
L3009: def get_discriminator_value(v: Any) -> str:    Function `get_discriminator_value`
Returns or fetches data.
L3014: class ThanksgivingDinner(BaseModel):    Class (`ThanksgivingDinner`) component used by
the app (see file context: None).
L3066: def __get_pydantic_core_schema__(self, source_type: Any, handler:
GetCoreSchemaHandler) -> CoreSchema:    Function `__get_pydantic_core_schema__` utility or
script function.
L3075: def _convert_schema(    Function `_convert_schema` utility or script function.
L3157: def _get_type_name(x: Any) -> str:    Function `_get_type_name` utility or script
function.
L3178: class _AllowAnyJson:    Class (`_AllowAnyJson`) component used by the app (see file
context: None).

```

```

L3180: def __get_pydantic_core_schema__(cls, source_type: Any, handler: GetCoreSchemaHandler)
-> CoreSchema:    Function `__get_pydantic_core_schema__` utility or script function.
L3216: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).
L3262: class _OnErrorOmit:    Class (`_OnErrorOmit`) component used by the app (see file
context: None).
L3264: def __get_pydantic_core_schema__(cls, source_type: Any, handler: GetCoreSchemaHandler)
-> CoreSchema:    Function `__get_pydantic_core_schema__` utility or script function.
L3281: class FailFast(_fields.PydanticMetadata, BaseMetadata):    Class (`FailFast`)
component used by the app (see file context: None).
L3294: class Model(BaseModel):    Class (`Model`) component used by the app (see file
context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/annotated_handlers.py

```

L24: class GetJsonSchemaHandler:    Class (`GetJsonSchemaHandler`) component used by the app
(see file context: None).
L33: def __call__(self, core_schema: CoreSchemaOrField, /) -> JsonSchemaValue:    Function
`__call__` utility or script function.
L49: def resolve_ref_schema(self, maybe_ref_json_schema: JsonSchemaValue, /) ->
JsonSchemaValue:    Function `resolve_ref_schema` utility or script function.
L66: class GetCoreSchemaHandler:    Class (`GetCoreSchemaHandler`) component used by the app
(see file context: None).
L69: def __call__(self, source_type: Any, /) -> core_schema.CoreSchema:    Function `__call__`
utility or script function.
L84: def generate_schema(self, source_type: Any, /) -> core_schema.CoreSchema:    Function
`generate_schema` Generates content (often AI-generated).
L99: def resolve_ref_schema(self, maybe_ref_schema: core_schema.CoreSchema, /) ->
core_schema.CoreSchema:    Function `resolve_ref_schema` utility or script function.
L116: def field_name(self) -> str | None:    Function `field_name` utility or script
function.
L120: def _get_types_namespace(self) -> NamespacesTuple:    Function `_get_types_namespace`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/warnings.py

```

L22: class PydanticDeprecationWarning(DeprecationWarning):    Class
(`PydanticDeprecationWarning`) component used by the app (see file context: None).
L38: def __init__(    Function `__init__` utility or script function.
L46: def __str__(self) -> str:    Function `__str__` utility or script function.
L56: class PydanticDeprecatedSince20(PydanticDeprecationWarning):    Class

```

```

(`PydanticDeprecatedSince20`) component used by the app (see file context: None).
L59: def __init__(self, message: str, *args: object) -> None:    Object (singleton).
L63: class PydanticDeprecatedSince26(PydanticDeprecationWarning): # pragma: no cover    Class
(`PydanticDeprecatedSince26`) component used by the app (see file context: None).
L66: def __init__(self, message: str, *args: object) -> None:    Object (singleton).
L70: class PydanticDeprecatedSince29(PydanticDeprecationWarning):    Class
(`PydanticDeprecatedSince29`) component used by the app (see file context: None).
L73: def __init__(self, message: str, *args: object) -> None:    Object (singleton).
L77: class PydanticDeprecatedSince210(PydanticDeprecationWarning):    Class
(`PydanticDeprecatedSince210`) component used by the app (see file context: None).
L80: def __init__(self, message: str, *args: object) -> None:    Object (singleton).
L84: class PydanticDeprecatedSince211(PydanticDeprecationWarning):    Class
(`PydanticDeprecatedSince211`) component used by the app (see file context: None).
L87: def __init__(self, message: str, *args: object) -> None:    Object (singleton).
L91: class PydanticDeprecatedSince212(PydanticDeprecationWarning):    Class
(`PydanticDeprecatedSince212`) component used by the app (see file context: None).
L94: def __init__(self, message: str, *args: object) -> None:    Object (singleton).
L98: class GenericBeforeBaseModelWarning(Warning):    Class (`GenericBeforeBaseModelWarning`)
component used by the app (see file context: None).
L102: class PydanticExperimentalWarning(Warning):    Class (`PydanticExperimentalWarning`)
component used by the app (see file context: None).
L109: class CoreSchemaGenerationWarning(UserWarning):    Class (`CoreSchemaGenerationWarning`)
component used by the app (see file context: None).
L113: class ArbitraryTypeWarning(CoreSchemaGenerationWarning):    Class
(`ArbitraryTypeWarning`) component used by the app (see file context: None).
L117: class UnsupportedFieldAttributeWarning(CoreSchemaGenerationWarning):    Class
(`UnsupportedFieldAttributeWarning`) component used by the app (see file context: None).
L121: class TypedDictExtraConfigWarning(CoreSchemaGenerationWarning):    Class
(`TypedDictExtraConfigWarning`) component used by the app (see file context: None).

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/color.py

```

L33: class RGBA:    Class (`RGBA`) component used by the app (see file context: None).
L38: def __init__(self, r: float, g: float, b: float, alpha: Optional[float]):    Function
`__init__` utility or script function.
L46: def __getitem__(self, item: Any) -> Any:    Function `__getitem__` utility or script
function.
L77: class Color(_repr.Representation):    Class (`Color`) component used by the app (see
file context: None).
L82: def __init__(self, value: ColorType) -> None:    Function `__init__` utility or script
function.
L101: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility or
script function.
L108: def original(self) -> ColorType:    Function `original` utility or script function.
L112: def as_named(self, *, fallback: bool = False) -> str:    Function `as_named` utility or
script function.
L138: def as_hex(self) -> str:    Function `as_hex` utility or script function.
L156: def as_rgb(self) -> str:    Function `as_rgb` utility or script function.

```

```

L166: def as_rgb_tuple(self, *, alpha: Optional[bool] = None) -> ColorTuple:    Function
`as_rgb_tuple` utility or script function.
L192: def as_hsl(self) -> str:    Function `as_hsl` utility or script function.
L201: def as_hsl_tuple(self, *, alpha: Optional[bool] = None) -> HslColorTuple:    Function
`as_hsl_tuple` utility or script function.
L230: def _alpha_float(self) -> float:    Function `_alpha_float` utility or script function.
L234: def __get_pydantic_core_schema__(    Function `__get_pydantic_core_schema__` utility or
script function.
L242: def _validate(cls, __input_value: Any, _: Any) -> 'Color':    Function `_validate`
utility or script function.
L245: def __str__(self) -> str:    Function `__str__` utility or script function.
L248: def __repr_args__(self) -> 'repr.ReprArgs':    Function `__repr_args__` utility or
script function.
L251: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L254: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L258: def parse_tuple(value: tuple[Any, ...]) -> RGBA:    Function `parse_tuple` utility or
script function.
L280: def parse_str(value: str) -> RGBA:    Function `parse_str` utility or script function.
L339: def ints_to_rgba(r: Union[int, str], g: Union[int, str], b: Union[int, str], alpha:
Optional[float] = None) -> RGBA:    Function `ints_to_rgba` utility or script function.
L354: def parse_color_value(value: Union[int, str], max_val: int = 255) -> float:    Function
`parse_color_value` utility or script function.
L381: def parse_float_alpha(value: Union[None, str, float, int]) -> Optional[float]:
Function `parse_float_alpha` utility or script function.
L411: def parse_hsl(h: str, h_units: str, sat: str, light: str, alpha: Optional[float] =
None) -> RGBA:    Function `parse_hsl` utility or script function.
L439: def float_to_255(c: float) -> int:    Function `float_to_255` utility or script
function.

```

Q_base appwrite/venv/lib/python3.12/site-packages/pydantic/main.py

```

L82: def _check_frozen(model_cls: type[BaseModel], name: str, value: Any) -> None:    Function
`_check_frozen` utility or script function.
L95: def _model_field_setattr_handler(model: BaseModel, name: str, val: Any) -> None:
Function `_model_field_setattr_handler` utility or script function.
L100: def _private_setattr_handler(model: BaseModel, name: str, val: Any) -> None:    Function
`_private_setattr_handler` utility or script function.
L119: class BaseModel(metaclass=_model_construction.ModelMetaclass):    Class (`BaseModel`)
component used by the app (see file context: None).
L253: def __init__(self, /, **data: Any) -> None:    Function `__init__` utility or script
function.
L277: def model_fields(cls) -> dict[str, FieldInfo]:    Function `model_fields` utility or
script function.
L288: def model_computed_fields(cls) -> dict[str, ComputedFieldInfo]:    Function
`model_computed_fields` utility or script function.
L298: def model_extra(self) -> dict[str, Any] | None:    Function `model_extra` utility or
script function.
L307: def model_fields_set(self) -> set[str]:    Function `model_fields_set` utility or

```

```

script function.
L317: def model_construct(cls, _fields_set: set[str] | None = None, **values: Any) -> Self:
# noqa: C901    Function `model_construct` utility or script function.
L393: def model_copy(self, *, update: Mapping[str, Any] | None = None, deep: bool = False) ->
Self:    Function `model_copy` utility or script function.
L427: def model_dump(    Function `model_dump` utility or script function.
L493: def model_dump_json(    Function `model_dump_json` utility or script function.
L562: def model_json_schema(    Function `model_json_schema` utility or script function.
L601: def model_parametrized_name(cls, params: tuple[type[Any], ...]) -> str:    Function
`model_parametrized_name` utility or script function.
L627: def model_post_init(self, context: Any, /) -> None:    Function `model_post_init`
utility or script function.
L633: def model_rebuild(    Function `model_rebuild` utility or script function.
L694: def model_validate(    Function `model_validate` utility or script function.
L743: def model_validate_json(    Function `model_validate_json` utility or script function.
L787: def model_validate_strings(    Function `model_validate_strings` utility or script
function.
L825: def __get_pydantic_core_schema__(cls, source: type[BaseModel], handler:
GetCoreSchemaHandler, /) -> CoreSchema:    Function `__get_pydantic_core_schema__` utility or
script function.
L845: def __get_pydantic_json_schema__(    Function `__get_pydantic_json_schema__` utility or
script function.
L871: def __pydantic_init_subclass__(cls, **kwargs: Any) -> None:    Function
`__pydantic_init_subclass__` utility or script function.
L894: def __pydantic_on_complete__(cls) -> None:    Function `__pydantic_on_complete__`
utility or script function.
L904: def __class_getitem__(    Function `__class_getitem__` utility or script function.
L971: def __copy__(self) -> Self:    Function `__copy__` utility or script function.
L990: def __deepcopy__(self, memo: dict[int, Any] | None = None) -> Self:    Function
`__deepcopy__` utility or script function.
L1015: def __getattr__(self, item: str) -> Any:    Function `__getattr__` utility or script
function.
L1044: def __setattr__(self, name: str, value: Any) -> None:    Function `__setattr__`
utility or script function.
L1052: def _setattr_handler(self, name: str, value: Any) -> Callable[[BaseModel, str, Any],
None] | None:    Function `_setattr_handler` utility or script function.
L1107: def __delattr__(self, item: str) -> Any:    Function `__delattr__` utility or script
function.
L1142: def __replace__(self, **changes: Any) -> Self:    Function `__replace__` utility or
script function.
L1145: def __getstate__(self) -> dict[Any, Any]:    Function `__getstate__` utility or script
function.
L1156: def __setstate__(self, state: dict[Any, Any]) -> None:    Function `__setstate__`
utility or script function.
L1164: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L1226: def __init_subclass__(cls, **kwargs: Unpack[ConfigDict]):    Function
`__init_subclass__` utility or script function.
L1233: class MyModel(BaseModel, extra='allow'): ...    Class (`MyModel`) component used by
the app (see file context: None).
L1248: def __iter__(self) -> TupleGenerator:    Function `__iter__` utility or script
function.

```

```

L1255: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L1258: def __repr_args__(self) -> _repr.ReprArgs:    Function `__repr_args__` utility or
script function.
L1293: def __str__(self) -> str:    Function `__str__` utility or script function.
L1301: def __fields__(self) -> dict[str, FieldInfo]:    Function `__fields__` utility or
script function.
L1314: def __fields_set__(self) -> set[str]:    Function `__fields_set__` utility or script
function.
L1323: def dict( # noqa: D102    Function `dict` utility or script function.
L1348: def json( # noqa: D102    Function `json` utility or script function.
L1383: def parse_obj(cls, obj: Any) -> Self: # noqa: D102    Function `parse_obj` utility or
script function.
L1397: def parse_raw( # noqa: D102    Function `parse_raw` utility or script function.
L1451: def parse_file( # noqa: D102    Function `parse_file` utility or script function.
L1483: def from_orm(cls, obj: Any) -> Self: # noqa: D102    Function `from_orm` utility or
script function.
L1498: def construct(cls, _fields_set: set[str] | None = None, **values: Any) -> Self: #
noqa: D102    Function `construct` utility or script function.
L1511: def copy(    Function `copy` utility or script function.
L1585: def schema( # noqa: D102    Function `schema` utility or script function.
L1600: def schema_json( # noqa: D102    Function `schema_json` utility or script function.
L1620: def validate(cls, value: Any) -> Self: # noqa: D102    Function `validate` utility or
script function.
L1633: def update_forward_refs(cls, **localns: Any) -> None: # noqa: D102    Function
`update_forward_refs` utility or script function.
L1646: def _iter(self, *args: Any, **kwargs: Any) -> Any:    Function `_iter` utility or
script function.
L1660: def _copy_and_set_values(self, *args: Any, **kwargs: Any) -> Any:    Function
`_copy_and_set_values` utility or script function.
L1675: def _get_value(cls, *args: Any, **kwargs: Any) -> Any:    Function `_get_value`
utility or script function.
L1689: def _calculate_keys(self, *args: Any, **kwargs: Any) -> Any:    Function
`_calculate_keys` utility or script function.
L1704: def create_model(    Function `create_model` Creates a resource or document.
L1720: def create_model(    Function `create_model` Creates a resource or document.
L1735: def create_model( # noqa: C901    Function `create_model` Creates a resource or
document.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/pydantic/errors.py

```

L82: class PydanticErrorMixin:    Class (`PydanticErrorMixin`) component used by the app (see
file context: None).
L90: def __init__(self, message: str, *, code: PydanticErrorCodes | None) -> None:    Function
`__init__` utility or script function.
L94: def __str__(self) -> str:    Function `__str__` utility or script function.
L101: class PydanticUserError(PydanticErrorMixin, RuntimeError):    Class
(`PydanticUserError`) component used by the app (see file context: None).
L105: class PydanticUndefinedAnnotation(PydanticErrorMixin, NameError):    Class

```



```
(`PydanticUndefinedAnnotation`) component used by the app (see file context: None).
L113: def __init__(self, name: str, message: str) -> None:    Function `__init__` utility or
script function.
L118: def from_name_error(cls, name_error: NameError) -> Self:    Function `from_name_error`
utility or script function.
L134: class PydanticImportError(PydanticErrorMixin, ImportError):    Class
(`PydanticImportError`) component used by the app (see file context: None).
L141: def __init__(self, message: str) -> None:    Function `__init__` utility or script
function.
L145: class PydanticSchemaGenerationError(PydanticUserError):    Class
(`PydanticSchemaGenerationError`) component used by the app (see file context: None).
L152: def __init__(self, message: str) -> None:    Function `__init__` utility or script
function.
L156: class PydanticInvalidForJsonSchema(PydanticUserError):    Class
(`PydanticInvalidForJsonSchema`) component used by the app (see file context: None).
L163: def __init__(self, message: str) -> None:    Function `__init__` utility or script
function.
L167: class PydanticForbiddenQualifier(PydanticUserError):    Class
(`PydanticForbiddenQualifier`) component used by the app (see file context: None).
L179: def __init__(self, qualifier: Qualifier, annotation: Any) -> None:    Function
`__init__` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/root_model.py

```
L23: class _RootModelMetaclass(_model_construction.ModelMetaclass): ...    Class
(`_RootModelMetaclass`) component used by the app (see file context: None).
L32: class RootModel(BaseModel, Generic[RootModelRootType], metaclass=_RootModelMetaclass):
Class (`RootModel`) component used by the app (see file context: None).
L52: def __init_subclass__(cls, **kwargs):    Function `__init_subclass__` utility or script
function.
L60: def __init__(self, /, root: RootModelRootType = PydanticUndefined, **data) -> None:    #
type: ignore    Function `__init__` utility or script function.
L73: def model_construct(cls, root: RootModelRootType, _fields_set: set[str] | None = None)
-> Self:    # type: ignore    Function `model_construct` utility or script function.
L88: def __getstate__(self) -> dict[Any, Any]:    Function `__getstate__` utility or script
function.
L94: def __setstate__(self, state: dict[Any, Any]) -> None:    Function `__setstate__`
utility or script function.
L98: def __copy__(self) -> Self:    Function `__copy__` utility or script function.
L108: def __deepcopy__(self, memo: dict[int, Any] | None = None) -> Self:    Function
`__deepcopy__` utility or script function.
L120: def model_dump(    # type: ignore    Function `model_dump` utility or script function.
L149: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L156: def __repr_args__(self) -> _repr.ReprArgs:    Function `__repr_args__` utility or
script function.
```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_core_metadata.py

```

L13: class CoreMetadata(TypedDict, total=False):    Class (`CoreMetadata`) component used by
the app (see file context: None).
L47: def update_core_metadata(    Function `update_core_metadata` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_generate_schema.py

```

L202: def check_validator_fields_against_field_name(    Function
`check_validator_fields_against_field_name` utility or script function.
L219: def check_decorator_fields_exist(decorators: Iterable[AnyFieldDecorator], fields:
Iterable[str]) -> None:    Function `check_decorator_fields_exist` utility or script
function.
L246: def filter_field_decorator_info_by_field(    Function
`filter_field_decorator_info_by_field` utility or script function.
L252: def apply_each_item_validators(    Function `apply_each_item_validators` utility or
script function.
L287: def _extract_json_schema_info_from_field_info(    Function
`_extract_json_schema_info_from_field_info` utility or script function.
L303: def _add_custom_serialization_from_json_encoders(    Function
`_add_custom_serialization_from_json_encoders` utility or script function.
L346: class InvalidSchemaError(Exception):    Class (`InvalidSchemaError`) component used by
the app (see file context: None).
L350: class GenerateSchema:    Class (`GenerateSchema`) component used by the app (see file
context: None).
L362: def __init__(    Function `__init__` utility or script function.
L376: def __init_subclass__(cls) -> None:    Function `__init_subclass__` utility or script
function.
L385: def _config_wrapper(self) -> ConfigWrapper:    Function `_config_wrapper` utility or
script function.
L389: def _types_namespace(self) -> NamespacesTuple:    Function `_types_namespace` utility
or script function.
L393: def _arbitrary_types(self) -> bool:    Function `_arbitrary_types` utility or script
function.
L398: def _list_schema(self, items_type: Any) -> CoreSchema:    Function `_list_schema`
utility or script function.
L401: def _dict_schema(self, keys_type: Any, values_type: Any) -> CoreSchema:    Function
`_dict_schema` utility or script function.
L404: def _set_schema(self, items_type: Any) -> CoreSchema:    Function `_set_schema` utility
or script function.
L407: def _frozenset_schema(self, items_type: Any) -> CoreSchema:    Function

```

```

`_frozenset_schema` utility or script function.
L410: def _enum_schema(self, enum_type: type[Enum]) -> CoreSchema:    Function `_enum_schema`
utility or script function.
L439: def get_json_schema(schema: CoreSchema, handler: GetJsonSchemaHandler) ->
JsonSchemaValue:    Function `get_json_schema` Returns or fetches data.
L465: def get_json_schema_no_cases(_, handler: GetJsonSchemaHandler) -> JsonSchemaValue:
Function `get_json_schema_no_cases` Returns or fetches data.
L482: def _ip_schema(self, tp: Any) -> CoreSchema:    Function `_ip_schema` utility or script
function.
L494: def ser_ip(ip: Any, info: core_schema.SerializationInfo) -> str | IpType:    Function
`ser_ip` utility or script function.
L515: def _path_schema(self, tp: Any, path_type: Any) -> CoreSchema:    Function
`_path_schema` utility or script function.
L527: def path_validator(input_value: str | bytes) -> os.PathLike[Any]: # type: ignore
Function `path_validator` utility or script function.
L544: def ser_path(path: Any, info: core_schema.SerializationInfo) -> str | os.PathLike[Any]:
Function `ser_path` utility or script function.
L573: def _deque_schema(self, items_type: Any) -> CoreSchema:    Function `_deque_schema`
utility or script function.
L598: def _mapping_schema(self, tp: Any, keys_type: Any, values_type: Any) -> CoreSchema:
Function `_mapping_schema` utility or script function.
L644: def _fraction_schema(self) -> CoreSchema:    Function `_fraction_schema` utility or
script function.
L661: def _arbitrary_type_schema(self, tp: Any) -> CoreSchema:    Function
`_arbitrary_type_schema` utility or script function.
L673: def _unknown_type_schema(self, obj: Any) -> CoreSchema:    Function
`_unknown_type_schema` utility or script function.
L684: def _apply_discriminator_to_union(    Function `_apply_discriminator_to_union` utility
or script function.
L703: def clean_schema(self, schema: CoreSchema) -> CoreSchema:    Function `clean_schema`
utility or script function.
L706: def _add_js_function(self, metadata_schema: CoreSchema, js_function: Callable[...,
Any]) -> None:    Function `_add_js_function` utility or script function.
L717: def generate_schema(    Function `generate_schema` Generates content (often
AI-generated).
L756: def _model_schema(self, cls: type[BaseModel]) -> core_schema.CoreSchema:    Function
`_model_schema` utility or script function.
L895: def _resolve_self_type(self, obj: Any) -> Any:    Function `_resolve_self_type` utility
or script function.
L901: def _generate_schema_from_get_schema_method(self, obj: Any, source: Any) ->
core_schema.CoreSchema | None:    Function `_generate_schema_from_get_schema_method` utility
or script function.
L960: def _resolve_forward_ref(self, obj: Any) -> Any:    Function `_resolve_forward_ref`
utility or script function.
L983: def _get_args_resolving_forward_refs(self, obj: Any, required: Literal[True]) ->
tuple[Any, ...]: ...    Function `_get_args_resolving_forward_refs` utility or script
function.
L986: def _get_args_resolving_forward_refs(self, obj: Any) -> tuple[Any, ...] | None: ...
Function `_get_args_resolving_forward_refs` utility or script function.
L988: def _get_args_resolving_forward_refs(self, obj: Any, required: bool = False) ->
tuple[Any, ...] | None:    Function `_get_args_resolving_forward_refs` utility or script

```

```

function.
L1002: def _get_first_arg_or_any(self, obj: Any) -> Any:    Function `_get_first_arg_or_any`
utility or script function.
L1008: def _get_first_two_args_or_any(self, obj: Any) -> tuple[Any, Any]:    Function
`_get_first_two_args_or_any`    utility or script function.
L1017: def _generate_schema_inner(self, obj: Any) -> core_schema.CoreSchema:    Function
`_generate_schema_inner`    utility or script function.
L1045: def match_type(self, obj: Any) -> core_schema.CoreSchema:    # noqa: C901    Function
`match_type`    utility or script function.
L1167: def _match_generic_type(self, obj: Any, origin: Any) -> CoreSchema:    # noqa: C901
Function `_match_generic_type`    utility or script function.
L1218: def _generate_td_field_schema(    Function `_generate_td_field_schema`    utility or
script function.
L1238: def _generate_md_field_schema(    Function `_generate_md_field_schema`    utility or
script function.
L1256: def _generate_dc_field_schema(    Function `_generate_dc_field_schema`    utility or
script function.
L1278: def _common_field_schema(    # C901    Function `_common_field_schema`    utility or script
function.
L1283: def set_discriminator(schema: CoreSchema) -> CoreSchema:    Function
`set_discriminator`    Sets or updates a value.
L1335: def _union_schema(self, union_type: Any) -> core_schema.CoreSchema:    Function
`_union_schema`    utility or script function.
L1362: def _type_alias_type_schema(self, obj: TypeAliasType) -> CoreSchema:    Function
`_type_alias_type_schema`    utility or script function.
L1381: def _literal_schema(self, literal_type: Any) -> CoreSchema:    Function
`_literal_schema`    utility or script function.
L1394: def _typed_dict_schema(self, typed_dict_cls: Any, origin: Any) ->
core_schema.CoreSchema:    Function `_typed_dict_schema`    utility or script function.
L1533: def _namedtuple_schema(self, namedtuple_cls: Any, origin: Any) ->
core_schema.CoreSchema:    Function `_namedtuple_schema`    utility or script function.
L1579: def _generate_parameter_schema(    Function `_generate_parameter_schema`    utility or
script function.
L1624: def _generate_parameter_v3_schema(    Function `_generate_parameter_v3_schema`    utility
or script function.
L1674: def _tuple_schema(self, tuple_type: Any) -> core_schema.CoreSchema:    Function
`_tuple_schema`    utility or script function.
L1704: def _type_schema(self) -> core_schema.CoreSchema:    Function `_type_schema`    utility
or script function.
L1711: def _zoneinfo_schema(self) -> core_schema.CoreSchema:    Function `_zoneinfo_schema`
utility or script function.
L1722: def _union_is_subclass_schema(self, union_type: Any) -> core_schema.CoreSchema:
Function `_union_is_subclass_schema`    utility or script function.
L1727: def _subclass_schema(self, type_: Any) -> core_schema.CoreSchema:    Function
`_subclass_schema`    utility or script function.
L1766: def _sequence_schema(self, items_type: Any) -> core_schema.CoreSchema:    Function
`_sequence_schema`    utility or script function.
L1789: def _iterable_schema(self, type_: Any) -> core_schema.GeneratorSchema:    Function
`_iterable_schema`    utility or script function.
L1795: def _pattern_schema(self, pattern_type: Any) -> core_schema.CoreSchema:    Function
`_pattern_schema`    utility or script function.

```

```

L1823: def _hashable_schema(self) -> core_schema.CoreSchema:    Function `_hashable_schema`
utility or script function.
L1835: def _dataclass_schema(    Function `_dataclass_schema`    utility or script function.
L1957: def _call_schema(self, function: ValidateCallSupportedTypes) ->
core_schema.CallSchema:    Function `_call_schema`    utility or script function.
L1982: def _arguments_schema(    Function `_arguments_schema`    utility or script function.
L2057: def _arguments_v3_schema(    Function `_arguments_v3_schema`    utility or script
function.
L2125: def _unsubstituted_typevar_schema(self, typevar: typing.TypeVar) ->
core_schema.CoreSchema:    Function `_unsubstituted_typevar_schema`    utility or script
function.
L2145: def _computed_field_schema(    Function `_computed_field_schema`    utility or script
function.
L2195: def _annotated_schema(self, annotated_type: Any) -> core_schema.CoreSchema:    Function
`_annotated_schema`    utility or script function.
L2210: def _apply_annotations(    Function `_apply_annotations`    utility or script function.
L2227: def inner_handler(obj: Any) -> CoreSchema:    Function `inner_handler`    utility or
script function.
L2258: def _apply_single_annotation(    Function `_apply_single_annotation`    utility or script
function.
L2374: def _apply_single_annotation_json_schema(    Function
`_apply_single_annotation_json_schema`    utility or script function.
L2390: def _get_unsupported_field_info_attributes(self, field_info: FieldInfo) ->
list[tuple[str, Any]]:    Function `_get_unsupported_field_info_attributes`    utility or script
function.
L2412: def _get_wrapped_inner_schema(    Function `_get_wrapped_inner_schema`    utility or
script function.
L2421: def new_handler(source: Any) -> core_schema.CoreSchema:    Function `new_handler`
utility or script function.
L2440: def _apply_field_serializers(    Function `_apply_field_serializers`    utility or script
function.
L2496: def _apply_model_serializers(    Function `_apply_model_serializers`    utility or script
function.
L2561: def apply_validators(    Function `apply_validators`    utility or script function.
L2587: def _validators_require_validate_default(validators:
Iterable[Decorator[ValidatorDecoratorInfo]]) -> bool:    Function
`_validators_require_validate_default`    utility or script function.
L2603: def _convert_to_aliases(    Function `_convert_to_aliases`    utility or script function.
L2612: def apply_model_validators(    Function `apply_model_validators`    utility or script
function.
L2659: def wrap_default(field_info: FieldInfo, schema: core_schema.CoreSchema) ->
core_schema.CoreSchema:    Function `wrap_default`    utility or script function.
L2684: def _extract_get_pydantic_json_schema(tp: Any) -> GetJsonSchemaFunction | None:
Function `_extract_get_pydantic_json_schema`    utility or script function.
L2716: def resolve_original_schema(schema: CoreSchema, definitions: _Definitions) ->
CoreSchema | None:    Function `resolve_original_schema`    utility or script function.
L2725: def _inlining_behavior(    Function `_inlining_behavior`    utility or script function.
L2745: class _Definitions:    Class (`_Definitions`)    component used by the app (see file
context: None).
L2766: def __init__(self) -> None:    Function `__init__`    utility or script function.
L2771: def get_schema_or_ref(self, tp: Any, /) -> Generator[tuple[str,

```

```

core_schema.DefinitionReferenceSchema | None]]:  Function `get_schema_or_ref` Returns or
fetches data.
L2803: def get_schema_from_ref(self, ref: str) -> CoreSchema | None:  Function
`get_schema_from_ref` Returns or fetches data.
L2807: def create_definition_reference_schema(self, schema: CoreSchema) ->
core_schema.DefinitionReferenceSchema:  Function `create_definition_reference_schema`
Creates a resource or document.
L2816: def unpack_definitions(self, schema: core_schema.DefinitionsSchema) -> CoreSchema:
Function `unpack_definitions` utility or script function.
L2822: def finalize_schema(self, schema: CoreSchema) -> CoreSchema:  Function
`finalize_schema` utility or script function.
L2880: def _resolve_definition(self, ref: str, definitions: dict[str, CoreSchema]) ->
CoreSchema:  Function `_resolve_definition` utility or script function.
L2899: class _FieldNameStack:  Class (`_FieldNameStack`) component used by the app (see
file context: None).
L2902: def __init__(self) -> None:  Function `__init__` utility or script function.
L2906: def push(self, field_name: str) -> Iterator[None]:  Function `push` utility or
script function.
L2911: def get(self) -> str | None:  Function `get` Returns or fetches data.
L2918: class _ModelTypeStack:  Class (`_ModelTypeStack`) component used by the app (see
file context: None).
L2921: def __init__(self) -> None:  Function `__init__` utility or script function.
L2925: def push(self, type_obj: type) -> Iterator[None]:  Function `push` utility or script
function.
L2930: def get(self) -> type | None:  Function `get` Returns or fetches data.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pydantic/_internal/_repr.py

```

L22: class PlainRepr(str):  Class (`PlainRepr`) component used by the app (see file
context: None).
L27: def __repr__(self) -> str:  Function `__repr__` utility or script function.
L31: class Representation:  Class (`Representation`) component used by the app (see file
context: None).
L39: def __repr_args__(self) -> ReprArgs:  Function `__repr_args__` utility or script
function.
L52: def __repr_name__(self) -> str:  Function `__repr_name__` utility or script function.
L56: def __repr_recursion__(self, object: Any) -> str:  Object (singleton).
L61: def __repr_str__(self, join_str: str) -> str:  Function `__repr_str__` utility or
script function.
L64: def __pretty__(self, fmt: Callable[[Any], Any], **kwargs: Any) -> Generator[Any]:
Function `__pretty__` utility or script function.
L77: def __rich_repr__(self) -> RichReprResult:  Function `__rich_repr__` utility or script
function.
L85: def __str__(self) -> str:  Function `__str__` utility or script function.
L88: def __repr__(self) -> str:  Function `__repr__` utility or script function.
L92: def display_as_type(obj: Any) -> str:  Function `display_as_type` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_serializers.py

```
L32: def serialize_sequence_via_list(    Function `serialize_sequence_via_list`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_docs_extraction.py

```
L12: class DocstringVisitor(ast.NodeVisitor):    Class (`DocstringVisitor`)    component used by the app (see file context: None).
L13: def __init__(self) -> None:    Function `__init__`    utility or script function.
L20: def visit(self, node: ast.AST) -> Any:    Function `visit`    utility or script function.
L25: def visit_AnnAssign(self, node: ast.AnnAssign) -> Any:    Function `visit_AnnAssign` utility or script function.
L29: def visit_Expr(self, node: ast.Expr) -> Any:    Function `visit_Expr`    utility or script function.
L41: def _dedent_source_lines(source: list[str]) -> str:    Function `_dedent_source_lines` utility or script function.
L52: def _extract_source_from_frame(cls: type[Any]) -> list[str] | None:    Function `_extract_source_from_frame`    utility or script function.
L82: def extract_docstrings_from_cls(cls: type[Any], use_inspect: bool = False) -> dict[str, str]:    Function `extract_docstrings_from_cls`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_import_utils.py

```
L10: def import_cached_base_model() -> type['BaseModel']:    Function `import_cached_base_model`    utility or script function.
L17: def import_cached_field_info() -> type['FieldInfo']:    Function `import_cached_field_info`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_config.py

```

L29: class ConfigWrapper:    Class (`ConfigWrapper`)    component used by the app (see file
context: None).
L93: def __init__(self, config: ConfigDict | dict[str, Any] | type[Any] | None, *, check:
bool = True):    Function `__init__`    utility or script function.
L100: def for_model(    Function `for_model`    utility or script function.
L154: def __getattr__(self, name: str) -> Any:    Function `__getattr__`    utility or script
function.
L163: def core_config(self, title: str | None) -> core_schema.CoreConfig:    Function
`core_config`    utility or script function.
L239: def __repr__(self):    Function `__repr__`    utility or script function.
L244: class ConfigWrapperStack:    Class (`ConfigWrapperStack`)    component used by the app
(see file context: None).
L247: def __init__(self, config_wrapper: ConfigWrapper):    Function `__init__`    utility or
script function.
L251: def tail(self) -> ConfigWrapper:    Function `tail`    utility or script function.
L255: def push(self, config_wrapper: ConfigWrapper | ConfigDict | None):    Function `push`
utility or script function.
L323: def prepare_config(config: ConfigDict | dict[str, Any] | type[Any] | None) ->
ConfigDict:    Function `prepare_config`    utility or script function.
L373: def check_deprecated(config_dict: ConfigDict) -> None:    Function `check_deprecated`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_validators.py

```

L28: def sequence_validator(    Function `sequence_validator`    utility or script function.
L68: def import_string(value: Any) -> Any:    Function `import_string`    utility or script
function.
L79: def _import_string_logic(dotted_path: str) -> Any:    Function `_import_string_logic`
utility or script function.
L131: def pattern_either_validator(input_value: Any, /) -> re.Pattern[Any]:    Function
`pattern_either_validator`    utility or script function.
L141: def pattern_str_validator(input_value: Any, /) -> re.Pattern[str]:    Function
`pattern_str_validator`    utility or script function.
L155: def pattern_bytes_validator(input_value: Any, /) -> re.Pattern[bytes]:    Function
`pattern_bytes_validator`    utility or script function.
L172: def compile_pattern(pattern: PatternType) -> re.Pattern[PatternType]:    Function
`compile_pattern`    utility or script function.
L179: def ip_v4_address_validator(input_value: Any, /) -> IPv4Address:    Function
`ip_v4_address_validator`    utility or script function.
L189: def ip_v6_address_validator(input_value: Any, /) -> IPv6Address:    Function
`ip_v6_address_validator`    utility or script function.
L199: def ip_v4_network_validator(input_value: Any, /) -> IPv4Network:    Function
`ip_v4_network_validator`    utility or script function.
L214: def ip_v6_network_validator(input_value: Any, /) -> IPv6Network:    Function
`ip_v6_network_validator`    utility or script function.

```



```

L229: def ip_v4_interface_validator(input_value: Any, /) -> IPv4Interface:    Function
`ip_v4_interface_validator` utility or script function.
L239: def ip_v6_interface_validator(input_value: Any, /) -> IPv6Interface:    Function
`ip_v6_interface_validator` utility or script function.
L249: def fraction_validator(input_value: Any, /) -> Fraction:    Function
`fraction_validator` utility or script function.
L259: def forbid_inf_nan_check(x: Any) -> Any:    Function `forbid_inf_nan_check` utility or
script function.
L265: def _safe_repr(v: Any) -> int | float | str:    Function `_safe_repr` utility or script
function.
L275: def greater_than_validator(x: Any, gt: Any) -> Any:    Function `greater_than_validator`
utility or script function.
L284: def greater_than_or_equal_validator(x: Any, ge: Any) -> Any:    Function
`greater_than_or_equal_validator` utility or script function.
L293: def less_than_validator(x: Any, lt: Any) -> Any:    Function `less_than_validator`
utility or script function.
L302: def less_than_or_equal_validator(x: Any, le: Any) -> Any:    Function
`less_than_or_equal_validator` utility or script function.
L311: def multiple_of_validator(x: Any, multiple_of: Any) -> Any:    Function
`multiple_of_validator` utility or script function.
L320: def min_length_validator(x: Any, min_length: Any) -> Any:    Function
`min_length_validator` utility or script function.
L331: def max_length_validator(x: Any, max_length: Any) -> Any:    Function
`max_length_validator` utility or script function.
L343: def _extract_decimal_digits_info(decimal: Decimal) -> tuple[int, int]:    Function
`_extract_decimal_digits_info` utility or script function.
L386: def max_digits_validator(x: Any, max_digits: Any) -> Any:    Function
`max_digits_validator` utility or script function.
L400: def decimal_places_validator(x: Any, decimal_places: Any) -> Any:    Function
`decimal_places_validator` utility or script function.
L415: def deque_validator(input_value: Any, handler:
core_schema.ValidatorFunctionWrapHandler) -> collections.deque[Any]:    Function
`deque_validator` utility or script function.
L419: def defaultdict_validator(    Function `defaultdict_validator` utility or script
function.
L429: def get_defaultdict_default_default_factory(values_source_type: Any) -> Callable[[],
Any]:    Function `get_defaultdict_default_default_factory` Returns or fetches data.
L434: def infer_default() -> Callable[[], Any]:    Function `infer_default` utility or script
function.
L458: def type_var_default_factory() -> None:    Function `type_var_default_factory` utility
or script function.
L488: def validate_str_is_valid_iana_tz(value: Any, /) -> ZoneInfo:    Function
`validate_str_is_valid_iana_tz` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_fields.p
y


```

L39: class PydanticMetadata(Representation):    Class (`PydanticMetadata`) component used by
the app (see file context: None).
L46: class PydanticExtraInfo:    Class (`PydanticExtraInfo`) component used by the app (see
file context: None).
L52: def pydantic_general_metadata(**metadata: Any) -> BaseMetadata:    Function
`pydantic_general_metadata` utility or script function.
L65: def _general_metadata_cls() -> type[BaseMetadata]:    Function `_general_metadata_cls`
utility or script function.
L69: class _PydanticGeneralMetadata(PydanticMetadata, BaseMetadata):    Class
(`_PydanticGeneralMetadata`) component used by the app (see file context: None).
L72: def __init__(self, metadata: Any):    Function `__init__` utility or script function.
L78: def _check_protected_namespaces(    Function `_check_protected_namespaces` utility or
script function.
L121: def _update_fields_from_docstrings(cls: type[Any], fields: dict[str, FieldInfo],
use_inspect: bool = False) -> None:    Function `_update_fields_from_docstrings` utility or
script function.
L128: def _apply_field_title_generator_to_field_info(    Function
`_apply_field_title_generator_to_field_info` utility or script function.
L141: def _apply_alias_generator_to_field_info(    Function
`_apply_alias_generator_to_field_info` utility or script function.
L191: def update_field_from_config(config_wrapper: ConfigWrapper, field_name: str,
field_info: FieldInfo) -> None:    Function `update_field_from_config` utility or script
function.
L224: def collect_model_fields( # noqa: C901    Function `collect_model_fields` utility or
script function.
L436: def rebuild_model_fields(    Function `rebuild_model_fields` utility or script
function.
L483: def _recreate_field_info(    Function `_recreate_field_info` utility or script
function.
L527: def collect_dataclass_fields(    Function `collect_dataclass_fields` utility or script
function.
L635: def rebuild_dataclass_fields(    Function `rebuild_dataclass_fields` utility or script
function.
L681: def is_valid_field_name(name: str) -> bool:    Function `is_valid_field_name` utility
or script function.
L685: def is_valid_privateattr_name(name: str) -> bool:    Function
`is_valid_privateattr_name` utility or script function.
L689: def takes_validated_data_argument(    Function `takes_validated_data_argument` utility
or script function.
L705: def resolve_default_value(    Function `resolve_default_value` utility or script
function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/pydantic/_internal/_validate_e_call.py

```

L19: def extract_function_name(func: ValidateCallSupportedTypes) -> str:    Function

```

```

`extract_function_name` utility or script function.
L24: def extract_function_qualname(func: ValidateCallSupportedTypes) -> str: Function
`extract_function_qualname` utility or script function.
L29: def update_wrapper_attributes(wrapped: ValidateCallSupportedTypes, wrapper:
Callable[..., Any]): Function `update_wrapper_attributes` utility or script function.
L39: def wrapper_function(*args, **kwargs): Function `wrapper_function` utility or script
function.
L50: class ValidateCallWrapper: Class (`ValidateCallWrapper`) component used by the app
(see file context: None).
L66: def __init__( Function `__init__` utility or script function.
L92: def _create_validators(self) -> None: Function `_create_validators` utility or script
function.
L133: def __call__(self, *args: Any, **kwargs: Any) -> Any: Function `__call__` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_schema a_generation_shared.py

```

L21: class GenerateJsonSchemaHandler(GetJsonSchemaHandler): Class
(`GenerateJsonSchemaHandler`) component used by the app (see file context: None).
L31: def __init__(self, generate_json_schema: GenerateJsonSchema, handler_override:
HandlerOverride | None) -> None: Function `__init__` utility or script function.
L36: def __call__(self, core_schema: CoreSchemaOrField, /) -> JsonSchemaValue: Function
`__call__` utility or script function.
L39: def resolve_ref_schema(self, maybe_ref_json_schema: JsonSchemaValue) -> JsonSchemaValue:
Function `resolve_ref_schema` utility or script function.
L65: class CallbackGetCoreSchemaHandler(GetCoreSchemaHandler): Class
(`CallbackGetCoreSchemaHandler`) component used by the app (see file context: None).
L72: def __init__( Function `__init__` utility or script function.
L82: def __call__(self, source_type: Any, /) -> core_schema.CoreSchema: Function `__call__`
utility or script function.
L92: def _get_types_namespace(self) -> NamespacesTuple: Function `_get_types_namespace`
utility or script function.
L95: def generate_schema(self, source_type: Any, /) -> core_schema.CoreSchema: Function
`generate_schema` Generates content (often AI-generated).
L99: def field_name(self) -> str | None: Function `field_name` utility or script function.
L102: def resolve_ref_schema(self, maybe_ref_schema: core_schema.CoreSchema) ->
core_schema.CoreSchema: Function `resolve_ref_schema` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_git.py

```

L9: def is_git_repo(dir: Path) -> bool: Function `is_git_repo` utility or script function.

```

```
L14: def have_git() -> bool: # pragma: no cover    Function `have_git` utility or script
function.
L25: def git_revision(dir: Path) -> str:    Function `git_revision` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_forward_ref.py

```
L8: class PydanticRecursiveRef:    Class (`PydanticRecursiveRef`) component used by the app
(see file context: None).
L14: def __call__(self) -> None:    Function `__call__` utility or script function.
L19: def __or__(self, other):    Function `__or__` utility or script function.
L22: def __ror__(self, other):    Function `__ror__` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_model_construction.py

```
L52: class _ModelNamespaceDict(dict):    Class (`_ModelNamespaceDict`) component used by the
app (see file context: None).
L57: def __setitem__(self, k: str, v: object) -> None:    Object (singleton).
L68: def NoInitField(    Function `NoInitField` utility or script function.
L83: class ModelMetaclass(ABCMeta):    Class (`ModelMetaclass`) component used by the app
(see file context: None).
L84: def __new__(    Function `__new__` utility or script function.
L142: def wrapped_model_post_init(self: BaseModel, context: Any, /) -> None:    Function
`wrapped_model_post_init` utility or script function.
L285: def __getattr__(self, item: str) -> Any:    Function `__getattr__` utility or script
function.
L293: def __prepare__(cls, *args: Any, **kwargs: Any) -> dict[str, object]:    Object
(singleton).
L300: def register(self, subclass: type[_T]) -> type[_T]:    Function `register` utility or
script function.
L312: def _collect_bases_data(bases: tuple[type[Any], ...]) -> tuple[set[str], set[str],
dict[str, ModelPrivateAttr]]:    Function `_collect_bases_data` utility or script function.
L330: def __fields__(self) -> dict[str, FieldInfo]:    Function `__fields__` utility or
script function.
L339: def __pydantic_fields_complete__(self) -> bool:    Function
`__pydantic_fields_complete__` utility or script function.
L357: def __dir__(self) -> list[str]:    Function `__dir__` utility or script function.
L364: def init_private_attributes(self: BaseModel, context: Any, /) -> None:    Function
`init_private_attributes` Initialisation routine.
L388: def get_model_post_init(namespace: dict[str, Any], bases: tuple[type[Any], ...]) ->
```

```

Callable[..., Any] | None:    Function `get_model_post_init` Returns or fetches data.
L400: def inspect_namespace( # noqa C901    Function `inspect_namespace` utility or script
function.
L537: def set_default_hash_func(cls: type[BaseModel], bases: tuple[type[Any], ...]) -> None:
    Function `set_default_hash_func` Sets or updates a value.
L550: def make_hash_func(cls: type[BaseModel]) -> Any:    Function `make_hash_func` utility
or script function.
L553: def hash_func(self: Any) -> int:    Function `hash_func` utility or script function.
L566: def set_model_fields(    Function `set_model_fields` Sets or updates a value.
L600: def complete_model_class(    Function `complete_model_class` utility or script
function.
L724: def set_deprecated_descriptors(cls: type[BaseModel]) -> None:    Function
`set_deprecated_descriptors` Sets or updates a value.
L743: class _DeprecatedFieldDescriptor:    Class (`_DeprecatedFieldDescriptor`) component
used by the app (see file context: None).
L754: def __init__(self, msg: str, wrapped_property: property | None = None) -> None:
Function `__init__` utility or script function.
L758: def __set_name__(self, cls: type[BaseModel], name: str) -> None:    Function
`__set_name__` utility or script function.
L761: def __get__(self, obj: BaseModel | None, obj_type: type[BaseModel] | None = None) ->
Any:    Function `__get__` utility or script function.
L776: def __set__(self, obj: Any, value: Any) -> NoReturn:    Function `__set__` utility or
script function.
L780: class _PydanticWeakRef:    Class (`_PydanticWeakRef`) component used by the app (see
file context: None).
L797: def __init__(self, obj: Any):    Function `__init__` utility or script function.
L805: def __call__(self) -> Any:    Function `__call__` utility or script function.
L811: def __reduce__(self) -> tuple[Callable, tuple[weakref.ReferenceType | None]]:
Function `__reduce__` utility or script function.
L815: def build_lenient_weakvaluedict(d: dict[str, Any] | None) -> dict[str, Any] | None:
Function `build_lenient_weakvaluedict` Constructs or prepares an object.
L835: def unpack_lenient_weakvaluedict(d: dict[str, Any] | None) -> dict[str, Any] | None:
Function `unpack_lenient_weakvaluedict` utility or script function.
L852: def default_ignored_types() -> tuple[type[Any], ...]:    Function
`default_ignored_types` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_known_annotated_metadata.py

```

L101: def as_jsonable_value(v: Any) -> Any:    Function `as_jsonable_value` utility or script
function.
L107: def expand_grouped_metadata(annotations: Iterable[Any]) -> Iterable[Any]:    Function
`expand_grouped_metadata` utility or script function.
L148: def _get_at_to_constraint_map() -> dict[type, str]:    Function
`_get_at_to_constraint_map` utility or script function.
L169: def apply_known_metadata(annotation: Any, schema: CoreSchema) -> CoreSchema | None:    #

```

```

noqa: C901 Function `apply_known_metadata` utility or script function.
L231: def _apply_constraint_with_incompatibility_info( Function
`_apply_constraint_with_incompatibility_info` utility or script function.
L310: def val_func(v: Any) -> Any: Function `val_func` utility or script function.
L321: def val_func(v: Any) -> Any: Function `val_func` utility or script function.
L342: def collect_known_metadata(annotations: Iterable[Any]) -> tuple[dict[str, Any],
list[Any]]: Function `collect_known_metadata` utility or script function.
L387: def check_metadata(metadata: dict[str, Any], allowed: Iterable[str], source_type: Any)
-> None: Function `check_metadata` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_decorators.py

```

L32: class ValidatorDecoratorInfo: Class (`ValidatorDecoratorInfo`) component used by the
app (see file context: None).
L56: class FieldValidatorDecoratorInfo: Class (`FieldValidatorDecoratorInfo`) component
used by the app (see file context: None).
L79: class RootValidatorDecoratorInfo: Class (`RootValidatorDecoratorInfo`) component used
by the app (see file context: None).
L93: class FieldSerializerDecoratorInfo: Class (`FieldSerializerDecoratorInfo`) component
used by the app (see file context: None).
L116: class ModelSerializerDecoratorInfo: Class (`ModelSerializerDecoratorInfo`) component
used by the app (see file context: None).
L135: class ModelValidatorDecoratorInfo: Class (`ModelValidatorDecoratorInfo`) component
used by the app (see file context: None).
L165: class PydanticDescriptorProxy(Generic[ReturnType]): Class (`PydanticDescriptorProxy`)
component used by the app (see file context: None).
L183: def __post_init__(self): Function `__post_init__` utility or script function.
L189: def _call_wrapped_attr(self, func: Callable[[Any], None], *, name: str) ->
PydanticDescriptorProxy[ReturnType]: Function `_call_wrapped_attr` utility or script
function.
L199: def __get__(self, obj: object | None, obj_type: type[object] | None = None) ->
PydanticDescriptorProxy[ReturnType]: Object (singleton).
L206: def __set_name__(self, instance: Any, name: str) -> None: Function `__set_name__`
utility or script function.
L210: def __getattr__(self, name: str, /) -> Any: Function `__getattr__` utility or script
function.
L219: class Decorator(Generic[DecoratorInfoType]): Class (`Decorator`) component used by
the app (see file context: None).
L240: def build( Function `build` Constructs or prepares an object.
L276: def bind_to_cls(self, cls: Any) -> Decorator[DecoratorInfoType]: Function
`bind_to_cls` utility or script function.
L293: def get_bases(tp: type[Any]) -> tuple[type[Any], ...]: Function `get_bases` Returns
or fetches data.
L310: def mro(tp: type[Any]) -> tuple[type[Any], ...]: Function `mro` utility or script
function.

```

```

L328: def mro_for_bases(bases: tuple[type[Any], ...]) -> tuple[type[Any], ...]:    Function
`mro_for_bases` utility or script function.
L329: def merge_seqs(seqs: list[deque[type[Any]]]) -> Iterable[type[Any]]:    Function
`merge_seqs` utility or script function.
L359: def get_attribute_from_bases(tp: type[Any] | tuple[type[Any], ...], name: str) -> Any:
    Function `get_attribute_from_bases` Returns or fetches data.
L394: def get_attribute_from_base_dicts(tp: type[Any], name: str) -> Any:    Function
`get_attribute_from_base_dicts` Returns or fetches data.
L416: class DecoratorInfos:    Class (`DecoratorInfos`) component used by the app (see file
context: None).
L432: def build(    Function `build` Constructs or prepares an object.
L488: def _validate(self) -> None:    Function `_validate` utility or script function.
L499: def update_from_config(self, config_wrapper: ConfigWrapper) -> None:    Function
`update_from_config` utility or script function.
L505: def _decorator_infos_for_class(    Function `_decorator_infos_for_class` utility or
script function.
L550: def inspect_validator(    Function `inspect_validator` utility or script function.
L590: def inspect_field_serializer(serializer: Callable[..., Any], mode: Literal['plain',
'wrap']) -> tuple[bool, bool]:    Function `inspect_field_serializer` utility or script
function.
L629: def inspect_annotated_serializer(serializer: Callable[..., Any], mode: Literal['plain',
'wrap']) -> bool:    Function `inspect_annotated_serializer` utility or script function.
L657: def inspect_model_serializer(serializer: Callable[..., Any], mode: Literal['plain',
'wrap']) -> bool:    Function `inspect_model_serializer` utility or script function.
L685: def _serializer_info_arg(mode: Literal['plain', 'wrap'], n_positional: int) -> bool |
None:    Function `_serializer_info_arg` utility or script function.
L710: def is_instance_method_from_sig(function: AnyDecoratorCallable) -> bool:    Function
`is_instance_method_from_sig` utility or script function.
L729: def ensure_classmethod_based_on_signature(function: AnyDecoratorCallable) -> Any:
Function `ensure_classmethod_based_on_signature` utility or script function.
L745: def _is_classmethod_from_sig(function: AnyDecoratorCallable) -> bool:    Function
`_is_classmethod_from_sig` utility or script function.
L753: def unwrap_wrapped_function(    Function `unwrap_wrapped_function` utility or script
function.
L805: def get_callable_return_type(    Function `get_callable_return_type` Returns or fetches
data.
L839: def count_positional_required_params(sig: Signature) -> int:    Function
`count_positional_required_params` utility or script function.
L861: def ensure_property(f: Any) -> Any:    Function `ensure_property` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_decorators_v1.py

```

L15: class V1OnlyValueValidator(Protocol):    Class (`V1OnlyValueValidator`) component used
by the app (see file context: None).

```

```

L18: def __call__(self, __value: Any) -> Any: ...    Function `__call__` utility or script
function.
L21: class V1ValidatorWithValues(Protocol):    Class (`V1ValidatorWithValues`) component used
by the app (see file context: None).
L24: def __call__(self, __value: Any, values: dict[str, Any]) -> Any: ...    Function
`__call__` utility or script function.
L27: class V1ValidatorWithValuesKwOnly(Protocol):    Class (`V1ValidatorWithValuesKwOnly`)
component used by the app (see file context: None).
L30: def __call__(self, __value: Any, *, values: dict[str, Any]) -> Any: ...    Function
`__call__` utility or script function.
L33: class V1ValidatorWithKwargs(Protocol):    Class (`V1ValidatorWithKwargs`) component used
by the app (see file context: None).
L36: def __call__(self, __value: Any, **kwargs: Any) -> Any: ...    Function `__call__`
utility or script function.
L39: class V1ValidatorWithValuesAndKwargs(Protocol):    Class
(`V1ValidatorWithValuesAndKwargs`) component used by the app (see file context: None).
L42: def __call__(self, __value: Any, values: dict[str, Any], **kwargs: Any) -> Any: ...
Function `__call__` utility or script function.
L50: def can_be_keyword(param: Parameter) -> bool:    Function `can_be_keyword` utility or
script function.
L54: def make_generic_v1_field_validator(validator: V1Validator) ->
core_schema.WithInfoValidatorFunction:    Function `make_generic_v1_field_validator` utility
or script function.
L95: def wrapper1(value: Any, info: core_schema.ValidationInfo) -> Any:    Function `wrapper1`
utility or script function.
L102: def wrapper2(value: Any, _: core_schema.ValidationInfo) -> Any:    Function `wrapper2`
utility or script function.
L113: class V1RootValidatorFunction(Protocol):    Class (`V1RootValidatorFunction`) component
used by the app (see file context: None).
L116: def __call__(self, __values: RootValidatorValues) -> RootValidatorValues: ...
Function `__call__` utility or script function.
L119: class V2CoreBeforeRootValidator(Protocol):    Class (`V2CoreBeforeRootValidator`)
component used by the app (see file context: None).
L122: def __call__(self, __values: RootValidatorValues, __info: core_schema.ValidationInfo)
-> RootValidatorValues: ...    Function `__call__` utility or script function.
L125: class V2CoreAfterRootValidator(Protocol):    Class (`V2CoreAfterRootValidator`)
component used by the app (see file context: None).
L128: def __call__(    Function `__call__` utility or script function.
L133: def make_v1_generic_root_validator(    Function `make_v1_generic_root_validator`
utility or script function.
L147: def _wrapper1(values: RootValidatorValues, _: core_schema.ValidationInfo) ->
RootValidatorValues:    Function `_wrapper1` utility or script function.
L153: def _wrapper2(fields_tuple: RootValidatorFieldsTuple, _: core_schema.ValidationInfo) ->
RootValidatorFieldsTuple:    Function `_wrapper2` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_names

pace_utils.py

```

L30: class NamespacesTuple(NamedTuple):  Class (`NamespacesTuple`) component used by the
app (see file context: None).
L36: def eval_type(tp: type[Any], ns: NamespacesTuple) -> None:  Function `eval_type`
utility or script function.
L48: def get_module_ns_of(obj: Any) -> dict[str, Any]:  Function `get_module_ns_of` Returns
or fetches data.
L66: class LazyLocalNamespace(Mapping[str, Any]):  Class (`LazyLocalNamespace`) component
used by the app (see file context: None).
L86: def __init__(self, *namespaces: MappingNamespace) -> None:  Function `__init__`
utility or script function.
L90: def data(self) -> dict[str, Any]:  Function `data` utility or script function.
L93: def __len__(self) -> int:  Function `__len__` utility or script function.
L96: def __getitem__(self, key: str) -> Any:  Function `__getitem__` utility or script
function.
L99: def __contains__(self, key: object) -> bool:  Object (singleton).
L102: def __iter__(self) -> Iterator[str]:  Function `__iter__` utility or script function.
L106: def ns_for_function(obj: Callable[..., Any], parent_namespace: MappingNamespace | None
= None) -> NamespacesTuple:  Function `ns_for_function` utility or script function.
L143: class NsResolver:  Class (`NsResolver`) component used by the app (see file context:
None).
L170: def func() -> None:  Function `func` utility or script function.
L173: class Model(BaseModel):  Class (`Model`) component used by the app (see file context:
None).
L192: class Sub:  Class (`Sub`) component used by the app (see file context: None).
L195: class Model:  Class (`Model`) component used by the app (see file context: None).
L223: def __init__(  Function `__init__` utility or script function.
L233: def types_namespace(self) -> NamespacesTuple:  Function `types_namespace` utility or
script function.
L284: def push(self, tp: type[Any] | TypeAliasType, /) -> Generator[None]:  Function `push`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_typing_extra.py

```

L47: def is_annotated(tp: Any, /) -> bool:  Function `is_annotated` utility or script
function.
L59: def annotated_type(tp: Any, /) -> Any | None:  Function `annotated_type` utility or
script function.
L64: def unpack_type(tp: Any, /) -> Any | None:  Function `unpack_type` utility or script
function.
L69: def is_hashable(tp: Any, /) -> bool:  Function `is_hashable` utility or script
function.
L82: def is_callable(tp: Any, /) -> bool:  Function `is_callable` utility or script

```



```

function.
L102: def is_classvar_annotation(tp: Any, /) -> bool:    Function `is_classvar_annotation`
utility or script function.
L145: def is_finalvar(tp: Any, /) -> bool:    Function `is_finalvar`    utility or script
function.
L164: def is_none_type(tp: Any, /) -> bool:    Function `is_none_type`    utility or script
function.
L180: def is_namedtuple(tp: Any, /) -> bool:    Function `is_namedtuple`    utility or script
function.
L196: def is_generic_alias(tp: Any, /) -> bool:    Function `is_generic_alias`    utility or
script function.
L215: def parent_frame_namespace(*, parent_depth: int = 2, force: bool = False) -> dict[str,
Any] | None:    Function `parent_frame_namespace`    utility or script function.
L225: def func() -> None:    Function `func`    utility or script function.
L228: class C:    Class (`C`)    component used by the app (see file context: None).
L279: def _type_convert(arg: Any) -> Any:    Function `_type_convert`    utility or script
function.
L297: def safe_get_annotations(obj: Any) -> dict[str, Any]:    Function `safe_get_annotations`
utility or script function.
L314: def get_model_type_hints(    Function `get_model_type_hints`    Returns or fetches data.
L373: def get_cls_type_hints(    Function `get_cls_type_hints`    Returns or fetches data.
L403: def try_eval_type(    Function `try_eval_type`    utility or script function.
L428: def eval_type(    Function `eval_type`    utility or script function.
L449: def eval_type_lenient(    Function `eval_type_lenient`    utility or script function.
L458: def eval_type_backport(    Function `eval_type_backport`    utility or script function.
L504: def _eval_type_backport(    Function `_eval_type_backport`    utility or script function.
L534: def _eval_type(    Function `_eval_type`    utility or script function.
L569: def is_backport_fixable_error(e: TypeError) -> bool:    Function
`is_backport_fixable_error`    utility or script function.
L575: def signature_no_eval(f: Callable[..., Any]) -> Signature:    Function
`signature_no_eval`    utility or script function.
L585: def get_function_type_hints(    Function `get_function_type_hints`    Returns or fetches
data.
L629: def _make_forward_ref(    Function `_make_forward_ref`    utility or script function.
L662: def get_type_hints(    # noqa: C901    Function `get_type_hints`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_discriminated_union.py

```

L19: class MissingDefinitionForUnionRef(Exception):    Class (`MissingDefinitionForUnionRef`)
component used by the app (see file context: None).
L24: def __init__(self, ref: str) -> None:    Function `__init__`    utility or script function.
L29: def set_discriminator_in_metadata(schema: CoreSchema, discriminator: Any) -> None:
Function `set_discriminator_in_metadata`    Sets or updates a value.
L34: def apply_discriminator(    Function `apply_discriminator`    utility or script function.
L73: class _ApplyInferredDiscriminator:    Class (`_ApplyInferredDiscriminator`)    component

```

```

used by the app (see file context: None).
L86: def __init__(self, discriminator: str, definitions: dict[str, core_schema.CoreSchema]):
    Function `__init__` utility or script function.
L140: def apply(self, schema: core_schema.CoreSchema) -> core_schema.CoreSchema:    Function
`apply` utility or script function.
L170: def _apply_to_root(self, schema: core_schema.CoreSchema) -> core_schema.CoreSchema:
Function `_apply_to_root` utility or script function.
L237: def _handle_choice(self, choice: core_schema.CoreSchema) -> None:    Function
`_handle_choice` utility or script function.
L292: def _is_discriminator_shared(self, choice: core_schema.TaggedUnionSchema) -> bool:
Function `_is_discriminator_shared` utility or script function.
L304: def _infer_discriminator_values_for_choice( # noqa C901    Function
`_infer_discriminator_values_for_choice` utility or script function.
L375: def _infer_discriminator_values_for_typed_dict_choice(    Function
`_infer_discriminator_values_for_typed_dict_choice` utility or script function.
L389: def _infer_discriminator_values_for_model_choice(    Function
`_infer_discriminator_values_for_model_choice` utility or script function.
L400: def _infer_discriminator_values_for_dataclass_choice(    Function
`_infer_discriminator_values_for_dataclass_choice` utility or script function.
L413: def _infer_discriminator_values_for_field(self, field: CoreSchemaField, source: str) ->
list[str | int]:    Function `_infer_discriminator_values_for_field` utility or script
function.
L432: def _infer_discriminator_values_for_inner_schema(    Function
`_infer_discriminator_values_for_inner_schema` utility or script function.
L478: def _set_unique_choice_for_values(self, choice: core_schema.CoreSchema, values:
Sequence[str | int]) -> None:    Function `_set_unique_choice_for_values` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_utils.py

```

L74: def can_be_positional(param: Parameter) -> bool:    Function `can_be_positional` utility
or script function.
L78: def func(a, /, b, *, c):    Function `func` utility or script function.
L93: def sequence_like(v: Any) -> bool:    Function `sequence_like` utility or script
function.
L97: def lenient_isinstance(o: Any, class_or_tuple: type[Any] | tuple[type[Any], ...] | None)
-> bool: # pragma: no cover    Function `lenient_isinstance` utility or script function.
L104: def lenient_issubclass(cls: Any, class_or_tuple: Any) -> bool: # pragma: no cover
Function `lenient_issubclass` utility or script function.
L113: def is_model_class(cls: Any) -> TypeGuard[type[BaseModel]]:    Function `is_model_class`
utility or script function.
L122: def is_valid_identifier(identifier: str) -> bool:    Function `is_valid_identifier`
utility or script function.
L133: def deep_update(mapping: dict[KeyType, Any], *updating_mappings: dict[KeyType, Any]) ->
dict[KeyType, Any]:    Function `deep_update` utility or script function.
L144: def update_not_none(mapping: dict[Any, Any], **update: Any) -> None:    Function
`update_not_none` utility or script function.

```

```

L151: def unique_list(    Function `unique_list` utility or script function.
L173: class ValueItems(_repr.Representation):    Class (`ValueItems`) component used by the
app (see file context: None).
L178: def __init__(self, value: Any, items: AbstractSetIntStr | MappingIntStrAny) -> None:
Function `__init__` utility or script function.
L186: def is_excluded(self, item: Any) -> bool:    Function `is_excluded` utility or script
function.
L193: def is_included(self, item: Any) -> bool:    Function `is_included` utility or script
function.
L200: def for_element(self, e: int | str) -> AbstractSetIntStr | MappingIntStrAny | None:
Function `for_element` utility or script function.
L207: def _normalize_indexes(self, items: MappingIntStrAny, v_length: int) -> dict[int | str,
Any]:    Function `_normalize_indexes` utility or script function.
L245: def merge(cls, base: Any, override: Any, intersect: bool = False) -> Any:    Function
`merge` utility or script function.
L283: def _coerce_items(items: AbstractSetIntStr | MappingIntStrAny) -> MappingIntStrAny:
Function `_coerce_items` utility or script function.
L294: def _coerce_value(cls, value: Any) -> Any:    Function `_coerce_value` utility or
script function.
L300: def is_true(v: Any) -> bool:    Function `is_true` utility or script function.
L303: def __repr_args__(self) -> _repr.ReprArgs:    Function `__repr_args__` utility or
script function.
L309: def LazyClassAttribute(name: str, get_value: Callable[[], T]) -> T: ...    Function
`LazyClassAttribute` utility or script function.
L313: class LazyClassAttribute:    Class (`LazyClassAttribute`) component used by the app
(see file context: None).
L319: def __init__(self, name: str, get_value: Callable[[], Any]) -> None:    Function
`__init__` utility or script function.
L324: def value(self) -> Any:    Function `value` utility or script function.
L327: def __get__(self, instance: Any, owner: type[Any]) -> None:    Function `__get__`
utility or script function.
L336: def smart_deepcopy(obj: Obj) -> Obj:    Function `smart_deepcopy` utility or script
function.
L360: def all_identical(left: Iterable[Any], right: Iterable[Any]) -> bool:    Function
`all_identical` utility or script function.
L375: def get_first_not_none(a: Any, b: Any) -> Any:    Function `get_first_not_none` Returns
or fetches data.
L381: class SafeGetItemProxy:    Class (`SafeGetItemProxy`) component used by the app (see
file context: None).
L393: def __getitem__(self, key: str, /) -> Any:    Function `__getitem__` utility or script
function.
L402: def __contains__(self, key: str, /) -> bool:    Function `__contains__` utility or
script function.
L410: class deprecated_instance_property(Generic[_ModelT, _RT]):    Class
(`deprecated_instance_property`) component used by the app (see file context: None).
L418: def __init__(self, fget: Callable[[type[_ModelT]], _RT], /) -> None:    Function
`__init__` utility or script function.
L423: def __get__(self, instance: None, objtype: type[_ModelT]) -> _RT: ...    Function
`__get__` utility or script function.
L430: def __get__(self, instance: _ModelT, objtype: type[_ModelT]) -> _RT: ...    Function
`__get__` utility or script function.

```

```
L431: def __get__(self, instance: _ModelT | None, objtype: type[_ModelT]) -> _RT:    Function
`__get__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_signature.py

```
L18: class _HAS_DEFAULT_FACTORY_CLASS:    Class (`_HAS_DEFAULT_FACTORY_CLASS`)    component used
by the app (see file context: None).
L19: def __repr__(self):    Function `__repr__`    utility or script function.
L26: def _field_name_for_signature(field_name: str, field_info: FieldInfo) -> str:    Function
`_field_name_for_signature`    utility or script function.
L47: def _process_param_defaults(param: Parameter) -> Parameter:    Function
`_process_param_defaults`    utility or script function.
L81: def _generate_signature_parameters( # noqa: C901 (ignore complexity, could use a
refactor)    Function `_generate_signature_parameters`    utility or script function.
L165: def generate_pydantic_signature(    Function `generate_pydantic_signature`    Generates
content (often AI-generated).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_dataclasses.py

```
L40: class PydanticDataclass(StandardDataclass, Protocol):    Class (`PydanticDataclass`)
component used by the app (see file context: None).
L62: def __pydantic_fields_complete__(cls) -> bool: ...    Function
`__pydantic_fields_complete__`    utility or script function.
L65: def set_dataclass_fields(    Function `set_dataclass_fields`    Sets or updates a value.
L85: def complete_dataclass(    Function `complete_dataclass`    utility or script function.
L118: def __init__(__dataclass_self__: PydanticDataclass, *args: Any, **kwargs: Any) -> None:
    Function `__init__`    utility or script function.
L193: def is_stdlib_dataclass(cls: type[Any], /) -> TypeIs[type[StandardDataclass]]:
Function `is_stdlib_dataclass`    utility or script function.
L208: def as_dataclass_field(pydantic_field: FieldInfo) -> dataclasses.Field[Any]:    Function
`as_dataclass_field`    utility or script function.
L230: def patch_base_fields(cls: type[Any]) -> Generator[None]:    Function
`patch_base_fields`    utility or script function.
L249: class A:    Class (`A`)    component used by the app (see file context: None).
L257: class B(A):    Class (`B`)    component used by the app (see file context: None).
L267: class A:    Class (`A`)    component used by the app (see file context: None).
```

Q_base

appwrite/venv/lib/python3.12/site-packages/pydantic/_internal/_generics.py

```

L42: class LimitedDict(dict[KT, VT]):    Class (`LimitedDict`)    component used by the app (see
file context: None).
L43: def __init__(self, size_limit: int = _LIMITED_DICT_SIZE) -> None:    Function `__init__`
utility or script function.
L47: def __setitem__(self, key: KT, value: VT, /) -> None:    Function `__setitem__`    utility
or script function.
L62: class DeepChainMap(ChainMap[KT, VT]):    # type: ignore    Class (`DeepChainMap`)
component used by the app (see file context: None).
L67: class DeepChainMap(ChainMap):    Class (`DeepChainMap`)    component used by the app (see
file context: None).
L74: def clear(self) -> None:    Function `clear`    utility or script function.
L78: def __setitem__(self, key: KT, value: VT) -> None:    Function `__setitem__`    utility or
script function.
L82: def __delitem__(self, key: KT) -> None:    Function `__delitem__`    utility or script
function.
L99: class PydanticGenericMetadata(TypedDict):    Class (`PydanticGenericMetadata`)    component
used by the app (see file context: None).
L105: def create_generic_submodel(    Function `create_generic_submodel`    Creates a resource
or document.
L152: def _get_caller_frame_info(depth: int = 2) -> tuple[str | None, bool]:    Function
`_get_caller_frame_info`    utility or script function.
L177: def iter_contained_typevars(v: Any) -> Iterator[TypeVar]:    Function
`iter_contained_typevars`    utility or script function.
L196: def get_args(v: Any) -> Any:    Function `get_args`    Returns or fetches data.
L203: def get_origin(v: Any) -> Any:    Function `get_origin`    Returns or fetches data.
L210: def get_standard_typevars_map(cls: Any) -> dict[TypeVar, Any] | None:    Function
`get_standard_typevars_map`    Returns or fetches data.
L227: def get_model_typevars_map(cls: type[BaseModel]) -> dict[TypeVar, Any]:    Function
`get_model_typevars_map`    Returns or fetches data.
L245: def replace_types(type_: Any, type_map: Mapping[TypeVar, Any] | None) -> Any:
Function `replace_types`    utility or script function.
L345: def map_generic_model_arguments(cls: type[BaseModel], args: tuple[Any, ...]) ->
dict[TypeVar, Any]:    Function `map_generic_model_arguments`    Maps or converts between
representations.
L353: class Model[T, U, V = int](BaseModel): ...    Class (`Model`)    component used by the app
(see file context: None).
L402: def generic_recursion_self_type(    Function `generic_recursion_self_type`    utility or
script function.
L433: def recursively_defined_type_refs() -> set[str]:    Function
`recursively_defined_type_refs`    utility or script function.
L441: def get_cached_generic_type_early(parent: type[BaseModel], typevar_values: Any) ->
type[BaseModel] | None:    Function `get_cached_generic_type_early`    Returns or fetches data.
L461: def get_cached_generic_type_late(    Function `get_cached_generic_type_late`    Returns or
fetches data.
L471: def set_cached_generic_type(    Function `set_cached_generic_type`    Sets or updates a
value.

```

```

L488: def _union_orderings_key(typevar_values: Any) -> Any:    Function `_union_orderings_key`
        utility or script function.
L509: def _early_cache_key(cls: type[BaseModel], typevar_values: Any) ->
GenericTypesCacheKey:    Function `_early_cache_key`    utility or script function.
L521: def _late_cache_key(origin: type[BaseModel], args: tuple[Any, ...], typevar_values:
Any) -> GenericTypesCacheKey:    Function `_late_cache_key`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_schema_a_gather.py

```

L19: class GatherResult(TypedDict):    Class (`GatherResult`)    component used by the app (see
file context: None).
L34: class MissingDefinitionError(LookupError):    Class (`MissingDefinitionError`)    component
used by the app (see file context: None).
L37: def __init__(self, schema_reference: str, /) -> None:    Function `__init__`    utility or
script function.
L42: class GatherContext:    Class (`GatherContext`)    component used by the app (see file
context: None).
L69: def traverse_metadata(schema: AllSchemas, ctx: GatherContext) -> None:    Function
`traverse_metadata`    utility or script function.
L75: def traverse_definition_ref(def_ref_schema: DefinitionReferenceSchema, ctx:
GatherContext) -> None:    Function `traverse_definition_ref`    utility or script function.
L96: def traverse_schema(schema: AllSchemas, context: GatherContext) -> None:    Function
`traverse_schema`    utility or script function.
L195: def gather_schemas_for_cleaning(schema: CoreSchema, definitions: dict[str, CoreSchema])
-> GatherResult:    Function `gather_schemas_for_cleaning`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_mock_val_ser.py

```

L21: class MockCoreSchema(Mapping[str, Any]):    Class (`MockCoreSchema`)    component used by
the app (see file context: None).
L28: def __init__(    Function `__init__`    utility or script function.
L40: def __getitem__(self, key: str) -> Any:    Function `__getitem__`    utility or script
function.
L43: def __len__(self) -> int:    Function `__len__`    utility or script function.
L46: def __iter__(self) -> Iterator[str]:    Function `__iter__`    utility or script function.
L49: def _get_built(self) -> CoreSchema:    Function `_get_built`    utility or script function.
L60: def rebuild(self) -> CoreSchema | None:    Function `rebuild`    utility or script
function.
L71: class MockValSer(Generic[ValSer]):    Class (`MockValSer`)    component used by the app
(see file context: None).

```

```

L178: def __init__(    Function `__init__`    utility or script function.
L191: def __getattr__(self, item: str) -> None:    Function `__getattr__`    utility or script
function.
L102: def rebuild(self) -> ValSer | None:    Function `rebuild`    utility or script function.
L112: def set_type_adapter_mocks(adapter: TypeAdapter) -> None:    Function
`set_type_adapter_mocks`    Sets or updates a value.
L124: def attempt_rebuild_fn(attr_fn: Callable[[TypeAdapter], T]) -> Callable[[], T | None]:
    Function `attempt_rebuild_fn`    utility or script function.
L125: def handler() -> T | None:    Function `handler`    utility or script function.
L151: def set_model_mocks(cls: type[BaseModel], undefined_name: str = 'all referenced types')
-> None:    Function `set_model_mocks`    Sets or updates a value.
L163: def attempt_rebuild_fn(attr_fn: Callable[[type[BaseModel]], T]) -> Callable[[], T |
None]:    Function `attempt_rebuild_fn`    utility or script function.
L164: def handler() -> T | None:    Function `handler`    utility or script function.
L190: def set_dataclass_mocks(cls: type[PydanticDataclass], undefined_name: str = 'all
referenced types') -> None:    Function `set_dataclass_mocks`    Sets or updates a value.
L204: def attempt_rebuild_fn(attr_fn: Callable[[type[PydanticDataclass]], T]) -> Callable[[],
T | None]:    Function `attempt_rebuild_fn`    utility or script function.
L205: def handler() -> T | None:    Function `handler`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/_internal/_core_u
tils.py**

```

L41: def is_core_schema(    Function `is_core_schema`    utility or script function.
L47: def is_core_schema_field(    Function `is_core_schema_field`    utility or script function.
L53: def is_function_with_inner_schema(    Function `is_function_with_inner_schema`    utility
or script function.
L59: def is_list_like_schema_with_items_schema(    Function
`is_list_like_schema_with_items_schema`    utility or script function.
L65: def get_type_ref(type_: Any, args_override: tuple[type[Any], ...] | None = None) -> str:
    Function `get_type_ref`    Returns or fetches data.
L103: def get_ref(s: core_schema.CoreSchema) -> None | str:    Function `get_ref`    Returns or
fetches data.
L110: def _clean_schema_for_pretty_print(obj: Any, strip_metadata: bool = True) -> Any:    #
pragma: no cover    Function `_clean_schema_for_pretty_print`    utility or script function.
L141: def pretty_print_core_schema(    Function `pretty_print_core_schema`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/plugin/_loader.py

```

L22: def get_plugins() -> Iterable[PydanticPluginProtocol]:    Function `get_plugins`    Returns
or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/plugin/__init__.py

```

L30: class SchemaTypePath(NamedTuple):    Class (`SchemaTypePath`)    component used by the app
(see file context: None).
L40: class PydanticPluginProtocol(Protocol):    Class (`PydanticPluginProtocol`)    component
used by the app (see file context: None).
L43: def new_schema_validator(    Function `new_schema_validator`    utility or script function.
L75: class BaseValidateHandlerProtocol(Protocol):    Class (`BaseValidateHandlerProtocol`)
component used by the app (see file context: None).
L85: def on_success(self, result: Any) -> None:    Function `on_success`    utility or script
function.
L93: def on_error(self, error: ValidationError) -> None:    Function `on_error`    utility or
script function.
L101: def on_exception(self, exception: Exception) -> None:    Function `on_exception`
utility or script function.
L110: class ValidatePythonHandlerProtocol(BaseValidateHandlerProtocol, Protocol):    Class
(`ValidatePythonHandlerProtocol`)    component used by the app (see file context: None).
L113: def on_enter(    Function `on_enter`    utility or script function.
L140: class ValidateJsonHandlerProtocol(BaseValidateHandlerProtocol, Protocol):    Class
(`ValidateJsonHandlerProtocol`)    component used by the app (see file context: None).
L143: def on_enter(    Function `on_enter`    utility or script function.
L171: class ValidateStringsHandlerProtocol(BaseValidateHandlerProtocol, Protocol):    Class
(`ValidateStringsHandlerProtocol`)    component used by the app (see file context: None).
L174: def on_enter(    Function `on_enter`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/plugin/_schema_validator.py

```

L22: def create_schema_validator(    Function `create_schema_validator`    Creates a resource or
document.
L56: class PluggableSchemaValidator:    Class (`PluggableSchemaValidator`)    component used by
the app (see file context: None).
L61: def __init__(    Function `__init__`    utility or script function.
L95: def __getattr__(self, name: str) -> Any:    Function `__getattr__`    utility or script
function.
L99: def build_wrapper(func: Callable[P, R], event_handlers:
list[BaseValidateHandlerProtocol]) -> Callable[P, R]:    Function `build_wrapper`    Constructs
or prepares an object.
L109: def wrapper(*args: P.args, **kwargs: P.kwargs) -> R:    Function `wrapper`    utility or
script function.
L131: def filter_handlers(handler_cls: BaseValidateHandlerProtocol, method_name: str) ->
bool:    Function `filter_handlers`    utility or script function.

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/class_validators.py

```

L21: class _OnlyValueValidatorClsMethod(Protocol):    Class (`_OnlyValueValidatorClsMethod`)
component used by the app (see file context: None).
L22: def __call__(self, __cls: Any, __value: Any) -> Any: ...    Function `__call__` utility
or script function.
L24: class _V1ValidatorWithValuesClsMethod(Protocol):    Class
(`_V1ValidatorWithValuesClsMethod`) component used by the app (see file context: None).
L25: def __call__(self, __cls: Any, __value: Any, values: dict[str, Any]) -> Any: ...
Function `__call__` utility or script function.
L27: class _V1ValidatorWithValuesKwOnlyClsMethod(Protocol):    Class
(`_V1ValidatorWithValuesKwOnlyClsMethod`) component used by the app (see file context:
None).
L28: def __call__(self, __cls: Any, __value: Any, *, values: dict[str, Any]) -> Any: ...
Function `__call__` utility or script function.
L30: class _V1ValidatorWithKwargsClsMethod(Protocol):    Class
(`_V1ValidatorWithKwargsClsMethod`) component used by the app (see file context: None).
L31: def __call__(self, __cls: Any, **kwargs: Any) -> Any: ...    Function `__call__` utility
or script function.
L33: class _V1ValidatorWithValuesAndKwargsClsMethod(Protocol):    Class
(`_V1ValidatorWithValuesAndKwargsClsMethod`) component used by the app (see file context:
None).
L34: def __call__(self, __cls: Any, values: dict[str, Any], **kwargs: Any) -> Any: ...
Function `__call__` utility or script function.
L36: class _V1RootValidatorClsMethod(Protocol):    Class (`_V1RootValidatorClsMethod`)
component used by the app (see file context: None).
L37: def __call__(    Function `__call__` utility or script function.
L82: def validator(    Function `validator` utility or script function.
L138: def dec(f: Any) -> _decorators.PydanticDescriptorProxy[Any]:    Function `dec` utility
or script function.
L159: def root_validator(    Function `root_validator` utility or script function.
L172: def root_validator(    Function `root_validator` utility or script function.
L185: def root_validator(    Function `root_validator` utility or script function.
L204: def root_validator(    Function `root_validator` utility or script function.
L248: def dec(f: Callable[..., Any] | classmethod[Any, Any, Any] | staticmethod[Any, Any]) ->
Any:    Function `dec` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/copy_internals.py

```

L29: def _iter(    Function `_iter` utility or script function.
L98: def _copy_and_set_values(    Function `_copy_and_set_values` utility or script function.

```

```
L124: def _get_value(    Function `_get_value`    utility or script function.
L198: def _calculate_keys(    Function `_calculate_keys`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/json.py

```
L29: def isoformat(o: Union[datetime.date, datetime.time]) -> str:    Function `isoformat`
utility or script function.
L33: def decimal_encoder(dec_value: Decimal) -> Union[int, float]:    Function
`decimal_encoder`    utility or script function.
L86: def pydantic_encoder(obj: Any) -> Any:    Function `pydantic_encoder`    utility or script
function.
L117: def custom_pydantic_encoder(type_encoders: dict[Any, Callable[[type[Any]], Any]], obj:
Any) -> Any:    Function `custom_pydantic_encoder`    utility or script function.
L136: def timedelta_isoformat(td: datetime.timedelta) -> str:    Function
`timedelta_isoformat`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/parse.py

```
L20: class Protocol(str, Enum):    Class (`Protocol`)    component used by the app (see file
context: None).
L26: def load_str_bytes(    Function `load_str_bytes`    Loads data from storage or remote.
L60: def load_file(    Function `load_file`    Loads data from storage or remote.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/config.py

```
L19: class _ConfigMetaclass(type):    Class (`_ConfigMetaclass`)    component used by the app
(see file context: None).
L20: def __getattr__(self, item: str) -> Any:    Function `__getattr__`    utility or script
function.
L30: class BaseConfig(metaclass=_ConfigMetaclass):    Class (`BaseConfig`)    component used by
the app (see file context: None).
L37: def __getattr__(self, item: str) -> Any:    Function `__getattr__`    utility or script
function.
L49: def __init_subclass__(cls, **kwargs: Any) -> None:    Function `__init_subclass__`
```

utility or script function.

L54: class _ExtraMeta(type): Class (`\_ExtraMeta`) component used by the app (see file context: None).

L55: def __getattr__(self, __name: str) -> Any: Function `\_\_getattr\_\_` utility or script function.

L69: class Extra(metaclass=_ExtraMeta): Class (`Extra`) component used by the app (see file context: None).

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/tools.py

L30: def parse_obj_as(type_: type[T], obj: Any, type_name: NameFactory | None = None) -> T: Function `parse\_obj\_as` utility or script function.

L49: def schema_of(Function `schema\_of` utility or script function.

L85: def schema_json_of(Function `schema\_json\_of` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/deprecated/validator.py

L30: def validate_arguments(Function `validate\_arguments` utility or script function.

L36: def validate_arguments(func: 'AnyCallableT') -> 'AnyCallableT': ... Function `validate\_arguments` utility or script function.

L43: def validate_arguments(func: Optional['AnyCallableT'] = None, *, config: 'ConfigType' = None) -> Any: Function `validate\_arguments` utility or script function.

L51: def validate(_func: 'AnyCallable') -> 'AnyCallable': Function `validate` utility or script function.

L55: def wrapper_function(*args: Any, **kwargs: Any) -> Any: Function `wrapper\_function` utility or script function.

L76: class ValidatedFunction: Class (`ValidatedFunction`) component used by the app (see file context: None).

L77: def __init__(self, function: 'AnyCallable', config: 'ConfigType'): Function `\_\_init\_\_` utility or script function.

L145: def init_model_instance(self, *args: Any, **kwargs: Any) -> BaseModel: Function `init\_model\_instance` Initialisation routine.

L149: def call(self, *args: Any, **kwargs: Any) -> Any: Function `call` utility or script function.

L153: def build_values(self, args: tuple[Any, ...], kwargs: dict[str, Any]) -> dict[str, Any]: Function `build\_values` Constructs or prepares an object.

L196: def execute(self, m: BaseModel) -> Any: Function `execute` utility or script function.

L229: def create_model(self, fields: dict[str, Any], takes_args: bool, takes_kwargs: bool, config: 'ConfigType') -> None: Function `create\_model` Creates a resource or document.

```

L243: class DecoratorBaseModel(BaseModel):  Class (`DecoratorBaseModel`) component used by
the app (see file context: None).
L246: def check_args(cls, v: Optional[list[Any]]) -> Optional[list[Any]]:  Function
`check_args` utility or script function.
L254: def check_kwargs(cls, v: Optional[dict[str, Any]]) -> Optional[dict[str, Any]]:
Function `check_kwargs` utility or script function.
L264: def check_positional_only(cls, v: Optional[list[str]]) -> None:  Function
`check_positional_only` utility or script function.
L274: def check_duplicate_kwargs(cls, v: Optional[list[str]]) -> None:  Function
`check_duplicate_kwargs` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/class_validators.py

```

L16: class Validator:  Class (`Validator`) component used by the app (see file context:
None).
L19: def __init__(  Function `__init__` utility or script function.
L52: def validator(  Function `validator` utility or script function.
L92: def dec(f: AnyCallable) -> 'AnyClassMethod':  Function `dec` utility or script
function.
L108: def root_validator(_func: AnyCallable) -> 'AnyClassMethod':  Function `root_validator`
utility or script function.
L113: def root_validator(  Function `root_validator` utility or script function.
L119: def root_validator(  Function `root_validator` utility or script function.
L133: def dec(f: AnyCallable) -> 'AnyClassMethod':  Function `dec` utility or script
function.
L143: def _prepare_validator(function: AnyCallable, allow_reuse: bool) -> 'AnyClassMethod':
Function `_prepare_validator` utility or script function.
L161: class ValidatorGroup:  Class (`ValidatorGroup`) component used by the app (see file
context: None).
L162: def __init__(self, validators: 'ValidatorListDict') -> None:  Function `__init__`
utility or script function.
L166: def get_validators(self, name: str) -> Optional[Dict[str, Validator]]:  Function
`get_validators` Returns or fetches data.
L176: def check_for_unused(self) -> None:  Function `check_for_unused` utility or script
function.
L195: def extract_validators(namespace: Dict[str, Any]) -> Dict[str, List[Validator]]:
Function `extract_validators` utility or script function.
L209: def extract_root_validators(namespace: Dict[str, Any]) -> Tuple[List[AnyCallable],
List[Tuple[bool, AnyCallable]]]:  Function `extract_root_validators` utility or script
function.
L234: def inherit_validators(base_validators: 'ValidatorListDict', validators:
'ValidatorListDict') -> 'ValidatorListDict':  Function `inherit_validators` utility or
script function.
L242: def make_generic_validator validator: AnyCallable) -> 'ValidatorCallable':  Function
`make_generic_validator` utility or script function.

```

```

L281: def prep_validators(v_funcs: Iterable[AnyCallable]) -> 'ValidatorsList':    Function
`prep_validators` utility or script function.
L288: def _generic_validator_cls validator: AnyCallable, sig: 'Signature', args: Set[str]) ->
'ValidatorCallable':    Function `_generic_validator_cls` utility or script function.
L322: def _generic_validator_basic validator: AnyCallable, sig: 'Signature', args: Set[str])
-> 'ValidatorCallable':    Function `_generic_validator_basic` utility or script function.
L355: def gather_all_validators(type_: 'ModelOrDc') -> Dict[str, 'AnyClassMethod']:
Function `gather_all_validators` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/mypy.py

```

L87: def parse_mypy_version(version: str) -> Tuple[int, ...]:    Function `parse_mypy_version`
utility or script function.
L98: def plugin(version: str) -> 'TypingType[Plugin]':    Function `plugin` utility or script
function.
L108: class PydanticPlugin(Plugin):    Class (`PydanticPlugin`) component used by the app
(see file context: None).
L109: def __init__(self, options: Options) -> None:    Function `__init__` utility or script
function.
L114: def get_base_class_hook(self, fullname: str) -> 'Optional[Callable[[ClassDefContext],
None]]':    Function `get_base_class_hook` Returns or fetches data.
L122: def get_metaclass_hook(self, fullname: str) -> Optional[Callable[[ClassDefContext],
None]]:    Function `get_metaclass_hook` Returns or fetches data.
L127: def get_function_hook(self, fullname: str) -> 'Optional[Callable[[FunctionContext],
Type]]':    Function `get_function_hook` Returns or fetches data.
L133: def get_method_hook(self, fullname: str) -> Optional[Callable[[MethodContext], Type]]:
Function `get_method_hook` Returns or fetches data.
L138: def get_class_decorator_hook(self, fullname: str) ->
Optional[Callable[[ClassDefContext], None]]:    Function `get_class_decorator_hook` Returns
or fetches data.
L147: def report_config_data(self, ctx: ReportConfigContext) -> Dict[str, Any]:    Function
`report_config_data` utility or script function.
L154: def _pydantic_model_class_maker_callback(self, ctx: ClassDefContext) -> None:
Function `_pydantic_model_class_maker_callback` utility or script function.
L158: def _pydantic_model_metaclass_marker_callback(self, ctx: ClassDefContext) -> None:
Function `_pydantic_model_metaclass_marker_callback` utility or script function.
L171: def _pydantic_field_callback(self, ctx: FunctionContext) -> 'Type':    Function
`_pydantic_field_callback` utility or script function.
L225: class PydanticPluginConfig:    Class (`PydanticPluginConfig`) component used by the app
(see file context: None).
L239: def __init__(self, options: Options) -> None:    Function `__init__` utility or script
function.
L258: def to_data(self) -> Dict[str, Any]:    Function `to_data` utility or script function.
L262: def from_orm_callback(ctx: MethodContext) -> Type:    Function `from_orm_callback`
utility or script function.
L287: class PydanticModelTransformer:    Class (`PydanticModelTransformer`) component used by
the app (see file context: None).

```

```

L297: def __init__(self, ctx: ClassDefContext, plugin_config: PydanticPluginConfig) -> None:
    Function `__init__` utility or script function.
L301: def transform(self) -> None:    Function `transform` utility or script function.
L326: def adjust_validator_signatures(self) -> None:    Function `adjust_validator_signatures`
    utility or script function.
L344: def collect_config(self) -> 'ModelConfigData':    Function `collect_config` utility or
    script function.
L375: def collect_fields(self, model_config: 'ModelConfigData') ->
    List['PydanticModelField']:    Function `collect_fields` utility or script function.
L459: def add_initializer(self, fields: List['PydanticModelField'], config:
    'ModelConfigData', is_settings: bool) -> None:    Function `add_initializer` utility or
    script function.
L481: def add_construct_method(self, fields: List['PydanticModelField']) -> None:    Function
    `add_construct_method` utility or script function.
L539: def set_frozen(self, fields: List['PydanticModelField'], frozen: bool) -> None:
    Function `set_frozen` Sets or updates a value.
L572: def get_config_update(self, substmt: AssignmentStmt) -> Optional['ModelConfigData']:
    Function `get_config_update` Returns or fetches data.
L601: def get_is_required(cls: ClassDef, stmt: AssignmentStmt, lhs: NameExpr) -> bool:
    Function `get_is_required` Returns or fetches data.
L627: def type_has_implicit_default(type_: Optional[ProperType]) -> bool:    Function
    `type_has_implicit_default` utility or script function.
L644: def get_alias_info(stmt: AssignmentStmt) -> Tuple[Optional[str], bool]:    Function
    `get_alias_info` Returns or fetches data.
L672: def get_field_arguments(    Function `get_field_arguments` Returns or fetches data.
L688: def should_init_forbid_extra(self, fields: List['PydanticModelField'], config:
    'ModelConfigData') -> bool:    Function `should_init_forbid_extra` utility or script
    function.
L703: def is_dynamic_alias_present(fields: List['PydanticModelField'], has_alias_generator:
    bool) -> bool:    Function `is_dynamic_alias_present` utility or script function.
L718: class PydanticModelField:    Class (`PydanticModelField`) component used by the app
    (see file context: None).
L719: def __init__(    Function `__init__` utility or script function.
L729: def to_var(self, info: TypeInfo, use_alias: bool) -> Var:    Function `to_var` utility
    or script function.
L735: def to_argument(self, info: TypeInfo, typed: bool, force_optional: bool, use_alias:
    bool) -> Argument:    Function `to_argument` utility or script function.
L747: def serialize(self) -> JsonDict:    Function `serialize` utility or script function.
L751: def deserialize(cls, info: TypeInfo, data: JsonDict) -> 'PydanticModelField':
    Function `deserialize` utility or script function.
L755: class ModelConfigData:    Class (`ModelConfigData`) component used by the app (see file
    context: None).
L756: def __init__(    Function `__init__` utility or script function.
L772: def set_values_dict(self) -> Dict[str, Any]:    Function `set_values_dict` Sets or
    updates a value.
L775: def update(self, config: Optional['ModelConfigData']) -> None:    Function `update`
    utility or script function.
L781: def setdefault(self, key: str, value: Any) -> None:    Function `setdefault` Sets or
    updates a value.
L794: def error_from_orm(model_name: str, api: CheckerPluginInterface, context: Context) ->
    None:    Function `error_from_orm` utility or script function.

```

```

L798: def error_invalid_config_value(name: str, api: SemanticAnalyzerPluginInterface,
context: Context) -> None:    Function `error_invalid_config_value`    utility or script
function.
L802: def error_required_dynamic_aliases(api: SemanticAnalyzerPluginInterface, context:
Context) -> None:    Function `error_required_dynamic_aliases`    utility or script function.
L806: def error_unexpected_behavior(    Function `error_unexpected_behavior`    utility or
script function.
L816: def error_untyped_fields(api: SemanticAnalyzerPluginInterface, context: Context) ->
None:    Function `error_untyped_fields`    utility or script function.
L820: def error_default_and_default_factory_specified(api: CheckerPluginInterface, context:
Context) -> None:    Function `error_default_and_default_factory_specified`    utility or script
function.
L824: def add_method(    Function `add_method`    utility or script function.
L907: def get_fullname(x: Union[FuncBase, SymbolNode]) -> str:    Function `get_fullname`
Returns or fetches data.
L917: def get_name(x: Union[FuncBase, SymbolNode]) -> str:    Function `get_name`    Returns or
fetches data.
L927: def parse_toml(config_file: str) -> Optional[Dict[str, Any]]:    Function `parse_toml`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/fields.py

```

L69: class UndefinedType:    Class (`UndefinedType`)    component used by the app (see file
context: None).
L70: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L73: def __copy__(self: T) -> T:    Function `__copy__`    utility or script function.
L76: def __reduce__(self) -> str:    Function `__reduce__`    utility or script function.
L79: def __deepcopy__(self: T, _: Any) -> T:    Function `__deepcopy__`    utility or script
function.
L97: class FieldInfo(Representation):    Class (`FieldInfo`)    component used by the app (see
file context: None).
L151: def __init__(self, default: Any = Undefined, **kwargs: Any) -> None:    Function
`__init__`    utility or script function.
L180: def __repr_args__(self) -> 'ReprArgs':    Function `__repr_args__`    utility or script
function.
L189: def get_constraints(self) -> Set[str]:    Function `get_constraints`    Returns or fetches
data.
L197: def update_from_config(self, from_config: Dict[str, Any]) -> None:    Function
`update_from_config`    utility or script function.
L216: def _validate(self) -> None:    Function `_validate`    utility or script function.
L221: def Field(    Function `Field`    utility or script function.
L364: class ModelField(Representation):    Class (`ModelField`)    component used by the app
(see file context: None).
L393: def __init__(    Function `__init__`    utility or script function.
L436: def get_default(self) -> Any:    Function `get_default`    Returns or fetches data.
L440: def _get_field_info(    Function `_get_field_info`    utility or script function.
L484: def infer(    Function `infer`    utility or script function.

```

```

L516: def set_config(self, config: Type['BaseConfig']) -> None:    Function `set_config` Sets
or updates a value.
L534: def alt_alias(self) -> bool:    Function `alt_alias` utility or script function.
L537: def prepare(self) -> None:    Function `prepare` utility or script function.
L557: def _set_default_and_type(self) -> None:    Function `_set_default_and_type` utility or
script function.
L581: def _type_analysis(self) -> None:    # noqa: C901 (ignore complexity)    Function
`_type_analysis` utility or script function.
L758: def prepare_discriminated_union_sub_fields(self) -> None:    Function
`prepare_discriminated_union_sub_fields` utility or script function.
L786: def _create_sub_type(self, type_: Type[Any], name: str, *, for_keys: bool = False) ->
'ModelField':    Function `_create_sub_type` utility or script function.
L814: def populate_validators(self) -> None:    Function `populate_validators` utility or
script function.
L850: def validate(    Function `validate` utility or script function.
L898: def _validate_sequence_like(    # noqa: C901 (ignore complexity)    Function
`_validate_sequence_like` utility or script function.
L955: def _validate_iterable(    Function `_validate_iterable` utility or script function.
L970: def _validate_tuple(    Function `_validate_tuple` utility or script function.
L1000: def _validate_mapping_like(    Function `_validate_mapping_like` utility or script
function.
L1035: def _get_mapping_value(self, original: T, converted: Dict[Any, Any]) -> Union[T,
Dict[Any, Any]]:    Function `_get_mapping_value` utility or script function.
L1053: def _validate_singleton(    Function `_validate_singleton` utility or script function.
L1100: def _validate_discriminated_union(    Function `_validate_discriminated_union` utility
or script function.
L1149: def _apply_validators(    Function `_apply_validators` utility or script function.
L1159: def is_complex(self) -> bool:    Function `is_complex` utility or script function.
L1171: def _type_display(self) -> PyObjectStr:    Function `_type_display` utility or script
function.
L1190: def __repr_args__(self) -> 'ReprArgs':    Function `__repr_args__` utility or script
function.
L1204: class ModelPrivateAttr(Representation):    Class (`ModelPrivateAttr`) component used
by the app (see file context: None).
L1207: def __init__(self, default: Any = Undefined, *, default_factory:
Optional[NoArgAnyCallable] = None) -> None:    Function `__init__` utility or script
function.
L1211: def get_default(self) -> Any:    Function `get_default` Returns or fetches data.
L1214: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L1221: def PrivateAttr(    Function `PrivateAttr` utility or script function.
L1246: class DeferredType:    Class (`DeferredType`) component used by the app (see file
context: None).
L1252: def is_finalvar_with_default_val(type_: Type[Any], val: Any) -> bool:    Function
`is_finalvar_with_default_val` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/annotated_typ

es.py

```

L13: def is_legacy_typeddict(typeddict_cls: Type['TypedDict']) -> bool: # type:
ignore[valid-type]    Function `is_legacy_typeddict` utility or script function.
L18: def is_legacy_typeddict(_: Any) -> Any:    Function `is_legacy_typeddict` utility or
script function.
L22: def create_model_from_typeddict(    Function `create_model_from_typeddict` Creates a
resource or document.
L58: def create_model_from_namedtuple(namedtuple_cls: Type['NamedTuple'], **kwargs: Any) ->
Type['BaseModel']:    Function `create_model_from_namedtuple` Creates a resource or document.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/env_settings.py**

```

L19: class SettingsError(ValueError):    Class (`SettingsError`) component used by the app
(see file context: None).
L23: class BaseSettings(BaseModel):    Class (`BaseSettings`) component used by the app (see
file context: None).
L31: def __init__(    Function `__init__` utility or script function.
L50: def _build_values(    Function `_build_values` utility or script function.
L82: class Config(BaseConfig):    Class (`Config`) component used by the app (see file
context: None).
L94: def prepare_field(cls, field: ModelField) -> None:    Function `prepare_field` utility
or script function.
L122: def customise_sources(    Function `customise_sources` utility or script function.
L131: def parse_env_var(cls, field_name: str, raw_val: str) -> Any:    Function
`parse_env_var` utility or script function.
L138: class InitSettingsSource:    Class (`InitSettingsSource`) component used by the app
(see file context: None).
L141: def __init__(self, init_kwargs: Dict[str, Any]):    Function `__init__` utility or
script function.
L144: def __call__(self, settings: BaseSettings) -> Dict[str, Any]:    Function `__call__`
utility or script function.
L147: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L151: class EnvSettingsSource:    Class (`EnvSettingsSource`) component used by the app (see
file context: None).
L154: def __init__(    Function `__init__` utility or script function.
L166: def __call__(self, settings: BaseSettings) -> Dict[str, Any]: # noqa C901    Function
`__call__` utility or script function.
L213: def _read_env_files(self, case_sensitive: bool) -> Dict[str, Optional[str]]:    Function
`_read_env_files` utility or script function.
L231: def field_is_complex(self, field: ModelField) -> Tuple[bool, bool]:    Function
`field_is_complex` utility or script function.
L247: def explode_env_vars(self, field: ModelField, env_vars: Mapping[str, Optional[str]]) ->
Dict[str, Any]:    Function `explode_env_vars` utility or script function.

```

```

L268: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L275: class SecretsSettingsSource:    Class (`SecretsSettingsSource`) component used by the
app (see file context: None).
L278: def __init__(self, secrets_dir: Optional[StrPath]):    Function `__init__` utility or
script function.
L281: def __call__(self, settings: BaseSettings) -> Dict[str, Any]:    Function `__call__`
utility or script function.
L322: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L326: def read_env_file(    Function `read_env_file` utility or script function.
L341: def find_case_path(dir_path: Path, file_name: str, case_sensitive: bool) ->
Optional[Path]:    Function `find_case_path` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/networks.py

```

L44: class Parts(TypedDict, total=False):    Class (`Parts`) component used by the app (see
file context: None).
L56: class HostParts(TypedDict, total=False):    Class (`HostParts`) component used by the
app (see file context: None).
L66: class Parts(dict):    Class (`Parts`) component used by the app (see file context:
None).
L113: def url_regex() -> Pattern[str]:    Function `url_regex` utility or script function.
L123: def multi_host_url_regex() -> Pattern[str]:    Function `multi_host_url_regex` utility
or script function.
L141: def ascii_domain_regex() -> Pattern[str]:    Function `ascii_domain_regex` utility or
script function.
L152: def int_domain_regex() -> Pattern[str]:    Function `int_domain_regex` utility or
script function.
L161: def host_regex() -> Pattern[str]:    Function `host_regex` utility or script function.
L171: class AnyUrl(str):    Class (`AnyUrl`) component used by the app (see file context:
None).
L184: def __new__(cls, url: Optional[str], **kwargs) -> object:    Object (singleton).
L187: def __init__(    Function `__init__` utility or script function.
L215: def build(    Function `build` Constructs or prepares an object.
L259: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__` utility or script function.
L263: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L267: def validate(cls, value: Any, field: 'ModelField', config: 'BaseConfig') -> 'AnyUrl':
Function `validate` utility or script function.
L289: def _build_url(cls, m: Match[str], url: str, parts: 'Parts') -> 'AnyUrl':    Function
`_build_url` utility or script function.
L311: def _match_url(url: str) -> Optional[Match[str]]:    Function `_match_url` utility or
script function.
L315: def _validate_port(port: Optional[str]) -> None:    Function `_validate_port` utility
or script function.
L320: def validate_parts(cls, parts: 'Parts', validate_port: bool = True) -> 'Parts':
Function `validate_parts` utility or script function.

```

```

L342: def validate_host(cls, parts: 'Parts') -> Tuple[str, Optional[str], str, bool]:
Function `validate_host` utility or script function.
L384: def get_default_parts(parts: 'Parts') -> 'Parts': Function `get_default_parts`
Returns or fetches data.
L388: def apply_default_parts(cls, parts: 'Parts') -> 'Parts': Function
`apply_default_parts` utility or script function.
L394: def __repr__(self) -> str: Function `__repr__` utility or script function.
L399: class AnyHttpUrl(AnyUrl): Class (`AnyHttpUrl`) component used by the app (see file
context: None).
L405: class HttpUrl(AnyHttpUrl): Class (`HttpUrl`) component used by the app (see file
context: None).
L412: def get_default_parts(parts: 'Parts') -> 'Parts': Function `get_default_parts`
Returns or fetches data.
L416: class FileUrl(AnyUrl): Class (`FileUrl`) component used by the app (see file
context: None).
L423: class MultiHostDsn(AnyUrl): Class (`MultiHostDsn`) component used by the app (see
file context: None).
L426: def __init__(self, *args: Any, hosts: Optional[List['HostParts']] = None, **kwargs:
Any): Function `__init__` utility or script function.
L431: def _match_url(url: str) -> Optional[Match[str]]: Function `_match_url` utility or
script function.
L435: def validate_parts(cls, parts: 'Parts', validate_port: bool = True) -> 'Parts':
Function `validate_parts` utility or script function.
L439: def _build_url(cls, m: Match[str], url: str, parts: 'Parts') -> 'MultiHostDsn':
Function `_build_url` utility or script function.
L487: class PostgresDsn(MultiHostDsn): Class (`PostgresDsn`) component used by the app
(see file context: None).
L504: class CockroachDsn(AnyUrl): Class (`CockroachDsn`) component used by the app (see
file context: None).
L513: class AmqpDsn(AnyUrl): Class (`AmqpDsn`) component used by the app (see file
context: None).
L518: class RedisDsn(AnyUrl): Class (`RedisDsn`) component used by the app (see file
context: None).
L524: def get_default_parts(parts: 'Parts') -> 'Parts': Function `get_default_parts`
Returns or fetches data.
L532: class MongoDsn(AnyUrl): Class (`MongoDsn`) component used by the app (see file
context: None).
L537: def get_default_parts(parts: 'Parts') -> 'Parts': Function `get_default_parts`
Returns or fetches data.
L543: class KafkaDsn(AnyUrl): Class (`KafkaDsn`) component used by the app (see file
context: None).
L547: def get_default_parts(parts: 'Parts') -> 'Parts': Function `get_default_parts`
Returns or fetches data.
L554: def stricturl( Function `stricturl` utility or script function.
L575: def import_email_validator() -> None: Function `import_email_validator` utility or
script function.
L583: class EmailStr(str): Class (`EmailStr`) component used by the app (see file context:
None).
L585: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None: Function
`__modify_schema__` utility or script function.
L589: def __get_validators__(cls) -> 'CallableGenerator': Function `__get_validators__`

```

```

utility or script function.
L597: def validate(cls, value: Union[str]) -> str:    Function `validate`    utility or script
function.
L601: class NameEmail(Representation):    Class (`NameEmail`)    component used by the app (see
file context: None).
L604: def __init__(self, name: str, email: str):    Function `__init__`    utility or script
function.
L608: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L612: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L616: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L622: def validate(cls, value: Any) -> 'NameEmail':    Function `validate`    utility or script
function.
L628: def __str__(self) -> str:    Function `__str__`    utility or script function.
L632: class IPvAnyAddress(_BaseAddress):    Class (`IPvAnyAddress`)    component used by the app
(see file context: None).
L636: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L640: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L644: def validate(cls, value: Union[str, bytes, int]) -> Union[IPv4Address, IPv6Address]:
Function `validate`    utility or script function.
L656: class IPvAnyInterface(_BaseAddress):    Class (`IPvAnyInterface`)    component used by the
app (see file context: None).
L660: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L664: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L668: def validate(cls, value: NetworkType) -> Union[IPv4Interface, IPv6Interface]:
Function `validate`    utility or script function.
L680: class IPvAnyNetwork(_BaseNetwork):    # type: ignore    Class (`IPvAnyNetwork`)    component
used by the app (see file context: None).
L682: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L686: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L690: def validate(cls, value: NetworkType) -> Union[IPv4Network, IPv6Network]:    Function
`validate`    utility or script function.
L711: def validate_email(value: Union[str]) -> Tuple[str, str]:    Function `validate_email`
utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/datetime_pars
e.py**

```

L66: def get_numeric(value: StrBytesIntFloat, native_expected_type: str) -> Union[None, int,

```

```

float]:    Function `get_numeric` Returns or fetches data.
L77: def from_unix_seconds(seconds: Union[int, float]) -> datetime:    Function
`from_unix_seconds` utility or script function.
L89: def _parse_timezone(value: Optional[str], error: Type[Exception]) -> Union[None, int,
timezone]:    Function `_parse_timezone` utility or script function.
L105: def parse_date(value: Union[date, StrBytesIntFloat]) -> date:    Function `parse_date`
utility or script function.
L137: def parse_time(value: Union[time, StrBytesIntFloat]) -> time:    Function `parse_time`
utility or script function.
L175: def parse_datetime(value: Union[datetime, StrBytesIntFloat]) -> datetime:    Function
`parse_datetime` utility or script function.
L213: def parse_duration(value: StrBytesIntFloat) -> timedelta:    Function `parse_duration`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/typing.py

```

L60: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
Function `evaluate_forwardref` utility or script function.
L65: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
Function `evaluate_forwardref` utility or script function.
L74: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
Function `evaluate_forwardref` utility or script function.
L81: def evaluate_forwardref(type_: ForwardRef, globalns: Any, localns: Any) -> Any:
Function `evaluate_forwardref` utility or script function.
L101: def get_all_type_hints(obj: Any, globalns: Any = None, localns: Any = None) -> Any:
Function `get_all_type_hints` Returns or fetches data.
L126: def get_origin(tp: Type[Any]) -> Optional[Type[Any]]:    Function `get_origin` Returns
or fetches data.
L135: def get_origin(tp: Type[Any]) -> Optional[Type[Any]]:    Function `get_origin` Returns
or fetches data.
L150: def get_args(tp: Type[Any]) -> Tuple[Any, ...]:    Function `get_args` Returns or
fetches data.
L168: def _generic_get_args(tp: Type[Any]) -> Tuple[Any, ...]:    Function `_generic_get_args`
utility or script function.
L188: def get_args(tp: Type[Any]) -> Tuple[Any, ...]:    Function `get_args` Returns or
fetches data.
L207: def convert_generics(tp: Type[Any]) -> Type[Any]:    Function `convert_generics`
utility or script function.
L218: def convert_generics(tp: Type[Any]) -> Type[Any]:    Function `convert_generics`
utility or script function.
L261: def is_union(tp: Optional[Type[Any]]) -> bool:    Function `is_union` utility or script
function.
L270: def is_union(tp: Optional[Type[Any]]) -> bool:    Function `is_union` utility or script
function.
L357: def is_none_type(type_: Any) -> bool:    Function `is_none_type` utility or script
function.
L362: def is_none_type(type_: Any) -> bool:    Function `is_none_type` utility or script

```

```

function.
L375: def is_none_type(type_: Any) -> bool:    Function `is_none_type` utility or script
function.
L379: def display_as_type(v: Type[Any]) -> str:    Function `display_as_type` utility or
script function.
L397: def resolve_annotations(raw_annotations: Dict[str, Type[Any]], module_name:
Optional[str]) -> Dict[str, Type[Any]]:    Function `resolve_annotations` utility or script
function.
L432: def is_callable_type(type_: Type[Any]) -> bool:    Function `is_callable_type` utility
or script function.
L436: def is_literal_type(type_: Type[Any]) -> bool:    Function `is_literal_type` utility or
script function.
L440: def literal_values(type_: Type[Any]) -> Tuple[Any, ...]:    Function `literal_values`
utility or script function.
L444: def all_literal_values(type_: Type[Any]) -> Tuple[Any, ...]:    Function
`all_literal_values` utility or script function.
L457: def is_namedtuple(type_: Type[Any]) -> bool:    Function `is_namedtuple` utility or
script function.
L467: def is_typeddict(type_: Type[Any]) -> bool:    Function `is_typeddict` utility or
script function.
L477: def _check_typeddict_special(type_: Any) -> bool:    Function `_check_typeddict_special`
utility or script function.
L481: def is_typeddict_special(type_: Any) -> bool:    Function `is_typeddict_special`
utility or script function.
L491: def is_new_type(type_: Type[Any]) -> bool:    Function `is_new_type` utility or script
function.
L498: def new_type_supertype(type_: Type[Any]) -> Type[Any]:    Function `new_type_supertype`
utility or script function.
L504: def _check_classvar(v: Optional[Type[Any]]) -> bool:    Function `_check_classvar`
utility or script function.
L511: def _check_finalvar(v: Optional[Type[Any]]) -> bool:    Function `_check_finalvar`
utility or script function.
L521: def is_classvar(ann_type: Type[Any]) -> bool:    Function `is_classvar` utility or
script function.
L533: def is_finalvar(ann_type: Type[Any]) -> bool:    Function `is_finalvar` utility or
script function.
L537: def update_field_forward_refs(field: 'ModelField', globalns: Any, localns: Any) ->
None:    Function `update_field_forward_refs` utility or script function.
L559: def update_model_forward_refs(    Function `update_model_forward_refs` utility or
script function.
L598: def get_class(type_: Type[Any]) -> Union[None, bool, Type[Any]]:    Function `get_class`
Returns or fetches data.
L616: def get_sub_types(tp: Any) -> List[Any]:    Function `get_sub_types` Returns or fetches
data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/json.py

```

L19: def isoformat(o: Union[datetime.date, datetime.time]) -> str:    Function `isoformat`
utility or script function.
L23: def decimal_encoder(dec_value: Decimal) -> Union[int, float]:    Function
`decimal_encoder` utility or script function.
L72: def pydantic_encoder(obj: Any) -> Any:    Function `pydantic_encoder` utility or script
function.
L93: def custom_pydantic_encoder(type_encoders: Dict[Any, Callable[[Type[Any]], Any]], obj:
Any) -> Any:    Function `custom_pydantic_encoder` utility or script function.
L106: def timedelta_isoformat(td: datetime.timedelta) -> str:    Function
`timedelta_isoformat` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/parse.py

```

L10: class Protocol(str, Enum):    Class (`Protocol`) component used by the app (see file
context: None).
L15: def load_str_bytes(    Function `load_str_bytes` Loads data from storage or remote.
L47: def load_file(    Function `load_file` Loads data from storage or remote.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/schema.py

```

L96: def _apply_modify_schema(    Function `_apply_modify_schema` utility or script function.
L109: def schema(    Function `schema` utility or script function.
L162: def model_schema(    Function `model_schema` utility or script function.
L200: def get_field_info_schema(field: ModelField, schema_overrides: bool = False) ->
Tuple[Dict[str, Any], bool]:    Function `get_field_info_schema` Returns or fetches data.
L222: def field_schema(    Function `field_schema` utility or script function.
L289: def get_field_schema_validations(field: ModelField) -> Dict[str, Any]:    Function
`get_field_schema_validations` Returns or fetches data.
L322: def get_model_name_map(unique_models: TypeModelSet) -> Dict[TypeModelOrEnum, str]:
Function `get_model_name_map` Returns or fetches data.
L349: def get_flat_models_from_model(model: Type['BaseModel'], known_models:
Optional[TypeModelSet] = None) -> TypeModelSet:    Function `get_flat_models_from_model`
Returns or fetches data.
L369: def get_flat_models_from_field(field: ModelField, known_models: TypeModelSet) ->
TypeModelSet:    Function `get_flat_models_from_field` Returns or fetches data.
L398: def get_flat_models_from_fields(fields: Sequence[ModelField], known_models:
TypeModelSet) -> TypeModelSet:    Function `get_flat_models_from_fields` Returns or fetches
data.
L416: def get_flat_models_from_models(models: Sequence[Type['BaseModel']]) -> TypeModelSet:
Function `get_flat_models_from_models` Returns or fetches data.
L428: def get_long_model_name(model: TypeModelOrEnum) -> str:    Function
`get_long_model_name` Returns or fetches data.
L432: def field_type_schema(    Function `field_type_schema` utility or script function.

```

```

L551: def model_process_schema(    Function `model_process_schema`    utility or script
function.
L601: def model_type_schema(    Function `model_type_schema`    utility or script function.
L655: def enum_process_schema(enum: Type[Enum], *, field: Optional[ModelField] = None) ->
Dict[str, Any]:    Function `enum_process_schema`    utility or script function.
L681: def field_singleton_sub_fields_schema(    Function `field_singleton_sub_fields_schema`
utility or script function.
L804: def add_field_type_to_schema(field_type: Any, schema_: Dict[str, Any]) -> None:
Function `add_field_type_to_schema`    utility or script function.
L818: def get_schema_ref(name: str, ref_prefix: Optional[str], ref_template: str,
schema_overrides: bool) -> Dict[str, Any]:    Function `get_schema_ref`    Returns or fetches
data.
L826: def field_singleton_schema(    # noqa: C901 (ignore complexity)    Function
`field_singleton_schema`    utility or script function.
L954: def multitypes_literal_field_for_schema(values: Tuple[Any, ...], field: ModelField) ->
ModelField:    Function `multitypes_literal_field_for_schema`    utility or script function.
L976: def encode_default(dft: Any) -> Any:    Function `encode_default`    utility or script
function.
L1001: def get_annotation_from_field_info(    Function `get_annotation_from_field_info`
Returns or fetches data.
L1030: def get_annotation_with_constraints(annotation: Any, field_info: FieldInfo) ->
Tuple[Type[Any], Set[str]]:    # noqa: C901    Function `get_annotation_with_constraints`
Returns or fetches data.
L1040: def go(type_: Any) -> Type[Any]:    Function `go`    utility or script function.
L1093: def constraint_func(**kw: Any) -> Type[Any]:    # noqa: F811    Function
`constraint_func`    utility or script function.
L1100: def constraint_func(**kw: Any) -> Type[Any]:    Function `constraint_func`    utility or
script function.
L1109: def constraint_func(**kw: Any) -> Type[Any]:    Function `constraint_func`    utility or
script function.
L1150: def normalize_name(name: str) -> str:    Function `normalize_name`    utility or script
function.
L1157: class SkipField(Exception):    Class (`SkipField`)    component used by the app (see file
context: None).
L1162: def __init__(self, message: str) -> None:    Function `__init__`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/dataclasses.py

```

L17: class M:    Class (`M`)    component used by the app (see file context: None).
L66: class Dataclass:    Class (`Dataclass`)    component used by the app (see file context:
None).
L80: def __init__(self, *args: object, **kwargs: object) -> None:    Object (singleton).
L84: def __get_validators__(cls: Type['Dataclass']) -> 'CallableGenerator':    Function
`__get_validators__`    utility or script function.
L88: def __validate__(cls: Type['DataclassT'], v: Any) -> 'DataclassT':    Function
`__validate__`    utility or script function.

```



```

L106: def dataclass(    Function `dataclass`    utility or script function.
L123: def dataclass(    Function `dataclass`    utility or script function.
L143: def dataclass(    Function `dataclass`    utility or script function.
L159: def dataclass(    Function `dataclass`    utility or script function.
L176: def dataclass(    Function `dataclass`    utility or script function.
L198: def wrap(cls: Type[Any]) -> 'DataclassClassOrWrapper':    Function `wrap`    utility or
script function.
L242: def set_validation(cls: Type['DataclassT'], value: bool) ->
Generator[Type['DataclassT'], None, None]:    Function `set_validation`    Sets or updates a
value.
L251: class DataclassProxy:    Class (`DataclassProxy`)    component used by the app (see file
context: None).
L254: def __init__(self, dc_cls: Type['Dataclass']) -> None:    Function `__init__`    utility
or script function.
L257: def __call__(self, *args: Any, **kwargs: Any) -> Any:    Function `__call__`    utility or
script function.
L261: def __getattr__(self, name: str) -> Any:    Function `__getattr__`    utility or script
function.
L264: def __setattr__(self, __name: str, __value: Any) -> None:    Function `__setattr__`
utility or script function.
L267: def __instancecheck__(self, instance: Any) -> bool:    Function `__instancecheck__`
utility or script function.
L270: def __copy__(self) -> 'DataclassProxy':    Function `__copy__`    utility or script
function.
L273: def __deepcopy__(self, memo: Any) -> 'DataclassProxy':    Function `__deepcopy__`
utility or script function.
L277: def _add_pydantic_validation_attributes( # noqa: C901 (ignore complexity)    Function
`_add_pydantic_validation_attributes`    utility or script function.
L291: def handle_extra_init(self: 'Dataclass', *args: Any, **kwargs: Any) -> None:    Function
`handle_extra_init`    utility or script function.
L310: def new_post_init(self: 'Dataclass', *args: Any, **kwargs: Any) -> None:    Function
`new_post_init`    utility or script function.
L328: def new_init(self: 'Dataclass', *args: Any, **kwargs: Any) -> None:    Function
`new_init`    utility or script function.
L363: def _get_validators(cls: 'DataclassClassOrWrapper') -> 'CallableGenerator':    Function
`_get_validators`    utility or script function.
L367: def _validate_dataclass(cls: Type['DataclassT'], v: Any) -> 'DataclassT':    Function
`_validate_dataclass`    utility or script function.
L380: def create_pydantic_model_from_dataclass(    Function
`create_pydantic_model_from_dataclass`    Creates a resource or document.
L421: def _is_field_cached_property(obj: 'Dataclass', k: str) -> bool:    Function
`_is_field_cached_property`    utility or script function.
L426: def _is_field_cached_property(obj: 'Dataclass', k: str) -> bool:    Function
`_is_field_cached_property`    utility or script function.
L430: def _dataclass_validate_values(self: 'Dataclass') -> None:    Function
`_dataclass_validate_values`    utility or script function.
L452: def _dataclass_validate_assignment_setattr(self: 'Dataclass', name: str, value: Any) ->
None:    Function `_dataclass_validate_assignment_setattr`    utility or script function.
L465: def is_builtin_dataclass(_cls: Type[Any]) -> bool:    Function `is_builtin_dataclass`
utility or script function.
L477: class A:    Class (`A`)    component used by the app (see file context: None).

```

```
L481: class B(A):    Class (`B`) component used by the app (see file context: None).
L494: def make_dataclass_validator(dc_cls: Type['Dataclass'], config: Type[BaseConfig]) ->
'CallableGenerator':    Function `make_dataclass_validator` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/validators.py

```
L60: def str_validator(v: Any) -> Union[str]:    Function `str_validator` utility or script
function.
L75: def strict_str_validator(v: Any) -> Union[str]:    Function `strict_str_validator`
utility or script function.
L81: def bytes_validator(v: Any) -> Union[bytes]:    Function `bytes_validator` utility or
script function.
L94: def strict_bytes_validator(v: Any) -> Union[bytes]:    Function `strict_bytes_validator`
utility or script function.
L107: def bool_validator(v: Any) -> bool:    Function `bool_validator` utility or script
function.
L128: def int_validator(v: Any) -> int:    Function `int_validator` utility or script
function.
L147: def strict_int_validator(v: Any) -> int:    Function `strict_int_validator` utility or
script function.
L153: def float_validator(v: Any) -> float:    Function `float_validator` utility or script
function.
L163: def strict_float_validator(v: Any) -> float:    Function `strict_float_validator`
utility or script function.
L169: def float_finite_validator(v: 'Number', field: 'ModelField', config: 'BaseConfig') ->
'Number':    Function `float_finite_validator` utility or script function.
L179: def number_multiple_validator(v: 'Number', field: 'ModelField') -> 'Number':    Function
`number_multiple_validator` utility or script function.
L188: def number_size_validator(v: 'Number', field: 'ModelField') -> 'Number':    Function
`number_size_validator` utility or script function.
L203: def constant_validator(v: 'Any', field: 'ModelField') -> 'Any':    Function
`constant_validator` utility or script function.
L216: def anystr_length_validator(v: 'StrBytes', config: 'BaseConfig') -> 'StrBytes':
Function `anystr_length_validator` utility or script function.
L230: def anystr_strip_whitespace(v: 'StrBytes') -> 'StrBytes':    Function
`anystr_strip_whitespace` utility or script function.
L234: def anystr_upper(v: 'StrBytes') -> 'StrBytes':    Function `anystr_upper` utility or
script function.
L238: def anystr_lower(v: 'StrBytes') -> 'StrBytes':    Function `anystr_lower` utility or
script function.
L242: def ordered_dict_validator(v: Any) -> 'AnyOrderedDict':    Function
`ordered_dict_validator` utility or script function.
L252: def dict_validator(v: Any) -> Dict[Any, Any]:    Function `dict_validator` utility or
script function.
L262: def list_validator(v: Any) -> List[Any]:    Function `list_validator` utility or script
function.
L271: def tuple_validator(v: Any) -> Tuple[Any, ...]:    Function `tuple_validator` utility
```

or script function.

L280: def set_validator(v: Any) -> Set[Any]: Function `set\_validator` Sets or updates a value.

L289: def frozenset_validator(v: Any) -> FrozenSet[Any]: Function `frozenset\_validator` utility or script function.

L298: def deque_validator(v: Any) -> Deque[Any]: Function `deque\_validator` utility or script function.

L307: def enum_member_validator(v: Any, field: 'ModelField', config: 'BaseConfig') -> Enum: Function `enum\_member\_validator` utility or script function.

L316: def uuid_validator(v: Any, field: 'ModelField') -> UUID: Function `uuid\_validator` utility or script function.

L340: def decimal_validator(v: Any) -> Decimal: Function `decimal\_validator` utility or script function.

L359: def hashable_validator(v: Any) -> Hashable: Function `hashable\_validator` utility or script function.

L366: def ip_v4_address_validator(v: Any) -> IPv4Address: Function `ip\_v4\_address\_validator` utility or script function.

L376: def ip_v6_address_validator(v: Any) -> IPv6Address: Function `ip\_v6\_address\_validator` utility or script function.

L386: def ip_v4_network_validator(v: Any) -> IPv4Network: Function `ip\_v4\_network\_validator` utility or script function.

L402: def ip_v6_network_validator(v: Any) -> IPv6Network: Function `ip\_v6\_network\_validator` utility or script function.

L418: def ip_v4_interface_validator(v: Any) -> IPv4Interface: Function `ip\_v4\_interface\_validator` utility or script function.

L428: def ip_v6_interface_validator(v: Any) -> IPv6Interface: Function `ip\_v6\_interface\_validator` utility or script function.

L438: def path_validator(v: Any) -> Path: Function `path\_validator` utility or script function.

L448: def path_exists_validator(v: Any) -> Path: Function `path\_exists\_validator` utility or script function.

L455: def callable_validator(v: Any) -> AnyCallable: Function `callable\_validator` utility or script function.

L467: def enum_validator(v: Any) -> Enum: Function `enum\_validator` utility or script function.

L474: def int_enum_validator(v: Any) -> IntEnum: Function `int\_enum\_validator` utility or script function.

L481: def make_literal_validator(type_: Any) -> Callable[[Any], Any]: Function `make\_literal\_validator` utility or script function.

L489: def literal_validator(v: Any) -> Any: Function `literal\_validator` utility or script function.

L498: def constr_length_validator(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig') -> 'StrBytes': Function `constr\_length\_validator` utility or script function.

L512: def constr_strip_whitespace(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig') -> 'StrBytes': Function `constr\_strip\_whitespace` utility or script function.

L520: def constr_upper(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig') -> 'StrBytes': Function `constr\_upper` utility or script function.

L528: def constr_lower(v: 'StrBytes', field: 'ModelField', config: 'BaseConfig') -> 'StrBytes': Function `constr\_lower` utility or script function.

L535: def validate_json(v: Any, config: 'BaseConfig') -> Any: Function `validate\_json` utility or script function.

```

L550: def make_arbitrary_type_validator(type_: Type[T]) -> Callable[[T], T]:    Function
`make_arbitrary_type_validator` utility or script function.
L551: def arbitrary_type_validator(v: Any) -> T:    Function `arbitrary_type_validator`
utility or script function.
L559: def make_class_validator(type_: Type[T]) -> Callable[[Any], Type[T]]:    Function
`make_class_validator` utility or script function.
L560: def class_validator(v: Any) -> Type[T]:    Function `class_validator` utility or script
function.
L568: def any_class_validator(v: Any) -> Type[T]:    Function `any_class_validator` utility
or script function.
L574: def none_validator(v: Any) -> 'Literal[None]':    Function `none_validator` utility or
script function.
L580: def pattern_validator(v: Any) -> Pattern[str]:    Function `pattern_validator` utility
or script function.
L595: def make_namedtuple_validator(    Function `make_namedtuple_validator` utility or
script function.
L607: def namedtuple_validator(values: Tuple[Any, ...]) -> NamedTupleT:    Function
`namedtuple_validator` utility or script function.
L620: def make_typeddict_validator(    Function `make_typeddict_validator` utility or script
function.
L632: def typeddict_validator(values: 'TypedDict') -> Dict[str, Any]:    # type:
ignore[valid-type]    Function `typeddict_validator` utility or script function.
L638: class IfConfig:    Class (`IfConfig`) component used by the app (see file context:
None).
L639: def __init__(self, validator: AnyCallable, *config_attr_names: str, ignored_value: Any
= False) -> None:    Function `__init__` utility or script function.
L644: def check(self, config: Type['BaseConfig']) -> bool:    Function `check` utility or
script function.
L699: def find_validators(    # noqa: C901 (ignore complexity)    Function `find_validators`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/config.py

```

L19: class SchemaExtraCallable(Protocol):    Class (`SchemaExtraCallable`) component used by
the app (see file context: None).
L21: def __call__(self, schema: Dict[str, Any]) -> None:    Function `__call__` utility or
script function.
L25: def __call__(self, schema: Dict[str, Any], model_class: Type[BaseModel]) -> None:
Function `__call__` utility or script function.
L34: class Extra(str, Enum):    Class (`Extra`) component used by the app (see file context:
None).
L46: class ConfigDict(TypedDict, total=False):    Class (`ConfigDict`) component used by the
app (see file context: None).
L80: class BaseConfig:    Class (`BaseConfig`) component used by the app (see file context:
None).
L118: def get_field_info(cls, name: str) -> Dict[str, Any]:    Function `get_field_info`
Returns or fetches data.

```

```

L143: def prepare_field(cls, field: 'ModelField') -> None:    Function `prepare_field`
utility or script function.
L150: def get_config(config: Union[ConfigDict, Type[object], None]) -> Type[BaseConfig]:
Object (singleton).
L161: class Config(BaseConfig):    Class (`Config`)    component used by the app (see file
context: None).
L169: def inherit_config(self_config: 'ConfigType', parent_config: 'ConfigType', **namespace:
Any) -> 'ConfigType':    Function `inherit_config`    utility or script function.
L186: def prepare_config(config: Type[BaseConfig], cls_name: str) -> None:    Function
`prepare_config`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/_hypothesis_p
login.py**

```

L58: def is_valid_email(s: str) -> bool:    Function `is_valid_email`    utility or script
function.
L122: def add_luhn_digit(card_number: str) -> str:    Function `add_luhn_digit`    utility or
script function.
L185: def _registered(typ: Type[pydantic.types.T]) -> Type[pydantic.types.T]:    Function
`_registered`    utility or script function.
L190: def _registered(typ: pydantic.types.ConstrainedNumberMeta) ->
pydantic.types.ConstrainedNumberMeta:    Function `_registered`    utility or script function.
L194: def _registered(    Function `_registered`    utility or script function.
L208: def resolves(    Function `resolves`    utility or script function.
L211: def inner(f): # type: ignore    Function `inner`    utility or script function.
L223: def resolve_json(cls): # type: ignore[no-untyped-def]    Function `resolve_json`
utility or script function.
L243: def resolve_conbytes(cls): # type: ignore[no-untyped-def] # pragma: no cover
Function `resolve_conbytes`    utility or script function.
L264: def resolve_condecimal(cls): # type: ignore[no-untyped-def]    Function
`resolve_condecimal`    utility or script function.
L282: def resolve_confloat(cls): # type: ignore[no-untyped-def]    Function
`resolve_confloat`    utility or script function.
L314: def resolve_conint(cls): # type: ignore[no-untyped-def]    Function `resolve_conint`
utility or script function.
L337: def resolve_condate(cls): # type: ignore[no-untyped-def]    Function `resolve_condate`
utility or script function.
L356: def resolve_constr(cls): # type: ignore[no-untyped-def] # pragma: no cover    Function
`resolve_constr`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/utils.py

```

L122: def import_string(dotted_path: str) -> Any:    Function `import_string` utility or
script function.
L141: def truncate(v: Union[str], *, max_len: int = 80) -> str:    Function `truncate`
utility or script function.
L158: def sequence_like(v: Any) -> bool:    Function `sequence_like` utility or script
function.
L162: def validate_field_name(bases: Iterable[Type[Any]], field_name: str) -> None:
Function `validate_field_name` utility or script function.
L174: def lenient_isinstance(o: Any, class_or_tuple: Union[Type[Any], Tuple[Type[Any], ...],
None]) -> bool:    Function `lenient_isinstance` utility or script function.
L181: def lenient_issubclass(cls: Any, class_or_tuple: Union[Type[Any], Tuple[Type[Any],
...], None]) -> bool:    Function `lenient_issubclass` utility or script function.
L190: def in_ipython() -> bool:    Function `in_ipython` utility or script function.
L202: def is_valid_identififier(identififier: str) -> bool:    Function `is_valid_identififier`
utility or script function.
L214: def deep_update(mapping: Dict[KeyType, Any], *updating_mappings: Dict[KeyType, Any]) ->
Dict[KeyType, Any]:    Function `deep_update` utility or script function.
L225: def update_not_none(mapping: Dict[Any, Any], **update: Any) -> None:    Function
`update_not_none` utility or script function.
L229: def almost_equal_floats(value_1: float, value_2: float, *, delta: float = 1e-8) ->
bool:    Function `almost_equal_floats` utility or script function.
L236: def generate_model_signature(    Function `generate_model_signature` Generates content
(often AI-generated).
L301: def get_model(obj: Union[Type['BaseModel'], Type['Dataclass']]) -> Type['BaseModel']:
Function `get_model` Returns or fetches data.
L314: def to_camel(string: str) -> str:    Function `to_camel` utility or script function.
L318: def to_lower_camel(string: str) -> str:    Function `to_lower_camel` utility or script
function.
L328: def unique_list(    Function `unique_list` utility or script function.
L351: class PyObjectStr(str):    Class (`PyObjectStr`) component used by the app (see file
context: None).
L357: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L361: class Representation:    Class (`Representation`) component used by the app (see file
context: None).
L371: def __repr_args__(self) -> 'ReprArgs':    Function `__repr_args__` utility or script
function.
L382: def __repr_name__(self) -> str:    Function `__repr_name__` utility or script function.
L388: def __repr_str__(self, join_str: str) -> str:    Function `__repr_str__` utility or
script function.
L391: def __pretty__(self, fmt: Callable[[Any], Any], **kwargs: Any) -> Generator[Any, None,
None]:    Function `__pretty__` utility or script function.
L406: def __str__(self) -> str:    Function `__str__` utility or script function.
L409: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L412: def __rich_repr__(self) -> 'RichReprResult':    Function `__rich_repr__` utility or
script function.
L421: class GetterDict(Representation):    Class (`GetterDict`) component used by the app
(see file context: None).
L430: def __init__(self, obj: Any):    Function `__init__` utility or script function.
L433: def __getitem__(self, key: str) -> Any:    Function `__getitem__` utility or script
function.
L439: def get(self, key: Any, default: Any = None) -> Any:    Function `get` Returns or

```

fetches data.

L442: def extra_keys(self) -> Set[Any]: Function `extra\_keys` utility or script function.

L448: def keys(self) -> List[Any]: Function `keys` utility or script function.

L455: def values(self) -> List[Any]: Function `values` utility or script function.

L458: def items(self) -> Iterator[Tuple[str, Any]]: Function `items` utility or script function.

L462: def __iter__(self) -> Iterator[str]: Function `\_\_iter\_\_` utility or script function.

L467: def __len__(self) -> int: Function `\_\_len\_\_` utility or script function.

L470: def __contains__(self, item: Any) -> bool: Function `\_\_contains\_\_` utility or script function.

L473: def __eq__(self, other: Any) -> bool: Function `\_\_eq\_\_` utility or script function.

L476: def __repr_args__(self) -> 'ReprArgs': Function `\_\_repr\_args\_\_` utility or script function.

L479: def __repr_name__(self) -> str: Function `\_\_repr\_name\_\_` utility or script function.

L483: class ValueItems(Representation): Class (`ValueItems`) component used by the app (see file context: None).

L490: def __init__(self, value: Any, items: Union['AbstractSetIntStr', 'MappingIntStrAny']) -> None: Function `\_\_init\_\_` utility or script function.

L498: def is_excluded(self, item: Any) -> bool: Function `is\_excluded` utility or script function.

L506: def is_included(self, item: Any) -> bool: Function `is\_included` utility or script function.

L514: def for_element(self, e: 'IntStr') -> Optional[Union['AbstractSetIntStr', 'MappingIntStrAny']]: Function `for\_element` utility or script function.

L523: def _normalize_indexes(self, items: 'MappingIntStrAny', v_length: int) -> 'DictIntStrAny': Function `\_normalize\_indexes` utility or script function.

L563: def merge(cls, base: Any, override: Any, intersect: bool = False) -> Any: Function `merge` utility or script function.

L602: def _coerce_items(items: Union['AbstractSetIntStr', 'MappingIntStrAny']) -> 'MappingIntStrAny': Function `\_coerce\_items` utility or script function.

L616: def _coerce_value(cls, value: Any) -> Any: Function `\_coerce\_value` utility or script function.

L622: def is_true(v: Any) -> bool: Function `is\_true` utility or script function.

L625: def __repr_args__(self) -> 'ReprArgs': Function `\_\_repr\_args\_\_` utility or script function.

L629: class ClassAttribute: Class (`ClassAttribute`) component used by the app (see file context: None).

L639: def __init__(self, name: str, value: Any) -> None: Function `\_\_init\_\_` utility or script function.

L643: def __get__(self, instance: Any, owner: Type[Any]) -> None: Function `\_\_get\_\_` utility or script function.

L661: def path_type(p: 'Path') -> str: Function `path\_type` utility or script function.

L676: def smart_deepcopy(obj: Obj) -> Obj: Function `smart\_deepcopy` utility or script function.

L697: def is_valid_field(name: str) -> bool: Function `is\_valid\_field` utility or script function.

L717: def is_valid_private_name(name: str) -> bool: Function `is\_valid\_private\_name` utility or script function.

L724: def all_identical(left: Iterable[Any], right: Iterable[Any]) -> bool: Function `all\_identical` utility or script function.

L740: def assert_never(obj: NoReturn, msg: str) -> NoReturn: Function `assert\_never`

utility or script function.

L750: def get_unique_discriminator_alias(all_aliases: Collection[str], discriminator_key: str) -> str: Function `get\_unique\_discriminator\_alias` Returns or fetches data.

L760: def get_discriminator_alias_and_values(tp: Any, discriminator_key: str) -> Tuple[str, Tuple[str, ...]]: Function `get\_discriminator\_alias\_and\_values` Returns or fetches data.

L801: def _get_union_alias_and_all_values(Function `\_get\_union\_alias\_and\_all\_values` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/generics.py

L64: class GenericModel(BaseModel): Class (`GenericModel`) component used by the app (see file context: None).

L75: def __class_getitem__(cls: Type[GenericModelT], params: Union[Type[Any], Tuple[Type[Any], ...]]) -> Type[Any]: Function `\_\_class\_getitem\_\_` utility or script function.

L87: def _cache_key(_params: Any) -> CacheKey: Function `\_cache\_key` utility or script function.

L171: def __concrete_name__(cls: Type[Any], params: Tuple[Type[Any], ...]) -> str: Function `\_\_concrete\_name\_\_` utility or script function.

L187: def __parameterized_bases__(cls, typevars_map: Parametrization) -> Iterator[Type[Any]]: Function `\_\_parameterized\_bases\_\_` utility or script function.

L200: class A(GenericModel, Generic[T]): Class (`A`) component used by the app (see file context: None).

L203: class B(A[V], Generic[V]): Class (`B`) component used by the app (see file context: None).

L210: def build_base_model(Function `build\_base\_model` Constructs or prepares an object.

L251: def replace_types(type_: Any, type_map: Mapping[Any, Any]) -> Any: Function `replace\_types` utility or script function.

L333: def check_parameters_count(cls: Type[GenericModel], parameters: Tuple[Any, ...]) -> None: Function `check\_parameters\_count` utility or script function.

L344: def iter_contained_typevars(v: Any) -> Iterator[TypeVarType]: Function `iter\_contained\_typevars` utility or script function.

L359: def get_caller_frame_info() -> Tuple[Optional[str], bool]: Function `get\_caller\_frame\_info` Returns or fetches data.

L377: def _prepare_model_fields(Function `\_prepare\_model\_fields` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/version.py

L16: def version_info() -> str: Function `version\_info` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/tools.py

```

L18: def _generate_parsing_type_name(type_: Any) -> str:    Function
`_generate_parsing_type_name` utility or script function.
L23: def _get_parsing_type(type_: Any, *, type_name: Optional[NameFactory] = None) -> Any:
Function `_get_parsing_type` utility or script function.
L36: def parse_obj_as(type_: Type[T], obj: Any, *, type_name: Optional[NameFactory] = None)
-> T:    Function `parse_obj_as` utility or script function.
L41: def parse_file_as(    Function `parse_file_as` utility or script function.
L63: def parse_raw_as(    Function `parse_raw_as` utility or script function.
L85: def schema_of(type_: Any, *, title: Optional[NameFactory] = None, **schema_kwargs: Any)
-> 'DictStrAny':    Function `schema_of` utility or script function.
L90: def schema_json_of(type_: Any, *, title: Optional[NameFactory] = None,
**schema_json_kwargs: Any) -> str:    Function `schema_json_of` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/types.py

```

L137: def _registered(typ: Type[T]) -> Type[T]:    Function `_registered` utility or script
function.
L142: def _registered(typ: 'ConstrainedNumberMeta') -> 'ConstrainedNumberMeta':    Function
`_registered` utility or script function.
L146: def _registered(typ: Union[Type[T], 'ConstrainedNumberMeta']) -> Union[Type[T],
'ConstrainedNumberMeta']:    Function `_registered` utility or script function.
L157: class ConstrainedNumberMeta(type):    Class (`ConstrainedNumberMeta`) component used by
the app (see file context: None).
L158: def __new__(cls, name: str, bases: Any, dct: Dict[str, Any]) -> 'ConstrainedInt':    #
type: ignore    Function `__new__` utility or script function.
L175: class StrictBool(int):    Class (`StrictBool`) component used by the app (see file
context: None).
L181: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__` utility or script function.
L185: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L189: def validate(cls, value: Any) -> bool:    Function `validate` utility or script
function.
L202: class ConstrainedInt(int, metaclass=ConstrainedNumberMeta):    Class (`ConstrainedInt`)
component used by the app (see file context: None).
L211: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__` utility or script function.
L222: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L228: def conint(    Function `conint` utility or script function.
L250: class PositiveInt(ConstrainedInt):    Class (`PositiveInt`) component used by the app
(see file context: None).

```

```

L253: class NegativeInt(ConstrainedInt):  Class (`NegativeInt`)  component used by the app
(see file context: None).
L256: class NonPositiveInt(ConstrainedInt):  Class (`NonPositiveInt`)  component used by the
app (see file context: None).
L259: class NonNegativeInt(ConstrainedInt):  Class (`NonNegativeInt`)  component used by the
app (see file context: None).
L262: class StrictInt(ConstrainedInt):  Class (`StrictInt`)  component used by the app (see
file context: None).
L269: class ConstrainedFloat(float, metaclass=ConstrainedNumberMeta):  Class
(`ConstrainedFloat`)  component used by the app (see file context: None).
L279: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:  Function
`__modify_schema__`  utility or script function.
L299: def __get_validators__(cls) -> 'CallableGenerator':  Function `__get_validators__`
utility or script function.
L306: def confloat(  Function `confloat`  utility or script function.
L330: class PositiveFloat(ConstrainedFloat):  Class (`PositiveFloat`)  component used by the
app (see file context: None).
L333: class NegativeFloat(ConstrainedFloat):  Class (`NegativeFloat`)  component used by the
app (see file context: None).
L336: class NonPositiveFloat(ConstrainedFloat):  Class (`NonPositiveFloat`)  component used
by the app (see file context: None).
L339: class NonNegativeFloat(ConstrainedFloat):  Class (`NonNegativeFloat`)  component used
by the app (see file context: None).
L342: class StrictFloat(ConstrainedFloat):  Class (`StrictFloat`)  component used by the app
(see file context: None).
L345: class FiniteFloat(ConstrainedFloat):  Class (`FiniteFloat`)  component used by the app
(see file context: None).
L352: class ConstrainedBytes(bytes):  Class (`ConstrainedBytes`)  component used by the app
(see file context: None).
L361: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:  Function
`__modify_schema__`  utility or script function.
L365: def __get_validators__(cls) -> 'CallableGenerator':  Function `__get_validators__`
utility or script function.
L373: def conbytes(  Function `conbytes`  utility or script function.
L398: class StrictBytes(ConstrainedBytes):  Class (`StrictBytes`)  component used by the app
(see file context: None).
L405: class ConstrainedStr(str):  Class (`ConstrainedStr`)  component used by the app (see
file context: None).
L416: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:  Function
`__modify_schema__`  utility or script function.
L425: def __get_validators__(cls) -> 'CallableGenerator':  Function `__get_validators__`
utility or script function.
L434: def validate(cls, value: Union[str]) -> Union[str]:  Function `validate`  utility or
script function.
L445: def _get_pattern(regex: Union[str, Pattern[str]]) -> str:  Function `_get_pattern`
utility or script function.
L449: def constr(  Function `constr`  utility or script function.
L478: class StrictStr(ConstrainedStr):  Class (`StrictStr`)  component used by the app (see
file context: None).
L486: class ConstrainedSet(set):  # type: ignore  Class (`ConstrainedSet`)  component used
by the app (see file context: None).

```

```

L496: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L500: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L504: def set_length_validator(cls, v: 'Optional[Set[T]]') -> 'Optional[Set[T]]':    Function
`set_length_validator`    Sets or updates a value.
L520: def conset(item_type: Type[T], *, min_items: Optional[int] = None, max_items:
Optional[int] = None) -> Type[Set[T]]:    Function `conset`    utility or script function.
L528: class ConstrainedFrozenSet(frozenset):    # type: ignore    Class (`ConstrainedFrozenSet`)
component used by the app (see file context: None).
L538: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L542: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L546: def frozenset_length_validator(cls, v: 'Optional[FrozenSet[T]]') ->
'Optional[FrozenSet[T]]':    Function `frozenset_length_validator`    utility or script
function.
L562: def confrozenset(    Function `confrozenset`    utility or script function.
L575: class ConstrainedList(list):    # type: ignore    Class (`ConstrainedList`)    component
used by the app (see file context: None).
L586: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L592: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L596: def list_length_validator(cls, v: 'Optional[List[T]]') -> 'Optional[List[T]]':
Function `list_length_validator`    utility or script function.
L612: def unique_items_validator(cls, v: 'Optional[List[T]]') -> 'Optional[List[T]]':
Function `unique_items_validator`    utility or script function.
L623: def conlist(    Function `conlist`    utility or script function.
L641: class PyObject:    Class (`PyObject`)    component used by the app (see file context:
None).
L645: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L649: def validate(cls, value: Any) -> Any:    Function `validate`    utility or script
function.
L667: class ConstrainedDecimal(Decimal, metaclass=ConstrainedNumberMeta):    Class
(`ConstrainedDecimal`)    component used by the app (see file context: None).
L677: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L688: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L695: def validate(cls, value: Decimal) -> Decimal:    Function `validate`    utility or script
function.
L735: def condecimal(    Function `condecimal`    utility or script function.
L761: class UUID1(UUID):    Class (`UUID1`)    component used by the app (see file context:
None).
L765: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L768: class UUID3(UUID1):    Class (`UUID3`)    component used by the app (see file context:
None).
L771: class UUID4(UUID1):    Class (`UUID4`)    component used by the app (see file context:

```

```

None).
L774: class UUID5(UUID1):    Class (`UUID5`)    component used by the app (see file context:
None).
L785: class FilePath(Path):    Class (`FilePath`)    component used by the app (see file
context: None).
L787: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L791: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L797: def validate(cls, value: Path) -> Path:    Function `validate`    utility or script
function.
L803: class DirectoryPath(Path):    Class (`DirectoryPath`)    component used by the app (see
file context: None).
L805: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L809: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L815: def validate(cls, value: Path) -> Path:    Function `validate`    utility or script
function.
L825: class JsonWrapper:    Class (`JsonWrapper`)    component used by the app (see file
context: None).
L829: class JsonMeta(type):    Class (`JsonMeta`)    component used by the app (see file
context: None).
L830: def __getitem__(self, t: Type[Any]) -> Type[JsonWrapper]:    Function `__getitem__`
utility or script function.
L841: class Json(metaclass=JsonMeta):    Class (`Json`)    component used by the app (see file
context: None).
L843: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L850: class SecretField(abc.ABC):    Class (`SecretField`)    component used by the app (see
file context: None).
L861: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L864: def __str__(self) -> str:    Function `__str__`    utility or script function.
L867: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L871: def get_secret_value(self) -> Any:    # pragma: no cover    Function `get_secret_value`
Returns or fetches data.
L875: class SecretStr(SecretField):    Class (`SecretStr`)    component used by the app (see
file context: None).
L880: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__`    utility or script function.
L891: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L896: def validate(cls, value: Any) -> 'SecretStr':    Function `validate`    utility or script
function.
L902: def __init__(self, value: str):    Function `__init__`    utility or script function.
L905: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L908: def __len__(self) -> int:    Function `__len__`    utility or script function.
L911: def display(self) -> str:    Function `display`    utility or script function.
L915: def get_secret_value(self) -> str:    Function `get_secret_value`    Returns or fetches
data.
L919: class SecretBytes(SecretField):    Class (`SecretBytes`)    component used by the app (see

```

```

file context: None).
L924: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:    Function
`__modify_schema__` utility or script function.
L935: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L940: def validate(cls, value: Any) -> 'SecretBytes':    Function `validate` utility or
script function.
L946: def __init__(self, value: bytes):    Function `__init__` utility or script function.
L949: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L952: def __len__(self) -> int:    Function `__len__` utility or script function.
L955: def display(self) -> str:    Function `display` utility or script function.
L959: def get_secret_value(self) -> bytes:    Function `get_secret_value` Returns or fetches
data.
L966: class PaymentCardBrand(str, Enum):    Class (`PaymentCardBrand`) component used by the
app (see file context: None).
L974: def __str__(self) -> str:    Function `__str__` utility or script function.
L978: class PaymentCardNumber(str):    Class (`PaymentCardNumber`) component used by the app
(see file context: None).
L990: def __init__(self, card_number: str):    Function `__init__` utility or script
function.
L996: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L1006: def masked(self) -> str:    Function `masked` utility or script function.
L1011: def validate_digits(cls, card_number: str) -> str:    Function `validate_digits`
utility or script function.
L1017: def validate_luhn_check_digit(cls, card_number: str) -> str:    Function
`validate_luhn_check_digit` utility or script function.
L1037: def validate_length_for_brand(cls, card_number: 'PaymentCardNumber') ->
'PaymentCardNumber':    Function `validate_length_for_brand` utility or script function.
L1059: def _get_brand(card_number: str) -> PaymentCardBrand:    Function `_get_brand` utility
or script function.
L1092: class ByteSize(int):    Class (`ByteSize`) component used by the app (see file
context: None).
L1094: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L1098: def validate(cls, v: StrIntFloat) -> 'ByteSize':    Function `validate` utility or
script function.
L1119: def human_readable(self, decimal: bool = False) -> str:    Function `human_readable`
utility or script function.
L1137: def to(self, unit: str) -> float:    Function `to` utility or script function.
L1153: class PastDate(date):    Class (`PastDate`) component used by the app (see file
context: None).
L1155: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L1160: def validate(cls, value: date) -> date:    Function `validate` utility or script
function.
L1166: class FutureDate(date):    Class (`FutureDate`) component used by the app (see file
context: None).
L1168: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L1173: def validate(cls, value: date) -> date:    Function `validate` utility or script

```

```

function.
L1180: class ConstrainedDate(date, metaclass=ConstrainedNumberMeta):  Class
(`ConstrainedDate`) component used by the app (see file context: None).
L1187: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None:  Function
`__modify_schema__` utility or script function.
L1191: def __get_validators__(cls) -> 'CallableGenerator':  Function `__get_validators__`
utility or script function.
L1196: def conddate(  Function `conddate` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/decorator.py

```

L21: def validate_arguments(func: None = None, *, config: 'ConfigType' = None) ->
Callable[['AnyCallableT'], 'AnyCallableT']:  Function `validate_arguments` utility or
script function.
L26: def validate_arguments(func: 'AnyCallableT') -> 'AnyCallableT':  Function
`validate_arguments` utility or script function.
L30: def validate_arguments(func: Optional['AnyCallableT'] = None, *, config: 'ConfigType' =
None) -> Any:  Function `validate_arguments` utility or script function.
L35: def validate(_func: 'AnyCallable') -> 'AnyCallable':  Function `validate` utility or
script function.
L39: def wrapper_function(*args: Any, **kwargs: Any) -> Any:  Function `wrapper_function`
utility or script function.
L60: class ValidatedFunction:  Class (`ValidatedFunction`) component used by the app (see
file context: None).
L61: def __init__(self, function: 'AnyCallableT', config: 'ConfigType'):  # noqa C901
Function `__init__` utility or script function.
L128: def init_model_instance(self, *args: Any, **kwargs: Any) -> BaseModel:  Function
`init_model_instance` Initialisation routine.
L132: def call(self, *args: Any, **kwargs: Any) -> Any:  Function `call` utility or script
function.
L136: def build_values(self, args: Tuple[Any, ...], kwargs: Dict[str, Any]) -> Dict[str,
Any]:  Function `build_values` Constructs or prepares an object.
L179: def execute(self, m: BaseModel) -> Any:  Function `execute` utility or script
function.
L208: def create_model(self, fields: Dict[str, Any], takes_args: bool, takes_kwargs: bool,
config: 'ConfigType') -> None:  Function `create_model` Creates a resource or document.
L211: class CustomConfig:  Class (`CustomConfig`) component used by the app (see file
context: None).
L226: class DecoratorBaseModel(BaseModel):  Class (`DecoratorBaseModel`) component used by
the app (see file context: None).
L228: def check_args(cls, v: Optional[List[Any]]) -> Optional[List[Any]]:  Function
`check_args` utility or script function.
L235: def check_kwargs(cls, v: Optional[Dict[str, Any]]) -> Optional[Dict[str, Any]]:
Function `check_kwargs` utility or script function.
L244: def check_positional_only(cls, v: Optional[List[str]]) -> None:  Function
`check_positional_only` utility or script function.
L253: def check_duplicate_kwargs(cls, v: Optional[List[str]]) -> None:  Function

```

```
`check_duplicate_kwargs` utility or script function.
L261: class Config(CustomConfig): Class (`Config`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/color.py

```
L26: class RGBA: Class (`RGBA`) component used by the app (see file context: None).
L33: def __init__(self, r: float, g: float, b: float, alpha: Optional[float]): Function
`__init__` utility or script function.
L41: def __getitem__(self, item: Any) -> Any: Function `__getitem__` utility or script
function.
L63: class Color(Representation): Class (`Color`) component used by the app (see file
context: None).
L66: def __init__(self, value: ColorType) -> None: Function `__init__` utility or script
function.
L83: def __modify_schema__(cls, field_schema: Dict[str, Any]) -> None: Function
`__modify_schema__` utility or script function.
L86: def original(self) -> ColorType: Function `original` utility or script function.
L92: def as_named(self, *, fallback: bool = False) -> str: Function `as_named` utility or
script function.
L105: def as_hex(self) -> str: Function `as_hex` utility or script function.
L119: def as_rgb(self) -> str: Function `as_rgb` utility or script function.
L131: def as_rgb_tuple(self, *, alpha: Optional[bool] = None) -> ColorTuple: Function
`as_rgb_tuple` utility or script function.
L153: def as_hsl(self) -> str: Function `as_hsl` utility or script function.
L164: def as_hsl_tuple(self, *, alpha: Optional[bool] = None) -> HslColorTuple: Function
`as_hsl_tuple` utility or script function.
L188: def _alpha_float(self) -> float: Function `_alpha_float` utility or script function.
L192: def __get_validators__(cls) -> 'CallableGenerator': Function `__get_validators__`
utility or script function.
L195: def __str__(self) -> str: Function `__str__` utility or script function.
L198: def __repr_args__(self) -> 'ReprArgs': Function `__repr_args__` utility or script
function.
L201: def __eq__(self, other: Any) -> bool: Function `__eq__` utility or script function.
L204: def __hash__(self) -> int: Function `__hash__` utility or script function.
L208: def parse_tuple(value: Tuple[Any, ...]) -> RGBA: Function `parse_tuple` utility or
script function.
L222: def parse_str(value: str) -> RGBA: Function `parse_str` utility or script function.
L280: def ints_to_rgba(r: Union[int, str], g: Union[int, str], b: Union[int, str], alpha:
Optional[float]) -> RGBA: Function `ints_to_rgba` utility or script function.
L284: def parse_color_value(value: Union[int, str], max_val: int = 255) -> float: Function
`parse_color_value` utility or script function.
L299: def parse_float_alpha(value: Union[None, str, float, int]) -> Optional[float]:
Function `parse_float_alpha` utility or script function.
L321: def parse_hsl(h: str, h_units: str, sat: str, light: str, alpha: Optional[float] =
None) -> RGBA: Function `parse_hsl` utility or script function.
L340: def float_to_255(c: float) -> int: Function `float_to_255` utility or script
```



```
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/main.py

```
L98: def validate_custom_root_type(fields: Dict[str, ModelField]) -> None:    Function
`validate_custom_root_type` utility or script function.
L103: def generate_hash_function(frozen: bool) -> Optional[Callable[[Any], int]]:    Function
`generate_hash_function` Generates content (often AI-generated).
L104: def hash_function(self_: Any) -> int:    Function `hash_function` utility or script
function.
L122: class ModelMetaclass(ABCMeta):    Class (`ModelMetaclass`) component used by the app
(see file context: None).
L124: def __new__(mcs, name, bases, namespace, **kwargs):    # noqa C901    Function `__new__`
utility or script function.
L175: def is_untouched(v: Any) -> bool:    Function `is_untouched` utility or script
function.
L321: def __instancecheck__(self, instance: Any) -> bool:    Function `__instancecheck__`
utility or script function.
L333: class BaseModel(Representation, metaclass=ModelMetaclass):    Class (`BaseModel`)
component used by the app (see file context: None).
L355: def __init__(__pydantic_self__, **data: Any) -> None:    Function `__init__` utility or
script function.
L375: def __setattr__(self, name, value):    # noqa: C901 (ignore complexity)    Function
`__setattr__` utility or script function.
L430: def __getstate__(self) -> 'DictAny':    Function `__getstate__` utility or script
function.
L438: def __setstate__(self, state: 'DictAny') -> None:    Function `__setstate__` utility or
script function.
L444: def _init_private_attributes(self) -> None:    Function `_init_private_attributes`
utility or script function.
L450: def dict(    Function `dict` utility or script function.
L484: def json(    Function `json` utility or script function.
L530: def _enforce_dict_if_root(cls, obj: Any) -> Any:    Function `_enforce_dict_if_root`
utility or script function.
L541: def parse_obj(cls: Type['Model'], obj: Any) -> 'Model':    Function `parse_obj` utility
or script function.
L552: def parse_raw(    Function `parse_raw` utility or script function.
L575: def parse_file(    Function `parse_file` utility or script function.
L595: def from_orm(cls: Type['Model'], obj: Any) -> 'Model':    Function `from_orm` utility
or script function.
L609: def construct(cls: Type['Model'], _fields_set: Optional['SetStr'] = None, **values:
Any) -> 'Model':    Function `construct` utility or script function.
L632: def _copy_and_set_values(self: 'Model', values: 'DictStrAny', fields_set: 'SetStr', *,
deep: bool) -> 'Model':    Function `_copy_and_set_values` utility or script function.
L650: def copy(    Function `copy` utility or script function.
L683: def schema(cls, by_alias: bool = True, ref_template: str = default_ref_template) ->
'DictStrAny':    Function `schema` utility or script function.
```



```

L692: def schema_json(    Function `schema_json`    utility or script function.
L702: def __get_validators__(cls) -> 'CallableGenerator':    Function `__get_validators__`
utility or script function.
L706: def validate(cls: Type['Model'], value: Any) -> 'Model':    Function `validate`    utility
or script function.
L745: def _decompose_class(cls: Type['Model'], obj: Any) -> GetterDict:    Function
`_decompose_class`    utility or script function.
L752: def _get_value(    Function `_get_value`    utility or script function.
L825: def __try_update_forward_refs__(cls, **localns: Any) -> None:    Function
`__try_update_forward_refs__`    utility or script function.
L833: def update_forward_refs(cls, **localns: Any) -> None:    Function `update_forward_refs`
utility or script function.
L839: def __iter__(self) -> 'TupleGenerator':    Function `__iter__`    utility or script
function.
L845: def _iter(    Function `_iter`    utility or script function.
L901: def _calculate_keys(    Function `_calculate_keys`    utility or script function.
L928: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L934: def __repr_args__(self) -> 'ReprArgs':    Function `__repr_args__`    utility or script
function.
L946: def create_model(    Function `create_model`    Creates a resource or document.
L960: def create_model(    Function `create_model`    Creates a resource or document.
L973: def create_model(    Function `create_model`    Creates a resource or document.
L1053: def validate_model( # noqa: C901 (ignore complexity)    Function `validate_model`
utility or script function.

```

Q_base

**appwrite/venv/lib/python3.12/site-packages/pydantic/v1/error_wrapper
s.py**

```

L16: class _ErrorDictRequired(TypedDict):    Class (`_ErrorDictRequired`)    component used by
the app (see file context: None).
L21: class ErrorDict(_ErrorDictRequired, total=False):    Class (`ErrorDict`)    component used
by the app (see file context: None).
L28: class ErrorWrapper(Representation):    Class (`ErrorWrapper`)    component used by the app
(see file context: None).
L31: def __init__(self, exc: Exception, loc: Union[str, 'Loc']) -> None:    Function
`__init__`    utility or script function.
L35: def loc_tuple(self) -> 'Loc':    Function `loc_tuple`    utility or script function.
L41: def __repr_args__(self) -> 'ReprArgs':    Function `__repr_args__`    utility or script
function.
L50: class ValidationError(Representation, ValueError):    Class (`ValidationError`)
component used by the app (see file context: None).
L53: def __init__(self, errors: Sequence[ErrorList], model: 'ModelOrDc') -> None:    Function
`__init__`    utility or script function.
L58: def errors(self) -> List['ErrorDict']:    Function `errors`    utility or script function.
L67: def json(self, *, indent: Union[None, int, str] = 2) -> str:    Function `json`    utility
or script function.

```

```

L70: def __str__(self) -> str:    Function `__str__`    utility or script function.
L78: def __repr_args__(self) -> 'ReprArgs':    Function `__repr_args__`    utility or script
function.
L82: def display_errors(errors: List['ErrorDict']) -> str:    Function `display_errors`
utility or script function.
L86: def _display_error_loc(error: 'ErrorDict') -> str:    Function `_display_error_loc`
utility or script function.
L90: def _display_error_type_and_ctx(error: 'ErrorDict') -> str:    Function
`_display_error_type_and_ctx`    utility or script function.
L99: def flatten_errors(    Function `flatten_errors`    utility or script function.
L119: def error_dict(exc: Exception, config: Type['BaseConfig'], loc: 'Loc') -> 'ErrorDict':
    Function `error_dict`    utility or script function.
L139: def get_exc_type(cls: Type[Exception]) -> str:    Function `get_exc_type`    Returns or
fetches data.
L149: def _get_exc_type(cls: Type[Exception]) -> str:    Function `_get_exc_type`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/v1/errors.py

```

L108: def cls_kwargs(cls: Type['PydanticErrorMixin'], ctx: 'DictStrAny') ->
'PydanticErrorMixin':    Function `cls_kwargs`    utility or script function.
L119: class PydanticErrorMixin:    Class (`PydanticErrorMixin`)    component used by the app
(see file context: None).
L123: def __init__(self, **ctx: Any) -> None:    Function `__init__`    utility or script
function.
L126: def __str__(self) -> str:    Function `__str__`    utility or script function.
L129: def __reduce__(self) -> Tuple[Callable[...], 'PydanticErrorMixin'],
Tuple[Type['PydanticErrorMixin'], 'DictStrAny']]:    Function `__reduce__`    utility or script
function.
L133: class PydanticTypeError(PydanticErrorMixin, TypeError):    Class (`PydanticTypeError`)
component used by the app (see file context: None).
L137: class PydanticValueError(PydanticErrorMixin, ValueError):    Class
(`PydanticValueError`)    component used by the app (see file context: None).
L141: class ConfigError(RuntimeError):    Class (`ConfigError`)    component used by the app
(see file context: None).
L145: class MissingError(PydanticValueError):    Class (`MissingError`)    component used by the
app (see file context: None).
L149: class ExtraError(PydanticValueError):    Class (`ExtraError`)    component used by the app
(see file context: None).
L153: class NoneIsNotAllowedError(PydanticTypeError):    Class (`NoneIsNotAllowedError`)
component used by the app (see file context: None).
L158: class NoneIsAllowedError(PydanticTypeError):    Class (`NoneIsAllowedError`)    component
used by the app (see file context: None).
L163: class WrongConstantError(PydanticValueError):    Class (`WrongConstantError`)    component
used by the app (see file context: None).
L166: def __str__(self) -> str:    Function `__str__`    utility or script function.
L171: class NotNoneError(PydanticTypeError):    Class (`NotNoneError`)    component used by the

```

```

app (see file context: None).
L176: class BoolError(PydanticTypeError):    Class (`BoolError`)    component used by the app
(see file context: None).
L180: class BytesError(PydanticTypeError):    Class (`BytesError`)    component used by the app
(see file context: None).
L184: class DictError(PydanticTypeError):    Class (`DictError`)    component used by the app
(see file context: None).
L188: class EmailError(PydanticValueError):    Class (`EmailError`)    component used by the app
(see file context: None).
L192: class UrlError(PydanticValueError):    Class (`UrlError`)    component used by the app
(see file context: None).
L196: class UrlSchemeError(UrlError):    Class (`UrlSchemeError`)    component used by the app
(see file context: None).
L201: class UrlSchemePermittedError(UrlError):    Class (`UrlSchemePermittedError`)    component
used by the app (see file context: None).
L205: def __init__(self, allowed_schemes: Set[str]):    Function `__init__`    utility or script
function.
L209: class UrlUserInfoError(UrlError):    Class (`UrlUserInfoError`)    component used by the
app (see file context: None).
L214: class UrlHostError(UrlError):    Class (`UrlHostError`)    component used by the app (see
file context: None).
L219: class UrlHostTldError(UrlError):    Class (`UrlHostTldError`)    component used by the app
(see file context: None).
L224: class UrlPortError(UrlError):    Class (`UrlPortError`)    component used by the app (see
file context: None).
L229: class UrlExtraError(UrlError):    Class (`UrlExtraError`)    component used by the app
(see file context: None).
L234: class EnumMemberError(PydanticTypeError):    Class (`EnumMemberError`)    component used
by the app (see file context: None).
L237: def __str__(self) -> str:    Function `__str__`    utility or script function.
L242: class IntegerError(PydanticTypeError):    Class (`IntegerError`)    component used by the
app (see file context: None).
L246: class FloatError(PydanticTypeError):    Class (`FloatError`)    component used by the app
(see file context: None).
L250: class PathError(PydanticTypeError):    Class (`PathError`)    component used by the app
(see file context: None).
L254: class _PathValueError(PydanticValueError):    Class (`_PathValueError`)    component used
by the app (see file context: None).
L255: def __init__(self, *, path: Path) -> None:    Function `__init__`    utility or script
function.
L259: class PathNotExistsError(_PathValueError):    Class (`PathNotExistsError`)    component
used by the app (see file context: None).
L264: class PathNotAFileError(_PathValueError):    Class (`PathNotAFileError`)    component used
by the app (see file context: None).
L269: class PathNotADirectoryError(_PathValueError):    Class (`PathNotADirectoryError`)
component used by the app (see file context: None).
L274: class PyObjectError(PydanticTypeError):    Class (`PyObjectError`)    component used by
the app (see file context: None).
L278: class SequenceError(PydanticTypeError):    Class (`SequenceError`)    component used by
the app (see file context: None).
L282: class IterableError(PydanticTypeError):    Class (`IterableError`)    component used by

```

the app (see file context: None).

L286: class ListError(PydanticTypeError): Class (`ListError`) component used by the app (see file context: None).

L290: class SetError(PydanticTypeError): Class (`SetError`) component used by the app (see file context: None).

L294: class FrozenSetError(PydanticTypeError): Class (`FrozenSetError`) component used by the app (see file context: None).

L298: class DequeError(PydanticTypeError): Class (`DequeError`) component used by the app (see file context: None).

L302: class TupleError(PydanticTypeError): Class (`TupleError`) component used by the app (see file context: None).

L306: class TupleLengthError(PydanticValueError): Class (`TupleLengthError`) component used by the app (see file context: None).

L310: def __init__(self, *, actual_length: int, expected_length: int) -> None: Function `\_\_init\_\_` utility or script function.

L314: class ListMinLengthError(PydanticValueError): Class (`ListMinLengthError`) component used by the app (see file context: None).

L318: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L322: class ListMaxLengthError(PydanticValueError): Class (`ListMaxLengthError`) component used by the app (see file context: None).

L326: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L330: class ListUniqueItemsError(PydanticValueError): Class (`ListUniqueItemsError`) component used by the app (see file context: None).

L335: class SetMinLengthError(PydanticValueError): Class (`SetMinLengthError`) component used by the app (see file context: None).

L339: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L343: class SetMaxLengthError(PydanticValueError): Class (`SetMaxLengthError`) component used by the app (see file context: None).

L347: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L351: class FrozenSetMinLengthError(PydanticValueError): Class (`FrozenSetMinLengthError`) component used by the app (see file context: None).

L355: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L359: class FrozenSetMaxLengthError(PydanticValueError): Class (`FrozenSetMaxLengthError`) component used by the app (see file context: None).

L363: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L367: class AnyStrMinLengthError(PydanticValueError): Class (`AnyStrMinLengthError`) component used by the app (see file context: None).

L371: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L375: class AnyStrMaxLengthError(PydanticValueError): Class (`AnyStrMaxLengthError`) component used by the app (see file context: None).

L379: def __init__(self, *, limit_value: int) -> None: Function `\_\_init\_\_` utility or script function.

L383: class StrError(PydanticTypeError): Class (`StrError`) component used by the app (see file context: None).

```

L387: class StrRegexError(PydanticValueError):    Class (`StrRegexError`)    component used by
the app (see file context: None).
L391: def __init__(self, *, pattern: str) -> None:    Function `__init__`    utility or script
function.
L395: class _NumberBoundError(PydanticValueError):    Class (`_NumberBoundError`)    component
used by the app (see file context: None).
L396: def __init__(self, *, limit_value: Union[int, float, Decimal]) -> None:    Function
`__init__`    utility or script function.
L400: class NumberNotGtError(_NumberBoundError):    Class (`NumberNotGtError`)    component used
by the app (see file context: None).
L405: class NumberNotGeError(_NumberBoundError):    Class (`NumberNotGeError`)    component used
by the app (see file context: None).
L410: class NumberNotLtError(_NumberBoundError):    Class (`NumberNotLtError`)    component used
by the app (see file context: None).
L415: class NumberNotLeError(_NumberBoundError):    Class (`NumberNotLeError`)    component used
by the app (see file context: None).
L420: class NumberNotFiniteError(PydanticValueError):    Class (`NumberNotFiniteError`)
component used by the app (see file context: None).
L425: class NumberNotMultipleError(PydanticValueError):    Class (`NumberNotMultipleError`)
component used by the app (see file context: None).
L429: def __init__(self, *, multiple_of: Union[int, float, Decimal]) -> None:    Function
`__init__`    utility or script function.
L433: class DecimalError(PydanticTypeError):    Class (`DecimalError`)    component used by the
app (see file context: None).
L437: class DecimalIsNotFiniteError(PydanticValueError):    Class (`DecimalIsNotFiniteError`)
component used by the app (see file context: None).
L442: class DecimalMaxDigitsError(PydanticValueError):    Class (`DecimalMaxDigitsError`)
component used by the app (see file context: None).
L446: def __init__(self, *, max_digits: int) -> None:    Function `__init__`    utility or
script function.
L450: class DecimalMaxPlacesError(PydanticValueError):    Class (`DecimalMaxPlacesError`)
component used by the app (see file context: None).
L454: def __init__(self, *, decimal_places: int) -> None:    Function `__init__`    utility or
script function.
L458: class DecimalWholeDigitsError(PydanticValueError):    Class (`DecimalWholeDigitsError`)
component used by the app (see file context: None).
L462: def __init__(self, *, whole_digits: int) -> None:    Function `__init__`    utility or
script function.
L466: class DateTimeError(PydanticValueError):    Class (`DateTimeError`)    component used by
the app (see file context: None).
L470: class DateError(PydanticValueError):    Class (`DateError`)    component used by the app
(see file context: None).
L474: class DateNotInThePastError(PydanticValueError):    Class (`DateNotInThePastError`)
component used by the app (see file context: None).
L479: class DateNotInTheFutureError(PydanticValueError):    Class (`DateNotInTheFutureError`)
component used by the app (see file context: None).
L484: class TimeError(PydanticValueError):    Class (`TimeError`)    component used by the app
(see file context: None).
L488: class DurationError(PydanticValueError):    Class (`DurationError`)    component used by
the app (see file context: None).
L492: class HashableError(PydanticTypeError):    Class (`HashableError`)    component used by

```

the app (see file context: None).

L496: class UUIDError(PydanticTypeError): Class (`UUIDError`) component used by the app (see file context: None).

L500: class UUIDVersionError(PydanticValueError): Class (`UUIDVersionError`) component used by the app (see file context: None).

L504: def __init__(self, *, required_version: int) -> None: Function `\_\_init\_\_` utility or script function.

L508: class ArbitraryTypeError(PydanticTypeError): Class (`ArbitraryTypeError`) component used by the app (see file context: None).

L512: def __init__(self, *, expected_arbitrary_type: Type[Any]) -> None: Function `\_\_init\_\_` utility or script function.

L516: class ClassError(PydanticTypeError): Class (`ClassError`) component used by the app (see file context: None).

L521: class SubclassError(PydanticTypeError): Class (`SubclassError`) component used by the app (see file context: None).

L525: def __init__(self, *, expected_class: Type[Any]) -> None: Function `\_\_init\_\_` utility or script function.

L529: class JsonError(PydanticValueError): Class (`JsonError`) component used by the app (see file context: None).

L533: class JsonTypeError(PydanticTypeError): Class (`JsonTypeError`) component used by the app (see file context: None).

L538: class PatternError(PydanticValueError): Class (`PatternError`) component used by the app (see file context: None).

L543: class DataclassTypeError(PydanticTypeError): Class (`DataclassTypeError`) component used by the app (see file context: None).

L548: class CallableError(PydanticTypeError): Class (`CallableError`) component used by the app (see file context: None).

L552: class EnumError(PydanticTypeError): Class (`EnumError`) component used by the app (see file context: None).

L557: class IntEnumError(PydanticTypeError): Class (`IntEnumError`) component used by the app (see file context: None).

L562: class IPvAnyAddressError(PydanticValueError): Class (`IPvAnyAddressError`) component used by the app (see file context: None).

L566: class IPvAnyInterfaceError(PydanticValueError): Class (`IPvAnyInterfaceError`) component used by the app (see file context: None).

L570: class IPvAnyNetworkError(PydanticValueError): Class (`IPvAnyNetworkError`) component used by the app (see file context: None).

L574: class IPv4AddressError(PydanticValueError): Class (`IPv4AddressError`) component used by the app (see file context: None).

L578: class IPv6AddressError(PydanticValueError): Class (`IPv6AddressError`) component used by the app (see file context: None).

L582: class IPv4NetworkError(PydanticValueError): Class (`IPv4NetworkError`) component used by the app (see file context: None).

L586: class IPv6NetworkError(PydanticValueError): Class (`IPv6NetworkError`) component used by the app (see file context: None).

L590: class IPv4InterfaceError(PydanticValueError): Class (`IPv4InterfaceError`) component used by the app (see file context: None).

L594: class IPv6InterfaceError(PydanticValueError): Class (`IPv6InterfaceError`) component used by the app (see file context: None).

L598: class ColorError(PydanticValueError): Class (`ColorError`) component used by the app (see file context: None).

```

L602: class StrictBoolError(PydanticValueError):  Class (`StrictBoolError`) component used
by the app (see file context: None).
L606: class NotDigitError(PydanticValueError):  Class (`NotDigitError`) component used by
the app (see file context: None).
L611: class LuhnValidationError(PydanticValueError):  Class (`LuhnValidationError`)
component used by the app (see file context: None).
L616: class InvalidLengthForBrand(PydanticValueError):  Class (`InvalidLengthForBrand`)
component used by the app (see file context: None).
L621: class InvalidByteSize(PydanticValueError):  Class (`InvalidByteSize`) component used
by the app (see file context: None).
L625: class InvalidByteSizeUnit(PydanticValueError):  Class (`InvalidByteSizeUnit`)
component used by the app (see file context: None).
L629: class MissingDiscriminator(PydanticValueError):  Class (`MissingDiscriminator`)
component used by the app (see file context: None).
L634: class InvalidDiscriminator(PydanticValueError):  Class (`InvalidDiscriminator`)
component used by the app (see file context: None).
L641: def __init__(self, *, discriminator_key: str, discriminator_value: Any, allowed_values:
Sequence[Any]) -> None:  Function `__init__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/experimental/arguments_schema.py

```

L14: def generate_arguments_schema(  Function `generate_arguments_schema` Generates content
(often AI-generated).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/pydantic/experimental/pipe_line.py

```

L39: class _ValidateAs:  Class (`_ValidateAs`) component used by the app (see file context:
None).
L45: class _ValidateAsDefer:  Class (`_ValidateAsDefer`) component used by the app (see
file context: None).
L49: def tp(self) -> type[Any]:  Function `tp` utility or script function.
L54: class _Transform:  Class (`_Transform`) component used by the app (see file context:
None).
L59: class _PipelineOr:  Class (`_PipelineOr`) component used by the app (see file context:
None).
L65: class _PipelineAnd:  Class (`_PipelineAnd`) component used by the app (see file
context: None).
L71: class _Eq:  Class (`_Eq`) component used by the app (see file context: None).
L76: class _NotEq:  Class (`_NotEq`) component used by the app (see file context: None).
L81: class _In:  Class (`_In`) component used by the app (see file context: None).

```



```

L186: class _NotIn:    Class (`_NotIn`)    component used by the app (see file context: None).
L111: class _Constraint:    Class (`_Constraint`)    component used by the app (see file
context: None).
L122: class _FieldTypeMarker:    Class (`_FieldTypeMarker`)    component used by the app (see
file context: None).
L131: class _Pipeline(Generic[_InT, _OutT]):    Class (`_Pipeline`)    component used by the app
(see file context: None).
L136: def transform(    Function `transform`    utility or script function.
L148: def validate_as(self, tp: type[_NewOutT], *, strict: bool = False) -> _Pipeline[_InT,
_NewOutT]: ...    Function `validate_as`    utility or script function.
L151: def validate_as(    Function `validate_as`    utility or script function.
L161: def validate_as(self, tp: Any, *, strict: bool = ...) -> _Pipeline[_InT, Any]: ...
Function `validate_as`    utility or script function.
L163: def validate_as(self, tp: type[_NewOutT] | EllipsisType | Any, *, strict: bool = False)
-> _Pipeline[_InT, Any]: # type: ignore    Function `validate_as`    utility or script
function.
L175: def validate_as_deferred(self, func: Callable[[], type[_NewOutT]]) -> _Pipeline[_InT,
_NewOutT]:    Function `validate_as_deferred`    utility or script function.
L185: def constrain(self: _Pipeline[_InT, _NewOutGe], constraint: annotated_types.Ge) ->
_Pipeline[_InT, _NewOutGe]: ...    Function `constrain`    utility or script function.
L188: def constrain(self: _Pipeline[_InT, _NewOutGt], constraint: annotated_types.Gt) ->
_Pipeline[_InT, _NewOutGt]: ...    Function `constrain`    utility or script function.
L191: def constrain(self: _Pipeline[_InT, _NewOutLe], constraint: annotated_types.Le) ->
_Pipeline[_InT, _NewOutLe]: ...    Function `constrain`    utility or script function.
L194: def constrain(self: _Pipeline[_InT, _NewOutLt], constraint: annotated_types.Lt) ->
_Pipeline[_InT, _NewOutLt]: ...    Function `constrain`    utility or script function.
L197: def constrain(    Function `constrain`    utility or script function.
L202: def constrain(    Function `constrain`    utility or script function.
L207: def constrain(    Function `constrain`    utility or script function.
L212: def constrain(self: _Pipeline[_InT, _OutT], constraint: annotated_types.Predicate) ->
_Pipeline[_InT, _OutT]: ...    Function `constrain`    utility or script function.
L215: def constrain(    Function `constrain`    utility or script function.
L220: def constrain(self: _Pipeline[_InT, _OutT], constraint: _Eq) -> _Pipeline[_InT, _OutT]:
...    Function `constrain`    utility or script function.
L223: def constrain(self: _Pipeline[_InT, _OutT], constraint: _NotEq) -> _Pipeline[_InT,
_OutT]: ...    Function `constrain`    utility or script function.
L226: def constrain(self: _Pipeline[_InT, _OutT], constraint: _In) -> _Pipeline[_InT, _OutT]:
...    Function `constrain`    utility or script function.
L229: def constrain(self: _Pipeline[_InT, _OutT], constraint: _NotIn) -> _Pipeline[_InT,
_OutT]: ...    Function `constrain`    utility or script function.
L232: def constrain(self: _Pipeline[_InT, _NewOutT], constraint: Pattern[str]) ->
_Pipeline[_InT, _NewOutT]: ...    Function `constrain`    utility or script function.
L234: def constrain(self, constraint: _ConstraintAnnotation) -> Any:    Function `constrain`
utility or script function.
L244: def predicate(self: _Pipeline[_InT, _NewOutT], func: Callable[[ _NewOutT], bool]) ->
_Pipeline[_InT, _NewOutT]:    Function `predicate`    utility or script function.
L248: def gt(self: _Pipeline[_InT, _NewOutGt], gt: _NewOutGt) -> _Pipeline[_InT, _NewOutGt]:
    Function `gt`    utility or script function.
L252: def lt(self: _Pipeline[_InT, _NewOutLt], lt: _NewOutLt) -> _Pipeline[_InT, _NewOutLt]:
    Function `lt`    utility or script function.
L256: def ge(self: _Pipeline[_InT, _NewOutGe], ge: _NewOutGe) -> _Pipeline[_InT, _NewOutGe]:

```



```

Function `ge` utility or script function.
L260: def le(self: _Pipeline[_InT, _NewOutLe], le: _NewOutLe) -> _Pipeline[_InT, _NewOutLe]:
    Function `le` utility or script function.
L264: def len(self: _Pipeline[_InT, _NewOutLen], min_len: int, max_len: int | None = None) ->
_Pipeline[_InT, _NewOutLen]:    Function `len` utility or script function.
L269: def multiple_of(self: _Pipeline[_InT, _NewOutDiv], multiple_of: _NewOutDiv) ->
_Pipeline[_InT, _NewOutDiv]: ...    Function `multiple_of` utility or script function.
L272: def multiple_of(self: _Pipeline[_InT, _NewOutMod], multiple_of: _NewOutMod) ->
_Pipeline[_InT, _NewOutMod]: ...    Function `multiple_of` utility or script function.
L274: def multiple_of(self: _Pipeline[_InT, Any], multiple_of: Any) -> _Pipeline[_InT, Any]:
    Function `multiple_of` utility or script function.
L278: def eq(self: _Pipeline[_InT, _OutT], value: _OutT) -> _Pipeline[_InT, _OutT]:
Function `eq` utility or script function.
L282: def not_eq(self: _Pipeline[_InT, _OutT], value: _OutT) -> _Pipeline[_InT, _OutT]:
Function `not_eq` utility or script function.
L286: def in_(self: _Pipeline[_InT, _OutT], values: Container[_OutT]) -> _Pipeline[_InT,
_OutT]:    Function `in` utility or script function.
L290: def not_in(self: _Pipeline[_InT, _OutT], values: Container[_OutT]) -> _Pipeline[_InT,
_OutT]:    Function `not_in` utility or script function.
L295: def datetime_tz_naive(self: _Pipeline[_InT, datetime.datetime]) -> _Pipeline[_InT,
datetime.datetime]:    Function `datetime_tz_naive` utility or script function.
L298: def datetime_tz_aware(self: _Pipeline[_InT, datetime.datetime]) -> _Pipeline[_InT,
datetime.datetime]:    Function `datetime_tz_aware` utility or script function.
L301: def datetime_tz(    Function `datetime_tz` utility or script function.
L306: def datetime_with_tz(    Function `datetime_with_tz` utility or script function.
L312: def str_lower(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:    Function
`str_lower` utility or script function.
L315: def str_upper(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:    Function
`str_upper` utility or script function.
L318: def str_title(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:    Function
`str_title` utility or script function.
L321: def str_strip(self: _Pipeline[_InT, str]) -> _Pipeline[_InT, str]:    Function
`str_strip` utility or script function.
L324: def str_pattern(self: _Pipeline[_InT, str], pattern: str) -> _Pipeline[_InT, str]:
Function `str_pattern` utility or script function.
L327: def str_contains(self: _Pipeline[_InT, str], substring: str) -> _Pipeline[_InT, str]:
Function `str_contains` utility or script function.
L330: def str_starts_with(self: _Pipeline[_InT, str], prefix: str) -> _Pipeline[_InT, str]:
Function `str_starts_with` utility or script function.
L333: def str_ends_with(self: _Pipeline[_InT, str], suffix: str) -> _Pipeline[_InT, str]:
Function `str_ends_with` utility or script function.
L337: def otherwise(self, other: _Pipeline[_OtherIn, _OtherOut]) -> _Pipeline[_InT |
_OtherIn, _OutT | _OtherOut]:    Function `otherwise` utility or script function.
L343: def then(self, other: _Pipeline[_OutT, _OtherOut]) -> _Pipeline[_InT, _OtherOut]:
Function `then` utility or script function.
L349: def __get_pydantic_core_schema__(self, source_type: Any, handler: GetCoreSchemaHandler)
-> cs.CoreSchema:    Function `__get_pydantic_core_schema__` utility or script function.
L361: def __supports_type__(self, _: _OutT) -> bool:    Function `__supports_type__` utility
or script function.
L370: def _check_func(    Function `_check_func` utility or script function.
L373: def handler(v: Any) -> Any:    Function `handler` utility or script function.

```

```

L384: def _apply_step(step: _Step, s: cs.CoreSchema | None, handler: GetCoreSchemaHandler,
source_type: Any) -> cs.CoreSchema:  Function `_apply_step` utility or script function.
L401: def _apply_parse(  Function `_apply_parse` utility or script function.
L420: def _apply_transform(  Function `_apply_transform` utility or script function.
L443: def _apply_constraint( # noqa: C901  Function `_apply_constraint` utility or script
function.
L459: def check_gt(v: Any) -> bool:  Function `check_gt` utility or script function.
L474: def check_ge(v: Any) -> bool:  Function `check_ge` utility or script function.
L489: def check_lt(v: Any) -> bool:  Function `check_lt` utility or script function.
L504: def check_le(v: Any) -> bool:  Function `check_le` utility or script function.
L527: def check_len(v: Any) -> bool:  Function `check_len` utility or script function.
L544: def check_multiple_of(v: Any) -> bool:  Function `check_multiple_of` utility or
script function.
L557: def check_tz_aware(v: object) -> bool:  Object (singleton).
L568: def check_tz_naive(v: object) -> bool:  Object (singleton).
L590: def predicate_func(v: Any) -> Any:  Function `predicate_func` utility or script
function.
L605: def check_not_eq(v: Any) -> bool:  Function `check_not_eq` utility or script
function.
L612: def check_eq(v: Any) -> bool:  Function `check_eq` utility or script function.
L619: def check_in(v: Any) -> bool:  Function `check_in` utility or script function.
L626: def check_not_in(v: Any) -> bool:  Function `check_not_in` utility or script
function.
L637: def check_pattern(v: object) -> bool:  Object (singleton).
L645: class _SupportsRange(annotated_types.SupportsLe, annotated_types.SupportsGe, Protocol):
    Class (`_SupportsRange`) component used by the app (see file context: None).
L649: class _SupportsLen(Protocol):  Class (`_SupportsLen`) component used by the app (see
file context: None).
L650: def __len__(self) -> int: ...  Function `__len__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/_distutils_hack/__init__.py

```

L10: def warn_distutils_present():  Function `warn_distutils_present` utility or script
function.
L25: def clear_distutils():  Function `clear_distutils` utility or script function.
L45: def enabled():  Function `enabled` utility or script function.
L63: def ensure_local_distutils():  Function `ensure_local_distutils` utility or script
function.
L80: def do_override():  Function `do_override` utility or script function.
L92: class _TrivialRe:  Class (`_TrivialRe`) component used by the app (see file context:
None).
L93: def __init__(self, *patterns) -> None:  Function `__init__` utility or script
function.
L96: def match(self, string):  Function `match` utility or script function.
L100: class DistutilsMetaFinder:  Class (`DistutilsMetaFinder`) component used by the app
(see file context: None).
L101: def find_spec(self, fullname, path, target=None):  Function `find_spec` utility or

```

```

script function.
L111: def spec_for_distutils(self):    Function `spec_for_distutils` utility or script
function.
L132: class DistutilsLoader(importlib.abc.Loader):    Class (`DistutilsLoader`) component
used by the app (see file context: None).
L133: def create_module(self, spec):    Function `create_module` Creates a resource or
document.
L137: def exec_module(self, module):    Function `exec_module` utility or script function.
L145: def is_cpython():    Function `is_cpython` utility or script function.
L152: def spec_for_pip(self):    Function `spec_for_pip` utility or script function.
L163: def pip_imported_during_build(cls):    Function `pip_imported_during_build` utility or
script function.
L174: def frame_file_is_setup(frame):    Function `frame_file_is_setup` utility or script
function.
L181: def spec_for_sensitive_tests(self):    Function `spec_for_sensitive_tests` utility or
script function.
L214: def add_shim():    Function `add_shim` utility or script function.
L218: class shim:    Class (`shim`) component used by the app (see file context: None).
L219: def __enter__(self) -> None:    Function `__enter__` utility or script function.
L222: def __exit__(self, exc: object, value: object, tb: object) -> None:    Object
(singleton).
L226: def insert_shim():    Function `insert_shim` utility or script function.
L230: def _remove_shim():    Function `_remove_shim` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/compat.py

```

L37: def _resolve_char_detection() -> ModuleType | None:    Function `_resolve_char_detection`
utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/hooks.py

```

L25: def default_hooks() -> dict[str, list[_t.HookType]]:    Function `default_hooks` utility
or script function.
L32: def dispatch_hook(    Function `dispatch_hook` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/models.py

```

L109: class RequestEncodingMixin:    Class (`RequestEncodingMixin`) component used by the app
(see file context: None).
L113: def path_url(self) -> str:    Function `path_url` utility or script function.
L135: def _encode_params(data: str) -> str: ...    Function `_encode_params` utility or

```

```

script function.
L139: def _encode_params(data: bytes) -> bytes: ... Function `_encode_params` utility or
script function.
L143: def _encode_params( Function `_encode_params` utility or script function.
L149: def _encode_params(data: _t.KVDataType) -> str: ... Function `_encode_params`
utility or script function.
L152: def _encode_params( Function `_encode_params` utility or script function.
L184: def _encode_files( Function `_encode_files` utility or script function.
L255: class RequestHooksMixin: Class (`RequestHooksMixin`) component used by the app (see
file context: None).
L258: def register_hook( Function `register_hook` utility or script function.
L271: def deregister_hook(self, event: str, hook: _t.HookType) -> bool: Function
`deregister_hook` utility or script function.
L283: class Request(RequestHooksMixin): Class (`Request`) component used by the app (see
file context: None).
L321: def __init__( Function `__init__` utility or script function.
L355: def __repr__(self) -> str: Function `__repr__` utility or script function.
L358: def prepare(self) -> PreparedRequest: Function `prepare` utility or script function.
L376: class PreparedRequest(RequestEncodingMixin, RequestHooksMixin): Class
(`PreparedRequest`) component used by the app (see file context: None).
L405: def __init__(self) -> None: Function `__init__` utility or script function.
L422: def prepare( Function `prepare` utility or script function.
L451: def __repr__(self) -> str: Function `__repr__` utility or script function.
L454: def copy(self) -> PreparedRequest: Function `copy` utility or script function.
L465: def prepare_method(self, method: str | None) -> None: Function `prepare_method`
utility or script function.
L472: def _get_idna_encoded_host(host: str) -> str: Function `_get_idna_encoded_host`
utility or script function.
L481: def prepare_url( Function `prepare_url` utility or script function.
L563: def prepare_headers(self, headers: Mapping[str, str | bytes] | None) -> None:
Function `prepare_headers` utility or script function.
L574: def prepare_body( Function `prepare_body` utility or script function.
L652: def prepare_content_length(self, body: _t.BodyType) -> None: Function
`prepare_content_length` utility or script function.
L668: def prepare_auth( Function `prepare_auth` utility or script function.
L697: def prepare_cookies( Function `prepare_cookies` utility or script function.
L720: def prepare_hooks(self, hooks: _t.HooksInputType | None) -> None: Function
`prepare_hooks` utility or script function.
L730: class Response: Class (`Response`) component used by the app (see file context:
None).
L763: def __init__(self) -> None: Function `__init__` utility or script function.
L810: def __enter__(self) -> Self: Function `__enter__` utility or script function.
L813: def __exit__(self, *args: Any) -> None: Function `__exit__` utility or script
function.
L816: def __getstate__(self) -> dict[str, Any]: Function `__getstate__` utility or script
function.
L824: def __setstate__(self, state: dict[str, Any]) -> None: Function `__setstate__`
utility or script function.
L832: def __repr__(self) -> str: Function `__repr__` utility or script function.
L835: def __bool__(self) -> bool: Function `__bool__` utility or script function.
L845: def __nonzero__(self) -> bool: Function `__nonzero__` utility or script function.

```

```

L855: def __iter__(self) -> Iterator[bytes]:    Function `__iter__`    utility or script
function.
L860: def ok(self) -> bool:    Function `ok`    utility or script function.
L875: def is_redirect(self) -> bool:    Function `is_redirect`    utility or script function.
L882: def is_permanent_redirect(self) -> bool:    Function `is_permanent_redirect`    utility or
script function.
L890: def next(self) -> PreparedRequest | None:    Function `next`    utility or script
function.
L895: def apparent_encoding(self) -> str | None:    Function `apparent_encoding`    utility or
script function.
L905: def iter_content(    Function `iter_content`    utility or script function.
L909: def iter_content(    Function `iter_content`    utility or script function.
L912: def iter_content(    Function `iter_content`    utility or script function.
L933: def generate() -> Generator[bytes, None, None]:    Function `generate`    Generates
content (often AI-generated).
L976: def iter_lines(    Function `iter_lines`    utility or script function.
L983: def iter_lines(    Function `iter_lines`    utility or script function.
L990: def iter_lines(    Function `iter_lines`    utility or script function.
L1031: def content(self) -> bytes:    Function `content`    utility or script function.
L1050: def text(self) -> str:    Function `text`    utility or script function.
L1087: def json(self, **kwargs: Any) -> Any:    Function `json`    utility or script function.
L1123: def links(self) -> dict[str, dict[str, str]]:    Function `links`    utility or script
function.
L1140: def raise_for_status(self) -> None:    Function `raise_for_status`    utility or script
function.
L1169: def close(self) -> None:    Function `close`    utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/help.py

```

L37: def _implementation():    Function `_implementation`    utility or script function.
L69: def info() -> dict[str, Any]:    Function `info`    utility or script function.
L128: def main():    Function `main`    Entry point / main routine.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/api.py

```

L24: def request(    Function `request`    utility or script function.
L74: def get(    Function `get`    Returns or fetches data.
L90: def options(url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:    Function
`options`    utility or script function.
L102: def head(url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:    Function
`head`    utility or script function.
L117: def post(    Function `post`    utility or script function.
L137: def put(    Function `put`    utility or script function.
L154: def patch(    Function `patch`    utility or script function.
L171: def delete(url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:    Function
`delete`    Deletes a resource.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/exceptions.py

```

L20: class RequestException(IOError):    Class (`RequestException`) component used by the app
(see file context: None).
L28: def __init__(self, *args: Any, **kwargs: Any) -> None:    Function `__init__` utility or
script function.
L38: class InvalidJSONError(RequestException):    Class (`InvalidJSONError`) component used
by the app (see file context: None).
L42: class JSONDecodeError(InvalidJSONError, CompatJSONDecodeError):    Class
(`JSONDecodeError`) component used by the app (see file context: None).
L45: def __init__(self, *args: Any, **kwargs: Any) -> None:    Function `__init__` utility or
script function.
L55: def __reduce__(self) -> tuple[Any, ...] | str:    Function `__reduce__` utility or
script function.
L66: class HTTPError(RequestException):    Class (`HTTPError`) component used by the app (see
file context: None).
L70: class ConnectionError(RequestException):    Class (`ConnectionError`) component used by
the app (see file context: None).
L74: class ProxyError(ConnectionError):    Class (`ProxyError`) component used by the app
(see file context: None).
L78: class SSLError(ConnectionError):    Class (`SSLError`) component used by the app (see
file context: None).
L82: class Timeout(RequestException):    Class (`Timeout`) component used by the app (see
file context: None).
L91: class ConnectTimeout(ConnectionError, Timeout):    Class (`ConnectTimeout`) component
used by the app (see file context: None).
L98: class ReadTimeout(Timeout):    Class (`ReadTimeout`) component used by the app (see file
context: None).
L102: class URLRequired(RequestException):    Class (`URLRequired`) component used by the app
(see file context: None).
L106: class TooManyRedirects(RequestException):    Class (`TooManyRedirects`) component used
by the app (see file context: None).
L110: class MissingSchema(RequestException, ValueError):    Class (`MissingSchema`) component
used by the app (see file context: None).
L114: class InvalidSchema(RequestException, ValueError):    Class (`InvalidSchema`) component
used by the app (see file context: None).
L118: class InvalidURL(RequestException, ValueError):    Class (`InvalidURL`) component used
by the app (see file context: None).
L122: class InvalidHeader(RequestException, ValueError):    Class (`InvalidHeader`) component
used by the app (see file context: None).
L126: class InvalidProxyURL(InvalidURL):    Class (`InvalidProxyURL`) component used by the
app (see file context: None).
L130: class ChunkedEncodingError(RequestException):    Class (`ChunkedEncodingError`)
component used by the app (see file context: None).
L134: class ContentDecodingError(RequestException, BaseHTTPError):    Class
(`ContentDecodingError`) component used by the app (see file context: None).
L138: class StreamConsumedError(RequestException, TypeError):    Class (`StreamConsumedError`)
component used by the app (see file context: None).

```

```

L142: class RetryError(RequestException):    Class (`RetryError`)    component used by the app
(see file context: None).
L146: class UnrewindableBodyError(RequestException):    Class (`UnrewindableBodyError`)
component used by the app (see file context: None).
L153: class RequestsWarning(Warning):    Class (`RequestsWarning`)    component used by the app
(see file context: None).
L157: class FileModeWarning(RequestsWarning, DeprecationWarning):    Class (`FileModeWarning`)
component used by the app (see file context: None).
L161: class RequestsDependencyWarning(RequestsWarning):    Class (`RequestsDependencyWarning`)
component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/__init__.py

```

L60: def check_compatibility(    Function `check_compatibility`    utility or script function.
L99: def _check_cryptography(cryptography_version: str) -> None:    Function
`_check_cryptography`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/sessions.py

```

L76: def merge_setting(    Function `merge_setting`    utility or script function.
L108: def merge_hooks(    Function `merge_hooks`    utility or script function.
L127: class SessionRedirectMixin:    Class (`SessionRedirectMixin`)    component used by the app
(see file context: None).
L132: def send(self, request: PreparedRequest, **kwargs: Any) -> Response: ...    Function
`send`    utility or script function.
L134: def get_redirect_target(self, resp: Response) -> str | None:    Function
`get_redirect_target`    Returns or fetches data.
L154: def should_strip_auth(self, old_url: str, new_url: str) -> bool:    Function
`should_strip_auth`    utility or script function.
L186: def resolve_redirects(    Function `resolve_redirects`    utility or script function.
L309: def rebuild_auth(    Function `rebuild_auth`    utility or script function.
L334: def rebuild_proxies(    Function `rebuild_proxies`    utility or script function.
L370: def rebuild_method(    Function `rebuild_method`    utility or script function.
L395: class Session(SessionRedirectMixin):    Class (`Session`)    component used by the app
(see file context: None).
L442: def __init__(self) -> None:    Function `__init__`    utility or script function.
L505: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L508: def __exit__(self, *args: Any) -> None:    Function `__exit__`    utility or script
function.
L511: def prepare_request(self, request: Request) -> PreparedRequest:    Function
`prepare_request`    utility or script function.
L557: def request(    Function `request`    utility or script function.
L655: def get(    Function `get`    Returns or fetches data.

```



```

L673: def options(self, url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
Function `options` utility or script function.
L684: def head(self, url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
Function `head` utility or script function.
L695: def post( Function `post` utility or script function.
L714: def put( Function `put` utility or script function.
L728: def patch( Function `patch` utility or script function.
L742: def delete(self, url: _t.UriType, **kwargs: Unpack[_t.RequestKwargs]) -> Response:
Function `delete` Deletes a resource.
L752: def send(self, request: PreparedRequest, **kwargs: Any) -> Response: Function `send`
utility or script function.
L831: def merge_environment_settings( Function `merge_environment_settings` utility or
script function.
L870: def get_adapter(self, url: str) -> BaseAdapter: Function `get_adapter` Returns or
fetches data.
L883: def close(self) -> None: Function `close` utility or script function.
L888: def mount(self, prefix: str, adapter: BaseAdapter) -> None: Function `mount` utility
or script function.
L899: def __getstate__(self) -> dict[str, Any]: Function `__getstate__` utility or script
function.
L903: def __setstate__(self, state: dict[str, Any]) -> None: Function `__setstate__`
utility or script function.
L908: def session() -> Session: Function `session` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/requests/utils.py

```

L99: def proxy_bypass_registry(host: str) -> bool: Function `proxy_bypass_registry`
utility or script function.
L137: def proxy_bypass(host: str) -> bool: # noqa Function `proxy_bypass` utility or
script function.
L149: def dict_to_sequence( Function `dict_to_sequence` utility or script function.
L160: def super_len(o: Any) -> int: Function `super_len` utility or script function.
L231: def get_netrc_auth( Function `get_netrc_auth` Returns or fetches data.
L283: def guess_filename(obj: Any) -> str | None: Function `guess_filename` utility or
script function.
L290: def extract_zipped_paths(path: str) -> str: Function `extract_zipped_paths` utility
or script function.
L329: def atomic_open(filename: str) -> Generator[BufferedWriter, None, None]: Function
`atomic_open` utility or script function.
L341: def from_key_val_list( Function `from_key_val_list` utility or script function.
L371: def to_key_val_list(value: None) -> None: ... Function `to_key_val_list` utility or
script function.
L373: def to_key_val_list( Function `to_key_val_list` utility or script function.
L376: def to_key_val_list( Function `to_key_val_list` utility or script function.
L408: def parse_list_header(value: str) -> list[str]: Function `parse_list_header` utility
or script function.
L440: def parse_dict_header(value: str) -> dict[str, str | None]: Function
`parse_dict_header` utility or script function.

```



```

L475: def unquote_header_value(value: str, is_filename: bool = False) -> str:    Function
`unquote_header_value`    utility or script function.
L500: def dict_from_cookiejar(cj: CookieJar) -> dict[str, str | None]:    Function
`dict_from_cookiejar`    utility or script function.
L511: def add_dict_to_cookiejar(cj: CookieJar, cookie_dict: dict[str, str]) -> CookieJar:
Function `add_dict_to_cookiejar`    utility or script function.
L522: def get_encodings_from_content(content: str) -> list[str]:    Function
`get_encodings_from_content`    Returns or fetches data.
L547: def _parse_content_type_header(header: str) -> tuple[str, dict[str, Any]]:    Function
`_parse_content_type_header`    utility or script function.
L569: def get_encoding_from_headers(headers: CaseInsensitiveDict[str]) -> str | None:
Function `get_encoding_from_headers`    Returns or fetches data.
L594: def stream_decode_response_unicode(    Function `stream_decode_response_unicode`
utility or script function.
L614: def iter_slices(    Function `iter_slices`    utility or script function.
L618: def iter_slices(    Function `iter_slices`    utility or script function.
L621: def iter_slices(    Function `iter_slices`    utility or script function.
L633: def get_unicode_from_response(r: Response) -> str | bytes | None:    Function
`get_unicode_from_response`    Returns or fetches data.
L680: def unquote_unreserved(uri: str) -> str:    Function `unquote_unreserved`    utility or
script function.
L704: def requote_uri(uri: str) -> str:    Function `requote_uri`    utility or script function.
L726: def address_in_network(ip: str, net: str) -> bool:    Function `address_in_network`
utility or script function.
L741: def dotted_netmask(mask: int) -> str:    Function `dotted_netmask`    utility or script
function.
L752: def is_ipv4_address(string_ip: str) -> bool:    Function `is_ipv4_address`    utility or
script function.
L763: def is_valid_cidr(string_network: str) -> bool:    Function `is_valid_cidr`    utility or
script function.
L788: def set_environ(env_name: str, value: str | None) -> Generator[None, None, None]:
Function `set_environ`    Sets or updates a value.
L810: def should_bypass_proxies(url: str, no_proxy: str | None) -> bool:    Function
`should_bypass_proxies`    utility or script function.
L819: def get_proxy(key: str) -> str | None:    Function `get_proxy`    Returns or fetches data.
L873: def get_environ_proxies(url: str, no_proxy: str | None = None) -> dict[str, str]:
Function `get_environ_proxies`    Returns or fetches data.
L885: def select_proxy(url: str, proxies: dict[str, str] | None) -> str | None:    Function
`select_proxy`    utility or script function.
L911: def resolve_proxies(    Function `resolve_proxies`    utility or script function.
L942: def default_user_agent(name: str = "python-requests") -> str:    Function
`default_user_agent`    utility or script function.
L951: def default_headers() -> CaseInsensitiveDict[str]:    Function `default_headers`
utility or script function.
L965: def parse_header_links(value: str) -> list[dict[str, str]]:    Function
`parse_header_links`    utility or script function.
L1008: def guess_json_utf(data: bytes) -> str | None:    Function `guess_json_utf`    utility or
script function.
L1040: def prepend_scheme_if_needed(url: str, new_scheme: str) -> str:    Function
`prepend_scheme_if_needed`    utility or script function.
L1070: def get_auth_from_url(url: str) -> tuple[str, str]:    Function `get_auth_from_url`

```

Returns or fetches data.

L1087: def check_header_validity(header: tuple[str | bytes, str | bytes]) -> None: Function `check\_header\_validity` utility or script function.

L1098: def _validate_header_part(Function `\_validate\_header\_part` utility or script function.

L1122: def urldefragauth(url: str) -> str: Function `urldefragauth` utility or script function.

L1139: def rewind_body(prepared_request: PreparedRequest) -> None: Function `rewind\_body` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/_internal_utils.py

L26: def to_native_string(string: str | bytes, encoding: str = "ascii") -> str: Function `to\_native\_string` utility or script function.

L39: def unicode_is_ascii(u_string: str) -> bool: Function `unicode\_is\_ascii` utility or script function.

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/cookies.py

L31: class MockRequest: Class (`MockRequest`) component used by the app (see file context: None).

L45: def __init__(self, request: PreparedRequest) -> None: Function `\_\_init\_\_` utility or script function.

L51: def get_type(self) -> str: Function `get\_type` Returns or fetches data.

L54: def get_host(self) -> str: Function `get\_host` Returns or fetches data.

L57: def get_origin_req_host(self) -> str: Function `get\_origin\_req\_host` Returns or fetches data.

L60: def get_full_url(self) -> str: Function `get\_full\_url` Returns or fetches data.

L80: def is_unverifiable(self) -> bool: Function `is\_unverifiable` utility or script function.

L83: def has_header(self, name: str) -> bool: Function `has\_header` utility or script function.

L86: def get_header(self, name: str, default: str | None = None) -> str | None: Function `get\_header` Returns or fetches data.

L89: def add_header(self, key: str, val: str) -> None: Function `add\_header` utility or script function.

L95: def add_unredirected_header(self, name: str, value: str) -> None: Function `add\_unredirected\_header` utility or script function.

L98: def get_new_headers(self) -> dict[str, str]: Function `get\_new\_headers` Returns or fetches data.

L102: def unverifiable(self) -> bool: Function `unverifiable` utility or script function.

L106: def origin_req_host(self) -> str: Function `origin\_req\_host` utility or script function.

```

L110: def host(self) -> str:    Function `host`    utility or script function.
L114: class MockResponse:    Class (`MockResponse`)    component used by the app (see file
context: None).
L121: def __init__(self, headers: Any) -> None:    Function `__init__`    utility or script
function.
L128: def info(self) -> Any:    Function `info`    utility or script function.
L131: def getheaders(self, name: str) -> Any:    Function `getheaders`    Returns or fetches
data.
L135: def extract_cookies_to_jar(    Function `extract_cookies_to_jar`    utility or script
function.
L153: def get_cookie_header(jar: CookieJar, request: PreparedRequest) -> str | None:
Function `get_cookie_header`    Returns or fetches data.
L164: def remove_cookie_by_name(    Function `remove_cookie_by_name`    utility or script
function.
L185: class CookieConflictError(RuntimeError):    Class (`CookieConflictError`)    component
used by the app (see file context: None).
L191: class RequestsCookieJar(CookieJar, MutableMapping[str, str | None]): # type:
ignore[misc]    Class (`RequestsCookieJar`)    component used by the app (see file context:
None).
L211: def get( # type: ignore[override]    Function `get`    Returns or fetches data.
L229: def set(    Function `set`    Sets or updates a value.
L250: def iterkeys(self) -> Iterator[str]:    Function `iterkeys`    utility or script function.
L259: def keys(self) -> list[str]: # type: ignore[override]    Function `keys`    utility or
script function.
L267: def intervalues(self) -> Iterator[str | None]:    Function `intervalues`    utility or
script function.
L276: def values(self) -> list[str | None]: # type: ignore[override]    Function `values`
utility or script function.
L284: def iteritems(self) -> Iterator[tuple[str, str | None]]:    Function `iteritems`
utility or script function.
L293: def items(self) -> list[tuple[str, str | None]]: # type: ignore[override]    Function
`items`    utility or script function.
L302: def list_domains(self) -> list[str]:    Function `list_domains`    utility or script
function.
L310: def list_paths(self) -> list[str]:    Function `list_paths`    utility or script function.
L318: def multiple_domains(self) -> bool:    Function `multiple_domains`    utility or script
function.
L331: def get_dict(    Function `get_dict`    Returns or fetches data.
L348: def __iter__(self) -> Iterator[Cookie]: # type: ignore[override]    Function `__iter__`
utility or script function.
L352: def __contains__(self, name: object) -> bool:    Object (singleton).
L358: def __getitem__(self, name: str) -> str | None:    Function `__getitem__`    utility or
script function.
L367: def __setitem__(    Function `__setitem__`    utility or script function.
L376: def __delitem__(self, name: str) -> None:    Function `__delitem__`    utility or script
function.
L382: def set_cookie(self, cookie: Cookie, *args: Any, **kwargs: Any) -> None:    Function
`set_cookie`    Sets or updates a value.
L391: def update( # type: ignore[override]    Function `update`    utility or script function.
L401: def _find(    Function `_find`    utility or script function.
L423: def _find_no_duplicates(    Function `_find_no_duplicates`    utility or script function.

```

```

L454: def __getstate__(self) -> dict[str, Any]:    Function `__getstate__`    utility or script
function.
L461: def __setstate__(self, state: dict[str, Any]) -> None:    Function `__setstate__`
utility or script function.
L467: def copy(self) -> RequestsCookieJar:    Function `copy`    utility or script function.
L474: def get_policy(self) -> CookiePolicy:    Function `get_policy`    Returns or fetches data.
L479: def _copy_cookie_jar(jar: CookieJar | None) -> CookieJar | None:    # type:
ignore[reportUnusedFunction]    # cross-module usage in models.py    Function `_copy_cookie_jar`
utility or script function.
L494: def create_cookie(name: str, value: str, **kwargs: Any) -> Cookie:    Function
`create_cookie`    Creates a resource or document.
L531: def morsel_to_cookie(morsel: Morsel[Any]) -> Cookie:    Function `morsel_to_cookie`
utility or script function.
L564: def cookiejar_from_dict(    Function `cookiejar_from_dict`    utility or script function.
L572: def cookiejar_from_dict(    Function `cookiejar_from_dict`    utility or script function.
L579: def cookiejar_from_dict(    Function `cookiejar_from_dict`    utility or script function.
L604: def merge_cookies(    Function `merge_cookies`    utility or script function.

```

Q_base appwrite/venv/lib/python3.12/site-packages/requests/auth.py

```

L134: def _basic_auth_str(username: bytes | str, password: bytes | str) -> str:    Function
`_basic_auth_str`    utility or script function.
L178: class AuthBase:    Authentication component (`AuthBase`)    handles user authentication
flows.
L181: def __call__(self, r: PreparedRequest) -> PreparedRequest:    Function `__call__`
utility or script function.
L185: class HTTPBasicAuth(AuthBase):    Authentication component (`HTTPBasicAuth`)    handles
user authentication flows.
L192: def __init__(self, username: str, password: str) -> None: ...    Function `__init__`
utility or script function.
L194: def __init__(self, username: bytes, password: bytes) -> None: ...    Function `__init__`
utility or script function.
L196: def __init__(self, username: bytes | str, password: bytes | str) -> None:    Function
`__init__`    utility or script function.
L100: def __eq__(self, other: object) -> bool:    Object (singleton).
L108: def __ne__(self, other: Any) -> bool:    Function `__ne__`    utility or script function.
L111: def __call__(self, r: PreparedRequest) -> PreparedRequest:    Function `__call__`
utility or script function.
L116: class HTTPProxyAuth(HTTPBasicAuth):    Authentication component (`HTTPProxyAuth`)
handles user authentication flows.
L119: def __call__(self, r: PreparedRequest) -> PreparedRequest:    Function `__call__`
utility or script function.
L124: class HTTPDigestAuth(AuthBase):    Authentication component (`HTTPDigestAuth`)    handles
user authentication flows.
L137: def __init__(self, username: str, password: str) -> None: ...    Function `__init__`
utility or script function.
L139: def __init__(self, username: bytes, password: bytes) -> None: ...    Function `__init__`
utility or script function.

```

```

L141: def __init__(self, username: bytes | str, password: bytes | str) -> None:    Function
`__init__`    utility or script function.
L147: def init_per_thread_state(self) -> None:    Function `init_per_thread_state`
Initialisation routine.
L157: def build_digest_header(self, method: str, url: str) -> str | None:    Function
`build_digest_header`    Constructs or prepares an object.
L176: def md5_utf8(x: str | bytes) -> str:    Function `md5_utf8`    utility or script function.
L184: def sha_utf8(x: str | bytes) -> str:    Function `sha_utf8`    utility or script function.
L192: def sha256_utf8(x: str | bytes) -> str:    Function `sha256_utf8`    utility or script
function.
L200: def sha512_utf8(x: str | bytes) -> str:    Function `sha512_utf8`    utility or script
function.
L210: def KD(s: str, d: str) -> str:    Function `KD`    utility or script function.
L268: def handle_redirect(self, r: Response, **kwargs: Any) -> None:    Function
`handle_redirect`    utility or script function.
L273: def handle_401(self, r: Response, **kwargs: Any) -> Response:    Function `handle_401`
utility or script function.
L321: def __call__(self, r: PreparedRequest) -> PreparedRequest:    Function `__call__`
utility or script function.
L345: def __eq__(self, other: object) -> bool:    Object (singleton).
L353: def __ne__(self, other: Any) -> bool:    Function `__ne__`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/adapters.py

```

L66: def SOCKSProxyManager(*args: Any, **kwargs: Any) -> None:    Function `SOCKSProxyManager`
utility or script function.
L85: def _urllib3_request_context(    Function `_urllib3_request_context`    utility or script
function.
L122: class BaseAdapter:    Class (`BaseAdapter`)    component used by the app (see file
context: None).
L125: def __init__(self) -> None:    Function `__init__`    utility or script function.
L128: def send(    Function `send`    utility or script function.
L153: def close(self) -> None:    Function `close`    utility or script function.
L158: class HTTPAdapter(BaseAdapter):    Class (`HTTPAdapter`)    component used by the app (see
file context: None).
L201: def __init__(    Function `__init__`    utility or script function.
L223: def __getstate__(self) -> dict[str, Any]:    Function `__getstate__`    utility or script
function.
L226: def __setstate__(self, state: dict[str, Any]) -> None:    Function `__setstate__`
utility or script function.
L239: def init_poolmanager(    Function `init_poolmanager`    Initialisation routine.
L269: def proxy_manager_for(self, proxy: str, **proxy_kwargs: Any) -> Any:    Function
`proxy_manager_for`    utility or script function.
L307: def cert_verify(    Function `cert_verify`    utility or script function.
L365: def build_response(self, req: PreparedRequest, resp: Any) -> Response:    Function
`build_response`    Constructs or prepares an object.
L403: def build_connection_pool_key_attributes(    Function

```

```

`build_connection_pool_key_attributes` Constructs or prepares an object.
L455: def get_connection_with_tls_context( Function `get_connection_with_tls_context`
Returns or fetches data.
L512: def get_connection( Function `get_connection` Returns or fetches data.
L555: def close(self) -> None: Function `close` utility or script function.
L565: def request_url( Function `request_url` utility or script function.
L599: def add_headers(self, request: PreparedRequest, **kwargs: Any) -> None: Function
`add_headers` utility or script function.
L613: def proxy_headers(self, proxy: str) -> dict[str, str]: Function `proxy_headers`
utility or script function.
L634: def send( Function `send` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/structures.py

```

L20: class CaseInsensitiveDict(MutableMapping[str, _VT], Generic[_VT]): Class
(`CaseInsensitiveDict`) component used by the app (see file context: None).
L49: def __init__( Function `__init__` utility or script function.
L59: def __setitem__(self, key: str, value: _VT) -> None: Function `__setitem__` utility
or script function.
L64: def __getitem__(self, key: str) -> _VT: Function `__getitem__` utility or script
function.
L67: def __delitem__(self, key: str) -> None: Function `__delitem__` utility or script
function.
L70: def __iter__(self) -> Iterator[str]: Function `__iter__` utility or script function.
L73: def __len__(self) -> int: Function `__len__` utility or script function.
L76: def lower_items(self) -> Iterator[tuple[str, _VT]]: Function `lower_items` utility or
script function.
L80: def __eq__(self, other: object) -> bool: Object (singleton).
L89: def copy(self) -> CaseInsensitiveDict[_VT]: Function `copy` utility or script
function.
L92: def __repr__(self) -> str: Function `__repr__` utility or script function.
L96: class LookupDict(dict[str, _VT]): Class (`LookupDict`) component used by the app (see
file context: None).
L101: def __init__(self, name: Any = None) -> None: Function `__init__` utility or script
function.
L105: def __repr__(self) -> str: Function `__repr__` utility or script function.
L108: def __getattr__(self, key: str) -> _VT | None: Function `__getattr__` utility or
script function.
L118: def __getitem__(self, key: str) -> _VT | None: # type: ignore[override] Function
`__getitem__` utility or script function.
L124: def get(self, key: str, default: None = None) -> _VT | None: ... Function `get`
Returns or fetches data.
L127: def get(self, key: str, default: _D | _VT) -> _D | _VT: ... Function `get` Returns
or fetches data.
L129: def get(self, key: str, default: _D | None = None) -> _VT | _D | None: Function `get`
Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/_types.py

```

L28: class SupportsRead(Protocol[_T_co]):    Class (`SupportsRead`) component used by the app
(see file context: None).
L29: def read(self, length: int = ..., /) -> _T_co: ...    Function `read` utility or script
function.
L33: class SupportsItems(Protocol[_KT_co, _VT_co]):    Class (`SupportsItems`) component used
by the app (see file context: None).
L34: def items(self) -> Iterable[tuple[_KT_co, _VT_co]]: ...    Function `items` utility or
script function.
L42: def is_prepared(request: PreparedRequest) -> TypeIs[_ValidatedRequest]:    Function
`is_prepared` utility or script function.
L64: class _ValidatedRequest(PreparedRequest):    Class (`_ValidatedRequest`) component used
by the app (see file context: None).
L152: class BaseRequestKwargs(TypedDict, total=False):    Class (`BaseRequestKwargs`)
component used by the app (see file context: None).
L165: class RequestKwargs(BaseRequestKwargs, total=False):    Class (`RequestKwargs`)
component used by the app (see file context: None).
L172: class GetKwargs(BaseRequestKwargs, total=False):    Class (`GetKwargs`) component used
by the app (see file context: None).
L176: class PostKwargs(BaseRequestKwargs, total=False):    Class (`PostKwargs`) component
used by the app (see file context: None).
L179: class DataKwargs(BaseRequestKwargs, total=False):    Class (`DataKwargs`) component
used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/requests/status_codes.py

```

L109: def _init():    Function `_init` utility or script function.
L116: def doc(code: int) -> str:    Function `doc` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_bdist_wheel.py

```

L50: def safe_name(name: str) -> str:    Function `safe_name` utility or script function.
L57: def safe_version(version: str) -> str:    Function `safe_version` utility or script
function.
L74: def _is_32bit_interpreter() -> bool:    Function `_is_32bit_interpreter` utility or
script function.
L78: def python_tag() -> str:    Function `python_tag` utility or script function.
L82: def get_platform(archive_root: str | None) -> str:    Function `get_platform` Returns or
fetches data.
L102: def get_flag(    Function `get_flag` Returns or fetches data.

```

```

L119: def get_abi_tag() -> str | None:    Function `get_abi_tag` Returns or fetches data.
L159: def safer_name(name: str) -> str:    Function `safer_name` utility or script function.
L163: def safer_version(version: str) -> str:    Function `safer_version` utility or script
function.
L167: def remove_readonly(    Function `remove_readonly` utility or script function.
L175: def remove_readonly_exc(func: Callable[..., object], path: str, exc: Exception) ->
None:    Object (singleton).
L180: class bdist_wheel(Command):    Class (`bdist_wheel`) component used by the app (see
file context: None).
L248: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L269: def finalize_options(self):    Function `finalize_options` utility or script function.
L313: def wheel_dist_name(self):    Function `wheel_dist_name` utility or script function.
L323: def get_tag(self) -> tuple[str, str, str]:    Function `get_tag` Returns or fetches
data.
L381: def run(self):    Function `run` utility or script function.
L471: def write_wheelfile(    Function `write_wheelfile` utility or script function.
L495: def _ensure_relative(self, path: str) -> str:    Function `_ensure_relative` utility or
script function.
L503: def license_paths(self) -> Iterable[str]:    Function `license_paths` utility or script
function.
L547: def egg2dist(self, egginfo_path: str, distinfo_path: str):    Function `egg2dist`
utility or script function.
L550: def adios(p: str) -> None:    Function `adios` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_metadata.py

```

L20: def _nonblank(str: str) -> bool | Literal[""]:    Function `_nonblank` utility or script
function.
L25: def yield_lines(iterable: Iterable[str]) -> Iterator[str]:    Function `yield_lines`
utility or script function.
L43: def _(text: str) -> Iterator[str]:    Function `_` utility or script function.
L47: def split_sections(    Function `split_sections` utility or script function.
L74: def safe_extra(extra: str) -> str:    Function `safe_extra` utility or script function.
L82: def safe_name(name: str) -> str:    Function `safe_name` utility or script function.
L89: def requires_to_requires_dist(requirement: Requirement) -> str:    Function
`requires_to_requires_dist` utility or script function.
L104: def convert_requirements(requirements: list[str]) -> Iterator[str]:    Function
`convert_requirements` utility or script function.
L116: def generate_requirements(    Function `generate_requirements` Generates content (often
AI-generated).
L147: def pkginfo_to_metadata(egg_info_path: str, pkginfo_path: str) -> Message:    Function
`pkginfo_to_metadata` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/__main__.py

```
L11: def main() -> NoReturn: # needed for console script    Function `main`    Entry point /
main routine.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/macosx_libfile.py

```
L252: def swap32(x: int) -> int:    Function `swap32`    utility or script function.
L261: def get_base_class_and_magic_number(    Function `get_base_class_and_magic_number`
Returns or fetches data.
L288: def read_data(struct_class: type[ctypes.Structure], lib_file: BufferedIOBase):
Function `read_data`    utility or script function.
L292: def extract_macosx_min_system_version(path_to_lib: str):    Function
`extract_macosx_min_system_version`    utility or script function.
L300: class FatHeader(BaseClass):    Class (`FatHeader`)    component used by the app (see file
context: None).
L306: class FatArch(BaseClass):    Class (`FatArch`)    component used by the app (see file
context: None).
L311: class FatArch(BaseClass):    Class (`FatArch`)    component used by the app (see file
context: None).
L350: def read_mach_header(    Function `read_mach_header`    utility or script function.
L363: class SegmentBase(base_class):    Class (`SegmentBase`)    component used by the app (see
file context: None).
L368: class MachHeader(base_class):    Class (`MachHeader`)    component used by the app (see
file context: None).
L373: class MachHeader(base_class):    Class (`MachHeader`)    component used by the app (see
file context: None).
L383: class VersionMinCommand(base_class):    Class (`VersionMinCommand`)    component used by
the app (see file context: None).
L390: class VersionBuild(base_class):    Class (`VersionBuild`)    component used by the app
(see file context: None).
L400: def parse_version(version: int) -> tuple[int, int, int]:    Function `parse_version`
utility or script function.
L407: def calculate_macosx_platform_tag(archive_root: StrPath, platform_tag: str) -> str:
Function `calculate_macosx_platform_tag`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_setuptools_logging.py

```
L8: def _not_warning(record: logging.LogRecord) -> bool:    Function `_not_warning`    utility
or script function.
L12: def configure() -> None:    Function `configure`    utility or script function.
```

Q_base appwrite/.venv/lib/python3.12/site-packages/wheel/wheelfile.py

```

L33: class WheelError(Exception):    Class (`WheelError`)    component used by the app (see file
context: None).
L37: def urlsafe_b64encode(data: bytes) -> bytes:    Function `urlsafe_b64encode`    utility or
script function.
L42: def urlsafe_b64decode(data: bytes) -> bytes:    Function `urlsafe_b64decode`    utility or
script function.
L48: def get_zipinfo_datetime(    Function `get_zipinfo_datetime`    Returns or fetches data.
L58: class WheelFile(ZipFile):    Class (`WheelFile`)    component used by the app (see file
context: None).
L65: def __init__(    Function `__init__`    utility or script function.
L134: def open(    Function `open`    utility or script function.
L140: def _update_crc(newdata: bytes) -> None:    Function `_update_crc`    utility or script
function.
L168: def write_files(self, base_dir: str) -> None:    Function `write_files`    utility or
script function.
L190: def write(    Function `write`    utility or script function.
L207: def writestr(    Function `writestr`    utility or script function.
L238: def close(self) -> None:    Function `close`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/unpack.py

```

L8: def unpack(path: str, dest: str = ".") -> None:    Function `unpack`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/convert.py

```

L49: def convert_requires(requires: str, metadata: Message) -> None:    Function
`convert_requires`    utility or script function.
L67: def convert_pkg_info(pkginfo: str, metadata: Message) -> None:    Function
`convert_pkg_info`    utility or script function.
L98: def normalize(name: str) -> str:    Function `normalize`    utility or script function.
L102: class ConvertSource(metaclass=ABCMeta):    Class (`ConvertSource`)    component used by
the app (see file context: None).
L111: def dist_info_dir(self) -> str:    Function `dist_info_dir`    utility or script function.
L115: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents`    Generates content (often AI-generated).
L119: class EggFileSource(ConvertSource):    Class (`EggFileSource`)    component used by the

```

```

app (see file context: None).
L120: def __init__(self, path: Path):    Function `__init__`    utility or script function.
L136: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents`    Generates content (often AI-generated).
L164: class EggDirectorySource(EggFileSource):    Class (`EggDirectorySource`)    component used
by the app (see file context: None).
L165: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents`    Generates content (often AI-generated).
L193: class WininstFileSource(ConvertSource):    Class (`WininstFileSource`)    component used
by the app (see file context: None).
L223: def __init__(self, path: Path):    Function `__init__`    utility or script function.
L253: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents`    Generates content (often AI-generated).
L287: def convert(files: list[str], dest_dir: str, verbose: bool) -> None:    Function
`convert`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/__init__.py

```

L15: def unpack_f(args: argparse.Namespace) -> None:    Function `unpack_f`    utility or script
function.
L21: def pack_f(args: argparse.Namespace) -> None:    Function `pack_f`    utility or script
function.
L27: def convert_f(args: argparse.Namespace) -> None:    Function `convert_f`    utility or
script function.
L33: def tags_f(args: argparse.Namespace) -> None:    Function `tags_f`    utility or script
function.
L52: def info_f(args: argparse.Namespace) -> None:    Function `info_f`    utility or script
function.
L61: def version_f(args: argparse.Namespace) -> None:    Function `version_f`    utility or
script function.
L67: def parse_build_tag(build_tag: str) -> str:    Function `parse_build_tag`    utility or
script function.
L85: def parser() -> argparse.ArgumentParser:    Function `parser`    utility or script
function.
L157: def main() -> int:    Function `main`    Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/pack.py

```

L14: def pack(directory: str, dest_dir: str, build_number: str | None) -> None:    Function
`pack`    utility or script function.
L75: def compute_tagline(tags: list[str]) -> str:    Function `compute_tagline`    utility or

```

```
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/info.py

```
L15: def info(path: str, verbose: bool = False) -> None:    Function `info` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/wheel/_commands/tags.py

```
L12: def _compute_tags(original_tags: Iterable[str], new_tags: str | None) -> set[str]:
Function `_compute_tags` utility or script function.
L26: def tags(    Function `tags` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/typing_inspection/introspection.py

```
L28: def is_union_origin(obj: Any, /) -> bool:    Function `is_union_origin` utility or
script function.
L62: def is_union_origin(obj: Any, /) -> bool:    Function `is_union_origin` utility or
script function.
L94: def _literal_type_check(value: Any, /) -> None:    Function `_literal_type_check`
utility or script function.
L103: def get_literal_values(    Function `get_literal_values` Returns or fetches data.
L223: class AnnotationSource(IntEnum):    Class (`AnnotationSource`) component used by the
app (see file context: None).
L247: class Test:    Class (`Test`) component used by the app (see file context: None).
L260: class Test:    Class (`Test`) component used by the app (see file context: None).
L272: class TD(TypedDict):    Class (`TD`) component used by the app (see file context:
None).
L285: class NT(NamedTuple):    Class (`NT`) component used by the app (see file context:
None).
L297: def func(a: int) -> str:    Function `func` utility or script function.
L317: def allowed_qualifiers(self) -> set[Qualifier]:    Function `allowed_qualifiers`
utility or script function.
L336: class ForbiddenQualifier(Exception):    Class (`ForbiddenQualifier`) component used by
the app (see file context: None).
L342: def __init__(self, qualifier: Qualifier, /) -> None:    Function `__init__` utility or
script function.
L346: class _UnknownTypeEnum(Enum):    Class (`_UnknownTypeEnum`) component used by the app
```

```
(see file context: None).
L349: def __str__(self) -> str:    Function `__str__`    utility or script function.
L352: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L363: class InspectedAnnotation(NamedTuple):    Class (`InspectedAnnotation`)    component used
by the app (see file context: None).
L375: class C:    Class (`C`)    component used by the app (see file context: None).
L387: def inspect_annotation( # noqa: PLR0915    Function `inspect_annotation`    utility or
script function.
L511: def _unpack_annotated_inner(    Function `_unpack_annotated_inner`    utility or script
function.
L578: def _unpack_annotated(    Function `_unpack_annotated`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/typing_inspection/typing_objects.py

```
L60: def _compile_identity_check_function(member: LiteralString, function_name:
LiteralString) -> FunctionType:    Function `_compile_identity_check_function`    utility or
script function.
L105: def _compile_isinstance_check_function(member: LiteralString, function_name:
LiteralString) -> FunctionType:    Function `_compile_isinstance_check_function`    utility or
script function.
L298: def is_namedtuple(obj: Any, /) -> bool:    Function `is_namedtuple`    utility or script
function.
L348: def is_newtype(obj: Any, /) -> bool:    Function `is_newtype`    utility or script
function.
L496: def is_typealiastype(obj: Any, /) -> 'TypeIs[TypeAliasType]':    Function
`is_typealiastype`    utility or script function.
L532: def is_deprecated(obj: Any, /) -> 'TypeIs[deprecated]':    Function `is_deprecated`
utility or script function.
L537: def is_deprecated(obj: Any, /) -> 'TypeIs[deprecated]':    Function `is_deprecated`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/service.py

```
L12: class Service:    Service (`Service`)    provides specific operations (often background
tasks).
L13: def __init__(self, client: Client):    Function `__init__`    utility or script function.
L16: def _normalize_value(self, value: Any) -> Any:    Function `_normalize_value`    utility or
script function.
L34: def _parse_response(    Function `_parse_response`    utility or script function.
```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/query.py

```

L4: class Query():    Class (`Query`)    component used by the app (see file context: None).
L5: def __init__(self, method, attribute=None, values=None):    Function `__init__`    utility
or script function.
L14: def __str__(self):    Function `__str__`    utility or script function.
L22: def equal(attribute, value):    Function `equal`    utility or script function.
L26: def not_equal(attribute, value):    Function `not_equal`    utility or script function.
L30: def regex(attribute, pattern):    Function `regex`    utility or script function.
L44: def less_than(attribute, value):    Function `less_than`    utility or script function.
L48: def less_than_equal(attribute, value):    Function `less_than_equal`    utility or script
function.
L52: def greater_than(attribute, value):    Function `greater_than`    utility or script
function.
L56: def greater_than_equal(attribute, value):    Function `greater_than_equal`    utility or
script function.
L60: def is_null(attribute):    Function `is_null`    utility or script function.
L64: def is_not_null(attribute):    Function `is_not_null`    utility or script function.
L68: def exists(attributes):    Function `exists`    utility or script function.
L81: def not_exists(attributes):    Function `not_exists`    utility or script function.
L94: def between(attribute, start, end):    Function `between`    utility or script function.
L98: def starts_with(attribute, value):    Function `starts_with`    utility or script function.
L102: def ends_with(attribute, value):    Function `ends_with`    utility or script function.
L106: def select(attributes):    Function `select`    utility or script function.
L110: def search(attribute, value):    Function `search`    utility or script function.
L114: def order_asc(attribute):    Function `order_asc`    utility or script function.
L118: def order_desc(attribute):    Function `order_desc`    utility or script function.
L122: def order_random():    Function `order_random`    utility or script function.
L126: def cursor_before(id):    Function `cursor_before`    utility or script function.
L130: def cursor_after(id):    Function `cursor_after`    utility or script function.
L134: def limit(limit):    Function `limit`    utility or script function.
L138: def offset(offset):    Function `offset`    utility or script function.
L142: def contains(attribute, value):    Function `contains`    utility or script function.
L152: def contains_any(attribute, value):    Function `contains_any`    utility or script
function.
L161: def contains_all(attribute, value):    Function `contains_all`    utility or script
function.
L170: def not_contains(attribute, value):    Function `not_contains`    utility or script
function.
L174: def not_search(attribute, value):    Function `not_search`    utility or script function.
L178: def not_between(attribute, start, end):    Function `not_between`    utility or script
function.
L182: def not_starts_with(attribute, value):    Function `not_starts_with`    utility or script
function.
L186: def not_ends_with(attribute, value):    Function `not_ends_with`    utility or script
function.
L190: def created_before(value):    Function `created_before`    Creates a resource or document.
L194: def created_after(value):    Function `created_after`    Creates a resource or document.
L198: def created_between(start, end):    Function `created_between`    Creates a resource or
document.

```

```

L202: def updated_before(value):    Function `updated_before` utility or script function.
L206: def updated_after(value):    Function `updated_after` utility or script function.
L210: def updated_between(start, end):    Function `updated_between` utility or script
function.
L214: def or_queries(queries):    Function `or_queries` utility or script function.
L218: def and_queries(queries):    Function `and_queries` utility or script function.
L222: def elem_match(attribute, queries):    Function `elem_match` utility or script
function.
L236: def distance_equal(attribute, values, distance, meters=True):    Function
`distance_equal` utility or script function.
L240: def distance_not_equal(attribute, values, distance, meters=True):    Function
`distance_not_equal` utility or script function.
L244: def distance_greater_than(attribute, values, distance, meters=True):    Function
`distance_greater_than` utility or script function.
L248: def distance_less_than(attribute, values, distance, meters=True):    Function
`distance_less_than` utility or script function.
L252: def intersects(attribute, values):    Function `intersects` utility or script function.
L256: def not_intersects(attribute, values):    Function `not_intersects` utility or script
function.
L260: def crosses(attribute, values):    Function `crosses` utility or script function.
L264: def not_crosses(attribute, values):    Function `not_crosses` utility or script
function.
L268: def overlaps(attribute, values):    Function `overlaps` utility or script function.
L272: def not_overlaps(attribute, values):    Function `not_overlaps` utility or script
function.
L276: def touches(attribute, values):    Function `touches` utility or script function.
L280: def not_touches(attribute, values):    Function `not_touches` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/input_file.py

```

L4: class InputFile:    Class (`InputFile`) component used by the app (see file context:
None).
L6: def from_path(cls, path):    Function `from_path` utility or script function.
L15: def from_bytes(cls, bytes, filename, mime_type = None):    Function `from_bytes` utility
or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/role.py

```

L1: class Role:    Class (`Role`) component used by the app (see file context: None).
L4: def any():    Function `any` utility or script function.
L12: def user(id, status = ""):    Function `user` utility or script function.
L32: def users(status = ""):    Function `users` utility or script function.
L51: def guests():    Function `guests` utility or script function.
L63: def team(id, role = ""):    Function `team` utility or script function.

```

```
L83: def member(id):    Function `member`  utility or script function.
L100: def label(name):  Function `label`   utility or script function.
```

Q_base appwrite/venv/lib/python3.12/site-packages/appwrite/client.py

```
L11: class Client:    Class (`Client`)  component used by the app (see file context: None).
L12: def __init__(self):  Function `__init__`  utility or script function.
L26: def set_self_signed(self, status=True):  Function `set_self_signed`  Sets or updates a
value.
L30: def set_endpoint(self, endpoint):  Function `set_endpoint`  Sets or updates a value.
L37: def add_header(self, key, value):  Function `add_header`  utility or script function.
L41: def get_headers(self):  Function `get_headers`  Returns or fetches data.
L44: def set_project(self, value):  Function `set_project`  Sets or updates a value.
L50: def set_key(self, value):  Function `set_key`  Sets or updates a value.
L56: def set_jwt(self, value):  Function `set_jwt`  Sets or updates a value.
L62: def set_locale(self, value):  Function `set_locale`  Sets or updates a value.
L66: def set_session(self, value):  Function `set_session`  Sets or updates a value.
L72: def set_forwarded_user_agent(self, value):  Function `set_forwarded_user_agent`  Sets
or updates a value.
L78: def set_dev_key(self, value):  Function `set_dev_key`  Sets or updates a value.
L84: def set_cookie(self, value):  Function `set_cookie`  Sets or updates a value.
L90: def set_impersonate_user_id(self, value):  Function `set_impersonate_user_id`  Sets or
updates a value.
L96: def set_impersonate_user_email(self, value):  Function `set_impersonate_user_email`
Sets or updates a value.
L102: def set_impersonate_user_phone(self, value):  Function `set_impersonate_user_phone`
Sets or updates a value.
L108: def call(self, method, path='', headers=None, params=None, response_type='json'):
Function `call`  utility or script function.
L176: def chunked_upload(  Function `chunked_upload`  utility or script function.
L258: def flatten(self, data, prefix='', stringify=False):  Function `flatten`  utility or
script function.
```

Q_base

appwrite/venv/lib/python3.12/site-packages/appwrite/operator.py

```
L5: class Condition(Enum):  Class (`Condition`)  component used by the app (see file
context: None).
L16: class Operator():  Class (`Operator`)  component used by the app (see file context:
None).
L17: def __init__(self, method, values=None):  Function `__init__`  utility or script
function.
L23: def __str__(self):  Function `__str__`  utility or script function.
L31: def increment(value=1, max=None):  Function `increment`  utility or script function.
L42: def decrement(value=1, min=None):  Function `decrement`  utility or script function.
L53: def multiply(factor, max=None):  Function `multiply`  utility or script function.
```



```

L64: def divide(divisor, min=None):    Function `divide` utility or script function.
L77: def modulo(divisor):             Function `modulo` utility or script function.
L85: def power(exponent, max=None):    Function `power` utility or script function.
L96: def array_append(values):         Function `array_append` utility or script function.
L100: def array_prepend(values):       Function `array_prepend` utility or script function.
L104: def array_insert(index, value):  Function `array_insert` utility or script function.
L108: def array_remove(value):         Function `array_remove` utility or script function.
L112: def array_unique():              Function `array_unique` utility or script function.
L116: def array_intersect(values):     Function `array_intersect` utility or script function.
L120: def array_diff(values):          Function `array_diff` utility or script function.
L124: def array_filter(condition, value=None): Function `array_filter` utility or script function.
L129: def string_concat(value):        Function `string_concat` utility or script function.
L133: def string_replace(search, replace): Function `string_replace` utility or script function.
L137: def toggle():                   Function `toggle` utility or script function.
L141: def date_add_days(days):         Function `date_add_days` utility or script function.
L145: def date_sub_days(days):         Function `date_sub_days` utility or script function.
L149: def date_set_now():              Function `date_set_now` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/appwrite/id.py

```

L5: class ID:    Class (`ID`) component used by the app (see file context: None).
L9: def __hex_timestamp():    Function `__hex_timestamp` utility or script function.
L17: def custom(id):          Function `custom` utility or script function.
L22: def unique(padding = 7): Function `unique` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/exception.py

```

L1: class AppwriteException(Exception):    Class (`AppwriteException`) component used by the app (see file context: None).
L2: def __init__(self, message, code = 0, type = None, response = None):    Function `__init__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/permission.py

```

L1: class Permission:    Class (`Permission`) component used by the app (see file context: None).
L4: def read(role):      Function `read` utility or script function.
L8: def write(role):     Function `write` utility or script function.
L12: def create(role):    Function `create` Creates a resource or document.

```

```
L16: def update(role):    Function `update`    utility or script function.
L20: def delete(role):    Function `delete`    Deletes a resource.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/session_list.py

```
L7: class SessionList(AppwriteModel):    Class (`SessionList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_archive_list.py

```
L7: class BackupArchiveList(AppwriteModel):    Class (`BackupArchiveList`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_dropbox.py

```
L6: class OAuth2Dropbox(AppwriteModel):    Authentication component (`OAuth2Dropbox`)    handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_x.py

```
L6: class OAuth2X(AppwriteModel):    Authentication component (`OAuth2X`)    handles user
authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_polygon.py

```
L7: class ColumnPolygon(AppwriteModel):    Class (`ColumnPolygon`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_facebook.py

```
L6: class OAuth2Facebook(AppwriteModel):    Authentication component (`OAuth2Facebook`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/activity_event_list.py

```
L7: class ActivityEventList(AppwriteModel):    Class (`ActivityEventList`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/framework.py

```
L7: class Framework(AppwriteModel):    Class (`Framework`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algorithm_pass.py

```
L6: class AlgoPhpass(AppwriteModel):    Class (`AlgoPhpass`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_float.py

```
L7: class AttributeFloat(AppwriteModel):    Class (`AttributeFloat`) component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_line.py

```
L7: class AttributeLine(AppwriteModel):    Class (`AttributeLine`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_web.py

```
L7: class PlatformWeb(AppwriteModel):    Class (`PlatformWeb`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/key.py

```
L6: class Key(AppwriteModel):    Class (`Key`) component used by the app (see file context:
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/site.py

```
L7: class Site(AppwriteModel):    Class (`Site`) component used by the app (see file context:
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/locale_code.py

```
L6: class LocaleCode(AppwriteModel):    Class (`LocaleCode`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_restoration.py

```
L6: class BackupRestoration(AppwriteModel):    Class (`BackupRestoration`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/project.py

```
L18: class Project(AppwriteModel):    Class (`Project`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/transaction.py

```
L6: class Transaction(AppwriteModel):    Class (`Transaction`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_status.py

```
L7: class HealthStatus(AppwriteModel):    Class (`HealthStatus`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_windows.py

```
L7: class PlatformWindows(AppwriteModel):    Class (`PlatformWindows`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_membership_privacy.py

```
L6: class PolicyMembershipPrivacy(AppwriteModel):    Class (`PolicyMembershipPrivacy`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/continent.py

```
L6: class Continent(AppwriteModel):    Class (`Continent`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_ip.py

```
L7: class AttributeIp(AppwriteModel):    Class (`AttributeIp`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algo_bcrypt.py

```
L6: class AlgoBcrypt(AppwriteModel):    Class (`AlgoBcrypt`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/ephemeral_key.py

```
L6: class EphemeralKey(AppwriteModel):    Class (`EphemeralKey`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_policy.py

```
L6: class BackupPolicy(AppwriteModel):    Class (`BackupPolicy`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/index.py

```
L7: class Index(AppwriteModel):    Class (`Index`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/transaction_list.py

```
L7: class TransactionList(AppwriteModel):    Class (`TransactionList`)    component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/bucket_list.py

```
L7: class BucketList(AppwriteModel):    Class (`BucketList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/user_list.py

```
L9: class UserList(AppwriteModel, Generic[T]):    Class (`UserList`)    component used by the
app (see file context: None).
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'UserList[T]':
Function `with_data`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_zoom.py

```
L6: class OAuth2Zoom(AppwriteModel):    Authentication component (`OAuth2Zoom`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/country.py

```
L6: class Country(AppwriteModel):    Class (`Country`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_okta.py

```
L6: class OAuth2Okta(AppwriteModel):    Authentication component (`OAuth2Okta`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/message.py

```
L7: class Message(AppwriteModel):    Class (`Message`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_polygon.py

```
L7: class AttributePolygon(AppwriteModel):    Class (`AttributePolygon`) component used by the app (see file context: None).
```


Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/language.py

```
L6: class Language(AppwriteModel):    Class (`Language`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/document_list.py

```
L9: class DocumentList(AppwriteModel, Generic[T]):    Class (`DocumentList`) component used by the app (see file context: None).
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) ->
'DocumentList[T]':    Function `with_data` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/subscriber_list.py

```
L7: class SubscriberList(AppwriteModel):    Class (`SubscriberList`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/headers.py

```
L6: class Headers(AppwriteModel):    Class (`Headers`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_bitbucket.py

```
L6: class OAuth2Bitbucket(AppwriteModel):    Authentication component (`OAuth2Bitbucket`)
```

```
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_github.py

```
L6: class OAuth2Github(AppwriteModel):    Authentication component (`OAuth2Github`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_figma.py

```
L6: class OAuth2Figma(AppwriteModel):    Authentication component (`OAuth2Figma`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_yahoo.py

```
L6: class OAuth2Yahoo(AppwriteModel):    Authentication component (`OAuth2Yahoo`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/function_list.py

```
L7: class FunctionList(AppwriteModel):    Class (`FunctionList`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/log.py

```
L6: class Log(AppwriteModel):    Class (`Log`) component used by the app (see file context:
```

```
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_time.py

```
L6: class HealthTime(AppwriteModel):    Class (`HealthTime`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/database.py

```
L9: class Database(AppwriteModel):    Database abstraction (`Database`) encapsulates DB
access/setup.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_microsoft.py

```
L6: class OAuth2Microsoft(AppwriteModel):    Authentication component (`OAuth2Microsoft`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_relationship.py

```
L7: class AttributeRelationship(AppwriteModel):    Class (`AttributeRelationship`) component
used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/password_dictionary.py

```
L6: class PolicyPasswordDictionary(AppwriteModel):    Class (`PolicyPasswordDictionary`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_email.py

```
L7: class AttributeEmail(AppwriteModel):    Class (`AttributeEmail`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/key_list.py

```
L7: class KeyList(AppwriteModel):    Class (`KeyList`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_amazon.py

```
L6: class OAuth2Amazon(AppwriteModel):    Authentication component (`OAuth2Amazon`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algoscript_modified.py

```
L6: class AlgoScriptModified(AppwriteModel):    Class (`AlgoScriptModified`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/billing_limits.py

```
L6: class BillingLimits(AppwriteModel):    Class (`BillingLimits`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/phone.py

```
L6: class Phone(AppwriteModel):    Class (`Phone`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_varchar.py

```
L7: class ColumnVarchar(AppwriteModel):    Class (`ColumnVarchar`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_autodesk.py

```
L6: class OAuth2Autodesk(AppwriteModel):    Authentication component (`OAuth2Autodesk`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_point.py

```
L7: class AttributePoint(AppwriteModel):    Class (`AttributePoint`)    component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_text.py

```
L7: class ColumnText(AppwriteModel):    Class (`ColumnText`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_factors.py

```
L6: class MfaFactors(AppwriteModel):    Class (`MfaFactors`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/deployment.py

```
L7: class Deployment(AppwriteModel):    Class (`Deployment`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_boolean.py

```
L7: class ColumnBoolean(AppwriteModel):    Class (`ColumnBoolean`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_mediumtext.py

```
L7: class ColumnMediumtext(AppwriteModel):    Class (`ColumnMediumtext`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/email_template.py

```
L6: class EmailTemplate(AppwriteModel):    Class (`EmailTemplate`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/site_list.py

```
L7: class SiteList(AppwriteModel):    Class (`SiteList`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/phone_list.py

```
L7: class PhoneList(AppwriteModel):    Class (`PhoneList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/bucket.py

```
L6: class Bucket(AppwriteModel):    Class (`Bucket`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/country_list.py

```
L7: class CountryList(AppwriteModel):    Class (`CountryList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/variable.py

```
L6: class Variable(AppwriteModel):    Class (`Variable`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_type.py

```
L6: class MfaType(AppwriteModel):    Class (`MfaType`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/runtime.py

```
L6: class Runtime(AppwriteModel):    Class (`Runtime`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_bigint.py

```
L7: class ColumnBigint(AppwriteModel):    Class (`ColumnBigint`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_etsy.py

```
L6: class OAuth2Etsy(AppwriteModel):    Authentication component (`OAuth2Etsy`)    handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_linkedin.py


```
L6: class OAuth2Linkedin(AppwriteModel):    Authentication component (`OAuth2Linkedin`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/execution.py

```
L9: class Execution(AppwriteModel):    Class (`Execution`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_index_list.py

```
L7: class ColumnIndexList(AppwriteModel):    Class (`ColumnIndexList`)    component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/jwt.py

```
L6: class Jwt(AppwriteModel):    Class (`Jwt`)    component used by the app (see file context:
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/provider_list.py

```
L7: class ProviderList(AppwriteModel):    Class (`ProviderList`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_slack.py

```
L6: class OAuth2Slack(AppwriteModel):    Authentication component (`OAuth2Slack`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/locale_code_list.py

```
L7: class LocaleCodeList(AppwriteModel):    Class (`LocaleCodeList`) component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_auth0.py

```
L6: class OAuth2Auth0(AppwriteModel):    Authentication component (`OAuth2Auth0`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_bitly.py

```
L6: class OAuth2Bitly(AppwriteModel):    Authentication component (`OAuth2Bitly`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/proxy_rule_list.py

```
L7: class ProxyRuleList(AppwriteModel):    Class (`ProxyRuleList`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_list.py

```
L24: class ColumnList(AppwriteModel):    Class (`ColumnList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/email_template_list.py

```
L7: class EmailTemplateList(AppwriteModel):    Class (`EmailTemplateList`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/framework_adapter.py

```
L6: class FrameworkAdapter(AppwriteModel):    Class (`FrameworkAdapter`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/token.py

```
L6: class Token(AppwriteModel):    Class (`Token`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_antivirus.py

```
L7: class HealthAntivirus(AppwriteModel):    Class (`HealthAntivirus`)    component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_kick.py

```
L6: class OAuth2Kick(AppwriteModel):    Authentication component (`OAuth2Kick`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/index_list.py

```
L7: class IndexList(AppwriteModel):    Class (`IndexList`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_keycloak.py

```
L6: class OAuth2Keycloak(AppwriteModel):    Authentication component (`OAuth2Keycloak`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_android.py

```
L7: class PlatformAndroid(AppwriteModel):    Class (`PlatformAndroid`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/identity.py

```
L6: class Identity(AppwriteModel):    Class (`Identity`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/preferences.py

```

L8: class Preferences(AppwriteModel, Generic[T]):    Class (`Preferences`) component used by
the app (see file context: None).
L15: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) ->
'Preferences[T]':    Function `with_data` utility or script function.
L26: def data(self) -> T:    Function `data` utility or script function.
L30: def data(self, value: T) -> None:    Function `data` utility or script function.
L33: def to_dict(self) -> Dict[str, Any]:    Function `to_dict` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/topic_list.py

```

L7: class TopicList(AppwriteModel):    Class (`TopicList`) component used by the app (see
file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_disqus.py

```

L6: class OAuth2Disqus(AppwriteModel):    Authentication component (`OAuth2Disqus`) handles
user authentication flows.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/collection_list.py

```

L7: class CollectionList(AppwriteModel):    Class (`CollectionList`) component used by the
app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/topic.py

```

L6: class Topic(AppwriteModel):    Class (`Topic`) component used by the app (see file
context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/resource_token.py

```
L6: class ResourceToken(AppwriteModel):    Class (`ResourceToken`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/message_list.py

```
L7: class MessageList(AppwriteModel):    Class (`MessageList`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_certificate.py

```
L6: class HealthCertificate(AppwriteModel):    Class (`HealthCertificate`) component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/resource_token_list.py

```
L7: class ResourceTokenList(AppwriteModel):    Class (`ResourceTokenList`) component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_float.py

```
L7: class ColumnFloat(AppwriteModel):    Class (`ColumnFloat`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/team_list.py

```
L9: class TeamList(AppwriteModel, Generic[T]):    Class (`TeamList`) component used by the
app (see file context: None).
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'TeamList[T]':
Function `with_data` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/team.py

```
L9: class Team(AppwriteModel, Generic[T]):    Class (`Team`) component used by the app (see
file context: None).
L36: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'Team[T]':
Function `with_data` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/subscriber.py

```
L7: class Subscriber(AppwriteModel):    Class (`Subscriber`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_list.py

```
L24: class AttributeList(AppwriteModel):    Class (`AttributeList`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/language_list.py

```
L7: class LanguageList(AppwriteModel):    Class (`LanguageList`) component used by the app
```

```
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_podio.py

```
L6: class OAuth2Podio(AppwriteModel):    Authentication component (`OAuth2Podio`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/base_model.py

```
L9: class AppwriteModel(BaseModel):    Class (`AppwriteModel`) component used by the app (see
file context: None).
L17: def from_dict(cls: Type[ModelType], data: Optional[Dict[str, Any]]) ->
Optional[ModelType]:    Function `from_dict` utility or script function.
L23: def to_dict(self) -> Dict[str, Any]:    Function `to_dict` utility or script function.
L26: def to_json(self) -> str:    Function `to_json` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_point.py

```
L7: class ColumnPoint(AppwriteModel):    Class (`ColumnPoint`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/currency.py

```
L6: class Currency(AppwriteModel):    Class (`Currency`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_challenge.py

```
L6: class MfaChallenge(AppwriteModel):    Class (`MfaChallenge`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_password_history.py

```
L6: class PolicyPasswordHistory(AppwriteModel):    Class (`PolicyPasswordHistory`)    component
used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/variable_list.py

```
L7: class VariableList(AppwriteModel):    Class (`VariableList`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_discord.py

```
L6: class OAuth2Discord(AppwriteModel):    Authentication component (`OAuth2Discord`)    handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_list.py

```
L11: class PlatformList(AppwriteModel):    Class (`PlatformList`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algo_sha.py

```
L6: class AlgoSha(AppwriteModel):    Class (`AlgoSha`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_varchar.py

```
L7: class AttributeVarchar(AppwriteModel):    Class (`AttributeVarchar`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_longtext.py

```
L7: class AttributeLongtext(AppwriteModel):    Class (`AttributeLongtext`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_restoration_list.py

```
L7: class BackupRestorationList(AppwriteModel):    Class (`BackupRestorationList`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/continent_list.py

```
L7: class ContinentList(AppwriteModel):    Class (`ContinentList`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/document.py

```
L8: class Document(AppwriteModel, Generic[T]):    Class (`Document`) component used by the
app (see file context: None).
L38: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'Document[T]':
Function `with_data` utility or script function.
L49: def data(self) -> T:    Function `data` utility or script function.
L53: def data(self, value: T) -> None:    Function `data` utility or script function.
L56: def to_dict(self) -> Dict[str, Any]:    Function `to_dict` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_string.py

```
L7: class ColumnString(AppwriteModel):    Class (`ColumnString`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_paypal.py

```
L6: class OAuth2Paypal(AppwriteModel):    Authentication component (`OAuth2Paypal`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/session.py

```
L6: class Session(AppwriteModel):    Class (`Session`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/dev_key.

py

```
L6: class DevKey(AppwriteModel):    Class (`DevKey`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_policy_list.py

```
L7: class BackupPolicyList(AppwriteModel):    Class (`BackupPolicyList`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_apple.py

```
L7: class PlatformApple(AppwriteModel):    Class (`PlatformApple`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algoscript.py

```
L6: class AlgoScript(AppwriteModel):    Class (`AlgoScript`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/collection.py

```
L25: class Collection(AppwriteModel):    Class (`Collection`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/proxy_rule.py

```
L8: class ProxyRule(AppwriteModel):    Class (`ProxyRule`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/specification_list.py

```
L7: class SpecificationList(AppwriteModel):    Class (`SpecificationList`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/target_list.py

```
L7: class TargetList(AppwriteModel):    Class (`TargetList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_info.py

```
L7: class ColumnIp(AppwriteModel):    Class (`ColumnIp`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/deployment_list.py

```
L7: class DeploymentList(AppwriteModel):    Class (`DeploymentList`)    component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/currency_list.py

```
L7: class CurrencyList(AppwriteModel):    Class (`CurrencyList`)    component used by the app  
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/table_list.py

```
L7: class TableList(AppwriteModel):    Class (`TableList`)    component used by the app (see  
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_url.py

```
L7: class ColumnUrl(AppwriteModel):    Class (`ColumnUrl`)    component used by the app (see  
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/file.py

```
L6: class File(AppwriteModel):    Class (`File`)    component used by the app (see file context:  
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_user_limit.py

```
L6: class PolicyUserLimit(AppwriteModel):    Class (`PolicyUserLimit`)    component used by the  
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_password_personal_data.py

```
L6: class PolicyPasswordPersonalData(AppwriteModel):    Class (`PolicyPasswordPersonalData`)
component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/execution_list.py

```
L7: class ExecutionList(AppwriteModel):    Class (`ExecutionList`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_enum.py

```
L7: class AttributeEnum(AppwriteModel):    Class (`AttributeEnum`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_twitch.py

```
L6: class OAuth2Twitch(AppwriteModel):    Authentication component (`OAuth2Twitch`)    handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/log_list.py

```
L7: class LogList(AppwriteModel):    Class (`LogList`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_box.py

```
L6: class OAuth2Box(AppwriteModel):    Authentication component (`OAuth2Box`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/provider.py

```
L6: class Provider(AppwriteModel):    Class (`Provider`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/specification.py

```
L6: class Specification(AppwriteModel):    Class (`Specification`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_tradeshift.py

```
L6: class OAuth2Tradeshift(AppwriteModel):    Authentication component (`OAuth2Tradeshift`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/webhook.py

```
L6: class Webhook(AppwriteModel):    Class (`Webhook`) component used by the app (see file context: None).
```


Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/locale.py**

```
L6: class Locale(AppwriteModel):    Class (`Locale`)    component used by the app (see file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_notion.py**

```
L6: class OAuth2Notion(AppwriteModel):    Authentication component (`OAuth2Notion`)    handles user authentication flows.
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mfa_recovery_codes.py**

```
L6: class MfaRecoveryCodes(AppwriteModel):    Class (`MfaRecoveryCodes`)    component used by the app (see file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/identity_list.py**

```
L7: class IdentityList(AppwriteModel):    Class (`IdentityList`)    component used by the app (see file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/activity_event.py**

```
L6: class ActivityEvent(AppwriteModel):    Class (`ActivityEvent`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_dailymotion.py

```
L6: class OAuth2Dailymotion(AppwriteModel):    Authentication component (`OAuth2Dailymotion`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_duration.py

```
L6: class PolicySessionDuration(AppwriteModel):    Class (`PolicySessionDuration`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/target.py

```
L6: class Target(AppwriteModel):    Class (`Target`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_relationship.py

```
L7: class ColumnRelationship(AppwriteModel):    Class (`ColumnRelationship`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_enum.py

```
L7: class ColumnEnum(AppwriteModel):    Class (`ColumnEnum`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_google.py

```
L6: class OAuth2Google(AppwriteModel):    Authentication component (`OAuth2Google`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/platform_linux.py

```
L7: class PlatformLinux(AppwriteModel):    Class (`PlatformLinux`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/membership_list.py

```
L7: class MembershipList(AppwriteModel):    Class (`MembershipList`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_yandex.py

```
L6: class OAuth2Yandex(AppwriteModel):    Authentication component (`OAuth2Yandex`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_index.py

```
L6: class ColumnIndex(AppwriteModel):    Class (`ColumnIndex`) component used by the app (see file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/user.py**

```
L17: class User(AppwriteModel, Generic[T]):    Class (`User`) component used by the app (see
file context: None).
L89: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'User[T]':
Function `with_data` utility or script function.
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/webhook_list.py**

```
L7: class WebhookList(AppwriteModel):    Class (`WebhookList`) component used by the app (see
file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_provider_list.py**

```
L46: class OAuth2ProviderList(AppwriteModel):    Authentication component
(`OAuth2ProviderList`) handles user authentication flows.
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_integer.py**

```
L7: class ColumnInteger(AppwriteModel):    Class (`ColumnInteger`) component used by the app
(see file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_status_list.py**

```
L7: class HealthStatusList(AppwriteModel):    Class (`HealthStatusList`) component used by
the app (see file context: None).
```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/row.py**

```

L8: class Row(AppwriteModel, Generic[T]):    Class (`Row`) component used by the app (see
file context: None).
L38: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'Row[T]':
Function `with_data` utility or script function.
L49: def data(self) -> T:    Function `data` utility or script function.
L53: def data(self, value: T) -> None:    Function `data` utility or script function.
L56: def to_dict(self) -> Dict[str, Any]:    Function `to_dict` utility or script function.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_stripe.py**

```

L6: class OAuth2Stripe(AppwriteModel):    Authentication component (`OAuth2Stripe`) handles
user authentication flows.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/database_list.py**

```

L7: class DatabaseList(AppwriteModel):    Database abstraction (`DatabaseList`) encapsulates
DB access/setup.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_string.py**

```

L7: class AttributeString(AppwriteModel):    Class (`AttributeString`) component used by the
app (see file context: None).

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/framework_list.py**

```
L7: class FrameworkList(AppwriteModel):    Class (`FrameworkList`)    component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_invalidation.py

```
L6: class PolicySessionInvalidation(AppwriteModel):    Class (`PolicySessionInvalidation`)
component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_oidc.py

```
L6: class OAuth2Oidc(AppwriteModel):    Authentication component (`OAuth2Oidc`) handles user
authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_integer.py

```
L7: class AttributeInteger(AppwriteModel):    Class (`AttributeInteger`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_datetime.py

```
L7: class AttributeDatetime(AppwriteModel):    Class (`AttributeDatetime`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_list.py

```
L15: class PolicyList(AppwriteModel):    Class (`PolicyList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/health_queue.py

```
L6: class HealthQueue(AppwriteModel):    Class (`HealthQueue`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/runtime_list.py

```
L7: class RuntimeList(AppwriteModel):    Class (`RuntimeList`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/file_list.py

```
L7: class FileList(AppwriteModel):    Class (`FileList`)    component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_boolean.py

```
L7: class AttributeBoolean(AppwriteModel):    Class (`AttributeBoolean`)    component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_alert.py

```
L6: class PolicySessionAlert(AppwriteModel):    Class (`PolicySessionAlert`) component used
by the app (see file context: None).
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_
mediumtext.py**

```
L7: class AttributeMediumtext(AppwriteModel):    Class (`AttributeMediumtext`) component used
by the app (see file context: None).
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/row_list.p
y**

```
L9: class RowList(AppwriteModel, Generic[T]):    Class (`RowList`) component used by the app
(see file context: None).
L24: def with_data(cls, data: Dict[str, Any], model_type: Type[T] = dict) -> 'RowList[T]':
Function `with_data` utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/function.
py**

```
L7: class Function(AppwriteModel):    Class (`Function`) component used by the app (see file
context: None).
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_
url.py**

```
L7: class AttributeUrl(AppwriteModel):    Class (`AttributeUrl`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/oauth2_fusion_auth.py

```
L6: class OAuth2FusionAuth(AppwriteModel):    Authentication component (`OAuth2FusionAuth`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_bigint.py

```
L7: class AttributeBigint(AppwriteModel):    Class (`AttributeBigint`) component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/backup_archive.py

```
L6: class BackupArchive(AppwriteModel):    Class (`BackupArchive`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_email.py

```
L7: class ColumnEmail(AppwriteModel):    Class (`ColumnEmail`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/table.py

```
L25: class Table(AppwriteModel):    Class (`Table`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_spotify.py

```
L6: class OAuth2Spotify(AppwriteModel):    Authentication component (`OAuth2Spotify`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_datetime.py

```
L7: class ColumnDatetime(AppwriteModel):    Class (`ColumnDatetime`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/block.py

```
L6: class Block(AppwriteModel):    Class (`Block`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/auth_provider.py

```
L6: class AuthProvider(AppwriteModel):    Authentication component (`AuthProvider`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_authentik.py

```
L6: class OAuth2Authentik(AppwriteModel):    Authentication component (`OAuth2Authentik`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_line.py

```
L7: class ColumnLine(AppwriteModel):    Class (`ColumnLine`)    component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_salesforce.py

```
L6: class OAuth2Salesforce(AppwriteModel):    Authentication component (`OAuth2Salesforce`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/column_longtext.py

```
L7: class ColumnLongtext(AppwriteModel):    Class (`ColumnLongtext`)    component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_zoho.py

```
L6: class OAuth2Zoho(AppwriteModel):    Authentication component (`OAuth2Zoho`)    handles user
authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_word_press.py

```
L6: class OAuth2WordPress(AppwriteModel):    Authentication component (`OAuth2WordPress`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/membership.py

```
L6: class Membership(AppwriteModel):    Class (`Membership`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mock_number.py

```
L6: class MockNumber(AppwriteModel):    Class (`MockNumber`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/attribute_text.py

```
L7: class AttributeText(AppwriteModel):    Class (`AttributeText`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/mock_number_list.py

```
L7: class MockNumberList(AppwriteModel):    Class (`MockNumberList`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algo_argon2.py

```
L6: class AlgoArgon2(AppwriteModel):    Class (`AlgoArgon2`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_apple.py

```
L6: class OAuth2Apple(AppwriteModel):    Authentication component (`OAuth2Apple`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/o_auth2_gitlab.py

```
L6: class OAuth2Gitlab(AppwriteModel):    Authentication component (`OAuth2Gitlab`) handles
user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/policy_session_limit.py

```
L6: class PolicySessionLimit(AppwriteModel):    Class (`PolicySessionLimit`) component used
by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/models/algo_md5.py

```
L6: class AlgoMd5(AppwriteModel):    Class (`AlgoMd5`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/utis/deprecated.py

```
L11: def deprecated(reason=None):    Function `deprecated` utility or script function.
L21: def old_function(...):    Function `old_function` utility or script function.
L24: def decorator(func):    Function `decorator` utility or script function.
```

```
L31: def wrapped(*args, **kwargs):    Function `wrapped`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/encoders/value_class_encoder.py

```
L58: class ValueClassEncoder(json.JSONEncoder):    Class (`ValueClassEncoder`)    component used
by the app (see file context: None).
L59: def default(self, o):    Function `default`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/avatars.py

```
L13: class Avatars(Service):    Class (`Avatars`)    component used by the app (see file
context: None).
L15: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L18: def get_browser(    Function `get_browser`    Returns or fetches data.
L72: def get_credit_card(    Function `get_credit_card`    Returns or fetches data.
L127: def get_favicon(    Function `get_favicon`    Returns or fetches data.
L166: def get_flag(    Function `get_flag`    Returns or fetches data.
L221: def get_image(    Function `get_image`    Returns or fetches data.
L272: def get_initials(    Function `get_initials`    Returns or fetches data.
L327: def get_qr(    Function `get_qr`    Returns or fetches data.
L380: def get_screenshot(    Function `get_screenshot`    Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/activities.py

```
L8: class Activities(Service):    Class (`Activities`)    component used by the app (see file
context: None).
L10: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L13: def list_events(    Function `list_events`    utility or script function.
L48: def get_event(    Function `get_event`    Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/projects.py

y

```

L82: class Project(Service):    Class (`Project`) component used by the app (see file
context: None).
L84: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L87: def delete(    Function `delete` Deletes a resource.
L114: def update_auth_method(    Function `update_auth_method` utility or script function.
L159: def list_keys(    Function `list_keys` utility or script function.
L199: def create_key(    Function `create_key` Creates a resource or document.
L257: def create_ephemeral_key(    Function `create_ephemeral_key` Creates a resource or
document.
L304: def get_key(    Function `get_key` Returns or fetches data.
L341: def update_key(    Function `update_key` utility or script function.
L397: def delete_key(    Function `delete_key` Deletes a resource.
L435: def update_labels(    Function `update_labels` utility or script function.
L473: def list_mock_phones(    Function `list_mock_phones` utility or script function.
L513: def create_mock_phone(    Function `create_mock_phone` Creates a resource or document.
L558: def get_mock_phone(    Function `get_mock_phone` Returns or fetches data.
L595: def update_mock_phone(    Function `update_mock_phone` utility or script function.
L640: def delete_mock_phone(    Function `delete_mock_phone` Deletes a resource.
L678: def list_o_auth2_providers(    Function `list_o_auth2_providers` utility or script
function.
L718: def update_o_auth2_amazon(    Function `update_o_auth2_amazon` utility or script
function.
L761: def update_o_auth2_apple(    Function `update_o_auth2_apple` utility or script
function.
L812: def update_o_auth2_auth0(    Function `update_o_auth2_auth0` utility or script
function.
L859: def update_o_auth2_authentic(    Function `update_o_auth2_authentic` utility or script
function.
L906: def update_o_auth2_autodesk(    Function `update_o_auth2_autodesk` utility or script
function.
L949: def update_o_auth2_bitbucket(    Function `update_o_auth2_bitbucket` utility or script
function.
L992: def update_o_auth2_bitly(    Function `update_o_auth2_bitly` utility or script
function.
L1035: def update_o_auth2_box(    Function `update_o_auth2_box` utility or script function.
L1078: def update_o_auth2_dailymotion(    Function `update_o_auth2_dailymotion` utility or
script function.
L1121: def update_o_auth2_discord(    Function `update_o_auth2_discord` utility or script
function.
L1164: def update_o_auth2_disqus(    Function `update_o_auth2_disqus` utility or script
function.
L1207: def update_o_auth2_dropbox(    Function `update_o_auth2_dropbox` utility or script
function.
L1250: def update_o_auth2_etsy(    Function `update_o_auth2_etsy` utility or script function.
L1293: def update_o_auth2_facebook(    Function `update_o_auth2_facebook` utility or script
function.
L1336: def update_o_auth2_figma(    Function `update_o_auth2_figma` utility or script
function.

```

```

L1379: def update_o_auth2_fusion_auth(    Function `update_o_auth2_fusion_auth`    utility or
script function.
L1426: def update_o_auth2_git_hub(    Function `update_o_auth2_git_hub`    utility or script
function.
L1469: def update_o_auth2_gitlab(    Function `update_o_auth2_gitlab`    utility or script
function.
L1516: def update_o_auth2_google(    Function `update_o_auth2_google`    utility or script
function.
L1559: def update_o_auth2_keycloak(    Function `update_o_auth2_keycloak`    utility or script
function.
L1610: def update_o_auth2_kick(    Function `update_o_auth2_kick`    utility or script function.
L1653: def update_o_auth2_linkedin(    Function `update_o_auth2_linkedin`    utility or script
function.
L1696: def update_o_auth2_microsoft(    Function `update_o_auth2_microsoft`    utility or script
function.
L1743: def update_o_auth2_notion(    Function `update_o_auth2_notion`    utility or script
function.
L1786: def update_o_auth2_oidc(    Function `update_o_auth2_oidc`    utility or script function.
L1845: def update_o_auth2_okta(    Function `update_o_auth2_okta`    utility or script function.
L1896: def update_o_auth2_paypal(    Function `update_o_auth2_paypal`    utility or script
function.
L1939: def update_o_auth2_paypal_sandbox(    Function `update_o_auth2_paypal_sandbox`    utility
or script function.
L1982: def update_o_auth2_podio(    Function `update_o_auth2_podio`    utility or script
function.
L2025: def update_o_auth2_salesforce(    Function `update_o_auth2_salesforce`    utility or
script function.
L2068: def update_o_auth2_slack(    Function `update_o_auth2_slack`    utility or script
function.
L2111: def update_o_auth2_spotify(    Function `update_o_auth2_spotify`    utility or script
function.
L2154: def update_o_auth2_stripe(    Function `update_o_auth2_stripe`    utility or script
function.
L2197: def update_o_auth2_tradeshift(    Function `update_o_auth2_tradeshift`    utility or
script function.
L2240: def update_o_auth2_tradeshift_sandbox(    Function `update_o_auth2_tradeshift_sandbox`
utility or script function.
L2283: def update_o_auth2_twitch(    Function `update_o_auth2_twitch`    utility or script
function.
L2326: def update_o_auth2_word_press(    Function `update_o_auth2_word_press`    utility or
script function.
L2369: def update_o_auth2_x(    Function `update_o_auth2_x`    utility or script function.
L2412: def update_o_auth2_yahoo(    Function `update_o_auth2_yahoo`    utility or script
function.
L2455: def update_o_auth2_yandex(    Function `update_o_auth2_yandex`    utility or script
function.
L2498: def update_o_auth2_zoho(    Function `update_o_auth2_zoho`    utility or script function.
L2541: def update_o_auth2_zoom(    Function `update_o_auth2_zoom`    utility or script function.
L2584: def get_o_auth2_provider(    Function `get_o_auth2_provider`    Returns or fetches data.
L2743: def list_platforms(    Function `list_platforms`    utility or script function.
L2783: def create_android_platform(    Function `create_android_platform`    Creates a resource

```



```

or document.
L2835: def update_android_platform(    Function `update_android_platform`    utility or script
function.
L2887: def create_apple_platform(    Function `create_apple_platform`    Creates a resource or
document.
L2939: def update_apple_platform(    Function `update_apple_platform`    utility or script
function.
L2991: def create_linux_platform(    Function `create_linux_platform`    Creates a resource or
document.
L3043: def update_linux_platform(    Function `update_linux_platform`    utility or script
function.
L3095: def create_web_platform(    Function `create_web_platform`    Creates a resource or
document.
L3147: def update_web_platform(    Function `update_web_platform`    utility or script function.
L3199: def create_windows_platform(    Function `create_windows_platform`    Creates a resource
or document.
L3251: def update_windows_platform(    Function `update_windows_platform`    utility or script
function.
L3303: def get_platform(    Function `get_platform`    Returns or fetches data.
L3357: def delete_platform(    Function `delete_platform`    Deletes a resource.
L3395: def list_policies(    Function `list_policies`    utility or script function.
L3435: def update_membership_privacy_policy(    Function `update_membership_privacy_policy`
utility or script function.
L3491: def update_password_dictionary_policy(    Function `update_password_dictionary_policy`
utility or script function.
L3529: def update_password_history_policy(    Function `update_password_history_policy`
utility or script function.
L3566: def update_password_personal_data_policy(    Function
`update_password_personal_data_policy`    utility or script function.
L3604: def update_session_alert_policy(    Function `update_session_alert_policy`    utility or
script function.
L3642: def update_session_duration_policy(    Function `update_session_duration_policy`
utility or script function.
L3680: def update_session_invalidation_policy(    Function
`update_session_invalidation_policy`    utility or script function.
L3718: def update_session_limit_policy(    Function `update_session_limit_policy`    utility or
script function.
L3753: def update_user_limit_policy(    Function `update_user_limit_policy`    utility or script
function.
L3788: def get_policy(    Function `get_policy`    Returns or fetches data.
L3854: def update_protocol(    Function `update_protocol`    utility or script function.
L3899: def update_service(    Function `update_service`    utility or script function.
L3944: def update_smtp(    Function `update_smtp`    utility or script function.
L4015: def create_smtp_test(    Function `create_smtp_test`    Creates a resource or document.
L4053: def list_email_templates(    Function `list_email_templates`    utility or script
function.
L4093: def update_email_template(    Function `update_email_template`    utility or script
function.
L4160: def get_email_template(    Function `get_email_template`    Returns or fetches data.
L4202: def list_variables(    Function `list_variables`    utility or script function.
L4242: def create_variable(    Function `create_variable`    Creates a resource or document.

```

```
L4299: def get_variable(    Function `get_variable`  Returns or fetches data.
L4336: def update_variable(    Function `update_variable`  utility or script function.
L4386: def delete_variable(    Function `delete_variable`  Deletes a resource.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/messaging.py

```
L18: class Messaging(Service):    Class (`Messaging`) component used by the app (see file
context: None).
L20: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L23: def list_messages(    Function `list_messages` utility or script function.
L68: def create_email(    Function `create_email` Creates a resource or document.
L164: def update_email(    Function `update_email` utility or script function.
L247: def create_push(    Function `create_push` Creates a resource or document.
L373: def update_push(    Function `update_push` utility or script function.
L484: def create_sms(    Function `create_sms` Creates a resource or document.
L553: def update_sms(    Function `update_sms` utility or script function.
L616: def get_message(    Function `get_message` Returns or fetches data.
L654: def delete(    Function `delete` Deletes a resource.
L692: def list_message_logs(    Function `list_message_logs` utility or script function.
L739: def list_targets(    Function `list_targets` utility or script function.
L786: def list_providers(    Function `list_providers` utility or script function.
L831: def create_apns_provider(    Function `create_apns_provider` Creates a resource or
document.
L905: def update_apns_provider(    Function `update_apns_provider` utility or script
function.
L976: def create_fcm_provider(    Function `create_fcm_provider` Creates a resource or
document.
L1029: def update_fcm_provider(    Function `update_fcm_provider` utility or script function.
L1080: def create_mailgun_provider(    Function `create_mailgun_provider` Creates a resource
or document.
L1163: def update_mailgun_provider(    Function `update_mailgun_provider` utility or script
function.
L1244: def create_msg91_provider(    Function `create_msg91_provider` Creates a resource or
document.
L1308: def update_msg91_provider(    Function `update_msg91_provider` utility or script
function.
L1370: def create_resend_provider(    Function `create_resend_provider` Creates a resource or
document.
L1444: def update_resend_provider(    Function `update_resend_provider` utility or script
function.
L1516: def create_sendgrid_provider(    Function `create_sendgrid_provider` Creates a
resource or document.
L1590: def update_sendgrid_provider(    Function `update_sendgrid_provider` utility or script
function.
L1662: def create_smtp_provider(    Function `create_smtp_provider` Creates a resource or
```

```

document.
L1768: def update_smtp_provider(    Function `update_smtp_provider`    utility or script
function.
L1868: def create_tesign_provider(    Function `create_tesign_provider`    Creates a
resource or document.
L1932: def update_tesign_provider(    Function `update_tesign_provider`    utility or script
function.
L1994: def create_textmagic_provider(    Function `create_textmagic_provider`    Creates a
resource or document.
L2058: def update_textmagic_provider(    Function `update_textmagic_provider`    utility or
script function.
L2120: def create_twilio_provider(    Function `create_twilio_provider`    Creates a resource or
document.
L2184: def update_twilio_provider(    Function `update_twilio_provider`    utility or script
function.
L2246: def create_vonage_provider(    Function `create_vonage_provider`    Creates a resource or
document.
L2310: def update_vonage_provider(    Function `update_vonage_provider`    utility or script
function.
L2372: def get_provider(    Function `get_provider`    Returns or fetches data.
L2410: def delete_provider(    Function `delete_provider`    Deletes a resource.
L2448: def list_provider_logs(    Function `list_provider_logs`    utility or script function.
L2495: def list_subscriber_logs(    Function `list_subscriber_logs`    utility or script
function.
L2542: def list_topics(    Function `list_topics`    utility or script function.
L2587: def create_topic(    Function `create_topic`    Creates a resource or document.
L2637: def get_topic(    Function `get_topic`    Returns or fetches data.
L2675: def update_topic(    Function `update_topic`    utility or script function.
L2722: def delete_topic(    Function `delete_topic`    Deletes a resource.
L2760: def list_topic_logs(    Function `list_topic_logs`    utility or script function.
L2807: def list_subscribers(    Function `list_subscribers`    utility or script function.
L2859: def create_subscriber(    Function `create_subscriber`    Creates a resource or document.
L2911: def get_subscriber(    Function `get_subscriber`    Returns or fetches data.
L2956: def delete_subscriber(    Function `delete_subscriber`    Deletes a resource.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/webhooks.py

```

L8: class Webhooks(Service):    Class (`Webhooks`) component used by the app (see file
context: None).
L10: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L13: def list(    Function `list`    utility or script function.
L53: def create(    Function `create`    Creates a resource or document.
L136: def get(    Function `get`    Returns or fetches data.
L173: def update(    Function `update`    utility or script function.
L252: def delete(    Function `delete`    Deletes a resource.

```

```
L290: def update_secret(    Function `update_secret`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/tokens.py

```
L8: class Tokens(Service):    Class (`Tokens`)    component used by the app (see file context:
None).
L10: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L13: def list(    Function `list`    utility or script function.
L67: def create_file_token(    Function `create_file_token`    Creates a resource or document.
L116: def get(    Function `get`    Returns or fetches data.
L153: def update(    Function `update`    utility or script function.
L195: def delete(    Function `delete`    Deletes a resource.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/function_s.py

```
L23: class Functions(Service):    Class (`Functions`)    component used by the app (see file
context: None).
L25: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L28: def list(    Function `list`    utility or script function.
L73: def create(    Function `create`    Creates a resource or document.
L210: def list_runtimes(    Function `list_runtimes`    utility or script function.
L236: def list_specifications(    Function `list_specifications`    utility or script function.
L262: def get(    Function `get`    Returns or fetches data.
L299: def update(    Function `update`    utility or script function.
L433: def delete(    Function `delete`    Deletes a resource.
L471: def update_function_deployment(    Function `update_function_deployment`    utility or
script function.
L516: def list_deployments(    Function `list_deployments`    utility or script function.
L568: def create_deployment(    Function `create_deployment`    Creates a resource or document.
L642: def create_duplicate_deployment(    Function `create_duplicate_deployment`    Creates a
resource or document.
L692: def create_template_deployment(    Function `create_template_deployment`    Creates a
resource or document.
L772: def create_vcs_deployment(    Function `create_vcs_deployment`    Creates a resource or
document.
L831: def get_deployment(    Function `get_deployment`    Returns or fetches data.
L875: def delete_deployment(    Function `delete_deployment`    Deletes a resource.
L920: def get_deployment_download(    Function `get_deployment_download`    Returns or fetches
data.
L969: def update_deployment_status(    Function `update_deployment_status`    utility or script
```

```

function.
L1014: def list_executions(    Function `list_executions`    utility or script function.
L1061: def create_execution(    Function `create_execution`    Creates a resource or document.
L1128: def get_execution(    Function `get_execution`    Returns or fetches data.
L1172: def delete_execution(    Function `delete_execution`    Deletes a resource.
L1217: def list_variables(    Function `list_variables`    utility or script function.
L1264: def create_variable(    Function `create_variable`    Creates a resource or document.
L1328: def get_variable(    Function `get_variable`    Returns or fetches data.
L1372: def update_variable(    Function `update_variable`    utility or script function.
L1429: def delete_variable(    Function `delete_variable`    Deletes a resource.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/sites.py

```

L23: class Sites(Service):    Class (`Sites`)    component used by the app (see file context:
None).
L25: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L28: def list(    Function `list`    utility or script function.
L73: def create(    Function `create`    Creates a resource or document.
L217: def list_frameworks(    Function `list_frameworks`    utility or script function.
L243: def list_specifications(    Function `list_specifications`    utility or script function.
L269: def get(    Function `get`    Returns or fetches data.
L306: def update(    Function `update`    utility or script function.
L448: def delete(    Function `delete`    Deletes a resource.
L486: def update_site_deployment(    Function `update_site_deployment`    utility or script
function.
L531: def list_deployments(    Function `list_deployments`    utility or script function.
L583: def create_deployment(    Function `create_deployment`    Creates a resource or document.
L656: def create_duplicate_deployment(    Function `create_duplicate_deployment`    Creates a
resource or document.
L701: def create_template_deployment(    Function `create_template_deployment`    Creates a
resource or document.
L781: def create_vcs_deployment(    Function `create_vcs_deployment`    Creates a resource or
document.
L840: def get_deployment(    Function `get_deployment`    Returns or fetches data.
L884: def delete_deployment(    Function `delete_deployment`    Deletes a resource.
L929: def get_deployment_download(    Function `get_deployment_download`    Returns or fetches
data.
L978: def update_deployment_status(    Function `update_deployment_status`    utility or script
function.
L1023: def list_logs(    Function `list_logs`    utility or script function.
L1070: def get_log(    Function `get_log`    Returns or fetches data.
L1114: def delete_log(    Function `delete_log`    Deletes a resource.
L1159: def list_variables(    Function `list_variables`    utility or script function.
L1206: def create_variable(    Function `create_variable`    Creates a resource or document.
L1270: def get_variable(    Function `get_variable`    Returns or fetches data.
L1314: def update_variable(    Function `update_variable`    utility or script function.
L1371: def delete_variable(    Function `delete_variable`    Deletes a resource.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/backups.py

```
L13: class Backups(Service):    Class (`Backups`) component used by the app (see file
context: None).
L15: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L18: def list_archives(    Function `list_archives` utility or script function.
L53: def create_archive(    Function `create_archive` Creates a resource or document.
L95: def get_archive(    Function `get_archive` Returns or fetches data.
L132: def delete_archive(    Function `delete_archive` Deletes a resource.
L170: def list_policies(    Function `list_policies` utility or script function.
L205: def create_policy(    Function `create_policy` Creates a resource or document.
L278: def get_policy(    Function `get_policy` Returns or fetches data.
L315: def update_policy(    Function `update_policy` utility or script function.
L370: def delete_policy(    Function `delete_policy` Deletes a resource.
L408: def create_restoration(    Function `create_restoration` Creates a resource or
document.
L463: def list_restorations(    Function `list_restorations` utility or script function.
L498: def get_restoration(    Function `get_restoration` Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/locale.py

```
L13: class Locale(Service):    Class (`Locale`) component used by the app (see file context:
None).
L15: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L18: def get(    Function `get` Returns or fetches data.
L46: def list_codes(    Function `list_codes` utility or script function.
L72: def list_continents(    Function `list_continents` utility or script function.
L98: def list_countries(    Function `list_countries` utility or script function.
L124: def list_countries_eu(    Function `list_countries_eu` utility or script function.
L150: def list_countries_phones(    Function `list_countries_phones` utility or script
function.
L176: def list_currencies(    Function `list_currencies` utility or script function.
L202: def list_languages(    Function `list_languages` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/tables_db.py

```

L41: class TablesDB(Service):    Class (`TablesDB`) component used by the app (see file
context: None).
L43: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L46: def list(    Function `list` utility or script function.
L91: def create(    Function `create` Creates a resource or document.
L142: def list_transactions(    Function `list_transactions` utility or script function.
L177: def create_transaction(    Function `create_transaction` Creates a resource or
document.
L213: def get_transaction(    Function `get_transaction` Returns or fetches data.
L250: def update_transaction(    Function `update_transaction` utility or script function.
L298: def delete_transaction(    Function `delete_transaction` Deletes a resource.
L336: def create_operations(    Function `create_operations` Creates a resource or document.
L379: def get(    Function `get` Returns or fetches data.
L416: def update(    Function `update` utility or script function.
L464: def delete(    Function `delete` Deletes a resource.
L502: def list_tables(    Function `list_tables` utility or script function.
L554: def create_table(    Function `create_table` Creates a resource or document.
L630: def get_table(    Function `get_table` Returns or fetches data.
L674: def update_table(    Function `update_table` utility or script function.
L743: def delete_table(    Function `delete_table` Deletes a resource.
L788: def list_columns(    Function `list_columns` utility or script function.
L842: def create_big_int_column(    Function `create_big_int_column` Creates a resource or
document.
L919: def update_big_int_column(    Function `update_big_int_column` utility or script
function.
L995: def create_boolean_column(    Function `create_boolean_column` Creates a resource or
document.
L1064: def update_boolean_column(    Function `update_boolean_column` utility or script
function.
L1131: def create_datetime_column(    Function `create_datetime_column` Creates a resource or
document.
L1199: def update_datetime_column(    Function `update_datetime_column` utility or script
function.
L1266: def create_email_column(    Function `create_email_column` Creates a resource or
document.
L1335: def update_email_column(    Function `update_email_column` utility or script function.
L1403: def create_enum_column(    Function `create_enum_column` Creates a resource or
document.
L1478: def update_enum_column(    Function `update_enum_column` utility or script function.
L1553: def create_float_column(    Function `create_float_column` Creates a resource or
document.
L1630: def update_float_column(    Function `update_float_column` utility or script function.
L1706: def create_integer_column(    Function `create_integer_column` Creates a resource or
document.
L1783: def update_integer_column(    Function `update_integer_column` utility or script
function.
L1859: def create_ip_column(    Function `create_ip_column` Creates a resource or document.
L1928: def update_ip_column(    Function `update_ip_column` utility or script function.
L1996: def create_line_column(    Function `create_line_column` Creates a resource or
document.
L2059: def update_line_column(    Function `update_line_column` utility or script function.

```

L2126: def create_longtext_column(Function `create\_longtext\_column` Creates a resource or document.

L2200: def update_longtext_column(Function `update\_longtext\_column` utility or script function.

L2268: def create_mediumtext_column(Function `create\_mediumtext\_column` Creates a resource or document.

L2342: def update_mediumtext_column(Function `update\_mediumtext\_column` utility or script function.

L2410: def create_point_column(Function `create\_point\_column` Creates a resource or document.

L2473: def update_point_column(Function `update\_point\_column` utility or script function.

L2540: def create_polygon_column(Function `create\_polygon\_column` Creates a resource or document.

L2603: def update_polygon_column(Function `update\_polygon\_column` utility or script function.

L2670: def create_relationship_column(Function `create\_relationship\_column` Creates a resource or document.

L2749: def create_string_column(Function `create\_string\_column` Creates a resource or document.

L2833: def update_string_column(Function `update\_string\_column` utility or script function.

L2907: def create_text_column(Function `create\_text\_column` Creates a resource or document.

L2981: def update_text_column(Function `update\_text\_column` utility or script function.

L3049: def create_url_column(Function `create\_url\_column` Creates a resource or document.

L3118: def update_url_column(Function `update\_url\_column` utility or script function.

L3186: def create_varchar_column(Function `create\_varchar\_column` Creates a resource or document.

L3267: def update_varchar_column(Function `update\_varchar\_column` utility or script function.

L3339: def get_column(Function `get\_column` Returns or fetches data.

L3422: def delete_column(Function `delete\_column` Deletes a resource.

L3474: def update_relationship_column(Function `update\_relationship\_column` utility or script function.

L3535: def list_indexes(Function `list\_indexes` utility or script function.

L3589: def create_index(Function `create\_index` Creates a resource or document.

L3666: def get_index(Function `get\_index` Returns or fetches data.

L3717: def delete_index(Function `delete\_index` Deletes a resource.

L3769: def list_rows(Function `list\_rows` utility or script function.

L3837: def create_row(Function `create\_row` Creates a resource or document.

L3908: def create_rows(Function `create\_rows` Creates a resource or document.

L3968: def upsert_rows(Function `upsert\_rows` utility or script function.

L4029: def update_rows(Function `update\_rows` utility or script function.

L4092: def delete_rows(Function `delete\_rows` Deletes a resource.

L4150: def get_row(Function `get\_row` Returns or fetches data.

L4215: def upsert_row(Function `upsert\_row` utility or script function.

L4284: def update_row(Function `update\_row` utility or script function.

L4353: def delete_row(Function `delete\_row` Deletes a resource.

L4409: def decrement_row_column(Function `decrement\_row\_column` utility or script function.

L4485: def increment_row_column(Function `increment\_row\_column` utility or script


```
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/proxy.py

```
L10: class Proxy(Service):    Class (`Proxy`) component used by the app (see file context:
None).
L12: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L15: def list_rules(    Function `list_rules` utility or script function.
L55: def create_api_rule(    Function `create_api_rule` Creates a resource or document.
L95: def create_function_rule(    Function `create_function_rule` Creates a resource or
document.
L147: def create_redirect_rule(    Function `create_redirect_rule` Creates a resource or
document.
L215: def create_site_rule(    Function `create_site_rule` Creates a resource or document.
L267: def get_rule(    Function `get_rule` Returns or fetches data.
L304: def delete_rule(    Function `delete_rule` Deletes a resource.
L342: def update_rule_status(    Function `update_rule_status` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/teams.py

```
L13: class Teams(Service):    Class (`Teams`) component used by the app (see file context:
None).
L15: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L18: def list(    Function `list` utility or script function.
L67: def create(    Function `create` Creates a resource or document.
L121: def get(    Function `get` Returns or fetches data.
L162: def update_name(    Function `update_name` utility or script function.
L211: def delete(    Function `delete` Deletes a resource.
L249: def list_memberships(    Function `list_memberships` utility or script function.
L301: def create_membership(    Function `create_membership` Creates a resource or document.
L378: def get_membership(    Function `get_membership` Returns or fetches data.
L422: def update_membership(    Function `update_membership` utility or script function.
L475: def delete_membership(    Function `delete_membership` Deletes a resource.
L520: def update_membership_status(    Function `update_membership_status` utility or script
function.
L582: def get_prefs(    Function `get_prefs` Returns or fetches data.
L623: def update_prefs(    Function `update_prefs` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/graphql.py

```
L6: class GraphQL(Service):    Class (`GraphQL`) component used by the app (see file context:
None).
L8: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L11: def query(    Function `query` utility or script function.
L50: def mutation(    Function `mutation` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/databases.py

```
L41: class Databases(Service):    Database abstraction (`Databases`) encapsulates DB
access/setup.
L43: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L47: def list(    Function `list` utility or script function.
L95: def create(    Function `create` Creates a resource or document.
L148: def list_transactions(    Function `list_transactions` utility or script function.
L183: def create_transaction(    Function `create_transaction` Creates a resource or
document.
L219: def get_transaction(    Function `get_transaction` Returns or fetches data.
L256: def update_transaction(    Function `update_transaction` utility or script function.
L304: def delete_transaction(    Function `delete_transaction` Deletes a resource.
L342: def create_operations(    Function `create_operations` Creates a resource or document.
L386: def get(    Function `get` Returns or fetches data.
L426: def update(    Function `update` utility or script function.
L477: def delete(    Function `delete` Deletes a resource.
L518: def list_collections(    Function `list_collections` utility or script function.
L573: def create_collection(    Function `create_collection` Creates a resource or document.
L652: def get_collection(    Function `get_collection` Returns or fetches data.
L699: def update_collection(    Function `update_collection` utility or script function.
L771: def delete_collection(    Function `delete_collection` Deletes a resource.
L819: def list_attributes(    Function `list_attributes` utility or script function.
L876: def create_big_int_attribute(    Function `create_big_int_attribute` Creates a resource
or document.
L956: def update_big_int_attribute(    Function `update_big_int_attribute` utility or script
function.
L1035: def create_boolean_attribute(    Function `create_boolean_attribute` Creates a
resource or document.
L1107: def update_boolean_attribute(    Function `update_boolean_attribute` utility or script
function.
L1177: def create_datetime_attribute(    Function `create_datetime_attribute` Creates a
resource or document.
L1248: def update_datetime_attribute(    Function `update_datetime_attribute` utility or
script function.
```

L1318: def create_email_attribute(Function `create\_email\_attribute` Creates a resource or document.

L1390: def update_email_attribute(Function `update\_email\_attribute` utility or script function.

L1461: def create_enum_attribute(Function `create\_enum\_attribute` Creates a resource or document.

L1540: def update_enum_attribute(Function `update\_enum\_attribute` utility or script function.

L1618: def create_float_attribute(Function `create\_float\_attribute` Creates a resource or document.

L1698: def update_float_attribute(Function `update\_float\_attribute` utility or script function.

L1777: def create_integer_attribute(Function `create\_integer\_attribute` Creates a resource or document.

L1857: def update_integer_attribute(Function `update\_integer\_attribute` utility or script function.

L1936: def create_ip_attribute(Function `create\_ip\_attribute` Creates a resource or document.

L2008: def update_ip_attribute(Function `update\_ip\_attribute` utility or script function.

L2079: def create_line_attribute(Function `create\_line\_attribute` Creates a resource or document.

L2145: def update_line_attribute(Function `update\_line\_attribute` utility or script function.

L2214: def create_longtext_attribute(Function `create\_longtext\_attribute` Creates a resource or document.

L2288: def update_longtext_attribute(Function `update\_longtext\_attribute` utility or script function.

L2356: def create_mediumtext_attribute(Function `create\_mediumtext\_attribute` Creates a resource or document.

L2430: def update_mediumtext_attribute(Function `update\_mediumtext\_attribute` utility or script function.

L2499: def create_point_attribute(Function `create\_point\_attribute` Creates a resource or document.

L2565: def update_point_attribute(Function `update\_point\_attribute` utility or script function.

L2635: def create_polygon_attribute(Function `create\_polygon\_attribute` Creates a resource or document.

L2701: def update_polygon_attribute(Function `update\_polygon\_attribute` utility or script function.

L2771: def create_relationship_attribute(Function `create\_relationship\_attribute` Creates a resource or document.

L2852: def update_relationship_attribute(Function `update\_relationship\_attribute` utility or script function.

L2917: def create_string_attribute(Function `create\_string\_attribute` Creates a resource or document.

L3001: def update_string_attribute(Function `update\_string\_attribute` utility or script function.

L3075: def create_text_attribute(Function `create\_text\_attribute` Creates a resource or document.

L3149: def update_text_attribute(Function `update\_text\_attribute` utility or script function.

```

L3218: def create_url_attribute(    Function `create_url_attribute`    Creates a resource or
document.
L3290: def update_url_attribute(    Function `update_url_attribute`    utility or script
function.
L3360: def create_varchar_attribute(    Function `create_varchar_attribute`    Creates a
resource or document.
L3441: def update_varchar_attribute(    Function `update_varchar_attribute`    utility or script
function.
L3514: def get_attribute(    Function `get_attribute`    Returns or fetches data.
L3600: def delete_attribute(    Function `delete_attribute`    Deletes a resource.
L3655: def list_documents(    Function `list_documents`    utility or script function.
L3726: def create_document(    Function `create_document`    Creates a resource or document.
L3800: def create_documents(    Function `create_documents`    Creates a resource or document.
L3863: def upsert_documents(    Function `upsert_documents`    utility or script function.
L3927: def update_documents(    Function `update_documents`    utility or script function.
L3993: def delete_documents(    Function `delete_documents`    Deletes a resource.
L4054: def get_document(    Function `get_document`    Returns or fetches data.
L4122: def upsert_document(    Function `upsert_document`    utility or script function.
L4194: def update_document(    Function `update_document`    utility or script function.
L4266: def delete_document(    Function `delete_document`    Deletes a resource.
L4325: def decrement_document_attribute(    Function `decrement_document_attribute`    utility
or script function.
L4404: def increment_document_attribute(    Function `increment_document_attribute`    utility
or script function.
L4483: def list_indexes(    Function `list_indexes`    utility or script function.
L4540: def create_index(    Function `create_index`    Creates a resource or document.
L4620: def get_index(    Function `get_index`    Returns or fetches data.
L4674: def delete_index(    Function `delete_index`    Deletes a resource.

```

Q_base

**appwrite/venv/lib/python3.12/site-packages/appwrite/services/storage.
py**

```

L14: class Storage(Service):    Class (`Storage`) component used by the app (see file
context: None).
L16: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L19: def list_buckets(    Function `list_buckets`    utility or script function.
L64: def create_bucket(    Function `create_bucket`    Creates a resource or document.
L153: def get_bucket(    Function `get_bucket`    Returns or fetches data.
L190: def update_bucket(    Function `update_bucket`    utility or script function.
L279: def delete_bucket(    Function `delete_bucket`    Deletes a resource.
L317: def list_files(    Function `list_files`    utility or script function.
L369: def create_file(    Function `create_file`    Creates a resource or document.
L442: def get_file(    Function `get_file`    Returns or fetches data.
L486: def update_file(    Function `update_file`    utility or script function.
L540: def delete_file(    Function `delete_file`    Deletes a resource.
L585: def get_file_download(    Function `get_file_download`    Returns or fetches data.

```

```
L634: def get_file_preview(    Function `get_file_preview`  Returns or fetches data.
L738: def get_file_view(      Function `get_file_view`    Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/health.py

```
L13: class Health(Service):    Class (`Health`) component used by the app (see file context:
None).
L15: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L18: def get(    Function `get`  Returns or fetches data.
L44: def get_antivirus(    Function `get_antivirus`  Returns or fetches data.
L70: def get_cache(    Function `get_cache`  Returns or fetches data.
L96: def get_certificate(    Function `get_certificate`  Returns or fetches data.
L131: def get_console_pausing(    Function `get_console_pausing`  Returns or fetches data.
L172: def get_db(    Function `get_db`  Returns or fetches data.
L198: def get_pub_sub(    Function `get_pub_sub`  Returns or fetches data.
L224: def get_queue_audits(    Function `get_queue_audits`  Returns or fetches data.
L260: def get_queue_builds(    Function `get_queue_builds`  Returns or fetches data.
L295: def get_queue_certificates(    Function `get_queue_certificates`  Returns or fetches
data.
L330: def get_queue_databases(    Function `get_queue_databases`  Returns or fetches data.
L370: def get_queue_deletes(    Function `get_queue_deletes`  Returns or fetches data.
L405: def get_failed_jobs(    Function `get_failed_jobs`  Returns or fetches data.
L448: def get_queue_functions(    Function `get_queue_functions`  Returns or fetches data.
L483: def get_queue_logs(    Function `get_queue_logs`  Returns or fetches data.
L518: def get_queue_mails(    Function `get_queue_mails`  Returns or fetches data.
L553: def get_queue_messaging(    Function `get_queue_messaging`  Returns or fetches data.
L588: def get_queue_migrations(    Function `get_queue_migrations`  Returns or fetches data.
L623: def get_queue_stats_resources(    Function `get_queue_stats_resources`  Returns or
fetches data.
L658: def get_queue_usage(    Function `get_queue_usage`  Returns or fetches data.
L693: def get_queue_webhooks(    Function `get_queue_webhooks`  Returns or fetches data.
L728: def get_storage(    Function `get_storage`  Returns or fetches data.
L754: def get_storage_local(    Function `get_storage_local`  Returns or fetches data.
L780: def get_time(    Function `get_time`  Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/users.py

```
L25: class Users(Service):    Class (`Users`) component used by the app (see file context:
None).
L27: def __init__(self, client) -> None:    Function `__init__` utility or script function.
L30: def list(    Function `list` utility or script function.
```

```

L79: def create(    Function `create`    Creates a resource or document.
L139: def create_argon2_user(    Function `create_argon2_user`    Creates a resource or
document.
L200: def create_bcrypt_user(    Function `create_bcrypt_user`    Creates a resource or
document.
L261: def list_identities(    Function `list_identities`    utility or script function.
L306: def delete_identity(    Function `delete_identity`    Deletes a resource.
L344: def create_md5_user(    Function `create_md5_user`    Creates a resource or document.
L405: def create_ph_pass_user(    Function `create_ph_pass_user`    Creates a resource or
document.
L466: def create_scrypt_user(    Function `create_scrypt_user`    Creates a resource or
document.
L562: def create_scrypt_modified_user(    Function `create_scrypt_modified_user`    Creates a
resource or document.
L644: def create_sha_user(    Function `create_sha_user`    Creates a resource or document.
L710: def get(    Function `get`    Returns or fetches data.
L751: def delete(    Function `delete`    Deletes a resource.
L789: def update_email(    Function `update_email`    utility or script function.
L838: def update_impersonator(    Function `update_impersonator`    utility or script function.
L888: def create_jwt(    Function `create_jwt`    Creates a resource or document.
L936: def update_labels(    Function `update_labels`    utility or script function.
L987: def list_logs(    Function `list_logs`    utility or script function.
L1034: def list_memberships(    Function `list_memberships`    utility or script function.
L1086: def update_mfa(    Function `update_mfa`    utility or script function.
L1135: def delete_mfa_authenticator(    Function `delete_mfa_authenticator`    Deletes a
resource.
L1180: def list_mfa_factors(    Function `list_mfa_factors`    utility or script function.
L1217: def get_mfa_recovery_codes(    Function `get_mfa_recovery_codes`    Returns or fetches
data.
L1254: def update_mfa_recovery_codes(    Function `update_mfa_recovery_codes`    utility or
script function.
L1292: def create_mfa_recovery_codes(    Function `create_mfa_recovery_codes`    Creates a
resource or document.
L1330: def update_name(    Function `update_name`    utility or script function.
L1379: def update_password(    Function `update_password`    utility or script function.
L1428: def update_phone(    Function `update_phone`    utility or script function.
L1477: def get_prefs(    Function `get_prefs`    Returns or fetches data.
L1518: def update_prefs(    Function `update_prefs`    utility or script function.
L1567: def list_sessions(    Function `list_sessions`    utility or script function.
L1609: def create_session(    Function `create_session`    Creates a resource or document.
L1649: def delete_sessions(    Function `delete_sessions`    Deletes a resource.
L1687: def delete_session(    Function `delete_session`    Deletes a resource.
L1732: def update_status(    Function `update_status`    utility or script function.
L1781: def list_targets(    Function `list_targets`    utility or script function.
L1828: def create_target(    Function `create_target`    Creates a resource or document.
L1897: def get_target(    Function `get_target`    Returns or fetches data.
L1941: def update_target(    Function `update_target`    utility or script function.
L2001: def delete_target(    Function `delete_target`    Deletes a resource.
L2046: def create_token(    Function `create_token`    Creates a resource or document.
L2095: def update_email_verification(    Function `update_email_verification`    utility or
script function.

```

```
L2144: def update_phone_verification(    Function `update_phone_verification`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/services/account.py

```
L23: class Account(Service):    Class (`Account`)    component used by the app (see file
context: None).
L25: def __init__(self, client) -> None:    Function `__init__`    utility or script function.
L28: def get(    Function `get`    Returns or fetches data.
L61: def create(    Function `create`    Creates a resource or document.
L122: def update_email(    Function `update_email`    utility or script function.
L173: def list_identities(    Function `list_identities`    utility or script function.
L213: def delete_identity(    Function `delete_identity`    Deletes a resource.
L251: def create_jwt(    Function `create_jwt`    Creates a resource or document.
L287: def list_logs(    Function `list_logs`    utility or script function.
L327: def update_mfa(    Function `update_mfa`    utility or script function.
L369: def create_mfa_authenticator(    Function `create_mfa_authenticator`    Creates a resource
or document.
L407: def update_mfa_authenticator(    Function `update_mfa_authenticator`    utility or script
function.
L456: def delete_mfa_authenticator(    Function `delete_mfa_authenticator`    Deletes a
resource.
L494: def create_mfa_challenge(    Function `create_mfa_challenge`    Creates a resource or
document.
L532: def update_mfa_challenge(    Function `update_mfa_challenge`    utility or script
function.
L577: def list_mfa_factors(    Function `list_mfa_factors`    utility or script function.
L603: def get_mfa_recovery_codes(    Function `get_mfa_recovery_codes`    Returns or fetches
data.
L629: def create_mfa_recovery_codes(    Function `create_mfa_recovery_codes`    Creates a
resource or document.
L656: def update_mfa_recovery_codes(    Function `update_mfa_recovery_codes`    utility or
script function.
L683: def update_name(    Function `update_name`    utility or script function.
L725: def update_password(    Function `update_password`    utility or script function.
L772: def update_phone(    Function `update_phone`    utility or script function.
L821: def get_prefs(    Function `get_prefs`    Returns or fetches data.
L854: def update_prefs(    Function `update_prefs`    utility or script function.
L896: def create_recovery(    Function `create_recovery`    Creates a resource or document.
L941: def update_recovery(    Function `update_recovery`    utility or script function.
L995: def list_sessions(    Function `list_sessions`    utility or script function.
L1021: def delete_sessions(    Function `delete_sessions`    Deletes a resource.
L1048: def create_anonymous_session(    Function `create_anonymous_session`    Creates a
resource or document.
L1075: def create_email_password_session(    Function `create_email_password_session`    Creates
```

```

a resource or document.
L1123: def update_magic_url_session(    Function `update_magic_url_session`    utility or script
function.
L1171: def update_phone_session(    Function `update_phone_session`    utility or script
function.
L1218: def create_session(    Function `create_session`    Creates a resource or document.
L1263: def get_session(    Function `get_session`    Returns or fetches data.
L1300: def update_session(    Function `update_session`    utility or script function.
L1338: def delete_session(    Function `delete_session`    Deletes a resource.
L1376: def update_status(    Function `update_status`    utility or script function.
L1410: def create_email_token(    Function `create_email_token`    Creates a resource or
document.
L1463: def create_magic_url_token(    Function `create_magic_url_token`    Creates a resource or
document.
L1521: def create_o_auth2_token(    Function `create_o_auth2_token`    Creates a resource or
document.
L1577: def create_phone_token(    Function `create_phone_token`    Creates a resource or
document.
L1624: def create_email_verification(    Function `create_email_verification`    Creates a
resource or document.
L1666: def create_verification(    Function `create_verification`    Creates a resource or
document.
L1709: def update_email_verification(    Function `update_email_verification`    utility or
script function.
L1755: def update_verification(    Function `update_verification`    utility or script function.
L1802: def create_phone_verification(    Function `create_phone_verification`    Creates a
resource or document.
L1829: def update_phone_verification(    Function `update_phone_verification`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/credit_card.py

```

L3: class CreditCard(Enum):    Class (`CreditCard`)    component used by the app (see file
context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/framework.py

```

L3: class Framework(Enum):    Class (`Framework`)    component used by the app (see file
context: None).

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/compression.py

```
L3: class Compression(Enum):    Class (`Compression`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/message_status.py

```
L3: class MessageStatus(Enum):    Class (`MessageStatus`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/image_gravity.py

```
L3: class ImageGravity(Enum):    Class (`ImageGravity`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/flag.py

```
L3: class Flag(Enum):    Class (`Flag`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/column_status.py

```
L3: class ColumnStatus(Enum):    Class (`ColumnStatus`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/authentication_factor.py

```
L3: class AuthenticationFactor(Enum):    Authentication component (`AuthenticationFactor`)
handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/project_policy.py

```
L3: class ProjectPolicy(Enum):    Class (`ProjectPolicy`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/scopes.py

```
L3: class Scopes(Enum):    Class (`Scopes`) component used by the app (see file context:
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/browser_permission.py

```
L3: class BrowserPermission(Enum):    Class (`BrowserPermission`) component used by the app
(see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/relation_mutate.py

```
L3: class RelationMutate(Enum):    Class (`RelationMutate`) component used by the app (see
file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/email_template_locale.py

```
L3: class EmailTemplateLocale(Enum):    Class (`EmailTemplateLocale`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/order_by.py

```
L3: class OrderBy(Enum):    Class (`OrderBy`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/runtime.py

```
L3: class Runtime(Enum):    Class (`Runtime`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/execution_method.py

```
L3: class ExecutionMethod(Enum):    Class (`ExecutionMethod`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/email_template_type.py

```
L3: class EmailTemplateType(Enum):    Class (`EmailTemplateType`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/protocol_id.py

```
L3: class ProtocolId(Enum):    Class (`ProtocolId`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/proxy_resource_type.py

```
L3: class ProxyResourceType(Enum):    Class (`ProxyResourceType`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/password_hash.py

```
L3: class PasswordHash(Enum):    Class (`PasswordHash`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/image_format.py

```
L3: class ImageFormat(Enum):    Class (`ImageFormat`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/message_priority.py

```
L3: class MessagePriority(Enum):    Class (`MessagePriority`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/status_code.py

```
L3: class StatusCode(Enum):    Class (`StatusCode`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/vcs_reference_type.py

```
L3: class VCSReferenceType(Enum):    Class (`VCSReferenceType`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/adapter.py

```
L3: class Adapter(Enum):    Class (`Adapter`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/index_status.py

```
L3: class IndexStatus(Enum):    Class (`IndexStatus`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/proxy_rule_status.py

```
L3: class ProxyRuleStatus(Enum):    Class (`ProxyRuleStatus`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/execution_status.py

```
L3: class ExecutionStatus(Enum):    Class (`ExecutionStatus`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/relationship_type.py

```
L3: class RelationshipType(Enum):    Class (`RelationshipType`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/browser.py

```
L3: class Browser(Enum):    Class (`Browser`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/smtp_encryption.py

```
L3: class SmtEncryption(Enum):    Class (`SmtEncryption`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/proxy_rule_deployment_resource_type.py

```
L3: class ProxyRuleDeploymentResourceType(Enum):    Class (`ProxyRuleDeploymentResourceType`)    component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/attribute_status.py

```
L3: class AttributeStatus(Enum):    Class (`AttributeStatus`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/backup_services.py

```
L3: class BackupServices(Enum):    Class (`BackupServices`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/authenticator_type.py

```
L3: class AuthenticatorType(Enum):    Authentication component (`AuthenticatorType`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/oauth_provider.py

```
L3: class OAuthProvider(Enum):    Authentication component (`OAuthProvider`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/deployment_download_type.py

```
L3: class DeploymentDownloadType(Enum):    Class (`DeploymentDownloadType`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/auth_method.py

```
L3: class AuthMethod(Enum):    Authentication component (`AuthMethod`) handles user authentication flows.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/theme.py

```
L3: class Theme(Enum):    Class (`Theme`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/deployment_status.py

```
L3: class DeploymentStatus(Enum):    Class (`DeploymentStatus`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/tables_db_index_type.py

```
L3: class TablesDBIndexType(Enum):    Class (`TablesDBIndexType`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/template_reference_type.py

```
L3: class TemplateReferenceType(Enum):    Class (`TemplateReferenceType`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/database_type.py

```
L3: class DatabaseType(Enum):    Database abstraction (`DatabaseType`) encapsulates DB access/setup.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/service_id.py

```
L3: class ServiceId(Enum):    Class (`ServiceId`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/build_runtime.py

```
L3: class BuildRuntime(Enum):    Class (`BuildRuntime`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/health_check_status.py

```
L3: class HealthCheckStatus(Enum):    Class (`HealthCheckStatus`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/platform_type.py

```
L3: class PlatformType(Enum):    Class (`PlatformType`) component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/secure.py

```
L3: class Secure(Enum):    Class (`Secure`)    component used by the app (see file context: None).
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/execution
_trigger.py**

```
L3: class ExecutionTrigger(Enum):    Class (`ExecutionTrigger`)    component used by the app  
(see file context: None).
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/messaging
g_provider_type.py**

```
L3: class MessagingProviderType(Enum):    Class (`MessagingProviderType`)    component used by  
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/name.py

```
L3: class Name(Enum):    Class (`Name`)    component used by the app (see file context: None).
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/databases
_index_type.py**

```
L3: class DatabasesIndexType(Enum):    Database abstraction (`DatabasesIndexType`)    encapsulates DB access/setup.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/health_ant

ivirus_status.py

```
L3: class HealthAntivirusStatus(Enum):    Class (`HealthAntivirusStatus`) component used by
the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/appwrite/enums/timezone.py

```
L3: class Timezone(Enum):    Class (`Timezone`) component used by the app (see file context:
None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/legacy.py

```
L12: class ResultDict(TypedDict):    Class (`ResultDict`) component used by the app (see file
context: None).
L18: def detect(    Function `detect` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/md.py

```
L14: def final(cls): # type: ignore[misc,no-untyped-def]    Function `final` utility or
script function.
L48: class CharInfo:    Class (`CharInfo`) component used by the app (see file context:
None).
L78: def __init__(self) -> None:    Function `__init__` utility or script function.
L97: def update(self, character: str) -> None:    Function `update` utility or script
function.
L206: class MessDetectorPlugin:    Class (`MessDetectorPlugin`) component used by the app
(see file context: None).
L214: def feed_info(self, character: str, info: CharInfo) -> None:    Function `feed_info`
utility or script function.
L221: def reset(self) -> None: # Defensive:    Function `reset` utility or script function.
L228: def ratio(self) -> float:    Function `ratio` utility or script function.
L237: class TooManySymbolOrPunctuationPlugin(MessDetectorPlugin):    Class
(`TooManySymbolOrPunctuationPlugin`) component used by the app (see file context: None).
L246: def __init__(self) -> None:    Function `__init__` utility or script function.
L254: def feed_info(self, character: str, info: CharInfo) -> None:    Function `feed_info`
```

```

utility or script function.
L269: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L275: def ratio(self) -> float: Function `ratio` utility or script function.
L287: class TooManyAccentuatedPlugin(MessDetectorPlugin): Class
(`TooManyAccentuatedPlugin`) component used by the app (see file context: None).
L290: def __init__(self) -> None: Function `__init__` utility or script function.
L294: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L301: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L306: def ratio(self) -> float: Function `ratio` utility or script function.
L315: class UnprintablePlugin(MessDetectorPlugin): Class (`UnprintablePlugin`) component
used by the app (see file context: None).
L318: def __init__(self) -> None: Function `__init__` utility or script function.
L322: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L333: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L337: def ratio(self) -> float: Function `ratio` utility or script function.
L345: class SuspiciousDuplicateAccentPlugin(MessDetectorPlugin): Class
(`SuspiciousDuplicateAccentPlugin`) component used by the app (see file context: None).
L353: def __init__(self) -> None: Function `__init__` utility or script function.
L360: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L375: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L382: def ratio(self) -> float: Function `ratio` utility or script function.
L390: class SuspiciousRange(MessDetectorPlugin): Class (`SuspiciousRange`) component used
by the app (see file context: None).
L398: def __init__(self) -> None: Function `__init__` utility or script function.
L404: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L427: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L434: def ratio(self) -> float: Function `ratio` utility or script function.
L446: class SuperWeirdWordPlugin(MessDetectorPlugin): Class (`SuperWeirdWordPlugin`)
component used by the app (see file context: None).
L463: def __init__(self) -> None: Function `__init__` utility or script function.
L481: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L556: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L572: def ratio(self) -> float: Function `ratio` utility or script function.
L580: class CjkUncommonPlugin(MessDetectorPlugin): Class (`CjkUncommonPlugin`) component
used by the app (see file context: None).
L587: def __init__(self) -> None: Function `__init__` utility or script function.
L591: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L598: def reset(self) -> None: # Abstract Function `reset` utility or script function.
L603: def ratio(self) -> float: Function `ratio` utility or script function.
L615: class ArchaicUpperLowerPlugin(MessDetectorPlugin): Class (`ArchaicUpperLowerPlugin`)
component used by the app (see file context: None).
L628: def __init__(self) -> None: Function `__init__` utility or script function.
L643: def feed_info(self, character: str, info: CharInfo) -> None: Function `feed_info`
utility or script function.
L688: def reset(self) -> None: # Abstract Function `reset` utility or script function.

```

```

L700: def ratio(self) -> float:    Function `ratio`    utility or script function.
L708: class ArabicIsolatedFormPlugin(MessDetectorPlugin):    Class
(`ArabicIsolatedFormPlugin`)    component used by the app (see file context: None).
L711: def __init__(self) -> None:    Function `__init__`    utility or script function.
L715: def reset(self) -> None:    # Abstract    Function `reset`    utility or script function.
L719: def feed_info(self, character: str, info: CharInfo) -> None:    Function `feed_info`
utility or script function.
L727: def ratio(self) -> float:    Function `ratio`    utility or script function.
L737: def is_suspiciously_successive_range(    Function `is_suspiciously_successive_range`
utility or script function.
L811: def mess_ratio(    Function `mess_ratio`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/model
s.py**

```

L12: class CharsetMatch:    Class (`CharsetMatch`)    component used by the app (see file
context: None).
L13: def __init__(    Function `__init__`    utility or script function.
L41: def __eq__(self, other: object) -> bool:    Object (singleton).
L48: def __lt__(self, other: object) -> bool:    Object (singleton).
L71: def multi_byte_usage(self) -> float:    Function `multi_byte_usage`    utility or script
function.
L74: def __str__(self) -> str:    Function `__str__`    utility or script function.
L90: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L93: def add_submatch(self, other: CharsetMatch) -> None:    Function `add_submatch`    utility
or script function.
L105: def encoding(self) -> str:    Function `encoding`    utility or script function.
L109: def encoding_aliases(self) -> list[str]:    Function `encoding_aliases`    utility or
script function.
L122: def bom(self) -> bool:    Function `bom`    utility or script function.
L126: def byte_order_mark(self) -> bool:    Function `byte_order_mark`    utility or script
function.
L130: def languages(self) -> list[str]:    Function `languages`    utility or script function.
L138: def language(self) -> str:    Function `language`    utility or script function.
L166: def chaos(self) -> float:    Function `chaos`    utility or script function.
L170: def coherence(self) -> float:    Function `coherence`    utility or script function.
L176: def percent_chaos(self) -> float:    Function `percent_chaos`    utility or script
function.
L180: def percent_coherence(self) -> float:    Function `percent_coherence`    utility or script
function.
L184: def raw(self) -> bytes | bytearray:    Function `raw`    utility or script function.
L191: def submatch(self) -> list[CharsetMatch]:    Function `submatch`    utility or script
function.
L195: def has_submatch(self) -> bool:    Function `has_submatch`    utility or script function.
L199: def alphabets(self) -> list[str]:    Function `alphabets`    utility or script function.
L209: def could_be_from_charset(self) -> list[str]:    Function `could_be_from_charset`

```

```

utility or script function.
L217: def output(self, encoding: str = "utf_8") -> bytes:    Function `output`    utility or
script function.
L247: def fingerprint(self) -> int:    Function `fingerprint`    utility or script function.
L254: class CharsetMatches:    Class (`CharsetMatches`)    component used by the app (see file
context: None).
L260: def __init__(self, results: list[CharsetMatch] | None = None):    Function `__init__`
utility or script function.
L263: def __iter__(self) -> Iterator[CharsetMatch]:    Function `__iter__`    utility or script
function.
L266: def __getitem__(self, item: int | str) -> CharsetMatch:    Function `__getitem__`
utility or script function.
L280: def __len__(self) -> int:    Function `__len__`    utility or script function.
L283: def __bool__(self) -> bool:    Function `__bool__`    utility or script function.
L286: def append(self, item: CharsetMatch) -> None:    Function `append`    utility or script
function.
L306: def best(self) -> CharsetMatch | None:    Function `best`    utility or script function.
L314: def first(self) -> CharsetMatch | None:    Function `first`    utility or script function.
L325: class CliDetectionResult:    Class (`CliDetectionResult`)    component used by the app
(see file context: None).
L326: def __init__(    Function `__init__`    utility or script function.
L353: def __dict__(self) -> dict[str, Any]:    # type: ignore    Function `__dict__`    utility or
script function.
L368: def to_json(self) -> str:    Function `to_json`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/api.py

```

L57: def from_bytes(    Function `from_bytes`    utility or script function.
L864: def from_fp(    Function `from_fp`    utility or script function.
L894: def from_path(    Function `from_path`    utility or script function.
L925: def is_binary(    Function `is_binary`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/utls.py

```

L39: def _character_flags(character: str) -> int:    Function `_character_flags`    utility or
script function.
L74: def is_accentuated(character: str) -> bool:    Function `is_accentuated`    utility or
script function.
L79: def remove_accent(character: str) -> str:    Function `remove_accent`    utility or script
function.
L99: def unicode_range(character: str) -> str | None:    Function `unicode_range`    utility or

```

```

script function.
L116: def is_latin(character: str) -> bool:    Function `is_latin` utility or script
function.
L121: def is_punctuation(character: str) -> bool:    Function `is_punctuation` utility or
script function.
L136: def is_symbol(character: str) -> bool:    Function `is_symbol` utility or script
function.
L151: def is_emoticon(character: str) -> bool:    Function `is_emoticon` utility or script
function.
L161: def is_separator(character: str) -> bool:    Function `is_separator` utility or script
function.
L171: def is_case_variable(character: str) -> bool:    Function `is_case_variable` utility or
script function.
L176: def is_cjk(character: str) -> bool:    Function `is_cjk` utility or script function.
L181: def is_hiragana(character: str) -> bool:    Function `is_hiragana` utility or script
function.
L186: def is_katakana(character: str) -> bool:    Function `is_katakana` utility or script
function.
L191: def is_hangul(character: str) -> bool:    Function `is_hangul` utility or script
function.
L196: def is_thai(character: str) -> bool:    Function `is_thai` utility or script function.
L201: def is_arabic(character: str) -> bool:    Function `is_arabic` utility or script
function.
L206: def is_arabic_isolated_form(character: str) -> bool:    Function
`is_arabic_isolated_form` utility or script function.
L211: def is_cjk_uncommon(character: str) -> bool:    Function `is_cjk_uncommon` utility or
script function.
L216: def is_unicode_range_secondary(range_name: str) -> bool:    Function
`is_unicode_range_secondary` utility or script function.
L221: def is_unprintable(character: str) -> bool:    Function `is_unprintable` utility or
script function.
L231: def any_specified_encoding(    Function `any_specified_encoding` utility or script
function.
L266: def is_multi_byte_encoding(name: str) -> bool:    Function `is_multi_byte_encoding`
utility or script function.
L286: def identify_sig_or_bom(sequence: bytes | bytearray) -> tuple[str | None, bytes]:
Function `identify_sig_or_bom` utility or script function.
L304: def should_strip_sig_or_bom(iana_encoding: str) -> bool:    Function
`should_strip_sig_or_bom` utility or script function.
L308: def iana_name(cp_name: str, strict: bool = True) -> str:    Function `iana_name`
utility or script function.
L325: def cp_similarity(iana_name_a: str, iana_name_b: str) -> float:    Function
`cp_similarity` utility or script function.
L345: def is_cp_similar(iana_name_a: str, iana_name_b: str) -> bool:    Function
`is_cp_similar` utility or script function.
L356: def set_logging_handler(    Function `set_logging_handler` Sets or updates a value.
L369: def cut_sequence_chunks(    Function `cut_sequence_chunks` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/cd.py

```

L29: def encoding_unicode_range(iana_name: str) -> list[str]:    Function
`encoding_unicode_range` utility or script function.
L68: def unicode_range_languages(primary_range: str) -> list[str]:    Function
`unicode_range_languages` utility or script function.
L84: def encoding_languages(iana_name: str) -> list[str]:    Function `encoding_languages`
utility or script function.
L104: def mb_encoding_languages(iana_name: str) -> list[str]:    Function
`mb_encoding_languages` utility or script function.
L125: def get_target_features(language: str) -> tuple[bool, bool]:    Function
`get_target_features` Returns or fetches data.
L141: def alphabet_languages(    Function `alphabet_languages` utility or script function.
L175: def characters_popularity_compare(    Function `characters_popularity_compare` utility
or script function.
L276: def alpha_unicode_split(decoded_sequence: str) -> list[str]:    Function
`alpha_unicode_split` utility or script function.
L350: def merge_coherence_ratios(results: list[CoherenceMatches]) -> CoherenceMatches:
Function `merge_coherence_ratios` utility or script function.
L378: def filter_alt_coherence_matches(results: CoherenceMatches) -> CoherenceMatches:
Function `filter_alt_coherence_matches` utility or script function.
L406: def coherence_ratio(    Function `coherence_ratio` utility or script function.

```

Q_base**appwrite/.venv/lib/python3.12/site-packages/charset_normalizer/cli/__main__.py**

```

L17: def query_yes_no(question: str, default: str = "yes") -> bool:    # Defensive:    Function
`query_yes_no` utility or script function.
L32: class FileType:    Class (`FileType`) component used by the app (see file context:
None).
L51: def __init__(    Function `__init__` utility or script function.
L63: def __call__(self, string: str) -> typing.IO:    # type: ignore[type-arg]    Function
`__call__` utility or script function.
L81: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L91: def cli_detect(argv: list[str] | None = None) -> int:    Function `cli_detect` utility
or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/parser.py

```

L14: def make_regex(string: str, extra_flags: int = 0) -> Pattern[str]:    Function
`make_regex` utility or script function.
L35: class Original(NamedTuple):    Class (`Original`) component used by the app (see file
context: None).

```



```

L40: class Binding(NamedTuple):    Class (`Binding`)    component used by the app (see file
context: None).
L47: class Position:    Class (`Position`)    component used by the app (see file context:
None).
L48: def __init__(self, chars: int, line: int) -> None:    Function `__init__`    utility or
script function.
L53: def start(cls) -> "Position":    Function `start`    utility or script function.
L56: def set(self, other: "Position") -> None:    Function `set`    Sets or updates a value.
L60: def advance(self, string: str) -> None:    Function `advance`    utility or script
function.
L65: class Error(Exception):    Class (`Error`)    component used by the app (see file context:
None).
L69: class Reader:    Class (`Reader`)    component used by the app (see file context: None).
L70: def __init__(self, stream: IO[str]) -> None:    Function `__init__`    utility or script
function.
L75: def has_next(self) -> bool:    Function `has_next`    utility or script function.
L78: def set_mark(self) -> None:    Function `set_mark`    Sets or updates a value.
L81: def get_marked(self) -> Original:    Function `get_marked`    Returns or fetches data.
L87: def peek(self, count: int) -> str:    Function `peek`    utility or script function.
L90: def read(self, count: int) -> str:    Function `read`    utility or script function.
L97: def read_regex(self, regex: Pattern[str]) -> Sequence[str]:    Function `read_regex`
utility or script function.
L105: def decode_escapes(regex: Pattern[str], string: str) -> str:    Function
`decode_escapes`    utility or script function.
L106: def decode_match(match: Match[str]) -> str:    Function `decode_match`    utility or
script function.
L112: def parse_key(reader: Reader) -> Optional[str]:    Function `parse_key`    utility or
script function.
L123: def parse_unquoted_value(reader: Reader) -> str:    Function `parse_unquoted_value`
utility or script function.
L128: def parse_value(reader: Reader) -> str:    Function `parse_value`    utility or script
function.
L142: def parse_binding(reader: Reader) -> Binding:    Function `parse_binding`    utility or
script function.
L179: def parse_stream(stream: IO[str]) -> Iterator[Binding]:    Function `parse_stream`
utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/__init__.py

```

L6: def load_ipython_extension(ipython: Any) -> None:    Function `load_ipython_extension`
Loads data from storage or remote.
L12: def get_cli_string(    Function `get_cli_string`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/dotenv/variables.py

```

L18: class Atom(metaclass=ABCMeta):  Class (`Atom`)  component used by the app (see file
context: None).
L19: def __ne__(self, other: object) -> bool:  Object (singleton).
L26: def resolve(self, env: Mapping[str, Optional[str]]) -> str: ...  Function `resolve`
utility or script function.
L29: class Literal(Atom):  Class (`Literal`)  component used by the app (see file context:
None).
L30: def __init__(self, value: str) -> None:  Function `__init__`  utility or script
function.
L33: def __repr__(self) -> str:  Function `__repr__`  utility or script function.
L36: def __eq__(self, other: object) -> bool:  Object (singleton).
L41: def __hash__(self) -> int:  Function `__hash__`  utility or script function.
L44: def resolve(self, env: Mapping[str, Optional[str]]) -> str:  Function `resolve`
utility or script function.
L48: class Variable(Atom):  Class (`Variable`)  component used by the app (see file context:
None).
L49: def __init__(self, name: str, default: Optional[str]) -> None:  Function `__init__`
utility or script function.
L53: def __repr__(self) -> str:  Function `__repr__`  utility or script function.
L56: def __eq__(self, other: object) -> bool:  Object (singleton).
L61: def __hash__(self) -> int:  Function `__hash__`  utility or script function.
L64: def resolve(self, env: Mapping[str, Optional[str]]) -> str:  Function `resolve`
utility or script function.
L70: def parse_variables(value: str) -> Iterator[Atom]:  Function `parse_variables`  utility
or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/cli.py

```

L24: def enumerate_env() -> Optional[str]:  Function `enumerate_env`  utility or script
function.
L62: def cli(ctx: click.Context, file: Any, quote: Any, export: Any) -> None:  Function
`cli`  utility or script function.
L68: def stream_file(path: os.PathLike) -> Iterator[IO[str]]:  Function `stream_file`
utility or script function.
L93: def list_values(ctx: click.Context, output_format: str) -> None:  Function
`list_values`  utility or script function.
L116: def set_value(ctx: click.Context, key: Any, value: Any) -> None:  Function `set_value`
Sets or updates a value.
L137: def get(ctx: click.Context, key: Any) -> None:  Function `get`  Returns or fetches
data.
L154: def unset(ctx: click.Context, key: Any) -> None:  Function `unset`  utility or script
function.
L184: def run(ctx: click.Context, override: bool, cmdline: tuple[str, ...]) -> None:
Function `run`  utility or script function.
L204: def run_command(command: List[str], env: Dict[str, str]) -> None:  Function
`run_command`  utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/ipython.py

```
L12: class IPythonDotEnv(Magics):    Class (`IPythonDotEnv`) component used by the app (see
file context: None).
L34: def dotenv(self, line):    Function `dotenv` utility or script function.
L48: def load_ipython_extension(ipython):    Function `load_ipython_extension` Loads data
from storage or remote.
```

Q_base appwrite/.venv/lib/python3.12/site-packages/dotenv/main.py

```
L22: def _load_dotenv_disabled() -> bool:    Function `_load_dotenv_disabled` utility or
script function.
L32: def with_warn_for_invalid_lines(mappings: Iterator[Binding]) -> Iterator[Binding]:
Function `with_warn_for_invalid_lines` utility or script function.
L42: class DotEnv:    Class (`DotEnv`) component used by the app (see file context: None).
L43: def __init__(    Function `__init__` utility or script function.
L61: def _get_stream(self) -> Iterator[IO[str]]:    Function `_get_stream` utility or script
function.
L75: def dict(self) -> Dict[str, Optional[str]]:    Function `dict` utility or script
function.
L91: def parse(self) -> Iterator[Tuple[str, Optional[str]]]:    Function `parse` utility or
script function.
L97: def set_as_environment_variables(self) -> bool:    Function
`set_as_environment_variables` Sets or updates a value.
L112: def get(self, key: str) -> Optional[str]:    Function `get` Returns or fetches data.
L125: def get_key(    Function `get_key` Returns or fetches data.
L139: def rewrite(    Function `rewrite` utility or script function.
L193: def set_key(    Function `set_key` Sets or updates a value.
L248: def unset_key(    Function `unset_key` utility or script function.
L289: def resolve_variables(    Function `resolve_variables` utility or script function.
L314: def _walk_to_root(path: str) -> Iterator[str]:    Function `_walk_to_root` utility or
script function.
L332: def find_dotenv(    Function `find_dotenv` utility or script function.
L343: def _is_interactive():    Function `_is_interactive` utility or script function.
L353: def _is_debugger():    Function `_is_debugger` utility or script function.
L383: def load_dotenv(    Function `load_dotenv` Loads data from storage or remote.
L432: def dotenv_values(    Function `dotenv_values` utility or script function.
L468: def _is_file_or_fifo(path: StrPath) -> bool:    Function `_is_file_or_fifo` utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_core_metadata_a.py

```

L28: def get_metadata_version(self):    Function `get_metadata_version` Returns or fetches
data.
L36: def rfc822_unescape(content: str) -> str:    Function `rfc822_unescape` utility or
script function.
L44: def _read_field_from_msg(msg: Message, field: str) -> str | None:    Function
`_read_field_from_msg` utility or script function.
L52: def _read_field_unescaped_from_msg(msg: Message, field: str) -> str | None:    Function
`_read_field_unescaped_from_msg` utility or script function.
L60: def _read_list_from_msg(msg: Message, field: str) -> list[str] | None:    Function
`_read_list_from_msg` utility or script function.
L68: def _read_payload_from_msg(msg: Message) -> str | None:    Function
`_read_payload_from_msg` utility or script function.
L75: def read_pkg_file(self, file):    Function `read_pkg_file` utility or script function.
L117: def single_line(val):    Function `single_line` utility or script function.
L131: def write_pkg_info(self, base_dir):    Function `write_pkg_info` utility or script
function.
L150: def write_pkg_file(self, file):    # noqa: C901 # is too complex (14) # FIXME
Function `write_pkg_file` utility or script function.
L154: def write_field(key, value):    Function `write_field` utility or script function.
L225: def _write_requirements(self, file):    Function `_write_requirements` utility or
script function.
L245: def _include_extra(req: str, extra: str, condition: str) -> Requirement:    Function
`_include_extra` utility or script function.
L256: def _write_provides_extra(file, processed_extras, safe, unsafe):    Function
`_write_provides_extra` utility or script function.
L274: def get_fullname(self):    Function `get_fullname` Returns or fetches data.
L278: def _distribution_fullname(name: str, version: str) -> str:    Function
`_distribution_fullname` utility or script function.
L297: def _safe_license_file(file):    Function `_safe_license_file` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_normalization.
py**

```

L20: def safe_identifier(name: str) -> str:    Function `safe_identifier` utility or script
function.
L32: def safe_name(component: str) -> str:    Function `safe_name` utility or script
function.
L44: def safe_version(version: str) -> str:    Function `safe_version` utility or script
function.
L69: def best_effort_version(version: str) -> str:    Function `best_effort_version` utility
or script function.
L101: def safe_extra(extra: str) -> str:    Function `safe_extra` utility or script function.
L111: def filename_component(value: str) -> str:    Function `filename_component` utility or
script function.
L120: def filename_component_broken(value: str) -> str:    Function

```

```

`filename_component_broken` utility or script function.
L135: def safer_name(value: str) -> str: Function `safer_name` utility or script function.
L148: def safer_best_effort_version(value: str) -> str: Function
`safer_best_effort_version` utility or script function.
L155: def _missing_canonicalize_license_expression(expression: str) -> str: Function
`_missing_canonicalize_license_expression` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/discovery.py

```

L63: def _valid_name(path: StrPath) -> bool: Function `_valid_name` utility or script
function.
L68: class _Filter: Class (`_Filter`) component used by the app (see file context: None).
L74: def __init__(self, *patterns: str) -> None: Function `__init__` utility or script
function.
L77: def __call__(self, item: str) -> bool: Function `__call__` utility or script
function.
L80: def __contains__(self, item: str) -> bool: Function `__contains__` utility or script
function.
L84: class _Finder: Class (`_Finder`) component used by the app (see file context: None).
L91: def find( Function `find` utility or script function.
L126: def _find_iter( Function `_find_iter` utility or script function.
L132: class PackageFinder(_Finder): Class (`PackageFinder`) component used by the app (see
file context: None).
L140: def _find_iter( Function `_find_iter` utility or script function.
L174: def _looks_like_package(path: StrPath, _package_name: str) -> bool: Function
`_looks_like_package` utility or script function.
L179: class PEP420PackageFinder(PackageFinder): Class (`PEP420PackageFinder`) component
used by the app (see file context: None).
L181: def _looks_like_package(_path: StrPath, _package_name: str) -> bool: Function
`_looks_like_package` utility or script function.
L185: class ModuleFinder(_Finder): Class (`ModuleFinder`) component used by the app (see
file context: None).
L191: def _find_iter( Function `_find_iter` utility or script function.
L210: class FlatLayoutPackageFinder(PEP420PackageFinder): Class (`FlatLayoutPackageFinder`)
component used by the app (see file context: None).
L256: def _looks_like_package(_path: StrPath, package_name: str) -> bool: Function
`_looks_like_package` utility or script function.
L263: class FlatLayoutModuleFinder(ModuleFinder): Class (`FlatLayoutModuleFinder`)
component used by the app (see file context: None).
L293: def _find_packages_within(root_pkg: str, pkg_dir: StrPath) -> list[str]: Function
`_find_packages_within` utility or script function.
L298: class ConfigDiscovery: Class (`ConfigDiscovery`) component used by the app (see file
context: None).
L303: def __init__(self, distribution: Distribution) -> None: Function `__init__` utility
or script function.
L309: def _disable(self): Function `_disable` utility or script function.
L313: def _ignore_ext_modules(self): Function `_ignore_ext_modules` utility or script

```

```

function.
L326: def _root_dir(self) -> StrPath:    Function `_root_dir`    utility or script function.
L331: def _package_dir(self) -> dict[str, str]:    Function `_package_dir`    utility or script
function.
L336: def __call__(    Function `__call__`    utility or script function.
L359: def _explicitly_specified(self, ignore_ext_modules: bool) -> bool:    Function
`_explicitly_specified`    utility or script function.
L372: def _analyse_package_layout(self, ignore_ext_modules: bool) -> bool:    Function
`_analyse_package_layout`    utility or script function.
L390: def _analyse_explicit_layout(self) -> bool:    Function `_analyse_explicit_layout`
utility or script function.
L408: def _analyse_src_layout(self) -> bool:    Function `_analyse_src_layout`    utility or
script function.
L433: def _analyse_flat_layout(self) -> bool:    Function `_analyse_flat_layout`    utility or
script function.
L446: def _analyse_flat_packages(self) -> bool:    Function `_analyse_flat_packages`    utility
or script function.
L453: def _analyse_flat_modules(self) -> bool:    Function `_analyse_flat_modules`    utility or
script function.
L459: def _ensure_no_accidental_inclusion(self, detected: list[str], kind: str):    Function
`_ensure_no_accidental_inclusion`    utility or script function.
L482: def analyse_name(self) -> None:    Function `analyse_name`    utility or script function.
L499: def _find_name_single_package_or_module(self) -> str | None:    Function
`_find_name_single_package_or_module`    utility or script function.
L509: def _find_name_from_packages(self) -> str | None:    Function `_find_name_from_packages`
utility or script function.
L526: def remove_nested_packages(packages: list[str]) -> list[str]:    Function
`remove_nested_packages`    utility or script function.
L544: def remove_stubs(packages: list[str]) -> list[str]:    Function `remove_stubs`    utility
or script function.
L553: def find_parent_package(    Function `find_parent_package`    utility or script function.
L577: def find_package_path(    Function `find_package_path`    utility or script function.
L611: def construct_package_dir(packages: list[str], package_path: StrPath) -> dict[str,
str]:    Function `construct_package_dir`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/installer.py

```

L22: def _fixup_find_links(find_links):    Function `_fixup_find_links`    utility or script
function.
L30: def fetch_build_egg(dist, req) -> metadata.Distribution | metadata.PathDistribution:
Function `fetch_build_egg`    utility or script function.
L39: def _present(req):    Function `_present`    utility or script function.
L43: def _fetch_build_eggs(dist, requires: _reqs.StrOrIter) -> list[metadata.Distribution]:
Function `_fetch_build_eggs`    utility or script function.
L62: def _dist_matches_req(egg_dist, req):    Function `_dist_matches_req`    utility or script
function.
L70: def _fetch_build_egg_no_warn(dist, req):    # noqa: C901    # is too complex (16)    # FIXME

```

```

Function `_fetch_build_egg_no_warn` utility or script function.
L130: def strip_marker(req) -> packaging.requirements.Requirement: Function `_strip_marker`
utility or script function.
L142: def _warn_wheel_not_available(dist): Function `_warn_wheel_not_available` utility or
script function.
L149: class _DeprecatedInstaller(SetuptoolsDeprecationWarning): Class
(`_DeprecatedInstaller`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_imp.py

```

L19: def find_spec(module, paths): Function `_find_spec` utility or script function.
L28: def find_module(module, paths=None): Function `_find_module` utility or script
function.
L76: def get_frozen_object(module, paths=None): Function `_get_frozen_object` Returns or
fetches data.
L83: def get_module(module, paths, info): Function `_get_module` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/archive_util.py

```

L25: class UnrecognizedFormat(DistutilsError): Class (`UnrecognizedFormat`) component used
by the app (see file context: None).
L29: def default_filter(src, dst): Function `_default_filter` utility or script function.
L34: def unpack_archive( Function `_unpack_archive` utility or script function.
L68: def unpack_directory(filename, extract_dir, progress_filter=default_filter) -> None:
Function `_unpack_directory` utility or script function.
L95: def unpack_zipfile(filename, extract_dir, progress_filter=default_filter) -> None:
Function `_unpack_zipfile` utility or script function.
L110: def _unpack_zipfile_obj(zipfile_obj, extract_dir, progress_filter=default_filter):
Function `_unpack_zipfile_obj` utility or script function.
L140: def _resolve_tar_file_or_dir(tar_obj, tar_member_obj): Function
`_resolve_tar_file_or_dir` utility or script function.
L161: def _iter_open_tar(tar_obj, extract_dir, progress_filter): Function `_iter_open_tar`
utility or script function.
L190: def unpack_tarfile(filename, extract_dir, progress_filter=default_filter) -> bool:
Function `_unpack_tarfile` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_entry_points.py

```

L14: def ensure_valid(ep):    Function `ensure_valid` utility or script function.
L34: def load_group(value, group):    Function `load_group` Loads data from storage or
remote.
L45: def by_group_and_name(ep):    Function `by_group_and_name` utility or script function.
L49: def validate(eps: metadata.EntryPoints):    Function `validate` utility or script
function.
L58: def load(eps):    Function `load` Loads data from storage or remote.
L69: def _(eps):    Function `_` utility or script function.
L86: def render(eps: metadata.EntryPoints):    Function `render` utility or script function.
L93: def render_items(eps):    Function `render_items` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_reqs.py

```

L23: def parse_strings(strs: _StrOrIter) -> Iterator[str]:    Function `parse_strings`
utility or script function.
L35: def parse(strs: _StrOrIter) -> Iterator[Requirement]: ...    Function `parse` utility or
script function.
L37: def parse(strs: _StrOrIter, parser: Callable[[str], _T]) -> Iterator[_T]: ...    Function
`parse` utility or script function.
L38: def parse(strs: _StrOrIter, parser: Callable[[str], _T] = parse_req) -> Iterator[_T]: #
type: ignore[assignment]    Function `parse` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/setuptools/dist.py

```

L73: def __getattr__(name: str) -> Any: # pragma: no cover    Function `__getattr__` utility
or script function.
L84: def check_importable(dist, attr, value):    Function `check_importable` utility or
script function.
L94: def assert_string_list(dist, attr: str, value: _Sequence) -> None:    Function
`assert_string_list` utility or script function.
L108: def check_nsp(dist, attr, value):    Function `check_nsp` utility or script function.
L136: def check_extras(dist, attr, value):    Function `check_extras` utility or script
function.
L148: def _check_extra(extra, reqs):    Function `_check_extra` utility or script function.
L158: def _check_marker(marker):    Function `_check_marker` utility or script function.
L165: def assert_bool(dist, attr, value):    Function `assert_bool` utility or script
function.
L171: def invalid_unless_false(dist, attr, value):    Function `invalid_unless_false` utility
or script function.
L179: def check_requirements(dist, attr: str, value: _OrderedStrSequence) -> None:    Function
`check_requirements` utility or script function.
L193: def check_specifier(dist, attr, value):    Function `check_specifier` utility or script
function.
L202: def check_entry_points(dist, attr, value):    Function `check_entry_points` utility or
script function.

```



```

L210: def check_package_data(dist, attr, value):  Function `check_package_data` utility or
function.
L225: def check_packages(dist, attr, value):  Function `check_packages` utility or script
function.
L242: class Distribution(_Distribution):  Class (`Distribution`) component used by the app
(see file context: None).
L303: def __init__(self, attrs: MutableMapping[str, Any] | None = None) -> None:  Function
`__init__` utility or script function.
L335: def _validate_metadata(self):  Function `_validate_metadata` utility or script
function.
L348: def _set_metadata_defaults(self, attrs):  Function `_set_metadata_defaults` utility
or script function.
L359: def _normalize_version(version):  Function `_normalize_version` utility or script
function.
L374: def _finalize_requires(self):  Function `_finalize_requires` utility or script
function.
L393: def _normalize_requires(self):  Function `_normalize_requires` utility or script
function.
L407: def _finalize_license_expression(self) -> None:  Function
`_finalize_license_expression` utility or script function.
L447: def _finalize_license_files(self) -> None:  Function `_finalize_license_files`
utility or script function.
L468: def _expand_patterns(  Function `_expand_patterns` utility or script function.
L488: def _find_pattern(pattern: str, enforce_match: bool = True) -> list[str]:  Function
`_find_pattern` utility or script function.
L546: def _parse_config_files(self, filenames=None):  # noqa: C901  Function
`_parse_config_files` utility or script function.
L625: def _enforce_underscore(self, opt: str, section: str) -> str:  Function
`_enforce_underscore` utility or script function.
L648: def _enforce_option_lowercase(self, opt: str, section: str) -> str:  Function
`_enforce_option_lowercase` utility or script function.
L671: def _skip_setupcfg_normalization(self, section: str) -> bool:  Function
`_skip_setupcfg_normalization` utility or script function.
L681: def _is_setuptools_section(self, section: str) -> bool:  Function
`_is_setuptools_section` utility or script function.
L689: def _set_command_options(self, command_obj, option_dict=None):  # noqa: C901  Function
`_set_command_options` utility or script function.
L734: def _get_project_config_files(self, filenames: Iterable[StrPath] | None):  Function
`_get_project_config_files` utility or script function.
L746: def parse_config_files(  Function `parse_config_files` utility or script function.
L768: def fetch_build_eggs(self, requires: _StrOrIter) -> list[metadata.Distribution]:
Function `fetch_build_eggs` utility or script function.
L774: def finalize_options(self) -> None:  Function `finalize_options` utility or script
function.
L783: def by_order(hook):  Function `by_order` utility or script function.
L793: def _removed(ep):  Function `_removed` utility or script function.
L806: def _finalize_setup_keywords(self):  Function `_finalize_setup_keywords` utility or
script function.
L812: def get_egg_cache_dir(self) -> str:  Function `get_egg_cache_dir` Returns or fetches
data.
L833: def fetch_build_egg(self, req):  Function `fetch_build_egg` utility or script

```

```

function.
L839: def get_command_class(self, command: str) -> type[distutils.cmd.Command]: # type:
ignore[override] # Not doing complex overrides yet Function `get_command_class` Returns or
fetches data.
L857: def print_commands(self): Function `print_commands` utility or script function.
L864: def get_command_list(self): Function `get_command_list` Returns or fetches data.
L871: def include(self, **attrs) -> None: Function `include` utility or script function.
L893: def exclude_package(self, package: str) -> None: Function `exclude_package` utility
or script function.
L914: def has_contents_for(self, package: str) -> bool: Function `has_contents_for`
utility or script function.
L925: def _exclude_misc(self, name: str, value: _Sequence) -> None: Function
`_exclude_misc` utility or script function.
L942: def _include_misc(self, name: str, value: _Sequence) -> None: Function
`_include_misc` utility or script function.
L963: def exclude(self, **attrs) -> None: Function `exclude` utility or script function.
L986: def _exclude_packages(self, packages: _Sequence) -> None: Function
`_exclude_packages` utility or script function.
L993: def _parse_command_opts(self, parser, args): Function `_parse_command_opts` utility
or script function.
L1020: def get_cmdline_options(self) -> dict[str, dict[str, str | None]]: Function
`get_cmdline_options` Returns or fetches data.
L1059: def iter_distribution_names(self) -> Iterator[str]: Function
`iter_distribution_names` utility or script function.
L1074: def handle_display_options(self, option_order): Function `handle_display_options`
utility or script function.
L1102: def run_command(self, command) -> None: Function `run_command` utility or script
function.
L1111: def _setuptools_commands() -> set[str]: Function `_setuptools_commands` utility or
script function.
L1122: class DistDeprecationWarning(SetuptoolsDeprecationWarning): Class
(`DistDeprecationWarning`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/depends.py

```

L20: class Require: Class (`Require`) component used by the app (see file context: None).
L23: def __init__( Function `__init__` utility or script function.
L43: def full_name(self): Function `full_name` utility or script function.
L49: def version_ok(self, version): Function `version_ok` utility or script function.
L58: def get_version( Function `get_version` Returns or fetches data.
L87: def is_present(self, paths=None): Function `is_present` utility or script function.
L91: def is_current(self, paths=None): Function `is_current` utility or script function.
L99: def maybe_close(f): Function `maybe_close` utility or script function.
L101: def empty(): Function `empty` utility or script function.
L115: def get_module_constant( Function `get_module_constant` Returns or fetches data.
L145: def extract_constant( Function `extract_constant` utility or script function.

```

Q_base appwrite/.venv/lib/python3.12/site-packages/setuptools/glob.py

```

L23: def glob(pathname: AnyStr, recursive: bool = False) -> list[AnyStr]:    Function `glob`
utility or script function.
L37: def iglob(pathname: AnyStr, recursive: bool = False) -> Iterator[AnyStr]:    Function
`iglob` utility or script function.
L55: def _iglob(pathname: AnyStr, recursive: bool) -> Iterator[AnyStr]:    Function `_iglob`
utility or script function.
L92: def glob1(dirname: StrPath, pattern: str) -> list[str]: ...    Function `glob1` utility
or script function.
L94: def glob1(dirname: BytesPath, pattern: bytes) -> list[bytes]: ...    Function `glob1`
utility or script function.
L95: def glob1(dirname: StrOrBytesPath, pattern: str | bytes) -> list[str] | list[bytes]:
Function `glob1` utility or script function.
L109: def glob0(dirname, basename):    Function `glob0` utility or script function.
L126: def glob2(dirname: StrPath, pattern: str) -> Iterator[str]: ...    Function `glob2`
utility or script function.
L128: def glob2(dirname: BytesPath, pattern: bytes) -> Iterator[bytes]: ...    Function
`glob2` utility or script function.
L129: def glob2(dirname: StrOrBytesPath, pattern: str | bytes) -> Iterator[str | bytes]:
Function `glob2` utility or script function.
L137: def _rlistdir(dirname: StrPath) -> Iterator[str]: ...    Function `_rlistdir` utility
or script function.
L139: def _rlistdir(dirname: BytesPath) -> Iterator[bytes]: ...    Function `_rlistdir`
utility or script function.
L140: def _rlistdir(dirname: StrOrBytesPath) -> Iterator[str | bytes]:    Function `_rlistdir`
utility or script function.
L162: def has_magic(s: str | bytes) -> bool:    Function `has_magic` utility or script
function.
L169: def _isrecursive(pattern: str | bytes) -> bool:    Function `_isrecursive` utility or
script function.
L176: def escape(pathname):    Function `escape` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/logging.py

```

L10: def _not_warning(record):    Function `_not_warning` utility or script function.
L14: def configure() -> None:    Function `configure` utility or script function.
L38: def set_threshold(level: int) -> int:    Function `set_threshold` Sets or updates a
value.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_scripts.py

```

L25: class _SplitArgs(TypedDict, total=False):  Class (`_SplitArgs`)  component used by the
app (see file context: None).
L30: class CommandSpec(list):  Class (`CommandSpec`)  component used by the app (see file
context: None).
L40: def best(cls):  Function `best`  utility or script function.
L47: def _sys_executable(cls):  Function `_sys_executable`  utility or script function.
L52: def from_param(cls, param: Self | str | Iterable[str] | None) -> Self:  Function
`from_param`  utility or script function.
L68: def from_environment(cls):  Function `from_environment`  utility or script function.
L72: def from_string(cls, string: str) -> Self:  Function `from_string`  utility or script
function.
L80: def install_options(self, script_text: str):  Function `install_options`  utility or
script function.
L87: def _extract_options(orig_script):  Function `_extract_options`  utility or script
function.
L96: def as_header(self):  Function `as_header`  utility or script function.
L100: def _strip_quotes(item):  Function `_strip_quotes`  utility or script function.
L108: def _render(items):  Function `_render`  utility or script function.
L115: class WindowsCommandSpec(CommandSpec):  Class (`WindowsCommandSpec`)  component used
by the app (see file context: None).
L119: class ScriptWriter:  Class (`ScriptWriter`)  component used by the app (see file
context: None).
L143: def importlib_load_entry_point(spec, group, name):  Function
`importlib_load_entry_point`  utility or script function.
L165: def get_args(cls, dist, header=None):  Function `get_args`  Returns or fetches data.
L190: def _ensure_safe_name(name):  Function `_ensure_safe_name`  utility or script
function.
L199: def best(cls):  Function `best`  utility or script function.
L209: def _get_script_args(cls, type_, name, header, script_text):  Function
`_get_script_args`  utility or script function.
L214: def get_header(  Function `get_header`  Returns or fetches data.
L225: class WindowsScriptWriter(ScriptWriter):  Class (`WindowsScriptWriter`)  component
used by the app (see file context: None).
L229: def best(cls):  Function `best`  utility or script function.
L242: def _get_script_args(cls, type_, name, header, script_text):  Function
`_get_script_args`  utility or script function.
L258: def _adjust_header(cls, type_, orig_header):  Function `_adjust_header`  utility or
script function.
L272: def _use_header(new_header):  Function `_use_header`  utility or script function.
L284: class WindowsExecutableLauncherWriter(WindowsScriptWriter):  Class
(`WindowsExecutableLauncherWriter`)  component used by the app (see file context: None).
L286: def _get_script_args(cls, type_, name, header, script_text):  Function
`_get_script_args`  utility or script function.
L316: def get_win_launcher(type):  Function `get_win_launcher`  Returns or fetches data.
L335: def load_launcher_manifest(name):  Function `load_launcher_manifest`  Loads data from
storage or remote.
L340: def _first_line_re():  Function `_first_line_re`  utility or script function.
L352: def is_64bit():  Function `is_64bit`  utility or script function.
L356: def isascii(s):  Function `isascii`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/launch.py

```
L13: def run() -> None:    Function `run`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_shutil.py

```

L16: def chmod(*args: object, **kwargs: object) -> None: # type: ignore[misc] # Mypy reuses
the imported definition anyway    Object (singleton).
L23: def attempt_chmod_verbose(path, mode):    Function `attempt_chmod_verbose`    utility or
script function.
L32: def _auto_chmod(    Function `_auto_chmod`    utility or script function.
L43: def rmtree(path, ignore_errors=False, onexc=_auto_chmod):    Function `rmtree`    utility
or script function.
L51: def rmdir(path, **opts):    Function `rmdir`    utility or script function.
L56: def current_umask():    Function `current_umask`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/__init__.py

```

L52: def _install_setup_requires(attrs):    Function `_install_setup_requires`    utility or
script function.
L55: class MinimalDistribution(distutils.core.Distribution):    Class (`MinimalDistribution`)
component used by the app (see file context: None).
L61: def __init__(self, attrs: Mapping[str, object]) -> None:    Object (singleton).
L68: def _get_project_config_files(self, filenames=None):    Function
`_get_project_config_files`    utility or script function.
L76: def finalize_options(self):    Function `finalize_options`    utility or script function.
L90: def _fetch_build_eggs(dist: Distribution):    Function `_fetch_build_eggs`    utility or
script function.
L111: def setup(**attrs) -> Distribution:    Function `setup`    Sets or updates a value.
L129: class Command(_Command):    Class (`Command`)    component used by the app (see file
context: None).
L176: def __init__(self, dist: Distribution, **kw) -> None:    Function `__init__`    utility or
script function.
L185: def reinitialize_command(    Function `reinitialize_command`    utility or script
function.
L189: def reinitialize_command(    Function `reinitialize_command`    utility or script
function.
L192: def reinitialize_command(    Function `reinitialize_command`    utility or script
function.
L200: def initialize_options(self) -> None:    Function `initialize_options`    Initialisation
routine.

```

```

L209: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L218: def run(self) -> None:    Function `run` utility or script function.
L227: def _find_all_simple(path):    Function `_find_all_simple` utility or script function.
L239: def findall(dir=os.curdir):    Function `findall` utility or script function.
L251: class sic(str):    Class (`sic`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_path.py

```

L17: def ensure_directory(path):    Function `ensure_directory` utility or script function.
L23: def same_path(p1: StrPath, p2: StrPath) -> bool:    Function `same_path` utility or
script function.
L42: def _cygwin_patch(filename: StrPath):    # pragma: nocover    Function `_cygwin_patch`
utility or script function.
L53: def normpath(filename: StrPath) -> str:    Function `normpath` utility or script
function.
L59: def paths_on_pythonpath(paths):    Function `paths_on_pythonpath` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/build_meta.py

```

L71: class SetupRequirementsError(BaseException):    Class (`SetupRequirementsError`)
component used by the app (see file context: None).
L72: def __init__(self, specifiers) -> None:    Function `__init__` utility or script
function.
L76: class Distribution(setuptools.dist.Distribution):    Class (`Distribution`) component
used by the app (see file context: None).
L77: def fetch_build_eggs(self, specifiers) -> NoReturn:    Function `fetch_build_eggs`
utility or script function.
L84: def patch(cls) -> Iterator[None]:    Function `patch` utility or script function.
L99: def no_install_setup_requires():    Function `no_install_setup_requires` utility or
script function.
L114: def _get_immediate_subdirectories(a_dir):    Function `_get_immediate_subdirectories`
utility or script function.
L120: def _file_with_extension(directory: StrPath, extension: str | tuple[str, ...]):
Function `_file_with_extension` utility or script function.
L132: def _open_setup_script(setup_script):    Function `_open_setup_script` utility or
script function.
L141: def suppress_known_deprecation():    Function `suppress_known_deprecation` utility or
script function.
L163: class _ConfigSettingsTranslator:    Class (`_ConfigSettingsTranslator`) component used
by the app (see file context: None).
L170: def _get_config(self, key: str, config_settings: _ConfigSettings) -> list[str]:

```

```

Function `_get_config` utility or script function.
L192: def _global_args(self, config_settings: _ConfigSettings) -> Iterator[str]: Function
`_global_args` utility or script function.
L224: def __dist_info_args(self, config_settings: _ConfigSettings) -> Iterator[str]:
Function `_dist_info_args` utility or script function.
L250: def _editable_args(self, config_settings: _ConfigSettings) -> Iterator[str]: Function
`_editable_args` utility or script function.
L266: def _arbitrary_args(self, config_settings: _ConfigSettings) -> Iterator[str]:
Function `_arbitrary_args` utility or script function.
L290: class _BuildMetaBackend(_ConfigSettingsTranslator): Class (`_BuildMetaBackend`)
component used by the app (see file context: None).
L291: def _get_build_requires( Function `_get_build_requires` utility or script function.
L307: def run_setup(self, setup_script: str = 'setup.py') -> None: Function `run_setup`
utility or script function.
L330: def get_requires_for_build_wheel( Function `get_requires_for_build_wheel` Returns or
fetches data.
L335: def get_requires_for_build_sdist( Function `get_requires_for_build_sdist` Returns or
fetches data.
L340: def _bubble_up_info_directory( Function `_bubble_up_info_directory` utility or
script function.
L355: def _find_info_directory(self, metadata_directory: StrPath, suffix: str) -> Path:
Function `_find_info_directory` utility or script function.
L368: def prepare_metadata_for_build_wheel( Function `prepare_metadata_for_build_wheel`
utility or script function.
L385: def _build_with_temp_dir( Function `_build_with_temp_dir` utility or script
function.
L421: def build_wheel( Function `build_wheel` Constructs or prepares an object.
L427: def _build(cmd: list[str]): Function `_build` utility or script function.
L449: def build_sdist( Function `build_sdist` Constructs or prepares an object.
L456: def _get_dist_info_dir(self, metadata_directory: StrPath | None) -> str | None:
Function `_get_dist_info_dir` utility or script function.
L463: def build_editable( Function `build_editable` Constructs or prepares an object.
L478: def get_requires_for_build_editable( Function `get_requires_for_build_editable`
Returns or fetches data.
L483: def prepare_metadata_for_build_editable( Function
`prepare_metadata_for_build_editable` utility or script function.
L491: class _BuildMetaLegacyBackend(_BuildMetaBackend): Class (`_BuildMetaLegacyBackend`)
component used by the app (see file context: None).
L503: def run_setup(self, setup_script: str = 'setup.py') -> None: Function `run_setup`
utility or script function.
L531: class _IncompatibleBdistWheel(SetuptoolsDeprecationWarning): Class
(`_IncompatibleBdistWheel`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_static.py

```

L9: class Static: Class (`Static`) component used by the app (see file context: None).
L27: def _prevent_modification(target: type, method: str, copying: str) -> None: Function

```

```

`_prevent_modification` utility or script function.
L40: def _replacement(self: Static, *args, **kwargs):    Function `_replacement` utility or
script function.
L61: class Str(str, Static):    Class (`Str`) component used by the app (see file context:
None).
L65: class Tuple(tuple, Static):    Class (`Tuple`) component used by the app (see file
context: None).
L69: class List(list, Static):    Class (`List`) component used by the app (see file context:
None).
L108: class Dict(dict, Static):    Class (`Dict`) component used by the app (see file
context: None).
L145: class SpecifierSet(packaging.specifiers.SpecifierSet, Static):    Class (`SpecifierSet`)
component used by the app (see file context: None).
L152: def noop(value: T) -> T:    Function `noop` utility or script function.
L163: def attempt_conversion(value: T) -> T:    Function `attempt_conversion` utility or
script function.
L173: def is_static(value: object) -> bool:    Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/monkey.py

```

L26: def _get_mro(cls):    Function `_get_mro` utility or script function.
L41: def get_unpatched(item: _UnpatchT) -> _UnpatchT: ...    Function `get_unpatched` Returns
or fetches data.
L43: def get_unpatched(item: object) -> None: ...    Object (singleton).
L44: def get_unpatched(    Function `get_unpatched` Returns or fetches data.
L54: def get_unpatched_class(cls: type[_T]) -> type[_T]:    Function `get_unpatched_class`
Returns or fetches data.
L72: def patch_all() -> None:    Function `patch_all` utility or script function.
L93: def _patch_distribution_metadata():    Function `_patch_distribution_metadata` utility
or script function.
L108: def patch_func(replacement, target_mod, func_name) -> None:    Function `patch_func`
utility or script function.
L125: def get_unpatched_function(candidate):    Function `get_unpatched_function` Returns or
fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/namespaces.py

```

L11: class Installer:    Class (`Installer`) component used by the app (see file context:
None).
L14: def install_namespaces(self) -> None:    Function `install_namespaces` utility or script
function.
L28: def uninstall_namespaces(self) -> None:    Function `uninstall_namespaces` utility or
script function.

```



```

L35: def _get_nspkg_file(self):    Function `_get_nspkg_file` utility or script function.
L39: def _get_target(self):      Function `_get_target` utility or script function.
L63: def _get_root(self):        Function `_get_root` utility or script function.
L66: def _gen_nspkg_line(self, pkg):  Function `_gen_nspkg_line` utility or script
function.
L75: def _get_all_ns_packages(self):  Function `_get_all_ns_packages` utility or script
function.
L81: def _pkg_names(pkg):        Function `_pkg_names` utility or script function.
L96: class DevelopInstaller(Installer):  Class (`DevelopInstaller`) component used by the
app (see file context: None).
L97: def _get_root(self):        Function `_get_root` utility or script function.
L100: def _get_target(self):      Function `_get_target` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_itertools.py

```

L5: def ensure_unique(iterable, key=lambda x: x):    Function `ensure_unique` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/unicode_utils.py

```

L10: def decompose(path):    Function `decompose` utility or script function.
L22: def filesys_decode(path):  Function `filesys_decode` utility or script function.
L43: def try_encode(string, enc):  Function `try_encode` utility or script function.
L51: def _read_utf8_with_fallback(file: str, fallback_encoding=py39.LOCALE_ENCODING) -> str:
Function `_read_utf8_with_fallback` utility or script function.
L67: def _cfg_read_utf8_with_fallback(    Function `_cfg_read_utf8_with_fallback` utility or
script function.
L83: class _Utf8EncodingNeeded(SetuptoolsDeprecationWarning):  Class (`_Utf8EncodingNeeded`)
component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_discovery.py

```

L8: def extras_from_dep(dep):    Function `extras_from_dep` utility or script function.
L20: def extras_from_deps(deps):  Function `extras_from_deps` utility or script function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/setuptools/msvc.py

```

L35: class winreg:    Class (`winreg`)    component used by the app (see file context: None).
L44: class PlatformInfo:    Class (`PlatformInfo`)    component used by the app (see file
context: None).
L56: def __init__(self, arch: str) -> None:    Function `__init__`    utility or script
function.
L60: def target_cpu(self) -> str:    Function `target_cpu`    utility or script function.
L71: def target_is_x86(self) -> bool:    Function `target_is_x86`    utility or script function.
L82: def current_is_x86(self) -> bool:    Function `current_is_x86`    utility or script
function.
L93: def current_dir(self, hidex86=False, x64=False) -> str:    Function `current_dir`
utility or script function.
L117: def target_dir(self, hidex86=False, x64=False) -> str:    Function `target_dir`    utility
or script function.
L141: def cross_dir(self, forcex86=False) -> str:    Function `cross_dir`    utility or script
function.
L165: class RegistryInfo:    Class (`RegistryInfo`)    component used by the app (see file
context: None).
L182: def __init__(self, platform_info: PlatformInfo) -> None:    Function `__init__`    utility
or script function.
L186: def visualstudio(self) -> LiteralString:    Function `visualstudio`    utility or script
function.
L198: def sxs(self) -> LiteralString:    Function `sxs`    utility or script function.
L210: def vc(self) -> LiteralString:    Function `vc`    utility or script function.
L222: def vs(self) -> LiteralString:    Function `vs`    utility or script function.
L234: def vc_for_python(self) -> LiteralString:    Function `vc_for_python`    utility or script
function.
L246: def microsoft_sdk(self) -> LiteralString:    Function `microsoft_sdk`    utility or script
function.
L258: def windows_sdk(self) -> LiteralString:    Function `windows_sdk`    utility or script
function.
L270: def netfx_sdk(self) -> LiteralString:    Function `netfx_sdk`    utility or script
function.
L282: def windows_kits_roots(self) -> LiteralString:    Function `windows_kits_roots`    utility
or script function.
L294: def microsoft(self, key: LiteralString, x86: bool = False) -> LiteralString: ...
Function `microsoft`    utility or script function.
L296: def microsoft(self, key: str, x86: bool = False) -> str: ...    # type: ignore[misc]
Function `microsoft`    utility or script function.
L297: def microsoft(self, key: str, x86: bool = False) -> str:    Function `microsoft`
utility or script function.
L316: def lookup(self, key: str, name: str) -> str | None:    Function `lookup`    utility or
script function.
L358: class SystemInfo:    Class (`SystemInfo`)    component used by the app (see file context:
None).
L376: def __init__(    Function `__init__`    utility or script function.
L387: def _find_latest_available_vs_ver(self):    Function `_find_latest_available_vs_ver`
utility or script function.
L407: def find_reg_vs_vers(self) -> list[float]:    Function `find_reg_vs_vers`    utility or

```

```

script function.
L438: def find_programdata_vs_vers(self) -> dict[float, str]:    Function
`find_programdata_vs_vers` utility or script function.
L481: def _as_float_version(version):    Function `_as_float_version` utility or script
function.
L498: def VSInstallDir(self) -> str:    Function `VSInstallDir` utility or script function.
L516: def VCInstallDir(self) -> str:    Function `VCInstallDir` utility or script function.
L533: def _guess_vc(self):    Function `_guess_vc` utility or script function.
L563: def _guess_vc_legacy(self):    Function `_guess_vc_legacy` utility or script function.
L586: def WindowsSdkVersion(self) -> tuple[LiteralString, ...]:    Function
`WindowsSdkVersion` utility or script function.
L608: def WindowsSdkLastVersion(self) -> str:    Function `WindowsSdkLastVersion` utility or
script function.
L620: def WindowsSdkDir(self) -> str:    # noqa: C901 # is too complex (12) # FIXME
Function `WindowsSdkDir` utility or script function.
L663: def WindowsSDKExecutablePath(self) -> str | None:    Function `WindowsSDKExecutablePath`
utility or script function.
L700: def FSharpInstallDir(self) -> str:    Function `FSharpInstallDir` utility or script
function.
L713: def UniversalCRTSdkDir(self) -> str | None:    Function `UniversalCRTSdkDir` utility or
script function.
L734: def UniversalCRTSdkLastVersion(self) -> str:    Function `UniversalCRTSdkLastVersion`
utility or script function.
L750: def NetFxSdkVersion(self) -> tuple[LiteralString, ...]:    Function `NetFxSdkVersion`
utility or script function.
L767: def NetFxSdkDir(self) -> str | None:    Function `NetFxSdkDir` utility or script
function.
L785: def FrameworkDir32(self) -> str:    Function `FrameworkDir32` utility or script
function.
L801: def FrameworkDir64(self) -> str:    Function `FrameworkDir64` utility or script
function.
L817: def FrameworkVersion32(self) -> tuple[str, ...]:    Function `FrameworkVersion32`
utility or script function.
L829: def FrameworkVersion64(self) -> tuple[str, ...]:    Function `FrameworkVersion64`
utility or script function.
L840: def _find_dot_net_versions(self, bits) -> tuple[str, ...]:    Function
`_find_dot_net_versions` utility or script function.
L871: def _use_last_dir_name(path: StrPath, prefix: str = '') -> str:    Function
`_use_last_dir_name` utility or script function.
L896: class _EnvironmentDict(TypedDict):    Class (`_EnvironmentDict`) component used by the
app (see file context: None).
L904: class EnvironmentInfo:    Class (`EnvironmentInfo`) component used by the app (see file
context: None).
L928: def __init__(self, arch, vc_ver=None, vc_min_ver=0) -> None:    Function `__init__`
utility or script function.
L938: def vs_ver(self):    Function `vs_ver` utility or script function.
L950: def vc_ver(self):    Function `vc_ver` utility or script function.
L962: def VSTools(self):    Function `VSTools` utility or script function.
L982: def VCIncludes(self):    Function `VCIncludes` utility or script function.
L997: def VCLibraries(self):    Function `VCLibraries` utility or script function.
L1018: def VCStoreRefs(self):    Function `VCStoreRefs` utility or script function.

```

```

L1032: def VCTools(self):    Function `VCTools` utility or script function.
L1083: def OSLibraries(self):  Function `OSLibraries` utility or script function.
L1103: def OSIncludes(self):  Function `OSIncludes` utility or script function.
L1129: def OSLibpath(self):   Function `OSLibpath` utility or script function.
L1169: def SdkTools(self):    Function `SdkTools` utility or script function.
L1180: def _sdk_tools(self):   Function `_sdk_tools` utility or script function.
L1216: def _sdk_subdir(self) -> str:  Function `_sdk_subdir` utility or script function.
L1229: def SdkSetup(self):    Function `SdkSetup` utility or script function.
L1244: def FxTools(self):     Function `FxTools` utility or script function.
L1275: def NetFxSDKLibraries(self):  Function `NetFxSDKLibraries` utility or script
function.
L1291: def NetFxSDKIncludes(self):  Function `NetFxSDKIncludes` utility or script function.
L1306: def VsTDb(self):       Function `VsTDb` utility or script function.
L1318: def MSBuild(self):     Function `MSBuild` utility or script function.
L1346: def HTMLHelpWorkshop(self):  Function `HTMLHelpWorkshop` utility or script function.
L1361: def UCRTLibraries(self) -> list[str]:  Function `UCRTLibraries` utility or script
function.
L1383: def UCRTIncludes(self) -> list[str]:  Function `UCRTIncludes` utility or script
function.
L1403: def _ucrt_subdir(self) -> str:  Function `_ucrt_subdir` utility or script function.
L1416: def FSharp(self):      Function `FSharp` utility or script function.
L1431: def VCRuntimeRedist(self) -> str | None:  Function `VCRuntimeRedist` utility or
script function.
L1465: def return_env(self, exists: bool = True) -> _EnvironmentDict:  Function `return_env`
utility or script function.
L1526: def _build_paths(self, name, spec_path_lists, exists):  Function `_build_paths`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/warnings.py

```

L25: class SetuptoolsWarning(UserWarning):  Class (`SetuptoolsWarning`) component used by
the app (see file context: None).
L29: def emit(  Function `emit` utility or script function.
L55: def _format(  Function `_format` utility or script function.
L89: class InformationOnly(SetuptoolsWarning):  Class (`InformationOnly`) component used by
the app (see file context: None).
L99: class SetuptoolsDeprecationWarning(SetuptoolsWarning):  Class
(`SetuptoolsDeprecationWarning`) component used by the app (see file context: None).
L108: def _should_enforce():  Function `_should_enforce` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/windows_suppor

ort.py

```
L4: def windows_only(func):    Function `windows_only` utility or script function.
L11: def hide_file(path: str) -> None:    Function `hide_file` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/extension.py

```
L17: def _have_cython() -> bool:    Function `_have_cython` utility or script function.
L39: class Extension(_Extension):    Class (`Extension`) component used by the app (see file
context: None).
L145: def __init__(    Function `__init__` utility or script function.
L163: def _convert_pyx_sources_to_lang(self):    Function `_convert_pyx_sources_to_lang`
utility or script function.
L178: class Library(Extension):    Class (`Library`) component used by the app (see file
context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/errors.py

```
L33: class InvalidConfigError(OptionError):    # type: ignore[valid-type, misc] # distutils
imports are `Any` on python 3.12+    Class (`InvalidConfigError`) component used by the app
(see file context: None).
L37: class RemovedConfigError(OptionError):    # type: ignore[valid-type, misc] # distutils
imports are `Any` on python 3.12+    Class (`RemovedConfigError`) component used by the app
(see file context: None).
L41: class RemovedCommandError(BaseError, RuntimeError):    # type: ignore[valid-type, misc] #
distutils imports are `Any` on python 3.12+    Class (`RemovedCommandError`) component used
by the app (see file context: None).
L51: class PackageDiscoveryError(BaseError, RuntimeError):    # type: ignore[valid-type, misc]
# distutils imports are `Any` on python 3.12+    Class (`PackageDiscoveryError`) component
used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/wheel.py

```
L39: def _get_supported_tags():    Function `_get_supported_tags` utility or script function.
L46: def unpack(src_dir, dst_dir) -> None:    Function `unpack` utility or script function.
L69: def disable_info_traces() -> Iterator[None]:    Function `disable_info_traces` utility
or script function.
L82: class Wheel:    Class (`Wheel`) component used by the app (see file context: None).
L83: def __init__(self, filename) -> None:    Function `__init__` utility or script function.
L91: def tags(self):    Function `tags` utility or script function.
L99: def is_compatible(self):    Function `is_compatible` utility or script function.
```

```

L103: def egg_name(self):    Function `egg_name` utility or script function.
L113: def get_dist_info(self, zf):    Function `get_dist_info` Returns or fetches data.
L123: def install_as_egg(self, destination_eggsdir) -> None:    Function `install_as_egg`
utility or script function.
L128: def _install_as_egg(self, destination_eggsdir, zf):    Function `_install_as_egg`
utility or script function.
L139: def _convert_metadata(zf, destination_eggsdir, dist_info, egg_info):    Function
`_convert_metadata` utility or script function.
L140: def get_metadata(name):    Function `get_metadata` Returns or fetches data.
L176: def _convert_requires(destination_eggsdir, dist_info):    Function `_convert_requires`
utility or script function.
L186: def raw_req(req):    Function `raw_req` utility or script function.
L191: def eval(req, **env):    Function `eval` utility or script function.
L194: def for_extra(req):    Function `for_extra` utility or script function.
L220: def _move_data_entries(destination_eggsdir, dist_data):    Function `_move_data_entries`
utility or script function.
L250: def _fix_namespace_packages(egg_info, destination_eggsdir):    Function
`_fix_namespace_packages` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_dependencies.py

```

L6: class TestGetModuleConstant:    Class (`TestGetModuleConstant`) component used by the app
(see file context: None).
L7: def test_basic(self):    Function `test_basic` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_develop.py

```

L27: def temp_user(monkeypatch):    Function `temp_user` utility or script function.
L36: def test_env(tmpdir, temp_user):    Function `test_env` utility or script function.
L51: class TestNamespaces:    Class (`TestNamespaces`) component used by the app (see file
context: None).
L53: def install_develop(src_dir, target):    Function `install_develop` utility or script
function.
L75: def test_namespace_package_importable(self, tmpdir):    Function
`test_namespace_package_importable` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_exten n.py

```
L9: def test_reimport_extern():    Function `test_reimport_extern`    utility or script
function.
L14: def test_distribution_picklable():    Function `test_distribution_picklable`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build _py.py

```
L17: def test_directories_in_package_data_glob(tmpdir_cwd):    Function
`test_directories_in_package_data_glob`    utility or script function.
L37: def test_recursive_in_package_data_glob(tmpdir_cwd):    Function
`test_recursive_in_package_data_glob`    utility or script function.
L63: def test_read_only(tmpdir_cwd):    Function `test_read_only`    utility or script function.
L96: def test_executable_data(tmpdir_cwd):    Function `test_executable_data`    utility or
script function.
L160: def test_excluded_subpackages(tmpdir_cwd):    Function `test_excluded_subpackages`
utility or script function.
L207: def test_existing_egg_info(tmpdir_cwd, monkeypatch):    Function
`test_existing_egg_info`    utility or script function.
L303: def test_get_outputs(tmpdir_cwd):    Function `test_get_outputs`    utility or script
function.
L337: class TestTypeInfoFiles:    Class (`TestTypeInfoFiles`)    component used by the app (see
file context: None).
L422: def test_type_files_included_by_default(self, tmpdir_cwd, pyproject, example):
Function `test_type_files_included_by_default`    utility or script function.
L436: def test_type_files_can_be_excluded(self, tmpdir_cwd, pyproject, example):    Function
`test_type_files_can_be_excluded`    utility or script function.
L448: def test_stub_only_package(self, tmpdir_cwd):    Function `test_stub_only_package`
utility or script function.
L467: def get_finalized_build_py(script_name="%build_py-test%"):    Function
`get_finalized_build_py`    Returns or fetches data.
L475: def get_outputs(build_py):    Function `get_outputs`    Returns or fetches data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_find_ py_modules.py

```
L13: class TestModuleFinder:    Class (`TestModuleFinder`)    component used by the app (see
```

```

file context: None).
L14: def find(self, path, *args, **kwargs):  Function `find` utility or script function.
L38: def test_finder(self, tmp_path, example):  Function `test_finder` utility or script
function.
L44: def test_symlinked_packages_are_included(self, tmp_path):  Function
`test_symlinked_packages_are_included` utility or script function.
L51: class TestFlatLayoutModuleFinder:  Class (`TestFlatLayoutModuleFinder`) component used
by the app (see file context: None).
L52: def find(self, path, *args, **kwargs):  Function `find` utility or script function.
L70: def test_unwanted_files_not_included(self, tmp_path, example):  Function
`test_unwanted_files_not_included` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/textwrap.py

```

L4: def DAL(s):  Function `DAL` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_logging.py

```

L24: def test_verbosity_level(tmp_path, monkeypatch, flags, expected_level):  Function
`test_verbosity_level` utility or script function.
L45: def flaky_on_pypy(func):  Function `flaky_on_pypy` utility or script function.
L47: def _func():  Function `_func` utility or script function.
L60: def test_patching_does_not_cause_problems():  Function
`test_patching_does_not_cause_problems` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_ext.py

```

L24: class TestBuildExt:  Class (`TestBuildExt`) component used by the app (see file
context: None).
L25: def test_get_ext_filename(self):  Function `test_get_ext_filename` utility or script
function.
L38: def test_abi3_filename(self):  Function `test_abi3_filename` utility or script
function.
L59: def test_ext_suffix_override(self):  Function `test_ext_suffix_override` utility or

```



```

script function.
L91: def dist_with_example(self):    Function `dist_with_example`    utility or script function.
L108: def test_get_outputs(self, tmpdir_cwd, monkeypatch):    Function `test_get_outputs`
utility or script function.
L140: def test_get_output_mapping_with_stub(self, tmpdir_cwd, monkeypatch):    Function
`test_get_output_mapping_with_stub`    utility or script function.
L158: def C(file):    Function `C`    utility or script function.
L182: class TestBuildExtInplace:    Class (`TestBuildExtInplace`)    component used by the app
(see file context: None).
L183: def get_build_ext_cmd(self, optional: bool, **opts) -> build_ext:    Function
`get_build_ext_cmd`    Returns or fetches data.
L197: def get_log_messages(self, caplog, capsys):    Function `get_log_messages`    Returns or
fetches data.
L206: def test_optional(self, tmpdir_cwd, caplog, capsys):    Function `test_optional`
utility or script function.
L219: def test_non_optional(self, tmpdir_cwd):    Function `test_non_optional`    utility or
script function.
L226: def test_build_ext_config_handling(tmpdir_cwd):    Function
`test_build_ext_config_handling`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_dist_info.py

```

L19: class TestDistInfo:    Class (`TestDistInfo`)    component used by the app (see file
context: None).
L20: def test_invalid_version(self, tmp_path):    Function `test_invalid_version`    utility or
script function.
L32: def test_tag_arguments(self, tmp_path):    Function `test_tag_arguments`    utility or
script function.
L53: def test_output_dir(self, tmp_path, keep_egg_info):    Function `test_output_dir`
utility or script function.
L69: class TestWheelCompatibility:    Class (`TestWheelCompatibility`)    component used by the
app (see file context: None).
L110: def test_dist_info_is_the_same_as_in_wheel(    Function
`test_dist_info_is_the_same_as_in_wheel`    utility or script function.
L133: def run_command_inner(*cmd, **kwargs):    Function `run_command_inner`    utility or
script function.
L146: def run_command(*args, **kwargs):    Function `run_command`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_dist.py

```

L18: def test_dist_fetch_build_egg(tmpdir, setuptools_wheel):    Function
`test_dist_fetch_build_egg` utility or script function.
L25: def sdist_with_index(distname, version):    Function `sdist_with_index` utility or
script function.
L75: def test_provides_extras_deterministic_order():    Function
`test_provides_extras_deterministic_order` utility or script function.
L135: def test_check_package_data(package_data, expected_message):    Function
`test_check_package_data` utility or script function.
L143: def test_check_specifier():    Function `test_check_specifier` utility or script
function.
L159: def test_metadata_name():    Function `test_metadata_name` utility or script function.
L173: def test_dist_default_py_modules(tmp_path, dist_name, py_module):    Function
`test_dist_default_py_modules` utility or script function.
L216: def test_dist_default_packages(    Function `test_dist_default_packages` utility or
script function.
L267: def test_dist_default_name(tmp_path, dist_name, package_dir, package_files):    Function
`test_dist_default_name` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_find_packages.py

```

L15: class TestFindPackages:    Class (`TestFindPackages`) component used by the app (see
file context: None).
L16: def setup_method(self, method):    Function `setup_method` Sets or updates a value.
L20: def teardown_method(self, method):    Function `teardown_method` utility or script
function.
L23: def _make_pkg_structure(self):    Function `_make_pkg_structure` utility or script
function.
L52: def _mkdir(self, path, parent_dir=None):    Function `_mkdir` utility or script
function.
L58: def _touch(self, path, dir_=None):    Function `_touch` utility or script function.
L64: def test_regular_package(self):    Function `test_regular_package` utility or script
function.
L69: def test_exclude(self):    Function `test_exclude` utility or script function.
L74: def test_exclude_recursive(self):    Function `test_exclude_recursive` utility or script
function.
L83: def test_include_excludes_other(self):    Function `test_include_excludes_other` utility
or script function.
L93: def test_dir_with_dot_is_skipped(self):    Function `test_dir_with_dot_is_skipped`
utility or script function.
L101: def test_dir_with_packages_in_subdir_is_excluded(self):    Function
`test_dir_with_packages_in_subdir_is_excluded` utility or script function.
L113: def test_symlinked_packages_are_included(self):    Function
`test_symlinked_packages_are_included` utility or script function.
L127: def _assert_packages(self, actual, expected):    Function `_assert_packages` utility or
script function.

```

```

L130: def test_pep420_ns_package(self):    Function `test_pep420_ns_package` utility or
script function.
L136: def test_pep420_ns_package_no_includes(self):    Function
`test_pep420_ns_package_no_includes` utility or script function.
L140: def test_pep420_ns_package_no_includes_or_excludes(self):    Function
`test_pep420_ns_package_no_includes_or_excludes` utility or script function.
L145: def test_regular_package_with_nested_pep420_ns_packages(self):    Function
`test_regular_package_with_nested_pep420_ns_packages` utility or script function.
L152: def test_pep420_ns_package_no_non_package_dirs(self):    Function
`test_pep420_ns_package_no_non_package_dirs` utility or script function.
L159: class TestFlatLayoutPackageFinder:    Class (`TestFlatLayoutPackageFinder`) component
used by the app (see file context: None).
L207: def test_unwanted_directories_not_included(self, tmp_path, example):    Function
`test_unwanted_directories_not_included` utility or script function.
L214: def ensure_files(root_path, files):    Function `ensure_files` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_archive_util.py

```

L10: def tarfile_with_unicode(tmpdir):    Function `tarfile_with_unicode` utility or script
function.
L34: def test_unicode_files(tarfile_with_unicode, tmpdir):    Function `test_unicode_files`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_install_scripts.py

```

L13: class TestInstallScripts:    Class (`TestInstallScripts`) component used by the app (see
file context: None).
L23: def _run_install_scripts(self, install_dir, executable=None):    Function
`_run_install_scripts` utility or script function.
L36: def test_sys_executable_escaping_unix(self, tmpdir, monkeypatch):    Function
`test_sys_executable_escaping_unix` utility or script function.
L50: def test_sys_executable_escaping_win32(self, tmpdir, monkeypatch):    Function
`test_sys_executable_escaping_win32` utility or script function.
L64: def test_executable_with_spaces_escaping_unix(self, tmpdir):    Function
`test_executable_with_spaces_escaping_unix` utility or script function.
L78: def test_executable_arg_escaping_win32(self, tmpdir):    Function
`test_executable_arg_escaping_win32` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_bdist_egg.py

```
L21: def setup_context(tmpdir):    Function `setup_context`  Sets or updates a value.
L30: class Test:    Class (`Test`)  component used by the app (see file context: None).
L33: def test_bdist_egg(self):    Function `test_bdist_egg`  utility or script function.
L57: def test_exclude_source_files(self):    Function `test_exclude_source_files`  utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_virtualenv.py

```
L11: def pytest_virtualenv_works(venv):    Function `pytest_virtualenv_works`  utility or
script function.
L21: def test_clean_env_install(venv_without_setuptools, setuptools_wheel):    Function
`test_clean_env_install`  utility or script function.
L29: def access_pypi():    Function `access_pypi`  utility or script function.
L86: def test_pip_upgrade_from_source(    Function `test_pip_upgrade_from_source`  utility or
script function.
L108: def test_no_missing_dependencies(bare_venv, request):    Function
`test_no_missing_dependencies`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_glob.py

```
L42: def test_glob(monkeypatch, tmpdir, tree, pattern, matches):    Function `test_glob`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/fixtures.py

```
L21: def user_override(monkeypatch):    Function `user_override`  utility or script function.
L35: def tmpdir_cwd(tmpdir):    Function `tmpdir_cwd`  utility or script function.
L41: def workaround_xdist_376(request):    Function `workaround_xdist_376`  utility or script
```

```

function.
L58: def sample_project(tmp_path):    Function `sample_project` utility or script function.
L71: def sample_project_cwd(sample_project):    Function `sample_project_cwd` utility or
script function.
L84: def _build_distributions(tmp_path_factory, request):    Function `_build_distributions`
utility or script function.
L112: def setuptools_sdist(tmp_path_factory, request):    Function `setuptools_sdist` Sets or
updates a value.
L122: def setuptools_wheel(tmp_path_factory, request):    Function `setuptools_wheel` Sets or
updates a value.
L132: def venv(tmp_path, setuptools_wheel):    Function `venv` utility or script function.
L154: def venv_without_setuptools(tmp_path):    Function `venv_without_setuptools` utility or
script function.
L164: def bare_venv(tmp_path):    Function `bare_venv` utility or script function.
L173: def make_sdist(dist_path, files):    Function `make_sdist` utility or script function.
L190: def make_trivial_sdist(dist_path, distname, version, setuptools_wheel=None):    Function
`make_trivial_sdist` utility or script function.
L230: def make_nspkg_sdist(dist_path, distname, version):    Function `make_nspkg_sdist`
utility or script function.
L266: def make_python_requires_sdist(dist_path, distname, version, python_requires):
Function `make_python_requires_sdist` utility or script function.
L290: def create_setup_requires_package(    Function `create_setup_requires_package` Creates
a resource or document.
L368: def pbr_package(tmp_path, monkeypatch, venv):    Function `pbr_package` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_bdist_wheel.py

```

L216: def bdist_wheel_cmd(**kwargs):    Function `bdist_wheel_cmd` utility or script
function.
L231: def mkexample(tmp_path_factory, name):    Function `mkexample` utility or script
function.
L238: def wheel_paths(tmp_path_factory):    Function `wheel_paths` utility or script
function.
L251: def dummy_dist(tmp_path_factory):    Function `dummy_dist` utility or script function.
L256: def licenses_dist(tmp_path_factory):    Function `licenses_dist` utility or script
function.
L260: def test_no_scripts(wheel_paths):    Function `test_no_scripts` utility or script
function.
L267: def test_unicode_record(wheel_paths):    Function `test_unicode_record` utility or
script function.
L286: def test_preserve_unicode_metadata(monkeypatch, tmp_path):    Function
`test_preserve_unicode_metadata` utility or script function.
L295: class simpler_bdist_wheel(bdist_wheel):    Class (`simpler_bdist_wheel`) component used
by the app (see file context: None).

```

```

L298: def __init__(self) -> None:    Function `__init__` utility or script function.
L302: def license_paths(self):    Function `license_paths` utility or script function.
L314: def test_licenses_default(dummy_dist, monkeypatch, tmp_path):    Function
`test_licenses_default` utility or script function.
L325: def test_licenses_deprecated(dummy_dist, monkeypatch, tmp_path):    Function
`test_licenses_deprecated` utility or script function.
L351: def test_licenses_override(dummy_dist, monkeypatch, tmp_path, config_file, config):
Function `test_licenses_override` utility or script function.
L366: def test_licenses_preserve_folder_structure(licenses_dist, monkeypatch, tmp_path):
Function `test_licenses_preserve_folder_structure` utility or script function.
L382: def test_licenses_disabled(dummy_dist, monkeypatch, tmp_path):    Function
`test_licenses_disabled` utility or script function.
L392: def test_build_number(dummy_dist, monkeypatch, tmp_path):    Function
`test_build_number` utility or script function.
L401: def test_universal_deprecated(dummy_dist, monkeypatch, tmp_path):    Function
`test_universal_deprecated` utility or script function.
L446: def test_limited_abi(monkeypatch, tmp_path, tmp_path_factory):    Function
`test_limited_abi` utility or script function.
L457: def test_build_from_readonly_tree(dummy_dist, monkeypatch, tmp_path):    Function
`test_build_from_readonly_tree` utility or script function.
L475: def test_compression(dummy_dist, monkeypatch, tmp_path, option, compress_type):
Function `test_compression` utility or script function.
L486: def test_wheelfile_line_endings(wheel_paths):    Function `test_wheelfile_line_endings`
utility or script function.
L494: def test_unix_epoch_timestamps(dummy_dist, monkeypatch, tmp_path):    Function
`test_unix_epoch_timestamps` utility or script function.
L503: def test_get_abi_tag_windows(monkeypatch):    Function `test_get_abi_tag_windows`
utility or script function.
L515: def test_get_abi_tag_pypy_old(monkeypatch):    Function `test_get_abi_tag_pypy_old`
utility or script function.
L521: def test_get_abi_tag_pypy_new(monkeypatch):    Function `test_get_abi_tag_pypy_new`
utility or script function.
L527: def test_get_abi_tag_graalpy(monkeypatch):    Function `test_get_abi_tag_graalpy`
utility or script function.
L535: def test_get_abi_tag_fallback(monkeypatch):    Function `test_get_abi_tag_fallback`
utility or script function.
L541: def test_platform_with_space(dummy_dist, monkeypatch):    Function
`test_platform_with_space` utility or script function.
L547: def test_data_dir_with_tag_build(monkeypatch, tmp_path):    Function
`test_data_dir_with_tag_build` utility or script function.
L609: def test_platform_linux32(reported, expected, monkeypatch):    Function
`test_platform_linux32` utility or script function.
L619: def test_no_ctypes(monkeypatch) -> None:    Function `test_no_ctypes` utility or script
function.
L620: def _fake_import(name: str, *args, **kwargs):    Function `_fake_import` utility or
script function.
L641: def test_dist_info_provided(dummy_dist, monkeypatch, tmp_path):    Function
`test_dist_info_provided` utility or script function.
L666: def test_allow_grace_period_parent_directory_license(monkeypatch, tmp_path):    Function
`test_allow_grace_period_parent_directory_license` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_config_discovery.py

```

L24: class TestFindParentPackage:    Class (`TestFindParentPackage`)    component used by the
app (see file context: None).
L25: def test_single_package(self, tmp_path):    Function `test_single_package`    utility or
script function.
L33: def test_multiple_toplevel(self, tmp_path):    Function `test_multiple_toplevel`    utility
or script function.
L43: class TestDiscoverPackagesAndPyModules:    Class (`TestDiscoverPackagesAndPyModules`)
component used by the app (see file context: None).
L70: def _get_info(self, circumstance):    Function `_get_info`    utility or script function.
L77: def test_sdist_filelist(self, tmp_path, circumstance):    Function `test_sdist_filelist`
utility or script function.
L88: def test_project(self, tmp_path, circumstance):    Function `test_project`    utility or
script function.
L171: def test_purposefully_empty(self, tmp_path, config_file, param, circumstance):
Function `test_purposefully_empty`    utility or script function.
L213: def test_flat_layout_with_extra_files(self, tmp_path, extra_files, pkgs):    Function
`test_flat_layout_with_extra_files`    utility or script function.
L226: def test_flat_layout_with_dangerous_extra_files(self, tmp_path, extra_files):
Function `test_flat_layout_with_dangerous_extra_files`    utility or script function.
L232: def test_flat_layout_with_single_module(self, tmp_path):    Function
`test_flat_layout_with_single_module`    utility or script function.
L238: def test_flat_layout_with_multiple_modules(self, tmp_path):    Function
`test_flat_layout_with_multiple_modules`    utility or script function.
L244: def test_py_modules_when_wheel_dir_is_cwd(self, tmp_path):    Function
`test_py_modules_when_wheel_dir_is_cwd`    utility or script function.
L258: class TestNoConfig:    Class (`TestNoConfig`)    component used by the app (see file
context: None).
L271: def test_discover_name(self, tmp_path, example):    Function `test_discover_name`
utility or script function.
L276: def test_build_with_discovered_name(self, tmp_path):    Function
`test_build_with_discovered_name`    utility or script function.
L285: class TestWithAttrDirective:    Class (`TestWithAttrDirective`)    component used by the
app (see file context: None).
L293: def test_setupcfg_metadata(self, tmp_path, folder, opts):    Function
`test_setupcfg_metadata`    utility or script function.
L316: def test_pyproject_metadata(self, tmp_path):    Function `test_pyproject_metadata`
utility or script function.
L333: class TestWithCExtension:    Class (`TestWithCExtension`)    component used by the app
(see file context: None).
L334: def _simulate_package_with_extension(self, tmp_path):    Function
`_simulate_package_with_extension`    utility or script function.
L367: def test_skip_discovery_with_setupcfg_metadata(self, tmp_path):    Function
`test_skip_discovery_with_setupcfg_metadata`    utility or script function.
L395: def test_dont_skip_discovery_with_pyproject_metadata(self, tmp_path):    Function
`test_dont_skip_discovery_with_pyproject_metadata`    utility or script function.

```

```

L415: class TestWithPackageData:  Class (`TestWithPackageData`)  component used by the app
(see file context: None).
L416: def _simulate_package_with_data_files(self, tmp_path, src_root):  Function
`_simulate_package_with_data_files`  utility or script function.
L485: def test_include_package_data(self, tmp_path, src_root, files):  Function
`test_include_package_data`  utility or script function.
L512: def test_compatible_with_numpy_configuration(tmp_path):  Function
`test_compatible_with_numpy_configuration`  utility or script function.
L526: def test_name_discovery_doesnt_break_cli(tmpdir_cwd):  Function
`test_name_discovery_doesnt_break_cli`  utility or script function.
L535: def test_preserve_explicit_name_with_dynamic_version(tmpdir_cwd, monkeypatch):
Function `test_preserve_explicit_name_with_dynamic_version`  utility or script function.
L559: def spy_analyse_name():  Function `spy_analyse_name`  utility or script function.
L571: def _populate_project_dir(root, files, options):  Function `_populate_project_dir`
utility or script function.
L588: def _write_setupcfg(root, options):  Function `_write_setupcfg`  utility or script
function.
L611: def _run_build(path, *flags):  Function `_run_build`  utility or script function.
L616: def _get_dist(dist_path, attrs):  Function `_get_dist`  utility or script function.
L638: def _run_sdist_programatically(dist_path, attrs):  Function
`_run_sdist_programatically`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_setuptools.py

```

L6: class TestEdit:  Class (`TestEdit`)  component used by the app (see file context: None).
L8: def parse_config(filename):  Function `parse_config`  utility or script function.
L15: def write_text(file, content):  Function `write_text`  utility or script function.
L19: def test_utf8_encoding_retained(self, tmpdir):  Function `test_utf8_encoding_retained`
utility or script function.
L31: def test_case_retained(self, tmpdir):  Function `test_case_retained`  utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/text.py

```

L1: class Filenames:  Class (`Filenames`)  component used by the app (see file context:
None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_sdist.

py

```

L155: def quiet():    Function `quiet`    utility or script function.
L165: def posix(path):    Function `posix`    utility or script function.
L173: def decompose(path):    Function `decompose`    utility or script function.
L185: def read_all_bytes(filename):    Function `read_all_bytes`    utility or script function.
L190: def latin1_fail():    Function `latin1_fail`    utility or script function.
L115: def touch(path):    Function `touch`    utility or script function.
L120: def symlink_or_skip_test(src, dst):    Function `symlink_or_skip_test`    utility or
script function.
L129: class TestSdistTest:    Class (`TestSdistTest`)    component used by the app (see file
context: None).
L131: def source_dir(self, tmpdir):    Function `source_dir`    utility or script function.
L155: def assert_package_data_in_manifest(self, cmd):    Function
`assert_package_data_in_manifest`    utility or script function.
L162: def setup_with_extension(self):    Function `setup_with_extension`    Sets or updates a
value.
L175: def test_package_data_in_sdist(self):    Function `test_package_data_in_sdist`    utility
or script function.
L191: def test_package_data_and_include_package_data_in_sdist(self):    Function
`test_package_data_and_include_package_data_in_sdist`    utility or script function.
L209: def test_extension_sources_in_sdist(self):    Function `test_extension_sources_in_sdist`
utility or script function.
L220: def test_missing_extension_sources(self):    Function `test_missing_extension_sources`
utility or script function.
L234: def test_symlinked_extension_sources(self):    Function
`test_symlinked_extension_sources`    utility or script function.
L273: def test_invalid_extension_depends(self, reason, caplog):    Function
`test_invalid_extension_depends`    utility or script function.
L316: def test_custom_build_py(self):    Function `test_custom_build_py`    utility or script
function.
L325: class CustomBuildPy(OrigBuildPy):    Class (`CustomBuildPy`)    component used by the app
(see file context: None).
L330: def get_data_files(self):    Function `get_data_files`    Returns or fetches data.
L354: def test_setup_py_exists(self):    Function `test_setup_py_exists`    utility or script
function.
L366: def test_setup_py_missing(self):    Function `test_setup_py_missing`    utility or script
function.
L380: def test_setup_py_excluded(self):    Function `test_setup_py_excluded`    utility or
script function.
L395: def test_defaults_case_sensitivity(self, source_dir):    Function
`test_defaults_case_sensitivity`    utility or script function.
L423: def test_exclude_dev_only_cache_folders(self, source_dir):    Function
`test_exclude_dev_only_cache_folders`    utility or script function.
L464: def test_manifest_is_written_with_utf8_encoding(self):    Function
`test_manifest_is_written_with_utf8_encoding`    utility or script function.
L493: def test_write_manifest_allows_utf8_filenames(self):    Function
`test_write_manifest_allows_utf8_filenames`    utility or script function.
L526: def test_write_manifest_skips_non_utf8_filenames(self):    Function
`test_write_manifest_skips_non_utf8_filenames`    utility or script function.

```

```

L562: def test_manifest_is_read_with_utf8_encoding(self):    Function
`test_manifest_is_read_with_utf8_encoding` utility or script function.
L593: def test_read_manifest_skips_non_utf8_filenames(self):    Function
`test_read_manifest_skips_non_utf8_filenames` utility or script function.
L625: def test_sdist_with_utf8_encoded_filename(self):    Function
`test_sdist_with_utf8_encoded_filename` utility or script function.
L656: def make_strings(cls, item):    Function `make_strings` utility or script function.
L665: def test_sdist_with_latin1_encoded_filename(self):    Function
`test_sdist_with_latin1_encoded_filename` utility or script function.
L736: def test_add_files_referenced_by_config_directives(self, source_dir, config):
Function `test_add_files_referenced_by_config_directives` utility or script function.
L764: def test_pyproject_toml_in_sdist(self, source_dir):    Function
`test_pyproject_toml_in_sdist` utility or script function.
L778: def test_pyproject_toml_excluded(self, source_dir):    Function
`test_pyproject_toml_excluded` utility or script function.
L794: def test_build_subcommand_source_files(self, source_dir):    Function
`test_build_subcommand_source_files` utility or script function.
L811: class build_custom(Command):    Class (`build_custom`) component used by the app (see
file context: None).
L812: def initialize_options(self): ...    Function `initialize_options` Initialisation
routine.
L814: def finalize_options(self): ...    Function `finalize_options` utility or script
function.
L816: def run(self): ...    Function `run` utility or script function.
L818: def get_source_files(self):    Function `get_source_files` Returns or fetches data.
L832: def test_build_base_pathlib(self, source_dir):    Function `test_build_base_pathlib`
utility or script function.
L847: def test_default_revctrl():    Function `test_default_revctrl` utility or script
function.
L868: class TestRegressions:    Class (`TestRegressions`) component used by the app (see file
context: None).
L875: def files_for_symlink_in_extension_depends(tmp_path, dep_path):    Function
`files_for_symlink_in_extension_depends` utility or script function.
L904: def test_symlink_in_extension_depends(self, monkeypatch, tmp_path, dep_path):
Function `test_symlink_in_extension_depends` utility or script function.
L920: def files_for_external_path_in_extension_depends(tmp_path, dep_path):    Function
`files_for_external_path_in_extension_depends` utility or script function.
L952: def test_external_path_in_extension_depends(self, monkeypatch, tmp_path, dep_path):
Function `test_external_path_in_extension_depends` utility or script function.
L963: def run_sdist(monkeypatch, project):    Function `run_sdist` utility or script
function.
L974: def test_sanity_check_setuptools_own_sdist(setuptools_sdist):    Function
`test_sanity_check_setuptools_own_sdist` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_name
spaces.py**

```

L9: class TestNamespaces:    Class (`TestNamespaces`)    component used by the app (see file
context: None).
L10: def test_mixed_site_and_non_site(self, tmpdir):    Function
`test_mixed_site_and_non_site`    utility or script function.
L52: def test_namespace_package_installed_and_cwd(self, tmpdir):    Function
`test_namespace_package_installed_and_cwd`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_shutil_wrapper.py

```

L8: def test_rmtree_readonly(monkeypatch, tmp_path):    Function `test_rmtree_readonly`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_windows_wrappers.py

```

L28: class WrapperTester:    Class (`WrapperTester`)    component used by the app (see file
context: None).
L30: def prep_script(cls, template):    Function `prep_script`    utility or script function.
L35: def create_script(cls, tmpdir):    Function `create_script`    Creates a resource or
document.
L55: def win_launcher_exe(prefix):    Function `win_launcher_exe`    utility or script function.
L64: class TestCLI(WrapperTester):    Class (`TestCLI`)    component used by the app (see file
context: None).
L82: def test_basic(self, tmpdir):    Function `test_basic`    utility or script function.
L130: def test_symlink(self, tmpdir):    Function `test_symlink`    utility or script function.
L167: def test_with_options(self, tmpdir):    Function `test_with_options`    utility or script
function.
L216: class TestGUI(WrapperTester):    Class (`TestGUI`)    component used by the app (see file
context: None).
L236: def test_basic(self, tmpdir):    Function `test_basic`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_script_writer.py

```

L4: class TestWindowsScriptWriter:    Class (`TestWindowsScriptWriter`)    component used by the
app (see file context: None).

```

```
L5: def test_header(self):    Function `test_header`    utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_bdist
_deprecations.py**

```
L15: def test_bdist_rpm_warning(distutils_cmd, tmpdir_cwd):    Function
`test_bdist_rpm_warning`    utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_egg_i
nfo.py**

```
L24: class Environment(str):    Class (`Environment`)    component used by the app (see file
context: None).
L29: def env():    Function `env`    utility or script function.
L49: class TestEggInfo:    Class (`TestEggInfo`)    component used by the app (see file context:
None).
L63: def _create_project(self):    Function `_create_project`    utility or script function.
L68: def run():    Function `run`    utility or script function.
L75: def _extract_mv_version(pkg_info_lines: list[str]) -> tuple[int, int]:    Function
`_extract_mv_version`    utility or script function.
L80: def test_egg_info_save_version_info_setup_empty(self, tmpdir_cwd, env):    Function
`test_egg_info_save_version_info_setup_empty`    utility or script function.
L107: def _validate_content_order(content, expected):    Function `_validate_content_order`
utility or script function.
L116: def test_egg_info_save_version_info_setup_defaults(self, tmpdir_cwd, env):    Function
`test_egg_info_save_version_info_setup_defaults`    utility or script function.
L151: def test_expected_files_produced(self, tmpdir_cwd, env):    Function
`test_expected_files_produced`    utility or script function.
L167: def test_handling_utime_error(self, tmpdir_cwd, env):    Function
`test_handling_utime_error`    utility or script function.
L182: def test_license_is_a_string(self, tmpdir_cwd, env):    Function
`test_license_is_a_string`    utility or script function.
L215: def test_rebuilt(self, tmpdir_cwd, env):    Function `test_rebuilt`    utility or script
function.
L230: def test_manifest_template_is_read(self, tmpdir_cwd, env):    Function
`test_manifest_template_is_read`    utility or script function.
L248: def _setup_script_with_requires(self, requires, use_setup_cfg=False):    Function
`_setup_script_with_requires`    utility or script function.
L267: class RequiresTestHelper:    Utility (`RequiresTestHelper`)    helper methods for common
tasks.
L269: def parametrize(*test_list, **format_dict):    Function `parametrize`    utility or script
function.
```

```

L462: def test_requires(    Function `test_requires`    utility or script function.
L483: def test_install_requires_unordered_disallowed(self, tmpdir_cwd, env):    Function
`test_install_requires_unordered_disallowed`    utility or script function.
L494: def test_extras_require_with_invalid_marker(self, tmpdir_cwd, env):    Function
`test_extras_require_with_invalid_marker`    utility or script function.
L502: def test_extras_require_with_invalid_marker_in_req(self, tmpdir_cwd, env):    Function
`test_extras_require_with_invalid_marker_in_req`    utility or script function.
L510: def test_provides_extra(self, tmpdir_cwd, env):    Function `test_provides_extra`
utility or script function.
L527: def test_doesnt_provides_extra(self, tmpdir_cwd, env):    Function
`test_doesnt_provides_extra`    utility or script function.
L610: def test_setup_cfg_license_file(self, tmpdir_cwd, env, files, license_in_sources):
Function `test_setup_cfg_license_file`    utility or script function.
L836: def test_setup_cfg_license_files(    Function `test_setup_cfg_license_files`    utility or
script function.
L1020: def test_setup_cfg_license_file_license_files(    Function
`test_setup_cfg_license_file_license_files`    utility or script function.
L1041: def test_license_file_attr_pkg_info(self, tmpdir_cwd, env):    Function
`test_license_file_attr_pkg_info`    utility or script function.
L1080: def test_metadata_version(self, tmpdir_cwd, env):    Function `test_metadata_version`
utility or script function.
L1094: def test_long_description_content_type(self, tmpdir_cwd, env):    Function
`test_long_description_content_type`    utility or script function.
L1121: def test_long_description(self, tmpdir_cwd, env):    Function `test_long_description`
utility or script function.
L1144: def test_project_urls(self, tmpdir_cwd, env):    Function `test_project_urls`    utility
or script function.
L1176: def test_license(self, tmpdir_cwd, env):    Function `test_license`    utility or script
function.
L1189: def test_license_escape(self, tmpdir_cwd, env):    Function `test_license_escape`
utility or script function.
L1207: def test_python_requires_egg_info(self, tmpdir_cwd, env):    Function
`test_python_requires_egg_info`    utility or script function.
L1224: def test_manifest_maker_warning_suppression(self):    Function
`test_manifest_maker_warning_suppression`    utility or script function.
L1233: def test_egg_info_includes_setup_py(self, tmpdir_cwd):    Function
`test_egg_info_includes_setup_py`    utility or script function.
L1247: def _run_egg_info_command(self, tmpdir_cwd, env, cmd=None, output=None):    Function
`_run_egg_info_command`    utility or script function.
L1266: def test_egg_info_tag_only_once(self, tmpdir_cwd, env):    Function
`test_egg_info_tag_only_once`    utility or script function.
L1285: class TestWriteEntries:    Class (`TestWriteEntries`)    component used by the app (see
file context: None).
L1286: def test_invalid_entry_point(self, tmpdir_cwd, env):    Function
`test_invalid_entry_point`    utility or script function.
L1296: def test_valid_entry_point(self, tmpdir_cwd, env):    Function `test_valid_entry_point`
utility or script function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/setuptools/tests/test_manifest.py

```

L26: def make_local_path(s):    Function `make_local_path` utility or script function.
L45: def quiet():              Function `quiet` utility or script function.
L54: def touch(filename):      Function `touch` utility or script function.
L135: def pattern_match(request):    Function `pattern_match` utility or script function.
L146: def pattern_mismatch(request):  Function `pattern_mismatch` utility or script
function.
L150: def test_translated_pattern_match(pattern_match):    Function
`test_translated_pattern_match` utility or script function.
L155: def test_translated_pattern_mismatch(pattern_mismatch):    Function
`test_translated_pattern_mismatch` utility or script function.
L160: class TempDirTestCase:    Class (`TempDirTestCase`) component used by the app (see file
context: None).
L161: def setup_method(self, method):    Function `setup_method` Sets or updates a value.
L166: def teardown_method(self, method):    Function `teardown_method` utility or script
function.
L171: class TestManifestTest(TempDirTestCase):    Class (`TestManifestTest`) component used
by the app (see file context: None).
L172: def setup_method(self, method):    Function `setup_method` Sets or updates a value.
L211: def make_manifest(self, contents):    Function `make_manifest` utility or script
function.
L217: def get_files(self):    Function `get_files` Returns or fetches data.
L228: def test_no_manifest(self):    Function `test_no_manifest` utility or script function.
L232: def test_empty_files(self):    Function `test_empty_files` utility or script function.
L237: def test_include(self):    Function `test_include` utility or script function.
L243: def test_exclude(self):    Function `test_exclude` utility or script function.
L255: def test_include_multiple(self):    Function `test_include_multiple` utility or script
function.
L269: def test_graft(self):    Function `test_graft` utility or script function.
L281: def test_graft_glob_syntax(self):    Function `test_graft_glob_syntax` utility or
script function.
L293: def test_graft_global_exclude(self):    Function `test_graft_global_exclude` utility or
script function.
L305: def test_global_include(self):    Function `test_global_include` utility or script
function.
L322: def test_graft_prune(self):    Function `test_graft_prune` utility or script function.
L335: class TestFileListTest(TempDirTestCase):    Class (`TestFileListTest`) component used
by the app (see file context: None).
L342: def _compat_record_logs(self, monkeypatch, caplog):    Function `_compat_record_logs`
utility or script function.
L345: def _log(_logger, level, msg, args):    Function `_log` utility or script function.
L352: def get_records(self, caplog, *levels):    Function `get_records` Returns or fetches
data.
L355: def assertNoWarnings(self, caplog):    Function `assertNoWarnings` utility or script
function.
L359: def assertWarnings(self, caplog):    Function `assertWarnings` utility or script
function.

```

```

L366: def make_files(self, files):    Function `make_files` utility or script function.
L373: def test_process_template_line(self):    Function `test_process_template_line` utility
or script function.
L436: def test_exclude_pattern(self):    Function `test_exclude_pattern` utility or script
function.
L453: def test_include_pattern(self):    Function `test_include_pattern` utility or script
function.
L471: def test_process_template_line_invalid(self):    Function
`test_process_template_line_invalid` utility or script function.
L488: def test_include(self, caplog):    Function `test_include` utility or script function.
L505: def test_exclude(self, caplog):    Function `test_exclude` utility or script function.
L522: def test_global_include(self, caplog):    Function `test_global_include` utility or
script function.
L539: def test_global_exclude(self, caplog):    Function `test_global_exclude` utility or
script function.
L556: def test_recursive_include(self, caplog):    Function `test_recursive_include` utility
or script function.
L573: def test_recursive_exclude(self, caplog):    Function `test_recursive_exclude` utility
or script function.
L590: def test_graft(self, caplog):    Function `test_graft` utility or script function.
L607: def test_prune(self, caplog):    Function `test_prune` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/environment.py

```

L10: class VirtualEnv(jaraco.envs.VirtualEnv):    Class (`VirtualEnv`) component used by the
app (see file context: None).
L18: def run(self, cmd, *args, **kwargs):    Function `run` utility or script function.
L37: def _which_dirs(cmd):    Function `_which_dirs` utility or script function.
L46: def run_setup_py(cmd, pypath=None, path=None, data_stream=0, env=None):    Function
`run_setup_py` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/namespaces.py

```

L7: def iter_namespace_pkgs(namespace):    Function `iter_namespace_pkgs` utility or script
function.
L13: def build_namespace_package(tmpdir, name, version="1.0", impl="pkg_resources"):
Function `build_namespace_package` Constructs or prepares an object.
L58: def build_pep420_namespace_package(tmpdir, name):    Function
`build_pep420_namespace_package` Constructs or prepares an object.
L81: def make_site_dir(target):    Function `make_site_dir` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_wheel.py

```

L82: def test_wheel_info(filename, info):    Function `test_wheel_info` utility or script
function.
L92: def build_wheel(extra_file_defs=None, **kwargs):    Function `build_wheel` Constructs or
prepares an object.
L116: def tree_set(root):    Function `tree_set` utility or script function.
L124: def flatten_tree(tree):    Function `flatten_tree` utility or script function.
L139: def format_install_tree(tree):    Function `format_install_tree` utility or script
function.
L150: def _check_wheel_install(    Function `_check_wheel_install` utility or script
function.
L170: class Record:    Class (`Record`) component used by the app (see file context: None).
L171: def __init__(self, id, **kwargs) -> None:    Function `__init__` utility or script
function.
L175: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L554: def test_wheel_install(params):    Function `test_wheel_install` utility or script
function.
L579: def test_wheel_no_dist_dir():    Function `test_wheel_no_dist_dir` utility or script
function.
L594: def test_wheel_is_compatible(monkeypatch):    Function `test_wheel_is_compatible`
utility or script function.
L595: def sys_tags():    Function `sys_tags` utility or script function.
L605: def test_wheel_mode():    Function `test_wheel_mode` utility or script function.
L607: def build_wheel(extra_file_defs=None, **kwargs):    Function `build_wheel` Constructs
or prepares an object.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_warnings.py

```

L62: def test_formatting(monkeypatch, example_name):    Function `test_formatting` utility or
script function.
L76: def test_due_date_enforcement(monkeypatch):    Function `test_due_date_enforcement`
utility or script function.
L77: class _MyDeprecation(SetuptoolsDeprecationWarning):    Class (`_MyDeprecation`)
component used by the app (see file context: None).
L105: def _get_message(warn_info):    Function `_get_message` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_distu

tils_adoption.py

```

L13: def win_sr(env):    Function `win_sr` utility or script function.
L25: def find_distutils(venv, imports='distutils', env=None, **kwargs):    Function
`find_distutils` utility or script function.
L31: def count_meta_path(venv, env=None):    Function `count_meta_path` utility or script
function.
L50: def test_distutils_stdlib(venv):    Function `test_distutils_stdlib` utility or script
function.
L59: def test_distutils_local_with_setuptools(venv):    Function
`test_distutils_local_with_setuptools` utility or script function.
L70: def test_distutils_local(venv):    Function `test_distutils_local` utility or script
function.
L80: def test_pip_import(venv):    Function `test_pip_import` utility or script function.
L89: def test_distutils_has_origin():    Function `test_distutils_has_origin` utility or
script function.
L129: def test_modules_are_not_duplicated_on_import(distutils_version, imported_module,
venv):    Function `test_modules_are_not_duplicated_on_import` utility or script function.
L155: def test_log_module_is_not_duplicated_on_import(distutils_version, venv):    Function
`test_log_module_is_not_duplicated_on_import` utility or script function.
L188: def test_consistent_error_from_modified_py(distutils_version, imported_module, venv):
Function `test_consistent_error_from_modified_py` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_core_metadata.py

```

L66: def test_rfc822_unescape(content, result):    Function `test_rfc822_unescape` utility or
script function.
L70: def __read_test_cases():    Function `__read_test_cases` utility or script function.
L169: def test_read_metadata(name, attrs):    Function `test_read_metadata` utility or script
function.
L209: def __maintainer_test_cases():    Function `__maintainer_test_cases` utility or script
function.
L212: def merge_dicts(d1, d2):    Function `merge_dicts` utility or script function.
L278: def test_maintainer_author(name, attrs, tmpdir):    Function `test_maintainer_author`
utility or script function.
L317: class TestParityWithMetadataFromPyPaWheel:    Class
(`TestParityWithMetadataFromPyPaWheel`) component used by the app (see file context: None).
L318: def base_example(self):    Function `base_example` utility or script function.
L346: def test_requires_dist(self, tmp_path):    Function `test_requires_dist` utility or
script function.
L368: def dist(self, request, monkeypatch, tmp_path):    Function `dist` utility or script
function.
L384: def test_pkg_info_roundtrip(self, tmp_path, dist):    Function `test_pkg_info_roundtrip`
utility or script function.

```

```

L412: class TestPEP643:    Class (`TestPEP643`)    component used by the app (see file context:
None).
L451: def test_static_config_has_no_dynamic(self, file, tmpdir_cwd):    Function
`test_static_config_has_no_dynamic`    utility or script function.
L474: def test_modified_fields_marked_as_dynamic(self, file, fields, tmpdir_cwd):    Function
`test_modified_fields_marked_as_dynamic`    utility or script function.
L498: def test_license_files_dynamic(self, extra_toml, tmpdir_cwd):    Function
`test_license_files_dynamic`    utility or script function.
L532: def _makedist(**attrs):    Function `_makedist`    utility or script function.
L538: def _get_pkginfo(dist: Distribution):    Function `_get_pkginfo`    utility or script
function.
L544: def _get_metadata(dist: Distribution | None = None):    Function `_get_metadata`
utility or script function.
L548: def _valid_metadata(text: str) -> bool:    Function `_valid_metadata`    utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build
.py**

```

L6: def test_distribution_gives_setuptools_build_obj(tmpdir_cwd):    Function
`test_distribution_gives_setuptools_build_obj`    utility or script function.
L23: class Subcommand(Command):    Class (`Subcommand`)    component used by the app (see file
context: None).
L26: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L29: def finalize_options(self):    Function `finalize_options`    utility or script function.
L32: def run(self):    Function `run`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_uni
code_utils.py**

```

L4: def test_filesys_decode_fs_encoding_is_None(monkeypatch):    Function
`test_filesys_decode_fs_encoding_is_None`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_setu
uptools.py**

```

L23: def isolated_dir(tmpdir_cwd):    Function `isolated_dir`    utility or script function.

```

```

L27: def makeSetup(**args):    Function `makeSetup` utility or script function.
L47: class TestDepends:    Class (`TestDepends`) component used by the app (see file context:
None).
L48: def testExtractConst(self):    Function `testExtractConst` utility or script function.
L53: def f1():    Function `f1` utility or script function.
L72: def testFindModule(self):    Function `testFindModule` utility or script function.
L81: def sample_module(self, monkeypatch, tmp_path):    Function `sample_module` utility or
script function.
L90: def testModuleExtract(self, sample_module):    Function `testModuleExtract` utility or
script function.
L97: def testRequire(self, sample_module):    Function `testRequire` utility or script
function.
L120: def test_require_present(self):    Function `test_require_present` utility or script
function.
L138: class TestDistro:    Class (`TestDistro`) component used by the app (see file context:
None).
L139: def setup_method(self, method):    Function `setup_method` Sets or updates a value.
L150: def testDistroType(self):    Function `testDistroType` utility or script function.
L153: def testExcludePackage(self):    Function `testExcludePackage` utility or script
function.
L170: def testIncludeExclude(self):    Function `testIncludeExclude` utility or script
function.
L183: def testExcludePackages(self):    Function `testExcludePackages` utility or script
function.
L189: def testEmpty(self):    Function `testEmpty` utility or script function.
L195: def testContents(self):    Function `testContents` utility or script function.
L208: def testInvalidIncludeExclude(self):    Function `testInvalidIncludeExclude` utility or
script function.
L229: def example_source(tmpdir):    Function `example_source` utility or script function.
L236: def test_findall(example_source):    Function `test_findall` utility or script
function.
L243: def test_findall_curdir(example_source):    Function `test_findall_curdir` utility or
script function.
L251: def can_symlink(tmpdir):    Function `can_symlink` utility or script function.
L265: def test_findall_missing_symlink(tmpdir):    Function `test_findall_missing_symlink`
utility or script function.
L273: def test_its_own_wheel_does_not_contain_tests(setuptools_wheel):    Function
`test_its_own_wheel_does_not_contain_tests` utility or script function.
L281: def test_wheel_includes_cli_scripts(setuptools_wheel):    Function
`test_wheel_includes_cli_scripts` utility or script function.
L288: def test_wheel_includes_vendored_metadata(setuptools_wheel):    Function
`test_wheel_includes_vendored_metadata` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/contexts.py

```

L13: def tempdir(cd=lambda dir: None, **kwargs):    Function `tempdir` utility or script
function.
L25: def environment(**replacements):    Function `environment` utility or script function.
L49: def quiet():    Function `quiet` utility or script function.
L69: def save_user_site_setting():    Function `save_user_site_setting` Saves data to storage
or remote.
L78: def suppress_exceptions(*excs):    Function `suppress_exceptions` utility or script
function.
L85: def multiproc(request):    Function `multiproc` utility or script function.
L98: def session_locked_tmp_dir(request, tmp_path_factory, name):    Function
`sessions_locked_tmp_dir` utility or script function.
L112: def save_paths():    Function `save_paths` Saves data to storage or remote.
L123: def save_sys_modules():    Function `save_sys_modules` Saves data to storage or remote.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_meta.py

```

L37: class BuildBackendBase:    Class (`BuildBackendBase`) component used by the app (see
file context: None).
L38: def __init__(self, cwd='.', env=None, backend_name='setuptools.build_meta') -> None:
Function `__init__` utility or script function.
L44: class BuildBackend(BuildBackendBase):    Class (`BuildBackend`) component used by the
app (see file context: None).
L47: def __init__(self, *args, **kwargs) -> None:    Function `__init__` utility or script
function.
L51: def __getattr__(self, name: str) -> Callable[..., Any]:    Function `__getattr__`
utility or script function.
L54: def method(*args, **kw):    Function `method` utility or script function.
L72: def _kill(self, pid):    Function `_kill` utility or script function.
L79: class BuildBackendCaller(BuildBackendBase):    Class (`BuildBackendCaller`) component
used by the app (see file context: None).
L80: def __init__(self, *args, **kwargs) -> None:    Function `__init__` utility or script
function.
L85: def __call__(self, name, *args, **kw) -> Any:    Function `__call__` utility or script
function.
L113: def run():    Function `run` utility or script function.
L132: def run():    Function `run` utility or script function.
L141: def function():    Function `function` utility or script function.
L154: def run():    Function `run` utility or script function.
L198: def run():    Function `run` utility or script function.
L218: def run():    Function `run` utility or script function.
L226: class TestBuildMetaBackend:    Class (`TestBuildMetaBackend`) component used by the app
(see file context: None).
L229: def get_build_backend(self):    Function `get_build_backend` Returns or fetches data.
L233: def build_backend(self, tmpdir, request):    Function `build_backend` Constructs or
prepares an object.

```

```

L238: def test_get_requires_for_build_wheel(self, build_backend):    Function
`test_get_requires_for_build_wheel` utility or script function.
L243: def test_get_requires_for_build_sdist(self, build_backend):    Function
`test_get_requires_for_build_sdist` utility or script function.
L248: def test_build_wheel(self, build_backend):    Function `test_build_wheel` utility or
script function.
L269: def test_build_with_existing_file_present(self, build_type, tmpdir_cwd):    Function
`test_build_with_existing_file_present` utility or script function.
L320: def test_build_with_pyproject_config(self, tmpdir, setup_script):    Function
`test_build_with_pyproject_config` utility or script function.
L465: def test_static_metadata_in_pyproject_config(self, tmpdir):    Function
`test_static_metadata_in_pyproject_config` utility or script function.
L484: def run():    Function `run` utility or script function.
L528: def test_build_sdist(self, build_backend):    Function `test_build_sdist` utility or
script function.
L535: def test_prepare_metadata_for_build_wheel(self, build_backend):    Function
`test_prepare_metadata_for_build_wheel` utility or script function.
L543: def test_prepare_metadata_inplace(self, build_backend):    Function
`test_prepare_metadata_inplace` utility or script function.
L560: def test_build_sdist_explicit_dist(self, build_backend):    Function
`test_build_sdist_explicit_dist` utility or script function.
L567: def test_build_sdist_version_change(self, build_backend):    Function
`test_build_sdist_version_change` utility or script function.
L592: def test_build_sdist_pyproject_toml_exists(self, tmpdir_cwd):    Function
`test_build_sdist_pyproject_toml_exists` utility or script function.
L617: def test_build_sdist_setup_py_exists(self, tmpdir_cwd):    Function
`test_build_sdist_setup_py_exists` utility or script function.
L627: def test_build_sdist_setup_py_manifest_excluded(self, tmpdir_cwd):    Function
`test_build_sdist_setup_py_manifest_excluded` utility or script function.
L653: def test_build_sdist_builds_targz_even_if_zip_indicated(self, tmpdir_cwd):    Function
`test_build_sdist_builds_targz_even_if_zip_indicated` utility or script function.
L695: def test_build_sdist_relative_path_import(self, tmpdir_cwd):    Function
`test_build_sdist_relative_path_import` utility or script function.
L712: def _assert_link_tree(self, parent_dir):    Function `_assert_link_tree` utility or
script function.
L719: def test_editable_without_config_settings(self, tmpdir_cwd):    Function
`test_editable_without_config_settings` utility or script function.
L733: def test_build_wheel_inplace(self, tmpdir_cwd):    Function `test_build_wheel_inplace`
utility or script function.
L744: def test_editable_with_config_settings(self, tmpdir_cwd, config_settings):    Function
`test_editable_with_config_settings` utility or script function.
L769: def test_setup_requires(self, setup_literal, requirements, use_wheel, tmpdir_cwd):
Function `test_setup_requires` utility or script function.
L785: def run():    Function `run` utility or script function.
L806: def test_setup_requires_with_auto_discovery(self, tmpdir_cwd):    Function
`test_setup_requires_with_auto_discovery` utility or script function.
L834: def test_dont_install_setup_requires(self, tmpdir_cwd):    Function
`test_dont_install_setup_requires` utility or script function.
L850: def run():    Function `run` utility or script function.
L885: def test_sys_argv_passthrough(self, tmpdir_cwd):    Function `test_sys_argv_passthrough`
utility or script function.

```

```

L906: def test_setup_py_file_abspath(self, tmpdir_cwd):    Function
`test_setup_py_file_abspath` utility or script function.
L912: def test_build_with_empty_setuppy(self, build_backend, build_hook):    Function
`test_build_with_empty_setuppy` utility or script function.
L921: class TestBuildMetaLegacyBackend(TestBuildMetaBackend):    Class
(`TestBuildMetaLegacyBackend`) component used by the app (see file context: None).
L925: def test_build_sdist_relative_path_import(self, tmpdir_cwd):    Function
`test_build_sdist_relative_path_import` utility or script function.
L932: def test_sys_argv_passthrough(self, tmpdir_cwd):    Function `test_sys_argv_passthrough`
utility or script function.
L940: def test_sys_exit_0_in_setuppy(monkeypatch, tmp_path):    Function
`test_sys_exit_0_in_setuppy` utility or script function.
L953: def test_system_exit_in_setuppy(monkeypatch, tmp_path):    Function
`test_system_exit_in_setuppy` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_build_clib.py

```

L12: class TestBuildCLib:    Class (`TestBuildCLib`) component used by the app (see file
context: None).
L14: def test_build_libraries(self, mock_newer):    Function `test_build_libraries` utility
or script function.
L61: def test_build_libraries_reproducible(self, mock_newer):    Function
`test_build_libraries_reproducible` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/test_editable_install.py

```

L43: def editable_opts(request):    Function `editable_opts` utility or script function.
L131: def test_editable_with_pyproject(tmp_path, venv, files, editable_opts):    Function
`test_editable_with_pyproject` utility or script function.
L156: def test_editable_with_flat_layout(tmp_path, venv, editable_opts):    Function
`test_editable_with_flat_layout` utility or script function.
L196: def test_editable_with_single_module(tmp_path, venv, editable_opts):    Function
`test_editable_with_single_module` utility or script function.
L234: class TestLegacyNamespaces:    Class (`TestLegacyNamespaces`) component used by the app
(see file context: None).
L237: def test_nspkg_file_is_unique(self, tmp_path, monkeypatch):    Function
`test_nspkg_file_is_unique` utility or script function.
L271: def test_namespace_package_importable(    Function `test_namespace_package_importable`
utility or script function.
L298: class TestPep420Namespaces:    Class (`TestPep420Namespaces`) component used by the app

```

```

(see file context: None).
L299: def test_namespace_package_importable(self, venv, tmp_path, editable_opts):  Function
`test_namespace_package_importable` utility or script function.
L314: def test_namespace_created_via_package_dir(self, venv, tmp_path, editable_opts):
Function `test_namespace_created_via_package_dir` utility or script function.
L348: def test_namespace_accidental_config_in_lenient_mode(self, venv, tmp_path):  Function
`test_namespace_accidental_config_in_lenient_mode` utility or script function.
L399: def test_editable_with_prefix(tmp_path, sample_project, editable_opts):  Function
`test_editable_with_prefix` utility or script function.
L439: class TestFinderTemplate:  Class (`TestFinderTemplate`) component used by the app
(see file context: None).
L445: def install_finder(self, finder):  Function `install_finder` utility or script
function.
L450: def test_packages(self, tmp_path):  Function `test_packages` utility or script
function.
L482: def test_namespace(self, tmp_path):  Function `test_namespace` utility or script
function.
L505: def test_combine_namespaces(self, tmp_path):  Function `test_combine_namespaces`
utility or script function.
L532: def test_combine_namespaces_nested(self, tmp_path):  Function
`test_combine_namespaces_nested` utility or script function.
L575: def test_dynamic_path_computation(self, tmp_path):  Function
`test_dynamic_path_computation` utility or script function.
L611: def test_no_recursion(self, tmp_path):  Function `test_no_recursion` utility or
script function.
L632: def test_similar_name(self, tmp_path):  Function `test_similar_name` utility or
script function.
L656: def test_case_sensitivity(self, tmp_path):  Function `test_case_sensitivity` utility
or script function.
L697: def test_namespace_case_sensitivity(self, tmp_path):  Function
`test_namespace_case_sensitivity` utility or script function.
L738: def test_intermediate_packages(self, tmp_path):  Function `test_intermediate_packages`
utility or script function.
L783: def test_pkg_roots(tmp_path):  Function `test_pkg_roots` utility or script function.
L832: class TestOverallBehaviour:  Class (`TestOverallBehaviour`) component used by the app
(see file context: None).
L901: def test_editable_install(self, tmp_path, venv, layout, editable_opts):  Function
`test_editable_install` utility or script function.
L952: class TestLinkTree:  Class (`TestLinkTree`) component used by the app (see file
context: None).
L969: def test_generated_tree(self, tmp_path):  Function `test_generated_tree` utility or
script function.
L1003: def test_strict_install(self, tmp_path, venv):  Function `test_strict_install`
utility or script function.
L1036: def test_compat_install(tmp_path, venv):  Function `test_compat_install` utility or
script function.
L1069: def test_pbr_integration(pbr_package, venv, editable_opts):  Function
`test_pbr_integration` utility or script function.
L1086: class TestCustomBuildPy:  Class (`TestCustomBuildPy`) component used by the app (see
file context: None).
L1107: class my_build_py(orig):  Class (`my_build_py`) component used by the app (see file

```

```

context: None).
L1108: def run(self):    Function `run`    utility or script function.
L1117: def test_safeguarded_from_errors(self, tmp_path, venv):    Function
`test_safeguarded_from_errors`    utility or script function.
L1128: class TestCustomBuildWheel:    Class (`TestCustomBuildWheel`)    component used by the
app (see file context: None).
L1129: def install_custom_build_wheel(self, dist):    Function `install_custom_build_wheel`
utility or script function.
L1132: class MyBdistWheel(bdist_wheel_cls):    Class (`MyBdistWheel`)    component used by the
app (see file context: None).
L1133: def get_tag(self):    Function `get_tag`    Returns or fetches data.
L1142: def test_access_plat_name(self, tmpdir_cwd):    Function `test_access_plat_name`
utility or script function.
L1157: class TestCustomBuildExt:    Class (`TestCustomBuildExt`)    component used by the app
(see file context: None).
L1158: def install_custom_build_ext_distutils(self, dist):    Function
`install_custom_build_ext_distutils`    utility or script function.
L1161: class MyBuildExt(build_ext_cls):    Class (`MyBuildExt`)    component used by the app
(see file context: None).
L1169: def test_distutils_leave_inplace_files(self, tmpdir_cwd):    Function
`test_distutils_leave_inplace_files`    utility or script function.
L1189: def test_debugging_tips(tmpdir_cwd, monkeypatch):    Function `test_debugging_tips`
utility or script function.
L1208: def test_encode_pth():    Function `test_encode_pth`    utility or script function.
L1214: def install_project(name, venv, tmp_path, files, *opts):    Function `install_project`
utility or script function.
L1226: def _addsitedirs(new_dirs):    Function `_addsitedirs`    utility or script function.
L1242: def assert_path(pkg, expected):    Function `assert_path`    utility or script function.
L1250: def assert_link_to(file: Path, other: Path) -> None:    Function `assert_link_to`
utility or script function.
L1260: def comparable_path(str_with_path: str) -> str:    Function `comparable_path`    utility
or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/integration/helpers.py

```

L18: def run(cmd, env=None):    Function `run`    utility or script function.
L38: class Archive:    Class (`Archive`)    component used by the app (see file context: None).
L41: def __init__(self, filename) -> None:    Function `__init__`    utility or script function.
L50: def __iter__(self) -> Iterator[ZipInfo] | Iterator[tarfile.TarInfo]:    Function
`__iter__`    utility or script function.
L55: def get_name(self, zip_or_tar_info):    Function `get_name`    Returns or fetches data.
L60: def get_content(self, zip_or_tar_info):    Function `get_content`    Returns or fetches
data.
L70: def get_sdist_members(sdist_path):    Function `get_sdist_members`    Returns or fetches
data.

```



```
L78: def get_wheel_members(wheel_path):    Function `get_wheel_members`  Returns or fetches
data.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/integration/test_pip_install_sdist.py

```
L100: def venv_python(tmp_path):    Function `venv_python`  utility or script function.
L107: def _prepare(tmp_path, venv_python, monkeypatch):    Function `_prepare`  utility or
script function.
L127: def test_install_sdist(package, version, tmp_path, venv_python, setuptools_wheel):
Function `test_install_sdist`  utility or script function.
L151: def retrieve_sdist(package, version, tmp_path):    Function `retrieve_sdist`  utility or
script function.
L171: def retrieve_pypi_sdist_metadata(package, version):    Function
`retrieve_pypi_sdist_metadata`  utility or script function.
L186: def download(url, dest, md5_digest):    Function `download`  utility or script function.
L198: def build_deps(package, sdist_file):    Function `build_deps`  Constructs or prepares an
object.
L217: def _read_pyproject(archive):    Function `_read_pyproject`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/integration/test_pbr.py

```
L7: def test_pbr_integration(pbr_package, venv):    Function `test_pbr_integration`  utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_setupcfg.py

```
L23: class ErrConfigHandler(ConfigHandler[Target]):    Class (`ErrConfigHandler`)  component
used by the app (see file context: None).
L29: def make_package_dir(name, base_dir, ns=False):    Function `make_package_dir`  utility
or script function.
L40: def fake_env(    Function `fake_env`  utility or script function.
L66: def get_dist(tmpdir, kwargs_initial=None, parse=True):    Function `get_dist`  Returns or
fetches data.
L77: def test_parsers_implemented():    Function `test_parsers_implemented`  utility or script
```

```

function.
L83: class TestConfigurationReader:  Class (`TestConfigurationReader`)  component used by
the app (see file context: None).
L84: def test_basic(self, tmpdir):  Function `test_basic`  utility or script function.
L99: def test_no_config(self, tmpdir):  Function `test_no_config`  utility or script
function.
L103: def test_ignore_errors(self, tmpdir):  Function `test_ignore_errors`  utility or
script function.
L119: class TestMetadata:  Class (`TestMetadata`)  component used by the app (see file
context: None).
L120: def test_basic(self, tmpdir):  Function `test_basic`  utility or script function.
L157: def test_license_cfg(self, tmpdir):  Function `test_license_cfg`  utility or script
function.
L177: def test_file_mixed(self, tmpdir):  Function `test_file_mixed`  utility or script
function.
L191: def test_file_sandboxed(self, tmpdir):  Function `test_file_sandboxed`  utility or
script function.
L201: def test_aliases(self, tmpdir):  Function `test_aliases`  utility or script function.
L225: def test_multiline(self, tmpdir):  Function `test_multiline`  utility or script
function.
L245: def test_dict(self, tmpdir):  Function `test_dict`  utility or script function.
L260: def test_version(self, tmpdir):  Function `test_version`  utility or script function.
L294: def test_version_file(self, tmpdir):  Function `test_version_file`  utility or script
function.
L306: def test_version_with_package_dir_simple(self, tmpdir):  Function
`test_version_with_package_dir_simple`  utility or script function.
L320: def test_version_with_package_dir_rename(self, tmpdir):  Function
`test_version_with_package_dir_rename`  utility or script function.
L334: def test_version_with_package_dir_complex(self, tmpdir):  Function
`test_version_with_package_dir_complex`  utility or script function.
L348: def test_unknown_meta_item(self, tmpdir):  Function `test_unknown_meta_item`  utility
or script function.
L353: def test_usupported_section(self, tmpdir):  Function `test_usupported_section`
utility or script function.
L359: def test_classifiers(self, tmpdir):  Function `test_classifiers`  utility or script
function.
L389: def test_interpolation(self, tmpdir):  Function `test_interpolation`  utility or
script function.
L395: def test_non_ascii_1(self, tmpdir):  Function `test_non_ascii_1`  utility or script
function.
L400: def test_non_ascii_3(self, tmpdir):  Function `test_non_ascii_3`  utility or script
function.
L405: def test_non_ascii_4(self, tmpdir):  Function `test_non_ascii_4`  utility or script
function.
L414: def test_not_utf8(self, tmpdir):  Function `test_not_utf8`  utility or script
function.
L454: def test_invalid_options_previously_deprecated(  Function
`test_invalid_options_previously_deprecated`  utility or script function.
L471: class TestOptions:  Class (`TestOptions`)  component used by the app (see file
context: None).
L472: def test_basic(self, tmpdir):  Function `test_basic`  utility or script function.

```

```

L515: def test_multiline(self, tmpdir):    Function `test_multiline` utility or script
function.
L567: def test_package_dir_fail(self, tmpdir):    Function `test_package_dir_fail` utility or
script function.
L573: def test_package_data(self, tmpdir):    Function `test_package_data` utility or script
function.
L595: def test_packages(self, tmpdir):    Function `test_packages` utility or script
function.
L601: def test_find_directive(self, tmpdir):    Function `test_find_directive` utility or
script function.
L638: def test_find_namespace_directive(self, tmpdir):    Function
`test_find_namespace_directive` utility or script function.
L677: def test_extras_require(self, tmpdir):    Function `test_extras_require` utility or
script function.
L709: def test_raises_accidental_env_marker_misconfig(self, config, tmpdir):    Function
`test_raises_accidental_env_marker_misconfig` utility or script function.
L730: def test_warn_accidental_env_marker_misconfig(self, config, tmpdir):    Function
`test_warn_accidental_env_marker_misconfig` utility or script function.
L756: def test_nowarn_accidental_env_marker_misconfig(self, config, tmpdir, recwarn):
Function `test_nowarn_accidental_env_marker_misconfig` utility or script function.
L764: def test_dash_preserved_extras_require(self, tmpdir):    Function
`test_dash_preserved_extras_require` utility or script function.
L770: def test_entry_points(self, tmpdir):    Function `test_entry_points` utility or script
function.
L801: def test_case_sensitive_entry_points(self, tmpdir):    Function
`test_case_sensitive_entry_points` utility or script function.
L819: def test_data_files(self, tmpdir):    Function `test_data_files` utility or script
function.
L836: def test_data_files_globby(self, tmpdir):    Function `test_data_files_globby` utility
or script function.
L871: def test_python_requires_simple(self, tmpdir):    Function `test_python_requires_simple`
utility or script function.
L884: def test_python_requires_compound(self, tmpdir):    Function
`test_python_requires_compound` utility or script function.
L897: def test_python_requires_invalid(self, tmpdir):    Function
`test_python_requires_invalid` utility or script function.
L911: def test_cmdclass(self, tmpdir):    Function `test_cmdclass` utility or script
function.
L932: def test_requirements_file(self, tmpdir):    Function `test_requirements_file` utility
or script function.
L956: class TestExternalSetters:    Class (`TestExternalSetters`) component used by the app
(see file context: None).
L967: def _fake_distribution_init(self, dist, attrs):    Function `_fake_distribution_init`
utility or script function.
L978: def test_external_setters(self, mock_parent_init, tmpdir):    Function
`test_external_setters` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_pyprojecttoml.py

```

L85: def create_example(path, pkg_root):    Function `create_example`    Creates a resource or
document.
L114: def verify_example(config, path, pkg_root):    Function `verify_example`    utility or
script function.
L140: def test_read_configuration(tmp_path):    Function `test_read_configuration`    utility or
script function.
L159: def test_discovered_package_dir_with_attr_directive_in_config(tmp_path, pkg_root,
opts):    Function `test_discovered_package_dir_with_attr_directive_in_config`    utility or
script function.
L181: class TestEntryPoints:    Class (`TestEntryPoints`)    component used by the app (see file
context: None).
L182: def write_entry_points(self, tmp_path):    Function `write_entry_points`    utility or
script function.
L188: def pyproject(self, dynamic=None):    Function `pyproject`    utility or script function.
L193: def test_all_listed_in_dynamic(self, tmp_path):    Function `test_all_listed_in_dynamic`
utility or script function.
L205: def test_scripts_not_listed_in_dynamic(self, tmp_path, missing_dynamic):    Function
`test_scripts_not_listed_in_dynamic`    utility or script function.
L214: class TestClassifiers:    Class (`TestClassifiers`)    component used by the app (see file
context: None).
L215: def test_dynamic(self, tmp_path):    Function `test_dynamic`    utility or script
function.
L244: def test_dynamic_without_config(self, tmp_path):    Function
`test_dynamic_without_config`    utility or script function.
L257: def test_dynamic_readme_from_setup_script_args(self, tmp_path):    Function
`test_dynamic_readme_from_setup_script_args`    utility or script function.
L271: def test_dynamic_without_file(self, tmp_path):    Function `test_dynamic_without_file`
utility or script function.
L289: class TestImportNames:    Class (`TestImportNames`)    component used by the app (see file
context: None).
L298: def test_not_implemented(self, monkeypatch, tmp_path, example):    Function
`test_not_implemented`    utility or script function.
L325: def test_ignore_unrelated_config(tmp_path, example):    Function
`test_ignore_unrelated_config`    utility or script function.
L347: def test_invalid_example(tmp_path, example, error_msg):    Function
`test_invalid_example`    utility or script function.
L359: def test_empty(tmp_path, config):    Function `test_empty`    utility or script function.
L368: def test_include_package_data_by_default(tmp_path, config):    Function
`test_include_package_data_by_default`    utility or script function.
L379: def test_include_package_data_in_setuppy(tmp_path):    Function
`test_include_package_data_in_setuppy`    utility or script function.
L399: def test_warn_tools_typo(tmp_path):    Function `test_warn_tools_typo`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_expand.py

```

L14: def write_files(files, root_dir):    Function `write_files` utility or script function.
L21: def test_glob_relative(tmp_path, monkeypatch):    Function `test_glob_relative` utility
or script function.
L40: def test_read_files(tmp_path, monkeypatch):    Function `test_read_files` utility or
script function.
L69: class TestReadAttr:    Class (`TestReadAttr`) component used by the app (see file
context: None).
L80: def test_read_attr_encoding_cookie(self, example, tmp_path):    Function
`test_read_attr_encoding_cookie` utility or script function.
L84: def test_read_attr(self, tmp_path, monkeypatch):    Function `test_read_attr` utility or
script function.
L119: def test_read_annotated_attr(self, tmp_path, example):    Function
`test_read_annotated_attr` utility or script function.
L138: def test_read_dynamic_attr(self, tmp_path, monkeypatch, example):    Function
`test_read_dynamic_attr` utility or script function.
L149: def test_import_order(self, tmp_path):    Function `test_import_order` utility or
script function.
L178: def test_resolve_class(monkeypatch, tmp_path, package_dir, file, module, return_value):
    Function `test_resolve_class` utility or script function.
L195: def test_find_packages(tmp_path, args, pkgs):    Function `test_find_packages` utility
or script function.
L239: def test_fill_package_dir(tmp_path, files, where, expected_package_dir):    Function
`test_fill_package_dir` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/test_pyprojecttoml_dynamic_deps.py

```

L11: def test_dynamic_dependencies(tmp_path):    Function `test_dynamic_dependencies` utility
or script function.
L36: def test_dynamic_optional_dependencies(tmp_path):    Function
`test_dynamic_optional_dependencies` utility or script function.
L61: def test_mixed_dynamic_optional_dependencies(tmp_path):    Function
`test_mixed_dynamic_optional_dependencies` utility or script function.
L91: def test_mixed_extras_require_optional_dependencies(tmp_path):    Function
`test_mixed_extras_require_optional_dependencies` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/tes

t_apply_pyprojecttoml.py

```

L35: def makedist(path, **attrs):    Function `makedist` utility or script function.
L39: def _mock_expand_patterns(patterns, *_ , **__):    Function `_mock_expand_patterns`
utility or script function.
L52: def test_apply_pyproject_equivalent_to_setupcfg(url, monkeypatch, tmp_path):    Function
`test_apply_pyproject_equivalent_to_setupcfg` utility or script function.
L168: def main_cli(): pass    Function `main_cli` Entry point / main routine.
L169: def main_gui(): pass    Function `main_gui` Entry point / main routine.
L170: def main_tomatoes(): pass    Function `main_tomatoes` Entry point / main routine.
L200: def _pep621_example_project(    Function `_pep621_example_project` utility or script
function.
L218: def test_pep621_example(tmp_path):    Function `test_pep621_example` utility or script
function.
L233: def test_readme_content_type(tmp_path, readme, ctype):    Function
`test_readme_content_type` utility or script function.
L239: def test_undefined_content_type(tmp_path):    Function `test_undefined_content_type`
utility or script function.
L245: def test_no_explicit_content_type_for_missing_extension(tmp_path):    Function
`test_no_explicit_content_type_for_missing_extension` utility or script function.
L274: def test_utf8_maintainer_in_metadata( # issue-3663    Function
`test_utf8_maintainer_in_metadata` utility or script function.
L325: def test_license_in_metadata(    Function `test_license_in_metadata` utility or script
function.
L350: def test_license_classifier_with_license_expression(tmp_path):    Function
`test_license_classifier_with_license_expression` utility or script function.
L364: def test_license_classifier_without_license_expression(tmp_path):    Function
`test_license_classifier_without_license_expression` utility or script function.
L386: class TestLicenseFiles:    Class (`TestLicenseFiles`) component used by the app (see
file context: None).
L387: def base_pyproject(    Function `base_pyproject` utility or script function.
L411: def base_pyproject_license_pep639(self, tmp_path, additional_text=""):    Function
`base_pyproject_license_pep639` utility or script function.
L419: def test_both_license_and_license_files_defined(self, tmp_path):    Function
`test_both_license_and_license_files_defined` utility or script function.
L441: def test_both_license_and_license_files_defined_pep639(self, tmp_path):    Function
`test_both_license_and_license_files_defined_pep639` utility or script function.
L456: def test_license_files_defined_twice(self, tmp_path):    Function
`test_license_files_defined_twice` utility or script function.
L465: def test_default_patterns(self, tmp_path):    Function `test_default_patterns` utility
or script function.
L480: def test_missing_patterns(self, tmp_path):    Function `test_missing_patterns` utility
or script function.
L492: def test_deprecated_file_expands_to_text(self, tmp_path):    Function
`test_deprecated_file_expands_to_text` utility or script function.
L510: class TestPyModules:    Class (`TestPyModules`) component used by the app (see file
context: None).
L513: def dist(self, name):    Function `dist` utility or script function.
L526: def test_valid_module_name(self, tmp_path, monkeypatch, module):    Function
`test_valid_module_name` utility or script function.

```

```

L531: def test_invalid_module_name(self, tmp_path, monkeypatch, module):    Function
`test_invalid_module_name` utility or script function.
L537: class TestExtModules:    Class (`TestExtModules`) component used by the app (see file
context: None).
L538: def make_dist(self, toml_config):    Function `make_dist` utility or script function.
L544: def test_pyproject_sets_attribute(self, tmp_path, monkeypatch):    Function
`test_pyproject_sets_attribute` utility or script function.
L560: def test_pyproject_define_macros_as_tuples(self, tmp_path, monkeypatch):    Function
`test_pyproject_define_macros_as_tuples` utility or script function.
L578: class TestDeprecatedFields:    Class (`TestDeprecatedFields`) component used by the app
(see file context: None).
L579: def test_namespace_packages(self, tmp_path):    Function `test_namespace_packages`
utility or script function.
L593: class TestPresetField:    Class (`TestPresetField`) component used by the app (see file
context: None).
L594: def pyproject(self, tmp_path, dynamic, extra_content=""):    Function `pyproject`
utility or script function.
L621: def test_not_listed_in_dynamic(self, tmp_path, attr, field, value):    Function
`test_not_listed_in_dynamic` utility or script function.
L642: def test_listed_in_dynamic(self, tmp_path, attr, field, value):    Function
`test_listed_in_dynamic` utility or script function.
L649: def test_license_files_exempt_from_dynamic(self, monkeypatch, tmp_path):    Function
`test_license_files_exempt_from_dynamic` utility or script function.
L669: def test_warning_overwritten_dependencies(self, tmp_path):    Function
`test_warning_overwritten_dependencies` utility or script function.
L678: def test_optional_dependencies_dont_remove_env_markers(self, tmp_path):    Function
`test_optional_dependencies_dont_remove_env_markers` utility or script function.
L705: def test_scripts_dont_require_dynamic_entry_points(self, tmp_path, field, group):
Function `test_scripts_dont_require_dynamic_entry_points` utility or script function.
L713: class TestMeta:    Class (`TestMeta`) component used by the app (see file context:
None).
L714: def test_example_file_in_sdist(self, setuptools_sdist):    Function
`test_example_file_in_sdist` utility or script function.
L720: class TestInteropCommandLineParsing:    Class (`TestInteropCommandLineParsing`)
component used by the app (see file context: None).
L721: def test_version(self, tmp_path, monkeypatch, capsys):    Function `test_version`
utility or script function.
L739: class TestStaticConfig:    Class (`TestStaticConfig`) component used by the app (see
file context: None).
L740: def test_mark_static_fields(self, tmp_path, monkeypatch):    Function
`test_mark_static_fields` utility or script function.
L768: def core_metadata(dist) -> str:    Function `core_metadata` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/tests/config/do
wnloads/__init__.py**

```

L21: def output_file(url: str, download_dir: Path = DOWNLOAD_DIR) -> Path:    Function
`output_file` utility or script function.
L28: def retrieve_file(url: str, download_dir: Path = DOWNLOAD_DIR, wait: float = 5) -> Path:
    Function `retrieve_file` utility or script function.
L43: def urls_from_file(list_file: Path) -> list[str]:    Function `urls_from_file` utility
or script function.
L52: def download(url: str, dest: Path):    Function `download` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/log.py

```

L26: def set_threshold(level):    Function `set_threshold` Sets or updates a value.
L32: def set_verbosity(v):    Function `set_verbosity` Sets or updates a value.
L41: class Log(logging.Logger):    Class (`Log`) component used by the app (see file context:
None).
L44: def __init__(self, threshold=WARN):    Function `__init__` utility or script function.
L49: def threshold(self):    Function `threshold` utility or script function.
L53: def threshold(self, level):    Function `threshold` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/archive_util.py

```

L33: def _get_gid(name):    Function `_get_gid` utility or script function.
L46: def _get_uid(name):    Function `_get_uid` utility or script function.
L59: def make_tarball(    Function `make_tarball` utility or script function.
L108: def _set_uid_gid(tarinfo):    Function `_set_uid_gid` utility or script function.
L126: def make_zipfile(    Function `make_zipfile` utility or script function.
L198: def check_archive_formats(formats):    Function `check_archive_formats` utility or
script function.
L210: def make_archive(    Function `make_archive` utility or script function.
L220: def make_archive(    Function `make_archive` utility or script function.
L229: def make_archive(    Function `make_archive` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/dist.py

```

L62: def _ensure_list(value: str | Iterable[str], fieldname) -> str | list[str]:    Function

```



```

`_ensure_list` utility or script function.
L77: class Distribution: Class (`Distribution`) component used by the app (see file
context: None).
L153: def __init__(self, attrs: MutableMapping[str, Any] | None = None) -> None: # noqa:
C901 Function `_init__` utility or script function.
L309: def get_option_dict(self, command): Function `get_option_dict` Returns or fetches
data.
L320: def dump_option_dicts(self, header=None, commands=None, indent: str = "") -> None:
Function `dump_option_dicts` utility or script function.
L346: def find_config_files(self): Function `find_config_files` utility or script
function.
L369: def _gen_paths(self): Function `_gen_paths` utility or script function.
L388: def parse_config_files(self, filenames=None): # noqa: C901 Function
`parse_config_files` utility or script function.
L456: def parse_command_line(self): Function `parse_command_line` utility or script
function.
L523: def _get_toplevel_options(self): Function `_get_toplevel_options` utility or script
function.
L537: def _parse_command_opts(self, parser, args): # noqa: C901 Function
`_parse_command_opts` utility or script function.
L635: def finalize_options(self) -> None: Function `finalize_options` utility or script
function.
L648: def _show_help( Function `_show_help` utility or script function.
L699: def handle_display_options(self, option_order): Function `handle_display_options`
utility or script function.
L738: def print_command_list(self, commands, header, max_length) -> None: Function
`print_command_list` utility or script function.
L755: def print_commands(self) -> None: Function `print_commands` utility or script
function.
L780: def get_command_list(self): Function `get_command_list` Returns or fetches data.
L810: def get_command_packages(self): Function `get_command_packages` Returns or fetches
data.
L822: def get_command_class(self, command: str) -> type[Command]: Function
`get_command_class` Returns or fetches data.
L861: def get_command_obj( Function `get_command_obj` Returns or fetches data.
L865: def get_command_obj( Function `get_command_obj` Returns or fetches data.
L868: def get_command_obj(self, command: str, create: bool = True) -> Command | None:
Function `get_command_obj` Returns or fetches data.
L897: def _set_command_options(self, command_obj, option_dict=None): # noqa: C901 Function
`_set_command_options` utility or script function.
L940: def reinitialize_command( Function `reinitialize_command` utility or script
function.
L944: def reinitialize_command( Function `reinitialize_command` utility or script
function.
L947: def reinitialize_command( Function `reinitialize_command` utility or script
function.
L991: def announce(self, msg, level: int = logging.INFO) -> None: Function `announce`
utility or script function.
L994: def run_commands(self) -> None: Function `run_commands` utility or script function.
L1004: def run_command(self, command: str) -> None: Function `run_command` utility or
script function.

```

```

L1024: def has_pure_modules(self) -> bool:    Function `has_pure_modules` utility or script
function.
L1027: def has_ext_modules(self) -> bool:    Function `has_ext_modules` utility or script
function.
L1030: def has_c_libraries(self) -> bool:    Function `has_c_libraries` utility or script
function.
L1033: def has_modules(self) -> bool:    Function `has_modules` utility or script function.
L1036: def has_headers(self) -> bool:    Function `has_headers` utility or script function.
L1039: def has_scripts(self) -> bool:    Function `has_scripts` utility or script function.
L1042: def has_data_files(self) -> bool:    Function `has_data_files` utility or script
function.
L1045: def is_pure(self) -> bool:    Function `is_pure` utility or script function.
L1060: def _(self) -> None:    Function `_` utility or script function.
L1107: class DistributionMetadata:    Class (`DistributionMetadata`) component used by the
app (see file context: None).
L1136: def __init__(    Function `__init__` utility or script function.
L1161: def read_pkg_file(self, file: IO[str]) -> None:    Function `read_pkg_file` utility or
script function.
L1165: def _read_field(name: str) -> str | None:    Function `_read_field` utility or script
function.
L1171: def _read_list(name):    Function `_read_list` utility or script function.
L1213: def write_pkg_info(self, base_dir: str | os.PathLike[str]) -> None:    Function
`write_pkg_info` utility or script function.
L1220: def write_pkg_file(self, file: SupportsWrite[str]) -> None:    Function
`write_pkg_file` utility or script function.
L1237: def maybe_write(header, val):    Function `maybe_write` utility or script function.
L1259: def _write_list(self, file, name, values):    Function `_write_list` utility or script
function.
L1266: def get_name(self) -> str:    Function `get_name` Returns or fetches data.
L1269: def get_version(self) -> str:    Function `get_version` Returns or fetches data.
L1272: def get_fullname(self) -> str:    Function `get_fullname` Returns or fetches data.
L1276: def _fullname(name: str, version: str) -> str:    Function `_fullname` utility or
script function.
L1294: def get_author(self) -> str | None:    Function `get_author` Returns or fetches data.
L1297: def get_author_email(self) -> str | None:    Function `get_author_email` Returns or
fetches data.
L1300: def get_maintainer(self) -> str | None:    Function `get_maintainer` Returns or
fetches data.
L1303: def get_maintainer_email(self) -> str | None:    Function `get_maintainer_email`
Returns or fetches data.
L1306: def get_contact(self) -> str | None:    Function `get_contact` Returns or fetches
data.
L1309: def get_contact_email(self) -> str | None:    Function `get_contact_email` Returns or
fetches data.
L1312: def get_url(self) -> str | None:    Function `get_url` Returns or fetches data.
L1315: def get_license(self) -> str | None:    Function `get_license` Returns or fetches
data.
L1320: def get_description(self) -> str | None:    Function `get_description` Returns or
fetches data.
L1323: def get_long_description(self) -> str | None:    Function `get_long_description`
Returns or fetches data.

```

```

L1326: def get_keywords(self) -> str | list[str]:    Function `get_keywords` Returns or
fetches data.
L1329: def set_keywords(self, value: str | Iterable[str]) -> None:    Function `set_keywords`
Sets or updates a value.
L1332: def get_platforms(self) -> str | list[str] | None:    Function `get_platforms` Returns
or fetches data.
L1335: def set_platforms(self, value: str | Iterable[str]) -> None:    Function
`set_platforms` Sets or updates a value.
L1338: def get_classifiers(self) -> str | list[str]:    Function `get_classifiers` Returns or
fetches data.
L1341: def set_classifiers(self, value: str | Iterable[str]) -> None:    Function
`set_classifiers` Sets or updates a value.
L1344: def get_download_url(self) -> str | None:    Function `get_download_url` Returns or
fetches data.
L1348: def get_requires(self) -> str | list[str]:    Function `get_requires` Returns or
fetches data.
L1351: def set_requires(self, value: Iterable[str]) -> None:    Function `set_requires` Sets
or updates a value.
L1358: def get_provides(self) -> str | list[str]:    Function `get_provides` Returns or
fetches data.
L1361: def set_provides(self, value: Iterable[str]) -> None:    Function `set_provides` Sets
or updates a value.
L1369: def get_obsoletes(self) -> str | list[str]:    Function `get_obsoletes` Returns or
fetches data.
L1372: def set_obsoletes(self, value: Iterable[str]) -> None:    Function `set_obsoletes`
Sets or updates a value.
L1380: def fix_help_options(options):    Function `fix_help_options` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/cmd.py

```

L134: class Command:    Class (`Command`) component used by the app (see file context: None).
L175: def __init__(self, dist: Distribution) -> None:    Function `__init__` utility or script
function.
L117: def ensure_finalized(self) -> None:    Function `ensure_finalized` utility or script
function.
L136: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
L151: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L166: def dump_options(self, header=None, indent=""):    Function `dump_options` utility or
script function.
L181: def run(self) -> None:    Function `run` utility or script function.
L195: def announce(self, msg: object, level: int = logging.DEBUG) -> None:    Object
(singleton).

```

```

L198: def debug_print(self, msg: object) -> None:    Object (singleton).
L221: def _ensure_stringlike(self, option, what, default=None):    Function
`_ensure_stringlike` utility or script function.
L230: def ensure_string(self, option: str, default: str | None = None) -> None:    Function
`ensure_string` utility or script function.
L236: def ensure_string_list(self, option: str) -> None:    Function `ensure_string_list`
utility or script function.
L257: def _ensure_tested_string(self, option, tester, what, error_fmt, default=None):
Function `_ensure_tested_string` utility or script function.
L264: def ensure_filename(self, option: str) -> None:    Function `ensure_filename` utility
or script function.
L270: def ensure_dirname(self, option: str) -> None:    Function `ensure_dirname` utility or
script function.
L280: def get_command_name(self) -> str:    Function `get_command_name` Returns or fetches
data.
L286: def set_undefined_options(    Function `set_undefined_options` Sets or updates a value.
L311: def get_finalized_command(self, command: str, create: bool = True) -> Command:
Function `get_finalized_command` Returns or fetches data.
L324: def reinitialize_command(    Function `reinitialize_command` utility or script
function.
L328: def reinitialize_command(    Function `reinitialize_command` utility or script
function.
L331: def reinitialize_command(    Function `reinitialize_command` utility or script
function.
L336: def run_command(self, command: str) -> None:    Function `run_command` utility or
script function.
L343: def get_sub_commands(self) -> list[str]:    Function `get_sub_commands` Returns or
fetches data.
L358: def warn(self, msg: object) -> None:    Object (singleton).
L361: def execute(    Function `execute` utility or script function.
L370: def mkpath(self, name: str, mode: int = 0o777) -> None:    Function `mkpath` utility or
script function.
L374: def copy_file(    Function `copy_file` utility or script function.
L384: def copy_file(    Function `copy_file` utility or script function.
L393: def copy_file(    Function `copy_file` utility or script function.
L414: def copy_tree(    Function `copy_tree` utility or script function.
L436: def move_file(    Function `move_file` utility or script function.
L440: def move_file(    Function `move_file` utility or script function.
L443: def move_file(    Function `move_file` utility or script function.
L452: def spawn(    Function `spawn` utility or script function.
L461: def make_archive(    Function `make_archive` utility or script function.
L471: def make_archive(    Function `make_archive` utility or script function.
L480: def make_archive(    Function `make_archive` utility or script function.
L498: def make_file(    Function `make_file` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/_mod

ified.py

```
L23: def _newer(source, target):    Function `_newer` utility or script function.
L29: def newer(    Function `_newer` utility or script function.
L47: def newer_pairwise(    Function `_newer_pairwise` utility or script function.
L64: def newer_group(    Function `_newer_group` utility or script function.
L85: def missing_as_newer(source):    Function `_missing_as_newer` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/text_file.py

```
L10: class TextFile:    Class (`TextFile`) component used by the app (see file context:
None).
L79: def __init__(self, filename=None, file=None, **options):    Function `__init__` utility
or script function.
L114: def open(self, filename):    Function `open` utility or script function.
L121: def close(self):    Function `close` utility or script function.
L130: def gen_error(self, msg, line=None):    Function `gen_error` utility or script
function.
L142: def error(self, msg, line=None):    Function `error` utility or script function.
L145: def warn(self, msg, line=None):    Function `warn` utility or script function.
L155: def readline(self):    # noqa: C901    Function `readline` utility or script function.
L272: def readlines(self):    Function `readlines` utility or script function.
L282: def unreadline(self, line):    Function `unreadline` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/filelist.py

```
L21: class FileList:    Class (`FileList`) component used by the app (see file context:
None).
L36: def __init__(self, warn: object = None, debug_print: object = None) -> None:    Object
(singleton).
L42: def set_allfiles(self, allfiles: Iterable[str]) -> None:    Function `set_allfiles` Sets
or updates a value.
L45: def findall(self, dir: str | os.PathLike[str] = os.curdir) -> None:    Function `findall`
utility or script function.
L48: def debug_print(self, msg: object) -> None:    Object (singleton).
L59: def append(self, item: str) -> None:    Function `append` utility or script function.
L62: def extend(self, items: Iterable[str]) -> None:    Function `extend` utility or script
function.
L65: def sort(self) -> None:    Function `sort` utility or script function.
```

```

L74: def remove_duplicates(self) -> None:    Function `remove_duplicates` utility or script
function.
L82: def _parse_template_line(self, line):    Function `_parse_template_line` utility or
script function.
L112: def process_template_line(self, line: str) -> None:    # noqa: C901    Function
`process_template_line` utility or script function.
L201: def include_pattern(    Function `include_pattern` utility or script function.
L209: def include_pattern(    Function `include_pattern` utility or script function.
L218: def include_pattern(    Function `include_pattern` utility or script function.
L225: def include_pattern(    Function `include_pattern` utility or script function.
L273: def exclude_pattern(    Function `exclude_pattern` utility or script function.
L281: def exclude_pattern(    Function `exclude_pattern` utility or script function.
L290: def exclude_pattern(    Function `exclude_pattern` utility or script function.
L297: def exclude_pattern(    Function `exclude_pattern` utility or script function.
L324: def _find_all_simple(path):    Function `_find_all_simple` utility or script function.
L335: class _UniqueDirs(set):    Class (`_UniqueDirs`) component used by the app (see file
context: None).
L342: def __call__(self, walk_item):    Function `__call__` utility or script function.
L358: def filter(cls, items):    Function `filter` utility or script function.
L362: def findall(dir: str | os.PathLike[str] = os.curdir):    Function `findall` utility or
script function.
L374: def glob_to_re(pattern):    Function `glob_to_re` utility or script function.
L397: def translate_pattern(pattern, anchor=True, prefix=None, is_regex=False):    Function
`translate_pattern` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/_msvccompiler.py

```

L10: def __getattr__(name):    Function `__getattr__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/core.py

```

L43: def gen_usage(script_name):    Function `gen_usage` utility or script function.
L97: def setup(**attrs):    # noqa: C901    Function `setup` Sets or updates a value.
L114: class found in 'cmdclass' is used in place of the default, which is    Class (`found`)
component used by the app (see file context: None).
L194: def run_commands(dist):    Function `run_commands` utility or script function.
L221: def run_setup(script_name, script_args: Iterable[str] | None = None, stop_after="run"):
Function `run_setup` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/dir_util.py

```

L15: class SkipRepeatAbsolutePaths(set):    Class (`SkipRepeatAbsolutePaths`) component used
by the app (see file context: None).
L23: def __init__(self):    Function `__init__` utility or script function.
L27: def clear(cls):    Function `clear` utility or script function.
L30: def wrap(self, func):    Function `wrap` utility or script function.
L32: def wrapper(path, *args, **kwargs):    Function `wrapper` utility or script function.
L48: def mkpath(name: pathlib.Path, mode=0o777, verbose=True) -> None:    Function `mkpath`
utility or script function.
L67: def _(name: str, *args, **kwargs):    Function `_` utility or script function.
L72: def _(name: None, *args, **kwargs):    Function `_` utility or script function.
L79: def create_tree(base_dir, files, mode=0o777, verbose=True):    Function `create_tree`
Creates a resource or document.
L97: def copy_tree(    Function `copy_tree` utility or script function.
L147: def _copy_one(    Function `_copy_one` utility or script function.
L194: def _build_cmdtuple(path, cmdtuples):    Function `_build_cmdtuple` utility or script
function.
L205: def remove_tree(directory, verbose=True):    Function `remove_tree` utility or script
function.
L224: def ensure_relative(path):    Function `ensure_relative` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/file_util.py

```

L15: def _copy_file_contents(src, dst, buffer_size=16 * 1024):    # noqa: C901    Function
`_copy_file_contents` utility or script function.
L63: def copy_file(    # noqa: C901    Function `copy_file` utility or script function.
L167: def move_file(src, dst, verbose=True):    # noqa: C901    Function `move_file` utility or
script function.
L223: def write_file(filename, contents):    Function `write_file` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/fancy_getopt.py

```

L37: class FancyGetopt:    Class (`FancyGetopt`) component used by the app (see file context:
None).

```

```

L49: def __init__(self, option_table=None):    Function `__init__`    utility or script
function.
L89: def _build_index(self):    Function `_build_index`    utility or script function.
L94: def set_option_table(self, option_table):    Function `set_option_table`    Sets or updates
a value.
L98: def add_option(self, long_option, short_option=None, help_string=None):    Function
`add_option`    utility or script function.
L108: def has_option(self, long_option):    Function `has_option`    utility or script function.
L113: def get_attr_name(self, long_option):    Function `get_attr_name`    Returns or fetches
data.
L119: def _check_alias_dict(self, aliases, what):    Function `_check_alias_dict`    utility or
script function.
L131: def set_aliases(self, alias):    Function `set_aliases`    Sets or updates a value.
L136: def set_negative_aliases(self, negative_alias):    Function `set_negative_aliases`    Sets
or updates a value.
L144: def _grok_option_table(self):    # noqa: C901    Function `_grok_option_table`    utility or
script function.
L224: def getopt(self, args: Sequence[str] | None = None, object=None):    # noqa: C901
Object (singleton).
L285: def get_option_order(self):    Function `get_option_order`    Returns or fetches data.
L295: def generate_help(self, header=None):    # noqa: C901    Function `generate_help`
Generates content (often AI-generated).
L373: def print_help(self, header=None, file=None):    Function `print_help`    utility or
script function.
L380: def fancy_getopt(options, negative_opt, object, args: Sequence[str] | None):    Object
(singleton).
L389: def wrap_text(text, width):    Function `wrap_text`    utility or script function.
L443: def translate_longopt(opt):    Function `translate_longopt`    utility or script function.
L450: class OptionDummy:    Class (`OptionDummy`)    component used by the app (see file
context: None).
L454: def __init__(self, options: Sequence[Any] = []):    Function `__init__`    utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/versi
on.py**

```

L35: def suppress_known_deprecation():    Function `suppress_known_deprecation`    utility or
script function.
L45: class Version:    Class (`Version`)    component used by the app (see file context: None).
L52: def __init__(self, vstring=None):    Function `__init__`    utility or script function.
L61: def __repr__(self):    Function `__repr__`    utility or script function.
L64: def __eq__(self, other):    Function `__eq__`    utility or script function.
L70: def __lt__(self, other):    Function `__lt__`    utility or script function.
L76: def __le__(self, other):    Function `__le__`    utility or script function.
L82: def __gt__(self, other):    Function `__gt__`    utility or script function.
L88: def __ge__(self, other):    Function `__ge__`    utility or script function.

```



```

L112: class StrictVersion(Version):    Class (`StrictVersion`) component used by the app (see
file context: None).
L152: def parse(self, vstring):    Function `parse` utility or script function.
L169: def __str__(self):    Function `__str__` utility or script function.
L180: def _cmp(self, other):    Function `_cmp` utility or script function.
L193: def _cmp_prerelease(self, other):    Function `_cmp_prerelease` utility or script
function.
L280: class LooseVersion(Version):    Class (`LooseVersion`) component used by the app (see
file context: None).
L314: def parse(self, vstring):    Function `parse` utility or script function.
L328: def __str__(self):    Function `__str__` utility or script function.
L331: def __repr__(self):    Function `__repr__` utility or script function.
L334: def _cmp(self, other):    Function `_cmp` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/_macos_compat.py

```

L5: def bypass_compiler_fixup(cmd, args):    Function `bypass_compiler_fixup` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/spawn.py

```

L29: def _debug(cmd):    Function `_debug` utility or script function.
L36: def _inject_macos_ver(env: _MappingT | None) -> _MappingT | dict[str, str | int] | None:
    Function `_inject_macos_ver` utility or script function.
L48: def _resolve(env: None) -> os._Environ[str]: ...    Function `_resolve` utility or
script function.
L50: def _resolve(env: _MappingT) -> _MappingT: ...    Function `_resolve` utility or script
function.
L51: def _resolve(env: _MappingT | None) -> _MappingT | os._Environ[str]:    Function
`_resolve` utility or script function.
L55: def spawn(    Function `spawn` utility or script function.
L94: def find_executable(executable: str, path: str | None = None) -> str | None:    Function
`find_executable` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/dep_util.py

```
L6: def __getattr__(name):    Function `__getattr__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/extension.py

```
L23: class Extension:    Class (`Extension`)    component used by the app (see file context:
None).
L92: def __init__(    Function `__init__`    utility or script function.
L152: def __repr__(self):    Function `__repr__`    utility or script function.
L156: def read_setup_file(filename):    # noqa: C901    Function `read_setup_file`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/errors.py

```
L20: class DistutilsError(Exception):    Class (`DistutilsError`)    component used by the app
(see file context: None).
L26: class DistutilsModuleError(DistutilsError):    Class (`DistutilsModuleError`)    component
used by the app (see file context: None).
L33: class DistutilsClassError(DistutilsError):    Class (`DistutilsClassError`)    component
used by the app (see file context: None).
L42: class DistutilsGetoptError(DistutilsError):    Class (`DistutilsGetoptError`)    component
used by the app (see file context: None).
L48: class DistutilsArgError(DistutilsError):    Class (`DistutilsArgError`)    component used
by the app (see file context: None).
L55: class DistutilsFileError(DistutilsError):    Class (`DistutilsFileError`)    component used
by the app (see file context: None).
L63: class DistutilsOptionError(DistutilsError):    Class (`DistutilsOptionError`)    component
used by the app (see file context: None).
L74: class DistutilsSetupError(DistutilsError):    Class (`DistutilsSetupError`)    component
used by the app (see file context: None).
L81: class DistutilsPlatformError(DistutilsError):    Class (`DistutilsPlatformError`)
component used by the app (see file context: None).
L89: class DistutilsExecError(DistutilsError):    Class (`DistutilsExecError`)    component used
by the app (see file context: None).
L96: class DistutilsInternalError(DistutilsError):    Class (`DistutilsInternalError`)
component used by the app (see file context: None).
L103: class DistutilsTemplateError(DistutilsError):    Class (`DistutilsTemplateError`)
component used by the app (see file context: None).
L107: class DistutilsByteCompileError(DistutilsError):    Class (`DistutilsByteCompileError`)
component used by the app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/versionpredicate.py

```
L16: def splitUp(pred):    Function `splitUp`    utility or script function.
L40: class VersionPredicate:    Class (`VersionPredicate`)    component used by the app (see
file context: None).
L105: def __init__(self, versionPredicateStr):    Function `__init__`    utility or script
function.
L130: def __str__(self):    Function `__str__`    utility or script function.
L137: def satisfied_by(self, version):    Function `satisfied_by`    utility or script function.
L151: def split_provision(value):    Function `split_provision`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/utility.py

```
L35: def get_host_platform() -> str:    Function `get_host_platform`    Returns or fetches data.
L49: def get_platform() -> str:    Function `get_platform`    Returns or fetches data.
L67: def _clear_cached_macosx_ver():    Function `_clear_cached_macosx_ver`    utility or script
function.
L73: def get_macosx_target_ver_from_syscfg():    Function `get_macosx_target_ver_from_syscfg`
Returns or fetches data.
L86: def get_macosx_target_ver():    Function `get_macosx_target_ver`    Returns or fetches
data.
L118: def split_version(s: str) -> list[int]:    Function `split_version`    utility or script
function.
L124: def convert_path(pathname: str | os.PathLike[str]) -> str:    Function `convert_path`
utility or script function.
L142: def change_root(    Function `change_root`    utility or script function.
L166: def check_envron() -> None:    Function `check_envron`    utility or script function.
L188: def subst_vars(s, local_vars: Mapping[str, object]) -> str:    Object (singleton).
L207: def _subst_compat(s):    Function `_subst_compat`    utility or script function.
L213: def _subst(match):    Function `_subst`    utility or script function.
L227: def grok_environment_error(exc: object, prefix: str = "error: ") -> str:    Object
(singleton).
L238: def _init_regex():    Function `_init_regex`    utility or script function.
L245: def split_quoted(s: str) -> list[str]:    Function `split_quoted`    utility or script
function.
L311: def execute(    Function `execute`    utility or script function.
L331: def strtobool(val: str) -> bool:    Function `strtobool`    utility or script function.
L347: def byte_compile(    # noqa: C901    Function `byte_compile`    utility or script function.
L480: def rfc822_escape(header: str) -> str:    Function `rfc822_escape`    utility or script
function.
L495: def is_mingw() -> bool:    Function `is_mingw`    utility or script function.
```

```
L504: def is_freethreaded():    Function `is_freethreaded`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/sysconfig.py

```
L133: def deprecated(message):    Function `deprecated`    utility or script function.
L59: def _is_python_source_dir(d):    Function `_is_python_source_dir`    utility or script
function.
L71: def _is_parent(dir_a, dir_b):    Function `_is_parent`    utility or script function.
L81: def _fix_pcbuild(d):    Function `_fix_pcbuild`    utility or script function.
L95: def _python_build():    Function `_python_build`    utility or script function.
L117: def get_python_version():    Function `get_python_version`    Returns or fetches data.
L125: def get_python_inc(plat_specific: bool = False, prefix: str | None = None) -> str:
Function `get_python_inc`    Returns or fetches data.
L151: def _extant(path):    Function `_extant`    utility or script function.
L158: def _get_python_inc_posix(prefix, spec_prefix, plat_specific):    Function
`_get_python_inc_posix`    utility or script function.
L166: def _get_python_inc_posix_python(plat_specific):    Function
`_get_python_inc_posix_python`    utility or script function.
L182: def _get_python_inc_from_config(plat_specific, spec_prefix):    Function
`_get_python_inc_from_config`    utility or script function.
L205: def _get_python_inc_posix_prefix(prefix):    Function `_get_python_inc_posix_prefix`
utility or script function.
L211: def _get_python_inc_nt(prefix, spec_prefix, plat_specific):    Function
`_get_python_inc_nt`    utility or script function.
L223: def _posix_lib(standard_lib, libpython, early_prefix, prefix):    Function `_posix_lib`
utility or script function.
L230: def get_python_lib(    Function `get_python_lib`    Returns or fetches data.
L278: def _customize_macos():    Function `_customize_macos`    utility or script function.
L295: def customize_compiler(compiler: CCompiler) -> None:    Function `customize_compiler`
utility or script function.
L382: def get_config_h_filename() -> str:    Function `get_config_h_filename`    Returns or
fetches data.
L387: def get_makefile_filename() -> str:    Function `get_makefile_filename`    Returns or
fetches data.
L392: def parse_config_h(fp, g=None):    Function `parse_config_h`    utility or script
function.
L409: def parse_makefile(fn, g=None):    # noqa: C901    Function `parse_makefile`    utility or
script function.
L521: def expand_makefile_vars(s, vars):    Function `expand_makefile_vars`    utility or script
function.
L550: def get_config_vars() -> dict[str, str | int]: ...    Function `get_config_vars`
Returns or fetches data.
L552: def get_config_vars(arg: str, /, *args: str) -> list[str | int]: ...    Function
`get_config_vars`    Returns or fetches data.
L553: def get_config_vars(*args: str) -> list[str | int] | dict[str, str | int]:    Function
```

```

`get_config_vars` Returns or fetches data.
L575: def get_config_var(name: Literal["SO"]) -> int | str | None: ...    Function
`get_config_var` Returns or fetches data.
L577: def get_config_var(name: str) -> int | str | None: ...    Function `get_config_var`
Returns or fetches data.
L578: def get_config_var(name: str) -> int | str | None:    Function `get_config_var` Returns
or fetches data.
L591: def _add_flags(value: str, type: str) -> str:    Function `_add_flags` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_cmd.py

```

L12: class MyCmd(Command):    Class (`MyCmd`) component used by the app (see file context:
None).
L13: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L18: def cmd(request):    Function `cmd` utility or script function.
L22: class TestCommand:    Class (`TestCommand`) component used by the app (see file context:
None).
L23: def test_ensure_string_list(self, cmd):    Function `test_ensure_string_list` utility or
script function.
L48: def test_make_file(self, cmd):    Function `test_make_file` utility or script function.
L54: def _execute(func, args, exec_msg, level):    Function `_execute` utility or script
function.
L61: def test_dump_options(self, cmd):    Function `test_dump_options` utility or script
function.
L64: def _announce(msg, level):    Function `_announce` utility or script function.
L76: def test_ensure_string(self, cmd):    Function `test_ensure_string` utility or script
function.
L88: def test_ensure_filename(self, cmd):    Function `test_ensure_filename` utility or
script function.
L95: def test_ensure_dirname(self, cmd):    Function `test_ensure_dirname` utility or script
function.
L102: def test_debug_print(self, cmd, capsys, monkeypatch):    Function `test_debug_print`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_install.py

```

L21: def _make_ext_name(modname):    Function `_make_ext_name` utility or script function.
L27: class TestInstall(    Class (`TestInstall`) component used by the app (see file context:
None).

```

```

L34: def test_home_installation_scheme(self):    Function `test_home_installation_scheme`
utility or script function.
L56: def check_path(got, expected):    Function `check_path`    utility or script function.
L75: def test_user_site(self, monkeypatch):    Function `test_user_site`    utility or script
function.
L86: def _expanduser(path):    Function `_expanduser`    utility or script function.
L130: def test_handle_extra_path(self):    Function `test_handle_extra_path`    utility or
script function.
L159: def test_finalize_options(self):    Function `test_finalize_options`    utility or script
function.
L183: def test_record(self):    Function `test_record`    utility or script function.
L208: def test_record_extensions(self):    Function `test_record_extensions`    utility or
script function.
L240: def test_debug_mode(self, caplog, monkeypatch):    Function `test_debug_mode`    utility
or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_build_py.py**

```

L15: class TestBuildPy(support.TempdirManager):    Class (`TestBuildPy`)    component used by
the app (see file context: None).
L16: def test_package_data(self):    Function `test_package_data`    utility or script function.
L60: def test_empty_package_dir(self):    Function `test_empty_package_dir`    utility or script
function.
L82: def test_byte_compile(self):    Function `test_byte_compile`    utility or script function.
L98: def test_byte_compile_optimized(self):    Function `test_byte_compile_optimized`    utility
or script function.
L115: def test_dir_in_package_data(self):    Function `test_dir_in_package_data`    utility or
script function.
L147: def test_dont_write_bytecode(self, caplog):    Function `test_dont_write_bytecode`
utility or script function.
L163: def test_namespace_package_does_not_warn(self, caplog):    Function
`test_namespace_package_does_not_warn`    utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_bdist_rpm.py**

```

L24: def sys_executable_encodable():    Function `sys_executable_encodable`    utility or script
function.
L40: class TestBuildRpm(    Class (`TestBuildRpm`)    component used by the app (see file
context: None).
L47: def test_quiet(self):    Function `test_quiet`    utility or script function.

```

```
L90: def test_no_optimize_flag(self):    Function `test_no_optimize_flag`  utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_core.py

```
L39: class install(_install):    Class (`install`)  component used by the app (see file
context: None).
L48: def main():    Function `main`  Entry point / main routine.
L57: def save_stdout(monkeypatch):    Function `save_stdout`  Saves data to storage or remote.
L62: def temp_file(tmp_path):    Function `temp_file`  utility or script function.
L68: class TestCore:    Class (`TestCore`)  component used by the app (see file context:
None).
L69: def test_run_setup_provides_file(self, temp_file):    Function
`test_run_setup_provides_file`  utility or script function.
L75: def test_run_setup_preserves_sys_argv(self, temp_file):    Function
`test_run_setup_preserves_sys_argv`  utility or script function.
L82: def test_run_setup_defines_subclass(self, temp_file):    Function
`test_run_setup_defines_subclass`  utility or script function.
L90: def test_run_setup_uses_current_dir(self, tmp_path):    Function
`test_run_setup_uses_current_dir`  utility or script function.
L108: def test_run_setup_within_if_main(self, temp_file):    Function
`test_run_setup_within_if_main`  utility or script function.
L114: def test_run_commands(self, temp_file):    Function `test_run_commands`  utility or
script function.
L122: def test_debug_mode(self, capsys, monkeypatch):    Function `test_debug_mode`  utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_config_cmd.py

```
L15: def info_log(request, monkeypatch):    Function `info_log`  utility or script function.
L22: class TestConfig(support.TempdirManager):    Class (`TestConfig`)  component used by the
app (see file context: None).
L23: def _info(self, msg, *args):    Function `_info`  utility or script function.
L27: def test_dump_file(self):    Function `test_dump_file`  utility or script function.
L36: def test_search_cpp(self):    Function `test_search_cpp`  utility or script function.
L56: def test_finalize_options(self):    Function `test_finalize_options`  utility or script
function.
L70: def test_clean(self):    Function `test_clean`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_build_ext.py

```

L37: def user_site_dir(request):    Function `user_site_dir`    utility or script function.
L62: def safe_extension_import(name, path):    Function `safe_extension_import`    utility or
script function.
L70: def extension_redirect(mod, path):    Function `extension_redirect`    utility or script
function.
L91: class TestBuildExt(TempdirManager):    Class (`TestBuildExt`)    component used by the app
(see file context: None).
L92: def build_ext(self, *args, **kwargs):    Function `build_ext`    Constructs or prepares an
object.
L96: def test_build_ext(self, copy_so):    Function `test_build_ext`    utility or script
function.
L148: def _test_xx(copy_so):    Function `_test_xx`    utility or script function.
L185: def test_solaris_enable_shared(self):    Function `test_solaris_enable_shared`    utility
or script function.
L207: def test_user_site(self):    Function `test_user_site`    utility or script function.
L235: def test_optional_extension(self):    Function `test_optional_extension`    utility or
script function.
L251: def test_finalize_options(self):    Function `test_finalize_options`    utility or script
function.
L323: def test_check_extensions_list(self):    Function `test_check_extensions_list`    utility
or script function.
L383: def test_get_source_files(self):    Function `test_get_source_files`    utility or script
function.
L390: def test_unicode_module_names(self):    Function `test_unicode_module_names`    utility or
script function.
L403: def test_export_symbols__init__(self):    Function `test_export_symbols__init__`
utility or script function.
L416: def test_compiler_option(self):    Function `test_compiler_option`    utility or script
function.
L427: def test_get_outputs(self):    Function `test_get_outputs`    utility or script function.
L490: def test_ext_fullpath(self):    Function `test_ext_fullpath`    utility or script
function.
L529: def test_deployment_target_default(self):    Function `test_deployment_target_default`
utility or script function.
L537: def test_deployment_target_too_low(self):    Function `test_deployment_target_too_low`
utility or script function.
L545: def test_deployment_target_higher_ok(self):    # pragma: no cover    Function
`test_deployment_target_higher_ok`    utility or script function.
L557: def _try_compile_deployment_target(self, operator, target):    # pragma: no cover
Function `_try_compile_deployment_target`    utility or script function.
L624: class TestParallelBuildExt(TestBuildExt):    Class (`TestParallelBuildExt`)    component
used by the app (see file context: None).
L625: def build_ext(self, *args, **kwargs):    Function `build_ext`    Constructs or prepares an
object.

```


Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_version.py**

```
L10: def suppress_deprecation():    Function `suppress_deprecation`    utility or script
function.
L15: class TestVersion:    Class (`TestVersion`)    component used by the app (see file context:
None).
L16: def test_prerelease(self):    Function `test_prerelease`    utility or script function.
L25: def test_cmp_strict(self):    Function `test_cmp_strict`    utility or script function.
L60: def test_cmp(self):    Function `test_cmp`    utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_log.py**

```
L7: class TestLog:    Class (`TestLog`)    component used by the app (see file context: None).
L8: def test_non_ascii(self, caplog):    Function `test_non_ascii`    utility or script
function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_file_util.py**

```
L14: def stuff(request, tmp_path):    Function `stuff`    utility or script function.
L21: class TestFileUtil:    Utility (`TestFileUtil`)    helper methods for common tasks.
L22: def test_move_file_verbosity(self, caplog):    Function `test_move_file_verbosity`
utility or script function.
L45: def test_move_file_exception_unpacking_rename(self):    Function
`test_move_file_exception_unpacking_rename`    utility or script function.
L54: def test_move_file_exception_unpacking_unlink(self):    Function
`test_move_file_exception_unpacking_unlink`    utility or script function.
L64: def test_copy_file_hard_link(self):    Function `test_copy_file_hard_link`    utility or
script function.
L82: def test_copy_file_hard_link_failure(self):    Function
`test_copy_file_hard_link_failure`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/

test_dist.py

```

L24: class test_dist(Command):  Class (`test_dist`) component used by the app (see file
context: None).
L31: def initialize_options(self):  Function `initialize_options` Initialisation routine.
L35: class TestDistribution(Distribution):  Class (`TestDistribution`) component used by
the app (see file context: None).
L43: def find_config_files(self):  Function `find_config_files` utility or script function.
L48: def clear_argv():  Function `clear_argv` utility or script function.
L55: class TestDistributionBehavior(support.TempdirManager):  Class
(`TestDistributionBehavior`) component used by the app (see file context: None).
L56: def create_distribution(self, configfiles=()):  Function `create_distribution` Creates
a resource or document.
L63: def test_command_packages_unspecified(self, clear_argv):  Function
`test_command_packages_unspecified` utility or script function.
L68: def test_command_packages_cmdline(self, clear_argv):  Function
`test_command_packages_cmdline` utility or script function.
L92: def test_venv_install_options(self, tmp_path, clear_argv):  Function
`test_venv_install_options` utility or script function.
L153: def test_command_packages_configfile(self, tmp_path, clear_argv):  Function
`test_command_packages_configfile` utility or script function.
L177: def test_empty_options(self, request):  Function `test_empty_options` utility or
script function.
L184: def _warn(msg):  Function `_warn` utility or script function.
L204: def test_finalize_options(self):  Function `test_finalize_options` utility or script
function.
L220: def test_get_command_packages(self):  Function `test_get_command_packages` utility or
script function.
L231: def test_announce(self):  Function `test_announce` utility or script function.
L237: def test_find_config_files_disable(self, temp_home):  Function
`test_find_config_files_disable` utility or script function.
L250: def test_script_args_list_coercion(self):  Function `test_script_args_list_coercion`
utility or script function.
L260: def test_find_config_files_permission_error(self, fake_home):  Function
`test_find_config_files_permission_error` utility or script function.
L271: class TestMetadata(support.TempdirManager):  Class (`TestMetadata`) component used by
the app (see file context: None).
L272: def format_metadata(self, dist):  Function `format_metadata` utility or script
function.
L277: def test_simple_metadata(self):  Function `test_simple_metadata` utility or script
function.
L286: def test_provides(self):  Function `test_provides` utility or script function.
L300: def test_provides_illegal(self):  Function `test_provides_illegal` utility or script
function.
L306: def test_requires(self):  Function `test_requires` utility or script function.
L322: def test_requires_illegal(self):  Function `test_requires_illegal` utility or script
function.
L328: def test_requires_to_list(self):  Function `test_requires_to_list` utility or script
function.
L333: def test_obsoletes(self):  Function `test_obsoletes` utility or script function.

```

```

L349: def test_obsoletes_illegal(self):    Function `test_obsoletes_illegal` utility or
script function.
L355: def test_obsoletes_to_list(self):    Function `test_obsoletes_to_list` utility or
script function.
L360: def test_classifier(self):    Function `test_classifier` utility or script function.
L371: def test_classifier_invalid_type(self, caplog):    Function
`test_classifier_invalid_type` utility or script function.
L384: def test_keywords(self):    Function `test_keywords` utility or script function.
L393: def test_keywords_invalid_type(self, caplog):    Function `test_keywords_invalid_type`
utility or script function.
L406: def test_platforms(self):    Function `test_platforms` utility or script function.
L415: def test_platforms_invalid_types(self, caplog):    Function
`test_platforms_invalid_types` utility or script function.
L428: def test_download_url(self):    Function `test_download_url` utility or script
function.
L438: def test_long_description(self):    Function `test_long_description` utility or script
function.
L453: def test_custom_pydistutils(self, temp_home):    Function `test_custom_pydistutils`
utility or script function.
L462: def test_extra_pydistutils(self, monkeypatch, tmp_path):    Function
`test_extra_pydistutils` utility or script function.
L468: def test_fix_help_options(self):    Function `test_fix_help_options` utility or script
function.
L474: def test_show_help(self, request, capsys):    Function `test_show_help` utility or
script function.
L487: def test_read_metadata(self):    Function `test_read_metadata` utility or script
function.
L516: def test_round_trip_through_email_generator(self):    Function
`test_round_trip_through_email_generator` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_archive_util.py**

```

L28: def can_fs_encode(filename):    Function `can_fs_encode` utility or script function.
L41: def all_equal(values):    Function `all_equal` utility or script function.
L45: def same_drive(*paths):    Function `same_drive` utility or script function.
L49: class ArchiveUtilTestCase(support.TempdirManager):    Class (`ArchiveUtilTestCase`)
component used by the app (see file context: None).
L51: def test_make_tarball(self, name='archive'):    Function `test_make_tarball` utility or
script function.
L59: def test_make_tarball_gzip(self):    Function `test_make_tarball_gzip` utility or script
function.
L63: def test_make_tarball_bzip2(self):    Function `test_make_tarball_bzip2` utility or
script function.
L68: def test_make_tarball_xz(self):    Function `test_make_tarball_xz` utility or script
function.

```

```

L74: def test_make_tarball_latin1(self):    Function `test_make_tarball_latin1` utility or
script function.
L81: def test_make_tarball_extended(self):  Function `test_make_tarball_extended` utility
or script function.
L88: def _make_tarball(self, tmpdir, target_name, suffix, **kwargs):  Function
`_make_tarball` utility or script function.
L104: def _tarinfo(self, path):    Function `_tarinfo` utility or script function.
L123: def _create_files(self):    Function `_create_files` utility or script function.
L137: def test_tarfile_vs_tar(self):  Function `test_tarfile_vs_tar` utility or script
function.
L181: def test_make_zipfile(self):    Function `test_make_zipfile` utility or script
function.
L195: def test_make_zipfile_no_zlib(self):  Function `test_make_zipfile_no_zlib` utility or
script function.
L202: def fake_zipfile(*a, **kw):    Function `fake_zipfile` utility or script function.
L221: def test_check_archive_formats(self):  Function `test_check_archive_formats` utility
or script function.
L228: def test_make_archive(self):    Function `test_make_archive` utility or script
function.
L234: def test_make_archive_cwd(self):  Function `test_make_archive_cwd` utility or script
function.
L237: def _breaks(*args, **kw):    Function `_breaks` utility or script function.
L250: def test_make_archive_tar(self):  Function `test_make_archive_tar` utility or script
function.
L259: def test_make_archive_gztar(self):  Function `test_make_archive_gztar` utility or
script function.
L267: def test_make_archive_bztar(self):  Function `test_make_archive_bztar` utility or
script function.
L276: def test_make_archive_xztar(self):  Function `test_make_archive_xztar` utility or
script function.
L285: def test_make_archive_owner_group(self):  Function `test_make_archive_owner_group`
utility or script function.
L318: def test_tarfile_root_owner(self):  Function `test_tarfile_root_owner` utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_build_scripts.py**

```

L13: class TestBuildScripts(support.TempdirManager):  Class (`TestBuildScripts`) component
used by the app (see file context: None).
L14: def test_default_settings(self):    Function `test_default_settings` utility or script
function.
L24: def test_build(self):    Function `test_build` utility or script function.
L39: def get_build_scripts_cmd(self, target, scripts):  Function `get_build_scripts_cmd`
Returns or fetches data.
L50: def write_sample_scripts(dir):    Function `write_sample_scripts` utility or script

```

```
function.
L71: def test_version_int(self):    Function `test_version_int`    utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_filelist.py**

```
L31: def make_local_path(s):    Function `make_local_path`    utility or script function.
L36: class TestFileList:    Class (`TestFileList`)    component used by the app (see file
context: None).
L37: def assertNoWarnings(self, caplog):    Function `assertNoWarnings`    utility or script
function.
L42: def assertWarnings(self, caplog):    Function `assertWarnings`    utility or script
function.
L47: def test_glob_to_re(self):    Function `test_glob_to_re`    utility or script function.
L66: def test_process_template_line(self):    Function `test_process_template_line`    utility
or script function.
L111: def test_debug_print(self, capsys, monkeypatch):    Function `test_debug_print`    utility
or script function.
L120: def test_set_allfiles(self):    Function `test_set_allfiles`    utility or script
function.
L126: def test_remove_duplicates(self):    Function `test_remove_duplicates`    utility or
script function.
L134: def test_translate_pattern(self):    Function `test_translate_pattern`    utility or
script function.
L150: def test_exclude_pattern(self):    Function `test_exclude_pattern`    utility or script
function.
L166: def test_include_pattern(self):    Function `test_include_pattern`    utility or script
function.
L184: def test_process_template(self, caplog):    Function `test_process_template`    utility or
script function.
L299: class TestFindAll:    Class (`TestFindAll`)    component used by the app (see file
context: None).
L301: def test_missing_symlink(self, temp_cwd):    Function `test_missing_symlink`    utility or
script function.
L305: def test_basic_discovery(self, temp_cwd):    Function `test_basic_discovery`    utility or
script function.
L317: def test_non_local_discovery(self, tmp_path):    Function `test_non_local_discovery`
utility or script function.
L327: def test_symlink_loop(self, tmp_path):    Function `test_symlink_loop`    utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/

test_install_scripts.py

```
L11: class TestInstallScripts(support.TempdirManager):  Class (`TestInstallScripts`)
component used by the app (see file context: None).
L12: def test_default_settings(self):  Function `test_default_settings`  utility or script
function.
L33: def test_installation(self):  Function `test_installation`  utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_install_headers.py**

```
L11: class TestInstallHeaders(  Class (`TestInstallHeaders`)  component used by the app (see
file context: None).
L14: def test_simple_run(self):  Function `test_simple_run`  utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_install_lib.py**

```
L16: class TestInstallLib(  Class (`TestInstallLib`)  component used by the app (see file
context: None).
L19: def test_finalize_options(self):  Function `test_finalize_options`  utility or script
function.
L40: def test_byte_compile(self):  Function `test_byte_compile`  utility or script function.
L56: def test_get_outputs(self):  Function `test_get_outputs`  utility or script function.
L76: def test_get_inputs(self):  Function `test_get_inputs`  utility or script function.
L96: def test_dont_write_bytecode(self, caplog):  Function `test_dont_write_bytecode`
utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_bdist.py**

```
L7: class TestBuild(support.TempdirManager):  Class (`TestBuild`)  component used by the app
(see file context: None).
L8: def test_formats(self):  Function `test_formats`  utility or script function.
L30: def test_skip_build(self):  Function `test_skip_build`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_sdist.py

```

L48: def project_dir(request, distutils_managed_tempdir):    Function `project_dir` utility
or script function.
L65: def clean_lines(filepath):    Function `clean_lines` utility or script function.
L70: class TestSDist(support.TempdirManager):    Class (`TestSDist`) component used by the
app (see file context: None).
L71: def get_cmd(self, metadata=None):    Function `get_cmd` Returns or fetches data.
L90: def test_prune_file_list(self):    Function `test_prune_file_list` utility or script
function.
L141: def test_make_distribution(self):    Function `test_make_distribution` utility or
script function.
L170: def test_add_defaults(self):    Function `test_add_defaults` utility or script
function.
L255: def warnings(messages, prefix='warning: '):    Function `warnings` utility or script
function.
L259: def test_metadata_check_option(self, caplog):    Function `test_metadata_check_option`
utility or script function.
L277: def test_show_formats(self, capsys):    Function `test_show_formats` utility or script
function.
L289: def test_finalize_options(self):    Function `test_finalize_options` utility or script
function.
L314: def _check_template(self, content, caplog):    Function `_check_template` utility or
script function.
L323: def test_invalid_template_unknown_command(self, caplog):    Function
`test_invalid_template_unknown_command` utility or script function.
L326: def test_invalid_template_wrong_arguments(self, caplog):    Function
`test_invalid_template_wrong_arguments` utility or script function.
L331: def test_invalid_template_wrong_path(self, caplog):    Function
`test_invalid_template_wrong_path` utility or script function.
L337: def test_get_file_list(self):    Function `test_get_file_list` utility or script
function.
L367: def test_manifest_marker(self):    Function `test_manifest_marker` utility or script
function.
L379: def test_manifest_comments(self):    Function `test_manifest_comments` utility or
script function.
L398: def test_manual_manifest(self):    Function `test_manual_manifest` utility or script
function.
L430: def test_make_distribution_owner_group(self):    Function
`test_make_distribution_owner_group` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/

test_modified.py

```

L12: class TestDepUtil(support.TempdirManager):    Utility (`TestDepUtil`) helper methods for
common tasks.
L13: def test_newer(self):    Function `test_newer` utility or script function.
L32: def _setup_1234(self):    Function `_setup_1234` utility or script function.
L47: def test_newer_pairwise(self):    Function `test_newer_pairwise` utility or script
function.
L52: def test_newer_pairwise_mismatch(self):    Function `test_newer_pairwise_mismatch`
utility or script function.
L61: def test_newer_pairwise_empty(self):    Function `test_newer_pairwise_empty` utility or
script function.
L64: def test_newer_pairwise_fresh(self):    Function `test_newer_pairwise_fresh` utility or
script function.
L69: def test_newer_group(self):    Function `test_newer_group` utility or script function.
L97: def groups_target(tmp_path):    Function `groups_target` utility or script function.
L115: def test_newer_pairwise_group(groups_target):    Function `test_newer_pairwise_group`
utility or script function.
L122: def test_newer_group_no_sources_no_target(tmp_path):    Function
`test_newer_group_no_sources_no_target` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_clean.py**

```

L8: class TestClean(support.TempdirManager):    Class (`TestClean`) component used by the app
(see file context: None).
L9: def test_simple_run(self):    Function `test_simple_run` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_check.py**

```

L21: class TestCheck(support.TempdirManager):    Class (`TestCheck`) component used by the
app (see file context: None).
L22: def _run(self, metadata=None, cwd=None, **options):    Function `_run` utility or script
function.
L39: def test_check_metadata(self):    Function `test_check_metadata` utility or script
function.
L81: def test_check_author_maintainer(self):    Function `test_check_author_maintainer`
utility or script function.
L105: def test_check_document(self):    Function `test_check_document` utility or script
function.

```



```

L120: def test_check_restructuredtext(self):    Function `test_check_restructuredtext`
utility or script function.
L151: def test_check_restructuredtext_with_syntax_highlight(self):    Function
`test_check_restructuredtext_with_syntax_highlight` utility or script function.
L162: def foo():    Function `foo` utility or script function.
L172: def foo():    Function `foo` utility or script function.
L192: def test_check_all(self):    Function `test_check_all` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
__init__.py

```

L14: def missing_compiler_executable(cmd_names: Sequence[str] = []):    # pragma: no cover
Function `missing_compiler_executable` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_install_data.py

```

L12: class TestInstallData(    Class (`TestInstallData`) component used by the app (see file
context: None).
L15: def test_simple_run(self):    Function `test_simple_run` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_extension.py

```

L12: class TestExtension:    Class (`TestExtension`) component used by the app (see file
context: None).
L13: def test_read_setup_file(self):    Function `test_read_setup_file` utility or script
function.
L63: def test_extension_init(self):    Function `test_extension_init` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_bdist_dumb.py

```
L26: class TestBuildDumb( Class (`TestBuildDumb`) component used by the app (see file
context: None).
L30: def test_simple_built(self): Function `test_simple_built` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_util.py

```
L32: def environment(monkeypatch): Function `environment` utility or script function.
L44: class TestUtil: Utility (`TestUtil`) helper methods for common tasks.
L45: def test_get_host_platform(self): Function `test_get_host_platform` utility or script
function.
L55: def test_get_platform(self): Function `test_get_platform` utility or script function.
L66: def test_convert_path(self): Function `test_convert_path` utility or script function.
L72: def test_change_root(self): Function `test_change_root` utility or script function.
L76: def _isabs(path): Function `_isabs` utility or script function.
L81: def _join(*path): Function `_join` utility or script function.
L93: def _isabs(path): Function `_isabs` utility or script function.
L98: def _splitdrive(path): Function `_splitdrive` utility or script function.
L105: def _join(*path): Function `_join` utility or script function.
L122: def test_check_envron(self): Function `test_check_envron` utility or script
function.
L131: def test_check_envron_getpwuid(self): Function `test_check_envron_getpwuid`
utility or script function.
L159: def test_split_quoted(self): Function `test_split_quoted` utility or script
function.
L167: def test_strtobool(self): Function `test_strtobool` utility or script function.
L192: def test_rfc822_escape(self, given, wanted): Function `test_rfc822_escape` utility
or script function.
L228: def test_dont_write_bytecode(self): Function `test_dont_write_bytecode` utility or
script function.
L239: def test_grok_environment_error(self): Function `test_grok_environment_error`
utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/test_build.py

```
L10: class TestBuild(support.TempdirManager): Class (`TestBuild`) component used by the
app (see file context: None).
L11: def test_finalize_options(self): Function `test_finalize_options` utility or script
function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_text_file.py**

```
L17: class TestTextFile(support.TempdirManager):  Class (`TestTextFile`) component used by
the app (see file context: None).
L18: def test_class(self):  Function `test_class` utility or script function.
L54: def test_input(count, description, file, expected_result):  Function `test_input`
utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_dir_util.py**

```
L24: def stuff(request, monkeypatch, distutils_managed_tempdir):  Function `stuff` utility
or script function.
L32: class TestDirUtil(support.TempdirManager):  Utility (`TestDirUtil`) helper methods for
common tasks.
L33: def test_mkpath_remove_tree_verbosity(self, caplog):  Function
`test_mkpath_remove_tree_verbosity` utility or script function.
L48: def test_mkpath_with_custom_mode(self):  Function `test_mkpath_with_custom_mode`
utility or script function.
L57: def test_create_tree_verbosity(self, caplog):  Function `test_create_tree_verbosity`
utility or script function.
L68: def test_copy_tree_verbosity(self, caplog):  Function `test_copy_tree_verbosity`
utility or script function.
L87: def test_copy_tree_skips_nfs_temp_files(self):  Function
`test_copy_tree_skips_nfs_temp_files` utility or script function.
L98: def test_ensure_relative(self):  Function `test_ensure_relative` utility or script
function.
L106: def test_copy_tree_exception_in_listdir(self):  Function
`test_copy_tree_exception_in_listdir` utility or script function.
L117: def test_mkpath_exception_uncached(self, monkeypatch, tmp_path):  Function
`test_mkpath_exception_uncached` utility or script function.
L124: class FailPath(pathlib.Path):  Class (`FailPath`) component used by the app (see file
context: None).
L125: def mkdir(self, *args, **kwargs):  Function `mkdir` utility or script function.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
support.py**

```

L17: class TempdirManager:  Manager (`TempdirManager`)  orchestration/utility for managing
resources or behaviors.
L22: def mkdtemp(self):  Function `mkdtemp`  utility or script function.
L31: def write_file(self, path, content='xxx'):  Function `write_file`  utility or script
function.
L38: def create_dist(self, pkg_name='foo', **kw):  Function `create_dist`  Creates a
resource or document.
L56: class DummyCommand:  Class (`DummyCommand`)  component used by the app (see file
context: None).
L59: def __init__(self, **kwargs):  Function `__init__`  utility or script function.
L62: def ensure_finalized(self):  Function `ensure_finalized`  utility or script function.
L66: def copy_xxmodule_c(directory):  Function `copy_xxmodule_c`  utility or script
function.
L71: def test_compile(self):  Function `test_compile`  utility or script function.
L81: def _get_xxmodule_path():  Function `_get_xxmodule_path`  utility or script function.
L86: def fixup_build_ext(cmd):  Function `fixup_build_ext`  utility or script function.
L123: def combine_markers(cls):  Function `combine_markers`  utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_spawn.py**

```

L18: class TestSpawn(support.TempdirManager):  Class (`TestSpawn`)  component used by the
app (see file context: None).
L20: def test_spawn(self):  Function `test_spawn`  utility or script function.
L47: def test_find_executable(self, tmp_path):  Function `test_find_executable`  utility or
script function.
L130: def _make_executable(tmp_path, ext):  Function `_make_executable`  utility or script
function.
L138: def test_spawn_missing_exe(self):  Function `test_spawn_missing_exe`  utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/
test_build_clib.py**

```

L11: class TestBuildCLib(support.TempdirManager):  Class (`TestBuildCLib`)  component used
by the app (see file context: None).
L12: def test_check_library_dist(self):  Function `test_check_library_dist`  utility or
script function.
L45: def test_get_source_files(self):  Function `test_get_source_files`  utility or script
function.
L71: def test_build_libraries(self):  Function `test_build_libraries`  utility or script
function.

```

```

L75: class FakeCompiler:    Class (`FakeCompiler`)    component used by the app (see file
context: None).
L76: def compile(*args, **kw):    Function `compile`    utility or script function.
L94: def test_finalize_options(self):    Function `test_finalize_options`    utility or script
function.
L111: def test_run(self):    Function `test_run`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/tests/ test_sysconfig.py

```

L20: def _gen_makefile(root, contents):    Function `_gen_makefile`    utility or script
function.
L26: class TestSysconfig:    Class (`TestSysconfig`)    component used by the app (see file
context: None).
L27: def test_get_config_h_filename(self):    Function `test_get_config_h_filename`    utility
or script function.
L33: def test_get_makefile_filename(self):    Function `test_get_makefile_filename`    utility
or script function.
L37: def test_get_python_lib(self, tmp_path):    Function `test_get_python_lib`    utility or
script function.
L40: def test_get_config_vars(self):    Function `test_get_config_vars`    utility or script
function.
L48: def test_srcdir_simple(self):    Function `test_srcdir_simple`    utility or script
function.
L60: def test_srcdir_python_build(self):    Function `test_srcdir_python_build`    utility or
script function.
L71: def test_srcdir_independent_of_cwd(self):    Function `test_srcdir_independent_of_cwd`
utility or script function.
L81: def customize_compiler(self):    Function `customize_compiler`    utility or script
function.
L83: class compiler:    Class (`compiler`)    component used by the app (see file context:
None).
L87: def __init__(self):    Function `__init__`    utility or script function.
L90: def set_executables(self, **kw):    Function `set_executables`    Sets or updates a value.
L115: def test_customize_compiler(self):    Function `test_customize_compiler`    utility or
script function.
L174: def test_parse_makefile_base(self, tmp_path):    Function `test_parse_makefile_base`
utility or script function.
L186: def test_parse_makefile_literal_dollar(self, tmp_path):    Function
`test_parse_makefile_literal_dollar`    utility or script function.
L198: def test_sysconfig_module(self):    Function `test_sysconfig_module`    utility or script
function.
L222: def test_sysconfig_compiler_vars(self):    Function `test_sysconfig_compiler_vars`
utility or script function.
L233: def test_S0_deprecation(self):    Function `test_S0_deprecation`    utility or script
function.

```

```

L237: def test_customize_compiler_before_get_config_vars(self, tmp_path):    Function
`test_customize_compiler_before_get_config_vars` utility or script function.
L263: def test_parse_config_h(self):    Function `test_parse_config_h` utility or script
function.
L275: def test_win_ext_suffix(self):    Function `test_win_ext_suffix` utility or script
function.
L285: def test_win_build_venv_from_source_tree(self, tmp_path):    Function
`test_win_build_venv_from_source_tree` utility or script function.
L302: def test_get_python_inc_missing_config_dir(self, monkeypatch):    Function
`test_get_python_inc_missing_config_dir` utility or script function.
L312: def override(name):    Function `override` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/com
mand/install.py**

```

L99: def _load_sysconfig_schemes():    Function `_load_sysconfig_schemes` utility or script
function.
L107: def _load_schemes():    Function `_load_schemes` utility or script function.
L123: def _get_implementation():    Function `_get_implementation` utility or script
function.
L130: def _select_scheme(ob, name):    Function `_select_scheme` utility or script function.
L135: def _remove_set(ob, attrs):    Function `_remove_set` utility or script function.
L142: def _resolve_scheme(name):    Function `_resolve_scheme` utility or script function.
L151: def _load_scheme(name):    Function `_load_scheme` utility or script function.
L155: def _inject_headers(name, scheme):    Function `_inject_headers` utility or script
function.
L169: def _scheme_attrs(scheme):    Function `_scheme_attrs` utility or script function.
L174: class install(Command):    Class (`install`) component used by the app (see file
context: None).
L247: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
L324: def finalize_options(self) -> None:    # noqa: C901    Function `finalize_options`
utility or script function.
L507: def dump_dirs(self, msg) -> None:    Function `dump_dirs` utility or script function.
L527: def finalize_unix(self) -> None:    Function `finalize_unix` utility or script
function.
L576: def finalize_other(self) -> None:    Function `finalize_other` utility or script
function.
L598: def select_scheme(self, name) -> None:    Function `select_scheme` utility or script
function.
L601: def _expand_attrs(self, attrs):    Function `_expand_attrs` utility or script function.
L610: def expand_basedirs(self) -> None:    Function `expand_basedirs` utility or script
function.
L615: def expand_dirs(self) -> None:    Function `expand_dirs` utility or script function.
L626: def convert_paths(self, *names) -> None:    Function `convert_paths` utility or script
function.

```

```

L632: def handle_extra_path(self) -> None:    Function `handle_extra_path` utility or script
function.
L667: def change_roots(self, *names) -> None:    Function `change_roots` utility or script
function.
L673: def create_home_path(self) -> None:    Function `create_home_path` Creates a resource
or document.
L685: def run(self):    Function `run` utility or script function.
L735: def create_path_file(self):    Function `create_path_file` Creates a resource or
document.
L747: def get_outputs(self):    Function `get_outputs` Returns or fetches data.
L763: def get_inputs(self):    Function `get_inputs` Returns or fetches data.
L775: def has_lib(self):    Function `has_lib` utility or script function.
L782: def has_headers(self):    Function `has_headers` utility or script function.
L787: def has_scripts(self):    Function `has_scripts` utility or script function.
L792: def has_data(self):    Function `has_data` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/com
mand/install_egg_info.py**

```

L18: class install_egg_info(Command):    Class (`install_egg_info`) component used by the app
(see file context: None).
L26: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L30: def basename(self):    Function `basename` utility or script function.
L39: def finalize_options(self):    Function `finalize_options` utility or script function.
L44: def run(self):    Function `run` utility or script function.
L58: def get_outputs(self):    Function `get_outputs` Returns or fetches data.
L67: def safe_name(name):    Function `safe_name` utility or script function.
L75: def safe_version(version):    Function `safe_version` utility or script function.
L85: def to_filename(name):    Function `to_filename` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/com
mand/bdist.py**

```

L21: def deprecated(message):    Function `deprecated` utility or script function.
L25: def show_formats():    Function `show_formats` utility or script function.
L37: class ListCompat(dict[str, tuple[str, str]]):    Class (`ListCompat`) component used by
the app (see file context: None).
L40: def append(self, item: object) -> None:    Object (singleton).
L48: class bdist(Command):    Class (`bdist`) component used by the app (see file context:
None).
L105: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L114: def finalize_options(self) -> None:    Function `finalize_options` utility or script

```

```
function.
L142: def run(self) -> None:    Function `run`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build.py

```
L19: class build(Command):    Class (`build`)    component used by the app (see file context:
None).
L51: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L67: def finalize_options(self) -> None:    # noqa: C901    Function `finalize_options`    utility
or script function.
L128: def run(self) -> None:    Function `run`    utility or script function.
L139: def has_pure_modules(self):    Function `has_pure_modules`    utility or script function.
L142: def has_c_libraries(self):    Function `has_c_libraries`    utility or script function.
L145: def has_ext_modules(self):    Function `has_ext_modules`    utility or script function.
L148: def has_scripts(self):    Function `has_scripts`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/bdist_dumb.py

```
L18: class bdist_dumb(Command):    Class (`bdist_dumb`)    component used by the app (see file
context: None).
L62: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L73: def finalize_options(self):    Function `finalize_options`    utility or script function.
L94: def run(self):    Function `run`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_clib.py

```
L28: class build_clib(Command):    Class (`build_clib`)    component used by the app (see file
context: None).
L45: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L60: def finalize_options(self) -> None:    Function `finalize_options`    utility or script
function.
L87: def run(self) -> None:    Function `run`    utility or script function.
L106: def check_library_list(self, libraries) -> None:    Function `check_library_list`
utility or script function.
```



```

L142: def get_library_names(self):    Function `get_library_names` Returns or fetches data.
L153: def get_source_files(self):    Function `get_source_files` Returns or fetches data.
L168: def build_libraries(self, libraries) -> None:    Function `build_libraries` Constructs
or prepares an object.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_scripts.py

```

L16: class install_scripts(Command):    Class (`install_scripts`) component used by the app
(see file context: None).
L28: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L34: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L43: def run(self) -> None:    Function `run` utility or script function.
L55: def get_inputs(self):    Function `get_inputs` Returns or fetches data.
L58: def get_outputs(self):    Function `get_outputs` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_scripts.py

```

L25: class build_scripts(Command):    Class (`build_scripts`) component used by the app (see
file context: None).
L36: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L42: def finalize_options(self):    Function `finalize_options` utility or script function.
L51: def get_source_files(self):    Function `get_source_files` Returns or fetches data.
L54: def run(self):    Function `run` utility or script function.
L59: def copy_scripts(self):    Function `copy_scripts` utility or script function.
L78: def _copy_script(self, script, outfiles, updated_files):    Function `_copy_script`
utility or script function.
L115: def _change_modes(self, outfiles):    Function `_change_modes` utility or script
function.
L122: def _change_mode(self, file):    Function `_change_mode` utility or script function.
L130: def _validate_shebang(shebang, encoding):    Function `_validate_shebang` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/install_lib.py

```

L20: class install_lib(Command):  Class (`install_lib`) component used by the app (see file
context: None).
L56: def initialize_options(self):  Function `initialize_options` Initialisation routine.
L65: def finalize_options(self) -> None:  Function `finalize_options` utility or script
function.
L92: def run(self) -> None:  Function `run` utility or script function.
L108: def build(self) -> None:  Function `build` Constructs or prepares an object.
L116: def install(self) -> list[str] | Any:  Function `install` utility or script function.
L126: def byte_compile(self, files) -> None:  Function `byte_compile` utility or script
function.
L157: def _mutate_outputs(self, has_any, build_cmd, cmd_option, output_dir):  Function
`_mutate_outputs` utility or script function.
L170: def _bytecode_filenames(self, py_filenames):  Function `_bytecode_filenames` utility
or script function.
L195: def get_outputs(self):  Function `get_outputs` Returns or fetches data.
L220: def get_inputs(self):  Function `get_inputs` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/com mand/build_py.py

```

L17: class build_py(Command):  Class (`build_py`) component used by the app (see file
context: None).
L36: def initialize_options(self):  Function `initialize_options` Initialisation routine.
L46: def finalize_options(self) -> None:  Function `finalize_options` utility or script
function.
L71: def run(self) -> None:  Function `run` utility or script function.
L101: def get_data_files(self):  Function `get_data_files` Returns or fetches data.
L123: def find_data_files(self, package, src_dir):  Function `find_data_files` utility or
script function.
L138: def build_package_data(self) -> None:  Function `build_package_data` Constructs or
prepares an object.
L148: def get_package_dir(self, package):  Function `get_package_dir` Returns or fetches
data.
L187: def check_package(self, package, package_dir):  Function `check_package` utility or
script function.
L213: def check_module(self, module, module_file):  Function `check_module` utility or
script function.
L220: def find_package_modules(self, package, package_dir):  Function `find_package_modules`
utility or script function.
L235: def find_modules(self):  Function `find_modules` utility or script function.
L287: def find_all_modules(self):  Function `find_all_modules` utility or script function.
L303: def get_source_files(self):  Function `get_source_files` Returns or fetches data.
L306: def get_module_outfile(self, build_dir, package, module):  Function
`get_module_outfile` Returns or fetches data.
L310: def get_outputs(self, include_bytecode: bool = True) -> list[str]:  Function
`get_outputs` Returns or fetches data.

```

```

L337: def build_module(self, module, module_file, package):    Function `build_module`
Constructs or prepares an object.
L353: def build_modules(self) -> None:    Function `build_modules`    Constructs or prepares an
object.
L362: def build_packages(self) -> None:    Function `build_packages`    Constructs or prepares
an object.
L382: def byte_compile(self, files) -> None:    Function `byte_compile`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/install_headers.py

```

L12: class install_headers(Command):    Class (`install_headers`)    component used by the app
(see file context: None).
L22: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L27: def finalize_options(self):    Function `finalize_options`    utility or script function.
L32: def run(self):    Function `run`    utility or script function.
L42: def get_inputs(self):    Function `get_inputs`    Returns or fetches data.
L45: def get_outputs(self):    Function `get_outputs`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/_framework_compat.py

```

L13: def enabled():    Function `enabled`    utility or script function.
L41: def vars():    Function `vars`    utility or script function.
L48: def scheme(name):    Function `scheme`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/clean.py

```

L15: class clean(Command):    Class (`clean`)    component used by the app (see file context:
None).
L36: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L44: def finalize_options(self):    Function `finalize_options`    utility or script function.
L54: def run(self):    Function `run`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/sdist.py

```

L23: def show_formats():    Function `show_formats`    utility or script function.
L37: class sdist(Command):  Class (`sdist`)    component used by the app (see file context:
None).
L40: def checking_metadata(self) -> bool:    Function `checking_metadata`    utility or script
function.
L126: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L149: def finalize_options(self) -> None:    Function `finalize_options`    utility or script
function.
L164: def run(self) -> None:    Function `run`    utility or script function.
L186: def get_file_list(self) -> None:    Function `get_file_list`    Returns or fetches data.
L227: def add_defaults(self) -> None:    Function `add_defaults`    utility or script function.
L250: def _cs_path_exists(fspath):    Function `_cs_path_exists`    utility or script function.
L266: def _add_defaults_standards(self):    Function `_add_defaults_standards`    utility or
script function.
L288: def _add_defaults_optional(self):    Function `_add_defaults_optional`    utility or
script function.
L294: def _add_defaults_python(self):    Function `_add_defaults_python`    utility or script
function.
L310: def _add_defaults_data_files(self):    Function `_add_defaults_data_files`    utility or
script function.
L327: def _add_defaults_ext(self):    Function `_add_defaults_ext`    utility or script
function.
L332: def _add_defaults_c_libs(self):    Function `_add_defaults_c_libs`    utility or script
function.
L337: def _add_defaults_scripts(self):    Function `_add_defaults_scripts`    utility or script
function.
L342: def read_template(self) -> None:    Function `read_template`    utility or script
function.
L377: def prune_file_list(self) -> None:    Function `prune_file_list`    utility or script
function.
L400: def write_manifest(self) -> None:    Function `write_manifest`    utility or script
function.
L419: def _manifest_is_not_generated(self):    Function `_manifest_is_not_generated`    utility
or script function.
L428: def read_manifest(self) -> None:    Function `read_manifest`    utility or script
function.
L440: def make_release_tree(self, base_dir, files) -> None:    Function `make_release_tree`
utility or script function.
L482: def make_distribution(self) -> None:    Function `make_distribution`    utility or script
function.
L513: def get_archive_files(self):    Function `get_archive_files`    Returns or fetches data.
L520: def is_comment(line: str) -> bool:    Function `is_comment`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/config.py

```

L28: class config(Command):    Class (`config`) component used by the app (see file context:
None).
L50: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L65: def finalize_options(self):    Function `finalize_options` utility or script function.
L81: def run(self):    Function `run` utility or script function.
L88: def _check_compiler(self):    Function `_check_compiler` utility or script function.
L102: def _gen_temp_sourcefile(self, body, headers, lang):    Function `_gen_temp_sourcefile`
utility or script function.
L114: def _preprocess(self, body, headers, include_dirs, lang):    Function `_preprocess`
utility or script function.
L121: def _compile(self, body, headers, include_dirs, lang):    Function `_compile` utility
or script function.
L130: def _link(self, body, headers, include_dirs, libraries, library_dirs, lang):    Function
`_link` utility or script function.
L147: def _clean(self, *filenames):    Function `_clean` utility or script function.
L160: def try_cpp(self, body=None, headers=None, include_dirs=None, lang="c"):    Function
`try_cpp` utility or script function.
L177: def search_cpp(self, pattern, body=None, headers=None, include_dirs=None, lang="c"):
Function `search_cpp` utility or script function.
L197: def try_compile(self, body, headers=None, include_dirs=None, lang="c"):    Function
`try_compile` utility or script function.
L212: def try_link(    Function `try_link` utility or script function.
L236: def try_run(    Function `try_run` utility or script function.
L267: def check_func(    Function `check_func` utility or script function.
L304: def check_lib(    Function `check_lib` utility or script function.
L329: def check_header(self, header, include_dirs=None, library_dirs=None, lang="c"):
Function `check_header` utility or script function.
L339: def dump_file(filename, head=None):    Function `dump_file` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/command/build_ext.py

```

L38: class build_ext(Command):    Class (`build_ext`) component used by the app (see file
context: None).
L112: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L137: def _python_lib_dir(sysconfig):    Function `_python_lib_dir` utility or script
function.
L161: def finalize_options(self) -> None:    # noqa: C901    Function `finalize_options`
utility or script function.
L300: def run(self) -> None:    # noqa: C901    Function `run` utility or script function.

```

```

L369: def check_extensions_list(self, extensions) -> None: # noqa: C901 Function
`check_extensions_list` utility or script function.
L457: def get_source_files(self): Function `get_source_files` Returns or fetches data.
L466: def get_outputs(self): Function `get_outputs` Returns or fetches data.
L477: def build_extensions(self) -> None: Function `build_extensions` Constructs or
prepares an object.
L485: def _build_extensions_parallel(self): Function `_build_extensions_parallel` utility
or script function.
L506: def _build_extensions_serial(self): Function `_build_extensions_serial` utility or
script function.
L512: def _filter_build_errors(self, ext): Function `_filter_build_errors` utility or
script function.
L520: def build_extension(self, ext) -> None: Function `build_extension` Constructs or
prepares an object.
L601: def swig_sources(self, sources, extension): Function `swig_sources` utility or
script function.
L657: def find_swig(self): Function `find_swig` utility or script function.
L681: def get_ext_fullpath(self, ext_name: str) -> str: Function `get_ext_fullpath`
Returns or fetches data.
L708: def get_ext_fullname(self, ext_name: str) -> str: Function `get_ext_fullname`
Returns or fetches data.
L717: def get_ext_filename(self, ext_name: str) -> str: Function `get_ext_filename`
Returns or fetches data.
L728: def get_export_symbols(self, ext: Extension) -> list[str]: Function
`get_export_symbols` Returns or fetches data.
L749: def _get_module_name_for_symbol(self, ext): Function `_get_module_name_for_symbol`
utility or script function.
L758: def get_libraries(self, ext: Extension) -> list[str]: # noqa: C901 Function
`get_libraries` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/install_data.py

```

L19: class install_data(Command): Class (`install_data`) component used by the app (see
file context: None).
L34: def initialize_options(self): Function `initialize_options` Initialisation routine.
L42: def finalize_options(self) -> None: Function `finalize_options` utility or script
function.
L50: def run(self) -> None: Function `run` utility or script function.
L56: def _copy(self, f: tuple[str | os.PathLike, Iterable[str | os.PathLike]]): Function
`_copy` utility or script function.
L79: def _ (self, f: str | os.PathLike): Function `_` utility or script function.
L90: def get_inputs(self): Function `get_inputs` Returns or fetches data.
L93: def get_outputs(self): Function `get_outputs` Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/bdist_rpm.py

```
L24: class bdist_rpm(Command):    Class (`bdist_rpm`) component used by the app (see file
context: None).
L154: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L199: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L232: def finalize_package_data(self) -> None:    Function `finalize_package_data` utility or
script function.
L278: def run(self) -> None:    # noqa: C901    Function `run` utility or script function.
L405: def _dist_path(self, path):    Function `_dist_path` utility or script function.
L408: def _make_spec_file(self):    # noqa: C901    Function `_make_spec_file` utility or
script function.
L579: def _format_changelog(self, changelog):    Function `_format_changelog` utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/commands/check.py

```
L18: class SilentReporter(docutils.utils.Reporter):    Class (`SilentReporter`) component
used by the app (see file context: None).
L19: def __init__(    Function `__init__` utility or script function.
L34: def system_message(self, level, message, *children, **kwargs):    Function
`system_message` utility or script function.
L41: class check(Command):    Class (`check`) component used by the app (see file context:
None).
L57: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L64: def finalize_options(self):    Function `finalize_options` utility or script function.
L67: def warn(self, msg):    Function `warn` utility or script function.
L72: def run(self):    Function `run` utility or script function.
L91: def check_metadata(self):    Function `check_metadata` utility or script function.
L108: def check_restructuredtext(self):    Function `check_restructuredtext` utility or
script function.
L119: def _check_rst_data(self, data):    Function `_check_rst_data` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/unix.py

```

L55: def _split_env(cmd):    Function `_split_env` utility or script function.
L73: def _split_aix(cmd):    Function `_split_aix` utility or script function.
L87: def _linker_params(linker_cmd, compiler_cmd):    Function `_linker_params` utility or
script function.
L115: class Compiler(base.Compiler):    Class (`Compiler`) component used by the app (see
file context: None).
L161: def _fix_lib_args(self, libraries, library_dirs, runtime_library_dirs):    Function
`_fix_lib_args` utility or script function.
L175: def preprocess(    Function `preprocess` utility or script function.
L212: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):    Function
`_compile` utility or script function.
L225: def create_static_lib(    Function `create_static_lib` Creates a resource or document.
L249: def link(    Function `link` utility or script function.
L317: def library_dir_option(self, dir):    Function `library_dir_option` utility or script
function.
L320: def _is_gcc(self):    Function `_is_gcc` utility or script function.
L325: def runtime_library_dir_option(self, dir: str) -> str | list[str]:    # type:
ignore[override] # Fixed in pypa/distutils#339    Function `runtime_library_dir_option`
utility or script function.
L365: def library_option(self, lib):    Function `library_option` utility or script function.
L369: def _library_root(dir):    Function `_library_root` utility or script function.
L403: def find_library_file(self, dirs, lib, debug=False):    Function `find_library_file`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/base.py

```

L51: class Compiler:    Class (`Compiler`) component used by the app (see file context:
None).
L133: def __init__(self, verbose: bool = False, force: bool = False) -> None:    Function
`__init__` utility or script function.
L168: def set_executables(self, **kwargs: str) -> None:    Function `set_executables` Sets or
updates a value.
L201: def set_executable(self, key, value):    Function `set_executable` Sets or updates a
value.
L207: def _find_macro(self, name):    Function `_find_macro` utility or script function.
L215: def _check_macro_definitions(self, definitions):    Function `_check_macro_definitions`
utility or script function.
L220: def _check_macro_definition(self, defn):    Function `_check_macro_definition` utility
or script function.
L233: def _is_valid_macro(name, value=None):    Function `_is_valid_macro` utility or script
function.
L244: def define_macro(self, name: str, value: str | None = None) -> None:    Function
`define_macro` utility or script function.
L259: def undefine_macro(self, name: str) -> None:    Function `undefine_macro` utility or
script function.

```



```

L277: def add_include_dir(self, dir: str) -> None:    Function `add_include_dir` utility or
script function.
L285: def set_include_dirs(self, dirs: list[str]) -> None:    Function `set_include_dirs`
Sets or updates a value.
L295: def add_library(self, libname: str) -> None:    Function `add_library` utility or
script function.
L311: def set_libraries(self, libnames: list[str]) -> None:    Function `set_libraries` Sets
or updates a value.
L319: def add_library_dir(self, dir: str) -> None:    Function `add_library_dir` utility or
script function.
L327: def set_library_dirs(self, dirs: list[str]) -> None:    Function `set_library_dirs`
Sets or updates a value.
L334: def add_runtime_library_dir(self, dir: str) -> None:    Function
`add_runtime_library_dir` utility or script function.
L340: def set_runtime_library_dirs(self, dirs: list[str]) -> None:    Function
`set_runtime_library_dirs` Sets or updates a value.
L348: def add_link_object(self, object: str) -> None:    Object (singleton).
L356: def set_link_objects(self, objects: list[str]) -> None:    Function `set_link_objects`
Sets or updates a value.
L369: def _setup_compile(    Function `_setup_compile` utility or script function.
L400: def _get_cc_args(self, pp_opts, debug, before):    Function `_get_cc_args` utility or
script function.
L409: def _fix_compile_args(    Function `_fix_compile_args` utility or script function.
L448: def _prep_compile(self, sources, output_dir, depends=None):    Function `_prep_compile`
utility or script function.
L464: def _fix_object_args(    Function `_fix_object_args` utility or script function.
L483: def _fix_lib_args(    Function `_fix_lib_args` utility or script function.
L525: def _need_link(self, objects, output_file):    Function `_need_link` utility or script
function.
L534: def detect_language(self, sources: str | list[str]) -> str | None:    Function
`detect_language` utility or script function.
L557: def preprocess(    Function `preprocess` utility or script function.
L577: def compile(    Function `compile` utility or script function.
L653: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):    Function
`_compile` utility or script function.
L659: def create_static_lib(    Function `create_static_lib` Creates a resource or document.
L696: def link(    Function `link` utility or script function.
L759: def link_shared_lib(    Function `link_shared_lib` utility or script function.
L790: def link_shared_object(    Function `link_shared_object` utility or script function.
L821: def link_executable(    Function `link_executable` utility or script function.
L855: def library_dir_option(self, dir: str) -> str:    Function `library_dir_option` utility
or script function.
L861: def runtime_library_dir_option(self, dir: str) -> str:    Function
`runtime_library_dir_option` utility or script function.
L867: def library_option(self, lib: str) -> str:    Function `library_option` utility or
script function.
L873: def has_function( # noqa: C901    Function `has_function` utility or script function.
L963: def find_library_file(    Function `find_library_file` utility or script function.
L1008: def object_filenames(    Function `object_filenames` utility or script function.
L1022: def out_extensions(self):    Function `out_extensions` utility or script function.
L1025: def _make_out_path(self, output_dir, strip_dir, src_name):    Function `_make_out_path`

```

```

utility or script function.
L1031: def _make_out_path_exts(cls, output_dir, strip_dir, src_name, extensions):  Function
`_make_out_path_exts` utility or script function.
L1051: def _make_relative(base: pathlib.Path):  Function `_make_relative` utility or script
function.
L1055: def shared_object_filename(  Function `shared_object_filename` utility or script
function.
L1062: def shared_object_filename(  Function `shared_object_filename` utility or script
function.
L1068: def shared_object_filename(  Function `shared_object_filename` utility or script
function.
L1080: def executable_filename(  Function `executable_filename` utility or script function.
L1087: def executable_filename(  Function `executable_filename` utility or script function.
L1093: def executable_filename(  Function `executable_filename` utility or script function.
L1104: def library_filename(  Function `library_filename` utility or script function.
L1127: def announce(self, msg: object, level: int = 1) -> None:  Object (singleton).
L1130: def debug_print(self, msg: object) -> None:  Object (singleton).
L1136: def warn(self, msg: object) -> None:  Object (singleton).
L1139: def execute(  Function `execute` utility or script function.
L1148: def spawn(  Function `spawn` utility or script function.
L1154: def move_file(  Function `move_file` utility or script function.
L1158: def move_file(  Function `move_file` utility or script function.
L1161: def move_file(  Function `move_file` utility or script function.
L1168: def mkpath(self, name, mode=0o777):  Function `mkpath` utility or script function.
L1188: def get_default_compiler(osname: str | None = None, platform: str | None = None) ->
str:  Function `get_default_compiler` Returns or fetches data.
L1237: def show_compilers() -> None:  Function `show_compilers` utility or script function.
L1254: def new_compiler(  Function `new_compiler` utility or script function.
L1305: def gen_preprocess_options(  Function `gen_preprocess_options` utility or script
function.
L1351: def gen_lib_options(  Function `gen_lib_options` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/msvc.py

```

L43: def _find_vc2015():  Function `_find_vc2015` utility or script function.
L72: def _find_vc2017():  Function `_find_vc2017` utility or script function.
L130: def _find_vcvarsall(plat_spec):  Function `_find_vcvarsall` utility or script
function.
L149: def _get_vc_env(plat_spec):  Function `_get_vc_env` utility or script function.
L179: def _find_exe(exe, paths=None):  Function `_find_exe` utility or script function.
L205: def _get_vcvars_spec(host_platform, platform):  Function `_get_vcvars_spec` utility
or script function.
L234: class Compiler(base.Compiler):  Class (`Compiler`) component used by the app (see
file context: None).
L263: def __init__(self, verbose=False, force=False) -> None:  Function `__init__` utility

```

```

or script function.
L270: def _configure(cls, vc_env):    Function `_configure` utility or script function.
L278: def _parse_path(val):    Function `_parse_path` utility or script function.
L281: def initialize(self, plat_name: str | None = None) -> None:    Function `_initialize`
Initialisation routine.
L363: def out_extensions(self) -> dict[str, str]:    Function `_out_extensions` utility or
script function.
L372: def compile( # noqa: C901    Function `_compile` utility or script function.
L466: def create_static_lib(    Function `_create_static_lib` Creates a resource or document.
L491: def link(    Function `_link` utility or script function.
L560: def spawn(self, cmd):    Function `_spawn` utility or script function.
L567: def _fallback_spawn(self, cmd, env):    Function `_fallback_spawn` utility or script
function.
L589: def library_dir_option(self, dir):    Function `_library_dir_option` utility or script
function.
L592: def runtime_library_dir_option(self, dir):    Function `_runtime_library_dir_option`
utility or script function.
L597: def library_option(self, lib):    Function `_library_option` utility or script function.
L600: def find_library_file(self, dirs, lib, debug=False):    Function `_find_library_file`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/zos.py

```

L105: class Compiler(unix.Compiler):    Class (`Compiler`) component used by the app (see
file context: None).
L110: def _get_zos_compiler_name(self):    Function `_get_zos_compiler_name` utility or
script function.
L139: def __init__(self, verbose=False, force=False):    Function `___init__` utility or
script function.
L144: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):    Function
`_compile` utility or script function.
L163: def runtime_library_dir_option(self, dir):    Function `_runtime_library_dir_option`
utility or script function.
L166: def link(    Function `_link` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/errors.py

```

L1: class Error(Exception):    Class (`Error`) component used by the app (see file context:
None).
L5: class PreprocessError(Error):    Class (`PreprocessError`) component used by the app (see

```

```

file context: None).
L9: class CompileError(Error):  Class (`CompileError`)  component used by the app (see file
context: None).
L13: class LibError(Error):  Class (`LibError`)  component used by the app (see file
context: None).
L18: class LinkError(Error):  Class (`LinkError`)  component used by the app (see file
context: None).
L23: class UnknownFileType(Error):  Class (`UnknownFileType`)  component used by the app
(see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/cygwin.py

```

L31: def get_msvcr():  Function `get_msvcr`  Returns or fetches data.
L42: class Compiler(unix.Compiler):  Class (`Compiler`)  component used by the app (see file
context: None).
L55: def __init__(self, verbose=False, force=False):  Function `__init__`  utility or script
function.
L92: def gcc_version(self):  Function `gcc_version`  utility or script function.
L106: def _compile(self, obj, src, ext, cc_args, extra_postargs, pp_opts):  Function
`_compile`  utility or script function.
L130: def link(  Function `link`  utility or script function.
L218: def runtime_library_dir_option(self, dir):  Function `runtime_library_dir_option`
utility or script function.
L227: def _make_out_path(self, output_dir, strip_dir, src_name):  Function `_make_out_path`
utility or script function.
L233: def out_extensions(self):  Function `out_extensions`  utility or script function.
L244: class MinGW32Compiler(Compiler):  Class (`MinGW32Compiler`)  component used by the app
(see file context: None).
L249: def __init__(self, verbose=False, force=False):  Function `__init__`  utility or
script function.
L268: def runtime_library_dir_option(self, dir):  Function `runtime_library_dir_option`
utility or script function.
L281: def check_config_h():  Function `check_config_h`  utility or script function.
L330: def is_cygwincc(cc):  Function `is_cygwincc`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_unix.py

```

L19: def save_values(monkeypatch):  Function `save_values`  Saves data to storage or remote.
L26: def compiler_wrapper(request):  Function `compiler_wrapper`  utility or script
function.

```

```

L27: class CompilerWrapper(unix.Compiler):    Class (`CompilerWrapper`) component used by the
app (see file context: None).
L28: def rpath_foo(self):    Function `rpath_foo` utility or script function.
L34: class TestUnixCCompiler(support.TempdirManager):    Class (`TestUnixCCompiler`)
component used by the app (see file context: None).
L36: def test_runtime_libdir_option(self):    # noqa: C901    Function
`test_runtime_libdir_option` utility or script function.
L66: def make_darwin_gcv(syscfg_macosx_ver):    Function `make_darwin_gcv` utility or script
function.
L67: def gcv(var):    Function `gcv` utility or script function.
L74: def do_darwin_test(syscfg_macosx_ver, env_macosx_ver, expected_flag):    Function
`do_darwin_test` utility or script function.
L123: def gcv(v):    Function `gcv` utility or script function.
L129: def gcv(v):    Function `gcv` utility or script function.
L135: def gcv(v):    Function `gcv` utility or script function.
L146: def gcv(v):    Function `gcv` utility or script function.
L158: def gcv(v):    Function `gcv` utility or script function.
L173: def gcv(v):    Function `gcv` utility or script function.
L186: def gcv(v):    Function `gcv` utility or script function.
L201: def gcv(v):    Function `gcv` utility or script function.
L216: def gcv(v):    Function `gcv` utility or script function.
L226: def test_cc_overrides_ldshared(self):    Function `test_cc_overrides_ldshared` utility
or script function.
L229: def gcv(v):    Function `gcv` utility or script function.
L234: def gcvs(*args, _orig=sysconfig.get_config_vars):    Function `gcvs` utility or script
function.
L248: def test_cxx_commands_used_are_correct(self):    Function
`test_cxx_commands_used_are_correct` utility or script function.
L249: def gcv(v):    Function `gcv` utility or script function.
L260: def gcvs(*args, _orig=sysconfig.get_config_vars):    Function `gcvs` utility or script
function.
L312: def test_cc_overrides_ldshared_for_cxx_correctly(self):    Function
`test_cc_overrides_ldshared_for_cxx_correctly` utility or script function.
L320: def gcv(v):    Function `gcv` utility or script function.
L331: def gcvs(*args, _orig=sysconfig.get_config_vars):    Function `gcvs` utility or script
function.
L355: def test_explicit_ldshared(self):    Function `test_explicit_ldshared` utility or
script function.
L359: def gcv(v):    Function `gcv` utility or script function.
L364: def gcvs(*args, _orig=sysconfig.get_config_vars):    Function `gcvs` utility or script
function.
L377: def test_has_function(self):    Function `test_has_function` utility or script
function.
L385: def test_find_library_file(self, monkeypatch):    Function `test_find_library_file`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/comp

ilers/C/tests/test_base.py

```
L13: def c_file(tmp_path):    Function `c_file`    utility or script function.
L34: def test_set_include_dirs(c_file):    Function `test_set_include_dirs`    utility or script
function.
L49: def test_has_function_prototype():    Function `test_has_function_prototype`    utility or
script function.
L72: def test_include_dirs_after_multiple_compile_calls(c_file):    Function
`test_include_dirs_after_multiple_compile_calls`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compiler/ilers/C/tests/test_cygwin.py

```
L14: def stuff(request, monkeypatch, distutils_managed_tempdir):    Function `stuff`    utility
or script function.
L21: class TestCygwinCCompiler(support.TempdirManager):    Class (`TestCygwinCCompiler`)
component used by the app (see file context: None).
L22: def _get_config_h_filename(self):    Function `_get_config_h_filename`    utility or script
function.
L27: def test_find_library_file(self):    Function `test_find_library_file`    utility or script
function.
L38: def test_runtime_library_dir_option(self):    Function `test_runtime_library_dir_option`
utility or script function.
L44: def test_check_config_h(self):    Function `test_check_config_h`    utility or script
function.
L68: def test_get_msvcr(self):    Function `test_get_msvcr`    utility or script function.
L72: def test_dll_libraries_not_none(self):    Function `test_dll_libraries_not_none`    utility
or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compiler/ilers/C/tests/test_msvc.py

```
L17: class Testmsvccompiler(support.TempdirManager):    Class (`Testmsvccompiler`)    component
used by the app (see file context: None).
L18: def test_no_compiler(self, monkeypatch):    Function `test_no_compiler`    utility or
script function.
L22: def _find_vcvarsall(plat_spec):    Function `_find_vcvarsall`    utility or script
function.
L44: def test_cross_platform_compilation_paths(self, monkeypatch, plat_name, expected):
Function `test_cross_platform_compilation_paths`    utility or script function.
L50: def _get_vcvars_spec(host_platform, platform):    Function `_get_vcvars_spec`    utility or
```

```

script function.
L57: def test_get_vc_env_unicode(self):    Function `test_get_vc_env_unicode`    utility or
script function.
L75: def test_get_vc(self, ver):    Function `test_get_vc`    utility or script function.
L87: class CheckThread(threading.Thread):    Class (`CheckThread`)    component used by the app
(see file context: None).
L90: def run(self):    Function `run`    utility or script function.
L96: def __bool__(self):    Function `__bool__`    utility or script function.
L100: class TestSpawn:    Class (`TestSpawn`)    component used by the app (see file context:
None).
L101: def test_concurrent_safe(self):    Function `test_concurrent_safe`    utility or script
function.
L119: def test_concurrent_safe_fallback(self):    Function `test_concurrent_safe_fallback`
utility or script function.
L129: def CCompiler_spawn(self, cmd):    Function `CCompiler_spawn`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compilers/C/tests/test_mingw.py

```

L10: class TestMinGW32Compiler:    Class (`TestMinGW32Compiler`)    component used by the app
(see file context: None).
L12: def test_compiler_type(self):    Function `test_compiler_type`    utility or script
function.
L17: def test_set_executables(self, monkeypatch):    Function `test_set_executables`    utility
or script function.
L30: def test_runtime_library_dir_option(self):    Function `test_runtime_library_dir_option`
utility or script function.
L36: def test_cygwincc_error(self, monkeypatch):    Function `test_cygwincc_error`    utility or
script function.
L43: def test_customize_compiler_with_msvc_python(self):    Function
`test_customize_compiler_with_msvc_python`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/compiler/_init_.py

```

L9: def consolidate_linker_args(args: _IterableT) -> _IterableT | str:    Function
`consolidate_linker_args`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_distutils/comp at/py39.py

```
L7: def add_ext_suffix_39(vars):  Function `add_ext_suffix_39`  utility or script function.
L28: class UnequalIterablesError(ValueError):  Class (`UnequalIterablesError`)  component
used by the app (see file context: None).
L29: def __init__(self, details=None):  Function `__init__`  utility or script function.
L38: def _zip_equal_generator(iterables):  Function `_zip_equal_generator`  utility or
script function.
L48: def _zip_equal(*iterables):  Function `_zip_equal`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/insta ll.py

```
L21: def __getattr__(name: str):  # pragma: no cover  Function `__getattr__`  utility or
script function.
L32: class install(orig.install):  Class (`install`)  component used by the app (see file
context: None).
L57: def initialize_options(self):  Function `initialize_options`  Initialisation routine.
L73: def finalize_options(self) -> None:  Function `finalize_options`  utility or script
function.
L83: def handle_extra_path(self):  Function `handle_extra_path`  utility or script function.
L95: def _called_from_setup(run_frame):  Function `_called_from_setup`  utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/insta ll_egg_info.py

```
L11: class install_egg_info(namespaces.Installer, Command):  Class (`install_egg_info`)
component used by the app (see file context: None).
L20: def initialize_options(self):  Function `initialize_options`  Initialisation routine.
L23: def finalize_options(self) -> None:  Function `finalize_options`  utility or script
function.
L31: def run(self) -> None:  Function `run`  utility or script function.
L41: def get_outputs(self):  Function `get_outputs`  Returns or fetches data.
L44: def copytree(self) -> None:  Function `copytree`  utility or script function.
L46: def skimmer(src, dst):  Function `skimmer`  utility or script function.
```


Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build
.py**

```
L12: class build(_build):    Class (`build`)    component used by the app (see file context:
None).
L19: class SubCommand(Protocol):    Class (`SubCommand`)    component used by the app (see file
context: None).
L83: def finalize_options(self):    Function `finalize_options`    utility or script function.
L88: def initialize_options(self) -> None:    Function `initialize_options`    Initialisation
routine.
L92: def finalize_options(self) -> None:    Function `finalize_options`    utility or script
function.
L96: def run(self) -> None:    Function `run`    utility or script function.
L100: def get_source_files(self) -> list[str]:    Function `get_source_files`    Returns or
fetches data.
L112: def get_outputs(self) -> list[str]:    Function `get_outputs`    Returns or fetches data.
L126: def get_output_mapping(self) -> dict[str, str]:    Function `get_output_mapping`
Returns or fetches data.
```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/egg_
info.py**

```
L40: def translate_pattern(glob):    # noqa: C901    # is too complex (14)    # FIXME    Function
`translate_pattern`    utility or script function.
L123: class InfoCommon:    Class (`InfoCommon`)    component used by the app (see file context:
None).
L128: def name(self):    Function `name`    utility or script function.
L131: def tagged_version(self):    Function `tagged_version`    utility or script function.
L135: def _maybe_tag(self, version):    Function `_maybe_tag`    utility or script function.
L146: def _already_tagged(self, version: str) -> bool:    Function `_already_tagged`    utility
or script function.
L151: def _safe_tags(self) -> str:    Function `_safe_tags`    utility or script function.
L159: def tags(self) -> str:    Function `tags`    utility or script function.
L170: class egg_info(InfoCommon, Command):    Class (`egg_info`)    component used by the app
(see file context: None).
L190: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L201: def tag_svn_revision(self) -> int | None:    Function `tag_svn_revision`    utility or
script function.
L205: def tag_svn_revision(self, value) -> None:    Function `tag_svn_revision`    utility or
script function.
L210: def save_version_info(self, filename) -> None:    Function `save_version_info`    Saves
data to storage or remote.
L221: def finalize_options(self) -> None:    Function `finalize_options`    utility or script
```

```

function.
L253: def _get_egg_basename(self, py_version=PY_MAJOR, platform=None):    Function
`_get_egg_basename` utility or script function.
L257: def write_or_delete_file(self, what, filename, data, force: bool = False) -> None:
Function `write_or_delete_file` utility or script function.
L275: def write_file(self, what, filename, data) -> None:    Function `write_file` utility or
script function.
L287: def delete_file(self, filename) -> None:    Function `delete_file` Deletes a resource.
L292: def run(self) -> None:    Function `run` utility or script function.
L314: def find_sources(self) -> None:    Function `find_sources` utility or script function.
L324: class FileList(_FileList):    Class (`FileList`) component used by the app (see file
context: None).
L327: def __init__(    Function `__init__` utility or script function.
L333: def process_template_line(self, line) -> None:    Function `process_template_line`
utility or script function.
L403: def _remove_files(self, predicate):    Function `_remove_files` utility or script
function.
L416: def include(self, pattern):    Function `include` utility or script function.
L422: def exclude(self, pattern):    Function `exclude` utility or script function.
L427: def recursive_include(self, dir, pattern):    Function `recursive_include` utility or
script function.
L436: def recursive_exclude(self, dir, pattern):    Function `recursive_exclude` utility or
script function.
L443: def graft(self, dir):    Function `graft` utility or script function.
L453: def prune(self, dir):    Function `prune` utility or script function.
L458: def global_include(self, pattern):    Function `global_include` utility or script
function.
L470: def global_exclude(self, pattern):    Function `global_exclude` utility or script
function.
L477: def append(self, item) -> None:    Function `append` utility or script function.
L484: def extend(self, paths) -> None:    Function `extend` utility or script function.
L487: def _repair(self):    Function `_repair` utility or script function.
L497: def _safe_path(self, path):    Function `_safe_path` utility or script function.
L525: class manifest_maker(sdist):    Class (`manifest_maker`) component used by the app (see
file context: None).
L528: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
L535: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L538: def run(self) -> None:    Function `run` utility or script function.
L552: def _manifest_normalize(self, path):    Function `_manifest_normalize` utility or
script function.
L556: def write_manifest(self) -> None:    Function `write_manifest` utility or script
function.
L568: def warn(self, msg) -> None:    Function `warn` utility or script function.
L573: def _should_suppress_warning(msg):    Function `_should_suppress_warning` utility or
script function.
L579: def add_defaults(self) -> None:    Function `add_defaults` utility or script function.
L597: def add_license_files(self) -> None:    Function `add_license_files` utility or script
function.
L603: def _add_referenced_files(self):    Function `_add_referenced_files` utility or script

```

```

function.
L611: def _safe_data_files(self, build_py):    Function `_safe_data_files` utility or script
function.
L636: def write_file(filename, contents) -> None:    Function `write_file` utility or script
function.
L649: def write_pkg_info(cmd, basename, filename) -> None:    Function `write_pkg_info`
utility or script function.
L665: def warn_depends_obsolete(cmd, basename, filename) -> None:    Function
`warn_depends_obsolete` utility or script function.
L680: def write_toplevel_names(cmd, basename, filename) -> None:    Function
`write_toplevel_names` utility or script function.
L687: def overwrite_arg(cmd, basename, filename) -> None:    Function `overwrite_arg` utility
or script function.
L691: def write_arg(cmd, basename, filename, force: bool = False) -> None:    Function
`write_arg` utility or script function.
L699: def write_entries(cmd, basename, filename) -> None:    Function `write_entries` utility
or script function.
L705: def _egg_basename(egg_name, egg_version, py_version=None, platform=None):    Function
`_egg_basename` utility or script function.
L715: class EggInfoDeprecationWarning(SetuptoolsDeprecationWarning):    Class
(`EggInfoDeprecationWarning`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build _clib.py

```

L9: class build_clib(orig.build_clib):    Class (`build_clib`) component used by the app (see
file context: None).
L27: def build_libraries(self, libraries) -> None:    Function `build_libraries` Constructs
or prepares an object.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/insta ll_scripts.py

```

L13: class install_scripts(orig.install_scripts):    Class (`install_scripts`) component used
by the app (see file context: None).
L18: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
L22: def run(self) -> None:    Function `run` utility or script function.
L33: def _install_ep_scripts(self):    Function `_install_ep_scripts` utility or script
function.
L53: def write_script(self, script_name, contents, mode: str = "t", *ignored) -> None:
Function `write_script` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/saveopts.py

```
L4: class saveopts(option_base):    Class (`saveopts`) component used by the app (see file
context: None).
L9: def run(self) -> None:    Function `run` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/bdist_egg.py

```
L33: def _get_purelib():    Function `_get_purelib` utility or script function.
L37: def strip_module(filename):    Function `strip_module` utility or script function.
L44: def sorted_walk(    Function `sorted_walk` utility or script function.
L56: def write_stub(resource, pyfile) -> None:    Function `write_stub` utility or script
function.
L59: def __bootstrap__():    Function `__bootstrap__` utility or script function.
L74: class bdist_egg(Command):    Class (`bdist_egg`) component used by the app (see file
context: None).
L98: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L107: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L129: def do_install_data(self) -> None:    Function `do_install_data` utility or script
function.
L154: def get_outputs(self):    Function `get_outputs` Returns or fetches data.
L157: def call_command(self, cmdname, **kw):    Function `call_command` utility or script
function.
L166: def run(self) -> None:    # noqa: C901 # is too complex (14) # FIXME    Function `run`
utility or script function.
L246: def zap_pyfiles(self) -> None:    Function `zap_pyfiles` utility or script function.
L271: def zip_safe(self):    Function `zip_safe` utility or script function.
L278: def gen_header(self) -> Literal["w"]:    Function `gen_header` utility or script
function.
L281: def copy_metadata_to(self, target_dir) -> None:    Function `copy_metadata_to` utility
or script function.
L293: def get_ext_outputs(self):    Function `get_ext_outputs` Returns or fetches data.
L326: def walk_egg(egg_dir: StrPath) -> Iterator[tuple[str, list[str], list[str]]]:
Function `walk_egg` utility or script function.
L336: def analyze_egg(egg_dir, stubs):    Function `analyze_egg` utility or script function.
L354: def write_safety_flag(egg_dir, safe) -> None:    Function `write_safety_flag` utility
or script function.
L372: def scan_module(egg_dir, base, name, stubs):    Function `scan_module` utility or
script function.
L412: def iter_symbols(code: CodeType) -> Iterator[str]:    Function `iter_symbols` utility
```

```

or script function.
L422: def can_scan() -> bool:    Function `can_scan`    utility or script function.
L440: def make_zipfile(    Function `make_zipfile`    utility or script function.
L458: def visit(z, dirname, names):    Function `visit`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/alias.py

```

L6: def shquote(arg):    Function `shquote`    utility or script function.
L16: class alias(option_base):    Class (`alias`)    component used by the app (see file
context: None).
L28: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L33: def finalize_options(self) -> None:    Function `finalize_options`    utility or script
function.
L40: def run(self) -> None:    Function `run`    utility or script function.
L67: def format_alias(name, aliases):    Function `format_alias`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/install_lib.py

```

L13: class install_lib(orig.install_lib):    Class (`install_lib`)    component used by the app
(see file context: None).
L18: def run(self) -> None:    Function `run`    utility or script function.
L25: def get_exclusions(self):    Function `get_exclusions`    Returns or fetches data.
L39: def _exclude_pkg_path(self, pkg, exclusion_path):    Function `_exclude_pkg_path`
utility or script function.
L48: def _all_packages(pkg_name):    Function `_all_packages`    utility or script function.
L57: def _get_SVEM_NSps(self):    Function `_get_SVEM_NSps`    utility or script function.
L74: def _gen_exclusion_paths():    Function `_gen_exclusion_paths`    utility or script
function.
L94: def copy_tree(    Function `copy_tree`    utility or script function.
L120: def pf(src: str, dst: str):    Function `pf`    utility or script function.
L132: def get_outputs(self):    Function `get_outputs`    Returns or fetches data.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build_py.py

```

L28: def make_writable(target) -> None:    Function `make_writable` utility or script
function.
L32: class build_py(orig.build_py):    Class (`build_py`) component used by the app (see file
context: None).
L46: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L53: def copy_file( # type: ignore[override] # No overload, no bytes support    Function
`copy_file` utility or script function.
L70: def run(self) -> None:    Function `run` utility or script function.
L87: def __getattr__(self, attr: str) -> Any:    Function `__getattr__` utility or script
function.
L94: def _get_data_files(self):    Function `_get_data_files` utility or script function.
L99: def get_data_files_without_manifest(self) -> list[tuple[str, str, str, list[str]]]:
Function `get_data_files_without_manifest` Returns or fetches data.
L109: def _get_pkg_data_files(self, package: str) -> tuple[str, str, str, list[str]]:
Function `_get_pkg_data_files` utility or script function.
L123: def find_data_files(self, package, src_dir):    Function `find_data_files` utility or
script function.
L141: def get_outputs(self, include_bytecode: bool = True) -> list[str]: # type:
ignore[override] # Using a real boolean instead of 0|1    Function `get_outputs` Returns or
fetches data.
L147: def get_output_mapping(self) -> dict[str, str]:    Function `get_output_mapping`
Returns or fetches data.
L155: def _get_module_mapping(self) -> Iterator[tuple[str, str]]:    Function
`_get_module_mapping` utility or script function.
L162: def _get_package_data_output_mapping(self) -> Iterator[tuple[str, str]]:    Function
`_get_package_data_output_mapping` utility or script function.
L170: def build_package_data(self) -> None:    Function `build_package_data` Constructs or
prepares an object.
L177: def analyze_manifest(self) -> None:    Function `analyze_manifest` utility or script
function.
L218: def _filter_build_files(    Function `_filter_build_files` utility or script function.
L239: def get_data_files(self) -> None:    Function `get_data_files` Returns or fetches data.
L242: def check_package(self, package, package_dir):    Function `check_package` utility or
script function.
L272: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L278: def get_package_dir(self, package: str) -> str:    Function `get_package_dir` Returns
or fetches data.
L284: def exclude_data_files(self, package, src_dir, files):    Function `exclude_data_files`
utility or script function.
L301: def _get_platform_patterns(spec, package, src_dir, extra_patterns=()):    Function
`_get_platform_patterns` utility or script function.
L320: def assert_relative(path):    Function `assert_relative` utility or script function.
L341: class _IncludePackageDataAbuse:    Class (`_IncludePackageDataAbuse`) component used by
the app (see file context: None).
L344: class _Warning(SetupToolsDeprecationWarning):    Class (`_Warning`) component used by
the app (see file context: None).
L387: def __init__(self) -> None:    Function `__init__` utility or script function.
L390: def is_module(self, file):    Function `is_module` utility or script function.
L393: def importable_subpackage(self, parent, file):    Function `importable_subpackage`
utility or script function.

```

```
L400: def warn(self, importable):    Function `warn`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/editable_wheel.py

```
L53: class _EditableMode(Enum):    Class (`_EditableMode`)    component used by the app (see
file context: None).
L66: def convert(cls, mode: str | None) -> _EditableMode:    Function `convert`    utility or
script function.
L104: class editable_wheel(Command):    Class (`editable_wheel`)    component used by the app
(see file context: None).
L118: def initialize_options(self):    Function `initialize_options`    Initialisation routine.
L124: def finalize_options(self) -> None:    Function `finalize_options`    utility or script
function.
L130: def run(self) -> None:    Function `run`    utility or script function.
L151: def _ensure_dist_info(self):    Function `_ensure_dist_info`    utility or script
function.
L162: def _install_namespaces(self, installation_dir, pth_prefix):    Function
`_install_namespaces`    utility or script function.
L172: def _find_egg_info_dir(self) -> str | None:    Function `_find_egg_info_dir`    utility or
script function.
L177: def _configure_build(    Function `_configure_build`    utility or script function.
L240: def _set_editable_mode(self):    Function `_set_editable_mode`    utility or script
function.
L251: def _collect_build_outputs(self) -> tuple[list[str], dict[str, str]]:    Function
`_collect_build_outputs`    utility or script function.
L265: def _run_build_commands(    Function `_run_build_commands`    utility or script function.
L280: def _run_build_subcommands(self) -> None:    Function `_run_build_subcommands`    utility
or script function.
L302: def _safely_run(self, cmd_name: str):    Function `_safely_run`    utility or script
function.
L330: def _create_wheel_file(self, bdist_wheel):    Function `_create_wheel_file`    utility or
script function.
L358: def _run_install(self, category: str):    Function `_run_install`    utility or script
function.
L364: def _select_strategy(    Function `_select_strategy`    utility or script function.
L391: class EditableStrategy(Protocol):    Class (`EditableStrategy`)    component used by the
app (see file context: None).
L392: def __call__(    Function `__call__`    utility or script function.
L395: def __enter__(self) -> Self: ...    Function `__enter__`    utility or script function.
L396: def __exit__(    Function `__exit__`    utility or script function.
L404: class _StaticPth:    Class (`_StaticPth`)    component used by the app (see file context:
None).
L405: def __init__(self, dist: Distribution, name: str, path_entries: list[Path]) -> None:
Function `__init__`    utility or script function.
L410: def __call__(    Function `__call__`    utility or script function.
```

```

L417: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L425: def __exit__(    Function `__exit__`    utility or script function.
L434: class _LinkTree(_StaticPth):    Class (`_LinkTree`)    component used by the app (see file
context: None).
L445: def __init__(    Function `__init__`    utility or script function.
L457: def __call__(    Function `__call__`    utility or script function.
L463: def _normalize_output(self, file: str) -> str | None:    Function `_normalize_output`
utility or script function.
L470: def _create_file(self, relative_output: str, src_file: str, link=None):    Function
`_create_file`    utility or script function.
L476: def _create_links(self, outputs, output_mapping: Mapping[str, str]):    Function
`_create_links`    utility or script function.
L491: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L496: def __exit__(    Function `__exit__`    utility or script function.
L512: class _TopLevelFinder:    Class (`_TopLevelFinder`)    component used by the app (see file
context: None).
L513: def __init__(self, dist: Distribution, name: str) -> None:    Function `__init__`
utility or script function.
L517: def template_vars(self) -> tuple[str, str, dict[str, str], dict[str, list[str]]]:
Function `template_vars`    utility or script function.
L544: def get_implementation(self) -> Iterator[tuple[str, bytes]]:    Function
`get_implementation`    Returns or fetches data.
L553: def __call__(    Function `__call__`    utility or script function.
L559: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L564: def __exit__(    Function `__exit__`    utility or script function.
L577: def _encode_pth(content: str) -> bytes:    Function `_encode_pth`    utility or script
function.
L598: def _can_symlink_files(base_dir: Path) -> bool:    Function `_can_symlink_files`
utility or script function.
L618: def _simple_layout(    Function `_simple_layout`    utility or script function.
L659: def _parent_path(pkg, pkg_path):    Function `_parent_path`    utility or script function.
L673: def _find_packages(dist: Distribution) -> Iterator[str]:    Function `_find_packages`
utility or script function.
L689: def _find_top_level_modules(dist: Distribution) -> Iterator[str]:    Function
`_find_top_level_modules`    utility or script function.
L698: def _find_package_roots(    Function `_find_package_roots`    utility or script function.
L711: def _absolute_root(path: StrPath) -> str:    Function `_absolute_root`    utility or
script function.
L722: def _find_virtual_namespaces(pkg_roots: dict[str, str]) -> Iterator[str]:    Function
`_find_virtual_namespaces`    utility or script function.
L746: def _find_namespaces(    Function `_find_namespaces`    utility or script function.
L755: def _remove_nested(pkg_roots: dict[str, str]) -> dict[str, str]:    Function
`_remove_nested`    utility or script function.
L768: def _is_nested(pkg: str, pkg_path: str, parent: str, parent_path: str) -> bool:
Function `_is_nested`    utility or script function.
L790: def _empty_dir(dir_: _P) -> _P:    Function `_empty_dir`    utility or script function.
L797: class _NamespaceInstaller(namespaces.Installer):    Class (`_NamespaceInstaller`)
component used by the app (see file context: None).
L798: def __init__(self, distribution, installation_dir, editable_name, src_root) -> None:
Function `__init__`    utility or script function.
L805: def _get_nspkg_file(self):    Function `_get_nspkg_file`    utility or script function.

```



```

L809: def _get_root(self):    Function `_get_root` utility or script function.
L828: class _EditableFinder: # MetaPathFinder    Class (`_EditableFinder`) component used by
the app (see file context: None).
L830: def find_spec(cls, fullname: str, path=None, target=None) -> ModuleSpec | None: #
type: ignore    Function `find_spec` utility or script function.
L848: def _find_spec(cls, fullname: str, candidate_path: Path) -> ModuleSpec | None:
Function `_find_spec` utility or script function.
L857: class _EditableNamespaceFinder: # PathEntryFinder    Class (`_EditableNamespaceFinder`)
component used by the app (see file context: None).
L859: def _path_hook(cls, path) -> type[_EditableNamespaceFinder]:    Function `_path_hook`
utility or script function.
L865: def _paths(cls, fullname: str) -> list[str]:    Function `_paths` utility or script
function.
L876: def find_spec(cls, fullname: str, target=None) -> ModuleSpec | None: # type: ignore
Function `find_spec` utility or script function.
L884: def find_module(cls, _fullname) -> None:    Function `find_module` utility or script
function.
L888: def install():    Function `install` utility or script function.
L903: def _finder_template(    Function `_finder_template` utility or script function.
L913: class LinksNotSupported(errors.FileError):    Class (`LinksNotSupported`) component
used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/dist_info.py

```

L20: class dist_info(Command):    Class (`dist_info`) component used by the app (see file
context: None).
L44: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L52: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L79: def _maybe_bkp_dir(self, dir_path: str, requires_bkp: bool):    Function `_maybe_bkp_dir`
utility or script function.
L92: def run(self) -> None:    Function `run` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/sdist.py

```

L20: def walk_revctrl(dirname='') -> Iterator:    Function `walk_revctrl` utility or script
function.
L26: class sdist(orig.sdist):    Class (`sdist`) component used by the app (see file context:
None).
L59: def run(self) -> None:    Function `run` utility or script function.

```

```

L78: def initialize_options(self) -> None:    Function `initialize_options`  Initialisation
routine.
L81: def make_distribution(self) -> None:    Function `make_distribution`  utility or script
function.
L90: def _remove_os_link():    Function `_remove_os_link`  utility or script function.
L95: class NoValue:    Class (`NoValue`)  component used by the app (see file context: None).
L109: def add_defaults(self) -> None:    Function `add_defaults`  utility or script function.
L113: def _add_defaults_optional(self):    Function `_add_defaults_optional`  utility or
script function.
L118: def _add_defaults_python(self):    Function `_add_defaults_python`  utility or script
function.
L125: def _add_defaults_build_sub_commands(self):    Function
`_add_defaults_build_sub_commands`  utility or script function.
L133: def _safe_data_files(self, build_py):    Function `_safe_data_files`  utility or script
function.
L146: def _add_data_files(self, data_files):    Function `_add_data_files`  utility or script
function.
L156: def _add_defaults_data_files(self):    Function `_add_defaults_data_files`  utility or
script function.
L162: def prune_file_list(self) -> None:    Function `prune_file_list`  utility or script
function.
L168: def check_readme(self) -> None:    Function `check_readme`  utility or script function.
L177: def make_release_tree(self, base_dir, files) -> None:    Function `make_release_tree`
utility or script function.
L190: def _manifest_is_not_generated(self):    Function `_manifest_is_not_generated`  utility
or script function.
L199: def read_manifest(self) -> None:    Function `read_manifest`  utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/setopt.py

```

L15: def config_file(kind="local"):    Function `config_file`  utility or script function.
L30: def edit_config(filename, settings) -> None:    Function `edit_config`  utility or script
function.
L71: class option_base(Command):    Class (`option_base`)  component used by the app (see file
context: None).
L85: def initialize_options(self):    Function `initialize_options`  Initialisation routine.
L90: def finalize_options(self) -> None:    Function `finalize_options`  utility or script
function.
L107: class setopt(option_base):    Class (`setopt`)  component used by the app (see file
context: None).
L121: def initialize_options(self):    Function `initialize_options`  Initialisation routine.
L128: def finalize_options(self) -> None:    Function `finalize_options`  utility or script
function.
L135: def run(self) -> None:    Function `run`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/_req uirestxt.py

```

L29: def _prepare(    Function `_prepare` utility or script function.
L39: def _convert_extras_requirements(    Function `_convert_extras_requirements` utility or
script function.
L57: def _move_install_requirements_markers(    Function `_move_install_requirements_markers`
utility or script function.
L89: def _suffix_for(req):    Function `_suffix_for` utility or script function.
L94: def _clean_req(req):    Function `_clean_req` utility or script function.
L101: def _no_marker(req):    Function `_no_marker` utility or script function.
L105: def _write_requirements(stream, reqs):    Function `_write_requirements` utility or
script function.
L108: def append_cr(line):    Function `_append_cr` utility or script function.
L115: def write_requirements(cmd, basename, filename):    Function `write_requirements`
utility or script function.
L128: def write_setup_requirements(cmd, basename, filename):    Function
`write_setup_requirements` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/build _ext.py

```

L43: def _customize_compiler_for_shlib(compiler):    Function `_customize_compiler_for_shlib`
utility or script function.
L79: def get_abi3_suffix():    Function `get_abi3_suffix` Returns or fetches data.
L89: class build_ext(_build_ext):    Class (`build_ext`) component used by the app (see file
context: None).
L94: def run(self) -> None:    Function `run` utility or script function.
L102: def _get_inplace_equivalent(self, build_py, ext: Extension) -> tuple[str, str]:
Function `_get_inplace_equivalent` utility or script function.
L112: def copy_extensions_to_source(self) -> None:    Function `copy_extensions_to_source`
utility or script function.
L129: def _get_equivalent_stub(self, ext: Extension, output_file: str) -> str:    Function
`_get_equivalent_stub` utility or script function.
L134: def _get_output_mapping(self) -> Iterator[tuple[str, str]]:    Function
`_get_output_mapping` utility or script function.
L159: def get_ext_filename(self, fullname: str) -> str:    Function `get_ext_filename`
Returns or fetches data.
L186: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L193: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L224: def setup_shlib_compiler(self) -> None:    Function `setup_shlib_compiler` Sets or
updates a value.

```

```

L251: def get_export_symbols(self, ext):    Function `get_export_symbols` Returns or fetches
data.
L256: def build_extension(self, ext) -> None:    Function `build_extension` Constructs or
prepares an object.
L269: def links_to_dynamic(self, ext):    Function `links_to_dynamic` utility or script
function.
L278: def get_source_files(self) -> list[str]:    Function `get_source_files` Returns or
fetches data.
L281: def _get_internal_depends(self) -> Iterator[str]:    Function `_get_internal_depends`
utility or script function.
L286: def skip(orig_path: str, reason: str) -> None:    Function `skip` utility or script
function.
L319: def get_outputs(self) -> list[str]:    Function `get_outputs` Returns or fetches data.
L324: def get_output_mapping(self) -> dict[str, str]:    Function `get_output_mapping`
Returns or fetches data.
L329: def __get_stubs_outputs(self):    Function `__get_stubs_outputs` utility or script
function.
L340: def __get_output_extensions(self):    Function `__get_output_extensions` utility or
script function.
L346: def write_stub(self, output_dir, ext, compile=False) -> None:    Function `write_stub`
utility or script function.
L350: def _write_stub_file(self, stub_file: str, ext: Extension, compile=False):    Function
`_write_stub_file` utility or script function.
L358: def __bootstrap__():    Function `__bootstrap__` utility or script function.
L388: def _compile_and_remove_stub(self, stub_file: str):    Function
`_compile_and_remove_stub` utility or script function.
L406: def link_shared_object(    Function `link_shared_object` utility or script function.
L441: def link_shared_object(    Function `link_shared_object` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/rotate
e.py**

```

L13: class rotate(Command):    Class (`rotate`) component used by the app (see file context:
None).
L25: def initialize_options(self):    Function `initialize_options` Initialisation routine.
L30: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L46: def run(self) -> None:    Function `run` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/command/devel
op.py**

```

L10: class develop(Command):    Class (`develop`) component used by the app (see file
context: None).
L31: def run(self) -> None:    Function `run` utility or script function.
L44: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
L47: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L51: class DevelopDeprecationWarning(SetuptoolsDeprecationWarning):    Class
(`DevelopDeprecationWarning`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/bdist _wheel.py

```

L34: def safe_version(version: str) -> str:    Function `safe_version` utility or script
function.
L51: def _is_32bit_interpreter() -> bool:    Function `_is_32bit_interpreter` utility or
script function.
L55: def python_tag() -> str:    Function `python_tag` utility or script function.
L59: def get_platform(archive_root: str | None) -> str:    Function `get_platform` Returns or
fetches data.
L79: def get_flag(    Function `get_flag` Returns or fetches data.
L96: def get_abi_tag() -> str | None:    Function `get_abi_tag` Returns or fetches data.
L131: def safer_version(version: str) -> str:    Function `safer_version` utility or script
function.
L135: class bdist_wheel(Command):    Class (`bdist_wheel`) component used by the app (see
file context: None).
L208: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
L230: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
L277: def _validate_py_limited_api(self) -> None:    Function `_validate_py_limited_api`
utility or script function.
L293: def wheel_dist_name(self) -> str:    Function `wheel_dist_name` utility or script
function.
L303: def get_tag(self) -> tuple[str, str, str]:    Function `get_tag` Returns or fetches
data.
L361: def run(self):    Function `run` utility or script function.
L454: def write_wheelfile(    Function `write_wheelfile` utility or script function.
L478: def _ensure_relative(self, path: str) -> str:    Function `_ensure_relative` utility or
script function.
L486: def license_paths(self) -> Iterable[str]:    Function `license_paths` utility or script
function.
L530: def egg2dist(self, egginfo_path: str, distinfo_path: str) -> None:    Function
`egg2dist` utility or script function.
L533: def adios(p: str) -> None:    Function `adios` utility or script function.
L592: def _zip_compression(self) -> int:    Function `_zip_compression` utility or script

```

```
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/easy_install.py

```
L10: class easy_install(Command):    Class (`easy_install`) component used by the app (see
file context: None).
```

```
L14: def __getattr__(name):    Function `__getattr__` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/test.py

```
L10: def __getattr__(name: str) -> type[_test]:    Function `__getattr__` utility or script
function.
```

```
L23: class _test(Command):    Class (`_test`) component used by the app (see file context:
None).
```

```
L40: def initialize_options(self) -> None:    Function `initialize_options` Initialisation
routine.
```

```
L43: def finalize_options(self) -> None:    Function `finalize_options` utility or script
function.
```

```
L46: def run(self) -> NoReturn:    Function `run` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/command/bdist_rpm.py

```
L7: class bdist_rpm(orig.bdist_rpm):    Class (`bdist_rpm`) component used by the app (see
file context: None).
```

```
L18: def run(self) -> None:    Function `run` utility or script function.
```

```
L34: def _make_spec_file(self):    Function `_make_spec_file` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/expand.py

```

L53: class StaticModule:    Dependency injection module (`StaticModule`) provides DI
bindings.
L56: def __init__(self, name: str, spec: ModuleSpec) -> None:    Function `__init__` utility
or script function.
L61: def _find_assignments(self) -> Iterator[tuple[ast.AST, ast.AST]]:    Function
`_find_assignments` utility or script function.
L68: def __getattr__(self, attr: str) -> Any:    Function `__getattr__` utility or script
function.
L80: def glob_relative(    Function `glob_relative` utility or script function.
L113: def read_files(    Function `read_files` utility or script function.
L133: def _filter_existing_files(filepaths: Iterable[StrPath]) -> Iterator[StrPath]:
Function `_filter_existing_files` utility or script function.
L141: def _read_file(filepath: bytes | StrPath) -> str:    Function `_read_file` utility or
script function.
L146: def _assert_local(filepath: StrPath, root_dir: str):    Function `_assert_local`
utility or script function.
L154: def read_attr(    Function `read_attr` utility or script function.
L194: def _find_spec(module_name: str, module_path: StrPath | None) -> ModuleSpec:    Function
`_find_spec` utility or script function.
L204: def _load_spec(spec: ModuleSpec, module_name: str) -> ModuleType:    Function
`_load_spec` utility or script function.
L215: def _find_module(    Function `_find_module` utility or script function.
L238: def resolve_class(    Function `resolve_class` utility or script function.
L254: def cmdclass(    Function `cmdclass` utility or script function.
L265: def find_packages(    Function `find_packages` utility or script function.
L320: def _nest_path(parent: StrPath, path: StrPath) -> str:    Function `_nest_path` utility
or script function.
L325: def version(value: Callable | Iterable[str | int] | str) -> str:    Function `version`
utility or script function.
L338: def canonic_package_data(package_data: dict) -> dict:    Function `canonic_package_data`
utility or script function.
L344: def canonic_data_files(    Function `canonic_data_files` utility or script function.
L361: def entry_points(    Function `entry_points` utility or script function.
L379: class EnsurePackagesDiscovered:    Class (`EnsurePackagesDiscovered`) component used by
the app (see file context: None).
L389: def __init__(self, distribution: Distribution) -> None:    Function `__init__` utility
or script function.
L393: def __call__(self) -> None:    Function `__call__` utility or script function.
L399: def __enter__(self) -> Self:    Function `__enter__` utility or script function.
L402: def __exit__(    Function `__exit__` utility or script function.
L411: def _get_package_dir(self) -> Mapping[str, str]:    Function `_get_package_dir` utility
or script function.
L417: def package_dir(self) -> Mapping[str, str]:    Function `package_dir` utility or script
function.
L422: class LazyMappingProxy(Mapping[_K, _V_co]):    Class (`LazyMappingProxy`) component
used by the app (see file context: None).
L436: def __init__(self, obtain_mapping_value: Callable[[], Mapping[_K, _V_co]]) -> None:
Function `__init__` utility or script function.
L440: def _target(self) -> Mapping[_K, _V_co]:    Function `_target` utility or script
function.
L445: def __getitem__(self, key: _K) -> _V_co:    Function `__getitem__` utility or script

```

```
function.
L448: def __len__(self) -> int:    Function `__len__`    utility or script function.
L451: def __iter__(self) -> Iterator[_K]:    Function `__iter__`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/pyproject.toml.py

```
L36: def load_file(filepath: StrPath) -> dict:    Function `load_file`    Loads data from
storage or remote.
L43: def validate(config: dict, filepath: StrPath) -> bool:    Function `validate`    utility or
script function.
L64: def apply_configuration(    Function `apply_configuration`    utility or script function.
L76: def read_configuration(    Function `read_configuration`    utility or script function.
L158: def expand_configuration(    Function `expand_configuration`    utility or script
function.
L181: class _ConfigExpander:    Class (`_ConfigExpander`)    component used by the app (see file
context: None).
L182: def __init__(    Function `__init__`    utility or script function.
L199: def _ensure_dist(self) -> Distribution:    Function `_ensure_dist`    utility or script
function.
L205: def _process_field(self, container: dict, field: str, fn: Callable):    Function
`_process_field`    utility or script function.
L210: def _canonic_package_data(self, field="package-data"):    Function
`_canonic_package_data`    utility or script function.
L214: def expand(self):    Function `expand`    utility or script function.
L231: def _expand_packages(self):    Function `_expand_packages`    utility or script function.
L243: def _expand_data_files(self):    Function `_expand_data_files`    utility or script
function.
L247: def _expand_cmdclass(self, package_dir: Mapping[str, str]):    Function
`_expand_cmdclass`    utility or script function.
L252: def _expand_all_dynamic(self, dist: Distribution, package_dir: Mapping[str, str]):
Function `_expand_all_dynamic`    utility or script function.
L282: def _ensure_previously_set(self, dist: Distribution, field: str):    Function
`_ensure_previously_set`    utility or script function.
L292: def _expand_directive(    Function `_expand_directive`    utility or script function.
L307: def _obtain(self, dist: Distribution, field: str, package_dir: Mapping[str, str]):
Function `_obtain`    utility or script function.
L317: def _obtain_version(self, dist: Distribution, package_dir: Mapping[str, str]):
Function `_obtain_version`    utility or script function.
L326: def _obtain_readme(self, dist: Distribution) -> dict[str, str] | None:    Function
`_obtain_readme`    utility or script function.
L341: def _obtain_entry_points(    Function `_obtain_entry_points`    utility or script
function.
L356: def _set_scripts(field: str, group: str):    Function `_set_scripts`    utility or script
function.
L368: def _obtain_classifiers(self, dist: Distribution):    Function `_obtain_classifiers`
```



```

utility or script function.
L375: def _obtain_dependencies(self, dist: Distribution):    Function `_obtain_dependencies`
utility or script function.
L382: def _obtain_optional_dependencies(self, dist: Distribution):    Function
`_obtain_optional_dependencies` utility or script function.
L402: def _parse_requirements_list(value):    Function `_parse_requirements_list` utility or
script function.
L411: def _ignore_errors(ignore_option_errors: bool):    Function `_ignore_errors` utility or
script function.
L422: class _EnsurePackagesDiscovered(_expand.EnsurePackagesDiscovered):    Class
(`_EnsurePackagesDiscovered`) component used by the app (see file context: None).
L423: def __init__(    Function `__init__` utility or script function.
L430: def __enter__(self) -> Self:    Function `__enter__` utility or script function.
L452: def __exit__(    Function `__exit__` utility or script function.
L467: class _ExperimentalConfiguration(SetuptoolsWarning):    Class
(`_ExperimentalConfiguration`) component used by the app (see file context: None).
L474: class _ToolsTypoInMetadata(SetuptoolsWarning):    Class (`_ToolsTypoInMetadata`)
component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/setupcfg
.py

```

L51: def read_configuration(    Function `read_configuration` utility or script function.
L77: def apply_configuration(dist: Distribution, filepath: StrPath) -> Distribution:
Function `apply_configuration` utility or script function.
L86: def _apply(    Function `_apply` utility or script function.
L117: def _get_option(target_obj: Distribution | DistributionMetadata, key: str):    Function
`_get_option` utility or script function.
L129: def configuration_to_dict(    Function `configuration_to_dict` utility or script
function.
L151: def parse_configuration(    Function `parse_configuration` utility or script function.
L197: def _warn_accidental_env_marker_misconfig(label: str, orig_value: str, parsed: list):
Function `_warn_accidental_env_marker_misconfig` utility or script function.
L229: class ConfigHandler(Generic[Target]):    Class (`ConfigHandler`) component used by the
app (see file context: None).
L245: def __init__(    Function `__init__` utility or script function.
L263: def _section_options(    Function `_section_options` utility or script function.
L274: def parsers(self) -> dict[str, Callable]:    Function `parsers` utility or script
function.
L280: def __setitem__(self, option_name, value) -> None:    Function `__setitem__` utility or
script function.
L307: def _parse_list(cls, value, separator=','):    Function `_parse_list` utility or script
function.
L327: def _parse_dict(cls, value):    Function `_parse_dict` utility or script function.
L344: def _parse_bool(cls, value):    Function `_parse_bool` utility or script function.
L354: def _exclude_files_parser(cls, key):    Function `_exclude_files_parser` utility or

```

```

script function.
L365: def parser(value):    Function `parser`    utility or script function.
L376: def _parse_file(self, value, root_dir: StrPath | None):    Function `_parse_file`
utility or script function.
L403: def _parse_attr(self, value, package_dir, root_dir: StrPath):    Function `_parse_attr`
utility or script function.
L424: def _get_parser_compound(cls, *parse_methods):    Function `_get_parser_compound`
utility or script function.
L433: def parse(value):    Function `parse`    utility or script function.
L444: def _parse_section_to_dict_with_key(cls, section_options, values_parser):    Function
`_parse_section_to_dict_with_key`    utility or script function.
L459: def _parse_section_to_dict(cls, section_options, values_parser=None):    Function
`_parse_section_to_dict`    utility or script function.
L471: def parse_section(self, section_options) -> None:    Function `parse_section`    utility
or script function.
L481: def parse(self) -> None:    Function `parse`    utility or script function.
L506: def _deprecated_config_handler(self, func, msg, **kw):    Function
`_deprecated_config_handler`    utility or script function.
L514: def config_handler(*args, **kwargs):    Function `config_handler`    utility or script
function.
L522: class ConfigMetadataHandler(ConfigHandler["DistributionMetadata"]):    Class
(`ConfigMetadataHandler`)    component used by the app (see file context: None).
L538: def __init__(    Function `__init__`    utility or script function.
L552: def parsers(self) -> dict[str, Callable]:    Function `parsers`    utility or script
function.
L579: def _parse_version(self, value):    Function `_parse_version`    utility or script
function.
L605: class ConfigOptionsHandler(ConfigHandler["Distribution"]):    Class
(`ConfigOptionsHandler`)    component used by the app (see file context: None).
L608: def __init__(    Function `__init__`    utility or script function.
L620: def _parse_list_semicolon(cls, value):    Function `_parse_list_semicolon`    utility or
script function.
L623: def _parse_file_in_root(self, value):    Function `_parse_file_in_root`    utility or
script function.
L626: def _parse_requirements_list(self, label: str, value: str):    Function
`_parse_requirements_list`    utility or script function.
L636: def parsers(self) -> dict[str, Callable]:    Function `parsers`    utility or script
function.
L666: def _parse_cmdclass(self, value):    Function `_parse_cmdclass`    utility or script
function.
L670: def _parse_packages(self, value):    Function `_parse_packages`    utility or script
function.
L695: def parse_section_packages__find(self, section_options):    Function
`parse_section_packages__find`    utility or script function.
L713: def parse_section_entry_points(self, section_options) -> None:    Function
`parse_section_entry_points`    utility or script function.
L721: def _parse_package_data(self, section_options):    Function `_parse_package_data`
utility or script function.
L725: def parse_section_package_data(self, section_options) -> None:    Function
`parse_section_package_data`    utility or script function.
L732: def parse_section_exclude_package_data(self, section_options) -> None:    Function

```

```

`parse_section_exclude_package_data` utility or script function.
L739: def parse_section_extras_require(self, section_options) -> None: # Core Metadata
Function `parse_section_extras_require` utility or script function.
L752: def parse_section_data_files(self, section_options) -> None: Function
`parse_section_data_files` utility or script function.
L761: class _AmbiguousMarker(SetuptoolsDeprecationWarning): Class (`_AmbiguousMarker`)
component used by the app (see file context: None).
L776: def message(cls, **kw): Function `message` utility or script function.
L781: class _DeprecatedConfig(SetuptoolsDeprecationWarning): Class (`_DeprecatedConfig`)
component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_apply_pyprojecttoml.py

```

L46: def apply(dist: Distribution, config: dict, filename: StrPath) -> Distribution:
Function `apply` utility or script function.
L69: def _apply_project_table(dist: Distribution, config: dict, root_dir: StrPath):
Function `_apply_project_table` utility or script function.
L87: def _apply_tool_table(dist: Distribution, config: dict, filename: StrPath): Function
`_apply_tool_table` utility or script function.
L129: def _handle_missing_dynamic(dist: Distribution, project_table: dict): Function
`_handle_missing_dynamic` utility or script function.
L140: def json_compatible_key(key: str) -> str: Function `json_compatible_key` utility or
script function.
L145: def _set_config(dist: Distribution, field: str, value: Any): Function `_set_config`
utility or script function.
L163: def _guess_content_type(file: str) -> str | None: Function `_guess_content_type`
utility or script function.
L176: def _long_description( Function `_long_description` utility or script function.
L201: def _license(dist: Distribution, val: str | dict, root_dir: StrPath | None): Function
`_license` utility or script function.
L228: def _people(dist: Distribution, val: list[dict], _root_dir: StrPath | None, kind: str):
Function `_people` utility or script function.
L246: def _project_urls(dist: Distribution, val: dict, _root_dir: StrPath | None): Function
`_project_urls` utility or script function.
L250: def _python_requires(dist: Distribution, val: str, _root_dir: StrPath | None):
Function `_python_requires` utility or script function.
L254: def _dependencies(dist: Distribution, val: list, _root_dir: StrPath | None): Function
`_dependencies` utility or script function.
L261: def _optional_dependencies(dist: Distribution, val: dict, _root_dir: StrPath | None):
Function `_optional_dependencies` utility or script function.
L268: def _ext_modules(dist: Distribution, val: list[dict]) -> list[Extension]: Function
`_ext_modules` utility or script function.
L275: def _adjust_ext_attrs(attrs: dict) -> dict: Function `_adjust_ext_attrs` utility or
script function.
L283: def _noop(_dist: Distribution, val: _T) -> _T: Function `_noop` utility or script

```

```

function.
L287: def _identity(val: _T) -> _T:    Function `_identity` utility or script function.
L291: def _unify_entry_points(project_table: dict):    Function `_unify_entry_points` utility
or script function.
L312: def _copy_command_options(pyproject: dict, dist: Distribution, filename: StrPath):
Function `_copy_command_options` utility or script function.
L331: def _valid_command_options(cmdclass: Mapping = EMPTY) -> dict[str, set[str]]:
Function `_valid_command_options` utility or script function.
L349: def _load_ep(ep: metadata.EntryPoint) -> tuple[str, type] | None:    Function `_load_ep`
utility or script function.
L364: def _normalise_cmd_option_key(name: str) -> str:    Function `_normalise_cmd_option_key`
utility or script function.
L368: def _normalise_cmd_options(desc: _OptionsList) -> set[str]:    Function
`_normalise_cmd_options` utility or script function.
L372: def _get_previous_entrypoints(dist: Distribution) -> dict[str, list]:    Function
`_get_previous_entrypoints` utility or script function.
L378: def _get_previous_scripts(dist: Distribution) -> list | None:    Function
`_get_previous_scripts` utility or script function.
L383: def _get_previous_gui_scripts(dist: Distribution) -> list | None:    Function
`_get_previous_gui_scripts` utility or script function.
L388: def _set_static_list_metadata(attr: str, dist: Distribution, val: list) -> None:
Function `_set_static_list_metadata` utility or script function.
L396: def _attrgetter(attr):    Function `_attrgetter` utility or script function.
L411: def _some_attrgetter(*items):    Function `_some_attrgetter` utility or script
function.
L424: def _acessor(obj):    Function `_acessor` utility or script function.
L511: class _MissingDynamic(SetuptoolsWarning):    Class (`_MissingDynamic`) component used
by the app (see file context: None).
L533: def details(cls, field: str, value: Any) -> str:    Function `_details` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/__init__.py

```

L16: def _deprecation_notice(fn: Fn) -> Fn:    Function `_deprecation_notice` utility or
script function.
L18: def _wrapper(*args, **kwargs):    Function `_wrapper` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate_pyproject/fastjsonschema_exceptions.py

```

L7: class JsonSchemaException(ValueError):    Class (`JsonSchemaException`) component used by

```

```

the app (see file context: None).
L13: class JsonSchemaValueException(JsonSchemaException):  Class
(`JsonSchemaValueException`) component used by the app (see file context: None).
L29: def __init__(self, message, value=None, name=None, definition=None, rule=None):
Function `__init__` utility or script function.
L38: def path(self):  Function `path` utility or script function.
L42: def rule_definition(self):  Function `rule_definition` utility or script function.
L48: class JsonSchemaDefinitionException(JsonSchemaException):  Class
(`JsonSchemaDefinitionException`) component used by the app (see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate _pyproject/formats.py

```

L66: def pep440(version: str) -> bool:  Function `pep440` utility or script function.
L80: def pep508_identifier(name: str) -> bool:  Function `pep508_identifier` utility or
script function.
L96: def pep508(value: str) -> bool:  Function `pep508` utility or script function.
L113: def pep508(value: str) -> bool:  # noqa: ARG001  Function `pep508` utility or script
function.
L117: def pep508_versionspec(value: str) -> bool:  Function `pep508_versionspec` utility or
script function.
L136: def pep517_backend_reference(value: str) -> bool:  Function `pep517_backend_reference`
utility or script function.
L151: def _download_classifiers() -> str:  Function `_download_classifiers` utility or
script function.
L164: class _TroveClassifier:  Class (`_TroveClassifier`) component used by the app (see
file context: None).
L179: def __init__(self) -> None:  Function `__init__` utility or script function.
L184: def _disable_download(self) -> None:  Function `_disable_download` utility or script
function.
L188: def __call__(self, value: str) -> bool:  Function `__call__` utility or script
function.
L220: def trove_classifier(value: str) -> bool:  Function `trove_classifier` utility or
script function.
L232: def pep561_stub_name(value: str) -> bool:  Function `pep561_stub_name` utility or
script function.
L247: def url(value: str) -> bool:  Function `url` utility or script function.
L281: def python_identifier(value: str) -> bool:  Function `python_identifier` utility or
script function.
L288: def python_qualified_identifier(value: str) -> bool:  Function
`python_qualified_identifier` utility or script function.
L298: def python_module_name(value: str) -> bool:  Function `python_module_name` utility or
script function.
L305: def python_module_name_relaxed(value: str) -> bool:  Function
`python_module_name_relaxed` utility or script function.
L324: def python_entrypoint_group(value: str) -> bool:  Function `python_entrypoint_group`

```

```

utility or script function.
L331: def python_entrypoint_name(value: str) -> bool:    Function `python_entrypoint_name`
utility or script function.
L344: def python_entrypoint_reference(value: str) -> bool:    Function
`python_entrypoint_reference` utility or script function.
L369: def uint8(value: builtins.int) -> bool:    Function `uint8` utility or script function.
L374: def uint16(value: builtins.int) -> bool:    Function `uint16` utility or script
function.
L379: def uint32(value: builtins.int) -> bool:    Function `uint32` utility or script
function.
L384: def uint64(value: builtins.int) -> bool:    Function `uint64` utility or script
function.
L389: def uint(value: builtins.int) -> bool:    Function `uint` utility or script function.
L394: def int8(value: builtins.int) -> bool:    Function `int8` utility or script function.
L399: def int16(value: builtins.int) -> bool:    Function `int16` utility or script function.
L404: def int32(value: builtins.int) -> bool:    Function `int32` utility or script function.
L409: def int64(value: builtins.int) -> bool:    Function `int64` utility or script function.
L414: def int(value: builtins.int) -> bool:    Function `int` utility or script function.
L422: def SPDX(value: str) -> bool:    Function `SPDX` utility or script function.
L439: def SPDX(value: str) -> bool:    # noqa: ARG001    Function `SPDX` utility or script
function.
L455: def import_name(value: str) -> bool:    Function `import_name` utility or script
function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/__init__.py**

```

L27: def validate(data: Any) -> bool:    Function `validate` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/error_reporting.py**

```

L56: class ValidationError(JsonSchemaValueException):    Class (`ValidationError`) component
used by the app (see file context: None).
L78: def _from_jsonschema(cls, ex: JsonSchemaValueException) -> Self:    Function
`_from_jsonschema` utility or script function.
L91: def detailed_errors() -> Generator[None, None, None]:    Function `detailed_errors`
utility or script function.
L98: class _ErrorFormatting:    Class (`_ErrorFormatting`) component used by the app (see
file context: None).
L99: def __init__(self, ex: JsonSchemaValueException):    Function `__init__` utility or
script function.

```

```

L106: def __str__(self) -> str:    Function `__str__`    utility or script function.
L113: def summary(self) -> str:    Function `summary`    utility or script function.
L120: def details(self) -> str:    Function `details`    utility or script function.
L127: def _simplify_name(name: str) -> str:    Function `_simplify_name`    utility or script
function.
L131: def _expand_summary(self) -> str:    Function `_expand_summary`    utility or script
function.
L147: def _expand_details(self) -> str:    Function `_expand_details`    utility or script
function.
L175: class _SummaryWriter:    Class (`_SummaryWriter`)    component used by the app (see file
context: None).
L178: def __init__(self, jargon: dict[str, str] | None = None):    Function `__init__`
utility or script function.
L212: def _jargon(self, term: str | list[str]) -> str | list[str]:    Function `_jargon`
utility or script function.
L217: def __call__(    Function `__call__`    utility or script function.
L259: def _is_unecessary(self, path: Sequence[str]) -> bool:    Function `_is_unecessary`
utility or script function.
L265: def _filter_unecessary(    Function `_filter_unecessary`    utility or script function.
L274: def _handle_simple_dict(self, value: dict, path: Sequence[str]) -> str | None:
Function `_handle_simple_dict`    utility or script function.
L281: def _handle_list(    Function `_handle_list`    utility or script function.
L296: def _is_property(self, path: Sequence[str]) -> bool:    Function `_is_property`    utility
or script function.
L308: def _label(self, path: Sequence[str]) -> str:    Function `_label`    utility or script
function.
L318: def _value(self, value: Any, path: Sequence[str]) -> str:    Function `_value`    utility
or script function.
L324: def _inline_attrs(self, schema: dict, path: Sequence[str]) -> Iterator[str]:    Function
`_inline_attrs`    utility or script function.
L329: def _child_prefix(self, parent_prefix: str, child_prefix: str) -> str:    Function
`_child_prefix`    utility or script function.
L333: def _separate_terms(word: str) -> list[str]:    Function `_separate_terms`    utility or
script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/fastjsonschema_validations.py**

```

L29: def validate(data, custom_formats={}, name_prefix=None):    Function `validate`    utility
or script function.
L33: def
validate_https__packaging_python_org_en_latest_specifications_declaring_build_dependencies(d
ata, custom_formats={}, name_prefix=None):    Function
`validate_https__packaging_python_org_en_latest_specifications_declaring_build_dependencies`
utility or script function.
L157: def validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html(data,

```

```

custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html` utility or
script function.
L584: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
le_directive_properties_file(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_f
ile_directive_properties_file` utility or script function.
L608: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
le_directive_for_dependencies(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_f
ile_directive_for_dependencies` utility or script function.
L612: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
le_directive(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_f
ile_directive` utility or script function.
L649: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_at
tr_directive(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_a
ttr_directive` utility or script function.
L670: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_ex
t_module(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_e
xt_module` utility or script function.
L875: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_fi
nd_directive(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_f
ind_directive` utility or script function.
L933: def
validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_pa
ckage_name(data, custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_userguide_pyproject_config_html__definitions_p
ackage_name` utility or script function.
L959: def
validate_https__setuptools_pypa_io_en_latest_deprecated_distutils_configfile_html(data,
custom_formats={}, name_prefix=None):    Function
`validate_https__setuptools_pypa_io_en_latest_deprecated_distutils_configfile_html` utility
or script function.
L978: def validate_https__packaging_python_org_en_latest_specifications_pyproject_toml(data,
custom_formats={}, name_prefix=None):    Function
`validate_https__packaging_python_org_en_latest_specifications_pyproject_toml` utility or
script function.
L1372: def
validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_d
ependency(data, custom_formats={}, name_prefix=None):    Function
`validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_

```



```

dependency` utility or script function.
L1380: def
validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_e
ntry_point_group(data, custom_formats={}, name_prefix=None): Function
`validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_
entry_point_group` utility or script function.
L1411: def
validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_a
uthor(data, custom_formats={}, name_prefix=None): Function
`validate_https__packaging_python_org_en_latest_specifications_pyproject_toml__definitions_
author` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/config/_validate
_pyproject/extra_validations.py**

```

L16: class RedefiningStaticFieldAsDynamic(ValidationError): Class
(`RedefiningStaticFieldAsDynamic`) component used by the app (see file context: None).
L28: class IncludedDependencyGroupMustExist(ValidationError): Class
(`IncludedDependencyGroupMustExist`) component used by the app (see file context: None).
L35: class ImportNameCollision(ValidationError): Class (`ImportNameCollision`) component
used by the app (see file context: None).
L44: class ImportNameMissing(ValidationError): Class (`ImportNameMissing`) component used
by the app (see file context: None).
L53: def validate_project_dynamic(pyproject: T) -> T: Function `validate_project_dynamic`
utility or script function.
L78: def validate_include_dependency(pyproject: T) -> T: Function
`validate_include_dependency` utility or script function.
L101: def _remove_private(items: Iterable[str]) -> Generator[str, None, None]: Function
`_remove_private` utility or script function.
L106: def validate_import_name_issues(pyproject: T) -> T: Function
`validate_import_name_issues` utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/compat/py310.p
y**

```

L14: def add_note(ex, note): Function `add_note` utility or script function.
L19: def add_note(ex, note): Function `add_note` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/compat/py311.py

```
L15: def shutil_rmtree(    Function `shutil_rmtree`    utility or script function.
L23: def _handler(fn: Callable[..., Any], path: str, excinfo: ExcInfo) -> None:    Function
`_handler`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_elffile.py

```
L18: class ELFInvalid(ValueError):    Class (`ELFInvalid`)    component used by the app (see
file context: None).
L22: class EIClass(enum.IntEnum):    Class (`EIClass`)    component used by the app (see file
context: None).
L27: class EIData(enum.IntEnum):    Class (`EIData`)    component used by the app (see file
context: None).
L32: class EMachine(enum.IntEnum):    Class (`EMachine`)    component used by the app (see file
context: None).
L40: class ELFFile:    Class (`ELFFile`)    component used by the app (see file context: None).
L45: def __init__(self, f: IO[bytes]) -> None:    Function `__init__`    utility or script
function.
L90: def _read(self, fmt: str) -> tuple[int, ...]:    Function `_read`    utility or script
function.
L94: def interpreter(self) -> str | None:    Function `interpreter`    utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_manylinux.py

```
L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:    Function
`_parse_elf`    utility or script function.
L40: def _is_linux_armhf(executable: str) -> bool:    Function `_is_linux_armhf`    utility or
script function.
L55: def _is_linux_i686(executable: str) -> bool:    Function `_is_linux_i686`    utility or
script function.
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:    Function
`_have_compatible_abi`    utility or script function.
L81: class _GLibCVersion(NamedTuple):    Class (`_GLibCVersion`)    component used by the app
(see file context: None).
L86: def _glibc_version_string_confstr() -> str | None:    Function
```

```

`_glibc_version_string_confstr` utility or script function.
L105: def _glibc_version_string_ctypes() -> str | None:    Function
`_glibc_version_string_ctypes` utility or script function.
L149: def _glibc_version_string() -> str | None:    Function `_glibc_version_string` utility
or script function.
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:    Function
`_parse_glibc_version` utility or script function.
L174: def _get_glibc_version() -> _GLibCVersion:    Function `_get_glibc_version` utility or
script function.
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:    Function
`_is_compatible` utility or script function.
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/metadata.py

```

L34: class ExceptionGroup(Exception):    Class (`ExceptionGroup`) component used by the app
(see file context: None).
L44: def __init__(self, message: str, exceptions: list[Exception]) -> None:    Function
`__init__` utility or script function.
L48: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L52: class InvalidMetadata(ValueError):    Class (`InvalidMetadata`) component used by the
app (see file context: None).
L58: def __init__(self, field: str, message: str) -> None:    Function `__init__` utility or
script function.
L67: class RawMetadata(TypedDict, total=False):    Class (`RawMetadata`) component used by
the app (see file context: None).
L186: def _parse_keywords(data: str) -> list[str]:    Function `_parse_keywords` utility or
script function.
L191: def _parse_project_urls(data: list[str]) -> dict[str, str]:    Function
`_parse_project_urls` utility or script function.
L230: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:    Function
`_get_payload` utility or script function.
L299: class RFC822Policy(email.policy.EmailPolicy):    Class (`RFC822Policy`) component used
by the app (see file context: None).
L309: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:    Function
`header_store_parse` utility or script function.
L316: class RFC822Message(email.message.EmailMessage):    Class (`RFC822Message`) component
used by the app (see file context: None).
L323: def __init__(self) -> None:    Function `__init__` utility or script function.
L326: def as_bytes(    Function `as_bytes` utility or script function.
L337: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
Function `parse_email` utility or script function.
L528: class _Validator(Generic[T]):    Class (`_Validator`) component used by the app (see
file context: None).

```

```

L542: def __init__(    Function `__init__`    utility or script function.
L549: def __set_name__(self, _owner: Metadata, name: str) -> None:    Function `__set_name__`
utility or script function.
L553: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:    Function
`__get__`    utility or script function.
L580: def _invalid_metadata(    Function `_invalid_metadata`    utility or script function.
L589: def _process_metadata_version(self, value: str) -> _MetadataVersion:    Function
`_process_metadata_version`    utility or script function.
L595: def _process_name(self, value: str) -> str:    Function `_process_name`    utility or
script function.
L608: def _process_version(self, value: str) -> version_module.Version:    Function
`_process_version`    utility or script function.
L618: def _process_summary(self, value: str) -> str:    Function `_process_summary`    utility
or script function.
L624: def _process_description_content_type(self, value: str) -> str:    Function
`_process_description_content_type`    utility or script function.
L656: def _process_dynamic(self, value: list[str]) -> list[str]:    Function
`_process_dynamic`    utility or script function.
L668: def _process_provides_extra(    Function `_process_provides_extra`    utility or script
function.
L683: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:    Function
`_process_requires_python`    utility or script function.
L691: def _process_requires_dist(    Function `_process_requires_dist`    utility or script
function.
L706: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
Function `_process_license_expression`    utility or script function.
L714: def _process_license_files(self, value: list[str]) -> list[str]:    Function
`_process_license_files`    utility or script function.
L740: def _process_import_names(self, value: list[str]) -> list[str]:    Function
`_process_import_names`    utility or script function.
L765: class Metadata:    Class (`Metadata`)    component used by the app (see file context:
None).
L777: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata:    Function
`from_raw`    utility or script function.
L834: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
Function `from_email`    utility or script function.
L946: def as_rfc822(self) -> RFC822Message:    Function `as_rfc822`    utility or script
function.
L954: def _write_metadata(self, message: RFC822Message) -> None:    Function `_write_metadata`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/markers.py

```

L40: class InvalidMarker(ValueError):    Class (`InvalidMarker`)    component used by the app
(see file context: None).

```

```

L46: class UndefinedComparison(ValueError):    Class (`UndefinedComparison`)    component used
by the app (see file context: None).
L52: class UndefinedEnvironmentName(ValueError):    Class (`UndefinedEnvironmentName`)
component used by the app (see file context: None).
L59: class Environment(TypedDict):    Class (`Environment`)    component used by the app (see
file context: None).
L131: def _normalize_extras(    Function `_normalize_extras`    utility or script function.
L147: def _normalize_extra_values(results: MarkerList) -> MarkerList:    Function
`_normalize_extra_values`    utility or script function.
L155: def _format_marker(    Function `_format_marker`    utility or script function.
L195: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
Function `_eval_op`    utility or script function.
L212: def _normalize(    Function `_normalize`    utility or script function.
L233: def _evaluate_markers(    Function `_evaluate_markers`    utility or script function.
L266: def format_full_version(info: sys._version_info) -> str:    Function
`format_full_version`    utility or script function.
L274: def default_environment() -> Environment:    Function `default_environment`    utility or
script function.
L292: class Marker:    Class (`Marker`)    component used by the app (see file context: None).
L293: def __init__(self, marker: str) -> None:    Function `__init__`    utility or script
function.
L323: def __str__(self) -> str:    Function `__str__`    utility or script function.
L326: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L329: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L332: def __eq__(self, other: object) -> bool:    Object (singleton).
L338: def evaluate(    Function `evaluate`    utility or script function.
L378: def _repair_python_full_version(    Function `_repair_python_full_version`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/specifiers.py

```

L26: def _coerce_version(version: UnparsedVersion) -> Version | None:    Function
`_coerce_version`    utility or script function.
L35: def _public_version(version: Version) -> Version:    Function `_public_version`    utility
or script function.
L39: def _base_version(version: Version) -> Version:    Function `_base_version`    utility or
script function.
L43: class InvalidSpecifier(ValueError):    Class (`InvalidSpecifier`)    component used by the
app (see file context: None).
L55: class BaseSpecifier(metaclass=abc.ABCMeta):    Class (`BaseSpecifier`)    component used by
the app (see file context: None).
L60: def _str(self) -> str:    Function `_str`    utility or script function.
L65: def __str__(self) -> str:    Function `__str__`    utility or script function.
L72: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L78: def __eq__(self, other: object) -> bool:    Object (singleton).

```

```

L88: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L96: def prereleases(self, value: bool) -> None:    Function `prereleases` utility or script
function.
L103: def contains(self, item: str, prereleases: bool | None = None) -> bool:    Function
`contains` utility or script function.
L109: def filter(    Function `filter` utility or script function.
L118: class Specifier(BaseSpecifier):    Class (`Specifier`) component used by the app (see
file context: None).
L243: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:    Function
`__init__` utility or script function.
L271: def _get_spec_version(self, version: str) -> Version | None:    Function
`_get_spec_version` utility or script function.
L283: def _require_spec_version(self, version: str) -> Version:    Function
`_require_spec_version` utility or script function.
L294: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L323: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility or
script function.
L327: def operator(self) -> str:    Function `operator` utility or script function.
L336: def version(self) -> str:    Function `version` utility or script function.
L344: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L362: def __str__(self) -> str:    Function `__str__` utility or script function.
L373: def _canonical_spec(self) -> tuple[str, str]:    Function `_canonical_spec` utility or
script function.
L386: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L389: def __eq__(self, other: object) -> bool:    Object (singleton).
L418: def _get_operator(self, op: str) -> CallableOperator:    Function `_get_operator`
utility or script function.
L424: def _compare_compatible(self, prospective: Version, spec: str) -> bool:    Function
`_compare_compatible` utility or script function.
L444: def _compare_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_equal` utility or script function.
L484: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_not_equal` utility or script function.
L487: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_less_than_equal` utility or script function.
L493: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
Function `_compare_greater_than_equal` utility or script function.
L499: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:    Function
`_compare_less_than` utility or script function.
L526: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
Function `_compare_greater_than` utility or script function.
L560: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:    Function
`_compare_arbitrary` utility or script function.
L563: def __contains__(self, item: str | Version) -> bool:    Function `__contains__` utility
or script function.
L584: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
Function `contains` utility or script function.
L611: def filter(    Function `filter` utility or script function.
L677: def _version_split(version: str) -> list[str]:    Function `_version_split` utility or

```

```

script function.
L699: def _version_join(components: list[str]) -> str:    Function `_version_join` utility or
script function.
L710: def _is_not_suffix(segment: str) -> bool:    Function `_is_not_suffix` utility or
script function.
L716: def _pad_version(left: list[str], right: list[str]) -> tuple[list[str], list[str]]:
Function `_pad_version` utility or script function.
L737: class SpecifierSet(BaseSpecifier):    Class (`SpecifierSet`) component used by the app
(see file context: None).
L746: def __init__(    Function `__init__` utility or script function.
L785: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L805: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility or
script function.
L808: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L829: def __str__(self) -> str:    Function `__str__` utility or script function.
L842: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L845: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:    Function `__and__`
utility or script function.
L876: def __eq__(self, other: object) -> bool:    Object (singleton).
L902: def __len__(self) -> int:    Function `__len__` utility or script function.
L906: def __iter__(self) -> Iterator[Specifier]:    Function `__iter__` utility or script
function.
L916: def __contains__(self, item: UnparsedVersion) -> bool:    Function `__contains__`
utility or script function.
L937: def contains(    Function `contains` utility or script function.
L977: def filter(    Function `filter` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_tokenizer.py

```

L12: class Token:    Class (`Token`) component used by the app (see file context: None).
L18: class ParserSyntaxError(Exception):    Class (`ParserSyntaxError`) component used by the
app (see file context: None).
L21: def __init__(    Function `__init__` utility or script function.
L34: def __str__(self) -> str:    Function `__str__` utility or script function.
L91: class Tokenizer:    Class (`Tokenizer`) component used by the app (see file context:
None).
L98: def __init__(    Function `__init__` utility or script function.
L109: def consume(self, name: str) -> None:    Function `consume` utility or script function.
L114: def check(self, name: str, *, peek: bool = False) -> bool:    Function `check` utility
or script function.
L135: def expect(self, name: str, *, expected: str) -> Token:    Function `expect` utility or
script function.
L144: def read(self) -> Token:    Function `read` utility or script function.
L154: def raise_syntax_error(    Function `raise_syntax_error` utility or script function.

```

```
L173: def enclosing_tokens(    Function `enclosing_tokens`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_parser.py

```
L15: class Node:    Class (`Node`)    component used by the app (see file context: None).
L18: def __init__(self, value: str) -> None:    Function `__init__`    utility or script
function.
L21: def __str__(self) -> str:    Function `__str__`    utility or script function.
L24: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L27: def serialize(self) -> str:    Function `serialize`    utility or script function.
L31: class Variable(Node):    Class (`Variable`)    component used by the app (see file context:
None).
L34: def serialize(self) -> str:    Function `serialize`    utility or script function.
L38: class Value(Node):    Class (`Value`)    component used by the app (see file context:
None).
L41: def serialize(self) -> str:    Function `serialize`    utility or script function.
L45: class Op(Node):    Class (`Op`)    component used by the app (see file context: None).
L48: def serialize(self) -> str:    Function `serialize`    utility or script function.
L59: class ParsedRequirement(NamedTuple):    Class (`ParsedRequirement`)    component used by
the app (see file context: None).
L70: def parse_requirement(source: str) -> ParsedRequirement:    Function `parse_requirement`
utility or script function.
L74: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:    Function
`_parse_requirement`    utility or script function.
L95: def _parse_requirement_details(    Function `_parse_requirement_details`    utility or
script function.
L148: def _parse_requirement_marker(    Function `_parse_requirement_marker`    utility or
script function.
L169: def _parse_extras(tokenizer: Tokenizer) -> list[str]:    Function `_parse_extras`
utility or script function.
L188: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:    Function
`_parse_extras_list`    utility or script function.
L215: def _parse_specifier(tokenizer: Tokenizer) -> str:    Function `_parse_specifier`
utility or script function.
L232: def _parse_version_many(tokenizer: Tokenizer) -> str:    Function `_parse_version_many`
utility or script function.
L264: def parse_marker(source: str) -> MarkerList:    Function `parse_marker`    utility or
script function.
L268: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:    Function
`_parse_full_marker`    utility or script function.
L274: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:    Function `_parse_marker`
utility or script function.
L286: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:    Function
`_parse_marker_atom`    utility or script function.
L308: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:    Function
```



```

`_parse_marker_item` utility or script function.
L322: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar: # noqa: RET503    Function
`_parse_marker_var` utility or script function.
L336: def process_env_var(env_var: str) -> Variable:    Function `process_env_var` utility or
script function.
L343: def process_python_str(python_str: str) -> Value:    Function `process_python_str`
utility or script function.
L348: def _parse_marker_op(tokenizer: Tokenizer) -> Op:    Function `_parse_marker_op`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/utls.py

```

L17: class InvalidName(ValueError):    Class (`InvalidName`) component used by the app (see
file context: None).
L23: class InvalidWheelFilename(ValueError):    Class (`InvalidWheelFilename`) component used
by the app (see file context: None).
L29: class InvalidSdistFilename(ValueError):    Class (`InvalidSdistFilename`) component used
by the app (see file context: None).
L42: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
Function `canonicalize_name` utility or script function.
L55: def is_normalized_name(name: str) -> bool:    Function `is_normalized_name` utility or
script function.
L59: def canonicalize_version(    Function `canonicalize_version` utility or script function.
L89: def parse_wheel_filename(    Function `parse_wheel_filename` utility or script function.
L132: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:    Function
`parse_sdist_filename` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/version.py

```

L39: def _deprecated(message: str) -> object:    Object (singleton).
L40: def decorator(func: object) -> object:    Object (singleton).
L42: def wrapper(*args: object, **kwargs: object) -> object:    Object (singleton).
L85: class _VersionReplace(TypedDict, total=False):    Class (`_VersionReplace`) component
used by the app (see file context: None).
L94: def parse(version: str) -> Version:    Function `parse` utility or script function.
L106: class InvalidVersion(ValueError):    Class (`InvalidVersion`) component used by the app
(see file context: None).
L116: class _BaseVersion:    Class (`_BaseVersion`) component used by the app (see file
context: None).
L125: def _key(self) -> tuple[Any, ...]: ...    Function `_key` utility or script function.

```

```

L127: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L133: def __lt__(self, other: _BaseVersion) -> bool:    Function `__lt__` utility or script
function.
L139: def __le__(self, other: _BaseVersion) -> bool:    Function `__le__` utility or script
function.
L145: def __eq__(self, other: object) -> bool:    Object (singleton).
L151: def __ge__(self, other: _BaseVersion) -> bool:    Function `__ge__` utility or script
function.
L157: def __gt__(self, other: _BaseVersion) -> bool:    Function `__gt__` utility or script
function.
L163: def __ne__(self, other: object) -> bool:    Object (singleton).
L238: def _validate_epoch(value: object, /) -> int:    Object (singleton).
L246: def _validate_release(value: object, /) -> tuple[int, ...]:    Object (singleton).
L258: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
Object (singleton).
L273: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:    Object
(singleton).
L282: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:    Object
(singleton).
L291: def _validate_local(value: object, /) -> LocalType | None:    Object (singleton).
L301: class _Version(NamedTuple):    Class (`_Version`) component used by the app (see file
context: None).
L310: class Version(_BaseVersion):    Class (`Version`) component used by the app (see file
context: None).
L348: def __init__(self, version: str) -> None:    Function `__init__` utility or script
function.
L374: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:    Function
`__replace__` utility or script function.
L408: def _key(self) -> CmpKey:    Function `_key` utility or script function.
L422: def _version(self) -> _Version:    Function `_version` utility or script function.
L429: def _version(self, value: _Version) -> None:    Function `_version` utility or script
function.
L438: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L446: def __str__(self) -> str:    Function `__str__` utility or script function.
L478: def _str(self) -> str:    Function `_str` utility or script function.
L483: def epoch(self) -> int:    Function `epoch` utility or script function.
L494: def release(self) -> tuple[int, ...]:    Function `release` utility or script function.
L510: def pre(self) -> tuple[str, int] | None:    Function `pre` utility or script function.
L525: def post(self) -> int | None:    Function `post` utility or script function.
L536: def dev(self) -> int | None:    Function `dev` utility or script function.
L547: def local(self) -> str | None:    Function `local` utility or script function.
L561: def public(self) -> str:    Function `public` utility or script function.
L574: def base_version(self) -> str:    Function `base_version` utility or script function.
L591: def is_prerelease(self) -> bool:    Function `is_prerelease` utility or script
function.
L608: def is_postrelease(self) -> bool:    Function `is_postrelease` utility or script
function.
L619: def is_devrelease(self) -> bool:    Function `is_devrelease` utility or script
function.
L630: def major(self) -> int:    Function `major` utility or script function.
L639: def minor(self) -> int:    Function `minor` utility or script function.

```

```

L650: def micro(self) -> int:    Function `micro` utility or script function.
L661: class _TrimmedRelease(Version):    Class (`_TrimmedRelease`) component used by the app
(see file context: None).
L664: def __init__(self, version: str | Version) -> None:    Function `__init__` utility or
script function.
L677: def release(self) -> tuple[int, ...]:    Function `release` utility or script function.
L695: def _parse_letter_version(    Function `_parse_letter_version` utility or script
function.
L722: def _parse_local_version(local: str | None) -> LocalType | None:    Function
`_parse_local_version` utility or script function.
L734: def _cmpkey(    Function `_cmpkey` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_structures.py

```

L9: class InfinityType:    Class (`InfinityType`) component used by the app (see file
context: None).
L12: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L15: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L18: def __lt__(self, other: object) -> bool:    Object (singleton).
L21: def __le__(self, other: object) -> bool:    Object (singleton).
L24: def __eq__(self, other: object) -> bool:    Object (singleton).
L27: def __gt__(self, other: object) -> bool:    Object (singleton).
L30: def __ge__(self, other: object) -> bool:    Object (singleton).
L33: def __neg__(self: object) -> "NegativeInfinityType":    Object (singleton).
L41: class NegativeInfinityType:    Class (`NegativeInfinityType`) component used by the app
(see file context: None).
L44: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L47: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L50: def __lt__(self, other: object) -> bool:    Object (singleton).
L53: def __le__(self, other: object) -> bool:    Object (singleton).
L56: def __eq__(self, other: object) -> bool:    Object (singleton).
L59: def __gt__(self, other: object) -> bool:    Object (singleton).
L62: def __ge__(self, other: object) -> bool:    Object (singleton).
L65: def __neg__(self: object) -> InfinityType:    Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/tags.py

```

L43: class Tag:    Class (`Tag`) component used by the app (see file context: None).
L53: def __init__(self, interpreter: str, abi: str, platform: str) -> None:    Function
`__init__` utility or script function.

```

```

L65: def interpreter(self) -> str:    Function `interpreter` utility or script function.
L69: def abi(self) -> str:    Function `abi` utility or script function.
L73: def platform(self) -> str:    Function `platform` utility or script function.
L76: def __eq__(self, other: object) -> bool:    Object (singleton).
L87: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L90: def __str__(self) -> str:    Function `__str__` utility or script function.
L93: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L96: def __setstate__(self, state: tuple[None, dict[str, Any]]) -> None:    Function
`__setstate__` utility or script function.
L104: def parse_tag(tag: str) -> frozenset[Tag]:    Function `parse_tag` utility or script
function.
L120: def _get_config_var(name: str, warn: bool = False) -> int | str | None:    Function
`_get_config_var` utility or script function.
L129: def _normalize_string(string: str) -> str:    Function `_normalize_string` utility or
script function.
L133: def _is_threaded_cpython(abis: list[str]) -> bool:    Function `_is_threaded_cpython`
utility or script function.
L149: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3_applies` utility or script function.
L159: def _cpython_abis(py_version: PythonVersion, warn: bool = False) -> list[str]:
Function `_cpython_abis` utility or script function.
L192: def cpython_tags(    Function `cpython_tags` utility or script function.
L248: def _generic_abi() -> list[str]:    Function `_generic_abi` utility or script function.
L289: def generic_tags(    Function `generic_tags` utility or script function.
L317: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:    Function
`_py_interpreter_range` utility or script function.
L332: def compatible_tags(    Function `compatible_tags` utility or script function.
L357: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:    Function
`_mac_arch` utility or script function.
L367: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:    Function
`_mac_binary_formats` utility or script function.
L399: def mac_platforms(    Function `mac_platforms` utility or script function.
L475: def ios_platforms(    Function `ios_platforms` utility or script function.
L532: def android_platforms(    Function `android_platforms` utility or script function.
L569: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:    Function
`_linux_platforms` utility or script function.
L588: def _generic_platforms() -> Iterator[str]:    Function `_generic_platforms` utility or
script function.
L592: def platform_tags() -> Iterator[str]:    Function `platform_tags` utility or script
function.
L608: def interpreter_name() -> str:    Function `interpreter_name` utility or script
function.
L619: def interpreter_version(*, warn: bool = False) -> str:    Function `interpreter_version`
utility or script function.
L627: def _version_nodot(version: PythonVersion) -> str:    Function `_version_nodot` utility
or script function.
L631: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:    Function `sys_tags` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/_musllinux.py

```

L18: class _MuslVersion(NamedTuple):    Class (`_MuslVersion`)    component used by the app (see
file context: None).
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:    Function
`_parse_musl_version`    utility or script function.
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:    Function
`_get_musl_version`    utility or script function.
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/requirements.py

```

L15: class InvalidRequirement(ValueError):    Class (`InvalidRequirement`)    component used by
the app (see file context: None).
L21: class Requirement:    Class (`Requirement`)    component used by the app (see file context:
None).
L34: def __init__(self, requirement_string: str) -> None:    Function `__init__`    utility or
script function.
L49: def _iter_parts(self, name: str) -> Iterator[str]:    Function `_iter_parts`    utility or
script function.
L67: def __str__(self) -> str:    Function `__str__`    utility or script function.
L70: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L73: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L76: def __eq__(self, other: object) -> bool:    Object (singleton).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/pylock.py

```

L46: class _FromMappingProtocol(Protocol):    # pragma: no cover    Class
(`_FromMappingProtocol`)    component used by the app (see file context: None).
L48: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict`    utility
or script function.
L57: def is_valid_pylock_path(path: Path) -> bool:    Function `is_valid_pylock_path`    utility
or script function.
L62: def _toml_key(key: str) -> str:    Function `_toml_key`    utility or script function.
L66: def _toml_value(key: str, value: Any) -> Any:    # noqa: ANN401    Function `_toml_value`

```

```

utility or script function.
L74: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_toml_dict_factory` utility or script function.
L82: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get` utility or script function.
L95: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required` utility or script function.
L102: def _get_sequence(    Function `_get_sequence` utility or script function.
L124: def _get_as(    Function `_get_as` utility or script function.
L143: def _get_required_as(    Function `_get_required_as` utility or script function.
L156: def _get_sequence_as(    Function `_get_sequence_as` utility or script function.
L175: def _get_object(    Function `_get_object` utility or script function.
L187: def _get_sequence_of_objects(    Function `_get_sequence_of_objects` utility or script
function.
L203: def _get_required_sequence_of_objects(    Function `_get_required_sequence_of_objects`
utility or script function.
L213: def _validate_normalized_name(name: str) -> NormalizedName:    Function
`_validate_normalized_name` utility or script function.
L220: def _validate_path_url(path: str | None, url: str | None) -> None:    Function
`_validate_path_url` utility or script function.
L225: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:    Function
`_validate_hashes` utility or script function.
L233: class PylockValidationError(Exception):    Class (`PylockValidationError`) component
used by the app (see file context: None).
L239: def __init__(    Function `__init__` utility or script function.
L257: def __str__(self) -> str:    Function `__str__` utility or script function.
L263: class _PylockRequiredKeyError(PylockValidationError):    Class
(`_PylockRequiredKeyError`) component used by the app (see file context: None).
L264: def __init__(self, key: str) -> None:    Function `__init__` utility or script
function.
L268: class PylockUnsupportedVersionError(PylockValidationError):    Class
(`PylockUnsupportedVersionError`) component used by the app (see file context: None).
L273: class PackageVcs:    Class (`PackageVcs`) component used by the app (see file context:
None).
L281: def __init__(    Function `__init__` utility or script function.
L300: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L314: class PackageDirectory:    Class (`PackageDirectory`) component used by the app (see
file context: None).
L319: def __init__(    Function `__init__` utility or script function.
L332: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L341: class PackageArchive:    Class (`PackageArchive`) component used by the app (see file
context: None).
L349: def __init__(    Function `__init__` utility or script function.
L368: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or
script function.
L382: class PackageSdist:    Class (`PackageSdist`) component used by the app (see file
context: None).
L390: def __init__(    Function `__init__` utility or script function.
L409: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict` utility or

```

```

script function.
L423: class PackageWheel:    Class (`PackageWheel`)    component used by the app (see file
context: None).
L431: def __init__(    Function `__init__`    utility or script function.
L450: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L464: class Package:    Class (`Package`)    component used by the app (see file context: None).
L479: def __init__(    Function `__init__`    utility or script function.
L512: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L553: def is_direct(self) -> bool:    Function `is_direct`    utility or script function.
L558: class Pylock:    Class (`Pylock`)    component used by the app (see file context: None).
L571: def __init__(    Function `__init__`    utility or script function.
L596: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L619: def from_dict(cls, d: Mapping[str, Any], /) -> Self:    Function `from_dict`    utility or
script function.
L627: def to_dict(self) -> Mapping[str, Any]:    Function `to_dict`    utility or script
function.
L631: def validate(self) -> None:    Function `validate`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/licenses/_spdx.py

```

L6: class SPDXLicense(TypedDict):    Class (`SPDXLicense`)    component used by the app (see
file context: None).
L10: class SPDXException(TypedDict):    Class (`SPDXException`)    component used by the app
(see file context: None).

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/packaging/licenses/__init__.py

```

L50: class InvalidLicenseExpression(ValueError):    Class (`InvalidLicenseExpression`)
component used by the app (see file context: None).
L60: def canonicalize_license_expression(    Function `canonicalize_license_expression`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/

functools/ __init__.py

```

L16: def compose(*funcs):    Function `compose` utility or script function.
L42: def compose_two(f1, f2):    Function `compose_two` utility or script function.
L48: def once(func):    Function `once` utility or script function.
L81: def wrapper(*args, **kwargs):    Function `wrapper` utility or script function.
L90: def method_cache(method, cache_wrapper=functools.lru_cache()):    Function `method_cache`
    utility or script function.
L158: def wrapper(self, *args, **kwargs):    Function `wrapper` utility or script function.
L171: def _special_method_cache(method, cache_wrapper):    Function `_special_method_cache`
    utility or script function.
L190: def proxy(self, /, *args, **kwargs):    Function `proxy` utility or script function.
L202: def apply(transform):    Function `apply` utility or script function.
L217: def wrap(func):    Function `wrap` utility or script function.
L223: def result_invoke(action):    Function `result_invoke` utility or script function.
L239: def wrap(func):    Function `wrap` utility or script function.
L241: def wrapper(*args, **kwargs):    Function `wrapper` utility or script function.
L251: def invoke(f, /, *args, **kwargs):    Function `invoke` utility or script function.
L296: def passthrough(func: Callable[..., object]) -> Callable[[_T], _T]:    Object
(singleton).
L306: def wrapper(first: _T, *args, **kwargs) -> _T:    Function `wrapper` utility or script
function.
L313: class Throttler:    Class (`Throttler`) component used by the app (see file context:
None).
L316: def __init__(self, func, max_rate=float('Inf')):    Function `__init__` utility or
script function.
L323: def reset(self):    Function `reset` utility or script function.
L326: def __call__(self, *args, **kwargs):    Function `__call__` utility or script function.
L330: def _wait(self):    Function `_wait` utility or script function.
L337: def __get__(self, obj, owner=None):    Function `__get__` utility or script function.
L341: def first_invoke(func1, func2):    Function `first_invoke` utility or script function.
L348: def wrapper(*args, **kwargs):    Function `wrapper` utility or script function.
L366: def retry_call(func, cleanup=lambda: None, retries=0, trap=()):    Function `retry_call`
utility or script function.
L383: def retry(*r_args, **r_kwargs):    Function `retry` utility or script function.
L398: def decorate(func):    Function `decorate` utility or script function.
L400: def wrapper(*f_args, **f_kwargs):    Function `wrapper` utility or script function.
L409: def print_yielded(func):    Function `print_yielded` utility or script function.
L425: def pass_none(func):    Function `pass_none` utility or script function.
L436: def wrapper(param, /, *args, **kwargs):    Function `wrapper` utility or script
function.
L444: def none_as(value, replacement=None):    Function `none_as` utility or script function.
L454: def assign_params(func, namespace):    Function `assign_params` utility or script
function.
L486: def save_method_args(method):    Function `save_method_args` Saves data to storage or
remote.
L523: def wrapper(self, /, *args, **kwargs):    Function `wrapper` utility or script
function.
L532: def except_(*exceptions, replace=None, use=None):    Function `except_` utility or
script function.

```



```

L556: def decorate(func):    Function `decorate` utility or script function.
L558: def wrapper(*args, **kwargs):    Function `wrapper` utility or script function.
L572: def identity(x):    Function `identity` utility or script function.
L583: def bypass_when(check, *, _op=identity):    Function `bypass_when` utility or script
function.
L599: def decorate(func):    Function `decorate` utility or script function.
L601: def wrapper(param, /):    Function `wrapper` utility or script function.
L609: def bypass_unless(check):    Function `bypass_unless` utility or script function.
L628: def _splat_inner(args, func):    Function `_splat_inner` utility or script function.
L634: def _(args: collections.abc.Mapping, func):    Function `_` utility or script function.
L639: def splat(func):    Function `splat` utility or script function.
L680: def chainable(method: Callable[[_T, ...], None]) -> Callable[[_T, ...], _T]:    Function
`chainable` utility or script function.
L710: def wrapper(self, *args, **kwargs):    Function `wrapper` utility or script function.
L717: def noop(*args, **kwargs):    Function `noop` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/show-newlines.py

```

L8: def report_newlines(filename):    Function `report_newlines` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/layouts.py

```

L9: def translate(input, translation):    Function `translate` utility or script function.
L19: def _translate_stream(stream, translation):    Function `_translate_stream` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/__init__.py

```

L17: def substitution(old, new):    Function `substitution` utility or script function.
L24: def multi_substitution(*substitutions):    Function `multi_substitution` utility or
script function.
L39: class FoldedCase(str):    Class (`FoldedCase`) component used by the app (see file
context: None).
L102: def __lt__(self, other):    Function `__lt__` utility or script function.

```

```

L105: def __gt__(self, other):    Function `__gt__`    utility or script function.
L108: def __eq__(self, other):    Function `__eq__`    utility or script function.
L111: def __ne__(self, other):    Function `__ne__`    utility or script function.
L114: def __hash__(self):        Function `__hash__`    utility or script function.
L117: def __contains__(self, other):    Function `__contains__`    utility or script function.
L120: def in_(self, other):      Function `in_`    utility or script function.
L126: def casefold(self):        Function `casefold`    utility or script function.
L129: def index(self, sub):      Function `index`    utility or script function.
L132: def split(self, splitter=' ', maxsplit=0):    Function `split`    utility or script
function.
L142: def is_decodable(value):    Function `is_decodable`    utility or script function.
L155: def is_binary(value):      Function `is_binary`    utility or script function.
L168: def trim(s):              Function `trim`    utility or script function.
L179: def wrap(s):              Function `wrap`    utility or script function.
L212: def unwrap(s):            Function `unwrap`    utility or script function.
L237: class Splitter:          Class (`Splitter`)    component used by the app (see file context:
None).
L245: def __init__(self, *args):    Function `__init__`    utility or script function.
L248: def __call__(self, s):        Function `__call__`    utility or script function.
L252: def indent(string, prefix=' ' * 4):    Function `indent`    utility or script function.
L260: class WordSet(tuple):      Class (`WordSet`)    component used by the app (see file context:
None).
L316: def capitalized(self):      Function `capitalized`    utility or script function.
L319: def lowered(self):         Function `lowered`    utility or script function.
L322: def camel_case(self):      Function `camel_case`    utility or script function.
L325: def headless_camel_case(self):    Function `headless_camel_case`    utility or script
function.
L331: def underscore_separated(self):    Function `underscore_separated`    utility or script
function.
L334: def dash_separated(self):    Function `dash_separated`    utility or script function.
L337: def space_separated(self):    Function `space_separated`    utility or script function.
L340: def trim_right(self, item):    Function `trim_right`    utility or script function.
L353: def trim_left(self, item):    Function `trim_left`    utility or script function.
L366: def trim(self, item):         Function `trim`    utility or script function.
L373: def __getitem__(self, item):    Function `__getitem__`    utility or script function.
L380: def parse(cls, identifier):    Function `parse`    utility or script function.
L385: def from_class_name(cls, subject):    Function `from_class_name`    utility or script
function.
L393: def simple_html_strip(s):    Function `simple_html_strip`    utility or script function.
L415: class SeparatedValues(str):    Class (`SeparatedValues`)    component used by the app (see
file context: None).
L431: def __iter__(self):          Function `__iter__`    utility or script function.
L436: class Stripper:             Class (`Stripper`)    component used by the app (see file context:
None).
L463: def __init__(self, prefix, lines):    Function `__init__`    utility or script function.
L468: def strip_prefix(cls, lines):    Function `strip_prefix`    utility or script function.
L473: def __call__(self, line):      Function `__call__`    utility or script function.
L480: def common_prefix(s1, s2):    Function `common_prefix`    utility or script function.
L490: def remove_prefix(text, prefix):    Function `remove_prefix`    utility or script
function.
L504: def remove_suffix(text, suffix):    Function `remove_suffix`    utility or script

```

```

function.
L518: def normalize_newlines(text):  Function `normalize_newlines`  utility or script
function.
L534: def _nonblank(str):  Function `_nonblank`  utility or script function.
L539: def yield_lines(iterable):  Function `yield_lines`  utility or script function.
L558: def _(text):  Function `_`  utility or script function.
L562: def clean(lines: Iterable[str]):  Function `clean`  utility or script function.
L569: def drop_comment(line):  Function `drop_comment`  utility or script function.
L584: def join_continuation(lines):  Function `join_continuation`  utility or script
function.
L617: def read_newlines(filename, limit=1024):  Function `read_newlines`  utility or script
function.
L636: def lines_from(input):  Function `lines_from`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/text/strip-prefix.py

```

L8: def strip_prefix():  Function `strip_prefix`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/jaraco/context/__init__.py

```

L24: def pushd(dir: str | os.PathLike) -> Iterator[str | os.PathLike]:  Function `pushd`
utility or script function.
L41: def tarball(  Function `tarball`  utility or script function.
L86: def _compose_tarfile_filters(*filters):  Function `_compose_tarfile_filters`  utility
or script function.
L87: def compose_two(f1, f2):  Function `compose_two`  utility or script function.
L93: def strip_first_component(  Function `strip_first_component`  utility or script
function.
L104: def _compose(*cmgrs):  Function `_compose`  utility or script function.
L124: def compose_two(inner, outer):  Function `compose_two`  utility or script function.
L125: def composed(*args, **kwargs):  Function `composed`  utility or script function.
L140: def remove_readonly(func, path, exc_info):  Function `remove_readonly`  utility or
script function.
L154: def robust_remover():  Function `robust_remover`  utility or script function.
L163: def temp_dir(remover=shutil.rmtree):  Function `temp_dir`  utility or script function.
L184: def repo_context(  Function `repo_context`  utility or script function.
L210: class ExceptionTrap:  Class (`ExceptionTrap`)  component used by the app (see file
context: None).
L246: def __init__(self, exceptions=(Exception,)):  Function `__init__`  utility or script
function.

```

```

L249: def __enter__(self):    Function `__enter__` utility or script function.
L253: def type(self):        Function `type` utility or script function.
L257: def value(self):        Function `value` utility or script function.
L261: def tb(self):          Function `tb` utility or script function.
L264: def __exit__(self, *exc_info):    Function `__exit__` utility or script function.
L271: def __bool__(self):     Function `__bool__` utility or script function.
L274: def raises(self, func, *, _test=bool):    Function `raises` utility or script function.
L294: def wrapper(*args, **kwargs):    Function `wrapper` utility or script function.
L301: def passes(self, func):    Function `passes` utility or script function.
L323: class suppress(contextlib.suppress, contextlib.ContextDecorator):    Class (`suppress`)
component used by the app (see file context: None).
L334: class on_interrupt(contextlib.ContextDecorator):    Class (`on_interrupt`) component
used by the app (see file context: None).
L355: def __init__(self, action='error', /, code=1):    Function `__init__` utility or script
function.
L359: def __enter__(self):    Function `__enter__` utility or script function.
L362: def __exit__(self, exctype, excinst, exctb):    Function `__exit__` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/autocommand.py

```

L26: def autocommand(    Function `autocommand` utility or script function.
L39: def autocommand_decorator(func):    Function `autocommand_decorator` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/automain.py

```

L22: class AutomainRequiresModuleError(AutocommandError, TypeError):    Class
(`AutomainRequiresModuleError`) component used by the app (see file context: None).
L26: def automain(module, *, args=(), kwargs=None):    Function `automain` utility or script
function.
L38: def main():    Function `main` Entry point / main routine.
L54: def automain_decorator(main):    Function `automain_decorator` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autocommand/autocommand.py

mmand/autoparse.py

```

L31: class AnnotationError(AutocommandError):    Class (`AnnotationError`)    component used by
the app (see file context: None).
L35: class PositionalArgError(AutocommandError):    Class (`PositionalArgError`)    component
used by the app (see file context: None).
L41: class KWArgError(AutocommandError):    Class (`KWArgError`)    component used by the app
(see file context: None).
L45: class DocstringError(AutocommandError):    Class (`DocstringError`)    component used by
the app (see file context: None).
L49: class TooManySplitsError(DocstringError):    Class (`TooManySplitsError`)    component used
by the app (see file context: None).
L57: def _get_type_description(annotation):    Function `_get_type_description`    utility or
script function.
L83: def _add_arguments(param, parser, used_char_args, add_nos):    Function `_add_arguments`
utility or script function.
L191: def make_parser(func_sig, description, epilog, add_nos):    Function `make_parser`
utility or script function.
L215: def parse_docstring(docstring):    Function `parse_docstring`    utility or script
function.
L232: def autoparse(    Function `autoparse`    utility or script function.
L291: def autoparse_wrapper(argv=None):    Function `autoparse_wrapper`    utility or script
function.
L312: def smart_open(filename_or_file, *args, **kwargs):    Function `smart_open`    utility or
script function.
L323: def work_with_file(name=sys.stdout):    Function `work_with_file`    utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autoco mmand/autoasync.py

```

L54: def autoasync(coro=None, *, loop=None, forever=False, pass_loop=False):    Function
`autoasync`    utility or script function.
L84: def get_file(host, port):    Function `get_file`    Returns or fetches data.
L92: def server(host, port, loop):    Function `server`    utility or script function.
L115: def autoasync_wrapper(*args, **kwargs):    Function `autoasync_wrapper`    utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/autoco mmand/errors.py

```
L19: class AutocommandError(Exception):  Class (`AutocommandError`)  component used by the
app (see file context: None).
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_bdist_wheel.py

```
L50: def safe_name(name: str) -> str:  Function `safe_name`  utility or script function.
L57: def safe_version(version: str) -> str:  Function `safe_version`  utility or script
function.
L74: def _is_32bit_interpreter() -> bool:  Function `_is_32bit_interpreter`  utility or
script function.
L78: def python_tag() -> str:  Function `python_tag`  utility or script function.
L82: def get_platform(archive_root: str | None) -> str:  Function `get_platform`  Returns or
fetches data.
L102: def get_flag(  Function `get_flag`  Returns or fetches data.
L119: def get_abi_tag() -> str | None:  Function `get_abi_tag`  Returns or fetches data.
L159: def safer_name(name: str) -> str:  Function `safer_name`  utility or script function.
L163: def safer_version(version: str) -> str:  Function `safer_version`  utility or script
function.
L167: def remove_readonly(  Function `remove_readonly`  utility or script function.
L175: def remove_readonly_exc(func: Callable[..., object], path: str, exc: Exception) ->
None:  Object (singleton).
L180: class bdist_wheel(Command):  Class (`bdist_wheel`)  component used by the app (see
file context: None).
L248: def initialize_options(self):  Function `initialize_options`  Initialisation routine.
L269: def finalize_options(self):  Function `finalize_options`  utility or script function.
L313: def wheel_dist_name(self):  Function `wheel_dist_name`  utility or script function.
L323: def get_tag(self) -> tuple[str, str, str]:  Function `get_tag`  Returns or fetches
data.
L381: def run(self):  Function `run`  utility or script function.
L471: def write_wheelfile(  Function `write_wheelfile`  utility or script function.
L495: def _ensure_relative(self, path: str) -> str:  Function `_ensure_relative`  utility or
script function.
L503: def license_paths(self) -> Iterable[str]:  Function `license_paths`  utility or script
function.
L547: def egg2dist(self, egginfo_path: str, distinfo_path: str):  Function `egg2dist`
utility or script function.
L550: def adios(p: str) -> None:  Function `adios`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_metadata.py

```

L20: def _nonblank(str: str) -> bool | Literal[""]:  Function `_nonblank` utility or script
function.
L25: def yield_lines(iterable: Iterable[str]) -> Iterator[str]:  Function `yield_lines`
utility or script function.
L43: def _(text: str) -> Iterator[str]:  Function `_` utility or script function.
L47: def split_sections(  Function `split_sections` utility or script function.
L74: def safe_extra(extra: str) -> str:  Function `safe_extra` utility or script function.
L82: def safe_name(name: str) -> str:  Function `safe_name` utility or script function.
L89: def requires_to_requires_dist(requirement: Requirement) -> str:  Function
`requires_to_requires_dist` utility or script function.
L104: def convert_requirements(requirements: list[str]) -> Iterator[str]:  Function
`convert_requirements` utility or script function.
L116: def generate_requirements(  Function `generate_requirements` Generates content (often
AI-generated).
L147: def pkginfo_to_metadata(egg_info_path: str, pkginfo_path: str) -> Message:  Function
`pkginfo_to_metadata` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/
__main__.py

```

L11: def main() -> NoReturn:  # needed for console script  Function `main` Entry point /
main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/
macosx_libfile.py

```

L252: def swap32(x: int) -> int:  Function `swap32` utility or script function.
L261: def get_base_class_and_magic_number(  Function `get_base_class_and_magic_number`
Returns or fetches data.
L288: def read_data(struct_class: type[ctypes.Structure], lib_file: BufferedIOBase):
Function `read_data` utility or script function.
L292: def extract_macosx_min_system_version(path_to_lib: str):  Function
`extract_macosx_min_system_version` utility or script function.
L300: class FatHeader(BaseClass):  Class (`FatHeader`) component used by the app (see file
context: None).
L306: class FatArch(BaseClass):  Class (`FatArch`) component used by the app (see file
context: None).
L311: class FatArch(BaseClass):  Class (`FatArch`) component used by the app (see file
context: None).
L350: def read_mach_header(  Function `read_mach_header` utility or script function.
L363: class SegmentBase(base_class):  Class (`SegmentBase`) component used by the app (see
file context: None).

```

```

L368: class MachHeader(base_class):    Class (`MachHeader`)    component used by the app (see
file context: None).
L373: class MachHeader(base_class):    Class (`MachHeader`)    component used by the app (see
file context: None).
L383: class VersionMinCommand(base_class):    Class (`VersionMinCommand`)    component used by
the app (see file context: None).
L390: class VersionBuild(base_class):    Class (`VersionBuild`)    component used by the app
(see file context: None).
L400: def parse_version(version: int) -> tuple[int, int, int]:    Function `parse_version`
utility or script function.
L407: def calculate_macosx_platform_tag(archive_root: StrPath, platform_tag: str) -> str:
Function `calculate_macosx_platform_tag`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_setuptools_logging.py

```

L8: def _not_warning(record: logging.LogRecord) -> bool:    Function `_not_warning`    utility
or script function.
L12: def configure() -> None:    Function `configure`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/wheelfile.py

```

L33: class WheelError(Exception):    Class (`WheelError`)    component used by the app (see file
context: None).
L37: def urlsafe_b64encode(data: bytes) -> bytes:    Function `urlsafe_b64encode`    utility or
script function.
L42: def urlsafe_b64decode(data: bytes) -> bytes:    Function `urlsafe_b64decode`    utility or
script function.
L48: def get_zipinfo_datetime(    Function `get_zipinfo_datetime`    Returns or fetches data.
L58: class WheelFile(ZipFile):    Class (`WheelFile`)    component used by the app (see file
context: None).
L65: def __init__(    Function `__init__`    utility or script function.
L123: def open(    Function `open`    utility or script function.
L129: def _update_crc(newdata: bytes) -> None:    Function `_update_crc`    utility or script
function.
L157: def write_files(self, base_dir: str) -> None:    Function `write_files`    utility or
script function.
L179: def write(    Function `write`    utility or script function.
L196: def writestr(    Function `writestr`    utility or script function.
L227: def close(self) -> None:    Function `close`    utility or script function.

```


Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/unpack.py

```
L8: def unpack(path: str, dest: str = ".") -> None:    Function `unpack` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/convert.py

```
L49: def convert_requires(requires: str, metadata: Message) -> None:    Function
`convert_requires` utility or script function.
L67: def convert_pkg_info(pkginfo: str, metadata: Message) -> None:    Function
`convert_pkg_info` utility or script function.
L98: def normalize(name: str) -> str:    Function `normalize` utility or script function.
L102: class ConvertSource(metaclass=ABCMeta):    Class (`ConvertSource`) component used by
the app (see file context: None).
L111: def dist_info_dir(self) -> str:    Function `dist_info_dir` utility or script function.
L115: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents` Generates content (often AI-generated).
L119: class EggFileSource(ConvertSource):    Class (`EggFileSource`) component used by the
app (see file context: None).
L120: def __init__(self, path: Path):    Function `__init__` utility or script function.
L136: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents` Generates content (often AI-generated).
L164: class EggDirectorySource(EggFileSource):    Class (`EggDirectorySource`) component used
by the app (see file context: None).
L165: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents` Generates content (often AI-generated).
L193: class WininstFileSource(ConvertSource):    Class (`WininstFileSource`) component used
by the app (see file context: None).
L223: def __init__(self, path: Path):    Function `__init__` utility or script function.
L253: def generate_contents(self) -> Iterator[tuple[str, bytes]]:    Function
`generate_contents` Generates content (often AI-generated).
L287: def convert(files: list[str], dest_dir: str, verbose: bool) -> None:    Function
`convert` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/__init__.py

```

L15: def unpack_f(args: argparse.Namespace) -> None:    Function `unpack_f`  utility or script
function.
L21: def pack_f(args: argparse.Namespace) -> None:     Function `pack_f`  utility or script
function.
L27: def convert_f(args: argparse.Namespace) -> None:   Function `convert_f`  utility or
script function.
L33: def tags_f(args: argparse.Namespace) -> None:     Function `tags_f`  utility or script
function.
L52: def version_f(args: argparse.Namespace) -> None:   Function `version_f`  utility or
script function.
L58: def parse_build_tag(build_tag: str) -> str:        Function `parse_build_tag`  utility or
script function.
L76: def parser() -> argparse.ArgumentParser:         Function `parser`  utility or script
function.
L141: def main() -> int:    Function `main`  Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/pack.py

```

L14: def pack(directory: str, dest_dir: str, build_number: str | None) -> None:    Function
`pack`  utility or script function.
L75: def compute_tagline(tags: list[str]) -> str:    Function `compute_tagline`  utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/wheel/_commands/tags.py

```

L12: def _compute_tags(original_tags: Iterable[str], new_tags: str | None) -> set[str]:
Function `_compute_tags`  utility or script function.
L26: def tags(    Function `tags`  utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/unix.py

```

L18: def getuid() -> NoReturn:    Function `getuid`  Returns or fetches data.
L26: class Unix(PlatformDirsABC): # noqa: PLR0904    Class (`Unix`)  component used by the
app (see file context: None).

```

```

L40: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L51: def _site_data_dirs(self) -> list[str]:    Function `_site_data_dirs` utility or script
function.
L58: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L71: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L82: def _site_config_dirs(self) -> list[str]:    Function `_site_config_dirs` utility or
script function.
L89: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L102: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L113: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L118: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script
function.
L129: def user_log_dir(self) -> str:    Function `user_log_dir` utility or script function.
L138: def user_documents_dir(self) -> str:    Function `user_documents_dir` utility or script
function.
L143: def user_downloads_dir(self) -> str:    Function `user_downloads_dir` utility or script
function.
L148: def user_pictures_dir(self) -> str:    Function `user_pictures_dir` utility or script
function.
L153: def user_videos_dir(self) -> str:    Function `user_videos_dir` utility or script
function.
L158: def user_music_dir(self) -> str:    Function `user_music_dir` utility or script
function.
L163: def user_desktop_dir(self) -> str:    Function `user_desktop_dir` utility or script
function.
L168: def user_runtime_dir(self) -> str:    Function `user_runtime_dir` utility or script
function.
L188: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.
L210: def site_data_path(self) -> Path:    Function `site_data_path` utility or script
function.
L215: def site_config_path(self) -> Path:    Function `site_config_path` utility or script
function.
L220: def site_cache_path(self) -> Path:    Function `site_cache_path` utility or script
function.
L224: def iter_config_dirs(self) -> Iterator[str]:    Function `iter_config_dirs` utility or
script function.
L229: def iter_data_dirs(self) -> Iterator[str]:    Function `iter_data_dirs` utility or
script function.
L235: def _get_user_media_dir(env_var: str, fallback_tilde_path: str) -> str:    Function
`_get_user_media_dir` utility or script function.
L245: def _get_user_dirs_folder(key: str) -> str | None:    Function `_get_user_dirs_folder`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/___main___.py

L26: def main() -> None: Function `main` Entry point / main routine.

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/api.py

```
L15: class PlatformDirsABC(ABC): # noqa: PLR0904 Class (`PlatformDirsABC`) component used
    by the app (see file context: None).
L18: def __init__( # noqa: PLR0913, PLR0917 Function `__init__` utility or script
    function.
L81: def _append_app_name_and_version(self, *base: str) -> str: Function
    `_append_app_name_and_version` utility or script function.
L91: def _optionally_create_directory(self, path: str) -> None: Function
    `_optionally_create_directory` utility or script function.
L95: def _first_item_as_path_if_multipath(self, directory: str) -> Path: Function
    `_first_item_as_path_if_multipath` utility or script function.
L103: def user_data_dir(self) -> str: Function `user_data_dir` utility or script function.
L108: def site_data_dir(self) -> str: Function `site_data_dir` utility or script function.
L113: def user_config_dir(self) -> str: Function `user_config_dir` utility or script
    function.
L118: def site_config_dir(self) -> str: Function `site_config_dir` utility or script
    function.
L123: def user_cache_dir(self) -> str: Function `user_cache_dir` utility or script
    function.
L128: def site_cache_dir(self) -> str: Function `site_cache_dir` utility or script
    function.
L133: def user_state_dir(self) -> str: Function `user_state_dir` utility or script
    function.
L138: def user_log_dir(self) -> str: Function `user_log_dir` utility or script function.
L143: def user_documents_dir(self) -> str: Function `user_documents_dir` utility or script
    function.
L148: def user_downloads_dir(self) -> str: Function `user_downloads_dir` utility or script
    function.
L153: def user_pictures_dir(self) -> str: Function `user_pictures_dir` utility or script
    function.
L158: def user_videos_dir(self) -> str: Function `user_videos_dir` utility or script
    function.
L163: def user_music_dir(self) -> str: Function `user_music_dir` utility or script
    function.
L168: def user_desktop_dir(self) -> str: Function `user_desktop_dir` utility or script
    function.
L173: def user_runtime_dir(self) -> str: Function `user_runtime_dir` utility or script
    function.
```

```

L178: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.
L182: def user_data_path(self) -> Path:     Function `user_data_path` utility or script
function.
L187: def site_data_path(self) -> Path:     Function `site_data_path` utility or script
function.
L192: def user_config_path(self) -> Path:   Function `user_config_path` utility or script
function.
L197: def site_config_path(self) -> Path:   Function `site_config_path` utility or script
function.
L202: def user_cache_path(self) -> Path:    Function `user_cache_path` utility or script
function.
L207: def site_cache_path(self) -> Path:    Function `site_cache_path` utility or script
function.
L212: def user_state_path(self) -> Path:    Function `user_state_path` utility or script
function.
L217: def user_log_path(self) -> Path:     Function `user_log_path` utility or script
function.
L222: def user_documents_path(self) -> Path: Function `user_documents_path` utility or
script function.
L227: def user_downloads_path(self) -> Path: Function `user_downloads_path` utility or
script function.
L232: def user_pictures_path(self) -> Path: Function `user_pictures_path` utility or
script function.
L237: def user_videos_path(self) -> Path:   Function `user_videos_path` utility or script
function.
L242: def user_music_path(self) -> Path:    Function `user_music_path` utility or script
function.
L247: def user_desktop_path(self) -> Path:  Function `user_desktop_path` utility or script
function.
L252: def user_runtime_path(self) -> Path:  Function `user_runtime_path` utility or script
function.
L257: def site_runtime_path(self) -> Path:  Function `site_runtime_path` utility or script
function.
L261: def iter_config_dirs(self) -> Iterator[str]: Function `iter_config_dirs` utility or
script function.
L266: def iter_data_dirs(self) -> Iterator[str]: Function `iter_data_dirs` utility or
script function.
L271: def iter_cache_dirs(self) -> Iterator[str]: Function `iter_cache_dirs` utility or
script function.
L276: def iter_runtime_dirs(self) -> Iterator[str]: Function `iter_runtime_dirs` utility
or script function.
L281: def iter_config_paths(self) -> Iterator[Path]: Function `iter_config_paths` utility
or script function.
L286: def iter_data_paths(self) -> Iterator[Path]: Function `iter_data_paths` utility or
script function.
L291: def iter_cache_paths(self) -> Iterator[Path]: Function `iter_cache_paths` utility or
script function.
L296: def iter_runtime_paths(self) -> Iterator[Path]: Function `iter_runtime_paths`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/___init___py

```

L30: def _set_platform_dir_class() -> type[PlatformDirsABC]:    Function
`_set_platform_dir_class`    utility or script function.
L53: def user_data_dir(    Function `user_data_dir`    utility or script function.
L77: def site_data_dir(    Function `site_data_dir`    utility or script function.
L101: def user_config_dir(    Function `user_config_dir`    utility or script function.
L125: def site_config_dir(    Function `site_config_dir`    utility or script function.
L149: def user_cache_dir(    Function `user_cache_dir`    utility or script function.
L173: def site_cache_dir(    Function `site_cache_dir`    utility or script function.
L197: def user_state_dir(    Function `user_state_dir`    utility or script function.
L221: def user_log_dir(    Function `user_log_dir`    utility or script function.
L245: def user_documents_dir() -> str:    Function `user_documents_dir`    utility or script
function.
L250: def user_downloads_dir() -> str:    Function `user_downloads_dir`    utility or script
function.
L255: def user_pictures_dir() -> str:    Function `user_pictures_dir`    utility or script
function.
L260: def user_videos_dir() -> str:    Function `user_videos_dir`    utility or script function.
L265: def user_music_dir() -> str:    Function `user_music_dir`    utility or script function.
L270: def user_desktop_dir() -> str:    Function `user_desktop_dir`    utility or script
function.
L275: def user_runtime_dir(    Function `user_runtime_dir`    utility or script function.
L299: def site_runtime_dir(    Function `site_runtime_dir`    utility or script function.
L323: def user_data_path(    Function `user_data_path`    utility or script function.
L347: def site_data_path(    Function `site_data_path`    utility or script function.
L371: def user_config_path(    Function `user_config_path`    utility or script function.
L395: def site_config_path(    Function `site_config_path`    utility or script function.
L419: def site_cache_path(    Function `site_cache_path`    utility or script function.
L443: def user_cache_path(    Function `user_cache_path`    utility or script function.
L467: def user_state_path(    Function `user_state_path`    utility or script function.
L491: def user_log_path(    Function `user_log_path`    utility or script function.
L515: def user_documents_path() -> Path:    Function `user_documents_path`    utility or script
function.
L520: def user_downloads_path() -> Path:    Function `user_downloads_path`    utility or script
function.
L525: def user_pictures_path() -> Path:    Function `user_pictures_path`    utility or script
function.
L530: def user_videos_path() -> Path:    Function `user_videos_path`    utility or script
function.
L535: def user_music_path() -> Path:    Function `user_music_path`    utility or script
function.
L540: def user_desktop_path() -> Path:    Function `user_desktop_path`    utility or script
function.
L545: def user_runtime_path(    Function `user_runtime_path`    utility or script function.
L569: def site_runtime_path(    Function `site_runtime_path`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/android.py

```

L14: class Android(PlatformDirsABC):    Class (`Android`) component used by the app (see file
context: None).
L24: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L29: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L34: def user_config_dir(self) -> str:   Function `user_config_dir` utility or script
function.
L42: def site_config_dir(self) -> str:   Function `site_config_dir` utility or script
function.
L47: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L52: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L57: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script
function.
L62: def user_log_dir(self) -> str:      Function `user_log_dir` utility or script function.
L73: def user_documents_dir(self) -> str: Function `user_documents_dir` utility or script
function.
L78: def user_downloads_dir(self) -> str: Function `user_downloads_dir` utility or script
function.
L83: def user_pictures_dir(self) -> str:  Function `user_pictures_dir` utility or script
function.
L88: def user_videos_dir(self) -> str:    Function `user_videos_dir` utility or script
function.
L93: def user_music_dir(self) -> str:     Function `user_music_dir` utility or script
function.
L98: def user_desktop_dir(self) -> str:   Function `user_desktop_dir` utility or script
function.
L103: def user_runtime_dir(self) -> str:  Function `user_runtime_dir` utility or script
function.
L114: def site_runtime_dir(self) -> str:   Function `site_runtime_dir` utility or script
function.
L120: def _android_folder() -> str | None: # noqa: C901    Function `_android_folder`
utility or script function.
L168: def _android_documents_folder() -> str:    Function `_android_documents_folder` utility
or script function.
L184: def _android_downloads_folder() -> str:    Function `_android_downloads_folder` utility
or script function.
L200: def _android_pictures_folder() -> str:    Function `_android_pictures_folder` utility
or script function.
L216: def _android_videos_folder() -> str:    Function `_android_videos_folder` utility or
script function.
L232: def _android_music_folder() -> str:    Function `_android_music_folder` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/macos.py

```
L15: class MacOS(PlatformDirsABC):    Class (`MacOS`) component used by the app (see file
context: None).
L28: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L33: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L51: def site_data_path(self) -> Path:    Function `site_data_path` utility or script
function.
L56: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L61: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L66: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L71: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L89: def site_cache_path(self) -> Path:    Function `site_cache_path` utility or script
function.
L94: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script
function.
L99: def user_log_dir(self) -> str:    Function `user_log_dir` utility or script function.
L104: def user_documents_dir(self) -> str:    Function `user_documents_dir` utility or script
function.
L109: def user_downloads_dir(self) -> str:    Function `user_downloads_dir` utility or script
function.
L114: def user_pictures_dir(self) -> str:    Function `user_pictures_dir` utility or script
function.
L119: def user_videos_dir(self) -> str:    Function `user_videos_dir` utility or script
function.
L124: def user_music_dir(self) -> str:    Function `user_music_dir` utility or script
function.
L129: def user_desktop_dir(self) -> str:    Function `user_desktop_dir` utility or script
function.
L134: def user_runtime_dir(self) -> str:    Function `user_runtime_dir` utility or script
function.
L139: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/platformdirs/windows.py

```
L16: class Windows(PlatformDirsABC):    Class (`Windows`) component used by the app (see file
```



```

context: None).
L28: def user_data_dir(self) -> str:    Function `user_data_dir`    utility or script function.
L38: def _append_parts(self, path: str, *, opinion_value: str | None = None) -> str:
Function `_append_parts`    utility or script function.
L54: def site_data_dir(self) -> str:    Function `site_data_dir`    utility or script function.
L60: def user_config_dir(self) -> str:    Function `user_config_dir`    utility or script
function.
L65: def site_config_dir(self) -> str:    Function `site_config_dir`    utility or script
function.
L70: def user_cache_dir(self) -> str:    Function `user_cache_dir`    utility or script
function.
L79: def site_cache_dir(self) -> str:    Function `site_cache_dir`    utility or script
function.
L85: def user_state_dir(self) -> str:    Function `user_state_dir`    utility or script
function.
L90: def user_log_dir(self) -> str:    Function `user_log_dir`    utility or script function.
L99: def user_documents_dir(self) -> str:    Function `user_documents_dir`    utility or script
function.
L104: def user_downloads_dir(self) -> str:    Function `user_downloads_dir`    utility or script
function.
L109: def user_pictures_dir(self) -> str:    Function `user_pictures_dir`    utility or script
function.
L114: def user_videos_dir(self) -> str:    Function `user_videos_dir`    utility or script
function.
L119: def user_music_dir(self) -> str:    Function `user_music_dir`    utility or script
function.
L124: def user_desktop_dir(self) -> str:    Function `user_desktop_dir`    utility or script
function.
L129: def user_runtime_dir(self) -> str:    Function `user_runtime_dir`    utility or script
function.
L138: def site_runtime_dir(self) -> str:    Function `site_runtime_dir`    utility or script
function.
L143: def get_win_folder_from_env_vars(csidl_name: str) -> str:    Function
`get_win_folder_from_env_vars`    Returns or fetches data.
L164: def get_win_folder_if_csidl_name_not_env_var(csidl_name: str) -> str | None:    Function
`get_win_folder_if_csidl_name_not_env_var`    Returns or fetches data.
L183: def get_win_folder_from_registry(csidl_name: str) -> str:    Function
`get_win_folder_from_registry`    Returns or fetches data.
L213: def get_win_folder_via_ctypes(csidl_name: str) -> str:    Function
`get_win_folder_via_ctypes`    Returns or fetches data.
L252: def _pick_get_win_folder() -> Callable[[str], str]:    Function `_pick_get_win_folder`
utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl/glob.py

```

L9: class Translator:  Class (`Translator`)  component used by the app (see file context:
None).
L24: def __init__(self, seps: str = _default_seps):  Function `__init__`  utility or script
function.
L28: def translate(self, pattern):  Function `translate`  utility or script function.
L35: def extend(self, pattern):  Function `extend`  utility or script function.
L46: def match_dirs(self, pattern):  Function `match_dirs`  utility or script function.
L54: def translate_core(self, pattern):  Function `translate_core`  utility or script
function.
L69: def replace(self, match):  Function `replace`  utility or script function.
L80: def restrict_rglob(self, pattern):  Function `restrict_rglob`  utility or script
function.
L94: def star_not_empty(self, pattern):  Function `star_not_empty`  utility or script
function.
L99: def handle_segment(match):  Function `handle_segment`  utility or script function.
L107: def separate(pattern):  Function `separate`  utility or script function.

```

Q_base

**appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl__
init__.py**

```

L27: def _parents(path):  Function `_parents`  utility or script function.
L46: def _ancestry(path):  Function `_ancestry`  utility or script function.
L77: def _difference(minuend, subtrahend):  Function `_difference`  utility or script
function.
L85: class InitializedState:  Class (`InitializedState`)  component used by the app (see
file context: None).
L91: def __init__(self, *args, **kwargs):  Function `__init__`  utility or script function.
L94: def __getstate__(self):  Function `__getstate__`  utility or script function.
L97: def __setstate__(self, state):  Function `__setstate__`  utility or script function.
L102: class CompleteDirs(InitializedState, zipfile.ZipFile):  Class (`CompleteDirs`)
component used by the app (see file context: None).
L114: def _implied_dirs(names):  Function `_implied_dirs`  utility or script function.
L119: def namelist(self):  Function `namelist`  utility or script function.
L123: def _name_set(self):  Function `_name_set`  utility or script function.
L126: def resolve_dir(self, name):  Function `resolve_dir`  utility or script function.
L136: def getinfo(self, name):  Function `getinfo`  Returns or fetches data.
L148: def make(cls, source):  Function `make`  utility or script function.
L167: def inject(cls, zf: zipfile.ZipFile) -> zipfile.ZipFile:  Function `inject`  utility
or script function.
L177: class FastLookup(CompleteDirs):  Class (`FastLookup`)  component used by the app (see
file context: None).
L183: def namelist(self):  Function `namelist`  utility or script function.
L187: def _namelist(self):  Function `_namelist`  utility or script function.
L190: def _name_set(self):  Function `_name_set`  utility or script function.
L194: def _name_set_prop(self):  Function `_name_set_prop`  utility or script function.
L198: def _extract_text_encoding(encoding=None, *args, **kwargs):  Function

```

```

`_extract_text_encoding` utility or script function.
L208: class Path: Class (`Path`) component used by the app (see file context: None).
L313: def __init__(self, root, at=""): Function `_init__` utility or script function.
L326: def __eq__(self, other): Function `_eq__` utility or script function.
L335: def __hash__(self): Function `_hash__` utility or script function.
L338: def open(self, mode='r', *args, pwd=None, **kwargs): Function `open` utility or
script function.
L358: def _base(self): Function `_base` utility or script function.
L362: def name(self): Function `name` utility or script function.
L366: def suffix(self): Function `suffix` utility or script function.
L370: def suffixes(self): Function `suffixes` utility or script function.
L374: def stem(self): Function `stem` utility or script function.
L378: def filename(self): Function `filename` utility or script function.
L381: def read_text(self, *args, **kwargs): Function `read_text` utility or script
function.
L386: def read_bytes(self): Function `read_bytes` utility or script function.
L390: def _is_child(self, path): Function `_is_child` utility or script function.
L393: def _next(self, at): Function `_next` utility or script function.
L396: def is_dir(self): Function `is_dir` utility or script function.
L399: def is_file(self): Function `is_file` utility or script function.
L402: def exists(self): Function `exists` utility or script function.
L405: def iterdir(self): Function `iterdir` utility or script function.
L411: def match(self, path_pattern): Function `match` utility or script function.
L414: def is_symlink(self): Function `is_symlink` utility or script function.
L422: def glob(self, pattern): Function `glob` utility or script function.
L431: def rglob(self, pattern): Function `rglob` utility or script function.
L434: def relative_to(self, other, *extra): Function `relative_to` utility or script
function.
L437: def __str__(self): Function `_str__` utility or script function.
L440: def __repr__(self): Function `_repr__` utility or script function.
L443: def joinpath(self, *other): Function `joinpath` utility or script function.
L450: def parent(self): Function `parent` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl/_functools.py

```

L6: def save_method_args(method): Function `save_method_args` Saves data to storage or
remote.
L14: def wrapper(self, /, *args, **kwargs): Function `wrapper` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zippl/compat/py313.py

```

L6: def identity(x):    Function `identity` utility or script function.
L11: def apply(transform):    Function `apply` utility or script function.
L12: def wrap(func):    Function `wrap` utility or script function.
L19: def compose(*funcs):    Function `compose` utility or script function.
L20: def compose_two(f1, f2):    Function `compose_two` utility or script function.
L26: def replace(pattern):    Function `replace` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zipper/compat/py310.py

```

L5: def _text_encoding(encoding, stacklevel=2, /):    # pragma: no cover    Function
`_text_encoding` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/zipper/compat/overlay.py

```

L28: class HashableNamespace(types.SimpleNamespace):    Class (`HashableNamespace`) component
used by the app (see file context: None).
L29: def __hash__(self):    Function `__hash__` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/tomli/_parser.py

```

L71: class DEPRECATED_DEFAULT:    Class (`DEPRECATED_DEFAULT`) component used by the app (see
file context: None).
L76: class TOMLDecodeError(ValueError):    Class (`TOMLDecodeError`) component used by the
app (see file context: None).
L87: def __init__(    Function `__init__` utility or script function.
L137: def load(__fp: IO[bytes], *, parse_float: ParseFloat = float) -> dict[str, Any]:
Function `load` Loads data from storage or remote.
L149: def loads(__s: str, *, parse_float: ParseFloat = float) -> dict[str, Any]:    Function
`loads` Loads data from storage or remote.
L220: class Flags:    Class (`Flags`) component used by the app (see file context: None).
L229: def __init__(self) -> None:    Function `__init__` utility or script function.
L233: def add_pending(self, key: Key, flag: int) -> None:    Function `add_pending` utility
or script function.
L236: def finalize_pending(self) -> None:    Function `finalize_pending` utility or script

```

```

function.
L241: def unset_all(self, key: Key) -> None:    Function `unset_all` utility or script
function.
L249: def set(self, key: Key, flag: int, *, recursive: bool) -> None:    # noqa: A003
Function `set` Sets or updates a value.
L260: def is_(self, key: Key, flag: int) -> bool:    Function `is_` utility or script
function.
L278: class NestedDict:    Class (`NestedDict`) component used by the app (see file context:
None).
L279: def __init__(self) -> None:    Function `__init__` utility or script function.
L283: def get_or_create_nest(    Function `get_or_create_nest` Returns or fetches data.
L300: def append_nest_to_list(self, key: Key) -> None:    Function `append_nest_to_list`
utility or script function.
L312: class Output:    Class (`Output`) component used by the app (see file context: None).
L313: def __init__(self) -> None:    Function `__init__` utility or script function.
L318: def skip_chars(src: str, pos: Pos, chars: Iterable[str]) -> Pos:    Function
`skip_chars` utility or script function.
L327: def skip_until(    Function `skip_until` utility or script function.
L349: def skip_comment(src: str, pos: Pos) -> Pos:    Function `skip_comment` utility or
script function.
L361: def skip_comments_and_array_ws(src: str, pos: Pos) -> Pos:    Function
`skip_comments_and_array_ws` utility or script function.
L370: def create_dict_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:    Function
`create_dict_rule` Creates a resource or document.
L390: def create_list_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]:    Function
`create_list_rule` Creates a resource or document.
L413: def key_value_rule(    Function `key_value_rule` utility or script function.
L447: def parse_key_value_pair(    Function `parse_key_value_pair` utility or script
function.
L463: def parse_key(src: str, pos: Pos) -> tuple[Pos, Key]:    Function `parse_key` utility
or script function.
L481: def parse_key_part(src: str, pos: Pos) -> tuple[Pos, str]:    Function `parse_key_part`
utility or script function.
L497: def parse_one_line_basic_str(src: str, pos: Pos) -> tuple[Pos, str]:    Function
`parse_one_line_basic_str` utility or script function.
L502: def parse_array(    Function `parse_array` utility or script function.
L528: def parse_inline_table(    Function `parse_inline_table` utility or script function.
L564: def parse_basic_str_escape(    Function `parse_basic_str_escape` utility or script
function.
L595: def parse_basic_str_escape_multiline(src: str, pos: Pos) -> tuple[Pos, str]:    Function
`parse_basic_str_escape_multiline` utility or script function.
L599: def parse_hex_char(src: str, pos: Pos, hex_len: int) -> tuple[Pos, str]:    Function
`parse_hex_char` utility or script function.
L612: def parse_literal_str(src: str, pos: Pos) -> tuple[Pos, str]:    Function
`parse_literal_str` utility or script function.
L621: def parse_multiline_str(src: str, pos: Pos, *, literal: bool) -> tuple[Pos, str]:
Function `parse_multiline_str` utility or script function.
L652: def parse_basic_str(src: str, pos: Pos, *, multiline: bool) -> tuple[Pos, str]:
Function `parse_basic_str` utility or script function.
L684: def parse_value(    Function `parse_value` utility or script function.
L760: def is_unicode_scalar_value(codepoint: int) -> bool:    Function

```

```
`is_unicode_scalar_value` utility or script function.
L764: def make_safe_parse_float(parse_float: ParseFloat) -> ParseFloat: Function
`make_safe_parse_float` utility or script function.
L776: def safe_parse_float(float_str: str) -> Any: Function `safe_parse_float` utility or
script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/tomli/_re.py

```
L59: def match_to_datetime(match: re.Match[str]) -> datetime | date: Function
`match_to_datetime` utility or script function.
L99: def cached_tz(hour_str: str, minute_str: str, sign_str: str) -> timezone: Function
`cached_tz` utility or script function.
L109: def match_to_localtime(match: re.Match[str]) -> time: Function `match_to_localtime`
utility or script function.
L116: def match_to_number(match: re.Match[str], parse_float: ParseFloat) -> Any: Function
`match_to_number` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/more_itertools/more.py

```
L189: def dl_split(x: float): Function `dl_split` utility or script function.
L196: def dl_mul(x, y): Function `dl_mul` utility or script function.
L206: def fsumprod(p, q): Function `_fsumprod` utility or script function.
L210: def chunked(iterable, n, strict=False): Function `chunked` utility or script
function.
L234: def ret(): Function `ret` utility or script function.
L245: def first(iterable, default=_marker): Function `first` utility or script function.
L272: def last(iterable, default=_marker): Function `last` utility or script function.
L300: def nth_or_last(iterable, n, default=_marker): Function `nth_or_last` utility or
script function.
L317: class peekable: Class (`peekable`) component used by the app (see file context:
None).
L376: def __init__(self, iterable): Function `__init__` utility or script function.
L380: def __iter__(self): Function `__iter__` utility or script function.
L383: def __bool__(self): Function `__bool__` utility or script function.
L390: def peek(self, default=_marker): Function `peek` utility or script function.
L406: def prepend(self, *items): Function `prepend` utility or script function.
L437: def __next__(self): Function `__next__` utility or script function.
L443: def _get_slice(self, index): Function `_get_slice` utility or script function.
L469: def __getitem__(self, index): Function `__getitem__` utility or script function.
L482: def consumer(func): Function `consumer` utility or script function.
```

```

L506: def wrapper(*args, **kwargs):  Function `wrapper` utility or script function.
L514: def ilen(iterable):  Function `ilen` utility or script function.
L524: def ilen(iterable):  Function `ilen` utility or script function.
L539: def iterate(func, start):  Function `iterate` utility or script function.
L559: def with_iter(context_manager):  Function `with_iter` utility or script function.
L574: def one(iterable, too_short=None, too_long=None):  Function `one` utility or script
function.
L630: def raise_(exception, *args):  Function `raise_` utility or script function.
L634: def strictly_n(iterable, n, too_short=None, too_long=None):  Function `strictly_n`
utility or script function.
L709: def distinct_permutations(iterable, r=None):  Function `distinct_permutations`
utility or script function.
L754: def _full(A):  Function `_full` utility or script function.
L778: def _partial(A, r):  Function `_partial` utility or script function.
L835: def permuted_items(permuted_indices):  Function `permuted_items` utility or script
function.
L859: def derangements(iterable, r=None):  Function `derangements` utility or script
function.
L921: def intersperse(e, iterable, n=1):  Function `intersperse` utility or script
function.
L947: def unique_to_each(*iterables):  Function `unique_to_each` utility or script
function.
L980: def windowed(seq, n, fillvalue=None, step=1):  Function `windowed` utility or script
function.
L1038: def substrings(iterable):  Function `substrings` utility or script function.
L1064: def substrings_indexes(seq, reverse=False):  Function `substrings_indexes` utility
or script function.
L1098: class bucket:  Class (`bucket`) component used by the app (see file context: None).
L1134: def __init__(self, iterable, key, validator=None):  Function `__init__` utility or
script function.
L1140: def __contains__(self, value):  Function `__contains__` utility or script function.
L1153: def _get_values(self, value):  Function `_get_values` utility or script function.
L1179: def __iter__(self):  Function `__iter__` utility or script function.
L1187: def __getitem__(self, value):  Function `__getitem__` utility or script function.
L1194: def spy(iterable, n=1):  Function `spy` utility or script function.
L1235: def interleave(*iterables):  Function `interleave` utility or script function.
L1249: def interleave_longest(*iterables):  Function `interleave_longest` utility or script
function.
L1267: def interleave_evenly(iterables, lengths=None):  Function `interleave_evenly`
utility or script function.
L1333: def interleave_randomly(*iterables):  Function `interleave_randomly` utility or
script function.
L1356: def collapse(iterable, base_type=None, levels=None):  Function `collapse` utility or
script function.
L1416: def side_effect(func, iterable, chunk_size=None, before=None, after=None):  Function
`side_effect` utility or script function.
L1477: def sliced(seq, n, strict=False):  Function `sliced` utility or script function.
L1500: def ret():  Function `ret` utility or script function.
L1511: def split_at(iterable, pred, maxsplit=-1, keep_separator=False):  Function `split_at`
utility or script function.
L1555: def split_before(iterable, pred, maxsplit=-1):  Function `split_before` utility or

```

```

script function.
L1590: def split_after(iterable, pred, maxsplit=-1):  Function `split_after`  utility or
script function.
L1628: def split_when(iterable, pred, maxsplit=-1):  Function `split_when`  utility or
script function.
L1673: def split_into(iterable, sizes):  Function `split_into`  utility or script function.
L1718: def padded(iterable, fillvalue=None, n=None, next_multiple=False):  Function `padded`
utility or script function.
L1751: def slice_generator():  Function `slice_generator`  utility or script function.
L1763: def repeat_each(iterable, n=2):  Function `repeat_each`  utility or script function.
L1772: def repeat_last(iterable, default=None):  Function `repeat_last`  utility or script
function.
L1791: def distribute(n, iterable):  Function `distribute`  utility or script function.
L1828: def stagger(iterable, offsets=(-1, 0, 1), longest=False, fillvalue=None):  Function
`stagger`  utility or script function.
L1856: def zip_equal(*iterables):  Function `zip_equal`  utility or script function.
L1887: def zip_offset(*iterables, offsets, longest=False, fillvalue=None):  Function
`zip_offset`  utility or script function.
L1926: def sort_together(  Function `sort_together`  utility or script function.
L1999: def unzip(iterable):  Function `unzip`  utility or script function.
L2040: def divide(n, iterable):  Function `divide`  utility or script function.
L2091: def always_iterable(obj, base_type=(str, bytes)):  Function `always_iterable`
utility or script function.
L2144: def adjacent(predicate, iterable, distance=1):  Function `adjacent`  utility or
script function.
L2183: def groupby_transform(iterable, keyfunc=None, valuefunc=None, reducefunc=None):
Function `groupby_transform`  utility or script function.
L2228: class numeric_range(abc.Sequence, abc.Hashable):  Class (`numeric_range`)  component
used by the app (see file context: None).
L2282: def __init__(self, *args):  Function `__init__`  utility or script function.
L2307: def __bool__(self):  Function `__bool__`  utility or script function.
L2313: def __contains__(self, elem):  Function `__contains__`  utility or script function.
L2323: def __eq__(self, other):  Function `__eq__`  utility or script function.
L2338: def __getitem__(self, key):  Function `__getitem__`  utility or script function.
L2365: def __hash__(self):  Function `__hash__`  utility or script function.
L2371: def __iter__(self):  Function `__iter__`  utility or script function.
L2378: def __len__(self):  Function `__len__`  utility or script function.
L2382: def _len(self):  Function `_len`  utility or script function.
L2398: def __reduce__(self):  Function `__reduce__`  utility or script function.
L2401: def __repr__(self):  Function `__repr__`  utility or script function.
L2408: def __reversed__(self):  Function `__reversed__`  utility or script function.
L2415: def count(self, value):  Function `count`  utility or script function.
L2418: def index(self, value):  Function `index`  utility or script function.
L2432: def _get_by_index(self, i):  Function `_get_by_index`  utility or script function.
L2440: def count_cycle(iterable, n=None):  Function `count_cycle`  utility or script
function.
L2456: def mark_ends(iterable):  Function `mark_ends`  utility or script function.
L2486: def locate(iterable, pred=bool, window_size=None):  Function `locate`  utility or
script function.
L2534: def longest_common_prefix(iterables):  Function `longest_common_prefix`  utility or
script function.

```



```

L2544: def lstrip(iterable, pred):    Function `lstrip` utility or script function.
L2562: def rstrip(iterable, pred):    Function `rstrip` utility or script function.
L2588: def strip(iterable, pred):     Function `strip` utility or script function.
L2605: class islice_extended:        Class (`islice_extended`) component used by the app (see
file context: None).
L2631: def __init__(self, iterable, *args):    Function `__init__` utility or script
function.
L2638: def __iter__(self):             Function `__iter__` utility or script function.
L2641: def __next__(self):             Function `__next__` utility or script function.
L2644: def __getitem__(self, key):      Function `__getitem__` utility or script function.
L2651: def _islice_helper(it, s):       Function `_islice_helper` utility or script function.
L2759: def always_reversible(iterable):    Function `always_reversible` utility or script
function.
L2777: def consecutive_groups(iterable, ordering=None):    Function `consecutive_groups`
utility or script function.
L2827: def difference(iterable, func=sub, *, initial=None):    Function `difference` utility
or script function.
L2869: class SequenceView(Sequence):    Class (`SequenceView`) component used by the app (see
file context: None).
L2899: def __init__(self, target):      Function `__init__` utility or script function.
L2904: def __getitem__(self, index):    Function `__getitem__` utility or script function.
L2907: def __len__(self):              Function `__len__` utility or script function.
L2910: def __repr__(self):             Function `__repr__` utility or script function.
L2914: class seekable:                Class (`seekable`) component used by the app (see file context:
None).
L3015: def __init__(self, iterable, maxlen=None):    Function `__init__` utility or script
function.
L3023: def __iter__(self):             Function `__iter__` utility or script function.
L3026: def __next__(self):             Function `__next__` utility or script function.
L3040: def __bool__(self):             Function `__bool__` utility or script function.
L3047: def peek(self, default=_marker):    Function `peek` utility or script function.
L3059: def elements(self):             Function `elements` utility or script function.
L3062: def seek(self, index):          Function `seek` utility or script function.
L3068: def relative_seek(self, count):    Function `relative_seek` utility or script
function.
L3075: class run_length:              Class (`run_length`) component used by the app (see file context:
None).
L3096: def encode(iterable):          Function `encode` utility or script function.
L3100: def decode(iterable):          Function `decode` utility or script function.
L3104: def exactly_n(iterable, n, predicate=bool):    Function `exactly_n` utility or script
function.
L3122: def circular_shifts(iterable, steps=1):    Function `circular_shifts` utility or
script function.
L3152: def make_decorator(wrapping_func, result_index=0):    Function `make_decorator`
utility or script function.
L3203: def decorator(*wrapping_args, **wrapping_kwargs):    Function `decorator` utility or
script function.
L3204: def outer_wrapper(f):          Function `outer_wrapper` utility or script function.
L3205: def inner_wrapper(*args, **kwargs):    Function `inner_wrapper` utility or script
function.
L3218: def map_reduce(iterable, keyfunc, valuefunc=None, reducefunc=None):    Function

```

```

`map_reduce` Maps or converts between representations.
L3291: def rlocate(iterable, pred=bool, window_size=None):  Function `rlocate` utility or
script function.
L3334: def replace(iterable, pred, substitutes, count=None, window_size=1):  Function
`replace` utility or script function.
L3395: def partitions(iterable):  Function `partitions` utility or script function.
L3415: def set_partitions(iterable, k=None, min_size=None, max_size=None):  Function
`set_partitions` Sets or updates a value.
L3469: def set_partitions_helper(L, k):  Function `set_partitions_helper` Sets or updates a
value.
L3496: class time_limited:  Class (`time_limited`) component used by the app (see file
context: None).
L3523: def __init__(self, limit_seconds, iterable):  Function `__init__` utility or script
function.
L3531: def __iter__(self):  Function `__iter__` utility or script function.
L3534: def __next__(self):  Function `__next__` utility or script function.
L3546: def only(iterable, default=None, too_long=None):  Function `only` utility or script
function.
L3583: def _ichunk(iterator, n):  Function `_ichunk` utility or script function.
L3587: def generator():  Function `generator` utility or script function.
L3595: def materialize_next(n=1):  Function `materialize_next` utility or script function.
L3613: def ichunked(iterable, n):  Function `ichunked` utility or script function.
L3649: def iequals(*iterables):  Function `iequals` utility or script function.
L3669: def distinct_combinations(iterable, r):  Function `distinct_combinations` utility or
script function.
L3709: def filter_except(validator, iterable, *exceptions):  Function `filter_except`
utility or script function.
L3733: def map_except(function, iterable, *exceptions):  Function `map_except` Maps or
converts between representations.
L3754: def map_if(iterable, pred, func, func_else=None):  Function `map_if` Maps or
converts between representations.
L3782: def _sample_unweighted(iterator, k, strict):  Function `_sample_unweighted` utility
or script function.
L3802: def _sample_weighted(iterator, k, weights, strict):  Function `_sample_weighted`
utility or script function.
L3841: def _sample_counted(population, k, counts, strict):  Function `_sample_counted`
utility or script function.
L3845: def feed(i):  Function `feed` utility or script function.
L3876: def sample(iterable, k, weights=None, *, counts=None, strict=False):  Function
`sample` utility or script function.
L3959: def is_sorted(iterable, key=None, reverse=False, strict=False):  Function `is_sorted`
utility or script function.
L3991: class AbortThread(BaseException):  Class (`AbortThread`) component used by the app
(see file context: None).
L3995: class callback_iter:  Class (`callback_iter`) component used by the app (see file
context: None).
L4046: def __init__(self, func, callback_kwd='callback', wait_seconds=0.1):  Function
`__init__` utility or script function.
L4058: def __enter__(self):  Function `__enter__` utility or script function.
L4061: def __exit__(self, exc_type, exc_value, traceback):  Function `__exit__` utility or
script function.

```

```

L4065: def __iter__(self):    Function `__iter__` utility or script function.
L4068: def __next__(self):    Function `__next__` utility or script function.
L4072: def done(self):        Function `done` utility or script function.
L4078: def result(self):       Function `result` utility or script function.
L4084: def _reader(self):      Function `_reader` utility or script function.
L4087: def callback(*args, **kwargs):  Function `callback` utility or script function.
L4122: def windowed_complete(iterable, n):  Function `windowed_complete` utility or script
function.
L4162: def all_unique(iterable, key=None):    Function `all_unique` utility or script
function.
L4197: def nth_product(index, *args):    Function `nth_product` utility or script function.
L4228: def nth_permutation(iterable, r, index):  Function `nth_permutation` utility or
script function.
L4272: def nth_combination_with_replacement(iterable, r, index):  Function
`nth_combination_with_replacement` utility or script function.
L4318: def value_chain(*args):    Function `value_chain` utility or script function.
L4352: def product_index(element, *args):  Function `product_index` utility or script
function.
L4377: def combination_index(element, iterable):  Function `combination_index` utility or
script function.
L4420: def combination_with_replacement_index(element, iterable):  Function
`combination_with_replacement_index` utility or script function.
L4477: def permutation_index(element, iterable):  Function `permutation_index` utility or
script function.
L4501: class countable:    Class (`countable`) component used by the app (see file context:
None).
L4519: def __init__(self, iterable):  Function `__init__` utility or script function.
L4523: def __iter__(self):    Function `__iter__` utility or script function.
L4526: def __next__(self):    Function `__next__` utility or script function.
L4533: def chunked_even(iterable, n):  Function `chunked_even` utility or script function.
L4583: def zip_broadcast(*objects, scalar_types=(str, bytes), strict=False):  Function
`zip_broadcast` utility or script function.
L4605: def is_scalar(obj):    Function `is_scalar` utility or script function.
L4639: def unique_in_window(iterable, n, key=None):  Function `unique_in_window` utility or
script function.
L4678: def duplicates_everseen(iterable, key=None):  Function `duplicates_everseen` utility
or script function.
L4708: def duplicates_justseen(iterable, key=None):  Function `duplicates_justseen` utility
or script function.
L4722: def classify_unique(iterable, key=None):  Function `classify_unique` utility or
script function.
L4764: def minmax(iterable_or_value, *others, key=None, default=_marker):  Function `minmax`
utility or script function.
L4841: def constrained_batches(    Function `constrained_batches` utility or script function.
L4891: def gray_product(*iterables):  Function `gray_product` utility or script function.
L4933: def partial_product(*iterables):  Function `partial_product` utility or script
function.
L4958: def takewhile_inclusive(predicate, iterable):  Function `takewhile_inclusive`
utility or script function.
L4972: def outer_product(func, xs, ys, *args, **kwargs):  Function `outer_product` utility
or script function.

```

```

L5005: def iter_suppress(iterable, *exceptions):  Function `iter_suppress` utility or
script function.
L5028: def filter_map(func, iterable):  Function `filter_map` utility or script function.
L5042: def powerset_of_sets(iterable):  Function `powerset_of_sets` utility or script
function.
L5060: def join_mappings(**field_to_map):  Function `join_mappings` utility or script
function.
L5078: def _complex_sumprod(v1, v2):  Function `_complex_sumprod` utility or script
function.
L5092: def dft(xarr):  Function `dft` utility or script function.
L5116: def idft(Xarr):  Function `idft` utility or script function.
L5140: def doublestarmap(func, iterable):  Function `doublestarmap` utility or script
function.
L5158: def _nth_prime_bounds(n):  Function `_nth_prime_bounds` utility or script function.
L5177: def nth_prime(n, *, approximate=False):  Function `nth_prime` utility or script
function.
L5203: def argmin(iterable, *, key=None):  Function `argmin` utility or script function.
L5236: def argmax(iterable, *, key=None):  Function `argmax` utility or script function.
L5264: def extract(iterable, indices):  Function `extract` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/more_ittertools/recipes.py

```

L120: def take(n, iterable):  Function `take` utility or script function.
L136: def tabulate(function, start=0):  Function `tabulate` utility or script function.
L154: def tail(n, iterable):  Function `tail` utility or script function.
L170: def consume(iterator, n=None):  Function `consume` utility or script function.
L210: def nth(iterable, n, default=None):  Function `nth` utility or script function.
L223: def all_equal(iterable, key=None):  Function `all_equal` utility or script function.
L249: def quantify(iterable, pred=bool):  Function `quantify` utility or script function.
L259: def pad_none(iterable):  Function `pad_none` utility or script function.
L276: def ncycles(iterable, n):  Function `ncycles` utility or script function.
L286: def dotproduct(vec1, vec2):  Function `dotproduct` utility or script function.
L299: def flatten(listOfLists):  Function `flatten` utility or script function.
L311: def repeatfunc(func, times=None, *args):  Function `repeatfunc` utility or script
function.
L338: def _pairwise(iterable):  Function `_pairwise` utility or script function.
L358: def pairwise(iterable):  Function `pairwise` utility or script function.
L364: class UnequalIterablesError(ValueError):  Class (`UnequalIterablesError`) component
used by the app (see file context: None).
L365: def __init__(self, details=None):  Function `__init__` utility or script function.
L375: def _zip_equal_generator(iterables):  Function `_zip_equal_generator` utility or
script function.
L383: def _zip_equal(*iterables):  Function `_zip_equal` utility or script function.
L399: def grouper(iterable, n, incomplete='fill', fillvalue=None):  Function `grouper`
utility or script function.

```

```

L439: def roundrobin(*iterables):    Function `roundrobin` utility or script function.
L457: def partition(pred, iterable):  Function `partition` utility or script function.
L485: def powerset(iterable):        Function `powerset` utility or script function.
L506: def unique_everseen(iterable, key=None):  Function `unique_everseen` utility or
script function.
L551: def unique_justseen(iterable, key=None):  Function `unique_justseen` utility or
script function.
L566: def unique(iterable, key=None, reverse=False):  Function `unique` utility or script
function.
L586: def iter_except(func, exception, first=None):  Function `iter_except` utility or
script function.
L615: def first_true(iterable, default=None, pred=None):  Function `first_true` utility or
script function.
L635: def random_product(*args, repeat=1):  Function `random_product` utility or script
function.
L655: def random_permutation(iterable, r=None):  Function `random_permutation` utility or
script function.
L673: def random_combination(iterable, r):  Function `random_combination` utility or script
function.
L689: def random_combination_with_replacement(iterable, r):  Function
`random_combination_with_replacement` utility or script function.
L706: def nth_combination(iterable, r, index):  Function `nth_combination` utility or
script function.
L748: def prepend(value, iterator):  Function `prepend` utility or script function.
L763: def convolve(signal, kernel):  Function `convolve` utility or script function.
L806: def before_and_after(predicate, it):  Function `before_and_after` utility or script
function.
L825: def triplewise(iterable):  Function `triplewise` utility or script function.
L841: def _sliding_window_islice(iterable, n):  Function `_sliding_window_islice` utility
or script function.
L849: def _sliding_window_deque(iterable, n):  Function `_sliding_window_deque` utility or
script function.
L858: def sliding_window(iterable, n):  Function `sliding_window` utility or script
function.
L883: def subslices(iterable):  Function `subslices` utility or script function.
L897: def polynomial_from_roots(roots):  Function `polynomial_from_roots` utility or script
function.
L919: def iter_index(iterable, value, start=0, stop=None):  Function `iter_index` utility
or script function.
L960: def sieve(n):  Function `sieve` utility or script function.
L981: def _batched(iterable, n, *, strict=False):  # pragma: no cover  Function `_batched`
utility or script function.
L1004: def batched(iterable, n, *, strict=False):  Function `batched` utility or script
function.
L1012: def transpose(it):  Function `transpose` utility or script function.
L1024: def _is_scalar(value, stringlike=(str, bytes)):  Function `_is_scalar` utility or
script function.
L1033: def _flatten_tensor(tensor):  Function `_flatten_tensor` utility or script function.
L1047: def reshape(matrix, shape):  Function `reshape` utility or script function.
L1088: def matmul(m1, m2):  Function `matmul` utility or script function.
L1103: def _factor_pollard(n):  Function `_factor_pollard` utility or script function.

```

```

L1122: def factor(n):    Function `factor` utility or script function.
L1155: def polynomial_eval(coefficients, x):  Function `polynomial_eval` utility or script
function.
L1178: def sum_of_squares(it):    Function `sum_of_squares` utility or script function.
L1189: def polynomial_derivative(coefficients):  Function `polynomial_derivative` utility
or script function.
L1208: def totient(n):    Function `totient` utility or script function.
L1249: def _shift_to_odd(n):    Function `_shift_to_odd` utility or script function.
L1257: def _strong_probable_prime(n, base):    Function `_strong_probable_prime` utility or
script function.
L1279: def is_prime(n):    Function `is_prime` utility or script function.
L1327: def loops(n):    Function `loops` utility or script function.
L1341: def multinomial(*counts):    Function `multinomial` utility or script function.
L1386: def _running_median_minheap_and_maxheap(iterator):  # pragma: no cover    Function
`_running_median_minheap_and_maxheap` utility or script function.
L1402: def _running_median_minheap_only(iterator):  # pragma: no cover    Function
`_running_median_minheap_only` utility or script function.
L1418: def _running_median_windowed(iterator, maxlen):    Function `_running_median_windowed`
utility or script function.
L1437: def running_median(iterable, *, maxlen=None):    Function `running_median` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/backports/tarfile/__init__.py

```

L159: def stn(s, length, encoding, errors):    Function `stn` utility or script function.
L167: def nts(s, encoding, errors):    Function `nts` utility or script function.
L175: def nti(s):    Function `nti` utility or script function.
L195: def itn(n, digits=8, format=DEFAULT_FORMAT):    Function `itn` utility or script
function.
L225: def calc_chksums(buf):    Function `calc_chksums` utility or script function.
L238: def copyfileobj(src, dst, length=None, exception=OSError, bufsize=None):    Function
`copyfileobj` utility or script function.
L263: def _safe_print(s):    Function `_safe_print` utility or script function.
L270: class TarError(Exception):    Class (`TarError`) component used by the app (see file
context: None).
L273: class ExtractError(TarError):    Class (`ExtractError`) component used by the app (see
file context: None).
L276: class ReadError(TarError):    Class (`ReadError`) component used by the app (see file
context: None).
L279: class CompressionError(TarError):    Class (`CompressionError`) component used by the
app (see file context: None).
L282: class StreamError(TarError):    Class (`StreamError`) component used by the app (see
file context: None).
L285: class HeaderError(TarError):    Class (`HeaderError`) component used by the app (see
file context: None).

```

```

L288: class EmptyHeaderError(HeaderError):  Class (`EmptyHeaderError`) component used by
the app (see file context: None).
L291: class TruncatedHeaderError(HeaderError):  Class (`TruncatedHeaderError`) component
used by the app (see file context: None).
L294: class EOFHeaderError(HeaderError):  Class (`EOFHeaderError`) component used by the
app (see file context: None).
L297: class InvalidHeaderError(HeaderError):  Class (`InvalidHeaderError`) component used
by the app (see file context: None).
L300: class SubsequentHeaderError(HeaderError):  Class (`SubsequentHeaderError`) component
used by the app (see file context: None).
L307: class _LowLevelFile:  Class (`_LowLevelFile`) component used by the app (see file
context: None).
L313: def __init__(self, name, mode):  Function `__init__` utility or script function.
L322: def close(self):  Function `close` utility or script function.
L325: def read(self, size):  Function `read` utility or script function.
L328: def write(self, s):  Function `write` utility or script function.
L331: class _Stream:  Class (`_Stream`) component used by the app (see file context: None).
L343: def __init__(self, name, mode, comptype, fileobj, bufsize,  Function `__init__`
utility or script function.
L414: def __del__(self):  Function `__del__` utility or script function.
L418: def _init_write_gz(self, compresslevel):  Function `_init_write_gz` utility or script
function.
L435: def write(self, s):  Function `write` utility or script function.
L445: def __write(self, s):  Function `__write` utility or script function.
L454: def close(self):  Function `close` utility or script function.
L476: def _init_read_gz(self):  Function `_init_read_gz` utility or script function.
L507: def tell(self):  Function `tell` utility or script function.
L512: def seek(self, pos=0):  Function `seek` utility or script function.
L525: def read(self, size):  Function `read` utility or script function.
L532: def _read(self, size):  Function `_read` utility or script function.
L559: def __read(self, size):  Function `__read` utility or script function.
L576: class _StreamProxy(object):  Object (singleton).
L581: def __init__(self, fileobj):  Function `__init__` utility or script function.
L585: def read(self, size):  Function `read` utility or script function.
L589: def getcomptype(self):  Function `getcomptype` Returns or fetches data.
L599: def close(self):  Function `close` utility or script function.
L606: class _FileInFile(object):  Object (singleton).
L612: def __init__(self, fileobj, offset, size, name, blockinfo=None):  Function `__init__`
utility or script function.
L637: def flush(self):  Function `flush` utility or script function.
L641: def mode(self):  Function `mode` utility or script function.
L644: def readable(self):  Function `readable` utility or script function.
L647: def writable(self):  Function `writable` utility or script function.
L650: def seekable(self):  Function `seekable` utility or script function.
L653: def tell(self):  Function `tell` utility or script function.
L658: def seek(self, position, whence=io.SEEK_SET):  Function `seek` utility or script
function.
L674: def read(self, size=None):  Function `read` utility or script function.
L705: def readinto(self, b):  Function `readinto` utility or script function.
L710: def close(self):  Function `close` utility or script function.
L714: class ExFileObject(io.BufferedReader):  Class (`ExFileObject`) component used by the

```



```

app (see file context: None).
L716: def __init__(self, tarfile, tarinfo):  Function `__init__`  utility or script
function.
L727: class FilterError(TarError):  Class (`FilterError`)  component used by the app (see
file context: None).
L730: class AbsolutePathError(FilterError):  Class (`AbsolutePathError`)  component used by
the app (see file context: None).
L731: def __init__(self, tarinfo):  Function `__init__`  utility or script function.
L735: class OutsideDestinationError(FilterError):  Class (`OutsideDestinationError`)
component used by the app (see file context: None).
L736: def __init__(self, tarinfo, path):  Function `__init__`  utility or script function.
L742: class SpecialFileError(FilterError):  Class (`SpecialFileError`)  component used by
the app (see file context: None).
L743: def __init__(self, tarinfo):  Function `__init__`  utility or script function.
L747: class AbsoluteLinkError(FilterError):  Class (`AbsoluteLinkError`)  component used by
the app (see file context: None).
L748: def __init__(self, tarinfo):  Function `__init__`  utility or script function.
L752: class LinkOutsideDestinationError(FilterError):  Class (`LinkOutsideDestinationError`)
component used by the app (see file context: None).
L753: def __init__(self, tarinfo, path):  Function `__init__`  utility or script function.
L759: def _get_filtered_attrs(member, dest_path, for_data=True):  Function
`_get_filtered_attrs`  utility or script function.
L822: def fully_trusted_filter(member, dest_path):  Function `fully_trusted_filter`  utility
or script function.
L825: def tar_filter(member, dest_path):  Function `tar_filter`  utility or script function.
L831: def data_filter(member, dest_path):  Function `data_filter`  utility or script
function.
L850: class TarInfo(object):  Object (singleton).
L885: def __init__(self, name=""):  Function `__init__`  utility or script function.
L910: def tarfile(self):  Function `tarfile`  utility or script function.
L919: def tarfile(self, tarfile):  Function `tarfile`  utility or script function.
L928: def path(self):  Function `path`  utility or script function.
L933: def path(self, name):  Function `path`  utility or script function.
L937: def linkpath(self):  Function `linkpath`  utility or script function.
L942: def linkpath(self, linkname):  Function `linkpath`  utility or script function.
L945: def __repr__(self):  Function `__repr__`  utility or script function.
L948: def replace(self, *,  Function `replace`  utility or script function.
L976: def get_info(self):  Function `get_info`  Returns or fetches data.
L1004: def tobuf(self, format=DEFAULT_FORMAT, encoding=ENCODING, errors="surrogateescape"):
Function `tobuf`  utility or script function.
L1021: def create_ustar_header(self, info, encoding, errors):  Function
`create_ustar_header`  Creates a resource or document.
L1034: def create_gnu_header(self, info, encoding, errors):  Function `create_gnu_header`
Creates a resource or document.
L1048: def create_pax_header(self, info, encoding):  Function `create_pax_header`  Creates a
resource or document.
L1107: def create_pax_global_header(cls, pax_headers):  Function `create_pax_global_header`
Creates a resource or document.
L1112: def _posix_split_name(self, name, encoding, errors):  Function `_posix_split_name`
utility or script function.
L1129: def _create_header(info, format, encoding, errors):  Function `_create_header`

```



```

utility or script function.
L1171: def _create_payload(payload):    Function `_create_payload` utility or script
function.
L1181: def _create_gnu_long_header(cls, name, type, encoding, errors):    Function
`_create_gnu_long_header` utility or script function.
L1198: def _create_pax_generic_header(cls, pax_headers, type, encoding):    Function
`_create_pax_generic_header` utility or script function.
L1249: def frombuf(cls, buf, encoding, errors):    Function `frombuf` utility or script
function.
L1312: def fromtarfile(cls, tarfile):    Function `fromtarfile` utility or script function.
L1332: def _proc_member(self, tarfile):    Function `_proc_member` utility or script
function.
L1345: def _proc_builtin(self, tarfile):    Function `_proc_builtin` utility or script
function.
L1367: def _proc_gnulong(self, tarfile):    Function `_proc_gnulong` utility or script
function.
L1394: def _proc_sparse(self, tarfile):    Function `_proc_sparse` utility or script
function.
L1422: def _proc_pax(self, tarfile):    Function `_proc_pax` utility or script function.
L1522: def _proc_gnusparses_00(self, next, pax_headers, buf):    Function `_proc_gnusparses_00`
utility or script function.
L1533: def _proc_gnusparses_01(self, next, pax_headers):    Function `_proc_gnusparses_01`
utility or script function.
L1539: def _proc_gnusparses_10(self, next, pax_headers, tarfile):    Function
`_proc_gnusparses_10` utility or script function.
L1555: def _apply_pax_info(self, pax_headers, encoding, errors):    Function `_apply_pax_info`
utility or script function.
L1578: def _decode_pax_field(self, value, encoding, fallback_encoding, fallback_errors):
Function `_decode_pax_field` utility or script function.
L1586: def _block(self, count):    Function `_block` utility or script function.
L1595: def isreg(self):    Function `isreg` utility or script function.
L1599: def isfile(self):    Function `isfile` utility or script function.
L1603: def isdir(self):    Function `isdir` utility or script function.
L1607: def issym(self):    Function `issym` utility or script function.
L1611: def islnk(self):    Function `islnk` utility or script function.
L1615: def ischr(self):    Function `ischr` utility or script function.
L1619: def isblk(self):    Function `isblk` utility or script function.
L1623: def isfifo(self):    Function `isfifo` utility or script function.
L1627: def issparse(self):    Function `issparse` utility or script function.
L1630: def isdev(self):    Function `isdev` utility or script function.
L1635: class TarFile(object):    Object (singleton).
L1663: def __init__(self, name=None, mode="r", fileobj=None, format=None,    Function
`__init__` utility or script function.
L1777: def open(cls, name=None, mode="r", fileobj=None, bufsize=RECORDSIZE, **kwargs):
Function `open` utility or script function.
L1818: def not_compressed(comptype):    Function `not_compressed` utility or script function.
L1873: def taropen(cls, name, mode="r", fileobj=None, **kwargs):    Function `taropen`
utility or script function.
L1881: def gzopen(cls, name, mode="r", fileobj=None, compresslevel=9, **kwargs):    Function
`gzopen` utility or script function.
L1914: def bz2open(cls, name, mode="r", fileobj=None, compresslevel=9, **kwargs):    Function

```

```

`bz2open` utility or script function.
L1942: def xzopen(cls, name, mode="r", fileobj=None, preset=None, **kwargs): Function
`xzopen` utility or script function.
L1980: def close(self): Function `close` utility or script function.
L2001: def getmember(self, name): Function `getmember` Returns or fetches data.
L2012: def getmembers(self): Function `getmembers` Returns or fetches data.
L2022: def getnames(self): Function `getnames` Returns or fetches data.
L2028: def gettarinfo(self, name=None, arcname=None, fileobj=None): Function `gettarinfo`
Returns or fetches data.
L2127: def list(self, verbose=True, *, members=None): Function `list` utility or script
function.
L2170: def add(self, name, arcname=None, recursive=True, *, filter=None): Function `add`
utility or script function.
L2221: def addfile(self, tarinfo, fileobj=None): Function `addfile` utility or script
function.
L2249: def _get_filter_function(self, filter): Function `_get_filter_function` utility or
script function.
L2273: def extractall(self, path=".", members=None, *, numeric_owner=False, Function
`extractall` utility or script function.
L2318: def extract(self, member, path="", set_attrs=True, *, numeric_owner=False, Function
`extract` utility or script function.
L2337: def _get_extract_tarinfo(self, member, filter_function, path): Function
`_get_extract_tarinfo` utility or script function.
L2360: def _extract_one(self, tarinfo, path, set_attrs, numeric_owner): Function
`_extract_one` utility or script function.
L2373: def _handle_nonfatal_error(self, e): Function `_handle_nonfatal_error` utility or
script function.
L2380: def _handle_fatal_error(self, e): Function `_handle_fatal_error` utility or script
function.
L2392: def extractfile(self, member): Function `extractfile` utility or script function.
L2424: def _extract_member(self, tarinfo, targetpath, set_attrs=True, Function
`_extract_member` utility or script function.
L2473: def mkdir(self, tarinfo, targetpath): Function `mkdir` utility or script
function.
L2488: def makefile(self, tarinfo, targetpath): Function `makefile` utility or script
function.
L2504: def makeunknown(self, tarinfo, targetpath): Function `makeunknown` utility or
script function.
L2512: def makefifo(self, tarinfo, targetpath): Function `makefifo` utility or script
function.
L2520: def makedev(self, tarinfo, targetpath): Function `makedev` utility or script
function.
L2538: def makelink(self, tarinfo, targetpath): Function `makelink` utility or script
function.
L2563: def chown(self, tarinfo, targetpath, numeric_owner): Function `chown` utility or
script function.
L2597: def chmod(self, tarinfo, targetpath): Function `chmod` utility or script function.
L2607: def utime(self, tarinfo, targetpath): Function `utime` utility or script function.
L2621: def next(self): Function `next` utility or script function.
L2688: def _getmember(self, name, tarinfo=None, normalize=False): Function `_getmember`
utility or script function.

```

```

L2728: def _load(self):    Function `_load` utility or script function.
L2737: def _check(self, mode=None):    Function `_check` utility or script function.
L2746: def _find_link_target(self, tarinfo):    Function `_find_link_target` utility or
script function.
L2765: def __iter__(self):    Function `__iter__` utility or script function.
L2796: def _dbg(self, level, msg):    Function `_dbg` utility or script function.
L2802: def __enter__(self):    Function `__enter__` utility or script function.
L2806: def __exit__(self, type, value, traceback):    Function `__exit__` utility or script
function.
L2820: def is_tarfile(name):    Function `is_tarfile` utility or script function.
L2841: def main():    Function `main` Entry point / main routine.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/backports/tarfile/compat/py38.py

```

L6: def removesuffix(self, suffix):    Function `removesuffix` utility or script function.
L13: def removeprefix(self, prefix):    Function `removeprefix` utility or script function.
L20: def removesuffix(self, suffix):    Function `removesuffix` utility or script function.
L23: def removeprefix(self, prefix):    Function `removeprefix` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_text.py

```

L7: class FoldedCase(str):    Class (`FoldedCase`) component used by the app (see file
context: None).
L67: def __lt__(self, other):    Function `__lt__` utility or script function.
L70: def __gt__(self, other):    Function `__gt__` utility or script function.
L73: def __eq__(self, other):    Function `__eq__` utility or script function.
L76: def __ne__(self, other):    Function `__ne__` utility or script function.
L79: def __hash__(self):    Function `__hash__` utility or script function.
L82: def __contains__(self, other):    Function `__contains__` utility or script function.
L85: def in_(self, other):    Function `in_` utility or script function.
L91: def lower(self):    Function `lower` utility or script function.
L94: def index(self, sub):    Function `index` utility or script function.
L97: def split(self, splitter=' ', maxsplit=0):    Function `split` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib

ib_metadata/_collections.py

```
L6: class FreezableDefaultDict(collections.defaultdict):  Class (`FreezableDefaultDict`)
component used by the app (see file context: None).
L21: def __missing__(self, key):  Function `__missing__`  utility or script function.
L24: def freeze(self):  Function `freeze`  utility or script function.
L28: class Pair(typing.NamedTuple):  Class (`Pair`)  component used by the app (see file
context: None).
L33: def parse(cls, text):  Function `parse`  utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_meta.py

```
L15: class PackageMetadata(Protocol):  Class (`PackageMetadata`)  component used by the app
(see file context: None).
L16: def __len__(self) -> int: ... # pragma: no cover  Function `__len__`  utility or
script function.
L18: def __contains__(self, item: str) -> bool: ... # pragma: no cover  Function
`__contains__`  utility or script function.
L20: def __getitem__(self, key: str) -> str: ... # pragma: no cover  Function `__getitem__`
utility or script function.
L22: def __iter__(self) -> Iterator[str]: ... # pragma: no cover  Function `__iter__`
utility or script function.
L25: def get(  Function `get`  Returns or fetches data.
L30: def get(self, name: str, failobj: _T) -> str | _T: ... # pragma: no cover  Function
`get`  Returns or fetches data.
L34: def get_all(  Function `get_all`  Returns or fetches data.
L39: def get_all(self, name: str, failobj: _T) -> list[Any] | _T:  Function `get_all`
Returns or fetches data.
L45: def json(self) -> dict[str, str | list[str]]:  Function `json`  utility or script
function.
L51: class SimplePath(Protocol):  Class (`SimplePath`)  component used by the app (see file
context: None).
L56: def joinpath(  Function `joinpath`  utility or script function.
L60: def __truediv__(  Function `__truediv__`  utility or script function.
L65: def parent(self) -> SimplePath: ... # pragma: no cover  Function `parent`  utility or
script function.
L67: def read_text(self, encoding=None) -> str: ... # pragma: no cover  Function
`read_text`  utility or script function.
L69: def read_bytes(self) -> bytes: ... # pragma: no cover  Function `read_bytes`  utility
or script function.
L71: def exists(self) -> bool: ... # pragma: no cover  Function `exists`  utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_compat.py

```
L17: def install(cls):    Function `install`    utility or script function.
L20: def disable_stdlib_finder():    Function `disable_stdlib_finder`    utility or script
function.
L29: def matches(finder):    Function `matches`    utility or script function.
L38: class NullFinder:    Class (`NullFinder`)    component used by the app (see file context:
None).
L45: def find_spec(*args, **kwargs):    Function `find_spec`    utility or script function.
L49: def pypy_partial(val):    Function `pypy_partial`    utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_init_.py

```
L61: class PackageNotFoundError(ModuleNotFoundError):    Class (`PackageNotFoundError`)
component used by the app (see file context: None).
L64: def __str__(self) -> str:    Function `__str__`    utility or script function.
L68: def name(self) -> str:    # type: ignore[override] # make readonly    Function `name`
utility or script function.
L73: class Sectioned:    Class (`Sectioned`)    component used by the app (see file context:
None).
L115: def section_pairs(cls, text):    Function `section_pairs`    utility or script function.
L123: def read(text, filter_=None):    Function `read`    utility or script function.
L134: def valid(line: str):    Function `valid`    utility or script function.
L138: class _EntryPointMatch(types.SimpleNamespace):    Class (`_EntryPointMatch`)    component
used by the app (see file context: None).
L144: class EntryPoint:    Class (`EntryPoint`)    component used by the app (see file context:
None).
L212: def __init__(self, name: str, value: str, group: str) -> None:    Function `__init__`
utility or script function.
L216: def load(self) -> Any:    Function `load`    Loads data from storage or remote.
L226: def module(self) -> str:    Function `module`    utility or script function.
L230: def attr(self) -> str:    Function `attr`    utility or script function.
L234: def extras(self) -> list[str]:    Function `extras`    utility or script function.
L238: def _match(self) -> _EntryPointMatch:    Function `_match`    utility or script function.
L249: def _for(self, dist):    Function `_for`    utility or script function.
L253: def matches(self, **params):    Function `matches`    utility or script function.
L278: def _disallow_dist(params):    Function `_disallow_dist`    utility or script function.
L293: def _key(self):    Function `_key`    utility or script function.
L296: def __lt__(self, other):    Function `__lt__`    utility or script function.
L299: def __eq__(self, other):    Function `__eq__`    utility or script function.
L302: def __setattr__(self, name, value):    Function `__setattr__`    utility or script
```

```

function.
L305: def __repr__(self):    Function `__repr__`    utility or script function.
L311: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L315: class EntryPoints(tuple):    Class (`EntryPoints`)    component used by the app (see file
context: None).
L322: def __getitem__(self, name: str) -> EntryPoint:    # type: ignore[override] # Work with
str instead of int    Function `__getitem__`    utility or script function.
L331: def __repr__(self):    Function `__repr__`    utility or script function.
L338: def select(self, **params) -> EntryPoints:    Function `select`    utility or script
function.
L346: def names(self) -> set[str]:    Function `names`    utility or script function.
L353: def groups(self) -> set[str]:    Function `groups`    utility or script function.
L360: def _from_text_for(cls, text, dist):    Function `_from_text_for`    utility or script
function.
L364: def _from_text(text):    Function `_from_text`    utility or script function.
L371: class PackagePath(pathlib.PurePosixPath):    Class (`PackagePath`)    component used by
the app (see file context: None).
L378: def read_text(self, encoding: str = 'utf-8') -> str:    Function `read_text`    utility or
script function.
L381: def read_binary(self) -> bytes:    Function `read_binary`    utility or script function.
L384: def locate(self) -> SimplePath:    Function `locate`    utility or script function.
L389: class FileHash:    Class (`FileHash`)    component used by the app (see file context:
None).
L390: def __init__(self, spec: str) -> None:    Function `__init__`    utility or script
function.
L393: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L397: class Distribution(metaclass=abc.ABCMeta):    Class (`Distribution`)    component used by
the app (see file context: None).
L409: def read_text(self, filename) -> str | None:    Function `read_text`    utility or script
function.
L432: def locate_file(self, path: str | os.PathLike[str]) -> SimplePath:    Function
`locate_file`    utility or script function.
L450: def from_name(cls, name: str) -> Distribution:    Function `from_name`    utility or
script function.
L468: def discover(    Function `discover`    utility or script function.
L488: def _prefer_valid(dists: Iterable[Distribution]) -> Iterable[Distribution]:    Function
`_prefer_valid`    utility or script function.
L498: def at(path: str | os.PathLike[str]) -> Distribution:    Function `at`    utility or
script function.
L507: def _discover_resolvers():    Function `_discover_resolvers`    utility or script
function.
L515: def metadata(self) -> _meta.PackageMetadata | None:    Function `metadata`    utility or
script function.
L538: def _assemble_message(text: str) -> _meta.PackageMetadata:    Function
`_assemble_message`    utility or script function.
L545: def name(self) -> str:    Function `name`    utility or script function.
L550: def _normalized_name(self):    Function `_normalized_name`    utility or script function.
L555: def version(self) -> str:    Function `version`    utility or script function.
L560: def entry_points(self) -> EntryPoints:    Function `entry_points`    utility or script
function.
L570: def files(self) -> list[PackagePath] | None:    Function `files`    utility or script

```

```

function.
L585: def make_file(name, hash=None, size_str=None):  Function `make_file`  utility or
script function.
L593: def make_files(lines):  Function `make_files`  utility or script function.
L601: def skip_missing_files(package_paths):  Function `skip_missing_files`  utility or
script function.
L612: def _read_files_distinfo(self):  Function `_read_files_distinfo`  utility or script
function.
L619: def _read_files_egginfo_installed(self):  Function `_read_files_egginfo_installed`
utility or script function.
L647: def _read_files_egginfo_sources(self):  Function `_read_files_egginfo_sources`
utility or script function.
L663: def requires(self) -> list[str] | None:  Function `requires`  utility or script
function.
L668: def _read_dist_info_reqs(self):  Function `_read_dist_info_reqs`  utility or script
function.
L671: def _read_egg_info_reqs(self):  Function `_read_egg_info_reqs`  utility or script
function.
L676: def _deps_from_requires_text(cls, source):  Function `_deps_from_requires_text`
utility or script function.
L680: def _convert_egg_info_reqs_to_simple_reqs(sections):  Function
`_convert_egg_info_reqs_to_simple_reqs`  utility or script function.
L691: def make_condition(name):  Function `make_condition`  utility or script function.
L694: def quoted_marker(section):  Function `quoted_marker`  utility or script function.
L702: def url_req_space(req):  Function `url_req_space`  utility or script function.
L715: def origin(self):  Function `origin`  utility or script function.
L718: def _load_json(self, filename):  Function `_load_json`  utility or script function.
L728: class DistributionFinder(MetaPathFinder):  Class (`DistributionFinder`)  component
used by the app (see file context: None).
L736: class Context:  Class (`Context`)  component used by the app (see file context: None).
L765: def __init__(self, **kwargs):  Function `__init__`  utility or script function.
L769: def path(self) -> list[str]:  Function `path`  utility or script function.
L780: def find_distributions(self, context=Context()) -> Iterable[Distribution]:  Function
`find_distributions`  utility or script function.
L791: def _clear_after_fork(cached):  Function `_clear_after_fork`  utility or script
function.
L804: class FastPath:  Class (`FastPath`)  component used by the app (see file context:
None).
L822: def __new__(cls, root):  Function `__new__`  utility or script function.
L825: def __init__(self, root):  Function `__init__`  utility or script function.
L828: def joinpath(self, child):  Function `joinpath`  utility or script function.
L831: def children(self):  Function `children`  utility or script function.
L838: def zip_children(self):  Function `zip_children`  utility or script function.
L848: def search(self, name):  Function `search`  utility or script function.
L852: def mtime(self):  Function `mtime`  utility or script function.
L858: def lookup(self, mtime):  Function `lookup`  utility or script function.
L862: class Lookup:  Class (`Lookup`)  component used by the app (see file context: None).
L867: def __init__(self, path: FastPath):  Function `__init__`  utility or script function.
L896: def search(self, prepared: Prepared):  Function `search`  utility or script function.
L913: class Prepared:  Class (`Prepared`)  component used by the app (see file context:
None).

```



```

L936: def __init__(self, name: str | None):    Function `__init__`    utility or script
function.
L944: def normalize(name):    Function `normalize`    utility or script function.
L951: def legacy_normalize(name):    Function `legacy_normalize`    utility or script function.
L958: def __bool__(self):    Function `__bool__`    utility or script function.
L963: class MetadataPathFinder(NullFinder, DistributionFinder):    Class
(`MetadataPathFinder`)    component used by the app (see file context: None).
L971: def find_distributions(    Function `find_distributions`    utility or script function.
L986: def _search_paths(cls, name, paths):    Function `_search_paths`    utility or script
function.
L994: def invalidate_caches(cls) -> None:    Function `invalidate_caches`    utility or script
function.
L998: class PathDistribution(Distribution):    Class (`PathDistribution`)    component used by
the app (see file context: None).
L999: def __init__(self, path: SimplePath) -> None:    Function `__init__`    utility or script
function.
L1006: def read_text(self, filename: str | os.PathLike[str]) -> str | None:    Function
`read_text`    utility or script function.
L1020: def locate_file(self, path: str | os.PathLike[str]) -> SimplePath:    Function
`locate_file`    utility or script function.
L1024: def _normalized_name(self):    Function `_normalized_name`    utility or script function.
L1036: def _name_from_stem(stem):    Function `_name_from_stem`    utility or script function.
L1053: def distribution(distribution_name: str) -> Distribution:    Function `distribution`
utility or script function.
L1062: def distributions(**kwargs) -> Iterable[Distribution]:    Function `distributions`
utility or script function.
L1070: def metadata(distribution_name: str) -> _meta.PackageMetadata | None:    Function
`metadata`    utility or script function.
L1079: def version(distribution_name: str) -> str:    Function `version`    utility or script
function.
L1098: def entry_points(**params) -> EntryPoints:    Function `entry_points`    utility or
script function.
L1113: def files(distribution_name: str) -> list[PackagePath] | None:    Function `files`
utility or script function.
L1122: def requires(distribution_name: str) -> list[str] | None:    Function `requires`
utility or script function.
L1132: def packages_distributions() -> Mapping[str, list[str]]:    Function
`packages_distributions`    utility or script function.
L1149: def _top_level_declared(dist):    Function `_top_level_declared`    utility or script
function.
L1153: def _topmost(name: PackagePath) -> str | None:    Function `_topmost`    utility or
script function.
L1161: def _get_toplevel_name(name: PackagePath) -> str:    Function `_get_toplevel_name`
utility or script function.
L1185: def _top_level_inferred(dist):    Function `_top_level_inferred`    utility or script
function.
L1188: def importable_name(name):    Function `importable_name`    utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_itertools.py

```
L5: def unique_everseen(iterable, key=None):    Function `unique_everseen` utility or script
function.
L24: def always_iterable(obj, base_type=(str, bytes)):    Function `always_iterable` utility
or script function.
L78: class bucket:    Class (`bucket`) component used by the app (see file context: None).
L114: def __init__(self, iterable, key, validator=None):    Function `__init__` utility or
script function.
L120: def __contains__(self, value):    Function `__contains__` utility or script function.
L133: def _get_values(self, value):    Function `_get_values` utility or script function.
L159: def __iter__(self):    Function `__iter__` utility or script function.
L167: def __getitem__(self, value):    Function `__getitem__` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/diagnose.py

```
L6: def inspect(path):    Function `inspect` utility or script function.
L15: def run():    Function `run` utility or script function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/_functools.py

```
L7: def method_cache(method, cache_wrapper=None):    Function `method_cache` utility or
script function.
L76: def wrapper(self, *args, **kwargs):    Function `wrapper` utility or script function.
L90: def pass_none(func):    Function `pass_none` utility or script function.
L101: def wrapper(param, *args, **kwargs):    Function `wrapper` utility or script function.
L109: def noop(*args, **kwargs):    Function `noop` utility or script function.
L121: def passthrough(func: Callable[..., object]) -> Callable[[_T], _T]:    Object
(singleton).
L131: def wrapper(first: _T, *args, **kwargs) -> _T:    Function `wrapper` utility or script
function.
```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib

ib_metadata/_adapters.py

```

L9: class RawPolicy(email.policy.EmailPolicy):    Class (`RawPolicy`) component used by the
app (see file context: None).
L10: def fold(self, name, value):    Function `fold` utility or script function.
L20: class Message(email.message.Message):    Class (`Message`) component used by the app
(see file context: None).
L78: def __new__(cls, orig: email.message.Message):    Function `__new__` utility or script
function.
L83: def __init__(self, *args, **kwargs):    Function `__init__` utility or script function.
L87: def __iter__(self):    Function `__iter__` utility or script function.
L90: def __getitem__(self, item):    Function `__getitem__` utility or script function.
L105: def _repair_headers(self):    Function `_repair_headers` utility or script function.
L106: def redent(value):    Function `redent` utility or script function.
L119: def as_string(self):    Function `as_string` utility or script function.
L123: def json(self):    Function `json` utility or script function.
L129: def transform(key):    Function `transform` utility or script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/compat/py311.py

```

L7: def wrap(path):    # pragma: no cover    Function `wrap` utility or script function.
L16: def relative_to(root, *, walk_up=False):    Function `relative_to` utility or script
function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/setuptools/_vendor/importlib_metadata/compat/py39.py

```

L18: def normalized_name(dist: Distribution) -> str | None:    Function `normalized_name`
utility or script function.
L32: def ep_matches(ep: EntryPoint, **params) -> bool:    Function `ep_matches` utility or
script function.

```

Q_base

appwrite/.venv/lib/python3.12/site-packages/annotated_types/test_cases.py

```

L15: class Case(NamedTuple):    Class (`Case`) component used by the app (see file context:

```

```

None).
L25: def cases() -> Iterable[Case]:    Function `cases`    utility or script function.
L147: class MyCustomGroupedMetadata(at.GroupedMetadata):    Class (`MyCustomGroupedMetadata`)
component used by the app (see file context: None).
L148: def __iter__(self) -> Iterator[at.Predicate]:    Function `__iter__`    utility or script
function.

```

Q_base

appwrite/venv/lib/python3.12/site-packages/annotated_types/__init__.py

```

L68: class SupportsGt(Protocol):    Class (`SupportsGt`)    component used by the app (see file
context: None).
L69: def __gt__(self: T, __other: T) -> bool:    Function `__gt__`    utility or script
function.
L73: class SupportsGe(Protocol):    Class (`SupportsGe`)    component used by the app (see file
context: None).
L74: def __ge__(self: T, __other: T) -> bool:    Function `__ge__`    utility or script
function.
L78: class SupportsLt(Protocol):    Class (`SupportsLt`)    component used by the app (see file
context: None).
L79: def __lt__(self: T, __other: T) -> bool:    Function `__lt__`    utility or script
function.
L83: class SupportsLe(Protocol):    Class (`SupportsLe`)    component used by the app (see file
context: None).
L84: def __le__(self: T, __other: T) -> bool:    Function `__le__`    utility or script
function.
L88: class SupportsMod(Protocol):    Class (`SupportsMod`)    component used by the app (see
file context: None).
L89: def __mod__(self: T, __other: T) -> T:    Function `__mod__`    utility or script function.
L93: class SupportsDiv(Protocol):    Class (`SupportsDiv`)    component used by the app (see
file context: None).
L94: def __div__(self: T, __other: T) -> T:    Function `__div__`    utility or script function.
L98: class BaseMetadata:    Class (`BaseMetadata`)    component used by the app (see file
context: None).
L109: class Gt(BaseMetadata):    Class (`Gt`)    component used by the app (see file context:
None).
L120: class Ge(BaseMetadata):    Class (`Ge`)    component used by the app (see file context:
None).
L131: class Lt(BaseMetadata):    Class (`Lt`)    component used by the app (see file context:
None).
L142: class Le(BaseMetadata):    Class (`Le`)    component used by the app (see file context:
None).
L153: class GroupedMetadata(Protocol):    Class (`GroupedMetadata`)    component used by the app
(see file context: None).
L185: def __is_annotated_types_grouped_metadata__(self) -> Literal[True]:    Function
`__is_annotated_types_grouped_metadata__`    utility or script function.

```

```

L188: def __iter__(self) -> Iterator[object]:  Object (singleton).
L194: def __init_subclass__(cls, *args: Any, **kwargs: Any) -> None:  Function
`__init_subclass__` utility or script function.
L200: def __iter__(self) -> Iterator[object]:  # noqa: F811  Object (singleton).
L205: class Interval(GroupedMetadata):  Class (`Interval`) component used by the app (see
file context: None).
L217: def __iter__(self) -> Iterator[BaseMetadata]:  Function `__iter__` utility or script
function.
L230: class MultipleOf(BaseMetadata):  Class (`MultipleOf`) component used by the app (see
file context: None).
L244: class MinLen(BaseMetadata):  Class (`MinLen`) component used by the app (see file
context: None).
L254: class MaxLen(BaseMetadata):  Class (`MaxLen`) component used by the app (see file
context: None).
L264: class Len(GroupedMetadata):  Class (`Len`) component used by the app (see file
context: None).
L274: def __iter__(self) -> Iterator[BaseMetadata]:  Function `__iter__` utility or script
function.
L283: class Timezone(BaseMetadata):  Class (`Timezone`) component used by the app (see file
context: None).
L300: class Unit(BaseMetadata):  Class (`Unit`) component used by the app (see file
context: None).
L323: class Predicate(BaseMetadata):  Class (`Predicate`) component used by the app (see
file context: None).
L346: def __repr__(self) -> str:  Function `__repr__` utility or script function.
L359: class Not:  Class (`Not`) component used by the app (see file context: None).
L362: def __call__(self, __v: Any) -> bool:  Function `__call__` utility or script
function.
L413: class DocInfo:  # type: ignore [no-redef]  Class (`DocInfo`) component used by the
app (see file context: None).
L422: def doc(  Function `doc` utility or script function.

```

Q_base appwrite/functions/validate_admin_writes/main.py

```

L25: def read_stdin():  Function `read_stdin` utility or script function.
L34: def make_client():  Function `make_client` utility or script function.
L47: def main():  Function `main` Entry point / main routine.

```

archive/ui/ActiveSessionViewModelFactory.kt

```

L11: class ActiveSessionViewModelFactory(  Class (`ActiveSessionViewModelFactory`)
component used by the app (see file context: None).

```

archive/ui/SessionsViewModelFactory.kt

L10: class SessionsViewModelFactory(Class (`SessionsViewModelFactory`) component used by the app (see file context: None).

archive/ui/ExtractionConfigScreen.kt

L20: fun ExtractionConfigScreen(Function `ExtractionConfigScreen` performs a specific operation used by the surrounding feature.

archive/ui/BaseAiViewModel.kt

L13: sealed class AiState { Sealed class (`AiState`) represents a closed hierarchy of types.
 L14: object Idle : AiState() Singleton/object (`Idle`) holds shared state or DI bindings.
 L15: object Loading : AiState() Singleton/object (`Loading`) holds shared state or DI bindings.
 L16: data class Success(val result: String) : AiState() Data model (`Success`) holds structured data used across the app.
 L17: data class Error(val message: String) : AiState() Data model (`Error`) holds structured data used across the app.
 L37: protected fun executeAiTask(Function `executeAiTask` performs a specific operation used by the surrounding feature.
 L62: fun resetAiState() { Function `resetAiState` performs a specific operation used by the surrounding feature.
 L66: fun cancelCurrentAiTask() { Function `cancelCurrentAiTask` performs a specific operation used by the surrounding feature.

docs/generate_pdf.py

L6: class QbasePDF(FPDF): Class (`QbasePDF`) component used by the app (see file context: docs/generate_pdf.py).
 L7: def header(self): Function `header` utility or script function.
 L17: def footer(self): Function `footer` utility or script function.
 L23: def sanitize_text(text): Function `sanitize\_text` utility or script function.
 L27: def build_pdf(md_path, pdf_path): Function `build\_pdf` Constructs or prepares an object.

core-auth/src/main/java/com/algorithmx/q_base/data/di/AuthModule.kt

L13: object AuthModule { Singleton/object (`AuthModule`) holds shared state or DI bindings.
 L17: fun provideAppwriteAccount(client: Client): Account = Account(client) Function `provideAppwriteAccount` DI provider method.

core-auth/src/main/java/com/algorithmx/q_base/data/auth/UserProfile.kt

L7: data class UserProfile(Data model (`UserProfile`) holds structured data used across the app.

core-auth/src/main/java/com/algorithmx/q_base/data/auth/ProfileRepository.kt

L14: class ProfileRepository @Inject constructor(Repository (`ProfileRepository`) handles data operations and coordination for a feature.

L21: private fun mapToUserProfile(map: Map<String, Any>): UserProfile { Function `mapToUserProfile` Maps or converts between representations.

L35: private fun userProfileToMap(profile: UserProfile): Map<String, Any> { Function `userProfileToMap` performs a specific operation used by the surrounding feature.

L48: suspend fun createOrUpdateProfile(Function `createOrUpdateProfile` Creates a resource or document.

L94: suspend fun updateProfile(profile: UserProfile): Result<Unit> { Suspend function `updateProfile` coroutine-friendly async operation.

L107: private suspend fun saveProfile(profile: UserProfile, email: String) { Function `saveProfile` Saves data to storage or remote.

L129: suspend fun findUserByFriendCode(friendCode: String): Result<UserProfile?> { Suspend function `findUserByFriendCode` coroutine-friendly async operation.

L148: suspend fun syncUserProfile(userId: String) { Suspend function `syncUserProfile` coroutine-friendly async operation.

L219: private suspend fun generateUniqueFriendCode(): String { Function `generateUniqueFriendCode` Generates content (often AI-generated).

L238: private suspend fun isFriendCodeUnique(friendCode: String): Boolean { Suspend function `isFriendCodeUnique` coroutine-friendly async operation.

L251: private fun generateFriendCode(): String { Function `generateFriendCode` Generates content (often AI-generated).

L259: suspend fun setupSecureBackup(userId: String, passphrase: String): Result<Unit> { Function `setupSecureBackup` Sets or updates a value.

L277: suspend fun checkHasSecureBackup(userId: String): Boolean { Suspend function `checkHasSecureBackup` coroutine-friendly async operation.

L287: suspend fun restoreSecureBackup(userId: String, passphrase: String): Result<Unit> { Suspend function `restoreSecureBackup` coroutine-friendly async operation.

core-auth/src/main/java/com/algorithmx/q_base/data/auth/ProfileCache.kt

L3: interface ProfileCache { Interface (`ProfileCache`) contract implemented by components.

L4: suspend fun upsert(profile: UserProfile) Suspend function `upsert` coroutine-friendly

async operation.

core-auth/src/main/java/com/algorithmx/q_base/data/auth/AuthRepository.kt

```
L23: data class AppwriteUser(    Data model (`AppwriteUser`)  holds structured data used
across the app.
L31: class AuthRepository @Inject constructor(    Repository (`AuthRepository`)  handles data
operations and coordination for a feature.
L52: private fun saveUserToPrefs(user: AppwriteUser) {    Function `saveUserToPrefs`  Saves
data to storage or remote.
L62: private fun getUserFromPrefs(): AppwriteUser? {    Function `getUserFromPrefs`  Returns
or fetches data.
L71: private fun clearUserFromPrefs() {    Function `clearUserFromPrefs`  performs a specific
operation used by the surrounding feature.
L81: fun checkCurrentSession() {    Function `checkCurrentSession`  performs a specific
operation used by the surrounding feature.
L103: private fun mapAppwriteUser(user: User<*>, photoUrl: String? = null): AppwriteUser {
Function `mapAppwriteUser`  Maps or converts between representations.
L116: private suspend fun fetchGooglePhotoUrl(): String? {    Suspend function
`fetchGooglePhotoUrl`  coroutine-friendly async operation.
L153: suspend fun signInWithEmail(email: String, pass: String): Result<AppwriteUser> {
Function `signInWithEmail`  Performs user sign-in.
L168: suspend fun signUpWithEmail(email: String, pass: String, username: String, photoUrl:
String? = null): Result<AppwriteUser> {    Function `signUpWithEmail`  Performs user sign-up.
L184: suspend fun signInWithGoogle(activity: ComponentActivity): Result<AppwriteUser> {
Function `signInWithGoogle`  Performs user sign-in.
L201: fun signOut() {    Function `signOut`  performs a specific operation used by the
surrounding feature.
```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/FirebaseAuthImpl.kt

```
L21: class FirebaseAuthImpl @Inject constructor(    Authentication component
(`FirebaseAuthImpl`)  handles user authentication flows.
```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/CoreDatabase.kt

```
L5: enum class CoreQueryOperator {    Enumeration (`CoreQueryOperator`)  defines a set of
named constants.
L13: data class CoreQuery(    Data model (`CoreQuery`)  holds structured data used across the
```

```

app.
L19: interface CoreDatabase {    Interface (`CoreDatabase`)    contract implemented by
components.
L20: suspend fun createDocument(collectionId: String, documentId: String, data: Map<String,
Any>): Result<Unit>    Function `createDocument`    Creates a resource or document.
L21: suspend fun getDocument(collectionId: String, documentId: String): Result<Map<String,
Any>?>    Function `getDocument`    Returns or fetches data.
L22: suspend fun updateDocument(collectionId: String, documentId: String, data: Map<String,
Any>): Result<Unit>    Suspend function `updateDocument`    coroutine-friendly async operation.
L23: suspend fun deleteDocument(collectionId: String, documentId: String): Result<Unit>
Function `deleteDocument`    Deletes a resource.
L24: suspend fun listDocuments(collectionId: String): Result<List<Map<String, Any>>>
Suspend function `listDocuments`    coroutine-friendly async operation.
L25: suspend fun queryDocuments(collectionId: String, queries: List<CoreQuery>):
Result<List<Map<String, Any>>>    Suspend function `queryDocuments`    coroutine-friendly async
operation.
L26: fun observeDocument(collectionId: String, documentId: String): Flow<Map<String, Any>?>
Function `observeDocument`    Observes changes and returns a Flow/Stream.
L27: fun observeCollection(collectionId: String): Flow<List<Map<String, Any>>>    Function
`observeCollection`    Observes changes and returns a Flow/Stream.

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/Appwrite DatabaseImpl.kt

```

L19: class AppwriteDatabaseImpl @Inject constructor(    Database abstraction
(`AppwriteDatabaseImpl`)    encapsulates DB access/setup.
L30: private suspend fun invokeSuspendReflective(    Suspend function
`invokeSuspendReflective`    coroutine-friendly async operation.
L56: private fun mapRow(row: Any): Map<String, Any> {    Function `mapRow`    Maps or converts
between representations.
L132: private fun mapRowList(rowList: Any): List<Map<String, Any>> {    Function `mapRowList`
Maps or converts between representations.
L143: private fun mapDocument(doc: io.appwrite.models.Document<*>): Map<String, Any> {
Function `mapDocument`    Maps or converts between representations.
L393: fun wrapValue(v: Any): List<Any> = if (v is List<*>) v.filterNotNull() else listOf(v)
Function `wrapValue`    performs a specific operation used by the surrounding feature.

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/Firebase DatabaseImpl.kt

```

L13: class FirebaseDatabaseImpl @Inject constructor(    Database abstraction
(`FirebaseDatabaseImpl`)    encapsulates DB access/setup.

```


core-auth/src/main/java/com/algorithmx/q_base/data/backend/BackendModule.kt

```

L16: annotation class FirebaseBackend    Annotation (`FirebaseBackend`)    used for DI/metadata
annotations.
L20: annotation class AppwriteBackend    Annotation (`AppwriteBackend`)    used for DI/metadata
annotations.
L24: object BackendModule {    Singleton/object (`BackendModule`)    holds shared state or DI
bindings.
L28: fun provideFirebaseAuth(): FirebaseAuth {    Function `provideFirebaseAuth`    DI provider
method.
L35: fun provideFirebaseAuthImpl(    Function `provideFirebaseAuthImpl`    DI provider method.
L45: fun provideFirebaseDatabaseImpl(    Function `provideFirebaseDatabaseImpl`    DI provider
method.
L54: fun provideAppwriteAuthImpl(    Function `provideAppwriteAuthImpl`    DI provider method.
L64: fun provideAppwriteDatabaseImpl(    Function `provideAppwriteDatabaseImpl`    DI provider
method.
L74: fun provideActiveAuth(    Function `provideActiveAuth`    DI provider method.
L82: fun provideActiveDatabase(    Function `provideActiveDatabase`    DI provider method.

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/CoreAuth.h.kt

```

L6: data class CoreUser(    Data model (`CoreUser`)    holds structured data used across the
app.
L13: interface CoreAuth {    Interface (`CoreAuth`)    contract implemented by components.
L17: suspend fun signInWithEmail(email: String, pass: String): Result<CoreUser>    Function
`signInWithEmail`    Performs user sign-in.
L18: suspend fun signUpWithEmail(email: String, pass: String, username: String):
Result<CoreUser>    Function `signUpWithEmail`    Performs user sign-up.
L19: suspend fun signInWithGoogle(activity: ComponentActivity): Result<CoreUser>    Function
`signInWithGoogle`    Performs user sign-in.
L20: suspend fun signOut(): Result<Unit>    Suspend function `signOut`    coroutine-friendly
async operation.
L21: suspend fun checkCurrentSession(): Result<CoreUser?>    Suspend function
`checkCurrentSession`    coroutine-friendly async operation.

```

core-auth/src/main/java/com/algorithmx/q_base/data/backend/AppwriteAuthImpl.kt

```

L18: class AppwriteAuthImpl @Inject constructor(    Authentication component
(`AppwriteAuthImpl`)    handles user authentication flows.
L37: private fun mapUser(user: User<*>): CoreUser {    Function `mapUser`    Maps or converts
between representations.

```

core-auth/src/main/java/com/algorithmx/q_base/ui/components/AuthComponents.kt

```
L45: fun AuthFormSection(    Function `AuthFormSection`    performs a specific operation used by
the surrounding feature.
L193: fun GoogleSignInButton(    Function `GoogleSignInButton`    performs a specific operation
used by the surrounding feature.
L284: fun GoogleIconGraphic() {    Function `GoogleIconGraphic`    performs a specific operation
used by the surrounding feature.
```

.venv/lib/python3.12/site-packages/pip/__pip-runner__.py

```
L15: def version_str(version): # type: ignore    Function `version_str`    utility or script
function.
L36: class PipImportRedirectingFinder:    Class (`PipImportRedirectingFinder`)    component used
by the app (see file context: None).
L38: def find_spec(self, fullname, path=None, target=None): # type: ignore    Function
`find_spec`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/__init__.py

```
L6: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main
routine.
```

.venv/lib/python3.12/site-packages/pip/_internal/pyproject.py

```
L18: def _is_list_of_str(obj: Any) -> bool:    Function `_is_list_of_str`    utility or script
function.
L22: def make_pyproject_path(unpacked_source_directory: str) -> str:    Function
`make_pyproject_path`    utility or script function.
L31: def load_pyproject_toml(    Function `load_pyproject_toml`    Loads data from storage or
remote.
```

.venv/lib/python3.12/site-packages/pip/_internal/build_env.py

```
L44: class ExtraEnviron(TypedDict, total=False):    Class (`ExtraEnviron`)    component used by
the app (see file context: None).
L51: def _dedup(a: str, b: str) -> tuple[str] | tuple[str, str]:    Function `_dedup`    utility
or script function.
L55: class _Prefix:    Class (`_Prefix`)    component used by the app (see file context: None).
```

```

L56: def __init__(self, path: str) -> None:    Function `__init__`    utility or script
function.
L64: def get_runnable_pip() -> str:    Function `get_runnable_pip`    Returns or fetches data.
L80: def _get_system_sitepackages() -> set[str]:    Function `_get_system_sitepackages`
utility or script function.
L100: class BuildEnvironmentInstaller(Protocol):    Class (`BuildEnvironmentInstaller`)
component used by the app (see file context: None).
L106: def install(    Function `install`    utility or script function.
L116: class SubprocessBuildEnvironmentInstaller:    Class
(`SubprocessBuildEnvironmentInstaller`)    component used by the app (see file context: None).
L121: def __init__(    Function `__init__`    utility or script function.
L131: def _deprecation_constraint_check(self) -> None:    Function
`_deprecation_constraint_check`    utility or script function.
L160: def install(    Function `install`    utility or script function.
L266: class InprocessBuildEnvironmentInstaller:    Class
(`InprocessBuildEnvironmentInstaller`)    component used by the app (see file context: None).
L280: def __init__(    Function `__init__`    utility or script function.
L320: def install(    Function `install`    utility or script function.
L372: def _install_impl(self, requirements: Iterable[str], prefix: _Prefix) -> None:
Function `_install_impl`    utility or script function.
L413: def _make_resolver(self) -> BaseResolver:    Function `_make_resolver`    utility or
script function.
L437: class BuildEnvironment:    Class (`BuildEnvironment`)    component used by the app (see
file context: None).
L440: def __init__(self, installer: BuildEnvironmentInstaller) -> None:    Function `__init__`
utility or script function.
L495: def __enter__(self) -> None:    Function `__enter__`    utility or script function.
L516: def __exit__(    Function `__exit__`    utility or script function.
L528: def check_requirements(    Function `check_requirements`    utility or script function.
L562: def install_requirements(    Function `install_requirements`    utility or script
function.
L578: class NoOpBuildEnvironment(BuildEnvironment):    Class (`NoOpBuildEnvironment`)
component used by the app (see file context: None).
L581: def __init__(self) -> None:    Function `__init__`    utility or script function.
L584: def __enter__(self) -> None:    Function `__enter__`    utility or script function.
L587: def __exit__(    Function `__exit__`    utility or script function.
L595: def cleanup(self) -> None:    Function `cleanup`    utility or script function.
L598: def install_requirements(    Function `install_requirements`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/configuration.py

```

L53: def _normalize_name(name: str) -> str:    Function `_normalize_name`    utility or script
function.
L60: def _disassemble_key(name: str) -> list[str]:    Function `_disassemble_key`    utility or
script function.
L70: def get_configuration_files() -> dict[Kind, list[str]]:    Function
`get_configuration_files`    Returns or fetches data.

```

```

L89: class Configuration:    Class (`Configuration`)    component used by the app (see file
context: None).
L103: def __init__(self, isolated: bool, load_only: Kind | None = None) -> None:    Function
`__init__`    utility or script function.
L124: def load(self) -> None:    Function `load`    Loads data from storage or remote.
L130: def get_file_to_edit(self) -> str | None:    Function `get_file_to_edit`    Returns or
fetches data.
L139: def items(self) -> Iterable[tuple[str, Any]]:    Function `items`    utility or script
function.
L145: def get_value(self, key: str) -> Any:    Function `get_value`    Returns or fetches data.
L160: def set_value(self, key: str, value: Any) -> None:    Function `set_value`    Sets or
updates a value.
L180: def unset_value(self, key: str) -> None:    Function `unset_value`    utility or script
function.
L214: def save(self) -> None:    Function `save`    Saves data to storage or remote.
L238: def _ensure_have_load_only(self) -> None:    Function `_ensure_have_load_only`    utility
or script function.
L244: def _dictionary(self) -> dict[str, dict[str, Any]]:    Function `_dictionary`    utility
or script function.
L255: def _load_config_files(self) -> None:    Function `_load_config_files`    utility or
script function.
L278: def _load_file(self, variant: Kind, fname: str) -> RawConfigParser:    Function
`_load_file`    utility or script function.
L289: def _construct_parser(self, fname: str) -> RawConfigParser:    Function
`_construct_parser`    utility or script function.
L310: def _load_environment_vars(self) -> None:    Function `_load_environment_vars`    utility
or script function.
L317: def _normalized_keys(    Function `_normalized_keys`    utility or script function.
L331: def get_envIRON_vars(self) -> Iterable[tuple[str, str]]:    Function `get_envIRON_vars`
Returns or fetches data.
L340: def iter_config_files(self) -> Iterable[tuple[Kind, list[str]]]:    Function
`iter_config_files`    utility or script function.
L372: def get_values_in_config(self, variant: Kind) -> dict[str, Any]:    Function
`get_values_in_config`    Returns or fetches data.
L376: def _get_parser_to_modify(self) -> tuple[str, RawConfigParser]:    Function
`_get_parser_to_modify`    utility or script function.
L390: def _mark_as_modified(self, fname: str, parser: RawConfigParser) -> None:    Function
`_mark_as_modified`    utility or script function.
L395: def __repr__(self) -> str:    Function `__repr__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/wheel_builder.py

```

L34: def _contains_egg_info(s: str) -> bool:    Function `_contains_egg_info`    utility or
script function.
L42: def _should_cache(    Function `_should_cache`    utility or script function.
L73: def _get_cache_dir(    Function `_get_cache_dir`    utility or script function.
L89: def _verify_one(req: InstallRequirement, wheel_path: str) -> None:    Function
`_verify_one`    utility or script function.

```

```

L118: def _build_one(    Function `_build_one`    utility or script function.
L152: def _build_one_inside_env(    Function `_build_one_inside_env`    utility or script
function.
L204: def build(    Function `build`    Constructs or prepares an object.

```

.venv/lib/python3.12/site-packages/pip/_internal/exceptions.py

```

L44: def _is_kebab_case(s: str) -> bool:    Function `_is_kebab_case`    utility or script
function.
L48: def _prefix_with_indent(    Function `_prefix_with_indent`    utility or script function.
L65: class PipError(Exception):    Class (`PipError`)    component used by the app (see file
context: None).
L69: class DiagnosticPipError(PipError):    Class (`DiagnosticPipError`)    component used by
the app (see file context: None).
L82: def __init__(    Function `__init__`    utility or script function.
L112: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L123: def __rich_console__(    Function `__rich_console__`    utility or script function.
L187: class ConfigurationError(PipError):    Class (`ConfigurationError`)    component used by
the app (see file context: None).
L191: class InstallationError(PipError):    Class (`InstallationError`)    component used by the
app (see file context: None).
L195: class FailedToPrepareCandidate(InstallationError):    Class (`FailedToPrepareCandidate`)
component used by the app (see file context: None).
L203: def __init__(    Function `__init__`    utility or script function.
L212: class MissingPyProjectBuildRequires(DiagnosticPipError):    Class
(`MissingPyProjectBuildRequires`)    component used by the app (see file context: None).
L217: def __init__(self, *, package: str) -> None:    Function `__init__`    utility or script
function.
L229: class InvalidPyProjectBuildRequires(DiagnosticPipError):    Class
(`InvalidPyProjectBuildRequires`)    component used by the app (see file context: None).
L234: def __init__(self, *, package: str, reason: str) -> None:    Function `__init__`
utility or script function.
L246: class NoneMetadataError(PipError):    Class (`NoneMetadataError`)    component used by the
app (see file context: None).
L255: def __init__(    Function `__init__`    utility or script function.
L268: def __str__(self) -> str:    Function `__str__`    utility or script function.
L274: class UserInstallationInvalid(InstallationError):    Class (`UserInstallationInvalid`)
component used by the app (see file context: None).
L277: def __str__(self) -> str:    Function `__str__`    utility or script function.
L281: class InvalidSchemeCombination(InstallationError):    Class (`InvalidSchemeCombination`)
component used by the app (see file context: None).
L282: def __str__(self) -> str:    Function `__str__`    utility or script function.
L287: class DistributionNotFound(InstallationError):    Class (`DistributionNotFound`)
component used by the app (see file context: None).
L291: class RequirementsFileParseError(InstallationError):    Class
(`RequirementsFileParseError`)    component used by the app (see file context: None).
L295: class BestVersionAlreadyInstalled(PipError):    Class (`BestVersionAlreadyInstalled`)
component used by the app (see file context: None).

```

```

L300: class BadCommand(PipError):    Class (`BadCommand`)    component used by the app (see file
context: None).
L304: class CommandError(PipError):    Class (`CommandError`)    component used by the app (see
file context: None).
L308: class PreviousBuildDirError(PipError):    Class (`PreviousBuildDirError`)    component
used by the app (see file context: None).
L312: class NetworkConnectionError(PipError):    Class (`NetworkConnectionError`)    component
used by the app (see file context: None).
L315: def __init__(    Function `__init__`    utility or script function.
L336: def __str__(self) -> str:    Function `__str__`    utility or script function.
L340: class InvalidWheelFilename(InstallationError):    Class (`InvalidWheelFilename`)
component used by the app (see file context: None).
L344: class UnsupportedWheel(InstallationError):    Class (`UnsupportedWheel`)    component used
by the app (see file context: None).
L348: class InvalidWheel(InstallationError):    Class (`InvalidWheel`)    component used by the
app (see file context: None).
L351: def __init__(self, location: str, name: str):    Function `__init__`    utility or script
function.
L355: def __str__(self) -> str:    Function `__str__`    utility or script function.
L359: class MetadataInconsistent(InstallationError):    Class (`MetadataInconsistent`)
component used by the app (see file context: None).
L367: def __init__(    Function `__init__`    utility or script function.
L375: def __str__(self) -> str:    Function `__str__`    utility or script function.
L382: class MetadataInvalid(InstallationError):    Class (`MetadataInvalid`)    component used
by the app (see file context: None).
L385: def __init__(self, ireq: InstallRequirement, error: str) -> None:    Function `__init__`
utility or script function.
L389: def __str__(self) -> str:    Function `__str__`    utility or script function.
L393: class InstallationSubprocessError(DiagnosticPipError, InstallationError):    Class
(`InstallationSubprocessError`)    component used by the app (see file context: None).
L398: def __init__(    Function `__init__`    utility or script function.
L430: def __str__(self) -> str:    Function `__str__`    utility or script function.
L434: class MetadataGenerationFailed(DiagnosticPipError, InstallationError):    Class
(`MetadataGenerationFailed`)    component used by the app (see file context: None).
L437: def __init__(    Function `__init__`    utility or script function.
L449: def __str__(self) -> str:    Function `__str__`    utility or script function.
L453: class HashErrors(InstallationError):    Class (`HashErrors`)    component used by the app
(see file context: None).
L456: def __init__(self) -> None:    Function `__init__`    utility or script function.
L459: def append(self, error: HashError) -> None:    Function `append`    utility or script
function.
L462: def __str__(self) -> str:    Function `__str__`    utility or script function.
L472: def __bool__(self) -> bool:    Function `__bool__`    utility or script function.
L476: class HashError(InstallationError):    Class (`HashError`)    component used by the app
(see file context: None).
L497: def body(self) -> str:    Function `body`    utility or script function.
L509: def __str__(self) -> str:    Function `__str__`    utility or script function.
L512: def _requirement_name(self) -> str:    Function `_requirement_name`    utility or script
function.
L522: class VcsHashUnsupported(HashError):    Class (`VcsHashUnsupported`)    component used by
the app (see file context: None).

```

```

L533: class DirectoryUrlHashUnsupported(HashError):    Class (`DirectoryUrlHashUnsupported`)
component used by the app (see file context: None).
L544: class HashMissing(HashError):    Class (`HashMissing`)    component used by the app (see
file context: None).
L558: def __init__(self, gotten_hash: str) -> None:    Function `__init__`    utility or script
function.
L565: def body(self) -> str:    Function `body`    utility or script function.
L586: class HashUnpinned(HashError):    Class (`HashUnpinned`)    component used by the app (see
file context: None).
L597: class HashMismatch(HashError):    Class (`HashMismatch`)    component used by the app (see
file context: None).
L615: def __init__(self, allowed: dict[str, list[str]], got: dict[str, _Hash]) -> None:
Function `__init__`    utility or script function.
L625: def body(self) -> str:    Function `body`    utility or script function.
L628: def _hash_comparison(self) -> str:    Function `_hash_comparison`    utility or script
function.
L640: def hash_then_or(hash_name: str) -> chain[str]:    Function `hash_then_or`    utility or
script function.
L655: class UnsupportedPythonVersion(InstallationError):    Class (`UnsupportedPythonVersion`)
component used by the app (see file context: None).
L660: class ConfigurationFileCouldNotBeLoaded(ConfigurationError):    Class
(`ConfigurationFileCouldNotBeLoaded`)    component used by the app (see file context: None).
L663: def __init__(    Function `__init__`    utility or script function.
L674: def __str__(self) -> str:    Function `__str__`    utility or script function.
L690: class ExternallyManagedEnvironment(DiagnosticPipError):    Class
(`ExternallyManagedEnvironment`)    component used by the app (see file context: None).
L702: def __init__(self, error: str | None) -> None:    Function `__init__`    utility or script
function.
L720: def _iter_externally_managed_error_keys() -> Iterator[str]:    Function
`_iter_externally_managed_error_keys`    utility or script function.
L742: def from_config(    Function `from_config`    utility or script function.
L763: class UninstallMissingRecord(DiagnosticPipError):    Class (`UninstallMissingRecord`)
component used by the app (see file context: None).
L766: def __init__(self, *, distribution: BaseDistribution) -> None:    Function `__init__`
utility or script function.
L790: class LegacyDistutilsInstall(DiagnosticPipError):    Class (`LegacyDistutilsInstall`)
component used by the app (see file context: None).
L793: def __init__(self, *, distribution: BaseDistribution) -> None:    Function `__init__`
utility or script function.
L805: class InvalidInstalledPackage(DiagnosticPipError):    Class (`InvalidInstalledPackage`)
component used by the app (see file context: None).
L808: def __init__(    Function `__init__`    utility or script function.
L835: class IncompleteDownloadError(DiagnosticPipError):    Class (`IncompleteDownloadError`)
component used by the app (see file context: None).
L841: def __init__(self, download: _FileDownload) -> None:    Function `__init__`    utility or
script function.
L869: class ResolutionTooDeepError(DiagnosticPipError):    Class (`ResolutionTooDeepError`)
component used by the app (see file context: None).
L874: def __init__(self) -> None:    Function `__init__`    utility or script function.
L889: class InstallWheelBuildError(DiagnosticPipError):    Class (`InstallWheelBuildError`)
component used by the app (see file context: None).

```

```

L892: def __init__(self, failed: list[InstallRequirement]) -> None:    Function `__init__`
utility or script function.
L903: class InvalidEggFragment(DiagnosticPipError):    Android UI component
(`InvalidEggFragment`)    activity/fragment presenting screens to the user.
L906: def __init__(self, link: Link, fragment: str) -> None:    Function `__init__`    utility
or script function.
L926: class BuildDependencyInstallError(DiagnosticPipError):    Class
(`BuildDependencyInstallError`)    component used by the app (see file context: None).
L931: def __init__(    Function `__init__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/__init__.py

```

L10: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main
routine.

```

.venv/lib/python3.12/site-packages/pip/_internal/cache.py

```

L27: def _hash_dict(d: dict[str, str]) -> str:    Function `_hash_dict`    utility or script
function.
L33: class Cache:    Class (`Cache`)    component used by the app (see file context: None).
L39: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script
function.
L44: def _get_cache_path_parts(self, link: Link) -> list[str]:    Function
`_get_cache_path_parts`    utility or script function.
L77: def _get_candidates(self, link: Link, canonical_package_name: str) -> list[Any]:
Function `_get_candidates`    utility or script function.
L87: def get_path_for_link(self, link: Link) -> str:    Function `get_path_for_link`    Returns
or fetches data.
L91: def get(    Function `get`    Returns or fetches data.
L103: class SimpleWheelCache(Cache):    Class (`SimpleWheelCache`)    component used by the app
(see file context: None).
L106: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script
function.
L109: def get_path_for_link(self, link: Link) -> str:    Function `get_path_for_link`    Returns
or fetches data.
L129: def get(    Function `get`    Returns or fetches data.
L173: class EphemWheelCache(SimpleWheelCache):    Class (`EphemWheelCache`)    component used by
the app (see file context: None).
L176: def __init__(self) -> None:    Function `__init__`    utility or script function.
L185: class CacheEntry:    Class (`CacheEntry`)    component used by the app (see file context:
None).
L186: def __init__(    Function `__init__`    utility or script function.
L209: class WheelCache(Cache):    Class (`WheelCache`)    component used by the app (see file
context: None).
L216: def __init__(self, cache_dir: str) -> None:    Function `__init__`    utility or script
function.

```



```

L221: def get_path_for_link(self, link: Link) -> str:    Function `get_path_for_link` Returns
or fetches data.
L224: def get_ephem_path_for_link(self, link: Link) -> str:    Function
`get_ephem_path_for_link` Returns or fetches data.
L227: def get(    Function `get` Returns or fetches data.
L238: def get_cache_entry(    Function `get_cache_entry` Returns or fetches data.
L267: def record_download_origin(cache_dir: str, download_info: DirectUrl) -> None:
Function `record_download_origin` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/self_outdated_check.py

```

L47: def _get_statefile_name(key: str) -> str:    Function `_get_statefile_name` utility or
script function.
L53: class SelfCheckState:    Class (`SelfCheckState`) component used by the app (see file
context: None).
L54: def __init__(self, cache_dir: str) -> None:    Function `__init__` utility or script
function.
L72: def key(self) -> str:    Function `key` utility or script function.
L75: def get(self, current_time: datetime.datetime) -> str | None:    Function `get` Returns
or fetches data.
L94: def set(self, pypi_version: str, current_time: datetime.datetime) -> None:    Function
`set` Sets or updates a value.
L133: class UpgradePrompt:    Class (`UpgradePrompt`) component used by the app (see file
context: None).
L137: def __rich__(self) -> Group:    Function `__rich__` utility or script function.
L157: def _get_current_remote_pip_version(    Function `_get_current_remote_pip_version`
utility or script function.
L185: def _compute_upgrade_prompt(    Function `_compute_upgrade_prompt` utility or script
function.
L206: def pip_self_version_check_fetch(    Function `pip_self_version_check_fetch` utility or
script function.
L243: def pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
Function `pip_self_version_check_emit` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/main.py

```

L4: def main(args: list[str] | None = None) -> int:    Function `main` Entry point / main
routine.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/list.py

```

L27: class _DistWithLatestInfo(BaseDistribution):    Class (`_DistWithLatestInfo`) component

```

```

used by the app (see file context: None).
L43: class ListCommand(IndexGroupCommand):    Class (`ListCommand`)    component used by the app
(see file context: None).
L54: def add_options(self) -> None:    Function `add_options`    utility or script function.
L140: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check`    utility or script function.
L147: def _build_package_finder(    Function `_build_package_finder`    utility or script
function.
L170: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L213: def get_outdated(    Function `get_outdated`    Returns or fetches data.
L222: def get_uptodate(    Function `get_uptodate`    Returns or fetches data.
L231: def get_not_required(    Function `get_not_required`    Returns or fetches data.
L245: def iter_packages_latest_infos(    Function `iter_packages_latest_infos`    utility or
script function.
L251: def latest_info(    Function `latest_info`    utility or script function.
L282: def output_package_listing(    Function `output_package_listing`    utility or script
function.
L305: def output_package_listing_columns(    Function `output_package_listing_columns`
utility or script function.
L322: def format_for_columns(    Function `format_for_columns`    utility or script function.
L335: def wheel_build_tag(dist: BaseDistribution) -> str | None:    Function `wheel_build_tag`
utility or script function.
L382: def format_for_json(packages: _ProcessedDists, options: Values) -> str:    Function
`format_for_json`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/install.py

```

L91: def _prevent_import_hook(name: str, args: tuple[Any, ...]) -> None:    Function
`_prevent_import_hook`    utility or script function.
L109: def _eagerly_import_modules() -> None:    Function `_eagerly_import_modules`    utility or
script function.
L120: def _prevent_further_imports() -> None:    Function `_prevent_further_imports`    utility
or script function.
L134: def _arg_refers_to_pip(arg: str) -> bool:    Function `_arg_refers_to_pip`    utility or
script function.
L142: class InstallCommand(RequirementCommand):    Class (`InstallCommand`)    component used by
the app (see file context: None).
L162: def add_options(self) -> None:    Function `add_options`    utility or script function.
L358: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check`    utility or script function.
L369: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L604: def _handle_target_dir(    Function `_handle_target_dir`    utility or script function.
L658: def _determine_conflicts(    Function `_determine_conflicts`    utility or script
function.
L670: def _warn_about_conflicts(    Function `_warn_about_conflicts`    utility or script
function.

```

```

L721: def installed_packages_summary(    Function `installed_packages_summary`    utility or
script function.
L745: def get_lib_location_guesses(    Function `get_lib_location_guesses`    Returns or fetches
data.
L763: def site_packages_writable(root: str | None, isolated: bool) -> bool:    Function
`sites_packages_writable`    utility or script function.
L770: def decide_user_install(    Function `decide_user_install`    utility or script function.
L839: def create_os_error_message(    Function `create_os_error_message`    Creates a resource
or document.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/lock.py

```

L26: class LockCommand(RequirementCommand):    Class (`LockCommand`)    component used by the
app (see file context: None).
L48: def add_options(self) -> None:    Function `add_options`    utility or script function.
L95: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/uninstall.py

```

L25: class UninstallCommand(Command, SessionCommandMixin):    Class (`UninstallCommand`)
component used by the app (see file context: None).
L40: def add_options(self) -> None:    Function `add_options`    utility or script function.
L64: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/index.py

```

L30: class IndexCommand(IndexGroupCommand):    Class (`IndexCommand`)    component used by the
app (see file context: None).
L40: def add_options(self) -> None:    Function `add_options`    utility or script function.
L60: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map`    utility or script function.
L65: def run(self, options: Values, args: list[str]) -> int:    Function `run`    utility or
script function.
L89: def _build_package_finder(    Function `_build_package_finder`    utility or script
function.
L116: def get_available_package_versions(self, options: Values, args: list[Any]) -> None:
Function `get_available_package_versions`    Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/debug.py

```

L28: def show_value(name: str, value: Any) -> None:    Function `show_value` utility or
script function.
L32: def show_sys_implementation() -> None:    Function `show_sys_implementation` utility or
script function.
L39: def create_vendor_txt_map() -> dict[str, str]:    Function `create_vendor_txt_map`
Creates a resource or document.
L51: def get_module_from_module_name(module_name: str) -> ModuleType | None:    Function
`get_module_from_module_name` Returns or fetches data.
L62: def get_vendor_version_from_module(module_name: str) -> str | None:    Function
`get_vendor_version_from_module` Returns or fetches data.
L77: def show_actual_vendor_versions(vendor_txt_versions: dict[str, str]) -> None:    Function
`show_actual_vendor_versions` utility or script function.
L98: def show_vendor_versions() -> None:    Function `show_vendor_versions` utility or script
function.
L106: def show_tags(options: Values) -> None:    Function `show_tags` utility or script
function.
L136: def ca_bundle_info(config: Configuration) -> str:    Function `ca_bundle_info` utility
or script function.
L153: class DebugCommand(Command):    Class (`DebugCommand`) component used by the app (see
file context: None).
L162: def add_options(self) -> None:    Function `add_options` utility or script function.
L167: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/help.py

```

L8: class HelpCommand(Command):    Class (`HelpCommand`) component used by the app (see file
context: None).
L15: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/freeze.py

```

L11: def _should_suppress_build_backends() -> bool:    Function
`_should_suppress_build_backends` utility or script function.
L15: def _dev_pkgs() -> set[str]:    Function `_dev_pkgs` utility or script function.
L24: class FreezeCommand(Command):    Class (`FreezeCommand`) component used by the app (see
file context: None).
L35: def add_options(self) -> None:    Function `add_options` utility or script function.
L87: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/configuration.py

```

L24: class ConfigurationCommand(Command):    Class (`ConfigurationCommand`) component used by
the app (see file context: None).
L60: def add_options(self) -> None:    Function `add_options` utility or script function.
L98: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map` utility or script function.
L108: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L146: def _determine_file(self, options: Values, need_value: bool) -> Kind | None:    Function
`_determine_file` utility or script function.
L176: def list_values(self, options: Values, args: list[str]) -> None:    Function
`list_values` utility or script function.
L183: def get_name(self, options: Values, args: list[str]) -> None:    Function `get_name`
Returns or fetches data.
L189: def set_name_value(self, options: Values, args: list[str]) -> None:    Function
`set_name_value` Sets or updates a value.
L195: def unset_name(self, options: Values, args: list[str]) -> None:    Function `unset_name`
utility or script function.
L201: def list_config_values(self, options: Values, args: list[str]) -> None:    Function
`list_config_values` utility or script function.
L217: def print_config_file_values(self, variant: Kind, fname: str) -> None:    Function
`print_config_file_values` utility or script function.
L225: def print_env_var_values(self) -> None:    Function `print_env_var_values` utility or
script function.
L233: def open_in_editor(self, options: Values, args: list[str]) -> None:    Function
`open_in_editor` utility or script function.
L255: def _get_n_args(self, args: list[str], example: str, n: int) -> Any:    Function
`_get_n_args` utility or script function.
L269: def _save_configuration(self) -> None:    Function `_save_configuration` utility or
script function.
L280: def _determine_editor(self, options: Values) -> str:    Function `_determine_editor`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/search.py

```

L26: class TransformedHit(TypedDict):    Class (`TransformedHit`) component used by the app
(see file context: None).
L35: class SearchCommand(Command, SessionCommandMixin):    Class (`SearchCommand`) component
used by the app (see file context: None).
L42: def add_options(self) -> None:    Function `add_options` utility or script function.
L54: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L70: def search(self, query: list[str], options: Values) -> list[dict[str, str]]:    Function
`search` utility or script function.
L88: def transform_hits(hits: list[dict[str, str]]) -> list[TransformedHit]:    Function

```

```

`transform_hits` utility or script function.
L116: def print_dist_installation_info(latest: str, dist: BaseDistribution | None) -> None:
Function `print_dist_installation_info` utility or script function.
L133: def get_installed_distribution(name: str) -> BaseDistribution | None:    Function
`get_installed_distribution` Returns or fetches data.
L138: def print_results(    Function `print_results` utility or script function.
L177: def highest_version(versions: list[str]) -> str:    Function `highest_version` utility
or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/__init__.py

```

L116: def create_command(name: str, **kwargs: Any) -> Command:    Function `create_command`
Creates a resource or document.
L128: def get_similar_commands(name: str) -> str | None:    Function `get_similar_commands`
Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/cache.py

```

L16: class CacheCommand(Command):    Class (`CacheCommand`) component used by the app (see
file context: None).
L40: def add_options(self) -> None:    Function `add_options` utility or script function.
L52: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:    Function
`handler_map` utility or script function.
L61: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L87: def get_cache_dir(self, options: Values, args: list[str]) -> None:    Function
`get_cache_dir` Returns or fetches data.
L93: def get_cache_info(self, options: Values, args: list[str]) -> None:    Function
`get_cache_info` Returns or fetches data.
L135: def list_cache_items(self, options: Values, args: list[str]) -> None:    Function
`list_cache_items` utility or script function.
L150: def format_for_human(self, files: list[str]) -> None:    Function `format_for_human`
utility or script function.
L163: def format_for_abspath(self, files: list[str]) -> None:    Function `format_for_abspath`
utility or script function.
L167: def remove_cache_items(self, options: Values, args: list[str]) -> None:    Function
`remove_cache_items` utility or script function.
L218: def purge_cache(self, options: Values, args: list[str]) -> None:    Function
`purge_cache` utility or script function.
L224: def _cache_dir(self, options: Values, subdir: str) -> str:    Function `_cache_dir`
utility or script function.
L227: def _find_http_files(self, options: Values) -> list[str]:    Function `_find_http_files`
utility or script function.
L234: def _find_wheels(self, options: Values, pattern: str) -> list[str]:    Function
`_find_wheels` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/commands/completion.py

```
L81: class CompletionCommand(Command):    Class (`CompletionCommand`) component used by the
app (see file context: None).
L86: def add_options(self) -> None:    Function `add_options` utility or script function.
L122: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/show.py

```
L20: def normalize_project_url_label(label: str) -> str:    Function
`normalize_project_url_label` utility or script function.
L27: class ShowCommand(Command):    Class (`ShowCommand`) component used by the app (see file
context: None).
L38: def add_options(self) -> None:    Function `add_options` utility or script function.
L50: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L64: class _PackageInfo(NamedTuple):    Class (`_PackageInfo`) component used by the app (see
file context: None).
L85: def search_packages_info(query: list[str]) -> Generator[_PackageInfo, None, None]:
Function `search_packages_info` utility or script function.
L102: def _get_requiring_packages(current_dist: BaseDistribution) -> Iterator[str]:
Function `_get_requiring_packages` utility or script function.
L178: def print_results(    Function `print_results` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/hash.py

```
L14: class HashCommand(Command):    Class (`HashCommand`) component used by the app (see file
context: None).
L25: def add_options(self) -> None:    Function `add_options` utility or script function.
L39: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L52: def _hash_of_file(path: str, algorithm: str) -> str:    Function `_hash_of_file` utility
or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/download.py

```
L16: class DownloadCommand(RequirementCommand):    Class (`DownloadCommand`) component used
by the app (see file context: None).
L36: def add_options(self) -> None:    Function `add_options` utility or script function.
```

```
L78: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/inspect.py

```
L19: class InspectCommand(Command):    Class (`InspectCommand`) component used by the app
(see file context: None).
L28: def add_options(self) -> None:    Function `add_options` utility or script function.
L48: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
L65: def _dist_to_dict(self, dist: BaseDistribution) -> dict[str, Any]:    Function
`_dist_to_dict` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/check.py

```
L18: class CheckCommand(Command):    Class (`CheckCommand`) component used by the app (see
file context: None).
L25: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/commands/wheel.py

```
L22: class WheelCommand(RequirementCommand):    Class (`WheelCommand`) component used by the
app (see file context: None).
L42: def add_options(self) -> None:    Function `add_options` utility or script function.
L94: def run(self, options: Values, args: list[str]) -> int:    Function `run` utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/models/link.py

```
L40: class LinkHash:    Class (`LinkHash`) component used by the app (see file context:
None).
L64: def __post_init__(self) -> None:    Function `__post_init__` utility or script function.
L69: def find_hash_url_fragment(cls, url: str) -> LinkHash | None:    Function
`find_hash_url_fragment` utility or script function.
L77: def as_dict(self) -> dict[str, str]:    Function `as_dict` utility or script function.
L80: def as_hashes(self) -> Hashes:    Function `as_hashes` utility or script function.
L84: def is_hash_allowed(self, hashes: Hashes | None) -> bool:    Function `is_hash_allowed`
utility or script function.
L94: class MetadataFile:    Class (`MetadataFile`) component used by the app (see file
context: None).
L99: def __post_init__(self) -> None:    Function `__post_init__` utility or script function.
```



```

L104: def supported_hashes(hashes: dict[str, str] | None) -> dict[str, str] | None:
Function `supported_hashes` utility or script function.
L115: def _clean_url_path_part(part: str) -> str: Function `_clean_url_path_part` utility
or script function.
L123: def _clean_file_url_path(part: str) -> str: Function `_clean_file_url_path` utility
or script function.
L144: def _clean_url_path(path: str, is_local_path: bool) -> str: Function
`_clean_url_path` utility or script function.
L166: def _ensure_quoted_url(url: str) -> str: Function `_ensure_quoted_url` utility or
script function.
L185: def _absolute_link_url(base_url: str, url: str) -> str: Function `_absolute_link_url`
utility or script function.
L197: class Link: Class (`Link`) component used by the app (see file context: None).
L214: def __init__( Function `_init__` utility or script function.
L283: def from_json( Function `from_json` utility or script function.
L340: def from_element( Function `from_element` utility or script function.
L391: def __str__(self) -> str: Function `__str__` utility or script function.
L401: def __repr__(self) -> str: Function `__repr__` utility or script function.
L404: def __hash__(self) -> int: Function `__hash__` utility or script function.
L407: def __eq__(self, other: Any) -> bool: Function `__eq__` utility or script function.
L412: def __lt__(self, other: Any) -> bool: Function `__lt__` utility or script function.
L418: def url(self) -> str: Function `url` utility or script function.
L422: def redacted_url(self) -> str: Function `redacted_url` utility or script function.
L426: def filename(self) -> str: Function `filename` utility or script function.
L440: def file_path(self) -> str: Function `file_path` utility or script function.
L444: def scheme(self) -> str: Function `scheme` utility or script function.
L448: def netloc(self) -> str: Function `netloc` utility or script function.
L455: def path(self) -> str: Function `path` utility or script function.
L458: def splitext(self) -> tuple[str, str]: Function `splitext` utility or script
function.
L462: def ext(self) -> str: Function `ext` utility or script function.
L466: def url_without_fragment(self) -> str: Function `url_without_fragment` utility or
script function.
L477: def _egg_fragment(self) -> str | None: Function `_egg_fragment` utility or script
function.
L493: def subdirectory_fragment(self) -> str | None: Function `subdirectory_fragment`
utility or script function.
L499: def metadata_link(self) -> Link | None: Function `metadata_link` utility or script
function.
L508: def as_hashes(self) -> Hashes: Function `as_hashes` utility or script function.
L512: def hash(self) -> str | None: Function `hash` utility or script function.
L516: def hash_name(self) -> str | None: Function `hash_name` utility or script function.
L520: def show_url(self) -> str: Function `show_url` utility or script function.
L524: def is_file(self) -> bool: Function `is_file` utility or script function.
L527: def is_existing_dir(self) -> bool: Function `is_existing_dir` utility or script
function.
L531: def is_wheel(self) -> bool: Function `is_wheel` utility or script function.
L535: def is_vcs(self) -> bool: Function `is_vcs` utility or script function.
L541: def is_yanked(self) -> bool: Function `is_yanked` utility or script function.
L545: def has_hash(self) -> bool: Function `has_hash` utility or script function.
L548: def is_hash_allowed(self, hashes: Hashes | None) -> bool: Function `is_hash_allowed`

```

```

utility or script function.
L557: class _CleanResult(NamedTuple):    Class (`_CleanResult`)    component used by the app
(see file context: None).
L589: def _clean_link(link: Link) -> _CleanResult:    Function `_clean_link`    utility or
script function.
L616: def links_equivalent(link1: Link, link2: Link) -> bool:    Function `links_equivalent`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/candidate.py

```

L10: class InstallationCandidate:    Class (`InstallationCandidate`)    component used by the
app (see file context: None).
L17: def __init__(self, name: str, version: str, link: Link) -> None:    Function `__init__`
utility or script function.
L22: def __str__(self) -> str:    Function `__str__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/direct_url.py

```

L30: class DirectUrl(PackagingDirectUrl):    Class (`DirectUrl`)    component used by the app
(see file context: None).
L31: def to_dict_compat(self) -> dict[str, Any]:    Function `to_dict_compat`    utility or
script function.
L35: def from_json(cls, s: str) -> DirectUrl:    Function `from_json`    utility or script
function.
L38: def to_json(self) -> str:    Function `to_json`    utility or script function.
L41: def is_local_editable(self) -> bool:    Function `is_local_editable`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/index.py

```

L4: class PackageIndex:    Class (`PackageIndex`)    component used by the app (see file
context: None).
L9: def __init__(self, url: str, file_storage_domain: str) -> None:    Function `__init__`
utility or script function.
L21: def _url_for_path(self, path: str) -> str:    Function `_url_for_path`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/search_scope.py

```

L18: class SearchScope:    Class (`SearchScope`)    component used by the app (see file context:

```

```

None).
L28: def create(    Function `create`    Creates a resource or document.
L69: def get_formatted_locations(self) -> str:    Function `get_formatted_locations`    Returns
or fetches data.
L104: def get_index_urls_locations(self, project_name: str) -> list[str]:    Function
`get_index_urls_locations`    Returns or fetches data.
L111: def mkurl_pypi_url(url: str) -> str:    Function `mkurl_pypi_url`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/format_control.py

```

L8: class FormatControl:    Class (`FormatControl`)    component used by the app (see file
context: None).
L13: def __init__(    Function `__init__`    utility or script function.
L26: def __eq__(self, other: object) -> bool:    Object (singleton).
L35: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L39: def handle_mutual_excludes(value: str, target: set[str], other: set[str]) -> None:
Function `handle_mutual_excludes`    utility or script function.
L61: def get_allowed_formats(self, canonical_name: str) -> frozenset[str]:    Function
`get_allowed_formats`    Returns or fetches data.
L73: def disallow_binaries(self) -> None:    Function `disallow_binaries`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/target_python.py

```

L11: class TargetPython:    Class (`TargetPython`)    component used by the app (see file
context: None).
L28: def __init__(    Function `__init__`    utility or script function.
L69: def format_given(self) -> str:    Function `format_given`    utility or script function.
L89: def get_sorted_tags(self) -> list[Tag]:    Function `get_sorted_tags`    Returns or fetches
data.
L114: def get_unsorted_tags(self) -> set[Tag]:    Function `get_unsorted_tags`    Returns or
fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/installation_report.py

```

L10: class InstallationReport:    Class (`InstallationReport`)    component used by the app (see
file context: None).
L11: def __init__(self, install_requirements: Sequence[InstallRequirement]):    Function

```

```

`__init__` utility or script function.
L15: def _install_req_to_dict(cls, ireq: InstallRequirement) -> dict[str, Any]: Function
`_install_req_to_dict` utility or script function.
L43: def to_dict(self) -> dict[str, Any]: Function `to_dict` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/selection_prefs.py

```

L10: class SelectionPreferences: Class (`SelectionPreferences`) component used by the app
(see file context: None).

```

.venv/lib/python3.12/site-packages/pip/_internal/models/scheme.py

```

L14: class Scheme: Class (`Scheme`) component used by the app (see file context: None).

```

.venv/lib/python3.12/site-packages/pip/_internal/models/wheel.py

```

L18: class Wheel: Class (`Wheel`) component used by the app (see file context: None).
L21: def __init__(self, filename: str) -> None: Function `__init__` utility or script
function.
L32: def get_formatted_file_tags(self) -> list[str]: Function `get_formatted_file_tags`
Returns or fetches data.
L36: def support_index_min(self, tags: list[Tag]) -> int: Function `support_index_min`
utility or script function.
L54: def find_most_preferred_tag( Function `find_most_preferred_tag` utility or script
function.
L75: def supported(self, tags: Iterable[Tag]) -> bool: Function `supported` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/models/release_control.py

```

L11: class ReleaseControl: Class (`ReleaseControl`) component used by the app (see file
context: None).
L20: def handle_mutual_excludes( Function `handle_mutual_excludes` utility or script
function.
L59: def get_ordered_args(self) -> list[tuple[str, str]]: Function `get_ordered_args`
Returns or fetches data.
L74: def allows_prereleases(self, canonical_name: NormalizedName) -> bool | None: Function
`allows_prereleases` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/compat.py

```
L16: def has_tls() -> bool:    Function `has_tls` utility or script function.
L29: def get_path_uid(path: str) -> int:    Function `get_path_uid` Returns or fetches data.
L62: def open_text_resource(    Function `open_text_resource` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/entrypoints.py

```
L24: def _wrapper(args: list[str] | None = None) -> int:    Function `_wrapper` utility or
script function.
L47: def get_best_invocation_for_this_pip() -> str:    Function
`get_best_invocation_for_this_pip` Returns or fetches data.
L74: def get_best_invocation_for_this_python() -> str:    Function
`get_best_invocation_for_this_python` Returns or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/datetime.py

```
L7: def today_is_later_than(year: int, month: int, day: int) -> bool:    Function
`today_is_later_than` utility or script function.
L14: def parse_iso_datetime(isodate: str) -> datetime.datetime:    Function
`parse_iso_datetime` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/urls.py

```
L9: def path_to_url(path: str) -> str:    Function `path_to_url` utility or script function.
L19: def url_to_path(url: str) -> str:    Function `url_to_path` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/_jaraco_text.py

```
L36: def _nonblank(str):    Function `_nonblank` utility or script function.
L41: def yield_lines(iterable):    Function `yield_lines` utility or script function.
L60: def _(text):    Function `_` utility or script function.
L64: def drop_comment(line):    Function `drop_comment` utility or script function.
L79: def join_continuation(lines):    Function `join_continuation` utility or script
function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/appdirs.py

```
L15: def user_cache_dir(appname: str) -> str:    Function `user_cache_dir` utility or script
```

```
function.
L19: def _macos_user_config_dir(appname: str, roaming: bool = True) -> str:    Function
`_macos_user_config_dir` utility or script function.
L33: def user_config_dir(appname: str, roaming: bool = True) -> str:    Function
`user_config_dir` utility or script function.
L42: def site_config_dirs(appname: str) -> list[str]:    Function `site_config_dirs` utility
or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utls/filesystem.py

```
L19: def check_path_owner(path: str) -> bool:    Function `check_path_owner` utility or
script function.
L47: def adjacent_tmp_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
Function `adjacent_tmp_file` utility or script function.
L76: def test_writable_dir(path: str) -> bool:    Function `test_writable_dir` utility or
script function.
L94: def _test_writable_dir_win(path: str) -> bool:    Function `_test_writable_dir_win`
utility or script function.
L122: def find_files(path: str, pattern: str) -> list[str]:    Function `find_files` utility
or script function.
L132: def file_size(path: str) -> int | float:    Function `file_size` utility or script
function.
L139: def format_file_size(path: str) -> str:    Function `format_file_size` utility or
script function.
L143: def directory_size(path: str) -> int | float:    Function `directory_size` utility or
script function.
L152: def format_directory_size(path: str) -> str:    Function `format_directory_size`
utility or script function.
L156: def copy_directory_permissions(directory: str, target_file: BinaryIO) -> None:
Function `copy_directory_permissions` utility or script function.
L168: def _subdirs_without_generic(    Function `_subdirs_without_generic` utility or script
function.
L192: def subdirs_without_files(path: str) -> Generator[Path]:    Function
`subdirs_without_files` utility or script function.
L197: def subdirs_without_wheels(path: str) -> Generator[Path]:    Function
`subdirs_without_wheels` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utls/retry.py

```
L14: def retry(    Function `retry` utility or script function.
L28: def wrapper(func: Callable[P, T]) -> Callable[P, T]:    Function `wrapper` utility or
script function.
L31: def retry_wrapped(*args: P.args, **kwargs: P.kwargs) -> T:    Function `retry_wrapped`
utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/logging.py

```

L40: class BrokenStdoutLoggingError(Exception):    Class (`BrokenStdoutLoggingError`)
component used by the app (see file context: None).
L46: def _is_broken_pipe_error(exc_class: type[BaseException], exc: BaseException) -> bool:
Function `_is_broken_pipe_error` utility or script function.
L60: def capture_logging() -> Generator[StringIO, None, None]:    Function `capture_logging`
utility or script function.
L92: def indent_log(num: int = 2) -> Generator[None, None, None]:    Function `indent_log`
utility or script function.
L106: def get_indentation() -> int:    Function `get_indentation` Returns or fetches data.
L110: class IndentingFormatter(logging.Formatter):    Class (`IndentingFormatter`) component
used by the app (see file context: None).
L113: def __init__(    Function `__init__` utility or script function.
L128: def get_message_start(self, formatted: str, levelno: int) -> str:    Function
`get_message_start` Returns or fetches data.
L144: def format(self, record: logging.LogRecord) -> str:    Function `format` utility or
script function.
L162: class IndentedRenderable:    Class (`IndentedRenderable`) component used by the app
(see file context: None).
L166: def __rich_console__(    Function `__rich_console__` utility or script function.
L177: class PipConsole(Console):    Class (`PipConsole`) component used by the app (see file
context: None).
L178: def on_broken_pipe(self) -> None:    Function `on_broken_pipe` utility or script
function.
L184: def get_console(*, stderr: bool = False) -> Console:    Function `get_console` Returns
or fetches data.
L193: class RichPipStreamHandler(RichHandler):    Class (`RichPipStreamHandler`) component
used by the app (see file context: None).
L196: def __init__(self, console: Console) -> None:    Function `__init__` utility or script
function.
L206: def emit(self, record: logging.LogRecord) -> None:    Function `emit` utility or script
function.
L234: def handleError(self, record: logging.LogRecord) -> None:    Function `handleError`
utility or script function.
L253: class BetterRotatingFileHandler(logging.handlers.RotatingFileHandler):    Class
(`BetterRotatingFileHandler`) component used by the app (see file context: None).
L254: def _open(self) -> TextIOWrapper:    Function `_open` utility or script function.
L259: class MaxLevelFilter(Filter):    Class (`MaxLevelFilter`) component used by the app
(see file context: None).
L260: def __init__(self, level: int) -> None:    Function `__init__` utility or script
function.
L263: def filter(self, record: logging.LogRecord) -> bool:    Function `filter` utility or
script function.
L267: class ExcludeLoggerFilter(Filter):    Class (`ExcludeLoggerFilter`) component used by
the app (see file context: None).
L272: def filter(self, record: logging.LogRecord) -> bool:    Function `filter` utility or
script function.
L278: def setup_logging(verbosity: int, no_color: bool, user_log_file: str | None) -> int:
Function `setup_logging` Sets or updates a value.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/unpacking.py

```

L45: def current_umask() -> int:    Function `current_umask`    utility or script function.
L52: def split_leading_dir(path: str) -> list[str]:    Function `split_leading_dir`    utility
or script function.
L64: def has_leading_dir(paths: Iterable[str]) -> bool:    Function `has_leading_dir`    utility
or script function.
L79: def is_within_directory(directory: str, target: str) -> bool:    Function
`is_within_directory`    utility or script function.
L90: def _get_default_mode_plus_executable() -> int:    Function
`_get_default_mode_plus_executable`    utility or script function.
L94: def set_extracted_file_to_default_mode_plus_executable(path: str) -> None:    Function
`set_extracted_file_to_default_mode_plus_executable`    Sets or updates a value.
L102: def zip_item_is_executable(info: ZipInfo) -> bool:    Function `zip_item_is_executable`
utility or script function.
L109: def unzip_file(filename: str, location: str, flatten: bool = True) -> None:    Function
`unzip_file`    utility or script function.
L155: def untar_file(filename: str, location: str) -> None:    Function `untar_file`    utility
or script function.
L206: def pip_filter(member: tarfile.TarInfo, path: str) -> tarfile.TarInfo:    Function
`pip_filter`    utility or script function.
L251: def is_symlink_target_in_tar(tar: tarfile.TarFile, tarinfo: tarfile.TarInfo) -> bool:
Function `is_symlink_target_in_tar`    utility or script function.
L265: def _untar_without_filter(    Function `_untar_without_filter`    utility or script
function.
L334: def unpack_file(    Function `unpack_file`    utility or script function.
L348: def _unzip() -> None:    Function `_unzip`    utility or script function.
L351: def _untar() -> None:    Function `_untar`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/subprocess.py

```

L20: def make_command(*args: str | HiddenText | CommandArgs) -> CommandArgs:    Function
`make_command`    utility or script function.
L37: def format_command_args(args: list[str] | CommandArgs) -> str:    Function
`format_command_args`    utility or script function.
L52: def reveal_command_args(args: list[str] | CommandArgs) -> list[str]:    Function
`reveal_command_args`    utility or script function.
L59: def call_subprocess(    Function `call_subprocess`    utility or script function.
L227: def runner_with_spinner_message(message: str) -> Callable[..., None]:    Function
`runner_with_spinner_message`    utility or script function.
L234: def runner(    Function `runner`    utility or script function.

```

**.venv/lib/python3.12/site-packages/pip/_internal/compatibility_tag
s.py**


```

L23: def version_info_to_nodot(version_info: tuple[int, ...]) -> str:    Function
`version_info_to_nodot` utility or script function.
L28: def _mac_platforms(arch: str) -> list[str]:    Function `_mac_platforms` utility or
script function.
L48: def _ios_platforms(arch: str) -> list[str]:    Function `_ios_platforms` utility or
script function.
L68: def _android_platforms(arch: str) -> list[str]:    Function `_android_platforms` utility
or script function.
L78: def _custom_manylinux_platforms(arch: str) -> list[str]:    Function
`_custom_manylinux_platforms` utility or script function.
L99: def _get_custom_platforms(arch: str) -> list[str]:    Function `_get_custom_platforms`
utility or script function.
L114: def _expand_allowed_platforms(platforms: list[str] | None) -> list[str] | None:
Function `_expand_allowed_platforms` utility or script function.
L131: def _get_python_version(version: str) -> PythonVersion:    Function
`_get_python_version` utility or script function.
L138: def _get_custom_interpreter(    Function `_get_custom_interpreter` utility or script
function.
L148: def get_supported(    Function `get_supported` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/glibc.py

```

L7: def glibc_version_string() -> str | None:    Function `glibc_version_string` utility or
script function.
L12: def glibc_version_string_confstr() -> str | None:    Function
`glibc_version_string_confstr` utility or script function.
L32: def glibc_version_string_ctypes() -> str | None:    Function
`glibc_version_string_ctypes` utility or script function.
L92: def libc_ver() -> tuple[str, str]:    Function `libc_ver` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/virtualenv.py

```

L15: def _running_under_venv() -> bool:    Function `_running_under_venv` utility or script
function.
L23: def _running_under_legacy_virtualenv() -> bool:    Function
`_running_under_legacy_virtualenv` utility or script function.
L32: def running_under_virtualenv() -> bool:    Function `running_under_virtualenv` utility
or script function.
L37: def _get_pyvenv_cfg_lines() -> list[str] | None:    Function `_get_pyvenv_cfg_lines`
utility or script function.
L52: def _no_global_under_venv() -> bool:    Function `_no_global_under_venv` utility or
script function.
L81: def _no_global_under_legacy_virtualenv() -> bool:    Function
`_no_global_under_legacy_virtualenv` utility or script function.
L95: def virtualenv_no_global() -> bool:    Function `virtualenv_no_global` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/deprecation.py

```

L18: class PipDeprecationWarning(Warning):    Class (`PipDeprecationWarning`) component used
by the app (see file context: None).
L26: def _showwarning(    Function `_showwarning` utility or script function.
L49: def install_warning_logger() -> None:    Function `install_warning_logger` utility or
script function.
L60: def deprecated(    Function `deprecated` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/filetypes.py

```

L19: def is_archive_file(name: str) -> bool:    Function `is_archive_file` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/egg_link.py

```

L19: def _egg_link_names(raw_name: str) -> list[str]:    Function `_egg_link_names` utility
or script function.
L34: def egg_link_path_from_sys_path(raw_name: str) -> str | None:    Function
`egg_link_path_from_sys_path` utility or script function.
L47: def egg_link_path_from_location(raw_name: str) -> str | None:    Function
`egg_link_path_from_location` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/hashes.py

```

L24: class Hashes:    Class (`Hashes`) component used by the app (see file context: None).
L30: def __init__(self, hashes: dict[str, list[str]] | None = None) -> None:    Function
`__init__` utility or script function.
L42: def __and__(self, other: Hashes) -> Hashes:    Function `__and__` utility or script
function.
L62: def digest_count(self) -> int:    Function `digest_count` utility or script function.
L65: def is_hash_allowed(self, hash_name: str, hex_digest: str) -> bool:    Function
`is_hash_allowed` utility or script function.
L69: def check_against_chunks(self, chunks: Iterable[bytes]) -> None:    Function
`check_against_chunks` utility or script function.
L92: def _raise(self, got: dict[str, _Hash]) -> NoReturn:    Function `_raise` utility or
script function.
L95: def check_against_file(self, file: BinaryIO) -> None:    Function `check_against_file`
utility or script function.
L103: def check_against_path(self, path: str) -> None:    Function `check_against_path`
utility or script function.
L107: def has_one_of(self, hashes: Mapping[str, str]) -> bool:    Function `has_one_of`
utility or script function.

```

```

L114: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L118: def __eq__(self, other: object) -> bool:    Object (singleton).
L123: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L135: class MissingHashes(Hashes):    Class (`MissingHashes`) component used by the app (see
file context: None).
L143: def __init__(self) -> None:    Function `__init__` utility or script function.
L149: def _raise(self, gots: dict[str, _Hash]) -> NoReturn:    Function `_raise` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utls/temp_dir.py

```

L38: def global_tempdir_manager() -> Generator[None, None, None]:    Function
`global_tempdir_manager` utility or script function.
L48: class TempDirectoryTypeRegistry:    Class (`TempDirectoryTypeRegistry`) component used
by the app (see file context: None).
L51: def __init__(self) -> None:    Function `__init__` utility or script function.
L54: def set_delete(self, kind: str, value: bool) -> None:    Function `set_delete` Sets or
updates a value.
L60: def get_delete(self, kind: str) -> bool:    Function `get_delete` Returns or fetches
data.
L71: def tempdir_registry() -> Generator[TempDirectoryTypeRegistry, None, None]:    Function
`tempdir_registry` utility or script function.
L84: class _Default:    Class (`_Default`) component used by the app (see file context:
None).
L91: class TempDirectory:    Class (`TempDirectory`) component used by the app (see file
context: None).
L112: def __init__(    Function `__init__` utility or script function.
L148: def path(self) -> str:    Function `path` utility or script function.
L152: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L155: def __enter__(self: _T) -> _T:    Function `__enter__` utility or script function.
L158: def __exit__(self, exc: Any, value: Any, tb: Any) -> None:    Function `__exit__`
utility or script function.
L169: def _create(self, kind: str) -> str:    Function `_create` utility or script function.
L179: def cleanup(self) -> None:    Function `cleanup` utility or script function.
L187: def onerror(    Function `onerror` utility or script function.
L224: class AdjacentTempDirectory(TempDirectory):    Class (`AdjacentTempDirectory`)
component used by the app (see file context: None).
L246: def __init__(self, original: str, delete: bool | None = None) -> None:    Function
`__init__` utility or script function.
L251: def _generate_names(cls, name: str) -> Generator[str, None, None]:    Function
`_generate_names` utility or script function.
L276: def _create(self, kind: str) -> str:    Function `_create` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utls/pylock.py

```

L32: def _pylock_package_from_install_requirement(    Function

```

```

`_pylock_package_from_install_requirement` utility or script function.
L116: def pylock_from_install_requirements( Function `pylock_from_install_requirements`
utility or script function.
L135: def _is_url(s: str) -> bool: Function `_is_url` utility or script function.
L139: def is_valid_pylock_filename(filename: str) -> bool: Function
`is_valid_pylock_filename` utility or script function.
L147: def _package_dist_url( Function `_package_dist_url` utility or script function.
L177: def package_vcs_requirement_url( Function `package_vcs_requirement_url` utility or
script function.
L192: def package_archive_requirement_url( Function `package_archive_requirement_url`
utility or script function.
L208: def package_directory_requirement_url( Function `package_directory_requirement_url`
utility or script function.
L227: def package_sdist_requirement_url( Function `package_sdist_requirement_url` utility
or script function.
L233: def package_wheel_requirement_url( Function `package_wheel_requirement_url` utility
or script function.
L239: def _get_pylock_path_or_url_content(path_or_url: str, session: PipSession) -> str:
Function `_get_pylock_path_or_url_content` utility or script function.
L255: def select_from_pylock_path_or_url( Function `select_from_pylock_path_or_url`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/wheel.py

```

L18: def parse_wheel(wheel_zip: ZipFile, name: str) -> tuple[str, Message]: Function
`parse_wheel` utility or script function.
L36: def wheel_dist_info_dir(source: ZipFile, name: str) -> str: Function
`wheel_dist_info_dir` utility or script function.
L67: def read_wheel_metadata_file(source: ZipFile, path: str) -> bytes: Function
`read_wheel_metadata_file` utility or script function.
L76: def wheel_metadata(source: ZipFile, dist_info_dir: str) -> Message: Function
`wheel_metadata` utility or script function.
L95: def wheel_version(wheel_data: Message) -> tuple[int, ...]: Function `wheel_version`
utility or script function.
L111: def check_compatibility(version: tuple[int, ...], name: str) -> None: Function
`check_compatibility` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/utils/misc.py

```

L70: def get_pip_version() -> str: Function `get_pip_version` Returns or fetches data.
L77: def normalize_version_info(py_version_info: tuple[int, ...]) -> tuple[int, int, int]:
Function `normalize_version_info` utility or script function.
L96: def ensure_dir(path: str) -> None: Function `ensure_dir` utility or script function.
L106: def get_prog() -> str: Function `get_prog` Returns or fetches data.
L120: def rmtree(dir: str, ignore_errors: bool = False, onexc: OnExc | None = None) -> None:
Function `rmtree` utility or script function.

```

```

L133: def _onerror_ignore(*_args: Any) -> None:    Function `_onerror_ignore` utility or
script function.
L137: def _onerror_reraise(*_args: Any) -> None:    Function `_onerror_reraise` utility or
script function.
L141: def rmtree_errorhandler(    Function `rmtree_errorhandler` utility or script function.
L182: def display_path(path: str) -> str:    Function `display_path` utility or script
function.
L193: def backup_dir(dir: str, ext: str = ".bak") -> str:    Function `backup_dir` utility or
script function.
L204: def ask_path_exists(message: str, options: Iterable[str]) -> str:    Function
`ask_path_exists` utility or script function.
L211: def _check_no_input(message: str) -> None:    Function `_check_no_input` utility or
script function.
L219: def ask(message: str, options: Iterable[str]) -> str:    Function `ask` utility or
script function.
L234: def ask_input(message: str) -> str:    Function `ask_input` utility or script function.
L240: def ask_password(message: str) -> str:    Function `ask_password` utility or script
function.
L246: def strtobool(val: str) -> int:    Function `strtobool` utility or script function.
L262: def format_size(bytes: float) -> str:    Function `format_size` utility or script
function.
L273: def tabulate(rows: Iterable[Iterable[Any]]) -> tuple[list[str], list[int]]:    Function
`tabulate` utility or script function.
L287: def is_installable_dir(path: str) -> bool:    Function `is_installable_dir` utility or
script function.
L304: def read_chunks(    Function `read_chunks` utility or script function.
L315: def normalize_path(path: str, resolve_symlinks: bool = True) -> str:    Function
`normalize_path` utility or script function.
L328: def splitext(path: str) -> tuple[str, str]:    Function `splitext` utility or script
function.
L337: def renames(old: str, new: str) -> None:    Function `renames` utility or script
function.
L354: def is_local(path: str) -> bool:    Function `is_local` utility or script function.
L368: def write_output(msg: Any, *_args: Any) -> None:    Function `write_output` utility or
script function.
L372: class StreamWrapper(StringIO):    Class (`StreamWrapper`) component used by the app
(see file context: None).
L376: def from_stream(cls, orig_stream: TextIO) -> StreamWrapper:    Function `from_stream`
utility or script function.
L384: def encoding(self) -> str:    # type: ignore    Function `encoding` utility or script
function.
L389: def enum(*sequential: Any, **named: Any) -> type[Any]:    Function `enum` utility or
script function.
L396: def build_netloc(host: str, port: int | None) -> str:    Function `build_netloc`
Constructs or prepares an object.
L408: def build_url_from_netloc(netloc: str, scheme: str = "https") -> str:    Function
`build_url_from_netloc` Constructs or prepares an object.
L418: def parse_netloc(netloc: str) -> tuple[str | None, int | None]:    Function
`parse_netloc` utility or script function.
L427: def split_auth_from_netloc(netloc: str) -> NetlocTuple:    Function
`split_auth_from_netloc` utility or script function.

```

```

L456: def redact_netloc(netloc: str) -> str:    Function `redact_netloc` utility or script
function.
L476: def _transform_url(    Function `_transform_url` utility or script function.
L496: def _get_netloc(netloc: str) -> NetlocTuple:    Function `_get_netloc` utility or
script function.
L500: def _redact_netloc(netloc: str) -> tuple[str]:    Function `_redact_netloc` utility or
script function.
L504: def split_auth_netloc_from_url(    Function `split_auth_netloc_from_url` utility or
script function.
L516: def remove_auth_from_url(url: str) -> str:    Function `remove_auth_from_url` utility
or script function.
L523: def redact_auth_from_url(url: str) -> str:    Function `redact_auth_from_url` utility
or script function.
L528: def redact_auth_from_requirement(req: Requirement) -> str:    Function
`redact_auth_from_requirement` utility or script function.
L536: class HiddenText:    Class (`HiddenText`) component used by the app (see file context:
None).
L540: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L543: def __str__(self) -> str:    Function `__str__` utility or script function.
L546: def __eq__(self, other: object) -> bool:    Object (singleton).
L560: def hide_value(value: str) -> HiddenText:    Function `hide_value` utility or script
function.
L564: def hide_url(url: str) -> HiddenText:    Function `hide_url` utility or script
function.
L569: def protect_pip_from_modification_on_windows(modifying_pip: bool) -> None:    Function
`protect_pip_from_modification_on_windows` utility or script function.
L595: def check_externally_managed() -> None:    Function `check_externally_managed` utility
or script function.
L610: def is_console_interactive() -> bool:    Function `is_console_interactive` utility or
script function.
L615: def hash_file(path: str, blocksize: int = 1 << 20) -> tuple[Any, int]:    Function
`hash_file` utility or script function.
L627: def pairwise(iterable: Iterable[Any]) -> Iterator[tuple[Any, Any]]:    Function
`pairwise` utility or script function.
L638: def partition(    Function `partition` utility or script function.
L651: class ConfiguredBuildBackendHookCaller(BuildBackendHookCaller):    Class
(`ConfiguredBuildBackendHookCaller`) component used by the app (see file context: None).
L652: def __init__(    Function `__init__` utility or script function.
L666: def build_wheel(    Function `build_wheel` Constructs or prepares an object.
L677: def build_sdist(    Function `build_sdist` Constructs or prepares an object.
L685: def build_editable(    Function `build_editable` Constructs or prepares an object.
L696: def get_requires_for_build_wheel(    Function `get_requires_for_build_wheel` Returns or
fetches data.
L702: def get_requires_for_build_sdist(    Function `get_requires_for_build_sdist` Returns or
fetches data.
L708: def get_requires_for_build_editable(    Function `get_requires_for_build_editable`
Returns or fetches data.
L714: def prepare_metadata_for_build_wheel(    Function `prepare_metadata_for_build_wheel`
utility or script function.
L727: def prepare_metadata_for_build_editable(    Function
`prepare_metadata_for_build_editable` utility or script function.

```

```
L741: def warn_if_run_as_root() -> None:    Function `warn_if_run_as_root` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/direct_url_helpers.py

```
L9: def direct_url_as_pep440_direct_reference(direct_url: DirectUrl, name: str) -> str:
Function `direct_url_as_pep440_direct_reference` utility or script function.
L36: def direct_url_for_editable(source_dir: str) -> DirectUrl:    Function
`direct_url_for_editable` utility or script function.
L43: def direct_url_from_link(    Function `direct_url_from_link` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/packaging.py

```
L13: def check_requires_python(    Function `check_requires_python` utility or script function.
L37: def get_requirement(req_string: str) -> Requirement:    Function `get_requirement`
Returns or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_internal/utils/_log.py

```
L16: class VerboseLogger(logging.Logger):    Class (`VerboseLogger`) component used by the app (see file context: None).
L22: def verbose(self, msg: str, *args: Any, **kwargs: Any) -> None:    Function `verbose` utility or script function.
L26: def getLogger(name: str) -> VerboseLogger:    Function `getLogger` Returns or fetches data.
L31: def init_logging() -> None:    Function `init_logging` Initialisation routine.
```

.venv/lib/python3.12/site-packages/pip/_internal/operations/freeze.py

```
L25: class _EditableInfo(NamedTuple):    Class (`_EditableInfo`) component used by the app (see file context: None).
L30: def freeze(    Function `freeze` utility or script function.
L151: def _format_as_name_version(dist: BaseDistribution) -> str:    Function
`_format_as_name_version` utility or script function.
L161: def _get_editable_info(dist: BaseDistribution) -> _EditableInfo:    Function
`_get_editable_info` utility or script function.
L228: class FrozenRequirement:    Class (`FrozenRequirement`) component used by the app (see file context: None).
L235: def canonical_name(self) -> NormalizedName:    Function `canonical_name` utility or
```

```

script function.
L239: def from_dist(cls, dist: BaseDistribution) -> FrozenRequirement:  Function `from_dist`
      utility or script function.
L255: def __str__(self) -> str:  Function `__str__`  utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/operations/prepare.py

```

L65: def _get_prepared_distribution(  Function `_get_prepared_distribution`  utility or
script function.
L83: def unpack_vcs_link(link: Link, location: str, verbosity: int) -> None:  Function
`unpack_vcs_link`  utility or script function.
L90: class File:  Class (`File`)  component used by the app (see file context: None).
L94: def __post_init__(self) -> None:  Function `__post_init__`  utility or script function.
L104: def get_http_url(  Function `get_http_url`  Returns or fetches data.
L128: def get_file_url(  Function `get_file_url`  Returns or fetches data.
L152: def unpack_url(  Function `unpack_url`  utility or script function.
L195: def _check_download_dir(  Function `_check_download_dir`  utility or script function.
L225: class RequirementPreparer:  Class (`RequirementPreparer`)  component used by the app
(see file context: None).
L228: def __init__(  Function `__init__`  utility or script function.
L288: def _log_preparing_link(self, req: InstallRequirement) -> None:  Function
`_log_preparing_link`  utility or script function.
L315: def _ensure_link_req_src_dir(  Function `_ensure_link_req_src_dir`  utility or script
function.
L338: def _get_linked_req_hashes(self, req: InstallRequirement) -> Hashes:  Function
`_get_linked_req_hashes`  utility or script function.
L370: def _fetch_metadata_only(  Function `_fetch_metadata_only`  utility or script
function.
L389: def _fetch_metadata_using_link_data_attr(  Function
`_fetch_metadata_using_link_data_attr`  utility or script function.
L430: def _fetch_metadata_using_lazy_wheel(  Function `_fetch_metadata_using_lazy_wheel`
utility or script function.
L459: def _complete_partial_requirements(  Function `_complete_partial_requirements`
utility or script function.
L500: def prepare_linked_requirement(  Function `prepare_linked_requirement`  utility or
script function.
L544: def prepare_linked_requirements_more(  Function `prepare_linked_requirements_more`
utility or script function.
L574: def _prepare_linked_requirement(  Function `_prepare_linked_requirement`  utility or
script function.
L670: def save_linked_requirement(self, req: InstallRequirement) -> None:  Function
`save_linked_requirement`  Saves data to storage or remote.
L696: def prepare_editable_requirement(  Function `prepare_editable_requirement`  utility or
script function.
L729: def prepare_installed_requirement(  Function `prepare_installed_requirement`  utility
or script function.

```


.venv/lib/python3.12/site-packages/pip/_internal/operations/check.py

```

L28: class PackageDetails(NamedTuple):    Class (`PackageDetails`) component used by the app
(see file context: None).
L44: def create_package_set_from_installed() -> tuple[PackageSet, bool]:    Function
`create_package_set_from_installed` Creates a resource or document.
L61: def check_package_set(    Function `check_package_set` utility or script function.
L106: def check_install_conflicts(to_install: list[InstallRequirement]) -> ConflictDetails:
Function `check_install_conflicts` utility or script function.
L126: def check_unsupported(    Function `check_unsupported` utility or script function.
L142: def _simulate_installation_of(    Function `_simulate_installation_of` utility or
script function.
L161: def _create_whitelist(    Function `_create_whitelist` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/operations/install/wheel.l.py

```

L57: class File(Protocol):    Class (`File`) component used by the app (see file context:
None).
L62: def save(self) -> None:    Function `save` Saves data to storage or remote.
L72: def rehash(path: str, blocksize: int = 1 << 20) -> tuple[str, str]:    Function `rehash`
utility or script function.
L79: def csv_io_kwargs(mode: str) -> dict[str, Any]:    Function `csv_io_kwargs` utility or
script function.
L86: def fix_script(path: str) -> bool:    Function `fix_script` utility or script function.
L106: def wheel_root_is_purelib(metadata: Message) -> bool:    Function
`wheel_root_is_purelib` utility or script function.
L110: def get_entrypoints(dist: BaseDistribution) -> tuple[dict[str, str], dict[str, str]]:
Function `get_entrypoints` Returns or fetches data.
L121: def message_about_scripts_not_on_PATH(scripts: Sequence[str]) -> str | None:    Function
`message_about_scripts_not_on_PATH` utility or script function.
L193: def _normalized_outrows(    Function `_normalized_outrows` utility or script function.
L219: def _record_to_fs_path(record_path: RecordPath, lib_dir: str) -> str:    Function
`_record_to_fs_path` utility or script function.
L223: def _fs_to_record_path(path: str, lib_dir: str) -> RecordPath:    Function
`_fs_to_record_path` utility or script function.
L233: def get_csv_rows_for_installed(    Function `get_csv_rows_for_installed` Returns or
fetches data.
L265: def get_console_script_specs(console: dict[str, str]) -> list[str]:    Function
`get_console_script_specs` Returns or fetches data.
L340: class ZipBackedFile:    Class (`ZipBackedFile`) component used by the app (see file
context: None).
L341: def __init__(    Function `__init__` utility or script function.
L349: def _getinfo(self) -> ZipInfo:    Function `_getinfo` utility or script function.
L352: def save(self) -> None:    Function `save` Saves data to storage or remote.
L378: class ScriptFile:    Class (`ScriptFile`) component used by the app (see file context:
None).

```

```

L379: def __init__(self, file: File) -> None:    Function `__init__`    utility or script
function.
L385: def save(self) -> None:    Function `save`    Saves data to storage or remote.
L390: class MissingCallableSuffix(InstallationError):    Class (`MissingCallableSuffix`)
component used by the app (see file context: None).
L391: def __init__(self, entry_point: str) -> None:    Function `__init__`    utility or script
function.
L400: def _raise_for_invalid_entrypoint(specification: str) -> None:    Function
`_raise_for_invalid_entrypoint`    utility or script function.
L406: class PipScriptMaker(ScriptMaker):    Class (`PipScriptMaker`)    component used by the
app (see file context: None).
L419: def make(    Function `make`    utility or script function.
L426: def _install_wheel( # noqa: C901, PLR0915 function is too long    Function
`_install_wheel`    utility or script function.
L466: def record_installed(    Function `record_installed`    utility or script function.
L475: def is_dir_path(path: RecordPath) -> bool:    Function `is_dir_path`    utility or script
function.
L478: def assert_no_path_traversal(dest_dir_path: str, target_path: str) -> None:    Function
`assert_no_path_traversal`    utility or script function.
L488: def root_scheme_file_maker(    Function `root_scheme_file_maker`    utility or script
function.
L491: def make_root_scheme_file(record_path: RecordPath) -> File:    Function
`make_root_scheme_file`    utility or script function.
L499: def data_scheme_file_maker(    Function `data_scheme_file_maker`    utility or script
function.
L504: def make_data_scheme_file(record_path: RecordPath) -> File:    Function
`make_data_scheme_file`    utility or script function.
L533: def is_data_scheme_path(path: RecordPath) -> bool:    Function `is_data_scheme_path`
utility or script function.
L543: def is_script_scheme_path(path: RecordPath) -> bool:    Function `is_script_scheme_path`
utility or script function.
L562: def is_entrypoint_wrapper(file: File) -> bool:    Function `is_entrypoint_wrapper`
utility or script function.
L597: def pyc_source_file_paths() -> Generator[str, None, None]:    Function
`pyc_source_file_paths`    utility or script function.
L610: def pyc_output_path(path: str) -> str:    Function `pyc_output_path`    utility or script
function.
L666: def _generate_file(path: str, **kwargs: Any) -> Generator[BinaryIO, None, None]:
Function `_generate_file`    utility or script function.
L716: def req_error_context(req_description: str) -> Generator[None, None, None]:    Function
`req_error_context`    utility or script function.
L724: def install_wheel(    Function `install_wheel`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/locations/_distutils.py

```

L136: def distutils_scheme(    Function `distutils_scheme`    utility or script function.
L116: def get_scheme(    Function `get_scheme`    Returns or fetches data.
L151: def get_bin_prefix() -> str:    Function `get_bin_prefix`    Returns or fetches data.

```

```
L168: def get_purelib() -> str:    Function `get_purelib`  Returns or fetches data.
L172: def get_platlib() -> str:    Function `get_platlib`  Returns or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_internal/locations/base.py

```
L20: def get_major_minor_version() -> str:    Function `get_major_minor_version`  Returns or
fetches data.
L28: def change_root(new_root: str, pathname: str) -> str:    Function `change_root`  utility
or script function.
L56: def get_src_prefix() -> str:    Function `get_src_prefix`  Returns or fetches data.
L81: def is_osx_framework() -> bool:    Function `is_osx_framework`  utility or script
function.
```

.venv/lib/python3.12/site-packages/pip/_internal/locations/__init__.py

```
L45: def _should_use_sysconfig() -> bool:    Function `_should_use_sysconfig`  utility or
script function.
L75: def _looks_like_bpo_44860() -> bool:    Function `_looks_like_bpo_44860`  utility or
script function.
L89: def _looks_like_red_hat_patched_platlib_purelib(scheme: dict[str, str]) -> bool:
Function `_looks_like_red_hat_patched_platlib_purelib`  utility or script function.
L100: def _looks_like_red_hat_lib() -> bool:    Function `_looks_like_red_hat_lib`  utility or
script function.
L115: def _looks_like_debian_scheme() -> bool:    Function `_looks_like_debian_scheme`
utility or script function.
L123: def _looks_like_red_hat_scheme() -> bool:    Function `_looks_like_red_hat_scheme`
utility or script function.
L143: def _looks_like_slackware_scheme() -> bool:    Function `_looks_like_slackware_scheme`
utility or script function.
L159: def _looks_like_msys2_mingw_scheme() -> bool:    Function
`_looks_like_msys2_mingw_scheme`  utility or script function.
L177: def _warn_mismatched(old: pathlib.Path, new: pathlib.Path, *, key: str) -> None:
Function `_warn_mismatched`  utility or script function.
L187: def _warn_if_mismatch(old: pathlib.Path, new: pathlib.Path, *, key: str) -> bool:
Function `_warn_if_mismatch`  utility or script function.
L195: def _log_context(    Function `_log_context`  utility or script function.
L213: def get_scheme(    Function `get_scheme`  Returns or fetches data.
L379: def get_bin_prefix() -> str:    Function `get_bin_prefix`  Returns or fetches data.
L390: def get_bin_user() -> str:    Function `get_bin_user`  Returns or fetches data.
L394: def _looks_like_deb_system_dist_packages(value: str) -> bool:    Function
`_looks_like_deb_system_dist_packages`  utility or script function.
L411: def get_purelib() -> str:    Function `get_purelib`  Returns or fetches data.
L425: def get_platlib() -> str:    Function `get_platlib`  Returns or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_internal/locations/_sysconfig.py

```

L33: def _should_use_osx_framework_prefix() -> bool:    Function
`_should_use_osx_framework_prefix` utility or script function.
L59: def _infer_prefix() -> str:    Function `_infer_prefix` utility or script function.
L90: def _infer_user() -> str:    Function `_infer_user` utility or script function.
L105: def _infer_home() -> str:    Function `_infer_home` utility or script function.
L128: def get_scheme(    Function `get_scheme` Returns or fetches data.
L206: def get_bin_prefix() -> str:    Function `get_bin_prefix` Returns or fetches data.
L213: def get_purelib() -> str:    Function `get_purelib` Returns or fetches data.
L217: def get_platlib() -> str:    Function `get_platlib` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/base.py

```

L44: class BaseEntryPoint(Protocol):    Class (`BaseEntryPoint`) component used by the app
(see file context: None).
L46: def name(self) -> str:    Function `name` utility or script function.
L50: def value(self) -> str:    Function `value` utility or script function.
L54: def group(self) -> str:    Function `group` utility or script function.
L58: def _convert_installed_files_path(    Function `_convert_installed_files_path` utility
or script function.
L88: class RequiresEntry(NamedTuple):    Class (`RequiresEntry`) component used by the app
(see file context: None).
L94: class BaseDistribution(Protocol):    Class (`BaseDistribution`) component used by the
app (see file context: None).
L96: def from_directory(cls, directory: str) -> BaseDistribution:    Function `from_directory`
utility or script function.
L104: def from_metadata_file_contents(    Function `from_metadata_file_contents` utility or
script function.
L122: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:    Function
`from_wheel` utility or script function.
L135: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L138: def __str__(self) -> str:    Function `__str__` utility or script function.
L142: def location(self) -> str | None:    Function `location` utility or script function.
L156: def editable_project_location(self) -> str | None:    Function
`editable_project_location` utility or script function.
L178: def installed_location(self) -> str | None:    Function `installed_location` utility or
script function.
L191: def info_location(self) -> str | None:    Function `info_location` utility or script
function.
L207: def installed_by_distutils(self) -> bool:    Function `installed_by_distutils` utility
or script function.
L220: def installed_as_egg(self) -> bool:    Function `installed_as_egg` utility or script
function.
L234: def installed_with_setuptools_egg_info(self) -> bool:    Function
`installed_with_setuptools_egg_info` utility or script function.

```

```

L252: def installed_with_dist_info(self) -> bool:    Function `installed_with_dist_info`
utility or script function.
L268: def canonical_name(self) -> NormalizedName:    Function `canonical_name`    utility or
script function.
L272: def version(self) -> Version:    Function `version`    utility or script function.
L276: def raw_version(self) -> str:    Function `raw_version`    utility or script function.
L280: def setuptools_filename(self) -> str:    Function `setuptools_filename`    Sets or updates
a value.
L288: def direct_url(self) -> DirectUrl | None:    Function `direct_url`    utility or script
function.
L314: def installer(self) -> str:    Function `installer`    utility or script function.
L326: def requested(self) -> bool:    Function `requested`    utility or script function.
L330: def editable(self) -> bool:    Function `editable`    utility or script function.
L334: def local(self) -> bool:    Function `local`    utility or script function.
L344: def in_usersite(self) -> bool:    Function `in_usersite`    utility or script function.
L350: def in_site_packages(self) -> bool:    Function `in_site_packages`    utility or script
function.
L355: def is_file(self, path: InfoPath) -> bool:    Function `is_file`    utility or script
function.
L359: def iter_distutils_script_names(self) -> Iterator[str]:    Function
`iter_distutils_script_names`    utility or script function.
L367: def read_text(self, path: InfoPath) -> str:    Function `read_text`    utility or script
function.
L376: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:    Function `iter_entry_points`
utility or script function.
L379: def _metadata_impl(self) -> email.message.Message:    Function `_metadata_impl`    utility
or script function.
L383: def metadata(self) -> email.message.Message:    Function `metadata`    utility or script
function.
L396: def metadata_dict(self) -> dict[str, Any]:    Function `metadata_dict`    utility or
script function.
L407: def metadata_version(self) -> str | None:    Function `metadata_version`    utility or
script function.
L412: def raw_name(self) -> str:    Function `raw_name`    utility or script function.
L419: def requires_python(self) -> SpecifierSet:    Function `requires_python`    utility or
script function.
L437: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
Function `iter_dependencies`    utility or script function.
L445: def iter_raw_dependencies(self) -> Iterable[str]:    Function `iter_raw_dependencies`
utility or script function.
L449: def iter_provided_extras(self) -> Iterable[Normalized Name]:    Function
`iter_provided_extras`    utility or script function.
L461: def _iter_declared_entries_from_record(self) -> Iterator[str] | None:    Function
`_iter_declared_entries_from_record`    utility or script function.
L469: def _iter_declared_entries_from_legacy(self) -> Iterator[str] | None:    Function
`_iter_declared_entries_from_legacy`    utility or script function.
L490: def iter_declared_entries(self) -> Iterator[str] | None:    Function
`iter_declared_entries`    utility or script function.
L506: def _iter_requires_txt_entries(self) -> Iterator[RequiresEntry]:    Function
`_iter_requires_txt_entries`    utility or script function.
L531: def _iter_egg_info_extras(self) -> Iterable[str]:    Function `_iter_egg_info_extras`

```

```

utility or script function.
L541: def _iter_egg_info_dependencies(self) -> Iterable[str]:    Function
`_iter_egg_info_dependencies` utility or script function.
L569: def _add_egg_info_requires(self, metadata: email.message.Message) -> None:    Function
`_add_egg_info_requires` utility or script function.
L579: class BaseEnvironment:    Class (`BaseEnvironment`) component used by the app (see file
context: None).
L583: def default(cls) -> BaseEnvironment:    Function `default` utility or script function.
L587: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:    Function
`from_paths` utility or script function.
L590: def get_distribution(self, name: str) -> BaseDistribution | None:    Function
`get_distribution` Returns or fetches data.
L598: def _iter_distributions(self) -> Iterator[BaseDistribution]:    Function
`_iter_distributions` utility or script function.
L607: def iter_all_distributions(self) -> Iterator[BaseDistribution]:    Function
`iter_all_distributions` utility or script function.
L628: def iter_installed_distributions(    Function `iter_installed_distributions` utility or
script function.
L664: class Wheel(Protocol):    Class (`Wheel`) component used by the app (see file context:
None).
L667: def as_zipfile(self) -> zipfile.ZipFile:    Function `as_zipfile` utility or script
function.
L671: class FilesystemWheel(Wheel):    Class (`FilesystemWheel`) component used by the app
(see file context: None).
L672: def __init__(self, location: str) -> None:    Function `__init__` utility or script
function.
L675: def as_zipfile(self) -> zipfile.ZipFile:    Function `as_zipfile` utility or script
function.
L679: class MemoryWheel(Wheel):    Class (`MemoryWheel`) component used by the app (see file
context: None).
L680: def __init__(self, location: str, stream: IO[bytes]) -> None:    Function `__init__`
utility or script function.
L684: def as_zipfile(self) -> zipfile.ZipFile:    Function `as_zipfile` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/_json.py

```

L40: def json_name(field: str) -> str:    Function `json_name` utility or script function.
L44: def msg_to_json(msg: Message) -> dict[str, Any]:    Function `msg_to_json` utility or
script function.
L47: def sanitise_header(h: Header | str) -> str:    Function `sanitise_header` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/__init__.py

```

L30: def _should_use_importlib_metadata() -> bool:    Function

```

```

`_should_use_importlib_metadata` utility or script function.
L63: def _emit_pkg_resources_deprecation_if_needed() -> None:    Function
`_emit_pkg_resources_deprecation_if_needed` utility or script function.
L88: class Backend(Protocol):    Class (`Backend`) component used by the app (see file
context: None).
L95: def select_backend() -> Backend:    Function `select_backend` utility or script
function.
L108: def get_default_environment() -> BaseEnvironment:    Function `get_default_environment`
Returns or fetches data.
L118: def get_environment(paths: list[str] | None) -> BaseEnvironment:    Function
`get_environment` Returns or fetches data.
L128: def get_directory_distribution(directory: str) -> BaseDistribution:    Function
`get_directory_distribution` Returns or fetches data.
L137: def get_wheel_distribution(    Function `get_wheel_distribution` Returns or fetches
data.
L150: def get_metadata_distribution(    Function `get_metadata_distribution` Returns or
fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/pkg_resourc es.py

```

L39: class EntryPoint(NamedTuple):    Class (`EntryPoint`) component used by the app (see
file context: None).
L45: class InMemoryMetadata:    Class (`InMemoryMetadata`) component used by the app (see
file context: None).
L51: def __init__(self, metadata: Mapping[str, bytes], wheel_name: str) -> None:    Function
`__init__` utility or script function.
L55: def has_metadata(self, name: str) -> bool:    Function `has_metadata` utility or script
function.
L58: def get_metadata(self, name: str) -> str:    Function `get_metadata` Returns or fetches
data.
L67: def get_metadata_lines(self, name: str) -> Iterable[str]:    Function
`get_metadata_lines` Returns or fetches data.
L70: def metadata_isdir(self, name: str) -> bool:    Function `metadata_isdir` utility or
script function.
L73: def metadata_listdir(self, name: str) -> list[str]:    Function `metadata_listdir`
utility or script function.
L76: def run_script(self, script_name: str, namespace: str) -> None:    Function `run_script`
utility or script function.
L80: class Distribution(BaseDistribution):    Class (`Distribution`) component used by the
app (see file context: None).
L81: def __init__(self, dist: pkg_resources.Distribution) -> None:    Function `__init__`
utility or script function.
L88: def _extra_mapping(self) -> Mapping[NormalizedName, str]:    Function `_extra_mapping`
utility or script function.
L97: def from_directory(cls, directory: str) -> BaseDistribution:    Function `from_directory`
utility or script function.
L117: def from_metadata_file_contents(    Function `from_metadata_file_contents` utility or

```

```

script function.
L134: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:    Function
`from_wheel` utility or script function.
L155: def location(self) -> str | None:    Function `location` utility or script function.
L159: def installed_location(self) -> str | None:    Function `installed_location` utility or
script function.
L170: def info_location(self) -> str | None:    Function `info_location` utility or script
function.
L174: def installed_by_distutils(self) -> bool:    Function `installed_by_distutils` utility
or script function.
L184: def canonical_name(self) -> NormalizedName:    Function `canonical_name` utility or
script function.
L188: def version(self) -> Version:    Function `version` utility or script function.
L192: def raw_version(self) -> str:    Function `raw_version` utility or script function.
L195: def is_file(self, path: InfoPath) -> bool:    Function `is_file` utility or script
function.
L198: def iter_distutils_script_names(self) -> Iterator[str]:    Function
`iter_distutils_script_names` utility or script function.
L201: def read_text(self, path: InfoPath) -> str:    Function `read_text` utility or script
function.
L210: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:    Function `iter_entry_points`
utility or script function.
L216: def _metadata_impl(self) -> email.message.Message:    Function `_metadata_impl` utility
or script function.
L238: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
Function `iter_dependencies` utility or script function.
L246: def iter_provided_extras(self) -> Iterable[NormalizedName]:    Function
`iter_provided_extras` utility or script function.
L250: class Environment(BaseEnvironment):    Class (`Environment`) component used by the app
(see file context: None).
L251: def __init__(self, ws: pkg_resources.WorkingSet) -> None:    Function `__init__`
utility or script function.
L255: def default(cls) -> BaseEnvironment:    Function `default` utility or script function.
L259: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment:    Function
`from_paths` utility or script function.
L262: def _iter_distributions(self) -> Iterator[BaseDistribution]:    Function
`_iter_distributions` utility or script function.
L266: def _search_distribution(self, name: str) -> BaseDistribution | None:    Function
`_search_distribution` utility or script function.
L278: def get_distribution(self, name: str) -> BaseDistribution | None:    Function
`get_distribution` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_compat.py

```

L10: class BadMetadata(ValueError):    Class (`BadMetadata`) component used by the app (see
file context: None).
L11: def __init__(self, dist: importlib.metadata.Distribution, *, reason: str) -> None:

```



```

Function `__init__` utility or script function.
L15: def __str__(self) -> str: Function `__str__` utility or script function.
L19: class BasePath(Protocol): Class (`BasePath`) component used by the app (see file
context: None).
L31: def name(self) -> str: Function `name` utility or script function.
L35: def parent(self) -> BasePath: Function `parent` utility or script function.
L39: def get_info_location(d: importlib.metadata.Distribution) -> BasePath | None: Function
`get_info_location` Returns or fetches data.
L51: def parse_name_and_version_from_info_directory( Function
`parse_name_and_version_from_info_directory` utility or script function.
L75: def get_dist_canonical_name(dist: importlib.metadata.Distribution) -> NormalizedName:
Function `get_dist_canonical_name` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_en vs.py

```

L28: def _looks_like_wheel(location: str) -> bool: Function `_looks_like_wheel` utility or
script function.
L40: class _DistributionFinder: Class (`_DistributionFinder`) component used by the app
(see file context: None).
L55: def __init__(self) -> None: Function `__init__` utility or script function.
L58: def _find_impl(self, location: str) -> Iterator[FoundResult]: Function `_find_impl`
utility or script function.
L79: def find(self, location: str) -> Iterator[BaseDistribution]: Function `find` utility
or script function.
L91: def find_legacy_editables(self, location: str) -> Iterator[BaseDistribution]: Function
`find_legacy_editables` utility or script function.
L116: class Environment(BaseEnvironment): Class (`Environment`) component used by the app
(see file context: None).
L117: def __init__(self, paths: Sequence[str]) -> None: Function `__init__` utility or
script function.
L121: def default(cls) -> BaseEnvironment: Function `default` utility or script function.
L125: def from_paths(cls, paths: list[str] | None) -> BaseEnvironment: Function
`from_paths` utility or script function.
L130: def _iter_distributions(self) -> Iterator[BaseDistribution]: Function
`_iter_distributions` utility or script function.
L136: def get_distribution(self, name: str) -> BaseDistribution | None: Function
`get_distribution` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/metadata/importlib/_di sts.py

```

L38: class WheelDistribution(importlib.metadata.Distribution): Class (`WheelDistribution`)
component used by the app (see file context: None).
L49: def __init__( Function `__init__` utility or script function.

```

```

L58: def from_zipfile(    Function `from_zipfile`    utility or script function.
L77: def iterdir(self, path: InfoPath) -> Iterator[pathlib.PurePosixPath]:    Function
`iterdir`    utility or script function.
L83: def read_text(self, filename: str) -> str | None:    Function `read_text`    utility or
script function.
L96: def locate_file(self, path: str | PathLike[str]) -> pathlib.Path:    Function
`locate_file`    utility or script function.
L102: class Distribution(BaseDistribution):    Class (`Distribution`)    component used by the
app (see file context: None).
L103: def __init__(    Function `__init__`    utility or script function.
L114: def from_directory(cls, directory: str) -> BaseDistribution:    Function
`from_directory`    utility or script function.
L120: def from_metadata_file_contents(    Function `from_metadata_file_contents`    utility or
script function.
L137: def from_wheel(cls, wheel: Wheel, name: str) -> BaseDistribution:    Function
`from_wheel`    utility or script function.
L146: def location(self) -> str | None:    Function `location`    utility or script function.
L152: def info_location(self) -> str | None:    Function `info_location`    utility or script
function.
L158: def installed_location(self) -> str | None:    Function `installed_location`    utility or
script function.
L164: def canonical_name(self) -> NormalizedName:    Function `canonical_name`    utility or
script function.
L168: def version(self) -> Version:    Function `version`    utility or script function.
L179: def raw_version(self) -> str:    Function `raw_version`    utility or script function.
L182: def is_file(self, path: InfoPath) -> bool:    Function `is_file`    utility or script
function.
L185: def iter_distutils_script_names(self) -> Iterator[str]:    Function
`iter_distutils_script_names`    utility or script function.
L194: def read_text(self, path: InfoPath) -> str:    Function `read_text`    utility or script
function.
L200: def iter_entry_points(self) -> Iterable[BaseEntryPoint]:    Function `iter_entry_points`
utility or script function.
L204: def _metadata_impl(self) -> email.message.Message:    Function `_metadata_impl`    utility
or script function.
L218: def iter_provided_extras(self) -> Iterable[NormalizedName]:    Function
`iter_provided_extras`    utility or script function.
L224: def iter_dependencies(self, extras: Collection[str] = ()) -> Iterable[Requirement]:
Function `iter_dependencies`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_install.py

```

L62: class InstallRequirement:    Class (`InstallRequirement`)    component used by the app (see
file context: None).
L69: def __init__(    Function `__init__`    utility or script function.
L191: def __str__(self) -> str:    Function `__str__`    utility or script function.
L215: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L221: def format_debug(self) -> str:    Function `format_debug`    utility or script function.

```

```

L234: def name(self) -> str | None:    Function `name`    utility or script function.
L240: def supports_pyproject_editable(self) -> bool:    Function `supports_pyproject_editable`
        utility or script function.
L250: def specifier(self) -> SpecifierSet:    Function `specifier`    utility or script
        function.
L255: def is_direct(self) -> bool:    Function `is_direct`    utility or script function.
L260: def is_pinned(self) -> bool:    Function `is_pinned`    utility or script function.
L269: def match_markers(self, extras_requested: Iterable[str] | None = None) -> bool:
        Function `match_markers`    utility or script function.
L282: def has_hash_options(self) -> bool:    Function `has_hash_options`    utility or script
        function.
L291: def hashes(self, trust_internet: bool = True) -> Hashes:    Function `hashes`    utility
        or script function.
L318: def from_path(self) -> str | None:    Function `from_path`    utility or script function.
L333: def ensure_build_location(    Function `ensure_build_location`    utility or script
        function.
L376: def _set_requirement(self) -> None:    Function `_set_requirement`    utility or script
        function.
L398: def warn_on_mismatching_name(self) -> None:    Function `warn_on_mismatching_name`
        utility or script function.
L416: def check_if_exists(self, use_user_site: bool) -> None:    Function `check_if_exists`
        utility or script function.
L455: def is_wheel(self) -> bool:    Function `is_wheel`    utility or script function.
L461: def is_wheel_from_cache(self) -> bool:    Function `is_wheel_from_cache`    utility or
        script function.
L468: def unpacked_source_directory(self) -> str:    Function `unpacked_source_directory`
        utility or script function.
L475: def setup_py_path(self) -> str:    Function `setup_py_path`    Sets or updates a value.
L482: def pyproject_toml_path(self) -> str:    Function `pyproject_toml_path`    utility or
        script function.
L486: def load_pyproject_toml(self) -> None:    Function `load_pyproject_toml`    Loads data
        from storage or remote.
L506: def editable_sanity_check(self) -> None:    Function `editable_sanity_check`    utility or
        script function.
L519: def prepare_metadata(self) -> None:    Function `prepare_metadata`    utility or script
        function.
L555: def metadata(self) -> Any:    Function `metadata`    utility or script function.
L561: def set_dist(self, distribution: BaseDistribution) -> None:    Function `set_dist`    Sets
        or updates a value.
L564: def get_dist(self) -> BaseDistribution:    Function `get_dist`    Returns or fetches data.
L580: def assert_source_matches_version(self) -> None:    Function
        `assert_source_matches_version`    utility or script function.
L598: def ensure_has_source_dir(    Function `ensure_has_source_dir`    utility or script
        function.
L620: def needs_unpacked_archive(self, archive_source: Path) -> None:    Function
        `needs_unpacked_archive`    utility or script function.
L624: def ensure_pristine_source_checkout(self) -> None:    Function
        `ensure_pristine_source_checkout`    utility or script function.
L642: def update_editable(self) -> None:    Function `update_editable`    utility or script
        function.
L662: def uninstall(    Function `uninstall`    utility or script function.

```

```

L688: def _get_archive_name(self, path: str, parentdir: str, rootdir: str) -> str:    Function
`_get_archive_name`    utility or script function.
L689: def _clean_zip_name(name: str, prefix: str) -> str:    Function `_clean_zip_name`
utility or script function.
L702: def archive(self, build_dir: str | None) -> None:    Function `archive`    utility or
script function.
L769: def install(    Function `install`    utility or script function.
L804: def check_invalid_constraint_type(req: InstallRequirement) -> str:    Function
`check_invalid_constraint_type`    utility or script function.
L832: def _has_option(options: Values, reqs: list[InstallRequirement], option: str) -> bool:
Function `_has_option`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/pep723.py

```

L9: class PEP723Exception(ValueError):    Class (`PEP723Exception`)    component used by the app
(see file context: None).
L12: def __init__(self, msg: str) -> None:    Function `__init__`    utility or script function.
L16: def pep723_metadata(scriptfile: str) -> dict[str, Any]:    Function `pep723_metadata`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_set.py

```

L11: class RequirementSet:    Class (`RequirementSet`)    component used by the app (see file
context: None).
L12: def __init__(self, check_supported_wheels: bool = True) -> None:    Function `__init__`
utility or script function.
L20: def __str__(self) -> str:    Function `__str__`    utility or script function.
L27: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L40: def add_unnamed_requirement(self, install_req: InstallRequirement) -> None:    Function
`add_unnamed_requirement`    utility or script function.
L44: def add_named_requirement(self, install_req: InstallRequirement) -> None:    Function
`add_named_requirement`    utility or script function.
L50: def has_requirement(self, name: str) -> bool:    Function `has_requirement`    utility or
script function.
L58: def get_requirement(self, name: str) -> InstallRequirement:    Function `get_requirement`
Returns or fetches data.
L67: def all_requirements(self) -> list[InstallRequirement]:    Function `all_requirements`
utility or script function.
L71: def requirements_to_install(self) -> list[InstallRequirement]:    Function
`requirements_to_install`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/__init__.py

```

L26: class InstallationResult:    Class (`InstallationResult`)    component used by the app (see

```

```

file context: None).
L30: def _validate_requirements(    Function `_validate_requirements`    utility or script
function.
L38: def install_given_reqs(    Function `_install_given_reqs`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/constructors.py

```

L58: def _strip_extras(path: str) -> tuple[str, str | None]:    Function `_strip_extras`
utility or script function.
L70: def convert_extras(extras: str | None) -> set[str]:    Function `_convert_extras`    utility
or script function.
L76: def _set_requirement_extras(req: Requirement, new_extras: set[str]) -> Requirement:
Function `_set_requirement_extras`    utility or script function.
L101: def _parse_direct_url_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
    Function `_parse_direct_url_editable`    utility or script function.
L119: def _parse_pip_syntax_editable(editable_req: str) -> tuple[str | None, str, set[str]]:
    Function `_parse_pip_syntax_editable`    utility or script function.
L148: def parse_editable(editable_req: str) -> tuple[str | None, str, set[str]]:    Function
`parse_editable`    utility or script function.
L182: def check_first_requirement_in_file(filename: str) -> None:    Function
`check_first_requirement_in_file`    utility or script function.
L210: def deduce_helpful_msg(req: str) -> str:    Function `_deduce_helpful_msg`    utility or
script function.
L236: class RequirementParts:    Class (`RequirementParts`)    component used by the app (see
file context: None).
L243: def parse_req_from_editable(editable_req: str) -> RequirementParts:    Function
`parse_req_from_editable`    utility or script function.
L262: def install_req_from_editable(    Function `_install_req_from_editable`    utility or
script function.
L292: def _looks_like_path(name: str) -> bool:    Function `_looks_like_path`    utility or
script function.
L311: def _get_url_from_path(path: str, name: str) -> str | None:    Function
`_get_url_from_path`    utility or script function.
L345: def parse_req_from_line(name: str, line_source: str | None) -> RequirementParts:
Function `_parse_req_from_line`    utility or script function.
L393: def with_source(text: str) -> str:    Function `_with_source`    utility or script
function.
L398: def _parse_req_string(req_as_string: str) -> Requirement:    Function
`_parse_req_string`    utility or script function.
L424: def install_req_from_line(    Function `_install_req_from_line`    utility or script
function.
L457: def install_req_from_req_string(    Function `_install_req_from_req_string`    utility or
script function.
L493: def install_req_from_parsed_requirement(    Function
`install_req_from_parsed_requirement`    utility or script function.
L525: def install_req_from_link_and_ireq(    Function `_install_req_from_link_and_ireq`
utility or script function.
L541: def install_req_drop_extras(ireq: InstallRequirement) -> InstallRequirement:    Function

```

```

`install_req_drop_extras` utility or script function.
L565: def install_req_extend_extras( Function `install_req_extend_extras` utility or
script function.
L583: def _pylock_hashes_to_hash_options(hashes: Mapping[str, str]) -> dict[str, list[str]]:
Function `_pylock_hashes_to_hash_options` utility or script function.
L587: def install_req_from_pylock_package( Function `install_req_from_pylock_package`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_file.py

```

L105: class ParsedRequirement: Class (`ParsedRequirement`) component used by the app (see
file context: None).
L115: class ParsedLine: Class (`ParsedLine`) component used by the app (see file context:
None).
L123: def is_editable(self) -> bool: Function `is_editable` utility or script function.
L127: def requirement(self) -> str | None: Function `requirement` utility or script
function.
L136: def parse_requirements( Function `parse_requirements` utility or script function.
L163: def preprocess(content: str) -> ReqFileLines: Function `preprocess` utility or
script function.
L175: def handle_requirement_line( Function `handle_requirement_line` utility or script
function.
L209: def handle_option_line( Function `handle_option_line` utility or script function.
L287: def handle_line( Function `handle_line` utility or script function.
L331: class RequirementsFileParser: Class (`RequirementsFileParser`) component used by the
app (see file context: None).
L332: def __init__( Function `__init__` utility or script function.
L340: def parse( Function `parse` utility or script function.
L348: def _parse_and_recurse( Function `_parse_and_recurse` utility or script function.
L400: def _parse_file( Function `_parse_file` utility or script function.
L424: def get_line_parser(finder: PackageFinder | None) -> LineParser: Function
`get_line_parser` Returns or fetches data.
L425: def parse_line(line: str) -> tuple[str, Values]: Function `parse_line` utility or
script function.
L449: def break_args_options(line: str) -> tuple[str, str]: Function `break_args_options`
utility or script function.
L466: class OptionParsingError(Exception): Class (`OptionParsingError`) component used by
the app (see file context: None).
L467: def __init__(self, msg: str) -> None: Function `__init__` utility or script
function.
L471: def build_parser() -> optparse.OptionParser: Function `build_parser` Constructs or
prepares an object.
L484: def parser_exit(self: Any, msg: str) -> NoReturn: Function `parser_exit` utility or
script function.
L494: def join_lines(lines_enum: ReqFileLines) -> ReqFileLines: Function `join_lines`
utility or script function.
L525: def ignore_comments(lines_enum: ReqFileLines) -> ReqFileLines: Function
`ignore_comments` utility or script function.

```

```

L536: def expand_env_variables(lines_enum: ReqFileLines) -> ReqFileLines:    Function
`expand_env_variables`    utility or script function.
L563: def get_file_content(    Function `get_file_content`    Returns or fetches data.
L596: def _decode_req_file(data: bytes, url: str) -> str:    Function `_decode_req_file`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_dependency_group.py

```

L11: def parse_dependency_groups(groups: list[tuple[str, str]]) -> list[str]:    Function
`parse_dependency_groups`    utility or script function.
L21: def _resolve_all_groups(    Function `_resolve_all_groups`    utility or script function.
L41: def _build_resolvers(paths: Iterable[str]) -> dict[str, Any]:    Function
`_build_resolvers`    utility or script function.
L72: def _load_pyproject(path: str) -> dict[str, Any]:    Function `_load_pyproject`    utility
or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/req/req_uninstall.py

```

L24: def _script_names(    Function `_script_names`    utility or script function.
L43: def _unique(    Function `_unique`    utility or script function.
L47: def unique(*args: Any, **kw: Any) -> Generator[Any, None, None]:    Function `unique`
utility or script function.
L58: def uninstallation_paths(dist: BaseDistribution) -> Generator[str, None, None]:
Function `uninstallation_paths`    utility or script function.
L91: def compact(paths: Iterable[str]) -> set[str]:    Function `compact`    utility or script
function.
L110: def compress_for_rename(paths: Iterable[str]) -> set[str]:    Function
`compress_for_rename`    utility or script function.
L121: def norm_join(*a: str) -> str:    Function `norm_join`    utility or script function.
L144: def compress_for_output_listing(paths: Iterable[str]) -> tuple[set[str], set[str]]:
Function `compress_for_output_listing`    utility or script function.
L193: class StashedUninstallPathSet:    Class (`StashedUninstallPathSet`)    component used by
the app (see file context: None).
L197: def __init__(self) -> None:    Function `__init__`    utility or script function.
L205: def _get_directory_stash(self, path: str) -> str:    Function `_get_directory_stash`
utility or script function.
L219: def _get_file_stash(self, path: str) -> str:    Function `_get_file_stash`    utility or
script function.
L246: def stash(self, path: str) -> str:    Function `stash`    utility or script function.
L267: def commit(self) -> None:    Function `commit`    utility or script function.
L274: def rollback(self) -> None:    Function `rollback`    utility or script function.
L294: def can_rollback(self) -> bool:    Function `can_rollback`    utility or script function.
L298: class UninstallPathSet:    Class (`UninstallPathSet`)    component used by the app (see
file context: None).
L302: def __init__(self, dist: BaseDistribution) -> None:    Function `__init__`    utility or

```

```

script function.
L313: def _permitted(self, path: str) -> bool:    Function `_permitted` utility or script
function.
L324: def add(self, path: str) -> None:    Function `add` utility or script function.
L343: def add_pth(self, pth_file: str, entry: str) -> None:    Function `add_pth` utility or
script function.
L352: def remove(self, auto_confirm: bool = False, verbose: bool = False) -> None:    Function
`remove` utility or script function.
L381: def _allowed_to_proceed(self, verbose: bool) -> bool:    Function `_allowed_to_proceed`
utility or script function.
L384: def _display(msg: str, paths: Iterable[str]) -> None:    Function `_display` utility or
script function.
L409: def rollback(self) -> None:    Function `rollback` utility or script function.
L422: def commit(self) -> None:    Function `commit` utility or script function.
L427: def from_dist(cls, dist: BaseDistribution) -> UninstallPathSet:    Function `from_dist`
utility or script function.
L568: def iter_scripts_to_remove(    Function `iter_scripts_to_remove` utility or script
function.
L584: class UninstallPthEntries:    Class (`UninstallPthEntries`) component used by the app
(see file context: None).
L585: def __init__(self, pth_file: str) -> None:    Function `__init__` utility or script
function.
L590: def add(self, entry: str) -> None:    Function `add` utility or script function.
L605: def remove(self) -> None:    Function `remove` utility or script function.
L632: def rollback(self) -> bool:    Function `rollback` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/base.py

```

L11: class BaseResolver:    Class (`BaseResolver`) component used by the app (see file
context: None).
L12: def resolve(    Function `resolve` utility or script function.
L17: def get_installation_order(    Function `get_installation_order` Returns or fetches
data.

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/base.py

```

L18: def format_name(project: NormalizedName, extras: frozenset[NormalizedName]) -> str:
Function `format_name` utility or script function.
L26: class Constraint:    Class (`Constraint`) component used by the app (see file context:
None).
L33: def empty(cls) -> Constraint:    Function `empty` utility or script function.
L37: def from_ireq(cls, ireq: InstallRequirement) -> Constraint:    Function `from_ireq`
utility or script function.
L47: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L50: def __and__(self, other: InstallRequirement) -> Constraint:    Function `__and__`

```



```

utility or script function.
L69: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L78: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L85: class Requirement:    Class (`Requirement`)    component used by the app (see file context:
None).
L87: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L97: def name(self) -> str:    Function `name`    utility or script function.
L105: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L108: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L111: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L115: def _match_link(link: Link, candidate: Candidate) -> bool:    Function `_match_link`
utility or script function.
L121: class Candidate:    Class (`Candidate`)    component used by the app (see file context:
None).
L123: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L133: def name(self) -> str:    Function `name`    utility or script function.
L142: def version(self) -> Version:    Function `version`    utility or script function.
L146: def is_installed(self) -> bool:    Function `is_installed`    utility or script function.
L150: def is_editable(self) -> bool:    Function `is_editable`    utility or script function.
L154: def source_link(self) -> Link | None:    Function `source_link`    utility or script
function.
L157: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies`    utility or script function.
L160: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement`    Returns or fetches data.
L163: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/re solver.py

```

L41: class Resolver(BaseResolver):    Class (`Resolver`)    component used by the app (see file
context: None).
L44: def __init__(    Function `__init__`    utility or script function.
L76: def resolve(    Function `resolve`    utility or script function.
L186: def get_installation_order(    Function `get_installation_order`    Returns or fetches
data.
L218: def get_topological_weights(    Function `get_topological_weights`    Returns or fetches
data.
L249: def visit(node: str | None) -> None:    Function `visit`    utility or script function.
L321: def _req_set_item_sorter(    Function `_req_set_item_sorter`    utility or script

```

```
function.
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/reporter.py

```
L15: class PipReporter(BaseReporter[Requirement, Candidate, str]):  Class (`PipReporter`)
component used by the app (see file context: None).
L16: def __init__(self, constraints: Mapping[str, Constraint] | None = None) -> None:
Function `__init__` utility or script function.
L39: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:  Function
`rejecting_candidate` utility or script function.
L73: class PipDebuggingReporter(BaseReporter[Requirement, Candidate, str]):  Class
(`PipDebuggingReporter`) component used by the app (see file context: None).
L76: def starting(self) -> None:  Function `starting` utility or script function.
L79: def starting_round(self, index: int) -> None:  Function `starting_round` utility or
script function.
L82: def ending_round(self, index: int, state: Any) -> None:  Function `ending_round`
utility or script function.
L86: def ending(self, state: Any) -> None:  Function `ending` utility or script function.
L89: def adding_requirement(  Function `adding_requirement` utility or script function.
L94: def rejecting_candidate(self, criterion: Any, candidate: Candidate) -> None:  Function
`rejecting_candidate` utility or script function.
L97: def pinning(self, candidate: Candidate) -> None:  Function `pinning` utility or script
function.
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/candidates.py

```
L48: def as_base_candidate(candidate: Candidate) -> BaseCandidate | None:  Function
`as_base_candidate` utility or script function.
L60: def make_install_req_from_link(  Function `make_install_req_from_link` utility or
script function.
L90: def make_install_req_from_editable(  Function `make_install_req_from_editable` utility
or script function.
L112: def _make_install_req_from_dist(  Function `_make_install_req_from_dist` utility or
script function.
L134: class _InstallRequirementBackedCandidate(Candidate):  Class
(`_InstallRequirementBackedCandidate`) component used by the app (see file context: None).
L140: class exposes appropriate information to the resolver.  Class (`exposes`) component
used by the app (see file context: None).
L153: def __init__(  Function `__init__` utility or script function.
L171: def __str__(self) -> str:  Function `__str__` utility or script function.
L174: def __repr__(self) -> str:  Function `__repr__` utility or script function.
L177: def __hash__(self) -> int:  Function `__hash__` utility or script function.
L184: def __eq__(self, other: Any) -> bool:  Function `__eq__` utility or script function.
```

```

L190: def source_link(self) -> Link | None:    Function `source_link` utility or script
function.
L194: def project_name(self) -> NormalizedName:    Function `project_name` utility or script
function.
L201: def name(self) -> str:    Function `name` utility or script function.
L205: def version(self) -> Version:    Function `version` utility or script function.
L210: def format_for_error(self) -> str:    Function `format_for_error` utility or script
function.
L217: def _prepare_distribution(self) -> BaseDistribution:    Function `_prepare_distribution`
utility or script function.
L220: def _check_metadata_consistency(self, dist: BaseDistribution) -> None:    Function
`_check_metadata_consistency` utility or script function.
L244: def _prepare(self) -> BaseDistribution:    Function `_prepare` utility or script
function.
L271: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L279: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.
L283: class LinkCandidate(_InstallRequirementBackedCandidate):    Class (`LinkCandidate`)
component used by the app (see file context: None).
L286: def __init__(    Function `__init__` utility or script function.
L335: def _prepare_distribution(self) -> BaseDistribution:    Function `_prepare_distribution`
utility or script function.
L340: class EditableCandidate(_InstallRequirementBackedCandidate):    Class
(`EditableCandidate`) component used by the app (see file context: None).
L343: def __init__(    Function `__init__` utility or script function.
L360: def _prepare_distribution(self) -> BaseDistribution:    Function `_prepare_distribution`
utility or script function.
L364: class AlreadyInstalledCandidate(Candidate):    Class (`AlreadyInstalledCandidate`)
component used by the app (see file context: None).
L368: def __init__(    Function `__init__` utility or script function.
L386: def __str__(self) -> str:    Function `__str__` utility or script function.
L389: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L392: def __eq__(self, other: object) -> bool:    Object (singleton).
L397: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L401: def project_name(self) -> NormalizedName:    Function `project_name` utility or script
function.
L405: def name(self) -> str:    Function `name` utility or script function.
L409: def version(self) -> Version:    Function `version` utility or script function.
L415: def is_editable(self) -> bool:    Function `is_editable` utility or script function.
L418: def format_for_error(self) -> str:    Function `format_for_error` utility or script
function.
L421: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L431: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.
L435: class ExtrasCandidate(Candidate):    Class (`ExtrasCandidate`) component used by the
app (see file context: None).
L460: def __init__(    Function `__init__` utility or script function.
L479: def __str__(self) -> str:    Function `__str__` utility or script function.
L483: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```

```

L486: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L489: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L495: def project_name(self) -> NormalizedName:    Function `project_name` utility or script
function.
L499: def name(self) -> str:    Function `name` utility or script function.
L504: def version(self) -> Version:    Function `version` utility or script function.
L507: def format_for_error(self) -> str:    Function `format_for_error` utility or script
function.
L513: def is_installed(self) -> bool:    Function `is_installed` utility or script function.
L517: def is_editable(self) -> bool:    Function `is_editable` utility or script function.
L521: def source_link(self) -> Link | None:    Function `source_link` utility or script
function.
L524: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L552: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.
L559: class RequiresPythonCandidate(Candidate):    Class (`RequiresPythonCandidate`)
component used by the app (see file context: None).
L563: def __init__(self, py_version_info: tuple[int, ...] | None) -> None:    Function
`__init__` utility or script function.
L574: def __str__(self) -> str:    Function `__str__` utility or script function.
L577: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L581: def project_name(self) -> NormalizedName:    Function `project_name` utility or script
function.
L585: def name(self) -> str:    Function `name` utility or script function.
L589: def version(self) -> Version:    Function `version` utility or script function.
L592: def format_for_error(self) -> str:    Function `format_for_error` utility or script
function.
L595: def iter_dependencies(self, with_requires: bool) -> Iterable[Requirement | None]:
Function `iter_dependencies` utility or script function.
L598: def get_install_requirement(self) -> InstallRequirement | None:    Function
`get_install_requirement` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/provider.py

```

L56: def _get_with_identifier(    Function `_get_with_identifier` utility or script function.
L81: class PipProvider(_ProviderBase):    Class (`PipProvider`) component used by the app
(see file context: None).
L92: def __init__(    Function `__init__` utility or script function.
L109: def constraints(self) -> dict[str, Constraint]:    Function `constraints` utility or
script function.
L117: def identify(self, requirement_or_candidate: Requirement | Candidate) -> str:
Function `identify` utility or script function.
L120: def narrow_requirement_selection(    Function `narrow_requirement_selection` utility or
script function.
L176: def get_preference(    Function `get_preference` Returns or fetches data.
L256: def find_matches(    Function `find_matches` utility or script function.

```

```

L262: def _eligible_for_upgrade(identifier: str) -> bool:    Function `_eligible_for_upgrade`
utility or script function.
L300: def is_satisfied_by(requirement: Requirement, candidate: Candidate) -> bool:    Function
`is_satisfied_by` utility or script function.
L303: def get_dependencies(self, candidate: Candidate) -> Iterable[Requirement]:    Function
`get_dependencies` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/factory.py

```

L74: class ConflictCause(Protocol):    Class (`ConflictCause`) component used by the app (see
file context: None).
L85: class CollectedRootRequirements(NamedTuple):    Class (`CollectedRootRequirements`)
component used by the app (see file context: None).
L91: class Factory:    Class (`Factory`) component used by the app (see file context: None).
L92: def __init__(    Function `__init__` utility or script function.
L132: def force_reinstall(self) -> bool:    Function `force_reinstall` utility or script
function.
L135: def _fail_if_link_is_unsupported_wheel(self, link: Link) -> None:    Function
`_fail_if_link_is_unsupported_wheel` utility or script function.
L144: def _make_extras_candidate(    Function `_make_extras_candidate` utility or script
function.
L159: def _make_candidate_from_dist(    Function `_make_candidate_from_dist` utility or
script function.
L174: def _make_candidate_from_link(    Function `_make_candidate_from_link` utility or
script function.
L189: def _make_base_candidate_from_link(    Function `_make_base_candidate_from_link`
utility or script function.
L246: def _get_locked_installation_candidate(    Function `_get_locked_installation_candidate`
utility or script function.
L271: def _iter_found_candidates(    Function `_iter_found_candidates` utility or script
function.
L308: def _get_installed_candidate() -> Candidate | None:    Function
`_get_installed_candidate` utility or script function.
L337: def iter_index_candidate_infos() -> Iterator[IndexCandidateInfo]:    Function
`iter_index_candidate_infos` utility or script function.
L358: def is_pinned(specifier: SpecifierSet) -> bool:    Function `is_pinned` utility or
script function.
L392: def _iter_explicit_candidates_from_base(    Function
`_iter_explicit_candidates_from_base` utility or script function.
L414: def _iter_candidates_from_constraints(    Function `_iter_candidates_from_constraints`
utility or script function.
L448: def find_candidates(    Function `find_candidates` utility or script function.
L525: def _make_requirements_from_install_req(    Function
`_make_requirements_from_install_req` utility or script function.
L578: def collect_root_requirements(    Function `collect_root_requirements` utility or
script function.
L620: def make_requirement_from_candidate(    Function `make_requirement_from_candidate`

```

```

utility or script function.
L625: def make_requirements_from_spec(    Function `make_requirements_from_spec`    utility or
script function.
L643: def make_requires_python_requirement(    Function `make_requires_python_requirement`
utility or script function.
L654: def get_wheel_cache_entry(self, link: Link, name: str | None) -> CacheEntry | None:
Function `get_wheel_cache_entry`    Returns or fetches data.
L671: def get_dist_to_uninstall(self, candidate: Candidate) -> BaseDistribution | None:
Function `get_dist_to_uninstall`    Returns or fetches data.
L699: def _report_requires_python_error(    Function `_report_requires_python_error`    utility
or script function.
L721: def _report_single_requirement_conflict(    Function
`_report_single_requirement_conflict`    utility or script function.
L783: def _has_any_candidates(self, project_name: str) -> bool:    Function
`_has_any_candidates`    utility or script function.
L798: def get_installation_error(    Function `get_installation_error`    Returns or fetches
data.
L834: def text_join(parts: list[str]) -> str:    Function `text_join`    utility or script
function.
L840: def describe_trigger(parent: Candidate) -> str:    Function `describe_trigger`    utility
or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/re quirements.py

```

L14: class ExplicitRequirement(Requirement):    Class (`ExplicitRequirement`)    component used
by the app (see file context: None).
L15: def __init__(self, candidate: Candidate) -> None:    Function `__init__`    utility or
script function.
L18: def __str__(self) -> str:    Function `__str__`    utility or script function.
L21: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L24: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L27: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L33: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L38: def name(self) -> str:    Function `name`    utility or script function.
L42: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L45: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L48: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L52: class SpecifierRequirement(Requirement):    Class (`SpecifierRequirement`)    component
used by the app (see file context: None).
L53: def __init__(self, ireq: InstallRequirement) -> None:    Function `__init__`    utility or
script function.
L61: def _equal(self) -> str:    Function `_equal`    utility or script function.
L68: def __str__(self) -> str:    Function `__str__`    utility or script function.

```

```

L71: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L74: def __eq__(self, other: object) -> bool:    Object (singleton).
L79: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L87: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L92: def name(self) -> str:    Function `name`    utility or script function.
L95: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L108: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L111: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L124: class SpecifierWithoutExtrasRequirement(SpecifierRequirement):    Class
(`SpecifierWithoutExtrasRequirement`)    component used by the app (see file context: None).
L130: def __init__(self, ireq: InstallRequirement) -> None:    Function `__init__`    utility or
script function.
L138: def _equal(self) -> str:    Function `_equal`    utility or script function.
L145: def __eq__(self, other: object) -> bool:    Object (singleton).
L150: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L158: class RequiresPythonRequirement(Requirement):    Class (`RequiresPythonRequirement`)
component used by the app (see file context: None).
L161: def __init__(self, specifier: SpecifierSet, match: Candidate) -> None:    Function
`__init__`    utility or script function.
L173: def __str__(self) -> str:    Function `__str__`    utility or script function.
L176: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L179: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L186: def __eq__(self, other: Any) -> bool:    Function `__eq__`    utility or script function.
L195: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L199: def name(self) -> str:    Function `name`    utility or script function.
L202: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L205: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.
L208: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
L216: class UnsatisfiableRequirement(Requirement):    Class (`UnsatisfiableRequirement`)
component used by the app (see file context: None).
L219: def __init__(self, name: NormalizedName) -> None:    Function `__init__`    utility or
script function.
L222: def __str__(self) -> str:    Function `__str__`    utility or script function.
L225: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L228: def __eq__(self, other: object) -> bool:    Object (singleton).
L233: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L237: def project_name(self) -> NormalizedName:    Function `project_name`    utility or script
function.
L241: def name(self) -> str:    Function `name`    utility or script function.
L244: def format_for_error(self) -> str:    Function `format_for_error`    utility or script
function.
L247: def get_candidate_lookup(self) -> CandidateLookup:    Function `get_candidate_lookup`
Returns or fetches data.

```

```
L250: def is_satisfied_by(self, candidate: Candidate) -> bool:    Function `is_satisfied_by`
utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/resolvelib/found_candidates.py

```
L28: def _iter_built(infos: Iterator[IndexCandidateInfo]) -> Iterator[Candidate]:    Function
`_iter_built` utility or script function.
L59: def _iter_built_with_prepended(    Function `_iter_built_with_prepended` utility or
script function.
L81: def _iter_built_with_inserted(    Function `_iter_built_with_inserted` utility or script
function.
L113: class FoundCandidates(Sequence[Candidate]):    Class (`FoundCandidates`) component used
by the app (see file context: None).
L122: def __init__(    Function `__init__` utility or script function.
L135: def __getitem__(self, index: Any) -> Any:    Function `__getitem__` utility or script
function.
L141: def __iter__(self) -> Iterator[Candidate]:    Function `__iter__` utility or script
function.
L151: def __len__(self) -> int:    Function `__len__` utility or script function.
L157: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/resolution/legacy/resolver.py

```
L58: def _check_dist_requires_python(    Function `_check_dist_requires_python` utility or
script function.
L112: class Resolver(BaseResolver):    Class (`Resolver`) component used by the app (see file
context: None).
L119: def __init__(    Function `__init__` utility or script function.
L157: def resolve(    Function `resolve` utility or script function.
L194: def _add_requirement_to_set(    Function `_add_requirement_to_set` utility or script
function.
L309: def _is_upgrade_allowed(self, req: InstallRequirement) -> bool:    Function
`_is_upgrade_allowed` utility or script function.
L318: def _set_req_to_reinstall(self, req: InstallRequirement) -> None:    Function
`_set_req_to_reinstall` utility or script function.
L329: def _check_skip_installed(self, req_to_install: InstallRequirement) -> str | None:
Function `_check_skip_installed` utility or script function.
L381: def _find_requirement_link(self, req: InstallRequirement) -> Link | None:    Function
`_find_requirement_link` utility or script function.
L403: def _populate_link(self, req: InstallRequirement) -> None:    Function `_populate_link`
utility or script function.
L442: def _get_dist_for(self, req: InstallRequirement) -> BaseDistribution:    Function
`_get_dist_for` utility or script function.
```



```

L488: def _resolve_one(    Function `_resolve_one`    utility or script function.
L517: def add_req(subreq: Requirement, extras_requested: Iterable[str]) -> None:    Function
`add_req`    utility or script function.
L571: def get_installation_order(    Function `get_installation_order`    Returns or fetches
data.
L586: def schedule(req: InstallRequirement) -> None:    Function `schedule`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/index/collector.py

```

L46: def _match_vcs_scheme(url: str) -> str | None:    Function `_match_vcs_scheme`    utility
or script function.
L57: class _NotAPIContent(Exception):    Class (`_NotAPIContent`)    component used by the app
(see file context: None).
L58: def __init__(self, content_type: str, request_desc: str) -> None:    Function `__init__`
utility or script function.
L64: def _ensure_api_header(response: Response) -> None:    Function `_ensure_api_header`
utility or script function.
L86: class _NotHTTP(Exception):    Class (`_NotHTTP`)    component used by the app (see file
context: None).
L90: def _ensure_api_response(url: str, session: PipSession) -> None:    Function
`_ensure_api_response`    utility or script function.
L108: def _get_simple_response(url: str, session: PipSession) -> Response:    Function
`_get_simple_response`    utility or script function.
L171: def _get_encoding_from_headers(headers: ResponseHeaders) -> str | None:    Function
`_get_encoding_from_headers`    utility or script function.
L182: class CacheablePageContent:    Class (`CacheablePageContent`)    component used by the app
(see file context: None).
L183: def __init__(self, page: IndexContent) -> None:    Function `__init__`    utility or
script function.
L187: def __eq__(self, other: object) -> bool:    Object (singleton).
L190: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L194: class ParseLinks(Protocol):    Class (`ParseLinks`)    component used by the app (see file
context: None).
L195: def __call__(self, page: IndexContent) -> Iterable[Link]: ...    Function `__call__`
utility or script function.
L198: def with_cached_index_content(fn: ParseLinks) -> ParseLinks:    Function
`with_cached_index_content`    utility or script function.
L206: def wrapper(cacheable_page: CacheablePageContent) -> list[Link]:    Function `wrapper`
utility or script function.
L210: def wrapper_wrapper(page: IndexContent) -> list[Link]:    Function `wrapper_wrapper`
utility or script function.
L219: def parse_links(page: IndexContent) -> Iterable[Link]:    Function `parse_links`
utility or script function.
L248: class IndexContent:    Class (`IndexContent`)    component used by the app (see file
context: None).
L264: def __str__(self) -> str:    Function `__str__`    utility or script function.
L268: class HTMLLinkParser(HTMLParser):    Class (`HTMLLinkParser`)    component used by the app

```

```

(see file context: None).
L274: def __init__(self, url: str) -> None:    Function `__init__`    utility or script
function.
L281: def handle_starttag(self, tag: str, attrs: list[tuple[str, str | None]]) -> None:
Function `handle_starttag`    utility or script function.
L289: def get_href(self, attrs: list[tuple[str, str | None]]) -> str | None:    Function
`get_href`    Returns or fetches data.
L296: def _handle_get_simple_fail(    Function `_handle_get_simple_fail`    utility or script
function.
L306: def _make_index_content(    Function `_make_index_content`    utility or script function.
L319: def _get_index_content(link: Link, *, session: PipSession) -> IndexContent | None:
Function `_get_index_content`    utility or script function.
L379: class CollectedSources(NamedTuple):    Class (`CollectedSources`)    component used by the
app (see file context: None).
L384: class LinkCollector:    Class (`LinkCollector`)    component used by the app (see file
context: None).
L392: def __init__(    Function `__init__`    utility or script function.
L401: def create(    Function `create`    Creates a resource or document.
L435: def find_links(self) -> list[str]:    Function `find_links`    utility or script function.
L438: def fetch_response(self, location: Link) -> IndexContent | None:    Function
`fetch_response`    utility or script function.
L444: def collect_sources(    Function `collect_sources`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/index/sources.py

```

L31: class LinkSource:    Class (`LinkSource`)    component used by the app (see file context:
None).
L33: def link(self) -> Link | None:    Function `link`    utility or script function.
L37: def page_candidates(self) -> FoundCandidates:    Function `page_candidates`    utility or
script function.
L41: def file_links(self) -> FoundLinks:    Function `file_links`    utility or script function.
L46: def _is_html_file(file_url: str) -> bool:    Function `_is_html_file`    utility or script
function.
L50: class _FlatDirectoryToUrls:    Class (`_FlatDirectoryToUrls`)    component used by the app
(see file context: None).
L53: def __init__(self, path: str) -> None:    Function `__init__`    utility or script
function.
L59: def _scan_directory(self) -> None:    Function `_scan_directory`    utility or script
function.
L83: def page_candidates(self) -> list[str]:    Function `page_candidates`    utility or script
function.
L90: def project_name_to_urls(self) -> dict[str, list[str]]:    Function
`project_name_to_urls`    utility or script function.
L97: class _FlatDirectorySource(LinkSource):    Class (`_FlatDirectorySource`)    component used
by the app (see file context: None).
L108: def __init__(    Function `__init__`    utility or script function.
L125: def link(self) -> Link | None:    Function `link`    utility or script function.
L128: def page_candidates(self) -> FoundCandidates:    Function `page_candidates`    utility or

```

```

script function.
L132: def file_links(self) -> FoundLinks:    Function `file_links`    utility or script
function.
L137: class _LocalFileSource(LinkSource):    Class (`_LocalFileSource`)    component used by the
app (see file context: None).
L147: def __init__(    Function `__init__`    utility or script function.
L156: def link(self) -> Link | None:    Function `link`    utility or script function.
L159: def page_candidates(self) -> FoundCandidates:    Function `page_candidates`    utility or
script function.
L164: def file_links(self) -> FoundLinks:    Function `file_links`    utility or script
function.
L170: class _RemoteFileSource(LinkSource):    Class (`_RemoteFileSource`)    component used by
the app (see file context: None).
L179: def __init__(    Function `__init__`    utility or script function.
L190: def link(self) -> Link | None:    Function `link`    utility or script function.
L193: def page_candidates(self) -> FoundCandidates:    Function `page_candidates`    utility or
script function.
L198: def file_links(self) -> FoundLinks:    Function `file_links`    utility or script
function.
L202: class _IndexDirectorySource(LinkSource):    Class (`_IndexDirectorySource`)    component
used by the app (see file context: None).
L209: def __init__(    Function `__init__`    utility or script function.
L218: def link(self) -> Link | None:    Function `link`    utility or script function.
L221: def page_candidates(self) -> FoundCandidates:    Function `page_candidates`    utility or
script function.
L224: def file_links(self) -> FoundLinks:    Function `file_links`    utility or script
function.
L228: def build_source(    Function `build_source`    Constructs or prepares an object.

```

.venv/lib/python3.12/site-packages/pip/_internal/index/package_finder.py

```

L63: def _check_link_requires_python(    Function `_check_link_requires_python`    utility or
script function.
L110: class LinkType(enum.Enum):    Class (`LinkType`)    component used by the app (see file
context: None).
L122: class LinkEvaluator:    Class (`LinkEvaluator`)    component used by the app (see file
context: None).
L133: def __init__(    Function `__init__`    utility or script function.
L172: def evaluate_link(self, link: Link) -> tuple[LinkType, str]:    Function `evaluate_link`
utility or script function.
L283: def get_version_sort_key(v: str) -> tuple[int, ...]:    Function `get_version_sort_key`
Returns or fetches data.
L300: def filter_unallowed_hashes(    Function `filter_unallowed_hashes`    utility or script
function.
L375: class CandidatePreferences:    Class (`CandidatePreferences`)    component used by the app
(see file context: None).
L386: class BestCandidateResult:    Class (`BestCandidateResult`)    component used by the app

```

```

(see file context: None).
L402: def __post_init__(self) -> None:    Function `__post_init__`    utility or script
function.
L411: class CandidateEvaluator:    Class (`CandidateEvaluator`)    component used by the app
(see file context: None).
L418: def create(    Function `create`    Creates a resource or document.
L453: def __init__(    Function `__init__`    utility or script function.
L479: def get_applicable_candidates(    Function `get_applicable_candidates`    Returns or
fetches data.
L518: def _sort_key(self, candidate: InstallationCandidate) -> CandidateSortingKey:
Function `_sort_key`    utility or script function.
L583: def sort_best_candidate(    Function `sort_best_candidate`    utility or script function.
L596: def compute_best_candidate(    Function `compute_best_candidate`    utility or script
function.
L614: class PackageFinder:    Class (`PackageFinder`)    component used by the app (see file
context: None).
L621: def __init__(    Function `__init__`    utility or script function.
L672: def create(    Function `create`    Creates a resource or document.
L708: def target_python(self) -> TargetPython:    Function `target_python`    utility or script
function.
L712: def search_scope(self) -> SearchScope:    Function `search_scope`    utility or script
function.
L716: def search_scope(self, search_scope: SearchScope) -> None:    Function `search_scope`
utility or script function.
L720: def find_links(self) -> list[str]:    Function `find_links`    utility or script function.
L724: def index_urls(self) -> list[str]:    Function `index_urls`    utility or script function.
L728: def proxy(self) -> str | None:    Function `proxy`    utility or script function.
L732: def trusted_hosts(self) -> Iterable[str]:    Function `trusted_hosts`    utility or script
function.
L737: def custom_cert(self) -> str | None:    Function `custom_cert`    utility or script
function.
L745: def client_cert(self) -> str | None:    Function `client_cert`    utility or script
function.
L751: def release_control(self) -> ReleaseControl | None:    Function `release_control`
utility or script function.
L754: def set_release_control(self, release_control: ReleaseControl) -> None:    Function
`set_release_control`    Sets or updates a value.
L758: def prefer_binary(self) -> bool:    Function `prefer_binary`    utility or script
function.
L761: def set_prefer_binary(self) -> None:    Function `set_prefer_binary`    Sets or updates a
value.
L765: def uploaded_prior_to(self) -> datetime.datetime | None:    Function `uploaded_prior_to`
utility or script function.
L768: def requires_python_skipped_reasons(self) -> list[str]:    Function
`requires_python_skipped_reasons`    utility or script function.
L771: def make_link_evaluator(self, project_name: str) -> LinkEvaluator:    Function
`make_link_evaluator`    utility or script function.
L785: def _sort_links(self, links: Iterable[Link]) -> list[Link]:    Function `_sort_links`
utility or script function.
L801: def _log_skipped_link(self, link: Link, result: LinkType, detail: str) -> None:
Function `_log_skipped_link`    utility or script function.

```

```

L808: def get_install_candidate(    Function `get_install_candidate`  Returns or fetches data.
L833: def evaluate_links(    Function `evaluate_links`  utility or script function.
L847: def process_project_url(    Function `process_project_url`  utility or script function.
L868: def find_all_candidates(self, project_name: str) -> list[InstallationCandidate]:
Function `find_all_candidates`  utility or script function.
L925: def make_candidate_evaluator(    Function `make_candidate_evaluator`  utility or script
function.
L942: def find_best_candidate(    Function `find_best_candidate`  utility or script function.
L971: def find_requirement(    Function `find_requirement`  utility or script function.
L995: def _format_versions(cand_iter: Iterable[InstallationCandidate]) -> str:    Function
`_format_versions`  utility or script function.
L1030: def _should_install_candidate(    Function `_should_install_candidate`  utility or
script function.
L1072: def _find_name_version_sep(fragment: str, canonical_name: str) -> int:    Function
`_find_name_version_sep`  utility or script function.
L1098: def _extract_version_from_fragment(fragment: str, canonical_name: str) -> str | None:
Function `_extract_version_from_fragment`  utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/network/lazy_wheel.py

```

L22: class HTTPRangeRequestUnsupported(Exception):    Class (`HTTPRangeRequestUnsupported`)
component used by the app (see file context: None).
L26: def dist_from_wheel_url(    Function `dist_from_wheel_url`  utility or script function.
L45: class LazyZipOverHTTP:    Class (`LazyZipOverHTTP`)  component used by the app (see file
context: None).
L54: def __init__(    Function `__init__`  utility or script function.
L71: def mode(self) -> str:    Function `mode`  utility or script function.
L76: def name(self) -> str:    Function `name`  utility or script function.
L80: def seekable(self) -> bool:    Function `seekable`  utility or script function.
L84: def close(self) -> None:    Function `close`  utility or script function.
L89: def closed(self) -> bool:    Function `closed`  utility or script function.
L93: def read(self, size: int = -1) -> bytes:    Function `read`  utility or script function.
L107: def readable(self) -> bool:    Function `readable`  utility or script function.
L111: def seek(self, offset: int, whence: int = 0) -> int:    Function `seek`  utility or
script function.
L121: def tell(self) -> int:    Function `tell`  utility or script function.
L125: def truncate(self, size: int | None = None) -> int:    Function `truncate`  utility or
script function.
L135: def writable(self) -> bool:    Function `writable`  utility or script function.
L139: def __enter__(self) -> LazyZipOverHTTP:    Function `__enter__`  utility or script
function.
L143: def __exit__(self, *exc: Any) -> None:    Function `__exit__`  utility or script
function.
L147: def _stay(self) -> Generator[None, None, None]:    Function `_stay`  utility or script
function.
L158: def _check_zip(self) -> None:    Function `_check_zip`  utility or script function.
L173: def _stream_response(    Function `_stream_response`  utility or script function.
L183: def _merge(    Function `_merge`  utility or script function.

```

```
L205: def _download(self, start: int, end: int) -> None:    Function `_download` utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/network/session.py

```
L198: def looks_like_ci() -> bool:    Function `_looks_like_ci` utility or script function.
L109: def user_agent() -> str:    Function `_user_agent` utility or script function.
L210: class LocalFSAdapter(BaseAdapter):    Class (`LocalFSAdapter`) component used by the
app (see file context: None).
L211: def send(    Function `_send` utility or script function.
L251: def close(self) -> None:    Function `_close` utility or script function.
L255: class _SSLContextAdapterMixin:    Class (`_SSLContextAdapterMixin`) component used by
the app (see file context: None).
L263: def __init__(    Function `___init__` utility or script function.
L272: def init_poolmanager(    Function `_init_poolmanager` Initialisation routine.
L288: def proxy_manager_for(self, proxy: str, **proxy_kwargs: Any) -> ProxyManager:
Function `_proxy_manager_for` utility or script function.
L296: class HTTPAdapter(_SSLContextAdapterMixin, _BaseHTTPAdapter):    Class (`HTTPAdapter`)
component used by the app (see file context: None).
L300: class CacheControlAdapter(_SSLContextAdapterMixin, _BaseCacheControlAdapter):    Class
(`CacheControlAdapter`) component used by the app (see file context: None).
L304: class InsecureHTTPAdapter(HTTPAdapter):    Class (`InsecureHTTPAdapter`) component used
by the app (see file context: None).
L305: def cert_verify(    Function `_cert_verify` utility or script function.
L315: class InsecureCacheControlAdapter(CacheControlAdapter):    Class
(`InsecureCacheControlAdapter`) component used by the app (see file context: None).
L316: def cert_verify(    Function `_cert_verify` utility or script function.
L326: class PipSession(requests.Session):    Class (`PipSession`) component used by the app
(see file context: None).
L329: def __init__(    Function `___init__` utility or script function.
L413: def update_index_urls(self, new_index_urls: list[str]) -> None:    Function
`update_index_urls` utility or script function.
L420: def add_trusted_host(    Function `_add_trusted_host` utility or script function.
L453: def iter_secure_origins(self) -> Generator[SecureOrigin, None, None]:    Function
`iter_secure_origins` utility or script function.
L458: def is_secure_origin(self, location: Link) -> bool:    Function `_is_secure_origin`
utility or script function.
L525: def request(self, method: str, url: str, *args: Any, **kwargs: Any) -> Response:    #
type: ignore[override]    Function `_request` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/network/cache.py

```
L24: def is_from_cache(response: Response) -> bool:    Function `_is_from_cache` utility or
script function.
L29: def suppressed_cache_errors() -> Generator[None, None, None]:    Function
`suppressed_cache_errors` utility or script function.
```

```

L39: class SafeFileCache(SeparateBodyBaseCache):    Class (`SafeFileCache`) component used by
the app (see file context: None).
L57: def __init__(self, directory: str) -> None:    Function `__init__` utility or script
function.
L62: def _get_cache_path(self, name: str) -> str:    Function `_get_cache_path` utility or
script function.
L70: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L80: def _write_to_file(self, path: str, writer_func: Callable[[BinaryIO], Any]) -> None:
Function `_write_to_file` utility or script function.
L93: def _write(self, path: str, data: bytes) -> None:    Function `_write` utility or script
function.
L96: def _write_from_io(self, path: str, source_file: BinaryIO) -> None:    Function
`_write_from_io` utility or script function.
L99: def set(    Function `set` Sets or updates a value.
L105: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L112: def get_body(self, key: str) -> BinaryIO | None:    Function `get_body` Returns or
fetches data.
L121: def set_body(self, key: str, body: bytes) -> None:    Function `set_body` Sets or
updates a value.
L125: def set_body_from_io(self, key: str, body_file: BinaryIO) -> None:    Function
`set_body_from_io` Sets or updates a value.

```

.venv/lib/python3.12/site-packages/pip/_internal/network/utils.py

```

L31: def raise_for_status(resp: Response) -> None:    Function `raise_for_status` utility or
script function.
L59: def response_chunks(    Function `response_chunks` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/network/xmlrpc.py

```

L20: class PipXmlrpcTransport(xmlrpc.client.Transport):    Class (`PipXmlrpcTransport`)
component used by the app (see file context: None).
L25: def __init__(    Function `__init__` utility or script function.
L33: def request(    Function `request` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/network/auth.py

```

L44: class Credentials(NamedTuple):    Class (`Credentials`) component used by the app (see
file context: None).
L50: class KeyRingBaseProvider(ABC):    Class (`KeyRingBaseProvider`) component used by the
app (see file context: None).
L56: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None: ...
Function `get_auth_info` Returns or fetches data.
L59: def save_auth_info(self, url: str, username: str, password: str) -> None: ...    Function

```



```

`save_auth_info` Saves data to storage or remote.
L62: class KeyRingNullProvider(KeyRingBaseProvider):    Class (`KeyRingNullProvider`)
component used by the app (see file context: None).
L67: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:    Function
`get_auth_info` Returns or fetches data.
L70: def save_auth_info(self, url: str, username: str, password: str) -> None:    Function
`save_auth_info` Saves data to storage or remote.
L74: class KeyRingPythonProvider(KeyRingBaseProvider):    Class (`KeyRingPythonProvider`)
component used by the app (see file context: None).
L79: def __init__(self) -> None:    Function `__init__` utility or script function.
L84: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:    Function
`get_auth_info` Returns or fetches data.
L102: def save_auth_info(self, url: str, username: str, password: str) -> None:    Function
`save_auth_info` Saves data to storage or remote.
L106: class KeyRingCliProvider(KeyRingBaseProvider):    Class (`KeyRingCliProvider`)
component used by the app (see file context: None).
L117: def __init__(self, cmd: str) -> None:    Function `__init__` utility or script
function.
L120: def get_auth_info(self, url: str, username: str | None) -> AuthInfo | None:    Function
`get_auth_info` Returns or fetches data.
L129: def save_auth_info(self, url: str, username: str, password: str) -> None:    Function
`save_auth_info` Saves data to storage or remote.
L132: def _get_password(self, service_name: str, username: str) -> str | None:    Function
`_get_password` utility or script function.
L150: def _set_password(self, service_name: str, username: str, password: str) -> None:
Function `_set_password` utility or script function.
L166: def get_keyring_provider(provider: str) -> KeyRingBaseProvider:    Function
`get_keyring_provider` Returns or fetches data.
L191: def PATH_as_shutil_which_determines_it() -> str:    Function
`PATH_as_shutil_which_determines_it` utility or script function.
L227: class MultiDomainBasicAuth(AuthBase):    Authentication component
(`MultiDomainBasicAuth`) handles user authentication flows.
L228: def __init__(    Function `__init__` utility or script function.
L246: def keyring_provider(self) -> KeyRingBaseProvider:    Function `keyring_provider`
utility or script function.
L250: def keyring_provider(self, provider: str) -> None:    Function `keyring_provider`
utility or script function.
L258: def use_keyring(self) -> bool:    Function `use_keyring` utility or script function.
L264: def _get_keyring_auth(    Function `_get_keyring_auth` utility or script function.
L290: def _get_index_url(self, url: str) -> str | None:    Function `_get_index_url` utility
or script function.
L340: def _get_new_credentials(    Function `_get_new_credentials` utility or script
function.
L397: def _get_url_and_credentials(    Function `_get_url_and_credentials` utility or script
function.
L445: def __call__(self, req: PreparedRequest) -> PreparedRequest:    Function `__call__`
utility or script function.
L463: def _prompt_for_password(self, netloc: str) -> tuple[str | None, str | None, bool]:
Function `_prompt_for_password` utility or script function.
L475: def _should_save_password_to_keyring(self) -> bool:    Function
`_should_save_password_to_keyring` utility or script function.

```



```

L484: def handle_401(self, resp: Response, **kwargs: Any) -> Response:    Function
`handle_401` utility or script function.
L547: def warn_on_401(self, resp: Response, **kwargs: Any) -> None:    Function `warn_on_401`
utility or script function.
L555: def save_credentials(self, resp: Response, **kwargs: Any) -> None:    Function
`save_credentials` Saves data to storage or remote.

```

.venv/lib/python3.12/site-packages/pip/_internal/network/download.py

```

L31: def _get_http_response_size(resp: Response) -> int | None:    Function
`_get_http_response_size` utility or script function.
L38: def _get_http_response_etag_or_last_modified(resp: Response) -> str | None:    Function
`_get_http_response_etag_or_last_modified` utility or script function.
L46: def _log_download(    Function `_log_download` utility or script function.
L97: def sanitize_content_filename(filename: str) -> str:    Function
`sanitize_content_filename` utility or script function.
L104: def parse_content_disposition(content_disposition: str, default_filename: str) -> str:
Function `_parse_content_disposition` utility or script function.
L119: def _get_http_response_filename(resp: Response, link: Link) -> str:    Function
`_get_http_response_filename` utility or script function.
L141: class _FileDownload:    Class (`_FileDownload`) component used by the app (see file
context: None).
L150: def is_incomplete(self) -> bool:    Function `is_incomplete` utility or script
function.
L153: def write_chunk(self, data: bytes) -> None:    Function `write_chunk` utility or script
function.
L157: def reset_file(self) -> None:    Function `reset_file` utility or script function.
L164: class Downloader:    Class (`Downloader`) component used by the app (see file context:
None).
L165: def __init__(    Function `__init__` utility or script function.
L177: def batch(    Function `batch` utility or script function.
L185: def __call__(self, link: Link, location: str) -> tuple[str, str]:    Function `__call__`
utility or script function.
L200: def _process_response(self, download: _FileDownload, resp: Response) -> None:
Function `_process_response` utility or script function.
L219: def _attempt_resumes_or_redownloads(    Function `_attempt_resumes_or_redownloads`
utility or script function.
L259: def _cache_resumed_download(    Function `_cache_resumed_download` utility or script
function.
L315: def _http_get_resume(    Function `_http_get_resume` utility or script function.
L329: def _http_get(self, link: Link, headers: Mapping[str, str] = HEADERS) -> Response:
Function `_http_get` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/parser.py

```

L27: class PrettyHelpFormatter(optparse.IndentedHelpFormatter):    Class

```

```

(`PrettyHelpFormatter`) component used by the app (see file context: None).
L41: def __init__(self, *args: Any, **kwargs: Any) -> None: Function `__init__` utility or
script function.
L48: def format_option_strings(self, option: optparse.Option) -> str: Function
`format_option_strings` utility or script function.
L66: def format_option(self, option: optparse.Option) -> str: Function `format_option`
utility or script function.
L96: def format_heading(self, heading: str) -> str: Function `format_heading` utility or
script function.
L101: def format_usage(self, usage: str) -> str: Function `format_usage` utility or script
function.
L110: def format_description(self, description: str | None) -> str: Function
`format_description` utility or script function.
L129: def format_epilog(self, epilog: str | None) -> str: Function `format_epilog` utility
or script function.
L136: def expand_default(self, option: optparse.Option) -> str: Function `expand_default`
utility or script function.
L143: def indent_lines(self, text: str, indent: str) -> str: Function `indent_lines`
utility or script function.
L148: class UpdatingDefaultsHelpFormatter(PrettyHelpFormatter): Class
(`UpdatingDefaultsHelpFormatter`) component used by the app (see file context: None).
L157: def expand_default(self, option: optparse.Option) -> str: Function `expand_default`
utility or script function.
L180: class CustomOptionParser(optparse.OptionParser): Class (`CustomOptionParser`)
component used by the app (see file context: None).
L181: def insert_option_group( Function `insert_option_group` utility or script function.
L193: def option_list_all(self) -> list[optparse.Option]: Function `option_list_all`
utility or script function.
L202: class ConfigOptionParser(CustomOptionParser): Class (`ConfigOptionParser`) component
used by the app (see file context: None).
L206: def __init__( Function `__init__` utility or script function.
L219: def check_default(self, option: optparse.Option, key: str, val: Any) -> Any: Function
`check_default` utility or script function.
L226: def _get_ordered_configuration_items( Function `_get_ordered_configuration_items`
utility or script function.
L257: def _update_defaults(self, defaults: dict[str, Any]) -> dict[str, Any]: Function
`_update_defaults` utility or script function.
L321: def get_default_values(self) -> optparse.Values: Function `get_default_values`
Returns or fetches data.
L343: def error(self, msg: str) -> NoReturn: Function `error` utility or script function.
L347: def print_help(self, file: Any = None) -> None: Function `print_help` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/main_parser.py

```

L21: def create_main_parser() -> ConfigOptionParser: Function `create_main_parser` Creates
a resource or document.
L52: def identify_python_interpreter(python: str) -> str | None: Function

```

```
`identify_python_interpreter` utility or script function.
L71: def parse_command(args: list[str]) -> tuple[str, list[str]]: Function `parse_command`
utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/cli/progressBars.py

```
L33: def _rich_download_progress_bar( Function `_rich_download_progress_bar` utility or
script function.
L75: def _rich_install_progress_bar( Function `_rich_install_progress_bar` utility or
script function.
L97: def _raw_progress_bar( Function `_raw_progress_bar` utility or script function.
L103: def write_progress(current: int, total: int) -> None: Function `write_progress`
utility or script function.
L120: def get_download_progress_renderer( Function `get_download_progress_renderer`
Returns or fetches data.
L144: def get_install_progress_renderer( Function `get_install_progress_renderer` Returns
or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_internal/cli/autocompletion.py

```
L17: def autocomplete() -> None: Function `autocomplete` utility or script function.
L132: def get_path_completion_type( Function `get_path_completion_type` Returns or fetches
data.
L156: def auto_complete_paths(current: str, completion_type: str) -> Iterable[str]:
Function `auto_complete_paths` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/cli/req_command.py

```
L64: def should_ignore_regular_constraints(options: Values) -> bool: Function
`should_ignore_regular_constraints` utility or script function.
L84: def with_cleanup( Function `with_cleanup` utility or script function.
L91: def configure_tempdir_registry(registry: TempDirectoryTypeRegistry) -> None: Function
`configure_tempdir_registry` utility or script function.
L95: def wrapper(self: _CommandT, options: Values, args: list[str]) -> int: Function
`wrapper` utility or script function.
L112: def parse_constraint_files( Function `parse_constraint_files` utility or script
function.
L137: class RequirementCommand(IndexGroupCommand): Class (`RequirementCommand`) component
used by the app (see file context: None).
L138: def __init__(self, *args: Any, **kw: Any) -> None: Function `__init__` utility or
script function.
L145: def determine_resolver_variant(options: Values) -> str: Function
`determine_resolver_variant` utility or script function.
L153: def make_requirement_preparer( Function `make_requirement_preparer` utility or
```

```

script function.
L234: def make_resolver(    Function `make_resolver`    utility or script function.
L290: def get_requirements(    Function `get_requirements`    Returns or fetches data.
L435: def trace_basic_info(finder: PackageFinder) -> None:    Function `trace_basic_info`
utility or script function.
L445: def _build_package_finder(    Function `_build_package_finder`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/index_command.py

```

L36: def _create_truststore_ssl_context() -> SSLContext | None:    Function
`_create_truststore_ssl_context`    utility or script function.
L54: class SessionCommandMixin(CommandContextMixin):    Class (`SessionCommandMixin`)
component used by the app (see file context: None).
L59: def __init__(self) -> None:    Function `__init__`    utility or script function.
L64: def _get_index_urls(cls, options: Values) -> list[str] | None:    Function
`_get_index_urls`    utility or script function.
L77: def get_default_session(self, options: Values) -> PipSession:    Function
`get_default_session`    Returns or fetches data.
L87: def _build_session(    Function `_build_session`    utility or script function.
L140: def _pip_self_version_check_fetch(    Function `_pip_self_version_check_fetch`    utility
or script function.
L148: def _pip_self_version_check_emit(upgrade_prompt: UpgradePrompt | None) -> None:
Function `_pip_self_version_check_emit`    utility or script function.
L154: class IndexGroupCommand(Command, SessionCommandMixin):    Class (`IndexGroupCommand`)
component used by the app (see file context: None).
L161: def should_exclude_prerelease(    Function `should_exclude_prerelease`    utility or
script function.
L179: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/cmdoptions.py

```

L42: def raise_option_error(parser: OptionParser, option: Option, msg: str) -> None:
Function `raise_option_error`    utility or script function.
L56: def make_option_group(group: dict[str, Any], parser: ConfigOptionParser) -> OptionGroup:
Function `make_option_group`    utility or script function.
L68: def check_dist_restriction(options: Values, check_target: bool = False) -> None:
Function `check_dist_restriction`    utility or script function.
L116: def check_build_constraints(options: Values) -> None:    Function
`check_build_constraints`    utility or script function.
L139: def _path_option_check(option: Option, opt: str, value: str) -> str:    Function
`_path_option_check`    utility or script function.
L143: def _package_name_option_check(option: Option, opt: str, value: str) -> str:    Function
`_package_name_option_check`    utility or script function.
L147: class PipOption(Option):    Class (`PipOption`)    component used by the app (see file

```

```

context: None).
L348: def exists_action() -> Option:    Function `exists_action`  utility or script function.
L403: def extra_index_url() -> Option:    Function `extra_index_url`  utility or script
function.
L426: def find_links() -> Option:    Function `find_links`  utility or script function.
L442: def _handle_uploaded_prior_to(    Function `_handle_uploaded_prior_to`  utility or
script function.
L487: def uploaded_prior_to() -> Option:    Function `uploaded_prior_to`  utility or script
function.
L506: def trusted_host() -> Option:    Function `trusted_host`  utility or script function.
L518: def constraints() -> Option:    Function `constraints`  utility or script function.
L531: def build_constraints() -> Option:    Function `build_constraints`  Constructs or
prepares an object.
L546: def requirements() -> Option:    Function `requirements`  utility or script function.
L563: def requirements_from_scripts() -> Option:    Function `requirements_from_scripts`
utility or script function.
L575: def editable() -> Option:    Function `editable`  utility or script function.
L590: def _handle_src(option: Option, opt_str: str, value: str, parser: OptionParser) ->
None:    Function `_handle_src`  utility or script function.
L613: def _get_format_control(values: Values, option: Option) -> Any:    Function
`_get_format_control`  utility or script function.
L618: def _handle_no_binary(    Function `_handle_no_binary`  utility or script function.
L629: def _handle_only_binary(    Function `_handle_only_binary`  utility or script function.
L640: def no_binary() -> Option:    Function `no_binary`  utility or script function.
L658: def only_binary() -> Option:    Function `only_binary`  utility or script function.
L676: def _get_release_control(values: Values, option: Option) -> Any:    Function
`_get_release_control`  utility or script function.
L681: def _handle_all_releases(    Function `_handle_all_releases`  utility or script
function.
L693: def _handle_only_final(    Function `_handle_only_final`  utility or script function.
L705: def all_releases() -> Option:    Function `all_releases`  utility or script function.
L723: def only_final() -> Option:    Function `only_final`  utility or script function.
L740: def check_release_control_exclusive(options: Values) -> None:    Function
`check_release_control_exclusive`  utility or script function.
L772: def _convert_python_version(value: str) -> tuple[tuple[int, ...], str | None]:
Function `_convert_python_version`  utility or script function.
L801: def _handle_python_version(    Function `_handle_python_version`  utility or script
function.
L870: def add_target_python_options(cmd_opts: OptionGroup) -> None:    Function
`add_target_python_options`  utility or script function.
L877: def make_target_python(options: Values) -> TargetPython:    Function
`make_target_python`  utility or script function.
L888: def prefer_binary() -> Option:    Function `prefer_binary`  utility or script function.
L912: def _handle_no_cache_dir(    Function `_handle_no_cache_dir`  utility or script
function.
L961: def _handle_dependency_group(    Function `_handle_dependency_group`  utility or script
function.
L1040: def _handle_config_settings(    Function `_handle_config_settings`  utility or script
function.
L1118: def _handle_merge_hash(    Function `_handle_merge_hash`  utility or script function.
L1179: def check_list_path_option(options: Values) -> None:    Function

```

```
`check_list_path_option` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/cli/base_command.py

```
L48: class Command(CommandContextMixIn):  Class (`Command`) component used by the app (see
file context: None).
L52: def __init__(self, name: str, summary: str, isolated: bool = False) -> None:  Function
`__init__` utility or script function.
L82: def add_options(self) -> None:  Function `add_options` utility or script function.
L86: def pip_version_check(self, options: Values, args: list[str]) -> Iterator[None]:
Function `pip_version_check` utility or script function.
L96: def run(self, options: Values, args: list[str]) -> int:  Function `run` utility or
script function.
L99: def _run_wrapper(self, level_number: int, options: Values, args: list[str]) -> int:
Function `_run_wrapper` utility or script function.
L100: def _inner_run() -> int:  Function `_inner_run` utility or script function.
L161: def parse_args(self, args: list[str]) -> tuple[Values, list[str]]:  Function
`parse_args` utility or script function.
L165: def main(self, args: list[str]) -> int:  Function `main` Entry point / main routine.
L172: def _main(self, args: list[str]) -> int:  Function `_main` utility or script
function.
L260: def handler_map(self) -> dict[str, Callable[[Values, list[str]], None]]:  Function
`handler_map` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/cli/command_context.py

```
L8: class CommandContextMixIn:  Class (`CommandContextMixIn`) component used by the app
(see file context: None).
L9: def __init__(self) -> None:  Function `__init__` utility or script function.
L15: def main_context(self) -> Generator[None, None, None]:  Function `main_context` Entry
point / main routine.
L25: def enter_context(self, context_provider: AbstractContextManager[_T]) -> _T:  Function
`enter_context` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/cli/spinners.py

```
L30: class SpinnerInterface:  Class (`SpinnerInterface`) component used by the app (see
file context: None).
L31: def spin(self) -> None:  Function `spin` utility or script function.
L34: def finish(self, final_status: str) -> None:  Function `finish` utility or script
function.
L38: class InteractiveSpinner(SpinnerInterface):  Class (`InteractiveSpinner`) component
```

```

used by the app (see file context: None).
L39: def __init__(    Function `__init__`    utility or script function.
L59: def _write(self, status: str) -> None:    Function `_write`    utility or script function.
L71: def spin(self) -> None:    Function `spin`    utility or script function.
L78: def finish(self, final_status: str) -> None:    Function `finish`    utility or script
function.
L91: class NonInteractiveSpinner(SpinnerInterface):    Class (`NonInteractiveSpinner`)
component used by the app (see file context: None).
L92: def __init__(self, message: str, min_update_interval_seconds: float = 60.0) -> None:
Function `__init__`    utility or script function.
L98: def _update(self, status: str) -> None:    Function `_update`    utility or script
function.
L103: def spin(self) -> None:    Function `spin`    utility or script function.
L110: def finish(self, final_status: str) -> None:    Function `finish`    utility or script
function.
L117: class RateLimiter:    Class (`RateLimiter`)    component used by the app (see file
context: None).
L118: def __init__(self, min_update_interval_seconds: float) -> None:    Function `__init__`
utility or script function.
L122: def ready(self) -> bool:    Function `ready`    utility or script function.
L127: def reset(self) -> None:    Function `reset`    utility or script function.
L132: def open_spinner(message: str) -> Generator[SpinnerInterface, None, None]:    Function
`open_spinner`    utility or script function.
L155: class _PipRichSpinner:    Class (`_PipRichSpinner`)    component used by the app (see file
context: None).
L163: def __init__(self, label: str) -> None:    Function `__init__`    utility or script
function.
L170: def __rich_console__(    Function `__rich_console__`    utility or script function.
L175: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L181: def render(self) -> RenderableType:    Function `render`    utility or script function.
L187: def finish(self, status: str) -> None:    Function `finish`    utility or script function.
L194: def open_rich_spinner(label: str, console: Console | None = None) -> Generator[None]:
Function `open_rich_spinner`    utility or script function.
L220: def hidden_cursor(file: IO[str]) -> Generator[None, None, None]:    Function
`hidden_cursor`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/cli/main.py

```

L41: def main(args: list[str] | None = None) -> int:    Function `main`    Entry point / main
routine.

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/base.py

```

L13: class AbstractDistribution(metaclass=abc.ABCMeta):    Class (`AbstractDistribution`)
component used by the app (see file context: None).
L32: def __init__(self, req: InstallRequirement) -> None:    Function `__init__`    utility or

```

```

script function.
L37: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`  Constructs or
prepares an object.
L45: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`  Returns or fetches data.
L49: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`  utility
or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/installed.py

```

L12: class InstalledDistribution(AbstractDistribution):    Class (`InstalledDistribution`)
component used by the app (see file context: None).
L20: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`  Constructs or
prepares an object.
L23: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`  Returns or fetches data.
L27: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`  utility
or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/sdist.py

```

L19: class SourceDistribution(AbstractDistribution):    Class (`SourceDistribution`)
component used by the app (see file context: None).
L27: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`  Constructs or
prepares an object.
L32: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`  Returns or fetches data.
L35: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`  utility
or script function.
L73: def _prepare_build_backend(    Function `_prepare_build_backend`  utility or script
function.
L101: def _get_build_requires_wheel(self) -> Iterable[str]:    Function
`_get_build_requires_wheel`  utility or script function.
L109: def _get_build_requires_editable(self) -> Iterable[str]:    Function
`_get_build_requires_editable`  utility or script function.
L119: def _install_build_reqs(    Function `_install_build_reqs`  utility or script function.
L140: def _raise_conflicts(    Function `_raise_conflicts`  utility or script function.
L157: def _raise_missing_reqs(self, missing: set[str]) -> None:    Function
`_raise_missing_reqs`  utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/__init__.py


```
L7: def make_distribution_for_install_requirement(    Function
`make_distribution_for_install_requirement`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/distributions/wheel.py

```
L18: class WheelDistribution(AbstractDistribution):    Class (`WheelDistribution`)    component
used by the app (see file context: None).
L25: def build_tracker_id(self) -> str | None:    Function `build_tracker_id`    Constructs or
prepares an object.
L28: def get_metadata_distribution(self) -> BaseDistribution:    Function
`get_metadata_distribution`    Returns or fetches data.
L38: def prepare_distribution_metadata(    Function `prepare_distribution_metadata`    utility
or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/versioncontrol.py

```
L45: def is_url(name: str) -> bool:    Function `is_url`    utility or script function.
L55: def make_vcs_requirement_url(    Function `make_vcs_requirement_url`    utility or script
function.
L74: def find_path_to_project_root_from_repo_root(    Function
`find_path_to_project_root_from_repo_root`    utility or script function.
L103: class RemoteNotFoundError(Exception):    Class (`RemoteNotFoundError`)    component used
by the app (see file context: None).
L107: class RemoteNotValidError(Exception):    Class (`RemoteNotValidError`)    component used
by the app (see file context: None).
L108: def __init__(self, url: str):    Function `__init__`    utility or script function.
L114: class RevOptions:    Class (`RevOptions`)    component used by the app (see file context:
None).
L130: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L134: def arg_rev(self) -> str | None:    Function `arg_rev`    utility or script function.
L140: def to_args(self) -> CommandArgs:    Function `to_args`    utility or script function.
L152: def to_display(self) -> str:    Function `to_display`    utility or script function.
L158: def make_new(self, rev: str) -> RevOptions:    Function `make_new`    utility or script
function.
L168: class VcsSupport:    Class (`VcsSupport`)    component used by the app (see file context:
None).
L172: def __init__(self) -> None:    Function `__init__`    utility or script function.
L178: def __iter__(self) -> Iterator[str]:    Function `__iter__`    utility or script function.
L182: def backends(self) -> list[VersionControl]:    Function `backends`    utility or script
function.
L186: def dirnames(self) -> list[str]:    Function `dirnames`    utility or script function.
L190: def all_schemes(self) -> list[str]:    Function `all_schemes`    utility or script
function.
L196: def register(self, cls: type[VersionControl]) -> None:    Function `register`    utility
or script function.
L204: def unregister(self, name: str) -> None:    Function `unregister`    utility or script
```

```

function.
L208: def get_backend_for_dir(self, location: str) -> VersionControl | None:    Function
`get_backend_for_dir` Returns or fetches data.
L231: def get_backend_for_scheme(self, scheme: str) -> VersionControl | None:    Function
`get_backend_for_scheme` Returns or fetches data.
L240: def get_backend(self, name: str) -> VersionControl | None:    Function `get_backend`
Returns or fetches data.
L251: class VersionControl:    Class (`VersionControl`) component used by the app (see file
context: None).
L262: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:    Function
`should_add_vcs_url_prefix` utility or script function.
L270: def get_subdirectory(cls, location: str) -> str | None:    Function `get_subdirectory`
Returns or fetches data.
L278: def get_requirement_revision(cls, repo_dir: str) -> str:    Function
`get_requirement_revision` Returns or fetches data.
L285: def get_src_requirement(cls, repo_dir: str, project_name: str) -> str:    Function
`get_src_requirement` Returns or fetches data.
L309: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns
or fetches data.
L318: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:    Function
`is_immutable_rev_checkout` utility or script function.
L332: def make_rev_options(    Function `make_rev_options` utility or script function.
L345: def _is_local_repository(cls, repo: str) -> bool:    Function `_is_local_repository`
utility or script function.
L354: def get_netloc_and_auth(    Function `get_netloc_and_auth` Returns or fetches data.
L375: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
`get_url_rev_and_auth` Returns or fetches data.
L406: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
Function `make_rev_args` utility or script function.
L412: def get_url_rev_options(self, url: HiddenText) -> tuple[HiddenText, RevOptions]:
Function `get_url_rev_options` Returns or fetches data.
L428: def normalize_url(url: str) -> str:    Function `normalize_url` utility or script
function.
L436: def compare_urls(cls, url1: str, url2: str) -> bool:    Function `compare_urls` utility
or script function.
L442: def fetch_new(    Function `fetch_new` utility or script function.
L456: def switch(    Function `switch` utility or script function.
L471: def update(    Function `update` utility or script function.
L487: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L497: def obtain(self, dest: str, url: HiddenText, verbosity: int) -> None:    Function
`obtain` utility or script function.
L586: def unpack(self, location: str, url: HiddenText, verbosity: int) -> None:    Function
`unpack` utility or script function.
L599: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L609: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L616: def run_command(    Function `run_command` utility or script function.
L674: def is_repository_directory(cls, path: str) -> bool:    Function
`is_repository_directory` utility or script function.

```

```
L682: def get_repository_root(cls, location: str) -> str | None:    Function
`get_repository_root` Returns or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/subversion.py

```
L31: class Subversion(VersionControl):    Class (`Subversion`) component used by the app (see
file context: None).
L38: def should_add_vcs_url_prefix(cls, remote_url: str) -> bool:    Function
`should_add_vcs_url_prefix` utility or script function.
L42: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L46: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L75: def get_netloc_and_auth(    Function `get_netloc_and_auth` Returns or fetches data.
L90: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
`get_url_rev_and_auth` Returns or fetches data.
L98: def make_rev_args(username: str | None, password: HiddenText | None) -> CommandArgs:
Function `make_rev_args` utility or script function.
L108: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L132: def _get_svn_url_rev(cls, location: str) -> tuple[str | None, int]:    Function
`_get_svn_url_rev` utility or script function.
L182: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L186: def __init__(self, use_interactive: bool | None = None) -> None:    Function `__init__`
utility or script function.
L200: def call_vcs_version(self) -> tuple[int, ...]:    Function `call_vcs_version` utility
or script function.
L228: def get_vcs_version(self) -> tuple[int, ...]:    Function `get_vcs_version` Returns or
fetches data.
L248: def get_remote_call_options(self) -> CommandArgs:    Function `get_remote_call_options`
Returns or fetches data.
L279: def fetch_new(    Function `fetch_new` utility or script function.
L303: def switch(    Function `switch` utility or script function.
L319: def update(    Function `update` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/bazaar.py

```
L19: class Bazaar(VersionControl):    Class (`Bazaar`) component used by the app (see file
context: None).
L34: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L37: def fetch_new(    Function `fetch_new` utility or script function.
L58: def switch(    Function `switch` utility or script function.
L67: def update(    Function `update` utility or script function.
L92: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
```

```

`get_url_rev_and_auth` Returns or fetches data.
L100: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L115: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L125: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/mercurial.py

```

L21: class Mercurial(VersionControl):    Class (`Mercurial`) component used by the app (see
file context: None).
L34: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L37: def fetch_new(    Function `fetch_new` utility or script function.
L61: def switch(    Function `switch` utility or script function.
L86: def update(    Function `update` utility or script function.
L103: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L115: def get_revision(cls, location: str) -> str:    Function `get_revision` Returns or
fetches data.
L128: def get_requirement_revision(cls, location: str) -> str:    Function
`get_requirement_revision` Returns or fetches data.
L142: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L147: def get_subdirectory(cls, location: str) -> str | None:    Function `get_subdirectory`
Returns or fetches data.
L161: def get_repository_root(cls, location: str) -> str | None:    Function
`get_repository_root` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_internal/vcs/git.py

```

L58: def looks_like_hash(sha: str) -> bool:    Function `looks_like_hash` utility or script
function.
L62: class Git(VersionControl):    Class (`Git`) component used by the app (see file context:
None).
L79: def get_base_rev_args(rev: str) -> list[str]:    Function `get_base_rev_args` Returns or
fetches data.
L83: def run_command(cls, *args: Any, **kwargs: Any) -> str:    Function `run_command`
utility or script function.
L91: def is_immutable_rev_checkout(self, url: str, dest: str) -> bool:    Function
`is_immutable_rev_checkout` utility or script function.
L105: def get_git_version(self) -> tuple[int, ...]:    Function `get_git_version` Returns or
fetches data.
L119: def get_current_branch(cls, location: str) -> str | None:    Function
`get_current_branch` Returns or fetches data.

```

```

L144: def get_revision_sha(cls, dest: str, rev: str) -> tuple[str | None, bool]:    Function
`get_revision_sha` Returns or fetches data.
L190: def _should_fetch(cls, dest: str, rev: str) -> bool:    Function `_should_fetch`
utility or script function.
L213: def resolve_revision(    Function `resolve_revision` utility or script function.
L259: def is_commit_id_equal(cls, dest: str, name: str | None) -> bool:    Function
`is_commit_id_equal` utility or script function.
L273: def fetch_new(    Function `fetch_new` utility or script function.
L336: def switch(    Function `switch` utility or script function.
L358: def update(    Function `update` utility or script function.
L389: def get_remote_url(cls, location: str) -> str:    Function `get_remote_url` Returns or
fetches data.
L419: def _git_remote_to_pip_url(url: str) -> str:    Function `_git_remote_to_pip_url`
utility or script function.
L450: def has_commit(cls, location: str, rev: str) -> bool:    Function `has_commit` utility
or script function.
L466: def get_revision(cls, location: str, rev: str | None = None) -> str:    Function
`get_revision` Returns or fetches data.
L478: def get_subdirectory(cls, location: str) -> str | None:    Function `get_subdirectory`
Returns or fetches data.
L496: def get_url_rev_and_auth(cls, url: str) -> tuple[str, str | None, AuthInfo]:    Function
`get_url_rev_and_auth` Returns or fetches data.
L527: def update_submodules(cls, location: str, verbosity: int = 0) -> None:    Function
`update_submodules` utility or script function.
L541: def get_repository_root(cls, location: str) -> str | None:    Function
`get_repository_root` Returns or fetches data.
L566: def should_add_vcs_url_prefix(repo_url: str) -> bool:    Function
`should_add_vcs_url_prefix` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/__init__.py

```

L29: def vendored(modulename):    Function `vendored` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/tomli_w/_writer.py

```

L33: class Context:    Class (`Context`) component used by the app (see file context: None).
L34: def __init__(self, allow_multiline: bool, indent: int):    Function `__init__` utility
or script function.
L43: def dump(    Function `dump` utility or script function.
L56: def dumps(    Function `dumps` utility or script function.
L63: def gen_table_chunks(    Function `gen_table_chunks` utility or script function.
L100: def format_literal(obj: object, ctx: Context, *, nest_level: int = 0) -> str:    Object
(singleton).
L126: def format_decimal(obj: Decimal) -> str:    Function `format_decimal` utility or script
function.
L135: def format_inline_table(obj: Mapping, ctx: Context) -> str:    Function

```

```

`format_inline_table` utility or script function.
L156: def format_inline_array(obj: tuple | list, ctx: Context, nest_level: int) -> str:
Function `format_inline_array` utility or script function.
L171: def format_key_part(part: str) -> str: Function `format_key_part` utility or script
function.
L185: def format_string(s: str, *, allow_multiline: bool) -> str: Function `format_string`
utility or script function.
L215: def is_aot(obj: Any) -> bool: Function `is_aot` utility or script function.
L225: def is_suitable_inline_table(obj: Mapping, ctx: Context) -> bool: Function
`is_suitable_inline_table` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_collections.py

```

L15: class HasGettableStringKeys(Protocol): Class (`HasGettableStringKeys`) component used
by the app (see file context: None).
L16: def keys(self) -> typing.Iterator[str]: ... Function `keys` utility or script
function.
L18: def __getitem__(self, key: str) -> str: ... Function `__getitem__` utility or script
function.
L39: class _Sentinel(Enum): Class (`_Sentinel`) component used by the app (see file
context: None).
L43: def ensure_can_construct_http_header_dict( Function
`ensure_can_construct_http_header_dict` utility or script function.
L63: class RecentlyUsedContainer(typing.Generic[_KT, _VT], typing.MutableMapping[_KT, _VT]):
Class (`RecentlyUsedContainer`) component used by the app (see file context: None).
L82: def __init__( Function `__init__` utility or script function.
L93: def __getitem__(self, key: _KT) -> _VT: Function `__getitem__` utility or script
function.
L100: def __setitem__(self, key: _KT, value: _VT) -> None: Function `__setitem__` utility
or script function.
L125: def __delitem__(self, key: _KT) -> None: Function `__delitem__` utility or script
function.
L132: def __len__(self) -> int: Function `__len__` utility or script function.
L136: def __iter__(self) -> typing.NoReturn: Function `__iter__` utility or script
function.
L141: def clear(self) -> None: Function `clear` utility or script function.
L151: def keys(self) -> set[_KT]: # type: ignore[override] Function `keys` utility or
script function.
L156: class HTTPHeaderDictItemView(set[tuple[str, str]]): Class (`HTTPHeaderDictItemView`)
component used by the app (see file context: None).
L187: def __init__(self, headers: HTTPHeaderDict) -> None: Function `__init__` utility or
script function.
L190: def __len__(self) -> int: Function `__len__` utility or script function.
L193: def __iter__(self) -> typing.Iterator[tuple[str, str]]: Function `__iter__` utility
or script function.
L196: def __contains__(self, item: object) -> bool: Object (singleton).
L204: class HTTPHeaderDict(typing.MutableMapping[str, str]): Class (`HTTPHeaderDict`)
component used by the app (see file context: None).

```

```

L240: def __init__(self, headers: ValidHTTPHeaderSource | None = None, **kwargs: str):
Function `__init__` utility or script function.
L251: def __setitem__(self, key: str, val: str) -> None: Function `__setitem__` utility or
script function.
L257: def __getitem__(self, key: str) -> str: Function `__getitem__` utility or script
function.
L263: def __delitem__(self, key: str) -> None: Function `__delitem__` utility or script
function.
L268: def __contains__(self, key: object) -> bool: Object (singleton).
L275: def setdefault(self, key: str, default: str = "") -> str: Function `setdefault` Sets
or updates a value.
L278: def __eq__(self, other: object) -> bool: Object (singleton).
L289: def __ne__(self, other: object) -> bool: Object (singleton).
L292: def __len__(self) -> int: Function `__len__` utility or script function.
L295: def __iter__(self) -> typing.Iterator[str]: Function `__iter__` utility or script
function.
L300: def discard(self, key: str) -> None: Function `discard` utility or script function.
L306: def add(self, key: str, val: str, *, combine: bool = False) -> None: Function `add`
utility or script function.
L341: def extend(self, *args: ValidHTTPHeaderSource, **kwargs: str) -> None: Function
`extend` utility or script function.
L375: def getlist(self, key: str) -> list[str]: ... Function `getlist` Returns or fetches
data.
L378: def getlist(self, key: str, default: _DT) -> list[str] | _DT: ... Function `getlist`
Returns or fetches data.
L380: def getlist( Function `getlist` Returns or fetches data.
L400: def _prepare_for_method_change(self) -> Self: Function `_prepare_for_method_change`
utility or script function.
L426: def __repr__(self) -> str: Function `__repr__` utility or script function.
L429: def _copy_from(self, other: HTTPHeaderDict) -> None: Function `_copy_from` utility
or script function.
L434: def copy(self) -> Self: Function `copy` utility or script function.
L439: def iteritems(self) -> typing.Iterator[tuple[str, str]]: Function `iteritems`
utility or script function.
L446: def itermerged(self) -> typing.Iterator[tuple[str, str]]: Function `itermerged`
utility or script function.
L452: def items(self) -> HTTPHeaderDictItemView: # type: ignore[override] Function `items`
utility or script function.
L455: def _has_value_for_header(self, header_name: str, potential_value: str) -> bool:
Function `_has_value_for_header` utility or script function.
L460: def __ior__(self, other: object) -> HTTPHeaderDict: Object (singleton).
L469: def __or__(self, other: object) -> Self: Object (singleton).
L479: def __ror__(self, other: object) -> Self: Object (singleton).

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/fields.py

```

L15: def guess_content_type( Function `guess_content_type` utility or script function.
L31: def format_header_param_rfc2231(name: str, value: _TYPE_FIELD_VALUE) -> str: Function

```

```

`format_header_param_rfc2231` utility or script function.
L79: def format_multipart_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str:
Function `format_multipart_header_param` utility or script function.
L117: def format_header_param_html5(name: str, value: _TYPE_FIELD_VALUE) -> str: Function
`format_header_param_html5` utility or script function.
L135: def format_header_param(name: str, value: _TYPE_FIELD_VALUE) -> str: Function
`format_header_param` utility or script function.
L153: class RequestField: Class (`RequestField`) component used by the app (see file
context: None).
L171: def __init__( Function `__init__` utility or script function.
L200: def from_tuples( Function `from_tuples` utility or script function.
L244: def _render_part(self, name: str, value: _TYPE_FIELD_VALUE) -> str: Function
`_render_part` utility or script function.
L260: def _render_parts( Function `_render_parts` utility or script function.
L291: def render_headers(self) -> str: Function `render_headers` utility or script
function.
L310: def make_multipart( Function `make_multipart` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connection.py

```

L37: class BaseSSLError(BaseException): # type: ignore[no-redef] Class (`BaseSSLError`)
component used by the app (see file context: None).
L82: class HTTPConnection(HTTPConnection): Class (`HTTPConnection`) component used by the
app (see file context: None).
L132: def __init__( Function `__init__` utility or script function.
L163: def __str__(self) -> str: Function `__str__` utility or script function.
L166: def __repr__(self) -> str: Function `__repr__` utility or script function.
L170: def host(self) -> str: Function `host` utility or script function.
L189: def host(self, value: str) -> None: Function `host` utility or script function.
L198: def _new_conn(self) -> socket.socket: Function `_new_conn` utility or script
function.
L227: def set_tunnel( Function `set_tunnel` Sets or updates a value.
L244: def _wrap_ipv6(self, ip: bytes) -> bytes: Function `_wrap_ipv6` utility or script
function.
L253: def _tunnel(self) -> None: Function `_tunnel` utility or script function.
L296: def _tunnel(self) -> None: # noqa: F811 Function `_tunnel` utility or script
function.
L330: def connect(self) -> None: Function `connect` utility or script function.
L348: def is_closed(self) -> bool: Function `is_closed` utility or script function.
L352: def is_connected(self) -> bool: Function `is_connected` utility or script function.
L358: def has_connected_to_proxy(self) -> bool: Function `has_connected_to_proxy` utility
or script function.
L362: def proxy_is_forwarding(self) -> bool: Function `proxy_is_forwarding` utility or
script function.
L369: def proxy_is_tunneling(self) -> bool: Function `proxy_is_tunneling` utility or
script function.
L375: def close(self) -> None: Function `close` utility or script function.
L390: def putrequest( Function `putrequest` utility or script function.

```



```

L410: def putheader(self, header: str, *values: str) -> None: # type: ignore[override]
Function `putheader` utility or script function.
L424: def request( # type: ignore[override] Function `request` utility or script
function.
L521: def request_chunked( Function `request_chunked` utility or script function.
L540: def getresponse( # type: ignore[override] Function `getresponse` Returns or fetches
data.
L603: class HTTPSConnection(HTTPConnection): Class (`HTTPSConnection`) component used by
the app (see file context: None).
L621: def __init__( Function `__init__` utility or script function.
L683: def set_cert( Function `set_cert` Sets or updates a value.
L724: def connect(self) -> None: Function `connect` utility or script function.
L861: def _connect_tls_proxy(self, hostname: str, sock: socket.socket) -> ssl.SSLSocket:
Function `_connect_tls_proxy` utility or script function.
L891: class _WrappedAndVerifiedSocket(typing.NamedTuple): Class
(`_WrappedAndVerifiedSocket`) component used by the app (see file context: None).
L901: def _ssl_wrap_socket_and_match_hostname( Function
`_ssl_wrap_socket_and_match_hostname` utility or script function.
L1026: def _match_hostname( Function `_match_hostname` utility or script function.
L1052: def _wrap_proxy_error(err: Exception, proxy_scheme: str | None) -> ProxyError:
Function `_wrap_proxy_error` utility or script function.
L1077: def _get_default_user_agent() -> str: Function `_get_default_user_agent` utility or
script function.
L1081: class DummyConnection: Class (`DummyConnection`) component used by the app (see
file context: None).
L1092: def _url_from_connection( Function `_url_from_connection` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/response.py

```

L48: class ContentDecoder: Class (`ContentDecoder`) component used by the app (see file
context: None).
L49: def decompress(self, data: bytes, max_length: int = -1) -> bytes: Function
`decompress` utility or script function.
L53: def has_unconsumed_tail(self) -> bool: Function `has_unconsumed_tail` utility or
script function.
L56: def flush(self) -> bytes: Function `flush` utility or script function.
L60: class DeflateDecoder(ContentDecoder): Class (`DeflateDecoder`) component used by the
app (see file context: None).
L61: def __init__(self) -> None: Function `__init__` utility or script function.
L67: def decompress(self, data: bytes, max_length: int = -1) -> bytes: Function
`decompress` utility or script function.
L110: def has_unconsumed_tail(self) -> bool: Function `has_unconsumed_tail` utility or
script function.
L115: def flush(self) -> bytes: Function `flush` utility or script function.
L119: class GzipDecoderState: Class (`GzipDecoderState`) component used by the app (see
file context: None).
L125: class GzipDecoder(ContentDecoder): Class (`GzipDecoder`) component used by the app

```

```

(see file context: None).
L126: def __init__(self) -> None:    Function `__init__`    utility or script function.
L131: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L182: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L185: def flush(self) -> bytes:    Function `flush`    utility or script function.
L191: class BrotliDecoder(ContentDecoder):    Class (`BrotliDecoder`)    component used by the
app (see file context: None).
L195: def __init__(self) -> None:    Function `__init__`    utility or script function.
L203: def _decompress(self, data: bytes, output_buffer_limit: int = -1) -> bytes:    Function
`_decompress`    utility or script function.
L206: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L222: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L228: def flush(self) -> bytes:    Function `flush`    utility or script function.
L244: class ZstdDecoder(ContentDecoder):    Class (`ZstdDecoder`)    component used by the app
(see file context: None).
L245: def __init__(self) -> None:    Function `__init__`    utility or script function.
L248: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L283: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L288: def flush(self) -> bytes:    Function `flush`    utility or script function.
L294: class MultiDecoder(ContentDecoder):    Class (`MultiDecoder`)    component used by the app
(see file context: None).
L307: def __init__(self, modes: str) -> None:    Function `__init__`    utility or script
function.
L316: def flush(self) -> bytes:    Function `flush`    utility or script function.
L319: def decompress(self, data: bytes, max_length: int = -1) -> bytes:    Function
`decompress`    utility or script function.
L346: def has_unconsumed_tail(self) -> bool:    Function `has_unconsumed_tail`    utility or
script function.
L350: def _get_decoder(mode: str) -> ContentDecoder:    Function `_get_decoder`    utility or
script function.
L368: class BytesQueueBuffer:    Class (`BytesQueueBuffer`)    component used by the app (see
file context: None).
L382: def __init__(self) -> None:    Function `__init__`    utility or script function.
L386: def __len__(self) -> int:    Function `__len__`    utility or script function.
L389: def put(self, data: bytes) -> None:    Function `put`    utility or script function.
L393: def get(self, n: int) -> bytes:    Function `get`    Returns or fetches data.
L428: def get_all(self) -> bytes:    Function `get_all`    Returns or fetches data.
L445: class BaseHTTPResponse(io.IOBase):    Class (`BaseHTTPResponse`)    component used by the
app (see file context: None).
L460: def __init__(self) -> None:    Function `__init__`    utility or script function.
L495: def get_redirect_location(self) -> str | None | typing.Literal[False]:    Function
`get_redirect_location`    Returns or fetches data.
L508: def data(self) -> bytes:    Function `data`    utility or script function.
L511: def json(self) -> typing.Any:    Function `json`    utility or script function.
L533: def url(self) -> str | None:    Function `url`    utility or script function.

```

```

L537: def url(self, url: str | None) -> None:    Function `url` utility or script function.
L541: def connection(self) -> BaseHTTPConnection | None:    Function `connection` utility or
script function.
L545: def retries(self) -> Retry | None:    Function `retries` utility or script function.
L549: def retries(self, retries: Retry | None) -> None:    Function `retries` utility or
script function.
L555: def stream(    Function `stream` utility or script function.
L560: def read(    Function `read` utility or script function.
L568: def read1(    Function `read1` utility or script function.
L575: def read_chunked(    Function `read_chunked` utility or script function.
L582: def release_conn(self) -> None:    Function `release_conn` utility or script function.
L585: def drain_conn(self) -> None:    Function `drain_conn` utility or script function.
L588: def shutdown(self) -> None:    Function `shutdown` utility or script function.
L591: def close(self) -> None:    Function `close` utility or script function.
L594: def _init_decoder(self) -> None:    Function `_init_decoder` utility or script
function.
L613: def _decode(    Function `_decode` utility or script function.
L650: def _flush_decoder(self) -> bytes:    Function `_flush_decoder` utility or script
function.
L660: def readinto(self, b: bytearray) -> int:    Function `readinto` utility or script
function.
L669: def getheaders(self) -> HTTPHeaderDict:    Function `getheaders` Returns or fetches
data.
L672: def getheader(self, name: str, default: str | None = None) -> str | None:    Function
`getheader` Returns or fetches data.
L676: def info(self) -> HTTPHeaderDict:    Function `info` utility or script function.
L679: def geturl(self) -> str | None:    Function `geturl` Returns or fetches data.
L683: class HTTPResponse(BaseHTTPResponse):    Class (`HTTPResponse`) component used by the
app (see file context: None).
L689: class is also compatible with the Python standard library's :mod:`io`    Class (`is`)
component used by the app (see file context: None).
L716: def __init__(    Function `__init__` utility or script function.
L780: def release_conn(self) -> None:    Function `release_conn` utility or script function.
L787: def drain_conn(self) -> None:    Function `drain_conn` utility or script function.
L803: def data(self) -> bytes:    Function `data` utility or script function.
L814: def connection(self) -> HTTPConnection | None:    Function `connection` utility or
script function.
L817: def isclosed(self) -> bool:    Function `isclosed` utility or script function.
L820: def tell(self) -> int:    Function `tell` utility or script function.
L828: def _init_length(self, request_method: str | None) -> int | None:    Function
`_init_length` utility or script function.
L885: def _error_catcher(self) -> typing.Generator[None]:    Function `_error_catcher`
utility or script function.
L950: def _fp_read(    Function `_fp_read` utility or script function.
L1007: def _raw_read(    Function `_raw_read` utility or script function.
L1059: def read(    Function `read` utility or script function.
L1155: def read1(    Function `read1` utility or script function.
L1225: def stream(    Function `stream` utility or script function.
L1257: def readable(self) -> bool:    Function `readable` utility or script function.
L1260: def shutdown(self) -> None:    Function `shutdown` utility or script function.
L1269: def close(self) -> None:    Function `close` utility or script function.

```

```

L1282: def closed(self) -> bool:    Function `closed` utility or script function.
L1294: def fileno(self) -> int:     Function `fileno` utility or script function.
L1305: def flush(self) -> None:     Function `flush` utility or script function.
L1313: def supports_chunked_reads(self) -> bool:    Function `supports_chunked_reads` utility
or script function.
L1322: def _update_chunk_length(self) -> None:     Function `_update_chunk_length` utility or
script function.
L1340: def _handle_chunk(self, amt: int | None) -> bytes:    Function `_handle_chunk` utility
or script function.
L1362: def read_chunked(    Function `read_chunked` utility or script function.
L1447: def url(self) -> str | None:    Function `url` utility or script function.
L1456: def url(self, url: str | None) -> None:    Function `url` utility or script function.
L1459: def __iter__(self) -> typing.Iterator[bytes]:    Function `__iter__` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/exceptions.py

```

L18: class HTTPError(Exception):    Class (`HTTPError`) component used by the app (see file
context: None).
L22: class HTTPWarning(Warning):    Class (`HTTPWarning`) component used by the app (see file
context: None).
L29: class PoolError(HTTPError):    Class (`PoolError`) component used by the app (see file
context: None).
L32: def __init__(self, pool: ConnectionPool, message: str) -> None:    Function `__init__`
utility or script function.
L37: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__` utility or script
function.
L42: class RequestError(PoolError):    Class (`RequestError`) component used by the app (see
file context: None).
L45: def __init__(self, pool: ConnectionPool, url: str | None, message: str) -> None:
Function `__init__` utility or script function.
L49: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__` utility or script
function.
L54: class SSLError(HTTPError):    Class (`SSLError`) component used by the app (see file
context: None).
L58: class ProxyError(HTTPError):    Class (`ProxyError`) component used by the app (see file
context: None).
L64: def __init__(self, message: str, error: Exception) -> None:    Function `__init__`
utility or script function.
L69: class DecodeError(HTTPError):    Class (`DecodeError`) component used by the app (see
file context: None).
L73: class ProtocolError(HTTPError):    Class (`ProtocolError`) component used by the app
(see file context: None).
L84: class MaxRetryError(RequestError):    Class (`MaxRetryError`) component used by the app
(see file context: None).
L95: def __init__(    Function `__init__` utility or script function.
L104: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__` utility or script
function.

```

```

L109: class HostChangedError(RequestError):    Class (`HostChangedError`)    component used by
the app (see file context: None).
L112: def __init__(    Function `__init__`    utility or script function.
L120: class TimeoutStateError(HTTPErrors):    Class (`TimeoutStateError`)    component used by
the app (see file context: None).
L124: class TimeoutError(HTTPErrors):    Class (`TimeoutError`)    component used by the app (see
file context: None).
L132: class ReadTimeoutError(TimeoutError, RequestError):    Class (`ReadTimeoutError`)
component used by the app (see file context: None).
L138: class ConnectTimeoutError(TimeoutError):    Class (`ConnectTimeoutError`)    component
used by the app (see file context: None).
L142: class NewConnectionError(ConnectTimeoutError, HTTPErrors):    Class
(`NewConnectionError`)    component used by the app (see file context: None).
L145: def __init__(self, conn: HTTPConnection, message: str) -> None:    Function `__init__`
utility or script function.
L150: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L155: def pool(self) -> HTTPConnection:    Function `pool`    utility or script function.
L166: class NameResolutionError(NewConnectionError):    Class (`NameResolutionError`)
component used by the app (see file context: None).
L169: def __init__(self, host: str, conn: HTTPConnection, reason: socket.gaierror):
Function `__init__`    utility or script function.
L175: def __reduce__(self) -> _TYPE_REDUCE_RESULT:    Function `__reduce__`    utility or script
function.
L180: class EmptyPoolError(PoolError):    Class (`EmptyPoolError`)    component used by the app
(see file context: None).
L184: class FullPoolError(PoolError):    Class (`FullPoolError`)    component used by the app
(see file context: None).
L188: class ClosedPoolError(PoolError):    Class (`ClosedPoolError`)    component used by the
app (see file context: None).
L192: class LocationValueError(ValueError, HTTPErrors):    Class (`LocationValueError`)
component used by the app (see file context: None).
L196: class LocationParseError(LocationValueError):    Class (`LocationParseError`)    component
used by the app (see file context: None).
L199: def __init__(self, location: str) -> None:    Function `__init__`    utility or script
function.
L206: class URLSchemeUnknown(LocationValueError):    Class (`URLSchemeUnknown`)    component
used by the app (see file context: None).
L209: def __init__(self, scheme: str):    Function `__init__`    utility or script function.
L216: class ResponseError(HTTPErrors):    Class (`ResponseError`)    component used by the app
(see file context: None).
L223: class SecurityWarning(HTTPWarning):    Class (`SecurityWarning`)    component used by the
app (see file context: None).
L227: class InsecureRequestWarning(SecurityWarning):    Class (`InsecureRequestWarning`)
component used by the app (see file context: None).
L231: class NotOpenSSLWarning(SecurityWarning):    Class (`NotOpenSSLWarning`)    component used
by the app (see file context: None).
L235: class SystemTimeWarning(SecurityWarning):    Class (`SystemTimeWarning`)    component used
by the app (see file context: None).
L239: class InsecurePlatformWarning(SecurityWarning):    Class (`InsecurePlatformWarning`)
component used by the app (see file context: None).

```

```

L243: class DependencyWarning(HTTPWarning):    Class (`DependencyWarning`) component used by
the app (see file context: None).
L250: class ResponseNotChunked(ProtocolError, ValueError):    Class (`ResponseNotChunked`)
component used by the app (see file context: None).
L254: class BodyNotHttpLibCompatible(HTTPError):    Class (`BodyNotHttpLibCompatible`)
component used by the app (see file context: None).
L261: class IncompleteRead(HTTPError, httpLib_IncompleteRead):    Class (`IncompleteRead`)
component used by the app (see file context: None).
L272: def __init__(self, partial: int, expected: int) -> None:    Function `__init__` utility
or script function.
L276: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L283: class InvalidChunkLength(HTTPError, httpLib_IncompleteRead):    Class
(`InvalidChunkLength`) component used by the app (see file context: None).
L286: def __init__(self, response: HTTPResponse, length: bytes) -> None:    Function
`__init__` utility or script function.
L292: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L299: class InvalidHeader(HTTPError):    Class (`InvalidHeader`) component used by the app
(see file context: None).
L303: class ProxySchemeUnknown(AssertionError, URLSchemeUnknown):    Class
(`ProxySchemeUnknown`) component used by the app (see file context: None).
L308: def __init__(self, scheme: str | None) -> None:    Function `__init__` utility or
script function.
L320: class ProxySchemeUnsupported(ValueError):    Class (`ProxySchemeUnsupported`) component
used by the app (see file context: None).
L324: class HeaderParsingError(HTTPError):    Class (`HeaderParsingError`) component used by
the app (see file context: None).
L327: def __init__(    Function `__init__` utility or script function.
L334: class UnrewindableBodyError(HTTPError):    Class (`UnrewindableBodyError`) component
used by the app (see file context: None).

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_request_metho ds.py

```

L20: class RequestMethods:    Class (`RequestMethods`) component used by the app (see file
context: None).
L51: def __init__(self, headers: typing.Mapping[str, str] | None = None) -> None:    Function
`__init__` utility or script function.
L54: def urlopen(    Function `urlopen` utility or script function.
L69: def request(    Function `request` utility or script function.
L147: def request_encode_url(    Function `request_encode_url` utility or script function.
L184: def request_encode_body(    Function `request_encode_body` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/__init__.py

```

L74: def add_stderr_logger(    Function `add_stderr_logger` utility or script function.
L107: def disable_warnings(category: type[Warning] = exceptions.HTTPWarning) -> None:

```

Function `disable\_warnings` utility or script function.
 L117: def request(Function `request` utility or script function.

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/poolmanager.py

L56: class PoolKey(typing.NamedTuple): Class (`PoolKey`) component used by the app (see file context: None).
 L95: def _default_key_normalizer(Function `\_default\_key\_normalizer` utility or script function.
 L162: class PoolManager(RequestMethods): Manager (`PoolManager`) orchestration/utility for managing resources or behaviors.
 L199: def __init__(Function `\_init\_\_` utility or script function.
 L230: def __enter__(self) -> Self: Function `\_enter\_\_` utility or script function.
 L233: def __exit__(Function `\_exit\_\_` utility or script function.
 L243: def _new_pool(Function `\_new\_pool` utility or script function.
 L281: def clear(self) -> None: Function `clear` utility or script function.
 L290: def connection_from_host(Function `connection\_from\_host` utility or script function.
 L319: def connection_from_context(Function `connection\_from\_context` utility or script function.
 L344: def connection_from_pool_key(Function `connection\_from\_pool\_key` utility or script function.
 L370: def connection_from_url(Function `connection\_from\_url` utility or script function.
 L388: def _merge_pool_kwargs(Function `\_merge\_pool\_kwargs` utility or script function.
 L410: def _proxy_requires_url_absolute_form(self, parsed_url: Url) -> bool: Function `\_proxy\_requires\_url\_absolute\_form` utility or script function.
 L423: def urlopen(# type: ignore[override] Function `urlopen` utility or script function.
 L506: class ProxyManager(PoolManager): Manager (`ProxyManager`) orchestration/utility for managing resources or behaviors.
 L561: def __init__(Function `\_init\_\_` utility or script function.
 L602: def connection_from_host(Function `connection\_from\_host` utility or script function.
 L618: def _set_proxy_headers(Function `\_set\_proxy\_headers` utility or script function.
 L635: def urlopen(# type: ignore[override] Function `urlopen` utility or script function.
 L650: def proxy_from_url(url: str, **kw: typing.Any) -> ProxyManager: Function `proxy\_from\_url` utility or script function.

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/filepost.py

L22: def choose_boundary() -> str: Function `choose\_boundary` utility or script function.
 L29: def iter_field_objects(fields: _TYPE_FIELDS) -> typing.Iterable[RequestField]:
 Function `iter\_field\_objects` utility or script function.
 L51: def encode_multipart_formdata(Function `encode\_multipart\_formdata` utility or script function.

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/_base_connection.py

```

L12: class ProxyConfig(typing.NamedTuple):    Class (`ProxyConfig`) component used by the app
(see file context: None).
L19: class _ResponseOptions(typing.NamedTuple):    Class (`_ResponseOptions`) component used
by the app (see file context: None).
L35: class BaseHTTPConnection(Protocol):    Class (`BaseHTTPConnection`) component used by
the app (see file context: None).
L54: def __init__(    Function `__init__` utility or script function.
L67: def set_tunnel(    Function `set_tunnel` Sets or updates a value.
L75: def connect(self) -> None: ...    Function `connect` utility or script function.
L77: def request(    Function `request` utility or script function.
L93: def getresponse(self) -> BaseHTTPResponse: ...    Function `getresponse` Returns or
fetches data.
L95: def close(self) -> None: ...    Function `close` utility or script function.
L98: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L105: def is_connected(self) -> bool:    Function `is_connected` utility or script function.
L109: def has_connected_to_proxy(self) -> bool:    Function `has_connected_to_proxy` utility
or script function.
L115: class BaseHTTPSPConnection(BaseHTTPConnection, Protocol):    Class
(`BaseHTTPSPConnection`) component used by the app (see file context: None).
L140: def __init__(    Function `__init__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/connectionpool.py

```

L67: class ConnectionPool:    Class (`ConnectionPool`) component used by the app (see file
context: None).
L81: def __init__(self, host: str, port: int | None = None) -> None:    Function `__init__`
utility or script function.
L94: def __str__(self) -> str:    Function `__str__` utility or script function.
L97: def __enter__(self) -> Self:    Function `__enter__` utility or script function.
L100: def __exit__(    Function `__exit__` utility or script function.
L110: def close(self) -> None:    Function `close` utility or script function.
L120: class HTTPConnectionPool(ConnectionPool, RequestMethods):    Class
(`HTTPConnectionPool`) component used by the app (see file context: None).
L175: def __init__(    Function `__init__` utility or script function.
L236: def _new_conn(self) -> BaseHTTPConnection:    Function `_new_conn` utility or script
function.
L256: def _get_conn(self, timeout: float | None = None) -> BaseHTTPConnection:    Function
`_get_conn` utility or script function.
L294: def _put_conn(self, conn: BaseHTTPConnection | None) -> None:    Function `_put_conn`
utility or script function.
L337: def _validate_conn(self, conn: BaseHTTPConnection) -> None:    Function `_validate_conn`
utility or script function.

```



```

L342: def _prepare_proxy(self, conn: BaseHTTPConnection) -> None:    Function `_prepare_proxy`
        utility or script function.
L346: def _get_timeout(self, timeout: _TYPE_TIMEOUT) -> Timeout:    Function `_get_timeout`
        utility or script function.
L358: def _raise_timeout(    Function `_raise_timeout`    utility or script function.
L377: def _make_request(    Function `_make_request`    utility or script function.
L558: def close(self) -> None:    Function `close`    utility or script function.
L570: def is_same_host(self, url: str) -> bool:    Function `is_same_host`    utility or script
        function.
L592: def urlopen( # type: ignore[override]    Function `urlopen`    utility or script
        function.
L963: class HTTPSConnectionPool(HTTPConnectionPool):    Class (`HTTPSConnectionPool`)
        component used by the app (see file context: None).
L980: def __init__(    Function `__init__`    utility or script function.
L1029: def _prepare_proxy(self, conn: HTTPConnection) -> None: # type: ignore[override]
        Function `_prepare_proxy`    utility or script function.
L1044: def _new_conn(self) -> BaseHTTPConnection:    Function `_new_conn`    utility or script
        function.
L1085: def _validate_conn(self, conn: BaseHTTPConnection) -> None:    Function
        `_validate_conn`    utility or script function.
L1108: def connection_from_url(url: str, **kw: typing.Any) -> HTTPConnectionPool:    Function
        `connection_from_url`    utility or script function.
L1138: def _normalize_host(host: None, scheme: str | None) -> None: ...    Function
        `_normalize_host`    utility or script function.
L1142: def _normalize_host(host: str, scheme: str | None) -> str: ...    Function
        `_normalize_host`    utility or script function.
L1145: def _normalize_host(host: str | None, scheme: str | None) -> str | None:    Function
        `_normalize_host`    utility or script function.
L1163: def _url_from_pool(    Function `_url_from_pool`    utility or script function.
L1170: def _close_pool_connections(pool: queue.LifoQueue[typing.Any]) -> None:    Function
        `_close_pool_connections`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/timeout.py

```

L14: class _TYPE_DEFAULT(Enum):    Class (`_TYPE_DEFAULT`)    component used by the app (see
        file context: None).
L25: class Timeout:    Class (`Timeout`)    component used by the app (see file context: None).
L109: def __init__(    Function `__init__`    utility or script function.
L120: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L127: def resolve_default_timeout(timeout: _TYPE_TIMEOUT) -> float | None:    Function
        `resolve_default_timeout`    utility or script function.
L131: def _validate_timeout(cls, value: _TYPE_TIMEOUT, name: str) -> _TYPE_TIMEOUT:
        Function `_validate_timeout`    utility or script function.
L173: def from_float(cls, timeout: _TYPE_TIMEOUT) -> Timeout:    Function `from_float`
        utility or script function.
L188: def clone(self) -> Timeout:    Function `clone`    utility or script function.
L202: def start_connect(self) -> float:    Function `start_connect`    utility or script
        function.

```

```

L213: def get_connect_duration(self) -> float:    Function `get_connect_duration` Returns or
fetches data.
L228: def connect_timeout(self) -> _TYPE_TIMEOUT:    Function `connect_timeout` utility or
script function.
L246: def read_timeout(self) -> float | None:    Function `read_timeout` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/retry.py

```

L33: class RequestHistory(typing.NamedTuple):    Class (`RequestHistory`) component used by
the app (see file context: None).
L41: class Retry:    Class (`Retry`) component used by the app (see file context: None).
L211: def __init__(    Function `__init__` utility or script function.
L258: def new(self, **kw: typing.Any) -> Self:    Function `new` utility or script function.
L283: def from_int(    Function `from_int` utility or script function.
L301: def get_backoff_time(self) -> float:    Function `get_backoff_time` Returns or fetches
data.
L320: def parse_retry_after(self, retry_after: str) -> float:    Function `parse_retry_after`
utility or script function.
L341: def get_retry_after(self, response: BaseHTTPResponse) -> float | None:    Function
`get_retry_after` Returns or fetches data.
L351: def sleep_for_retry(self, response: BaseHTTPResponse) -> bool:    Function
`sleep_for_retry` utility or script function.
L359: def _sleep_backoff(self) -> None:    Function `_sleep_backoff` utility or script
function.
L365: def sleep(self, response: BaseHTTPResponse | None = None) -> None:    Function `sleep`
utility or script function.
L381: def _is_connection_error(self, err: Exception) -> bool:    Function
`_is_connection_error` utility or script function.
L389: def _is_read_error(self, err: Exception) -> bool:    Function `_is_read_error` utility
or script function.
L395: def _is_method_retryable(self, method: str) -> bool:    Function `_is_method_retryable`
utility or script function.
L403: def is_retry(    Function `is_retry` utility or script function.
L425: def is_exhausted(self) -> bool:    Function `is_exhausted` utility or script function.
L444: def increment(    Function `increment` utility or script function.
L541: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/wait.py

```

L33: def select_wait_for_socket(    Function `select_wait_for_socket` utility or script
function.
L57: def poll_wait_for_socket(    Function `poll_wait_for_socket` utility or script function.
L74: def do_poll(t: float | None) -> list[tuple[int, int]]:    Function `do_poll` utility or
script function.
L82: def _have_working_poll() -> bool:    Function `_have_working_poll` utility or script

```

```

function.
L95: def wait_for_socket(    Function `wait_for_socket`    utility or script function.
L113: def wait_for_read(sock: socket.socket, timeout: float | None = None) -> bool:
Function `wait_for_read`    utility or script function.
L120: def wait_for_write(sock: socket.socket, timeout: float | None = None) -> bool:
Function `wait_for_write`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/connection.py

```

L15: def is_connection_dropped(conn: BaseHTTPConnection) -> bool:    # Platform-specific
Function `is_connection_dropped`    utility or script function.
L27: def create_connection(    Function `create_connection`    Creates a resource or document.
L93: def _set_socket_options(    Function `_set_socket_options`    utility or script function.
L103: def allowed_gai_family() -> socket.AddressFamily:    Function `allowed_gai_family`
utility or script function.
L114: def _has_ipv6(host: str) -> bool:    Function `_has_ipv6`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/url.py

```

L80: class Url(    Class (`Url`)    component used by the app (see file context: None).
L100: def __new__(    # type: ignore[no-untyped-def]    Function `__new__`    utility or script
function.
L117: def hostname(self) -> str | None:    Function `hostname`    utility or script function.
L122: def request_uri(self) -> str:    Function `request_uri`    utility or script function.
L132: def authority(self) -> str | None:    Function `authority`    utility or script function.
L148: def netloc(self) -> str | None:    Function `netloc`    utility or script function.
L162: def url(self) -> str:    Function `url`    utility or script function.
L209: def __str__(self) -> str:    Function `__str__`    utility or script function.
L214: def _encode_invalid_chars(    Function `_encode_invalid_chars`    utility or script
function.
L221: def _encode_invalid_chars(    Function `_encode_invalid_chars`    utility or script
function.
L227: def _encode_invalid_chars(    Function `_encode_invalid_chars`    utility or script
function.
L263: def _remove_path_dot_segments(path: str) -> str:    Function `_remove_path_dot_segments`
utility or script function.
L294: def _normalize_host(host: None, scheme: str | None) -> None: ...    Function
`_normalize_host`    utility or script function.
L298: def _normalize_host(host: str, scheme: str | None) -> str: ...    Function
`_normalize_host`    utility or script function.
L301: def _normalize_host(host: str | None, scheme: str | None) -> str | None:    Function
`_normalize_host`    utility or script function.
L330: def _idna_encode(name: str) -> bytes:    Function `_idna_encode`    utility or script
function.
L349: def _encode_target(target: str) -> str:    Function `_encode_target`    utility or script

```

```
function.
L367: def parse_url(url: str) -> Url:    Function `parse_url`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/response.py

```
L9: def is_fp_closed(obj: object) -> bool:    Object (singleton).
L40: def assert_header_parsing(headers: httplib.HTTPMessage) -> None:    Function
`assert_header_parsing`    utility or script function.
L91: def is_response_to_head(response: httplib.HTTPResponse) -> bool:    Function
`is_response_to_head`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssltransport.py

```
L22: class SSLTransport:    Class (`SSLTransport`)    component used by the app (see file
context: None).
L34: def _validate_ssl_context_for_tls_in_tls(ssl_context: ssl.SSLContext) -> None:
Function `_validate_ssl_context_for_tls_in_tls`    utility or script function.
L49: def __init__(    Function `_init__`    utility or script function.
L72: def __enter__(self) -> Self:    Function `_enter__`    utility or script function.
L75: def __exit__(self, *_: typing.Any) -> None:    Function `_exit__`    utility or script
function.
L78: def fileno(self) -> int:    Function `_fileno`    utility or script function.
L81: def read(self, len: int = 1024, buffer: typing.Any | None = None) -> int | bytes:
Function `_read`    utility or script function.
L84: def recv(self, buflen: int = 1024, flags: int = 0) -> int | bytes:    Function `_recv`
utility or script function.
L89: def recv_into(    Function `_recv_into`    utility or script function.
L101: def sendall(self, data: bytes, flags: int = 0) -> None:    Function `_sendall`    utility
or script function.
L111: def send(self, data: bytes, flags: int = 0) -> int:    Function `_send`    utility or
script function.
L116: def makefile(    Function `_makefile`    utility or script function.
L168: def unwrap(self) -> None:    Function `_unwrap`    utility or script function.
L171: def close(self) -> None:    Function `_close`    utility or script function.
L175: def getpeercert(    Function `_getpeercert`    Returns or fetches data.
L180: def getpeercert(self, binary_form: typing.Literal[True]) -> bytes | None: ...
Function `_getpeercert`    Returns or fetches data.
L182: def getpeercert(self, binary_form: bool = False) -> _TYPE_PEER_CERT_RET:    Function
`getpeercert`    Returns or fetches data.
L185: def version(self) -> str | None:    Function `_version`    utility or script function.
L188: def cipher(self) -> tuple[str, str, int] | None:    Function `_cipher`    utility or script
function.
L191: def selected_alpn_protocol(self) -> str | None:    Function `_selected_alpn_protocol`
utility or script function.
L194: def shared_ciphers(self) -> list[tuple[str, str, int]] | None:    Function
```

```

`shared_ciphers` utility or script function.
L197: def compression(self) -> str | None: Function `compression` utility or script
function.
L200: def settimeout(self, value: float | None) -> None: Function `settimeout` Sets or
updates a value.
L203: def gettimeout(self) -> float | None: Function `gettimeout` Returns or fetches data.
L206: def _decref_socketios(self) -> None: Function `_decref_socketios` utility or script
function.
L209: def _wrap_ssl_read(self, len: int, buffer: bytearray | None = None) -> int | bytes:
Function `_wrap_ssl_read` utility or script function.
L220: def _ssl_io_loop(self, func: typing.Callable[[], None]) -> None: ... Function
`_ssl_io_loop` utility or script function.
L224: def _ssl_io_loop(self, func: typing.Callable[[bytes], int], arg1: bytes) -> int: ...
Function `_ssl_io_loop` utility or script function.
L228: def _ssl_io_loop( Function `_ssl_io_loop` utility or script function.
L235: def _ssl_io_loop( Function `_ssl_io_loop` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl_match_hostname.py

```

L20: class CertificateError(ValueError): Class (`CertificateError`) component used by the
app (see file context: None).
L24: def _dnsname_match( Function `_dnsname_match` utility or script function.
L80: def _ipaddress_match(ipname: str, host_ip: IPv4Address | IPv6Address) -> bool:
Function `_ipaddress_match` utility or script function.
L95: def match_hostname( Function `match_hostname` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/proxy.py

```

L11: def connection_requires_http_tunnel( Function `connection_requires_http_tunnel`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/ssl_.py

```

L30: def _is_bpo_43522_fixed( Function `_is_bpo_43522_fixed` utility or script function.
L56: def _is_has_never_check_common_name_reliable( Function
`_is_has_never_check_common_name_reliable` utility or script function.
L84: class _TYPE_PEER_CERT_RET_DICT(TypedDict, total=False): Class
(`_TYPE_PEER_CERT_RET_DICT`) component used by the app (see file context: None).
L152: def assert_fingerprint(cert: bytes | None, fingerprint: str) -> None: Function
`assert_fingerprint` utility or script function.
L186: def resolve_cert_reqs(candidate: None | int | str) -> VerifyMode: Function
`resolve_cert_reqs` utility or script function.

```

```

L209: def resolve_ssl_version(candidate: None | int | str) -> int:    Function
`resolve_ssl_version` utility or script function.
L225: def create_urllib3_context(    Function `create_urllib3_context` Creates a resource or
document.
L378: def ssl_wrap_socket(    Function `ssl_wrap_socket` utility or script function.
L396: def ssl_wrap_socket(    Function `ssl_wrap_socket` utility or script function.
L413: def ssl_wrap_socket(    Function `ssl_wrap_socket` utility or script function.
L487: def is_ipaddress(hostname: str | bytes) -> bool:    Function `is_ipaddress` utility or
script function.
L500: def _is_key_file_encrypted(key_file: str) -> bool:    Function `_is_key_file_encrypted`
utility or script function.
L511: def _ssl_wrap_socket_impl(    Function `_ssl_wrap_socket_impl` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/util.py

```

L7: def to_bytes(    Function `to_bytes` utility or script function.
L19: def to_str(    Function `to_str` utility or script function.
L31: def reraise(    Function `reraise` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/util/request.py

```

L35: class _TYPE_FAILEDTELL(Enum):    AI-related component (`_TYPE_FAILEDTELL`) coordinates
AI/LLM interactions.
L51: def make_headers(    Function `make_headers` utility or script function.
L133: def set_file_position(    Function `set_file_position` Sets or updates a value.
L153: def rewind_body(body: typing.IO[typing.AnyStr], body_pos: _TYPE_BODY_POSITION) -> None:
    Function `rewind_body` utility or script function.
L183: class ChunksAndContentLength(typing.NamedTuple):    Class (`ChunksAndContentLength`)
component used by the app (see file context: None).
L188: def body_to_chunks(    Function `body_to_chunks` utility or script function.
L221: def chunk_readable() -> typing.Iterable[bytes]:    Function `chunk_readable` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/connection.py

```

L29: def _is_legal_header_name(name: bytes) -> bool:    Function `_is_legal_header_name`
utility or script function.
L44: def _is_illegal_header_value(value: bytes) -> bool:    Function
`_is_illegal_header_value` utility or script function.
L54: class _LockedObject(typing.Generic[T]):    Class (`_LockedObject`) component used by the
app (see file context: None).

```

```

L68: def __init__(self, obj: T):    Function `__init__` utility or script function.
L72: def __enter__(self) -> T:    Function `__enter__` utility or script function.
L76: def __exit__(    Function `__exit__` utility or script function.
L85: class HTTP2Connection(HTTPSCConnection):    Class (`HTTP2Connection`) component used by
the app (see file context: None).
L86: def __init__(    Function `__init__` utility or script function.
L101: def _new_h2_conn(self) -> _LockedObject[h2.connection.H2Connection]:    Function
`_new_h2_conn` utility or script function.
L105: def connect(self) -> None:    Function `connect` utility or script function.
L112: def putrequest( # type: ignore[override]    Function `putrequest` utility or script
function.
L143: def putheader(self, header: str | bytes, *values: str | bytes) -> None: # type:
ignore[override]    Function `putheader` utility or script function.
L156: def endheaders(self, message_body: typing.Any = None) -> None: # type:
ignore[override]    Function `endheaders` utility or script function.
L170: def send(self, data: typing.Any) -> None:    Function `send` utility or script
function.
L215: def set_tunnel(    Function `set_tunnel` Sets or updates a value.
L226: def getresponse( # type: ignore[override]    Function `getresponse` Returns or fetches
data.
L268: def request( # type: ignore[override]    Function `request` utility or script
function.
L307: def close(self) -> None:    Function `close` utility or script function.
L324: class HTTP2Response(BaseHTTPResponse):    Class (`HTTP2Response`) component used by the
app (see file context: None).
L326: def __init__(    Function `__init__` utility or script function.
L349: def data(self) -> bytes:    Function `data` utility or script function.
L352: def get_redirect_location(self) -> None:    Function `get_redirect_location` Returns or
fetches data.
L355: def close(self) -> None:    Function `close` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/__init__.py

```

L15: def inject_into_urllib3() -> None:    Function `inject_into_urllib3` utility or script
function.
L43: def extract_from_urllib3() -> None:    Function `extract_from_urllib3` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/http2/probe.py

```

L6: class _HTTP2ProbeCache:    Class (`_HTTP2ProbeCache`) component used by the app (see file
context: None).
L13: def __init__(self) -> None:    Function `__init__` utility or script function.
L18: def acquire_and_get(self, host: str, port: int) -> bool | None:    Function
`acquire_and_get` utility or script function.
L51: def set_and_release(    Function `set_and_release` Sets or updates a value.

```

```
L65: def _values(self) -> dict[tuple[str, int], bool | None]:    Function `_values` utility
or script function.
L70: def _reset(self) -> None:    Function `_reset` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/pyopenssl sl.py

```
L50: class UnsupportedExtension(Exception): # type: ignore[no-redef]    Class
(`UnsupportedExtension`) component used by the app (see file context: None).
L139: def inject_into_urllib3() -> None:    Function `inject_into_urllib3` utility or script
function.
L150: def extract_from_urllib3() -> None:    Function `extract_from_urllib3` utility or
script function.
L159: def _validate_dependencies_met() -> None:    Function `_validate_dependencies_met`
utility or script function.
L185: def _dnsname_to_stdlib(name: str) -> str | None:    Function `_dnsname_to_stdlib`
utility or script function.
L199: def idna_encode(name: str) -> bytes | None:    Function `idna_encode` utility or script
function.
L226: def get_subj_alt_name(peer_cert: X509) -> list[tuple[str, str]]:    Function
`get_subj_alt_name` Returns or fetches data.
L274: class WrappedSocket:    Class (`WrappedSocket`) component used by the app (see file
context: None).
L277: def __init__(    Function `__init__` utility or script function.
L289: def fileno(self) -> int:    Function `fileno` utility or script function.
L293: def _decref_socketios(self) -> None:    Function `_decref_socketios` utility or script
function.
L299: def recv(self, *args: typing.Any, **kwargs: typing.Any) -> bytes:    Function `recv`
utility or script function.
L324: def recv_into(self, *args: typing.Any, **kwargs: typing.Any) -> int:    Function
`recv_into` utility or script function.
L347: def settimeout(self, timeout: float) -> None:    Function `settimeout` Sets or updates
a value.
L350: def _send_until_done(self, data: bytes) -> int:    Function `_send_until_done` utility
or script function.
L361: def sendall(self, data: bytes) -> None:    Function `sendall` utility or script
function.
L369: def shutdown(self, how: int) -> None:    Function `shutdown` utility or script
function.
L375: def close(self) -> None:    Function `close` utility or script function.
L380: def _real_close(self) -> None:    Function `_real_close` utility or script function.
L386: def getpeercert(    Function `getpeercert` Returns or fetches data.
L402: def version(self) -> str:    Function `version` utility or script function.
L405: def selected_alpn_protocol(self) -> str | None:    Function `selected_alpn_protocol`
utility or script function.
L413: class PyOpenSSLContext:    Class (`PyOpenSSLContext`) component used by the app (see
file context: None).
L420: def __init__(self, protocol: int) -> None:    Function `__init__` utility or script
```



```

function.
L430: def options(self) -> int:    Function `options` utility or script function.
L434: def options(self, value: int) -> None:    Function `options` utility or script
function.
L439: def verify_flags(self) -> int:    Function `verify_flags` utility or script function.
L443: def verify_flags(self, value: int) -> None:    Function `verify_flags` utility or
script function.
L448: def verify_mode(self) -> int:    Function `verify_mode` utility or script function.
L452: def verify_mode(self, value: ssl.VerifyMode) -> None:    Function `verify_mode` utility
or script function.
L455: def set_default_verify_paths(self) -> None:    Function `set_default_verify_paths` Sets
or updates a value.
L458: def set_ciphers(self, ciphers: bytes | str) -> None:    Function `set_ciphers` Sets or
updates a value.
L463: def load_verify_locations(    Function `load_verify_locations` Loads data from storage
or remote.
L480: def load_cert_chain(    Function `load_cert_chain` Loads data from storage or remote.
L496: def set_alpn_protocols(self, protocols: list[bytes | str]) -> None:    Function
`set_alpn_protocols` Sets or updates a value.
L500: def wrap_socket(    Function `wrap_socket` utility or script function.
L531: def _set_ctx_options(self) -> None:    Function `_set_ctx_options` utility or script
function.
L539: def minimum_version(self) -> int:    Function `minimum_version` utility or script
function.
L543: def minimum_version(self, minimum_version: int) -> None:    Function `minimum_version`
utility or script function.
L548: def maximum_version(self) -> int:    Function `maximum_version` utility or script
function.
L552: def maximum_version(self, maximum_version: int) -> None:    Function `maximum_version`
utility or script function.
L557: def _verify_callback(    Function `_verify_callback` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/socks.py

```

L75: class _TYPE SOCKS_OPTIONS(typing.TypedDict):    Class (`_TYPE SOCKS_OPTIONS`) component
used by the app (see file context: None).
L84: class SOCKSConnection(HTTPConnection):    Class (`SOCKSConnection`) component used by
the app (see file context: None).
L89: def __init__(    Function `__init__` utility or script function.
L98: def _new_conn(self) -> socks.socksocket:    Function `_new_conn` utility or script
function.
L161: class SOCKSHTTPConnection(SOCKSConnection, HTTPConnection):    Class
(`SOCKSHTTPConnection`) component used by the app (see file context: None).
L165: class SOCKSHTTPConnectionPool(HTTPConnectionPool):    Class (`SOCKSHTTPConnectionPool`)
component used by the app (see file context: None).
L169: class SOCKSHTTPConnectionPool(HTTPConnectionPool):    Class
(`SOCKSHTTPConnectionPool`) component used by the app (see file context: None).
L173: class SOCKSProxyManager(PoolManager):    Manager (`SOCKSProxyManager`)

```

orchestration/utility for managing resources or behaviors.

L184: def __init__(Function `\_\_init\_\_` utility or script function.

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/fetch.py

L71: class _RequestError(Exception): Class (`\_RequestError`) component used by the app (see file context: None).

L72: def __init__(Function `\_\_init\_\_` utility or script function.

L85: class _StreamingError(_RequestError): Class (`\_StreamingError`) component used by the app (see file context: None).

L89: class _TimeoutError(_RequestError): Class (`\_TimeoutError`) component used by the app (see file context: None).

L93: def _obj_from_dict(dict_val: dict[str, Any]) -> JsProxy: Function `\_obj\_from\_dict` utility or script function.

L97: class _ReadStream(io.RawIOBase): Class (`\_ReadStream`) component used by the app (see file context: None).

L98: def __init__(Function `\_\_init\_\_` utility or script function.

L118: def __del__(self) -> None: Function `\_del\_\_` utility or script function.

L122: def is_closed(self) -> bool: Function `\_is\_closed` utility or script function.

L127: def closed(self) -> bool: Function `\_closed` utility or script function.

L130: def close(self) -> None: Function `\_close` utility or script function.

L144: def readable(self) -> bool: Function `\_readable` utility or script function.

L147: def writable(self) -> bool: Function `\_writable` utility or script function.

L150: def seekable(self) -> bool: Function `\_seekable` utility or script function.

L153: def readinto(self, byte_obj: Buffer) -> int: Function `\_readinto` utility or script function.

L200: class _StreamingFetcher: Class (`\_StreamingFetcher`) component used by the app (see file context: None).

L201: def __init__(self) -> None: Function `\_init\_\_` utility or script function.

L214: def promise_resolver(js_resolve_fn: JsProxy, js_reject_fn: JsProxy) -> None: Function `\_promise\_resolver` utility or script function.

L215: def onMsg(e: JsProxy) -> None: Function `\_onMsg` utility or script function.

L219: def onErr(e: JsProxy) -> None: Function `\_onErr` utility or script function.

L229: def send(self, request: EmscriptenRequest) -> EmscriptenResponse: Function `\_send` utility or script function.

L302: class _JSPiReadStream(io.RawIOBase): Class (`\_JSPiReadStream`) component used by the app (see file context: None).

L324: def __init__(Function `\_\_init\_\_` utility or script function.

L342: def __del__(self) -> None: Function `\_del\_\_` utility or script function.

L346: def is_closed(self) -> bool: Function `\_is\_closed` utility or script function.

L351: def closed(self) -> bool: Function `\_closed` utility or script function.

L354: def close(self) -> None: Function `\_close` utility or script function.

L367: def readable(self) -> bool: Function `\_readable` utility or script function.

L370: def writable(self) -> bool: Function `\_writable` utility or script function.

L373: def seekable(self) -> bool: Function `\_seekable` utility or script function.

L376: def _get_next_buffer(self) -> bool: Function `\_get\_next\_buffer` utility or script function.

```

L392: def readinto(self, byte_obj: Buffer) -> int:    Function `readinto` utility or script
function.
L410: def is_in_browser_main_thread() -> bool:    Function `is_in_browser_main_thread`
utility or script function.
L414: def is_cross_origin_isolated() -> bool:    Function `is_cross_origin_isolated` utility
or script function.
L418: def is_in_node() -> bool:    Function `is_in_node` utility or script function.
L427: def is_worker_available() -> bool:    Function `is_worker_available` utility or script
function.
L449: def send_streaming_request(request: EmscriptenRequest) -> EmscriptenResponse | None:
Function `send_streaming_request` utility or script function.
L469: def _show_timeout_warning() -> None:    Function `_show_timeout_warning` utility or
script function.
L480: def _show_streaming_warning() -> None:    Function `_show_streaming_warning` utility or
script function.
L499: def send_request(request: EmscriptenRequest) -> EmscriptenResponse:    Function
`send_request` utility or script function.
L548: def send_jspi_request(    Function `send_jspi_request` utility or script function.
L626: def _run_sync_with_timeout(    Function `_run_sync_with_timeout` utility or script
function.
L680: def has_jspi() -> bool:    Function `has_jspi` utility or script function.
L699: def _is_node_js() -> bool:    Function `_is_node_js` utility or script function.
L714: def streaming_ready() -> bool | None:    Function `streaming_ready` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/connection.py

```

L25: class EmscriptenHTTPConnection:    Class (`EmscriptenHTTPConnection`) component used by
the app (see file context: None).
L46: def __init__(    Function `__init__` utility or script function.
L73: def set_tunnel(    Function `set_tunnel` Sets or updates a value.
L82: def connect(self) -> None:    Function `connect` utility or script function.
L85: def request(    Function `request` utility or script function.
L129: def getresponse(self) -> BaseHTTPResponse:    Function `getresponse` Returns or fetches
data.
L139: def close(self) -> None:    Function `close` utility or script function.
L144: def is_closed(self) -> bool:    Function `is_closed` utility or script function.
L152: def is_connected(self) -> bool:    Function `is_connected` utility or script function.
L157: def has_connected_to_proxy(self) -> bool:    Function `has_connected_to_proxy` utility
or script function.
L165: class EmscriptenHTTPSConnection(EmscriptenHTTPConnection):    Class
(`EmscriptenHTTPSConnection`) component used by the app (see file context: None).
L182: def __init__(    Function `__init__` utility or script function.
L242: def set_cert(    Function `set_cert` Sets or updates a value.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/response.py

```

L23: class EmscriptenResponse:    Class (`EmscriptenResponse`)    component used by the app (see
file context: None).
L30: class EmscriptenHttpResponseWrapper(BaseHTTPResponse):    Class
(`EmscriptenHttpResponseWrapper`)    component used by the app (see file context: None).
L31: def __init__(    Function `__init__`    utility or script function.
L56: def url(self) -> str | None:    Function `url`    utility or script function.
L60: def url(self, url: str | None) -> None:    Function `url`    utility or script function.
L64: def connection(self) -> BaseHTTPConnection | BaseHTTPSConnection | None:    Function
`connection`    utility or script function.
L68: def retries(self) -> Retry | None:    Function `retries`    utility or script function.
L72: def retries(self, retries: Retry | None) -> None:    Function `retries`    utility or
script function.
L76: def stream(    Function `stream`    utility or script function.
L102: def _init_length(self, request_method: str | None) -> int | None:    Function
`_init_length`    utility or script function.
L139: def read(    Function `read`    utility or script function.
L176: def read_chunked(    Function `read_chunked`    utility or script function.
L188: def release_conn(self) -> None:    Function `release_conn`    utility or script function.
L195: def drain_conn(self) -> None:    Function `drain_conn`    utility or script function.
L199: def data(self) -> bytes:    Function `data`    utility or script function.
L205: def json(self) -> typing.Any:    Function `json`    utility or script function.
L226: def close(self) -> None:    Function `close`    utility or script function.
L236: def _error_catcher(self) -> typing.Generator[None]:    Function `_error_catcher`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/__init__.py

```

L9: def inject_into_urllib3() -> None:    Function `inject_into_urllib3`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/urllib3/contrib/emscripten/request.py

```

L9: class EmscriptenRequest:    Class (`EmscriptenRequest`)    component used by the app (see
file context: None).
L18: def set_header(self, name: str, value: str) -> None:    Function `set_header`    Sets or
updates a value.
L21: def set_body(self, body: _TYPE_BODY | None) -> None:    Function `set_body`    Sets or
updates a value.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/providers.py

```

L17: class Preference(Protocol):    Class (`Preference`) component used by the app (see file
context: None).
L18: def __lt__(self, __other: Any) -> bool: ...    Function `__lt__` utility or script
function.
L21: class AbstractProvider(Generic[RT, CT, KT]):    Class (`AbstractProvider`) component
used by the app (see file context: None).
L24: def identify(self, requirement_or_candidate: RT | CT) -> KT:    Function `identify`
utility or script function.
L33: def get_preference(    Function `get_preference` Returns or fetches data.
L92: def find_matches(    Function `find_matches` utility or script function.
L127: def is_satisfied_by(self, requirement: RT, candidate: CT) -> bool:    Function
`is_satisfied_by` utility or script function.
L138: def get_dependencies(self, candidate: CT) -> Iterable[RT]:    Function
`get_dependencies` Returns or fetches data.
L146: def narrow_requirement_selection(    Function `narrow_requirement_selection` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/structs.py

```

L27: class RequirementInformation(NamedTuple, Generic[RT, CT]):    Class
(`RequirementInformation`) component used by the app (see file context: None).
L31: class State(NamedTuple, Generic[RT, CT, KT]):    Class (`State`) component used by the
app (see file context: None).
L45: class DirectedGraph(Generic[KT]):    Class (`DirectedGraph`) component used by the app
(see file context: None).
L48: def __init__(self) -> None:    Function `__init__` utility or script function.
L53: def __iter__(self) -> Iterator[KT]:    Function `__iter__` utility or script function.
L56: def __len__(self) -> int:    Function `__len__` utility or script function.
L59: def __contains__(self, key: KT) -> bool:    Function `__contains__` utility or script
function.
L62: def copy(self) -> DirectedGraph[KT]:    Function `copy` utility or script function.
L70: def add(self, key: KT) -> None:    Function `add` utility or script function.
L78: def remove(self, key: KT) -> None:    Function `remove` utility or script function.
L86: def connected(self, f: KT, t: KT) -> bool:    Function `connected` utility or script
function.
L89: def connect(self, f: KT, t: KT) -> None:    Function `connect` utility or script
function.
L99: def iter_edges(self) -> Iterator[tuple[KT, KT]]:    Function `iter_edges` utility or
script function.
L104: def iter_children(self, key: KT) -> Iterator[KT]:    Function `iter_children` utility
or script function.
L107: def iter_parents(self, key: KT) -> Iterator[KT]:    Function `iter_parents` utility or
script function.
L111: class IteratorMapping(Mapping[KT, Iterator[CT]], Generic[RT, CT, KT]):    Class
(`IteratorMapping`) component used by the app (see file context: None).
L112: def __init__(    Function `__init__` utility or script function.

```

```

L122: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L129: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L132: def __contains__(self, key: object) -> bool:    Object (singleton).
L135: def __getitem__(self, k: KT) -> Iterator[CT]:    Function `__getitem__` utility or
script function.
L142: def __iter__(self) -> Iterator[KT]:    Function `__iter__` utility or script function.
L146: def __len__(self) -> int:    Function `__len__` utility or script function.
L151: class _FactoryIterableView(Iterable[RT]):    Class (`_FactoryIterableView`) component
used by the app (see file context: None).
L160: def __init__(self, factory: Callable[[], Iterable[RT]]) -> None:    Function `__init__`
utility or script function.
L164: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L167: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L174: def __iter__(self) -> Iterator[RT]:    Function `__iter__` utility or script function.
L180: class _SequenceIterableView(Iterable[RT]):    Class (`_SequenceIterableView`) component
used by the app (see file context: None).
L187: def __init__(self, sequence: Sequence[RT]):    Function `__init__` utility or script
function.
L190: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L193: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L196: def __iter__(self) -> Iterator[RT]:    Function `__iter__` utility or script function.
L200: def build_iter_view(matches: Matches[CT]) -> Iterable[CT]:    Function `build_iter_view`
Constructs or prepares an object.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/reporters.py

```

L11: class BaseReporter(Generic[RT, CT, KT]):    Class (`BaseReporter`) component used by the
app (see file context: None).
L14: def starting(self) -> None:    Function `starting` utility or script function.
L17: def starting_round(self, index: int) -> None:    Function `starting_round` utility or
script function.
L23: def ending_round(self, index: int, state: State[RT, CT, KT]) -> None:    Function
`ending_round` utility or script function.
L30: def ending(self, state: State[RT, CT, KT]) -> None:    Function `ending` utility or
script function.
L33: def adding_requirement(self, requirement: RT, parent: CT | None) -> None:    Function
`adding_requirement` utility or script function.
L43: def resolving_conflicts(    Function `resolving_conflicts` utility or script function.
L51: def rejecting_candidate(self, criterion: Criterion[RT, CT], candidate: CT) -> None:
Function `rejecting_candidate` utility or script function.
L54: def pinning(self, candidate: CT) -> None:    Function `pinning` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/resolution.py

```

L38: def _build_result(state: State[RT, CT, KT]) -> Result[RT, CT, KT]:    Function
`_build_result` utility or script function.
L68: class Resolution(Generic[RT, CT, KT]):    Class (`Resolution`) component used by the app
(see file context: None).
L75: def __init__(    Function `_init__` utility or script function.
L90: def state(self) -> State[RT, CT, KT]:    Function `state` utility or script function.
L96: def _push_new_state(self) -> None:    Function `_push_new_state` utility or script
function.
L110: def _add_to_criteria(    Function `_add_to_criteria` utility or script function.
L154: def _remove_information_from_criteria(    Function `_remove_information_from_criteria`
utility or script function.
L181: def _get_preference(self, name: KT) -> Preference:    Function `_get_preference`
utility or script function.
L196: def _is_current_pin_satisfying(    Function `_is_current_pin_satisfying` utility or
script function.
L208: def _get_updated_criteria(self, candidate: CT) -> dict[KT, Criterion[RT, CT]]:
Function `_get_updated_criteria` utility or script function.
L214: def _attempt_to_pin_criterion(self, name: KT) -> list[Criterion[RT, CT]]:    Function
`_attempt_to_pin_criterion` utility or script function.
L251: def _patch_criteria(    Function `_patch_criteria` utility or script function.
L286: def _save_state(self) -> None:    Function `_save_state` utility or script function.
L298: def _rollback_states(self) -> None:    Function `_rollback_states` utility or script
function.
L305: def _backjump(self, causes: list[RequirementInformation[RT, CT]]) -> bool:    Function
`_backjump` utility or script function.
L412: def _extract_causes(    Function `_extract_causes` utility or script function.
L418: def resolve(self, requirements: Iterable[RT], max_rounds: int) -> State[RT, CT, KT]:
Function `resolve` utility or script function.
L563: class Resolver(AbstractResolver[RT, CT, KT]):    Class (`Resolver`) component used by
the app (see file context: None).
L568: def resolve( # type: ignore[override]    Function `resolve` utility or script
function.
L605: def _has_route_to_root(    Function `_has_route_to_root` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/options.py

```

L11: class ResolverException(Exception):    Class (`ResolverException`) component used by the
app (see file context: None).
L19: class RequirementsConflicted(ResolverException, Generic[RT, CT]):    Class
(`RequirementsConflicted`) component used by the app (see file context: None).
L20: def __init__(self, criterion: Criterion[RT, CT]) -> None:    Function `_init__` utility
or script function.
L24: def __str__(self) -> str:    Function `_str__` utility or script function.
L30: class InconsistentCandidate(ResolverException, Generic[RT, CT]):    Class
(`InconsistentCandidate`) component used by the app (see file context: None).
L31: def __init__(self, candidate: CT, criterion: Criterion[RT, CT]):    Function `_init__`
utility or script function.

```

```

L36: def __str__(self) -> str:    Function `__str__`    utility or script function.
L43: class ResolutionError(ResolverException):    Class (`ResolutionError`)    component used by
the app (see file context: None).
L47: class ResolutionImpossible(ResolutionError, Generic[RT, CT]):    Class
(`ResolutionImpossible`)    component used by the app (see file context: None).
L48: def __init__(self, causes: Collection[RequirementInformation[RT, CT]]):    Function
`__init__`    utility or script function.
L54: class ResolutionTooDeep(ResolutionError):    Class (`ResolutionTooDeep`)    component used
by the app (see file context: None).
L55: def __init__(self, round_count: int) -> None:    Function `__init__`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/abstract.py

```

L13: class Result(NamedTuple, Generic[RT, CT, KT]):    Class (`Result`)    component used by the
app (see file context: None).
L22: class AbstractResolver(Generic[RT, CT, KT]):    Class (`AbstractResolver`)    component
used by the app (see file context: None).
L27: def __init__(    Function `__init__`    utility or script function.
L35: def resolve(self, requirements: Iterable[RT], **kwargs: Any) -> Result[RT, CT, KT]:
Function `resolve`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/resolvelib/resolvers/criterion.py

```

L8: class Criterion(Generic[RT, CT]):    Class (`Criterion`)    component used by the app (see
file context: None).
L28: def __init__(    Function `__init__`    utility or script function.
L38: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L44: def iter_requirement(self) -> Iterator[RT]:    Function `iter_requirement`    utility or
script function.
L47: def iter_parent(self) -> Iterator[CT | None]:    Function `iter_parent`    utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/compat.py

```

L6: def ToASCII(label: str) -> bytes:    Function `ToASCII`    utility or script function.
L10: def ToUnicode(label: Union[bytes, bytearray]) -> str:    Function `ToUnicode`    utility or
script function.
L14: def nameprep(s: Any) -> None:    Function `nameprep`    utility or script function.

```


.venv/lib/python3.12/site-packages/pip/_vendor/idna/core.py

```

L14: class IDNAError(UnicodeError):    Class (`IDNAError`)    component used by the app (see
file context: None).
L20: class IDNABidiError(IDNAError):    Class (`IDNABidiError`)    component used by the app
(see file context: None).
L26: class InvalidCodepoint(IDNAError):    Class (`InvalidCodepoint`)    component used by the
app (see file context: None).
L32: class InvalidCodepointContext(IDNAError):    Class (`InvalidCodepointContext`)    component
used by the app (see file context: None).
L38: def _combining_class(cp: int) -> int:    Function `_combining_class`    utility or script
function.
L46: def _is_script(cp: str, script: str) -> bool:    Function `_is_script`    utility or script
function.
L50: def _punycode(s: str) -> bytes:    Function `_punycode`    utility or script function.
L54: def _unot(s: int) -> str:    Function `_unot`    utility or script function.
L58: def valid_label_length(label: Union[bytes, str]) -> bool:    Function
`valid_label_length`    utility or script function.
L64: def valid_string_length(label: Union[bytes, str], trailing_dot: bool) -> bool:
Function `valid_string_length`    utility or script function.
L70: def check_bidi(label: str, check_ltr: bool = False) -> bool:    Function `check_bidi`
utility or script function.
L140: def check_initial_combiner(label: str) -> bool:    Function `check_initial_combiner`
utility or script function.
L146: def check_hyphen_ok(label: str) -> bool:    Function `check_hyphen_ok`    utility or
script function.
L154: def check_nfc(label: str) -> None:    Function `check_nfc`    utility or script function.
L159: def valid_contextj(label: str, pos: int) -> bool:    Function `valid_contextj`    utility
or script function.
L203: def valid_contexto(label: str, pos: int, exception: bool = False) -> bool:    Function
`valid_contexto`    utility or script function.
L245: def check_label(label: Union[str, bytes, bytearray]) -> None:    Function `check_label`
utility or script function.
L284: def alabel(label: str) -> bytes:    Function `alabel`    utility or script function.
L303: def ulabel(label: Union[str, bytes, bytearray]) -> str:    Function `ulabel`    utility or
script function.
L332: def uts46_remap(domain: str, std3_rules: bool = True, transitional: bool = False) ->
str:    Function `uts46_remap`    utility or script function.
L366: def encode(    Function `encode`    utility or script function.
L405: def decode(    Function `decode`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/codec.py

```

L10: class Codec(codecs.Codec):    Class (`Codec`)    component used by the app (see file
context: None).
L11: def encode(self, data: str, errors: str = "strict") -> Tuple[bytes, int]:    Function
`encode`    utility or script function.
L20: def decode(self, data: bytes, errors: str = "strict") -> Tuple[str, int]:    Function

```

```

`decode` utility or script function.
L30: class IncrementalEncoder(codecs.BufferedIncrementalEncoder):    Class
(`IncrementalEncoder`) component used by the app (see file context: None).
L31: def _buffer_encode(self, data: str, errors: str, final: bool) -> Tuple[bytes, int]:
Function `_buffer_encode` utility or script function.
L64: class IncrementalDecoder(codecs.BufferedIncrementalDecoder):    Class
(`IncrementalDecoder`) component used by the app (see file context: None).
L65: def _buffer_decode(self, data: Any, errors: str, final: bool) -> Tuple[str, int]:
Function `_buffer_decode` utility or script function.
L100: class StreamWriter(Codec, codecs.StreamWriter):    Class (`StreamWriter`) component
used by the app (see file context: None).
L104: class StreamReader(Codec, codecs.StreamReader):    Class (`StreamReader`) component
used by the app (see file context: None).
L108: def search_function(name: str) -> Optional[codecs.CodecInfo]:    Function
`search_function` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/intranges.py

```

L12: def intranges_from_list(list_: List[int]) -> Tuple[int, ...]:    Function
`intranges_from_list` utility or script function.
L34: def _encode_range(start: int, end: int) -> int:    Function `_encode_range` utility or
script function.
L38: def _decode_range(r: int) -> Tuple[int, int]:    Function `_decode_range` utility or
script function.
L42: def intranges_contain(int_: int, ranges: Tuple[int, ...]) -> bool:    Function
`intranges_contain` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/idna/uts46data.py

```

L12: def _seg_0() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_0`
utility or script function.
L117: def _seg_1() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_1`
utility or script function.
L222: def _seg_2() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_2`
utility or script function.
L327: def _seg_3() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_3`
utility or script function.
L432: def _seg_4() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_4`
utility or script function.
L537: def _seg_5() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_5`
utility or script function.
L642: def _seg_6() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_6`
utility or script function.
L747: def _seg_7() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_7`
utility or script function.
L852: def _seg_8() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]:    Function `_seg_8`
utility or script function.

```

```

utility or script function.
L957: def _seg_9() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function `_seg_9`
utility or script function.
L1062: def _seg_10() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_10` utility or script function.
L1167: def _seg_11() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_11` utility or script function.
L1272: def _seg_12() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_12` utility or script function.
L1377: def _seg_13() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_13` utility or script function.
L1482: def _seg_14() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_14` utility or script function.
L1587: def _seg_15() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_15` utility or script function.
L1692: def _seg_16() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_16` utility or script function.
L1797: def _seg_17() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_17` utility or script function.
L1902: def _seg_18() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_18` utility or script function.
L2007: def _seg_19() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_19` utility or script function.
L2112: def _seg_20() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_20` utility or script function.
L2217: def _seg_21() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_21` utility or script function.
L2322: def _seg_22() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_22` utility or script function.
L2427: def _seg_23() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_23` utility or script function.
L2532: def _seg_24() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_24` utility or script function.
L2637: def _seg_25() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_25` utility or script function.
L2742: def _seg_26() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_26` utility or script function.
L2847: def _seg_27() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_27` utility or script function.
L2952: def _seg_28() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_28` utility or script function.
L3057: def _seg_29() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_29` utility or script function.
L3162: def _seg_30() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_30` utility or script function.
L3267: def _seg_31() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_31` utility or script function.
L3372: def _seg_32() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_32` utility or script function.
L3477: def _seg_33() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_33` utility or script function.

```

```

L3582: def _seg_34() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_34` utility or script function.
L3687: def _seg_35() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_35` utility or script function.
L3792: def _seg_36() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_36` utility or script function.
L3897: def _seg_37() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_37` utility or script function.
L4002: def _seg_38() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_38` utility or script function.
L4107: def _seg_39() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_39` utility or script function.
L4212: def _seg_40() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_40` utility or script function.
L4317: def _seg_41() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_41` utility or script function.
L4422: def _seg_42() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_42` utility or script function.
L4527: def _seg_43() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_43` utility or script function.
L4632: def _seg_44() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_44` utility or script function.
L4737: def _seg_45() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_45` utility or script function.
L4842: def _seg_46() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_46` utility or script function.
L4947: def _seg_47() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_47` utility or script function.
L5052: def _seg_48() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_48` utility or script function.
L5157: def _seg_49() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_49` utility or script function.
L5262: def _seg_50() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_50` utility or script function.
L5367: def _seg_51() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_51` utility or script function.
L5472: def _seg_52() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_52` utility or script function.
L5577: def _seg_53() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_53` utility or script function.
L5682: def _seg_54() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_54` utility or script function.
L5787: def _seg_55() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_55` utility or script function.
L5892: def _seg_56() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_56` utility or script function.
L5997: def _seg_57() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_57` utility or script function.
L6102: def _seg_58() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_58` utility or script function.
L6207: def _seg_59() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function

```

```

`_seg_59` utility or script function.
L6312: def _seg_60() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_60` utility or script function.
L6417: def _seg_61() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_61` utility or script function.
L6522: def _seg_62() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_62` utility or script function.
L6627: def _seg_63() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_63` utility or script function.
L6732: def _seg_64() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_64` utility or script function.
L6837: def _seg_65() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_65` utility or script function.
L6942: def _seg_66() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_66` utility or script function.
L7047: def _seg_67() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_67` utility or script function.
L7152: def _seg_68() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_68` utility or script function.
L7257: def _seg_69() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_69` utility or script function.
L7362: def _seg_70() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_70` utility or script function.
L7467: def _seg_71() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_71` utility or script function.
L7572: def _seg_72() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_72` utility or script function.
L7677: def _seg_73() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_73` utility or script function.
L7782: def _seg_74() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_74` utility or script function.
L7887: def _seg_75() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_75` utility or script function.
L7992: def _seg_76() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_76` utility or script function.
L8097: def _seg_77() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_77` utility or script function.
L8202: def _seg_78() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_78` utility or script function.
L8307: def _seg_79() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_79` utility or script function.
L8412: def _seg_80() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_80` utility or script function.
L8517: def _seg_81() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_81` utility or script function.
L8622: def _seg_82() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_82` utility or script function.
L8727: def _seg_83() -> List[Union[Tuple[int, str], Tuple[int, str, str]]]: Function
`_seg_83` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_elffile.py

```

L18: class ELFInvalid(ValueError):    Class (`ELFInvalid`) component used by the app (see
file context: None).
L22: class EIClass(enum.IntEnum):    Class (`EIClass`) component used by the app (see file
context: None).
L27: class EIData(enum.IntEnum):    Class (`EIData`) component used by the app (see file
context: None).
L32: class EMachine(enum.IntEnum):    Class (`EMachine`) component used by the app (see file
context: None).
L40: class ELFFile:    Class (`ELFFile`) component used by the app (see file context: None).
L45: def __init__(self, f: IO[bytes]) -> None:    Function `__init__` utility or script
function.
L90: def _read(self, fmt: str) -> tuple[int, ...]:    Function `_read` utility or script
function.
L94: def interpreter(self) -> str | None:    Function `interpreter` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_manylinux.py

```

L32: def _parse_elf(path: str) -> Generator[ELFFile | None, None, None]:    Function
`_parse_elf` utility or script function.
L40: def _is_linux_armhf(executable: str) -> bool:    Function `_is_linux_armhf` utility or
script function.
L55: def _is_linux_i686(executable: str) -> bool:    Function `_is_linux_i686` utility or
script function.
L65: def _have_compatible_abi(executable: str, archs: Sequence[str]) -> bool:    Function
`_have_compatible_abi` utility or script function.
L81: class _GLibCVersion(NamedTuple):    Class (`_GLibCVersion`) component used by the app
(see file context: None).
L86: def _glibc_version_string_confstr() -> str | None:    Function
`_glibc_version_string_confstr` utility or script function.
L105: def _glibc_version_string_ctypes() -> str | None:    Function
`_glibc_version_string_ctypes` utility or script function.
L149: def _glibc_version_string() -> str | None:    Function `_glibc_version_string` utility
or script function.
L154: def _parse_glibc_version(version_str: str) -> _GLibCVersion:    Function
`_parse_glibc_version` utility or script function.
L174: def _get_glibc_version() -> _GLibCVersion:    Function `_get_glibc_version` utility or
script function.
L182: def _is_compatible(arch: str, version: _GLibCVersion) -> bool:    Function
`_is_compatible` utility or script function.
L219: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/direct_url.py

```

L27: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L34: class _FromMappingProtocol(Protocol): # pragma: no cover    Class
(`_FromMappingProtocol`) component used by the app (see file context: None).
L36: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict`    utility
or script function.
L42: def _json_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_json_dict_factory`    utility or script function.
L46: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get`    utility or script function.
L59: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required`    utility or script function.
L66: def _get_object(    Function `_get_object`    utility or script function.
L83: def _strip_auth_from_netloc(netloc: str, safe_user_passwords: Collection[str]) -> str:
Function `_strip_auth_from_netloc`    utility or script function.
L94: def _strip_url(url: str, safe_user_passwords: Collection[str]) -> str:    Function
`_strip_url`    utility or script function.
L112: class DirectUrlValidationError(Exception):    Class (`DirectUrlValidationError`)
component used by the app (see file context: None).
L118: def __init__(    Function `__init__`    utility or script function.
L136: def __str__(self) -> str:    Function `__str__`    utility or script function.
L142: class _DirectUrlRequiredKeyError(DirectUrlValidationError):    Class
(`_DirectUrlRequiredKeyError`) component used by the app (see file context: None).
L143: def __init__(self, key: str) -> None:    Function `__init__`    utility or script
function.
L148: class VcsInfo:    Class (`VcsInfo`) component used by the app (see file context: None).
L153: def __init__(    Function `__init__`    utility or script function.
L165: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L175: class ArchiveInfo:    Class (`ArchiveInfo`) component used by the app (see file
context: None).
L178: def __init__(    Function `__init__`    utility or script function.
L186: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L221: class DirInfo:    Class (`DirInfo`) component used by the app (see file context: None).
L224: def __init__(    Function `__init__`    utility or script function.
L232: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L239: class DirectUrl:    Class (`DirectUrl`) component used by the app (see file context:
None).
L248: def __init__(    Function `__init__`    utility or script function.
L264: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L289: def from_dict(cls, d: Mapping[str, Any], /) -> Self:    Function `from_dict`    utility or
script function.
L293: def to_dict(    Function `to_dict`    utility or script function.
L320: def validate(self) -> None:    Function `validate`    utility or script function.

```


.venv/lib/python3.12/site-packages/pip/_vendor/packaging/metadata.py

```

L40: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L44: class InvalidMetadata(ValueError):    Class (`InvalidMetadata`)    component used by the
app (see file context: None).
L50: def __init__(self, field: str, message: str) -> None:    Function `__init__`    utility or
script function.
L59: class RawMetadata(TypedDict, total=False):    Class (`RawMetadata`)    component used by
the app (see file context: None).
L178: def _parse_keywords(data: str) -> list[str]:    Function `_parse_keywords`    utility or
script function.
L183: def _parse_project_urls(data: list[str]) -> dict[str, str]:    Function
`_parse_project_urls`    utility or script function.
L222: def _get_payload(msg: email.message.Message, source: bytes | str) -> str:    Function
`_get_payload`    utility or script function.
L291: class RFC822Policy(email.policy.EmailPolicy):    Class (`RFC822Policy`)    component used
by the app (see file context: None).
L301: def header_store_parse(self, name: str, value: str) -> tuple[str, str]:    Function
`header_store_parse`    utility or script function.
L308: class RFC822Message(email.message.EmailMessage):    Class (`RFC822Message`)    component
used by the app (see file context: None).
L315: def __init__(self) -> None:    Function `__init__`    utility or script function.
L318: def as_bytes(    Function `as_bytes`    utility or script function.
L329: def parse_email(data: bytes | str) -> tuple[RawMetadata, dict[str, list[str]]]:
Function `parse_email`    utility or script function.
L520: class _Validator(Generic[T]):    Class (`_Validator`)    component used by the app (see
file context: None).
L534: def __init__(    Function `__init__`    utility or script function.
L541: def __set_name__(self, _owner: Metadata, name: str) -> None:    Function `__set_name__`
utility or script function.
L545: def __get__(self, instance: Metadata, _owner: type[Metadata]) -> T:    Function
`__get__`    utility or script function.
L572: def _invalid_metadata(    Function `_invalid_metadata`    utility or script function.
L581: def _process_metadata_version(self, value: str) -> _MetadataVersion:    Function
`_process_metadata_version`    utility or script function.
L587: def _process_name(self, value: str) -> str:    Function `_process_name`    utility or
script function.
L600: def _process_version(self, value: str) -> version_module.Version:    Function
`_process_version`    utility or script function.
L610: def _process_summary(self, value: str) -> str:    Function `_process_summary`    utility
or script function.
L616: def _process_description_content_type(self, value: str) -> str:    Function
`_process_description_content_type`    utility or script function.
L648: def _process_dynamic(self, value: list[str]) -> list[str]:    Function
`_process_dynamic`    utility or script function.
L660: def _process_provides_extra(    Function `_process_provides_extra`    utility or script
function.
L675: def _process_requires_python(self, value: str) -> specifiers.SpecifierSet:    Function
`_process_requires_python`    utility or script function.
L683: def _process_requires_dist(    Function `_process_requires_dist`    utility or script

```



```

function.
L698: def _process_license_expression(self, value: str) -> NormalizedLicenseExpression:
Function `_process_license_expression` utility or script function.
L706: def _process_license_files(self, value: list[str]) -> list[str]: Function
`_process_license_files` utility or script function.
L732: def _process_import_names(self, value: list[str]) -> list[str]: Function
`_process_import_names` utility or script function.
L757: class Metadata: Class (`Metadata`) component used by the app (see file context:
None).
L769: def from_raw(cls, data: RawMetadata, *, validate: bool = True) -> Metadata: Function
`from_raw` utility or script function.
L823: def from_email(cls, data: bytes | str, *, validate: bool = True) -> Metadata:
Function `from_email` utility or script function.
L932: def as_rfc822(self) -> RFC822Message: Function `as_rfc822` utility or script
function.
L940: def _write_metadata(self, message: RFC822Message) -> None: Function `_write_metadata`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/markers.py

```

L30: def __dir__() -> list[str]: Function `__dir__` utility or script function.
L54: class InvalidMarker(ValueError): Class (`InvalidMarker`) component used by the app
(see file context: None).
L62: class UndefinedComparison(ValueError): Class (`UndefinedComparison`) component used
by the app (see file context: None).
L71: class UndefinedEnvironmentName(ValueError): Class (`UndefinedEnvironmentName`)
component used by the app (see file context: None).
L75: class Environment(TypedDict): Class (`Environment`) component used by the app (see
file context: None).
L152: def _normalize_extras( Function `_normalize_extras` utility or script function.
L168: def _normalize_extra_values(results: MarkerList) -> MarkerList: Function
`_normalize_extra_values` utility or script function.
L176: def _format_marker( Function `_format_marker` utility or script function.
L216: def _eval_op(lhs: str, op: Op, rhs: str | AbstractSet[str], *, key: str) -> bool:
Function `_eval_op` utility or script function.
L233: def _normalize( Function `_normalize` utility or script function.
L254: def _evaluate_markers( Function `_evaluate_markers` utility or script function.
L287: def _format_full_version(info: sys._version_info) -> str: Function
`_format_full_version` utility or script function.
L295: def default_environment() -> Environment: Function `default_environment` utility or
script function.
L317: class Marker: Class (`Marker`) component used by the app (see file context: None).
L339: def __init__(self, marker: str) -> None: Function `__init__` utility or script
function.
L370: def _from_markers(cls, markers: MarkerList) -> Marker: Function `_from_markers`
utility or script function.
L379: def __str__(self) -> str: Function `__str__` utility or script function.
L382: def __repr__(self) -> str: Function `__repr__` utility or script function.

```

```

L385: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L388: def __eq__(self, other: object) -> bool:    Object (singleton).
L394: def __getstate__(self) -> str:    Function `__getstate__` utility or script function.
L399: def __setstate__(self, state: object) -> None:    Object (singleton).
L423: def __and__(self, other: Marker) -> Marker:    Function `__and__` utility or script
function.
L428: def __or__(self, other: Marker) -> Marker:    Function `__or__` utility or script
function.
L433: def evaluate(    Function `evaluate` utility or script function.
L482: def _repair_python_full_version(    Function `_repair_python_full_version` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/specifiers.py

```

L48: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L52: def _validate_spec(spec: object, /) -> TypeGuard[tuple[str, str]]:    Object (singleton).
L61: def _validate_pre(pre: object, /) -> TypeGuard[bool | None]:    Object (singleton).
L74: def _trim_release(release: tuple[int, ...]) -> tuple[int, ...]:    Function
`_trim_release` utility or script function.
L82: class _BoundaryKind(enum.Enum):    Class (`_BoundaryKind`) component used by the app
(see file context: None).
L90: class _BoundaryVersion:    Class (`_BoundaryVersion`) component used by the app (see
file context: None).
L113: def __init__(self, version: Version, kind: _BoundaryKind) -> None:    Function
`__init__` utility or script function.
L118: def _is_family(self, other: Version) -> bool:    Function `_is_family` utility or
script function.
L133: def __eq__(self, other: object) -> bool:    Object (singleton).
L138: def __lt__(self, other: _BoundaryVersion | Version) -> bool:    Function `__lt__`
utility or script function.
L145: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L148: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L153: class _LowerBound:    Class (`_LowerBound`) component used by the app (see file
context: None).
L163: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:    Function
`__init__` utility or script function.
L167: def __eq__(self, other: object) -> bool:    Object (singleton).
L172: def __lt__(self, other: _LowerBound) -> bool:    Function `__lt__` utility or script
function.
L185: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L188: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L194: class _UpperBound:    Class (`_UpperBound`) component used by the app (see file
context: None).
L204: def __init__(self, version: _VersionOrBoundary, inclusive: bool) -> None:    Function
`__init__` utility or script function.
L208: def __eq__(self, other: object) -> bool:    Object (singleton).
L213: def __lt__(self, other: _UpperBound) -> bool:    Function `__lt__` utility or script
function.

```

```

L226: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L229: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L246: def _range_is_empty(lower: _LowerBound, upper: _UpperBound) -> bool:    Function
`_range_is_empty` utility or script function.
L255: def _intersect_ranges(    Function `_intersect_ranges` utility or script function.
L281: def _next_prefix_dev0(version: Version) -> Version:    Function `_next_prefix_dev0`
utility or script function.
L287: def _base_dev0(version: Version) -> Version:    Function `_base_dev0` utility or script
function.
L292: def _coerce_version(version: UnparsedVersion) -> Version | None:    Function
`_coerce_version` utility or script function.
L301: def _public_version(version: Version) -> Version:    Function `_public_version` utility
or script function.
L307: def _post_base(version: Version) -> Version:    Function `_post_base` utility or script
function.
L315: def _earliest_prerelease(version: Version) -> Version:    Function
`_earliest_prerelease` utility or script function.
L323: def _nearest_non_prerelease(    Function `_nearest_non_prerelease` utility or script
function.
L344: class InvalidSpecifier(ValueError):    Class (`InvalidSpecifier`) component used by the
app (see file context: None).
L356: class BaseSpecifier(metaclass=abc.ABCMeta):    Class (`BaseSpecifier`) component used
by the app (see file context: None).
L361: def _str(self) -> str:    Function `_str` utility or script function.
L366: def __str__(self) -> str:    Function `__str__` utility or script function.
L373: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L379: def __eq__(self, other: object) -> bool:    Object (singleton).
L389: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L397: def prereleases(self, value: bool) -> None:    Function `prereleases` utility or script
function.
L404: def contains(self, item: str, prereleases: bool | None = None) -> bool:    Function
`contains` utility or script function.
L410: def filter(    Function `filter` utility or script function.
L418: def filter(    Function `filter` utility or script function.
L426: def filter(    Function `filter` utility or script function.
L438: class Specifier(BaseSpecifier):    Class (`Specifier`) component used by the app (see
file context: None).
L573: def __init__(self, spec: str = "", prereleases: bool | None = None) -> None:    Function
`__init__` utility or script function.
L611: def _get_spec_version(self, version: str) -> Version | None:    Function
`_get_spec_version` utility or script function.
L623: def _require_spec_version(self, version: str) -> Version:    Function
`_require_spec_version` utility or script function.
L633: def _to_ranges(self) -> Sequence[_VersionRange]:    Function `_to_ranges` utility or
script function.
L657: def _wildcard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:    Function
`_wildcard_ranges` utility or script function.
L670: def _standard_ranges(self, op: str, ver_str: str) -> list[_VersionRange]:    Function
`_standard_ranges` utility or script function.
L733: def prereleases(self) -> bool | None:    Function `prereleases` utility or script

```

```

function.
L761: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility or
script function.
L764: def __getstate__(self) -> tuple[tuple[str, str], bool | None]:    Function
`__getstate__` utility or script function.
L770: def __setstate__(self, state: object) -> None:    Object (singleton).
L805: def operator(self) -> str:    Function `operator` utility or script function.
L814: def version(self) -> str:    Function `version` utility or script function.
L822: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L840: def __str__(self) -> str:    Function `__str__` utility or script function.
L851: def _canonical_spec(self) -> tuple[str, str]:    Function `_canonical_spec` utility or
script function.
L864: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L867: def __eq__(self, other: object) -> bool:    Object (singleton).
L896: def _get_operator(self, op: str) -> CallableOperator:    Function `_get_operator`
utility or script function.
L902: def _compare_compatible(self, prospective: Version, spec: str) -> bool:    Function
`_compare_compatible` utility or script function.
L922: def _get_wildcard_split(self, spec: str) -> tuple[list[str], int]:    Function
`_get_wildcard_split` utility or script function.
L938: def _compare_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_equal` utility or script function.
L974: def _compare_not_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_not_equal` utility or script function.
L977: def _compare_less_than_equal(self, prospective: Version, spec: str) -> bool:    Function
`_compare_less_than_equal` utility or script function.
L983: def _compare_greater_than_equal(self, prospective: Version, spec: str) -> bool:
Function `_compare_greater_than_equal` utility or script function.
L989: def _compare_less_than(self, prospective: Version, spec_str: str) -> bool:    Function
`_compare_less_than` utility or script function.
L1014: def _compare_greater_than(self, prospective: Version, spec_str: str) -> bool:
Function `_compare_greater_than` utility or script function.
L1046: def _compare_arbitrary(self, prospective: Version | str, spec: str) -> bool:
Function `_compare_arbitrary` utility or script function.
L1049: def __contains__(self, item: str | Version) -> bool:    Function `__contains__`
utility or script function.
L1070: def contains(self, item: UnparsedVersion, prereleases: bool | None = None) -> bool:
Function `contains` utility or script function.
L1098: def filter(    Function `filter` utility or script function.
L1106: def filter(    Function `filter` utility or script function.
L1113: def filter(    Function `filter` utility or script function.
L1198: def _pep440_filter_prereleases(    Function `_pep440_filter_prereleases` utility or
script function.
L1240: def _version_split(version: str) -> list[str]:    Function `_version_split` utility or
script function.
L1262: def _version_join(components: list[str]) -> str:    Function `_version_join` utility
or script function.
L1273: def _is_not_suffix(segment: str) -> bool:    Function `_is_not_suffix` utility or
script function.
L1279: def _numeric_prefix_len(split: list[str]) -> int:    Function `_numeric_prefix_len`
utility or script function.

```

```

L1293: def _left_pad(split: list[str], target_numeric_len: int) -> list[str]:    Function
`_left_pad` utility or script function.
L1307: def _operator_cost(op_entry: tuple[CallableOperator, str, str]) -> int:    Function
`_operator_cost` utility or script function.
L1334: class SpecifierSet(BaseSpecifier):    Class (`SpecifierSet`) component used by the app
(see file context: None).
L1362: def __init__(    Function `__init__` utility or script function.
L1407: def _canonical_specs(self) -> tuple[Specifier, ...]:    Function `_canonical_specs`
utility or script function.
L1417: def prereleases(self) -> bool | None:    Function `prereleases` utility or script
function.
L1437: def prereleases(self, value: bool | None) -> None:    Function `prereleases` utility
or script function.
L1441: def __getstate__(self) -> tuple[tuple[Specifier, ...], bool | None]:    Function
`__getstate__` utility or script function.
L1447: def __setstate__(self, state: object) -> None:    Object (singleton).
L1504: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L1525: def __str__(self) -> str:    Function `__str__` utility or script function.
L1538: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L1541: def __and__(self, other: SpecifierSet | str) -> SpecifierSet:    Function `__and__`
utility or script function.
L1574: def __eq__(self, other: object) -> bool:    Object (singleton).
L1600: def __len__(self) -> int:    Function `__len__` utility or script function.
L1604: def __iter__(self) -> Iterator[Specifier]:    Function `__iter__` utility or script
function.
L1614: def _get_ranges(self) -> Sequence[_VersionRange]:    Function `_get_ranges` utility or
script function.
L1636: def is_unsatisfiable(self) -> bool:    Function `is_unsatisfiable` utility or script
function.
L1669: def _check_prerelease_only_ranges(self) -> bool:    Function
`_check_prerelease_only_ranges` utility or script function.
L1682: def _check_arbitrary_unsatisfiable(self) -> bool:    Function
`_check_arbitrary_unsatisfiable` utility or script function.
L1721: def __contains__(self, item: UnparsedVersion) -> bool:    Function `__contains__`
utility or script function.
L1742: def contains(    Function `contains` utility or script function.
L1788: def filter(    Function `filter` utility or script function.
L1796: def filter(    Function `filter` utility or script function.
L1803: def filter(    Function `filter` utility or script function.
L1899: def _filter_versions(    Function `_filter_versions` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/dependency _groups.py

```

L19: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L28: class DuplicateGroupNames(ValueError):    Class (`DuplicateGroupNames`) component used
by the app (see file context: None).
L34: class CyclicDependencyGroup(ValueError):    Class (`CyclicDependencyGroup`) component

```

```

used by the app (see file context: None).
L39: def __init__(self, requested_group: str, group: str, include_group: str) -> None:
Function `__init__` utility or script function.
L57: class InvalidDependencyGroupObject(ValueError):    Class (`InvalidDependencyGroupObject`)
    component used by the app (see file context: None).
L69: class DependencyGroupInclude:    Class (`DependencyGroupInclude`)    component used by the
app (see file context: None).
L72: def __init__(self, include_group: str) -> None:    Function `__init__` utility or script
function.
L80: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L84: class DependencyGroupResolver:    Class (`DependencyGroupResolver`)    component used by
the app (see file context: None).
L96: def __init__(    Function `__init__` utility or script function.
L115: def lookup(self, group: str) -> tuple[Requirement | DependencyGroupInclude, ...]:
Function `lookup` utility or script function.
L129: def resolve(self, group: str) -> tuple[Requirement, ...]:    Function `resolve` utility
or script function.
L142: def _resolve(    Function `_resolve` utility or script function.
L200: def _parse_group(    Function `_parse_group` utility or script function.
L255: def resolve_dependency_groups(    Function `resolve_dependency_groups` utility or
script function.
L277: def _normalize_name(name: str) -> str:    Function `_normalize_name` utility or script
function.
L281: def _normalize_group_names(    Function `_normalize_group_names` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_tokenizer.p **y**

```

L12: class Token:    Class (`Token`)    component used by the app (see file context: None).
L18: class ParserSyntaxError(Exception):    Class (`ParserSyntaxError`)    component used by the
app (see file context: None).
L21: def __init__(    Function `__init__` utility or script function.
L34: def __str__(self) -> str:    Function `__str__` utility or script function.
L91: class Tokenizer:    Class (`Tokenizer`)    component used by the app (see file context:
None).
L98: def __init__(    Function `__init__` utility or script function.
L109: def consume(self, name: str) -> None:    Function `consume` utility or script function.
L114: def check(self, name: str, *, peek: bool = False) -> bool:    Function `check` utility
or script function.
L135: def expect(self, name: str, *, expected: str) -> Token:    Function `expect` utility or
script function.
L144: def read(self) -> Token:    Function `read` utility or script function.
L154: def raise_syntax_error(    Function `raise_syntax_error` utility or script function.
L173: def enclosing_tokens(    Function `enclosing_tokens` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_parser.py

```

L15: class Node:    Class (`Node`)    component used by the app (see file context: None).
L18: def __init__(self, value: str) -> None:    Function `__init__`    utility or script
function.
L21: def __str__(self) -> str:    Function `__str__`    utility or script function.
L24: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L27: def serialize(self) -> str:    Function `serialize`    utility or script function.
L30: def __getstate__(self) -> str:    Function `__getstate__`    utility or script function.
L34: def _restore_value(self, value: object) -> None:    Object (singleton).
L41: def __setstate__(self, state: object) -> None:    Object (singleton).
L59: class Variable(Node):    Class (`Variable`)    component used by the app (see file context:
None).
L62: def serialize(self) -> str:    Function `serialize`    utility or script function.
L66: class Value(Node):    Class (`Value`)    component used by the app (see file context:
None).
L69: def serialize(self) -> str:    Function `serialize`    utility or script function.
L73: class Op(Node):    Class (`Op`)    component used by the app (see file context: None).
L76: def serialize(self) -> str:    Function `serialize`    utility or script function.
L87: class ParsedRequirement(NamedTuple):    Class (`ParsedRequirement`)    component used by
the app (see file context: None).
L98: def parse_requirement(source: str) -> ParsedRequirement:    Function `parse_requirement`
utility or script function.
L102: def _parse_requirement(tokenizer: Tokenizer) -> ParsedRequirement:    Function
`_parse_requirement`    utility or script function.
L123: def _parse_requirement_details(    Function `_parse_requirement_details`    utility or
script function.
L176: def _parse_requirement_marker(    Function `_parse_requirement_marker`    utility or
script function.
L197: def _parse_extras(tokenizer: Tokenizer) -> list[str]:    Function `_parse_extras`
utility or script function.
L216: def _parse_extras_list(tokenizer: Tokenizer) -> list[str]:    Function
`_parse_extras_list`    utility or script function.
L243: def _parse_specifier(tokenizer: Tokenizer) -> str:    Function `_parse_specifier`
utility or script function.
L260: def _parse_version_many(tokenizer: Tokenizer) -> str:    Function `_parse_version_many`
utility or script function.
L292: def parse_marker(source: str) -> MarkerList:    Function `parse_marker`    utility or
script function.
L296: def _parse_full_marker(tokenizer: Tokenizer) -> MarkerList:    Function
`_parse_full_marker`    utility or script function.
L302: def _parse_marker(tokenizer: Tokenizer) -> MarkerList:    Function `_parse_marker`
utility or script function.
L314: def _parse_marker_atom(tokenizer: Tokenizer) -> MarkerAtom:    Function
`_parse_marker_atom`    utility or script function.
L336: def _parse_marker_item(tokenizer: Tokenizer) -> MarkerItem:    Function
`_parse_marker_item`    utility or script function.
L350: def _parse_marker_var(tokenizer: Tokenizer) -> MarkerVar:    # noqa: RET503    Function
`_parse_marker_var`    utility or script function.
L364: def process_env_var(env_var: str) -> Variable:    Function `process_env_var`    utility or

```



```

script function.
L371: def process_python_str(python_str: str) -> Value:    Function `process_python_str`
utility or script function.
L376: def _parse_marker_op(tokenizer: Tokenizer) -> Op:    Function `_parse_marker_op`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/utils.py

```

L27: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L39: class InvalidName(ValueError):    Class (`InvalidName`)    component used by the app (see
file context: None).
L45: class InvalidWheelFilename(ValueError):    Class (`InvalidWheelFilename`)    component used
by the app (see file context: None).
L51: class InvalidSdistFilename(ValueError):    Class (`InvalidSdistFilename`)    component used
by the app (see file context: None).
L66: def canonicalize_name(name: str, *, validate: bool = False) -> NormalizedName:
Function `canonicalize_name`    utility or script function.
L103: def is_normalized_name(name: str) -> bool:    Function `is_normalized_name`    utility or
script function.
L119: def canonicalize_version(    Function `canonicalize_version`    utility or script
function.
L157: def parse_wheel_filename(    Function `parse_wheel_filename`    utility or script
function.
L249: def parse_sdist_filename(filename: str) -> tuple[NormalizedName, Version]:    Function
`parse_sdist_filename`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/version.py

```

L37: def _deprecated(message: str) -> object:    Object (singleton).
L38: def decorator(func: Callable[[...], object]) -> object:    Object (singleton).
L40: def wrapper(*args: object, **kwargs: object) -> object:    Object (singleton).
L66: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L81: class _VersionReplace(TypedDict, total=False):    Class (`_VersionReplace`)    component
used by the app (see file context: None).
L90: def normalize_pre(letter: str, /) -> str:    Function `normalize_pre`    utility or script
function.
L111: def parse(version: str) -> Version:    Function `parse`    utility or script function.
L125: class InvalidVersion(ValueError):    Class (`InvalidVersion`)    component used by the app
(see file context: None).
L135: class _BaseVersion:    Class (`_BaseVersion`)    component used by the app (see file
context: None).
L144: def _key(self) -> tuple[Any, ...]: ...    Function `_key`    utility or script function.
L146: def __hash__(self) -> int:    Function `__hash__`    utility or script function.
L152: def __lt__(self, other: _BaseVersion) -> bool:    Function `__lt__`    utility or script
function.
L158: def __le__(self, other: _BaseVersion) -> bool:    Function `__le__`    utility or script

```



```

function.
L164: def __eq__(self, other: object) -> bool:    Object (singleton).
L170: def __ge__(self, other: _BaseVersion) -> bool:    Function `__ge__` utility or script
function.
L176: def __gt__(self, other: _BaseVersion) -> bool:    Function `__gt__` utility or script
function.
L182: def __ne__(self, other: object) -> bool:    Object (singleton).
L266: def _validate_epoch(value: object, /) -> int:    Object (singleton).
L274: def _validate_release(value: object, /) -> tuple[int, ...]:    Object (singleton).
L286: def _validate_pre(value: object, /) -> tuple[Literal["a", "b", "rc"], int] | None:
Object (singleton).
L299: def _validate_post(value: object, /) -> tuple[Literal["post"], int] | None:    Object
(singleton).
L308: def _validate_dev(value: object, /) -> tuple[Literal["dev"], int] | None:    Object
(singleton).
L317: def _validate_local(value: object, /) -> LocalType | None:    Object (singleton).
L327: class _Version(NamedTuple):    Class (`_Version`) component used by the app (see file
context: None).
L336: class Version(_BaseVersion):    Class (`Version`) component used by the app (see file
context: None).
L404: def __init__(self, version: str) -> None:    Function `__init__` utility or script
function.
L455: def from_parts(    Function `from_parts` utility or script function.
L501: def __replace__(self, **kwargs: Unpack[_VersionReplace]) -> Self:    Function
`__replace__` utility or script function.
L560: def _key(self) -> CmpKey:    Function `_key` utility or script function.
L574: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L592: def __lt__(self, other: _BaseVersion) -> bool:    Function `__lt__` utility or script
function.
L619: def __le__(self, other: _BaseVersion) -> bool:    Function `__le__` utility or script
function.
L646: def __eq__(self, other: object) -> bool:    Object (singleton).
L673: def __ge__(self, other: _BaseVersion) -> bool:    Function `__ge__` utility or script
function.
L700: def __gt__(self, other: _BaseVersion) -> bool:    Function `__gt__` utility or script
function.
L727: def __ne__(self, other: object) -> bool:    Object (singleton).
L754: def __getstate__(    Function `__getstate__` utility or script function.
L776: def __setstate__(self, state: object) -> None:    Object (singleton).
L823: def _version(self) -> _Version:    Function `_version` utility or script function.
L830: def _version(self, value: _Version) -> None:    Function `_version` utility or script
function.
L840: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L848: def __str__(self) -> str:    Function `__str__` utility or script function.
L880: def _str(self) -> str:    Function `_str` utility or script function.
L885: def epoch(self) -> int:    Function `epoch` utility or script function.
L896: def release(self) -> tuple[int, ...]:    Function `release` utility or script function.
L912: def pre(self) -> tuple[Literal["a", "b", "rc"], int] | None:    Function `pre` utility
or script function.
L927: def post(self) -> int | None:    Function `post` utility or script function.
L938: def dev(self) -> int | None:    Function `dev` utility or script function.

```

```

L949: def local(self) -> str | None:    Function `local` utility or script function.
L963: def public(self) -> str:    Function `public` utility or script function.
L979: def base_version(self) -> str:    Function `base_version` utility or script function.
L1000: def is_prerelease(self) -> bool:    Function `is_prerelease` utility or script
function.
L1017: def is_postrelease(self) -> bool:    Function `is_postrelease` utility or script
function.
L1028: def is_devrelease(self) -> bool:    Function `is_devrelease` utility or script
function.
L1039: def major(self) -> int:    Function `major` utility or script function.
L1048: def minor(self) -> int:    Function `minor` utility or script function.
L1059: def micro(self) -> int:    Function `micro` utility or script function.
L1070: class _TrimmedRelease(Version):    Class (`_TrimmedRelease`) component used by the app
(see file context: None).
L1073: def __init__(self, version: str | Version) -> None:    Function `__init__` utility or
script function.
L1086: def release(self) -> tuple[int, ...]:    Function `release` utility or script
function.
L1104: def _parse_letter_version(    Function `_parse_letter_version` utility or script
function.
L1131: def _parse_local_version(local: str | None) -> LocalType | None:    Function
`_parse_local_version` utility or script function.
L1157: def _cmpkey(    Function `_cmpkey` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_structures.py

```

L18: class InfinityType:    Class (`InfinityType`) component used by the app (see file
context: None).
L21: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L25: class NegativeInfinityType:    Class (`NegativeInfinityType`) component used by the app
(see file context: None).
L28: def __repr__(self) -> str:    Function `__repr__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/tags.py

```

L54: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L75: def _compute_32_bit_interpreter() -> bool:    Function `_compute_32_bit_interpreter`
utility or script function.
L82: class UnsortedTagsError(ValueError):    Class (`UnsortedTagsError`) component used by
the app (see file context: None).
L88: class Tag:    Class (`Tag`) component used by the app (see file context: None).
L108: def __init__(self, interpreter: str, abi: str, platform: str) -> None:    Function
`__init__` utility or script function.
L128: def interpreter(self) -> str:    Function `interpreter` utility or script function.
L137: def abi(self) -> str:    Function `abi` utility or script function.

```

```

L144: def platform(self) -> str:    Function `platform` utility or script function.
L150: def __eq__(self, other: object) -> bool:    Object (singleton).
L161: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L164: def __str__(self) -> str:    Function `__str__` utility or script function.
L167: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L170: def __getstate__(self) -> tuple[str, str, str]:    Function `__getstate__` utility or
script function.
L175: def __setstate__(self, state: object) -> None:    Object (singleton).
L203: def parse_tag(tag: str, *, validate_order: bool = False) -> frozenset[Tag]:    Function
`parse_tag` utility or script function.
L240: def _get_config_var(name: str, warn: bool = False) -> int | str | None:    Function
`_get_config_var` utility or script function.
L249: def _normalize_string(string: str) -> str:    Function `_normalize_string` utility or
script function.
L253: def _is_threaded_cpython(abis: list[str]) -> bool:    Function `_is_threaded_cpython`
utility or script function.
L269: def _abi3_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3_applies` utility or script function.
L279: def _abi3t_applies(python_version: PythonVersion, threading: bool) -> bool:    Function
`_abi3t_applies` utility or script function.
L292: def _cpython_abis(py_version: PythonVersion, warn: bool = False) -> list[str]:
Function `_cpython_abis` utility or script function.
L325: def cpython_tags(    Function `cpython_tags` utility or script function.
L404: def _generic_abi() -> list[str]:    Function `_generic_abi` utility or script function.
L445: def generic_tags(    Function `generic_tags` utility or script function.
L486: def _py_interpreter_range(py_version: PythonVersion) -> Iterator[str]:    Function
`_py_interpreter_range` utility or script function.
L501: def compatible_tags(    Function `compatible_tags` utility or script function.
L536: def _mac_arch(arch: str, is_32bit: bool = _32_BIT_INTERPRETER) -> str:    Function
`_mac_arch` utility or script function.
L546: def _mac_binary_formats(version: AppleVersion, cpu_arch: str) -> list[str]:    Function
`_mac_binary_formats` utility or script function.
L578: def mac_platforms(    Function `mac_platforms` utility or script function.
L667: def ios_platforms(    Function `ios_platforms` utility or script function.
L729: def android_platforms(    Function `android_platforms` utility or script function.
L766: def _linux_platforms(is_32bit: bool = _32_BIT_INTERPRETER) -> Iterator[str]:    Function
`_linux_platforms` utility or script function.
L785: def _emscripten_platforms() -> Iterator[str]:    Function `_emscripten_platforms`
utility or script function.
L794: def _generic_platforms() -> Iterator[str]:    Function `_generic_platforms` utility or
script function.
L798: def platform_tags() -> Iterator[str]:    Function `platform_tags` utility or script
function.
L816: def interpreter_name() -> str:    Function `interpreter_name` utility or script
function.
L829: def interpreter_version(*, warn: bool = False) -> str:    Function `interpreter_version`
utility or script function.
L841: def _version_nodot(version: PythonVersion) -> str:    Function `_version_nodot` utility
or script function.
L845: def sys_tags(*, warn: bool = False) -> Iterator[Tag]:    Function `sys_tags` utility or
script function.

```

```
L889: def create_compatible_tags_selector(    Function `create_compatible_tags_selector`
Creates a resource or document.
L919: def selector(    Function `selector`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/errors.py

```
L11: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L19: class ExceptionGroup(Exception):    Class (`ExceptionGroup`)    component used by the app
(see file context: None).
L29: def __init__(self, message: str, exceptions: list[Exception]) -> None:    Function
`__init__`    utility or script function.
L33: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L38: class _ErrorCollector:    Class (`_ErrorCollector`)    component used by the app (see file
context: None).
L59: def finalize(self, msg: str) -> None:    Function `finalize`    utility or script function.
L65: def on_exit(self, msg: str) -> typing.Generator[_ErrorCollector, None, None]:    Function
`on_exit`    utility or script function.
L75: def collect(self, *err_cls: type[Exception]) -> typing.Generator[None, None, None]:
Function `collect`    utility or script function.
L89: def error(    Function `error`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/_musllinux.py

```
L18: class _MuslVersion(NamedTuple):    Class (`_MuslVersion`)    component used by the app (see
file context: None).
L23: def _parse_musl_version(output: str) -> _MuslVersion | None:    Function
`_parse_musl_version`    utility or script function.
L34: def _get_musl_version(executable: str) -> _MuslVersion | None:    Function
`_get_musl_version`    utility or script function.
L56: def platform_tags(archs: Sequence[str]) -> Iterator[str]:    Function `platform_tags`
utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/requirements.py

```
L20: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
L24: class InvalidRequirement(ValueError):    Class (`InvalidRequirement`)    component used by
the app (see file context: None).
L30: class Requirement:    Class (`Requirement`)    component used by the app (see file context:
None).
L53: def __init__(self, requirement_string: str) -> None:    Function `__init__`    utility or
script function.
```

```

L68: def _iter_parts(self, name: str) -> Iterator[str]:    Function `_iter_parts` utility or
script function.
L86: def __getstate__(self) -> str:    Function `__getstate__` utility or script function.
L91: def __setstate__(self, state: object) -> None:    Object (singleton).
L110: def __str__(self) -> str:    Function `__str__` utility or script function.
L113: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L116: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L119: def __eq__(self, other: object) -> bool:    Object (singleton).

```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/pylock.py

```

L54: def __dir__() -> list[str]:    Function `__dir__` utility or script function.
L62: class _FromMappingProtocol(Protocol):    # pragma: no cover    Class
(`_FromMappingProtocol`) component used by the app (see file context: None).
L64: def _from_dict(cls, d: Mapping[str, Any]) -> Self: ...    Function `_from_dict` utility
or script function.
L73: def is_valid_pylock_path(path: Path) -> bool:    Function `is_valid_pylock_path` utility
or script function.
L78: def _toml_key(key: str) -> str:    Function `_toml_key` utility or script function.
L82: def _toml_value(key: str, value: Any) -> Any:    # noqa: ANN401    Function `_toml_value`
utility or script function.
L90: def _toml_dict_factory(data: list[tuple[str, Any]]) -> dict[str, Any]:    Function
`_toml_dict_factory` utility or script function.
L98: def _get(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T | None:
Function `_get` utility or script function.
L111: def _get_required(d: Mapping[str, Any], expected_type: type[_T], key: str) -> _T:
Function `_get_required` utility or script function.
L118: def _get_sequence(    Function `_get_sequence` utility or script function.
L140: def _get_as(    Function `_get_as` utility or script function.
L159: def _get_required_as(    Function `_get_required_as` utility or script function.
L172: def _get_sequence_as(    Function `_get_sequence_as` utility or script function.
L191: def _get_object(    Function `_get_object` utility or script function.
L203: def _get_sequence_of_objects(    Function `_get_sequence_of_objects` utility or script
function.
L219: def _get_required_sequence_of_objects(    Function `_get_required_sequence_of_objects`
utility or script function.
L229: def _validate_normalized_name(name: str) -> NormalizedName:    Function
`_validate_normalized_name` utility or script function.
L236: def _validate_path_url(path: str | None, url: str | None) -> None:    Function
`_validate_path_url` utility or script function.
L241: def _path_name(path: str | None) -> str | None:    Function `_path_name` utility or
script function.
L254: def _url_name(url: str | None) -> str | None:    Function `_url_name` utility or script
function.
L261: def _validate_hashes(hashes: Mapping[str, Any]) -> Mapping[str, Any]:    Function
`_validate_hashes` utility or script function.
L269: class PylockValidationError(Exception):    Class (`PylockValidationError`) component
used by the app (see file context: None).

```

```

L275: def __init__(    Function `__init__`    utility or script function.
L293: def __str__(self) -> str:    Function `__str__`    utility or script function.
L299: class _PylockRequiredKeyError(PylockValidationError):    Class
(`_PylockRequiredKeyError`)    component used by the app (see file context: None).
L300: def __init__(self, key: str) -> None:    Function `__init__`    utility or script
function.
L304: class PylockUnsupportedVersionError(PylockValidationError):    Class
(`PylockUnsupportedVersionError`)    component used by the app (see file context: None).
L308: class PylockSelectError(Exception):    Class (`PylockSelectError`)    component used by
the app (see file context: None).
L313: class PackageVcs:    Class (`PackageVcs`)    component used by the app (see file context:
None).
L321: def __init__(    Function `__init__`    utility or script function.
L340: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L354: class PackageDirectory:    Class (`PackageDirectory`)    component used by the app (see
file context: None).
L359: def __init__(    Function `__init__`    utility or script function.
L372: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L381: class PackageArchive:    Class (`PackageArchive`)    component used by the app (see file
context: None).
L389: def __init__(    Function `__init__`    utility or script function.
L408: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L422: class PackageSdist:    Class (`PackageSdist`)    component used by the app (see file
context: None).
L430: def __init__(    Function `__init__`    utility or script function.
L449: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L462: def filename(self) -> str:    Function `filename`    utility or script function.
L471: class PackageWheel:    Class (`PackageWheel`)    component used by the app (see file
context: None).
L479: def __init__(    Function `__init__`    utility or script function.
L498: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L511: def filename(self) -> str:    Function `filename`    utility or script function.
L520: class Package:    Class (`Package`)    component used by the app (see file context: None).
L535: def __init__(    Function `__init__`    utility or script function.
L568: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L649: def is_direct(self) -> bool:    Function `is_direct`    utility or script function.
L654: class Pylock:    Class (`Pylock`)    component used by the app (see file context: None).
L667: def __init__(    Function `__init__`    utility or script function.
L692: def _from_dict(cls, d: Mapping[str, Any]) -> Self:    Function `_from_dict`    utility or
script function.
L715: def from_dict(cls, d: Mapping[str, Any], /) -> Self:    Function `from_dict`    utility or
script function.
L723: def to_dict(self) -> Mapping[str, Any]:    Function `to_dict`    utility or script
function.
L727: def validate(self) -> None:    Function `validate`    utility or script function.

```

```
L733: def select(    Function `select`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/_spdx.py

```
L6: class SPDXLicense(TypedDict):    Class (`SPDXLicense`)    component used by the app (see file context: None).
```

```
L10: class SPDXException(TypedDict):    Class (`SPDXException`)    component used by the app (see file context: None).
```

.venv/lib/python3.12/site-packages/pip/_vendor/packaging/licenses/__init__.py

```
L47: def __dir__() -> list[str]:    Function `__dir__`    utility or script function.
```

```
L60: class InvalidLicenseExpression(ValueError):    Class (`InvalidLicenseExpression`)    component used by the app (see file context: None).
```

```
L71: def canonicalize_license_expression(    Function `canonicalize_license_expression`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_impl.py

```
L16: class SubprocessRunner(Protocol):    Class (`SubprocessRunner`)    component used by the app (see file context: None).
```

```
L19: def __call__(    Function `__call__`    utility or script function.
```

```
L28: def write_json(obj: Mapping[str, Any], path: str, **kwargs) -> None:    Function `write_json`    utility or script function.
```

```
L33: def read_json(path: str) -> Mapping[str, Any]:    Function `read_json`    utility or script function.
```

```
L38: class BackendUnavailable(Exception):    Class (`BackendUnavailable`)    component used by the app (see file context: None).
```

```
L41: def __init__(    Function `__init__`    utility or script function.
```

```
L55: class HookMissing(Exception):    Class (`HookMissing`)    component used by the app (see file context: None).
```

```
L58: def __init__(self, hook_name: str) -> None:    Function `__init__`    utility or script function.
```

```
L63: class UnsupportedOperation(Exception):    Class (`UnsupportedOperation`)    component used by the app (see file context: None).
```

```
L66: def __init__(self, traceback: str) -> None:    Function `__init__`    utility or script function.
```

```
L70: def default_subprocess_runner(    Function `default_subprocess_runner`    utility or script function.
```

```

L86: def quiet_subprocess_runner(    Function `quiet_subprocess_runner`    utility or script
function.
L102: def norm_and_check(source_tree: str, requested: str) -> str:    Function
`norm_and_check`    utility or script function.
L126: class BuildBackendHookCaller:    Class (`BuildBackendHookCaller`)    component used by the
app (see file context: None).
L129: def __init__(    Function `__init__`    utility or script function.
L159: def subprocess_runner(self, runner: "SubprocessRunner") -> Iterator[None]:    Function
`subprocess_runner`    utility or script function.
L178: def _supported_features(self) -> Sequence[str]:    Function `_supported_features`
utility or script function.
L182: def get_requires_for_build_wheel(    Function `get_requires_for_build_wheel`    Returns or
fetches data.
L200: def prepare_metadata_for_build_wheel(    Function `prepare_metadata_for_build_wheel`
utility or script function.
L233: def build_wheel(    Function `build_wheel`    Constructs or prepares an object.
L265: def get_requires_for_build_editable(    Function `get_requires_for_build_editable`
Returns or fetches data.
L283: def prepare_metadata_for_build_editable(    Function
`prepare_metadata_for_build_editable`    utility or script function.
L315: def build_editable(    Function `build_editable`    Constructs or prepares an object.
L348: def get_requires_for_build_sdist(    Function `get_requires_for_build_sdist`    Returns or
fetches data.
L360: def build_sdist(    Function `build_sdist`    Constructs or prepares an object.
L378: def _call_hook(self, hook_name: str, kwargs: Mapping[str, Any]) -> Any:    Function
`_call_hook`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/_in_process.py

```

L31: def write_json(obj, path, **kwargs):    Function `write_json`    utility or script
function.
L36: def read_json(path):    Function `read_json`    utility or script function.
L41: class BackendUnavailable(Exception):    Class (`BackendUnavailable`)    component used by
the app (see file context: None).
L44: def __init__(self, message, traceback=None):    Function `__init__`    utility or script
function.
L50: class HookMissing(Exception):    Class (`HookMissing`)    component used by the app (see
file context: None).
L53: def __init__(self, hook_name=None):    Function `__init__`    utility or script function.
L58: def _build_backend():    Function `_build_backend`    utility or script function.
L81: class _BackendPathFinder:    Class (`_BackendPathFinder`)    component used by the app (see
file context: None).
L89: def __init__(self, backend_path, backend_module):    Function `__init__`    utility or
script function.
L94: def find_spec(self, fullname, _path, _target=None):    Function `find_spec`    utility or
script function.
L111: def find_distributions(self, context=None):    Function `find_distributions`    utility or

```



```

script function.
L119: def _supported_features():    Function `_supported_features` utility or script
function.
L132: def get_requires_for_build_wheel(config_settings):    Function
`get_requires_for_build_wheel` Returns or fetches data.
L146: def get_requires_for_build_editable(config_settings):    Function
`get_requires_for_build_editable` Returns or fetches data.
L160: def prepare_metadata_for_build_wheel(    Function `prepare_metadata_for_build_wheel`
utility or script function.
L184: def prepare_metadata_for_build_editable(    Function
`prepare_metadata_for_build_editable` utility or script function.
L215: def _dist_info_files(whl_zip):    Function `_dist_info_files` utility or script
function.
L227: def _get_wheel_metadata_from_wheel(whl_basename, metadata_directory, config_settings):
Function `_get_wheel_metadata_from_wheel` utility or script function.
L245: def _find_already_built_wheel(metadata_directory):    Function
`_find_already_built_wheel` utility or script function.
L268: def build_wheel(wheel_directory, config_settings, metadata_directory=None):    Function
`build_wheel` Constructs or prepares an object.
L285: def build_editable(wheel_directory, config_settings, metadata_directory=None):
Function `build_editable` Constructs or prepares an object.
L306: def get_requires_for_build_sdist(config_settings):    Function
`get_requires_for_build_sdist` Returns or fetches data.
L320: class _DummyException(Exception):    Class (`_DummyException`) component used by the
app (see file context: None).
L324: class GotUnsupportedOperation(Exception):    Class (`GotUnsupportedOperation`)
component used by the app (see file context: None).
L327: def __init__(self, traceback):    Function `__init__` utility or script function.
L331: def build_sdist(sdist_directory, config_settings):    Function `build_sdist` Constructs
or prepares an object.
L353: def main():    Function `main` Entry point / main routine.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pyproject_hooks/_in_process/_init__.py

```

L13: def _in_proc_script_path():    Function `_in_proc_script_path` utility or script
function.
L18: def _in_proc_script_path():    Function `_in_proc_script_path` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_ssl_constants.py

```

L28: def _set_ssl_context_verify_mode(    Function `_set_ssl_context_verify_mode` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_windows.py

```

L39: class CERT_CONTEXT(Structure):    Class (`CERT_CONTEXT`) component used by the app (see
file context: None).
L53: class CERT_ENHKEY_USAGE(Structure):    Class (`CERT_ENHKEY_USAGE`) component used by the
app (see file context: None).
L63: class CERT_USAGE_MATCH(Structure):    Class (`CERT_USAGE_MATCH`) component used by the
app (see file context: None).
L70: class CERT_CHAIN_PARA(Structure):    AI-related component (`CERT_CHAIN_PARA`)
coordinates AI/LLM interactions.
L90: class CERT_TRUST_STATUS(Structure):    Class (`CERT_TRUST_STATUS`) component used by the
app (see file context: None).
L97: class CERT_CHAIN_ELEMENT(Structure):    AI-related component (`CERT_CHAIN_ELEMENT`)
coordinates AI/LLM interactions.
L112: class CERT_SIMPLE_CHAIN(Structure):    AI-related component (`CERT_SIMPLE_CHAIN`)
coordinates AI/LLM interactions.
L127: class CERT_CHAIN_CONTEXT(Structure):    AI-related component (`CERT_CHAIN_CONTEXT`)
coordinates AI/LLM interactions.
L144: class SSL_EXTRA_CERT_CHAIN_POLICY_PARA(Structure):    AI-related component
(`SSL_EXTRA_CERT_CHAIN_POLICY_PARA`) coordinates AI/LLM interactions.
L153: class CERT_CHAIN_POLICY_PARA(Structure):    AI-related component
(`CERT_CHAIN_POLICY_PARA`) coordinates AI/LLM interactions.
L164: class CERT_CHAIN_POLICY_STATUS(Structure):    AI-related component
(`CERT_CHAIN_POLICY_STATUS`) coordinates AI/LLM interactions.
L177: class CERT_CHAIN_ENGINE_CONFIG(Structure):    AI-related component
(`CERT_CHAIN_ENGINE_CONFIG`) coordinates AI/LLM interactions.
L238: def _handle_win_error(result: bool, _: Any, args: Any) -> Any:    Function
`_handle_win_error` utility or script function.
L323: def _verify_peercerts_impl(    Function `_verify_peercerts_impl` utility or script
function.
L415: def _get_and_verify_cert_chain(    Function `_get_and_verify_cert_chain` utility or
script function.
L505: def _verify_using_custom_ca_certs(    Function `_verify_using_custom_ca_certs` utility
or script function.
L558: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:    Function
`_configure_context` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_api.py

```

L34: def inject_into_ssl() -> None:    Function `inject_into_ssl` utility or script function.
L66: def extract_from_ssl() -> None:    Function `extract_from_ssl` utility or script
function.
L77: class SSLContext(_truststore_SSLContext_super_class):    # type: ignore[misc]    Class
(`SSLContext`) component used by the app (see file context: None).
L81: def __class__(self) -> type:    Function `__class__` utility or script function.
L87: def __init__(self, protocol: int = None) -> None:    # type: ignore[assignment]    Function
`__init__` utility or script function.
L91: class TruststoreSSLObject(ssl.SSLObject):    Class (`TruststoreSSLObject`) component

```

used by the app (see file context: None).

L96: def do_handshake(self) -> None: Function `do\_handshake` utility or script function.

L103: def wrap_socket(Function `wrap\_socket` utility or script function.

L136: def wrap_bio(Function `wrap\_bio` utility or script function.

L154: def load_verify_locations(Function `load\_verify\_locations` Loads data from storage or remote.

L164: def load_cert_chain(Function `load\_cert\_chain` Loads data from storage or remote.

L174: def load_default_certs(Function `load\_default\_certs` Loads data from storage or remote.

L179: def set_alpn_protocols(self, alpn_protocols: typing.Iterable[str]) -> None: Function `set\_alpn\_protocols` Sets or updates a value.

L182: def set_npn_protocols(self, npn_protocols: typing.Iterable[str]) -> None: Function `set\_npn\_protocols` Sets or updates a value.

L185: def set_ciphers(self, __cipherlist: str) -> None: Function `set\_ciphers` Sets or updates a value.

L188: def get_ciphers(self) -> typing.Any: Function `get\_ciphers` Returns or fetches data.

L191: def session_stats(self) -> dict[str, int]: Function `session\_stats` utility or script function.

L194: def cert_store_stats(self) -> dict[str, int]: Function `cert\_store\_stats` utility or script function.

L197: def set_default_verify_paths(self) -> None: Function `set\_default\_verify\_paths` Sets or updates a value.

L201: def get_ca_certs(Function `get\_ca\_certs` Returns or fetches data.

L206: def get_ca_certs(self, binary_form: typing.Literal[True] = ...) -> list[bytes]: ... Function `get\_ca\_certs` Returns or fetches data.

L209: def get_ca_certs(self, binary_form: bool = ...) -> typing.Any: ... Function `get\_ca\_certs` Returns or fetches data.

L211: def get_ca_certs(self, binary_form: bool = False) -> list[typing.Any] | list[bytes]: Function `get\_ca\_certs` Returns or fetches data.

L215: def check_hostname(self) -> bool: Function `check\_hostname` utility or script function.

L219: def check_hostname(self, value: bool) -> None: Function `check\_hostname` utility or script function.

L223: def hostname_checks_common_name(self) -> bool: Function `hostname\_checks\_common\_name` utility or script function.

L227: def hostname_checks_common_name(self, value: bool) -> None: Function `hostname\_checks\_common\_name` utility or script function.

L231: def keylog_filename(self) -> str: Function `keylog\_filename` utility or script function.

L235: def keylog_filename(self, value: str) -> None: Function `keylog\_filename` utility or script function.

L239: def maximum_version(self) -> ssl.TLSVersion: Function `maximum\_version` utility or script function.

L243: def maximum_version(self, value: ssl.TLSVersion) -> None: Function `maximum\_version` utility or script function.

L249: def minimum_version(self) -> ssl.TLSVersion: Function `minimum\_version` utility or script function.

L253: def minimum_version(self, value: ssl.TLSVersion) -> None: Function `minimum\_version` utility or script function.

L259: def options(self) -> ssl.Options: Function `options` utility or script function.

L263: def options(self, value: ssl.Options) -> None: Function `options` utility or script

```

function.
L269: def post_handshake_auth(self) -> bool:    Function `post_handshake_auth`  utility or
script function.
L273: def post_handshake_auth(self, value: bool) -> None:    Function `post_handshake_auth`
utility or script function.
L277: def protocol(self) -> ssl._SSLMethod:    Function `protocol`  utility or script
function.
L281: def security_level(self) -> int:    Function `security_level`  utility or script
function.
L285: def verify_flags(self) -> ssl.VerifyFlags:    Function `verify_flags`  utility or script
function.
L289: def verify_flags(self, value: ssl.VerifyFlags) -> None:    Function `verify_flags`
utility or script function.
L295: def verify_mode(self) -> ssl.VerifyMode:    Function `verify_mode`  utility or script
function.
L299: def verify_mode(self, value: ssl.VerifyMode) -> None:    Function `verify_mode`  utility
or script function.
L310: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:    Function
`_get_unverified_chain_bytes`  utility or script function.
L319: def _get_unverified_chain_bytes(sslobj: ssl.SSLObject) -> list[bytes]:    Function
`_get_unverified_chain_bytes`  utility or script function.
L324: def _verify_peer certs(    Function `_verify_peer certs`  utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_openssl.py

```

L25: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:    Function
`_configure_context`  utility or script function.
L51: def _capath_contains_certs(capath: str) -> bool:    Function `_capath_contains_certs`
utility or script function.
L61: def _verify_peer certs_impl(    Function `_verify_peer certs_impl`  utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/truststore/_macos.py

```

L31: def _load_cdll(name: str, macos10_16_path: str) -> CDLL:    Function `_load_cdll`
utility or script function.
L223: def _handle_osstatus(result: OSStatus, _: typing.Any, args: typing.Any) -> typing.Any:
Function `_handle_osstatus`  utility or script function.
L283: class CFConst:    Class (`CFConst`)  component used by the app (see file context: None).
L294: def _bytes_to_cf_data_ref(value: bytes) -> CFDataRef:    # type: ignore[valid-type]
Function `_bytes_to_cf_data_ref`  utility or script function.
L300: def _bytes_to_cf_string(value: bytes) -> CFString:    Function `_bytes_to_cf_string`
utility or script function.
L314: def _cf_string_ref_to_str(cf_string_ref: CFStringRef) -> str | None:    # type:
ignore[valid-type]    Function `_cf_string_ref_to_str`  utility or script function.
L337: def _der_certs_to_cf_cert_array(certs: list[bytes]) -> CFMutableArrayRef:    # type:

```

```

ignore[valid-type]    Function `_der_certs_to_cf_cert_array` utility or script function.
L368: def _configure_context(ctx: ssl.SSLContext) -> typing.Iterator[None]:    Function
`_configure_context` utility or script function.
L380: def _verify_peer certs_impl(    Function `_verify_peer certs_impl` utility or script
function.
L469: def _verify_peer certs_impl_macos_10_13(    Function `_verify_peer certs_impl_macos_10_13`
utility or script function.
L513: def _verify_peer certs_impl_macos_10_14(    Function `_verify_peer certs_impl_macos_10_14`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/certifi/core.py

```

L10: def exit_cacert_ctx() -> None:    Function `exit_cacert_ctx` utility or script function.
L21: def where() -> str:    Function `where` utility or script function.
L46: def contents() -> str:    Function `contents` utility or script function.
L56: def where() -> str:    Function `where` utility or script function.
L82: def contents() -> str:    Function `contents` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/console.py

```

L40: def reset_color():    Function `reset_color` utility or script function.
L44: def colorize(color_key, text):    Function `colorize` utility or script function.
L48: def ansiformat(attr, text):    Function `ansiformat` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexer.py

```

L37: class LexerMeta(type):    Class (`LexerMeta`) component used by the app (see file
context: None).
L43: def __new__(mcs, name, bases, d):    Function `__new__` utility or script function.
L49: class Lexer(metaclass=LexerMeta):    Class (`Lexer`) component used by the app (see file
context: None).
L145: def __init__(self, **options):    Function `__init__` utility or script function.
L156: def __init__(self, **options):    Function `__init__` utility or script function.
L175: def __repr__(self):    Function `__repr__` utility or script function.
L181: def add_filter(self, filter_, **options):    Function `add_filter` utility or script
function.
L189: def analyse_text(text):    Function `analyse_text` utility or script function.
L206: def _preprocess_lexer_input(self, text):    Function `_preprocess_lexer_input` utility
or script function.
L255: def get_tokens(self, text, unfiltered=False):    Function `get_tokens` Returns or
fetches data.
L271: def streamer():    Function `streamer` utility or script function.
L279: def get_tokens_unprocessed(self, text):    Function `get_tokens_unprocessed` Returns or
fetches data.

```

```

L291: class DelegatingLexer(Lexer):  Class (`DelegatingLexer`) component used by the app
(see file context: None).
L301: def __init__(self, _root_lexer, _language_lexer, _needle=Other, **options):  Function
`__init__` utility or script function.
L307: def get_tokens_unprocessed(self, text):  Function `get_tokens_unprocessed` Returns or
fetches data.
L330: class include(str): # pylint: disable=invalid-name  Class (`include`) component used
by the app (see file context: None).
L337: class _inherit:  Class (`_inherit`) component used by the app (see file context:
None).
L341: def __repr__(self):  Function `__repr__` utility or script function.
L347: class combined(tuple): # pylint: disable=invalid-name  Class (`combined`) component
used by the app (see file context: None).
L352: def __new__(cls, *args):  Function `__new__` utility or script function.
L355: def __init__(self, *args):  Function `__init__` utility or script function.
L360: class _PseudoMatch:  Class (`_PseudoMatch`) component used by the app (see file
context: None).
L365: def __init__(self, start, text):  Function `__init__` utility or script function.
L369: def start(self, arg=None):  Function `start` utility or script function.
L372: def end(self, arg=None):  Function `end` utility or script function.
L375: def group(self, arg=None):  Function `group` utility or script function.
L380: def groups(self):  Function `groups` utility or script function.
L383: def groupdict(self):  Function `groupdict` utility or script function.
L387: def bygroups(*args):  Function `bygroups` utility or script function.
L391: def callback(lexer, match, ctx=None):  Function `callback` utility or script
function.
L413: class _This:  Class (`_This`) component used by the app (see file context: None).
L422: def using(_other, **kwargs):  Function `using` utility or script function.
L444: def callback(lexer, match, ctx=None):  Function `callback` utility or script
function.
L459: def callback(lexer, match, ctx=None):  Function `callback` utility or script
function.
L472: class default:  Class (`default`) component used by the app (see file context: None).
L480: def __init__(self, state):  Function `__init__` utility or script function.
L484: class words(Future):  Class (`words`) component used by the app (see file context:
None).
L491: def __init__(self, words, prefix='', suffix=''):  Function `__init__` utility or
script function.
L496: def get(self):  Function `get` Returns or fetches data.
L500: class RegexLexerMeta(LexerMeta):  Class (`RegexLexerMeta`) component used by the app
(see file context: None).
L506: def _process_regex(cls, regex, rflags, state):  Function `_process_regex` utility or
script function.
L512: def _process_token(cls, token):  Function `_process_token` utility or script
function.
L518: def _process_new_state(cls, new_state, unprocessed, processed):  Function
`_process_new_state` utility or script function.
L553: def _process_state(cls, unprocessed, processed, state):  Function `_process_state`
utility or script function.
L596: def process_tokendef(cls, name, tokendefs=None):  Function `process_tokendef` utility
or script function.

```

```

L604: def get_tokendefs(cls):    Function `get_tokendefs` Returns or fetches data.
L653: def __call__(cls, *args, **kws):    Function `__call__` utility or script function.
L667: class RegexLexer(Lexer, metaclass=RegexLexerMeta):    Class (`RegexLexer`) component
used by the app (see file context: None).
L702: def get_tokens_unprocessed(self, text, stack=('root',)):    Function
`get_tokens_unprocessed` Returns or fetches data.
L764: class LexerContext:    Class (`LexerContext`) component used by the app (see file
context: None).
L769: def __init__(self, text, pos, stack=None, end=None):    Function `__init__` utility or
script function.
L775: def __repr__(self):    Function `__repr__` utility or script function.
L779: class ExtendedRegexLexer(RegexLexer):    Class (`ExtendedRegexLexer`) component used by
the app (see file context: None).
L784: def get_tokens_unprocessed(self, text=None, context=None):    Function
`get_tokens_unprocessed` Returns or fetches data.
L851: def do_insertions(insertions, tokens):    Function `do_insertions` utility or script
function.
L915: class ProfilingRegexLexerMeta(RegexLexerMeta):    Class (`ProfilingRegexLexerMeta`)
component used by the app (see file context: None).
L918: def _process_regex(cls, regex, rflags, state):    Function `_process_regex` utility or
script function.
L926: def match_func(text, pos, endpos=sys.maxsize):    Function `match_func` utility or
script function.
L937: class ProfilingRegexLexer(RegexLexer, metaclass=ProfilingRegexLexerMeta):    Class
(`ProfilingRegexLexer`) component used by the app (see file context: None).
L943: def get_tokens_unprocessed(self, text, stack=('root',)):    Function
`get_tokens_unprocessed` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/regexopt.py

```

L22: def make_charset(letters):    Function `make_charset` utility or script function.
L26: def regex_opt_inner(strings, open_paren):    Function `regex_opt_inner` utility or
script function.
L82: def regex_opt(strings, prefix='', suffix=''):    Function `regex_opt` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/token.py

```

L12: class _TokenType(tuple):    Class (`_TokenType`) component used by the app (see file
context: None).
L15: def split(self):    Function `split` utility or script function.
L24: def __init__(self, *args):    Function `__init__` utility or script function.
L28: def __contains__(self, val):    Function `__contains__` utility or script function.
L34: def __getattr__(self, val):    Function `__getattr__` utility or script function.
L43: def __repr__(self):    Function `__repr__` utility or script function.
L46: def __copy__(self):    Function `__copy__` utility or script function.

```

```

L50: def __deepcopy__(self, memo):    Function `__deepcopy__` utility or script function.
L85: def is_token_subtype(ttype, other):    Function `is_token_subtype` utility or script
function.
L94: def string_to_tokentype(s):    Function `string_to_tokentype` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/modeline.py

```

L22: def get_filetype_from_line(l): # noqa: E741    Function `get_filetype_from_line` Returns
or fetches data.
L28: def get_filetype_from_buffer(buf, max_lines=5):    Function `get_filetype_from_buffer`
Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/sphinxext.py

```

L60: class PygmentsDoc(Directive):    Class (`PygmentsDoc`) component used by the app (see
file context: None).
L71: def run(self):    Function `run` utility or script function.
L90: def document_lexers_overview(self):    Function `document_lexers_overview` utility or
script function.
L101: def format_link(name, url):    Function `format_link` utility or script function.
L121: def write_row(*columns):    Function `write_row` utility or script function.
L132: def write_seperator():    Function `write_seperator` utility or script function.
L150: def document_lexers(self):    Function `document_lexers` utility or script function.
L215: def document_formatters(self):    Function `document_formatters` utility or script
function.
L233: def document_filters(self):    Function `document_filters` utility or script function.
L246: def setup(app):    Function `setup` Sets or updates a value.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/__init__.py

```

L35: def lex(code, lexer):    Function `lex` utility or script function.
L52: def format(tokens, formatter, outfile=None): # pylint: disable=redefined-builtin
Function `format` utility or script function.
L77: def highlight(code, lexer, formatter, outfile=None):    Function `highlight` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/unistring.py

```

L82: def combine(*args):    Function `combine` utility or script function.
L86: def allexcept(*args):    Function `allexcept` utility or script function.
L93: def _handle_runs(char_list): # pragma: no cover    Function `_handle_runs` utility or

```



```
script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/style.py

```
L58: class StyleMeta(type):    Class (`StyleMeta`) component used by the app (see file
context: None).
L60: def __new__(mcs, name, bases, dct):    Function `__new__` utility or script function.
L66: def colorformat(text):    Function `colorformat` utility or script function.
L126: def style_for_token(cls, token):    Function `style_for_token` utility or script
function.
L156: def list_styles(cls):    Function `list_styles` utility or script function.
L159: def styles_token(cls, ttype):    Function `styles_token` utility or script function.
L162: def __iter__(cls):    Function `__iter__` utility or script function.
L166: def __len__(cls):    Function `__len__` utility or script function.
L170: class Style(metaclass=StyleMeta):    Class (`Style`) component used by the app (see
file context: None).
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filter.py

```
L12: def apply_filters(stream, filters, lexer=None):    Function `apply_filters` utility or
script function.
L18: def _apply(filter_, stream):    Function `_apply` utility or script function.
L25: def simplefilter(f):    Function `simplefilter` utility or script function.
L30: def lowercase(self, lexer, stream, options):    Function `lowercase` utility or script
function.
L41: class Filter:    Class (`Filter`) component used by the app (see file context: None).
L47: def __init__(self, **options):    Function `__init__` utility or script function.
L50: def filter(self, lexer, stream):    Function `filter` utility or script function.
L54: class FunctionFilter(Filter):    Class (`FunctionFilter`) component used by the app (see
file context: None).
L63: def __init__(self, **options):    Function `__init__` utility or script function.
L68: def filter(self, lexer, stream):    Function `filter` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/scanner.py

```
L20: class EndOfText(RuntimeError):    Class (`EndOfText`) component used by the app (see
file context: None).
L27: class Scanner:    Class (`Scanner`) component used by the app (see file context: None).
L35: def __init__(self, text, flags=0):    Function `__init__` utility or script function.
L49: def eos(self):    Function `eos` utility or script function.
L54: def check(self, pattern):    Function `check` utility or script function.
L66: def test(self, pattern):    Function `test` utility or script function.
L72: def scan(self, pattern):    Function `scan` utility or script function.
L95: def get_char(self):    Function `get_char` Returns or fetches data.
```

```
L99: def __repr__(self):    Function `__repr__`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/util.py

```
L30: class ClassNotFound(ValueError):    Class (`ClassNotFound`)    component used by the app
(see file context: None).
L34: class OptionError(Exception):    Class (`OptionError`)    component used by the app (see
file context: None).
L40: def get_choice_opt(options, optname, allowed, default=None, normcase=False):    Function
`get_choice_opt`    Returns or fetches data.
L53: def get_bool_opt(options, optname, default=None):    Function `get_bool_opt`    Returns or
fetches data.
L82: def get_int_opt(options, optname, default=None):    Function `get_int_opt`    Returns or
fetches data.
L94: def get_list_opt(options, optname, default=None):    Function `get_list_opt`    Returns or
fetches data.
L110: def docstring_headline(obj):    Function `docstring_headline`    utility or script
function.
L122: def make_analysator(f):    Function `make_analysator`    utility or script function.
L124: def text_analyse(text):    Function `text_analyse`    utility or script function.
L139: def shebang_matches(text, regex):    Function `shebang_matches`    utility or script
function.
L184: def doctype_matches(text, regex):    Function `doctype_matches`    utility or script
function.
L197: def html_doctype_matches(text):    Function `html_doctype_matches`    utility or script
function.
L205: def looks_like_xml(text):    Function `looks_like_xml`    utility or script function.
L221: def surrogatepair(c):    Function `surrogatepair`    utility or script function.
L230: def format_lines(var_name, seq, raw=False, indent_level=0):    Function `format_lines`
utility or script function.
L249: def duplicates_removed(it, already_seen=()):    Function `duplicates_removed`    utility
or script function.
L265: class Future:    Class (`Future`)    component used by the app (see file context: None).
L271: def get(self):    Function `get`    Returns or fetches data.
L275: def guess_decode(text):    Function `guess_decode`    utility or script function.
L296: def guess_decode_from_terminal(text, term):    Function `guess_decode_from_terminal`
utility or script function.
L313: def terminal_encoding(term):    Function `terminal_encoding`    utility or script
function.
L321: class UnclosingTextIOWrapper(TextIOWrapper):    Class (`UnclosingTextIOWrapper`)
component used by the app (see file context: None).
L323: def close(self):    Function `close`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatter.py

```
L19: def _lookup_style(style):    Function `_lookup_style`    utility or script function.
```

```

L25: class Formatter:    Class (`Formatter`) component used by the app (see file context:
None).
L83: def __init__(self, **options):    Function `__init__` utility or script function.
L99: def get_style_defs(self, arg=''):    Function `get_style_defs` Returns or fetches data.
L114: def format(self, tokensource, outfile):    Function `format` utility or script
function.
L128: def __class_getitem__(cls, name):    Function `__class_getitem__` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/plugin.py

```

L43: def iter_entry_points(group_name):    Function `iter_entry_points` utility or script
function.
L55: def find_plugin_lexers():    Function `find_plugin_lexers` utility or script function.
L60: def find_plugin_formatters():    Function `find_plugin_formatters` utility or script
function.
L65: def find_plugin_styles():    Function `find_plugin_styles` utility or script function.
L70: def find_plugin_filters():    Function `find_plugin_filters` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/filters/__init___.py

```

L22: def find_filter_class(filtername):    Function `find_filter_class` utility or script
function.
L32: def get_filter_by_name(filtername, **options):    Function `get_filter_by_name` Returns
or fetches data.
L45: def get_all_filters():    Function `get_all_filters` Returns or fetches data.
L52: def _replace_special(ttype, value, regex, specialttype,    Function `_replace_special`
utility or script function.
L65: class CodeTagFilter(Filter):    Class (`CodeTagFilter`) component used by the app (see
file context: None).
L78: def __init__(self, **options):    Function `__init__` utility or script function.
L86: def filter(self, lexer, stream):    Function `filter` utility or script function.
L97: class SymbolFilter(Filter):    Class (`SymbolFilter`) component used by the app (see
file context: None).
L673: def __init__(self, **options):    Function `__init__` utility or script function.
L679: def filter(self, lexer, stream):    Function `filter` utility or script function.
L687: class KeywordCaseFilter(Filter):    Class (`KeywordCaseFilter`) component used by the
app (see file context: None).
L701: def __init__(self, **options):    Function `__init__` utility or script function.
L707: def filter(self, lexer, stream):    Function `filter` utility or script function.
L715: class NameHighlightFilter(Filter):    Class (`NameHighlightFilter`) component used by
the app (see file context: None).
L739: def __init__(self, **options):    Function `__init__` utility or script function.
L748: def filter(self, lexer, stream):    Function `filter` utility or script function.
L756: class ErrorToken(Exception):    Class (`ErrorToken`) component used by the app (see

```

```

file context: None).
L760: class RaiseOnErrorTokenFilter(Filter):  Class (`RaiseOnErrorTokenFilter`) component
used by the app (see file context: None).
L772: def __init__(self, **options):  Function `__init__` utility or script function.
L782: def filter(self, lexer, stream):  Function `filter` utility or script function.
L789: class VisibleWhitespaceFilter(Filter):  Class (`VisibleWhitespaceFilter`) component
used by the app (see file context: None).
L819: def __init__(self, **options):  Function `__init__` utility or script function.
L836: def filter(self, lexer, stream):  Function `filter` utility or script function.
L843: def replacefunc(wschar):  Function `replacefunc` utility or script function.
L868: class GobbleFilter(Filter):  Class (`GobbleFilter`) component used by the app (see
file context: None).
L882: def __init__(self, **options):  Function `__init__` utility or script function.
L886: def gobble(self, value, left):  Function `gobble` utility or script function.
L892: def filter(self, lexer, stream):  Function `filter` utility or script function.
L907: class TokenMergeFilter(Filter):  Class (`TokenMergeFilter`) component used by the app
(see file context: None).
L913: def __init__(self, **options):  Function `__init__` utility or script function.
L916: def filter(self, lexer, stream):  Function `filter` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/python.py

```

L25: class PythonLexer(RegexLexer):  Class (`PythonLexer`) component used by the app (see
file context: None).
L65: def innerstring_rules(ttype):  Function `innerstring_rules` utility or script
function.
L85: def fstring_rules(ttype):  Function `fstring_rules` utility or script function.
L408: def analyse_text(text):  Function `analyse_text` utility or script function.
L416: class Python2Lexer(RegexLexer):  Class (`Python2Lexer`) component used by the app
(see file context: None).
L433: def innerstring_rules(ttype):  Function `innerstring_rules` utility or script
function.
L635: def analyse_text(text):  Function `analyse_text` utility or script function.
L639: class _PythonConsoleLexerBase(RegexLexer):  Class (`_PythonConsoleLexerBase`)
component used by the app (see file context: None).
L676: class PythonConsoleLexer(DelegatingLexer):  Class (`PythonConsoleLexer`) component
used by the app (see file context: None).
L706: def __init__(self, **options):  Function `__init__` utility or script function.
L719: class _ReplaceInnerCode(DelegatingLexer):  Class (`_ReplaceInnerCode`) component used
by the app (see file context: None).
L720: def __init__(self, **options):  Function `__init__` utility or script function.
L725: class PythonTracebackLexer(RegexLexer):  Class (`PythonTracebackLexer`) component
used by the app (see file context: None).
L782: class Python2TracebackLexer(RegexLexer):  Class (`Python2TracebackLexer`) component
used by the app (see file context: None).
L830: class CythonLexer(RegexLexer):  Class (`CythonLexer`) component used by the app (see
file context: None).

```

```

L1009: class DgLexer(RegexLexer):    Class (`DgLexer`)    component used by the app (see file
context: None).
L1108: class NumPyLexer(PythonLexer):    Class (`NumPyLexer`)    component used by the app (see
file context: None).
L1189: def get_tokens_unprocessed(self, text):    Function `get_tokens_unprocessed`    Returns
or fetches data.
L1197: def analyse_text(text):    Function `analyse_text`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/lexers/__init___.py

```

L35: def _fn_matches(fn, glob):    Function `_fn_matches`    utility or script function.
L43: def _load_lexers(module_name):    Function `_load_lexers`    utility or script function.
L51: def get_all_lexers(plugins=True):    Function `get_all_lexers`    Returns or fetches data.
L65: def find_lexer_class(name):    Function `find_lexer_class`    utility or script function.
L83: def find_lexer_class_by_name(_alias):    Function `find_lexer_class_by_name`    utility or
script function.
L110: def get_lexer_by_name(_alias, **options):    Function `get_lexer_by_name`    Returns or
fetches data.
L135: def load_lexer_from_file(filename, lexername="CustomLexer", **options):    Function
`load_lexer_from_file`    Loads data from storage or remote.
L169: def find_lexer_class_for_filename(_fn, code=None):    Function
`find_lexer_class_for_filename`    utility or script function.
L194: def get_rating(info):    Function `get_rating`    Returns or fetches data.
L212: def get_lexer_for_filename(_fn, code=None, **options):    Function
`get_lexer_for_filename`    Returns or fetches data.
L231: def get_lexer_for_mimetype(_mime, **options):    Function `get_lexer_for_mimetype`
Returns or fetches data.
L250: def _iter_lexerclasses(plugins=True):    Function `_iter_lexerclasses`    utility or
script function.
L261: def guess_lexer_for_filename(_fn, _text, **options):    Function
`guess_lexer_for_filename`    utility or script function.
L292: def type_sort(t):    Function `type_sort`    utility or script function.
L304: def guess_lexer(_text, **options):    Function `guess_lexer`    utility or script
function.
L308: class is called with the text as argument, and the lexer which returned the    Class
(`is`)    component used by the app (see file context: None).
L343: class _automodule(types.ModuleType):    Class (`_automodule`)    component used by the app
(see file context: None).
L346: def __getattr__(self, name):    Function `__getattr__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/styles/__init___.py

```

L24: def get_style_by_name(name):    Function `get_style_by_name`    Returns or fetches data.

```

```
L56: def get_all_styles():    Function `get_all_styles` Returns or fetches data.
```

.venv/lib/python3.12/site-packages/pip/_vendor/pygments/formatters/____init__.py

```
L28: def _fn_matches(fn, glob):    Function `_fn_matches` utility or script function.
L36: def _load_formatters(module_name):    Function `_load_formatters` utility or script
function.
L44: def get_all_formatters():    Function `get_all_formatters` Returns or fetches data.
L55: def find_formatter_class(alias):    Function `find_formatter_class` utility or script
function.
L70: def get_formatter_by_name(_alias, **options):    Function `get_formatter_by_name`
Returns or fetches data.
L84: def load_formatter_from_file(filename, formattername="CustomFormatter", **options):
Function `load_formatter_from_file` Loads data from storage or remote.
L118: def get_formatter_for_filename(fn, **options):    Function `get_formatter_for_filename`
Returns or fetches data.
L140: class _automodule(types.ModuleType):    Class (`_automodule`) component used by the app
(see file context: None).
L143: def __getattr__(self, name):    Function `__getattr__` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/distro/distro.py

```
L61: class VersionDict(TypedDict):    Class (`VersionDict`) component used by the app (see
file context: None).
L67: class InfoDict(TypedDict):    Class (`InfoDict`) component used by the app (see file
context: None).
L160: def linux_distribution(full_distribution_name: bool = True) -> Tuple[str, str, str]:
Function `linux_distribution` utility or script function.
L203: def id() -> str:    Function `id` utility or script function.
L287: def name(pretty: bool = False) -> str:    Function `name` utility or script function.
L326: def version(pretty: bool = False, best: bool = False) -> str:    Function `version`
utility or script function.
L374: def version_parts(best: bool = False) -> Tuple[str, str, str]:    Function
`version_parts` utility or script function.
L391: def major_version(best: bool = False) -> str:    Function `major_version` utility or
script function.
L404: def minor_version(best: bool = False) -> str:    Function `minor_version` utility or
script function.
L417: def build_number(best: bool = False) -> str:    Function `build_number` Constructs or
prepares an object.
L430: def like() -> str:    Function `like` utility or script function.
L447: def codename() -> str:    Function `codename` utility or script function.
L471: def info(pretty: bool = False, best: bool = False) -> InfoDict:    Function `info`
utility or script function.
L515: def os_release_info() -> Dict[str, str]:    Function `os_release_info` utility or
```

```

script function.
L525: def lsb_release_info() -> Dict[str, str]:    Function `lsb_release_info` utility or
script function.
L536: def distro_release_info() -> Dict[str, str]:    Function `distro_release_info` utility
or script function.
L546: def uname_info() -> Dict[str, str]:    Function `uname_info` utility or script
function.
L554: def os_release_attr(attribute: str) -> str:    Function `os_release_attr` utility or
script function.
L573: def lsb_release_attr(attribute: str) -> str:    Function `lsb_release_attr` utility or
script function.
L593: def distro_release_attr(attribute: str) -> str:    Function `distro_release_attr`
utility or script function.
L612: def uname_attr(attribute: str) -> str:    Function `uname_attr` utility or script
function.
L633: class cached_property: # type: ignore    Class (`cached_property`) component used by
the app (see file context: None).
L639: def __init__(self, f: Callable[[Any], Any]) -> None:    Function `__init__` utility or
script function.
L643: def __get__(self, obj: Any, owner: Type[Any]) -> Any:    Function `__get__` utility or
script function.
L649: class LinuxDistribution:    Class (`LinuxDistribution`) component used by the app (see
file context: None).
L667: def __init__(    Function `__init__` utility or script function.
L800: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L817: def linux_distribution(    Function `linux_distribution` utility or script function.
L833: def id(self) -> str:    Function `id` utility or script function.
L839: def normalize(distro_id: str, table: Dict[str, str]) -> str:    Function `normalize`
utility or script function.
L861: def name(self, pretty: bool = False) -> str:    Function `name` utility or script
function.
L884: def version(self, pretty: bool = False, best: bool = False) -> str:    Function
`version` utility or script function.
L926: def version_parts(self, best: bool = False) -> Tuple[str, str, str]:    Function
`version_parts` utility or script function.
L942: def major_version(self, best: bool = False) -> str:    Function `major_version` utility
or script function.
L950: def minor_version(self, best: bool = False) -> str:    Function `minor_version` utility
or script function.
L958: def build_number(self, best: bool = False) -> str:    Function `build_number`
Constructs or prepares an object.
L966: def like(self) -> str:    Function `like` utility or script function.
L974: def codename(self) -> str:    Function `codename` utility or script function.
L991: def info(self, pretty: bool = False, best: bool = False) -> InfoDict:    Function `info`
utility or script function.
L1010: def os_release_info(self) -> Dict[str, str]:    Function `os_release_info` utility or
script function.
L1019: def lsb_release_info(self) -> Dict[str, str]:    Function `lsb_release_info` utility
or script function.
L1029: def distro_release_info(self) -> Dict[str, str]:    Function `distro_release_info`
utility or script function.

```

```

L1039: def uname_info(self) -> Dict[str, str]:    Function `uname_info` utility or script
function.
L1048: def oslevel_info(self) -> str:    Function `oslevel_info` utility or script function.
L1054: def os_release_attr(self, attribute: str) -> str:    Function `os_release_attr`
utility or script function.
L1063: def lsb_release_attr(self, attribute: str) -> str:    Function `lsb_release_attr`
utility or script function.
L1072: def distro_release_attr(self, attribute: str) -> str:    Function `distro_release_attr`
utility or script function.
L1081: def uname_attr(self, attribute: str) -> str:    Function `uname_attr` utility or
script function.
L1091: def _os_release_info(self) -> Dict[str, str]:    Function `_os_release_info` utility
or script function.
L1104: def _parse_os_release_content(lines: TextIO) -> Dict[str, str]:    Function
`_parse_os_release_content` utility or script function.
L1154: def _lsb_release_info(self) -> Dict[str, str]:    Function `_lsb_release_info` utility
or script function.
L1173: def _parse_lsb_release_content(lines: Iterable[str]) -> Dict[str, str]:    Function
`_parse_lsb_release_content` utility or script function.
L1197: def _uname_info(self) -> Dict[str, str]:    Function `_uname_info` utility or script
function.
L1209: def _oslevel_info(self) -> str:    Function `_oslevel_info` utility or script
function.
L1219: def _debian_version(self) -> str:    Function `_debian_version` utility or script
function.
L1229: def _parse_uname_content(lines: Sequence[str]) -> Dict[str, str]:    Function
`_parse_uname_content` utility or script function.
L1248: def _to_str(bytestring: bytes) -> str:    Function `_to_str` utility or script
function.
L1253: def _distro_release_info(self) -> Dict[str, str]:    Function `_distro_release_info`
utility or script function.
L1311: def _parse_distro_release_file(self, filepath: str) -> Dict[str, str]:    Function
`_parse_distro_release_file` utility or script function.
L1334: def _parse_distro_release_content(line: str) -> Dict[str, str]:    Function
`_parse_distro_release_content` utility or script function.
L1362: def main() -> None:    Function `main` Entry point / main routine.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/compat.py

```

L29: def _resolve_char_detection():    Function `_resolve_char_detection` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/hooks.py

```

L16: def default_hooks():    Function `default_hooks` utility or script function.
L23: def dispatch_hook(key, hooks, hook_data, **kwargs):    Function `dispatch_hook` utility

```


or script function.

.venv/lib/python3.12/site-packages/pip/_vendor/requests/models.py

```

L86: class RequestEncodingMixin:  Class (`RequestEncodingMixin`)  component used by the app
(see file context: None).
L88: def path_url(self):  Function `path_url`  utility or script function.
L109: def _encode_params(data):  Function `_encode_params`  utility or script function.
L139: def _encode_files(files, data):  Function `_encode_files`  utility or script function.
L208: class RequestHooksMixin:  Class (`RequestHooksMixin`)  component used by the app (see
file context: None).
L209: def register_hook(self, event, hook):  Function `register_hook`  utility or script
function.
L220: def deregister_hook(self, event, hook):  Function `deregister_hook`  utility or script
function.
L232: class Request(RequestHooksMixin):  Class (`Request`)  component used by the app (see
file context: None).
L260: def __init__(  Function `__init__`  utility or script function.
L294: def __repr__(self):  Function `__repr__`  utility or script function.
L297: def prepare(self):  Function `prepare`  utility or script function.
L315: class PreparedRequest(RequestEncodingMixin, RequestHooksMixin):  Class
(`PreparedRequest`)  component used by the app (see file context: None).
L336: def __init__(self):  Function `__init__`  utility or script function.
L353: def prepare(  Function `prepare`  utility or script function.
L381: def __repr__(self):  Function `__repr__`  utility or script function.
L384: def copy(self):  Function `copy`  utility or script function.
L395: def prepare_method(self, method):  Function `prepare_method`  utility or script
function.
L402: def _get_idna_encoded_host(host):  Function `_get_idna_encoded_host`  utility or
script function.
L411: def prepare_url(self, url, params):  Function `prepare_url`  utility or script
function.
L485: def prepare_headers(self, headers):  Function `prepare_headers`  utility or script
function.
L496: def prepare_body(self, data, files, json=None):  Function `prepare_body`  utility or
script function.
L574: def prepare_content_length(self, body):  Function `prepare_content_length`  utility or
script function.
L590: def prepare_auth(self, auth, url=""):  Function `prepare_auth`  utility or script
function.
L612: def prepare_cookies(self, cookies):  Function `prepare_cookies`  utility or script
function.
L632: def prepare_hooks(self, hooks):  Function `prepare_hooks`  utility or script function.
L642: class Response:  Class (`Response`)  component used by the app (see file context:
None).
L660: def __init__(self):  Function `__init__`  utility or script function.
L707: def __enter__(self):  Function `__enter__`  utility or script function.
L710: def __exit__(self, *args):  Function `__exit__`  utility or script function.

```

```

L713: def __getstate__(self):    Function `__getstate__` utility or script function.
L721: def __setstate__(self, state):    Function `__setstate__` utility or script function.
L729: def __repr__(self):    Function `__repr__` utility or script function.
L732: def __bool__(self):    Function `__bool__` utility or script function.
L742: def __nonzero__(self):    Function `__nonzero__` utility or script function.
L752: def __iter__(self):    Function `__iter__` utility or script function.
L757: def ok(self):    Function `ok` utility or script function.
L772: def is_redirect(self):    Function `is_redirect` utility or script function.
L779: def is_permanent_redirect(self):    Function `is_permanent_redirect` utility or script
function.
L787: def next(self):    Function `next` utility or script function.
L792: def apparent_encoding(self):    Function `apparent_encoding` utility or script
function.
L801: def iter_content(self, chunk_size=1, decode_unicode=False):    Function `iter_content`
utility or script function.
L818: def generate():    Function `generate` Generates content (often AI-generated).
L859: def iter_lines(    Function `iter_lines` utility or script function.
L893: def content(self):    Function `content` utility or script function.
L912: def text(self):    Function `text` utility or script function.
L949: def json(self, **kwargs):    Function `json` utility or script function.
L985: def links(self):    Function `links` utility or script function.
L1001: def raise_for_status(self):    Function `raise_for_status` utility or script function.
L1030: def close(self):    Function `close` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/help.py

```

L27: def _implementation():    Function `_implementation` utility or script function.
L59: def info():    Function `info` utility or script function.
L118: def main():    Function `main` Entry point / main routine.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/api.py

```

L14: def request(method, url, **kwargs):    Function `request` utility or script function.
L62: def get(url, params=None, **kwargs):    Function `get` Returns or fetches data.
L76: def options(url, **kwargs):    Function `options` utility or script function.
L88: def head(url, **kwargs):    Function `head` utility or script function.
L103: def post(url, data=None, json=None, **kwargs):    Function `post` utility or script
function.
L118: def put(url, data=None, **kwargs):    Function `put` utility or script function.
L133: def patch(url, data=None, **kwargs):    Function `patch` utility or script function.
L148: def delete(url, **kwargs):    Function `delete` Deletes a resource.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/exceptions.py

```

L13: class RequestException(IOError):    Class (`RequestException`) component used by the app
(see file context: None).
L18: def __init__(self, *args, **kwargs):    Function `__init__` utility or script function.
L28: class InvalidJSONError(RequestException):    Class (`InvalidJSONError`) component used
by the app (see file context: None).
L32: class JSONDecodeError(InvalidJSONError, CompatJSONDecodeError):    Class
(`JSONDecodeError`) component used by the app (see file context: None).
L35: def __init__(self, *args, **kwargs):    Function `__init__` utility or script function.
L45: def __reduce__(self):    Function `__reduce__` utility or script function.
L56: class HTTPError(RequestException):    Class (`HTTPError`) component used by the app (see
file context: None).
L60: class ConnectionError(RequestException):    Class (`ConnectionError`) component used by
the app (see file context: None).
L64: class ProxyError(ConnectionError):    Class (`ProxyError`) component used by the app
(see file context: None).
L68: class SSLError(ConnectionError):    Class (`SSLError`) component used by the app (see
file context: None).
L72: class Timeout(RequestException):    Class (`Timeout`) component used by the app (see
file context: None).
L81: class ConnectTimeout(ConnectionError, Timeout):    Class (`ConnectTimeout`) component
used by the app (see file context: None).
L88: class ReadTimeout(Timeout):    Class (`ReadTimeout`) component used by the app (see file
context: None).
L92: class URLRequired(RequestException):    Class (`URLRequired`) component used by the app
(see file context: None).
L96: class TooManyRedirects(RequestException):    Class (`TooManyRedirects`) component used
by the app (see file context: None).
L100: class MissingSchema(RequestException, ValueError):    Class (`MissingSchema`) component
used by the app (see file context: None).
L104: class InvalidSchema(RequestException, ValueError):    Class (`InvalidSchema`) component
used by the app (see file context: None).
L108: class InvalidURL(RequestException, ValueError):    Class (`InvalidURL`) component used
by the app (see file context: None).
L112: class InvalidHeader(RequestException, ValueError):    Class (`InvalidHeader`) component
used by the app (see file context: None).
L116: class InvalidProxyURL(InvalidURL):    Class (`InvalidProxyURL`) component used by the
app (see file context: None).
L120: class ChunkedEncodingError(RequestException):    Class (`ChunkedEncodingError`)
component used by the app (see file context: None).
L124: class ContentDecodingError(RequestException, BaseHTTPError):    Class
(`ContentDecodingError`) component used by the app (see file context: None).
L128: class StreamConsumedError(RequestException, TypeError):    Class (`StreamConsumedError`)
component used by the app (see file context: None).
L132: class RetryError(RequestException):    Class (`RetryError`) component used by the app
(see file context: None).
L136: class UnrewindableBodyError(RequestException):    Class (`UnrewindableBodyError`)
component used by the app (see file context: None).
L143: class RequestsWarning(Warning):    Class (`RequestsWarning`) component used by the app
(see file context: None).
L147: class FileModeWarning(RequestsWarning, DeprecationWarning):    Class (`FileModeWarning`)
component used by the app (see file context: None).

```

```
L151: class RequestsDependencyWarning(RequestsWarning):  Class (`RequestsDependencyWarning`)
      component used by the app (see file context: None).
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/__init__.py

```
L51: def check_compatibility(urllib3_version, chardet_version, charset_normalizer_version):
Function `check_compatibility` utility or script function.
L83: def _check_cryptography(cryptography_version):  Function `_check_cryptography` utility
or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/sessions.py

```
L62: def merge_setting(request_setting, session_setting, dict_class=OrderedDict):  Function
`merge_setting` utility or script function.
L92: def merge_hooks(request_hooks, session_hooks, dict_class=OrderedDict):  Function
`merge_hooks` utility or script function.
L107: class SessionRedirectMixin:  Class (`SessionRedirectMixin`) component used by the app
(see file context: None).
L108: def get_redirect_target(self, resp):  Function `get_redirect_target` Returns or
fetches data.
L128: def should_strip_auth(self, old_url, new_url):  Function `should_strip_auth` utility
or script function.
L160: def resolve_redirects(  Function `resolve_redirects` utility or script function.
L283: def rebuild_auth(self, prepared_request, response):  Function `rebuild_auth` utility
or script function.
L303: def rebuild_proxies(self, prepared_request, proxies):  Function `rebuild_proxies`
utility or script function.
L334: def rebuild_method(self, prepared_request, response):  Function `rebuild_method`
utility or script function.
L357: class Session(SessionRedirectMixin):  Class (`Session`) component used by the app
(see file context: None).
L391: def __init__(self):  Function `__init__` utility or script function.
L454: def __enter__(self):  Function `__enter__` utility or script function.
L457: def __exit__(self, *args):  Function `__exit__` utility or script function.
L460: def prepare_request(self, request):  Function `prepare_request` utility or script
function.
L503: def request(  Function `request` utility or script function.
L596: def get(self, url, **kwargs):  Function `get` Returns or fetches data.
L607: def options(self, url, **kwargs):  Function `options` utility or script function.
L618: def head(self, url, **kwargs):  Function `head` utility or script function.
L629: def post(self, url, data=None, json=None, **kwargs):  Function `post` utility or
script function.
L642: def put(self, url, data=None, **kwargs):  Function `put` utility or script function.
L654: def patch(self, url, data=None, **kwargs):  Function `patch` utility or script
function.
L666: def delete(self, url, **kwargs):  Function `delete` Deletes a resource.
```

```

L676: def send(self, request, **kwargs):  Function `send` utility or script function.
L753: def merge_environment_settings(self, url, proxies, stream, verify, cert):  Function
`merge_environment_settings` utility or script function.
L784: def get_adapter(self, url):  Function `get_adapter` Returns or fetches data.
L797: def close(self):  Function `close` utility or script function.
L802: def mount(self, prefix, adapter):  Function `mount` utility or script function.
L813: def __getstate__(self):  Function `__getstate__` utility or script function.
L817: def __setstate__(self, state):  Function `__setstate__` utility or script function.
L822: def session():  Function `session` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/utils.py

```

L76: def proxy_bypass_registry(host):  Function `proxy_bypass_registry` utility or script
function.
L114: def proxy_bypass(host): # noqa  Function `proxy_bypass` utility or script function.
L126: def dict_to_sequence(d):  Function `dict_to_sequence` utility or script function.
L135: def super_len(o):  Function `super_len` utility or script function.
L206: def get_netrc_auth(url, raise_errors=False):  Function `get_netrc_auth` Returns or
fetches data.
L250: def guess_filename(obj):  Function `guess_filename` utility or script function.
L257: def extract_zipped_paths(path):  Function `extract_zipped_paths` utility or script
function.
L296: def atomic_open(filename):  Function `atomic_open` utility or script function.
L308: def from_key_val_list(value):  Function `from_key_val_list` utility or script
function.
L335: def to_key_val_list(value):  Function `to_key_val_list` utility or script function.
L365: def parse_list_header(value):  Function `parse_list_header` utility or script
function.
L397: def parse_dict_header(value):  Function `parse_dict_header` utility or script
function.
L432: def unquote_header_value(value, is_filename=False):  Function `unquote_header_value`
utility or script function.
L457: def dict_from_cookiejar(cj):  Function `dict_from_cookiejar` utility or script
function.
L468: def add_dict_to_cookiejar(cj, cookie_dict):  Function `add_dict_to_cookiejar` utility
or script function.
L479: def get_encodings_from_content(content):  Function `get_encodings_from_content`
Returns or fetches data.
L504: def _parse_content_type_header(header):  Function `_parse_content_type_header`
utility or script function.
L526: def get_encoding_from_headers(headers):  Function `get_encoding_from_headers` Returns
or fetches data.
L551: def stream_decode_response_unicode(iterator, r):  Function
`stream_decode_response_unicode` utility or script function.
L568: def iter_slices(string, slice_length):  Function `iter_slices` utility or script
function.
L578: def get_unicode_from_response(r):  Function `get_unicode_from_response` Returns or
fetches data.

```

```

L623: def unquote_unreserved(uri):    Function `unquote_unreserved` utility or script
function.
L647: def requote_uri(uri):    Function `requote_uri` utility or script function.
L669: def address_in_network(ip, net):    Function `address_in_network` utility or script
function.
L684: def dotted_netmask(mask):    Function `dotted_netmask` utility or script function.
L695: def is_ipv4_address(string_ip):    Function `is_ipv4_address` utility or script
function.
L706: def is_valid_cidr(string_network):    Function `is_valid_cidr` utility or script
function.
L731: def set_environ(env_name, value):    Function `set_environ` Sets or updates a value.
L752: def should_bypass_proxies(url, no_proxy):    Function `should_bypass_proxies` utility
or script function.
L761: def get_proxy(key):    Function `get_proxy` Returns or fetches data.
L813: def get_environ_proxies(url, no_proxy=None):    Function `get_environ_proxies` Returns
or fetches data.
L825: def select_proxy(url, proxies):    Function `select_proxy` utility or script function.
L851: def resolve_proxies(request, proxies, trust_env=True):    Function `resolve_proxies`
utility or script function.
L878: def default_user_agent(name="python-requests"):    Function `default_user_agent`
utility or script function.
L887: def default_headers():    Function `default_headers` utility or script function.
L901: def parse_header_links(value):    Function `parse_header_links` utility or script
function.
L944: def guess_json_utf(data):    Function `guess_json_utf` utility or script function.
L976: def prepend_scheme_if_needed(url, new_scheme):    Function `prepend_scheme_if_needed`
utility or script function.
L1005: def get_auth_from_url(url):    Function `get_auth_from_url` Returns or fetches data.
L1021: def check_header_validity(header):    Function `check_header_validity` utility or
script function.
L1032: def _validate_header_part(header, header_part, header_validator_index):    Function
`_validate_header_part` utility or script function.
L1051: def urldefragauth(url):    Function `urldefragauth` utility or script function.
L1068: def rewind_body(prepared_request):    Function `rewind_body` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/_internal_utils.py

```

L26: def to_native_string(string, encoding="ascii"):    Function `to_native_string` utility
or script function.
L39: def unicode_is_ascii(u_string):    Function `unicode_is_ascii` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/cookies.py

```

L23: class MockRequest:  Class (`MockRequest`)  component used by the app (see file context:
None).
L35: def __init__(self, request):  Function `__init__`  utility or script function.
L40: def get_type(self):  Function `get_type`  Returns or fetches data.
L43: def get_host(self):  Function `get_host`  Returns or fetches data.
L46: def get_origin_req_host(self):  Function `get_origin_req_host`  Returns or fetches
data.
L49: def get_full_url(self):  Function `get_full_url`  Returns or fetches data.
L69: def is_unverifiable(self):  Function `is_unverifiable`  utility or script function.
L72: def has_header(self, name):  Function `has_header`  utility or script function.
L75: def get_header(self, name, default=None):  Function `get_header`  Returns or fetches
data.
L78: def add_header(self, key, val):  Function `add_header`  utility or script function.
L84: def add_unredirected_header(self, name, value):  Function `add_unredirected_header`
utility or script function.
L87: def get_new_headers(self):  Function `get_new_headers`  Returns or fetches data.
L91: def unverifiable(self):  Function `unverifiable`  utility or script function.
L95: def origin_req_host(self):  Function `origin_req_host`  utility or script function.
L99: def host(self):  Function `host`  utility or script function.
L103: class MockResponse:  Class (`MockResponse`)  component used by the app (see file
context: None).
L110: def __init__(self, headers):  Function `__init__`  utility or script function.
L117: def info(self):  Function `info`  utility or script function.
L120: def getheaders(self, name):  Function `getheaders`  Returns or fetches data.
L124: def extract_cookies_to_jar(jar, request, response):  Function `extract_cookies_to_jar`
utility or script function.
L140: def get_cookie_header(jar, request):  Function `get_cookie_header`  Returns or fetches
data.
L151: def remove_cookie_by_name(cookiejar, name, domain=None, path=None):  Function
`remove_cookie_by_name`  utility or script function.
L170: class CookieConflictError(RuntimeError):  Class (`CookieConflictError`)  component
used by the app (see file context: None).
L176: class RequestsCookieJar(cookiejarlib.CookieJar, MutableMapping):  Class
(`RequestsCookieJar`)  component used by the app (see file context: None).
L194: def get(self, name, default=None, domain=None, path=None):  Function `get`  Returns or
fetches data.
L206: def set(self, name, value, **kwargs):  Function `set`  Sets or updates a value.
L225: def iterkeys(self):  Function `iterkeys`  utility or script function.
L234: def keys(self):  Function `keys`  utility or script function.
L242: def itervalues(self):  Function `itervalues`  utility or script function.
L251: def values(self):  Function `values`  utility or script function.
L259: def iteritems(self):  Function `iteritems`  utility or script function.
L268: def items(self):  Function `items`  utility or script function.
L277: def list_domains(self):  Function `list_domains`  utility or script function.
L285: def list_paths(self):  Function `list_paths`  utility or script function.
L293: def multiple_domains(self):  Function `multiple_domains`  utility or script function.
L306: def get_dict(self, domain=None, path=None):  Function `get_dict`  Returns or fetches
data.
L321: def __contains__(self, name):  Function `__contains__`  utility or script function.
L327: def __getitem__(self, name):  Function `__getitem__`  utility or script function.
L336: def __setitem__(self, name, value):  Function `__setitem__`  utility or script

```



```

function.
L343: def __delitem__(self, name):    Function `__delitem__` utility or script function.
L349: def set_cookie(self, cookie, *args, **kwargs):    Function `set_cookie` Sets or updates
a value.
L358: def update(self, other):    Function `update` utility or script function.
L366: def _find(self, name, domain=None, path=None):    Function `_find` utility or script
function.
L386: def _find_no_duplicates(self, name, domain=None, path=None):    Function
`_find_no_duplicates` utility or script function.
L415: def __getstate__(self):    Function `__getstate__` utility or script function.
L422: def __setstate__(self, state):    Function `__setstate__` utility or script function.
L428: def copy(self):    Function `copy` utility or script function.
L435: def get_policy(self):    Function `get_policy` Returns or fetches data.
L440: def _copy_cookie_jar(jar):    Function `_copy_cookie_jar` utility or script function.
L455: def create_cookie(name, value, **kwargs):    Function `create_cookie` Creates a
resource or document.
L492: def morsel_to_cookie(morsel):    Function `morsel_to_cookie` utility or script
function.
L521: def cookiejar_from_dict(cookie_dict, cookiejar=None, overwrite=True):    Function
`cookiejar_from_dict` utility or script function.
L542: def merge_cookies(cookiejar, cookies):    Function `merge_cookies` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/auth.py

```

L25: def _basic_auth_str(username, password):    Function `_basic_auth_str` utility or script
function.
L69: class AuthBase:    Authentication component (`AuthBase`) handles user authentication
flows.
L72: def __call__(self, r):    Function `__call__` utility or script function.
L76: class HTTPBasicAuth(AuthBase):    Authentication component (`HTTPBasicAuth`) handles
user authentication flows.
L79: def __init__(self, username, password):    Function `__init__` utility or script
function.
L83: def __eq__(self, other):    Function `__eq__` utility or script function.
L91: def __ne__(self, other):    Function `__ne__` utility or script function.
L94: def __call__(self, r):    Function `__call__` utility or script function.
L99: class HTTPProxyAuth(HTTPBasicAuth):    Authentication component (`HTTPProxyAuth`)
handles user authentication flows.
L102: def __call__(self, r):    Function `__call__` utility or script function.
L107: class HTTPDigestAuth(AuthBase):    Authentication component (`HTTPDigestAuth`) handles
user authentication flows.
L110: def __init__(self, username, password):    Function `__init__` utility or script
function.
L116: def init_per_thread_state(self):    Function `init_per_thread_state` Initialisation
routine.
L126: def build_digest_header(self, method, url):    Function `build_digest_header`
Constructs or prepares an object.

```



```

L145: def md5_utf8(x):    Function `md5_utf8`    utility or script function.
L153: def sha_utf8(x):    Function `sha_utf8`    utility or script function.
L161: def sha256_utf8(x): Function `sha256_utf8` utility or script function.
L169: def sha512_utf8(x): Function `sha512_utf8` utility or script function.
L236: def handle_redirect(self, r, **kwargs):    Function `handle_redirect` utility or script
function.
L241: def handle_401(self, r, **kwargs):    Function `handle_401`    utility or script function.
L285: def __call__(self, r):    Function `__call__`    utility or script function.
L305: def __eq__(self, other):    Function `__eq__`    utility or script function.
L313: def __ne__(self, other):    Function `__ne__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/adapters.py

```

L63: def SOCKSProxyManager(*args, **kwargs):    Function `SOCKSProxyManager`    utility or
script function.
L77: def _urllib3_request_context(    Function `_urllib3_request_context`    utility or script
function.
L114: class BaseAdapter:    Class (`BaseAdapter`)    component used by the app (see file
context: None).
L117: def __init__(self):    Function `__init__`    utility or script function.
L120: def send(    Function `send`    utility or script function.
L139: def close(self):    Function `close`    utility or script function.
L144: class HTTPAdapter(BaseAdapter):    Class (`HTTPAdapter`)    component used by the app (see
file context: None).
L179: def __init__(    Function `__init__`    utility or script function.
L201: def __getstate__(self):    Function `__getstate__`    utility or script function.
L204: def __setstate__(self, state):    Function `__setstate__`    utility or script function.
L217: def init_poolmanager(    Function `init_poolmanager`    Initialisation routine.
L243: def proxy_manager_for(self, proxy, **proxy_kwargs):    Function `proxy_manager_for`
utility or script function.
L281: def cert_verify(self, conn, url, verify, cert):    Function `cert_verify`    utility or
script function.
L337: def build_response(self, req, resp):    Function `build_response`    Constructs or
prepares an object.
L374: def build_connection_pool_key_attributes(self, request, verify, cert=None):    Function
`build_connection_pool_key_attributes`    Constructs or prepares an object.
L424: def get_connection_with_tls_context(self, request, verify, proxies=None, cert=None):
Function `get_connection_with_tls_context`    Returns or fetches data.
L473: def get_connection(self, url, proxies=None):    Function `get_connection`    Returns or
fetches data.
L514: def close(self):    Function `close`    utility or script function.
L524: def request_url(self, request, proxies):    Function `request_url`    utility or script
function.
L556: def add_headers(self, request, **kwargs):    Function `add_headers`    utility or script
function.
L570: def proxy_headers(self, proxy):    Function `proxy_headers`    utility or script function.
L591: def send(    Function `send`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/structures.py

```

L13: class CaseInsensitiveDict(MutableMapping):    Class (`CaseInsensitiveDict`)    component
used by the app (see file context: None).
L40: def __init__(self, data=None, **kwargs):    Function `__init__`    utility or script
function.
L46: def __setitem__(self, key, value):    Function `__setitem__`    utility or script function.
L51: def __getitem__(self, key):    Function `__getitem__`    utility or script function.
L54: def __delitem__(self, key):    Function `__delitem__`    utility or script function.
L57: def __iter__(self):    Function `__iter__`    utility or script function.
L60: def __len__(self):    Function `__len__`    utility or script function.
L63: def lower_items(self):    Function `lower_items`    utility or script function.
L67: def __eq__(self, other):    Function `__eq__`    utility or script function.
L76: def copy(self):    Function `copy`    utility or script function.
L79: def __repr__(self):    Function `__repr__`    utility or script function.
L83: class LookupDict(dict):    Class (`LookupDict`)    component used by the app (see file
context: None).
L86: def __init__(self, name=None):    Function `__init__`    utility or script function.
L90: def __repr__(self):    Function `__repr__`    utility or script function.
L93: def __getitem__(self, key):    Function `__getitem__`    utility or script function.
L98: def get(self, key, default=None):    Function `get`    Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/requests/status_codes.py

```

L109: def _init():    Function `_init`    utility or script function.
L116: def doc(code):    Function `doc`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/unix.py

```

L18: def getuid() -> NoReturn:    Function `getuid`    Returns or fetches data.
L26: class Unix(PlatformDirsABC):    # noqa: PLR0904    Class (`Unix`)    component used by the
app (see file context: None).
L40: def user_data_dir(self) -> str:    Function `user_data_dir`    utility or script function.
L51: def _site_data_dirs(self) -> list[str]:    Function `_site_data_dirs`    utility or script
function.
L58: def site_data_dir(self) -> str:    Function `site_data_dir`    utility or script function.
L71: def user_config_dir(self) -> str:    Function `user_config_dir`    utility or script
function.
L82: def _site_config_dirs(self) -> list[str]:    Function `_site_config_dirs`    utility or
script function.
L89: def site_config_dir(self) -> str:    Function `site_config_dir`    utility or script
function.
L102: def user_cache_dir(self) -> str:    Function `user_cache_dir`    utility or script
function.

```

```

L113: def site_cache_dir(self) -> str:    Function `site_cache_dir`  utility or script
function.
L118: def user_state_dir(self) -> str:    Function `user_state_dir`  utility or script
function.
L129: def user_log_dir(self) -> str:      Function `user_log_dir`    utility or script function.
L138: def user_documents_dir(self) -> str:  Function `user_documents_dir` utility or script
function.
L143: def user_downloads_dir(self) -> str:  Function `user_downloads_dir` utility or script
function.
L148: def user_pictures_dir(self) -> str:   Function `user_pictures_dir` utility or script
function.
L153: def user_videos_dir(self) -> str:     Function `user_videos_dir`  utility or script
function.
L158: def user_music_dir(self) -> str:      Function `user_music_dir`   utility or script
function.
L163: def user_desktop_dir(self) -> str:     Function `user_desktop_dir` utility or script
function.
L168: def user_runtime_dir(self) -> str:     Function `user_runtime_dir` utility or script
function.
L188: def site_runtime_dir(self) -> str:     Function `site_runtime_dir` utility or script
function.
L210: def site_data_path(self) -> Path:      Function `site_data_path`  utility or script
function.
L215: def site_config_path(self) -> Path:     Function `site_config_path` utility or script
function.
L220: def site_cache_path(self) -> Path:      Function `site_cache_path` utility or script
function.
L224: def iter_config_dirs(self) -> Iterator[str]: Function `iter_config_dirs` utility or
script function.
L229: def iter_data_dirs(self) -> Iterator[str]: Function `iter_data_dirs` utility or
script function.
L235: def _get_user_media_dir(env_var: str, fallback_tilde_path: str) -> str:  Function
`_get_user_media_dir`  utility or script function.
L245: def _get_user_dirs_folder(key: str) -> str | None:  Function `_get_user_dirs_folder`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/__main__.py

```

L26: def main() -> None:    Function `main`  Entry point / main routine.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/api.py

```

L15: class PlatformDirsABC(ABC): # noqa: PLR0904    Class (`PlatformDirsABC`) component used
by the app (see file context: None).
L18: def __init__( # noqa: PLR0913, PLR0917    Function `__init__`  utility or script

```

```

function.
L81: def _append_app_name_and_version(self, *base: str) -> str:    Function
`_append_app_name_and_version` utility or script function.
L91: def _optionally_create_directory(self, path: str) -> None:    Function
`_optionally_create_directory` utility or script function.
L95: def _first_item_as_path_if_multipath(self, directory: str) -> Path:    Function
`_first_item_as_path_if_multipath` utility or script function.
L103: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L108: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L113: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L118: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L123: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L128: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L133: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script
function.
L138: def user_log_dir(self) -> str:    Function `user_log_dir` utility or script function.
L143: def user_documents_dir(self) -> str:    Function `user_documents_dir` utility or script
function.
L148: def user_downloads_dir(self) -> str:    Function `user_downloads_dir` utility or script
function.
L153: def user_pictures_dir(self) -> str:    Function `user_pictures_dir` utility or script
function.
L158: def user_videos_dir(self) -> str:    Function `user_videos_dir` utility or script
function.
L163: def user_music_dir(self) -> str:    Function `user_music_dir` utility or script
function.
L168: def user_desktop_dir(self) -> str:    Function `user_desktop_dir` utility or script
function.
L173: def user_runtime_dir(self) -> str:    Function `user_runtime_dir` utility or script
function.
L178: def site_runtime_dir(self) -> str:    Function `site_runtime_dir` utility or script
function.
L182: def user_data_path(self) -> Path:    Function `user_data_path` utility or script
function.
L187: def site_data_path(self) -> Path:    Function `site_data_path` utility or script
function.
L192: def user_config_path(self) -> Path:    Function `user_config_path` utility or script
function.
L197: def site_config_path(self) -> Path:    Function `site_config_path` utility or script
function.
L202: def user_cache_path(self) -> Path:    Function `user_cache_path` utility or script
function.
L207: def site_cache_path(self) -> Path:    Function `site_cache_path` utility or script
function.
L212: def user_state_path(self) -> Path:    Function `user_state_path` utility or script
function.
L217: def user_log_path(self) -> Path:    Function `user_log_path` utility or script

```

```

function.
L222: def user_documents_path(self) -> Path:    Function `user_documents_path`  utility or
script function.
L227: def user_downloads_path(self) -> Path:    Function `user_downloads_path`  utility or
script function.
L232: def user_pictures_path(self) -> Path:    Function `user_pictures_path`  utility or
script function.
L237: def user_videos_path(self) -> Path:    Function `user_videos_path`  utility or script
function.
L242: def user_music_path(self) -> Path:    Function `user_music_path`  utility or script
function.
L247: def user_desktop_path(self) -> Path:    Function `user_desktop_path`  utility or script
function.
L252: def user_runtime_path(self) -> Path:    Function `user_runtime_path`  utility or script
function.
L257: def site_runtime_path(self) -> Path:    Function `site_runtime_path`  utility or script
function.
L261: def iter_config_dirs(self) -> Iterator[str]:    Function `iter_config_dirs`  utility or
script function.
L266: def iter_data_dirs(self) -> Iterator[str]:    Function `iter_data_dirs`  utility or
script function.
L271: def iter_cache_dirs(self) -> Iterator[str]:    Function `iter_cache_dirs`  utility or
script function.
L276: def iter_runtime_dirs(self) -> Iterator[str]:    Function `iter_runtime_dirs`  utility
or script function.
L281: def iter_config_paths(self) -> Iterator[Path]:    Function `iter_config_paths`  utility
or script function.
L286: def iter_data_paths(self) -> Iterator[Path]:    Function `iter_data_paths`  utility or
script function.
L291: def iter_cache_paths(self) -> Iterator[Path]:    Function `iter_cache_paths`  utility or
script function.
L296: def iter_runtime_paths(self) -> Iterator[Path]:    Function `iter_runtime_paths`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/__init__.py

```

L30: def _set_platform_dir_class() -> type[PlatformDirsABC]:    Function
`_set_platform_dir_class`  utility or script function.
L53: def user_data_dir(    Function `user_data_dir`  utility or script function.
L77: def site_data_dir(    Function `site_data_dir`  utility or script function.
L101: def user_config_dir(    Function `user_config_dir`  utility or script function.
L125: def site_config_dir(    Function `site_config_dir`  utility or script function.
L149: def user_cache_dir(    Function `user_cache_dir`  utility or script function.
L173: def site_cache_dir(    Function `site_cache_dir`  utility or script function.
L197: def user_state_dir(    Function `user_state_dir`  utility or script function.
L221: def user_log_dir(    Function `user_log_dir`  utility or script function.
L245: def user_documents_dir() -> str:    Function `user_documents_dir`  utility or script
function.

```

```

L250: def user_downloads_dir() -> str:    Function `user_downloads_dir` utility or script
function.
L255: def user_pictures_dir() -> str:    Function `user_pictures_dir` utility or script
function.
L260: def user_videos_dir() -> str:    Function `user_videos_dir` utility or script function.
L265: def user_music_dir() -> str:    Function `user_music_dir` utility or script function.
L270: def user_desktop_dir() -> str:    Function `user_desktop_dir` utility or script
function.
L275: def user_runtime_dir(    Function `user_runtime_dir` utility or script function.
L299: def site_runtime_dir(    Function `site_runtime_dir` utility or script function.
L323: def user_data_path(    Function `user_data_path` utility or script function.
L347: def site_data_path(    Function `site_data_path` utility or script function.
L371: def user_config_path(    Function `user_config_path` utility or script function.
L395: def site_config_path(    Function `site_config_path` utility or script function.
L419: def site_cache_path(    Function `site_cache_path` utility or script function.
L443: def user_cache_path(    Function `user_cache_path` utility or script function.
L467: def user_state_path(    Function `user_state_path` utility or script function.
L491: def user_log_path(    Function `user_log_path` utility or script function.
L515: def user_documents_path() -> Path:    Function `user_documents_path` utility or script
function.
L520: def user_downloads_path() -> Path:    Function `user_downloads_path` utility or script
function.
L525: def user_pictures_path() -> Path:    Function `user_pictures_path` utility or script
function.
L530: def user_videos_path() -> Path:    Function `user_videos_path` utility or script
function.
L535: def user_music_path() -> Path:    Function `user_music_path` utility or script
function.
L540: def user_desktop_path() -> Path:    Function `user_desktop_path` utility or script
function.
L545: def user_runtime_path(    Function `user_runtime_path` utility or script function.
L569: def site_runtime_path(    Function `site_runtime_path` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/android.py

```

L14: class Android(PlatformDirsABC):    Class (`Android`) component used by the app (see file
context: None).
L24: def user_data_dir(self) -> str:    Function `user_data_dir` utility or script function.
L29: def site_data_dir(self) -> str:    Function `site_data_dir` utility or script function.
L34: def user_config_dir(self) -> str:    Function `user_config_dir` utility or script
function.
L42: def site_config_dir(self) -> str:    Function `site_config_dir` utility or script
function.
L47: def user_cache_dir(self) -> str:    Function `user_cache_dir` utility or script
function.
L52: def site_cache_dir(self) -> str:    Function `site_cache_dir` utility or script
function.
L57: def user_state_dir(self) -> str:    Function `user_state_dir` utility or script

```

```

function.
L62: def user_log_dir(self) -> str:    Function `user_log_dir`    utility or script function.
L73: def user_documents_dir(self) -> str:    Function `user_documents_dir`    utility or script
function.
L78: def user_downloads_dir(self) -> str:    Function `user_downloads_dir`    utility or script
function.
L83: def user_pictures_dir(self) -> str:    Function `user_pictures_dir`    utility or script
function.
L88: def user_videos_dir(self) -> str:    Function `user_videos_dir`    utility or script
function.
L93: def user_music_dir(self) -> str:    Function `user_music_dir`    utility or script
function.
L98: def user_desktop_dir(self) -> str:    Function `user_desktop_dir`    utility or script
function.
L103: def user_runtime_dir(self) -> str:    Function `user_runtime_dir`    utility or script
function.
L114: def site_runtime_dir(self) -> str:    Function `site_runtime_dir`    utility or script
function.
L120: def _android_folder() -> str | None:    # noqa: C901    Function `_android_folder`
utility or script function.
L168: def _android_documents_folder() -> str:    Function `_android_documents_folder`    utility
or script function.
L184: def _android_downloads_folder() -> str:    Function `_android_downloads_folder`    utility
or script function.
L200: def _android_pictures_folder() -> str:    Function `_android_pictures_folder`    utility
or script function.
L216: def _android_videos_folder() -> str:    Function `_android_videos_folder`    utility or
script function.
L232: def _android_music_folder() -> str:    Function `_android_music_folder`    utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/macos.py

```

L15: class MacOS(PlatformDirsABC):    Class (`MacOS`)    component used by the app (see file
context: None).
L28: def user_data_dir(self) -> str:    Function `user_data_dir`    utility or script function.
L33: def site_data_dir(self) -> str:    Function `site_data_dir`    utility or script function.
L51: def site_data_path(self) -> Path:    Function `site_data_path`    utility or script
function.
L56: def user_config_dir(self) -> str:    Function `user_config_dir`    utility or script
function.
L61: def site_config_dir(self) -> str:    Function `site_config_dir`    utility or script
function.
L66: def user_cache_dir(self) -> str:    Function `user_cache_dir`    utility or script
function.
L71: def site_cache_dir(self) -> str:    Function `site_cache_dir`    utility or script
function.
L89: def site_cache_path(self) -> Path:    Function `site_cache_path`    utility or script

```

```

function.
L94: def user_state_dir(self) -> str:    Function `user_state_dir`  utility or script
function.
L99: def user_log_dir(self) -> str:    Function `user_log_dir`  utility or script function.
L104: def user_documents_dir(self) -> str:    Function `user_documents_dir`  utility or script
function.
L109: def user_downloads_dir(self) -> str:    Function `user_downloads_dir`  utility or script
function.
L114: def user_pictures_dir(self) -> str:    Function `user_pictures_dir`  utility or script
function.
L119: def user_videos_dir(self) -> str:    Function `user_videos_dir`  utility or script
function.
L124: def user_music_dir(self) -> str:    Function `user_music_dir`  utility or script
function.
L129: def user_desktop_dir(self) -> str:    Function `user_desktop_dir`  utility or script
function.
L134: def user_runtime_dir(self) -> str:    Function `user_runtime_dir`  utility or script
function.
L139: def site_runtime_dir(self) -> str:    Function `site_runtime_dir`  utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/platformdirs/windows.p y

```

L16: class Windows(PlatformDirsABC):    Class (`Windows`)  component used by the app (see file
context: None).
L28: def user_data_dir(self) -> str:    Function `user_data_dir`  utility or script function.
L38: def _append_parts(self, path: str, *, opinion_value: str | None = None) -> str:
Function `_append_parts`  utility or script function.
L54: def site_data_dir(self) -> str:    Function `site_data_dir`  utility or script function.
L60: def user_config_dir(self) -> str:    Function `user_config_dir`  utility or script
function.
L65: def site_config_dir(self) -> str:    Function `site_config_dir`  utility or script
function.
L70: def user_cache_dir(self) -> str:    Function `user_cache_dir`  utility or script
function.
L79: def site_cache_dir(self) -> str:    Function `site_cache_dir`  utility or script
function.
L85: def user_state_dir(self) -> str:    Function `user_state_dir`  utility or script
function.
L90: def user_log_dir(self) -> str:    Function `user_log_dir`  utility or script function.
L99: def user_documents_dir(self) -> str:    Function `user_documents_dir`  utility or script
function.
L104: def user_downloads_dir(self) -> str:    Function `user_downloads_dir`  utility or script
function.
L109: def user_pictures_dir(self) -> str:    Function `user_pictures_dir`  utility or script
function.
L114: def user_videos_dir(self) -> str:    Function `user_videos_dir`  utility or script

```



```

function.
L119: def user_music_dir(self) -> str:    Function `user_music_dir`    utility or script
function.
L124: def user_desktop_dir(self) -> str:    Function `user_desktop_dir`    utility or script
function.
L129: def user_runtime_dir(self) -> str:    Function `user_runtime_dir`    utility or script
function.
L138: def site_runtime_dir(self) -> str:    Function `site_runtime_dir`    utility or script
function.
L143: def get_win_folder_from_env_vars(csidl_name: str) -> str:    Function
`get_win_folder_from_env_vars`    Returns or fetches data.
L164: def get_win_folder_if_csidl_name_not_env_var(csidl_name: str) -> str | None:    Function
`get_win_folder_if_csidl_name_not_env_var`    Returns or fetches data.
L183: def get_win_folder_from_registry(csidl_name: str) -> str:    Function
`get_win_folder_from_registry`    Returns or fetches data.
L219: def get_win_folder_via_ctypes(csidl_name: str) -> str:    Function
`get_win_folder_via_ctypes`    Returns or fetches data.
L258: def _pick_get_win_folder() -> Callable[[str], str]:    Function `_pick_get_win_folder`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_parser.py

```

L77: class DEPRECATED_DEFAULT:    Class (`DEPRECATED_DEFAULT`)    component used by the app (see
file context: None).
L82: class TOMLDecodeError(ValueError):    Class (`TOMLDecodeError`)    component used by the
app (see file context: None).
L93: def __init__(    Function `__init__`    utility or script function.
L143: def load(__fp: IO[bytes], *, parse_float: ParseFloat = float) -> dict[str, Any]:
Function `load`    Loads data from storage or remote.
L155: def loads(__s: str, *, parse_float: ParseFloat = float) -> dict[str, Any]:    Function
`loads`    Loads data from storage or remote.
L226: class Flags:    Class (`Flags`)    component used by the app (see file context: None).
L235: def __init__(self) -> None:    Function `__init__`    utility or script function.
L239: def add_pending(self, key: Key, flag: int) -> None:    Function `add_pending`    utility
or script function.
L242: def finalize_pending(self) -> None:    Function `finalize_pending`    utility or script
function.
L247: def unset_all(self, key: Key) -> None:    Function `unset_all`    utility or script
function.
L255: def set(self, key: Key, flag: int, *, recursive: bool) -> None:    # noqa: A003
Function `set`    Sets or updates a value.
L266: def is_(self, key: Key, flag: int) -> bool:    Function `is_`    utility or script
function.
L284: class NestedDict:    Class (`NestedDict`)    component used by the app (see file context:
None).
L285: def __init__(self) -> None:    Function `__init__`    utility or script function.
L289: def get_or_create_nest(    Function `get_or_create_nest`    Returns or fetches data.
L306: def append_nest_to_list(self, key: Key) -> None:    Function `append_nest_to_list`

```

utility or script function.

L318: class Output: Class (`Output`) component used by the app (see file context: None).

L319: def __init__(self) -> None: Function `\_\_init\_\_` utility or script function.

L324: def skip_chars(src: str, pos: Pos, chars: Iterable[str]) -> Pos: Function
`skip\_chars` utility or script function.

L333: def skip_until(Function `skip\_until` utility or script function.

L355: def skip_comment(src: str, pos: Pos) -> Pos: Function `skip\_comment` utility or
script function.

L367: def skip_comments_and_array_ws(src: str, pos: Pos) -> Pos: Function
`skip\_comments\_and\_array\_ws` utility or script function.

L376: def create_dict_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]: Function
`create\_dict\_rule` Creates a resource or document.

L396: def create_list_rule(src: str, pos: Pos, out: Output) -> tuple[Pos, Key]: Function
`create\_list\_rule` Creates a resource or document.

L419: def key_value_rule(Function `key\_value\_rule` utility or script function.

L453: def parse_key_value_pair(Function `parse\_key\_value\_pair` utility or script
function.

L469: def parse_key(src: str, pos: Pos) -> tuple[Pos, Key]: Function `parse\_key` utility
or script function.

L491: def parse_key_part(src: str, pos: Pos) -> tuple[Pos, str]: Function `parse\_key\_part`
utility or script function.

L507: def parse_one_line_basic_str(src: str, pos: Pos) -> tuple[Pos, str]: Function
`parse\_one\_line\_basic\_str` utility or script function.

L512: def parse_array(Function `parse\_array` utility or script function.

L538: def parse_inline_table(Function `parse\_inline\_table` utility or script function.

L572: def parse_basic_str_escape(Function `parse\_basic\_str\_escape` utility or script
function.

L601: def parse_basic_str_escape_multiline(src: str, pos: Pos) -> tuple[Pos, str]: Function
`parse\_basic\_str\_escape\_multiline` utility or script function.

L605: def parse_hex_char(src: str, pos: Pos, hex_len: int) -> tuple[Pos, str]: Function
`parse\_hex\_char` utility or script function.

L618: def parse_literal_str(src: str, pos: Pos) -> tuple[Pos, str]: Function
`parse\_literal\_str` utility or script function.

L627: def parse_multiline_str(src: str, pos: Pos, *, literal: bool) -> tuple[Pos, str]:
Function `parse\_multiline\_str` utility or script function.

L658: def parse_basic_str(src: str, pos: Pos, *, multiline: bool) -> tuple[Pos, str]:
Function `parse\_basic\_str` utility or script function.

L690: def parse_value(Function `parse\_value` utility or script function.

L766: def is_unicode_scalar_value(codepoint: int) -> bool: Function
`is\_unicode\_scalar\_value` utility or script function.

L770: def make_safe_parse_float(parse_float: ParseFloat) -> ParseFloat: Function
`make\_safe\_parse\_float` utility or script function.

L782: def safe_parse_float(float_str: str) -> Any: Function `safe\_parse\_float` utility or
script function.

.venv/lib/python3.12/site-packages/pip/_vendor/tomli/_re.py

L57: def match_to_datetime(match: re.Match[str]) -> datetime | date: Function

```

`match_to_datetime` utility or script function.
L96: def cached_tz(hour_str: str, minute_str: str, sign_str: str) -> timezone:    Function
`cached_tz` utility or script function.
L106: def match_to_localtime(match: re.Match[str]) -> time:    Function `match_to_localtime`
utility or script function.
L112: def match_to_number(match: re.Match[str], parse_float: ParseFloat) -> Any:    Function
`match_to_number` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/exceptions.py

```

L1: class UnpackException(Exception):    Class (`UnpackException`) component used by the app
(see file context: None).
L10: class BufferFull(UnpackException):    Class (`BufferFull`) component used by the app
(see file context: None).
L14: class OutOfData(UnpackException):    Class (`OutOfData`) component used by the app (see
file context: None).
L18: class FormatError(ValueError, UnpackException):    Class (`FormatError`) component used
by the app (see file context: None).
L22: class StackError(ValueError, UnpackException):    Class (`StackError`) component used by
the app (see file context: None).
L30: class ExtraData(UnpackValueError):    Class (`ExtraData`) component used by the app (see
file context: None).
L37: def __init__(self, unpacked, extra):    Function `__init__` utility or script function.
L41: def __str__(self):    Function `__str__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/__init__.py

```

L20: def pack(o, stream, **kwargs):    Function `pack` utility or script function.
L30: def packb(o, **kwargs):    Function `packb` utility or script function.
L39: def unpack(stream, **kwargs):    Function `unpack` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/ext.py

```

L6: class ExtType(namedtuple("ExtType", "code data")):    Class (`ExtType`) component used by
the app (see file context: None).
L9: def __new__(cls, code, data):    Function `__new__` utility or script function.
L19: class Timestamp:    Class (`Timestamp`) component used by the app (see file context:
None).
L31: def __init__(self, seconds, nanoseconds=0):    Function `__init__` utility or script
function.
L53: def __repr__(self):    Function `__repr__` utility or script function.
L57: def __eq__(self, other):    Function `__eq__` utility or script function.
L63: def __ne__(self, other):    Function `__ne__` utility or script function.
L67: def __hash__(self):    Function `__hash__` utility or script function.

```

```

L71: def from_bytes(b):    Function `from_bytes` utility or script function.
L97: def to_bytes(self):   Function `to_bytes` utility or script function.
L119: def from_unix(unix_sec):  Function `from_unix` utility or script function.
L129: def to_unix(self):    Function `to_unix` utility or script function.
L138: def from_unix_nano(unix_ns):  Function `from_unix_nano` utility or script function.
L146: def to_unix_nano(self):  Function `to_unix_nano` utility or script function.
L154: def to_datetime(self):  Function `to_datetime` utility or script function.
L165: def from_datetime(dt):  Function `from_datetime` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/msgpack/fallback.py

```

L13: class BytesIO:    Class (`BytesIO`) component used by the app (see file context: None).
L14: def __init__(self, s=b''):    Function `__init__` utility or script function.
L21: def write(self, s):    Function `write` utility or script function.
L28: def getvalue(self):    Function `getvalue` Returns or fetches data.
L36: def newlist_hint(size):  Function `newlist_hint` utility or script function.
L58: def _check_type_strict(obj, t, type=type, tuple=tuple):  Function `_check_type_strict` utility or script function.
L65: def _get_data_from_buffer(obj):  Function `_get_data_from_buffer` utility or script function.
L72: def unpackb(packed, **kwargs):  Function `unpackb` utility or script function.
L130: class Unpacker:    Class (`Unpacker`) component used by the app (see file context: None).
L226: def __init__(    Function `__init__` utility or script function.
L318: def feed(self, next_bytes):  Function `feed` utility or script function.
L334: def _consume(self):  Function `_consume` utility or script function.
L339: def _got_extradata(self):  Function `_got_extradata` utility or script function.
L342: def _get_extradata(self):  Function `_get_extradata` utility or script function.
L345: def read_bytes(self, n):  Function `read_bytes` utility or script function.
L350: def _read(self, n, raise_outofdata=True):  Function `_read` utility or script function.
L358: def _reserve(self, n, raise_outofdata=True):  Function `_reserve` utility or script function.
L392: def _read_header(self):  Function `_read_header` utility or script function.
L488: def _unpack(self, execute=EX_CONSTRUCT):  Function `_unpack` utility or script function.
L562: def __iter__(self):  Function `__iter__` utility or script function.
L565: def __next__(self):  Function `__next__` utility or script function.
L578: def skip(self):  Function `skip` utility or script function.
L582: def unpack(self):  Function `unpack` utility or script function.
L590: def read_array_header(self):  Function `read_array_header` utility or script function.
L595: def read_map_header(self):  Function `read_map_header` utility or script function.
L600: def tell(self):  Function `tell` utility or script function.
L604: class Packer:    Class (`Packer`) component used by the app (see file context: None).
L653: def __init__(    Function `__init__` utility or script function.
L676: def _pack(    Function `_pack` utility or script function.
L800: def pack(self, obj):  Function `pack` utility or script function.

```

```

L811: def pack_map_pairs(self, pairs):    Function `pack_map_pairs` utility or script
function.
L818: def pack_array_header(self, n):    Function `pack_array_header` utility or script
function.
L827: def pack_map_header(self, n):    Function `pack_map_header` utility or script function.
L836: def pack_ext_type(self, typecode, data):    Function `pack_ext_type` utility or script
function.
L865: def _pack_array_header(self, n):    Function `_pack_array_header` utility or script
function.
L874: def _pack_map_header(self, n):    Function `_pack_map_header` utility or script
function.
L883: def _pack_map_pairs(self, n, pairs, nest_limit=DEFAULT_RECURSE_LIMIT):    Function
`_pack_map_pairs` utility or script function.
L889: def _pack_raw_header(self, n):    Function `_pack_raw_header` utility or script
function.
L901: def _pack_bin_header(self, n):    Function `_pack_bin_header` utility or script
function.
L913: def bytes(self):    Function `bytes` utility or script function.
L917: def reset(self):    Function `reset` utility or script function.
L924: def getbuffer(self):    Function `getbuffer` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/pkg_resources/_init_.py

```

L135: class _LoaderProtocol(Protocol):    Class (`_LoaderProtocol`) component used by the app
(see file context: None).
L136: def load_module(self, fullname: str, /) -> types.ModuleType: ...    Function
`load_module` Loads data from storage or remote.
L139: class _ZipLoaderModule(Protocol):    Dependency injection module (`_ZipLoaderModule`)
provides DI bindings.
L146: class PEP440Warning(RuntimeWarning):    Class (`PEP440Warning`) component used by the
app (see file context: None).
L159: def _declare_state(vartype: str, varname: str, initial_value: _T) -> _T:    Function
`_declare_state` utility or script function.
L164: def __getstate__() -> dict[str, Any]:    Function `__getstate__` utility or script
function.
L172: def __setstate__(state: dict[str, Any]) -> dict[str, Any]:    Function `__setstate__`
utility or script function.
L179: def _sget_dict(val):    Function `_sget_dict` utility or script function.
L183: def _sset_dict(key, ob, state):    Function `_sset_dict` utility or script function.
L188: def _sget_object(val):    Function `_sget_object` utility or script function.
L192: def _sset_object(key, ob, state):    Function `_sset_object` utility or script
function.
L199: def get_supported_platform():    Function `get_supported_platform` Returns or fetches
data.
L309: class ResolutionError(Exception):    Class (`ResolutionError`) component used by the
app (see file context: None).
L312: def __repr__(self):    Function `__repr__` utility or script function.

```

```

L316: class VersionConflict(ResolutionError):  Class (`VersionConflict`) component used by
the app (see file context: None).
L327: def dist(self) -> Distribution:  Function `dist` utility or script function.
L331: def req(self) -> Requirement:  Function `req` utility or script function.
L334: def report(self):  Function `report` utility or script function.
L337: def with_context(self, required_by: set[Distribution | str]):  Function `with_context`
utility or script function.
L348: class ContextualVersionConflict(VersionConflict):  Class (`ContextualVersionConflict`)
component used by the app (see file context: None).
L357: def required_by(self) -> set[str]:  Function `required_by` utility or script
function.
L361: class DistributionNotFound(ResolutionError):  Class (`DistributionNotFound`)
component used by the app (see file context: None).
L370: def req(self) -> Requirement:  Function `req` utility or script function.
L374: def requirers(self) -> set[str] | None:  Function `requirers` utility or script
function.
L378: def requirers_str(self):  Function `requirers_str` utility or script function.
L383: def report(self):  Function `report` utility or script function.
L386: def __str__(self):  Function `__str__` utility or script function.
L390: class UnknownExtra(ResolutionError):  Class (`UnknownExtra`) component used by the
app (see file context: None).
L404: def register_loader_type(  Function `register_loader_type` utility or script
function.
L417: def get_provider(moduleOrReq: str) -> IResourceProvider: ...  Function `get_provider`
Returns or fetches data.
L419: def get_provider(moduleOrReq: Requirement) -> Distribution: ...  Function
`get_provider` Returns or fetches data.
L420: def get_provider(moduleOrReq: str | Requirement) -> IResourceProvider | Distribution:
Function `get_provider` Returns or fetches data.
L434: def _macos_vers():  Function `_macos_vers` utility or script function.
L447: def _macos_arch(machine):  Function `_macos_arch` utility or script function.
L451: def get_build_platform():  Function `get_build_platform` Returns or fetches data.
L482: def compatible_platforms(provided: str | None, required: str | None):  Function
`compatible_platforms` utility or script function.
L532: def get_distribution(dist: _DistributionT) -> _DistributionT: ...  Function
`get_distribution` Returns or fetches data.
L534: def get_distribution(dist: _PkgReqType) -> Distribution: ...  Function
`get_distribution` Returns or fetches data.
L535: def get_distribution(dist: Distribution | _PkgReqType) -> Distribution:  Function
`get_distribution` Returns or fetches data.
L547: def load_entry_point(dist: _EPDistType, group: str, name: str) -> _ResolvedEntryPoint:
Function `load_entry_point` Loads data from storage or remote.
L553: def get_entry_map(  Function `get_entry_map` Returns or fetches data.
L557: def get_entry_map(dist: _EPDistType, group: str) -> dict[str, EntryPoint]: ...
Function `get_entry_map` Returns or fetches data.
L558: def get_entry_map(dist: _EPDistType, group: str | None = None):  Function
`get_entry_map` Returns or fetches data.
L563: def get_entry_info(dist: _EPDistType, group: str, name: str):  Function
`get_entry_info` Returns or fetches data.
L568: class IMetadataProvider(Protocol):  Class (`IMetadataProvider`) component used by the
app (see file context: None).

```

```

L569: def has_metadata(self, name: str) -> bool:    Function `has_metadata` utility or script
function.
L572: def get_metadata(self, name: str) -> str:    Function `get_metadata` Returns or fetches
data.
L575: def get_metadata_lines(self, name: str) -> Iterator[str]:    Function
`get_metadata_lines` Returns or fetches data.
L581: def metadata_isdir(self, name: str) -> bool:    Function `metadata_isdir` utility or
script function.
L584: def metadata_listdir(self, name: str) -> list[str]:    Function `metadata_listdir`
utility or script function.
L587: def run_script(self, script_name: str, namespace: dict[str, Any]) -> None:    Function
`run_script` utility or script function.
L591: class IResourceProvider(IMetadataProvider, Protocol):    Class (`IResourceProvider`)
component used by the app (see file context: None).
L594: def get_resource_filename(    Function `get_resource_filename` Returns or fetches data.
L601: def get_resource_stream(    Function `get_resource_stream` Returns or fetches data.
L608: def get_resource_string(    Function `get_resource_string` Returns or fetches data.
L615: def has_resource(self, resource_name: str) -> bool:    Function `has_resource` utility
or script function.
L618: def resource_isdir(self, resource_name: str) -> bool:    Function `resource_isdir`
utility or script function.
L621: def resource_listdir(self, resource_name: str) -> list[str]:    Function
`resource_listdir` utility or script function.
L625: class WorkingSet:    Class (`WorkingSet`) component used by the app (see file context:
None).
L628: def __init__(self, entries: Iterable[str] | None = None):    Function `__init__`
utility or script function.
L643: def _build_master(cls):    Function `_build_master` utility or script function.
L663: def _build_from_requirements(cls, req_spec):    Function `_build_from_requirements`
utility or script function.
L684: def add_entry(self, entry: str):    Function `add_entry` utility or script function.
L699: def __contains__(self, dist: Distribution) -> bool:    Function `__contains__` utility
or script function.
L703: def find(self, req: Requirement) -> Distribution | None:    Function `find` utility or
script function.
L727: def iter_entry_points(self, group: str, name: str | None = None):    Function
`iter_entry_points` utility or script function.
L741: def run_script(self, requires: str, script_name: str):    Function `run_script` utility
or script function.
L749: def __iter__(self) -> Iterator[Distribution]:    Function `__iter__` utility or script
function.
L766: def add(    Function `add` utility or script function.
L805: def resolve(    Function `resolve` utility or script function.
L814: def resolve(    Function `resolve` utility or script function.
L824: def resolve(    Function `resolve` utility or script function.
L832: def resolve(    Function `resolve` utility or script function.
L906: def _resolve_dist(    Function `_resolve_dist` utility or script function.
L938: def find_plugins(    Function `find_plugins` utility or script function.
L946: def find_plugins(    Function `find_plugins` utility or script function.
L955: def find_plugins(    Function `find_plugins` utility or script function.
L962: def find_plugins(    Function `find_plugins` utility or script function.

```



```

L1052: def require(self, *requirements: _NestedStr):    Function `require` utility or script
function.
L1068: def subscribe(    Function `subscribe` utility or script function.
L1084: def __added_new(self, dist):    Function `__added_new` utility or script function.
L1088: def __getstate__(self):    Function `__getstate__` utility or script function.
L1097: def __setstate__(self, e_k_b_n_c):    Function `__setstate__` utility or script
function.
L1106: class _ReqExtras(Dict["Requirement", Tuple[str, ...]]):    Class (`_ReqExtras`)
component used by the app (see file context: None).
L1111: def markers_pass(self, req: Requirement, extras: tuple[str, ...] | None = None):
Function `markers_pass` utility or script function.
L1126: class Environment:    Class (`Environment`) component used by the app (see file
context: None).
L1129: def __init__(    Function `__init__` utility or script function.
L1156: def can_add(self, dist: Distribution):    Function `can_add` utility or script
function.
L1170: def remove(self, dist: Distribution):    Function `remove` utility or script function.
L1174: def scan(self, search_path: Iterable[str] | None = None):    Function `scan` utility
or script function.
L1189: def __getitem__(self, project_name: str) -> list[Distribution]:    Function
`__getitem__` utility or script function.
L1200: def add(self, dist: Distribution):    Function `add` utility or script function.
L1209: def best_match(    Function `best_match` utility or script function.
L1217: def best_match(    Function `best_match` utility or script function.
L1224: def best_match(    Function `best_match` utility or script function.
L1258: def obtain(    Function `obtain` utility or script function.
L1264: def obtain(    Function `obtain` utility or script function.
L1270: def obtain(    Function `obtain` utility or script function.
L1275: def obtain(    Function `obtain` utility or script function.
L1293: def __iter__(self) -> Iterator[str]:    Function `__iter__` utility or script
function.
L1299: def __iadd__(self, other: Distribution | Environment):    Function `__iadd__` utility
or script function.
L1311: def __add__(self, other: Distribution | Environment):    Function `__add__` utility or
script function.
L1323: class ExtractionError(RuntimeError):    Class (`ExtractionError`) component used by
the app (see file context: None).
L1343: class ResourceManager:    Manager (`ResourceManager`) orchestration/utility for
managing resources or behaviors.
L1348: def __init__(self):    Function `__init__` utility or script function.
L1351: def resource_exists(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_exists` utility or script function.
L1355: def resource_isdir(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_isdir` utility or script function.
L1359: def resource_filename(    Function `resource_filename` utility or script function.
L1367: def resource_stream(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_stream` utility or script function.
L1373: def resource_string(    Function `resource_string` utility or script function.
L1381: def resource_listdir(self, package_or_requirement: _PkgReqType, resource_name: str):
Function `resource_listdir` utility or script function.
L1385: def extraction_error(self) -> NoReturn:    Function `extraction_error` utility or

```



```

script function.
L1415: def get_cache_path(self, archive_name: str, names: Iterable[StrPath] = ()):  Function
`get_cache_path` Returns or fetches data.
L1441: def _warn_unsafe_extraction_path(path):  Function `_warn_unsafe_extraction_path`
utility or script function.
L1467: def postprocess(self, tempname: StrOrBytesPath, filename: StrOrBytesPath):  Function
`postprocess` utility or script function.
L1487: def set_extraction_path(self, path: str):  Function `set_extraction_path` Sets or
updates a value.
L1511: def cleanup_resources(self, force: bool = False) -> list[str]:  Function
`cleanup_resources` utility or script function.
L1526: def get_default_cache() -> str:  Function `get_default_cache` Returns or fetches
data.
L1535: def safe_name(name: str):  Function `safe_name` utility or script function.
L1543: def safe_version(version: str):  Function `safe_version` utility or script function.
L1555: def _forgiving_version(version):  Function `_forgiving_version` utility or script
function.
L1580: def _safe_segment(segment):  Function `_safe_segment` utility or script function.
L1587: def safe_extra(extra: str):  Function `safe_extra` utility or script function.
L1596: def to_filename(name: str):  Function `to_filename` utility or script function.
L1604: def invalid_marker(text: str):  Function `invalid_marker` utility or script
function.
L1618: def evaluate_marker(text: str, extra: str | None = None) -> bool:  Function
`evaluate_marker` utility or script function.
L1633: class NullProvider:  Class (`NullProvider`) component used by the app (see file
context: None).
L1640: def __init__(self, module: _ModuleLike):  Function `__init__` utility or script
function.
L1644: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
Function `get_resource_filename` Returns or fetches data.
L1647: def get_resource_stream(self, manager: ResourceManager, resource_name: str):
Function `get_resource_stream` Returns or fetches data.
L1650: def get_resource_string(  Function `get_resource_string` Returns or fetches data.
L1655: def has_resource(self, resource_name: str):  Function `has_resource` utility or
script function.
L1658: def _get_metadata_path(self, name):  Function `_get_metadata_path` utility or script
function.
L1661: def has_metadata(self, name: str) -> bool:  Function `has_metadata` utility or
script function.
L1668: def get_metadata(self, name: str):  Function `get_metadata` Returns or fetches data.
L1681: def get_metadata_lines(self, name: str) -> Iterator[str]:  Function
`get_metadata_lines` Returns or fetches data.
L1684: def resource_isdir(self, resource_name: str):  Function `resource_isdir` utility or
script function.
L1687: def metadata_isdir(self, name: str) -> bool:  Function `metadata_isdir` utility or
script function.
L1690: def resource_listdir(self, resource_name: str):  Function `resource_listdir` utility
or script function.
L1693: def metadata_listdir(self, name: str) -> list[str]:  Function `metadata_listdir`
utility or script function.
L1698: def run_script(self, script_name: str, namespace: dict[str, Any]):  Function

```

```

`run_script` utility or script function.
L1727: def _has(self, path) -> bool: Function `_has` utility or script function.
L1732: def _isdir(self, path) -> bool: Function `_isdir` utility or script function.
L1737: def _listdir(self, path) -> list[str]: Function `_listdir` utility or script
function.
L1742: def _fn(self, base: str | None, resource_name: str): Function `_fn` utility or
script function.
L1753: def _validate_resource_path(path): Function `_validate_resource_path` utility or
script function.
L1827: def _get(self, path) -> bytes: Function `_get` utility or script function.
L1839: def _parents(path): Function `_parents` utility or script function.
L1850: class EggProvider(NullProvider): Class (`EggProvider`) component used by the app
(see file context: None).
L1853: def __init__(self, module: _ModuleLike): Function `__init__` utility or script
function.
L1857: def _setup_prefix(self): Function `_setup_prefix` utility or script function.
L1864: def _set_egg(self, path: str): Function `_set_egg` utility or script function.
L1870: class DefaultProvider(EggProvider): Class (`DefaultProvider`) component used by the
app (see file context: None).
L1873: def _has(self, path) -> bool: Function `_has` utility or script function.
L1876: def _isdir(self, path) -> bool: Function `_isdir` utility or script function.
L1879: def _listdir(self, path): Function `_listdir` utility or script function.
L1882: def get_resource_stream(self, manager: object, resource_name: str): Object
(singleton).
L1885: def _get(self, path) -> bytes: Function `_get` utility or script function.
L1890: def _register(cls): Function `_register` utility or script function.
L1903: class EmptyProvider(NullProvider): Class (`EmptyProvider`) component used by the
app (see file context: None).
L1911: def _get(self, path) -> bytes: Function `_get` utility or script function.
L1914: def _listdir(self, path): Function `_listdir` utility or script function.
L1917: def __init__(self): Function `__init__` utility or script function.
L1924: class ZipManifests(Dict[str, "MemoizedZipManifests.manifest_mod"]): Class
(`ZipManifests`) component used by the app (see file context: None).
L1931: def build(cls, path: str): Function `build` Constructs or prepares an object.
L1952: class MemoizedZipManifests(ZipManifests): Class (`MemoizedZipManifests`) component
used by the app (see file context: None).
L1957: class manifest_mod(NamedTuple): Class (`manifest_mod`) component used by the app
(see file context: None).
L1961: def load(self, path: str) -> dict[str, zipfile.ZipInfo]: # type: ignore[override] #
ZipManifests.load is a classmethod Function `load` Loads data from storage or remote.
L1975: class ZipProvider(EggProvider): Class (`ZipProvider`) component used by the app
(see file context: None).
L1983: def __init__(self, module: _ZipLoaderModule): Function `__init__` utility or script
function.
L1987: def _zipinfo_name(self, fspath): Function `_zipinfo_name` utility or script
function.
L1997: def _parts(self, zip_path): Function `_parts` utility or script function.
L2006: def zipinfo(self): Function `zipinfo` utility or script function.
L2009: def get_resource_filename(self, manager: ResourceManager, resource_name: str):
Function `get_resource_filename` Returns or fetches data.
L2023: def _get_date_and_size(zip_stat): Function `_get_date_and_size` utility or script

```

```

function.
L2032: def _extract_resource(self, manager: ResourceManager, zip_path) -> str: # noqa: C901
    Function `_extract_resource` utility or script function.
L2086: def _is_current(self, file_path, zip_path): Function `_is_current` utility or
script function.
L2102: def _get_eager_resources(self): Function `_get_eager_resources` utility or script
function.
L2111: def _index(self): Function `_index` utility or script function.
L2128: def _has(self, fspath) -> bool: Function `_has` utility or script function.
L2132: def _isdir(self, fspath) -> bool: Function `_isdir` utility or script function.
L2135: def _listdir(self, fspath): Function `_listdir` utility or script function.
L2138: def _eager_to_zip(self, resource_name: str): Function `_eager_to_zip` utility or
script function.
L2141: def _resource_to_zip(self, resource_name: str): Function `_resource_to_zip` utility
or script function.
L2148: class FileMetadata(EmptyProvider): Class (`FileMetadata`) component used by the app
(see file context: None).
L2160: def __init__(self, path: StrPath): Function `__init__` utility or script function.
L2163: def _get_metadata_path(self, name): Function `_get_metadata_path` utility or script
function.
L2166: def has_metadata(self, name: str) -> bool: Function `has_metadata` utility or
script function.
L2169: def get_metadata(self, name: str): Function `get_metadata` Returns or fetches data.
L2178: def _warn_on_replacement(self, metadata): Function `_warn_on_replacement` utility
or script function.
L2185: def get_metadata_lines(self, name: str) -> Iterator[str]: Function
`get_metadata_lines` Returns or fetches data.
L2189: class PathMetadata(DefaultProvider): Class (`PathMetadata`) component used by the
app (see file context: None).
L2209: def __init__(self, path: str, egg_info: str): Function `__init__` utility or script
function.
L2214: class EggMetadata(ZipProvider): Class (`EggMetadata`) component used by the app
(see file context: None).
L2217: def __init__(self, importer: zipimport.zipimporter): Function `__init__` utility or
script function.
L2234: def register_finder(importer_type: type[_T], distribution_finder:
_DistFinderType[_T]): Function `register_finder` utility or script function.
L2244: def find_distributions(path_item: str, only: bool = False): Function
`find_distributions` utility or script function.
L2251: def find_eggs_in_zip( Function `find_eggs_in_zip` utility or script function.
L2282: def find_nothing( Function `find_nothing` utility or script function.
L2291: def find_on_path(importer: object | None, path_item, only=False): Object
(singleton).
L2311: def dist_factory(path_item, entry, only): Function `dist_factory` utility or script
function.
L2330: class NoDists: Class (`NoDists`) component used by the app (see file context:
None).
L2339: def __bool__(self): Function `__bool__` utility or script function.
L2342: def __call__(self, fullpath): Function `__call__` utility or script function.
L2346: def safe_listdir(path: StrOrBytesPath): Function `safe_listdir` utility or script
function.

```

```

L2362: def distributions_from_metadata(path: str):    Function `distributions_from_metadata`
utility or script function.
L2380: def non_empty_lines(path):    Function `non_empty_lines` utility or script function.
L2390: def resolve_egg_link(path):    Function `resolve_egg_link` utility or script function.
L2416: def register_namespace_handler(    Function `register_namespace_handler` utility or
script function.
L2424: def namespace_handler(importer, path_entry, moduleName, module):    Function
`namespace_handler` utility or script function.
L2436: def _handle_ns(packageName, path_item):    Function `_handle_ns` utility or script
function.
L2473: def _rebuild_mod_path(orig_path, package_name, module: types.ModuleType):    Function
`_rebuild_mod_path` utility or script function.
L2480: def safe_sys_path_index(entry):    Function `safe_sys_path_index` utility or script
function.
L2489: def position_in_sys_path(path):    Function `position_in_sys_path` utility or script
function.
L2507: def declare_namespace(packageName: str):    Function `declare_namespace` utility or
script function.
L2550: def fixup_namespace_packages(path_item: str, parent: str | None = None):    Function
`fixup_namespace_packages` utility or script function.
L2562: def file_ns_handler(    Function `file_ns_handler` utility or script function.
L2587: def null_ns_handler(    Function `null_ns_handler` utility or script function.
L2600: def normalize_path(filename: StrPath) -> str: ...    Function `normalize_path` utility
or script function.
L2602: def normalize_path(filename: BytesPath) -> bytes: ...    Function `normalize_path`
utility or script function.
L2603: def normalize_path(filename: StrOrBytesPath):    Function `normalize_path` utility or
script function.
L2608: def _cygwin_patch(filename: StrOrBytesPath):    # pragma: nocover    Function
`_cygwin_patch` utility or script function.
L2623: def _normalize_cached(filename: StrPath) -> str: ...    Function `_normalize_cached`
utility or script function.
L2625: def _normalize_cached(filename: BytesPath) -> bytes: ...    Function
`_normalize_cached` utility or script function.
L2626: def _normalize_cached(filename: StrOrBytesPath) -> str | bytes: ...    Function
`_normalize_cached` utility or script function.
L2630: def _normalize_cached(filename):    Function `_normalize_cached` utility or script
function.
L2634: def _is_egg_path(path):    Function `_is_egg_path` utility or script function.
L2641: def _is_zip_egg(path):    Function `_is_zip_egg` utility or script function.
L2649: def _is_unpacked_egg(path):    Function `_is_unpacked_egg` utility or script function.
L2658: def _set_parent_ns(packageName):    Function `_set_parent_ns` utility or script
function.
L2681: class EntryPoint:    Class (`EntryPoint`) component used by the app (see file context:
None).
L2684: def __init__(    Function `__init__` utility or script function.
L2700: def __str__(self):    Function `__str__` utility or script function.
L2708: def __repr__(self):    Function `__repr__` utility or script function.
L2712: def load(    Function `load` Loads data from storage or remote.
L2719: def load(    Function `load` Loads data from storage or remote.
L2725: def load(    Function `load` Loads data from storage or remote.

```

```

L2747: def resolve(self) -> _ResolvedEntryPoint:  Function `resolve`  utility or script
function.
L2757: def require(  Function `require`  utility or script function.
L2785: def parse(cls, src: str, dist: Distribution | None = None):  Function `parse`
utility or script function.
L2805: def _parse_extras(cls, extras_spec):  Function `_parse_extras`  utility or script
function.
L2814: def parse_group(  Function `parse_group`  utility or script function.
L2832: def parse_map(  Function `parse_map`  utility or script function.
L2856: def _version_from_file(lines):  Function `_version_from_file`  utility or script
function.
L2862: def is_version_line(line):  Function `is_version_line`  utility or script function.
L2871: class Distribution:  Class (`Distribution`)  component used by the app (see file
context: None).
L2876: def __init__(  Function `__init__`  utility or script function.
L2896: def from_location(  Function `from_location`  utility or script function.
L2923: def _reload_version(self):  Function `_reload_version`  utility or script function.
L2927: def hashcmp(self):  Function `hashcmp`  utility or script function.
L2937: def __hash__(self):  Function `__hash__`  utility or script function.
L2940: def __lt__(self, other: Distribution):  Function `__lt__`  utility or script
function.
L2943: def __le__(self, other: Distribution):  Function `__le__`  utility or script
function.
L2946: def __gt__(self, other: Distribution):  Function `__gt__`  utility or script
function.
L2949: def __ge__(self, other: Distribution):  Function `__ge__`  utility or script
function.
L2952: def __eq__(self, other: object):  Object (singleton).
L2958: def __ne__(self, other: object):  Object (singleton).
L2966: def key(self):  Function `key`  utility or script function.
L2974: def parsed_version(self):  Function `parsed_version`  utility or script function.
L2988: def _forgiving_parsed_version(self):  Function `_forgiving_parsed_version`  utility
or script function.
L3014: def version(self):  Function `version`  utility or script function.
L3029: def _dep_map(self):  Function `_dep_map`  utility or script function.
L3041: def _filter_extras(dm: dict[str | None, list[Requirement]]):  Function
`_filter_extras`  utility or script function.
L3061: def _build_dep_map(self):  Function `_build_dep_map`  utility or script function.
L3068: def requires(self, extras: Iterable[str] = ()):  Function `requires`  utility or
script function.
L3082: def _get_metadata_path_for_display(self, name):  Function
`_get_metadata_path_for_display`  utility or script function.
L3099: def _get_metadata(self, name):  Function `_get_metadata`  utility or script function.
L3103: def _get_version(self):  Function `_get_version`  utility or script function.
L3107: def activate(self, path: list[str] | None = None, replace: bool = False):  Function
`activate`  utility or script function.
L3118: def egg_name(self):  Function `egg_name`  utility or script function.
L3130: def __repr__(self):  Function `__repr__`  utility or script function.
L3136: def __str__(self):  Function `__str__`  utility or script function.
L3144: def __getattr__(self, attr):  Function `_getattr__`  utility or script function.
L3150: def __dir__(self):  Function `__dir__`  utility or script function.

```

```

L3157: def from_filename(    Function `from_filename` utility or script function.
L3167: def as_requirement(self):    Function `as_requirement` utility or script function.
L3176: def load_entry_point(self, group: str, name: str) -> _ResolvedEntryPoint:    Function
`load_entry_point` Loads data from storage or remote.
L3184: def get_entry_map(self, group: None = None) -> dict[str, dict[str, EntryPoint]]: ...
Function `get_entry_map` Returns or fetches data.
L3186: def get_entry_map(self, group: str) -> dict[str, EntryPoint]: ...    Function
`get_entry_map` Returns or fetches data.
L3187: def get_entry_map(self, group: str | None = None):    Function `get_entry_map` Returns
or fetches data.
L3197: def get_entry_info(self, group: str, name: str):    Function `get_entry_info` Returns
or fetches data.
L3202: def insert_on( # noqa: C901    Function `insert_on` utility or script function.
L3275: def check_version_conflict(self):    Function `check_version_conflict` utility or
script function.
L3301: def has_version(self):    Function `has_version` utility or script function.
L3312: def clone(self, **kw: str | int | IResourceProvider | None):    Function `clone`
utility or script function.
L3322: def extras(self):    Function `extras` utility or script function.
L3326: class EggInfoDistribution(Distribution):    Class (`EggInfoDistribution`) component
used by the app (see file context: None).
L3327: def _reload_version(self):    Function `_reload_version` utility or script function.
L3345: class DistInfoDistribution(Distribution):    Class (`DistInfoDistribution`) component
used by the app (see file context: None).
L3355: def _parsed_pkg_info(self):    Function `_parsed_pkg_info` utility or script function.
L3365: def _dep_map(self):    Function `_dep_map` utility or script function.
L3372: def _compute_dependencies(self) -> dict[str | None, list[Requirement]]:    Function
`_compute_dependencies` utility or script function.
L3381: def reqs_for_extra(extra):    Function `reqs_for_extra` utility or script function.
L3405: def issue_warning(*args, **kw):    Function `issue_warning` utility or script
function.
L3418: def parse_requirements(strs: _NestedStr):    Function `parse_requirements` utility or
script function.
L3427: class RequirementParseError(_packaging_requirements.InvalidRequirement):    Class
(`RequirementParseError`) component used by the app (see file context: None).
L3431: class Requirement(_packaging_requirements.Requirement):    Class (`Requirement`)
component used by the app (see file context: None).
L3432: def __init__(self, requirement_string: str):    Function `__init__` utility or script
function.
L3450: def __eq__(self, other: object):    Object (singleton).
L3453: def __ne__(self, other):    Function `__ne__` utility or script function.
L3456: def __contains__(self, item: Distribution | str | tuple[str, ...]) -> bool:    Function
`__contains__` utility or script function.
L3468: def __hash__(self):    Function `__hash__` utility or script function.
L3471: def __repr__(self):    Function `__repr__` utility or script function.
L3475: def parse(s: str | Iterable[str]):    Function `parse` utility or script function.
L3480: def _always_object(classes):    Function `_always_object` utility or script function.
L3490: def _find_adapter(registry: Mapping[type, _AdapterT], ob: object) -> _AdapterT:
Object (singleton).
L3501: def ensure_directory(path: StrOrBytesPath):    Function `ensure_directory` utility or
script function.

```

```

L3507: def _bypass_ensure_directory(path):    Function `_bypass_ensure_directory` utility or
script function.
L3520: def split_sections(s: _NestedStr) -> Iterator[tuple[str | None, list[str]]]:
Function `split_sections` utility or script function.
L3546: def _mkstemp(*args, **kw):    Function `_mkstemp` utility or script function.
L3564: class PkgResourcesDeprecationWarning(Warning):    Class
(`PkgResourcesDeprecationWarning`) component used by the app (see file context: None).
L3577: def _read_utf8_with_fallback(file: str, fallback_encoding=_LOCALE_ENCODING) -> str:
Function `_read_utf8_with_fallback` utility or script function.
L3606: def _call_aside(f, *args, **kwargs):    Function `_call_aside` utility or script
function.
L3612: def _initialize(g=globals()):    Function `_initialize` utility or script function.
L3624: def _initialize_master_working_set():    Function `_initialize_master_working_set`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/controller.py

```

L39: def parse_uri(uri: str) -> tuple[str, str, str, str, str]:    Function `parse_uri`
utility or script function.
L50: class CacheController:    Class (`CacheController`) component used by the app (see file
context: None).
L53: def __init__(    Function `__init__` utility or script function.
L66: def _urlnorm(cls, uri: str) -> str:    Function `_urlnorm` utility or script function.
L86: def cache_url(cls, uri: str) -> str:    Function `cache_url` utility or script function.
L89: def parse_cache_control(self, headers: Mapping[str, str]) -> dict[str, int | None]:
Function `parse_cache_control` utility or script function.
L143: def _load_from_cache(self, request: PreparedRequest) -> HTTPResponse | None:    Function
`_load_from_cache` utility or script function.
L169: def cached_request(self, request: PreparedRequest) -> HTTPResponse | Literal[False]:
Function `cached_request` utility or script function.
L279: def conditional_headers(self, request: PreparedRequest) -> dict[str, str]:    Function
`conditional_headers` utility or script function.
L294: def _cache_set(    Function `_cache_set` utility or script function.
L324: def cache_response(    Function `cache_response` utility or script function.
L471: def update_cached_response(    Function `update_cached_response` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/_cmd.py

```

L22: def setup_logging() -> None:    Function `setup_logging` Sets or updates a value.
L28: def get_session() -> requests.Session:    Function `get_session` Returns or fetches
data.
L40: def get_args() -> Namespace:    Function `get_args` Returns or fetches data.
L46: def main() -> None:    Function `main` Entry point / main routine.

```


.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/adapter.py

```
L26: class CacheControlAdapter(HTTPAdapter):    Class (`CacheControlAdapter`) component used
by the app (see file context: None).
L29: def __init__(    Function `__init__` utility or script function.
L50: def send(    Function `send` utility or script function.
L80: def build_response( # type: ignore[override]    Function `build_response` Constructs or
prepares an object.
L137: def _update_chunk_length(    Function `_update_chunk_length` utility or script
function.
L165: def close(self) -> None:    Function `close` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/filewrapper.py

```
L15: class CallbackFileWrapper:    Class (`CallbackFileWrapper`) component used by the app
(see file context: None).
L34: def __init__(    Function `__init__` utility or script function.
L41: def __getattr__(self, name: str) -> Any:    Function `__getattr__` utility or script
function.
L53: def __is_fp_closed(self) -> bool:    Function `__is_fp_closed` utility or script
function.
L71: def _close(self) -> None:    Function `_close` utility or script function.
L99: def read(self, amt: int | None = None) -> bytes:    Function `read` utility or script
function.
L110: def _safe_read(self, amt: int) -> bytes:    Function `_safe_read` utility or script
function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/cache.py

```
L19: class BaseCache:    Class (`BaseCache`) component used by the app (see file context:
None).
L20: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L23: def set(    Function `set` Sets or updates a value.
L28: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L31: def close(self) -> None:    Function `close` utility or script function.
L35: class DictCache(BaseCache):    Class (`DictCache`) component used by the app (see file
context: None).
L36: def __init__(self, init_dict: MutableMapping[str, bytes] | None = None) -> None:
Function `__init__` utility or script function.
L40: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L43: def set(    Function `set` Sets or updates a value.
L49: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
```



```

L55: class SeparateBodyBaseCache(BaseCache):    Class (`SeparateBodyBaseCache`) component
used by the app (see file context: None).
L68: def set_body(self, key: str, body: bytes) -> None:    Function `set_body` Sets or
updates a value.
L71: def get_body(self, key: str) -> IO[bytes] | None:    Function `get_body` Returns or
fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/wrapper.py

```

L20: def CacheControl(    Function `CacheControl` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/heuristics.py

```

L18: def expire_after(delta: timedelta, date: datetime | None = None) -> datetime:    Function
`expire_after` utility or script function.
L23: def datetime_to_header(dt: datetime) -> str:    Function `datetime_to_header` utility or
script function.
L27: class BaseHeuristic:    Class (`BaseHeuristic`) component used by the app (see file
context: None).
L28: def warning(self, response: HTTPResponse) -> str | None:    Function `warning` utility
or script function.
L39: def update_headers(self, response: HTTPResponse) -> dict[str, str]:    Function
`update_headers` utility or script function.
L48: def apply(self, response: HTTPResponse) -> HTTPResponse:    Function `apply` utility or
script function.
L60: class OneDayCache(BaseHeuristic):    Class (`OneDayCache`) component used by the app
(see file context: None).
L66: def update_headers(self, response: HTTPResponse) -> dict[str, str]:    Function
`update_headers` utility or script function.
L80: class ExpiresAfter(BaseHeuristic):    Class (`ExpiresAfter`) component used by the app
(see file context: None).
L85: def __init__(self, **kw: Any) -> None:    Function `__init__` utility or script
function.
L88: def update_headers(self, response: HTTPResponse) -> dict[str, str]:    Function
`update_headers` utility or script function.
L92: def warning(self, response: HTTPResponse) -> str | None:    Function `warning` utility
or script function.
L97: class LastModified(BaseHeuristic):    Class (`LastModified`) component used by the app
(see file context: None).
L124: def update_headers(self, resp: HTTPResponse) -> dict[str, str]:    Function
`update_headers` utility or script function.
L156: def warning(self, resp: HTTPResponse) -> str | None:    Function `warning` utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/serialize.py

```
L17: class Serializer:    Class (`Serializer`) component used by the app (see file context:
None).
L20: def dumps(    Function `dumps` utility or script function.
L62: def serialize(self, data: dict[str, Any]) -> bytes:    Function `serialize` utility or
script function.
L65: def loads(    Function `loads` Loads data from storage or remote.
L83: def prepare_response(    Function `prepare_response` utility or script function.
L135: def _loads_v4(    Function `_loads_v4` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/caches/file_cache.py

```
L22: class _FileCacheMixin:    Class (`_FileCacheMixin`) component used by the app (see file
context: None).
L25: def __init__(    Function `__init__` utility or script function.
L55: def encode(x: str) -> str:    Function `encode` utility or script function.
L58: def _fn(self, name: str) -> str:    Function `_fn` utility or script function.
L65: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L74: def set(    Function `set` Sets or updates a value.
L80: def _write(self, path: str, data: bytes) -> None:    Function `_write` utility or script
function.
L98: def _delete(self, key: str, suffix: str) -> None:    Function `_delete` utility or
script function.
L107: class FileCache(_FileCacheMixin, BaseCache):    Class (`FileCache`) component used by
the app (see file context: None).
L113: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L117: class SeparateBodyFileCache(_FileCacheMixin, SeparateBodyBaseCache):    Class
(`SeparateBodyFileCache`) component used by the app (see file context: None).
L123: def get_body(self, key: str) -> IO[bytes] | None:    Function `get_body` Returns or
fetches data.
L130: def set_body(self, key: str, body: bytes) -> None:    Function `set_body` Sets or
updates a value.
L134: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L139: def url_to_file_path(url: str, filecache: FileCache) -> str:    Function
`url_to_file_path` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/cachecontrol/caches/redis_cache.py

```
L16: class RedisCache(BaseCache):    Class (`RedisCache`) component used by the app (see file
context: None).
```

```

L17: def __init__(self, conn: Redis[bytes]) -> None:    Function `__init__` utility or script
function.
L20: def get(self, key: str) -> bytes | None:    Function `get` Returns or fetches data.
L23: def set(    Function `set` Sets or updates a value.
L37: def delete(self, key: str) -> None:    Function `delete` Deletes a resource.
L40: def clear(self) -> None:    Function `clear` utility or script function.
L46: def close(self) -> None:    Function `close` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/compat.py

```

L30: def quote(s):    Function `quote` utility or script function.
L93: class CertificateError(ValueError):    Class (`CertificateError`) component used by the
app (see file context: None).
L96: def _dnsname_match(dn, hostname, max_wildcards=1):    Function `_dnsname_match` utility
or script function.
L145: def match_hostname(cert, hostname):    Function `match_hostname` utility or script
function.
L192: class Container(object):    Object (singleton).
L197: def __init__(self, **kwargs):    Function `__init__` utility or script function.
L205: def which(cmd, mode=os.F_OK | os.X_OK, path=None):    Function `which` utility or
script function.
L219: def _access_check(fn, mode):    Function `_access_check` utility or script function.
L277: class ZipExtFile(BaseZipExtFile):    Class (`ZipExtFile`) component used by the app
(see file context: None).
L279: def __init__(self, base):    Function `__init__` utility or script function.
L282: def __enter__(self):    Function `__enter__` utility or script function.
L285: def __exit__(self, *exc_info):    Function `__exit__` utility or script function.
L289: class ZipFile(BaseZipFile):    Class (`ZipFile`) component used by the app (see file
context: None).
L291: def __enter__(self):    Function `__enter__` utility or script function.
L294: def __exit__(self, *exc_info):    Function `__exit__` utility or script function.
L298: def open(self, *args, **kwargs):    Function `open` utility or script function.
L307: def python_implementation():    Function `python_implementation` utility or script
function.
L325: def callable(obj):    Function `callable` utility or script function.
L345: def fsencode(filename):    Function `fsencode` utility or script function.
L354: def fsdecode(filename):    Function `fsdecode` utility or script function.
L371: def _get_normal_name(orig_enc):    Function `_get_normal_name` utility or script
function.
L382: def detect_encoding(readline):    Function `detect_encoding` utility or script
function.
L407: def read_or_stop():    Function `read_or_stop` utility or script function.
L413: def find_cookie(line):    Function `find_cookie` utility or script function.
L494: def _recursive_repr(fillvalue='...'):    Function `_recursive_repr` utility or script
function.
L500: def decorating_function(user_function):    Function `decorating_function` utility or
script function.
L503: def wrapper(self):    Function `wrapper` utility or script function.

```

```

L524: class ChainMap(MutableMapping):  Class (`ChainMap`)  component used by the app (see
file context: None).
L537: def __init__(self, *maps):  Function `__init__`  utility or script function.
L544: def __missing__(self, key):  Function `__missing__`  utility or script function.
L547: def __getitem__(self, key):  Function `__getitem__`  utility or script function.
L557: def get(self, key, default=None):  Function `get`  Returns or fetches data.
L560: def __len__(self):  Function `__len__`  utility or script function.
L564: def __iter__(self):  Function `__iter__`  utility or script function.
L567: def __contains__(self, key):  Function `__contains__`  utility or script function.
L570: def __bool__(self):  Function `__bool__`  utility or script function.
L574: def __repr__(self):  Function `__repr__`  utility or script function.
L579: def fromkeys(cls, iterable, *args):  Function `fromkeys`  utility or script function.
L583: def copy(self):  Function `copy`  utility or script function.
L589: def new_child(self):  # like Django's Context.push()  Function `new_child`  utility or
script function.
L594: def parents(self):  # like Django's Context.pop()  Function `parents`  utility or
script function.
L598: def __setitem__(self, key, value):  Function `__setitem__`  utility or script
function.
L601: def __delitem__(self, key):  Function `__delitem__`  utility or script function.
L608: def popitem(self):  Function `popitem`  utility or script function.
L615: def pop(self, key, *args):  Function `pop`  utility or script function.
L623: def clear(self):  Function `clear`  utility or script function.
L632: def cache_from_source(path, debug_override=None):  Function `cache_from_source`
utility or script function.
L659: class OrderedDict(dict):  Class (`OrderedDict`)  component used by the app (see file
context: None).
L672: def __init__(self, *args, **kwargs):  Function `__init__`  utility or script function.
L689: def __setitem__(self, key, value, dict_setitem=dict.__setitem__):  Function
`__setitem__`  utility or script function.
L699: def __delitem__(self, key, dict_delitem=dict.__delitem__):  Function `__delitem__`
utility or script function.
L708: def __iter__(self):  Function `__iter__`  utility or script function.
L716: def __reversed__(self):  Function `__reversed__`  utility or script function.
L724: def clear(self):  Function `clear`  utility or script function.
L736: def popitem(self, last=True):  Function `popitem`  utility or script function.
L761: def keys(self):  Function `keys`  utility or script function.
L765: def values(self):  Function `values`  utility or script function.
L769: def items(self):  Function `items`  utility or script function.
L773: def iterkeys(self):  Function `iterkeys`  utility or script function.
L777: def itervalues(self):  Function `itervalues`  utility or script function.
L782: def iteritems(self):  Function `iteritems`  utility or script function.
L787: def update(*args, **kwargs):  Function `update`  utility or script function.
L822: def pop(self, key, default=__marker):  Function `pop`  utility or script function.
L835: def setdefault(self, key, default=None):  Function `setdefault`  Sets or updates a
value.
L842: def __repr__(self, _repr_running=None):  Function `__repr__`  utility or script
function.
L857: def __reduce__(self):  Function `__reduce__`  utility or script function.
L867: def copy(self):  Function `copy`  utility or script function.
L872: def fromkeys(cls, iterable, value=None):  Function `fromkeys`  utility or script

```

```

function.
L882: def __eq__(self, other):    Function `__eq__`    utility or script function.
L892: def __ne__(self, other):    Function `__ne__`    utility or script function.
L897: def viewkeys(self):    Function `viewkeys`    utility or script function.
L901: def viewvalues(self):    Function `viewvalues`    utility or script function.
L905: def viewitems(self):    Function `viewitems`    utility or script function.
L915: def valid_ident(s):    Function `valid_ident`    utility or script function.
L930: class ConvertingDict(dict):    Class (`ConvertingDict`)    component used by the app (see
file context: None).
L933: def __getitem__(self, key):    Function `__getitem__`    utility or script function.
L945: def get(self, key, default=None):    Function `get`    Returns or fetches data.
L957: def pop(self, key, default=None):    Function `pop`    utility or script function.
L967: class ConvertingList(list):    Class (`ConvertingList`)    component used by the app (see
file context: None).
L970: def __getitem__(self, key):    Function `__getitem__`    utility or script function.
L982: def pop(self, idx=-1):    Function `pop`    utility or script function.
L991: class ConvertingTuple(tuple):    Class (`ConvertingTuple`)    component used by the app
(see file context: None).
L994: def __getitem__(self, key):    Function `__getitem__`    utility or script function.
L1004: class BaseConfigurator(object):    Object (singleton).
L1024: def __init__(self, config):    Function `__init__`    utility or script function.
L1028: def resolve(self, s):    Function `resolve`    utility or script function.
L1051: def ext_convert(self, value):    Function `ext_convert`    utility or script function.
L1055: def cfg_convert(self, value):    Function `cfg_convert`    utility or script function.
L1090: def convert(self, value):    Function `convert`    utility or script function.
L1119: def configure_custom(self, config):    Function `configure_custom`    utility or script
function.
L1133: def as_tuple(self, value):    Function `as_tuple`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/__init__.py

```

L12: class DistlibException(Exception):    Class (`DistlibException`)    component used by the
app (see file context: None).
L20: class NullHandler(logging.Handler):    Class (`NullHandler`)    component used by the app
(see file context: None).
L22: def handle(self, record):    Function `handle`    utility or script function.
L25: def emit(self, record):    Function `emit`    utility or script function.
L28: def createLock(self):    Function `createLock`    Creates a resource or document.

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/scripts.py

```

L71: def enqueue_executable(executable):    Function `enqueue_executable`    utility or script
function.
L91: class ScriptMaker(object):    Object (singleton).
L100: def __init__(self, source_dir, target_dir, add_launchers=True, dry_run=False,
fileop=None):    Function `__init__`    utility or script function.

```

```

L114: def _get_alterate_executable(self, executable, options):    Function
`_get_alterate_executable` utility or script function.
L123: def _is_shell(self, executable):    Function `_is_shell` utility or script function.
L135: def _fix_jython_executable(self, executable):    Function `_fix_jython_executable`
utility or script function.
L147: def _build_shebang(self, executable, post_interp):    Function `_build_shebang` utility
or script function.
L183: def _get_shebang(self, encoding, post_interp=b'', options=None):    Function
`_get_shebang` utility or script function.
L249: def _get_script_text(self, entry):    Function `_get_script_text` utility or script
function.
L255: def get_manifest(self, exename):    Function `get_manifest` Returns or fetches data.
L259: def _write_script(self, names, shebang, script_bytes, filenames, ext):    Function
`_write_script` utility or script function.
L316: def get_script_filenames(self, name):    Function `get_script_filenames` Returns or
fetches data.
L326: def _make_script(self, entry, filenames, options=None):    Function `_make_script`
utility or script function.
L342: def _copy_script(self, script, filenames):    Function `_copy_script` utility or script
function.
L393: def dry_run(self):    Function `dry_run` utility or script function.
L397: def dry_run(self, value):    Function `dry_run` utility or script function.
L404: def _get_launcher(self, kind):    Function `_get_launcher` utility or script function.
L419: def make(self, specification, options=None):    Function `make` utility or script
function.
L438: def make_multiple(self, specifications, options=None):    Function `make_multiple`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/resources.py

```

L27: class ResourceCache(Cache):    Class (`ResourceCache`) component used by the app (see
file context: None).
L28: def __init__(self, base=None):    Function `__init__` utility or script function.
L34: def is_stale(self, resource, path):    Function `is_stale` utility or script function.
L45: def get(self, resource):    Function `get` Returns or fetches data.
L71: class ResourceBase(object):    Object (singleton).
L72: def __init__(self, finder, name):    Function `__init__` utility or script function.
L77: class Resource(ResourceBase):    Class (`Resource`) component used by the app (see file
context: None).
L85: def as_stream(self):    Function `as_stream` utility or script function.
L95: def file_path(self):    Function `file_path` utility or script function.
L102: def bytes(self):    Function `bytes` utility or script function.
L106: def size(self):    Function `size` utility or script function.
L110: class ResourceContainer(ResourceBase):    Class (`ResourceContainer`) component used by
the app (see file context: None).
L114: def resources(self):    Function `resources` utility or script function.
L118: class ResourceFinder(object):    Object (singleton).
L128: def __init__(self, module):    Function `__init__` utility or script function.

```

```

L133: def _adjust_path(self, path):    Function `_adjust_path` utility or script function.
L136: def _make_path(self, resource_name):    Function `_make_path` utility or script
function.
L148: def _find(self, path):    Function `_find` utility or script function.
L151: def get_cache_info(self, resource):    Function `get_cache_info` Returns or fetches
data.
L154: def find(self, resource_name):    Function `find` utility or script function.
L166: def get_stream(self, resource):    Function `get_stream` Returns or fetches data.
L169: def get_bytes(self, resource):    Function `get_bytes` Returns or fetches data.
L173: def get_size(self, resource):    Function `get_size` Returns or fetches data.
L176: def get_resources(self, resource):    Function `get_resources` Returns or fetches data.
L177: def allowed(f):    Function `allowed` utility or script function.
L182: def is_container(self, resource):    Function `is_container` utility or script
function.
L187: def iterator(self, resource_name):    Function `iterator` utility or script function.
L208: class ZipResourceFinder(ResourceFinder):    Class (`ZipResourceFinder`) component used
by the app (see file context: None).
L212: def __init__(self, module):    Function `__init__` utility or script function.
L223: def _adjust_path(self, path):    Function `_adjust_path` utility or script function.
L226: def _find(self, path):    Function `_find` utility or script function.
L244: def get_cache_info(self, resource):    Function `get_cache_info` Returns or fetches
data.
L249: def get_bytes(self, resource):    Function `get_bytes` Returns or fetches data.
L252: def get_stream(self, resource):    Function `get_stream` Returns or fetches data.
L255: def get_size(self, resource):    Function `get_size` Returns or fetches data.
L259: def get_resources(self, resource):    Function `get_resources` Returns or fetches data.
L274: def _is_directory(self, path):    Function `_is_directory` utility or script function.
L306: def register_finder(loader, finder_maker):    Function `register_finder` utility or
script function.
L313: def finder(package):    Function `finder` utility or script function.
L341: def finder_for_path(path):    Function `finder_for_path` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/distlib/util.py

```

L54: def parse_marker(marker_string):    Function `parse_marker` utility or script function.
L64: def marker_var(remaining):    Function `marker_var` utility or script function.
L100: def marker_expr(remaining):    Function `marker_expr` utility or script function.
L119: def marker_and(remaining):    Function `marker_and` utility or script function.
L130: def marker(remaining):    Function `marker` utility or script function.
L144: def parse_requirement(req):    Function `parse_requirement` utility or script function.
L196: def get_versions(ver_remaining):    Function `get_versions` Returns or fetches data.
L268: def get_resources_dests(resources_root, rules):    Function `get_resources_dests`
Returns or fetches data.
L271: def get_rel_path(root, path):    Function `get_rel_path` Returns or fetches data.
L294: def in_venv():    Function `in_venv` utility or script function.
L304: def get_executable():    Function `get_executable` Returns or fetches data.
L322: def proceed(prompt, allowed_chars, error_prompt=None, default=None):    Function
`proceed` utility or script function.

```



```

L338: def extract_by_key(d, keys):    Function `extract_by_key` utility or script function.
L348: def read_exports(stream):      Function `read_exports` utility or script function.
L368: def read_stream(cp, stream):   Function `read_stream` utility or script function.
L395: def write_exports(exports, stream): Function `write_exports` utility or script
function.
L415: def tempdir():                Function `tempdir` utility or script function.
L424: def chdir(d):                 Function `chdir` utility or script function.
L434: def socket_timeout(seconds=15): Function `socket_timeout` utility or script
function.
L443: class cached_property(object): Object (singleton).
L445: def __init__(self, func):      Function `__init__` utility or script function.
L450: def __get__(self, obj, cls=None): Function `__get__` utility or script function.
L459: def convert_path(pathname):    Function `convert_path` utility or script function.
L486: class FileOperator(object):    Object (singleton).
L488: def __init__(self, dry_run=False): Function `__init__` utility or script function.
L493: def _init_record(self):        Function `_init_record` utility or script function.
L498: def record_as_written(self, path): Function `record_as_written` utility or script
function.
L502: def newer(self, source, target): Function `newer` utility or script function.
L521: def copy_file(self, infile, outfile, check=True): Function `copy_file` utility or
script function.
L538: def copy_stream(self, instream, outfile, encoding=None): Function `copy_stream`
utility or script function.
L553: def write_binary_file(self, path, data): Function `write_binary_file` utility or
script function.
L562: def write_text_file(self, path, data, encoding): Function `write_text_file` utility
or script function.
L565: def set_mode(self, bits, mask, files): Function `set_mode` Sets or updates a value.
L579: def ensure_dir(self, path):    Function `ensure_dir` utility or script function.
L591: def byte_compile(self, path, optimize=False, force=False, prefix=None,
hashed_invalidation=False): Function `byte_compile` utility or script function.
L610: def ensure_removed(self, path): Function `ensure_removed` utility or script
function.
L631: def is_writable(self, path):    Function `is_writable` utility or script function.
L643: def commit(self):              Function `commit` utility or script function.
L653: def rollback(self):            Function `rollback` utility or script function.
L672: def resolve(module_name, dotted_path): Function `resolve` utility or script
function.
L687: class ExportEntry(object):     Object (singleton).
L689: def __init__(self, name, prefix, suffix, flags): Function `__init__` utility or
script function.
L696: def value(self):               Function `value` utility or script function.
L699: def __repr__(self):            # pragma: no cover Function `__repr__` utility or script
function.
L702: def __eq__(self, other):       Function `__eq__` utility or script function.
L720: def get_export_entry(specification): Function `get_export_entry` Returns or fetches
data.
L751: def get_cache_base(suffix=None): Function `get_cache_base` Returns or fetches data.
L792: def path_to_cache_dir(path, use_abspath=True): Function `path_to_cache_dir` utility
or script function.
L809: def ensure_slash(s):           Function `ensure_slash` utility or script function.

```



```

L815: def parse_credentials(netloc):    Function `parse_credentials` utility or script
function.
L830: def get_process_umask():    Function `get_process_umask` Returns or fetches data.
L836: def is_string_sequence(seq):    Function `is_string_sequence` utility or script
function.
L852: def split_filename(filename, project_name=None):    Function `split_filename` utility
or script function.
L882: def parse_name_and_version(p):    Function `parse_name_and_version` utility or script
function.
L898: def get_extras(requested, available):    Function `get_extras` Returns or fetches data.
L926: def _get_external_data(url):    Function `_get_external_data` utility or script
function.
L950: def get_project_data(name):    Function `get_project_data` Returns or fetches data.
L957: def get_package_data(name, version):    Function `get_package_data` Returns or fetches
data.
L963: class Cache(object):    Object (singleton).
L970: def __init__(self, base):    Function `__init__` utility or script function.
L984: def prefix_to_dir(self, prefix, use_abspath=True):    Function `prefix_to_dir` utility
or script function.
L990: def clear(self):    Function `clear` utility or script function.
L1007: class EventMixin(object):    Object (singleton).
L1012: def __init__(self):    Function `__init__` utility or script function.
L1015: def add(self, event, subscriber, append=True):    Function `add` utility or script
function.
L1035: def remove(self, event, subscriber):    Function `remove` utility or script function.
L1047: def get_subscribers(self, event):    Function `get_subscribers` Returns or fetches
data.
L1054: def publish(self, event, *args, **kwargs):    Function `publish` utility or script
function.
L1080: class Sequencer(object):    Object (singleton).
L1082: def __init__(self):    Function `__init__` utility or script function.
L1087: def add_node(self, node):    Function `add_node` utility or script function.
L1090: def remove_node(self, node, edges=False):    Function `remove_node` utility or script
function.
L1106: def add(self, pred, succ):    Function `add` utility or script function.
L1111: def remove(self, pred, succ):    Function `remove` utility or script function.
L1124: def is_step(self, step):    Function `is_step` utility or script function.
L1127: def get_steps(self, final):    Function `get_steps` Returns or fetches data.
L1153: def strong_connections(self):    Function `strong_connections` utility or script
function.
L1163: def strongconnect(node):    Function `strongconnect` utility or script function.
L1205: def dot(self):    Function `dot` utility or script function.
L1224: def unarchive(archive_filename, dest_dir, format=None, check=True):    Function
`unarchive` utility or script function.
L1226: def check_path(path):    Function `check_path` utility or script function.
L1275: def extraction_filter(member, path):    Function `extraction_filter` utility or script
function.
L1292: def zip_dir(directory):    Function `zip_dir` utility or script function.
L1313: class Progress(object):    Object (singleton).
L1316: def __init__(self, minval=0, maxval=100):    Function `__init__` utility or script
function.

```

```

L1324: def update(self, curval):  Function `update` utility or script function.
L1334: def increment(self, incr):  Function `increment` utility or script function.
L1338: def start(self):  Function `start` utility or script function.
L1342: def stop(self):  Function `stop` utility or script function.
L1348: def maximum(self):  Function `maximum` utility or script function.
L1352: def percentage(self):  Function `percentage` utility or script function.
L1362: def format_duration(self, duration):  Function `format_duration` utility or script
function.
L1372: def ETA(self):  Function `ETA` utility or script function.
L1391: def speed(self):  Function `speed` utility or script function.
L1412: def iglob(path_glob):  Function `iglob` utility or script function.
L1423: def _iglob(path_glob):  Function `_iglob` utility or script function.
L1458: class HTTPSConnection(httplib.HTTPSConnection):  Class (`HTTPSConnection`) component
used by the app (see file context: None).
L1463: def connect(self):  Function `connect` utility or script function.
L1491: class HTTPSHandler(BaseHTTPSHandler):  Class (`HTTPSHandler`) component used by the
app (see file context: None).
L1493: def __init__(self, ca_certs, check_domain=True):  Function `__init__` utility or
script function.
L1498: def _conn_maker(self, *args, **kwargs):  Function `_conn_maker` utility or script
function.
L1514: def https_open(self, req):  Function `https_open` utility or script function.
L1533: class HTTPSOnlyHandler(HTTPSHandler, HTTPHandler):  Class (`HTTPSOnlyHandler`)
component used by the app (see file context: None).
L1535: def http_open(self, req):  Function `http_open` utility or script function.
L1543: class Transport(xmlrpclib.Transport):  Class (`Transport`) component used by the app
(see file context: None).
L1545: def __init__(self, timeout, use_datetime=0):  Function `__init__` utility or script
function.
L1549: def make_connection(self, host):  Function `make_connection` utility or script
function.
L1559: class SafeTransport(xmlrpclib.SafeTransport):  Class (`SafeTransport`) component
used by the app (see file context: None).
L1561: def __init__(self, timeout, use_datetime=0):  Function `__init__` utility or script
function.
L1565: def make_connection(self, host):  Function `make_connection` utility or script
function.
L1576: class ServerProxy(xmlrpclib.ServerProxy):  Class (`ServerProxy`) component used by
the app (see file context: None).
L1578: def __init__(self, uri, **kwargs):  Function `__init__` utility or script function.
L1601: def _csv_open(fn, mode, **kwargs):  Function `_csv_open` utility or script function.
L1612: class CSVBase(object):  Object (singleton).
L1619: def __enter__(self):  Function `__enter__` utility or script function.
L1622: def __exit__(self, *exc_info):  Function `__exit__` utility or script function.
L1626: class CSVReader(CSVBase):  Class (`CSVReader`) component used by the app (see file
context: None).
L1628: def __init__(self, **kwargs):  Function `__init__` utility or script function.
L1639: def __iter__(self):  Function `__iter__` utility or script function.
L1642: def next(self):  Function `next` utility or script function.
L1653: class CSVWriter(CSVBase):  Class (`CSVWriter`) component used by the app (see file
context: None).

```

```

L1655: def __init__(self, fn, **kwargs):    Function `__init__` utility or script function.
L1659: def writerow(self, row):    Function `writerow` utility or script function.
L1675: class Configurator(BaseConfigurator):    Class (`Configurator`) component used by the
app (see file context: None).
L1680: def __init__(self, config, base=None):    Function `__init__` utility or script
function.
L1684: def configure_custom(self, config):    Function `configure_custom` utility or script
function.
L1686: def convert(o):    Function `convert` utility or script function.
L1716: def __getitem__(self, key):    Function `__getitem__` utility or script function.
L1722: def inc_convert(self, value):    Function `inc_convert` utility or script function.
L1731: class SubprocessMixin(object):    Object (singleton).
L1736: def __init__(self, verbose=False, progress=None):    Function `__init__` utility or
script function.
L1740: def reader(self, stream, context):    Function `reader` utility or script function.
L1761: def run_command(self, cmd, **kwargs):    Function `run_command` utility or script
function.
L1777: def normalize_name(name):    Function `normalize_name` utility or script function.
L1794: class PyPIRCFile(object):    Object (singleton).
L1799: def __init__(self, fn=None, url=None):    Function `__init__` utility or script
function.
L1805: def read(self):    Function `read` utility or script function.
L1858: def update(self, username, password):    Function `update` utility or script function.
L1871: def _load_pypirc(index):    Function `_load_pypirc` utility or script function.
L1878: def _store_pypirc(index):    Function `_store_pypirc` utility or script function.
L1888: def get_host_platform():    Function `get_host_platform` Returns or fetches data.
L1978: def get_platform():    Function `get_platform` Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_null_file.py

```

L5: class NullFile(IO[str]):    Class (`NullFile`) component used by the app (see file
context: None).
L6: def close(self) -> None:    Function `close` utility or script function.
L9: def isatty(self) -> bool:    Function `isatty` utility or script function.
L12: def read(self, __n: int = 1) -> str:    Function `read` utility or script function.
L15: def readable(self) -> bool:    Function `readable` utility or script function.
L18: def readline(self, __limit: int = 1) -> str:    Function `readline` utility or script
function.
L21: def readlines(self, __hint: int = 1) -> List[str]:    Function `readlines` utility or
script function.
L24: def seek(self, __offset: int, __whence: int = 1) -> int:    Function `seek` utility or
script function.
L27: def seekable(self) -> bool:    Function `seekable` utility or script function.
L30: def tell(self) -> int:    Function `tell` utility or script function.
L33: def truncate(self, __size: Optional[int] = 1) -> int:    Function `truncate` utility or
script function.
L36: def writable(self) -> bool:    Function `writable` utility or script function.
L39: def writelines(self, __lines: Iterable[str]) -> None:    Function `writelines` utility

```

or script function.

```
L42: def __next__(self) -> str:    Function `__next__`    utility or script function.
L45: def __iter__(self) -> Iterator[str]:    Function `__iter__`    utility or script function.
L48: def __enter__(self) -> IO[str]:    Function `__enter__`    utility or script function.
L51: def __exit__(    Function `__exit__`    utility or script function.
L59: def write(self, text: str) -> int:    Function `write`    utility or script function.
L62: def flush(self) -> None:    Function `flush`    utility or script function.
L65: def fileno(self) -> int:    Function `fileno`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/segment.py

```
L35: class ControlType(IntEnum):    Class (`ControlType`)    component used by the app (see file
context: None).
L64: class Segment(NamedTuple):    Class (`Segment`)    component used by the app (see file
context: None).
L82: def cell_length(self) -> int:    Function `cell_length`    utility or script function.
L91: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.
L100: def __bool__(self) -> bool:    Function `__bool__`    utility or script function.
L105: def is_control(self) -> bool:    Function `is_control`    utility or script function.
L111: def _split_cells(cls, segment: "Segment", cut: int) -> Tuple["Segment", "Segment"]:
Function `_split_cells`    utility or script function.
L158: def split_cells(self, cut: int) -> Tuple["Segment", "Segment"]:    Function
`split_cells`    utility or script function.
L185: def line(cls) -> "Segment":    Function `line`    utility or script function.
L190: def apply_style(    Function `apply_style`    utility or script function.
L231: def filter_control(    Function `filter_control`    utility or script function.
L250: def split_lines(cls, segments: Iterable["Segment"]) -> Iterable[List["Segment"]]:
Function `split_lines`    utility or script function.
L279: def split_and_crop_lines(    Function `split_and_crop_lines`    utility or script
function.
L326: def adjust_line_length(    Function `adjust_line_length`    utility or script function.
L371: def get_line_length(cls, line: List["Segment"]) -> int:    Function `get_line_length`
Returns or fetches data.
L384: def get_shape(cls, lines: List[List["Segment"]]) -> Tuple[int, int]:    Function
`get_shape`    Returns or fetches data.
L398: def set_shape(    Function `set_shape`    Sets or updates a value.
L434: def align_top(    Function `align_top`    utility or script function.
L463: def align_bottom(    Function `align_bottom`    utility or script function.
L492: def align_middle(    Function `align_middle`    utility or script function.
L523: def simplify(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:    Function
`simplify`    utility or script function.
L550: def strip_links(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:    Function
`strip_links`    utility or script function.
L567: def strip_styles(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:    Function
`strip_styles`    utility or script function.
L580: def remove_color(cls, segments: Iterable["Segment"]) -> Iterable["Segment"]:    Function
`remove_color`    utility or script function.
```

```

L602: def divide(    Function `divide`    utility or script function.
L671: class Segments:    Class (`Segments`)    component used by the app (see file context:
None).
L680: def __init__(self, segments: Iterable[Segment], new_lines: bool = False) -> None:
Function `__init__`    utility or script function.
L684: def __rich_console__(    Function `__rich_console__`    utility or script function.
L696: class SegmentLines:    Class (`SegmentLines`)    component used by the app (see file
context: None).
L697: def __init__(self, lines: Iterable[List[Segment]], new_lines: bool = False) -> None:
Function `__init__`    utility or script function.
L708: def __rich_console__(    Function `__rich_console__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/emoji.py

```

L18: class NoEmoji(Exception):    Class (`NoEmoji`)    component used by the app (see file
context: None).
L22: class Emoji(JupyterMixin):    Class (`Emoji`)    component used by the app (see file
context: None).
L27: def __init__(    Function `__init__`    utility or script function.
L53: def replace(cls, text: str) -> str:    Function `replace`    utility or script function.
L64: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L67: def __str__(self) -> str:    Function `__str__`    utility or script function.
L70: def __rich_console__(    Function `__rich_console__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/styled.py

```

L11: class Styled:    Class (`Styled`)    component used by the app (see file context: None).
L19: def __init__(self, renderable: "RenderableType", style: "StyleType") -> None:    Function
`__init__`    utility or script function.
L23: def __rich_console__(    Function `__rich_console__`    utility or script function.
L31: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_log_render.py

```

L14: class LogRender:    Class (`LogRender`)    component used by the app (see file context:
None).
L15: def __init__(    Function `__init__`    utility or script function.
L32: def __call__(    Function `__call__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/constrain.py

```

L10: class Constrain(JupyterMixin):    Class (`Constrain`)    component used by the app (see

```

```

file context: None).
L18: def __init__(self, renderable: "RenderableType", width: Optional[int] = 80) -> None:
Function `__init__` utility or script function.
L22: def __rich_console__(    Function `__rich_console__` utility or script function.
L31: def __rich_measure__(    Function `__rich_measure__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/tree.py

```

L14: class Tree(JupyterMixin):    Class (`Tree`) component used by the app (see file context:
None).
L37: def __init__(    Function `__init__` utility or script function.
L55: def add(    Function `add` utility or script function.
L86: def __rich_console__(    Function `__rich_console__` utility or script function.
L101: def make_guide(index: int, style: Style) -> Segment:    Function `make_guide` utility
or script function.
L176: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L223: class Segment(NamedTuple):    Class (`Segment`) component used by the app (see file
context: None).

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/protocol.py

```

L10: def is_renderable(check_object: Any) -> bool:    Function `is_renderable` utility or
script function.
L19: def rich_cast(renderable: object) -> "RenderableType":    Object (singleton).

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/syntax.py

```

L124: class SyntaxTheme(ABC):    Class (`SyntaxTheme`) component used by the app (see file
context: None).
L128: def get_style_for_token(self, token_type: TokenType) -> Style:    Function
`get_style_for_token` Returns or fetches data.
L133: def get_background_style(self) -> Style:    Function `get_background_style` Returns or
fetches data.
L138: class PygmentsSyntaxTheme(SyntaxTheme):    Class (`PygmentsSyntaxTheme`) component used
by the app (see file context: None).
L141: def __init__(self, theme: Union[str, Type[PygmentsStyle]]) -> None:    Function
`__init__` utility or script function.
L154: def get_style_for_token(self, token_type: TokenType) -> Style:    Function
`get_style_for_token` Returns or fetches data.
L176: def get_background_style(self) -> Style:    Function `get_background_style` Returns or
fetches data.
L180: class ANSISyntaxTheme(SyntaxTheme):    Class (`ANSISyntaxTheme`) component used by the
app (see file context: None).
L183: def __init__(self, style_map: Dict[TokenType, Style]) -> None:    Function `__init__`

```

```

utility or script function.
L189: def get_style_for_token(self, token_type: TokenType) -> Style:    Function
`get_style_for_token` Returns or fetches data.
L209: def get_background_style(self) -> Style:    Function `get_background_style` Returns or
fetches data.
L216: class _SyntaxHighlightRange(NamedTuple):    Class (`_SyntaxHighlightRange`) component
used by the app (see file context: None).
L229: class PaddingProperty:    Class (`PaddingProperty`) component used by the app (see file
context: None).
L232: def __get__(self, obj: Syntax, objtype: Type[Syntax]) -> Tuple[int, int, int, int]:
Function `__get__` utility or script function.
L236: def __set__(self, obj: Syntax, padding: PaddingDimensions) -> None:    Function
`__set__` utility or script function.
L240: class Syntax(JupyterMixin):    Class (`Syntax`) component used by the app (see file
context: None).
L265: def get_theme(cls, name: Union[str, SyntaxTheme]) -> SyntaxTheme:    Function
`get_theme` Returns or fetches data.
L276: def __init__(    Function `__init__` utility or script function.
L317: def from_path(    Function `from_path` utility or script function.
L380: def guess_lexer(cls, path: str, code: Optional[str] = None) -> str:    Function
`guess_lexer` utility or script function.
L421: def _get_base_style(self) -> Style:    Function `_get_base_style` utility or script
function.
L426: def _get_token_color(self, token_type: TokenType) -> Optional[Color]:    Function
`_get_token_color` utility or script function.
L439: def lexer(self) -> Optional[Lexer]:    Function `lexer` utility or script function.
L458: def default_lexer(self) -> Lexer:    Function `default_lexer` utility or script
function.
L467: def highlight(    Function `highlight` utility or script function.
L505: def line_tokenize() -> Iterable[Tuple[Any, str]]:    Function `line_tokenize` utility
or script function.
L514: def tokens_to_spans() -> Iterable[Tuple[str, Optional[Style]]]:    Function
`tokens_to_spans` utility or script function.
L552: def stylize_range(    Function `stylize_range` utility or script function.
L573: def _get_line_numbers_color(self, blend: float = 0.3) -> Color:    Function
`_get_line_numbers_color` utility or script function.
L589: def _numbers_column_width(self) -> int:    Function `_numbers_column_width` utility or
script function.
L599: def _get_number_styles(self, console: Console) -> Tuple[Style, Style, Style]:
Function `_get_number_styles` utility or script function.
L622: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L640: def __rich_console__(    Function `__rich_console__` utility or script function.
L649: def _get_syntax(    Function `_get_syntax` utility or script function.
L787: def _apply_stylized_ranges(self, text: Text) -> None:    Function
`_apply_stylized_ranges` utility or script function.
L820: def _process_code(self, code: str) -> Tuple[bool, str]:    Function `_process_code`
utility or script function.
L841: def _get_code_index_for_syntax_position(    Function
`_get_code_index_for_syntax_position` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_extension.py

```
L4: def load_ipython_extension(ip: Any) -> None: # pragma: no cover    Function
`load_ipython_extension` Loads data from storage or remote.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/control.py

```
L48: class Control:    Class (`Control`) component used by the app (see file context: None).
L58: def __init__(self, *codes: Union[ControlType, ControlCode]) -> None:    Function
`__init__` utility or script function.
L69: def bell(cls) -> "Control":    Function `bell` utility or script function.
L74: def home(cls) -> "Control":    Function `home` utility or script function.
L79: def move(cls, x: int = 0, y: int = 0) -> "Control":    Function `move` utility or script
function.
L91: def get_codes() -> Iterable[ControlCode]:    Function `get_codes` Returns or fetches
data.
L108: def move_to_column(cls, x: int, y: int = 0) -> "Control":    Function `move_to_column`
utility or script function.
L132: def move_to(cls, x: int, y: int) -> "Control":    Function `move_to` utility or script
function.
L145: def clear(cls) -> "Control":    Function `clear` utility or script function.
L150: def show_cursor(cls, show: bool) -> "Control":    Function `show_cursor` utility or
script function.
L155: def alt_screen(cls, enable: bool) -> "Control":    Function `alt_screen` utility or
script function.
L163: def title(cls, title: str) -> "Control":    Function `title` utility or script
function.
L171: def __str__(self) -> str:    Function `__str__` utility or script function.
L174: def __rich_console__(    Function `__rich_console__` utility or script function.
L181: def strip_control_codes(    Function `strip_control_codes` utility or script function.
L195: def escape_control_codes(    Function `escape_control_codes` utility or script
function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/status.py

```
L11: class Status(JupyterMixin):    Class (`Status`) component used by the app (see file
context: None).
L23: def __init__(    Function `__init__` utility or script function.
L45: def renderable(self) -> Spinner:    Function `renderable` utility or script function.
L49: def console(self) -> "Console":    Function `console` utility or script function.
L53: def update(    Function `update` utility or script function.
L85: def start(self) -> None:    Function `start` utility or script function.
L89: def stop(self) -> None:    Function `stop` utility or script function.
L93: def __rich__(self) -> RenderableType:    Function `__rich__` utility or script function.
L96: def __enter__(self) -> "Status":    Function `__enter__` utility or script function.
```



```
L100: def __exit__(    Function `__exit__`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/color_triplet.py

```
L4: class ColorTriplet(NamedTuple):    Class (`ColorTriplet`)    component used by the app (see
file context: None).
L15: def hex(self) -> str:    Function `hex`    utility or script function.
L21: def rgb(self) -> str:    Function `rgb`    utility or script function.
L31: def normalized(self) -> Tuple[float, float, float]:    Function `normalized`    utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress.py

```
L64: class _TrackThread(Thread):    Class (`_TrackThread`)    component used by the app (see
file context: None).
L67: def __init__(self, progress: "Progress", task_id: "TaskID", update_period: float):
Function `__init__`    utility or script function.
L76: def run(self) -> None:    Function `run`    utility or script function.
L90: def __enter__(self) -> "_TrackThread":    Function `__enter__`    utility or script
function.
L94: def __exit__(    Function `__exit__`    utility or script function.
L104: def track(    Function `track`    utility or script function.
L182: class _Reader(RawIOBase, BinaryIO):    Class (`_Reader`)    component used by the app (see
file context: None).
L185: def __init__(    Function `__init__`    utility or script function.
L198: def __enter__(self) -> "_Reader":    Function `__enter__`    utility or script function.
L202: def __exit__(    Function `__exit__`    utility or script function.
L210: def __iter__(self) -> BinaryIO:    Function `__iter__`    utility or script function.
L213: def __next__(self) -> bytes:    Function `__next__`    utility or script function.
L219: def closed(self) -> bool:    Function `closed`    utility or script function.
L222: def fileno(self) -> int:    Function `fileno`    utility or script function.
L225: def isatty(self) -> bool:    Function `isatty`    utility or script function.
L229: def mode(self) -> str:    Function `mode`    utility or script function.
L233: def name(self) -> str:    Function `name`    utility or script function.
L236: def readable(self) -> bool:    Function `readable`    utility or script function.
L239: def seekable(self) -> bool:    Function `seekable`    utility or script function.
L242: def writable(self) -> bool:    Function `writable`    utility or script function.
L245: def read(self, size: int = -1) -> bytes:    Function `read`    utility or script function.
L250: def readinto(self, b: Union[bytearray, memoryview, mmap]):    # type:
ignore[no-untyped-def, override]    Function `readinto`    utility or script function.
L255: def readline(self, size: int = -1) -> bytes:    # type: ignore[override]    Function
`readline`    utility or script function.
L260: def readlines(self, hint: int = -1) -> List[bytes]:    Function `readlines`    utility or
script function.
L265: def close(self) -> None:    Function `close`    utility or script function.
L270: def seek(self, offset: int, whence: int = 0) -> int:    Function `seek`    utility or
```

```

script function.
L275: def tell(self) -> int:    Function `tell` utility or script function.
L278: def write(self, s: Any) -> int:    Function `write` utility or script function.
L281: def writelines(self, lines: Iterable[Any]) -> None:    Function `writelines` utility or
script function.
L285: class _ReadContext(ContextManager[_I], Generic[_I]):    Class (`_ReadContext`)
component used by the app (see file context: None).
L288: def __init__(self, progress: "Progress", reader: _I) -> None:    Function `__init__`
utility or script function.
L292: def __enter__(self) -> _I:    Function `__enter__` utility or script function.
L296: def __exit__(    Function `__exit__` utility or script function.
L306: def wrap_file(    Function `wrap_file` utility or script function.
L372: def open(    Function `open` utility or script function.
L397: def open(    Function `open` utility or script function.
L421: def open(    Function `open` utility or script function.
L507: class ProgressColumn(ABC):    Class (`ProgressColumn`) component used by the app (see
file context: None).
L512: def __init__(self, table_column: Optional[Column] = None) -> None:    Function
`__init__` utility or script function.
L517: def get_table_column(self) -> Column:    Function `get_table_column` Returns or fetches
data.
L521: def __call__(self, task: "Task") -> RenderableType:    Function `__call__` utility or
script function.
L545: def render(self, task: "Task") -> RenderableType:    Function `render` utility or
script function.
L549: class RenderableColumn(ProgressColumn):    Class (`RenderableColumn`) component used by
the app (see file context: None).
L556: def __init__(    Function `__init__` utility or script function.
L562: def render(self, task: "Task") -> RenderableType:    Function `render` utility or
script function.
L566: class SpinnerColumn(ProgressColumn):    Class (`SpinnerColumn`) component used by the
app (see file context: None).
L576: def __init__(    Function `__init__` utility or script function.
L592: def set_spinner(    Function `set_spinner` Sets or updates a value.
L607: def render(self, task: "Task") -> RenderableType:    Function `render` utility or
script function.
L616: class TextColumn(ProgressColumn):    Class (`TextColumn`) component used by the app
(see file context: None).
L619: def __init__(    Function `__init__` utility or script function.
L635: def render(self, task: "Task") -> Text:    Function `render` utility or script
function.
L646: class BarColumn(ProgressColumn):    Class (`BarColumn`) component used by the app (see
file context: None).
L657: def __init__(    Function `__init__` utility or script function.
L673: def render(self, task: "Task") -> ProgressBar:    Function `render` utility or script
function.
L688: class TimeElapsedColumn(ProgressColumn):    Class (`TimeElapsedColumn`) component used
by the app (see file context: None).
L691: def render(self, task: "Task") -> Text:    Function `render` utility or script
function.
L700: class TaskProgressColumn(TextColumn):    Class (`TaskProgressColumn`) component used by

```

```

the app (see file context: None).
L714: def __init__(    Function `__init__`  utility or script function.
L737: def render_speed(cls, speed: Optional[float]) -> Text:    Function `render_speed`
utility or script function.
L756: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L772: class TimeRemainingColumn(ProgressColumn):    Class (`TimeRemainingColumn`) component
used by the app (see file context: None).
L783: def __init__(    Function `__init__`  utility or script function.
L793: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L820: class FileSizeColumn(ProgressColumn):    Class (`FileSizeColumn`) component used by the
app (see file context: None).
L823: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L829: class TotalFileSizeColumn(ProgressColumn):    Class (`TotalFileSizeColumn`) component
used by the app (see file context: None).
L832: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L838: class MofNCompleteColumn(ProgressColumn):    Class (`MofNCompleteColumn`) component
used by the app (see file context: None).
L850: def __init__(self, separator: str = "/", table_column: Optional[Column] = None):
Function `__init__`  utility or script function.
L854: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L865: class DownloadColumn(ProgressColumn):    Class (`DownloadColumn`) component used by the
app (see file context: None).
L872: def __init__(    Function `__init__`  utility or script function.
L878: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L914: class TransferSpeedColumn(ProgressColumn):    Class (`TransferSpeedColumn`) component
used by the app (see file context: None).
L917: def render(self, task: "Task") -> Text:    Function `render`  utility or script
function.
L926: class ProgressSample(NamedTuple):    Class (`ProgressSample`) component used by the app
(see file context: None).
L936: class Task:    Class (`Task`) component used by the app (see file context: None).
L983: def get_time(self) -> float:    Function `get_time`  Returns or fetches data.
L988: def started(self) -> bool:    Function `started`  utility or script function.
L993: def remaining(self) -> Optional[float]:    Function `remaining`  utility or script
function.
L1000: def elapsed(self) -> Optional[float]:    Function `elapsed`  utility or script
function.
L1009: def finished(self) -> bool:    Function `finished`  utility or script function.
L1014: def percentage(self) -> float:    Function `percentage`  utility or script function.
L1023: def speed(self) -> Optional[float]:    Function `speed`  utility or script function.
L1041: def time_remaining(self) -> Optional[float]:    Function `time_remaining`  utility or
script function.
L1054: def _reset(self) -> None:    Function `_reset`  utility or script function.
L1061: class Progress(JupyterMixin):    Class (`Progress`) component used by the app (see
file context: None).

```

```

L1077: def __init__(    Function `__init__`    utility or script function.
L1114: def get_default_columns(cls) -> Tuple[ProgressColumn, ...]:    Function
`get_default_columns`    Returns or fetches data.
L1145: def console(self) -> Console:    Function `console`    utility or script function.
L1149: def tasks(self) -> List[Task]:    Function `tasks`    utility or script function.
L1155: def task_ids(self) -> List[TaskID]:    Function `task_ids`    utility or script function.
L1161: def finished(self) -> bool:    Function `finished`    utility or script function.
L1168: def start(self) -> None:    Function `start`    utility or script function.
L1173: def stop(self) -> None:    Function `stop`    utility or script function.
L1179: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L1183: def __exit__(    Function `__exit__`    utility or script function.
L1191: def track(    Function `track`    utility or script function.
L1236: def wrap_file(    Function `wrap_file`    utility or script function.
L1279: def open(    Function `open`    utility or script function.
L1295: def open(    Function `open`    utility or script function.
L1310: def open(    Function `open`    utility or script function.
L1387: def start_task(self, task_id: TaskID) -> None:    Function `start_task`    utility or
script function.
L1401: def stop_task(self, task_id: TaskID) -> None:    Function `stop_task`    utility or
script function.
L1416: def update(    Function `update`    utility or script function.
L1477: def reset(    Function `reset`    utility or script function.
L1516: def advance(self, task_id: TaskID, advance: float = 1) -> None:    Function `advance`
utility or script function.
L1546: def refresh(self) -> None:    Function `refresh`    utility or script function.
L1551: def get_renderable(self) -> RenderableType:    Function `get_renderable`    Returns or
fetches data.
L1556: def get_renderables(self) -> Iterable[RenderableType]:    Function `get_renderables`
Returns or fetches data.
L1561: def make_tasks_table(self, tasks: Iterable[Task]) -> Table:    Function
`make_tasks_table`    utility or script function.
L1594: def __rich__(self) -> RenderableType:    Function `__rich__`    utility or script
function.
L1599: def add_task(    Function `add_task`    utility or script function.
L1642: def remove_task(self, task_id: TaskID) -> None:    Function `remove_task`    utility or
script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/cells.py

```

L34: def cached_cell_len(text: str) -> int:    Function `cached_cell_len`    utility or script
function.
L51: def cell_len(text: str, _cell_len: Callable[[str], int] = cached_cell_len) -> int:
Function `cell_len`    utility or script function.
L68: def get_character_cell_size(character: str) -> int:    Function `get_character_cell_size`
Returns or fetches data.
L96: def set_cell_size(text: str, total: int) -> str:    Function `set_cell_size`    Sets or
updates a value.
L131: def chop_cells(    Function `chop_cells`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/prompt.py

```

L11: class PromptError(Exception):    Class (`PromptError`)    component used by the app (see
file context: None).
L15: class InvalidResponse(PromptError):    Class (`InvalidResponse`)    component used by the
app (see file context: None).
L23: def __init__(self, message: TextType) -> None:    Function `__init__`    utility or script
function.
L26: def __rich__(self) -> TextType:    Function `__rich__`    utility or script function.
L30: class PromptBase(Generic[PromptType]):    Class (`PromptBase`)    component used by the app
(see file context: None).
L54: def __init__(    Function `__init__`    utility or script function.
L80: def ask(    Function `ask`    utility or script function.
L97: def ask(    Function `ask`    utility or script function.
L112: def ask(    Function `ask`    utility or script function.
L151: def render_default(self, default: DefaultType) -> Text:    Function `render_default`
utility or script function.
L162: def make_prompt(self, default: DefaultType) -> Text:    Function `make_prompt`    utility
or script function.
L194: def get_input(    Function `get_input`    Returns or fetches data.
L213: def check_choice(self, value: str) -> bool:    Function `check_choice`    utility or
script function.
L227: def process_response(self, value: str) -> PromptType:    Function `process_response`
utility or script function.
L258: def on_validate_error(self, value: str, error: InvalidResponse) -> None:    Function
`on_validate_error`    utility or script function.
L267: def pre_prompt(self) -> None:    Function `pre_prompt`    utility or script function.
L271: def __call__(self, *, stream: Optional[TextIO] = None) -> PromptType:    Function
`__call__`    utility or script function.
L275: def __call__(    Function `__call__`    utility or script function.
L280: def __call__(self, *, default: Any = ..., stream: Optional[TextIO] = None) -> Any:
Function `__call__`    utility or script function.
L304: class Prompt(PromptBase[str]):    Class (`Prompt`)    component used by the app (see file
context: None).
L316: class IntPrompt(PromptBase[int]):    Class (`IntPrompt`)    component used by the app (see
file context: None).
L328: class FloatPrompt(PromptBase[float]):    Class (`FloatPrompt`)    component used by the
app (see file context: None).
L340: class Confirm(PromptBase[bool]):    Class (`Confirm`)    component used by the app (see
file context: None).
L353: def render_default(self, default: DefaultType) -> Text:    Function `render_default`
utility or script function.
L358: def process_response(self, value: str) -> bool:    Function `process_response`    utility
or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/box.py

```

L10: class Box:    Class (`Box`)    component used by the app (see file context: None).

```

```

L27: def __init__(self, box: str, *, ascii: bool = False) -> None:    Function `__init__`
utility or script function.
L61: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L64: def __str__(self) -> str:    Function `__str__`    utility or script function.
L67: def substitute(self, options: "ConsoleOptions", safe: bool = True) -> "Box":    Function
`substitute`    utility or script function.
L85: def get_plain_headed_box(self) -> "Box":    Function `get_plain_headed_box`    Returns or
fetches data.
L95: def get_top(self, widths: Iterable[int]) -> str:    Function `get_top`    Returns or
fetches data.
L115: def get_row(    Function `get_row`    Returns or fetches data.
L164: def get_bottom(self, widths: Iterable[int]) -> str:    Function `get_bottom`    Returns or
fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/scope.py

```

L14: def render_scope(    Function `render_scope`    utility or script function.
L41: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:    Function `sort_items`
utility or script function.
L75: def test(foo: float, bar: float) -> None:    Function `test`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_emoji_replace.py

```

L12: def _emoji_replace(    Function `_emoji_replace`    utility or script function.
L23: def do_replace(match: Match[str]) -> str:    Function `do_replace`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/console.py

```

L79: class NoChange:    Class (`NoChange`)    component used by the app (see file context:
None).
L109: class ConsoleDimensions(NamedTuple):    Class (`ConsoleDimensions`)    component used by
the app (see file context: None).
L119: class ConsoleOptions:    Class (`ConsoleOptions`)    component used by the app (see file
context: None).
L149: def ascii_only(self) -> bool:    Function `ascii_only`    utility or script function.
L153: def copy(self) -> "ConsoleOptions":    Function `copy`    utility or script function.
L163: def update(    Function `update`    utility or script function.
L200: def update_width(self, width: int) -> "ConsoleOptions":    Function `update_width`
utility or script function.
L213: def update_height(self, height: int) -> "ConsoleOptions":    Function `update_height`
utility or script function.
L226: def reset_height(self) -> "ConsoleOptions":    Function `reset_height`    utility or
script function.

```

```

L236: def update_dimensions(self, width: int, height: int) -> "ConsoleOptions":    Function
`update_dimensions` utility or script function.
L253: class RichCast(Protocol):    Class (`RichCast`) component used by the app (see file
context: None).
L256: def __rich__(    Function `__rich__` utility or script function.
L263: class ConsoleRenderable(Protocol):    Class (`ConsoleRenderable`) component used by the
app (see file context: None).
L266: def __rich_console__(    Function `__rich_console__` utility or script function.
L282: class CaptureError(Exception):    Class (`CaptureError`) component used by the app (see
file context: None).
L286: class NewLine:    Class (`NewLine`) component used by the app (see file context: None).
L289: def __init__(self, count: int = 1) -> None:    Function `__init__` utility or script
function.
L292: def __rich_console__(    Function `__rich_console__` utility or script function.
L298: class ScreenUpdate:    Class (`ScreenUpdate`) component used by the app (see file
context: None).
L301: def __init__(self, lines: List[List[Segment]], x: int, y: int) -> None:    Function
`__init__` utility or script function.
L306: def __rich_console__(    Function `__rich_console__` utility or script function.
L316: class Capture:    Class (`Capture`) component used by the app (see file context: None).
L324: def __init__(self, console: "Console") -> None:    Function `__init__` utility or
script function.
L328: def __enter__(self) -> "Capture":    Function `__enter__` utility or script function.
L332: def __exit__(    Function `__exit__` utility or script function.
L340: def get(self) -> str:    Function `get` Returns or fetches data.
L349: class ThemeContext:    Class (`ThemeContext`) component used by the app (see file
context: None).
L352: def __init__(self, console: "Console", theme: Theme, inherit: bool = True) -> None:
Function `__init__` utility or script function.
L357: def __enter__(self) -> "ThemeContext":    Function `__enter__` utility or script
function.
L361: def __exit__(    Function `__exit__` utility or script function.
L370: class PagerContext:    Class (`PagerContext`) component used by the app (see file
context: None).
L373: def __init__(    Function `__init__` utility or script function.
L385: def __enter__(self) -> "PagerContext":    Function `__enter__` utility or script
function.
L389: def __exit__(    Function `__exit__` utility or script function.
L409: class ScreenContext:    Class (`ScreenContext`) component used by the app (see file
context: None).
L412: def __init__(    Function `__init__` utility or script function.
L420: def update(    Function `update` utility or script function.
L438: def __enter__(self) -> "ScreenContext":    Function `__enter__` utility or script
function.
L444: def __exit__(    Function `__exit__` utility or script function.
L456: class Group:    Class (`Group`) component used by the app (see file context: None).
L464: def __init__(self, *renderables: "RenderableType", fit: bool = True) -> None:
Function `__init__` utility or script function.
L470: def renderables(self) -> List["RenderableType"]:    Function `renderables` utility or
script function.
L475: def __rich_measure__(    Function `__rich_measure__` utility or script function.

```



```

L483: def __rich_console__(    Function `__rich_console__`    utility or script function.
L489: def group(fit: bool = True) -> Callable[... , Callable[... , Group]]:    Function `group`
utility or script function.
L496: def decorator(    Function `decorator`    utility or script function.
L502: def _replace(*args: Any, **kwargs: Any) -> Group:    Function `_replace`    utility or
script function.
L511: def _is_jupyter() -> bool:    # pragma: no cover    Function `_is_jupyter`    utility or
script function.
L542: class ConsoleThreadLocals(threading.local):    Class (`ConsoleThreadLocals`)    component
used by the app (see file context: None).
L550: class RenderHook(ABC):    Class (`RenderHook`)    component used by the app (see file
context: None).
L554: def process_renderables(    Function `process_renderables`    utility or script function.
L572: def get_windows_console_features() -> "WindowsConsoleFeatures":    # pragma: no cover
Function `get_windows_console_features`    Returns or fetches data.
L582: def detect_legacy_windows() -> bool:    Function `detect_legacy_windows`    utility or
script function.
L587: class Console:    Class (`Console`)    component used by the app (see file context: None).
L625: def __init__(    Function `__init__`    utility or script function.
L759: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L763: def file(self) -> IO[str]:    Function `file`    utility or script function.
L772: def file(self, new_file: IO[str]) -> None:    Function `file`    utility or script
function.
L777: def _buffer(self) -> List[Segment]:    Function `_buffer`    utility or script function.
L782: def _buffer_index(self) -> int:    Function `_buffer_index`    utility or script function.
L787: def _buffer_index(self, value: int) -> None:    Function `_buffer_index`    utility or
script function.
L791: def _theme_stack(self) -> ThemeStack:    Function `_theme_stack`    utility or script
function.
L795: def _detect_color_system(self) -> Optional[ColorSystem]:    Function
`_detect_color_system`    utility or script function.
L819: def _enter_buffer(self) -> None:    Function `_enter_buffer`    utility or script
function.
L823: def _exit_buffer(self) -> None:    Function `_exit_buffer`    utility or script function.
L828: def set_live(self, live: "Live") -> bool:    Function `set_live`    Sets or updates a
value.
L844: def clear_live(self) -> None:    Function `clear_live`    utility or script function.
L849: def push_render_hook(self, hook: RenderHook) -> None:    Function `push_render_hook`
utility or script function.
L858: def pop_render_hook(self) -> None:    Function `pop_render_hook`    utility or script
function.
L863: def __enter__(self) -> "Console":    Function `__enter__`    utility or script function.
L868: def __exit__(self, exc_type: Any, exc_value: Any, traceback: Any) -> None:    Function
`__exit__`    utility or script function.
L872: def begin_capture(self) -> None:    Function `begin_capture`    utility or script
function.
L876: def end_capture(self) -> str:    Function `end_capture`    utility or script function.
L887: def push_theme(self, theme: Theme, *, inherit: bool = True) -> None:    Function
`push_theme`    utility or script function.
L898: def pop_theme(self) -> None:    Function `pop_theme`    utility or script function.
L902: def use_theme(self, theme: Theme, *, inherit: bool = True) -> ThemeContext:    Function

```



```

`use_theme` utility or script function.
L915: def color_system(self) -> Optional[str]: Function `color_system` utility or script
function.
L928: def encoding(self) -> str: Function `encoding` utility or script function.
L937: def is_terminal(self) -> bool: Function `is_terminal` utility or script function.
L985: def is_dumb_terminal(self) -> bool: Function `is_dumb_terminal` utility or script
function.
L997: def options(self) -> ConsoleOptions: Function `options` utility or script function.
L1011: def size(self) -> ConsoleDimensions: Function `size` utility or script function.
L1052: def size(self, new_size: Tuple[int, int]) -> None: Function `size` utility or
script function.
L1063: def width(self) -> int: Function `width` utility or script function.
L1072: def width(self, width: int) -> None: Function `width` utility or script function.
L1081: def height(self) -> int: Function `height` utility or script function.
L1090: def height(self, height: int) -> None: Function `height` utility or script
function.
L1098: def bell(self) -> None: Function `bell` utility or script function.
L1102: def capture(self) -> Capture: Function `capture` utility or script function.
L1119: def pager( Function `pager` utility or script function.
L1142: def line(self, count: int = 1) -> None: Function `line` utility or script function.
L1152: def clear(self, home: bool = True) -> None: Function `clear` utility or script
function.
L1163: def status( Function `status` utility or script function.
L1196: def show_cursor(self, show: bool = True) -> bool: Function `show_cursor` utility or
script function.
L1207: def set_alt_screen(self, enable: bool = True) -> bool: Function `set_alt_screen`
Sets or updates a value.
L1229: def is_alt_screen(self) -> bool: Function `is_alt_screen` utility or script
function.
L1237: def set_window_title(self, title: str) -> bool: Function `set_window_title` Sets or
updates a value.
L1269: def screen( Function `screen` utility or script function.
L1283: def measure( Function `measure` utility or script function.
L1300: def render( Function `render` utility or script function.
L1351: def render_lines( Function `render_lines` utility or script function.
L1415: def render_str( Function `render_str` utility or script function.
L1476: def get_style( Function `get_style` Returns or fetches data.
L1506: def _collect_renderables( Function `_collect_renderables` utility or script
function.
L1539: def align_append(renderable: RenderableType) -> None: Function `align_append`
utility or script function.
L1548: def check_text() -> None: Function `check_text` utility or script function.
L1585: def rule( Function `rule` utility or script function.
L1606: def control(self, *control: Control) -> None: Function `control` utility or script
function.
L1616: def out( Function `out` utility or script function.
L1648: def print( Function `print` utility or script function.
L1747: def print_json( Function `print_json` utility or script function.
L1808: def update_screen( Function `update_screen` utility or script function.
L1842: def update_screen_lines( Function `update_screen_lines` utility or script function.
L1862: def print_exception( Function `print_exception` utility or script function.

```

```

L1898: def _caller_frame_info( Function `_caller_frame_info` utility or script function.
L1932: def log( Function `log` utility or script function.
L2013: def on_broken_pipe(self) -> None: Function `on_broken_pipe` utility or script
function.
L2027: def _check_buffer(self) -> None: Function `_check_buffer` utility or script
function.
L2042: def _write_buffer(self) -> None: Function `_write_buffer` utility or script
function.
L2115: def _render_buffer(self, buffer: Iterable[Segment]) -> str: Function
`_render_buffer` utility or script function.
L2139: def input( Function `input` utility or script function.
L2173: def export_text(self, *, clear: bool = True, styles: bool = False) -> str: Function
`export_text` utility or script function.
L2205: def save_text(self, path: str, *, clear: bool = True, styles: bool = False) -> None:
Function `save_text` Saves data to storage or remote.
L2219: def export_html( Function `export_html` utility or script function.
L2294: def save_html( Function `save_html` Saves data to storage or remote.
L2325: def export_svg( Function `export_svg` utility or script function.
L2356: def get_svg_style(style: Style) -> str: Function `get_svg_style` Returns or fetches
data.
L2416: def escape_text(text: str) -> str: Function `escape_text` utility or script
function.
L2420: def make_tag( Function `make_tag` utility or script function.
L2425: def stringify(value: object) -> str: Object (singleton).
L2576: def save_svg( Function `save_svg` Saves data to storage or remote.
L2615: def _svg_hash(svg_main_code: str) -> str: Function `_svg_hash` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/jupyter.py

```

L18: class JupyterRenderable: Class (`JupyterRenderable`) component used by the app (see
file context: None).
L21: def __init__(self, html: str, text: str) -> None: Function `__init__` utility or
script function.
L25: def _repr_mimebundle_( Function `_repr_mimebundle_` utility or script function.
L36: class JupyterMixin: Class (`JupyterMixin`) component used by the app (see file
context: None).
L41: def _repr_mimebundle_( Function `_repr_mimebundle_` utility or script function.
L59: def _render_segments(segments: Iterable[Segment]) -> str: Function `_render_segments`
utility or script function.
L60: def escape(text: str) -> str: Function `escape` utility or script function.
L84: def display(segments: Iterable[Segment], text: str) -> None: Function `display`
utility or script function.
L98: def print(*args: Any, **kwargs: Any) -> None: Function `print` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/abc.py

```

L4: class RichRenderable(ABC):    Class (`RichRenderable`)    component used by the app (see
file context: None).
L16: def __subclasshook__(cls, other: type) -> bool:    Function `__subclasshook__`    utility
or script function.
L28: class Foo:    Class (`Foo`)    component used by the app (see file context: None).

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/progress_bar.py

```

L18: class ProgressBar(JupyterMixin):    Class (`ProgressBar`)    component used by the app (see
file context: None).
L33: def __init__(    Function `__init__`    utility or script function.
L57: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L61: def percentage_completed(self) -> Optional[float]:    Function `percentage_completed`
utility or script function.
L70: def _get_pulse_segments(    Function `_get_pulse_segments`    utility or script function.
L116: def update(self, completed: float, total: Optional[float] = None) -> None:    Function
`update`    utility or script function.
L126: def _render_pulse(    Function `_render_pulse`    utility or script function.
L156: def __rich_console__(    Function `__rich_console__`    utility or script function.
L200: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/json.py

```

L9: class JSON:    Class (`JSON`)    component used by the app (see file context: None).
L25: def __init__(    Function `__init__`    utility or script function.
L54: def from_data(    Function `from_data`    utility or script function.
L101: def __rich__(self) -> Text:    Function `__rich__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/__main__.py

```

L18: class ColorBox:    Class (`ColorBox`)    component used by the app (see file context:
None).
L19: def __rich_console__(    Function `__rich_console__`    utility or script function.
L33: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L39: def make_test_card() -> Table:    Function `make_test_card`    utility or script function.
L90: def comparison(renderable1: RenderableType, renderable2: RenderableType) -> Table:
Function `comparison`    utility or script function.
L157: def iter_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:    Function `iter_last`
utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/measure.py

```

L11: class Measurement(NamedTuple):    Class (`Measurement`) component used by the app (see
file context: None).
L20: def span(self) -> int:    Function `span` utility or script function.
L24: def normalize(self) -> "Measurement":    Function `normalize` utility or script
function.
L34: def with_maximum(self, width: int) -> "Measurement":    Function `with_maximum` utility
or script function.
L46: def with_minimum(self, width: int) -> "Measurement":    Function `with_minimum` utility
or script function.
L59: def clamp(    Function `clamp` utility or script function.
L79: def get(    Function `get` Returns or fetches data.
L125: def measure_renderables(    Function `measure_renderables` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/text.py

```

L47: class Span(NamedTuple):    Class (`Span`) component used by the app (see file context:
None).
L57: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L60: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L63: def split(self, offset: int) -> Tuple["Span", Optional["Span"]]:    Function `split`
utility or script function.
L76: def move(self, offset: int) -> "Span":    Function `move` utility or script function.
L88: def right_crop(self, offset: int) -> "Span":    Function `right_crop` utility or script
function.
L102: def extend(self, cells: int) -> "Span":    Function `extend` utility or script
function.
L118: class Text(JupyterMixin):    Class (`Text`) component used by the app (see file
context: None).
L144: def __init__(    Function `__init__` utility or script function.
L167: def __len__(self) -> int:    Function `__len__` utility or script function.
L170: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L173: def __str__(self) -> str:    Function `__str__` utility or script function.
L176: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L179: def __add__(self, other: Any) -> "Text":    Function `__add__` utility or script
function.
L186: def __eq__(self, other: object) -> bool:    Object (singleton).
L191: def __contains__(self, other: object) -> bool:    Object (singleton).
L198: def __getitem__(self, slice: Union[int, slice]) -> "Text":    Function `__getitem__`
utility or script function.
L199: def get_text_at(offset: int) -> "Text":    Function `get_text_at` Returns or fetches
data.
L225: def cell_len(self) -> int:    Function `cell_len` utility or script function.
L230: def markup(self) -> str:    Function `markup` utility or script function.
L260: def from_markup(    Function `from_markup` utility or script function.
L294: def from_ansi(    Function `from_ansi` utility or script function.
L332: def styled(    Function `styled` utility or script function.

```

```

L357: def assemble(    Function `assemble` utility or script function.
L403: def plain(self) -> str:    Function `plain` utility or script function.
L410: def plain(self, new_text: str) -> None:    Function `plain` utility or script function.
L421: def spans(self) -> List[Span]:    Function `spans` utility or script function.
L426: def spans(self, spans: List[Span]) -> None:    Function `spans` utility or script
function.
L430: def blank_copy(self, plain: str = "") -> "Text":    Function `blank_copy` utility or
script function.
L443: def copy(self) -> "Text":    Function `copy` utility or script function.
L457: def stylize(    Function `stylize` utility or script function.
L483: def stylize_before(    Function `stylize_before` utility or script function.
L509: def apply_meta(    Function `apply_meta` utility or script function.
L523: def on(self, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Text":
Function `on` utility or script function.
L543: def remove_suffix(self, suffix: str) -> None:    Function `remove_suffix` utility or
script function.
L552: def get_style_at_offset(self, console: "Console", offset: int) -> Style:    Function
`get_style_at_offset` Returns or fetches data.
L572: def extend_style(self, spaces: int) -> None:    Function `extend_style` utility or
script function.
L593: def highlight_regex(    Function `highlight_regex` utility or script function.
L633: def highlight_words(    Function `highlight_words` utility or script function.
L662: def rstrip(self) -> None:    Function `rstrip` utility or script function.
L666: def rstrip_end(self, size: int) -> None:    Function `rstrip_end` utility or script
function.
L680: def set_length(self, new_length: int) -> None:    Function `set_length` Sets or updates
a value.
L689: def __rich_console__(    Function `__rich_console__` utility or script function.
L708: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L720: def render(self, console: "Console", end: str = "") -> Iterable["Segment"]:    Function
`render` utility or script function.
L759: def get_current_style() -> Style:    Function `get_current_style` Returns or fetches
data.
L779: def join(self, lines: Iterable["Text"]) -> "Text":    Function `join` utility or script
function.
L791: def iter_text() -> Iterable["Text"]:    Function `iter_text` utility or script
function.
L818: def expand_tabs(self, tab_size: Optional[int] = None) -> None:    Function `expand_tabs`
utility or script function.
L860: def truncate(    Function `truncate` utility or script function.
L887: def _trim_spans(self) -> None:    Function `_trim_spans` utility or script function.
L901: def pad(self, count: int, character: str = " ") -> None:    Function `pad` utility or
script function.
L918: def pad_left(self, count: int, character: str = " ") -> None:    Function `pad_left`
utility or script function.
L934: def pad_right(self, count: int, character: str = " ") -> None:    Function `pad_right`
utility or script function.
L945: def align(self, align: AlignMethod, width: int, character: str = " ") -> None:
Function `align` utility or script function.
L965: def append(    Function `append` utility or script function.
L1009: def append_text(self, text: "Text") -> "Text":    Function `append_text` utility or

```

```

script function.
L1031: def append_tokens(    Function `append_tokens`    utility or script function.
L1055: def copy_styles(self, text: "Text") -> None:    Function `copy_styles`    utility or
script function.
L1063: def split(    Function `split`    utility or script function.
L1092: def flatten_spans() -> Iterable[int]:    Function `flatten_spans`    utility or script
function.
L1107: def divide(self, offsets: Iterable[int]) -> Lines:    Function `divide`    utility or
script function.
L1186: def right_crop(self, amount: int = 1) -> None:    Function `right_crop`    utility or
script function.
L1202: def wrap(    Function `wrap`    utility or script function.
L1250: def fit(self, width: int) -> Lines:    Function `fit`    utility or script function.
L1266: def detect_indentation(self) -> int:    Function `detect_indentation`    utility or
script function.
L1287: def with_indent_guides(    Function `with_indent_guides`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/live.py

```

L22: class _RefreshThread(Thread):    Class (`_RefreshThread`)    component used by the app (see
file context: None).
L25: def __init__(self, live: "Live", refresh_per_second: float) -> None:    Function
`__init__`    utility or script function.
L31: def stop(self) -> None:    Function `stop`    utility or script function.
L34: def run(self) -> None:    Function `run`    utility or script function.
L41: class Live(JupyterMixin, RenderHook):    Class (`Live`)    component used by the app (see
file context: None).
L57: def __init__(    Function `__init__`    utility or script function.
L99: def is_started(self) -> bool:    Function `is_started`    utility or script function.
L103: def get_renderable(self) -> RenderableType:    Function `get_renderable`    Returns or
fetches data.
L111: def start(self, refresh: bool = False) -> None:    Function `start`    utility or script
function.
L145: def stop(self) -> None:    Function `stop`    utility or script function.
L179: def __enter__(self) -> Self:    Function `__enter__`    utility or script function.
L183: def __exit__(    Function `__exit__`    utility or script function.
L191: def _enable_redirect_io(self) -> None:    Function `_enable_redirect_io`    utility or
script function.
L201: def _disable_redirect_io(self) -> None:    Function `_disable_redirect_io`    utility or
script function.
L211: def renderable(self) -> RenderableType:    Function `renderable`    utility or script
function.
L226: def update(self, renderable: RenderableType, *, refresh: bool = False) -> None:
Function `update`    utility or script function.
L240: def refresh(self) -> None:    Function `refresh`    utility or script function.
L274: def process_renderables(    Function `process_renderables`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/bar.py

```

L17: class Bar(JupyterMixin):    Class (`Bar`)    component used by the app (see file context:
None).
L29: def __init__(    Function `__init__`    utility or script function.
L45: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L48: def __rich_console__(    Function `__rich_console__`    utility or script function.
L86: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/logging.py

```

L18: class RichHandler(Handler):    Class (`RichHandler`)    component used by the app (see file
context: None).
L65: def __init__(    Function `__init__`    utility or script function.
L117: def get_level_text(self, record: LogRecord) -> Text:    Function `get_level_text`
Returns or fetches data.
L132: def emit(self, record: LogRecord) -> None:    Function `emit`    utility or script
function.
L182: def render_message(self, record: LogRecord, message: str) -> "ConsoleRenderable":
Function `render_message`    utility or script function.
L207: def render(    Function `render`    utility or script function.
L283: def divide() -> None:    Function `divide`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/rule.py

```

L12: class Rule(JupyterMixin):    Class (`Rule`)    component used by the app (see file context:
None).
L23: def __init__(    Function `__init__`    utility or script function.
L46: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L49: def __rich_console__(    Function `__rich_console__`    utility or script function.
L105: def _rule_line(self, chars_len: int, width: int) -> Text:    Function `_rule_line`
utility or script function.
L111: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/pretty.py

```

L60: def _is_attr_object(obj: Any) -> bool:    Function `_is_attr_object`    utility or script
function.
L65: def _get_attr_fields(obj: Any) -> Sequence["_attr_module.Attribute[Any]"]:    Function
`_get_attr_fields`    utility or script function.
L70: def _is_dataclass_repr(obj: object) -> bool:    Object (singleton).
L93: def _has_default_namedtuple_repr(obj: object) -> bool:    Object (singleton).
L113: def _ipy_display_hook(    Function `_ipy_display_hook`    utility or script function.

```

```

L161: def _safe_isinstance(    Function `_safe_isinstance`    utility or script function.
L171: def install(    Function `install`    utility or script function.
L200: def display_hook(value: Any) -> None:    Function `display_hook`    utility or script
function.
L230: class RichFormatter(BaseFormatter):    # type: ignore[misc]    Class (`RichFormatter`)
component used by the app (see file context: None).
L233: def __call__(self, value: Any) -> Any:    Function `__call__`    utility or script
function.
L253: class Pretty(JupyterMixin):    Class (`Pretty`)    component used by the app (see file
context: None).
L273: def __init__(    Function `__init__`    utility or script function.
L304: def __rich_console__(    Function `__rich_console__`    utility or script function.
L339: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L357: def _get_braces_for_defaultdict(_object: DefaultDict[Any, Any]) -> Tuple[str, str,
str]:    Function `_get_braces_for_defaultdict`    utility or script function.
L365: def _get_braces_for_deque(_object: Deque[Any]) -> Tuple[str, str, str]:    Function
`_get_braces_for_deque`    utility or script function.
L375: def _get_braces_for_array(_object: "array[Any]") -> Tuple[str, str, str]:    Function
`_get_braces_for_array`    utility or script function.
L398: def is_expandable(obj: Any) -> bool:    Function `is_expandable`    utility or script
function.
L409: class Node:    Class (`Node`)    component used by the app (see file context: None).
L424: def iter_tokens(self) -> Iterable[str]:    Function `iter_tokens`    utility or script
function.
L446: def check_length(self, start_length: int, max_length: int) -> bool:    Function
`check_length`    utility or script function.
L463: def __str__(self) -> str:    Function `__str__`    utility or script function.
L467: def render(    Function `render`    utility or script function.
L494: class _Line:    Class (`_Line`)    component used by the app (see file context: None).
L507: def expandable(self) -> bool:    Function `expandable`    utility or script function.
L511: def check_length(self, max_length: int) -> bool:    Function `check_length`    utility or
script function.
L519: def expand(self, indent_size: int) -> Iterable["_Line"]:    Function `expand`    utility
or script function.
L552: def __str__(self) -> str:    Function `__str__`    utility or script function.
L561: def _is_namedtuple(obj: Any) -> bool:    Function `_is_namedtuple`    utility or script
function.
L580: def traverse(    Function `traverse`    utility or script function.
L601: def to_repr(obj: Any) -> str:    Function `to_repr`    utility or script function.
L621: def _traverse(obj: Any, root: bool = False, depth: int = 0) -> Node:    Function
`_traverse`    utility or script function.
L633: def iter_rich_args(rich_args: Any) -> Iterable[Union[Any, Tuple[str, Any]]]:    Function
`iter_rich_args`    utility or script function.
L731: def iter_attrs() -> (    Function `iter_attrs`    utility or script function.
L878: def pretty_repr(    Function `pretty_repr`    utility or script function.
L918: def pprint(    Function `pprint`    utility or script function.
L957: class BrokenRepr:    Class (`BrokenRepr`)    component used by the app (see file context:
None).
L958: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L964: class StockKeepingUnit(NamedTuple):    Class (`StockKeepingUnit`)    component used by the
app (see file context: None).

```



```
L1012: class Thing:    Class (`Thing`)    component used by the app (see file context: None).
L1013: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/panel.py

```
L17: class Panel(JupyterMixin):    Class (`Panel`)    component used by the app (see file
context: None).
L40: def __init__(    Function `__init__`    utility or script function.
L74: def fit(    Function `fit`    utility or script function.
L110: def _title(self) -> Optional[Text]:    Function `_title`    utility or script function.
L126: def _subtitle(self) -> Optional[Text]:    Function `_subtitle`    utility or script
function.
L141: def __rich_console__(    Function `__rich_console__`    utility or script function.
L159: def align_text(    Function `align_text`    utility or script function.
L277: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows_rendere r.py

```
L7: def legacy_windows_render(buffer: Iterable[Segment], term: LegacyWindowsTerm) -> None:
Function `legacy_windows_render`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_fileno.py

```
L6: def get_fileno(file_like: IO[str]) -> int | None:    Function `get_fileno`    Returns or
fetches data.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/palette.py

```
L11: class Palette:    Class (`Palette`)    component used by the app (see file context: None).
L14: def __init__(self, colors: Sequence[Tuple[int, int, int]]):    Function `__init__`
utility or script function.
L17: def __getitem__(self, number: int) -> ColorTriplet:    Function `__getitem__`    utility or
script function.
L20: def __rich__(self) -> "Table":    Function `__rich__`    utility or script function.
L45: def match(self, color: Tuple[int, int, int]) -> int:    Function `match`    utility or
script function.
L58: def get_color_distance(index: int) -> float:    Function `get_color_distance`    Returns or
fetches data.
L83: class ColorBox:    Class (`ColorBox`)    component used by the app (see file context:
None).
```

```
L84: def __rich_console__(    Function `__rich_console__`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/pager.py

```
L5: class Pager(ABC):    Class (`Pager`)    component used by the app (see file context: None).
L9: def show(self, content: str) -> None:    Function `show`    utility or script function.
L17: class SystemPager(Pager):    Class (`SystemPager`)    component used by the app (see file
context: None).
L20: def _pager(self, content: str) -> Any: # pragma: no cover    Function `_pager`    utility
or script function.
L23: def show(self, content: str) -> None:    Function `show`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/repr.py

```
L23: class ReprError(Exception):    Class (`ReprError`)    component used by the app (see file
context: None).
L28: def auto(cls: Optional[Type[T]]) -> Type[T]:    Function `auto`    utility or script
function.
L33: def auto(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:    Function `auto`
utility or script function.
L37: def auto(    Function `auto`    utility or script function.
L42: def do_replace(cls: Type[T], angular: Optional[bool] = None) -> Type[T]:    Function
`do_replace`    utility or script function.
L43: def auto_repr(self: T) -> str:    Function `auto_repr`    utility or script function.
L68: def auto_rich_repr(self: Type[T]) -> Result:    Function `auto_rich_repr`    utility or
script function.
L105: def rich_repr(cls: Optional[Type[T]]) -> Type[T]:    Function `rich_repr`    utility or
script function.
L110: def rich_repr(*, angular: bool = False) -> Callable[[Type[T]], Type[T]]:    Function
`rich_repr`    utility or script function.
L114: def rich_repr(    Function `rich_repr`    utility or script function.
L126: class Foo:    Class (`Foo`)    component used by the app (see file context: None).
L127: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/columns.py

```
L16: class Columns(JupyterMixin):    Class (`Columns`)    component used by the app (see file
context: None).
L31: def __init__(    Function `__init__`    utility or script function.
L54: def add_renderable(self, renderable: RenderableType) -> None:    Function
`add_renderable`    utility or script function.
L62: def __rich_console__(    Function `__rich_console__`    utility or script function.
L86: def iter_renderables(    Function `iter_renderables`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/ansi.py

```

L20: class _AnsiToken(NamedTuple):    Class (`_AnsiToken`)    component used by the app (see
file context: None).
L28: def _ansi_tokenize(ansi_text: str) -> Iterable[_AnsiToken]:    Function `_ansi_tokenize`
utility or script function.
L120: class AnsiDecoder:    Class (`AnsiDecoder`)    component used by the app (see file
context: None).
L123: def __init__(self) -> None:    Function `__init__`    utility or script function.
L126: def decode(self, terminal_text: str) -> Iterable[Text]:    Function `decode`    utility or
script function.
L138: def decode_line(self, line: str) -> Text:    Function `decode_line`    utility or script
function.
L224: def read(fd: int) -> bytes:    Function `read`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/live_render.py

```

L14: class LiveRender:    Class (`LiveRender`)    component used by the app (see file context:
None).
L22: def __init__(    Function `__init__`    utility or script function.
L33: def set_renderable(self, renderable: RenderableType) -> None:    Function
`set_renderable`    Sets or updates a value.
L41: def position_cursor(self) -> Control:    Function `position_cursor`    utility or script
function.
L62: def restore_cursor(self) -> Control:    Function `restore_cursor`    utility or script
function.
L76: def __rich_console__(    Function `__rich_console__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/padding.py

```

L19: class Padding(JupyterMixin):    Class (`Padding`)    component used by the app (see file
context: None).
L33: def __init__(    Function `__init__`    utility or script function.
L47: def indent(cls, renderable: "RenderableType", level: int) -> "Padding":    Function
`indent`    utility or script function.
L61: def unpack(pad: "PaddingDimensions") -> Tuple[int, int, int, int]:    Function `unpack`
utility or script function.
L76: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L79: def __rich_console__(    Function `__rich_console__`    utility or script function.
L125: def __rich_measure__(    Function `__rich_measure__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_timer.py

```
L13: def timer(subject: str = "time") -> Generator[None, None, None]:    Function `timer`
utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/align.py

```
L17: class Align(JupyterMixin):    Class (`Align`) component used by the app (see file
context: None).
L33: def __init__(    Function `__init__` utility or script function.
L60: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L64: def left(    Function `left` utility or script function.
L86: def center(    Function `center` utility or script function.
L108: def right(    Function `right` utility or script function.
L129: def __rich_console__(    Function `__rich_console__` utility or script function.
L147: def generate_segments() -> Iterable[Segment]:    Function `generate_segments` Generates
content (often AI-generated).
L192: def blank_lines(count: int) -> Iterable[Segment]:    Function `blank_lines` utility or
script function.
L221: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L228: class VerticalCenter(JupyterMixin):    Class (`VerticalCenter`) component used by the
app (see file context: None).
L240: def __init__(    Function `__init__` utility or script function.
L248: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L251: def __rich_console__(    Function `__rich_console__` utility or script function.
L265: def blank_lines(count: int) -> Iterable[Segment]:    Function `blank_lines` utility or
script function.
L278: def __rich_measure__(    Function `__rich_measure__` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/__init__.py

```
L23: def get_console() -> "Console":    Function `get_console` Returns or fetches data.
L39: def reconfigure(*args: Any, **kwargs: Any) -> None:    Function `reconfigure` utility or
script function.
L53: def print(    Function `print` utility or script function.
L77: def print_json(    Function `print_json` utility or script function.
L120: def inspect(    Function `inspect` utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_inspect.py

```
L15: def _first_paragraph(doc: str) -> str:    Function `_first_paragraph` utility or script
function.
L21: class Inspect(JupyterMixin):    Class (`Inspect`) component used by the app (see file
context: None).
L37: def __init__(    Function `__init__` utility or script function.
L64: def _make_title(self, obj: Any) -> Text:    Function `_make_title` utility or script
```

```

function.
L74: def __rich__(self) -> Panel:    Function `__rich__`    utility or script function.
L82: def _get_signature(self, name: str, obj: Any) -> Optional[Text]:    Function
`_get_signature`    utility or script function.
L121: def _render(self) -> Iterable[RenderableType]:    Function `_render`    utility or script
function.
L124: def sort_items(item: Tuple[str, Any]) -> Tuple[bool, str]:    Function `sort_items`
utility or script function.
L128: def safe_getattr(attr_name: str) -> Tuple[Any, Any]:    Function `safe_getattr`    utility
or script function.
L214: def _get_formatted_doc(self, object_: Any) -> Optional[str]:    Function
`_get_formatted_doc`    utility or script function.
L236: def get_object_types_mro(obj: Union[object, Type[Any]]) -> Tuple[type, ...]:    Object
(singleton).
L245: def get_object_types_mro_as_strings(obj: object) -> Collection[str]:    Object
(singleton).
L258: def is_object_one_of_types(    Function `is_object_one_of_types`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_loop.py

```

L6: def loop_first(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:    Function `loop_first`
utility or script function.
L18: def loop_last(values: Iterable[T]) -> Iterable[Tuple[bool, T]]:    Function `loop_last`
utility or script function.
L31: def loop_first_last(values: Iterable[T]) -> Iterable[Tuple[bool, bool, T]]:    Function
`loop_first_last`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/screen.py

```

L18: class Screen:    Class (`Screen`)    component used by the app (see file context: None).
L28: def __init__(    Function `__init__`    utility or script function.
L40: def __rich_console__(    Function `__rich_console__`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_windows.py

```

L6: class WindowsConsoleFeatures:    Class (`WindowsConsoleFeatures`)    component used by the
app (see file context: None).
L34: def get_windows_console_features() -> WindowsConsoleFeatures:    Function
`get_windows_console_features`    Returns or fetches data.
L40: def get_windows_console_features() -> WindowsConsoleFeatures:    Function
`get_windows_console_features`    Returns or fetches data.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/highlighter.py

```

L8: def _combine_regex(*regexes: str) -> str:    Function `_combine_regex` utility or script
function.
L17: class Highlighter(ABC):    Class (`Highlighter`) component used by the app (see file
context: None).
L20: def __call__(self, text: Union[str, Text]) -> Text:    Function `__call__` utility or
script function.
L42: def highlight(self, text: Text) -> None:    Function `highlight` utility or script
function.
L50: class NullHighlighter(Highlighter):    Class (`NullHighlighter`) component used by the
app (see file context: None).
L57: def highlight(self, text: Text) -> None:    Function `highlight` utility or script
function.
L61: class RegexHighlighter(Highlighter):    Class (`RegexHighlighter`) component used by the
app (see file context: None).
L67: def highlight(self, text: Text) -> None:    Function `highlight` utility or script
function.
L80: class ReprHighlighter(RegexHighlighter):    Class (`ReprHighlighter`) component used by
the app (see file context: None).
L106: class JSONHighlighter(RegexHighlighter):    Class (`JSONHighlighter`) component used by
the app (see file context: None).
L123: def highlight(self, text: Text) -> None:    Function `highlight` utility or script
function.
L143: class ISO8601Highlighter(RegexHighlighter):    Class (`ISO8601Highlighter`) component
used by the app (see file context: None).

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_wrap.py

```

L12: def words(text: str) -> Iterable[tuple[int, int, str]]:    Function `words` utility or
script function.
L26: def divide_line(text: str, width: int, fold: bool = True) -> list[int]:    Function
`divide_line` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/spinner.py

```

L13: class Spinner:    Class (`Spinner`) component used by the app (see file context: None).
L26: def __init__(    Function `__init__` utility or script function.
L50: def __rich_console__(    Function `__rich_console__` utility or script function.
L55: def __rich_measure__(    Function `__rich_measure__` utility or script function.
L61: def render(self, time: float) -> "RenderableType":    Function `render` utility or
script function.
L95: def update(    Function `update` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/style.py

```

L21: class _Bit:    Class (`_Bit`) component used by the app (see file context: None).
L26: def __init__(self, bit_no: int) -> None:    Function `__init__` utility or script
function.
L29: def __get__(self, obj: "Style", objtype: Type["Style"]) -> Optional[bool]:    Function
`__get__` utility or script function.
L36: class Style:    Class (`Style`) component used by the app (see file context: None).
L127: def __init__(    Function `__init__` utility or script function.
L151: def _make_color(color: Union[Color, str]) -> Color:    Function `_make_color` utility
or script function.
L204: def null(cls) -> "Style":    Function `null` utility or script function.
L209: def from_color(    Function `from_color` utility or script function.
L233: def from_meta(cls, meta: Optional[Dict[str, Any]]) -> "Style":    Function `from_meta`
utility or script function.
L254: def on(cls, meta: Optional[Dict[str, Any]] = None, **handlers: Any) -> "Style":
Function `on` utility or script function.
L286: def link_id(self) -> str:    Function `link_id` utility or script function.
L290: def __str__(self) -> str:    Function `__str__` utility or script function.
L336: def __bool__(self) -> bool:    Function `__bool__` utility or script function.
L340: def _make_ansi_codes(self, color_system: ColorSystem) -> str:    Function
`_make_ansi_codes` utility or script function.
L385: def normalize(cls, style: str) -> str:    Function `normalize` utility or script
function.
L401: def pick_first(cls, *values: Optional[StyleType]) -> StyleType:    Function `pick_first`
utility or script function.
L408: def __rich_repr__(self) -> Result:    Function `__rich_repr__` utility or script
function.
L427: def __eq__(self, other: Any) -> bool:    Function `__eq__` utility or script function.
L432: def __ne__(self, other: Any) -> bool:    Function `__ne__` utility or script function.
L437: def __hash__(self) -> int:    Function `__hash__` utility or script function.
L444: def color(self) -> Optional[Color]:    Function `color` utility or script function.
L449: def bgcolor(self) -> Optional[Color]:    Function `bgcolor` utility or script function.
L454: def link(self) -> Optional[str]:    Function `link` utility or script function.
L459: def transparent_background(self) -> bool:    Function `transparent_background` utility
or script function.
L464: def background_style(self) -> "Style":    Function `background_style` utility or script
function.
L469: def meta(self) -> Dict[str, Any]:    Function `meta` utility or script function.
L474: def without_color(self) -> "Style":    Function `without_color` utility or script
function.
L494: def parse(cls, style_definition: str) -> "Style":    Function `parse` utility or script
function.
L560: def get_html_style(self, theme: Optional[TerminalTheme] = None) -> str:    Function
`get_html_style` Returns or fetches data.
L597: def combine(cls, styles: Iterable["Style"]) -> "Style":    Function `combine` utility
or script function.
L610: def chain(cls, *styles: "Style") -> "Style":    Function `chain` utility or script
function.
L622: def copy(self) -> "Style":    Function `copy` utility or script function.

```

```

L645: def clear_meta_and_links(self) -> "Style":    Function `clear_meta_and_links` utility
or script function.
L667: def update_link(self, link: Optional[str] = None) -> "Style":    Function `update_link`
utility or script function.
L690: def render(    Function `render` utility or script function.
L716: def test(self, text: Optional[str] = None) -> None:    Function `test` utility or
script function.
L729: def _add(self, style: Optional["Style"]) -> "Style":    Function `_add` utility or
script function.
L753: def __add__(self, style: Optional["Style"]) -> "Style":    Function `__add__` utility
or script function.
L761: class StyleStack:    Class (`StyleStack`) component used by the app (see file context:
None).
L766: def __init__(self, default_style: "Style") -> None:    Function `__init__` utility or
script function.
L769: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L773: def current(self) -> Style:    Function `current` utility or script function.
L777: def push(self, style: Style) -> None:    Function `push` utility or script function.
L785: def pop(self) -> Style:    Function `pop` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/theme.py

```

L8: class Theme:    Class (`Theme`) component used by the app (see file context: None).
L18: def __init__(    Function `__init__` utility or script function.
L31: def config(self) -> str:    Function `config` utility or script function.
L39: def from_file(    Function `from_file` utility or script function.
L59: def read(    Function `read` utility or script function.
L76: class ThemeStackError(Exception):    Class (`ThemeStackError`) component used by the app
(see file context: None).
L80: class ThemeStack:    Class (`ThemeStack`) component used by the app (see file context:
None).
L87: def __init__(self, theme: Theme) -> None:    Function `__init__` utility or script
function.
L91: def push_theme(self, theme: Theme, inherit: bool = True) -> None:    Function
`push_theme` utility or script function.
L105: def pop_theme(self) -> None:    Function `pop_theme` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/terminal_theme.py

```

L9: class TerminalTheme:    Class (`TerminalTheme`) component used by the app (see file
context: None).
L20: def __init__(    Function `__init__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/layout.py


```

L32: class LayoutRender(NamedTuple):    Class (`LayoutRender`)    component used by the app (see
file context: None).
L43: class LayoutError(Exception):    Class (`LayoutError`)    component used by the app (see
file context: None).
L47: class NoSplitter(LayoutError):    Class (`NoSplitter`)    component used by the app (see
file context: None).
L51: class _Placeholder:    Class (`_Placeholder`)    component used by the app (see file
context: None).
L56: def __init__(self, layout: "Layout", style: StyleType = "") -> None:    Function
`__init__`    utility or script function.
L60: def __rich_console__(    Function `__rich_console__`    utility or script function.
L80: class Splitter(ABC):    Class (`Splitter`)    component used by the app (see file context:
None).
L86: def get_tree_icon(self) -> str:    Function `get_tree_icon`    Returns or fetches data.
L90: def divide(    Function `divide`    utility or script function.
L101: class RowSplitter(Splitter):    Class (`RowSplitter`)    component used by the app (see
file context: None).
L106: def get_tree_icon(self) -> str:    Function `get_tree_icon`    Returns or fetches data.
L109: def divide(    Function `divide`    utility or script function.
L121: class ColumnSplitter(Splitter):    Class (`ColumnSplitter`)    component used by the app
(see file context: None).
L126: def get_tree_icon(self) -> str:    Function `get_tree_icon`    Returns or fetches data.
L129: def divide(    Function `divide`    utility or script function.
L142: class Layout:    Class (`Layout`)    component used by the app (see file context: None).
L156: def __init__(    Function `__init__`    utility or script function.
L177: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.
L184: def renderable(self) -> RenderableType:    Function `renderable`    utility or script
function.
L189: def children(self) -> List["Layout"]:    Function `children`    utility or script
function.
L194: def map(self) -> RenderMap:    Function `map`    Maps or converts between representations.
L198: def get(self, name: str) -> Optional["Layout"]:    Function `get`    Returns or fetches
data.
L216: def __getitem__(self, name: str) -> "Layout":    Function `__getitem__`    utility or
script function.
L223: def tree(self) -> "Tree":    Function `tree`    utility or script function.
L229: def summary(layout: "Layout") -> Table:    Function `summary`    utility or script
function.
L248: def recurse(tree: "Tree", layout: "Layout") -> None:    Function `recurse`    utility or
script function.
L261: def split(    Function `split`    utility or script function.
L286: def add_split(self, *layouts: Union["Layout", RenderableType]) -> None:    Function
`add_split`    utility or script function.
L299: def split_row(self, *layouts: Union["Layout", RenderableType]) -> None:    Function
`split_row`    utility or script function.
L307: def split_column(self, *layouts: Union["Layout", RenderableType]) -> None:    Function
`split_column`    utility or script function.
L315: def unsplit(self) -> None:    Function `unsplit`    utility or script function.
L319: def update(self, renderable: RenderableType) -> None:    Function `update`    utility or
script function.

```

```

L328: def refresh_screen(self, console: "Console", layout_name: str) -> None:    Function
`refresh_screen` utility or script function.
L345: def _make_region_map(self, width: int, height: int) -> RegionMap:    Function
`_make_region_map` utility or script function.
L366: def render(self, console: Console, options: ConsoleOptions) -> RenderMap:    Function
`render` utility or script function.
L395: def __rich_console__(    Function `__rich_console__` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/diagnose.py

```

L10: def report() -> None:    # pragma: no cover    Function `report` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_pick.py

```

L4: def pick_bool(*values: Optional[bool]) -> bool:    Function `pick_bool` utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_win32_console.py

```

L29: class LegacyWindowsError(Exception):    Class (`LegacyWindowsError`) component used by
the app (see file context: None).
L33: class WindowsCoordinates(NamedTuple):    Class (`WindowsCoordinates`) component used by
the app (see file context: None).
L44: def from_param(cls, value: "WindowsCoordinates") -> COORD:    Function `from_param`
utility or script function.
L57: class CONSOLE_SCREEN_BUFFER_INFO(Structure):    Class (`CONSOLE_SCREEN_BUFFER_INFO`)
component used by the app (see file context: None).
L67: class CONSOLE_CURSOR_INFO(ctypes.Structure):    Class (`CONSOLE_CURSOR_INFO`) component
used by the app (see file context: None).
L78: def GetStdHandle(handle: int = STDOUT) -> wintypes.HANDLE:    Function `GetStdHandle`
utility or script function.
L95: def GetConsoleMode(std_handle: wintypes.HANDLE) -> int:    Function `GetConsoleMode`
utility or script function.
L128: def FillConsoleOutputCharacter(    Function `FillConsoleOutputCharacter` utility or
script function.
L169: def FillConsoleOutputAttribute(    Function `FillConsoleOutputAttribute` utility or
script function.
L204: def SetConsoleTextAttribute(    Function `SetConsoleTextAttribute` utility or script
function.
L228: def GetConsoleScreenBufferInfo(    Function `GetConsoleScreenBufferInfo` utility or
script function.
L252: def SetConsoleCursorPosition(    Function `SetConsoleCursorPosition` utility or script
function.

```

```

L275: def GetConsoleCursorInfo(    Function `GetConsoleCursorInfo`    utility or script
function.
L299: def SetConsoleCursorInfo(    Function `SetConsoleCursorInfo`    utility or script
function.
L319: def SetConsoleTitle(title: str) -> bool:    Function `SetConsoleTitle`    utility or
script function.
L331: class LegacyWindowsTerm:    Class (`LegacyWindowsTerm`)    component used by the app (see
file context: None).
L362: def __init__(self, file: "IO[str]") -> None:    Function `__init__`    utility or script
function.
L377: def cursor_position(self) -> WindowsCoordinates:    Function `cursor_position`    utility
or script function.
L387: def screen_size(self) -> WindowsCoordinates:    Function `screen_size`    utility or
script function.
L396: def write_text(self, text: str) -> None:    Function `write_text`    utility or script
function.
L405: def write_styled(self, text: str, style: Style) -> None:    Function `write_styled`
utility or script function.
L444: def move_cursor_to(self, new_position: WindowsCoordinates) -> None:    Function
`move_cursor_to`    utility or script function.
L454: def erase_line(self) -> None:    Function `erase_line`    utility or script function.
L470: def erase_end_of_line(self) -> None:    Function `erase_end_of_line`    utility or script
function.
L484: def erase_start_of_line(self) -> None:    Function `erase_start_of_line`    utility or
script function.
L493: def move_cursor_up(self) -> None:    Function `move_cursor_up`    utility or script
function.
L503: def move_cursor_down(self) -> None:    Function `move_cursor_down`    utility or script
function.
L514: def move_cursor_forward(self) -> None:    Function `move_cursor_forward`    utility or
script function.
L526: def move_cursor_to_column(self, column: int) -> None:    Function
`move_cursor_to_column`    utility or script function.
L535: def move_cursor_backward(self) -> None:    Function `move_cursor_backward`    utility or
script function.
L547: def hide_cursor(self) -> None:    Function `hide_cursor`    utility or script function.
L553: def show_cursor(self) -> None:    Function `show_cursor`    utility or script function.
L559: def set_title(self, title: str) -> None:    Function `set_title`    Sets or updates a
value.
L568: def _get_cursor_size(self) -> int:    Function `_get_cursor_size`    utility or script
function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/color.py

```

L21: class ColorSystem(IntEnum):    Class (`ColorSystem`)    component used by the app (see file
context: None).
L29: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L32: def __str__(self) -> str:    Function `__str__`    utility or script function.

```

```

L36: class ColorType(IntEnum):    Class (`ColorType`)    component used by the app (see file
context: None).
L45: def __repr__(self) -> str:    Function `__repr__`    utility or script function.
L288: class ColorParseError(Exception):    Class (`ColorParseError`)    component used by the
app (see file context: None).
L303: class Color(NamedTuple):    Class (`Color`)    component used by the app (see file
context: None).
L315: def __rich__(self) -> "Text":    Function `__rich__`    utility or script function.
L326: def __rich_repr__(self) -> Result:    Function `__rich_repr__`    utility or script
function.
L333: def system(self) -> ColorSystem:    Function `system`    utility or script function.
L340: def is_system_defined(self) -> bool:    Function `is_system_defined`    utility or script
function.
L345: def is_default(self) -> bool:    Function `is_default`    utility or script function.
L349: def get_truecolor(    Function `get_truecolor`    Returns or fetches data.
L381: def from_ansi(cls, number: int) -> "Color":    Function `from_ansi`    utility or script
function.
L397: def from_triplet(cls, triplet: "ColorTriplet") -> "Color":    Function `from_triplet`
utility or script function.
L409: def from_rgb(cls, red: float, green: float, blue: float) -> "Color":    Function
`from_rgb`    utility or script function.
L423: def default(cls) -> "Color":    Function `default`    utility or script function.
L433: def parse(cls, color: str) -> "Color":    Function `parse`    utility or script function.
L485: def get_ansi_codes(self, foreground: bool = True) -> Tuple[str, ...]:    Function
`get_ansi_codes`    Returns or fetches data.
L513: def downgrade(self, system: ColorSystem) -> "Color":    Function `downgrade`    utility or
script function.
L571: def parse_rgb_hex(hex_color: str) -> ColorTriplet:    Function `parse_rgb_hex`    utility
or script function.
L580: def blend_rgb(    Function `blend_rgb`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/traceback.py

```

L55: def _iter_syntax_lines(    Function `_iter_syntax_lines`    utility or script function.
L83: def install(    Function `install`    utility or script function.
L134: def excepthook(    Function `excepthook`    utility or script function.
L159: def ipy_excepthook_closure(ip: Any) -> None:    # pragma: no cover    Function
`ipy_excepthook_closure`    utility or script function.
L163: def ipy_show_traceback(*args: Any, **kwargs: Any) -> None:    Function
`ipy_show_traceback`    utility or script function.
L169: def ipy_display_traceback(    Function `ipy_display_traceback`    utility or script
function.
L215: class Frame:    Class (`Frame`)    component used by the app (see file context: None).
L225: class _SyntaxError:    Class (`_SyntaxError`)    component used by the app (see file
context: None).
L235: class Stack:    Class (`Stack`)    component used by the app (see file context: None).
L247: class Trace:    Class (`Trace`)    component used by the app (see file context: None).
L251: class PathHighlighter(RegexHighlighter):    Class (`PathHighlighter`)    component used by

```

```

the app (see file context: None).
L255: class Traceback:    Class (`Traceback`)    component used by the app (see file context:
None).
L286: def __init__(    Function `__init__`    utility or script function.
L340: def from_exception(    Function `from_exception`    utility or script function.
L413: def extract(    Function `extract`    utility or script function.
L454: def safe_str(_object: Any) -> str:    Function `safe_str`    utility or script function.
L502: def get_locals(    Function `get_locals`    Returns or fetches data.
L603: def __rich_console__(    Function `__rich_console__`    utility or script function.
L635: def render_stack(stack: Stack, last: bool) -> RenderResult:    Function `render_stack`
utility or script function.
L706: def _render_syntax_error(self, syntax_error: _SyntaxError) -> RenderResult:    Function
`_render_syntax_error`    utility or script function.
L729: def _guess_lexer(cls, filename: str, code: str) -> str:    Function `_guess_lexer`
utility or script function.
L745: def _render_stack(self, stack: Stack) -> RenderResult:    Function `_render_stack`
utility or script function.
L749: def render_locals(frame: Frame) -> Iterable[ConsoleRenderable]:    Function
`render_locals`    utility or script function.
L877: def bar(    Function `bar`    utility or script function.
L883: def foo(a: Any) -> None:    Function `foo`    utility or script function.
L896: def error() -> None:    Function `error`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/table.py

```

L39: class Column:    Class (`Column`)    component used by the app (see file context: None).
L117: def copy(self) -> "Column":    Function `copy`    utility or script function.
L122: def cells(self) -> Iterable["RenderableType"]:    Function `cells`    utility or script
function.
L127: def flexible(self) -> bool:    Function `flexible`    utility or script function.
L133: class Row:    Class (`Row`)    component used by the app (see file context: None).
L143: class _Cell(NamedTuple):    Class (`_Cell`)    component used by the app (see file
context: None).
L154: class Table(JupyterMixin):    Class (`Table`)    component used by the app (see file
context: None).
L189: def __init__(    Function `__init__`    utility or script function.
L254: def grid(    Function `grid`    utility or script function.
L287: def expand(self) -> bool:    Function `expand`    utility or script function.
L292: def expand(self, expand: bool) -> None:    Function `expand`    utility or script
function.
L297: def _extra_width(self) -> int:    Function `_extra_width`    utility or script function.
L307: def row_count(self) -> int:    Function `row_count`    utility or script function.
L311: def get_row_style(self, console: "Console", index: int) -> StyleType:    Function
`get_row_style`    Returns or fetches data.
L321: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L355: def padding(self) -> Tuple[int, int, int, int]:    Function `padding`    utility or script
function.
L360: def padding(self, padding: PaddingDimensions) -> "Table":    Function `padding`    utility

```

```

or script function.
L365: def add_column(    Function `add_column`    utility or script function.
L423: def add_row(    Function `add_row`    utility or script function.
L441: def add_cell(column: Column, renderable: "RenderableType") -> None:    Function
`add_cell`    utility or script function.
L470: def add_section(self) -> None:    Function `add_section`    utility or script function.
L476: def __rich_console__(    Function `__rich_console__`    utility or script function.
L497: def render_annotation(    Function `render_annotation`    utility or script function.
L523: def _calculate_column_widths(    Function `_calculate_column_widths`    utility or script
function.
L588: def _collapse_widths(    Function `_collapse_widths`    utility or script function.
L626: def _get_cells(    Function `_get_cells`    utility or script function.
L641: def get_padding(first_row: bool, last_row: bool) -> Tuple[int, int, int, int]:
Function `get_padding`    Returns or fetches data.
L699: def _get_padding_width(self, column_index: int) -> int:    Function `_get_padding_width`
utility or script function.
L707: def _measure_column(    Function `_measure_column`    utility or script function.
L747: def _render(    Function `_render`    utility or script function.
L839: def align_cell(    Function `align_cell`    utility or script function.
L967: def header(text: str) -> None:    Function `header`    utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/errors.py

```

L1: class ConsoleError(Exception):    Class (`ConsoleError`)    component used by the app (see
file context: None).
L5: class StyleError(Exception):    Class (`StyleError`)    component used by the app (see file
context: None).
L9: class StyleSyntaxError(ConsoleError):    Class (`StyleSyntaxError`)    component used by the
app (see file context: None).
L13: class MissingStyle(StyleError):    Class (`MissingStyle`)    component used by the app (see
file context: None).
L17: class StyleStackError(ConsoleError):    Class (`StyleStackError`)    component used by the
app (see file context: None).
L21: class NotRenderableError(ConsoleError):    Class (`NotRenderableError`)    component used
by the app (see file context: None).
L25: class MarkupError(ConsoleError):    Class (`MarkupError`)    component used by the app (see
file context: None).
L29: class LiveError(ConsoleError):    Class (`LiveError`)    component used by the app (see
file context: None).
L33: class NoAltScreen(ConsoleError):    Class (`NoAltScreen`)    component used by the app (see
file context: None).

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_stack.py

```

L6: class Stack(List[T]):    Class (`Stack`)    component used by the app (see file context:
None).

```

```
L10: def top(self) -> T:    Function `top`    utility or script function.
L14: def push(self, item: T) -> None:    Function `push`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/filesize.py

```
L18: def _to_str(    Function `_to_str`    utility or script function.
L43: def pick_unit_and_suffix(size: int, suffixes: List[str], base: int) -> Tuple[int, str]:
    Function `pick_unit_and_suffix`    utility or script function.
L52: def decimal(    Function `decimal`    utility or script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/markup.py

```
L20: class Tag(NamedTuple):    Class (`Tag`)    component used by the app (see file context:
None).
L28: def __str__(self) -> str:    Function `__str__`    utility or script function.
L34: def markup(self) -> str:    Function `markup`    utility or script function.
L48: def escape(    Function `escape`    utility or script function.
L61: def escape_backslashes(match: Match[str]) -> str:    Function `escape_backslashes`
utility or script function.
L73: def _parse(markup: str) -> Iterable[Tuple[int, Optional[str], Optional[Tag]]]:
Function `_parse`    utility or script function.
L106: def render(    Function `render`    utility or script function.
L146: def pop_style(style_name: str) -> Tuple[int, Tag]:    Function `pop_style`    utility or
script function.
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/region.py

```
L4: class Region(NamedTuple):    Class (`Region`)    component used by the app (see file
context: None).
```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/containers.py

```
L30: class Renderables:    Class (`Renderables`)    component used by the app (see file context:
None).
L33: def __init__(    Function `__init__`    utility or script function.
L40: def __rich_console__(    Function `__rich_console__`    utility or script function.
L46: def __rich_measure__(    Function `__rich_measure__`    utility or script function.
L59: def append(self, renderable: "RenderableType") -> None:    Function `append`    utility or
script function.
L62: def __iter__(self) -> Iterable["RenderableType"]:    Function `__iter__`    utility or
script function.
L66: class Lines:    Class (`Lines`)    component used by the app (see file context: None).
```

```

L69: def __init__(self, lines: Iterable["Text"] = ()) -> None:    Function `__init__` utility
or script function.
L72: def __repr__(self) -> str:    Function `__repr__` utility or script function.
L75: def __iter__(self) -> Iterator["Text"]:    Function `__iter__` utility or script
function.
L79: def __getitem__(self, index: int) -> "Text":    Function `__getitem__` utility or script
function.
L83: def __getitem__(self, index: slice) -> List["Text"]:    Function `__getitem__` utility
or script function.
L86: def __getitem__(self, index: Union[slice, int]) -> Union["Text", List["Text"]]:
Function `__getitem__` utility or script function.
L89: def __setitem__(self, index: int, value: "Text") -> "Lines":    Function `__setitem__`
utility or script function.
L93: def __len__(self) -> int:    Function `__len__` utility or script function.
L96: def __rich_console__(    Function `__rich_console__` utility or script function.
L102: def append(self, line: "Text") -> None:    Function `append` utility or script
function.
L105: def extend(self, lines: Iterable["Text"]) -> None:    Function `extend` utility or
script function.
L108: def pop(self, index: int = -1) -> "Text":    Function `pop` utility or script function.
L111: def justify(    Function `justify` utility or script function.

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/_ratio.py

```

L6: class Edge(Protocol):    Class (`Edge`) component used by the app (see file context:
None).
L14: def ratio_resolve(total: int, edges: Sequence[Edge]) -> List[int]:    Function
`ratio_resolve` utility or script function.
L75: def ratio_reduce(    Function `ratio_reduce` utility or script function.
L107: def ratio_distribute(    Function `ratio_distribute` utility or script function.
L147: class E:    Class (`E`) component used by the app (see file context: None).

```

.venv/lib/python3.12/site-packages/pip/_vendor/rich/file_proxy.py

```

L11: class FileProxy(io.TextIOBase):    Class (`FileProxy`) component used by the app (see
file context: None).
L14: def __init__(self, console: "Console", file: IO[str]) -> None:    Function `__init__`
utility or script function.
L21: def rich_proxied_file(self) -> IO[str]:    Function `rich_proxied_file` utility or
script function.
L25: def __getattr__(self, name: str) -> Any:    Function `__getattr__` utility or script
function.
L28: def write(self, text: str) -> int:    Function `write` utility or script function.
L50: def flush(self) -> None:    Function `flush` utility or script function.
L56: def fileno(self) -> int:    Function `fileno` utility or script function.

```


core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatEntity.kt

L9: data class ChatEntity(Data model (`ChatEntity`) holds structured data used across the app.

L22: fun ChatEntity.isAdmin(userId: String): Boolean { Function `ChatEntity` performs a specific operation used by the surrounding feature.

core-chat/src/main/java/com/algorithmx/q_base/data/chat/MessageEntity.kt

L20: data class MessageEntity(Data model (`MessageEntity`) holds structured data used across the app.

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatDao.kt

L6: data class ChatSummary(Data model (`ChatSummary`) holds structured data used across the app.

L19: interface ChatDao { Interface (`ChatDao`) contract implemented by components.

L21: suspend fun insertChat(chat: ChatEntity) Suspend function `insertChat` coroutine-friendly async operation.

L24: suspend fun getChatById(chatId: String): ChatEntity? Function `getChatById` Returns or fetches data.

L27: fun getChatByIdFlow(chatId: String): Flow<ChatEntity?> Function `getChatByIdFlow` Returns or fetches data.

L30: suspend fun getP2PChat(ids1: String, ids2: String): ChatEntity? Function `getP2PChat` Returns or fetches data.

L33: fun getAllChats(): Flow<List<ChatEntity>> Function `getAllChats` Returns or fetches data.

L46: fun getChatSummaries(): Flow<List<ChatSummary>> Function `getChatSummaries` Returns or fetches data.

L49: suspend fun updateBlockedStatus(chatId: String, isBlocked: Boolean) Suspend function `updateBlockedStatus` coroutine-friendly async operation.

L52: suspend fun updateReportedStatus(chatId: String, isReported: Boolean) Suspend function `updateReportedStatus` coroutine-friendly async operation.

L55: suspend fun updateMutedStatus(chatId: String, isMuted: Boolean) Suspend function `updateMutedStatus` coroutine-friendly async operation.

L58: suspend fun updateParticipants(chatId: String, participantIds: String) Suspend function `updateParticipants` coroutine-friendly async operation.

L61: suspend fun deleteChat(chat: ChatEntity) Function `deleteChat` Deletes a resource.

L64: suspend fun deleteChatById(chatId: String) Function `deleteChatById` Deletes a resource.

L67: suspend fun incrementUnreadCount(chatId: String) Suspend function `incrementUnreadCount` coroutine-friendly async operation.

L70: suspend fun clearUnreadCount(chatId: String) Suspend function `clearUnreadCount` coroutine-friendly async operation.

L73: fun getTotalUnreadCount(): Flow<Int?> Function `getTotalUnreadCount` Returns or fetches data.

L76: suspend fun deleteAllChats() Function `deleteAllChats` Deletes a resource.

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatDatabase.kt

L25: fun getDatabase(context: Context): ChatDatabase { Function `getDatabase` Returns or fetches data.

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatTypeConverters.kt

L8: object ChatTypeConverters { Singleton/object (`ChatTypeConverters`) holds shared state or DI bindings.

L13: fun fromAdminIds(adminIds: List<String>?): String { Function `fromAdminIds` performs a specific operation used by the surrounding feature.

L19: fun toAdminIds(value: String?): List<String> { Function `toAdminIds` performs a specific operation used by the surrounding feature.

core-chat/src/main/java/com/algorithmx/q_base/data/chat/ChatRemoteRepository.kt

L14: class ChatRemoteRepository @Inject constructor(Repository (`ChatRemoteRepository`) handles data operations and coordination for a feature.

L18: private suspend fun getCurrentUserId(): String? { Function `getCurrentUserId` Returns or fetches data.

L26: suspend fun createChatOnRemote(chat: ChatEntity) { Function `createChatOnRemote` Creates a resource or document.

L82: suspend fun addParticipantToRemote(chatId: String, userId: String) { Suspend function `addParticipantToRemote` coroutine-friendly async operation.

L104: suspend fun removeParticipantFromRemote(chatId: String, userId: String) { Suspend function `removeParticipantFromRemote` coroutine-friendly async operation.

L126: suspend fun promoteParticipantToAdminOnRemote(chatId: String, userId: String) { Suspend function `promoteParticipantToAdminOnRemote` coroutine-friendly async operation.

L148: suspend fun demoteAdminOnRemote(chatId: String, userId: String) { Suspend function `demoteAdminOnRemote` coroutine-friendly async operation.

L170: suspend fun clearChatMessagesOnRemote(chatId: String) { Suspend function `clearChatMessagesOnRemote` coroutine-friendly async operation.

L204: suspend fun deleteChatOnRemote(chatId: String) { Function `deleteChatOnRemote` Deletes a resource.

L234: suspend fun reportGroup(group: ChatEntity, reason: String) { Suspend function

```

`reportGroup` coroutine-friendly async operation.
L254: suspend fun reportMessage(message: MessageEntity, reason: String) {    Suspend function
`reportMessage` coroutine-friendly async operation.

```

core-chat/src/main/java/com/algorithmx/q_base/data/chat/MessageDao.kt

```

L7: interface MessageDao {    Interface (`MessageDao`) contract implemented by components.
L9: suspend fun insertMessage(message: MessageEntity)    Suspend function `insertMessage`
coroutine-friendly async operation.
L12: fun getMessagesForChat(chatId: String): Flow<List<MessageEntity>>    Function
`getMessagesForChat` Returns or fetches data.
L15: suspend fun getMessageById(messageId: String): MessageEntity?    Function
`getMessageById` Returns or fetches data.
L18: fun getAllMessages(): Flow<List<MessageEntity>>    Function `getAllMessages` Returns or
fetches data.
L21: suspend fun deleteMessage(message: MessageEntity)    Function `deleteMessage` Deletes a
resource.
L24: suspend fun deleteMessagesByChatId(chatId: String)    Function `deleteMessagesByChatId`
Deletes a resource.
L27: suspend fun deleteAllMessages()    Function `deleteAllMessages` Deletes a resource.
L30: suspend fun getPendingMessages(): List<MessageEntity>    Function `getPendingMessages`
Returns or fetches data.
L33: suspend fun updateMessageStatus(messageId: String, status: String)    Suspend function
`updateMessageStatus` coroutine-friendly async operation.

```

core-crypto/src/main/java/com/algorithmx/q_base/core_crypto/CryptoManager.kt

```

L21: class CryptoManager @Inject constructor(    Manager (`CryptoManager`)
orchestration/utility for managing resources or behaviors.
L37: fun initializeAndGetPublicKey(): String {    Function `initializeAndGetPublicKey`
Initialisation routine.
L57: fun encryptMessage(plaintext: String, receiverPublicKeyBase64: String): String {
Function `encryptMessage` Encrypts data.
L69: fun encryptSessionKey(sessionKey: ByteArray, receiverPublicKeyBase64: String): String {
Function `encryptSessionKey` Encrypts data.
L81: fun decryptMessage(ciphertextBase64: String): Result<String> {    Function
`decryptMessage` Decrypts data.
L91: fun decryptSessionKey(wrappedKeyBase64: String): Result<ByteArray> {    Function
`decryptSessionKey` Decrypts data.
L100: private fun decryptRaw(ciphertextBase64: String): ByteArray {    Function `decryptRaw`
Decrypts data.
L122: fun clearKeys() {    Function `clearKeys` performs a specific operation used by the
surrounding feature.

```

```

L130: fun getPublicKeyFingerprint(): String {    Function `getPublicKeyFingerprint` Returns
or fetches data.
L142: fun encryptFileContent(plaintext: ByteArray): Pair<ByteArray, String> {    Function
`encryptFileContent` Encrypts data.
L158: fun encryptWithSessionKey(plaintext: String): Pair<String, String> {    Function
`encryptWithSessionKey` Encrypts data.
L174: fun decryptWithSessionKey(ciphertextBase64: String, keyHandleBase64: String):
Result<String> {    Function `decryptWithSessionKey` Decrypts data.
L190: fun decryptFileContent(ciphertext: ByteArray, keyBase64: String): ByteArray {
Function `decryptFileContent` Decrypts data.
L206: fun exportEncryptedKeyset(passphrase: String): String {    Function
`exportEncryptedKeyset` performs a specific operation used by the surrounding feature.
L219: fun importEncryptedKeyset(encryptedBackupBase64: String, passphrase: String):
Result<Unit> {    Function `importEncryptedKeyset` performs a specific operation used by the
surrounding feature.
L242: private fun deriveKey(passphrase: String, salt: ByteArray): ByteArray {    Function
`deriveKey` performs a specific operation used by the surrounding feature.
L248: private fun encryptBackup(data: ByteArray, passphrase: String): String {    Function
`encryptBackup` Encrypts data.
L271: private fun decryptBackup(encryptedBase64: String, passphrase: String): ByteArray {
Function `decryptBackup` Decrypts data.
L290: private fun getLocalAead(): Aead {    Function `getLocalAead` Returns or fetches data.
L305: fun encryptLocalString(plaintext: String): String {    Function `encryptLocalString`
Encrypts data.
L312: fun decryptLocalString(ciphertextBase64: String): Result<String> {    Function
`decryptLocalString` Decrypts data.
L325: private fun getGlobalDecryptionKey(): javax.crypto.spec.SecretKeySpec {    Function
`getGlobalDecryptionKey` Returns or fetches data.
L340: fun encryptGlobalKey(plainText: String): String {    Function `encryptGlobalKey`
Encrypts data.
L355: fun decryptGlobalKey(combinedBase64: String): Result<String> {    Function
`decryptGlobalKey` Decrypts data.

```

app/src/androidTest/java/com/algorithmx/q_base/ExampleInstrumentedTest.kt

```

L17: class ExampleInstrumentedTest {    Class (`ExampleInstrumentedTest`) component used by
the app (see file context:
app/src/androidTest/java/com/algorithmx/q_base/ExampleInstrumentedTest.kt).
L19: fun useAppContext() {    Function `useAppContext` performs a specific operation used by
the surrounding feature.

```

app/src/test/java/com/algorithmx/q_base/ExampleUnitTest.kt

```

L12: class ExampleUnitTest {    Class (`ExampleUnitTest`) component used by the app (see file
context: app/src/test/java/com/algorithmx/q_base/ExampleUnitTest.kt).

```

```
L14: fun addition_isCorrect() {    Function `addition_isCorrect`    performs a specific
operation used by the surrounding feature.
```

app/src/test/java/com/algorithmx/q_base/ui/settings/ProfileViewModelTest.kt

```
L25: class ProfileViewModelTest {    Class (`ProfileViewModelTest`)    component used by the app
(see file context:
app/src/test/java/com/algorithmx/q_base/ui/settings/ProfileViewModelTest.kt).
L40: fun setup() {    Function `setup`    Sets or updates a value.
L66: fun tearDown() {    Function `tearDown`    performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/QbaseApplication.kt

```
L9: class QbaseApplication : Application() {    Class (`QbaseApplication`)    component used by
the app (see file context: app/src/main/java/com/algorithmx/q_base/QbaseApplication.kt).
```

app/src/main/java/com/algorithmx/q_base/MainActivity.kt

```
L47: class MainActivity : ComponentActivity() {    Android UI component (`MainActivity`)
activity/fragment presenting screens to the user.
L60: private fun checkNotificationPermission() {    Function `checkNotificationPermission`
performs a specific operation used by the surrounding feature.
L275: fun LoadingScreenCircularArchive() {    Function `LoadingScreenCircularArchive`
performs a specific operation used by the surrounding feature.
L299: fun LoadingScreen() {    Function `LoadingScreen`    performs a specific operation used by
the surrounding feature.
L339: fun MainScreen(    Function `MainScreen`    performs a specific operation used by the
surrounding feature.
L453: fun AppNavDisplay(navigationState: NavigationState, navigator: Navigator) {    Function
`AppNavDisplay`    performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/data/AppDatabase.kt

```
L50: fun getDatabase(context: Context): AppDatabase {    Function `getDatabase`    Returns or
fetches data.
```

app/src/main/java/com/algorithmx/q_base/data/DatabaseSeeder.kt

```

L22: class DatabaseSeeder @Inject constructor( Database abstraction (`DatabaseSeeder`)
encapsulates DB access/setup.
L32: private fun getColumnString(cursor: android.database.Cursor, index: Int): String? {
Function `getColumnString` Returns or fetches data.
L36: suspend fun seedDatabaseIfNeeded() = withContext(Dispatchers.IO) { Suspend function
`seedDatabaseIfNeeded` coroutine-friendly async operation.
L229: private suspend fun seedSampleChats() { Suspend function `seedSampleChats`
coroutine-friendly async operation.
L336: private suspend fun seedAncientSriLanka() { Suspend function `seedAncientSriLanka`
coroutine-friendly async operation.

```

app/src/main/java/com/algorithmx/q_base/data/di/NetworkModule.kt

```

L23: object NetworkModule { Singleton/object (`NetworkModule`) holds shared state or DI
bindings.
L27: fun provideOkHttpClient(): OkHttpClient { Function `provideOkHttpClient` DI provider
method.
L38: fun provideFirestore(): FirebaseFirestore = Firebase.firestore Function
`provideFirestore` DI provider method.
L42: fun provideAppwriteClient(@ApplicationContext context: Context): Client { Function
`provideAppwriteClient` DI provider method.
L99: fun shieldJsonObject(obj: org.json.JSONObject) { Function `shieldJsonObject` performs
a specific operation used by the surrounding feature.
L149: fun provideAppwriteStorage(client: Client): Storage { Function
`provideAppwriteStorage` DI provider method.
L155: fun provideAppwriteDatabases(client: Client): Databases { Function
`provideAppwriteDatabases` DI provider method.
L161: fun provideAppwriteTables(client: Client): Any? { Function `provideAppwriteTables`
DI provider method.
L178: fun provideNetworkMonitor(@ApplicationContext context: Context): NetworkMonitor {
Function `provideNetworkMonitor` DI provider method.

```

app/src/main/java/com/algorithmx/q_base/data/di/DatabaseModule.kt

```

L33: object DatabaseModule { Singleton/object (`DatabaseModule`) holds shared state or DI
bindings.
L37: fun provideDatabase(@ApplicationContext context: Context): AppDatabase { Function
`provideDatabase` DI provider method.
L42: fun provideQuestionDao(database: AppDatabase): QuestionDao = database.questionDao()
Function `provideQuestionDao` DI provider method.
L45: fun provideCollectionDao(database: AppDatabase): CollectionDao =
database.collectionDao() Function `provideCollectionDao` DI provider method.
L48: fun provideSessionDao(database: AppDatabase): SessionDao = database.sessionDao()
Function `provideSessionDao` DI provider method.
L51: fun provideProblemReportDao(database: AppDatabase): ProblemReportDao =
database.problemReportDao() Function `provideProblemReportDao` DI provider method.

```

```

L54: fun provideUserDao(database: AppDatabase): UserDao = database.userDao()    Function
`provideUserDao`    DI provider method.
L58: fun provideChatDatabase(@ApplicationContext context: Context): ChatDatabase {    Function
`provideChatDatabase`    DI provider method.
L63: fun provideChatDao(database: ChatDatabase): ChatDao = database.chatDao()    Function
`provideChatDao`    DI provider method.
L66: fun provideMessageDao(database: ChatDatabase): MessageDao = database.messageDao()
Function `provideMessageDao`    DI provider method.
L69: fun provideAiResponseDao(database: AppDatabase): AiResponseDao =
database.aiResponseDao()    Function `provideAiResponseDao`    DI provider method.
L72: fun provideBrainUsageDao(database: AppDatabase): BrainUsageDao =
database.brainUsageDao()    Function `provideBrainUsageDao`    DI provider method.
L75: fun provideCollectionVersionLedgerDao(database: AppDatabase): CollectionVersionLedgerDao
= database.collectionVersionLedgerDao()    Function `provideCollectionVersionLedgerDao`    DI
provider method.
L78: fun provideActionQueueDao(database: AppDatabase):
com.algorithmx.q_base.data.sync.ActionQueueDao = database.actionQueueDao()    Function
`provideActionQueueDao`    DI provider method.
L82: fun provideExploreRepository(    Function `provideExploreRepository`    DI provider method.
L94: fun provideSessionRepository(    Function `provideSessionRepository`    DI provider method.
L105: fun provideHomeRepository(    Function `provideHomeRepository`    DI provider method.
L117: fun provideImportRepository(@ApplicationContext context: Context): ImportRepository {
Function `provideImportRepository`    DI provider method.
L123: fun provideDataClearingRepository(    Function `provideDataClearingRepository`    DI
provider method.
L141: fun provideProfileCache(userDao: UserDao): ProfileCache {    Function
`provideProfileCache`    DI provider method.

```

app/src/main/java/com/algorithmx/q_base/data/di/BrainModule.kt

```

L14: object BrainModule {    Singleton/object (`BrainModule`)    holds shared state or DI
bindings.
L18: fun provideAiRepository(    Function `provideAiRepository`    DI provider method.

```

app/src/main/java/com/algorithmx/q_base/data/util/TypeConverters.kt

```

L7: class TypeConverters {    Class (`TypeConverters`)    component used by the app (see file
context: app/src/main/java/com/algorithmx/q_base/data/util/TypeConverters.kt).
L9: fun fromBrainTask(task: BrainTask): String {    Function `fromBrainTask`    performs a
specific operation used by the surrounding feature.
L14: fun toBrainTask(name: String): BrainTask {    Function `toBrainTask`    performs a specific
operation used by the surrounding feature.
L23: fun fromBrainProvider(provider: BrainProvider): String {    Function `fromBrainProvider`
performs a specific operation used by the surrounding feature.
L28: fun toBrainProvider(name: String): BrainProvider {    Function `toBrainProvider`
performs a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/data/util/ExportUtils.kt

```

L22: class ExportUtils @Inject constructor(    Utility (`ExportUtils`) helper methods for
common tasks.
L31: suspend fun prepareZip(setWithQuestions: SetWithQuestions): File =
withContext(Dispatchers.IO) {    Suspend function `prepareZip` coroutine-friendly async
operation.

```

app/src/main/java/com/algorithmx/q_base/data/util/MockExporter.kt

```

L24: class MockExporter @Inject constructor(    Class (`MockExporter`) component used by the
app (see file context: app/src/main/java/com/algorithmx/q_base/data/util/MockExporter.kt).
L32: suspend fun exportCollection(collectionId: String): File? = withContext(Dispatchers.IO)
{    Suspend function `exportCollection` coroutine-friendly async operation.
L68: suspend fun exportSession(sessionId: String): File? = withContext(Dispatchers.IO) {
Suspend function `exportSession` coroutine-friendly async operation.
L93: fun cleanup(file: File) {    Function `cleanup` performs a specific operation used by
the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/data/util/MockDownloader.kt

```

L22: class MockDownloader @Inject constructor(    Class (`MockDownloader`) component used by
the app (see file context:
app/src/main/java/com/algorithmx/q_base/data/util/MockDownloader.kt).
L35: suspend fun downloadAndImportMock(    Suspend function `downloadAndImportMock`
coroutine-friendly async operation.
L89: suspend fun downloadAndImportSession(    Suspend function `downloadAndImportSession`
coroutine-friendly async operation.
L134: private suspend fun importCollectionData(    Suspend function `importCollectionData`
coroutine-friendly async operation.
L185: private suspend fun importMockData(mockData: MockExport) {    Suspend function
`importMockData` coroutine-friendly async operation.

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionDao.kt

```

L9: interface SessionDao {    Interface (`SessionDao`) contract implemented by components.
L11: suspend fun insertSession(session: StudySession)    Suspend function `insertSession`
coroutine-friendly async operation.
L14: suspend fun insertSet(set: QuestionSet)    Suspend function `insertSet`
coroutine-friendly async operation.
L17: suspend fun updateSession(session: StudySession)    Suspend function `updateSession`
coroutine-friendly async operation.
L20: fun getAllSessions(): Flow<List<StudySession>>    Function `getAllSessions` Returns or

```



```

fetches data.
L23: fun getOngoingSessions(): Flow<List<StudySession>>    Function `getOngoingSessions`
Returns or fetches data.
L26: suspend fun getSessionById(sessionId: String): StudySession?    Function `getSessionById`
Returns or fetches data.
L29: fun getAllSets(): Flow<List<QuestionSet>>    Function `getAllSets`    Returns or fetches
data.
L32: fun getRecentSets(): Flow<List<QuestionSet>>    Function `getRecentSets`    Returns or
fetches data.
L35: fun getPinnedQuestions(): Flow<List<Question>>    Function `getPinnedQuestions`    Returns
or fetches data.
L38: suspend fun insertAttempts(attempts: List<SessionAttempt>)    Suspend function
`insertAttempts`    coroutine-friendly async operation.
L41: fun getAttemptsForSession(sessionId: String): Flow<List<SessionAttempt>>    Function
`getAttemptsForSession`    Returns or fetches data.
L44: suspend fun getAttemptsForSessionOnce(sessionId: String): List<SessionAttempt>
Function `getAttemptsForSessionOnce`    Returns or fetches data.
L47: suspend fun updateAttempt(attempt: SessionAttempt)    Suspend function `updateAttempt`
coroutine-friendly async operation.
L50: suspend fun getAttempt(sessionId: String, questionId: String): SessionAttempt?
Function `getAttempt`    Returns or fetches data.
L53: fun getLastSessionForStudyCollection(collectionId: String): Flow<StudySession?>
Function `getLastSessionForStudyCollection`    Returns or fetches data.
L56: suspend fun deleteSessionsByIds(sessionIds: List<String>)    Function
`deleteSessionsByIds`    Deletes a resource.
L59: suspend fun deleteAttemptsForSessions(sessionIds: List<String>)    Function
`deleteAttemptsForSessions`    Deletes a resource.
L62: suspend fun deleteAllSessions()    Function `deleteAllSessions`    Deletes a resource.
L65: suspend fun deleteAllAttempts()    Function `deleteAllAttempts`    Deletes a resource.
L68: suspend fun deleteAllSets()    Function `deleteAllSets`    Deletes a resource.

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionExport.kt

```

L6: data class SessionExport(    Data model (`SessionExport`)    holds structured data used
across the app.

```

app/src/main/java/com/algorithmx/q_base/data/sessions/StudySession.kt

```

L10: data class StudySession(    Data model (`StudySession`)    holds structured data used
across the app.

```

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionAttempt.kt

L33: data class SessionAttempt(Data model (`SessionAttempt`) holds structured data used across the app.

app/src/main/java/com/algorithmx/q_base/data/sessions/SessionRepository.kt

```
L19: class SessionRepository @Inject constructor( Repository (`SessionRepository`) handles
data operations and coordination for a feature.
L25: fun getCurrentUser(userId: String): Flow<UserEntity?> = Function `getCurrentUser`
Returns or fetches data.
L28: fun getAllSessions(): Flow<List<StudySession>> = sessionDao.getAllSessions() Function
`getAllSessions` Returns or fetches data.
L30: fun getAllStudyCollections(): Flow<List<StudyCollection>> =
collectionDao.getAllStudyCollections() Function `getAllStudyCollections` Returns or
fetches data.
L32: suspend fun getStudyCollectionByIdOnce(collectionId: String): StudyCollection? =
Function `getStudyCollectionByIdOnce` Returns or fetches data.
L35: suspend fun getStudyCollectionByNameOnce(name: String): StudyCollection? = Function
`getStudyCollectionByNameOnce` Returns or fetches data.
L38: fun getAllSets(): Flow<List<QuestionSet>> = sessionDao.getAllSets() Function
`getAllSets` Returns or fetches data.
L40: suspend fun getSessionById(sessionId: String): StudySession? =
sessionDao.getSessionById(sessionId) Function `getSessionById` Returns or fetches data.
L45: suspend fun createNewSession( Function `createNewSession` Creates a resource or
document.
L87: suspend fun createNewSessionSmart( Function `createNewSessionSmart` Creates a
resource or document.
L107: fun getQuestionsByStudyCollection(collection: String): Flow<List<Question>> =
Function `getQuestionsByStudyCollection` Returns or fetches data.
L110: fun getAttemptsForSession(sessionId: String): Flow<List<SessionAttempt>> = Function
`getAttemptsForSession` Returns or fetches data.
L113: suspend fun getQuestionById(questionId: String): Question? = Function
`getQuestionById` Returns or fetches data.
L116: fun getOptionsForQuestion(questionId: String): Flow<List<QuestionOption>> = Function
`getOptionsForQuestion` Returns or fetches data.
L119: suspend fun getAnswerForQuestion(questionId: String): Answer? = Function
`getAnswerForQuestion` Returns or fetches data.
L122: suspend fun updateAttemptAndRecalculate(attempt: SessionAttempt) { Suspend function
`updateAttemptAndRecalculate` coroutine-friendly async operation.
L191: suspend fun updateAttempt(attempt: SessionAttempt) { Suspend function `updateAttempt`
coroutine-friendly async operation.
L195: suspend fun updateSession(session: StudySession) { Suspend function `updateSession`
coroutine-friendly async operation.
```

```
L199: suspend fun saveAnswer(answer: Answer) {    Function `saveAnswer`    Saves data to storage
or remote.
L203: suspend fun deleteSessions(sessionIds: List<String>) {    Function `deleteSessions`
Deletes a resource.
```

app/src/main/java/com/algorithmx/q_base/data/core/UserDao.kt

```
L7: interface UserDao {    Interface (`UserDao`)    contract implemented by components.
L9: suspend fun insertUser(user: UserEntity)    Suspend function `insertUser`
coroutine-friendly async operation.
L12: suspend fun getUserById(userId: String): UserEntity?    Function `getUserById`    Returns
or fetches data.
L15: fun getCurrentUser(userId: String): Flow<UserEntity?>    Function `getCurrentUser`
Returns or fetches data.
L18: fun getAllUsers(): Flow<List<UserEntity>>    Function `getAllUsers`    Returns or fetches
data.
L21: suspend fun deleteAllUsers()    Function `deleteAllUsers`    Deletes a resource.
```

app/src/main/java/com/algorithmx/q_base/data/core/HomeRepository.kt

```
L18: class HomeRepository @Inject constructor(    Repository (`HomeRepository`)    handles data
operations and coordination for a feature.
L25: fun getCurrentUser(userId: String): Flow<com.algorithmx.q_base.data.core.UserEntity?> =
    Function `getCurrentUser`    Returns or fetches data.
L28: fun getOngoingSessions(): Flow<List<StudySession>> = sessionDao.getOngoingSessions()
Function `getOngoingSessions`    Returns or fetches data.
L30: fun getPinnedQuestions(): Flow<List<Question>> = sessionDao.getPinnedQuestions()
Function `getPinnedQuestions`    Returns or fetches data.
L32: fun getRecentSessions(): Flow<List<StudySession>> = sessionDao.getAllSessions()
Function `getRecentSessions`    Returns or fetches data.
L34: fun getAllStudyCollections(): Flow<List<StudyCollection>> =
collectionDao.getAllStudyCollections()    Function `getAllStudyCollections`    Returns or
fetches data.
L36: fun getAllStudyCollectionsWithCount(): Flow<List<StudyCollectionWithCount>> =    Function
`getAllStudyCollectionsWithCount`    Returns or fetches data.
L39: fun getTotalUnreadCount(): Flow<Int> = chatDao.getTotalUnreadCount().map { it ?: 0 }
Function `getTotalUnreadCount`    Returns or fetches data.
```

app/src/main/java/com/algorithmx/q_base/data/core/UserEntity.kt

```
L7: data class UserEntity(    Data model (`UserEntity`)    holds structured data used across the
app.
```

app/src/main/java/com/algorithmx/q_base/data/core/ConfigRepository.kt

```
L19: class ConfigRepository @Inject constructor( Repository (`ConfigRepository`) handles
data operations and coordination for a feature.
L47: suspend fun saveGeminiKey(key: String) { Function `saveGeminiKey` Saves data to
storage or remote.
L54: suspend fun saveGroqKey(key: String) { Function `saveGroqKey` Saves data to storage
or remote.
L61: suspend fun fetchRemoteConfig() { Suspend function `fetchRemoteConfig`
coroutine-friendly async operation.
L100: suspend fun getGeminiKeyDirectly(): String = geminiApiKey.first() Function
`getGeminiKeyDirectly` Returns or fetches data.
L101: suspend fun getGroqKeyDirectly(): String = groqApiKey.first() Function
`getGroqKeyDirectly` Returns or fetches data.
L103: suspend fun backupKeysToCloud(userId: String) { Suspend function `backupKeysToCloud`
coroutine-friendly async operation.
L137: suspend fun restoreKeysFromCloud(userId: String) { Suspend function
`restoreKeysFromCloud` coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/core/DataClearingRepository.kt

```
L17: class DataClearingRepository @Inject constructor( Repository
(`DataClearingRepository`) handles data operations and coordination for a feature.
L28: suspend fun clearAllData(clearCollections: Boolean) = withContext(Dispatchers.IO) {
Suspend function `clearAllData` coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/ai/BrainUsageEntity.kt

```
L9: data class BrainUsageEntity( Data model (`BrainUsageEntity`) holds structured data
used across the app.
```

app/src/main/java/com/algorithmx/q_base/data/ai/AiResponseDao.kt

```
L7: interface AiResponseDao { Interface (`AiResponseDao`) contract implemented by
components.
L9: fun getAllResponses(): Flow<List<AiResponseEntity>> Function `getAllResponses` Returns
or fetches data.
L12: suspend fun getResponseById(responseId: String): AiResponseEntity? Function
`getResponseById` Returns or fetches data.
L15: suspend fun insertResponse(response: AiResponseEntity) Suspend function
```

```

`insertResponse` coroutine-friendly async operation.
L18: suspend fun updateResponse(response: AiResponseEntity) Suspend function
`updateResponse` coroutine-friendly async operation.
L21: suspend fun deleteResponseById(responseId: String) Function `deleteResponseById`
Deletes a resource.
L24: suspend fun deleteAllAiResponses() Function `deleteAllAiResponses` Deletes a
resource.

```

app/src/main/java/com/algorithmx/q_base/data/ai/AiModuleIntegrator.kt

```

L17: class BrainConfigProviderImpl @Inject constructor( Class (`BrainConfigProviderImpl`)
component used by the app (see file context:
app/src/main/java/com/algorithmx/q_base/data/ai/AiModuleIntegrator.kt).
L32: class AiUsageLoggerImpl @Inject constructor( AI-related component
(`AiUsageLoggerImpl`) coordinates AI/LLM interactions.

```

app/src/main/java/com/algorithmx/q_base/data/ai/AiResponseEntity.kt

```

L6: data class AiResponseEntity( Data model (`AiResponseEntity`) holds structured data
used across the app.

```

app/src/main/java/com/algorithmx/q_base/data/ai/AiRepository.kt

```

L15: class AiRepository @Inject constructor( Repository (`AiRepository`) handles data
operations and coordination for a feature.
L24: suspend fun generateCollection( Function `generateCollection` Generates content
(often AI-generated).
L98: suspend fun saveAsSet( Function `saveAsSet` Saves data to storage or remote.
L118: suspend fun saveAsCollection( Function `saveAsCollection` Saves data to storage or
remote.
L150: private suspend fun saveQuestionsToSet(questions:
List<com.algorithmx.q_base.core_ai.brain.models.AiQuestion>, setId: String, collectionName:
String) { Function `saveQuestionsToSet` Saves data to storage or remote.
L191: suspend fun extractQuestionsFromText( Suspend function `extractQuestionsFromText`
coroutine-friendly async operation.
L265: suspend fun promoteAiResponseToDatabase( Suspend function
`promoteAiResponseToDatabase` coroutine-friendly async operation.
L294: suspend fun assistQuestionEditing(stem: String, options: String = "", context: String =
 ""): Result<String> { Suspend function `assistQuestionEditing` coroutine-friendly async
operation.
L308: suspend fun getAiAssistance(prompt: String): Result<String> { Function
`getAiAssistance` Returns or fetches data.
L312: suspend fun getAiResponseById(responseId: String): AiResponseEntity? { Function
`getAiResponseById` Returns or fetches data.

```

```
L316: private fun extractJsonFromResponse(response: String): String {    Function
`extractJsonFromResponse` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/data/ai/BrainUsageDao.kt

```
L11: interface BrainUsageDao {    Interface (`BrainUsageDao`) contract implemented by
components.
L13: suspend fun insertUsageRecord(record: BrainUsageEntity)    Suspend function
`insertUsageRecord` coroutine-friendly async operation.
L16: fun getRecentUsage(limit: Int = 100): Flow<List<BrainUsageEntity>>    Function
`getRecentUsage` Returns or fetches data.
L19: fun getTotalSuccessfulTokens(): Flow<Int?>    Function `getTotalSuccessfulTokens`
Returns or fetches data.
L22: fun getTotalTokensForTask(taskId: BrainTask): Flow<Int?>    Function
`getTotalTokensForTask` Returns or fetches data.
L25: suspend fun pruneOldRecords(olderThanMs: Long)    Suspend function `pruneOldRecords`
coroutine-friendly async operation.
L28: suspend fun deleteAllBrainUsage()    Function `deleteAllBrainUsage` Deletes a resource.
```

app/src/main/java/com/algorithmx/q_base/data/sync/ChatManagerRepository.kt

```
L23: class ChatManagerRepository @Inject constructor(    Repository (`ChatManagerRepository`)
handles data operations and coordination for a feature.
L37: suspend fun addParticipantToRemote(chatId: String, userId: String) {    Suspend function
`addParticipantToRemote` coroutine-friendly async operation.
L41: suspend fun removeParticipantFromRemote(chatId: String, userId: String) {    Suspend
function `removeParticipantFromRemote` coroutine-friendly async operation.
L45: suspend fun promoteParticipantToAdminOnRemote(chatId: String, userId: String) {
Suspend function `promoteParticipantToAdminOnRemote` coroutine-friendly async operation.
L49: suspend fun demoteAdminOnRemote(chatId: String, userId: String) {    Suspend function
`demoteAdminOnRemote` coroutine-friendly async operation.
L53: suspend fun createChatOnRemote(chat: ChatEntity) {    Function `createChatOnRemote`
Creates a resource or document.
L57: suspend fun getChatById(chatId: String): ChatEntity? {    Function `getChatById` Returns
or fetches data.
L61: suspend fun syncUserChatsFromRemote() {    Suspend function `syncUserChatsFromRemote`
coroutine-friendly async operation.
L126: suspend fun findExistingP2PChat(uid: String, userId: String): ChatEntity? {    Suspend
function `findExistingP2PChat` coroutine-friendly async operation.
L172: suspend fun ensureChatExistsLocally(chatId: String, senderId: String? = null) {
Suspend function `ensureChatExistsLocally` coroutine-friendly async operation.
L198: suspend fun fetchAndSyncChatMetadata(chatId: String) {    Suspend function
`fetchAndSyncChatMetadata` coroutine-friendly async operation.
L237: suspend fun deleteChatOnRemote(chatId: String) {    Function `deleteChatOnRemote`
Deletes a resource.
```

```
L241: fun deleteChatAndMessagesGlobally(chatId: String) {    Function
`deleteChatAndMessagesGlobally`    Deletes a resource.
```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncRepository.kt

```
L21: class MessageSyncRepository @Inject constructor(    Repository (`MessageSyncRepository`)
handles data operations and coordination for a feature.
L39: fun serializeWrappedKeys(map: Map<String, String>): String {    Function
`serializeWrappedKeys`    performs a specific operation used by the surrounding feature.
L45: fun deserializeWrappedKeys(jsonStr: String?): Map<String, String> {    Function
`deserializeWrappedKeys`    performs a specific operation used by the surrounding feature.
L61: suspend fun acknowledgeMessageDelivery(    Suspend function `acknowledgeMessageDelivery`
coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/sync/OfflineActionEntity.kt

```
L8: data class OfflineActionEntity(    Data model (`OfflineActionEntity`)    holds structured
data used across the app.
```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncIncomingGlobalExtensions.kt

```
L17: fun MessageSyncRepository.observeAllIncomingMessages(notificationHelper:
NotificationHelper): Flow<Unit> {    Function `MessageSyncRepository`    returns observable/Flow
data.
L205: suspend fun MessageSyncRepository.fetchAndSyncMessages(chatId: String) {    Suspend
function `MessageSyncRepository`    coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncRequestExtensions.kt

```
L12: suspend fun CollectionSyncRepository.sendSyncRequest(targetUserId: String,
targetCollectionId: String) {    Suspend function `CollectionSyncRepository`
coroutine-friendly async operation.
L34: fun CollectionSyncRepository.observeIncomingRequests(): Flow<List<SyncRequest>> =
callbackFlow {    Function `CollectionSyncRepository`    returns observable/Flow data.
L86: suspend fun CollectionSyncRepository.requestCollectionAccess(chatId: String,
```

```
collectionId: String) { Suspend function `CollectionSyncRepository` coroutine-friendly
async operation.
L107: fun CollectionSyncRepository.observeAccessRequests(chatId: String):
Flow<List<Map<String, Any>>> { Function `CollectionSyncRepository` returns observable/Flow
data.
L155: suspend fun CollectionSyncRepository.grantCollectionAccess(chatId: String,
collectionId: String, requesterId: String) { Suspend function `CollectionSyncRepository`
coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncOutgoingExtensions.kt

```
L11: suspend fun MessageSyncRepository.sendMessage(message: MessageEntity) { Suspend
function `MessageSyncRepository` coroutine-friendly async operation.
L143: suspend fun MessageSyncRepository.flushQueue() { Suspend function
`MessageSyncRepository` coroutine-friendly async operation.
L161: suspend fun MessageSyncRepository.clearChatMessagesOnRemote(chatId: String) { Suspend
function `MessageSyncRepository` coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/sync/SyncRequest.kt

```
L6: data class SyncRequest( Data model (`SyncRequest`) holds structured data used across
the app.
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncPatchExtensions.kt

```
L15: suspend fun CollectionSyncRepository.applyCollectionMicroUpdate(payload: String) {
Suspend function `CollectionSyncRepository` coroutine-friendly async operation.
L128: suspend fun CollectionSyncRepository.broadcastCollectionMicroUpdate(chatId: String,
collectionId: String, diff: JSONObject) { Suspend function `CollectionSyncRepository`
coroutine-friendly async operation.
L168: suspend fun CollectionSyncRepository.sendCollectionPatch(chatId: String, collectionId:
String, op: String, data: JSONObject) { Suspend function `CollectionSyncRepository`
coroutine-friendly async operation.
L185: suspend fun CollectionSyncRepository.applyCollectionPatch(jsonString: String) {
Suspend function `CollectionSyncRepository` coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncRepository.kt


```
L23: class CollectionSyncRepository @Inject constructor( Repository
(`CollectionSyncRepository`) handles data operations and coordination for a feature.
```

app/src/main/java/com/algorithmx/q_base/data/sync/MessageSyncInco mingExtensions.kt

```
L14: fun MessageSyncRepository.observeAndSyncMessages(chatId: String): Flow<MessageEntity?> {
Function `MessageSyncRepository` returns observable/Flow data.
```

app/src/main/java/com/algorithmx/q_base/data/sync/CollectionSyncFile Extensions.kt

```
L19: suspend fun CollectionSyncRepository.uploadQuestionBankZip(zipFile: File): Pair<String,
String> { Suspend function `CollectionSyncRepository` coroutine-friendly async operation.
L39: suspend fun CollectionSyncRepository.deleteQuestionBankZip(fileId: String) { Suspend
function `CollectionSyncRepository` coroutine-friendly async operation.
L48: suspend fun CollectionSyncRepository.shareCollectionToGroup(chatId: String,
collectionMetadata: Map<String, Any>) { Suspend function `CollectionSyncRepository`
coroutine-friendly async operation.
L165: suspend fun CollectionSyncRepository.acknowledgeCollectionDownload(collectionId:
String) { Suspend function `CollectionSyncRepository` coroutine-friendly async operation.
L203: fun CollectionSyncRepository.observeGroupLibrary(chatId: String): Flow<List<Map<String,
Any>>> { Function `CollectionSyncRepository` returns observable/Flow data.
L235: private suspend fun CollectionSyncRepository.mapGroupLibrary(list: List<Map<String,
Any>>): List<Map<String, Any>> { Suspend function `CollectionSyncRepository`
coroutine-friendly async operation.
```

app/src/main/java/com/algorithmx/q_base/data/sync/SyncRepository.kt

```
L18: class SyncRepository @Inject constructor( Repository (`SyncRepository`) handles data
operations and coordination for a feature.
L28: fun observeAndSyncMessages(chatId: String): Flow<MessageEntity?> { Function
`observeAndSyncMessages` Observes changes and returns a Flow/Stream.
L32: suspend fun sendMessage(message: MessageEntity) { Suspend function `sendMessage`
coroutine-friendly async operation.
L36: suspend fun flushQueue() { Suspend function `flushQueue` coroutine-friendly async
operation.
L40: suspend fun addParticipantToRemote(chatId: String, userId: String) { Suspend function
`addParticipantToRemote` coroutine-friendly async operation.
L44: suspend fun removeParticipantFromRemote(chatId: String, userId: String) { Suspend
function `removeParticipantFromRemote` coroutine-friendly async operation.
L48: suspend fun promoteParticipantToAdminOnRemote(chatId: String, userId: String) {
Suspend function `promoteParticipantToAdminOnRemote` coroutine-friendly async operation.
```

```

L52: suspend fun demoteAdminOnRemote(chatId: String, userId: String) { Suspend function
`demoteAdminOnRemote` coroutine-friendly async operation.
L56: suspend fun createChatOnRemote(chat: ChatEntity) { Function `createChatOnRemote`
Creates a resource or document.
L60: fun observeAllIncomingMessages(notificationHelper: NotificationHelper): Flow<Unit> {
Function `observeAllIncomingMessages` Observes changes and returns a Flow/Stream.
L64: suspend fun syncUserChatsFromRemote() { Suspend function `syncUserChatsFromRemote`
coroutine-friendly async operation.
L68: suspend fun findExistingP2PChat(uid: String, userId: String): ChatEntity? { Suspend
function `findExistingP2PChat` coroutine-friendly async operation.
L72: suspend fun fetchAndSyncMessages(chatId: String) { Suspend function
`fetchAndSyncMessages` coroutine-friendly async operation.
L76: suspend fun clearChatMessagesOnRemote(chatId: String) { Suspend function
`clearChatMessagesOnRemote` coroutine-friendly async operation.
L80: suspend fun deleteChatOnRemote(chatId: String) { Function `deleteChatOnRemote`
Deletes a resource.
L84: fun deleteChatAndMessagesGlobally(chatId: String) { Function
`deleteChatAndMessagesGlobally` Deletes a resource.
L88: suspend fun getChatById(chatId: String): ChatEntity? { Function `getChatById` Returns
or fetches data.
L93: suspend fun sendSessionInvite( Suspend function `sendSessionInvite`
coroutine-friendly async operation.
L103: suspend fun addSharedSessionToGroup( Suspend function `addSharedSessionToGroup`
coroutine-friendly async operation.
L113: fun observeSharedSessions(chatId: String): Flow<List<Map<String, Any>>> { Function
`observeSharedSessions` Observes changes and returns a Flow/Stream.
L117: suspend fun sendSessionPatch(chatId: String, sessionId: String, op: String, data:
JSONObject) { Suspend function `sendSessionPatch` coroutine-friendly async operation.
L122: suspend fun sendSyncRequest(targetUserId: String, targetCollectionId: String) {
Suspend function `sendSyncRequest` coroutine-friendly async operation.
L126: fun observeIncomingRequests(): Flow<List<SyncRequest>> { Function
`observeIncomingRequests` Observes changes and returns a Flow/Stream.
L130: suspend fun uploadQuestionBankZip(zipFile: File): Pair<String, String> { Suspend
function `uploadQuestionBankZip` coroutine-friendly async operation.
L134: suspend fun deleteQuestionBankZip(fileId: String) { Function `deleteQuestionBankZip`
Deletes a resource.
L138: suspend fun shareCollectionToGroup(chatId: String, collectionMetadata: Map<String,
Any>) { Suspend function `shareCollectionToGroup` coroutine-friendly async operation.
L142: suspend fun acknowledgeCollectionDownload(collectionId: String) { Suspend function
`acknowledgeCollectionDownload` coroutine-friendly async operation.
L146: suspend fun applyCollectionMicroUpdate(payload: String) { Suspend function
`applyCollectionMicroUpdate` coroutine-friendly async operation.
L150: suspend fun broadcastCollectionMicroUpdate(chatId: String, collectionId: String, diff:
JSONObject) { Suspend function `broadcastCollectionMicroUpdate` coroutine-friendly async
operation.
L154: fun observeGroupLibrary(chatId: String): Flow<List<Map<String, Any>>> { Function
`observeGroupLibrary` Observes changes and returns a Flow/Stream.
L158: suspend fun sendCollectionPatch(chatId: String, collectionId: String, op: String, data:
JSONObject) { Suspend function `sendCollectionPatch` coroutine-friendly async operation.
L162: suspend fun requestCollectionAccess(chatId: String, collectionId: String) { Suspend
function `requestCollectionAccess` coroutine-friendly async operation.

```

```

L166: fun observeAccessRequests(chatId: String): Flow<List<Map<String, Any>>> {    Function
`observeAccessRequests`    Observes changes and returns a Flow/Stream.
L170: suspend fun grantCollectionAccess(chatId: String, collectionId: String, requesterId:
String) {    Suspend function `grantCollectionAccess`    coroutine-friendly async operation.
L175: suspend fun reportSession(sessionId: String, reason: String) {    Suspend function
`reportSession`    coroutine-friendly async operation.
L179: suspend fun reportQuestion(    Suspend function `reportQuestion`    coroutine-friendly
async operation.
L188: suspend fun reportGroup(group: ChatEntity, reason: String) {    Suspend function
`reportGroup`    coroutine-friendly async operation.
L192: suspend fun reportUser(user: UserEntity, reason: String) {    Suspend function
`reportUser`    coroutine-friendly async operation.
L196: suspend fun reportCollection(collection: StudyCollection, reason: String) {    Suspend
function `reportCollection`    coroutine-friendly async operation.
L200: suspend fun reportMessage(message: MessageEntity, reason: String) {    Suspend function
`reportMessage`    coroutine-friendly async operation.

```

app/src/main/java/com/algorithmx/q_base/data/sync/UniversalQueueManager.kt

```

L16: class UniversalQueueManager @Inject constructor(    Manager (`UniversalQueueManager`)
orchestration/utility for managing resources or behaviors.
L22: suspend fun flushUniversalQueue() {    Suspend function `flushUniversalQueue`
coroutine-friendly async operation.
L56: private suspend fun processAction(action: OfflineActionEntity): Boolean {    Suspend
function `processAction`    coroutine-friendly async operation.

```

app/src/main/java/com/algorithmx/q_base/data/sync/ActionQueueDao.kt

```

L6: interface ActionQueueDao {    Interface (`ActionQueueDao`)    contract implemented by
components.
L8: suspend fun insertAction(action: OfflineActionEntity)    Suspend function `insertAction`
coroutine-friendly async operation.
L11: suspend fun getPendingActions(): List<OfflineActionEntity>    Function
`getPendingActions`    Returns or fetches data.
L14: suspend fun deleteAction(action: OfflineActionEntity)    Function `deleteAction`    Deletes
a resource.
L17: suspend fun updateAction(action: OfflineActionEntity)    Suspend function `updateAction`
coroutine-friendly async operation.
L20: suspend fun clearAllActions()    Suspend function `clearAllActions`    coroutine-friendly
async operation.

```

app/src/main/java/com/algorithmx/q_base/data/sync/PatchEvent.kt

L6: data class PatchEvent(Data model (`PatchEvent`) holds structured data used across the app.

app/src/main/java/com/algorithmx/q_base/data/sync/SessionSyncRepository.kt

L27: class SessionSyncRepository @Inject constructor(Repository (`SessionSyncRepository`) handles data operations and coordination for a feature.

L40: suspend fun sendSessionInvite(Suspend function `sendSessionInvite` coroutine-friendly async operation.

L62: suspend fun addSharedSessionToGroup(Suspend function `addSharedSessionToGroup` coroutine-friendly async operation.

L115: fun observeSharedSessions(chatId: String): Flow<List<Map<String, Any>>> { Function `observeSharedSessions` Observes changes and returns a Flow/Stream.

L157: suspend fun sendSessionPatch(chatId: String, sessionId: String, op: String, data: JSONObject) { Suspend function `sendSessionPatch` coroutine-friendly async operation.

L174: suspend fun applySessionPatch(jsonString: String) { Suspend function `applySessionPatch` coroutine-friendly async operation.

app/src/main/java/com/algorithmx/q_base/data/sync/ReportSyncRepository.kt

L20: class ReportSyncRepository @Inject constructor(Repository (`ReportSyncRepository`) handles data operations and coordination for a feature.

L29: suspend fun reportSession(sessionId: String, reason: String) { Suspend function `reportSession` coroutine-friendly async operation.

L52: suspend fun reportQuestion(Suspend function `reportQuestion` coroutine-friendly async operation.

L79: suspend fun reportGroup(group: ChatEntity, reason: String) { Suspend function `reportGroup` coroutine-friendly async operation.

L83: suspend fun reportUser(user: UserEntity, reason: String) { Suspend function `reportUser` coroutine-friendly async operation.

L103: suspend fun reportCollection(collection: StudyCollection, reason: String) { Suspend function `reportCollection` coroutine-friendly async operation.

L123: suspend fun reportMessage(message: MessageEntity, reason: String) { Suspend function `reportMessage` coroutine-friendly async operation.

app/src/main/java/com/algorithmx/q_base/data/collections/ExploreRepository.kt

```

L15: class ExploreRepository @Inject constructor( Repository (`ExploreRepository`) handles
data operations and coordination for a feature.
L22: fun getCurrentUser(userId: String): Flow<UserEntity?> = userDao.getCurrentUser(userId)
Function `getCurrentUser` Returns or fetches data.
L24: fun getStudyCollections(): Flow<List<StudyCollection>> =
collectionDao.getAllStudyCollections() Function `getStudyCollections` Returns or fetches
data.
L26: fun getStudyCollectionsWithCount(): Flow<List<StudyCollectionWithCount>> = Function
`getStudyCollectionsWithCount` Returns or fetches data.
L29: fun getStudyCollectionById(collectionId: String): Flow<StudyCollection?> =
collectionDao.getStudyCollectionById(collectionId) Function `getStudyCollectionById`
Returns or fetches data.
L31: fun getSetsByStudyCollectionId(collectionId: String): Flow<List<QuestionSet>> =
collectionDao.getSetsByStudyCollectionId(collectionId) Function
`getSetsByStudyCollectionId` Returns or fetches data.
L33: fun getLastSessionForStudyCollection(collectionId: String): Flow<StudySession?> =
sessionDao.getLastSessionForStudyCollection(collectionId) Function
`getLastSessionForStudyCollection` Returns or fetches data.
L35: fun getQuestionsByStudyCollection(collection: String): Flow<List<Question>> = Function
`getQuestionsByStudyCollection` Returns or fetches data.
L38: fun getQuestionsBySet(setId: String): Flow<List<Question>> =
collectionDao.getQuestionsForSet(setId) Function `getQuestionsBySet` Returns or fetches
data.
L40: suspend fun getQuestionById(questionId: String): Question? = Function
`getQuestionById` Returns or fetches data.
L43: suspend fun getSessionById(sessionId: String): StudySession? =
sessionDao.getSessionById(sessionId) Function `getSessionById` Returns or fetches data.
L45: suspend fun updateSession(session: StudySession) = sessionDao.updateSession(session)
Suspend function `updateSession` coroutine-friendly async operation.
L47: fun getOptionsForQuestion(questionId: String): Flow<List<QuestionOption>> = Function
`getOptionsForQuestion` Returns or fetches data.
L50: fun getAnswerForQuestion(questionId: String): Flow<Answer?> = Function
`getAnswerForQuestion` Returns or fetches data.
L53: suspend fun updateQuestion(question: Question) { Suspend function `updateQuestion`
coroutine-friendly async operation.
L57: suspend fun reportProblem(report: ProblemReport) { Suspend function `reportProblem`
coroutine-friendly async operation.
L61: fun getAllSets(): Flow<List<QuestionSet>> = sessionDao.getAllSets() Function
`getAllSets` Returns or fetches data.
L63: fun getAllSessions(): Flow<List<StudySession>> = sessionDao.getAllSessions() Function
`getAllSessions` Returns or fetches data.
L65: fun getPinnedQuestions(): Flow<List<Question>> = questionDao.getPinnedQuestions()
Function `getPinnedQuestions` Returns or fetches data.
L67: fun getQuestionCountByStudyCollection(collectionName: String): Flow<Int> = Function
`getQuestionCountByStudyCollection` Returns or fetches data.
L70: suspend fun addQuestionToSet(setId: String, questionId: String) { Suspend function
`addQuestionToSet` coroutine-friendly async operation.
L76: suspend fun addQuestionToSession(sessionId: String, questionId: String) { Suspend
function `addQuestionToSession` coroutine-friendly async operation.
L88: suspend fun saveSet(set: QuestionSet) { Function `saveSet` Saves data to storage or
remote.

```

```

L92: suspend fun saveAnswer(answer: Answer) {    Function `saveAnswer`    Saves data to storage
or remote.
L96: suspend fun updateStudyCollection(collection: StudyCollection) {    Suspend function
`updateStudyCollection`    coroutine-friendly async operation.
L100: suspend fun getStudyCollectionByIdOnce(collectionId: String): StudyCollection? {
Function `getStudyCollectionByIdOnce`    Returns or fetches data.
L104: suspend fun getStudyCollectionByNameOnce(name: String): StudyCollection? {    Function
`getStudyCollectionByNameOnce`    Returns or fetches data.
L108: suspend fun getSetIdForQuestion(questionId: String): String? {    Function
`getSetIdForQuestion`    Returns or fetches data.
L112: suspend fun deleteStudyCollection(collectionId: String) {    Function
`deleteStudyCollection`    Deletes a resource.

```

app/src/main/java/com/algorithmx/q_base/data/collections/ProblemReport.kt

```

L21: data class ProblemReport(    Data model (`ProblemReport`)    holds structured data used
across the app.

```

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionVersionLedger.kt

```

L11: data class CollectionVersionLedgerEntity(    Data model (`CollectionVersionLedgerEntity`)
holds structured data used across the app.
L18: interface CollectionVersionLedgerDao {    Interface (`CollectionVersionLedgerDao`)
contract implemented by components.
L20: suspend fun getLedgerForCollection(collectionId: String): CollectionVersionLedgerEntity?
Function `getLedgerForCollection`    Returns or fetches data.
L23: suspend fun insertLedger(ledger: CollectionVersionLedgerEntity)    Suspend function
`insertLedger`    coroutine-friendly async operation.
L26: suspend fun deleteLedger(collectionId: String)    Function `deleteLedger`    Deletes a
resource.

```

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionSet.kt

```

L23: data class QuestionSet(    Data model (`QuestionSet`)    holds structured data used across
the app.

```

app/src/main/java/com/algorithmx/q_base/data/collections/ImportRepo

sitory.kt

```
L20: class ImportRepository @Inject constructor(    Repository (`ImportRepository`) handles
data operations and coordination for a feature.
L30: suspend fun recognizeTextFromImage(uri: Uri): Result<String> =
withContext(Dispatchers.IO) {    Suspend function `recognizeTextFromImage` coroutine-friendly
async operation.
L41: suspend fun extractTextFromPdf(uri: Uri): Result<String> = withContext(Dispatchers.IO) {
    Suspend function `extractTextFromPdf` coroutine-friendly async operation.
L71: fun cleanRecognizedText(rawText: String): String {    Function `cleanRecognizedText`
performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionWithContent.kt

```
L6: data class QuestionWithContent(    Data model (`QuestionWithContent`) holds structured
data used across the app.
```

app/src/main/java/com/algorithmx/q_base/data/collections/Answer.kt

```
L10: data class Answer(    Data model (`Answer`) holds structured data used across the app.
```

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionWithSets.kt

```
L6: data class StudyCollectionWithSets(    Data model (`StudyCollectionWithSets`) holds
structured data used across the app.
```

app/src/main/java/com/algorithmx/q_base/data/collections/ProblemReportDao.kt

```
L7: interface ProblemReportDao {    Interface (`ProblemReportDao`) contract implemented by
components.
L9: suspend fun insertReport(report: ProblemReport)    Suspend function `insertReport`
coroutine-friendly async operation.
L12: fun getAllReports(): Flow<List<ProblemReport>>    Function `getAllReports` Returns or
fetches data.
L15: fun getReportsForQuestion(questionId: String): Flow<List<ProblemReport>>    Function
`getReportsForQuestion` Returns or fetches data.
```


app/src/main/java/com/algorithmx/q_base/data/collections/CollectionD ao.kt

```

L7: interface CollectionDao {    Interface (`CollectionDao`)    contract implemented by
components.
L9: fun getAllStudyCollections(): Flow<List<StudyCollection>>    Function
`getAllStudyCollections`    Returns or fetches data.
L16: fun getAllStudyCollectionsWithCount(): Flow<List<StudyCollectionWithCount>>    Function
`getAllStudyCollectionsWithCount`    Returns or fetches data.
L19: suspend fun getStudyCollectionCount(): Int    Function `getStudyCollectionCount`    Returns
or fetches data.
L22: fun getStudyCollectionById(collectionId: String): Flow<StudyCollection?>    Function
`getStudyCollectionById`    Returns or fetches data.
L25: suspend fun getStudyCollectionByIdOnce(collectionId: String): StudyCollection?
Function `getStudyCollectionByIdOnce`    Returns or fetches data.
L28: suspend fun getStudyCollectionByNameOnce(name: String): StudyCollection?    Function
`getStudyCollectionByNameOnce`    Returns or fetches data.
L31: fun getSetsByStudyCollectionId(collectionId: String): Flow<List<QuestionSet>>    Function
`getSetsByStudyCollectionId`    Returns or fetches data.
L34: fun getSetsByStudyCollectionName(collectionName: String): Flow<List<QuestionSet>>
Function `getSetsByStudyCollectionName`    Returns or fetches data.
L41: fun getCategoriesByStudyCollectionId(collectionId: String): Flow<List<String>>
Function `getCategoriesByStudyCollectionId`    Returns or fetches data.
L48: fun getQuestionsForSet(setId: String): Flow<List<Question>>    Function
`getQuestionsForSet`    Returns or fetches data.
L51: suspend fun getSetsByStudyCollectionIdOnce(collectionId: String): List<QuestionSet>
Function `getSetsByStudyCollectionIdOnce`    Returns or fetches data.
L58: suspend fun getQuestionsForSetOnce(setId: String): List<Question>    Function
`getQuestionsForSetOnce`    Returns or fetches data.
L61: suspend fun getCrossRefsForSetsBatch(setIds: List<String>): List<SetQuestionCrossRef>
Function `getCrossRefsForSetsBatch`    Returns or fetches data.
L64: suspend fun insertStudyCollections(collections: List<StudyCollection>)    Suspend
function `insertStudyCollections`    coroutine-friendly async operation.
L67: suspend fun updateStudyCollection(collection: StudyCollection)    Suspend function
`updateStudyCollection`    coroutine-friendly async operation.
L70: suspend fun insertSets(sets: List<QuestionSet>)    Suspend function `insertSets`
coroutine-friendly async operation.
L73: suspend fun insertCrossRefs(refs: List<SetQuestionCrossRef>)    Suspend function
`insertCrossRefs`    coroutine-friendly async operation.
L76: suspend fun updateStudyCollectionTimestamp(collectionId: String, timestamp: Long)
Suspend function `updateStudyCollectionTimestamp`    coroutine-friendly async operation.
L79: suspend fun deleteStudyCollectionById(collectionId: String)    Function
`deleteStudyCollectionById`    Deletes a resource.
L82: suspend fun deleteAllStudyCollections()    Function `deleteAllStudyCollections`    Deletes
a resource.

```

app/src/main/java/com/algorithmx/q_base/data/collections/Question.kt

L18: data class Question(Data model (`Question`) holds structured data used across the app.

app/src/main/java/com/algorithmx/q_base/data/collections/CollectionExport.kt

L5: data class CollectionExport(Data model (`CollectionExport`) holds structured data used across the app.

app/src/main/java/com/algorithmx/q_base/data/collections/SetWithQuestions.kt

L7: data class SetWithQuestions(Data model (`SetWithQuestions`) holds structured data used across the app.

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionDao.kt

```
L7: interface QuestionDao { Interface (`QuestionDao`) contract implemented by components.
L9: fun getQuestionsByStudyCollection(collection: String): Flow<List<Question>> Function
`getQuestionsByStudyCollection` Returns or fetches data.
L12: fun getQuestionsByCategory(category: String): Flow<List<Question>> Function
`getQuestionsByCategory` Returns or fetches data.
L15: fun getQuestionsByTag(tag: String): Flow<List<Question>> Function `getQuestionsByTag`
Returns or fetches data.
L18: fun getQuestionsByCategoryAndTag(category: String, tag: String): Flow<List<Question>>
Function `getQuestionsByCategoryAndTag` Returns or fetches data.
L21: fun getOptionsForQuestion(questionId: String): Flow<List<QuestionOption>> Function
`getOptionsForQuestion` Returns or fetches data.
L24: fun getAnswerForQuestion(questionId: String): Flow<Answer?> Function
`getAnswerForQuestion` Returns or fetches data.
L27: suspend fun getOptionsForQuestionOnce(questionId: String): List<QuestionOption>
Function `getOptionsForQuestionOnce` Returns or fetches data.
L30: suspend fun getAnswerForQuestionOnce(questionId: String): Answer? Function
`getAnswerForQuestionOnce` Returns or fetches data.
L33: suspend fun getQuestionById(questionId: String): Question? Function `getQuestionById`
Returns or fetches data.
L36: suspend fun updateQuestion(question: Question) Suspend function `updateQuestion`
coroutine-friendly async operation.
L39: suspend fun insertQuestions(questions: List<Question>) Suspend function
`insertQuestions` coroutine-friendly async operation.
L42: suspend fun insertOptions(options: List<QuestionOption>) Suspend function
```

```

`insertOptions` coroutine-friendly async operation.
L45: suspend fun insertAnswers(answers: List<Answer>) Suspend function `insertAnswers`
coroutine-friendly async operation.
L48: suspend fun insertSet(set: QuestionSet) Suspend function `insertSet`
coroutine-friendly async operation.
L51: suspend fun insertQuestion(question: Question) Suspend function `insertQuestion`
coroutine-friendly async operation.
L54: suspend fun insertOption(option: QuestionOption) Suspend function `insertOption`
coroutine-friendly async operation.
L57: suspend fun insertAnswer(answer: Answer) Suspend function `insertAnswer`
coroutine-friendly async operation.
L60: suspend fun insertSetQuestionCrossRef(crossRef: SetQuestionCrossRef) Suspend function
`insertSetQuestionCrossRef` coroutine-friendly async operation.
L63: fun getQuestionCountFlow(): Flow<Int> Function `getQuestionCountFlow` Returns or
fetches data.
L71: fun getUserCreatedQuestionCount(): Flow<Int> Function `getUserCreatedQuestionCount`
Returns or fetches data.
L79: fun getSharedQuestionCount(): Flow<Int> Function `getSharedQuestionCount` Returns or
fetches data.
L82: suspend fun getQuestionCount(): Int Function `getQuestionCount` Returns or fetches
data.
L85: fun getPinnedQuestions(): Flow<List<Question>> Function `getPinnedQuestions` Returns
or fetches data.
L89: suspend fun getSetWithContent(setId: String): SetWithQuestions? Function
`getSetWithContent` Returns or fetches data.
L92: fun getQuestionCountByStudyCollection(collectionName: String): Flow<Int> Function
`getQuestionCountByStudyCollection` Returns or fetches data.
L95: suspend fun getSetIdForQuestion(questionId: String): String? Function
`getSetIdForQuestion` Returns or fetches data.
L98: suspend fun deleteOptionsForQuestion(questionId: String) Function
`deleteOptionsForQuestion` Deletes a resource.
L101: suspend fun deleteSetById(setId: String) Function `deleteSetById` Deletes a
resource.
L104: suspend fun deleteSetsByIds(setIds: List<String>) Function `deleteSetsByIds` Deletes
a resource.
L107: suspend fun deleteCrossRefsForSets(setIds: List<String>) Function
`deleteCrossRefsForSets` Deletes a resource.
L110: suspend fun removeQuestionFromSet(setId: String, questionId: String) Suspend function
`removeQuestionFromSet` coroutine-friendly async operation.
L113: suspend fun deleteQuestionById(questionId: String) Function `deleteQuestionById`
Deletes a resource.
L116: suspend fun deleteAllQuestions() Function `deleteAllQuestions` Deletes a resource.
L119: suspend fun deleteAllOptions() Function `deleteAllOptions` Deletes a resource.
L122: suspend fun deleteAllAnswers() Function `deleteAllAnswers` Deletes a resource.
L125: suspend fun deleteAllCrossRefs() Function `deleteAllCrossRefs` Deletes a resource.

```

**app/src/main/java/com/algorithmx/q_base/data/collections/MockExport.
kt**

```
L5: data class QuestionExport(    Data model (`QuestionExport`) holds structured data used
across the app.
```

```
L12: data class MockExport(    Data model (`MockExport`) holds structured data used across
the app.
```

app/src/main/java/com/algorithmx/q_base/data/collections/QuestionOption.kt

```
L23: data class QuestionOption(    Data model (`QuestionOption`) holds structured data used
across the app.
```

app/src/main/java/com/algorithmx/q_base/data/collections/StudyCollection.kt

```
L10: data class StudyCollection(    Data model (`StudyCollection`) holds structured data used
across the app.
```

```
L37: data class StudyCollectionWithCount(    Data model (`StudyCollectionWithCount`) holds
structured data used across the app.
```

app/src/main/java/com/algorithmx/q_base/data/collections/SetQuestionCrossRef.kt

```
L32: data class SetQuestionCrossRef(    Data model (`SetQuestionCrossRef`) holds structured
data used across the app.
```

app/src/main/java/com/algorithmx/q_base/util/NotificationHelper.kt

```
L21: class NotificationHelper @Inject constructor(    Utility (`NotificationHelper`) helper
methods for common tasks.
```

```
L30: fun createNotificationChannels() {    Function `createNotificationChannels` Creates a
resource or document.
```

```
L55: fun showMessageNotification(chatId: String, senderName: String, message: String) {
Function `showMessageNotification` performs a specific operation used by the surrounding
feature.
```

```
L87: fun showSessionNotification(sessionId: String, title: String, description: String) {
Function `showSessionNotification` performs a specific operation used by the surrounding
feature.
```

app/src/main/java/com/algorithmx/q_base/util/NetworkMonitor.kt

L21: class NetworkMonitor @Inject constructor(Class (`NetworkMonitor`) component used by the app (see file context: app/src/main/java/com/algorithmx/q_base/util/NetworkMonitor.kt).
 L32: fun currentConnectivity(): Boolean { Function `currentConnectivity` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/navigation/Screen.kt

L7: sealed class Screen : NavKey { Sealed class (`Screen`) represents a closed hierarchy of types.

app/src/main/java/com/algorithmx/q_base/ui/navigation/Navigator.kt

L8: class Navigator(val state: NavigationState) { Class (`Navigator`) component used by the app (see file context:
 app/src/main/java/com/algorithmx/q_base/ui/navigation/Navigator.kt).
 L9: private fun normalizeRoute(route: NavKey): NavKey = when (route) { Function `normalizeRoute` performs a specific operation used by the surrounding feature.
 L14: private fun findTopLevelMatch(route: NavKey): NavKey? = Function `findTopLevelMatch` performs a specific operation used by the surrounding feature.
 L19: private fun resetStack(root: NavKey, stack: androidx.navigation3.runtime.NavBackStack<NavKey>) { Function `resetStack` performs a specific operation used by the surrounding feature.
 L24: fun navigate(route: NavKey) { Function `navigate` performs a specific operation used by the surrounding feature.
 L56: fun resetTo(route: NavKey) { Function `resetTo` performs a specific operation used by the surrounding feature.
 L78: fun goBack() { Function `goBack` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/navigation/NavigationState.kt

L27: fun rememberNavigationState(Function `rememberNavigationState` performs a specific operation used by the surrounding feature.
 L83: class NavigationState(Class (`NavigationState`) component used by the app (see file context: app/src/main/java/com/algorithmx/q_base/ui/navigation/NavigationState.kt).
 L98: fun NavigationState.toEntries(Function `NavigationState` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/navigation/AppEntryProvider.kt

```
L16: fun rememberAppEntryProvider(navigator: Navigator) = remember(navigator) {    Function
`rememberAppEntryProvider` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/navigation/AppEntryWrappers.kt

```
L20: fun ExplorePagerWrapper(key: Screen.ExplorePager, navigator: Navigator) {    Function
`ExplorePagerWrapper` performs a specific operation used by the surrounding feature.
L81: fun CollectionOverviewWrapper(key: Screen.CollectionOverview, navigator: Navigator) {
Function `CollectionOverviewWrapper` performs a specific operation used by the surrounding
feature.
L123: fun PinnedQuestionsWrapper(navigator: Navigator) {    Function `PinnedQuestionsWrapper`
performs a specific operation used by the surrounding feature.
L147: fun ExploreSetWrapper(key: Screen.ExploreSet, navigator: Navigator) {    Function
`ExploreSetWrapper` performs a specific operation used by the surrounding feature.
L193: fun SessionsWrapper(navigator: Navigator) {    Function `SessionsWrapper` performs a
specific operation used by the surrounding feature.
L220: fun NewSessionWizardWrapper(navigator: Navigator) {    Function
`NewSessionWizardWrapper` performs a specific operation used by the surrounding feature.
L238: fun ActiveSessionWrapper(key: Screen.ActiveSession, navigator: Navigator) {    Function
`ActiveSessionWrapper` performs a specific operation used by the surrounding feature.
L253: fun SessionResultsWrapper(key: Screen.SessionResults, navigator: Navigator) {
Function `SessionResultsWrapper` performs a specific operation used by the surrounding
feature.
L267: fun ChatDetailWrapper(key: Screen.ChatDetail, navigator: Navigator) {    Function
`ChatDetailWrapper` performs a specific operation used by the surrounding feature.
L294: fun ContactOverviewWrapper(key: Screen.ContactOverview, navigator: Navigator) {
Function `ContactOverviewWrapper` performs a specific operation used by the surrounding
feature.
L308: fun GroupOverviewWrapper(key: Screen.GroupOverview, navigator: Navigator) {    Function
`GroupOverviewWrapper` performs a specific operation used by the surrounding feature.
L322: fun ProfileWrapper(navigator: Navigator) {    Function `ProfileWrapper` performs a
specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModel.kt

```
L20: data class ExploreQuestionState(    Data model (`ExploreQuestionState`) holds structured
data used across the app.
L32: class ExploreViewModel @Inject constructor(    ViewModel (`ExploreViewModel`) manages UI
state and business logic for related screens.
```

```

L112: fun resetQuestionStates() { Function `resetQuestionStates` performs a specific
operation used by the surrounding feature.
L141: fun loadQuestionsByStudyCollection(collectionId: String) { Function
`loadQuestionsByStudyCollection` Loads data from storage or remote.
L156: fun loadQuestionsBySet(setId: String) { Function `loadQuestionsBySet` Loads data
from storage or remote.
L166: private suspend fun checkIsEditable(collection: StudyCollection?): Boolean { Suspend
function `checkIsEditable` coroutine-friendly async operation.
L175: fun loadPinnedQuestions() { Function `loadPinnedQuestions` Loads data from storage
or remote.
L191: fun updateCollectionAdminOnly(collectionId: String, isAdminOnly: Boolean) { Function
`updateCollectionAdminOnly` performs a specific operation used by the surrounding feature.
L213: fun loadCollectionOverview(collectionId: String) { Function `loadCollectionOverview`
Loads data from storage or remote.
L246: fun updateSessionProgress(sessionId: String, index: Int) { Function
`updateSessionProgress` performs a specific operation used by the surrounding feature.
L254: fun loadQuestionDetails(index: Int) { Function `loadQuestionDetails` Loads data from
storage or remote.
L272: fun selectOption(index: Int, optionLetter: String) { Function `selectOption`
performs a specific operation used by the surrounding feature.
L309: fun revealAnswer(index: Int) { Function `revealAnswer` performs a specific operation
used by the surrounding feature.
L317: fun togglePin(index: Int) { Function `togglePin` performs a specific operation used
by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModel SetExtensions.kt

```

L11: fun ExploreViewModel.toggleSetSelection(setId: String) { Function `ExploreViewModel`
performs a specific operation used by the surrounding feature.
L22: fun ExploreViewModel.clearSelection() { Function `ExploreViewModel` performs a
specific operation used by the surrounding feature.
L27: fun ExploreViewModel.deleteCollectionSet(setId: String) { Function `ExploreViewModel`
performs a specific operation used by the surrounding feature.
L34: suspend fun ExploreViewModel.getSetIdForQuestion(questionId: String): String? {
Suspend function `ExploreViewModel` coroutine-friendly async operation.
L38: fun ExploreViewModel.deleteSelectedSets() { Function `ExploreViewModel` performs a
specific operation used by the surrounding feature.
L50: fun ExploreViewModel.addQuestionToSet(index: Int, setId: String) { Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
L72: fun ExploreViewModel.addQuestionToSession(index: Int, sessionId: String) { Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
L94: fun ExploreViewModel.createSet(title: String, description: String, collectionId: String)
{ Function `ExploreViewModel` performs a specific operation used by the surrounding
feature.
L110: fun ExploreViewModel.deleteQuestion(index: Int) { Function `ExploreViewModel`
performs a specific operation used by the surrounding feature.
L137: fun ExploreViewModel.deleteQuestionFromSet(index: Int, setId: String) { Function

```

```
`ExploreViewModel` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModel AiExtensions.kt

```
L9: fun ExploreViewModel.askAi(index: Int, mode: String = "EXPLAIN") { Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
L37: fun ExploreViewModel.askAiAboutCollection(collection: StudyCollection) { Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
L56: fun ExploreViewModel.clearCollectionAiResponse() { Function `ExploreViewModel`
performs a specific operation used by the surrounding feature.
L60: fun ExploreViewModel.clearAiResponse(index: Int) { Function `ExploreViewModel`
performs a specific operation used by the surrounding feature.
L66: fun ExploreViewModel.saveAiResponseToQuestion(index: Int) { Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/PinnedQuestionsS creen.kt

```
L29: fun PinnedQuestionsScreen( Function `PinnedQuestionsScreen` performs a specific
operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreScreens.kt

```
L45: fun ExploreQuestionPagerScreen( Function `ExploreQuestionPagerScreen` performs a
specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/UnifiedExploreScr een.kt

```
L37: fun UnifiedExploreScreen( Function `UnifiedExploreScreen` performs a specific
operation used by the surrounding feature.
L172: fun MasterCollectionListItem( Function `MasterCollectionListItem` performs a
specific operation used by the surrounding feature.
L256: fun EmptyLibraryView(modifier: Modifier = Modifier) { Function `EmptyLibraryView`
performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/ExploreViewModel

ReportExtensions.kt

```
L10: fun ExploreViewModel.reportCollectionToGroup(collection: StudyCollection, reason:
String) {    Function `ExploreViewModel` performs a specific operation used by the
surrounding feature.
L32: fun ExploreViewModel.reportProblem(index: Int, explanation: String) {    Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
L62: fun ExploreViewModel.reportCollection(collection: StudyCollection, reason: String) {
Function `ExploreViewModel` performs a specific operation used by the surrounding feature.
L79: fun ExploreViewModel.deleteStudyCollection(collectionId: String) {    Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
L92: fun ExploreViewModel.reportSet(setId: String, reason: String) {    Function
`ExploreViewModel` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/CollectionOverviewScreen.kt

```
L39: fun CollectionOverviewScreen(    Function `CollectionOverviewScreen` performs a specific
operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/explore/CollectionOverviewComponents.kt

```
L21: fun StatCard(    Function `StatCard` performs a specific operation used by the
surrounding feature.
L44: fun SetItem(    Function `SetItem` performs a specific operation used by the surrounding
feature.
```

app/src/main/java/com/algorithmx/q_base/ui/state/AppAccessState.kt

```
L3: sealed interface AppAccessState {    Interface (`AppAccessState`) contract implemented by
components.
L4: data object RestoringSession : AppAccessState    Singleton/object (`RestoringSession`)
holds shared state or DI bindings.
L5: data object OnlineReady : AppAccessState    Singleton/object (`OnlineReady`) holds shared
state or DI bindings.
L6: data object SignedInOffline : AppAccessState    Singleton/object (`SignedInOffline`)
holds shared state or DI bindings.
L7: data object GuestOnline : AppAccessState    Singleton/object (`GuestOnline`) holds shared
state or DI bindings.
L8: data object OfflineGuest : AppAccessState    Singleton/object (`OfflineGuest`) holds
shared state or DI bindings.
```


app/src/main/java/com/algorithmx/q_base/ui/sessions/NewSessionWizardScreen.kt

```
L26: fun NewSessionWizardScreen(    Function `NewSessionWizardScreen` performs a specific
operation used by the surrounding feature.
L140: fun EmptyCollectionsView() {    Function `EmptyCollectionsView` performs a specific
operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionsScreens.kt

```
L51: fun SessionsListScreen(    Function `SessionsListScreen` performs a specific operation
used by the surrounding feature.
L176: fun AnimatedSessionItem(index: Int, content: @Composable () -> Unit) {    Function
`AnimatedSessionItem` performs a specific operation used by the surrounding feature.
L192: fun CategoryChip(name: String) {    Function `CategoryChip` performs a specific
operation used by the surrounding feature.
L220: fun SessionListItemExpressive(    Function `SessionListItemExpressive` performs a
specific operation used by the surrounding feature.
L319: fun EmptySessionsView() {    Function `EmptySessionsView` performs a specific operation
used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionWizardSteps.kt

```
L27: fun CategoryStep(    Function `CategoryStep` performs a specific operation used by the
surrounding feature.
L75: fun QuestionSelectionStep(    Function `QuestionSelectionStep` performs a specific
operation used by the surrounding feature.
L182: fun ConfigurationStep(    Function `ConfigurationStep` performs a specific operation
used by the surrounding feature.
L284: fun ConfigToggle(    Function `ConfigToggle` performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/ActiveSessionViewModel.kt

```
L25: sealed class SessionNavEvent {    Sealed class (`SessionNavEvent`) represents a closed
hierarchy of types.
L26: data class NavigateToResults(val sessionId: String) : SessionNavEvent()    Data model
(`NavigateToResults`) holds structured data used across the app.
```

```

L29: data class NavigatorDot(    Data model (`NavigatorDot`) holds structured data used
across the app.
L36: class ActiveSessionViewModel @Inject constructor(    ViewModel (`ActiveSessionViewModel`)
manages UI state and business logic for related screens.
L116: fun setSessionId(id: String, chatId: String? = null) {    Function `setSessionId` Sets
or updates a value.
L128: fun getSessionId(): String = _sessionId    Function `getSessionId` Returns or fetches
data.
L130: private fun loadSessionData() {    Function `loadSessionData` Loads data from storage
or remote.
L156: private fun startTimer() {    Function `startTimer` performs a specific operation used
by the surrounding feature.
L184: private fun loadAttempts() {    Function `loadAttempts` Loads data from storage or
remote.
L195: fun navigateToQuestion(index: Int) {    Function `navigateToQuestion` performs a
specific operation used by the surrounding feature.
L205: private fun loadQuestion(questionId: String) {    Function `loadQuestion` Loads data
from storage or remote.
L216: fun onAnswerSelected(optionLetter: String) {    Function `onAnswerSelected` performs a
specific operation used by the surrounding feature.
L257: fun toggleFlag() {    Function `toggleFlag` performs a specific operation used by the
surrounding feature.
L264: private fun updateAttempt(attempt: SessionAttempt) {    Function `updateAttempt`
performs a specific operation used by the surrounding feature.
L290: fun askAi(mode: String = "EXPLAIN") {    Function `askAi` performs a specific operation
used by the surrounding feature.
L309: fun clearAiResponse() {    Function `clearAiResponse` performs a specific operation
used by the surrounding feature.
L313: fun saveAiResponseToQuestion() {    Function `saveAiResponseToQuestion` Saves data to
storage or remote.
L331: fun submitSession() {    Function `submitSession` performs a specific operation used by
the surrounding feature.
L366: fun reportSession(reason: String) {    Function `reportSession` performs a specific
operation used by the surrounding feature.
L380: fun reportQuestion(reason: String) {    Function `reportQuestion` performs a specific
operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/ActiveSessionScreen.kt

```

L56: fun ActiveSessionScreen(    Function `ActiveSessionScreen` performs a specific operation
used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionsViewModel.kt

```

L20: class SessionsViewModel @Inject constructor(    ViewModel (`SessionsViewModel`) manages
UI state and business logic for related screens.
L96: fun onSearchQueryChange(query: String) {    Function `onSearchQueryChange` performs a
specific operation used by the surrounding feature.
L100: fun setWizardStep(step: Int) {    Function `setWizardStep` Sets or updates a value.
L104: fun selectCollection(name: String) {    Function `selectCollection` performs a specific
operation used by the surrounding feature.
L114: fun toggleQuestionSelection(id: String) {    Function `toggleQuestionSelection`
performs a specific operation used by the surrounding feature.
L121: fun selectAllQuestions() {    Function `selectAllQuestions` performs a specific
operation used by the surrounding feature.
L125: fun deselectAllQuestions() {    Function `deselectAllQuestions` performs a specific
operation used by the surrounding feature.
L129: fun selectRandomQuestions(count: Int) {    Function `selectRandomQuestions` performs a
specific operation used by the surrounding feature.
L140: fun setOrder(order: String) { _sessionOrder.value = order }    Function `setOrder` Sets
or updates a value.
L141: fun setTimingType(type: String) { _timingType.value = type }    Function `setTimingType`
Sets or updates a value.
L142: fun setTimeLimit(seconds: Int) { _timeLimitSeconds.value = seconds }    Function
`setTimeLimit` Sets or updates a value.
L143: fun setSessionIsAdminOnly(value: Boolean) { _sessionIsAdminOnly.value = value }
Function `setSessionIsAdminOnly` Sets or updates a value.
L145: fun launchSession(title: String) {    Function `launchSession` performs a specific
operation used by the surrounding feature.
L163: fun resetWizard() {    Function `resetWizard` performs a specific operation used by the
surrounding feature.
L174: fun toggleSessionSelection(sessionId: String) {    Function `toggleSessionSelection`
performs a specific operation used by the surrounding feature.
L185: fun clearSessionSelection() {    Function `clearSessionSelection` performs a specific
operation used by the surrounding feature.
L190: fun deleteSelectedSessions() {    Function `deleteSelectedSessions` Deletes a resource.
L200: fun reportSession(sessionId: String, reason: String) {    Function `reportSession`
performs a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionResultsViewModel.kt

```

L20: data class ReviewState(    Data model (`ReviewState`) holds structured data used across
the app.
L27: sealed class ResultsUiState {    Sealed class (`ResultsUiState`) represents a closed
hierarchy of types.
L28: object Loading : ResultsUiState()    Singleton/object (`Loading`) holds shared state or
DI bindings.
L29: data class Success(val session: StudySession?, val attempts: List<SessionAttempt>, val
score: Float) : ResultsUiState()    Data model (`Success`) holds structured data used across
the app.
L33: class SessionResultsViewModel @Inject constructor(    ViewModel

```

```
(`SessionResultsViewModel`) manages UI state and business logic for related screens.
L66: fun initSession(id: String) {    Function `initSession` Initialisation routine.
L72: private fun loadResults() {    Function `loadResults` Loads data from storage or remote.
L104: fun updateSessionAdminOnly(sessionId: String, isAdminOnly: Boolean) {    Function
`updateSessionAdminOnly` performs a specific operation used by the surrounding feature.
L128: fun selectQuestionForReview(attempt: SessionAttempt) {    Function
`selectQuestionForReview` performs a specific operation used by the surrounding feature.
L143: fun clearReview() {    Function `clearReview` performs a specific operation used by the
surrounding feature.
L147: fun reportCurrentSession(reason: String) {    Function `reportCurrentSession` performs
a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/SessionResultsScreen.kt

```
L39: fun SessionResultsScreen(    Function `SessionResultsScreen` performs a specific
operation used by the surrounding feature.
L162: fun ResultsContent(    Function `ResultsContent` performs a specific operation used by
the surrounding feature.
L334: fun AnimatedAttemptDot(    Function `AnimatedAttemptDot` performs a specific operation
used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/sessions/components/MasterNavigator.kt

```
L21: fun MasterNavigator(    Function `MasterNavigator` performs a specific operation used by
the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/settings/AiBrainManagerScreen.kt

```
L22: fun AiBrainManagerScreen(    Function `AiBrainManagerScreen` performs a specific
operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/settings/SecureBackupViewModel.kt

```
L14: data class SecureBackupState(    Data model (`SecureBackupState`) holds structured data
used across the app.
```

```

L22: class SecureBackupViewModel @Inject constructor(    ViewModel (`SecureBackupViewModel`)
manages UI state and business logic for related screens.
L34: fun checkBackupStatus() {    Function `checkBackupStatus`    performs a specific operation
used by the surrounding feature.
L43: fun setupBackup(passphrase: String) {    Function `setupBackup`    Sets or updates a value.
L64: fun restoreBackup(passphrase: String) {    Function `restoreBackup`    performs a specific
operation used by the surrounding feature.
L80: fun clearState() {    Function `clearState`    performs a specific operation used by the
surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/SettingsScreen.kt

```

L34: fun SettingsScreen(    Function `SettingsScreen`    performs a specific operation used by
the surrounding feature.
L58: fun SettingsContent(    Function `SettingsContent`    performs a specific operation used by
the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/ProfileViewModel.kt

```

L23: data class UserStats(    Data model (`UserStats`)    holds structured data used across the
app.
L31: class ProfileViewModel @Inject constructor(    ViewModel (`ProfileViewModel`)    manages UI
state and business logic for related screens.
L82: private fun loadUser() {    Function `loadUser`    Loads data from storage or remote.
L96: private fun loadBackupStatus() {    Function `loadBackupStatus`    Loads data from storage
or remote.
L110: private fun loadStats() {    Function `loadStats`    Loads data from storage or remote.
L130: private suspend fun tryUpdateProfile(updatedProfile: UserProfile) {    Suspend function
`tryUpdateProfile`    coroutine-friendly async operation.
L142: fun updateDisplayName(newName: String) {    Function `updateDisplayName`    performs a
specific operation used by the surrounding feature.
L160: fun updateIntro(newIntro: String) {    Function `updateIntro`    performs a specific
operation used by the surrounding feature.
L178: fun updateProfilePictureUrl(url: String) {    Function `updateProfilePictureUrl`
performs a specific operation used by the surrounding feature.
L196: fun togglePhotoVisibility(isVisible: Boolean) {    Function `togglePhotoVisibility`
performs a specific operation used by the surrounding feature.
L214: fun signOut(clearCollections: Boolean, onComplete: () -> Unit) {    Function `signOut`
performs a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/ProfileComponent.ts.kt

```

L40: data class AvatarTemplate(    Data model (`AvatarTemplate`)  holds structured data used
across the app.
L59: fun Modifier.bounceClick(onClick: () -> Unit = {}) = composed {    Function `Modifier`
performs a specific operation used by the surrounding feature.
L91: fun ProfileParallaxHeader(    Function `ProfileParallaxHeader`  performs a specific
operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/SettingsViewMod el.kt

```

L25: class SettingsViewModel @Inject constructor(    ViewModel (`SettingsViewModel`)  manages
UI state and business logic for related screens.
L44: fun updateModel(newModel: String) {    Function `updateModel`  performs a specific
operation used by the surrounding feature.
L56: fun updateSystemInstruction(instruction: String) {    Function `updateSystemInstruction`
performs a specific operation used by the surrounding feature.
L67: fun saveTaskConfig(task: BrainTask, config: TaskConfig) {    Function `saveTaskConfig`
Saves data to storage or remote.
L73: fun updateNotifications(enabled: Boolean) {    Function `updateNotifications`  performs a
specific operation used by the surrounding feature.
L79: fun updateTheme(mode: String) {    Function `updateTheme`  performs a specific operation
used by the surrounding feature.
L85: fun clearAllData(onComplete: () -> Unit) {    Function `clearAllData`  performs a
specific operation used by the surrounding feature.
L94: private fun calculateDbSize(): Double {    Function `calculateDbSize`  performs a
specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/AppThemeScreen .kt

```

L26: fun AppThemeScreen(    Function `AppThemeScreen`  performs a specific operation used by
the surrounding feature.
L85: data class ThemeOption(val id: String, val title: String, val subtitle: String)    Data
model (`ThemeOption`)  holds structured data used across the app.
L88: fun ThemeCard(    Function `ThemeCard`  performs a specific operation used by the
surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/SecureBackupDia log.kt

```

L16: fun SecureBackupDialog(    Function `SecureBackupDialog`  performs a specific operation
used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/ProfileScreen.kt

```

L35: fun ProfileScreen(    Function `ProfileScreen`    performs a specific operation used by the
surrounding feature.
L74: fun ProfileContent(    Function `ProfileContent`    performs a specific operation used by
the surrounding feature.
L290: fun ProfileContentPreview() {    Function `ProfileContentPreview`    performs a specific
operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/ProfileAvatar.kt

```

L29: fun ProfileAvatar(    Function `ProfileAvatar`    performs a specific operation used by the
surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/ProfileRowComponents.kt

```

L19: fun ProfileCardSection(    Function `ProfileCardSection`    performs a specific operation
used by the surrounding feature.
L54: fun ProfilePropertyRow(    Function `ProfilePropertyRow`    performs a specific operation
used by the surrounding feature.
L113: fun ProfilePropertyToggleRow(    Function `ProfilePropertyToggleRow`    performs a
specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/SettingsComponents.kt

```

L18: fun SettingsSection(    Function `SettingsSection`    performs a specific operation used by
the surrounding feature.
L31: fun SettingsSectionHeader(title: String) {    Function `SettingsSectionHeader`    performs
a specific operation used by the surrounding feature.
L44: fun SettingsToggleCard(    Function `SettingsToggleCard`    performs a specific operation
used by the surrounding feature.
L81: fun SettingsCard(    Function `SettingsCard`    performs a specific operation used by the
surrounding feature.
L117: fun UsageStatsCard(requests: Int, tokens: Int) {    Function `UsageStatsCard`    performs
a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/settings/components/ProfileStatsComponents.kt

```
L28: fun ProfileAchievementsProperty(stats: UserStats) {    Function
`ProfileAchievementsProperty` performs a specific operation used by the surrounding feature.
L63: fun BadgeBadge(    Function `BadgeBadge` performs a specific operation used by the
surrounding feature.
L134: fun StatCard(    Function `StatCard` performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/theme/Theme.kt

```
L98: fun QbaseTheme(    Function `QbaseTheme` performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ContactOverviewScreen.kt

```
L34: fun ContactOverviewScreen(    Function `ContactOverviewScreen` performs a specific
operation used by the surrounding feature.
L196: fun ActionButton(    Function `ActionButton` performs a specific operation used by the
surrounding feature.
L221: fun SettingsItem(    Function `SettingsItem` performs a specific operation used by the
surrounding feature.
L260: fun ReportDialog(    Function `ReportDialog` performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatDetailScreen.kt

```
L27: fun ChatDetailScreen(    Function `ChatDetailScreen` performs a specific operation used
by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/GroupOverviewScreen.kt

```
L35: fun GroupOverviewScreen(    Function `GroupOverviewScreen` performs a specific operation
used by the surrounding feature.
L334: fun ParticipantItem(user: UserEntity, isAdmin: Boolean, onClick: () -> Unit = {}) {
Function `ParticipantItem` performs a specific operation used by the surrounding feature.
```


app/src/main/java/com/algorithmx/q_base/ui/chat/NewChatScreen.kt

```
L10: fun NewChatScreen(    Function `NewChatScreen`    performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModelSharingExtensions.kt

```
L10: fun ChatViewModel.addSharedCollection(jsonPayload: String) {    Function `ChatViewModel`
performs a specific operation used by the surrounding feature.
L27: fun ChatViewModel.importSharedCollection(payload: String) {    Function `ChatViewModel`
performs a specific operation used by the surrounding feature.
L80: fun ChatViewModel.shareCollection(chatId: String, collectionId: String) {    Function
`ChatViewModel`    performs a specific operation used by the surrounding feature.
L132: fun ChatViewModel.resendCollection(collectionId: String) {    Function `ChatViewModel`
performs a specific operation used by the surrounding feature.
L176: fun ChatViewModel.shareSession(chatId: String, sessionId: String) {    Function
`ChatViewModel`    performs a specific operation used by the surrounding feature.
L217: fun ChatViewModel.joinSession(sessionIdOrPayload: String, onSessionImported: (String)
-> Unit) {    Function `ChatViewModel`    performs a specific operation used by the surrounding
feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatListScreen.kt

```
L44: fun ChatListScreen(    Function `ChatListScreen`    performs a specific operation used by
the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/BlockedListScreen.kt

```
L26: fun BlockedListScreen(    Function `BlockedListScreen`    performs a specific operation
used by the surrounding feature.
L71: fun BlockedChatItem(    Function `BlockedChatItem`    performs a specific operation used by
the surrounding feature.
L129: fun EmptyBlockedView(modifier: Modifier = Modifier) {    Function `EmptyBlockedView`
performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/AddParticipantDialog.kt

```
L23: fun AddParticipantDialog(    Function `AddParticipantDialog`    performs a specific
```

operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/chat/NewGroupScreen.kt

L29: fun NewGroupScreen(Function `NewGroupScreen` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatModels.kt

L10: data class ChatUiModel(Data model (`ChatUiModel`) holds structured data used across the app.
 L20: data class ChatListState(Data model (`ChatListState`) holds structured data used across the app.
 L29: data class ChatDetailState(Data model (`ChatDetailState`) holds structured data used across the app.
 L40: sealed class ChatNavEvent { Sealed class (`ChatNavEvent`) represents a closed hierarchy of types.
 L41: data class NavigateToChatDetail(val chatId: String) : ChatNavEvent() Data model (`NavigateToChatDetail`) holds structured data used across the app.

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModel.kt

L34: class ChatViewModel @Inject constructor(ViewModel (`ChatViewModel`) manages UI state and business logic for related screens.
 L72: fun canSendToChat(chatId: String): Flow<Boolean> { Function `canSendToChat` returns observable/Flow data.
 L95: fun requestAccess(collectionId: String) { Function `requestAccess` performs a specific operation used by the surrounding feature.
 L107: fun grantAccess(collectionId: String, requesterId: String) { Function `grantAccess` performs a specific operation used by the surrounding feature.
 L137: fun toggleLibraryMode(enabled: Boolean) { Function `toggleLibraryMode` performs a specific operation used by the surrounding feature.
 L176: fun toggleChatSelection(chatId: String) { Function `toggleChatSelection` performs a specific operation used by the surrounding feature.
 L188: fun clearSelection() { Function `clearSelection` performs a specific operation used by the surrounding feature.
 L193: fun deleteSelectedChats() { Function `deleteSelectedChats` Deletes a resource.
 L348: fun syncChatsFromRemote() { Function `syncChatsFromRemote` performs a specific operation used by the surrounding feature.
 L361: fun setChatId(chatId: String) { Function `setChatId` Sets or updates a value.

app/src/main/java/com/algorithmx/q_base/ui/chat/ContactSelector.kt

```
L38: fun ContactSelector(    Function `ContactSelector` performs a specific operation used by
the surrounding feature.
L301: fun UserItem(    Function `UserItem` performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModelAdminExtensions.kt

```
L9: fun ChatViewModel.addParticipant(chatId: String, userId: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L48: fun ChatViewModel.removeParticipant(chatId: String, userId: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L86: fun ChatViewModel.promoteParticipantToAdmin(chatId: String, userId: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L109: fun ChatViewModel.demoteAdmin(chatId: String, userId: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L136: fun ChatViewModel.leaveGroup(chatId: String) {    Function `ChatViewModel` performs a
specific operation used by the surrounding feature.
L156: fun ChatViewModel.reportGroup(chatId: String, reason: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L170: fun ChatViewModel.reportUser(userId: String, reason: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L183: fun ChatViewModel.reportMessage(message: MessageEntity, reason: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L194: fun ChatViewModel.toggleMute(chatId: String, isMuted: Boolean) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L203: fun ChatViewModel.toggleBlock(chatId: String, isBlocked: Boolean) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L212: fun ChatViewModel.deleteChat(chatId: String) {    Function `ChatViewModel` performs a
specific operation used by the surrounding feature.
L216: fun ChatViewModel.clearChatMessages(chatId: String) {    Function `ChatViewModel`
performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ChatViewModelMessageExtensions.kt

```
L9: fun ChatViewModel.startNewChat(userId: String, userName: String) {    Function
`ChatViewModel` performs a specific operation used by the surrounding feature.
L54: fun ChatViewModel.startNewGroup(participantIds: List<String>, groupName: String) {
Function `ChatViewModel` performs a specific operation used by the surrounding feature.
L77: fun ChatViewModel.startAiChat() {    Function `ChatViewModel` performs a specific
operation used by the surrounding feature.
L81: fun ChatViewModel.sendMessage(chatId: String, text: String, type: String = "TEXT",
senderId: String = currentUserId) {    Function `ChatViewModel` performs a specific operation
used by the surrounding feature.
```

```
L130: private fun ChatViewModel.handleAiChatResponse(chatId: String, userMessage: String) {
Function `ChatViewModel` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/ContactSelectorView Model.kt

```
L13: data class ContactSelectorState(    Data model (`ContactSelectorState`) holds structured
data used across the app.
L21: class ContactSelectorViewModel @Inject constructor(    ViewModel
(`ContactSelectorViewModel`) manages UI state and business logic for related screens.
L33: private fun loadLocalContacts() {    Function `loadLocalContacts` Loads data from
storage or remote.
L41: fun searchByFriendCode(code: String, excludedUserId: String? = null) {    Function
`searchByFriendCode` performs a specific operation used by the surrounding feature.
L93: fun clearSearchResult() {    Function `clearSearchResult` performs a specific operation
used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatItem.kt

```
L24: fun AnimatedChatItem(    Function `AnimatedChatItem` performs a specific operation used
by the surrounding feature.
L49: fun ChatItem(    Function `ChatItem` performs a specific operation used by the
surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/MessageBubble.kt

```
L43: fun AnimatedMessageItem(    Function `AnimatedMessageItem` performs a specific operation
used by the surrounding feature.
L82: fun MessageBubble(    Function `MessageBubble` performs a specific operation used by the
surrounding feature.
L177: private fun AIHeader(isAiLoading: Boolean) {    Function `AIHeader` performs a specific
operation used by the surrounding feature.
L210: private fun SenderAvatar(avatarUrl: String?, onClick: () -> Unit) {    Function
`SenderAvatar` performs a specific operation used by the surrounding feature.
L240: private fun SenderNameLabel(name: String, onClick: () -> Unit) {    Function
`SenderNameLabel` performs a specific operation used by the surrounding feature.
L253: private fun MessageContent(    Function `MessageContent` performs a specific operation
used by the surrounding feature.
L324: fun MessageBubblePreview() {    Function `MessageBubblePreview` performs a specific
operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/EmptyConnectView.kt

```
L15: fun EmptyConnectView(modifier: Modifier = Modifier) {    Function `EmptyConnectView`
performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatDetailDialogs.kt

```
L23: fun SessionPickerSheet(    Function `SessionPickerSheet`    performs a specific operation
used by the surrounding feature.
L85: fun CollectionPickerSheet(    Function `CollectionPickerSheet`    performs a specific
operation used by the surrounding feature.
L152: fun ChatDetailConfirmDialogs(    Function `ChatDetailConfirmDialogs`    performs a
specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/SharedLibraryView.kt

```
L27: fun SharedLibraryView(    Function `SharedLibraryView`    performs a specific operation
used by the surrounding feature.
L94: fun CollectionsTabContent(    Function `CollectionsTabContent`    performs a specific
operation used by the surrounding feature.
L151: fun SessionsTabContent(    Function `SessionsTabContent`    performs a specific operation
used by the surrounding feature.
L183: fun LibraryEmptyState(message: String) {    Function `LibraryEmptyState`    performs a
specific operation used by the surrounding feature.
L199: fun LibraryHeader(title: String, description: String) {    Function `LibraryHeader`
performs a specific operation used by the surrounding feature.
L207: fun SharedSessionCard(title: String, timestamp: Long, onJoin: () -> Unit) {    Function
`SharedSessionCard`    performs a specific operation used by the surrounding feature.
L231: fun PendingRequestsSection(accessRequests: List<Map<String, Any>>, onGrantAccess:
(String, String) -> Unit) {    Function `PendingRequestsSection`    performs a specific
operation used by the surrounding feature.
L245: fun SharedCollectionCard(    Function `SharedCollectionCard`    performs a specific
operation used by the surrounding feature.
L375: fun AccessRequestItem(    Function `AccessRequestItem`    performs a specific operation
used by the surrounding feature.
L412: fun SharedLibraryViewPreview() {    Function `SharedLibraryViewPreview`    performs a
specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatDetailDialogs.kt

ailHelpers.kt

```
L9: fun accessStateLabel(state: AppAccessState): String = when (state) {    Function
`accessStateLabel` performs a specific operation used by the surrounding feature.
L17: fun formatDateRelatively(timestamp: Long): String {    Function `formatDateRelatively`
performs a specific operation used by the surrounding feature.
L28: private fun isSameDay(cal1: Calendar, cal2: Calendar): Boolean {    Function `isSameDay`
performs a specific operation used by the surrounding feature.
L33: private fun isYesterday(now: Calendar, date: Calendar): Boolean {    Function
`isYesterday` performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/GuestConnectView.kt

```
L17: fun GuestConnectView(modifier: Modifier = Modifier) {    Function `GuestConnectView`
performs a specific operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/ChatDetailComponents.kt

```
L30: fun DateHeader(date: String) {    Function `DateHeader` performs a specific operation
used by the surrounding feature.
L53: fun SystemMessageItem(text: String) {    Function `SystemMessageItem` performs a
specific operation used by the surrounding feature.
L76: fun ChatDetailTopBar(    Function `ChatDetailTopBar` performs a specific operation used
by the surrounding feature.
L213: fun ChatDetailBottomBar(    Function `ChatDetailBottomBar` performs a specific
operation used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/chat/components/SpecialBubbleContents.kt

```
L23: fun CollectionBubbleContent(    Function `CollectionBubbleContent` performs a specific
operation used by the surrounding feature.
L64: fun SessionBubbleContent(payload: String, onJoin: (String) -> Unit, isMine: Boolean) {
Function `SessionBubbleContent` performs a specific operation used by the surrounding
feature.
L94: fun FileTransferBubbleContent(    Function `FileTransferBubbleContent` performs a
specific operation used by the surrounding feature.
L144: fun DecryptionErrorContent(status: String, isMine: Boolean, onDeleteChat: () -> Unit) {
Function `DecryptionErrorContent` performs a specific operation used by the surrounding
```

feature.

L183: fun MessageTimestampAndStatus(timeString: String, isMine: Boolean, status: String) {
Function `MessageTimestampAndStatus` performs a specific operation used by the surrounding
feature.

app/src/main/java/com/algorithmx/q_base/ui/auth/AuthViewModel.kt

L15: data class AuthState(Data model (`AuthState`) holds structured data used across the
app.
L24: class AuthViewModel @Inject constructor(ViewModel (`AuthViewModel`) manages UI state
and business logic for related screens.
L32: fun signIn(email: String, pass: String) { Function `signIn` Performs user sign-in.
L54: fun signUp(email: String, pass: String, username: String, photoUrl: String? = null) {
Function `signUp` Performs user sign-up.
L76: fun signInWithGoogle(activity: androidx.activity.ComponentActivity) { Function
`signInWithGoogle` Performs user sign-in.
L93: fun onGoogleSignInSuccess(user: AppwriteUser) { Function `onGoogleSignInSuccess`
performs a specific operation used by the surrounding feature.
L105: fun clearError() { Function `clearError` performs a specific operation used by the
surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/auth/SignupScreen.kt

L38: fun SignupScreen(Function `SignupScreen` performs a specific operation used by the
surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/auth/LoginScreen.kt

L35: fun LoginScreen(Function `LoginScreen` performs a specific operation used by the
surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/ai/AiGenerationScreen.kt

L20: fun AiGenerationScreen(Function `AiGenerationScreen` performs a specific operation
used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/ai/AiViewModel.kt

L16: sealed class AiUiState { Sealed class (`AiUiState`) represents a closed hierarchy of
types.

```

L17: object Idle : AiUiState() Singleton/object (`Idle`) holds shared state or DI
bindings.
L18: object Loading : AiUiState() Singleton/object (`Loading`) holds shared state or DI
bindings.
L19: data class Success(val message: String) : AiUiState() Data model (`Success`) holds
structured data used across the app.
L20: data class Error(val message: String) : AiUiState() Data model (`Error`) holds
structured data used across the app.
L24: class AiViewModel @Inject constructor( ViewModel (`AiViewModel`) manages UI state and
business logic for related screens.
L37: fun generateCollection( Function `generateCollection` Generates content (often
AI-generated).
L72: fun promoteResponse(targetCollectionId: String? = null, targetCollectionName: String? =
null) { Function `promoteResponse` performs a specific operation used by the surrounding
feature.
L86: fun resetState() { Function `resetState` performs a specific operation used by the
surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/home/HomeScreen.kt

```

L40: fun HomeScreen( Function `HomeScreen` performs a specific operation used by the
surrounding feature.
L195: fun QuickActionCard( Function `QuickActionCard` performs a specific operation used
by the surrounding feature.
L230: fun HomeCategoryCard( Function `HomeCategoryCard` performs a specific operation used
by the surrounding feature.
L303: fun AnimatedHomeItem( Function `AnimatedHomeItem` performs a specific operation used
by the surrounding feature.
L324: fun PinnedQuestionItem( Function `PinnedQuestionItem` performs a specific operation
used by the surrounding feature.
L371: fun EmptyHomeView(onNavigate: () -> Unit) { Function `EmptyHomeView` performs a
specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/home/HomeViewModel.kt

```

L20: class HomeViewModel @Inject constructor( ViewModel (`HomeViewModel`) manages UI state
and business logic for related screens.

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Extraction WizardSecondScreen.kt

```

L24: fun ExtractionWizardSecondScreen( Function `ExtractionWizardSecondScreen` performs a
specific operation used by the surrounding feature.

```


app/src/main/java/com/algorithmx/q_base/ui/content_import/QuestionEditorScreen.kt

L24: fun QuestionEditorScreen(Function `QuestionEditorScreen` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/content_import/Common WizardThirdScreen.kt

L26: fun WaitingView(message: String) { Function `WaitingView` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/content_import/ManualBuilderViewModel.kt

L18: class ManualBuilderViewModel @Inject constructor(ViewModel (`ManualBuilderViewModel`) manages UI state and business logic for related screens.
 L31: fun initialize(targetId: String?, name: String? = null) { Function `initialize` Initialisation routine.
 L61: private suspend fun createNewCollectionAndSet(name: String? = null) { Function `createNewCollectionAndSet` Creates a resource or document.
 L77: private suspend fun createNewSet(collectionId: String, title: String) { Function `createNewSet` Creates a resource or document.
 L90: private fun observeQuestions(setId: String) { Function `observeQuestions` Observes changes and returns a Flow/Stream.
 L96: fun getTargetSetId(): String? = _targetSetId.value Function `getTargetSetId` Returns or fetches data.
 L98: private fun getCurrentDate(): String { Function `getCurrentDate` Returns or fetches data.

app/src/main/java/com/algorithmx/q_base/ui/content_import/Common WizardSecondScreen.kt

L17: fun ImportConfigView(onProceed: (List<String>, String) -> Unit) { Function `ImportConfigView` performs a specific operation used by the surrounding feature.
 L82: fun GenerateConfigView(onProceed: (ExtractionConfigData) -> Unit) { Function `GenerateConfigView` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/content_import/ImportView

wModel.kt

```

L23: data class ExtractionConfigData(    Data model (`ExtractionConfigData`) holds structured
data used across the app.
L43: sealed class ImportStep {    Sealed class (`ImportStep`) represents a closed hierarchy
of types.
L44: data object NameAndDestination : ImportStep()    Singleton/object (`NameAndDestination`)
holds shared state or DI bindings.
L45: data object ChooseMethod : ImportStep()    Singleton/object (`ChooseMethod`) holds
shared state or DI bindings.
L46: data object MediaInput : ImportStep()    Singleton/object (`MediaInput`) holds shared
state or DI bindings.
L47: data class Configure(val mode: String) : ImportStep() // "IMPORT" or "GENERATE"    Data
model (`Configure`) holds structured data used across the app.
L48: data class Processing(val message: String = "AI is structuring your questions...") :
ImportStep()    Data model (`Processing`) holds structured data used across the app.
L49: data class Review(val questionCount: Int, val responseId: String) : ImportStep()    Data
model (`Review`) holds structured data used across the app.
L50: data class Error(val message: String) : ImportStep()    Data model (`Error`) holds
structured data used across the app.
L53: data object ExtractionIngest : ImportStep()    Singleton/object (`ExtractionIngest`)
holds shared state or DI bindings.
L54: data class ExtractionOverview(val responseId: String, val response:
com.algorithmx.q_base.core_ai.brain.models.AiCollectionResponse) : ImportStep()    Data model
(`ExtractionOverview`) holds structured data used across the app.
L57: data class Extracting(val source: String) : ImportStep()    Data model (`Extracting`)
holds structured data used across the app.
L58: data class Editing(val extractedText: String) : ImportStep()    Data model (`Editing`)
holds structured data used across the app.
L59: data class Config(val extractedText: String, val targetId: String? = null) :
ImportStep()    Data model (`Config`) holds structured data used across the app.
L60: data class Preview(val responseId: String, val response:
com.algorithmx.q_base.core_ai.brain.models.AiCollectionResponse) : ImportStep()    Data model
(`Preview`) holds structured data used across the app.
L61: data class Complete(val message: String) : ImportStep()    Data model (`Complete`) holds
structured data used across the app.
L65: class ImportViewModel @Inject constructor(    ViewModel (`ImportViewModel`) manages UI
state and business logic for related screens.
L116: fun togglePaperType(type: String) {    Function `togglePaperType` performs a specific
operation used by the surrounding feature.
L142: fun setInitialSource(source: String?, targetId: String? = null) {    Function
`setInitialSource` Sets or updates a value.
L153: private fun loadCollections() {    Function `loadCollections` Loads data from storage
or remote.
L161: fun navigateTo(step: ImportStep) {    Function `navigateTo` performs a specific
operation used by the surrounding feature.
L171: fun selectCategory(categoryId: String?) {    Function `selectCategory` performs a
specific operation used by the surrounding feature.
L175: fun updateNewCollectionName(name: String) {    Function `updateNewCollectionName`
performs a specific operation used by the surrounding feature.

```

```

L179: fun updateNewCollectionDescription(desc: String) {    Function
`updateNewCollectionDescription` performs a specific operation used by the surrounding
feature.
L183: fun updateCustomInstructions(instructions: String) {    Function
`updateCustomInstructions` performs a specific operation used by the surrounding feature.
L187: fun selectMethod(method: String) {    Function `selectMethod` performs a specific
operation used by the surrounding feature.
L191: fun onImagePicked(uri: Uri) {    Function `onImagePicked` performs a specific operation
used by the surrounding feature.
L199: fun onPdfPicked(uri: Uri) {    Function `onPdfPicked` performs a specific operation
used by the surrounding feature.
L207: fun onRawTextUpdated(text: String) {    Function `onRawTextUpdated` performs a specific
operation used by the surrounding feature.
L211: private fun handleExtractionResult(result: Result<String>) {    Function
`handleExtractionResult` performs a specific operation used by the surrounding feature.
L220: fun startDirectImport(types: List<String>, instructions: String) {    Function
`startDirectImport` performs a specific operation used by the surrounding feature.
L238: fun startAiGeneration(config: ExtractionConfigData) {    Function `startAiGeneration`
performs a specific operation used by the surrounding feature.
L256: private fun handleGenerationResult(result: Result<String>) {    Function
`handleGenerationResult` performs a specific operation used by the surrounding feature.
L274: fun promoteResponse(responseId: String, customName: String? = null, onFinish:
(String, String?) -> Unit) {    Function `promoteResponse` performs a specific operation used
by the surrounding feature.
L295: fun addPdf(uri: Uri) {    Function `addPdf` performs a specific operation used by the
surrounding feature.
L321: fun addOcr(uri: Uri) {    Function `addOcr` performs a specific operation used by the
surrounding feature.
L346: fun addClipboard(text: String) {    Function `addClipboard` performs a specific
operation used by the surrounding feature.
L359: fun removeDoc(id: String) {    Function `removeDoc` performs a specific operation used
by the surrounding feature.
L364: fun startPaperExtraction() {    Function `startPaperExtraction` performs a specific
operation used by the surrounding feature.
L401: fun handleRetry() {    Function `handleRetry` performs a specific operation used by the
surrounding feature.
L409: fun reset() {    Function `reset` performs a specific operation used by the surrounding
feature.
L435: fun currentStepNumber(): Int = when (val s = _uiState.value) {    Function
`currentStepNumber` performs a specific operation used by the surrounding feature.
L453: fun totalSteps(): Int = 5    Function `totalSteps` performs a specific operation used
by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Extraction WizardThirdScreen.kt

```

L21: fun ExtractionWizardThirdScreen(    Function `ExtractionWizardThirdScreen` performs a
specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ManualBuilderScreen.kt

```
L29: fun ManualBuilderScreen(    Function `ManualBuilderScreen` performs a specific operation
used by the surrounding feature.
L131: fun ManualQuestionItem(    Function `ManualQuestionItem` performs a specific operation
used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ImportWizardScreen.kt

```
L20: fun ImportWizardScreen(    Function `ImportWizardScreen` performs a specific operation
used by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/ExtractionWizardFirstScreen.kt

```
L22: data class ExtractedDocumentCard(    Data model (`ExtractedDocumentCard`) holds
structured data used across the app.
L31: fun ExtractionWizardFirstScreen(    Function `ExtractionWizardFirstScreen` performs a
specific operation used by the surrounding feature.
L243: fun ExtractedDocItem(    Function `ExtractedDocItem` performs a specific operation used
by the surrounding feature.
```

app/src/main/java/com/algorithmx/q_base/ui/content_import/QuestionEditorViewModel.kt

```
L15: data class QuestionEditorState(    Data model (`QuestionEditorState`) holds structured
data used across the app.
L29: class QuestionEditorViewModel @Inject constructor(    ViewModel
(`QuestionEditorViewModel`) manages UI state and business logic for related screens.
L41: fun init(questionId: String?, setId: String) {    Function `init` Initialisation
routine.
L70: fun updateStem(stem: String) {    Function `updateStem` performs a specific operation
used by the surrounding feature.
L74: fun updateOption(letter: String, text: String) {    Function `updateOption` performs a
specific operation used by the surrounding feature.
L81: fun updateCorrectAnswer(answer: String) {    Function `updateCorrectAnswer` performs a
specific operation used by the surrounding feature.
L85: fun updateExplanation(explanation: String) {    Function `updateExplanation` performs a
specific operation used by the surrounding feature.
```

```

L89: fun updateReferences(refs: String) {    Function `updateReferences`  performs a specific
operation used by the surrounding feature.
L93: fun getAiAssist() {    Function `getAiAssist`  Returns or fetches data.
L107: fun generateAiExplanation() {    Function `generateAiExplanation`  Generates content
(often AI-generated).
L129: fun applyAiExplanation() {    Function `applyAiExplanation`  performs a specific
operation used by the surrounding feature.
L137: fun discardAiExplanation() {    Function `discardAiExplanation`  performs a specific
operation used by the surrounding feature.
L141: fun clearAiSuggestions() {    Function `clearAiSuggestions`  performs a specific
operation used by the surrounding feature.
L145: fun saveQuestion() {    Function `saveQuestion`  Saves data to storage or remote.

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Common WizardFourthScreen.kt

```

L26: fun ReviewView(    Function `ReviewView`  performs a specific operation used by the
surrounding feature.
L227: fun ErrorView(message: String, onRetry: () -> Unit) {    Function `ErrorView`  performs
a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Extraction WizardFourthScreen.kt

```

L27: fun ExtractionWizardFourthScreen(    Function `ExtractionWizardFourthScreen`  performs a
specific operation used by the surrounding feature.
L281: fun CountBadge(label: String, count: Int, color: Color, modifier: Modifier = Modifier)
{    Function `CountBadge`  performs a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/content_import/Common WizardFirstScreen.kt

```

L26: fun CommonWizardFirstScreen(    Function `CommonWizardFirstScreen`  performs a specific
operation used by the surrounding feature.
L214: fun SmallSourceButton(icon: ImageVector, title: String, color: Color, modifier:
Modifier = Modifier, onClick: () -> Unit) {    Function `SmallSourceButton`  performs a
specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/ui/components/question/Que stionHeader.kt

L35: fun QuestionHeader(Function `QuestionHeader` performs a specific operation used by the surrounding feature.

L246: fun QuestionHeaderPreview() { Function `QuestionHeaderPreview` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/question/QuestionViewer.kt

L20: fun QuestionViewer(Function `QuestionViewer` performs a specific operation used by the surrounding feature.

L151: fun QuestionViewerPreview() { Function `QuestionViewerPreview` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/question/TrueFalseToggle.kt

L15: fun TrueFalseToggle(Function `TrueFalseToggle` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/question/OptionsList.kt

L29: fun OptionsList(Function `OptionsList` performs a specific operation used by the surrounding feature.

L341: fun OptionsListPreview() { Function `OptionsListPreview` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/ReportDialog.kt

L13: fun ReportDialog(Function `ReportDialog` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/ProfileIconButton.kt

L24: fun ProfileIconButton(Function `ProfileIconButton` performs a specific operation

used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/AiConfigSelector.kt

L16: fun AiConfigSelector(Function `AiConfigSelector` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/ui/components/reusable/CommonComponents.kt

L32: fun UnifiedTopAppBar(Function `UnifiedTopAppBar` performs a specific operation used by the surrounding feature.
 L125: private fun AppAccessStateBadge(appAccessState: AppAccessState) { Function `AppAccessStateBadge` performs a specific operation used by the surrounding feature.
 L150: fun SessionCard(Function `SessionCard` performs a specific operation used by the surrounding feature.
 L196: fun SessionListItem(Function `SessionListItem` performs a specific operation used by the surrounding feature.
 L230: fun SectionHeader(Function `SectionHeader` performs a specific operation used by the surrounding feature.
 L272: fun SessionCardPreview() { Function `SessionCardPreview` performs a specific operation used by the surrounding feature.
 L289: fun SessionListItemPreview() { Function `SessionListItemPreview` performs a specific operation used by the surrounding feature.
 L308: fun SectionHeaderPreview() { Function `SectionHeaderPreview` performs a specific operation used by the surrounding feature.

app/src/main/java/com/algorithmx/q_base/core_ai/brain/BrainConfigProvider.kt

L5: interface BrainConfigProvider { Interface (`BrainConfigProvider`) contract implemented by components.
 L6: suspend fun getApiKey(provider: BrainProvider): String Function `getApiKey` Returns or fetches data.

app/src/main/java/com/algorithmx/q_base/core_ai/brain/BrainDataStoreManager.kt

```

L24: class BrainDataStoreManager @Inject constructor(    Manager (`BrainDataStoreManager`)
orchestration/utility for managing resources or behaviors.
L29: private object PreferencesKeys {    Singleton/object (`PreferencesKeys`) holds shared
state or DI bindings.
L73: suspend fun markSeedAsApplied() {    Suspend function `markSeedAsApplied`
coroutine-friendly async operation.
L79: suspend fun resetSeedFlag() {    Suspend function `resetSeedFlag` coroutine-friendly
async operation.
L85: suspend fun saveEngineConfiguration(    Function `saveEngineConfiguration` Saves data to
storage or remote.
L99: suspend fun incrementUsageStats(tokens: Int) {    Suspend function `incrementUsageStats`
coroutine-friendly async operation.
L108: suspend fun saveThemeMode(mode: String) {    Function `saveThemeMode` Saves data to
storage or remote.
L114: suspend fun saveNotificationsEnabled(enabled: Boolean) {    Function
`saveNotificationsEnabled` Saves data to storage or remote.
L120: suspend fun saveTaskConfig(task: BrainTask, config: TaskConfig) {    Function
`saveTaskConfig` Saves data to storage or remote.
L135: suspend fun setMasterAiFreeze(freeze: Boolean) {    Function `setMasterAiFreeze` Sets
or updates a value.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/AiUsageLogger.kt

```

L6: interface AiUsageLogger {    Interface (`AiUsageLogger`) contract implemented by
components.
L7: suspend fun logUsage(    Suspend function `logUsage` coroutine-friendly async operation.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/CommonAiService.kt

```

L13: class CommonAiService @Inject constructor(    Service (`CommonAiService`) provides
specific operations (often background tasks).
L22: suspend fun generateNoteStructure(    Function `generateNoteStructure` Generates content
(often AI-generated).
L58: suspend fun generateBlocksForTopic(    Function `generateBlocksForTopic` Generates
content (often AI-generated).
L73: private fun constructGenerationPrompt(    Function `constructGenerationPrompt` performs
a specific operation used by the surrounding feature.
L104: private fun extractJsonFromResponse(response: String): String {    Function
`extractJsonFromResponse` performs a specific operation used by the surrounding feature.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/AiBrainManage

r.kt

```

L24: class AiBrainManager @Inject constructor(    Manager (`AiBrainManager`)
orchestration/utility for managing resources or behaviors.
L40: private suspend fun buildBrain(modelName: String): AiBrain? {    Function `buildBrain`
Constructs or prepares an object.
L67: suspend fun askBrain(task: BrainTask, prompt: String): Result<String> {    Suspend
function `askBrain`    coroutine-friendly async operation.
L131: suspend fun streamFromBrain(task: BrainTask, prompt: String): Flow<String> {    Function
`streamFromBrain`    returns observable/Flow data.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/BrainTask.kt

```

L3: enum class BrainTask(val displayName: String) {    Enumeration (`BrainTask`)    defines a
set of named constants.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/AiResponseModels.kt

```

L6: data class AiQuestion(    Data model (`AiQuestion`)    holds structured data used across the
app.
L15: data class AiOption(    Data model (`AiOption`)    holds structured data used across the
app.
L22: data class AiAnswer(    Data model (`AiAnswer`)    holds structured data used across the
app.
L29: data class AiCollectionResponse(    Data model (`AiCollectionResponse`)    holds structured
data used across the app.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/AiModels.kt

```

L6: enum class BlockType {    Enumeration (`BlockType`)    defines a set of named constants.
L16: data class AiGeneratedBlock(    Data model (`AiGeneratedBlock`)    holds structured data
used across the app.
L22: data class AiGeneratedTab(    Data model (`AiGeneratedTab`)    holds structured data used
across the app.
L27: data class NoteContext(    Data model (`NoteContext`)    holds structured data used across
the app.

```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/models/BrainModels.kt

```
L10: data class BrainConfig(    Data model (`BrainConfig`)    holds structured data used across the app.  
L17: data class TaskConfig(    Data model (`TaskConfig`)    holds structured data used across the app.  
L24: data class StoredBrainConfig(    Data model (`StoredBrainConfig`)    holds structured data used across the app.
```

app/src/main/java/com/algorithmx/q_base/core_ai/brain/di/AiCoreModule.kt

```
L16: object AiCoreModule {    Singleton/object (`AiCoreModule`)    holds shared state or DI bindings.  
L20: fun provideAiBrainManager(    Function `provideAiBrainManager`    DI provider method.  
L30: fun provideCommonAiService(aiBrainManager: AiBrainManager): CommonAiService {    Function `provideCommonAiService`    DI provider method.
```