

**Московский государственный технический
университет им. Н. Э. Баумана
Факультет «Информатика и системы управления»**

Кафедра «Системы обработки информации и управления»
Курс «Технологии машинного обучения»

Отчет по лабораторной работе №4
Подготовка обучающей и тестовой выборки, кросс-валидация и подбор
гиперпараметров на примере метода ближайших соседей.

Группа: РТ5-61

Студент: Савушкин Д. А.

Преподаватель: Гапанюк Ю.Е.

Москва, 2020 г.

Цель лабораторной работы: изучение сложных способов подготовки выборки и подбора гиперпараметров на примере метода ближайших соседей.

Задание:

1. Выберите набор данных (датасет) для решения задачи классификации или регрессии.
2. С использованием метода `train_test_split` разделите выборку на обучающую и тестовую.
3. Обучите модель ближайших соседей для произвольно заданного гиперпараметра `K`. Оцените качество модели с помощью подходящих для задачи метрик.
4. Постройте модель и оцените качество модели с использованием кросс-валидации.
5. Произведите подбор гиперпараметра `K` с использованием `GridSearchCV` и кросс-валидации.

Текст программы и экранные формы с примерами выполнения программы:

```
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
from sklearn.impute import SimpleImputer
import pandas_profiling as pp
import warnings
warnings.simplefilter("ignore")

data = pd.read_csv('datasets_494724_1288143_COVID19_line_list_data.csv')
data.head()
```

case_in_country	reporting date	Unnamed: 3	summary	location	country	gender	age	symptom_onset	If_onset_approximated	hosp_visit_date	exposure_start	exposure_end	visiting Wuhan	from Wuhan	death	recovered	symptom	source		
NaN	1/20/2020	NaN	First confirmed imported COVID-19 pneumonia pa...	Shenzhen, Guangdong	China	male	66.0	01/03/20		0.0	01/11/20	12/29/2019	01/04/20	1	0.0	0	0	NaN	Shenzhen Municipal Health Commission	http://wjw.sz.gov.cn
NaN	1/20/2020	NaN	First confirmed imported COVID-19 pneumonia pa...	Shanghai	China	female	56.0	1/15/2020		0.0	1/15/2020	NaN	01/12/20	0	1.0	0	0	NaN	Official Weibo of Shanghai Municipal Health Co...	https://www.weibo.com
NaN	1/21/2020	NaN	First confirmed imported cases in Zhejiang pa...	Zhejiang	China	male	46.0	01/04/20		0.0	1/17/2020	NaN	01/03/20	0	1.0	0	0	NaN	Health Commission of Zhejiang Province	http://www.zjwj.gov.cn
NaN	1/21/2020	NaN	new confirmed imported COVID-19 pneumonia in T...	Tianjin	China	female	60.0	NaN		NaN	1/19/2020	NaN	NaN	1	0.0	0	0	NaN	人民日报官方微博	https://m.weibo.cn

```
# проверим есть ли пропущенные значения
data.isnull().sum()

id
case_in_country    197
reporting date      1
Unnamed: 3         1085
summary            5
location           0
country            0
gender            183
age               242
symptom_onset      522
If_onset_approximated 525
hosp_visit_date    578
exposure_start     957
exposure_end       744
visiting Wuhan     0
from Wuhan         4
death              0
recovered          0
symptom            815
source             0
link               0
Unnamed: 21        1085
Unnamed: 22        1085
Unnamed: 23        1085
Unnamed: 24        1085
Unnamed: 25        1085
Unnamed: 26        1085
dtype: int64

# Удаление колонок, содержащих пустые значения
data_new_1 = data.drop(columns=['Unnamed: 21', 'link', 'source', 'summary', 'reporting date', 'Unnamed: 22', 'Unnamed: 23', 'Unnamed: 24', 'Unnamed: 25', 'symptom', 'Unnamed: 26', 'Unnamed: 3', 'symptom_onset', 'If_onset_approximated', 'hosp_visit_date', 'exposure_start', 'exposure_end', 'visiting Wuhan', 'from Wuhan', 'death', 'recovered'])
data_new_1.shape
((1085, 27), (1085, 10))

data_new_1.head()
```

id	case_in_country	location	country	gender	age	visiting Wuhan	from Wuhan	death	recovered
0	1	NaN	Shenzhen, Guangdong	China	male	66.0	1	0.0	0
1	2	NaN	Shanghai	China	female	56.0	0	1.0	0
9	1	NaN	Zhejiang	China	male	46.0	0	1.0	0

```
[ ] data_new_1.isnull().sum()
```

```
id          0
case_in_country  197
location     0
country      0
gender      183
age         242
visiting Wuhan  0
from Wuhan    4
death        0
recovered    0
dtype: int64
```

```
[ ] # Удаление строки, содержащих пустые значения
data_new_2 = data_new_1.dropna(axis=0,how='any',subset=['case_in_country','gender', 'age'])
(data_new_1.shape, data_new_2.shape)
```

```
((1085, 10), (635, 10))
```

```
[ ] data_new_2.head()
```

	id	case_in_country	location	country	gender	age	visiting Wuhan	from Wuhan	death	recovered
197	198	1.0	Bordeaux	France	male	48.0	1	0.0	0	0
198	199	2.0	Paris	France	male	31.0	0	1.0	0	02/12/20
199	200	3.0	Paris	France	female	30.0	0	1.0	0	02/12/20
200	201	4.0	Paris	France	male	80.0	0	1.0	2/14/2020	0
209	210	13.0	Paris	France	female	33.0	0	0.0	0	0

```
[ ] data_new_2.shape[0]
```

```
635
```

```
[ ] data_new_2['death'] = data_new_2['death'].apply(lambda x: 0 if x=='0' else 1)
```

```
[ ] data_new_2['recovered'] = data_new_2['recovered'].apply(lambda x: 0 if x=='0' else 1)
```

data_new_2

	id	case_in_country	location	country	gender	age	visiting Wuhan	from Wuhan	death	recovered
197	198	1.0	Bordeaux	France	male	48.0	1	0.0	0	0
198	199	2.0	Paris	France	male	31.0	0	1.0	0	1
199	200	3.0	Paris	France	female	30.0	0	1.0	0	1
200	201	4.0	Paris	France	male	80.0	0	1.0	1	0
209	210	13.0	Paris	France	female	33.0	0	0.0	0	0
...
1027	1028	32.0	Andalusia	Spain	male	58.0	0	0.0	0	0
1029	1030	34.0	Zaragoza	Spain	female	27.0	0	0.0	0	0
1030	1031	1.0	Jonkoping	Sweden	female	25.0	1	0.0	0	0
1052	1053	1.0	Lebanon	Lebanon	female	45.0	0	0.0	0	0
1084	1085	1.0	Bern	Switzerland	male	70.0	0	0.0	0	0

635 rows x 10 columns

```
[ ] data = pd.get_dummies(data_new_2)
data = data.drop(columns=['id', 'case_in_country'])
(data.shape, data.shape)
```

((635, 118), (635, 118))

```
[ ] from sklearn.model_selection import train_test_split
```

```
[ ] y = data.death
data.drop('death', axis=1, inplace=True)
X_cov, X_test, y_cov, y_test = train_test_split(data, y, test_size=0.2)
print(X_cov.shape, y_cov.shape)
print(X_test.shape, y_test.shape)
```

(508, 117) (508,)
(127, 117) (127,)

Обучение модели

```
[ ] from sklearn.neighbors import KNeighborsClassifier
```

```
[ ] KNeighborsClassifierObj = KNeighborsClassifier(n_neighbors=10)
```

```
[ ] KNeighborsClassifierObj.fit(X_cov, y_cov)
```

```
⦿ KNeighborsClassifier(algorithm='auto', leaf_size=30, metric='minkowski',  
                      metric_params=None, n_jobs=None, n_neighbors=10, p=2,  
                      weights='uniform')
```

```
[ ] y_predicted = KNeighborsClassifierObj.predict(X_test)
```

Метрика качества

```
[ ] from sklearn.metrics import accuracy_score, balanced_accuracy_score, precision_score, f1_score, classification_report
```

```
[ ] accuracy_score(y_test, y_predicted)
```

```
⦿ 0.9606299212598425
```

```
[ ] precision_score(y_test, y_predicted)
```

```
⦿ 0.0
```

Смертность не зависит от других параметров.

```
[ ] classification_report(y_test, y_predicted, output_dict = True)
```

```
{'0': {'f1-score': 0.9799196787148594,  
      'precision': 0.9606299212598425,  
      'recall': 1.0,  
      'support': 122},  
 '1': {'f1-score': 0.0, 'precision': 0.0, 'recall': 0.0, 'support': 5},  
 'accuracy': 0.9606299212598425,  
 'macro avg': {'f1-score': 0.4899598393574297,  
               'precision': 0.48031496062992124,  
               'recall': 0.5,  
               'support': 127},  
 'weighted avg': {'f1-score': 0.9413401638048255,  
                  'precision': 0.9228098456196913,  
                  'recall': 0.9606299212598425,  
                  'support': 127}}
```

Кросс-валидация

```
[ ] from sklearn.model_selection import cross_val_score
```

```
[ ] scores = cross_val_score(KNeighborsClassifierObj,  
                             X_cov, y_cov, cv=3,  
                             scoring='f1_weighted')  
scores, np.mean(scores)
```

```
(array([0.95610184, 0.96463877, 0.95584342]), 0.9588613436340419)
```

Подбор гиперпараметров

```
[ ] from sklearn.model_selection import GridSearchCV
```

```
[ ] n_range = np.array(range(5,55,5))  
    tuned_parameters = [{'n_neighbors': n_range}]
```

```
[ ] clf_gs = GridSearchCV(KNeighborsClassifier(), tuned_parameters, cv=5, scoring='f1_weighted')
```

```
[ ] clf_gs.fit(X_cov, y_cov)
```

```
GridSearchCV(cv=5, error_score=nan,  
             estimator=KNeighborsClassifier(algorithm='auto', leaf_size=30,  
                                           metric='minkowski',  
                                           metric_params=None, n_jobs=None,  
                                           n_neighbors=5, p=2,  
                                           weights='uniform'),  
             iid='deprecated', n_jobs=None,  
             param_grid=[{'n_neighbors': array([ 5, 10, 15, 20, 25, 30, 35, 40, 45, 50])}],  
             pre_dispatch='2*n_jobs', refit=True, return_train_score=False,  
             scoring='f1_weighted', verbose=0)
```

```
[ ] clf_gs.best_params_
```

```
{'n_neighbors': 5}
```

```
[ ] clf_gs.best_score_
```

```
0.9588742014124028
```

```
[ ] plt.plot(n_range, clf_gs.cv_results_['mean_test_score'])
```

```
[<matplotlib.lines.Line2D at 0x7f1752b97278>]
```

