

## MagtiCom OneWay Service

v.1.1.0 05.09.2007

MagtiCom customers can send MT (mobile terminated) messages to mobile user using MagtiCom OneWay Service.

*Note: by default customers can send MT (mobile terminated) messages only to MagtiCom Subscribers. To send MT to any other operator, please contact sales department.*

This service is running on HTTP port 80.

VPN connection is required between MagtiCom host and client host.

All requests made by client must be URL-encoded.

Client can use either HTTP POST or GET in their requests.

Client can have one or more SMS short number (xxxx) or string name which will be visible in from fields of SMS.

Client will be provided by username, password, client\_id.

Also with service\_id for each short number.

### OneWay Parameters:

URL: <http://81.95.160.47/mt/sendsms?>

username – client username provided by MagtiCom

password – client password provided by MagtiCom

client\_id – unique client ID provided by MagtiCom

service\_id – unique service ID provided by MagtiCom

type – text

to – subscriber msisdn (995XXyyyyyy)

text – message text

### Return codes:

0000 - message\_id : Operation successfull. message\_id is used in message status tracking query.

0001 : Internal error

0003 : Invalid Request

0004 : Invalid query

0005 : Empty message

0006 : Prefix error

0007 : MSISDN error

## Message Status Tracking:

<http://81.95.160.47/bi/track.php?>

### Parameters:

username – client username

password – client password

client\_id – unique client ID provided by MagtiCom

service\_id – unique service ID provided by MagtiCom

message\_id – unique message id returned with mt message

successfull send

### Reply Codes:

0 - Undefined

1 - Delivered to phone

2 - Not Delivered to Phone

4 - Queued on SMSC

8 - Delivered to SMSC

16 – Not Delivered to SMSC.

Customer can check message status during next 24 hours. If after 24 hours reply will NOT be “1 - Delivered to phone”, this means that this message will be removed from queue and will not be delivered to subscriber. Customer can resend this message.

### *Example:*

*<http://81.95.160.47/mt/sendsms?>*

*username=TestUser&password=TestPassword&client\_id=999&service\_id=999&to=99599123456&text=Test*

*In case of successful operation customer will get answer:*

*0000 – 12345678*

*where 12345678 is Message ID.*

*To track status of this message customer must use following URL:*

*<http://81.95.160.47/bi/track.php?>*

*username=TestUser&password=TestPassword&client\_id=999&service\_id=999&message\_id=12345678*