



Tools Extensions Window Help

al) x: 814, y: 710

2960-24TT Switch0

PC-PT PC0

2960-24TT Switch1

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
Version ID : V02
CLEI Code Number : COM3100BRA
Hardware Board Revision Number : 0x01

Switch Ports Model SW Version SW Image
* 1 26 WS-C2960-24TT-L 15.0(2)SE4 C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnnguyen

Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up

Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#hostname lsw
lsw(config)#int vlan1
lsw(config-if)#no sh

lsw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

lsw(config-if)#ip address 192.168.0.2 255.255.255.0
lsw(config-if)#exit
lsw(config)#
```

Copy Paste

Top