


# Validation Model & Classification Analysis

Ali Ridho Barakbah

Knowledge Engineering Research Group  
Soft Computing Laboratory  
Department of Information and Computer Engineering  
Electronic Engineering Polytechnic Institute of Surabaya




# Validation Model of Classification

---

- Holdout method
- Random subsampling
- K-fold cross validation
- Leave-one-out cross validation
- Bootstrap

# Holdout Method

- Split dataset into two groups
  - Training set: used to train the classifier
  - Test set: used to estimate the error rate of the trained classifier




- The holdout method has two basic drawbacks
  - In problems where we have a sparse dataset we may not be able to afford the “luxury” of setting aside a portion of the dataset for testing
  - Since it is a single train-and-test experiment, the holdout estimate of error rate will be misleading if we happen to get an “unfortunate” split

Ricardo Gutierrez-Osuna, *Pattern Analysis*, CSE@TAMU

# Random Subsampling

- Random subsampling performs K data splits of the entire dataset
  - Each data split randomly selects a (fixed) number of examples without replacement
  - For each data split we retrain the classifier from scratch with the training examples and then estimate  $E_i$  with the test examples




- The true error estimate is obtained as the average of the separate estimates  $E_i$
- This estimate is significantly better than the holdout estimate

$$E = \frac{1}{K} \sum_{i=1}^K E_i$$

Ricardo Gutierrez-Osuna, *Pattern Analysis*, CSE@TAMU

# K-fold Cross Validation

- Create a K-fold partition of the dataset
  - For each of  $K$  experiments, use  $K - 1$  folds for training and a different fold for testing
  - This procedure is illustrated in the following figure for  $K = 4$




- K-Fold cross validation is similar to random subsampling
  - The advantage of KFCV is that all the examples in the dataset are eventually used for both training and testing
  - As before, the true error is estimated as the average error rate on test examples

$$E = \frac{1}{K} \sum_{i=1}^K E_i$$

Ricardo Gutierrez-Osuna, *Pattern Analysis*, CSE@TAMU

# Leave-one-out Cross Validation

- LOO is the degenerate case of KFCV, where  $K$  is chosen as the total number of examples
  - For a dataset with  $N$  examples, perform ?? Experiments
  - For each experiment use  $N - 1$  examples for training and the remaining example for testing



- As usual, the true error is estimated as the average error rate on test examples

$$E = \frac{1}{N} \sum_{i=1}^N E_i$$

Ricardo Gutierrez-Osuna, *Pattern Analysis*, CSE@TAMU

# How many folds are needed?

---


- With a large number of folds
  - + The bias of the true error rate estimator will be small (the estimator will be very accurate)
  - The variance of the true error rate estimator will be large
  - The computational time will be very large as well (many experiments)
- With a small number of folds
  - + The number of experiments and, therefore, computation time are reduced
  - + The variance of the estimator will be small
  - The bias of the estimator will be large (conservative or larger than the true error rate)
- In practice, the choice for K depends on the size of the dataset
  - For large datasets, even 3-fold cross validation will be quite accurate
  - For very sparse datasets, we may have to use leave-one-out in order to train on as many examples as possible
- A common choice for is  $K=10$

Ricardo Gutierrez-Osuna, *Pattern Analysis*, CSE@TAMU



# Bootstrap

- The bootstrap is a resampling technique with replacement
  - From a dataset with ?? Examples
    - Randomly select (with replacement) ?? examples and use this set for training
    - The remaining examples that were not selected for training are used for testing
    - This value is likely to change from fold to fold
  - Repeat this process for a specified number of folds (??)
  - As before, the true error is estimated as the average error rate on test data





# Performance Analysis of Classification

---

- Commonly used error rate/ratio
- Dataset → supervised
- Used to analyze precision of classification result from a classification algorithm

$$Error = \frac{missclassified}{Number\ of\ data} \times 100\%$$

# Tugas Klasifikasi dengan k-NN

---

- Case : klasifikasi bunga Iris
- Source : UCI Repository
- Number of attributes : 4
- Number of instances : 150
- Number of classes : 3
  - Iris Setosa (50 instances)
  - Iris Versicolour (50 instances)
  - Iris Virginica (50 instances)

## Bunga iris



Iris Setosa



Iris Versicolor



Iris Virginica

# Assignment

---

- Lakukan performance analysis pada data Iris dengan menggunakan validation model:
  - Holdout method
  - Random subsampling
  - K-fold cross validation
  - Leave-one-out cross validation
  - Bootstrap
- Lakukan klasifikasi masing-masing data uji coba dan hitunglah error ratio-nya.
- Hitunglah error ratio rata-rata pada semua data uji coba (dalam persen).

# Metode klasifikasi

---

- Lakukan percobaan dengan melibatkan beberapa metode klasifikasi:
  - 1-NN
  - 3-NN
  - 5-NN

# References

---

- Tom Michael, Machine Learning, McGraw-Hill publisher, 1997.
- Ali Ridho Barakbah, *Machine Learning*, Lecture Handout, Electronic Engineering Polytechnic Institute of Surabaya.
- Ricardo Gutierrez-Osuna, *Pattern Analysis*, Lecture Courses, Department of Computer Science and Engineering - Texas A&M University.
- Tan, Steinbach, Kumar, *Introduction to Data Mining*, Pearson publisher, 2005.
- UCI Repository, Iris Dataset.