

Note on binding of an association particle to semantic particles

D. Gueorguiev 11/25/21

Primitive semantic particles

Let us consider two primitive semantic particles - V_i and V_j connected through association particle (link) $A_{i,j}$.

$$V_i \text{---} A_{i,j} \text{---} V_j$$

The particles V_i and V_j are represented by their semantic signatures \mathbf{V}_i and \mathbf{V}_j . The association link $A_{i,j}$ is represented with its association matrix $\mathbf{A}_{i,j}$ and semantic significance vector $\mathbf{W}_{i,j}$.

The association matrix $\mathbf{A}_{i,j}$ captures the affinity force $F(V_i, V_j, t)$ between the particles V_i and V_j at the time t of constructing the compound structure involving those particles. Note that the magnitude of affinity force between the particles may change as their semantic positions and signatures are altered in the future. A change in the affinity force $F(V_i, V_j, t + \Delta t)$ at a future moment $t + \Delta t$ may change the matrix $\mathbf{A}_{i,j}$ of the association link between the altered particles. Altering the semantic position of a particle will require reevaluating the semantic links of this particle with the relevant enclosing contexts.

The association matrix has the following structure:

$\mathbf{A}_{i,j} = [\mathbf{a}_{p_1, q_1} \dots \mathbf{a}_{p_m, q_n}]$ where the pairs p, q denote all relevant property pairs where the left property belongs to V_i and the right property belongs to V_j . Let us denote with \mathcal{P} the set of property indices which belong to V_i and with \mathcal{Q} the set of indices which belong to V_j . Then $p \in \mathcal{P}$ and $q \in \mathcal{Q}$. Note that the map $\mathcal{P} \rightarrow \mathcal{Q}$ is many-to-many. That is, the same index p may appear multiple times with different $q \in \mathcal{Q}$ and the same index q may appear multiple times with different $p \in \mathcal{P}$. The property association matrices $\mathbf{a}_{p,q}$ have the following structure:

$$\mathbf{a}_{p,q} = \begin{bmatrix} \mathbf{r}_1^p & \mathbf{r}_1^q \\ \mathbf{0} & \mathbf{0} \\ \mathbf{r}_2^p & \mathbf{r}_2^q \\ \mathbf{0} & \mathbf{0} \\ \vdots & \vdots \\ \mathbf{0} & \mathbf{0} \\ \mathbf{r}_k^p & \mathbf{r}_l^q \end{bmatrix}$$

So $\mathbf{a}_{p,q}$ is a two-column matrix of size $N \times 2$ with non-zero regions in each column denoted by the vectors \mathbf{r}_i where $\sum_i^k \text{size}(\mathbf{r}_i^p) \leq N$ and $\sum_j^l \text{size}(\mathbf{r}_j^q) \leq N$. The non-zero regions \mathbf{r}_i^p and \mathbf{r}_j^q are also known as the **active regions** of the association link between the two properties $P_p \in \text{ptree}(V_i)$ and $P_q \in \text{ptree}(V_j)$ at time t . For details refer to [Note On Binding Of An Association Property to Semantic Properties](#).