

Semantic tree operations

D. Gueorguiev 1/6/2021

Notation:

$T^{(m)}$ – an m -ary tree

$\mathcal{V}(T)$ - the set of all nodes of T

$P(v, T)$ – path from root of T to node v

(k, v) – tree tuple of T

k – tree factor, an integer

$\{\dot{k}_1, \dot{k}_2, \dots, \dot{k}_h\}$ - tuple of primitive factors

\dot{k} – primitive factor, an integer

$\mathcal{K}(T)$ – the set of all primitive factor tuples of T

$\mathcal{A}(T)$ – the set of all arcs of T

Summary and definitions

We are considering m -ary tree $T^{(m)}$ (abbreviated with T from now on), which is a tree in which each node has at most m children. Let us introduce the *tree tuple* (k, v) where v represents a *tree node* which is a semantic particle or a *subtree* of nodes (i.e. semantic particles). We will denote by $\mathcal{V}(T)$ the set of all nodes which belong to the tree T .

Here k is a *tree factor* which encodes uniquely the position of the node or the root of the subtree v in the parent tree T . More precisely, the factor k encodes uniquely the path $P(v, T)$ from the root of the tree to the node v or the root of subtree associated with k . Each tree factor k representing a node other than the root of T can be decomposed into a *tuple* t of *primitive factors* $\{\dot{k}_1, \dot{k}_2, \dots, \dot{k}_h\}$ where h is smaller or equal to the height of the tree. Here with dot-accented \dot{k} we denote a primitive factor i.e. a factor which cannot be represented by any other combination of primitive factors.

We will denote with $\mathcal{K}(T)$ the set of all tuples of primitive factors associated with tree T . The position in t of each of those primitive factors and their value encodes an *arc* from the set of arcs forming the path $P(v, T)$.

Definition: Arc of semantic tree

Let us define a tree with N nodes as:

$$T = \sum_{i=0}^N (k_i, v_i) \quad (1)$$

We denote with t_i the tuple of the primitive factors for k_i :


$$t_i = \{\dot{k}_{1,i}, \dot{k}_{2,i}, \dots, \dot{k}_{h,i}\}. \quad (2)$$

Every arc of T is represented by a tuple $t = \{\dot{k}_1, \dot{k}_2, \dots, \dot{k}_l\}$ such that $t \in \mathcal{K}(T)$. However not every tuple $t \in \mathcal{K}(T)$ represents an arc - the tuple $\{\dot{k}_0\}$ associated with the root of T does not correspond to an arc of T . We will denote with $\mathcal{A}(T)$ the set of all arcs of T . Obviously, $|\mathcal{A}(T)| = |\mathcal{K}(T)| - 1 = |\mathcal{V}(T)| - 1$.

If we substitute (2) in (1) we come up with the following simplified notation for T represented in terms of its primitive factors which will be used throughout this discussion:

$$T = \sum_{i=0}^N (\dot{k}_{1,i}, \dot{k}_{2,i}, \dots, \dot{k}_{h,i}, v_i) \quad (3)$$

Example



The root node V_3 is given with the tuple (k_0, v_3) . Its children are given with (k_1, v_2) , (k_2, v_4) , and (k_3, v_7) . Their children are accordingly (k_4, v_1) , (k_5, v_5) , (k_6, v_6) , and (k_7, v_8) . In a later paragraph we will introduce rules which will allow us to show that the following expansions take place:

$$\begin{aligned}
 k_1 &= \dot{k}_1 \dot{k}_0 \\
 k_2 &= \dot{k}_2 \dot{k}_0 \\
 k_3 &= \dot{k}_3 \dot{k}_0 \\
 k_4 &= \dot{k}_1 \dot{k}_1 \\
 k_5 &= \dot{k}_2 \dot{k}_1 \\
 k_6 &= \dot{k}_2 \dot{k}_2 \\
 k_7 &= \dot{k}_3 \dot{k}_1
 \end{aligned}$$

Thus, the tree T can be written as:

$$T = (\dot{k}_0, v_3) + (\dot{k}_1 \dot{k}_0, v_2) + (\dot{k}_2 \dot{k}_0, v_4) + (\dot{k}_3 \dot{k}_0, v_7) + (\dot{k}_1 \dot{k}_1, v_1) + (\dot{k}_2 \dot{k}_1, v_5) + (\dot{k}_2 \dot{k}_2, v_6) + (\dot{k}_3 \dot{k}_1, v_8).$$

Notice that for the root of the tree we always have:

$$k_0 = \dot{k}_0 \quad (4)$$

Definition: Weighted semantic tree

Let us assume that the two trees are weighted so that for each tree there is weight function which maps each tuple factor to a real number which is the weight corresponding the arc associated with the specified tuple factor. Let us denote by f and f^* the two weight functions corresponding to T and T^* . Generally, $f(k_i) \neq f^*(k_i)$. If $f \equiv f^*$ then T and T^* have the same weights on their matching arcs.

Definition: Semantic significance vector of a semantic tree

//TODO

Semantic subtree expansion and node comparison

The following operations are defined for tree factors:

Multiplication operation for semantic tuple factors

One possible implementation for the primitive factors $\dot{k}_1, \dot{k}_2, \dots, \dot{k}_m$ is to define them as the m digits greater than 0 of $(m + 1)$ -nary number system such that $0 = \dot{k}_0 < \dot{k}_1 < \dot{k}_2 < \dots < \dot{k}_m$. We define an operation `*` denoting digit concatenation $\dot{k}_i * \dot{k}_j = (m + 1)\dot{k}_i + \dot{k}_j$. Obviously,

$$\dot{k}_i * \dot{k}_j > \dot{k}_i \text{ for any pair } i, j = 1..m$$

Note that the latter implies that

$$\dot{k}_{i_1} * \dot{k}_{i_2} * \dots * \dot{k}_{i_n} > \dot{k}_{j_1} * \dot{k}_{j_2} * \dots * \dot{k}_{j_{n-1}} \text{ for any tuple where } i_p, j_q = 1..m, p = 1..n, q = 1..n - 1$$

$$(\dot{k}_i, (\dot{k}_j, v_j)) = (\dot{k}_i * \dot{k}_j, v_j)$$

Encoding a complete m -ary tree T of height h with the algebraic notation above:

$$T = (\dot{k}_0, v_0^0). \text{ Further we will assume that } \dot{k}_0 = 0.$$

$$v_0^0 = (\dot{k}_0, v_0^1) + (\dot{k}_1, v_1^1) + (\dot{k}_2, v_2^1) + \dots + (\dot{k}_m, v_m^1)$$

In general, we have:

$$v_q^p = (\dot{k}_0, v_{(q-1)m}^{p+1}) + (\dot{k}_1, v_{(q-1)m+1}^{p+1}) + (\dot{k}_2, v_{(q-1)m+2}^{p+1}) + \dots + (\dot{k}_m, v_{qm}^{p+1})$$

$$\text{where } q = 1..m^h, p = 1..h$$

Obviously, we have at most $\frac{(m^{h+1}-1)}{m-1}$ distinct terms v_q^p which represent nodes i.e. semantic values.

Tuple factor comparison operator

The expression for the tree also can be written as:

$$T = \sum_{i=0}^N (k_i, v_i) \text{ where } N \leq \frac{(m^{h+1}-1)}{m-1} \text{ and } k_i \text{ are the node factors given with } k_i = \dot{k}_{i_1} * \dot{k}_{i_2} * \dots * \dot{k}_{i_n}; n \leq h.$$

The node values v_i are the values v_q^p ordered in increasing order of k_i . This order corresponds to *level order traversal* of the m -ary tree. Note that with appropriately defined comparison operation ` $<$ ` we can model different ways of traversing the m -ary tree. For instance, if we define ` $<$ ` as the comparison for the values of $(m + 1 - \dot{k}_{i_1})m^{n-1} + (m + 1 - \dot{k}_{i_2})m^{n-2} + \dots + (m + 1 - \dot{k}_{i_n})$ we will have ordering which corresponds to the *preorder traversal* of the tree.

Example

Peter is Dimitar's son.

Dimitar's son has a friend in the neighborhood and his friend's name is James.


\Rightarrow *James is Peter's friend*

Peter is the son of Dimitar.

$$V_1 \ V_2 \ V_3 \ V_4 \ V_5 \ V_6$$

The son of Dimitar has a friend in the neighborhood and the name of his friend is James.

$$V_7 \ V_8 \ V_9 \ V_{10} \ V_{11} \ V_{12} \ V_{13} \ V_{14} \ V_{15} \ V_{16} \ V_{17} \ V_{18} \ V_{19} \ V_{20} \ V_{21} \ V_{22} \ V_{23} \ V_{24}$$



Expressing T_1 with the algebraic notation discussed earlier:

$$T_1 = (k_0, v_2) + (k_1, v_1) + (k_2, ((k_0, v_3) + (k_1, v_4) + (k_2, v_5) + (k_3, v_6)))$$

which is expanded to:

$$T_1 = (k_0, v_2) + (k_1, v_1) + (k_2 k_0, v_3) + (k_2 k_1, v_4) + (k_2 k_2, v_5) + (k_2 k_3, v_6)$$

Expressing T_2 with the algebraic notation yields:

$$\begin{aligned}
 T_2 = & (k_0, v_{17}) + \left(k_1, \left((k_0, v_{11}) + \left(k_1, \left((k_0, v_8) + (k_1, v_7) + (k_2, v_9) + (k_3, v_{10}) \right) \right) + \right. \right. \\
 & \left. \left(k_2, \left((k_0, v_{12}) + (k_1, v_{13}) \right) \right) + \left(k_3, \left((k_0, v_{14}) + (k_1, v_{15}) + (k_2, v_{16}) \right) \right) \right) \right) + \left(k_2, \left((k_0, v_{23}) + \right. \right. \\
 & \left. \left. \left(k_1, \left((k_0, v_{19}) + (k_1, v_{18}) + \left(k_2, \left((k_0, v_{20}) + (k_1, v_{21}) + (k_2, v_{22}) \right) \right) \right) \right) + (k_2, v_{24}) \right) \right)
 \end{aligned}$$

which is expanded to:

$$\begin{aligned}
 T_2 = & (k_0, v_{17}) + (k_1 k_0, v_{11}) + (k_1 k_1 k_0, v_8) + (k_1 k_1 k_1, v_7) + (k_1 k_1 k_2, v_9) + (k_1 k_1 k_3, v_{10}) \\
 & + (k_1 k_2 k_0, v_{12}) + (k_1 k_2 k_1, v_{13}) + (k_1 k_3 k_0, v_{14}) + (k_1 k_3 k_1, v_{15}) + (k_1 k_3 k_2, v_{16}) \\
 & + (k_2 k_0, v_{23}) + (k_2 k_1 k_0, v_{19}) + (k_2 k_1 k_1, v_{18}) + (k_2 k_1 k_2 k_0, v_{20}) + (k_2 k_1 k_2 k_1, v_{21}) \\
 & + (k_2 k_1 k_2 k_2, v_{22}) + (k_2 k_2, v_{24})
 \end{aligned}$$

Semantic Tree Difference

Let us have two trees represented as:

$$T = \sum_{i=0}^N (k_i, v_i) \text{ and } T^* = \sum_{i=0}^N (k_i^*, v_i)$$

Here $v_i, i = 1..N$ denote the nodes of the two trees (not subtrees) which are semantic particles with signatures $ssig(v_i)$. The sequences k_i and k_i^* denote the sequences of tuple factors which encode the position of each node v_i in each of the two trees.

Definition: *Matching arcs of trees*

Let us assume that the two trees are weighted so that for each tree there is weight function which maps each tuple factor to a real number which is the weight corresponding the arc associated with the specified tuple factor. Let us denote by f and f^* the two weight functions corresponding to T and T^* . Generally, $f(k_i) \neq f^*(k_i)$. If $f \equiv f^*$ then T and T^* have the same weights on their matching arcs.

We have the same set of semantic particles but they are arranged differently in two trees. We would like to define metric how different are the two trees.

//TODO