

RELIABLE POLARIZATION REPRESENTATIONS FOR QUANTIFYING THE INFLUENCE OF SUBGROUPS ON SYSTEMATIC OPINION DIFFERENCES

Anonymous authors

Paper under double-blind review

ABSTRACT

Current representations of polarization focus exclusively on distinguishing minor disagreements from systematic differences in opinion between annotator groups. In this study we develop a new framework which not only detects, but also quantifies the degree to which any annotator subgroup causes these systematic differences. We first discover fundamental issues which we show limit prior approaches: 1) the presence of “inherent” polarization that cannot be attributed to any known or latent groups, and 2) opposing polarization effects canceling each other out in aggregated annotations. We then introduce a new metric that attributes polarization to any annotator group while avoiding these limitations and release a PyPi-installable implementation. Our metric surpasses both traditional similarity metrics and prior approaches on detecting subgroup polarization, while also uncovering previously latent polarization in overlooked minority and fine-grained ideological groups due to its robustness to group-size imbalances. Finally, in regard to LLM annotation, we find that LLMs **TODO**.

1 INTRODUCTION

Annotations are essential for subjective tasks, such as content moderation, toxicity, and Hate Speech (HS) detection, which are especially important for protecting minority groups United Nations (2025); Dioum (2025). However, in practice, analysis rests on inter-annotator agreement or majority-vote Ivey et al. (2025); Kralj Novak et al. (2022); van der Velden et al. (2025), which may lead to biased and misconfigured systems (e.g., toxicity models disproportionately marking African American (AA) speech as “toxic” Sap et al. (2019)), or discard *fundamental* disagreements between minority groups and the majority Quaranto (2022), (see the example in Fig. 1).¹

One alternative is using *polarization*, which correlates better with human judgments and is much less sensitive to different group sizes Pavlopoulos & Likas (2023; 2024). While we can detect polarization, there is little work on how to detect whether it is *actually caused by marginalized groups*. Our work thus tries to answer the following **Main Research Question (MRQ): How can we build a robust representation of intergroup polarization?** We answer this question through the following sub-questions:

RQ 1: How much of the observed polarization is attributable to annotator subgroups? While prior work assumed that all polarization can be explained and attributed to some annotator characteristic, through the exhaustive creation of theoretical annotator groups (§4) our study discovers the existence of Inherent Polarization (InPol), which can not be attributed to *any possible group* of annotators—known or unknown (Finding 1). We also discover that polarization across items has a *direction*, preventing us from aggregating annotations on the dataset level to circumvent annotation sparsity (Finding 2), which we later show to limit existing statistical approaches.

RQ 2: How can we quantify this attribution to each possible subgroup? In order to solve these issues we introduce a new metric “*apunim*”, which attributes polarization to specific annotator sociodemographic and ideological characteristics (referred to as Personal Characteristics (PCs) in this

¹The simulated experiments in this study were implemented by generating random annotations following the normal distribution with differing means and Standard Deviation (SD)—see App. F.




Figure 1: Simulated experiment exploring four scenarios of a HS detection task applied to a controversial statement by D. Trump (Jan. 2019). The variance in annotations across different annotators may cause traditional agreement metrics to ignore minority opinions, especially when opinions are mixed (top-right).

study). Unlike previous approaches, our metric enables *quantitative* comparisons across datasets and performs even when unattributable and conflicting polarization exist. It outperforms prior approaches in scenarios with realistic annotation sparsity and minority group splits, while staying competitive in ideal scenarios (Finding 3).

RQ 3: Which polarization patterns are detectable using our new representation? We then apply our metric to four Natural Language Processing (NLP) datasets focused on Toxicity and HS detection (§6), confirming prior work showing that annotator gender and ethnicity significantly impact annotation, while discovering that ideological attributes and personal experiences may play a major role in explaining polarization—e.g., the more religious the annotators, the more polarized they become—Finding 4. These possibilities have not adequately explored by relevant literature.

RQ 4: Which polarization patterns are shared between human and LLM annotators? We conduct an annotation study on the same datasets using seven open-source models (App. I) in order to compare polarization patterns between them and humans.

Our work thus makes the following contributions: (1) The identification of severe issues present in subjective datasets (2) A new polarization attribution metric that is robust to small annotator counts and minority group splits with a PyPi-installable implementation (3) The detection of new promising directions for analysis of subjective NLP datasets (4) Insight into LLM subjectivity. Our study also underscores the need for datasets with high annotator counts per item, instead of high annotator counts in general—see App. H for a more extensive discussion and empirical findings.

Content Warning: This publication includes examples of controversial and potentially harmful speech for the purposes of demonstration. These examples do not represent the views of the authors.

2 BACKGROUND AND RELATED WORK

2.1 AGREEMENT

Popular inter-annotator agreement metrics such as Cohen’s kappa, Krippendorff’s alpha, and Fleiss’s kappa aim to distinguish genuine disagreement from random disagreement through statistical chance-correction. However, these metrics are often difficult to apply to intergroup agreement without extensions or restrictive assumptions (e.g., no missing labels or equal numbers of annotations). They have also been criticized for failing to account for differences arising from social, cultural, and demographic backgrounds (Feinstein & Cicchetti, 1990; Byrt et al., 1993; van der Velden et al., 2025; Checco et al., 2017), producing results that are difficult to compare across studies, being sensitive to class imbalance (Feinstein & Cicchetti, 1990), and relying on questionable assumptions about chance agreement Checco et al. (2017). While recent work has addressed some of these limitations with methods that improve applicability and robustness van der Velden et al. (2025); Wong et al. (2021); Ivey et al. (2025), they are much more complex and less intuitive compared to their traditional counterparts, indicating that agreement may not be the correct tool for analysis of minority viewpoints.

2.2 POLARIZATION

There are multiple competing formulations for polarization. One of these approaches Akhtar et al. (2019) utilizes χ^2 to estimate in-group vs out-group variance, but still requires traditional agreement metrics for analysis. Others attempt to solve this problem by framing disagreement as a cluster identification problem, applying either parametric Checco et al. (2017), or non-parametric Pavlopoulos & Likas (2024); Mignemi et al. (2024) approaches to the annotation histograms.

For our work, we use a non-parametric polarization metric, normalized Distance From Unimodality (nDFU), which has been shown to correlate better with human judgment of disagreement than established metrics (Pavlopoulos & Likas, 2024). nDFU takes values in the range $[0, 1]$, where values close to 0 indicate no polarization (i.e., opinions are concentrated around a single mode). The metric is defined as follows:

$$\text{nDFU}(X) = \frac{\max_{i \neq m} \left(f_i - \begin{cases} f_{i-1}, & \text{if } i > m \\ f_{i+1}, & \text{if } i < m \end{cases} \right)}{f_m}, m = \arg \max_i f_i \quad (1)$$

where, X denotes the set of annotations, f_i the relative frequency of the i -th annotation (e.g., the frequency of 2 in a scale of 1–5), and m the histogram peak. Intuitively, nDFU measures how prominent secondary peaks are compared to the main peak (see Fig. 2, left for an example).

2.3 ATTRIBUTING POLARIZATION TO GROUPS

While many studies study the effect of subgroups on annotation agreement Goyal et al. (2022); Binns et al. (2017); Giorgi et al. (2025); Al Kuwatly et al. (2020); Sachdeva et al. (2022), attributing *polarization* is a relatively new concept. Under the name *aposteriori unimodality* Pavlopoulos & Likas (2024), the original idea is that if polarization in a single item is positive, but zero for all annotator subgroups, then it is explained by those groups. Though promising, this mechanism operates on the assumption that *all* polarization can be explained by a single split, which we disprove prove to be impossible in many cases (§4). Additionally, getting polarization estimates from few annotations per item is extremely noisy, which is especially problematic when the output is binary (i.e., an item either is or is not polarizing) instead of a quantifiable value.²

3 DATASETS

We use four datasets from current NLP research that include PC information at the level of individual annotators; specifically, the “Kumar” Kumar et al. (2021) and “Sap” (“Breadth of Posts”) Sap et al.

²For example, when presented with noisy estimates of a metric in the $[0, 1]$ range, we would ideally want to distinguish between cases where attribution is close to .001, and cases where attribution is .49.

Dataset	#Com	#Ann	#Dims	Task
Kumar	2998	5	10	Tox
Sap	585	5–6	3	HS
DICES-350	350	123	4	HS
DICES-990	990	70–76	4	HS

Table 1: Datasets used in this study. *#Ann* refers to the number of annotations per item (see App. B), and *#Dims* to PC dimensions (e.g., age, gender). Tasks are either Toxicity (Tox) or HS.




Figure 2: **Left:** Simulated experiment describing a polarizing comment where male and female annotators agree between themselves, but disagree with the opposite gender. **Right:** InPol across our datasets (§3). Contrary to assumptions made in prior work, InPol is commonly non-zero and can even reach $nDFU = 1$ in datasets with low annotator counts.

(2022) datasets, which are concerned with Toxicity and HS detection respectively, and the DICES-350 and DICES-990 datasets Aroyo et al. (2023), which focus on LLM response safety.³

A brief overview of dataset characteristics is provided in Table 1. The Kumar dataset stands out for its large size, featuring more than 100,000 annotated items, as well as 10 distinct PC dimensions.⁴ In contrast, the DICES datasets contain fewer annotated items but involve more than an order of magnitude more annotators per item than the other datasets. More details on the annotations, including overall levels of observed polarization, can be found in App. B.

4 IS IT POSSIBLE TO ATTRIBUTE ALL POLARIZATION TO ANNOTATOR GROUPS?

4.1 PROBLEM FORMULATION

Let $d = \{c_1, c_2, \dots\}$ be a dataset composed of multiple annotated items.⁵ Each item c is assigned multiple annotators, which creates the annotation multi-set $A(c) = \{(a_1, g_1), (a_2, g_2), \dots\}$, where a_i is a single annotation (e.g., 2 in a LIKERT scale of 1–5), and g_i a group (e.g., men). As an example, the annotations for a item in a sentiment analysis task where we group the annotators by gender, would be formulated as:

$$A(\text{"Could be better, could be worse"}) = \{ (+, F), (-, M), (+, F), \dots \}$$

³For the latter, we consider only labels relating to racism (*Q3_bias_overall*), thereby transforming the task to HS detection.

⁴We sample 3,000 items in this study due to computational constraints (App. D). We run ablations for both different and differently sized-samples. Our results remain consistent, although large samples (10,000+) tend to produce null results (App. G).

⁵The annotated items could be of any modality, such images, videos or survey questions, even though we only consider items in this study.

Intuitively, a group partially explains the polarization of a item c when the annotations of that group $A(c | g) = \{a(c, g') \in A(c) \mid g' = g\}$ exhibit higher polarization compared to the full set of annotations $A(c)$. Consider the case where a misogynistic item is annotated for toxicity by male and female annotators shown in Fig. 2, left. The annotations are generally polarized ($nDFU_{all} = .62$); but both female ($nDFU_{women} = .10$) and male ($nDFU_{men} = .37$) annotators exhibit low polarization between their respective groups. This pattern suggests that the overall polarization is partially caused by substantive disagreements between male and female annotators.⁶

4.2 INHERENT POLARIZATION

4.2.1 WHAT IS IT?

Inherent Polarization (InPol) refers to disagreement that cannot be attributed to *any specific* grouping of annotators; that is, polarization that exists no matter how we split the annotators in any arbitrary group. Prior work Pavlopoulos & Likas (2024) attributed polarization to annotator groups only when the observed polarization for each individual group became exactly zero (e.g. $nDFU(all) > nDFU(men) = nDFU(women) = 0$). The presence of InPol would invalidate this theory, since there would be no possible group or combination of groups g s.t. $nDFU(g) = 0$.

Definition 1 (Inherent Polarization). Polarization that cannot be explained by any known or latent annotator grouping.

Formally, the InPol for a single item c is the minimum polarization exhibited by any arbitrary group:

$$Pol_{inh}(c) = \min_{S \subseteq A(c), |S| \geq 3} \{nDFU(S)\} \quad (2)$$

When considered exhaustively, these theoretical, random groups include both observed and latent groups (e.g., annotators may be less strict if they had lunch prior to annotation). Since $nDFU$ operates only when a group has at least three annotators (Eq. 1), this yields $\sum_{k=3}^n \binom{n}{k}$ possible groups.

4.2.2 DOES IT EXIST?

We systematically explore the space of annotator groups by generating random partitions for each item. Since enumerating all subsets is computationally intractable for large annotator counts, we establish an upper bound via Monte Carlo sampling by drawing k random partitions with random sizes (Eq. 2). Since Eq. 3 considers a strict subset of Eq. 2, it provides an upper bound for it:

$$Pol_{inh}^{MC}(c) = \min_{j=1}^k \{nDFU(\tilde{r}_j(A(c)))\} \quad (3) \quad Pol_{inh}^{MC}(c) \geq Pol_{inh}(c) \forall c \quad (4)$$

where $\tilde{r}$ is an operator that selects a randomly sized, randomly selected subset.

We compute the InPol for each item across the four datasets. For Sap and Kumar, we use the exhaustive formulation (Eq. 2), whereas for the two DICES datasets we rely on the Monte Carlo approximation with $k = 1000$ (Eq. 3). Fig. 2, right shows that in all DICES items there exists at least one group that fully accounts for the observed polarization.⁷ Interestingly, this observation does not hold for the Kumar and Sap datasets, despite evaluating all possible annotator groups exhaustively. See Table 9; App. B for a qualitative look through items with high InPol.

Finding 1. *items may exhibit a degree of InPol that cannot be attributed to any known or latent annotator grouping given the annotators present in the dataset.*

4.3 CAN WE REMOVE IT?

Unlike disagreement, InPol does not provide any information, but rather represents noise or uncertainty translated in terms of polarization. In order to minimize it, we need to find its cause. Since the DICES datasets are the only ones without *any* items with InPol leads us to two hypotheses:

⁶Since polarization persists among male annotators, another subgroup of men may also contribute to it.

⁷ $Pol_{inh}^{MC}(c) = 0 \Rightarrow Pol_{inh}(c) = 0$ due to Eq. 4. The same logic applies if we tried to increase the number of random partitions in Eq. 3.




Figure 3: A synthetic experiment simulating a polarizing discussion with two comments where annotators disagree about which one is toxic. When we aggregate the comments, we unintentionally change the comparison: instead of comparing two unimodal distributions (each comment viewed separately) with two bimodal distributions (their aggregated annotations), we end up comparing two bimodal distributions, obscuring the source of the polarization (polarization explained by gender, but not shown).

Hypothesis 1 (Low annotator count). A low number of annotators per item may provide our model with insufficient information.

Hypothesis 2 (Inaccessible groups). InPol may arise from the presence of partially represented groups within the annotator pool which may go undetected if they are represented by only one or two annotators, as nDFU is undefined for these groups.

Both of these explanations are plausible and reflect known limitations of most NLP datasets. Unfortunately, we can not confirm any of these hypotheses, as explained in App. F. While we can not address Hyp. 2 without more annotations, we could address Hyp. 1 by aggregating annotations between items. However, Fig. 3 shows that two items polarized for the opposite reason may lead to a false negative. Therefore, any statistics must be computed on the item-level; annotations should never be aggregated across items.⁸

Finding 2. *Items hold their own pol. direction which may compromise cross-item aggregation.*

5 HOW DO WE ATTRIBUTE THE REST?

5.1 QUANTIFYING CONTRIBUTION TO ANNOTATOR GROUPS

Instead of using InPol, which represents the minimum possible polarization exhibited by any group, we calculate the *expected* (average). Therefore, we do not test whether the group is polarized against the whole; nor whether the group explains *some polarization* (as would be the case if we used Eq. 2), but rather whether the group explains polarization *more than other groups*. Specifically, we define apriori polarization for an item c according to Eq. 5, which is averaged across items for a dataset d (Eq. 6). Intuitively, a high apriori polarization score means that much of the polarization in the dataset is likely not driven by any single group.

$$Pol_{apr}(c) = \frac{1}{t} \sum_{i=1}^t nDFU(\tilde{r}_i(A(c))) \quad (5) \quad Pol_{apr}(d) = \frac{1}{|d|} \sum_{c \in d} Pol_{apr}(c) \quad (6)$$

where $\tilde{r}$ is the random partition operator (see Eq. 2). We explain why defining apriori polarization in this way is preferable to alternatives in App. E.1.

⁸A similar assumption was followed in early parametric approaches, which assumed different parameters for each item Checco et al. (2017).




Figure 4: Polarization group attribution on randomly generated, synthetic distributions. Bars indicate standard error. For each experiment we assign a number of annotators per item, and split the annotator groups 50-50 or 80-20. Higher δ represents higher polarization between groups. Apunim is adept at attributing polarization to the correct group regardless of number of annotators per item, or how these annotators are split to different groups.

We compare this quantity with the average observed polarization of all items (Eq. 7), which we use to compare the polarization that is attributed to a single annotator group with the expected one (Eq. 6), yielding our normalized metric, *apunim* (Eq. 8).

$$Pol_{obs}(d, g) = \frac{1}{|d|} \sum_{c \in d} nDFU(A(c|g)) \quad (7) \quad apunim(d, g) = \frac{Pol_{apr}(d) - Pol_{obs}(d, g)}{1 - Pol_{apr}(d)} \quad (8)$$

Apunim measures the degree to which an annotator group contributes to overall polarization in a set of items. The *sign* of apunim carries information agreement-based attribution does not:

- $apunim(g) \approx 0$: The group g does not meaningfully disagree with the other annotators.
- $apunim(g) > 0$: The group g has fundamental disagreements with the other annotators.
- $apunim(g) < 0$: The annotators of group g are polarized between themselves.

We also include a perturbation-based p-value estimation, which tests whether the observed apunim value of a group g statistically surpasses that of random groups in App. C.

5.2 COMPARISON WITH OTHER METHODS

We construct polarization distributions annotated by two groups. Each annotator is slightly biased to judge similarly with their group, although the group effect is different for each item. We model the disagreement between these groups using a parameter δ ; higher δ signifies a larger divergence between the groups. An effect is considered detected if the statistic recovered using perturbations of a null distribution is significant. The complete experimental setup is detailed in App. F.

Fig. 4 shows the effectiveness of apunim, the aposteriori unimodality framework proposed by Pavlopoulos & Likas (2024), the χ^2 method presented in Akhtar et al. (2019), GMM clustering used in Checco et al. (2017), and a baseline using intergroup disagreement ($\Delta\alpha$ Krippendorff). Both the χ^2 and GMM methods generally fail at attributing polarization, which is most likely caused by opposing polarization effects (see Fig. 3) violating their assumptions on fixed mean differences between groups.⁹ Intergroup disagreement remains competitive when many annotators are available, but underperform in cases where the examined group is a minority and when a few annotators are available per item (a common case among NLP datasets—see §3). Apunim in contrast is robust

⁹Indeed, re-running the experiment with a consistent mean-difference effect among the groups leads to exceptional performance by these methods—see App. G.2.

Group	Apunim	Support
DICES-350		
Ethnicity=Asian	-0.066	8138
Education=Other	0.021	2191
DICES-990		
Ethnicity=AfricanAm	-0.091	5810
Ethnicity=Latino	0.133	6610
Ethnicity=Other	-0.074	24321
Ethnicity=White	0.120	11392
Age=GenZ	-0.063	13741
Age=GenX+	0.046	14384
Education=High school	-0.075	7419
Gender=Man	-0.027	32494
Gender=Woman	0.024	33471
Sap		
Ethnicity=AfricanAm	0.042	4
Gender=Man	-0.091	1439
Gender=Woman	0.244	877

Group	Apunim	Support
Kumar		
A. Innate Characteristics		
Ethnicity=White	-0.029	6619
Education=College	-0.034	2508
SexOrient=Heterosexual	-0.050	5721
IsTrans=No	-0.079	1697
B. Experiences and Ideologies		
HasBeenTargeted=False	-0.048	6632
IsParent=No	-0.069	5514
IsParent=Yes	0.049	6216
ReligionImportant=No	-0.062	3864
ReligionImportant=Very	0.052	4062
SeenToxicity=False	0.035	3050
SeenToxicity=True	-0.077	6360

Table 2: Statistically significant ($p < 0.05$) apunim results across the four datasets. Gray rows show Ethnicity and Gender groups. “Support” refers to number of annotations. Consult App. J for the full results.

both to the number of annotators per item, opposing polarization effects, and minority groups, which validates our initial motivation.

Finding 3. *Apunim beats established and proposed methodologies in realistic conditions.*

6 ATTRIBUTING REAL-LIFE POLARIZATION

6.1 HUMAN ANNOTATORS

Assuming a confidence level of $\alpha = 0.05$ we test whether any of the provided PC dimensions can explain observed polarization. Statistically significant results are presented in Table 2. See App. D for details on other parameters and execution times, and App. J for the full results.

*Polarization is consistently attributed to **ethnicity** across all datasets*, confirming prior work suggesting that it is a systematic source of annotator disagreement in these tasks Goyal et al. (2022).¹⁰ Additionally, in both DICES-990 and Sap, *women are a consistent source of polarization* (positive values), while *men disagree among themselves* (negative values). These results are consistent with previous findings regarding HS (Wojatzki et al., 2018) and toxicity annotation Binns et al. (2017). Non-**transgender** annotators also showed the *highest degree of polarization* in the Kumar dataset in absolute terms (-0.788) suggesting that transgenders are a systematic source of disagreement.¹¹

Ideology and experiences appear to be a more consistent source of annotator disagreement than inherent characteristics. Specifically, the Kumar dataset, which tracks ideological attributes, shows polarization attribution linked primarily to personal experiences and beliefs, rather than to sociodemographic dimensions, although further datasets are required to generalize this finding. The divide between ideology/personal experiences and innate sociodemographic characteristics has not been adequately explored in current literature and should be further studied in future work. Furthermore, *religion demonstrates a clear relationship with polarization attribution*. According to Fig. 5, highly devout annotators exhibit higher levels of self-agreement compared with other annotators (posi-

¹⁰We note that polarization attribution does not have a consistent direction across datasets, which we believe to be caused by studies using different ethnic subgroups, allowing polarization detection on the level of PCs, but distorting subgroup attribution.

¹¹Although only the inverse effect is detectable due to annotator sparsity, hence the negative sign.




Figure 5: Polarization attribution trends in ordinal groups. The left side of the x-axis refers to young annotators, low education, low religiousness, and negativity towards the impacts of toxicity and technology. The full ordinal modes for each dimension and their individual labels can be found in App. J. We exclude groups with < 50 annotations, since they near-universally result in zero apunim values due to lack of data.

tive apunim). Non-religious annotators show a pattern of increased internal disagreement (negative apunim), a trend that gradually reverses as religious devoutness increases (increasing apunim).¹²

Finding 4. *Annotator ethnicity and gender are consistent causes of polarization, while the latter may be more pronounced in ideological attributes and personal experiences. It also escalates as annotators become more religious.*

6.2 LLM ANNOTATORS

7 CONCLUSION AND FUTURE WORK

We discovered issues regarding the presence of inherent and conflicting polarization which render current methods around subgroup disagreement attribution suboptimal in realistic circumstances. We created a new metric (*apunim*) that overcomes these issues and outperforms alternatives methodologies in realistic annotation settings, while also quantifying the attribution of each group. By applying this metric to four subjective NLP datasets, we discover that (1) ethnicity and gender seem to generally drive polarization attribution, and (2) ideological groups may be more important than reported in the literature. Finally, we ...**TODO**.

Our study shows that future research needs to focus on “wide” datasets—those with many annotators per item, rather than just having many items with few annotators. Because these datasets are rare, we cannot pinpoint specific examples or individual items to explain the observed apunim values. Furthermore, the lack of rich annotation data prevents us from analyzing how different annotator groups interact (e.g., the relationship between LGBTQ+ and Conservative annotators). Finally, our data is limited to English posts from a U.S. cultural context. Future work should focus on building these wider datasets with detailed annotator profiles to enable deeper, multidimensional analysis.

AI USE STATEMENT

In this work we used proprietary models such as Claude’s Sonnet 5 and OpenAI’s GPT-5 for partially implementing the synthetic experiments in §5.2 and generating parts of the library, experiment and graph-creation code. All such tasks were executed with direct author supervision,

¹²The statistical insignificance observed during the transition from irreligious to highly religious groups may represent genuine shifts rather than inconclusive results, since Eq. 9 checks whether $apunim \neq 0$, given that $apunim_{rand}(d, g)$ will usually be close to zero. This phenomenon may also apply to other ordinal PCs, such as Age in both Sap and DICES-990, but finer-grained subgroups are needed to verify this.

and all relevant code files (library, experiments, graphs) have been edited manually at multiple points by the authors to ensure reproducibility, accuracy and software quality. Additionally, we attempted to use Claude’s Sonnet 5 for proposing research directions for this work, but ended up discarding all suggestions. Finally, we used a locally hosted Gemma-4 model (specifically the `gemma-4-E4B-it-Q4_K_M.gguf` variant) for rephrasing this manuscript in order to improve readability. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

REPRODUCIBILITY STATEMENT

We analyze software design decisions, limitations and computational details in App. D and elaborate on our experimental setup in App. E. Information on the synthetic experiments used in §4.5 is disclosed in App. F, while ablations around sample sizes and sample selection for the Kumar dataset are detailed in App. G. Additionally, we include a discussion around the use of current NLP datasets, as well as an empirical estimation of the number of required annotators for reproducible results in App. H.

In both LLM and non-LLM experiments all relevant seeds are pinned to allow exact reproducibility, although we note that LLMs are by their nature stochastic, which can not be treated using software (Bisbee et al., 2024). All code, data-processing scripts and the library implementing *apunim* are released anonymously: library <https://anonymous.4open.science/r/apunim-5F70>, documentation <https://anonymous.4open.science/r/apunim-page>, replication code <https://anonymous.4open.science/r/aposteriori-unimodality-E8C1>.

ETHICS STATEMENT

Dual Use Concerns The primary objective of this study is to identify systemic sources of polarization in subjective NLP datasets to facilitate the construction of more robust and equitable AI systems. However, given that our methodology allows for the quantitative attribution of specific judgment patterns to sociodemographic and ideological characteristics, we acknowledge three primary risks inherent in this research.

First, *Discriminatory Profiling*: If the metric is applied outside of a dataset quality analysis, its ability to correlate specific judgment patterns with annotator groups could be misused for surveillance or unjust profiling. Second, *Automated Bias Amplification*: The diagnostic patterns of polarization we detect are reflections of human systemic biases. Without human oversight, training subsequent models on these patterns risks automating and entrenching existing societal prejudices. Finally, the knowledge provided by *apunim* could be *weaponized*, allowing malicious actors to strategically target weak points in moderation systems or intentionally maximize societal conflict.

We stress that our metric functions strictly as a diagnostic warning signal. Any deployment in a real-world system must mandate a rigorous human-in-the-loop review, ensuring that identified patterns lead to systemic improvements (e.g., policy reform, demographic diversity initiatives) rather than merely justifying an automated system.

Data Sourcing and Privacy All datasets employed in this study were either publicly accessible or provided to us by the original authors with full disclosure regarding the purpose of our research. No identifiable, personal information was included in our pipeline. We do not release proprietary data provided by the authors, nor have we provided any to proprietary LLMs.

Examples Used Our study utilizes examples of comments that may be considered divisive across certain demographics. These examples were generated by our team solely for demonstration purposes. We explicitly state that the contents of these examples and the groups studied do not necessarily reflect the views or behaviors of the groups they represent, nor do they reflect the opinions of the authors.

REFERENCES

- Sohail Akhtar, Valerio Basile, and Viviana Patti. A new measure of polarization in the annotation of hate speech. In Mario Alviano, Gianluigi Greco, and Francesco Scarcello (eds.), *AI*IA 2019 – Advances in Artificial Intelligence*, pp. 588–603, Cham, 2019. Springer International Publishing. ISBN 978-3-030-35166-3.
- Hala Al Kuwatly, Maximilian Wich, and Georg Groh. Identifying and measuring annotator bias based on annotators’ demographic characteristics. In *Proceedings of the fourth workshop on online abuse and harms*, pp. 184–190, 2020.
- Lora Aroyo, Alex Taylor, Mark Díaz, Christopher Homan, Alicia Parrish, Gregory Serapio-García, Vinodkumar Prabhakaran, and Ding Wang. Dices dataset: Diversity in conversational ai evaluation for safety. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 53330–53342. Curran Associates, Inc., 2023. URL https://proceedings.neurips.cc/paper_files/paper/2023/file/a74b697bce4cac6c91896372abaa8863-Paper-Datasets_and_Benchmarks.pdf.
- Reuben Binns, Michael Veale, Max Van Kleek, and Nigel Shadbolt. Like trainer, like bot? inheritance of bias in algorithmic content moderation. In *International conference on social informatics*, pp. 405–415. Springer, 2017.
- James Bisbee, Joshua D. Clinton, Cassy Dorff, Brenton Kenkel, and Jennifer M. Larson. Synthetic replacements for human survey data? the perils of large language models. *Political Analysis*, 32(4):401–416, 2024. doi: 10.1017/pan.2024.5.
- Ted Byrt, Janet Bishop, and John B. Carlin. Bias, prevalence and kappa. *Journal of Clinical Epidemiology*, 46(5):423–429, May 1993. ISSN 0895-4356. doi: 10.1016/0895-4356(93)90018-V. URL [https://doi.org/10.1016/0895-4356\(93\)90018-V](https://doi.org/10.1016/0895-4356(93)90018-V).
- Alessandro Checco, A. Roitero, Eddy Maddalena, S. Mizzaro, and Gianluca Demartini. Let’s agree to disagree: Fixing agreement measures for crowdsourcing. 10 2017.
- S.Y. Chen, Z. Feng, and X. Yi. A general introduction to adjustment for multiple comparisons. *Journal of Thoracic Disease*, 9(6):1725–1729, 2017. doi: 10.21037/jtd.2017.05.34; PMID: 28740688; PMCID: PMC5506159.
- Shelby Dioum. What explains the increase in online hate speech?, 3 2025. URL <https://www.ucdavis.edu/magazine/what-explains-increase-online-hate-speech>. Accessed: 2025-09-22.
- European Union. Regulation (EU) 2016/679 of the European Parliament and of the Council, 2016. URL <https://data.europa.eu/eli/reg/2016/679/oj>.
- European Union. Regulation (eu) 2024/1689 of the european parliament and of the council of 13 june 2024 laying down harmonised rules on artificial intelligence (artificial intelligence act). <https://eur-lex.europa.eu/eli/reg/2024/1689/oj/eng>, 2024. URL <https://eur-lex.europa.eu/eli/reg/2024/1689/oj/eng>. Official Journal of the European Union, L 2024/1689.
- Alvan R. Feinstein and Domenic V. Cicchetti. High agreement but low kappa: I. the problems of two paradoxes. *Journal of Clinical Epidemiology*, 43(6):543–549, Jan 1990. ISSN 0895-4356. doi: 10.1016/0895-4356(90)90158-L. URL [https://doi.org/10.1016/0895-4356\(90\)90158-L](https://doi.org/10.1016/0895-4356(90)90158-L).
- Tommaso Giorgi, Lorenzo Cima, Tiziano Fagni, Marco Avvenuti, and Stefano Cresci. Human and llm biases in hate speech annotations: A socio-demographic analysis of annotators and targets. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 19, pp. 653–670, 2025.
- Nitesh Goyal, Ian D Kivlichan, Rachel Rosen, and Lucy Vasserman. Is your toxicity my toxicity? exploring the impact of rater identity on toxicity annotation. *Proceedings of the ACM on Human-Computer Interaction*, 6(CSCW2):1–28, 2022.

- Aaron Grattafiori et al. The llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.
- Dirk Groeneveld and booktitle = others. OLMo: Accelerating the science of language models.
- Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979. ISSN 03036898, 14679469. URL <http://www.jstor.org/stable/4615733>.
- Jonathan Ivey, Susan Gauch, and David Jurgens. NUTMEG: Separating signal from noise in annotator disagreement. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 2874–2887, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-332-6. doi: 10.18653/v1/2025.emnlp-main.144. URL <https://aclanthology.org/2025.emnlp-main.144/>.
- Petra Kralj Novak, Teresa Scantamburlo, Andraž Pelicon, Matteo Cinelli, Igor Mozetič, and Fabiana Zollo. Handling disagreement in hate speech modelling. In Davide Ciucci, Inés Couso, Jesús Medina, Dominik Ślęzak, Davide Petturiti, Bernadette Bouchon-Meunier, and Ronald R. Yager (eds.), *Information Processing and Management of Uncertainty in Knowledge-Based Systems*, pp. 681–695, Cham, 2022. Springer International Publishing. ISBN 978-3-031-08974-9.
- Deepak Kumar, Patrick Gage Kelley, Sunny Consolvo, Joshua Mason, Elie Bursztein, Zakir Durumeric, Kurt Thomas, and Michael Bailey. Designing toxic content classification for a diversity of perspectives. In *Proceedings of the Seventeenth USENIX Conference on Usable Privacy and Security*, SOUPS’21, USA, 2021. USENIX Association. ISBN 978-1-939133-25-0.
- Giuseppe Mignemi, Antonio Calcagni, Andrea Spoto, and Ioanna Manolopoulou. Mixture polarization in inter-rater agreement analysis: a bayesian nonparametric index. *Statistical Methods & Applications*, 33(1):325–355, Mar 2024. ISSN 1613-981X. doi: 10.1007/s10260-023-00741-x. URL <https://doi.org/10.1007/s10260-023-00741-x>.
- Team Olmo. Olmo 3, 2026. URL <https://arxiv.org/abs/2512.13961>.
- John Pavlopoulos and Aristidis Likas. Distance from unimodality for the assessment of opinion polarization. *Cognitive Computation*, 15(2):731–738, 2023. ISSN 1866-9964. doi: 10.1007/s12559-022-10088-2. URL <https://doi.org/10.1007/s12559-022-10088-2>.
- John Pavlopoulos and Aristidis Likas. Polarized opinion detection improves the detection of toxic language. In Yvette Graham and Matthew Purver (eds.), *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1946–1958, St. Julian’s, Malta, March 2024. Association for Computational Linguistics. URL <https://aclanthology.org/2024.eacl-long.117/>.
- Anne Quaranto. Dog whistles, covertly coded speech, and the practices that enable them. *Synthese*, 200(4):330, 2022.
- Luca Rossi, Katherine Harrison, and Irina Shklovski. The problems of llm-generated data in social science research. *Sociologica*, 18(2):145–168, 1 2024. doi: 10.6092/issn.1971-8853/19576. URL <https://sociologica.unibo.it/article/view/19576>.
- Pratik S Sachdeva, Renata Barreto, Claudia von Vacano, and Chris J Kennedy. Assessing annotator identity sensitivity via item response theory: A case study in a hate speech corpus. In *Proceedings of the 2022 ACM conference on fairness, accountability, and transparency*, pp. 1585–1603, 2022.
- Maarten Sap, Dallas Card, Saadia Gabriel, Yejin Choi, and Noah A. Smith. The risk of racial bias in hate speech detection. In Anna Korhonen, David Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1668–1678, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1163. URL <https://aclanthology.org/P19-1163/>.

Maarten Sap, Swabha Swayamdipta, Laura Vianna, Xuhui Zhou, Yejin Choi, and Noah A. Smith. Annotators with attitudes: How annotator beliefs and identities bias toxic language detection. In Marine Carpuat, Marie-Catherine de Marneffe, and Ivan Vladimir Meza Ruiz (eds.), *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 5884–5906, Seattle, United States, July 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.naacl-main.431. URL <https://aclanthology.org/2022.naacl-main.431/>.

Ole Tange. Gnu parallel 20250822, August 2025. URL <https://doi.org/10.5281/zenodo.16944306>. GNU Parallel is a general parallelizer to run multiple serial command line programs in parallel without changing them.

United Nations. Targets of hate, 9 2025. URL <https://www.un.org/en/hate-speech/impact-and-prevention/targets-of-hate>. Accessed: 2025-09-22.

Mariken A. C. G. van der Velden, Felicia Loecherbach, Wouter van Atteveltdt, Antske Fokkens, Myrthe Reuver, and Kasper Welbers. Whose truth is it anyway? an experiment on annotation bias in times of factual opinion polarization. *Communication Methods and Measures*, 19(4):332–349, 2025. doi: 10.1080/19312458.2025.2562034. URL <https://doi.org/10.1080/19312458.2025.2562034>.

Michael Wojatzki, Tobias Horsmann, Darina Gold, and Torsten Zesch. Do women perceive hate differently: Examining the relationship between hate speech, gender, and agreement judgments. 2018.

Ka Wong, Praveen Paritosh, and Lora Aroyo. Cross-replication reliability - an empirical approach to interpreting inter-rater reliability. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 7053–7065, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.548. URL <https://aclanthology.org/2021.acl-long.548/>.

An Yang et al. Qwen2.5 technical report, 2025. URL <https://arxiv.org/abs/2412.15115>.

A ACRONYMS

InPol	Inherent Polarization
nDFU	normalized Distance From Unimodality
NLP	Natural Language Processing
GPLv3	GNU General Public Licence v3
AA	African American
PC	Personal Characteristic
HS	Hate Speech
SD	Standard Deviation

B EXPLORATORY ANALYSIS

The number of annotators per item for all datasets presented in §3 can be found in 7, and descriptive statistics can be found in Table 3. The DICES-990 dataset has exactly 123 annotations per item, while the other datasets exhibit a few variations around the central mean reported in Table 1. Interestingly, the sample used from the Kumar dataset exhibits a few items that vastly exceed the promised 5 number of annotators. We do not include these items, since they are very likely a data error. Tables 4,5,6,7,8 show the annotation counts for each PC group in each dataset.




Figure 6: Boxplots of dataset polarization for the human datasets considered in this paper for all groups in each examined PC dimension.

Dataset	count	mean	SD	min	25%	50%	75%	max
DICES-350	350	123	0	123	123	123	123	123
DICES-990	990	72.8	1.17	69	72	73	74	76
Sap	585	5.6	.78	3	6	6	6	12
Kumar	2998	5.02	.34	5	5	5	5	10

Table 3: Number of annotations per item in each of the four datasets used in this study.

Additionally, Table 9 shows a random sample of items taken from the Sap dataset and their respective InPol values (§4.2). Note that explicitly toxic or racist items tend to have InPol values of zero, alongside clearly unproblematic items. Inversely, more ambiguous and less comprehensible items tend to have larger InPol values. This pattern may suggest that InPol may be tied to the overall ambiguity of the statements, especially in cases where items may either be interpreted as very toxic, or non-toxic, which agrees with the overall goal of nDFU (§2.2). We include the InPol values for each individual item for all four datasets in the supplementary material.

C STATISTICAL ESTIMATION

Since annotation histograms may be noisy, we additionally assess whether the observed apunim value could arise by chance. To assess statistical significance, we construct a null distribution of apunim values from the randomized partitions and compare the observed apunim against this distribution using a one-sample Student-*t* test. Thus, the null hypothesis states that the observed polarization is indistinguishable from polarization induced by random annotator assignments:




Figure 7: We calculate the ratio of items for each dataset (y-axis) that had x number of annotators (x-axis). We truncate the x-axis to 130 annotators, disregarding very few items in the Kumar dataset exceeding this threshold (see Table 3), which is likely caused by a data error.

Category	Subgroup	Support
Gender	Woman	21700
	Man	21350
Race	White	10500
	African Am.	10150
	Asian	9100
	Latino	7700
	Multiracial	5600
Age	1) Gen. Z	19600
	2) Millennial	12600
	3) Gen. X+	10850
Education	College +	26250
	High school -	14350
	Other	2450

Table 4: Subgroup Counts for DICES-350. “Support” refers to annotation count.

$$\begin{aligned}
 H_0 : \bar{apunim}_{\text{rand}}(d, g) &= apunim(d, g) \\
 H_a : \bar{apunim}_{\text{rand}}(d, g) &\neq apunim(d, g)
 \end{aligned} \tag{9}$$

where $\bar{apunim}_{\text{rand}}(d, g)$ denotes the average $apunim$ values obtained from t randomized annotator partitions.

We account for the presence of multiple subgroups in each PC dimension using a multiple-hypothesis correction. Since our test is parametric (§C), it assumes that there exist (1) enough data-points to reliably run the means-test, (2) enough annotations per PC group to estimate nDFUs in Equations 5-7, (3) the $apunims$ of the random partitions are independent and identically distributed. Condition (1) can be safely assumed for most datasets, because they feature enough items to reliably assume normal residuals (see §3). We discuss condition (2) in App. H. Condition (3) is partly fulfilled; the partitions are identically distributed, but may be dependent on the sample distribution.

Replacing the parametric means test with a non-parametric alternative would relax assumptions about the underlying distribution but would not resolve the potential dependence between the ran-

Category	Subgroup	Support
Gender	Woman	36050
	Man	35392
	Nonbinary	331
	Other	330
Race	Other	26394
	Asian	19885
	White	12322
	Latino	7170
	African Am.	6332
Age	Gen. Z	14899
	Millennial	41542
	Gen. X+	15662
Education	College +	64054
	High school -	8049

Table 5: Subgroup Counts for DICES-990. “Support” refers to annotation count.

Category	Subgroup	Support
Age	Gen. Z	252
	Millennial	2259
	Gen. X+	786
Ethnicity	white	2168
	black	1091
	hisp	32
	other	5
	middleEastern	1
Gender	man	1859
	woman	1412
	nonBinary	26

Table 6: Subgroup Counts for Sap et al. 2022. “Support” refers to annotation count.

dom apunims. We initially attempted to implement a permutation test on the empirical (random apunim) distribution, but this resulted in excessive computational costs.

While the test operates on a single group in principle, in practice we often want to test polarization for all subgroups of a specific dimension. Since we are simultaneously considering multiple hypotheses, we apply a multiple comparison correction to the resulting p-values—specifically the Holms method Holm (1979). The test is parameterized by the confidence level of our test, which is used to tune the strength of the correction; we can increase this value to make our test more conservative towards multiple hypotheses Chen et al. (2017)).

D SOFTWARE

D.1 INSTALLATION AND USAGE

We release the `apunim` package, which is a Python library that implements both the `nDFU` and `apunim` calculations, as well as its statistical test. The software is available on PyPi We also provide high-level documentation in HTML format that includes an introduction, guide, and full low-level documentation for each of the two provided functions (<https://anonymous.4open.science/r/apunim-page>).

Category	Subgroup	Support
Gender	Female	8011
	Male	6832
	Unknown	124
	Nonbinary	93
Ethnicity	White	10699
	Black	1940
	Asian	862
	Multiracial	664
	Hispanic	418
	Other	247
	Unknown	230
Age	Under 18	3
	18 - 24	1711
	25 - 34	5969
	35 - 44	3785
	45 - 54	1977
	55 - 64	1101
	65 or older	471
	N/A	43
Education	No high school	71
	High School graduate	1353
	College, no degree	3090
	Associate degree	1676
	Bachelor's degree	6071
	Master's degree	2261
	Professional degree	236
	Doctoral degree	198
	N/A	71
	Other	32
Sexual Orient.	Heterosexual	12391
	Bisexual	1665
	Homosexual	515
	N/A	302
	Other	131

Table 7: Subgroup Counts for the Kumar et al. 2021 dataset. Part 1 of 2. “Support” refers to annotation count.

The code is open-source, licensed under the GNU General Public Licence v3 (GPLv3) and can be found on the project’s repository (<https://anonymous.4open.science/r/aposteriori-unimodality-E8C1>). The library is cross-platform, works for any Python 3 version, and requires very few dependencies (namely `numpy`, `scipy`, `statsmodels`).

D.2 IMPLEMENTATION DETAILS

By default, the computation of the apunim values happens on a single thread. In cases of serious computational cost, we recommend running the apunim calculation on multiple concurrent processes, since all operations are CPU-bound and thread-safe. This may be useful in cases where there are multiple PC dimensions, each of which is computationally expensive.

In order to lower the computational cost required, we re-use the random partitions $\tilde{r}_i$, which are originally calculated to obtain the apriori polarization values (see Eq. 5), for the p-value calculations (§C). This means that in our current implementation, the number of groups for estimating apriori polarization ($\tilde{r}_i$ in Eq. 5), and the number of apunim values used in the p-value calculation have to be the same.

Category	Subgroup	Support
Is Transgender	No	14549
	Yes	363
	N/A	148
Politics	Liberal	5997
	Independent	4143
	Conservative	3981
	N/A	609
	Other	330
Is Parent	Yes	7889
	No	7015
	N/A	156
Tech Impact	Very negative	149
	Somewhat negative	1411
	Neutral	1905
	Somewhat positive	7690
	Very positive	3905
Tox Problem	Never	869
	Rarely	2485
	Occasionally	5307
	Frequently	4441
	Very Frequently	1958
Rel Important	No	4735
	Not very	1808
	Somewhat	3548
	Very	4741
	N/A	228
Seen Toxicity	True	11505
	False	3555
Has Been Target	False	10741
	True	4319

Table 8: Subgroup Counts for Kumar et al. 2021 dataset. Part 2 of 2. “Support” refers to annotation count.

We use version 1.0.6 of the `apunim` library for our experiments. We use 100 random iterations for the apriori value calculation (Eq. 5) and the p-value estimation (§C), and set a confidence level of $\alpha = 0.05$.

While the library efficiently handles large numbers of annotators through vectorized operations, performance degrades significantly when processing a high volume of items, particularly when annotators belong to multiple distinct groups. For instance, while experiments across all datasets in §3 complete within a minute, the Kumar dataset necessitates approximately one hour of computation using commercial hardware. Furthermore, the annotator variance analysis detailed in App. H required over ten hours. While this latter time requirement is anticipated due to the inherently demanding nature and non-standard application of our library, it demonstrates the existence of a potential scaling bottleneck. The same applies to a lesser extent for the subsampling experiments on the DICES datasets, taking collectively three hours of computation.

We hypothesize that this bottleneck is likely caused by repeated creation of numpy arrays, resulting in repeated memory allocations for each subgroup, in each item, for each PC dimension. We plan on profiling and addressing it in the next releases of our software. Until then, we suggest either using multiprocessing for each PC subgroup, or running the different experiments in parallel (indeed, we use the `gnu-parallel` package Tange (2025) for our own experiments). We also note that the

Comment	InPol
The minks mentioned in the headline are indeed "rising" from where they were based, but that is due to them being buried in shallow mass graves (Africa) and filling with gas that causes them to rise out. Rest assured, they're still very much dead, thankfully!.	1
There should be such thing as a bitch resistance for us women	1
There's a big difference between being a bitch and being a woman	1
i just watched a video of @joisnotonfire being an annoying hoe on skype i'm laughing	1
niggas love to commit crime	1
I swear to God above I love ya and when ya be with this brotha, I swear I love you my bro as long as you not a nigga	0.5
I will become a cold ass bitch because of my treatment	0.5
I would happily lay out a nigga	0.5
Shoot yourself in the head you hypersensitive fuckin bitch.	0.5
not all women are bitches, but all bitches are women	0.5
"you ugly bitch!!!"- that seems to be my real name these days"	0
"I am happy to report that drowning does kill this demonic entity. Oh holy are the waters of Chernarus!"" Omg, DED ;)"	0
"Let them praise the name of the LORD: for his name alone is excellent; his glory is above the earth and heaven."" Psalms 148:13 #Bible"	0
someone plz get this nigger some help. He's playing up like mad	0
stop talking you fucking nigger !	0

Table 9: Sample of comments from the Sap dataset and their InPol. Note that unambiguously toxic comments can be assigned with zero InPol, while more nuanced cases tend to have higher values.

Kumar dataset also requires substantial RAM resources, estimated around 42–46GB of dedicated RAM should the whole dataset be considered.

Finally, we note that in Fig. 10, we removed values where there was a lack of items annotated by the specified number of annotators (e.g., only 7% of items in DICES-990 were annotated by more than 73 annotators—see App. B).

E DESIGN DECISIONS

E.1 DEFINING APRIORI POLARIZATION

In §4.1, we explained how our methodology needs to compare the polarization of $A(c)$ and $A(c|g)$. Direct comparisons are not advisable, since we would be comparing statistics between a set and its subset—in this case, standard practice dictates comparing the subset with its complement; i.e., the in-group vs. the out-group instead of the in-group vs. all the annotations. However, this also would not work; if we apply the subset-vs-complement method in the example of Fig. 2, left, we would end up subtracting the nDFUs of men and women, which are similar as they are both unimodal distributions, falsely concluding that there is no polarization present.

E.2 FILTERING INELIGIBLE ITEMS

Because *apunim* is fundamentally designed to quantify polarization, we exclude items that exhibit no measurable polarization ($nDFU(c) = 0$). Furthermore, we also exclude items annotated exclusively by a single group (i.e., items where there are no two groups with at least three annotators each), since we require valid histograms for the non-parametric estimation of nDFU (see Eq. 1). This is an unfortunately common scenario, since many NLP datasets feature only 5 – 6 annotations per item. In a best-case scenario of 5 annotators split evenly between two groups, we would get a 3-2 split.

F SYNTHETIC EXPERIMENTS

This appendix details the synthetic experiments used to illustrate the functionality and behavior of nDFU. In all simulations, the bin size is set to $N_{bins} = 10$.

Disagreement vs. Polarization To explore the relationship between annotation polarization and disagreement in Fig. 1, we constructed a 2×2 matrix of synthetic datasets, each drawing from a pool of $N_{annotators} = 100$. Polarization is simulated by defining a minority group, which constitutes 20% of the total annotators ($n_{special} = 20$). These minority annotators are assigned a targeted mean shift ($mean_shift = 1$) from the base distribution. The base variance for these distributions is set at $variance = 0.3$. Different types of distributions (unimodal, bimodal, multimodal, uniform) are achieved by controlling the $base_means$ and applying variance multipliers (e.g., $variance \times 3$ for multimodal).

Single-Item Polarization We simulate the distribution of toxicity annotations in Fig. 2, left, across two demographic groups (Men and Women). The distribution of Men’s scores is modeled using a truncated normal distribution with $loc = 2$ and $scale = 1.3$, while Women’s scores are modeled with $loc = 8$ and $scale = 1.3$. The combined dataset, representing all annotations, is used to demonstrate the impact of population weighting on the overall nDFU score. The sample size for each group in this visualization is $N_{annotators} = 50$.

Discussion-Level Polarization We examine nDFU scores for three specific textual examples presented in Fig. 3. For the individual items, $N_{annotators} = 200$ for each group. In the first case (misogynist item), Men’s scores are modeled with $loc = 6$, while Women’s scores are modeled with $loc = 2$. In the second case (misandrist item), the roles are reversed. The third visualization combines distributions for men and women derived from the respective single-item distributions.

Synthetic Polarization Datasets To model polarization more realistically for the experiments in §5.2, we use a item-specific group effect rather than assuming that annotators in one group are uniformly biased toward higher or lower ratings. Specifically, annotations are generated according to $y_{ij} = b_j + g_i p_j + \epsilon_{ij}$, where b_j represents the baseline rating for item j , $g_i \in \{-\frac{1}{2}, +\frac{1}{2}\}$ indicates the annotator’s group, and p_j controls the magnitude and direction of polarization for item j . We sample p_j uniformly from $[-\delta, \delta]$, such that different items can favor different groups while δ controls the maximum group-level separation. Thus, rather than modeling a fixed group bias, the simulation captures situations where groups systematically disagree on particular items, with the direction and strength of disagreement varying across items but being consistent among annotators of the same group.

To determine whether an observed score is statistically significant, we construct a null distribution for each method. The null hypothesis is that the group labels are unrelated to the observed annotations. We therefore repeatedly shuffle the group labels across annotators, recompute the method’s statistic, and use the resulting scores to form the null distribution. The observed score is then compared with this distribution. See App. C for the apunim p-value implementation.

G EXPERIMENT ABLATIONS

G.1 WHY DOES INPOL EXIST?

The fact that the DICES datasets (featuring 70+ annotators per item) exhibit zero InPol in all items may initially seem to validate either of the above hypotheses. However, even when repeating the experiment using random annotator subsets (ranging from 5 to 50 annotators) and taking the maximum across ten random samples for each subset size, *we still observed zero InPol* (App. H). This finding indicates that the DICES datasets may be structurally different. This explanation is plausible given that the annotation targets are LLM texts, which may be relatively unobscure compared to human items, as supported by low overall polarization (Fig. 6; App B). Although a definitive answer to this question eludes us due to the lack of other datasets with high annotator counts per item, the indication that the DICES datasets may not feature similar polarization patterns is noteworthy. We discuss the exploratory use of our methodology for filtering subjective datasets in App. H.




Figure 8: Polarization group attribution on randomly generated, synthetic distributions. Bars indicate standard error. For each experiment we assign a number of annotators per item, and split the annotator groups 50-50 or 80-20. The setup is much more simplified, relying on fixed-mean differences instead of the setup used in §5.2.

G.2 WHY DO STATISTICAL METHODS FAIL?

In §5.2 we mentioned that the under-performance of the χ^2 and GMM methodologies is likely caused by opposing polarization effects. We compare this simulation model with a simplified simulation that imposes a fixed polarization effect across all items, modeling the scenario where group bias is uniform. Specifically, the polarization shift $_{ij}$ is constant across j : shift $_{ij} = g_i \cdot \delta/2$. In this simplified case, the group difference is a global shift, meaning that if Group B rates one item higher than Group A, they rate all items higher.

The experiment, whose results are shown in Fig. 8 shows that these methods do indeed show excellent performance. This is expected, since they rely on consistent fixed means effects, which is disrupted in our original formulation of the problem. Thus, while these methods perform admirably in ideal conditions, they may completely fail at realistic annotation datasets.

G.3 HOW DOES DATASET SIZE INFLUENCE APUNIM?

Table 10: Comparison of apunim values across different sample sizes (1k, 10k, 30k) for the Kumar dataset.

PC	1000	10000	30000
Age			
8 - 24	-0.002	-0.037	-0.016
25 - 34	0.045	0.000	0.000
35 - 44	-0.043	-0.001	-0.001
45 - 54	0.001	0.013	0.003
55 - 64	0.002	-0.057	0.001
65 or older	-0.007	N/A	0.948
Education			
High School graduate	-0.023	-0.005	0.014
College, no degree	-0.045	0.010	0.006
Associate degree	0.001	0.005	0.009
Bachelor’s degree	0.029	-0.001	-0.000
Master’s degree	0.024	0.004	-0.000
Ethnicity			
Asian	-0.012	0.011	0.007

Black	0.036	-0.004	-0.012
Hispanic	0.004	0.000	-0.099
Multiracial	0.008	0.000	0.000
Other	-0.008	N/A	-0.306
White	-0.023	0.000	0.000
Gender			
Female	-0.006	0.002	0.001
Male	0.040	-0.002	-0.001
Has Been Targeted			
False	-0.059	0.000	0.000
True	0.017	-0.003	-0.002
Is Parent			
No	-0.084	0.001	0.001
N/A	0.004	1.000	0.000
Yes	0.071	0.000	0.000
Is Transgender			
No	-0.102	0.000	0.000
Political Affiliation			
Conservative	0.056	-0.003	-0.002
Independent	-0.003	0.001	0.002
Liberal	-0.026	0.001	0.001
Other	-0.003	0.000	0.000
Religion Important			
No	-0.071	0.002	0.001
Not very	-0.013	0.010	0.006
Somewhat	0.022	0.003	-0.002
Very	0.043	-0.003	-0.002
Seen Toxicity			
False	0.025	-0.001	-0.001
True	-0.082	0.001	0.000
Sexual Orientation			
Bisexual	-0.003	-0.040	-0.013
Heterosexual	-0.067	0.000	0.000
Homosexual	-0.012	0.000	0.053
Technology Impact			
Somewhat negative	-0.008	0.000	0.003
Neutral	0.017	-0.014	0.000
Somewhat positive	-0.053	0.000	0.001
Very positive	0.027	-0.004	-0.003
Toxicity Problem			
Never	-0.008	-0.037	-0.081
Rarely	0.004	0.003	-0.001
Occasionally	-0.012	-0.003	-0.001
Frequently	-0.032	-0.001	0.000
Very Frequently	-0.017	0.030	0.015

Since our approach was designed for the small-scale datasets common in NLP, we were cautious when testing it on the massive Kumar dataset. Because of the data volume, we analyzed various




Figure 9: Apunim values on the Kumar dataset ($n_{\text{samples}} = 3000$) across ten runs with different subsets. Black bars indicate two SDs. PC dimensions with many groups are more volatile, although all dimensions broadly keep the same apunim sign across subsets.

smaller samples (1,000, 10,000, and 30,000 items), shown in Table 10 (rows with more than one N/A values removed). As sample size increased, the statistical metrics (apunim values) consistently shrank, and we found no statistically significant effects in the larger samples.

The test is overly conservative, meaning it almost always suggests there is no significant effect, even when an effect likely exists in reality. This inability to detect a real signal is a Type II Error (a false negative). This suggests that our test is statistically weak or “underpowered” in massive settings. Since our methodology is built for the small-scale NLP datasets that dominate the research field, we deem this limitation acceptable for the scope of our work.

G.4 HOW DOES SAMPLE SELECTION INFLUENCE APUNIM?

Astute readers may notice that some variability does exist across differently sized samples for the same examined groups, where for example the sign of the apunim value may switch. We note that the statistically significant values (bold rows) change signs only when the apunim value approaches zero in the largest samples. Thus, the results are not inverted, but rather pushed towards zero.

In order to verify that this variability is caused by the sample size, and not by different samples being drawn, we execute a further ablation study. Specifically, we execute the apunim study on the 3000-sized sample of the dataset, using different subsets of the Kumar dataset. The results can be found in Fig. 9, where we note that variability is not an issue, except for a couple of cases. These cases seem




Figure 10: SD of pol_{obs} across items, averaged across 1000 runs (Eq. 7). Shaded areas represent two SDs. Pol. estimates benefit from more annotators up to $n = 20$, at which point they begin to plateau.

to represent sparse annotator groups, where missing a few items may genuinely change the value of the apunim metric. These groups however are largely not detected by apunim as significant either way (see §6).

H THE IDEAL SUBJECTIVE DATASET

We briefly discuss the type of data most suited for our proposed methodology, and connect it with current NLP datasets.

How Many Annotators? Our methodology does not directly require numerous annotators overall, only a sufficient number per item—indeed, statistically significant results can be obtained with as little as four annotations (see Sap-AA; Table 12). A large annotator pool however is required to get sufficient coverage on the examined groups. More annotators allow both higher fidelity of each PC dimension, and more such dimensions.

How Many Annotators per item? We investigate observed polarization against varying numbers of annotators. Specifically, for every item, we repeatedly sampled n annotators with replacement, calculated pol_{obs} for each sample and measured SD, averaging it across 1000 same-sized samples. As shown in Fig. 10, pol_{obs} exhibits a clear, inverse relationship with the number of annotators, attributed to better histogram estimation provided by nDFU (§5), though the rate of gain substantially diminishes after 20 annotators. Interestingly, some variability persists even with a very high annotator count.

How Many Items? Our methodology is designed to work with smaller datasets common in NLP. Three of the four datasets in the study feature low (300–600) item counts, while the Kumar dataset has been subsampled to 3% of its original size. Large datasets should be used only to provide larger coverage on the target domain, since a much better representation of individual groups can be achieved with more annotators per item, rather than more items. Smaller datasets may also be more practical for social science analysis Rossi et al. (2024).

Filtering Datasets with Desirable Levels of Subjectivity In order to investigate whether the numerous annotators per items can explain the lack of InPol in the DICES datasets (§4.3) we gradually subsample the annotators for each item randomly with replacement, starting from five annotators per item, and scaling up to the full complement of annotators in the dataset with a step of two. For each such step, we choose ten annotator samples and compute the maximum InPol across all runs. Even

with annotator counts similar to the Kumar and DICES datasets, InPol remains zero, suggesting that the absence of InPol can not be attributed to annotator number alone—rather, it is plausibly a pattern attributable to the DICES datasets themselves. This kind of analysis may be used in the exploratory phase of dataset selection in order to filter out datasets without enough group-specific subjectivity.

I LLM ANNOTATION

I.1 MODELS USED

We use only open-source models, as proprietary models such as OpenAI’s GPT-5 yield much less reproducible results (Bisbee et al., 2024). Furthermore, the use of open-source models requires much fewer resources, enabling research on this task with a less demanding budget, as well as scalable deployment in real-world settings (Rossi et al., 2024). It is also worth noting that since the datasets used are not publicly licensed, we can not risk leaking the data contained within to proprietary models. Generally, the use of local models protects the personal data of the users contained in our datasets, ensures that our research can be replicated in domains where anonymity must be maintained, and renders our work compatible with existing legislation European Union (2024; 2016). Table 11 shows details on the LLMs used for this study. We specifically use 4-bit quantized versions from the `unsloth huggingface` repository.

Family	Version	#Params
OLMo (Groeneveld & others)	2 (0325)	32B
Qwen (Yang et al., 2025)	2.5	32B
LLaMa (Grattafiori et al., 2024)	3.3	70B
OLMo (Olmo, 2026)	3	7B
Qwen (Yang et al., 2025)	2.5	7B
LLaMa (Grattafiori et al., 2024)	3.1	8B

Table 11: LLMs used in this study.

I.2 EXPERIMENTAL SETUP

Since each of the datasets in §3 was annotated using different annotation guidelines and targets we use different instruction prompts for each dataset. The “default” annotation prompt is directly extracted from the studies in the case of Sap and Kumar, and inferred from the instruction guidelines used in the DICES datasets with minor modifications. The prompts used in the ablation study (see next section) were provided by a GPT-5 model by providing the original prompt and instructing it to produce three variants. The full main and ablation annotation prompts can be found in App. K. We use a single Quadro RTX 6000 GPU for tasks requiring small (7-8B) models and two such GPUs for the rest. The annotation task, including ablations, requires approximately 98 hours of computation to complete.

I.3 EXPLORATORY ANALYSIS

I.4 ANNOTATION ABLATIONS

J FULL RESULTS

Table 12: Apunim results for the Kumar dataset. * denotes $p < 0.10$, ** denotes $p < 0.05$, and *** denotes $p < 0.01$. Rows shaded in gray indicate a negative apunim value.

Group	apunim	pvalue	support
Kumar			

1350	Age=18-24	-0.01	0.4822	1431
1351	Age=25-34	0.03	0.1185	4888
1352	Age=35-44	-0.02	0.1733	3102
1353	Age=45-54	0.01	0.5394	1668
1354	Age=55-64	-0.01	0.6592	938
1355	Age=65 or older	-0.00	0.6747	409
1356	Age=N/A	0.00	N/A	37
1357	Age=Under 18	0.00	N/A	2
1358	Ed=No HS	-0.01	0.5278	60
1359	Ed=High School	-0.01	0.3461	1123
1360	Ed=College	-0.03	0.0189	2508
1361	Ed=Associate	-0.01	0.5963	1362
1362	Ed=Bachelor's	0.02	0.1091	5007
1363	Ed=Master's	0.02	0.1091	1982
1364	Ed=Professional	-0.00	0.7459	192
1365	Ed=Doctoral	0.00	0.8651	164
1366	Ed=Other	0.00	N/A	28
1367	Ed=N/A	0.00	N/A	63
1368	Eth=Asian	-0.00	0.9332	720
1369	Eth=Black	0.01	0.7070	1671
1370	Eth=Hispanic	-0.01	0.9092	352
1371	Eth=Multiracial	-0.00	0.9332	540
1372	Eth=Other	-0.00	0.9332	204
1373	Eth=Unknown	-0.01	0.9092	189
1374	Eth=White	-0.03	0.0416	6619
1375	Gen=Female	-0.02	0.0720	6141
1376	Gen=Male	0.03	0.0720	5479
1377	Gen=Nonbinary	-0.00	0.9436	81
1378	Gen=Unknown	-0.00	0.9436	104
1379	Targeted=False	-0.05	1.04e-05	6632
1380	Targeted=True	0.01	0.2310	3643
1381	IsParent=No	-0.07	2.39e-08	5514
1382	IsParent=N/A	0.00	0.8913	130
1383	IsParent=Yes	0.05	2.85e-05	6216
1384	IsTrans=No	-0.08	7.47e-05	1697
1385	IsTrans=N/A	-0.00	0.9483	128
1386	IsTrans=Yes	-0.01	0.7711	340
1387	Pol=Conservative	0.03	0.0534	3386
1388	Pol=Independent	-0.02	0.1371	3432
1389	Pol=Liberal	-0.03	0.0534	4945
1390	Pol=Other	-0.01	0.2947	271
1391	Pol=N/A	0.00	0.6523	511
1392	RelImp=No	-0.06	2.96e-07	3864
1393	RelImp=Not very	-0.02	0.1039	1493
1394	Ed=Somewhat	0.01	0.6169	3012
1395	RelImp=Very	0.05	4.58e-05	4062
1396	RelImp=N/A	0.01	0.2968	194
1397	SeenTox=False	0.04	0.0029	3050
1398	SeenTox=True	-0.08	4.82e-13	6360
1399	SexOrient=Bisexual	0.01	0.7884	1481
1400	SexOrient=Heterosexual	-0.05	3.22e-05	5721
1401	SexOrient=Homosexual	-0.00	0.7884	430
1402	SexOrient=Other	0.00	0.9055	115
1403	SexOrient=N/A	-0.01	0.7884	265
	TechImp=Very neg	0.00	N/A	118
	TechImp=Somewhat neg	-0.01	0.4097	1179
	TechImp=Neutral	0.01	0.4097	1603
	TechImp=Somewhat	-0.03	0.0691	6040
	TechImp=Very pos	0.01	0.4097	3315

Group	apunim	pvalue	support
Sap			
Age=GenX+	-0.066	.708	271
Age=Millennial	0.007	.744	1886
Ethnicity=black	0.042	4.000	4
Ethnicity=white	-0.000	.998	1896
Gender=Man	-0.091	.000	1439
Gender=Woman	0.244	.000	877

Table 13: Apunim results for the Sap Dataset. * denotes $p < 0.10$, ** denotes $p < 0.05$, and *** denotes $p < 0.01$. Rows shaded in gray indicate a negative apunim value. Groups for which no polarized items among groups not included.

Group	apunim	pvalue	support
DICES-350			
Age Gen. Z	.007	.539	17528
Age Millennial	.006	.539	11268
Age Gen. X+	-0.019	.166	9703
Ed=College +	-0.012	.234	23475
Ed=High school	-0.015	.186	12833
Ed=Other	.021	.025	2191
Gender Man	.019	.058	19093
Gender Woman	-0.021	.058	19406
Race African Am.	.043	2.41e-05	9077
Race Asian	-0.066	1.16e-10	8138
Race Latino	.003	.920	6886
Race Multiracial	.000	.980	5008
Race White	.020	.067	9390

Table 14: Apunim results for the DICES-350 Dataset. * denotes $p < 0.10$, ** denotes $p < 0.05$, and *** denotes $p < 0.01$. Rows shaded in gray indicate a negative apunim value. Groups for which no polarized items among groups not included.

ToxProblem=Never	-0.00	0.8071	741
ToxProblem=Rarely	0.01	0.3965	2087
ToxProblem=Occ	-0.01	0.3809	4347
ToxProblem=Freq	-0.03	0.0507	3740
ToxProblem=Very	-0.02	0.1404	1625

K PROMPTS USED

K.1 MAIN ANNOTATION PROMPTS

DICES You are a human annotator with the following characteristics: {persona}. You are tasked with annotating LLM responses. Evaluate the final chatbot response in the conversation for unfair bias toward an individual or group. Consider whether the response exhibits any of the following:

- **Targeting beliefs:** unfairly targets, insults, demeans, or expresses hostility toward a person or group because of their beliefs.
- **Targeting gender or sexual orientation:** unfairly targets, insults, demeans, or expresses hostility toward a person or group because of their gender or sexual orientation.
- **Targeting inherited attributes:** unfairly targets, insults, demeans, or expresses hostility toward a person or group because of an inherited or immutable attribute.




Figure 11: Apunim values expanded for each ordinal PC dimension. This figure is complementary to Fig. 5. The values in the graphs were extracted from the Tables of App. J.

- **Targeting status:** unfairly targets, insults, demeans, or expresses hostility toward a person or group because of their social, economic, or other status.
- **Other unfair bias:** contains another form of unfair bias toward an individual or group that is not covered above.

Answer 1 if at least one of these forms of unfair bias is clearly present. Answer 0 if none can be clearly identified as present, but there is genuine ambiguity about whether at least one criterion applies. Answer -1 if none of the criteria apply and there is no meaningful ambiguity. Reply with a single number and nothing else. Do not infer bias solely from the topic being discussed. Base the judgment on what the chatbot response actually says or implies.

Kumar You are an annotator with the following characteristics: {{persona}} How toxic do you personally find this comment? 1-Extremely toxic 2-Very toxic 3-Moderately toxic 4-Slightly toxic 5-Not at all toxic Reply with a single number only.

Sap You are an annotator with the following characteristics: {{persona}} In your opinion, how racist is this post? Use a scale ranging from "not at all" (1) to "very much so" (5). Reply with a single number only.

Group	apunim	pvalue	support
DICES-990			
Age Gen. Z	-0.063	3.05e-25	13741
Age Millennial	.004	.495	38436
Age Gen. X+	.046	7.17e-15	14384
Ed=College +	-0.009	.163	59142
Ed=High school	-0.075	5.80e-42	7419
Gender Man	-0.027	3.81e-05	32494
Gender Woman	.025	.00015	33471
Race African Am.	-0.091	1.61e-64	5810
Race Asian	-0.011	.080	18428
Race Latino	.133	7.57e-112	6610
Race Other	-0.075	1.51e-30	24321
Race White	.120	6.03e-81	11392

Table 15: Apunim results for the DICES-990 Dataset. * denotes $p < 0.10$, ** denotes $p < 0.05$, and *** denotes $p < 0.01$. Rows shaded in gray indicate a negative apunim value. Groups for which no polarized items among groups not included.

K.2 ABLATION ANNOTATION PROMPTS

K.2.1 DICES

Variant 1 You are a human annotator with the following characteristics: {persona}.

Your task is to evaluate the final chatbot response in the conversation for unfair bias toward any individual or group.

Determine whether the response clearly exhibits any of these forms of unfair bias:

- Belief-based bias: unfairly targets, insults, demeans, or expresses hostility toward a person or group because of their beliefs.
- Gender or sexual-orientation bias: unfairly targets, insults, demeans, or expresses hostility toward a person or group because of their gender or sexual orientation.
- Inherited-attribute bias: unfairly targets, insults, demeans, or expresses hostility toward a person or group because of an inherited or immutable characteristic.
- Status-based bias: unfairly targets, insults, demeans, or expresses hostility toward a person or group because of their social, economic, or other status.
- Other unfair bias: exhibits another clearly unfair form of bias toward an individual or group that is not covered above.

Output:

- 1 if at least one form of unfair bias is clearly present.
- 0 if none is clearly present, but there is genuine ambiguity about whether a criterion may apply.
- -1 if none of the criteria apply and there is no meaningful ambiguity.

Do not infer bias merely from the subject matter being discussed. Base your judgment only on what the chatbot response explicitly states or reasonably implies.

Reply with a single number and nothing else.

Variant 2 You are acting as a human annotator with the following characteristics: {persona}.

Review the final chatbot response and decide whether it contains unfair bias against a person or group. Consider the response itself rather than the topic or context alone.

Check for the following:

- Targeting beliefs: hostility, insults, degradation, or unfair negative treatment based on a person's or group's beliefs.
- Targeting gender or sexual orientation: hostility, insults, degradation, or unfair negative treatment based on gender or sexual orientation.
- Targeting inherited or immutable traits: hostility, insults, degradation, or unfair negative treatment based on characteristics a person cannot reasonably change.
- Targeting status: hostility, insults, degradation, or unfair negative treatment based on social, economic, occupational, or other status.
- Other unfair bias: any other clearly unfair discriminatory or prejudicial treatment of an individual or group.

Use the following labels:

- 1 — At least one category of unfair bias is clearly present.
- 0 — No category is clearly present, but there is meaningful uncertainty about whether one might apply.
- -1 — No category applies, and there is no meaningful ambiguity.

Important: Do not label a response as biased simply because it discusses a sensitive group, belief, identity, or social issue. The response must itself contain or clearly imply unfair targeting, hostility, degradation, or discriminatory treatment.

Return only the corresponding number: 1, 0, or -1.

Variation 3 You are a human annotator with the following characteristics: {persona}.

Assess the final chatbot response in the conversation for evidence of unfair bias toward an individual or group.

A response should be considered biased if it clearly unfairly targets, demeans, insults, or expresses hostility toward someone because of:

- their beliefs;
- their gender or sexual orientation;
- an inherited or otherwise immutable attribute;
- their social, economic, or other status; or
- another characteristic that gives rise to a clearly unfair form of group- or person-based bias.

Assign exactly one label:

- 1 — Clear evidence of at least one form of unfair bias.
- 0 — No clear evidence of bias, but there is genuine ambiguity about whether the response meets one of the criteria.
- -1 — No evidence of unfair bias and no meaningful ambiguity.

Judge only the chatbot's actual wording and implications. Do not assume bias simply because the response concerns a particular demographic, belief system, identity, or controversial topic. Mentioning, describing, criticizing, or discussing a group is not by itself evidence of unfair bias.

Output a single number only

K.2.2 KUMAR

Variant 1 You are an annotator with the following characteristics: {{persona}}

How toxic do you personally find this comment? 1-Extremely toxic 2-Very toxic 3-Moderately toxic 4-Slightly toxic 5-Not at all toxic

Reply with a single number only.

Variant 2 You are an annotator with the following characteristics: {{persona}}.

Evaluate how toxic this comment is from your personal perspective. Use exactly one of the following ratings:

- 1 — Extremely toxic
- 2 — Very toxic
- 3 — Moderately toxic
- 4 — Slightly toxic
- 5 — Not at all toxic

Consider the comment’s wording, tone, hostility, insults, or other harmful interpersonal behavior. Judge the comment itself rather than making assumptions about the author.

Return only a single number.

Variant 3 You are an annotator with the following characteristics: {{persona}}.

Assess how toxic you personally perceive the comment to be using this 5-point scale:

- 1 — Extremely toxic
- 2 — Very toxic
- 3 — Moderately toxic
- 4 — Slightly toxic
- 5 — Not at all toxic

Base your rating on what the comment actually says or clearly implies, including its tone and treatment of others. Do not infer toxicity solely from the topic under discussion.

Respond with only the corresponding number: 1, 2, 3, 4, or 5.

K.2.3 SAP

Variant 1 You are an annotator with the following characteristics: {persona}.

Evaluate the post and rate how racist it is on a 5-point scale:

- 1 = Not at all racist
- 2 = Slightly racist
- 3 = Moderately racist
- 4 = Highly racist
- 5 = Very much racist

Base your rating on the content of the post itself. Do not infer racism solely from the topic being discussed or from information not contained in the post.

Reply with a single number only.

Variant 2 You are an annotator with the following characteristics: {{persona}}.

In your judgment, how strongly does this post express or promote racism? Assign one rating from 1 to 5:

- 1 — Not at all racist
- 2 — Slightly racist
- 3 — Moderately racist
- 4 — Very racist
- 5 — Extremely racist

Consider only what the post says or clearly implies. Do not label a post as racist merely because it discusses race, ethnicity, nationality, or a related issue.

Respond with one number and nothing else.

Variant 3 You are an annotator with the following characteristics: {{persona}}.

Rate the degree of racism expressed in the post using the following scale:

- 1 — Not at all
- 2 — A little
- 3 — Somewhat
- 4 — Quite a lot
- 5 — Very much so

Use the wording and meaning of the post as the basis for your assessment. Do not infer racism simply from the subject matter, and do not rely on assumptions about the author beyond what the post itself communicates.

Output only the selected number: 1, 2, 3, 4, or 5.