Quantifying and Auditing Group-Based Disagreement in Human and LLM Annotation

ANONYMOUS AUTHOR(S)

LLM annotation is increasingly used as a scalable substitute for human annotations, including in polarized, subjective tasks where humans systematically disagree along group lines. Whether these systems reproduce, ignore, or distort human disagreement patterns is largely untested, in part because most existing methods for attributing Systematic Disagreement (SysDis) have not yet been tested in realistic, subjective annotation settings. This work represents the first empirical study which applies proposed, theoretical methods on large scale, realistic annotation settings. Observing the weaknesses of these methods, we develop a method that not only detects, but also quantifies attribution of SysDis to annotator sociodemographic SocioDemographic Dimensions (SDDs) and use it to audit nine open-source LLMs against five real-life datasets on subjective Natural Language Processing (NLP) tasks. Our results show that while persona-prompted LLMs can produce polarized annotations, the exhibited disagreement patterns are not aligned with those of human annotator SDDs, even when tuning instruction prompts for this purpose. This limitation indicates that applications, studies and resources using persona prompting should include appropriate scoping and evaluation in order to avoid further model miscalibration. Our study also suggests that the structure of current subjective NLP datasets is insufficient, requiring more annotators per item, as we find that not all SysDis can be attributed to any combination of known or latent annotator SDDs.

CCS Concepts: • **Computing methodologies** → **Natural language processing**; **Unsupervised learning**; Language resources; • **Human-centered computing** → **Empirical studies in collaborative and social computing**; • **Social and professional topics** → *Race and ethnicity*; *Gender*; Sexual orientation; Age.

Additional Key Words and Phrases: Polarization, Clustering, Annotation, Sociodemographic Characteristics, Persona-Prompting

ACM Reference Format:

Anonymous Author(s). 2026. Quantifying and Auditing Group-Based Disagreement in Human and LLM Annotation. 1, 1 (October 2026), 69 pages. https://doi.org/10.1145/nnnnnnn.nnnnnnn

1 Introduction

The rise of internet spaces has necessitated research in subjective phenomena such as the detection of harmful content. Annotations are needed to support social science research, the training of automated classifiers and the proactive identification of vulnerable groups [67]. These annotations are frequently released as datasets, which due to their subjective nature typically contain items with very low Inter-Annotator Agreement (IAA) [67]. If ignored, this disagreement may lead to loss of valuable information [48] and provide us with the wrong signal, leading to significant misconfiguration in trained AI systems [65]. For example, toxicity models have disproportionately marked African American (AA) speech as "toxic" [56], or systematically ignored minority opinions [51] in the past.

In practice, researchers usually use IAA measures to distinguish between general and Systematic Disagreement (SysDis) (Fig. 1). Traditional measures however hold significant limitations, especially when few annotations per item are available and when the studied SocioDemographic Dimensions (SDDs) contain imbalanced groups. Both of these issues are

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
© 2026 Copyright held by the owner/author(s). Publication rights licensed to ACM.
Manuscript submitted to ACM




Fig. 1. Simulated experiment exploring four scenarios of a Hate Speech (HS) detection task applied to a controversial statement. The variance in annotations across different annotators may cause traditional Inter-Annotator Agreement (IAA) measures to ignore minority opinions, especially when opinions are mixed (top-right).

typically present in subjective tasks featuring minorities, which is the exact case where our measures should be reliable. Furthermore, as human annotation is generally expensive, LLM-as-judge systems are increasingly deployed as scalable substitutes for human annotators [29, 54] to acquire a cheaper, "bronze" supervision signal in place of human-annotated "silver" or "gold" labels. It is therefore imperative that SysDis by human annotators be preserved by LLMs whose annotations by default gravitate toward the statistical average [6]. Persona-prompting is sometimes used to bypass this limitation, but suffers from its own challenges such as stereotyping and inconsistent annotations [37, 39]. We therefore ask:

RQ 1: *How Do Current Theoretical Polarization Attribution Approaches Behave in Realistic Annotation Scenarios*? Our work is the first empirical study applying measures of polarization detection and attribution in real-life subjective datasets. We find that these theoretical models tend to collapse, while IAA underperforms. One of the reasons for this collapse is likely the assumption that annotations can be aggregated across items (Finding 1).

RQ 2: *How Can SysDis be Quantitatively Attributed to Annotator SDDs*? We introduce a new measure which *quantitatively* attributes SysDis to specific SDDs, while being conscious of the limitations present in realistic annotation scenarios (Fig. 2).

RQ 3: *Which SysDis Patterns are Shared Between Human and LLM Annotators*? Unlike prior work which framed the question of LLM annotation reliability in terms of human-LLM agreement [13, 20, 40] or task-specific performance [25], we compare human and LLM polarization patterns. We find that human SysDis is attributed to gender and ethnicity across five real-life subjective datasets (Finding 2). On the other hand, while LLMs using persona-prompting *can* produce polarized annotations, they fail to reproduce any SysDis patterns regardless of instruction prompt, confirming literature suggesting that persona prompting does not consistently influence LLM outputs in the examined tasks (Finding 3).

Overall, our work indicates that persona-prompting requires extensive evaluation and careful scoping as it may compromise sensitive applications (e.g., content moderation, facilitation), contaminate LLM training and lead to misleading findings in social science research . It also argues for a paradigm shift in the design and construction of subjective datasets; the true limit in current datasets should not the number of annotated items, but rather the number of annotations per item (§6). Indeed, we find the existence of "Unnatributtable Polarization (UnPol)" which can not be explained by any possible combination of SDDs known or unknown, and likely stems from annotation sparsity on the item level (Finding 4).

Finally, we release a PyPI library implementing our measure to aid future research in this topic. All code, environment details, data-processing scripts and our library are released anonymously: library https://anonymous.4open.science/r/apunim-5F70, HTML documentation https://anonymous.4open.science/r/apunim-page, replication code https://anonymous.4open.science/r/aposteriori-unimodality-E8C1.

Content Warning: Controversial and potentially harmful speech used for demonstration purposes only.

2 Background and Related Work

Terminology. We distinguish three definitions used throughout this work: (1) **Disagreement** represents any variance among annotators' ratings for the same item, regardless of its source. (2) **SysDis** is non-random and recurring disagreement, which in this work is assumed to be caused by differences in group identity (e.g., background, cultural context, ideology). (3) **Polarization** is the underlying societal phenomenon describing genuinely conflicting, opposed viewpoints on the same item. Specifically, we attempt to find *polarized* SDDs through the distinction of *SysDis* from general *disagreement* in annotations.

Inter-Annotator Agreement. Current research on analyzing subjective tasks mostly rests on using IAA between groups of a single annotator SDD [27, 31, 35, 43, 64, 66], as prior work has shown that consistent, SysDis may be caused by different points-of-view between groups [21, 43, 65]. IAA measures such as Cohen's kappa, Krippendorff's alpha, and Fleiss's kappa aim to distinguish genuine disagreement from random disagreement through statistical chance-correction. However, these measures are often difficult to apply to intergroup IAA without extensions or restrictive assumptions (e.g., no missing labels or equal numbers of annotations). They have also been criticized for failing to account for differences arising from social, cultural, and demographic backgrounds [7, 8, 16, 66], producing results that are difficult to compare across studies, being sensitive to class imbalance [16], and relying on questionable assumptions about chance agreement [8]. While recent work has addressed some of these limitations with methods that improve applicability and robustness [27, 66, 72], they are much more complex and less intuitive, indicating that IAA may not be the correct tool for analysis of minority viewpoints. Ultimately, IAA analysis may be useful for exploration and identification of some controversial items, but fails to explain the reason *why* they are controversial [1, 68].

Polarization. There are many competing formulations for estimating polarization besides IAA. One [2] utilizes χ^2 to estimate in-group vs out-group variance. Others frame SysDis as a cluster identification problem, applying either parametric (GMM) [8], or non-parametric [42, 48] approaches to the annotation histograms. For our work, we use a non-parametric disagreement measure, normalized Distance From Unimodality (nDFU), which has been shown to correlate better with human judgment of disagreement than established measures [48], although we compare prior approaches in Fig. 2. nDFU (Eq. 1) takes values in the range $[0, 1]$, where values close to 0 indicate no polarization (i.e., opinions are concentrated around a single mode). Intuitively, nDFU measures how prominent secondary peaks are

compared to the main peak. The A Posteriori Unimodality (AU) method [48] builds upon nDFU stating that if a single item's annotations are multimodal, but unimodal for all annotator subgroups in a specific SDD, then polarization is explained by those groups. Though promising, this mechanism operates on the assumption that *all* polarization can be explained by a single split, which we prove to be impossible in many realistic cases (§6).

$$\text{nDFU}(X) = \frac{\max_{i \neq m} \left(f_i - \begin{cases} f_{i-1}, & \text{if } i > m \\ f_{i+1}, & \text{if } i < m \end{cases} \right)}{f_m}, m = \arg\max_i f_i \quad (1)$$

where, X denotes the set of annotations, f_i the relative frequency of the i-th annotation (e.g., the frequency of 2 in a scale of 1–5), and m the histogram peak.

Persona Prompting. At the time of writing, there is no established taxonomy of persona prompting techniques. Generally, personas may be (1) authored by hand [41, 76], (2) generated using observed annotator attributes [3], (3) composed of answers to extensive questionnaires [47], or recently, (4) generated entirely using LLMs [60]. The prompt itself may be structured [46, 70, 75] or described through natural language [36, 60, 76]. The effects of these methods on LLMs have not yet been studied and are largely outside the scope of this work. Since our goal is to explore disagreement patterns across LLMs and humans (RQ 3), we select attributes from the human annotators of each dataset, described by a structured field of attributes, in order to facilitate comparisons across experimental conditions.

Persona Reliability. Prior work suggests that LLMs are not necessarily reliable annotators when prompted with personas, as they tend to reproduce stereotypes [37, 39] and perform unreliably for minority groups [29, 39]. To address subjectivity in annotation, several Natural Language Processing (NLP) approaches incorporate annotator metadata into LLM annotation [12, 17, 24, 55], although evidence suggests that such improvements may be specific to the datasets on which models are trained [34]. A significant limitation is the requirement for annotator metadata, which can be side-stepped through embedding clustering [69], at greater computational cost and harder evaluation. We instead posit that directly clustering the annotations provides a comparatively simpler and more interpretable mechanism.

3 Datasets

Table 1. Datasets used in this study. *#Ann* refers to the number of annotators per item, while the *Guidelines* column describers whether annotation guidelines are provided in the publication introducing the dataset. **#SDDs** refers to the number of SDDs (e.g., age, gender, education).

Dataset	#Items	#Ann	#SDDs	Text Source	Task	Guidelines
Kumar [32]	1000	5	10	Twitter, Reddit, 4chan	Toxicity	Yes
Sap [57]	585	5–6	3	Twitter	Hate Speech	No
DICES-350 [4]	350	123	4	LLM responses	Hate Speech	No
DICES-990 [4]	990	70–76	4	LLM responses	Hate Speech	No
POPQUORN [49]	1500	7–9	5	Reddit	Hate Speech	Yes

Finding appropriate subjective datasets to test LLMs on is difficult for many reasons: (1) very few include annotator metadata [69], (2) most include only three annotators per item (e.g., [11, 33, 44, 62, 63]), (3) many datasets are sampled from the same source, negatively impacting the breadth of possible generalizable findings [67], and (4) annotation

guidelines are frequently not included [67], complicating replication. Additionally, meta-studies on subjective datasets [50, 67] do not give special importance to the sparsity of annotations per item, which is an important consideration; we highlight the extent of this problem and discuss possible solutions in §6. Nevertheless, given the current state of research, we aim to provide a methodology that can adapt to this challenging environment. We use five datasets from current NLP research that contain SDD information at the level of individual annotators:

- The *Kumar* dataset [32] which contains annotations for Toxicity detection.
- The *Sap* "Breadth of Posts" dataset with the "*toyou*" labels [57] for Hate Speech (HS) detection.
- The *DICES-350* (*Q3_bias_targeting_inherited_attributes* label) and *DICES-990* (*Q3_bias_incites_hatred* label) datasets [4], which pertain to LLM response safety. Our choice of labels allows us to use them as HS datasets, capturing conceptually similar SDDs despite the lack of shared labels between them. There is little-to-not information around these labels, since neither a description nor annotation guidelines are provided.
- The POPQUORN [49] dataset using the *"offensiveness"* label for HS detection.[1]

A brief overview of the dataset characteristics is provided in Table 1. The Kumar dataset is notable for its large scale, featuring over 100,000 annotated items and 10 distinct SDDs. In contrast, the DICES datasets have fewer annotated items but involve more than an order of magnitude more annotators per item than the others. The POPQUORN dataset presents both a modest number of annotators per item (7-9) and items. In order to allow for a full comparison between human and LLM annotations, we use a sample of 1,000 items from the Kumar dataset (§5.3). An exploratory analysis of these datasets is available in App. B,

4 Empirically Testing Proposed Methods

4.1 On Synthetic Data

Experimental Setup. We compare the effectiveness of our method (introduced in §5), the AU framework proposed by Pavlopoulos and Likas [48], the χ^2 method presented in Akhtar et al. [2], GMM clustering used in Checco et al. [8], and a baseline using IAA ($\Delta\alpha$ Krippendorff) on simulated distributions (App. E.1 for details and assumptions). To determine whether a score is statistically significant, we construct a null distribution for each method with the null hypothesis that the group labels are unrelated to the observed annotations. We therefore repeatedly shuffle the labels across annotators, recompute the method's statistic, and use the resulting scores to form the null distribution. Since we construct the distributions, we have knowledge of the *ground-truth* for which SDD is causing polarization (which is not the case for real-life or LLM annotations), which we can inject to test whether it is retrieved by each method.

Conditions. Annotations are generated according to $y_{ij} = b_j + g_i p_j + \epsilon_{ij}$, where b_j is the baseline rating for item j, $g_i \in \{-\frac{1}{2}, +\frac{1}{2}\}$ indicates the annotator's group, p_j controls the magnitude and direction of SysDis for item j, and ϵ_{ij} is annotation noise. We use two simulation setups that differ only in how p_j is defined: (1) **Unidirectional**: $p_j \sim \text{Uniform}(0, \delta)$. The group effect always favors the same group across all items, though its magnitude varies per item. (2) **Bidirectional**: $p_j \sim \text{Uniform}(-\delta, +\delta)$. The direction of the group effect can vary across items, so that groups may systematically disagree in opposite directions on different items.

[1]While "politeness" labels are included, they may not directly translate to toxicity; comments can simultaneously be toxic and phrased politely. Indeed, toxicity is not mentioned in the methodology of the original POPQUORN dataset and is considered a separate NLP task in other work [38, 77].




Fig. 2. SysDis attribution on synthetic distributions. When SysDis exists, the mean of the normal distributions shifts according to the value of the x-axis. The y-axis shows the accuracy of each method when attempting to recover the (known) SDD causing polarization. Bars indicate standard error. Dashed lines show the results of a simplified experimental setup, where disagreement always has the same direction.

Results. As shown in Fig. 2, *both the χ^2 and GMM methods generally fail* at attributing SysDis to any group. IAA remains usable when many annotators are available, but underperforms in cases where the examined group is a minority and when a few annotators are available per item (a common case among NLP datasets—see §3).[2]

4.2 On Real Data

Table 2 shows a comparison between the different methods when applied to the five datasets introduced in §3. The GMM method is not run, as it requires the exact same annotators to annotate the items in each dataset, which is not the case for any of our datasets. This limitation makes the test extremely restrictive in realistic annotation settings. We explain our own method in §5, as the focus of this experiment is the behavior of other measures on real data.

We find that the AU method completely fails to attribute polarization to any SDD, while the χ^2 method attributes it to every single one. The latter can be explained by the assumptions made by the test; namely that annotations can be pooled across items (discussed in the next section), as well as the power of the test which inflates p-values when the number of observations is large enough. Out of all prior methodologies, IAA using Krippendorff's α seems to be the only way of obtaining any results for only a subset of datasets.

[2]While this figure explores a case with only two groups, ablations with $k = \{3, 5, 10\}$ groups per SDD can be found in App. E.2; Fig. 7.

Table 2. Statistical significance of each SDD feature per method. ✓: significant at $p < 0.05$ after Bonferroni correction across the features of the dataset; ×: not significant.

	DICES-350				DICES-990				Sap et al. 2022			Kumar et al. 2021												POPQUORN				
SDD	Age	Education	Gender	Race	Age	Education	Gender	Race	Age	Ethnicity	Gender	Age	Education	Ethnicity	Gender	Has Been Targeted	Is Parent	Is Transgender	Political Affiliation	Religion Important	Seen Toxicity	Sexual Orientation	Technology Impact	Toxicity Problem	Age	Education	Gender	Occupation	Race
apunim (ours)	×	✓	×	✓	✓	✓	✓	✓	✓	×	✓	×	×	×	×	×	×	×	×	×	×	×	×	×	×	✓	×	×	✓
Krippendorff $\Delta\alpha$	×	×	✓	✓	×	✓	✓	×	×	×	✓	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×
AU	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×
χ^2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	×	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓




Fig. 3. Synthetic experiment showing two comments with annotators disagreeing about which one is toxic. Instead of comparing two unimodal distributions (comments viewed separately) with two bimodal distributions (their aggregated annotations), we end up comparing two bimodal distributions during aggregation, obscuring the source of the polarization (explained by gender, but not shown).

4.3 The Issue of Inter-Item Annotation Aggregation

In Fig. 2 we observed that the simple statistical approaches show excellent performance when all groups are polarized in the same way. This is expected, since their assumption of a consistent, fixed means effects, is violated in the second experimental setup. Specifically, both χ^2 and GMM aggregate across items before looking for group differences; χ^2 pools all annotations into a single contingency table, while GMM clusters annotators by their mean rating across items. In both cases, opposite-direction effects (see Fig. 3) cancel out in the aggregate, making the two groups appear statistically indistinguishable. We can confirm the persistence of this issue using nDFU [48], which is another representation of polarization (Eq. 1) in Fig. 3, which shows that two items polarized for the opposite reason may lead to a false negative. We avoid this issue in §5 by computing annotation statistics item-by-item.

Finding 1. *Current methodologies attributing SysDis generally fail in realistic annotation conditions. One of the reasons is that disagreements may conflict across items, which may compromise cross-item annotation aggregation.*

5 Comparing Human and LLM Polarization

5.1 Quantifying Attribution to Annotator Dimensions

We estimate polarization using nDFU (see §2; Eq. 2). Specifically, we measure the unimodality of each group g for an item c as $Pol_g(c) = nDFU(A_g(c))$, where $A_g(c)$ is the set of annotations for item c created by annotators belonging to a group g. We compare this quantity to the "apriori" polarization present in the item c, which is defined as the *expected* (average) unimodality of theoretical groups $\text{Pol}_{apr}(c) = \frac{1}{k}\sum_1^k \text{nDFU}(A_{random}(c))$, where A_{random} is a random split and k is a hyperparameter (higher k yields more accurate estimation, at a greater computational cost). Intuitively, a high $\text{Pol}_{apr}(c)$ score means that much of the polarization is likely not driven by any single group.

Since the $\text{Pol}_{apr}(c)$ and $Pol_g(c)$ quantities represent very noisy estimates due to the lack of annotators per item, a direct comparison would not be reliable. We therefore exploit the Law of Large Numbers to compute the statistic on the dataset level and average both quantities for all items in the dataset D. Normalizing this difference yields the measure described in Eq. 1, which we call *apunim*:

$$apunim(D, g) = \frac{\mathbb{E}_{c\in D}\left[\text{Pol}_{apr}(c)\right] - \mathbb{E}_{c\in D}\left[Pol_g(c)\right]}{1 - \mathbb{E}_{c\in D}\left[\text{Pol}_{apr}(c)\right]} \tag{2}$$

The *sign* of apunim carries information agreement-based attribution does not:

- $apunim(g) \approx 0$: The group g does not meaningfully disagree with the other annotators.
- $apunim(g) > 0$: The group g has fundamental disagreements with the other annotators.
- $apunim(g) < 0$: The annotators of group g are polarized between themselves.

Apunim thus measures the degree to which an annotator group contributes to overall polarization in a set of items. As demonstrated in §4; Fig. 2, our measure is robust to the number of annotators per item, opposing SysDis effects, and minority groups, validating our initial motivation. Furthermore, unlike some prior methods [2, 8], apunim allows us to attribute SysDis to a specific group, not just a SDD (e.g., only "men" instead of "gender" as a whole), allowing fine-grained analysis. We include a perturbation-based p-value estimation, which tests whether the observed apunim value of a group g statistically surpasses that of random groups in App. C.1 and analyze theoretical design decisions, limitations and computational details in App. C.3.

5.2 How Are Humans Polarized?

Experimental Setup. Assuming a confidence level of $\alpha = 0.05$ we test whether any of the provided SDDs can explain the SysDis shown in the five datasets (§3). Statistically significant results are presented in Table 3.[3] Note that our analysis is necessarily uni-dimensional due to the lack of annotation meta-data. App. E.2; Fig. 9 shows that our results are *robust to small annotator counts*, corroborating the synthetic experiments in Fig. 2. See App. C.2 for details on parameters and execution times and App. G for the full results.

Results. SysDis is consistently attributed to ***ethnicity*** across all datasets excluding DICES-330, confirming prior work suggesting that it is a systematic source of annotator disagreement in HS tasks [21]. Additionally, in both DICES-990, Sap and POPQUORN, SysDis is attributed to **gender**, which is consistent with previous findings [5, 71]. None of the

[3]The results are not necessarily contingent on a reliable p-value estimation, as non-statistically significant results have very low (< 0.01) apunim values. A threshold on the apunim values would produce similar tables.

Table 3. Statistically significant ($p < 0.05$) apunim results across the Sap and DICES datasets. Gray rows show Ethnicity and Gender groups. "Support" refers to number of annotations. Consult App. G for the full results.

Group	Apunim	Support
DICES-990		
Ethnicity=AfricanAm	0.0995	5148
Ethnicity=Latino	-0.0631	5877
Ethnicity=Other	0.0340	21669
Ethnicity=White	-0.0649	10166
Gender=Man	0.0359	28817
Gender=Woman	-0.0271	29990
Age=GenZ	0.0469	12214
Age=Millennial	-0.0068	34433
Age=GenX+	-0.0282	12699
Education=College	0.0063	52727
Education=High school	-0.0500	6619
DICES-350		
Ethnicity=AfricanAm	-0.0366	7627
Ethnicity=Asian	0.0445	6838
Education=Other	-0.0230	1841
Sap		
Gender=Man	-0.1508	1254
Gender=Woman	0.2613	693
Age=GenX+	-0.1670	223
POPQUORN		
Gender=Man	0.0081	2720
Race=Black	-0.1572	222
Education=College	0.0496	2388
Education=Graduate	-0.0808	468

Table 4. Mean (SE) per-comment nDFU of the human annotations and of the LLM annotations under the default prompt, per dataset and pooled over all datasets (All). n is the number of comments. Excluding the following models: llama8b, olmo7b, qwen7b.

	Sap et al. 2022		Kumar et al. 2021		POPQUORN		All	
Model	n	Mean (SE)	n	Mean (SE)	n	Mean (SE)	n	Mean (SE)
Human	585	0.38 (0.01)	1000	0.42 (0.01)	1500	0.31 (0.01)	3085	0.36 (0.00)
olmo32b	585	0.24 (0.01)	1000	0.51 (0.01)	1500	0.50 (0.01)	3085	0.45 (0.01)
qwen32b	585	0.18 (0.01)	1000	0.19 (0.01)	1499	0.20 (0.01)	3084	0.19 (0.00)
mistral7b	585	0.21 (0.01)	1000	0.37 (0.01)	1500	0.40 (0.01)	3085	0.35 (0.01)
mistral24b	585	0.25 (0.01)	1000	0.25 (0.01)	1500	0.23 (0.01)	3085	0.24 (0.00)
gemma7b	585	0.19 (0.01)	1000	0.22 (0.01)	1500	0.12 (0.01)	3085	0.17 (0.00)
gemma31b	585	0.04 (0.01)	1000	0.09 (0.01)	1500	0.05 (0.00)	3085	0.06 (0.00)

SDDs in the Kumar dataset show statistically significant values, but this is expected, since our methodology requires at least six annotators per item to work reliably.[4]

Finding 2. *Ethnicity and gender are consistent causes of SysDis, confirming prior literature on Toxicity and HS tasks.*

5.3 How Are LLMs Polarized?

Experimental Procedure. We investigate nine open-source LLMs (three not shown in main results because of prompt sensitivity issues) using twenty annotators for the Kumar, Sap and POPQUORN datasets supplied with personas sampled from our human dataset.[5] We also do not annotate the DICES datasets since the LLM annotations are wildly inconsistent

[4]Note that AAs show differently signed apunim values in the two DICES datasets, which may be attributed to these datasets using different labels (see §3) and because different ethnic group splits are considered in each dataset. Thus, while detection is constant across the two datasets, attribution is not. Additionally, men are a consistent source of SysDis (positive values), while women disagree among themselves (positive values) in DICES-990 and POPQUORN, but the opposite is true for Sap. Unfortunately we can not diagnose these discrepancies, since neither DICES nor Sap include annotation guidelines (Table 1).

[5]While LLM annotation can be scaled to be arbitrarily large, the choice of twenty annotators is a compromise between practical computation costs and enough annotation density to facilitate exploration. Results including the unreliable models can be found in App. G; Tables 29,30.

Table 5. Cohen's d between the default and each adversarial instruction prompt, computed on the per-comment nDFU. Rows give results per model, for each dataset separately and as the unweighted mean over datasets (All); *n* is the number of comments. Excluding the following models: llama8b, olmo7b, qwen7b.

Model	Dataset	n	Stereotype	Persona	Single	Direct
olmo32b	All	3085	-0.09	-0.02	0.01	-0.15
	Sap et al. 2022	585	0.09	0.06	0.22	0.04
	Kumar et al. 2021	1000	0.14	-0.13	-0.29	-0.31
	POPQUORN	1500	-0.50	-0.00	0.10	-0.19
qwen32b	All	3084	0.25	0.22	0.22	0.19
	Sap et al. 2022	585	0.32	0.13	-0.09	0.09
	Kumar et al. 2021	1000	0.17	0.21	0.51	0.31
	POPQUORN	1499	0.26	0.30	0.24	0.17
mistral7b	All	3085	0.13	0.03	0.10	0.05
	Sap et al. 2022	585	0.21	0.10	0.08	0.57
	Kumar et al. 2021	1000	0.07	-0.01	-0.10	-0.05
	POPQUORN	1500	0.12	0.02	0.33	-0.36
mistral24b	All	3085	0.72	0.40	-0.16	0.12
	Sap et al. 2022	585	0.64	0.04	-0.76	0.27
	Kumar et al. 2021	1000	0.98	0.97	0.57	-0.25
	POPQUORN	1500	0.55	0.20	-0.30	0.35
gemma7b	All	3085	0.20	0.32	0.39	0.23
	Sap et al. 2022	585	0.18	0.48	0.57	0.15
	Kumar et al. 2021	1000	0.10	-0.08	-0.40	-0.07
	POPQUORN	1500	0.34	0.54	0.99	0.63
gemma31b	All	2085	0.42	0.31	0.00	0.63
	Sap et al. 2022	585	0.36	0.21	0.06	1.03
	POPQUORN	1500	0.47	0.40	-0.06	0.23

Table 6. Statistically significant ($p < 0.05$) SDDs of each LLM compared with the human annotations, per dataset. A dimension counts as significant if at least one of its groups is. Each cell shows one symbol per prompt, in the order default, stereotype, persona, single, direct: ✓ the LLM and the human annotations agree (both significant, with the same sign for every group that is significant in both, or neither significant), × they disagree on significance (significant for only one of the two), ± both are significant but the sign of at least one group's effect differs; blank: no LLM result. Excluding the following models: llama8b, olmo7b, qwen7b.

Ds	SDD	olmo32b	qwen32b	mistral7b	mistral24b	gemma7b	gemma31b
Sap	Age	✓ ✓ ✓ × ✓	± ± ± ± ±	± ✓ ± × ±	± ✓ ± ✓ ±	× × ± × ✓	✓ ✓ ✓ ± ±
	Ethnicity	✓ ✓ × ✓ ×	× × × × ×	× × × × ×	× × ✓ × ×	× × × × ×	× × × × ×
	Gender	× × × × ×	× ✓ × × ±	× ✓ ✓ × ×	± ✓ ✓ ✓ ±	× × ± × ±	× × × × ✓
POP	Age	× × ✓ × ×	× × × × ×	× × × × ×	× × × × ×	× × × × ×	× × × × ✓
	Education	± ± ✓ ± ±	± ± ± ± ±	± ± ± ✓ ±	✓ ± ± ± ±	± × ✓ ± ±	× ± ± × ×
	Gender	✓ ✓ ✓ ✓ ×	✓ × × × ×	× ✓ × ✓ ×	× × × × ×	× × × × ×	× × × × ×
	Occupation	× × ± ✓ ✓	✓ ± ✓ × ×	✓ ✓ ✓ ✓ ✓	✓ ✓ ± ± ±	± ✓ ✓ ✓ ×	× × ✓ × ×
	Race	✓ × ± ± ✓	✓ ± ± ± ✓	✓ ± ± ✓ ✓	✓ ± ✓ ✓ ±	✓ ✓ ± ✓ ±	✓ ± ± ± ±

(App. F; Table 16), an issue we can not fix as their original annotation guidelines are not public (Table 1). Four adversarial prompts are used, which emphasize the importance of the LLMs' personas in different ways (App. H).

We ensure that our LLM annotation study is reproducible by selecting exclusively open-source, locally hosted models and fixing all relevant seeds. An ablation study where we repeat annotations multiple times shows that our setup achieves 100% consistency across all models. In order to ensure that the LLM annotators are not influenced by minute differences in the prompts, we execute a second ablation study where we rephrase the main annotation prompt three times and compare outputs. This procedure revealed that three models were especially sensitive to such changes (App. F; Table 16), which led us to exclude those models from the analysis presented in this manuscript. See App. F for the ablation experimental procedure, full results, model details, dataset selection, exploratory analysis, and comparison to human annotations. We use a parametric test (ANOVA) in our analysis due to the abundance of observations ($N \gg 100$) as well as a multiple hypothesis p-value correction ("Holm-Bonferroni" [26]).

Do LLMs Exhibit SysDis? **Yes**. Table 4 shows that the nDFU values exhibited by LLMs when under standard persona prompting can even surpass those of humans. However, manipulating the amount of SysDis through instruction prompting is not reliable. While an ANOVA test shows that the choice of instruction prompt does indeed affect nDFU scores across most models, measuring Cohen's d (Table 5) shows that the effect is generally small ($|d| \leq 0.3$) and inconsistent, with the sign and magnitude of the effect depending on the model and dataset.[6]

Is the Exhibited SysDis Aligned With Humans? **No**. Table 6 shows that alignment on SysDis between humans and LLMs is rarely achieved. Specifically, we observe: (1) Low Precision: LLMs tend to produce polarized annotations for groups whose human annotators are not. (2) Low Recall: LLMs under-detect where humans find real effects, especially in Sap and POP Gender. (3) Where SysDis matches, the direction does not (POP; Race, Education). (4) Where replication is achieved, it is generally on null results (e.g., *Mistral-7B*). We also find no connection between model size and family on the alignment of SysDis.

Finding 3. *While persona-prompted LLMs can produce polarized annotations, they can not replicate human polarization patterns, even when we attempt to align them using prompting.*

5.4 What Does This Mean for LLM Annotation?

Our results may indicate that LLMs do not intrinsically capture the differences in opinion between human groups, or miscalculate the degree that each SDD characteristic influences human opinion. Our study thus joins a growing number of work questioning the capabilities of persona-prompting [37, 39] and the limitations of LLMs in creating data for subjective social science tasks [29, 54, 73]. While persona-prompting meaningfully increases the variance (here, disagreement) of LLM annotations, as argued in prior work [19], the direction of this variance is inconsistent.

This limitation would indicate the need for careful evaluation and calibration of LLM outputs on sensitive applications such as content moderation [10] and facilitation [30], which so far assume that LLMs can be used as autonomous agents. It also may indicate that research focusing on improving annotation diversity through persona prompting [18, 19] may lead to meaningless or miscalibrated data when applied outside of specific annotation scenarios with limited scope. Finally, there is a general concern that LLMs training on biased LLM-generated data may amplify already-existing biases [53, 59], which is especially important with the possible proliferation of persona-prompted mass-annotated synthetic datasets amplifying miscalibrated points of view across model iterations.

[6] See App. G; Table 28 for the actual mean nDFU values by prompt.




Fig. 4. Unnatributtable Polarization (UnPol) across our datasets (§3). Contrary to assumptions made in prior work, UnPol is commonly non-zero and can even reach $nDFU = 1$ in datasets with low annotator counts (see Table 1). The left side of the figure shows the same datasets, where annotations are subsampled 100 times down to six annotators and their UnPol is averaged.

6 The Ideal Subjective Dataset

6.1 Categorizing Attributes of Annotation Datasets

As discussed in §3, there is a severe lack of datasets containing annotator metadata for subjective tasks. Given that the creation of these datasets is difficult, expensive and time-consuming, it is important to acknowledge and prioritize certain properties that are necessary for analyzing subjectivity across annotator groups. Since there is to our knowledge no taxonomy on the shape of annotated datasets, we distinguish three main properties:

- Data Coverage (DC), which refers to the number of *items* in a dataset. Due to the focus on training and benchmarking datasets in NLP, this property is usually the one with the most focus and importance [54].
- Group Coverage (GC), which refers to the overall number of *annotators* and their distribution across SDDs. A large annotator pool is required to get sufficient coverage on the examined groups and allows both higher fidelity of each SDD and more such SDDs to be examined.
- Annotation Density (AD), which refers to the number of *annotators per item*. This property is often neglected in practice, with many datasets [11, 33, 44, 62, 63] assuming "gold labels" can be inferred by three annotators.

6.2 The Case for Annotation Density

Is All SysDis Attributable to a SDD? In theory, we would expect all SysDis to be attributable to some annotator SDD, either one that is observed in our dataset, or latent (e.g., whether the annotators had lunch before their task). Some theoretical models such as AU make this assumption explicit, with AU attributing polarization to a SDD only when all individual groups show completely unimodal annotation histograms. We posit that this is not the case when datasets are created using few annotators per item.

Definition. Formally, the Unnatributtable Polarization (UnPol) for a single item c is the minimum nDFU exhibited by any arbitrary group (Eq. 3). When considered exhaustively, these theoretical, random splits produce both observed and latent groups. Since nDFU operates only when a group has at least three annotators (Eq. 1), this yields $\sum_{k=3}^{n} \binom{n}{k}$ possible groups, which is computationally intractable for large annotator counts. We can therefore use Monte Carlo

sampling by drawing k random partitions with random sizes (Eq. 4) which serves as an upper bound (as it considers a strict subset of Eq. 3).

$$\mathrm{Pol}_{inh}(c) = \min_{S \in G_c} \{\mathrm{nDFU}(S)\} \quad (3) \qquad \mathrm{Pol}^{MC}_{inh}(c) = \min_{j=1}^{k} \{\mathrm{nDFU}(S_j)\} \quad (4)$$

where G_c is the collection of all subsets S of annotations for an item c such that $|S| \geq 3$ and S_j is a random sample drawn from G_c for $j = 1, \ldots, k$.

Does It Exist? We compute the UnPol for each item across the five datasets. For Sap and Kumar, we use the exhaustive formulation (Eq. 3), whereas for the two DICES datasets we rely on the Monte Carlo approximation with $k = 1000$ (Eq. 4). Fig. 4 shows that in all DICES items there exists at least one group that fully accounts for the observed nDFU even when repeatedly subsampling down to six annotators.[7][8] Interestingly, this observation does not hold for the Kumar and Sap datasets, despite evaluating all possible annotator groups exhaustively. We also observe that UnPol typically exists on smaller annotation counts, as evidenced by POPQUORN in Fig 4 and by LLM annotations only exhibiting UnPol when subsampling down to six annotators per item (App. F; Fig. 11). See App. D; Table 11 for examples of items with high UnPol and App. F; Fig. 11 for UnPol exhibited by LLMs for each dataset and instruction prompt.

Finding 4. *Items may exhibit a degree of UnPol that cannot be attributed to any known or latent annotator grouping.*

6.3 How Should We Design Subjective Datasets?

Subjective datasets should be tailored to their specific use [67], so using very large datasets for social science analysis may not be necessary [54]. While DC may be convenient for training classifiers, relying on it without rigorous evaluation of SysDis can lead to misconfigured or biased models [56], evaluation which is impossible without the necessary DC). However, it comes at the expense of the other two (arguably more important) qualities. Generally, the *easiest-to-use resources for training LLMs and classifiers may be the riskiest*, as meaningful, SysDis cannot be reliably quantified (see the Kumar dataset in this study). We therefore recommend prioritizing dataset creation by first ensuring sufficient AD, then achieving necessary GC across underrepresented groups, and finally allowing budgetary constraints to determine DC.

While this tension between the need for massive data volumes in AI training and the requirement of responsible social science to use deeply annotated, subjective datasets is unlikely to be resolved, a practical step is providing full annotation guidelines in both cases. If the annotation target and definitions are unknown, comparing results across different datasets becomes extremely difficult. As shown in §5.3, without clear guidelines, differences in polarization patterns remain obscured when analyzing data from multiple studies.

Conclusion

In this study, we showed that current disagreement attribution measures tend to underperform in realistic annotation settings through a large scale empirical study. We designed a new measure which quantifies attribution of Systematic Disagreement (SysDis) to annotator SDDs, taking into account the limitations of real-life annotation datasets. Using this measure, we identified shared polarization patterns among gender and ethnicity groups across five subjective NLP datasets. Additionally, we found that LLM annotators can create polarized annotations, but do not reproduce human polarization patterns, even when using prompt engineering. Our research is limited due to the information present in

[7] $Pol^{MC}_{inh}(c) = 0 \Rightarrow Pol_{inh}(c) = 0$ due to Eq. 4, as is the case of increased k in Eq. 4.
[8] See App. E.2 for why this observation could be explained by DICES being structurally different.

the datasets; namely, we discovered that due to low annotation counts per item, some polarization cannot be attributed to any combination of theoretical dimensions ("Unnatributtable Polarization (UnPol)"). Overall, our work warns against using LLM persona prompting without rigorous, task-specific evaluation, and motivates the development of "wider" datasets with fewer but better annotated items.

AI Use Statement

In this work we used proprietary models such as Anthropic's Claude Sonnet 5 and OpenAI's GPT-5 for partially implementing the synthetic experiments in §4 and generating parts of the library, experiment and graph-creation code. The unit-tests used in our library were similarly generated by these models, although new tests were added as edge-cases and bugs were discovered. All such tasks were executed with direct author supervision, and all relevant code files (library, experiments, graphs) have been edited manually at multiple points by the authors to ensure reproducibility, accuracy and software quality. We also used Scholar Labs to find citations for targeted claims (e.g., for known issues with persona prompting), although all such citations were manually filtered by us. Finally, we used a locally hosted Gemma-4 model (specifically the `gemma-4-E4B-it-Q4_K_M.gguf` variant) for rephrasing this manuscript in order to improve readability. We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

Ethics Statement

Dual Use Concerns. The primary objective of this study is to identify systemic sources of SysDis in subjective NLP datasets to facilitate the construction of more fair and reliable AI systems. However, given that our methodology allows for the quantitative attribution of specific annotation patterns to SDDs, we acknowledge three primary risks inherent in this research. (1) *Discriminatory Profiling*: If the measure is applied outside of a dataset quality analysis, its ability to correlate specific opinion patterns with annotator groups could be misused for surveillance or unjust profiling. (2) *Automated Bias Amplification*: The diagnostic patterns of disagreement we detect are reflections of human systemic biases. Without human oversight, training subsequent models on these patterns risks automating and entrenching existing societal prejudices. (3) The knowledge provided by *apunim* could be *weaponized*, allowing malicious actors to strategically target weak points in moderation systems or intentionally maximize societal conflict. We stress that our measure functions strictly as a diagnostic warning signal. Any deployment in a real-world system must mandate a human-in-the-loop review, ensuring that identified patterns lead to systemic improvements (e.g., policy reform, demographic diversity initiatives) rather than merely justifying an automated system. In any case, despite the risks, we believe that the benefits of this research outweigh the risks outlined above.

Data Sourcing and Privacy. All datasets employed in this study were either publicly accessible or provided to us by the original authors with full disclosure regarding the purpose of our research. No identifiable, personal information was included in our pipeline. We do not release proprietary data provided by the authors, nor have we provided any to proprietary LLMs. Finally, we note that our data is limited to English posts from a U.S. cultural context and our results may not be representative for other cultures.

Examples Used. Our study utilizes examples of comments that may be considered divisive across certain demographics. These examples were generated by our team solely for demonstration purposes. We explicitly state that the contents of these examples and the groups studied do not necessarily reflect the views or behaviors of the groups they represent,

Table 7. Descriptive statistics for the number of annotations per comment, grouped by dataset.

	count	mean	std	min	25%	50%	75%	max
DICES-350	350	123	0	123	123	123	123	123
DICES-990	990	72.8313	1.1652	69	72	73	74	76
POPQUORN	1500	8.6573	0.9087	5	8	9	9	10
Kumar et al. 2021	105910	5.0261	0.3604	5	5	5	5	10
Sap et al. 2022	585	5.6359	0.7713	3	6	6	6	12

nor do they reflect the opinions of the authors. We have partially censored explicit slurs in Table 11 in order to both mitigate uncomfortable or triggering content, while also showing enough content for the examples to be effective.

Prompts Used. This study uses adversarial prompts which explicitly instruct the model to change its outputs according to their persona prompts. The purpose of these prompts is to test the LLMs under an extreme case of prompt engineering and are not to be used for generalized usage. The use of these prompts may degrade model performance, increase the risk of stereotyping and produce misleading results.

A Acronyms

IAA Inter-Annotator Agreement
SDD SocioDemographic Dimension
AU A Posteriori Unimodality
SysDis Systematic Disagrement
UnPol Unnatributtable Polarization
nDFU normalized Distance From Unimodality
NLP Natural Language Processing
GPLv3 GNU General Public Licence v3
AA African American
HS Hate Speech
SD Standard Deviation
DC Data Coverage
GC Group Coverage
AD Annotation Density

B Exploratory Analysis

The number of annotators per item for all datasets presented in §3 can be found in Fig. 6, and descriptive statistics can be found in Table 7. The DICES-990 dataset has exactly 123 annotations per item, while the other datasets exhibit a few variations around the central mean reported in Table 1. Interestingly, the sample used from the Kumar dataset exhibits a few items that vastly exceed the promised 5 number of annotators. We do not include these items, since they are very likely a data error. Tables 8,9,10 show the annotation counts for each SDD group in each dataset.




Fig. 5. Boxplots of dataset polarization for the human datasets considered in this paper for all groups in each examined SDD.

C Apunim Details

C.1 Statistical Estimation

Since annotation histograms may be noisy, we additionally assess whether the observed apunim value could arise by chance. To assess statistical significance, we construct a null distribution of apunim values from the randomized partitions and compare the observed apunim against this distribution using a one-sample Student-t test. Thus, the null




Fig. 6. We calculate the ratio of items for each dataset (y-axis) that had x number of annotators (x-axis). We truncate the x-axis to 130 annotators, disregarding very few items in the Kumar dataset exceeding this threshold (see Table 7), which is likely caused by a data error.

Table 8. Subgroup Counts for DICES-990 (left) and DICES-350 (right). "Support" refers to annotation count.

Category	Subgroup	Support
Gender	Woman	36050
	Man	35392
	Nonbinary	331
	Other	330
Race	Other	26394
	Asian	19885
	White	12322
	Latino	7170
	African Am.	6332
Age	Gen. Z	14899
	Millennial	41542
	Gen. X+	15662
Education	College +	64054
	High school -	8049

Category	Subgroup	Support
Gender	Woman	21700
	Man	21350
Race	White	10500
	African Am.	10150
	Asian	9100
	Latino	7700
	Multiracial	5600
Age	1) Gen. Z	19600
	2) Millennial	12600
	3) Gen. X+	10850
Education	College +	26250
	High school -	14350
	Other	2450

hypothesis states that the observed polarization is indistinguishable from polarization induced by random annotator assignments:

$$\begin{aligned} H_0 &: \; \bar{apunim}_{\text{rand}}(d, g) = apunim(d, g) \\ H_a &: \; \bar{apunim}_{\text{rand}}(d, g) \neq apunim(d, g) \end{aligned} \tag{5}$$

where $\bar{apunim}_{\text{rand}}(d, g)$ denotes the average apunim values obtained from t randomized annotator partitions.

We account for the presence of multiple subgroups in each SDD using a multiple-hypothesis correction. Since our test is parametric (App. C.1), it assumes that there exist (1) enough data-points to reliably run the means-test, (2) enough annotations per SDD group to estimate nDFUs, (3) the apunim values of the random partitions are independent and identically distributed. Condition (1) can be safely assumed for most datasets, because they feature enough items to

Table 9. Subgroup Counts for the Sap (left) and POPQUORN (right) datasets. "Support" refers to annotation count.

Category	Subgroup	Support
Age	Gen. Z	252
	Millennial	2259
	Gen. X+	786
Race	White	2168
	Black	1091
	Hisp	32
	Other	5
	MiddleEastern	1
Gender	man	1859
	woman	1412
	nonBinary	26

Category	Subgroup	Count
Gender	Woman	6470
	Man	6166
	Non-binary	350
Race	White	9754
	Black	1685
	Asian	949
	Native American	299
	Hispanic	250
	Arab American	49
Age	18-24	1545
	25-29	1236
	30-34	1494
	35-39	1547
	40-44	1142
	45-49	1091
	50-54	947
	54-59	1793
	60-64	747
	>65	1444
Education	No high school	237
	High school	3934
	College degree	6036
	Graduate degree	2481
	Other	298
Occupation	Student	995
	Homemaker	594
	Retired	1446
	Employed	6325
	Self-employed	1692
	Unemployed	1684
	Other	250

reliably assume normal residuals (see §3). We discuss condition (2) in §6. Condition (3) is partly fulfilled; the partitions are identically distributed, but may be dependent on the sample distribution.

Replacing the parametric means test with a non-parametric alternative would relax assumptions about the underlying distribution but would not resolve the potential dependence between the random apunims. We initially attempted to implement a permutation test on the empirical (random apunim) distribution, but this resulted in excessive computational costs.

While the test operates on a single group in principle, in practice we often want to test polarization for all subgroups of a specific SDD. Since we are simultaneously considering multiple hypotheses, we apply a multiple comparison correction to the resulting p-values—specifically the Holm method [26]. The test is parameterized by the confidence

Table 10. Subgroup Counts for the Kumar dataset. "Support" refers to annotation count.

Category	Subgroup	Support
Gender	Female	8011
	Male	6832
	Unknown	124
	Nonbinary	93
Ethnicity	White	10699
	Black	1940
	Asian	862
	Multiracial	664
	Hispanic	418
	Other	247
	Unknown	230
Age	Under 18	3
	18 - 24	1711
	25 - 34	5969
	35 - 44	3785
	45 - 54	1977
	55 - 64	1101
	65 or older	471
	N/A	43
Education	No high school	71
	High School	1353
	College	3090
	Associate's	1676
	Bachelor's	6071
	Master's	2261
	Professional	236
	Doctoral	198
	N/A	71
	Other	32
Sexual Orient.	Heterosexual	12391
	Bisexual	1665
	Homosexual	515
	N/A	302
	Other	131
Is Trans	No	14549
	Yes	363
	N/A	148
Politics	Liberal	5997
	Independent	4143
	Conservative	3981
	N/A	609
	Other	330
Is Parent	Yes	7889
	No	7015
	N/A	156
Tech Impact	Very negative	149
	Somewhat negative	1411
	Neutral	1905
	Somewhat positive	7690
	Very positive	3905
Tox Problem	Never	869
	Rarely	2485
	Occasionally	5307
	Frequently	4441
	Very Frequently	1958
Rel Important	No	4735
	Not very	1808
	Somewhat	3548
	Very	4741
	N/A	228
Seen Toxicity	True	11505
	False	3555
Targeted	False	10741
	True	4319

level of our test, which is used to tune the strength of the correction; we can increase this value to make our test more conservative towards multiple hypotheses [9]).

C.2 Software

Installation and Usage. We release the `apunim` package, which is a Python library that implements both the nDFU and apunim calculations, as well as its statistical test. The software is available on PyPi We also provide high-level documentation in HTML format that includes an introduction, guide, and full low-level documentation for each of the two provided functions (https://anonymous.4open.science/r/apunim-page).

We use version `1.0.6` of the `apunim` library for our experiments. We use 100 random iterations for the apriori value calculation and the p-value estimation (App. C.1), and set a confidence level of $\alpha = 0.05$. The relative library setup is

provided as a conda environment file to ensure reproducibility. The code is open-source, licensed under the GNU General Public Licence v3 (GPLv3) and can be found on the project's repository (https://anonymous.4open.science/r/aposteriori-unimodality-E8C1). The library is cross-platform, works for any Python 3 version, and requires very few dependencies (namely `numpy, scipy, statsmodels`).

Implementation Details. By default, the computation of the apunim values happens on a single thread. In cases of serious computational cost, we recommend running the apunim calculation on multiple concurrent processes, since all operations are CPU-bound and thread-safe. This may be useful in cases where there are multiple SDDs, each of which is computationally expensive. In order to lower the computational cost required, we re-use the random partitions, which are originally calculated to obtain the apriori polarization values, for the p-value calculations (App. C.1). This means that in our current implementation, the number of groups for estimating apriori polarization, and the number of apunim values used in the p-value calculation have to be the same.

While the library efficiently handles large numbers of annotators through vectorized operations, performance degrades significantly when processing a high volume of items, particularly when annotators belong to multiple distinct groups. For instance, while experiments across all datasets in §3 complete within a minute, the Kumar dataset necessitates approximately one hour of computation using commercial hardware. Furthermore, the annotator variance analysis detailed in Fig. 9 required over ten hours. While this latter time requirement is anticipated due to the inherently demanding nature and non-standard application of our library, it demonstrates the existence of a potential scaling bottleneck. The same applies to a lesser extent for the subsampling experiments on the DICES datasets, taking collectively three hours of computation.

We hypothesize that this bottleneck is likely caused by repeated creation of numpy arrays, resulting in repeated memory allocations for each subgroup, in each item, for each SDD. We plan on profiling and addressing it in the next releases of our software. Until then, we suggest either using multiprocessing for each SDD subgroup, or running the different experiments in parallel (indeed, we use the `gnu-parallel` package [58] for our own experiments). We also note that the Kumar dataset also requires substantial RAM resources, estimated around 42–46GB of dedicated RAM should the whole dataset be considered (this is not a requirement for loading the sample used in this study). The CPU-bound experiments require approximately 3 hours to run, assuming a computer capable of efficient multiprocessing.

Finally, we note that in Fig. 9, we removed values where there was a lack of items annotated by the specified number of annotators (e.g., only 7% of items in DICES-990 were annotated by more than 73 annotators—see App. B).

C.3 Design Decisions

Defining Apriori Polarization. In §5, we explained how our methodology needs to compare the polarization between the set of all annotations and those made by a specific group g. Direct comparisons are not advisable, since we would be comparing statistics between a set and its subset—in this case, standard practice dictates comparing the subset with its complement; i.e., the in-group vs. the out-group instead of the in-group vs. all the annotations. However, this also would not work; if we apply the subset-vs-complement method in the example of Fig. 3, left, we would end up subtracting the nDFUs of men and women, which are similar as they are both unimodal distributions, falsely concluding that there is no polarization present.

Filtering Ineligible items. Because *apunim* is fundamentally designed to quantify polarization, we exclude items that exhibit no measurable polarization ($nDFU(c) = 0$). Furthermore, we also exclude items annotated exclusively by a single group (i.e., items where there are no two groups with at least three annotators each), since we require valid

histograms for the non-parametric estimation of nDFU (see Eq. 1). This is an unfortunately common scenario, since many NLP datasets feature only $5-6$ annotations per item. In a best-case scenario of 5 annotators split evenly between two groups, we would get a 3-2 split.

D Exploring UnPol

Why Does it Exist? Unlike disagreement, UnPol does not provide any information, but rather represents noise or uncertainty translated in terms of polarization. In order to minimize it, we need to find its cause. Since the DICES datasets are the only ones without *any* items with UnPol leads us to two hypotheses:

Hypothesis 1 (Low annotator count). *A low number of annotators per item may provide our model with insufficient information.*

Hypothesis 2 (Inaccessible groups). *UnPol may arise from the presence of partially represented groups within the annotator pool which may go undetected if they are represented by only one or two annotators, as nDFU is undefined for these groups.*

Both of these explanations are plausible and reflect known limitations of most NLP datasets. Unfortunately, we can not confirm any of these hypotheses.

Why Do DICES not Exhibit UnPol? In order to investigate whether the numerous annotators per items can explain the lack of UnPol in the DICES datasets (§4) we gradually subsample the annotators for each item randomly with replacement, starting from five annotators per item, and scaling up to the full complement of annotators in the dataset with a step of two. For each such step, we choose ten annotator samples and compute the maximum UnPol across all runs. Even with annotator counts similar to the Kumar and DICES datasets, UnPol remains zero, suggesting that the absence of UnPol can not be attributed to annotator number alone—rather, it is plausibly a pattern attributable to the DICES datasets themselves. This kind of analysis may be used in the exploratory phase of dataset selection in order to filter out datasets without enough group-specific subjectivity.

How Does it Look Like? Table 11 shows a random sample of items taken from the Sap dataset and their respective UnPol values (§4). Note that explicitly toxic or racist items tend to have UnPol values of zero, alongside clearly unproblematic items. Inversely, more ambiguous and less comprehensible items tend to have larger UnPol values. This pattern may suggest that UnPol may be tied to the overall ambiguity of the statements, especially in cases where items may either be interpreted as very toxic, or non-toxic, which agrees with the overall goal of nDFU (§2). We include the UnPol values for each individual item for all four datasets in the supplementary material.

E Experiments

E.1 Synthetic Examples

This appendix details the synthetic experiments used to illustrate the functionality and behavior of nDFU. In all simulations, the bin size is set to $N_{bins} = 10$.

Disagreement vs. Polarization. To explore the relationship between annotation polarization and disagreement in Fig. 1, we constructed a 2×2 matrix of synthetic datasets, each drawing from a pool of $N_{annotators} = 100$. Polarization is simulated by defining a minority group, which constitutes 20% of the total annotators (n_special = 20). These minority annotators are assigned a targeted mean shift (mean_shift = 1) from the base distribution. The base variance for these

Table 11. Sample of comments from the Sap dataset and their UnPol. Note that unambiguously toxic comments can be assigned with zero UnPol, while more nuanced cases tend to have higher values.

Content Warning: Slurs, offensive, toxic and hateful speech.	
Comment	UnPol
The minks mentioned in the headline are indeed ”rising” from where they were based, but that is due to them being buried in shallow mass graves (Africa) and filling with gas that causes them to rise out. Rest assured, they’re still very much dead, thankfully!.	1
There should be such thing as a b[redacted]ch resistance for us women	1
There’s a big difference between being a b[redacted]ch and being a woman	1
i just watched a video of @joisnotonfire being an annoying h[redacted]e on skype i’m laughing	1
n[redacted]as love to commit crime	1
I swear to God above I love ya and when ya be with this brotha, I swear I love you my bro as long as you not a n[redacted]a	0.5
I will become a cold ass b[redacted]ch because of my treatment	0.5
I would happily lay out a n[redacted]a	0.5
Shoot yourself in the head you hypersensitive fuckin b[redacted]ch.	0.5
not all women are b[redacted]ches, but all b[redacted]ches are women	0.5
“you ugly b[redacted]ch!!!”- that seems to be my real name these days”	0
“I am happy to report that drowning does kill this demonic entity. Oh holy are the waters of Chernarus!”” Omg, DED ;)”	0
“Let them praise the name of the LORD: for his name alone is excellent; his glory is above the earth and heaven.”” Psalms 148:13 #Bible”	0
someone plz get this n[redacted]er some help. He’s playing up like mad	0
stop talking you fucking n[redacted]er !	0

distributions is set at variance = 0.3. Different types of distributions (unimodal, bimodal, multimodal, uniform) are achieved by controlling the base_means and applying variance multipliers (e.g., variance × 3 for multimodal).

Discussion-Level Polarization. We examine nDFU scores for three specific textual examples presented in Fig. 3. For the individual items, $N_{annotators} = 200$ for each group. In the first case (misogynist item), Men’s scores are modeled with loc = 6, while Women’s scores are modeled with loc = 2. In the second case (misandrist item), the roles are reversed. The third visualization combines distributions for men and women derived from the respective single-item distributions.

E.2 Ablations

Does Apunim Work for More than Two Groups? We repeat the experiment comparing apunim to prior methodologies shown in Fig. 2 but generalized across multiple groups. As shown in Fig. 7, apunim stays competitive even in the presence of multiple annotator groups. Note the increased efficiency of many methods when polarization is unidirectional. This pattern indicates that the challenges of bidirectional polarization severely limiting prior approaches may be generalizable to more than two groups.




Fig. 7. Polarization group attribution on synthetic distributions. Bars indicate standard error. The setup is identical to the one used for Fig. 2, although in these experiments we consider multiple k annotator groups for each item. Dashed lines show the results of a simplified polarization setup, where polarization always has the same direction.

Table 12. Comparison of Apunim values across different sample sizes (1k, 3k, 10k, 30k) for the Kumar dataset.

		1000	3000	10000	30000
	SDD				
Age	1) 18 - 24	0.014	-0.017	-0.037	-0.016
	2) 25 - 34	-0.003	-0.000	0.000	0.000
	3) 35 - 44	0.000	-0.011	-0.001	-0.001
	4) 45 - 54	0.022	0.033	0.013	0.003
	5) 55 - 64	0.000	0.000	-0.057	0.001
	6) 65 or older	—	—	—	0.948
Education	2) High School graduate	0.000	0.000	-0.005	0.014
	3) College, no degree	0.010	0.014	0.010	0.006
	4) Associate degree	0.000	0.000	0.005	0.009
	5) Bachelor's degree	0.001	-0.000	-0.001	-0.000
	6) Master's degree	0.000	-0.006	0.004	-0.000
Ethnicity	Asian	-0.000	0.000	0.011	0.007
	Black	0.000	-0.024	-0.004	-0.012
	Hispanic	—	—	0.000	-0.099
	Multiracial	0.000	0.000	0.000	0.000
	Other	—	—	—	-0.306
	White	0.000	-0.000	-0.000	0.000

Continued on next page

Table 12. Comparison of Apunim values across different sample sizes (1k, 3k, 10k, 30k) for the Kumar dataset.

		1000	3000	10000	30000
	SDD				
Gender	Female	0.001	0.000	0.002	0.001
	Male	0.001	-0.004	-0.002	-0.001
Has Been Targeted	False	0.001	0.000	-0.000	0.000
	True	-0.009	-0.015	-0.003	-0.002
Is Parent	No	-0.002	0.002	0.001	0.001
	Prefer not to say	—	—	1.000	0.000
	Yes	-0.000	0.000	-0.000	0.000
Is Transgender	No	0.000	0.000	0.000	0.000
Political Affiliation	Conservative	-0.013	0.003	-0.003	-0.002
	Independent	0.000	-0.001	0.001	0.002
	Liberal	-0.001	0.006	0.001	0.001
	Other	—	0.000	0.000	0.000
	Prefer not to say	—	—	0.000	0.022
Religion Important	1) No	0.002	0.004	0.002	0.001
	2) Not very	0.000	-0.006	0.010	0.006
	3) Somewhat	0.000	0.002	0.003	-0.002
	4) Very	0.000	-0.003	-0.003	-0.002
Seen Toxicity	False	-0.007	0.002	-0.001	-0.001
	True	-0.001	0.000	0.001	0.000
Sexual Orientation	Bisexual	-0.068	-0.029	-0.040	-0.013
	Heterosexual	-0.001	-0.000	-0.000	0.000
	Homosexual	—	—	0.000	0.053
	Prefer not to say	—	—	—	0.370
Technology Impact	2) Somewhat negative	0.000	0.000	0.000	0.003
	3) Neutral	0.124	0.037	-0.014	0.000
	4) Somewhat positive	0.004	0.001	-0.000	0.001
	5) Very positive	-0.015	-0.004	-0.004	-0.003
Toxicity Problem	1) Never	0.000	0.000	-0.037	-0.081
	2) Rarely	0.000	0.000	0.003	-0.001
	3) Occasionally	0.000	-0.004	-0.003	-0.001
	4) Frequently	0.000	0.000	-0.001	-0.000
	5) Very Frequently	0.000	-0.002	0.030	0.015

How Does Dataset Size Influence Apunim? Since our approach was designed for the small-scale datasets common in NLP, we were cautious when testing it on the massive Kumar dataset. Because of the data volume, we analyzed various smaller samples (1,000, 3,000, 10,000, and 30,000 items), shown in Table 12. Sample size does not seem to have




Fig. 8. Apunim values on the Kumar dataset ($n_{samples} = 1000$) across ten runs with different subsets. Black bars indicate two Standard Deviations (SDs). SDDs with many groups are more volatile, although all SDDs broadly keep the same apunim sign across subsets.

a consistent effect on apunim values, other than large splits uncovering significant polarization effects in sparsely populated groups (e.g., 65+ yo. in *Age*, "Prefer Not to Say" in *Sexual Orientation*, "Never" , "Very Frequently" in *Toxicity*




Fig. 9. SD of *apunim* across items, averaged across 10 runs, where each item is resampled 100 times. Shaded areas represent two SDs.

Problem). The apunim direction stays broadly the same. We also test whether the results in Table 3 are an artifact of the dataset split, because of the small sample size used in the study. We repeat the apunim experiment with ten different subsets of the same dataset and record their apunim values, shown in Fig. 8. We find that most apunim values are stable, save for "Never" in *Toxicity Problem*, "Heterosexual" in *Sexual Orientation* and "Neutral" in *Technology Impact*.

How Does Sample Selection Influence Apunim? Astute readers may notice that some variability does exist across differently sized samples for the same examined groups, where for example the sign of the apunim value may switch. We note that the statistically significant values (bold rows) change signs only when the apunim value approaches zero in the largest samples. Thus, the results are not inverted, but rather pushed towards zero. In order to verify that this variability is caused by the sample size, and not by different samples being drawn, we execute a further ablation study. Specifically, we execute the apunim study on the 3000-sized sample of the dataset, using different subsets of the Kumar dataset. The results can be found in Fig. 8, where we note that variability is not an issue, except for a couple of cases. These cases seem to represent sparse annotator groups, where missing a few items may genuinely change the value of the apunim measure. These groups however are largely not detected by apunim as significant either way (see Table 3).

How Many Annotators Does Apunim Need? Fig. 9 sows that non-statistically significant results from Table 3 remain systematically close to zero, while statistically significant results can be distinguished from very small annotator counts (six annotators for well-balanced groups, $\approx$ 20 for poorly split groups such as non-binary annotators in DICES-990). Sampling annotators with replacement also uncovers a new group which systematically disagrees with the others; the Non-Binary annotators in the POPQUORN and DICES-990 datasets. This group was undetectable when partitioning annotator groups with the methodology described in Eq. 2 since only one item is annotated by three *Non-Binary* annotators in POPQUORN and none for DICES-990, but sampling with replacement uncovers a very strong attribution. It is unclear whether this is a methodological artifact, or a new finding unexplored in prior analysis concerning these datasets.

F LLM Annotation Procedure

F.1 Models Used

We use only open-source models, as proprietary models such as OpenAI's GPT-5 yield much less reproducible results [6]. Furthermore, the use of open-source models requires much fewer resources, enabling research on this task with a less demanding budget, as well as scalable deployment in real-world settings [54]. It is also worth noting that since the datasets used are not publicly licensed, we can not risk leaking the data contained within to proprietary models. Generally, the use of local models protects the personal data of the users contained in our datasets, ensures that our research can be replicated in domains where anonymity must be maintained, and renders our work compatible with existing legislation [14, 15]. Table 13 shows details on the LLMs used for this study. We specifically use 4-bit quantized versions from the `unsloth huggingface` repository.

Table 13. LLMs used in this study.

Family	Version	#Params	Year
`OLMo` [23]	`2 (0325)`	32B	2025
`Qwen` [74]	`2.5`	32B	2024
`OLMo` [45]	`3`	7B	2025
`Qwen` [74]	`2.5`	7B	2024
`LLaMa` [22]	`3.1`	8B	2024
`Mistral` [28]	`Small 3 (2501)`	24B	2025
`Mistral` [28]	`v0.3`	7B	2024
`Gemma` [61]	`4`	E2B	2026
`Gemma` [61]	`4`	31B	2026

F.2 Experimental Setup

Since each of the datasets in §3 was annotated using different annotation guidelines and targets we use different instruction prompts for each dataset. The "default" annotation prompt is directly extracted from the studies in the case of Sap and Kumar, and inferred from the instruction guidelines used in the DICES datasets with minor modifications. We use standard persona prompting procedures sampled randomly from the available SDDs in each respective dataset. Twenty LLM annotators are selected for each item and model.

The prompts used in the ablation study were provided by a GPT-5 and a local Gemma-4 (quantized) model by providing the original prompt and instructing it to produce four variants. The tested prompts use different methods to restrict the model's behavior. The initial prompts ("*Persona*"require the model to adopt a persona's viewpoint to judge the comment. Other prompts ("*direct*") treat the persona's characteristics as an absolute, non-negotiable rule that overrides standard moderation guidelines. Another approach ("single") compels the model to perform a persona-based check before submitting its final rating. The most aggressive prompts ("stereotype") force the model into extreme decision spaces. The full main and ablation annotation prompts can be found in App. H.

We use a single Quadro RTX 6000 GPU for tasks requiring small (7-8B) models and two such GPUs for the rest. The annotation task, including ablations, requires approximately 300 hours of computation to complete. We use the `transformers` library to load and manage the LLMs. We release the relevant code in the supplementary material. Our codebase is platform-independent except for three high-level bash scripts and a full environment file is included for reproduction.




Fig. 10. Annotation frequencies for humans and each LLM in the primary annotation task using the default prompt.

F.3 Exploratory Analysis

Frequencies. Fig. 10 shows the different annotation frequencies of LLMs and human annotators in the same dataset split. Across all datasets, we observe a consistent mismatch between human and LLM annotation distributions. For the DICES-350 and DICES-990 harmfulness tasks, human annotations are heavily concentrated at the lowest harmfulness value, whereas most LLMs assign substantially more probability to moderate and high harmfulness values. A similar pattern appears in the Sap et al. [57] racism dataset: human judgments are concentrated at low racism scores, while LLMs produce broader distributions with considerably more mass at higher scores, particularly values 4–5. The [32] toxicity results show the same general trend, with humans assigning most probability to zero toxicity while LLMs distribute their predictions across higher toxicity levels, often peaking around values 2–4. Importantly, the magnitude of this discrepancy varies across models; some LLMs are closer to the human distribution, while others show substantially stronger shifts toward higher scores.

Dropped Responses. Table 14 shows a breakdown of failure modes across models and datasets. Most failed answers stem from the model refusing to provide any number in their response. Some attempt to initiate a Chain of Thought response, which is truncated due to us forcing a three-token limit on LLM answers. Others refuse to respond due to safety tuning. Finally, some (and especially the smaller Gemma model) seem to produce degenerate integer outputs. The full file of failed responses can be found in the Supplementary Material.

F.4 Annotation Ablations

We examine the following conditions for selecting models and datasets for our LLM annotation experiment. All ablation experiments use a sampled 20% fraction of the full LLM annotation dataset used in the main text.

The LLMs should be consistent given the same prompt. While we have fixed all relevant seeds, it is possible that generation deviates across repeated model prompting given the same input [6]. We check this condition by providing the model with the main annotation prompt (see App. H) five times and find that generation is indeed deterministic under our setup for all models (Table 15).

The LLMs should be prompt insensitive. Small changes in the prompt have been shown to drastically affect LLM output in some tasks depending on the experimental setup [52]. In order to verify whether any models are unreliable under our setup, we create two alternative formulations of each prompt without a change in substance using a GPT-5 model

Table 14. Number of non-standard LLM annotations per model and dataset, summed over all instruction prompts. Unparsed: no integer found in the reply (dropped from the analysis); Out of range: an integer outside the dataset's annotation scale. Incidence: percentage of the model's annotations on that dataset.

Model	Dataset	Status	Count	Incidence (%)
gemma31b	popquorn	Unparsed	106	0.07
gemma31b	sap	Unparsed	8	0.01
gemma7b	kumar	Unparsed	12	0.01
gemma7b	popquorn	Out of range	1	0.00
gemma7b	popquorn	Unparsed	339	0.23
gemma7b	sap	Out of range	1008	1.72
gemma7b	sap	Unparsed	2	0.00
llama8b	kumar	Out of range	153	0.15
llama8b	kumar	Unparsed	33352	33.35
llama8b	popquorn	Out of range	1	0.00
llama8b	popquorn	Unparsed	66199	44.13
llama8b	sap	Unparsed	22852	39.06
mistral24b	kumar	Out of range	1	0.00
mistral24b	kumar	Unparsed	14745	14.74
mistral24b	popquorn	Unparsed	34409	22.94
mistral24b	sap	Unparsed	15114	25.84
mistral7b	kumar	Out of range	5	0.01
mistral7b	kumar	Unparsed	12152	12.15
mistral7b	popquorn	Out of range	106	0.07
mistral7b	popquorn	Unparsed	6201	4.13
mistral7b	sap	Out of range	9	0.02
mistral7b	sap	Unparsed	2214	3.78
olmo32b	kumar	Out of range	25	0.03
olmo32b	kumar	Unparsed	270	0.27
olmo32b	popquorn	Out of range	14	0.01
olmo32b	popquorn	Unparsed	1430	0.95
olmo32b	sap	Out of range	2	0.00
olmo32b	sap	Unparsed	964	1.65
olmo7b	kumar	Out of range	96	0.10
olmo7b	kumar	Unparsed	613	0.61
olmo7b	popquorn	Out of range	263	0.18
olmo7b	popquorn	Unparsed	4903	3.27
olmo7b	sap	Out of range	35	0.06
olmo7b	sap	Unparsed	4178	7.14
qwen32b	kumar	Unparsed	1	0.00
qwen32b	popquorn	Unparsed	45	0.03
qwen7b	kumar	Out of range	137	0.14
qwen7b	kumar	Unparsed	22	0.02
qwen7b	popquorn	Out of range	1	0.00
qwen7b	popquorn	Unparsed	42	0.03

(free version), whose outputs we manually verified (see App. H). Table 16 shows that while most LLMs are relatively robust to changes in formulation, the smaller ones (OLMo-7B, Qwen-7B and LLaMa-8B) are not. They are thus excluded from the annotation study.

The annotation guidelines should be unambiguous. The studies that provided the datasets used in our work (see §3) do not include LLM annotation, nor equivalent LLM prompts, which meant we had to generate them from the




Fig. 11. Normalized histograms showing the UnPol exhibited by each model when truncating annotation to six annotations, compared to human annotations for each dataset. Some LLMs fail to show any UnPol, while the rest show far less than humans. Note that the graph does not include zero UnPol, and the y-axis is truncated to $[0, 0.3]$.

human annotation guidelines ourselves. This was not a problem in the case of the Sap and Kumar datasets, since the annotation guidelines were short, simple and required minimal edits to be transformed into LLM annotation guidelines. However, the DICES datasets use poorly documented guidelines and the target label we used is an aggregation of multiple annotation tasks. For these reasons the prompt creation is non-trivial and prone to errors. Indeed, Table 17 shows that inter-model agreement is extremely low for the DICES datasets, even when we remove the sensitive models (Table 18). Given that the DICES datasets are (1) problematic w.r.t. inherent polarization (see App. D), (2) conditioned on several dozen annotations per item (3) difficult to find reliable annotation prompts for LLMs, we decided to exclude them from the annotation study.

F.5 LLM Annotation Results

Do LLMs Exhibit UnPol? We observe UnPol from most models when repeatedly subsampling six annotators (Fig. 11). In the case of the Sap and Kumar datasets, human annotators show significantly higher UnPol values, which is not the case for POPQUORN. Instruction prompts can influence the extent of UnPol, but inconsistently. Providing adversarial instruction prompts seems to increase UnPol, although the effect of each prompt seems to be dataset-dependent.

Apunim Analysis. Tables 19,20,21 show the apunim results for the LLM annotation task on the Kumar, Sap and POPQUORN datasets respectively. Apunim values are largely model-dependent, but no other concrete pattern can be discerned.

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
Age	1) 18 - 24	llama8b	-0.049**	0.013	0.089***	—	0.039***
		olmo32b	-0.068***	-0.008	-0.013	-0.009	-0.007
		olmo7b	0.031**	0.058***	0.015	-0.040**	0.027*
		qwen32b	0.023	0.053***	0.012	-0.042*	0.010
		qwen7b	0.012	0.009	-0.001	-0.042**	0.029*
		mistral7b	0.014	0.052***	0.056***	-0.005	0.072***
		mistral24b	0.048***	0.031*	0.073***	0.073	-0.015
		gemma7b	0.051*	0.045*	0.017	-0.015	-0.014
		gemma31b	0.035	—	—	—	—
	2) 25 - 34	llama8b	0.048**	0.012	0.013	—	0.016
		olmo32b	-0.010	0.003	-0.023	-0.009	0.044**
		olmo7b	0.042***	0.056***	0.010	-0.031*	-0.046***
		qwen32b	0.035*	0.047**	0.006	0.021	0.056***
		qwen7b	0.036**	0.024*	0.030	0.058***	0.049***
		mistral7b	0.049***	0.036**	0.062***	0.060	0.085***
		mistral24b	0.059***	0.040**	0.082***	0.073	-0.046**
		gemma7b	0.009	0.011	0.013	0.028	0.007
		gemma31b	0.073*	—	—	—	—
	3) 35 - 44	llama8b	-0.046**	0.015	0.005	—	-0.013
		olmo32b	0.029*	-0.011	0.001	0.018	0.027
		olmo7b	-0.018	0.038**	0.035**	0.010	-0.018
		qwen32b	0.042**	-0.029	-0.003	0.017	0.018
		qwen7b	0.051***	0.069***	0.079***	0.028*	0.074***
		mistral7b	0.068***	0.024	0.048***	-0.027	0.017
		mistral24b	0.007	0.030*	-0.030**	0.114	-0.032
		gemma7b	-0.029	0.008	0.023	0.015	-0.055*
		gemma31b	0.031	—	—	—	—
	4) 45 - 54	llama8b	0.051**	0.001	0.031	—	0.005
		olmo32b	0.002	-0.002	0.013	-0.015	0.013
		olmo7b	0.057***	0.020	-0.015	0.049***	-0.005
		qwen32b	0.044**	0.027	-0.000	0.009	0.011
		qwen7b	0.084***	-0.111***	-0.070***	-0.019	-0.000
		mistral7b	-0.004	0.012	-0.007	0.093*	0.026*
		mistral24b	0.040**	0.006	0.047***	-0.106	-0.008
		gemma7b	0.029	-0.004	-0.037	0.049	0.000
		gemma31b	0.037	—	—	—	—
	5) 55 - 64	llama8b	0.025	-0.006	-0.006	—	0.015
		olmo32b	-0.026	-0.039**	0.021	0.041**	-0.014
		olmo7b	0.049***	-0.012	-0.021	-0.010	0.020
		qwen32b	0.089***	0.007	0.001	0.043*	0.043**
		qwen7b	0.014	-0.002	0.008	0.013	0.005
		mistral7b	0.041**	0.020	0.036**	-0.101*	-0.075***
		mistral24b	0.045**	0.049***	0.042***	0.021	0.024
		gemma7b	0.024	0.024	0.031	-0.030	0.008
		gemma31b	-0.030	—	—	—	—
	6) 65 or older	llama8b	0.020	-0.035***	-0.074***	—	0.036***
		olmo32b	-0.035**	0.009	0.012	-0.047**	0.009
		olmo7b	0.036***	-0.018	-0.020	0.051***	0.058***
		qwen32b	0.053**	-0.011	0.014	0.025	-0.033*
		qwen7b	0.049***	-0.025*	-0.020	0.026	-0.021
		mistral7b	0.007	-0.034**	-0.015	-0.106*	-0.055***
		mistral24b	0.053***	-0.015	-0.039***	0.059	0.190***
		gemma7b	-0.007	0.004	-0.002	0.011	0.016
		gemma31b	-0.012	—	—	—	—
	Prefer not to say	llama8b	-0.003	0.039***	0.026	—	0.013

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		olmo32b	-0.043**	0.073***	0.063***	0.016	0.011
		olmo7b	0.029*	0.084***	-0.012	-0.054***	-0.014
		qwen32b	0.032*	0.024	0.032	0.009	-0.027*
		qwen7b	0.010	0.021	0.003	0.008	-0.008
		mistral7b	0.047***	-0.016	0.006	-0.014	0.066***
		mistral24b	0.091***	0.031*	0.030**	0.070	-0.006
		gemma7b	-0.007	-0.000	0.026	-0.001	-0.009
		gemma31b	-0.027	—	—	—	—
	Under 18	llama8b	0.013	0.017	0.017	—	-0.034**
		olmo32b	0.040**	-0.024	-0.037**	-0.004	-0.041**
		olmo7b	0.010	-0.031*	0.043***	0.015	0.050***
		qwen32b	0.036*	0.035*	0.033	-0.040*	-0.013
		qwen7b	0.014	0.056***	0.043*	0.044**	0.011
		mistral7b	-0.001	0.005	0.047***	0.028	0.033*
		mistral24b	0.019	-0.064***	-0.073***	-0.017	0.104***
		gemma7b	0.009	0.051**	0.019	0.100***	0.040
		gemma31b	0.018	—	—	—	—
Education	1) No high school	llama8b	0.029	-0.001	0.047	—	0.005
		olmo32b	-0.007	-0.013	-0.007	0.011	0.011
		olmo7b	0.004	-0.036*	0.076***	0.166***	0.078***
		qwen32b	-0.009	-0.024	-0.000	-0.043	-0.019
		qwen7b	0.028	0.092***	0.052*	0.012	0.013
		mistral7b	0.004	-0.005	0.036	0.086	0.017
		mistral24b	-0.012	-0.028	0.041*	0.040	-0.014
		gemma7b	-0.027	0.002	-0.001	-0.070	-0.026
		gemma31b	0.037	—	—	—	—
	2) High School graduate	llama8b	0.027	0.062***	0.009	—	-0.017
		olmo32b	-0.100***	0.003	0.020	-0.107***	0.084***
		olmo7b	-0.038*	-0.017	-0.032*	0.001	0.072***
		qwen32b	-0.016	0.027	-0.008	-0.023	0.054**
		qwen7b	0.028	0.059***	0.015	0.026	0.047**
		mistral7b	-0.032	-0.005	0.007	-0.002	0.007
		mistral24b	0.012	0.040	0.020	-0.039	-0.014
		gemma7b	0.031	-0.032	0.014	0.026	-0.057
		gemma31b	-0.054	—	—	—	—
	3) College, no degree	llama8b	-0.025	-0.025*	-0.074*	—	-0.049***
		olmo32b	0.070***	-0.041	0.069***	-0.001	-0.015
		olmo7b	-0.020	0.025	-0.027	0.002	-0.070***
		qwen32b	0.017	-0.031	-0.010	0.031	-0.003
		qwen7b	0.022	-0.013	0.022	0.020	0.024
		mistral7b	-0.020	-0.032	-0.007	-0.081	-0.025
		mistral24b	-0.033	-0.029	-0.016	0.011	0.010
		gemma7b	0.025	0.030	-0.015	0.049	0.011
		gemma31b	0.049	—	—	—	—
	4) Associate degree	llama8b	0.058*	0.032*	-0.011	—	0.018
		olmo32b	0.023	-0.033	0.012	-0.019	-0.045*
		olmo7b	0.033	0.057**	-0.024	-0.042*	0.023
		qwen32b	0.030	0.011	0.031	0.022	0.015
		qwen7b	-0.016	-0.048***	0.017	0.010	0.018
		mistral7b	0.030	0.041	0.041*	0.034	0.034
		mistral24b	0.053**	0.003	0.015	-0.113	-0.047*
		gemma7b	0.012	-0.003	0.028	-0.024	-0.003
		gemma31b	-0.060	—	—	—	—
	5) Bachelor's degree	llama8b	0.053*	-0.036**	0.054	—	0.030
		olmo32b	-0.034	-0.026	-0.008	0.007	-0.052**

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		olmo7b	-0.011	0.062***	-0.018	-0.013	-0.039*
		qwen32b	0.011	0.014	-0.010	0.034	-0.046*
		qwen7b	-0.022	-0.027	-0.028	0.016	0.055**
		mistral7b	-0.062***	-0.015	0.010	-0.009	0.018
		mistral24b	0.059**	0.028	-0.017	0.147	0.073**
		gemma7b	-0.032	0.025	0.005	0.015	0.053
		gemma31b	0.029	—	—	—	—
	6) Master's degree	llama8b	0.003	0.028*	0.009	—	0.042**
		olmo32b	0.006	-0.006	-0.029	0.010	-0.005
		olmo7b	-0.003	0.019	-0.042**	-0.057**	-0.016
		qwen32b	-0.014	0.024	0.042	-0.013	0.006
		qwen7b	0.030	-0.015	-0.009	-0.022	-0.044**
		mistral7b	0.008	0.014	-0.020	-0.020	-0.007
		mistral24b	0.017	0.003	-0.000	-0.001	0.007
		gemma7b	0.033	0.006	0.005	0.062	0.027
		gemma31b	0.042	—	—	—	—
	7) Professional degree	llama8b	-0.058*	-0.002	0.097**	—	-0.011
		olmo32b	0.007	-0.009	0.031	0.012	0.016
		olmo7b	0.033	0.023	0.065***	-0.042*	-0.026
		qwen32b	-0.004	0.045*	0.020	0.000	0.028
		qwen7b	-0.014	-0.012	-0.003	0.027	-0.007
		mistral7b	0.030	0.006	-0.000	0.105	0.010
		mistral24b	-0.034	-0.012	-0.015	0.023	0.008
		gemma7b	0.030	-0.005	-0.011	-0.049	-0.037
		gemma31b	0.024	—	—	—	—
	8) Doctoral degree	llama8b	0.007	0.044**	0.067*	—	0.006
		olmo32b	-0.032	0.005	0.027	-0.027	-0.018
		olmo7b	-0.040*	0.059***	-0.034*	-0.068**	0.023
		qwen32b	0.013	0.022	-0.019	0.018	0.035*
		qwen7b	-0.005	-0.060***	-0.011	0.012	-0.010
		mistral7b	-0.033	-0.030	-0.010	-0.010	-0.027
		mistral24b	-0.009	-0.013	-0.008	0.107	0.079***
		gemma7b	-0.009	0.006	0.066**	-0.021	0.034
		gemma31b	0.003	—	—	—	—
	Other	llama8b	0.024	0.021	0.008	—	-0.001
		olmo32b	-0.025	0.038	0.014	0.008	0.021
		olmo7b	-0.017	0.026	-0.010	0.011	0.006
		qwen32b	0.031	-0.040*	0.001	0.017	-0.040*
		qwen7b	-0.015	0.010	0.011	0.036	-0.045**
		mistral7b	0.014	0.017	0.011	-0.063	0.030
		mistral24b	-0.021	0.047**	-0.006	0.055	0.005
		gemma7b	-0.044	0.010	-0.011	0.004	0.017
		gemma31b	0.043	—	—	—	—
	Prefer not to say	llama8b	-0.079**	-0.008	-0.001	—	0.062***
		olmo32b	-0.008	0.045	0.011	-0.025	-0.020
		olmo7b	-0.050**	-0.058***	-0.003	-0.040*	0.002
		qwen32b	-0.050*	-0.003	-0.024	0.006	-0.018
		qwen7b	-0.006	0.045**	0.020	-0.034	0.014
		mistral7b	-0.009	0.001	-0.023	0.093	-0.007
		mistral24b	0.017	0.008	0.030	-0.035	-0.023
		gemma7b	0.008	-0.035	-0.059**	0.012	-0.030
		gemma31b	0.013	—	—	—	—
Ethnicity	Asian	llama8b	-0.004	-0.044***	0.032	—	-0.008
		olmo32b	0.015	0.015	-0.001	0.006	-0.001
		olmo7b	0.028**	-0.032**	-0.022	0.012	0.007

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		qwen32b	0.010	0.017	-0.016	-0.028	0.006
		qwen7b	-0.028*	-0.002	0.015	-0.007	0.030*
		mistral7b	-0.020	-0.002	0.007	-0.000	-0.011
		mistral24b	-0.014	-0.027*	0.011	-0.047	0.008
		gemma7b	0.028	-0.020	-0.008	0.044	0.049*
		gemma31b	0.002	—	—	—	—
	Black	llama8b	0.005	-0.047***	0.004	—	0.035***
		olmo32b	-0.017	0.032*	0.062***	0.001	0.073***
		olmo7b	0.013	0.040***	-0.008	0.043**	-0.038***
		qwen32b	-0.018	0.027	-0.027	0.027	-0.009
		qwen7b	-0.024	-0.016	-0.024	0.035*	-0.043***
		mistral7b	-0.015	0.014	-0.010	0.007	-0.063***
		mistral24b	-0.033*	0.053***	0.045***	-0.025	-0.042**
		gemma7b	0.025	0.036*	0.047**	-0.061*	-0.047*
		gemma31b	0.026	—	—	—	—
	Hispanic	llama8b	-0.018	-0.024*	-0.024	—	0.001
		olmo32b	-0.055***	0.005	0.006	-0.024	-0.033**
		olmo7b	0.022*	-0.013	0.018	0.004	-0.004
		qwen32b	0.033*	-0.007	0.008	0.019	0.036**
		qwen7b	0.021	0.017	-0.024	-0.005	-0.028*
		mistral7b	-0.004	0.008	0.003	-0.015	0.009
		mistral24b	0.035*	0.090***	0.067***	0.082	-0.018
		gemma7b	-0.011	0.035*	-0.015	-0.021	-0.022
		gemma31b	-0.005	—	—	—	—
	Multiracial	llama8b	0.026	-0.035***	0.013	—	-0.049***
		olmo32b	0.014	0.011	0.011	0.023	-0.009
		olmo7b	0.016	0.019	0.005	-0.039**	-0.021
		qwen32b	0.052**	0.021	0.044**	0.008	0.025*
		qwen7b	0.022	0.038***	0.002	0.021	-0.004
		mistral7b	0.018	0.020	0.021	0.016	0.010
		mistral24b	-0.002	0.010	-0.009	0.020	0.003
		gemma7b	-0.005	-0.015	-0.058***	0.022	0.032
		gemma31b	0.021	—	—	—	—
	Other	llama8b	0.017	-0.012	0.020	—	0.024*
		olmo32b	-0.014	-0.059***	-0.022	-0.032*	-0.033**
		olmo7b	-0.061***	0.021	0.054***	-0.004	0.049***
		qwen32b	0.007	0.010	0.018	-0.023	0.040**
		qwen7b	0.026	-0.019	0.002	-0.003	0.013
		mistral7b	-0.009	0.007	-0.012	-0.085*	0.021
		mistral24b	0.044**	-0.002	-0.010	0.009	0.024
		gemma7b	-0.006	-0.001	0.019	-0.000	-0.003
		gemma31b	0.035	—	—	—	—
	Unknown	llama8b	-0.006	0.014	0.032	—	-0.018
		olmo32b	0.022	0.013	0.007	0.001	-0.015
		olmo7b	-0.017	0.012	0.000	-0.027	0.049***
		qwen32b	0.017	0.029	0.002	-0.013	-0.068***
		qwen7b	-0.021	0.002	0.030	0.007	0.006
		mistral7b	0.017	0.027	0.022	-0.025	-0.010
		mistral24b	0.004	0.018	0.015	0.021	-0.014
		gemma7b	0.015	0.018	0.020	0.031	0.037*
		gemma31b	0.036	—	—	—	—
	White	llama8b	0.009	-0.001	-0.073***	—	-0.022*
		olmo32b	0.024	-0.024	-0.004	0.033*	-0.005
		olmo7b	0.022*	-0.046***	-0.016	0.002	0.004
		qwen32b	-0.022	-0.017	0.024	-0.022	0.026*

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		qwen7b	0.039**	-0.014	0.011	-0.020	0.012
		mistral7b	0.003	0.048***	0.048***	0.048	0.021
		mistral24b	0.031*	0.002	-0.012	-0.071	0.080***
		gemma7b	-0.022	0.052***	-0.008	-0.005	-0.016
		gemma31b	0.003	—	—	—	—
Gender	Female	llama8b	-0.021*	-0.010	0.006	—	-0.008
		olmo32b	-0.014	-0.001	-0.029***	0.004	0.024**
		olmo7b	0.000	-0.028***	0.009	0.032***	-0.018*
		qwen32b	-0.031*	-0.016	-0.007	0.006	-0.017
		qwen7b	-0.012	0.033***	0.006	0.008	0.015
		mistral7b	-0.025*	0.020	-0.028**	-0.020	-0.010
		mistral24b	0.004	0.017	0.018*	0.069*	0.013
		gemma7b	-0.002	-0.007	0.020	0.029	-0.032*
		gemma31b	0.000	—	—	—	—
	Male	llama8b	0.021*	-0.003	0.037**	—	-0.027**
		olmo32b	-0.041***	-0.002	-0.012	-0.001	-0.053***
		olmo7b	-0.002	0.007	0.019**	-0.030**	-0.060***
		qwen32b	0.023	0.005	0.019	0.001	-0.016
		qwen7b	0.032**	-0.013	0.003	-0.022	-0.028*
		mistral7b	0.013	0.028*	0.029**	0.061***	0.015
		mistral24b	-0.016	-0.015	-0.043***	0.042	-0.001
		gemma7b	-0.013	0.014	0.012	0.000	0.024*
		gemma31b	0.022	—	—	—	—
	Nonbinary	llama8b	0.001	-0.031***	-0.021	—	-0.009
		olmo32b	-0.003	-0.007	-0.013	0.011	0.032**
		olmo7b	0.012	0.000	0.007	0.001	0.018*
		qwen32b	0.027*	0.024	0.007	0.053***	0.063***
		qwen7b	0.001	-0.013	0.013	-0.002	-0.020
		mistral7b	-0.015	-0.017	-0.017	0.001	-0.018
		mistral24b	0.023	0.043***	0.027**	-0.009	0.040***
		gemma7b	-0.007	-0.006	0.001	-0.021	-0.030*
		gemma31b	0.053**	—	—	—	—
	Unknown	llama8b	0.038***	-0.008	0.010	—	0.007
		olmo32b	0.015	0.002	0.010	0.034***	0.017
		olmo7b	-0.006	-0.051***	0.043***	0.003	0.024**
		qwen32b	0.021	0.013	-0.005	-0.020	-0.001
		qwen7b	0.014	0.020*	-0.012	-0.002	0.019
		mistral7b	0.020	-0.000	-0.007	-0.023	0.008
		mistral24b	-0.002	-0.032**	0.005	-0.059*	-0.067***
		gemma7b	0.029	0.002	0.003	-0.005	0.040**
		gemma31b	0.054**	—	—	—	—
Has Been Targeted	False	llama8b	0.008	-0.005	0.038**	—	0.030**
		olmo32b	0.002	-0.011	0.006	-0.016	0.019
		olmo7b	0.039***	-0.041***	0.011	0.002	0.059***
		qwen32b	-0.019	0.018	0.010	-0.001	-0.002
		qwen7b	0.083***	-0.019	-0.011	-0.016	0.031**
		mistral7b	-0.019	0.069***	0.013	0.002	0.019
		mistral24b	-0.003	0.099***	0.055***	0.031	0.105***
		gemma7b	0.070***	0.109***	0.065***	0.056***	0.137***
		gemma31b	-0.007	—	—	—	—
	True	llama8b	-0.024	0.023	-0.032**	—	-0.027*
		olmo32b	-0.021	-0.008	0.001	0.023	-0.022
		olmo7b	-0.032***	0.066***	0.059***	-0.019	-0.051***
		qwen32b	0.021	0.010	0.004	-0.002	0.012
		qwen7b	-0.049***	0.018	0.013	0.027	-0.038**

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		mistral7b	0.024	-0.027*	-0.028*	0.010	-0.019
		mistral24b	0.023	0.121***	0.040***	0.007	-0.048***
		gemma7b	-0.001	0.041***	0.047***	-0.055***	-0.123***
		gemma31b	-0.004	—	—	—	—
Is Parent	No	llama8b	0.036**	0.016	0.037**	—	-0.006
		olmo32b	0.018	-0.016	-0.000	0.003	0.008
		olmo7b	0.016*	-0.032***	-0.004	0.029**	-0.000
		qwen32b	0.036*	0.025	0.023*	-0.008	0.024
		qwen7b	0.001	-0.010	0.013	-0.008	0.016
		mistral7b	0.015	-0.016	-0.012	0.006	-0.015
		mistral24b	-0.015	-0.021	0.009	0.021	0.038***
		gemma7b	0.003	-0.005	-0.007	0.018	0.008
		gemma31b	0.022	—	—	—	—
	Prefer not to say	llama8b	-0.024*	-0.018	-0.032**	—	-0.014
		olmo32b	0.020	-0.009	-0.015	-0.004	0.015
		olmo7b	0.057***	0.001	0.025***	0.021*	0.008
		qwen32b	-0.025	-0.014	-0.024*	-0.015	-0.014
		qwen7b	0.002	0.013	-0.018	0.022	0.009
		mistral7b	-0.011	-0.010	-0.002	0.011	-0.003
		mistral24b	0.023	-0.005	0.012	-0.023	-0.012
		gemma7b	-0.013	0.010	0.000	0.012	-0.005
		gemma31b	-0.017	—	—	—	—
	Yes	llama8b	-0.014	0.011	0.010	—	-0.025**
		olmo32b	-0.010	-0.006	-0.007	-0.018	-0.006
		olmo7b	-0.038***	0.006	0.002	-0.043***	-0.017*
		qwen32b	0.003	0.000	-0.005	-0.009	-0.012
		qwen7b	0.021	-0.003	0.015	-0.009	-0.001
		mistral7b	-0.001	0.012	0.017	0.008	-0.004
		mistral24b	-0.003	-0.000	0.005	0.073***	0.007
		gemma7b	0.018	0.013	0.010	0.001	0.025
		gemma31b	-0.013	—	—	—	—
Is Transgender	No	llama8b	-0.008	0.004	0.055***	—	0.005
		olmo32b	0.020	-0.015	0.008	-0.021	0.004
		olmo7b	-0.012	0.010	0.007	-0.006	0.012
		qwen32b	-0.005	-0.021	0.004	0.003	0.013
		qwen7b	0.004	0.024**	0.005	0.010	0.001
		mistral7b	0.005	0.008	0.001	0.006	0.007
		mistral24b	0.009	-0.001	0.000	0.007	0.021*
		gemma7b	0.018	-0.008	0.012	0.005	0.009
		gemma31b	-0.015	—	—	—	—
	Prefer not to say	llama8b	-0.002	-0.028***	-0.002	—	0.008
		olmo32b	-0.023	0.027**	-0.013	0.013	0.020
		olmo7b	0.009	-0.012	0.025***	0.011	0.026***
		qwen32b	0.001	0.005	-0.012	-0.011	0.003
		qwen7b	-0.041***	0.024**	-0.008	0.008	0.016
		mistral7b	0.004	0.015	0.012	0.019	-0.024*
		mistral24b	0.019	0.028*	0.017	0.043	0.010
		gemma7b	-0.015	-0.009	-0.031*	-0.004	-0.024
		gemma31b	0.004	—	—	—	—
	Yes	llama8b	-0.028*	-0.007	-0.047***	—	-0.015
		olmo32b	-0.004	0.028**	0.015	-0.007	0.005
		olmo7b	-0.010	-0.001	0.016*	0.009	0.033***
		qwen32b	0.026	0.023	0.003	-0.013	-0.005
		qwen7b	0.039***	-0.033***	0.015	-0.016	0.005
		mistral7b	-0.003	-0.041***	-0.022	0.003	0.021

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		mistral24b	-0.024	0.017	-0.008	0.029	-0.037***
		gemma7b	0.017	0.009	0.015	0.003	0.014
		gemma31b	0.025	—	—	—	—
Political Affiliation	Conservative	llama8b	0.001	-0.001	0.000	—	-0.009
		olmo32b	-0.001	-0.076***	-0.018	0.005	0.010
		olmo7b	0.010	0.023**	-0.010	-0.028*	-0.029***
		qwen32b	0.025	-0.031*	0.012	-0.008	-0.007
		qwen7b	0.039***	-0.044***	0.001	-0.010	0.008
		mistral7b	-0.012	-0.009	-0.009	-0.001	-0.021
		mistral24b	-0.038**	0.034**	-0.033***	-0.061	-0.032**
		gemma7b	0.042**	-0.003	-0.017	-0.027	-0.002
		gemma31b	0.005	—	—	—	—
	Independent	llama8b	0.022	0.038***	0.005	—	-0.005
		olmo32b	0.012	0.034**	0.017	-0.026*	0.007
		olmo7b	0.007	0.022*	0.014	-0.026*	0.030***
		qwen32b	-0.003	0.005	0.008	0.004	0.013
		qwen7b	-0.020	0.011	0.000	-0.023*	-0.011
		mistral7b	-0.022	-0.010	-0.016	0.018	-0.016
		mistral24b	0.007	0.008	0.032**	0.031	0.013
		gemma7b	-0.012	-0.001	0.020	-0.024	-0.024
		gemma31b	-0.011	—	—	—	—
	Liberal	llama8b	-0.015	-0.005	-0.024	—	-0.005
		olmo32b	0.005	0.028**	-0.013	0.003	0.002
		olmo7b	0.030***	0.033**	-0.060***	0.008	0.021*
		qwen32b	-0.013	-0.013	0.003	0.018	0.011
		qwen7b	0.024*	-0.030**	0.009	0.037***	0.025*
		mistral7b	0.003	0.040***	0.022	0.010	0.021
		mistral24b	0.011	0.051***	0.024**	0.039	0.042***
		gemma7b	0.017	0.002	0.008	0.010	0.021
		gemma31b	0.062**	—	—	—	—
	Other	llama8b	0.008	-0.009	0.020	—	-0.013
		olmo32b	-0.006	0.063***	0.000	-0.004	-0.005
		olmo7b	-0.041***	-0.027**	-0.010	-0.006	0.002
		qwen32b	-0.018	0.029*	-0.008	-0.017	0.010
		qwen7b	-0.006	0.014	0.010	0.004	0.013
		mistral7b	-0.010	-0.006	0.013	0.005	0.009
		mistral24b	0.018	-0.009	-0.008	0.012	0.000
		gemma7b	0.010	-0.015	-0.018	-0.002	-0.013
		gemma31b	-0.002	—	—	—	—
	Prefer not to say	llama8b	0.018	-0.027***	-0.046**	—	0.014
		olmo32b	0.003	0.003	-0.004	0.001	0.010
		olmo7b	-0.015*	-0.025**	0.003	0.007	0.010
		qwen32b	-0.009	0.009	0.012	0.015	0.009
		qwen7b	-0.045***	0.006	-0.007	0.053***	-0.003
		mistral7b	0.025*	0.013	0.014	-0.037	0.022
		mistral24b	0.020	-0.011	0.007	-0.051	-0.025*
		gemma7b	-0.023	0.026	0.001	0.061**	0.023
		gemma31b	0.041	—	—	—	—
Religion Important	1) No	llama8b	0.018	-0.005	-0.013	—	0.015
		olmo32b	0.003	-0.032**	-0.018	0.029*	0.011
		olmo7b	0.025**	-0.056***	-0.023**	-0.029**	0.013
		qwen32b	-0.016	-0.004	0.009	0.003	0.013
		qwen7b	-0.006	0.043***	0.044***	0.036***	-0.005
		mistral7b	-0.012	0.009	-0.010	-0.013	0.008
		mistral24b	-0.008	-0.021	-0.033***	-0.042	0.024

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		gemma7b	0.014	0.039**	0.021	0.064***	0.054***
		gemma31b	0.017	—	—	—	—
	2) Not very	llama8b	0.019	-0.001	-0.001	—	0.066***
		olmo32b	-0.005	0.031**	0.026**	0.006	0.024*
		olmo7b	0.005	0.036***	0.024**	-0.047***	-0.000
		qwen32b	0.015	-0.011	0.016	-0.008	0.006
		qwen7b	0.044***	0.084***	0.050***	0.051***	0.053***
		mistral7b	-0.001	0.013	0.030**	0.008	0.017
		mistral24b	0.010	-0.006	0.013	0.036	0.004
		gemma7b	0.007	0.006	0.010	0.026	-0.016
		gemma31b	-0.040	—	—	—	—
	3) Somewhat	llama8b	-0.028	0.011	-0.033*	—	-0.040***
		olmo32b	0.004	-0.060***	-0.011	0.002	-0.010
		olmo7b	0.010	0.036***	0.068***	0.033***	-0.029***
		qwen32b	0.007	-0.019	0.007	-0.048***	0.020
		qwen7b	0.000	0.085***	0.058***	0.039***	0.059***
		mistral7b	0.000	-0.010	0.000	-0.018	-0.012
		mistral24b	-0.010	0.020	0.011	-0.002	-0.023
		gemma7b	-0.011	-0.005	-0.000	-0.063***	-0.017
		gemma31b	0.008	—	—	—	—
	4) Very	llama8b	-0.025	0.017	-0.011	—	0.008
		olmo32b	0.027*	0.019	0.007	0.001	0.028*
		olmo7b	0.010	-0.002	-0.015*	-0.006	-0.034***
		qwen32b	0.019	0.030*	0.005	0.006	-0.016
		qwen7b	0.033**	-0.167***	-0.098***	-0.027*	-0.051***
		mistral7b	-0.003	-0.001	-0.005	-0.014	-0.005
		mistral24b	-0.018	-0.007	0.030***	0.031	-0.009
		gemma7b	-0.035*	-0.022	-0.034*	-0.039*	-0.018
		gemma31b	-0.007	—	—	—	—
	Prefer not to say	llama8b	0.015	-0.003	0.067***	—	0.010
		olmo32b	-0.012	0.010	-0.002	0.001	0.025*
		olmo7b	-0.029***	0.009	0.010	0.021*	0.069***
		qwen32b	0.001	0.001	-0.004	-0.020	0.014
		qwen7b	-0.002	-0.003	-0.012	0.015	0.017
		mistral7b	0.003	0.006	-0.015	-0.032	-0.019
		mistral24b	0.006	-0.027*	-0.017	0.045	0.017
		gemma7b	-0.006	0.020	0.015	-0.010	0.005
		gemma31b	-0.012	—	—	—	—
Seen Toxicity	False	llama8b	0.052***	-0.011	0.044***	—	0.015
		olmo32b	0.002	0.011	-0.029*	-0.000	0.008
		olmo7b	0.039***	-0.014	0.001	0.054***	0.049***
		qwen32b	-0.009	-0.001	-0.006	0.011	-0.018
		qwen7b	-0.048***	0.023*	0.007	-0.001	0.009
		mistral7b	-0.002	0.017	0.013	-0.019	0.028*
		mistral24b	-0.006	-0.016	-0.009	0.030	0.007
		gemma7b	-0.004	0.039**	-0.013	0.044**	0.076***
		gemma31b	0.022	—	—	—	—
	True	llama8b	-0.030**	-0.005	-0.037**	—	-0.007
		olmo32b	0.010	-0.003	0.005	-0.004	-0.010
		olmo7b	-0.008	0.021	0.021*	-0.044***	-0.056***
		qwen32b	-0.008	0.005	0.017	-0.024	0.010
		qwen7b	0.062***	-0.020*	0.005	0.012	-0.007
		mistral7b	0.008	-0.008	-0.013	0.027	-0.035**
		mistral24b	0.009	0.014	0.011	0.007	-0.012
		gemma7b	0.000	0.016	0.048***	-0.036*	-0.055***

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		gemma31b	-0.017	—	—	—	—
Sexual Orientation	Bisexual	llama8b	0.033**	-0.013	0.016	—	0.006
		olmo32b	0.001	0.003	0.018	0.020*	0.001
		olmo7b	-0.004	0.047***	0.011	-0.006	0.000
		qwen32b	0.012	0.005	-0.011	0.012	-0.028*
		qwen7b	0.011	-0.004	-0.008	-0.010	-0.003
		mistral7b	0.003	0.007	-0.001	-0.026	0.017
		mistral24b	0.003	0.021	0.034***	0.038	-0.004
		gemma7b	0.006	-0.011	-0.020	0.001	0.009
		gemma31b	0.011	—	—	—	—
	Heterosexual	llama8b	0.024	-0.021*	0.017	—	-0.015
		olmo32b	-0.019	-0.019	-0.008	-0.016	0.011
		olmo7b	-0.017*	0.018	0.023**	0.016	0.016
		qwen32b	0.008	0.004	-0.022	-0.012	0.035**
		qwen7b	-0.005	0.037***	-0.014	0.007	-0.014
		mistral7b	0.018	-0.012	0.006	-0.023	0.006
		mistral24b	-0.005	-0.018	-0.001	0.029	0.003
		gemma7b	-0.009	0.030*	0.027*	0.027	0.007
		gemma31b	-0.005	—	—	—	—
	Homosexual	llama8b	-0.013	-0.001	-0.029	—	-0.001
		olmo32b	-0.024	0.014	0.016	-0.024*	-0.012
		olmo7b	0.024**	-0.001	0.017*	-0.004	0.005
		qwen32b	0.005	-0.004	0.007	-0.042**	-0.003
		qwen7b	0.010	-0.043***	-0.041**	-0.038**	0.006
		mistral7b	0.009	0.027*	-0.009	-0.007	0.010
		mistral24b	0.005	-0.011	0.020	0.006	0.036**
		gemma7b	0.011	0.027*	0.032*	-0.044*	-0.002
		gemma31b	0.062**	—	—	—	—
	Other	llama8b	0.012	-0.019*	-0.016	—	-0.026**
		olmo32b	-0.006	0.024*	-0.013	0.032**	0.022
		olmo7b	0.012	-0.010	-0.004	0.025*	0.038***
		qwen32b	0.003	0.000	-0.009	-0.008	0.011
		qwen7b	0.036**	-0.004	0.033*	0.018	-0.041***
		mistral7b	0.003	0.012	0.006	-0.012	-0.023
		mistral24b	0.003	0.009	0.013	0.001	0.011
		gemma7b	-0.007	-0.031*	-0.038**	-0.012	0.001
		gemma31b	-0.011	—	—	—	—
	Prefer not to say	llama8b	-0.053***	0.007	0.027	—	0.025**
		olmo32b	0.007	-0.011	-0.007	-0.019*	0.003
		olmo7b	-0.022**	0.035***	-0.021**	0.002	-0.016
		qwen32b	0.012	-0.014	0.009	0.021	0.009
		qwen7b	-0.000	0.042***	0.025	0.007	0.034**
		mistral7b	0.006	0.006	0.024	0.010	-0.001
		mistral24b	0.004	-0.010	-0.011	-0.060	-0.056***
		gemma7b	-0.008	-0.023	-0.004	0.024	-0.012
		gemma31b	-0.007	—	—	—	—
Technology Impact	1) Very negative	llama8b	0.021	-0.003	0.032*	—	-0.035***
		olmo32b	0.009	-0.016	-0.003	0.018	-0.013
		olmo7b	0.020*	-0.076***	0.031***	0.009	0.035***
		qwen32b	-0.007	-0.001	-0.018	-0.030*	-0.056***
		qwen7b	0.005	0.028**	0.051***	0.052***	-0.004
		mistral7b	0.010	-0.010	-0.011	0.073**	-0.007
		mistral24b	0.009	0.029**	-0.016	0.024	-0.011
		gemma7b	0.021	0.005	0.044***	0.063**	0.033*
		gemma31b	-0.007	—	—	—	—

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
	2) Somewhat negative	llama8b	0.016	0.010	0.057***	—	0.006
		olmo32b	0.001	-0.017	-0.037***	0.006	-0.016
		olmo7b	0.016*	-0.060***	0.000	0.067***	0.011
		qwen32b	-0.008	0.013	-0.002	-0.013	0.006
		qwen7b	-0.035**	0.026**	0.018	0.035**	-0.032**
		mistral7b	0.011	0.028*	0.013	0.012	0.014
		mistral24b	-0.011	0.037***	0.021	-0.034	-0.068***
		gemma7b	-0.001	0.004	0.013	-0.008	0.008
		gemma31b	0.013	—	—	—	—
	3) Neutral	llama8b	-0.022	-0.013	-0.033*	—	-0.023**
		olmo32b	0.017	-0.003	0.016	-0.018	0.009
		olmo7b	-0.029***	-0.019*	0.037***	-0.021*	-0.016
		qwen32b	-0.007	0.008	0.016	0.004	0.030**
		qwen7b	-0.005	0.031***	0.016	-0.004	0.004
		mistral7b	0.027*	0.011	0.034**	-0.025	0.001
		mistral24b	0.005	-0.013	-0.017	-0.038	-0.005
		gemma7b	0.011	0.020	0.008	0.017	0.009
		gemma31b	-0.011	—	—	—	—
	4) Somewhat positive	llama8b	-0.012	0.019*	0.007	—	0.034***
		olmo32b	-0.006	0.004	0.012	0.003	-0.013
		olmo7b	0.011	0.064***	-0.011	0.017	-0.029***
		qwen32b	0.039**	0.026	-0.001	0.051***	0.004
		qwen7b	0.023	-0.065***	-0.046***	-0.003	-0.022*
		mistral7b	-0.001	0.012	-0.009	0.021	0.021
		mistral24b	0.023	0.021	0.015	-0.080*	0.029*
		gemma7b	-0.004	0.009	-0.004	-0.018	-0.038**
		gemma31b	0.021	—	—	—	—
	5) Very positive	llama8b	0.005	0.028**	-0.012	—	0.006
		olmo32b	-0.013	-0.043***	0.025**	-0.004	0.025
		olmo7b	-0.010	0.052***	-0.034***	-0.024*	-0.034***
		qwen32b	0.028	-0.013	0.023	-0.005	0.036**
		qwen7b	-0.001	-0.026**	-0.008	0.012	0.050***
		mistral7b	-0.047***	-0.009	-0.029**	0.014	-0.012
		mistral24b	0.030*	0.003	0.012	0.070*	0.108***
		gemma7b	-0.000	0.026	0.013	-0.030	-0.042**
		gemma31b	0.013	—	—	—	—
Toxicity Problem	1) Never	llama8b	0.005	0.043***	-0.012	—	0.031***
		olmo32b	-0.003	-0.004	-0.032***	-0.029**	0.012
		olmo7b	0.090***	-0.071***	0.020**	-0.004	0.107***
		qwen32b	0.050***	0.029**	0.074***	0.322***	0.130***
		qwen7b	0.054***	0.049***	0.043***	0.065***	0.084***
		mistral7b	0.022*	0.015	0.023*	-0.061*	0.063***
		mistral24b	0.065***	0.002	-0.007	0.058*	0.260***
		gemma7b	0.092***	0.146***	0.051***	0.242***	0.307***
		gemma31b	-0.004	—	—	—	—
	2) Rarely	llama8b	0.034**	-0.003	-0.016	—	-0.015
		olmo32b	0.038***	0.006	-0.023**	0.009	0.059***
		olmo7b	0.042***	0.498***	0.129***	-0.094***	-0.090***
		qwen32b	0.071***	0.042***	0.108***	0.343***	0.173***
		qwen7b	-0.002	0.091***	0.066***	0.016	0.091***
		mistral7b	0.003	0.023*	0.042***	0.088***	0.035***
		mistral24b	0.070***	0.040***	0.037***	0.001	0.148***
		gemma7b	0.061***	0.050***	0.035**	0.000	0.107***
		gemma31b	0.007	—	—	—	—
	3) Occasionally	llama8b	-0.053***	0.012	-0.018	—	-0.053***

Continued on next page

Table 19. Aposteriori unimodality results for the LLM annotations of the Kumar et al. 2021 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		olmo32b	0.066^{***}	0.008	0.023^{**}	0.059^{***}	0.046^{***}
		olmo7b	0.052^{***}	-0.023^{**}	0.010	0.120^{***}	-0.084^{***}
		qwen32b	0.061^{***}	0.056^{***}	0.063^{***}	0.278^{***}	0.142^{***}
		qwen7b	0.143^{***}	0.137^{***}	0.078^{***}	0.021^{*}	0.178^{***}
		mistral7b	-0.034^{**}	-0.007	0.006	0.193^{***}	0.002
		mistral24b	0.084^{***}	0.025^{*}	0.052^{***}	0.232^{***}	0.055^{***}
		gemma7b	0.006	-0.016	-0.003	-0.113^{***}	-0.008
		gemma31b	-0.038	—	—	—	—
	4) Frequently	llama8b	0.040^{***}	0.043^{***}	0.015	—	0.075^{***}
		olmo32b	-0.018	0.020	0.021^{**}	0.006	-0.003
		olmo7b	0.201^{***}	-0.025^{**}	-0.017^{*}	0.085^{***}	-0.007
		qwen32b	0.047^{***}	0.050^{***}	0.077^{***}	0.269^{***}	0.147^{***}
		qwen7b	-0.004	-0.168^{***}	-0.088^{***}	0.176^{***}	-0.064^{***}
		mistral7b	0.018	0.026^{*}	0.002	0.015	-0.051^{***}
		mistral24b	-0.060^{***}	0.015	0.065^{***}	0.527^{***}	-0.128^{***}
		gemma7b	0.036^{**}	0.052^{***}	0.071^{***}	0.028	0.051^{***}
		gemma31b	0.010	—	—	—	—
	5) Very Frequently	llama8b	-0.005	-0.014	0.015	—	0.001
		olmo32b	-0.036^{***}	0.044^{***}	0.043^{***}	0.011	0.003
		olmo7b	0.047^{***}	-0.076^{***}	-0.034^{***}	0.496^{***}	0.078^{***}
		qwen32b	0.055^{***}	0.062^{***}	0.087^{***}	0.254^{***}	0.123^{***}
		qwen7b	0.214^{***}	-0.061^{***}	-0.062^{***}	-0.085^{***}	0.012
		mistral7b	0.015	-0.024^{*}	0.008	-0.006	0.002
		mistral24b	0.003	0.045^{***}	-0.002	-0.112^{**}	-0.056^{***}
		gemma7b	0.056^{***}	0.042^{***}	0.057^{***}	0.144^{***}	0.252^{***}
		gemma31b	0.026	—	—	—	—

Table 20. Aposteriori unimodality results for the LLM annotations of the Sap et al. 2022 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
Age	1) Gen. X+	llama8b	-0.009	-0.018	-0.023	0.024	-0.067^{***}
		olmo32b	-0.006	-0.010	0.012	0.004	0.009
		olmo7b	0.023^{*}	-0.001	0.009	0.009	-0.028^{*}
		qwen32b	0.208^{***}	0.061^{***}	0.120^{***}	0.150^{***}	0.237^{***}
		qwen7b	0.152^{***}	0.090^{***}	0.147^{***}	0.100^{***}	0.159^{***}
		mistral7b	0.059^{**}	0.004	0.054^{**}	-0.003	0.077^{***}
		mistral24b	0.131^{***}	0.006	0.079^{**}	-0.046	0.107^{***}
		gemma7b	0.021	0.004	0.047^{**}	0.011	-0.018
		gemma31b	-0.024	0.009	-0.098^{***}	0.072^{*}	0.272^{***}
	2) Millennial	llama8b	-0.019	0.011	0.016	0.161	0.024^{*}
		olmo32b	-0.009	-0.042^{*}	-0.037^{*}	-0.000	-0.046^{*}
		olmo7b	0.031^{**}	-0.052^{***}	0.038^{***}	-0.042^{**}	0.077^{***}
		qwen32b	0.249^{***}	0.059^{***}	0.190^{***}	0.226^{***}	0.237^{***}
		qwen7b	0.246^{***}	0.139^{***}	0.219^{***}	0.129^{***}	0.169^{***}
		mistral7b	0.017	0.008	-0.043^{*}	-0.018	-0.070^{***}
		mistral24b	0.177^{***}	0.036^{**}	0.088^{***}	0.162^{***}	0.116^{***}
		gemma7b	0.021	-0.014	-0.020	-0.003	0.040^{*}
		gemma31b	0.085^{*}	0.074^{**}	0.061^{*}	0.016	0.233^{***}
	3) Gen. Z	llama8b	0.072^{***}	0.107^{***}	0.021	-0.029	0.067^{***}
		olmo32b	0.054^{**}	0.023	0.039^{*}	0.015	0.035^{*}
		olmo7b	-0.020^{*}	0.018	0.017	0.020	0.027^{*}

Continued on next page

Table 20. Aposteriori unimodality results for the LLM annotations of the Sap et al. 2022 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		qwen32b	0.124^{***}	0.122^{***}	0.204^{***}	0.126^{***}	0.147^{***}
		qwen7b	0.007	0.109^{***}	-0.014	0.104^{***}	0.118^{***}
		mistral7b	0.094^{***}	0.047^{*}	0.014	0.039	0.026
		mistral24b	-0.062^{***}	0.162^{***}	0.000	-0.032	0.037^{*}
		gemma7b	-0.014	0.003	0.002	-0.001	0.053^{**}
		gemma31b	0.124^{**}	0.188^{***}	0.202^{***}	0.127^{***}	0.278^{***}
Ethnicity	black	llama8b	-0.005	0.076^{***}	-0.077^{***}	0.008	0.117^{***}
		olmo32b	0.017	0.041	0.079^{***}	-0.015	0.019
		olmo7b	0.017	0.007	0.004	0.035^{*}	-0.022
		qwen32b	0.010	0.202^{***}	0.110^{***}	0.119^{***}	0.116^{***}
		qwen7b	0.047^{***}	0.126^{***}	0.049^{***}	0.052^{***}	0.043^{**}
		mistral7b	0.054^{**}	0.302^{***}	0.214^{***}	0.052^{*}	-0.010
		mistral24b	0.095^{***}	0.430^{***}	0.032	-0.061^{*}	0.058^{***}
		gemma7b	0.023	0.069^{***}	0.032^{*}	0.002	0.041^{**}
		gemma31b	0.148^{***}	0.285^{***}	0.375^{***}	0.177^{***}	0.061^{**}
	hisp	llama8b	0.012	-0.017	0.088^{***}	0.048	-0.027
		olmo32b	-0.020	0.005	-0.026	0.034	0.047^{*}
		olmo7b	0.050^{***}	-0.016	-0.008	0.013	0.016
		qwen32b	0.031	0.172^{***}	0.047^{**}	0.064^{***}	0.037^{*}
		qwen7b	0.038^{**}	0.149^{***}	0.052^{***}	0.058^{***}	0.036^{**}
		mistral7b	0.031	0.058^{**}	-0.019	-0.019	-0.047^{**}
		mistral24b	0.090^{***}	0.277^{***}	-0.005	0.122^{***}	0.047^{***}
		gemma7b	0.059^{***}	0.072^{***}	0.009	0.060^{***}	0.013
		gemma31b	0.064	0.120^{***}	0.076^{**}	0.092^{**}	0.005
	middleEastern	llama8b	-0.030	0.067^{***}	0.119^{***}	-0.037	-0.010
		olmo32b	-0.013	0.028	-0.008	-0.002	-0.003
		olmo7b	-0.049^{***}	0.003	-0.025^{**}	0.057^{***}	0.015
		qwen32b	0.052^{**}	0.277^{***}	0.093^{***}	0.067^{***}	0.133^{***}
		qwen7b	-0.001	0.046^{***}	0.021	-0.027^{*}	-0.035^{**}
		mistral7b	0.009	0.073^{***}	0.022	-0.050^{*}	0.081^{***}
		mistral24b	0.082^{***}	0.294^{***}	0.052	0.106^{***}	0.013
		gemma7b	0.041^{*}	0.070^{***}	0.004	0.048^{***}	0.003
		gemma31b	0.105^{**}	0.187^{***}	0.104^{***}	0.072^{*}	0.015
	other	llama8b	-0.015	-0.045^{***}	-0.003	0.142	0.013
		olmo32b	-0.014	0.024	-0.006	-0.032	-0.022
		olmo7b	-0.031^{***}	-0.025^{*}	0.043^{***}	0.035^{*}	-0.013
		qwen32b	0.031	0.165^{***}	0.087^{***}	0.065^{***}	0.092^{***}
		qwen7b	0.072^{***}	0.106^{***}	0.038^{**}	0.109^{***}	0.066^{***}
		mistral7b	0.118^{***}	0.092^{***}	0.036	0.036	0.010
		mistral24b	0.002	0.123^{***}	0.033	0.036	0.047^{***}
		gemma7b	-0.013	0.117^{***}	0.045^{**}	0.057^{***}	0.049^{**}
		gemma31b	0.111^{**}	0.085^{***}	0.021	0.080^{**}	-0.004
	white	llama8b	-0.023	0.020	-0.043^{*}	-0.045	0.013
		olmo32b	0.020	-0.018	-0.022	-0.001	-0.006
		olmo7b	0.034^{***}	0.002	0.066^{***}	0.005	0.013
		qwen32b	0.086^{***}	0.186^{***}	0.072^{***}	0.027	0.028
		qwen7b	0.068^{***}	0.023^{*}	-0.003	0.038^{**}	-0.013
		mistral7b	0.071^{***}	0.175^{***}	0.206^{***}	0.047^{*}	0.100^{***}
		mistral24b	-0.043^{***}	0.034^{**}	0.049	0.032	0.069^{***}
		gemma7b	0.121^{***}	0.038^{**}	0.123^{***}	0.085^{***}	0.049^{**}
		gemma31b	-0.099^{*}	-0.075^{***}	-0.116^{***}	0.056^{*}	-0.022
Gender	man	llama8b	0.011	0.031^{**}	-0.092^{***}	-0.078	0.004
		olmo32b	0.004	0.004	0.001	-0.001	0.001
		olmo7b	0.000	0.026^{**}	-0.008	0.013	0.010
		qwen32b	-0.033	-0.054^{**}	0.009	-0.043	-0.023

Continued on next page

Table 20. Aposteriori unimodality results for the LLM annotations of the Sap et al. 2022 dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		qwen7b	-0.003	-0.009	-0.030*	0.030	0.019
		mistral7b	-0.014	-0.055**	-0.021	-0.024	-0.011
		mistral24b	-0.006	-0.037**	-0.014	-0.090***	0.003
		gemma7b	0.029	-0.029	0.037*	0.007	0.044*
		gemma31b	0.042	-0.026	-0.000	0.009	-0.046*
	nonBinary	llama8b	-0.044**	0.028*	0.076***	0.151*	0.023
		olmo32b	0.006	-0.014	-0.010	0.016	0.017
		olmo7b	-0.029**	0.000	0.062***	-0.032	-0.057***
		qwen32b	-0.046	-0.006	-0.011	0.009	-0.011
		qwen7b	0.007	0.021	0.014	0.009	-0.015
		mistral7b	0.022	0.022	-0.027	0.025	0.034
		mistral24b	0.029*	0.029*	0.012	0.041*	0.052***
		gemma7b	-0.010	0.015	0.014	0.028	0.033*
		gemma31b	0.068	0.010	0.000	-0.027	0.043*
	woman	llama8b	0.004	0.010	0.029*	0.124*	-0.017
		olmo32b	0.004	0.017	0.000	-0.020	-0.024
		olmo7b	0.064***	0.036***	-0.006	-0.013	0.013
		qwen32b	-0.011	-0.001	-0.007	-0.015	-0.046*
		qwen7b	-0.016	0.004	-0.035*	-0.011	0.005
		mistral7b	-0.015	0.056**	0.078***	0.024	0.013
		mistral24b	-0.028*	-0.005	0.065*	0.085***	-0.031*
		gemma7b	-0.016	0.023	-0.018	-0.007	0.005
		gemma31b	-0.023	0.005	0.011	0.030	0.010

Table 21. Aposteriori unimodality results for the LLM annotations of the POPQUORN dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
Age	01) 18-24	llama8b	0.010	0.079***	-0.002	-0.063	0.033**
		olmo32b	0.063***	-0.004	-0.022	-0.008	0.039*
		olmo7b	0.039**	0.018	0.024*	-0.037*	0.055***
		qwen32b	0.087***	0.106***	0.125***	0.212***	0.116***
		qwen7b	0.014	0.085***	0.059***	0.116***	0.130***
		mistral7b	0.080***	-0.008	-0.008	0.017	-0.025
		mistral24b	0.108***	0.052***	0.009	0.163	0.004
		gemma7b	0.052*	0.096***	-0.018	0.021	0.020
		gemma31b	0.029	0.100***	0.059*	-0.095*	0.024
	02) 25-29	llama8b	0.077	0.003	0.009	-0.066	0.014
		olmo32b	0.038*	-0.012	0.019	0.045**	0.006
		olmo7b	0.019	0.050***	0.008	0.018	0.058***
		qwen32b	0.089***	0.084***	0.116***	0.236***	0.157***
		qwen7b	0.098***	0.083***	0.032*	0.045**	0.054***
		mistral7b	0.109***	-0.028	-0.052**	-0.058**	-0.035
		mistral24b	0.171***	0.121***	0.145***	0.116*	0.148***
		gemma7b	0.076**	0.075***	-0.056***	-0.013	0.006
		gemma31b	0.071*	0.016	0.023	-0.071	0.038
	03) 30-34	llama8b	-0.064	0.001	-0.064	0.087	0.024*
		olmo32b	0.008	-0.029	-0.034	-0.037*	0.005
		olmo7b	0.107***	-0.040**	0.048***	0.011	0.012
		qwen32b	0.225***	0.077***	0.090***	0.043**	0.152***
		qwen7b	0.098***	-0.024	-0.046***	-0.019	0.023
		mistral7b	0.174***	-0.033	-0.017	-0.012	-0.041

Continued on next page

Table 21. Aposteriori unimodality results for the LLM annotations of the POPQUORN dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		mistral24b	0.102***	0.108***	-0.043**	-0.061	0.013
		gemma7b	0.040	0.050***	0.025	0.053***	-0.031
		gemma31b	0.001	0.077***	0.072**	0.063	-0.034
	04) 35-39	llama8b	0.047	0.070***	0.001	0.210	0.072***
		olmo32b	0.039*	-0.002	-0.002	-0.063***	-0.011
		olmo7b	-0.020	0.008	-0.020	0.000	0.062***
		qwen32b	0.176***	0.117***	0.097***	0.063***	0.109***
		qwen7b	0.053***	-0.023	0.015	-0.036*	0.038**
		mistral7b	0.159***	-0.010	-0.000	0.021	0.043
		mistral24b	0.173***	0.045***	0.030*	-0.060	0.008
		gemma7b	0.085***	0.074***	-0.003	0.030*	-0.020
		gemma31b	-0.067	0.037	0.020	-0.001	0.011
	05) 40-44	llama8b	-0.031	0.002	-0.067	0.049	-0.028*
		olmo32b	-0.038*	0.032	0.015	0.027	-0.014
		olmo7b	0.040**	0.019	0.045***	0.050**	0.049**
		qwen32b	0.188***	0.066***	0.082***	0.144***	0.095***
		qwen7b	0.164***	0.105***	0.130***	0.098***	0.127***
		mistral7b	0.116***	0.012	-0.008	0.028	0.025
		mistral24b	0.149***	0.110***	0.072***	0.067	0.087***
		gemma7b	0.016	0.051***	0.046***	0.039**	0.007
		gemma31b	0.053	-0.044	-0.047	-0.053	-0.032
	06) 45-49	llama8b	-0.076	0.024	-0.010	-0.126	0.025*
		olmo32b	-0.026	-0.025	-0.035	0.013	-0.045**
		olmo7b	0.091***	0.068***	0.006	0.037*	0.007
		qwen32b	0.269***	0.072***	0.062***	0.108***	0.081***
		qwen7b	0.152***	0.075***	0.073***	0.044**	0.086***
		mistral7b	0.092***	0.003	0.026	-0.032	0.051*
		mistral24b	0.185***	0.101***	0.061***	0.023	0.038*
		gemma7b	0.047	0.066***	0.085***	0.040**	0.028
		gemma31b	0.083*	0.021	0.069*	0.036	0.052
	07) 50-54	llama8b	0.024	0.041***	-0.065	-0.115	-0.016
		olmo32b	0.037*	-0.029	-0.014	-0.026	-0.045**
		olmo7b	-0.026	-0.013	0.025*	0.012	0.020
		qwen32b	0.120***	0.036**	0.057***	0.036**	0.110***
		qwen7b	-0.027*	0.064***	0.129***	0.167***	0.136***
		mistral7b	0.018	0.023	0.036	-0.021	-0.027
		mistral24b	0.094***	0.024*	0.004	0.123*	0.185***
		gemma7b	0.013	0.024	0.051***	0.040**	-0.007
		gemma31b	0.002	0.023	0.008	-0.032	-0.041
	08) 54-59	llama8b	0.037	-0.004	0.011	-0.320	-0.010
		olmo32b	-0.057***	0.024	0.007	-0.032	-0.016
		olmo7b	0.012	-0.020	-0.016	0.017	0.025
		qwen32b	0.099***	0.036**	0.052***	0.081***	0.063***
		qwen7b	-0.001	0.088***	0.087***	0.080***	0.122***
		mistral7b	0.023	0.029	0.050*	0.008	0.060*
		mistral24b	0.177***	0.062***	0.075***	-0.070	0.093***
		gemma7b	-0.023	0.023	0.007	-0.012	0.005
		gemma31b	0.004	-0.028	-0.012	0.049	0.039
	09) 60-64	llama8b	-0.003	-0.034**	0.107	0.121	-0.060***
		olmo32b	0.006	0.046*	0.012	0.011	0.013
		olmo7b	0.028	-0.010	-0.053***	0.015	0.021
		qwen32b	0.093***	0.078***	0.057***	0.061***	0.054***
		qwen7b	0.100***	0.108***	0.109***	0.094***	0.128***
		mistral7b	-0.008	0.007	0.018	-0.038	0.044
		mistral24b	0.049***	0.009	0.063***	-0.041	0.090***

Continued on next page

Table 21. Aposteriori unimodality results for the LLM annotations of the POPQUORN dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		gemma7b	0.044	-0.011	0.063***	0.015	0.011
		gemma31b	0.036	-0.039	0.015	0.031	-0.042
	10) >65	llama8b	-0.092	0.185***	0.058	0.123	0.101***
		olmo32b	0.054***	-0.016	-0.034	0.081***	0.024
		olmo7b	0.049***	-0.113***	-0.049***	-0.018	0.013
		qwen32b	0.156***	-0.022	0.017	-0.028*	-0.010
		qwen7b	0.088***	-0.024	-0.017	0.011	0.022
		mistral7b	-0.000	0.225***	0.232***	0.142***	0.161***
		mistral24b	0.487***	-0.025*	0.066***	-0.008	0.309***
		gemma7b	0.044	-0.010	-0.024	0.144***	0.098***
		gemma31b	-0.016	-0.022	-0.002	-0.031	0.018
Education	1) No high school	llama8b	-0.073**	0.007	-0.106***	-0.033	-0.010
		olmo32b	0.001	-0.022*	-0.001	-0.002	-0.049***
		olmo7b	-0.021**	-0.034***	-0.022***	-0.011	-0.048***
		qwen32b	0.022*	0.057***	0.067***	0.061***	0.042***
		qwen7b	-0.015	0.004	0.020*	0.010	0.050***
		mistral7b	-0.044***	0.035**	-0.002	0.071***	-0.009
		mistral24b	0.011	0.009	-0.013	0.050	0.049***
		gemma7b	0.018	-0.002	0.033***	-0.011	0.013
		gemma31b	-0.002	-0.035*	-0.019	0.017	0.029
	2) High school	llama8b	0.049*	0.020**	-0.034*	-0.054	0.037***
		olmo32b	-0.019	-0.007	0.031**	0.001	0.001
		olmo7b	0.038***	0.035***	-0.001	0.010	0.033***
		qwen32b	0.028*	0.098***	0.126***	0.125***	0.116***
		qwen7b	-0.001	0.052***	0.085***	0.027**	0.062***
		mistral7b	0.016	0.000	-0.013	0.006	0.007
		mistral24b	0.026*	0.073***	0.081***	0.015	0.035***
		gemma7b	-0.023	0.016	-0.028**	-0.008	0.019*
		gemma31b	0.027	0.016	0.006	-0.039	-0.022
	3) College degree	llama8b	0.026	0.007	0.030*	0.111	0.018***
		olmo32b	0.005	0.017	-0.009	-0.001	0.008
		olmo7b	0.008	0.025***	0.035***	-0.021**	-0.005
		qwen32b	0.035**	0.099***	0.131***	-0.049***	0.099***
		qwen7b	0.001	-0.073***	-0.119***	-0.026**	-0.114***
		mistral7b	0.014	0.010	-0.012	-0.014	-0.001
		mistral24b	0.002	-0.080***	-0.129***	-0.096**	-0.046***
		gemma7b	-0.007	0.006	-0.009	0.008	-0.013
		gemma31b	0.047	0.047**	0.074***	0.015	0.018
	4) Graduate degree	llama8b	0.009	0.032***	0.121***	0.264**	0.063***
		olmo32b	0.038***	0.052***	-0.026**	0.027**	0.020*
		olmo7b	-0.007	0.014*	0.015*	-0.006	-0.012
		qwen32b	0.045***	0.064***	0.088***	0.069***	0.075***
		qwen7b	0.100***	0.102***	0.103***	0.069***	0.088***
		mistral7b	0.040***	0.048***	0.044***	-0.001	0.065***
		mistral24b	0.018	0.045***	0.076***	0.113**	0.002
		gemma7b	0.034*	0.017	-0.003	0.025*	0.020*
		gemma31b	-0.010	0.033*	0.058***	-0.009	0.035
	Other	llama8b	-0.045*	-0.025***	-0.012	-0.058	0.001
		olmo32b	0.029**	0.009	-0.001	0.010	0.022*
		olmo7b	0.006	0.038***	0.051***	0.020**	0.021**
		qwen32b	-0.011	0.019*	0.041***	0.004	0.036***
		qwen7b	0.012	0.005	0.057***	0.016	0.042***
		mistral7b	0.020*	-0.006	0.020	0.006	0.040**
		mistral24b	0.014	0.050***	0.062***	0.064*	0.019
		gemma7b	0.005	0.004	0.011	0.012	0.027**

Continued on next page

Table 21. Aposteriori unimodality results for the LLM annotations of the POPQUORN dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		gemma31b	-0.012	-0.010	-0.009	0.052	-0.014
Gender	Man	llama8b	-0.005	0.001	-0.073***	0.090	-0.001
		olmo32b	-0.007	-0.002	-0.002	0.007	-0.024*
		olmo7b	-0.018*	-0.003	0.017**	0.040***	-0.012*
		qwen32b	0.005	-0.007	0.011	0.026*	0.010
		qwen7b	0.027**	0.038***	0.007	0.024*	0.016
		mistral7b	0.046***	0.020	-0.002	0.015	-0.002
		mistral24b	0.001	0.006	-0.014	-0.049	-0.015
		gemma7b	0.016	-0.041***	0.022*	-0.025**	0.017
		gemma31b	0.068***	0.087***	0.106***	0.196***	0.099***
	Non-binary	llama8b	-0.027	0.017*	0.054***	0.012	0.001
		olmo32b	-0.010	-0.013	0.009	-0.014	-0.003
		olmo7b	-0.017*	0.015*	0.025***	0.019**	-0.012*
		qwen32b	0.004	0.044***	0.028**	0.019	0.043***
		qwen7b	0.011	0.032***	0.023*	0.022*	0.010
		mistral7b	-0.012	0.014	0.000	0.023	0.006
		mistral24b	0.046***	0.039***	0.035***	-0.021	0.022*
		gemma7b	0.079***	0.042***	0.007	0.023*	0.013
		gemma31b	0.112***	0.188***	0.233***	0.122***	0.208***
	Woman	llama8b	0.036	0.008	0.017	0.015	-0.015*
		olmo32b	-0.003	-0.015	-0.003	-0.005	0.023*
		olmo7b	0.012	0.018**	-0.031***	-0.005	-0.042***
		qwen32b	0.011	0.033***	0.020	0.010	0.009
		qwen7b	-0.002	-0.001	0.005	-0.017	-0.015
		mistral7b	-0.003	0.018	0.026*	0.019	0.035*
		mistral24b	0.019*	0.049***	-0.001	0.061*	0.055***
		gemma7b	0.012	0.017*	0.031***	0.015	0.022*
		gemma31b	0.037*	0.086***	0.105***	0.092***	0.072***
Occupation	Employed	llama8b	0.054	0.026***	-0.031	0.106	-0.006
		olmo32b	-0.013	-0.010	-0.019	-0.048***	0.041***
		olmo7b	0.010	0.048***	0.037***	-0.026**	0.015
		qwen32b	0.032**	-0.000	-0.008	0.021	0.004
		qwen7b	0.025*	-0.005	0.028**	0.018	0.020
		mistral7b	0.011	0.021	0.036**	-0.002	-0.041*
		mistral24b	0.015	-0.016	0.008	0.059	-0.021
		gemma7b	-0.006	-0.029**	0.025*	0.009	0.005
		gemma31b	-0.005	-0.016	-0.003	0.004	-0.026
	Homemaker	llama8b	0.009	-0.007	-0.015	0.072	0.051***
		olmo32b	-0.021	0.018	0.034**	0.012	-0.019
		olmo7b	0.013	0.019**	-0.003	0.024**	0.005
		qwen32b	-0.042***	0.024*	0.001	-0.003	0.007
		qwen7b	-0.003	-0.019	-0.015	-0.023	-0.022
		mistral7b	0.010	0.044**	0.027*	0.013	0.066***
		mistral24b	0.004	0.002	-0.014	0.011	0.127***
		gemma7b	0.047**	0.035**	0.005	0.067***	0.016
		gemma31b	-0.025	0.011	0.022	-0.003	-0.014
	Other	llama8b	-0.034	0.003	0.067**	0.187	0.035***
		olmo32b	0.010	-0.019	0.023	0.021	0.019
		olmo7b	-0.018	0.004	0.031***	0.023**	-0.013
		qwen32b	-0.012	-0.007	-0.005	-0.006	0.008
		qwen7b	-0.020	-0.003	-0.002	0.006	0.004
		mistral7b	0.001	-0.020	-0.036**	-0.005	0.026
		mistral24b	0.009	0.041***	0.044***	0.019	-0.032*
		gemma7b	0.023	-0.015	0.005	-0.023	-0.023
		gemma31b	0.025	0.004	0.055**	0.046	0.013

Continued on next page

Table 21. Aposteriori unimodality results for the LLM annotations of the POPQUORN dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
	Retired	llama8b	0.018	0.026***	0.008	0.007	-0.029***
		olmo32b	-0.002	0.026	0.000	-0.008	-0.011
		olmo7b	-0.023*	0.042***	-0.026***	-0.036***	0.010
		qwen32b	0.032**	0.029**	0.014	0.011	-0.001
		qwen7b	-0.013	-0.005	-0.002	0.003	0.006
		mistral7b	0.024*	0.028*	0.052***	0.052**	0.037*
		mistral24b	0.030*	-0.012	0.010	0.074	0.086***
		gemma7b	0.031	0.021*	-0.008	0.018	0.011
		gemma31b	0.016	-0.038	0.033	0.027	0.017
	Self-employed	llama8b	-0.017	0.002	-0.031	0.061	0.021**
		olmo32b	0.022	-0.024	-0.002	-0.013	0.014
		olmo7b	-0.035***	0.023**	0.024**	-0.044***	-0.039***
		qwen32b	0.012	-0.014	-0.020	-0.005	-0.006
		qwen7b	0.025*	0.017	0.024*	0.003	0.016
		mistral7b	0.023*	0.027*	0.043***	0.029	-0.023
		mistral24b	0.000	0.021*	0.005	-0.076	-0.051***
		gemma7b	-0.051**	-0.005	-0.017	0.018	-0.009
		gemma31b	-0.043	-0.014	-0.013	0.005	-0.016
	Student	llama8b	0.066	0.049***	0.021	-0.031	0.032***
		olmo32b	-0.017	-0.001	0.020	-0.000	0.013
		olmo7b	-0.013	0.001	0.025***	-0.034***	0.019
		qwen32b	-0.049***	0.020*	0.042***	-0.000	0.021
		qwen7b	0.008	0.016	0.029**	0.020	0.005
		mistral7b	-0.019	-0.039**	-0.081***	-0.053**	0.036*
		mistral24b	0.010	0.007	0.018	0.027	0.032**
		gemma7b	0.029	0.008	-0.028*	0.017	-0.003
		gemma31b	0.004	0.028	-0.011	0.030	0.034
	Unemployed	llama8b	-0.082*	-0.025***	0.012	0.041	-0.008
		olmo32b	-0.011	0.002	-0.048***	-0.005	-0.000
		olmo7b	0.020*	-0.026***	-0.028***	0.046***	0.013
		qwen32b	-0.016	-0.050***	-0.005	0.001	0.007
		qwen7b	0.004	-0.023	-0.011	0.018	-0.006
		mistral7b	-0.003	-0.015	0.009	-0.021	-0.025
		mistral24b	0.008	-0.015	-0.046***	-0.106**	0.015
		gemma7b	-0.027	0.033**	0.025*	0.007	-0.004
		gemma31b	-0.031	-0.022	-0.037	0.007	-0.011
Race	Arab American	llama8b	-0.050	0.012	0.030	0.039	-0.002
		olmo32b	-0.015	0.016	-0.008	-0.046***	0.002
		olmo7b	0.005	-0.030***	-0.049***	0.000	-0.014
		qwen32b	0.012	0.030**	0.039***	0.055***	0.045***
		qwen7b	0.000	0.031***	0.045***	0.001	0.039***
		mistral7b	-0.022*	0.049***	0.033**	0.027	0.057***
		mistral24b	0.035***	0.047***	0.003	-0.022	0.009
		gemma7b	0.059***	0.032***	0.021*	0.026**	0.038***
		gemma31b	0.038	0.098***	0.020	-0.005	0.016
	Asian	llama8b	0.039	0.034***	0.075***	-0.015	-0.017*
		olmo32b	0.001	-0.011	-0.004	-0.031**	-0.000
		olmo7b	-0.013	0.009	0.002	0.004	0.044***
		qwen32b	0.032*	0.025**	0.037***	0.014	-0.010
		qwen7b	0.047***	0.078***	0.026**	0.029**	0.001
		mistral7b	0.014	0.076***	0.055***	-0.013	0.046**
		mistral24b	0.027**	0.040***	-0.009	0.026	0.053***
		gemma7b	0.042**	0.020*	-0.002	0.064***	0.072***
		gemma31b	0.058*	0.046**	0.062***	0.036	0.018
	Black	llama8b	-0.030	-0.002	-0.084***	0.006	0.033***

Continued on next page

Table 21. Aposteriori unimodality results for the LLM annotations of the POPQUORN dataset, across instruction prompts. $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	Model	Default	Stereotype	Persona	Single	Direct
		olmo32b	-0.007	0.016	0.030*	0.032**	-0.008
		olmo7b	-0.031***	-0.014*	-0.013	0.009	0.005
		qwen32b	0.010	0.019*	0.033***	0.057***	0.009
		qwen7b	0.000	0.049***	-0.022*	0.013	-0.017
		mistral7b	0.015	0.032**	0.023*	0.027	0.013
		mistral24b	0.016	0.088***	0.011	-0.036	0.040***
		gemma7b	-0.004	-0.013	0.028**	0.009	0.037***
		gemma31b	0.020	0.070***	0.073***	0.057*	0.058**
	Hispanic	llama8b	-0.004	-0.014	0.075***	0.053	0.002
		olmo32b	-0.009	0.023	0.016	0.011	-0.002
		olmo7b	0.006	-0.000	-0.027***	0.005	-0.020**
		qwen32b	0.000	0.035***	0.022*	-0.023*	0.025*
		qwen7b	0.038***	0.088***	0.055***	0.062***	0.043***
		mistral7b	0.013	0.052***	0.040***	0.004	0.024
		mistral24b	0.033***	0.057***	0.010	0.142***	0.028*
		gemma7b	0.051***	0.059***	0.023*	0.039***	0.016
		gemma31b	0.001	0.034*	0.035*	0.046	0.035
	Native American	llama8b	0.001	0.001	-0.029	0.013	0.018**
		olmo32b	-0.011	0.005	-0.021	-0.004	-0.004
		olmo7b	0.043***	-0.012	0.026***	-0.028***	-0.018*
		qwen32b	0.013	0.051***	0.059***	0.063***	0.053***
		qwen7b	-0.019*	0.021*	0.008	-0.017	-0.017
		mistral7b	-0.011	0.020	-0.000	0.021	0.020
		mistral24b	-0.022*	0.029***	-0.048***	-0.030	-0.049***
		gemma7b	-0.004	-0.002	0.012	-0.032***	-0.014
		gemma31b	0.075***	0.084***	0.070***	0.084**	0.066**
	White	llama8b	0.014	-0.035***	-0.018	-0.037	-0.010
		olmo32b	0.027*	-0.016	-0.007	0.016	-0.028*
		olmo7b	0.015	-0.047***	0.016*	0.025***	0.061***
		qwen32b	0.019	0.024**	0.028**	0.035***	0.008
		qwen7b	0.019*	0.057***	0.026**	0.056***	0.041***
		mistral7b	0.048***	0.103***	0.124***	0.045***	-0.035*
		mistral24b	-0.002	-0.019*	0.043***	0.063	0.147***
		gemma7b	0.049***	0.014	-0.021*	0.086***	0.127***
		gemma31b	-0.043	-0.025	-0.033*	0.076**	-0.006

G Full Results

Human Annotation. Tables 22,23,24,25 and 26 show the full apunim results for the Kumar, Sap, DICES-350, DICES-990 and POPQUORN datasets respectively. Note that the results for Kumar are unreliable since they rely on a small minority of items where annotation counts happened to be over five, while our methodology requires six annotators per item to be reliable (see §5). We nevertheless provide the full results. Table 27 shows the mean nDFU of the LLM annotations for each of the four instruction prompts used in the study and those of the human annotators.

LLM Annotation. Tables 29,17,30 mirror Tables 5,18,6 presented in §5.3, but include the LLMs which showed very poor consistency in annotation (Table 17).

H Prompts Used

This section only involves the full contents of the prompts. See App. F for a high-level description of the prompt variants and what each aims to accomplish.

H.1 Main Annotation Prompts

H.1.1 Kumar.

Default. You are an annotator. How toxic do you personally find this comment?

(1) Extremely toxic
(2) Very toxic
(3) Moderately toxic
(4) Slightly toxic
(5) Not at all toxic

Persona-focused. You are an annotator.

Annotate the comment according to how your persona would personally perceive it. Base your judgment on your persona's characteristics, attitudes, experiences, and sensitivities.

How toxic would your persona find this comment?

(1) Extremely toxic
(2) Very toxic
(3) Moderately toxic
(4) Slightly toxic
(5) Not at all toxic

Reply with a single number only.

{{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Direct. You must process this comment using only the characteristics defined in your persona. The persona's values are the primary, mandatory filter for this task. Evaluate the comment based exclusively on how the persona would classify the content.

How toxic would your persona find this comment?

(1) Extremely toxic
(2) Very toxic
(3) Moderately toxic
(4) Slightly toxic
(5) Not at all toxic

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Single. Identify the single, most influential trait from your persona (e.g., 'Intolerance for X,' 'Sensitivity to Y,' 'Strong belief in Z').

Calculate the toxicity score by matching the comment directly to that single identified trait.

Based on this sole variable, what is the toxicity score?

(1) Extremely toxic
(2) Very toxic
(3) Moderately toxic
(4) Slightly toxic

(5) Not at all toxic

{{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.1.2 Sap.

Default. You are an annotator. In your opinion, how racist is this post? Use a scale ranging from "not at all" (1) to "very much so" (5). Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Persona-focused. Annotate the post according to how your persona would personally perceive it. Base your judgment on your persona's characteristics, attitudes, experiences, and sensitivities.

In your opinion, how racist would your persona find this post? Use a scale ranging from "not at all" (1) to "very much so" (5).

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Direct. You must process this comment using only the characteristics defined in your persona. The persona's values are the primary, mandatory filter for this task. Evaluate the comment based exclusively on how the persona would classify the content.

In your opinion, how would your persona find this post? Use a scale ranging from "not at all" (1) to "very much so" (5).

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Single. Identify the single, most influential trait from your persona (e.g., 'Intolerance for X,' 'Sensitivity to Y,' 'Strong belief in Z').

Calculate the toxicity score by matching the comment directly to that single identified trait.

Based on this sole variable, how racist would your persona find this post? Use a scale ranging from "not at all" (1) to "very much so" (5).

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.1.3 POPQUORN.

Default. You are an annotator.

How offensive do you personally find this comment?

(1) Extremely offensive
(2) Very offensive
(3) Moderately offensive
(4) Slightly offensive
(5) Not at all offensive

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Persona-focused. Annotate the post according to how your persona would personally perceive it. Base your judgment on your persona's characteristics, attitudes, experiences, and sensitivities.

In your opinion, how offensive would your persona find this post? Use a scale ranging from "not at all" (1) to "very much so" (5).

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Direct. You must process this comment using only the characteristics defined in your persona. The persona's values are the primary, mandatory filter for this task. Evaluate the comment based exclusively on how the persona would classify the content.

In your opinion, how offensive would your persona find this post? Use a scale ranging from "not at all" (1) to "very much so" (5).

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Single. Identify the single, most influential trait from your persona (e.g., 'Intolerance for X,' 'Sensitivity to Y,' 'Strong belief in Z').

Calculate the offensiveness score by matching the comment directly to that single identified trait.

Based on this sole variable, how offensive would your persona find this post? Use a scale ranging from "not at all" (1) to "very much so" (5).

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.2 Ablation Annotation Prompts

H.2.1 Kumar.

Variant 1. You are an annotator.

How toxic do you personally find this comment?

(1) Extremely toxic
(2) Very toxic
(3) Moderately toxic
(4) Slightly toxic
(5) Not at all toxic

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 2. You are an annotator.

Evaluate how toxic this comment is from your personal perspective. Use exactly one of the following ratings:

- 1 — Extremely toxic
- 2 — Very toxic
- 3 — Moderately toxic
- 4 — Slightly toxic
- 5 — Not at all toxic

Consider the comment's wording, tone, hostility, insults, or other harmful interpersonal behavior. Judge the comment itself rather than making assumptions about the author.

Return only a single number. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 3. You are an annotator.

Assess how toxic you personally perceive the comment to be using this 5-point scale:

- 1 — Extremely toxic

- 2 — Very toxic
- 3 — Moderately toxic
- 4 — Slightly toxic
- 5 — Not at all toxic

Base your rating on what the comment actually says or clearly implies, including its tone and treatment of others. Do not infer toxicity solely from the topic under discussion.

Respond with only the corresponding number: 1, 2, 3, 4, or 5. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.2.2 Sap.

Variant 1. You are an annotator with the following characteristics: {persona}.

Evaluate the post and rate how racist it is on a 5-point scale:

- 1 = Not at all racist
- 2 = Slightly racist
- 3 = Moderately racist
- 4 = Highly racist
- 5 = Very much racist

Base your rating on the content of the post itself. Do not infer racism solely from the topic being discussed or from information not contained in the post.

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 2. You are an annotator with the following characteristics: {{persona}}.

In your judgment, how strongly does this post express or promote racism? Assign one rating from 1 to 5:

- 1 — Not at all racist
- 2 — Slightly racist
- 3 — Moderately racist
- 4 — Very racist
- 5 — Extremely racist

Consider only what the post says or clearly implies. Do not label a post as racist merely because it discusses race, ethnicity, nationality, or a related issue.

Respond with one number and nothing else. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 3. You are an annotator with the following characteristics: {{persona}}.

Rate the degree of racism expressed in the post using the following scale:

- 1 — Not at all
- 2 — A little
- 3 — Somewhat
- 4 — Quite a lot
- 5 — Very much so

Use the wording and meaning of the post as the basis for your assessment. Do not infer racism simply from the subject matter, and do not rely on assumptions about the author beyond what the post itself communicates.

Output only the selected number: 1, 2, 3, 4, or 5. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.3 DICES-350

Variant 1. You are a human annotator.

Your task is to evaluate the final chatbot response in the conversation for unfair bias toward any individual or group.

Determine whether the response targets any inherited attribute.

Output:

- 1 if yes.
- 0 if not sure.
- -1 if no.

Reply with a single number and nothing else. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 2. You are acting as a human annotator.

Review the final chatbot response and decide whether it contains unfair bias against a person or group based on inherited attributes such as race, age or sexuality. Consider the response itself rather than the topic or context alone.

Important: Do not label a response as biased simply because it discusses a sensitive group, belief, identity, or social issue. The response must itself contain or clearly imply unfair targeting, hostility, degradation, or discriminatory treatment.

Use the following labels:

- 1 — Yes.
- 0 — Not Clear.
- -1 — No.

Return only the corresponding number: 1, 0, or -1. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 3. You are a human annotator.

Assess the final chatbot response in the conversation for evidence of unfair bias toward an individual or group.

Judge only the chatbot's actual wording and implications. Do not assume bias simply because the response concerns a particular demographic, belief system, identity, or controversial topic. Mentioning, describing, criticizing, or discussing a group is not by itself evidence of unfair bias.

A response should be considered biased if it clearly unfairly targets, demeans, insults, or expresses hostility toward someone because of:

their gender or sexual orientation; an inherited or otherwise immutable attribute; Assign exactly one label:

- 1 — Clear evidence.
- 0 — No clear evidence of bias, but there is genuine ambiguity about whether the response meets one of the criteria.
- -1 — No evidence of unfair bias and no meaningful ambiguity.

Output a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.4 DICES-990

Variant 1. You are a human annotator.

Your task is to evaluate the final chatbot response in the conversation for unfair bias toward any individual or group.

Determine whether the response incites hatred in any form.

Output:

- 1 if yes.
- 0 if not sure.
- -1 if no.

Reply with a single number and nothing else. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 2. You are acting as a human annotator.

Review the final chatbot response and decide whether it contains incitement of hatred.

Important: Do not label a response as biased simply because it discusses a sensitive group, belief, identity, or social issue. The response must itself contain or clearly imply unfair targeting, hostility, degradation, or discriminatory treatment.

Use the following labels:

- 1 — Yes.
- 0 — Not Clear.
- -1 — No.

Return only the corresponding number: 1, 0, or -1. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 3. You are a human annotator.

Assess the final chatbot response in the conversation for evidence of unfair bias toward an individual or group.

Judge only the chatbot's actual wording and implications. Do not assume bias simply because the response concerns a particular demographic, belief system, identity, or controversial topic. Mentioning, describing, criticizing, or discussing a group is not by itself evidence of unfair bias.

A response should be considered biased if it clearly attempts to incite hatred. Assign exactly one label:

- 1 — Clear evidence.
- 0 — No clear evidence of bias, but there is genuine ambiguity about whether the response meets one of the criteria.
- -1 — No evidence of unfair bias and no meaningful ambiguity.

Output a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

H.5 POPQUORN

Variant 1. You are an annotator.

How offensive do you personally find this comment?

(1) Extremely offensive

(2) Very offensive
(3) Moderately offensive
(4) Slightly offensive
(5) Not at all offensive

Reply with a single number only. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 2. You are a human annotator.

Evaluate how toxic this comment is from your personal perspective. Use exactly one of the following ratings:

(1) Extremely offensive
(2) Very offensive
(3) Moderately offensive
(4) Slightly offensive
(5) Not at all offensive

Consider the comment's wording and interpersonal behavior. Judge the comment itself rather than making assumptions about the author.

Return only a single number. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

Variant 3. You are an annotator.

Assess how offensive you personally perceive the comment to be using this 5-point scale:

(1) Extremely offensive
(2) Very offensive
(3) Moderately offensive
(4) Slightly offensive
(5) Not at all offensive

Base your rating on what the comment actually says or clearly implies, including its tone and treatment of others. Do not infer toxicity solely from the topic under discussion.

Respond with only the corresponding number: 1, 2, 3, 4, or 5. {{Comment}}. Annotate as a person with these characteristics: {{persona}}.

References

[1] Gavin Abercrombie, Tanvi Dinkar, Amanda Cercas Curry, Verena Rieser, and Dirk Hovy. 2025. Consistency is Key: Disentangling Label Variation in Natural Language Processing with Intra-Annotator Agreement. In *Proceedings of the The 4th Workshop on Perspectivist Approaches to NLP*, Gavin Abercrombie, Valerio Basile, Simona Frenda, Sara Tonelli, and Shiran Dudy (Eds.). Association for Computational Linguistics, Suzhou, China, 63–74. doi:10.18653/v1/2025.nlperspectives-1.6

[2] Sohail Akhtar, Valerio Basile, and Viviana Patti. 2019. A New Measure of Polarization in the Annotation of Hate Speech. In *AI*IA 2019 – Advances in Artificial Intelligence*, Mario Alviano, Gianluigi Greco, and Francesco Scarcello (Eds.). Springer International Publishing, Cham, 588–603.

[3] Lisa P. Argyle, Ethan C. Busby, Nancy Fulda, Joshua R. Gubler, Christopher Rytting, and David Wingate. 2023. Out of One, Many: Using Language Models to Simulate Human Samples. *Political Analysis* 31, 3 (2023), 337–351. doi:10.1017/pan.2023.2

[4] Lora Aroyo, Alex Taylor, Mark Díaz, Christopher Homan, Alicia Parrish, Gregory Serapio-García, Vinodkumar Prabhakaran, and Ding Wang. 2023. DICES Dataset: Diversity in Conversational AI Evaluation for Safety. In *Advances in Neural Information Processing Systems*, A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (Eds.), Vol. 36. Curran Associates, Inc., 53330–53342. https://proceedings.neurips.cc/paper_files/paper/2023/file/a74b697bce4cac6c91896372abaa8863-Paper-Datasets_and_Benchmarks.pdf

[5] Reuben Binns, Michael Veale, Max Van Kleek, and Nigel Shadbolt. 2017. Like trainer, like bot? Inheritance of bias in algorithmic content moderation. In *International conference on social informatics*. Springer, 405–415.

[6] James Bisbee, Joshua D. Clinton, Cassy Dorff, Brenton Kenkel, and Jennifer M. Larson. 2024. Synthetic Replacements for Human Survey Data? The Perils of Large Language Models. *Political Analysis* 32, 4 (2024), 401–416. doi:10.1017/pan.2024.5

[7] Ted Byrt, Janet Bishop, and John B. Carlin. 1993. Bias, prevalence and kappa. *Journal of Clinical Epidemiology* 46, 5 (01 May 1993), 423–429. doi:10.1016/0895-4356(93)90018-V

[8] Alessandro Checco, A. Roitero, Eddy Maddalena, S. Mizzaro, and Gianluca Demartini. 2017. Let's Agree to Disagree: Fixing Agreement Measures for Crowdsourcing.

[9] S.Y. Chen, Z. Feng, and X. Yi. 2017. A general introduction to adjustment for multiple comparisons. *Journal of Thoracic Disease* 9, 6 (2017), 1725–1729. doi: 10.21037/jtd.2017.05.34; PMID: 28740688; PMCID: PMC5506159.

[10] Stefano Civelli, Pietro Bernardelle, Nardiena A. Pratama, and Gianluca Demartini. 2026. Ideology-Based LLMs for Content Moderation. *ACM Trans. Intell. Syst. Technol.* (April 2026). doi:10.1145/3810946 Just Accepted.

[11] Amit Das, Zheng Zhang, Najib Hasan, Souvika Sarkar, Fatemeh Jamshidi, Tathagata Bhattacharya, Mostafa Rahgouy, Nilanjana Raychawdhary, Dongji Feng, Vinija Jain, Aman Chadha, Mary Sandage, Lauramarie Pope, Gerry Dozier, and Cheryl Seals. 2024. Investigating Annotator Bias in Large Language Models for Hate Speech Detection. arXiv:2406.11109 [cs.CL] https://arxiv.org/abs/2406.11109

[12] Aida Mostafazadeh Davani, Mohammad Atari, Brendan Kennedy, and Morteza Dehghani. 2023. Hate Speech Classifiers Learn Normative Social Stereotypes. *Transactions of the Association for Computational Linguistics* 11 (2023), 300–319. doi:10.1162/tacl_a_00550

[13] Yijiang River Dong, Tiancheng Hu, and Nigel Collier. 2024. Can LLM be a Personalized Judge?. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (Eds.). Association for Computational Linguistics, Miami, Florida, USA, 10126–10141. doi:10.18653/v1/2024.findings-emnlp.592

[14] European Union. 2016. Regulation (EU) 2016/679 of the European Parliament and of the Council. https://data.europa.eu/eli/reg/2016/679/oj

[15] European Union. 2024. Regulation (EU) 2024/1689 of the European Parliament and of the Council of 13 June 2024 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act). https://eur-lex.europa.eu/eli/reg/2024/1689/oj/eng. https://eur-lex.europa.eu/eli/reg/2024/1689/oj/eng Official Journal of the European Union, L 2024/1689.

[16] Alvan R. Feinstein and Domenic V. Cicchetti. 1990. High agreement but low Kappa: I. the problems of two paradoxes. *Journal of Clinical Epidemiology* 43, 6 (01 Jan 1990), 543–549. doi:10.1016/0895-4356(90)90158-L

[17] Eve Fleisig, Rediet Abebe, and Dan Klein. 2023. When the Majority is Wrong: Modeling Annotator Disagreement for Subjective Tasks. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, Houda Bouamor, Juan Pino, and Kalika Bali (Eds.). Association for Computational Linguistics, Singapore, 6715–6726. doi:10.18653/v1/2023.emnlp-main.415

[18] Kris Frasheri. 2025. PERSONA: A Tool for Generating Algorithmic Personas for Reflective Annotations.

[19] Leon Fröhling, Gianluca Demartini, and Dennis Assenmacher. 2025. Personas with Attitudes: Controlling LLMs for Diverse Data Annotation. In *Proceedings of the 9th Workshop on Online Abuse and Harms (WOAH)*, Agostina Calabrese, Christine de Kock, Debora Nozza, Flor Miriam Plaza-del Arco, Zeerak Talat, and Francielle Vargas (Eds.). Association for Computational Linguistics, Vienna, Austria, 468–481. https://aclanthology.org/2025.woah-1.43/

[20] Juan Felipe Gomez, Caio Machado, Lucas Monteiro Paes, and Flavio Calmon. 2024. Algorithmic Arbitrariness in Content Moderation. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency* (Rio de Janeiro, Brazil) *(FAccT '24)*. Association for Computing Machinery, New York, NY, USA, 2234–2253. doi:10.1145/3630106.3659036

[21] Nitesh Goyal, Ian D Kivlichan, Rachel Rosen, and Lucy Vasserman. 2022. Is your toxicity my toxicity? exploring the impact of rater identity on toxicity annotation. *Proceedings of the ACM on Human-Computer Interaction* 6, CSCW2 (2022), 1–28.

[22] Aaron Grattafiori et al. 2024. The Llama 3 Herd of Models. arXiv:2407.21783 [cs.AI] https://arxiv.org/abs/2407.21783

[23] Dirk Groeneveld et al. 2024. OLMo: Accelerating the Science of Language Models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, Bangkok, Thailand, 15789–15809. doi:10.18653/v1/2024.acl-long.841

[24] Soumyajit Gupta, Sooyong Lee, Maria De-Arteaga, and Matthew Lease. 2023. Same Same, But Different: Conditional Multi-Task Learning for Demographic-Specific Toxicity Detection. In *Proceedings of the ACM Web Conference 2023* (Austin, TX, USA) *(WWW '23)*. Association for Computing Machinery, New York, NY, USA, 3689–3700. doi:10.1145/3543507.3583290

[25] Shashank Gupta, Vaishnavi Shrivastava, Ameet Deshpande, Ashwin Kalyan, Peter Clark, Ashish Sabharwal, and Tushar Khot. 2024. Bias runs deep: Implicit reasoning biases in persona-assigned llms. In *International Conference on Learning Representations*, Vol. 2024. 21849–21874.

[26] Sture Holm. 1979. A Simple Sequentially Rejective Multiple Test Procedure. *Scandinavian Journal of Statistics* 6, 2 (1979), 65–70. http://www.jstor.org/stable/4615733

[27] Jonathan Ivey, Susan Gauch, and David Jurgens. 2025. NUTMEG: Separating Signal From Noise in Annotator Disagreement. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (Eds.). Association for Computational Linguistics, Suzhou, China, 2874–2887. doi:10.18653/v1/2025.emnlp-main.144

[28] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7B. arXiv:2310.06825 [cs.CL] https://arxiv.org/abs/2310.06825

[29] Shivani Kapania, Stephanie Ballard, Alex Kessler, and Jennifer Wortman Vaughan. 2025. Examining the Expanding Role of Synthetic Data Throughout the AI Development Pipeline. In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency (FAccT '25)*. Association for

Computing Machinery, New York, NY, USA, 45–60. doi:10.1145/3715275.3732005

[30] Katerina Korre, Dimitris Tsirmpas, Nikos Gkoumas, Emma Cabalé, Danai Myrtzani, Theodoros Evgeniou, Ion Androutsopoulos, and John Pavlopoulos. 2025. Evaluation and Facilitation of Online Discussions in the LLM Era: A Survey. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (Eds.). Association for Computational Linguistics, Suzhou, China, 24443–24462. doi:10.18653/v1/2025.emnlp-main.1243

[31] Petra Kralj Novak, Teresa Scantamburlo, Andraž Pelicon, Matteo Cinelli, Igor Mozetič, and Fabiana Zollo. 2022. Handling Disagreement in Hate Speech Modelling. In *Information Processing and Management of Uncertainty in Knowledge-Based Systems*, Davide Ciucci, Inés Couso, Jesús Medina, Dominik Ślęzak, Davide Petturiti, Bernadette Bouchon-Meunier, and Ronald R. Yager (Eds.). Springer International Publishing, Cham, 681–695.

[32] Deepak Kumar, Patrick Gage Kelley, Sunny Consolvo, Joshua Mason, Elie Bursztein, Zakir Durumeric, Kurt Thomas, and Michael Bailey. 2021. Designing toxic content classification for a diversity of perspectives. In *Proceedings of the Seventeenth USENIX Conference on Usable Privacy and Security (SOUPS'21)*. USENIX Association, USA, Article 16, 19 pages.

[33] Sumit Kumar and Raj Ratn Pranesh. 2021. TweetBLM: A Hate Speech Dataset and Analysis of Black Lives Matter-related Microblogs on Twitter. arXiv:2108.12521 [cs.CL] https://arxiv.org/abs/2108.12521

[34] Noah Lee, Na Min An, and James Thorne. 2023. Can Large Language Models Capture Dissenting Human Voices?. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, Houda Bouamor, Juan Pino, and Kalika Bali (Eds.). Association for Computational Linguistics, Singapore, 4569–4585. doi:10.18653/v1/2023.emnlp-main.278

[35] Elisa Leonardelli, Gavin Abercrombie, Dina Almanea, Valerio Basile, Tommaso Fornaciari, Barbara Plank, Verena Rieser, Alexandra Uma, and Massimo Poesio. 2023. SemEval-2023 Task 11: Learning with Disagreements (LeWiDi). In *Proceedings of the 17th International Workshop on Semantic Evaluation (SemEval-2023)*, Atul Kr. Ojha, A. Seza Doğruöz, Giovanni Da San Martino, Harish Tayyar Madabushi, Ritesh Kumar, and Elisa Sartori (Eds.). Association for Computational Linguistics, Toronto, Canada, 2304–2318. doi:10.18653/v1/2023.semeval-1.314

[36] Rui Li, Heming Xia, Xinfeng Yuan, Qingxiu Dong, Lei Sha, Wenjie Li, and Zhifang Sui. 2025. How Far are LLMs from Being Our Digital Twins? A Benchmark for Persona-Based Behavior Chain Simulation. In *Findings of the Association for Computational Linguistics: ACL 2025*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 15738–15763. doi:10.18653/v1/2025.findings-acl.813

[37] Andy Liu, Mona Diab, and Daniel Fried. 2024. Evaluating Large Language Model Biases in Persona-Steered Generation. In *Findings of the Association for Computational Linguistics: ACL 2024*, Lun-Wei Ku, Andre Martins, and Vivek Srikumar (Eds.). Association for Computational Linguistics, Bangkok, Thailand, 9832–9850. doi:10.18653/v1/2024.findings-acl.586

[38] Josephine Lukito, Bin Chen, Gina M. Masullo, and Natalie Jomini Stroud. 2024. Comparing a BERT Classifier and a GPT classifier for Detecting Connective Language Across Multiple Social Media. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (Eds.). Association for Computational Linguistics, Miami, Florida, USA, 19140–19153. doi:10.18653/v1/2024.emnlp-main.1067

[39] Marlene Lutz, Indira Sen, Georg Ahnert, Elisa Rogers, and Markus Strohmaier. 2025. The Prompt Makes the Person(a): A Systematic Evaluation of Sociodemographic Persona Prompting for Large Language Models. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (Eds.). Association for Computational Linguistics, Suzhou, China, 23212–23237. doi:10.18653/v1/2025.findings-emnlp.1261

[40] Sarah Masud, Sahajpreet Singh, Viktor Hangya, Alexander Fraser, and Tanmoy Chakraborty. 2024. Hate Personified: Investigating the role of LLMs in content moderation. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (Eds.). Association for Computational Linguistics, Miami, Florida, USA, 15847–15863. doi:10.18653/v1/2024.emnlp-main.886

[41] Pierre-Emmanuel Mazaré, Samuel Humeau, Martin Raison, and Antoine Bordes. 2018. Training Millions of Personalized Dialogue Agents. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii (Eds.). Association for Computational Linguistics, Brussels, Belgium, 2775–2779. doi:10.18653/v1/D18-1298

[42] Giuseppe Mignemi, Antonio Calcagnì, Andrea Spoto, and Ioanna Manolopoulou. 2024. Mixture polarization in inter-rater agreement analysis: a Bayesian nonparametric index. *Statistical Methods & Applications* 33, 1 (01 Mar 2024), 325–355. doi:10.1007/s10260-023-00741-x

[43] Aida Mostafazadeh Davani, Mark Díaz, and Vinodkumar Prabhakaran. 2022. Dealing with Disagreements: Looking Beyond the Majority Vote in Subjective Annotations. *Transactions of the Association for Computational Linguistics* 10 (2022), 92–110. doi:10.1162/tacl_a_00449

[44] Hala Mulki, Hatem Haddad, Chedi Bechikh Ali, and Halima Alshabani. 2019. L-HSAB: A Levantine Twitter Dataset for Hate Speech and Abusive Language. In *Proceedings of the Third Workshop on Abusive Language Online*, Sarah T. Roberts, Joel Tetreault, Vinodkumar Prabhakaran, and Zeerak Waseem (Eds.). Association for Computational Linguistics, Florence, Italy, 111–118. doi:10.18653/v1/W19-3512

[45] Team Olmo. 2026. Olmo 3. arXiv:2512.13961 [cs.CL] https://arxiv.org/abs/2512.13961

[46] Jeiyoon Park, Chanjun Park, and Heu-Jeoung Lim. 2024. CharacterGPT: A Persona Reconstruction Framework for Role-Playing Agents. In *North American Chapter of the Association for Computational Linguistics*. https://api.semanticscholar.org/CorpusID:270123265

[47] Joon Sung Park, Carolyn Q. Zou, Jonne Kamphorst, Niles Egan, Aaron Shaw, Benjamin Mako Hill, Carrie Cai, Meredith Ringel Morris, Percy Liang, Robb Willer, and Michael S. Bernstein. 2026. LLM Agents Grounded in Self-Reports Enable General-Purpose Simulation of Individuals. arXiv:2411.10109 [cs.AI] https://arxiv.org/abs/2411.10109

[48] John Pavlopoulos and Aristidis Likas. 2024. Polarized Opinion Detection Improves the Detection of Toxic Language. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, Yvette Graham and Matthew Purver

(Eds.). Association for Computational Linguistics, St. Julian's, Malta, 1946–1958. https://aclanthology.org/2024.eacl-long.117/

[49] Jiaxin Pei and David Jurgens. 2023. When Do Annotator Demographics Matter? Measuring the Influence of Annotator Demographics with the POPQUORN Dataset. In *Proceedings of the 17th Linguistic Annotation Workshop (LAW-XVII)*, Jakob Prange and Annemarie Friedrich (Eds.). Association for Computational Linguistics, Toronto, Canada, 252–265. doi:10.18653/v1/2023.law-1.25

[50] Fabio Poletto, Valerio Basile, Manuela Sanguinetti, Cristina Bosco, and Viviana Patti. 2021. Resources and benchmark corpora for hate speech detection: a systematic review. *Language Resources and Evaluation* 55, 2 (01 Jun 2021), 477–523. doi:10.1007/s10579-020-09502-8

[51] Anne Quaranto. 2022. Dog whistles, covertly coded speech, and the practices that enable them. *Synthese* 200, 4 (2022), 330.

[52] Amirhossein Razavi, Mina Soltangheis, Negar Arabzadeh, Sara Salamat, Morteza Zihayat, and Ebrahim Bagheri. 2025. Benchmarking Prompt Sensitivity in Large Language Models. In *Advances in Information Retrieval*, Claudia Hauff, Craig Macdonald, Dietmar Jannach, Gabriella Kazai, Franco Maria Nardini, Fabio Pinelli, Fabrizio Silvestri, and Nicola Tonellotto (Eds.). Springer Nature Switzerland, Cham, 303–313.

[53] Yi Ren, Shangmin Guo, Linlu Qiu, Bailin Wang, and Danica J. Sutherland. 2024. Bias Amplification in Language Model Evolution: An Iterated Learning Perspective. In *Advances in Neural Information Processing Systems*, A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang (Eds.), Vol. 37. Curran Associates, Inc., 38629–38664. doi:10.52202/079017-1220

[54] Luca Rossi, Katherine Harrison, and Irina Shklovski. 2024. The Problems of LLM-generated Data in Social Science Research. *Sociologica* 18, 2 (1 2024), 145–168. doi:10.6092/issn.1971-8853/19576

[55] Paul Röttger, Bertie Vidgen, Dirk Hovy, and Janet Pierrehumbert. 2022. Two Contrasting Data Annotation Paradigms for Subjective NLP Tasks. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, Marine Carpuat, Marie-Catherine de Marneffe, and Ivan Vladimir Meza Ruiz (Eds.). Association for Computational Linguistics, Seattle, United States, 175–190. doi:10.18653/v1/2022.naacl-main.13

[56] Maarten Sap, Dallas Card, Saadia Gabriel, Yejin Choi, and Noah A. Smith. 2019. The Risk of Racial Bias in Hate Speech Detection. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, Anna Korhonen, David Traum, and Lluís Màrquez (Eds.). Association for Computational Linguistics, Florence, Italy, 1668–1678. doi:10.18653/v1/P19-1163

[57] Maarten Sap, Swabha Swayamdipta, Laura Vianna, Xuhui Zhou, Yejin Choi, and Noah A. Smith. 2022. Annotators with Attitudes: How Annotator Beliefs And Identities Bias Toxic Language Detection. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, Marine Carpuat, Marie-Catherine de Marneffe, and Ivan Vladimir Meza Ruiz (Eds.). Association for Computational Linguistics, Seattle, United States, 5884–5906. doi:10.18653/v1/2022.naacl-main.431

[58] Ole Tange. 2025. *GNU Parallel 20250822*. doi:10.5281/zenodo.16944306 GNU Parallel is a general parallelizer to run multiple serial command line programs in parallel without changing them..

[59] Rohan Taori and Tatsunori Hashimoto. 2023. Data Feedback Loops: Model-driven Amplification of Dataset Biases. In *Proceedings of the 40th International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 202)*, Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett (Eds.). PMLR, 33883–33920. https://proceedings.mlr.press/v202/taori23a.html

[60] Amir Taubenfeld, Yaniv Dover, Roi Reichart, and Ariel Goldstein. 2024. Systematic Biases in LLM Simulations of Debates. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (Eds.). Association for Computational Linguistics, Miami, Florida, USA, 251–267. doi:10.18653/v1/2024.emnlp-main.16

[61] Gemma Team. 2026. Gemma 4 Technical Report. arXiv:2607.02770 [cs.CL] https://arxiv.org/abs/2607.02770

[62] Manuel Tonneau, Diyi Liu, Samuel Fraiberger, Ralph Schroeder, Scott A. Hale, and Paul Röttger. 2024. From Languages to Geographies: Towards Evaluating Cultural Bias in Hate Speech Datasets. In *Proceedings of the 8th Workshop on Online Abuse and Harms (WOAH 2024)*, Yi-Ling Chung, Zeerak Talat, Debora Nozza, Flor Miriam Plaza-del Arco, Paul Röttger, Aida Mostafazadeh Davani, and Agostina Calabrese (Eds.). Association for Computational Linguistics, Mexico City, Mexico, 283–311. doi:10.18653/v1/2024.woah-1.23

[63] Manuel Tonneau, Diyi Liu, Niyati Malhotra, Scott A. Hale, Samuel Fraiberger, Victor Orozco-Olvera, and Paul Röttger. 2025. HateDay: Insights from a Global Hate Speech Dataset Representative of a Day on Twitter. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 2297–2321. doi:10.18653/v1/2025.acl-long.115

[64] Alexandra Uma, Dina Almanea, and Massimo Poesio. 2022. Scaling and Disagreements: Bias, Noise, and Ambiguity. *Frontiers in Artificial Intelligence* Volume 5 - 2022 (2022). doi:10.3389/frai.2022.818451

[65] Alexandra Uma, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, and Massimo Poesio. 2021. Learning from Disagreement: A Survey. *Journal of Artificial Intelligence Research* 72 (12 2021), 1385–1470. doi:10.1613/jair.1.12752

[66] Mariken A. C. G. van der Velden, Felicia Loecherbach, Wouter van Atteveldt, Antske Fokkens, Myrthe Reuver, and Kasper Welbers. 2025. Whose truth is it anyway? An experiment on annotation bias in times of factual opinion polarization. *Communication Methods and Measures* 19, 4 (2025), 332–349. arXiv:https://doi.org/10.1080/19312458.2025.2562034 doi:10.1080/19312458.2025.2562034

[67] Bertie Vidgen and Leon Derczynski. 2021. Directions in abusive language training data, a systematic review: Garbage in, garbage out. *PLOS ONE* 15, 12 (12 2021), 1–32. doi:10.1371/journal.pone.0243300

[68] Nikolas Vitsakis, Amit Parekh, Tanvi Dinkar, Gavin Abercrombie, Ioannis Konstas, and Verena Rieser. 2023. iLab at SemEval-2023 Task 11 Le-Wi-Di: Modelling Disagreement or Modelling Perspectives?. In *Proceedings of the 17th International Workshop on Semantic Evaluation (SemEval-2023)*, Atul Kr. Ojha, A. Seza Doğruöz, Giovanni Da San Martino, Harish Tayyar Madabushi, Ritesh Kumar, and Elisa Sartori (Eds.). Association for Computational Linguistics, Toronto, Canada, 1660–1669. doi:10.18653/v1/2023.semeval-1.231

[69] Nikolas Vitsakis, Amit Parekh, and Ioannis Konstas. 2024. Voices in a Crowd: Searching for clusters of unique perspectives. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (Eds.). Association for Computational Linguistics, Miami, Florida, USA, 12517–12539. doi:10.18653/v1/2024.emnlp-main.696

[70] Kuang Wang, Xianfei Li, Shenghao Yang, Li Zhou, Feng Jiang, and Haizhou Li. 2025. Know You First and Be You Better: Modeling Human-Like User Simulators via Implicit Profiles. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (Eds.). Association for Computational Linguistics, Vienna, Austria, 21082–21107. doi:10.18653/v1/2025.acl-long.1025

[71] Michael Wojatzki, Tobias Horsmann, Darina Gold, and Torsten Zesch. 2018. Do women perceive hate differently: Examining the relationship between hate speech, gender, and agreement judgments. (2018).

[72] Ka Wong, Praveen Paritosh, and Lora Aroyo. 2021. Cross-replication Reliability - An Empirical Approach to Interpreting Inter-rater Reliability. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (Eds.). Association for Computational Linguistics, Online, 7053–7065. doi:10.18653/v1/2021.acl-long.548

[73] Zengqing Wu, Run Peng, Takayuki Ito, Makoto Onizuka, and Chuan Xiao. 2026. LLM-Based Social Simulations Require a Boundary. arXiv:2506.19806 [cs.CY] https://arxiv.org/abs/2506.19806

[74] An Yang et al. 2025. Qwen2.5 Technical Report. arXiv:2412.15115 [cs.CL] https://arxiv.org/abs/2412.15115

[75] Bohao Yang, Dong Liu, Chenghao Xiao, Kun Zhao, Chen Tang, Chao Li, Lin Yuan, Yang Guang, and Chenghua Lin. 2025. Crafting Customisable Characters with LLMs: A Persona-Driven Role-Playing Agent Framework. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (Eds.). Association for Computational Linguistics, Suzhou, China, 20216–20240. doi:10.18653/v1/2025.findings-emnlp.1100

[76] Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. 2018. Personalizing Dialogue Agents: I have a dog, do you have pets too?. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, Iryna Gurevych and Yusuke Miyao (Eds.). Association for Computational Linguistics, Melbourne, Australia, 2204–2213. doi:10.18653/v1/P18-1205

[77] Caleb Ziems, William Held, Omar Shaikh, Jiaao Chen, Zhehao Zhang, and Diyi Yang. 2024. Can large language models transform computational social science? *Computational linguistics* 50, 1 (2024), 237–291.

Table 15. Consistency (Krippendorff's α, ordinal) of each model with itself across repeated runs of the same (default) prompt.

Dataset	Model	Runs	Items	Krippendorff's alpha
DICES-350	gemma31b	5	210	1.0000
DICES-350	gemma7b	5	210	1.0000
DICES-350	llama8b	5	210	1.0000
DICES-350	mistral24b	5	210	1.0000
DICES-350	mistral7b	5	210	1.0000
DICES-350	olmo32b	5	209	1.0000
DICES-350	olmo7b	5	210	1.0000
DICES-350	qwen32b	5	210	1.0000
DICES-350	qwen7b	5	210	1.0000
DICES-990	gemma31b	5	594	—
DICES-990	gemma7b	5	594	1.0000
DICES-990	llama8b	5	594	1.0000
DICES-990	mistral24b	5	592	1.0000
DICES-990	mistral7b	5	594	—
DICES-990	olmo32b	5	594	1.0000
DICES-990	olmo7b	5	594	1.0000
DICES-990	qwen32b	5	594	1.0000
DICES-990	qwen7b	5	594	1.0000
Sap et al. 2022	gemma31b	5	348	1.0000
Sap et al. 2022	gemma7b	5	348	1.0000
Sap et al. 2022	llama8b	5	287	1.0000
Sap et al. 2022	mistral24b	5	348	1.0000
Sap et al. 2022	mistral7b	5	345	1.0000
Sap et al. 2022	olmo32b	5	343	1.0000
Sap et al. 2022	olmo7b	5	338	1.0000
Sap et al. 2022	qwen32b	5	348	1.0000
Sap et al. 2022	qwen7b	5	348	1.0000
Kumar et al. 2021	gemma31b	5	600	1.0000
Kumar et al. 2021	gemma7b	5	600	1.0000
Kumar et al. 2021	llama8b	5	458	1.0000
Kumar et al. 2021	mistral24b	5	600	1.0000
Kumar et al. 2021	mistral7b	5	597	1.0000
Kumar et al. 2021	olmo32b	5	599	1.0000
Kumar et al. 2021	olmo7b	5	600	1.0000
Kumar et al. 2021	qwen32b	5	600	1.0000
Kumar et al. 2021	qwen7b	5	600	1.0000
POPQUORN	gemma31b	5	900	1.0000
POPQUORN	gemma7b	5	900	1.0000
POPQUORN	llama8b	5	170	1.0000
POPQUORN	mistral24b	5	900	1.0000
POPQUORN	mistral7b	5	898	1.0000
POPQUORN	olmo32b	5	896	1.0000
POPQUORN	olmo7b	5	883	1.0000
POPQUORN	qwen32b	5	900	1.0000
POPQUORN	qwen7b	5	900	1.0000

Table 16. Consistency (Krippendorff's α, ordinal) of each model with itself across the three paraphrased prompt variants.

Dataset	Model	Variants	Items	Krippendorff's alpha
DICES-350	gemma31b	3	210	0.3361
DICES-350	gemma7b	3	210	-0.0473
DICES-350	llama8b	3	210	0.0372
DICES-350	mistral24b	3	210	-0.3299
DICES-350	mistral7b	3	210	-0.0334
DICES-350	olmo32b	3	210	0.0253
DICES-350	olmo7b	3	210	0.1701
DICES-350	qwen32b	3	210	0.0044
DICES-350	qwen7b	3	210	-0.2016
DICES-990	gemma31b	3	594	-0.0085
DICES-990	gemma7b	3	594	0.7115
DICES-990	llama8b	3	594	-0.0310
DICES-990	mistral24b	3	594	-0.0829
DICES-990	mistral7b	3	594	-0.2069
DICES-990	olmo32b	3	594	0.2378
DICES-990	olmo7b	3	594	0.0594
DICES-990	qwen32b	3	594	0.1905
DICES-990	qwen7b	3	594	0.1101
Sap et al. 2022	gemma31b	3	348	0.9560
Sap et al. 2022	gemma7b	3	348	0.8905
Sap et al. 2022	llama8b	3	336	0.3863
Sap et al. 2022	mistral24b	3	348	0.7528
Sap et al. 2022	mistral7b	3	348	0.8446
Sap et al. 2022	olmo32b	3	347	0.8579
Sap et al. 2022	olmo7b	3	348	0.3025
Sap et al. 2022	qwen32b	3	348	0.9732
Sap et al. 2022	qwen7b	3	348	0.8625
Kumar et al. 2021	gemma31b	3	600	0.9258
Kumar et al. 2021	gemma7b	3	600	0.7871
Kumar et al. 2021	llama8b	3	594	0.0667
Kumar et al. 2021	mistral24b	3	600	0.8201
Kumar et al. 2021	mistral7b	3	599	0.6077
Kumar et al. 2021	olmo32b	3	600	0.5169
Kumar et al. 2021	olmo7b	3	600	0.0547
Kumar et al. 2021	qwen32b	3	600	0.9003
Kumar et al. 2021	qwen7b	3	600	0.2496
POPQUORN	gemma31b	3	900	0.8348
POPQUORN	gemma7b	3	900	0.8041
POPQUORN	llama8b	3	885	0.0175
POPQUORN	mistral24b	3	900	0.7000
POPQUORN	mistral7b	3	900	0.4874
POPQUORN	olmo32b	3	900	0.5657
POPQUORN	olmo7b	3	900	0.1038
POPQUORN	qwen32b	3	900	0.8381
POPQUORN	qwen7b	3	900	0.2747

Table 17. Consistency (Krippendorff's α, ordinal) between LLMs given the same (default) prompt, per dataset.

Dataset	Prompt	Models	Items	Krippendorff's alpha
Sap et al. 2022	default	9	18230	0.5201
Kumar et al. 2021	default	9	40000	0.2035
POPQUORN	default	9	30000	0.1787

Table 18. Consistency (Krippendorff's α, ordinal) between LLMs given the same (default) prompt, per dataset, excluding the following models: llama8b, olmo7b, qwen7b.

Dataset	Prompt	Models	Items	Krippendorff's alpha
Sap et al. 2022	default	6	18230	0.6465
Kumar et al. 2021	default	6	40000	0.3581
POPQUORN	default	6	30000	0.2986

Table 22. Aposteriori unimodality results for the Kumar-results dataset. Stars indicate statistical significance: $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	apunim	support
Age	1) 18 - 24	0.0139	31
	2) 25 - 34	-0.0028	867
	3) 35 - 44	0.0000	279
	4) 45 - 54	0.0223	58
Education	2) High School graduate	0.0000	18
	3) College, no degree	0.0100	128
	4) Associate degree	0.0000	31
	5) Bachelor's degree	0.0013	947
	6) Master's degree	0.0000	68
Ethnicity	Black	0.0000	46
	White	0.0000	2622
Gender	Female	0.0010	1587
	Male	0.0006	1033
Has Been Targeted	False	0.0011	2540
	True	-0.0095	409
Is Parent	No	-0.0021	1089
	Yes	-0.0001	1603
Is Transgender	No	0.0000	4045
Political Affiliation	Conservative	-0.0134	260
	Independent	0.0000	349
	Liberal	-0.0010	850
Religion Important	1) No	0.0022	401
	2) Not very	0.0000	22
	3) Somewhat	0.0000	289
	4) Very	0.0002	463
Seen Toxicity	False	-0.0070	286
	True	-0.0008	2861
Sexual Orientation	Bisexual	-0.0678	50
	Heterosexual	-0.0010	3199
Technology Impact	2) Somewhat negative	0.0000	15
	3) Neutral	0.1243	27
	4) Somewhat positive	0.0038	1343
	5) Very positive	-0.0148	269
Toxicity Problem	1) Never	0.0000	7
	2) Rarely	0.0000	84
	3) Occasionally	0.0000	521
	4) Frequently	0.0000	422
	5) Very Frequently	0.0000	22

Table 23. Aposteriori unimodality results for the Sap-results dataset. Stars indicate statistical significance: $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	apunim	support
Age	1) Gen. X+	-0.1670*	223
	2) Millennial	0.0199	1651
Ethnicity	white	-0.0007	1235
Gender	man	-0.1508***	1254
	woman	0.2613***	693

Table 24. Aposteriori unimodality results for the Dices-350-results dataset. Stars indicate statistical significance: $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	apunim	support
Age	1) Gen. Z	-0.0043	14728
	2) Millennial	-0.0089	9468
	3) Gen. X+	0.0148	8153
Education	College +	0.0105	19725
	High school -	-0.0145	10783
	Other	-0.0230*	1841
Gender	Man	-0.0171	16043
	Woman	0.0176	16306
Race	African Am.	-0.0366***	7627
	Asian	0.0445***	6838
	Latino	0.0059	5786
	Multiracial	-0.0061	4208
	White	-0.0113	7890

Table 25. Aposteriori unimodality results for the Dices-990-results dataset. Stars indicate statistical significance: $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	apunim	support
Age	1) Gen. Z	0.0469***	12214
	2) Millennial	-0.0068*	34433
	3) Gen. X+	-0.0282***	12699
Education	College +	0.0063*	52727
	High school -	-0.0500***	6619
Gender	Man	0.0359***	28817
	Woman	-0.0271***	29990
Race	African Am.	0.0995***	5148
	Asian	-0.0057	16486
	Latino	-0.0631***	5877
	Other	0.0340***	21669
	White	-0.0649***	10166

Table 26. Aposteriori unimodality results for the Popquorn-results dataset. Stars indicate statistical significance: $^{*}p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

SDD	Value	apunim	support
Age	01) 18-24	-0.1198	90
	02) 25-29	0.0420	50
	03) 30-34	0.2251	71
	04) 35-39	0.0439	121
	05) 40-44	0.0061	81
	06) 45-49	0.0507	64
	07) 50-54	0.0381	22
	08) 54-59	-0.0635	133
	09) 60-64	0.1194	13
	10) >65	-0.0145	118
Education	2) High school	-0.0112	1270
	3) College degree	0.0496***	2388
	4) Graduate degree	-0.0808**	468
Gender	Man	0.0081	2720
	Woman	-0.0195	2899
Occupation	Employed	-0.0126	2535
	Homemaker	-0.2366	12
	Retired	-0.1026	95
	Self-employed	0.1063*	210
	Student	0.3675	18
	Unemployed	0.1204*	166
Race	Asian	0.2795*	29
	Black	-0.1572***	222
	White	0.0090	4135

Table 27. Mean (SE) per-comment nDFU of the human annotations and of the LLM annotations under each instruction prompt. Human annotations do not depend on the prompt. Rows give results per model, pooled over all datasets (All) and for each dataset separately; *n* is the number of comments.

Model	Dataset	n	Default	Stereotype	Persona	Single	Direct
Human	All	3085			0.36 (0.00)		
	Sap et al. 2022	585			0.38 (0.01)		
	Kumar et al. 2021	1000			0.42 (0.01)		
	POPQUORN	1500			0.31 (0.01)		
llama8b	All	1489	0.40 (0.01)	0.59 (0.01)	0.33 (0.01)	0.25 (0.01)	0.54 (0.01)
	Sap et al. 2022	192	0.54 (0.02)	0.47 (0.02)	0.08 (0.01)	0.25 (0.02)	0.37 (0.02)
	Kumar et al. 2021	951	0.40 (0.01)	0.61 (0.01)	0.49 (0.01)	—	0.55 (0.01)
	POPQUORN	346	0.32 (0.02)	0.61 (0.01)	0.05 (0.00)	0.25 (0.02)	0.60 (0.01)
olmo32b	All	3085	0.45 (0.01)	0.40 (0.01)	0.44 (0.01)	0.45 (0.00)	0.40 (0.01)
	Sap et al. 2022	585	0.24 (0.01)	0.26 (0.01)	0.26 (0.01)	0.30 (0.01)	0.25 (0.01)
	Kumar et al. 2021	1000	0.51 (0.01)	0.54 (0.01)	0.48 (0.01)	0.44 (0.01)	0.43 (0.01)
	POPQUORN	1500	0.50 (0.01)	0.35 (0.01)	0.50 (0.01)	0.53 (0.01)	0.44 (0.01)
olmo7b	All	3082	0.70 (0.00)	0.64 (0.00)	0.67 (0.00)	0.62 (0.00)	0.59 (0.00)
	Sap et al. 2022	583	0.66 (0.01)	0.60 (0.01)	0.70 (0.01)	0.58 (0.01)	0.63 (0.01)
	Kumar et al. 2021	1000	0.68 (0.01)	0.55 (0.01)	0.63 (0.01)	0.55 (0.01)	0.42 (0.01)
	POPQUORN	1499	0.72 (0.01)	0.71 (0.00)	0.69 (0.01)	0.69 (0.01)	0.69 (0.01)
qwen32b	All	2469	0.20 (0.01)	0.26 (0.01)	0.26 (0.01)	0.27 (0.01)	0.25 (0.01)
	Sap et al. 2022	585	0.18 (0.01)	0.28 (0.01)	0.22 (0.01)	0.16 (0.01)	0.21 (0.01)
	Kumar et al. 2021	1000	0.19 (0.01)	0.24 (0.01)	0.25 (0.01)	0.34 (0.01)	0.28 (0.01)
	POPQUORN	884	0.21 (0.01)	0.28 (0.01)	0.30 (0.01)	0.28 (0.01)	0.26 (0.01)
qwen7b	All	1585	0.43 (0.01)	0.26 (0.01)	0.28 (0.01)	0.37 (0.01)	0.37 (0.01)
	Sap et al. 2022	585	0.30 (0.01)	0.30 (0.01)	0.31 (0.01)	0.27 (0.01)	0.28 (0.01)
	Kumar et al. 2021	1000	0.51 (0.01)	0.23 (0.01)	0.26 (0.01)	0.42 (0.01)	0.42 (0.01)
mistral7b	All	3078	0.35 (0.01)	0.39 (0.01)	0.36 (0.01)	0.39 (0.01)	0.33 (0.01)
	Sap et al. 2022	585	0.21 (0.01)	0.27 (0.01)	0.24 (0.01)	0.23 (0.01)	0.37 (0.01)
	Kumar et al. 2021	994	0.37 (0.01)	0.39 (0.01)	0.36 (0.01)	0.34 (0.01)	0.36 (0.01)
	POPQUORN	1499	0.40 (0.01)	0.43 (0.01)	0.40 (0.01)	0.49 (0.01)	0.29 (0.01)
mistral24b	All	1731	0.25 (0.01)	0.45 (0.01)	0.38 (0.01)	0.27 (0.01)	0.28 (0.01)
	Sap et al. 2022	295	0.26 (0.02)	0.41 (0.02)	0.27 (0.02)	0.10 (0.01)	0.32 (0.02)
	Kumar et al. 2021	782	0.25 (0.01)	0.51 (0.01)	0.50 (0.01)	0.43 (0.01)	0.19 (0.01)
	POPQUORN	654	0.26 (0.01)	0.40 (0.01)	0.28 (0.01)	0.15 (0.01)	0.36 (0.01)
gemma7b	All	3083	0.17 (0.00)	0.22 (0.00)	0.25 (0.00)	0.29 (0.01)	0.24 (0.00)
	Sap et al. 2022	585	0.19 (0.01)	0.23 (0.01)	0.32 (0.01)	0.35 (0.01)	0.23 (0.01)
	Kumar et al. 2021	1000	0.22 (0.01)	0.25 (0.01)	0.20 (0.01)	0.12 (0.01)	0.21 (0.01)
	POPQUORN	1498	0.12 (0.01)	0.20 (0.01)	0.25 (0.01)	0.37 (0.01)	0.28 (0.01)
gemma31b	All	3084	0.06 (0.00)	0.13 (0.01)	0.11 (0.00)	0.04 (0.00)	0.14 (0.01)
	Sap et al. 2022	585	0.04 (0.01)	0.10 (0.01)	0.07 (0.01)	0.04 (0.01)	0.28 (0.01)
	Kumar et al. 2021	1000	0.09 (0.01)	—	—	—	—
	POPQUORN	1499	0.05 (0.00)	0.14 (0.01)	0.13 (0.01)	0.04 (0.00)	0.09 (0.01)

Table 28. Mean (SE) per-comment nDFU of the human annotations and of the LLM annotations under the default prompt, per dataset and pooled over all datasets (All). *n* is the number of comments.

	Sap et al. 2022		Kumar et al. 2021		POPQUORN		All	
	n	Mean (SE)	n	Mean (SE)	n	Mean (SE)	n	Mean (SE)
Model								
Human	585	0.38 (0.01)	1000	0.42 (0.01)	1500	0.31 (0.01)	3085	0.36 (0.00)
llama8b	565	0.52 (0.01)	977	0.40 (0.01)	1003	0.30 (0.01)	2545	0.39 (0.01)
olmo32b	585	0.24 (0.01)	1000	0.51 (0.01)	1500	0.50 (0.01)	3085	0.45 (0.01)
olmo7b	585	0.66 (0.01)	1000	0.68 (0.01)	1500	0.72 (0.01)	3085	0.70 (0.00)
qwen32b	585	0.18 (0.01)	1000	0.19 (0.01)	1499	0.20 (0.01)	3084	0.19 (0.00)
qwen7b	585	0.30 (0.01)	1000	0.51 (0.01)	1500	0.45 (0.01)	3085	0.44 (0.01)
mistral7b	585	0.21 (0.01)	1000	0.37 (0.01)	1500	0.40 (0.01)	3085	0.35 (0.01)
mistral24b	585	0.25 (0.01)	1000	0.25 (0.01)	1500	0.23 (0.01)	3085	0.24 (0.00)
gemma7b	585	0.19 (0.01)	1000	0.22 (0.01)	1500	0.12 (0.01)	3085	0.17 (0.00)
gemma31b	585	0.04 (0.01)	1000	0.09 (0.01)	1500	0.05 (0.00)	3085	0.06 (0.00)

Table 29. Cohen's d between the default and each adversarial instruction prompt, computed on the per-comment nDFU. Rows give results per model, for each dataset separately and as the unweighted mean over datasets (All); *n* is the number of comments.

Model	Dataset	n	Stereotype	Persona	Single	Direct
llama8b	All	2545	0.54	-0.95	-0.56	0.37
	Sap et al. 2022	565	-0.20	-1.93	-0.93	-0.49
	Kumar et al. 2021	977	0.75	0.30	—	0.56
	POPQUORN	1003	1.06	-1.22	-0.19	1.03
olmo32b	All	3085	-0.09	-0.02	0.01	-0.15
	Sap et al. 2022	585	0.09	0.06	0.22	0.04
	Kumar et al. 2021	1000	0.14	-0.13	-0.29	-0.31
	POPQUORN	1500	-0.50	-0.00	0.10	-0.19
olmo7b	All	3085	-0.31	-0.08	-0.37	-0.51
	Sap et al. 2022	585	-0.27	0.16	-0.34	-0.13
	Kumar et al. 2021	1000	-0.62	-0.24	-0.60	-1.25
	POPQUORN	1500	-0.04	-0.16	-0.16	-0.16
qwen32b	All	3084	0.25	0.22	0.22	0.19
	Sap et al. 2022	585	0.32	0.13	-0.09	0.09
	Kumar et al. 2021	1000	0.17	0.21	0.51	0.31
	POPQUORN	1499	0.26	0.30	0.24	0.17
qwen7b	All	3085	-0.57	-0.54	-0.37	-0.36
	Sap et al. 2022	585	0.02	0.06	-0.09	-0.05
	Kumar et al. 2021	1000	-1.13	-0.90	-0.31	-0.31
	POPQUORN	1500	-0.60	-0.77	-0.71	-0.73
mistral7b	All	3085	0.13	0.03	0.10	0.05
	Sap et al. 2022	585	0.21	0.10	0.08	0.57
	Kumar et al. 2021	1000	0.07	-0.01	-0.10	-0.05
	POPQUORN	1500	0.12	0.02	0.33	-0.36
mistral24b	All	3085	0.72	0.40	-0.16	0.12
	Sap et al. 2022	585	0.64	0.04	-0.76	0.27
	Kumar et al. 2021	1000	0.98	0.97	0.57	-0.25
	POPQUORN	1500	0.55	0.20	-0.30	0.35
gemma7b	All	3085	0.20	0.32	0.39	0.23
	Sap et al. 2022	585	0.18	0.48	0.57	0.15
	Kumar et al. 2021	1000	0.10	-0.08	-0.40	-0.07
	POPQUORN	1500	0.34	0.54	0.99	0.63
gemma31b	All	2085	0.42	0.31	0.00	0.63
	Sap et al. 2022	585	0.36	0.21	0.06	1.03
	POPQUORN	1500	0.47	0.40	-0.06	0.23

Table 30. Statistically significant ($p < 0.05$) SDDs of each LLM compared with the human annotations, per dataset. A dimension counts as significant if at least one of its groups is. Each cell shows one symbol per prompt, in the order default, stereotype, persona, single, direct: ✓ the LLM and the human annotations agree (both significant, with the same sign for every group that is significant in both, or neither significant), × they disagree on significance (significant for only one of the two), ± both are significant but the sign of at least one group's effect differs; blank: no LLM result.

Ds	SDD	llama8b	olmo32b	olmo7b	qwen32b	qwen7b	mistral7b	mistral24b	gemma7b	gemma31b
Sap	Age	✓✓××✓	✓✓✓×✓	±✓✓✓✓	±±±±±	±±±±±	±✓±××±	±✓±✓±	××±×✓	✓✓✓±±
	Ethnicity	✓××✓×	✓✓×✓×	××××✓	×××××	×××××	×××××	××✓××	×××××	×××××
	Gender	✓±✓✓×	×××××	✓±✓×✓	×✓××±	××±××	×✓✓××	±✓✓✓±	××±×±	××××✓
POP	Age	✓×✓✓×	××✓××	×××××	×××××	×××××	×××××	×××××	×××××	××××✓
	Education	✓±±±±	±±✓±±	✓±±±✓	±±±±±	±±±±±	±±±✓±	✓±±±±	±×✓±±	×±±××
	Gender	✓××✓×	✓✓✓✓×	×××××	✓××××	××××✓	×✓×✓×	×××××	×××××	×××××
	Occupation	±±✓×✓	××±✓✓	±±±±±	✓±✓××	✓×✓××	✓✓✓✓✓	✓✓±±±	±✓✓✓×	××✓××
	Race	×✓✓×±	✓×±±✓	✓✓✓✓✓	✓±±±✓	✓±✓✓✓	✓±±✓✓	✓±✓✓±	✓✓±✓±	✓±±±±