PROTOCOL SPECIFICATION PRIME PUMP INTERFACE

Revision 1.0 1999. 9.

DONG HWA INSTRUMENT CO., LTD. Seoul, Korea

1. General

The standard data link is based on a controller / pump relationship, where the controller polls the pumps. If the controller wants to send data to a pump, it sends a block with data instead of a poll. If the controller wants to send data it answers with data on a poll. Half duplex is used. The protocol is code transparent and byte oriented. The protocol shall provide for variable length messages.

2. Data format

Asynchronous communication

9600 baud

1 start bit, 8 data bits, 1 parity bit (EVEN), 1 stop bit

3. Reliable Data Transfer

It must provide for reliable data transfer. Error checking to be implemented by LRC. Parity checking is required on each byte.

4. Operational Specifics


It shall operate half-duplex and transmit data in asynchronous start-stop format.

5. Communication specification

- Buffer size is application dependent. However, maximum is
 256bytes including control characters.
- The Pump respond to a poll or data within 30ms,
- i.e. transmit the first character after a complete poll or data.
- RS 422
- 6. Control Charaters in the Protocol

NO	CODE	CODE NO.	COMMENT	
1.	SOH	01 H	Start of head	
2.	STX	02 H	Start of text	
3.	ETX	03 H	End of text	
4.	ЕОТ	04 H	End of transmit	
5.	ENQ	05 H	Enquiry	
6.	ACK	06 H	Acknowledge	
7.	NAK	15 H	No Acknowledge	
8.	ЕОВ	17 H	End of block	
9.	FS	1C H	Field Seperator	

7. Data Format



* Pump No : 2 digit ASCII (01~99)


8. Command

NO	COMMAND	COMMENT	
1.	ENQ	Polling	Controller → Pump
2.	AQ	Request Authorize	Pump → Controller
3.	AP	Authorize	Controller → Pump
4.	PP	Filling	Pump → Controller
5.	LK	Filling completed	Pump → Controller
6.	TQ	Request data of filling completed	Controller → Pump
7.	TR	Anser of TQ	Pump → Controller
8.	ST	Preset Volume or Amount	Controller → Pump
9.	PC	Price Change	Controller ↔ Pump
10.	CQ	Request Volume totalization	Controller → Pump
11.	СТ	Anser of CQ	Pump → Controller

8-1. AQ, AP


(Controller)

(Pump)






ACK →




← ACK


8-2 <u>PP</u>

(Controller) (Pump)





* Data : 14 Byte (Volume 7 Byte, Amount 7 Byte)











(Controller) (Pump)









* Example Data: Unit price, 4 Byte 1097


Volume, 7 Byte 0018232 (18.232 Liter)

Amount, 7 Byte 0020000

8-5. ST

- Example : Preset Amount 20,000

(Controller) (Pump)



← ACK


* Example data: A = Preset Amount 7 Byte (Volume or Amount)


Q = Preset Volume 7 Byte

8-6. <u>PC</u>

(Controller)

(Pump)







^{*} Example Data : 4 Byte (Unit price)

8-7. <u>CQ, CT</u>

(Controller) (Pump)





^{*} Example Data: 9 Byte (Including 3 decimal point) 1234.567 Liter