Alphabet Rangoli

HackerRank

You are given an integer, N. Your task is to print an alphabet rangoli of size N. (Rangoli is a form of Indian folk art based on creation of patterns.)

Different sizes of alphabet rangoli are shown below:

```
#size 3

----c----
--c-b-c--
c-b-a-b-c
--c-b-c--
----c----

#size 5

--------e--------
------e-d-e------
----e-d-c-d-e----
--e-d-c-b-c-d-e--
e-d-c-b-a-b-c-d-e
--e-d-c-b-c-d-e--
----e-d-c-d-e----
------e-d-e------
--------e--------

#size 10

------------------j------------------
----------------j-i-j----------------
--------------j-i-h-i-j--------------
------------j-i-h-g-h-i-j------------
----------j-i-h-g-f-g-h-i-j----------
--------j-i-h-g-f-e-f-g-h-i-j--------
------j-i-h-g-f-e-d-e-f-g-h-i-j------
----j-i-h-g-f-e-d-c-d-e-f-g-h-i-j----
--j-i-h-g-f-e-d-c-b-c-d-e-f-g-h-i-j--
j-i-h-g-f-e-d-c-b-a-b-c-d-e-f-g-h-i-j
--j-i-h-g-f-e-d-c-b-c-d-e-f-g-h-i-j--
----j-i-h-g-f-e-d-c-d-e-f-g-h-i-j----
------j-i-h-g-f-e-d-e-f-g-h-i-j------
--------j-i-h-g-f-e-f-g-h-i-j--------
----------j-i-h-g-f-g-h-i-j----------
------------j-i-h-g-h-i-j------------
--------------j-i-h-i-j--------------
----------------j-i-j----------------
------------------j------------------
```

size : jmlh huruf, bkn ukuran kotaknya

all_alphabet = [a, b, c, ..., z] (0, 1, 2)

lebihnya dikit bisa ga eror w/ size 26/2 ke atas. *2 aja udah yak

alphabet = 27* [""] ohrsnya '_'

kan mau ini ini

~~alphabet = [all_alphabet[i] for i in range(size)]~~ → kalau gini dah same aja

hrsnya: for i in range(size): alphabet[i] = all_alphabet[i] bkn list baru

for i in range(size-1, -size, -1):
    ~~print~~ (f"{alphabet[i+size-1]}-{alphabet[i+size-2]}- ...
print("/n")

loop dlm loop? for j in range(size)

0+3-1 = 2
0+3-2 = 1
0+3-3 = 0

if i<0: i = abs(i)

i=2 → -- -- c -- --
i=1 → -- c- b -c --
i=0 → c- b- a -b -c
i=1 →
i=2 →

The center of the rangoli has the first alphabet letter *a*, and the boundary has the N^{th} alphabet letter (in alphabetical order).

2 1 0 1 2
-1 +1 +3 +1 -1
1 2 3 2 1

j: 1 2 3 4 5
-2 -4
1 2 3 2 1

Function Description

Complete the *rangoli* function in the editor below.

rangoli has the following parameters:

- *int size:* the size of the rangoli

print(f"{alphabet[i+size- 1 2 3 4 5 6 7 / 1 2 3 4 3 2 1

4+5-1 = 8

Returns

- *string:* a single string made up of each of the lines of the rangoli separated by a newline character (\n)

Input Format

Only one line of input containing $size$, the size of the rangoli.

Constraints

$0 < size < 27$ → krn total alfabet cuma 26

Sample Input

```
5
```

Sample Output

```
--------e--------
------e-d-e------
----e-d-c-d-e----
--e-d-c-b-c-d-e--
e-d-c-b-a-b-c-d-e
--e-d-c-b-c-d-e--
----e-d-c-d-e----
------e-d-e------
--------e--------
```

DEBUG
w/ case size = 5

something

2*1 2*2 2*3 2*4

i = 4

i = 3 j = 1 2 3 4 5 6 7 8 9

-2 -4 -6 -8

i = 2 1 2 3 4 5 4 3 2 1

i = 1 - - e - d - c - b - c - d - e - -

@ @

something = [1, 2, 3, 4]

counter += 1