

# Athlete Sort

You are given a spreadsheet that contains a list of  $N$  athletes and their details (such as age, height, weight and so on). You are required to sort the data based on the  $K^{\text{th}}$  attribute and print the final resulting table. Follow the example given below for better understanding.

| Rank | Age | Height (in cm) |                                  | Rank | Age | Height (in cm) |
|------|-----|----------------|----------------------------------|------|-----|----------------|
| 1    | 32  | 190            | sort based on $k=1$<br>i.e (age) | 5    | 24  | 176            |
| 2    | 35  | 175            |                                  | 4    | 26  | 195            |
| 3    | 41  | 188            |                                  | 1    | 32  | 190            |
| 4    | 26  | 195            |                                  | 2    | 35  | 175            |
| 5    | 24  | 176            |                                  | 3    | 41  | 188            |



Note that  $K$  is indexed from 0 to  $M - 1$ , where  $M$  is the number of attributes.

**Note:** If two attributes are the same for different rows, for example, if two athletes are of the same age, print the row that appeared first in the input.

## Input Format

The first line contains  $N$  and  $M$  separated by a space.  
The next  $N$  lines each contain  $M$  elements.  
The last line contains  $K$ .

## Constraints

$1 \leq N, M \leq 1000$  → Time Limit ?  
 $0 \leq K < M$   
Each element  $\leq 1000$

## Output Format

Print the  $N$  lines of the sorted table. Each line should contain the space separated elements. Check the sample below for clarity.

## Sample Input 0

```
5 3
10 2 5
7 1 0
9 9 9
1 23 12
6 5 9
1
```

array list  
arr

$k$     0 1 2

```
arr = [[10, 2, 5],
        [7, 1, 0],
        [9, 9, 9],
        [1, 23, 12],
        [6, 5, 9]]
```

$\min(\text{something}[K])$

7, 1, 0  
10, 2, 5  
9, 9, 9

atau pakai cara get index aja?

## Sample Output 0

```
7 1 0
10 2 5
6 5 9
9 9 9
1 23 12
```

## Explanation 0

The details are sorted based on the second attribute, since  $K$  is zero-indexed.

~~minjem\_yaa = arr.copy()~~

for i in range(n):       $N = \text{panjang arr}$

    some\_list.append(arr[i][k])

$i = 0, 1, 2, \dots, n-1$

PAKAI

METHOD

~~single\_index = some\_list.index(min(some\_list))~~

SORT

~~index\_sorting.append(single\_index)~~

sorted\_attr = sorted(some\_list)

print(some\_list)

>> [2, 1, 9, 23, 5]

print(sorted\_attr)

>> [1, 2, 5, 9, 23]



print(arr[?])

print("\n")

for i in range(n):

    ? = some\_list.index(sorted\_attr[i])

~~print(f"~~

ga usah pakai f string & loop!

pakai ini bisa print semua elemen dari list dgn separator space:

print(\*arr[?])

⚡ hati2 dgn row yg value attribute nya sama!

sempet gagal gr2 itu di test - -

|       |   |   |         |              |              |            |   |   |
|-------|---|---|---------|--------------|--------------|------------|---|---|
| e.g:  | 3 | 2 | output: | 1            | 5            | pdhl       | 1 | 5 |
| input | 3 | 1 |         | <del>1</del> | <del>5</del> | krny       | 1 | 4 |
|       | 1 | 5 |         | 3            | 1            | outputnya: | 3 | 1 |
|       | 1 | 4 |         |              |              |            |   |   |
|       | 0 |   |         |              |              |            |   |   |

\* hayolo gimana?

\* code before:

```
some_list = [ ]
```

```
for i in range(n):
```

```
    some_list.append(arr[i][k])
```

```
sorted_attr = sorted(some_list)
```

```
for i in range(n):
```

```
    index_sorted = some_list.index(sorted_attr[i])
```

```
    print(*arr[index_sorted])
```

0 1 2  
some\_list = [3, 1, 1]

sorted\_attr = [1, 1, 3]

for

0 1 2 0  
= some\_list[0]

bisa gk ini langsung  
dlm bentuk index aja?  
hm----

if some\_list.count(sorted\_attr[i])  
 > 1:

ape pakai dictionary?

some\_dict(?)


`some_dict = {}`  $\rightarrow$  `some_dict = {` <sup>key items</sup> `0: 3,`  
`some_dict[0] = 3` `1: 1,`  
`some_dict[1] = 1` `2: 1 }`  
`some_dict[2] = 1`

$\rightarrow$  `some_dict[i] = arr[i][k]`

~~`some_list = list (some_dict[i] for i in range(n))`~~  
~~`sorted_attr = sorted (some_list)`~~

~~`for i in range(n):`~~

`sorted_attr = dict(sorted(some_dict.items()), key =`

`>> sorted_attr = {`  `lambda x: x[1])`  
 $= \text{some\_dict.items()}[1]$   
 $x[0]$

`for i in sorted_attr.keys():`  
`print (*arr[i])`

`some_dict.items = ?`  
`>> [(0, 3),`  $x[1]$   
 $x[0]$  `(1, 1),`  
`(2, 1)]`