

New York University, CIMS, CS, Course CSCI-GA.3140-001, Spring 2024

## “Abstract Interpretation”

# Ch. 6, Structural Deductive Stateless Prefix Trace Semantics

Patrick Cousot

[pcousot@cs.nyu.edu](mailto:pcousot@cs.nyu.edu)    [cs.nyu.edu/~pcousot](http://cs.nyu.edu/~pcousot)

Class 2, Monday, January 29th, 2024, 4:55-6:55 PM, WWH, Room CIWW 202

These slides are available at

<http://cs.nyu.edu/~pcousot/courses/spring24/CSCI-GA.3140-001/slides/02--2024-01-30-syntax-semantics-traces-oo/slides-06--prefix-trace-semantics-AI.pdf>

# Ch. 6, Structural Deductive Stateless Prefix Trace Semantics

# Trace semantics, informally

Hand computation of

$$(1-1)-1 < (1-1)$$

is

$$\begin{aligned} a &= 1 - 1 \\ a &= 0 \\ b &= a - 1 \\ b &= 0 - 1 \\ b &= -1 \\ c &= b < a \\ c &= -1 < 0 \\ c &= \text{tt} \end{aligned}$$

← read from

partial trace

maximal finite trace

# Syntax and trace semantics of a language

- **syntax**: rules to write programs of the language;
- **semantics**: defines the runtime behavior of programs that is what and how they compute when executed:
  - **trace**: sequence of events recording the actions executed during a program execution,
  - **partial trace**: finite observation of an execution; this observation can stop at any time,
  - **finite (maximal) trace**: partial trace that ends upon execution termination,
  - **infinite trace**: infinite observation of an execution that never terminates,
  - **maximal trace**: finite or infinite execution trace.

# Traces

## Finite traces of a program: P

- Program:

(4.5)

```
ℓ1 x = x + 1 ;  
    while ℓ2 (tt) {  
        ℓ3 x = x + 1 ;  
        if ℓ4 (x > 2) ℓ5 break ; } ℓ6;ℓ7
```

- Prefix traces (from ℓ<sub>1</sub>, initially x = 0):

- ℓ<sub>1</sub>

•  $\ell_1 \xrightarrow{x = x + 1 = 1} \ell_2 \xrightarrow{tt} \ell_3 \xrightarrow{x = x + 1 = 2} \ell_4 \xrightarrow{\neg(x > 2)} \ell_2 \xrightarrow{tt} \ell_3$  (6.2)

- Finite (maximal) traces:

•  $\ell_1 \xrightarrow{x = x + 1 = 1} \ell_2 \xrightarrow{tt} \ell_3 \xrightarrow{x = x + 1 = 2} \ell_4 \xrightarrow{\neg(x > 2)} \ell_2 \xrightarrow{tt} \ell_3 \xrightarrow{x = x + 1 = 3} \ell_4 \xrightarrow{x > 2} \ell_5 \xrightarrow{\text{break}} \ell_6 \xrightarrow{\text{skip}} \ell_7$

## Infinite traces of a program: P

- Program:

$\ell_1 \text{ } x = 0 ; \mathbf{while} \ell_2 (\mathbf{tt}) \{ \ell_3 \text{ } x = x + 1 ; \} \ell_4$

- Infinite trace:

$\ell_1 \xrightarrow{x = 0 = 0} \ell_2 \xrightarrow{\mathbf{tt}} \ell_3 \xrightarrow{x = x + 1 = 1} \ell_2 \xrightarrow{\mathbf{tt}} \ell_3 \xrightarrow{x = x + 1 = 2} \ell_2 \dots \ell_2 \xrightarrow{\mathbf{tt}} \ell_3$   
 $\xrightarrow{x = x + 1 = n} \ell_2 \xrightarrow{\mathbf{tt}} \ell_3 \xrightarrow{x = x + 1 = n + 1} \ell_2 \dots$



# Traces

- $\mathbb{T}^+$ : the set of all finite traces,
- $\mathbb{T}^\infty$ : the set of all infinite traces,
- $\mathbb{T}^{+\infty}$ : the set of all finite or infinite traces.
- Conventions:
  - we write  $\pi = \ell\pi'$  to make clear that the trace  $\pi$  is assumed to start with the program label  $\ell$  (although  $\pi'$  is not itself a properly formed trace),
  - we write  $\pi = \pi'\ell$  when assuming that the trace  $\pi$  is finite and ends with label  $\ell$  (although, again,  $\pi'$  is not itself a properly formed trace).

## Trace concatenation $\frown$

- Definition:

$$\begin{array}{ll} \pi_1 \ell_1 \frown \ell_2 \pi_2 & \text{undefined if } \ell_1 \neq \ell_2 \\ \pi_1 \ell_1 \frown \ell_1 \pi_2 & \triangleq \pi_1 \ell_1 \pi_2 \quad \text{if } \pi_1 \text{ is finite} \\ \pi_1 \frown \pi_2 & \triangleq \pi_1 \quad \text{if } \pi_1 \text{ is infinite} \end{array}$$

- In pattern matching, we sometimes need the **empty trace**  $\ni$ . For example  $\ell \pi \ell' = \ell$  then  $\pi = \ni$  and  $\ell = \ell'$ .

# Value of variables

## Values of variables on a trace

- the value  $\varrho(\pi)x$  of variable  $x$  at the end of trace  $\pi$  is the last value assigned to  $x$  (or 0 at initialization).

$$\begin{aligned}\varrho(\pi^\ell \xrightarrow{x = A = v} \ell')x &\triangleq v \\ \varrho(\pi^\ell \xrightarrow{\dots} \ell')x &\triangleq \varrho(\pi^\ell)x \quad \text{otherwise} \\ \varrho(\ell)x &\triangleq 0\end{aligned}\tag{6.6}$$

# Prefix trace semantics of a statement

## Prefix trace semantics

- Let  $\pi_1 \text{at} \llbracket S \rrbracket$  be an initialization trace ending on entry  $\text{at} \llbracket S \rrbracket$  of statement  $S$ .
- $\mathcal{S}^* \llbracket S \rrbracket (\pi_1 \text{at} \llbracket S \rrbracket)$  is the set of prefix traces  $\text{at} \llbracket S \rrbracket \pi_2^\ell$  of  $S$  continuing the trace  $\pi_1 \text{at} \llbracket S \rrbracket$  and reaching some program label  $\ell \in \text{labx} \llbracket S \rrbracket$ .
- Schematically,

$$\begin{array}{c} \xrightarrow{\pi_1} \quad \text{at} \llbracket S \rrbracket \xrightarrow{\pi_2} \ell \\ \underbrace{\hspace{10em}}_{\in \mathcal{S}^* \llbracket S \rrbracket (\pi_1 \text{at} \llbracket S \rrbracket)} \end{array}$$

- Although our language is determinist, we consider a set of possible continuations to cope e.g. with inputs and random number generation.
- By convention  $\mathcal{S}^* \llbracket S \rrbracket (\pi_1^\ell) = \emptyset$  when  $\ell \neq \text{at} \llbracket S \rrbracket$ .

## Maximal finite trace semantics

- Let  $\pi_1 \text{at} \llbracket S \rrbracket$  be an initialization trace ending on entry  $\text{at} \llbracket S \rrbracket$  of statement  $S$ .
- $\mathcal{S}^+ \llbracket S \rrbracket (\pi_1 \text{at} \llbracket S \rrbracket)$  is the set of maximal finite traces  $\text{at} \llbracket S \rrbracket \pi_2 \text{after} \llbracket S \rrbracket$  of  $S$  continuing the trace  $\pi_1 \text{at} \llbracket S \rrbracket$  and reaching  $\text{after} \llbracket S \rrbracket$ .
- Schematically,

$$\xrightarrow{\pi_1} \text{at} \llbracket S \rrbracket \xrightarrow{\pi_2} \text{after} \llbracket S \rrbracket$$

$\underbrace{\hspace{10em}}_{\in \mathcal{S}^+ \llbracket S \rrbracket (\pi_1 \text{at} \llbracket S \rrbracket)}$

- Formally,

$$\mathcal{S}^+ \llbracket S \rrbracket (\pi_1 \text{at} \llbracket S \rrbracket) \triangleq \{ \pi_2^\ell \in \mathcal{S}^* \llbracket S \rrbracket (\pi_1 \text{at} \llbracket S \rrbracket) \mid \ell = \text{after} \llbracket S \rrbracket \} \quad (6.9)$$

# Introduction to rule-based structural definitions



## Structural definitions and proofs

- **Structural definitions** are recursive definitions over the syntax of programs;
- **Structural proofs** generalize proofs by recurrence to induction on the syntax of programs;
- Structural proofs are well suited to prove properties of structural definitions (e.g. that a structural definition is well-defined i.e. the recursive definition considered as a program does terminate).

## Example of rule-based structural definition

- Denotation of positive integers  $\mathbb{N}^+$  by a collection of sticks:

$$\mathbb{N}^+ ::= \mathbf{I} \mid \mathbb{N}^+ \mathbf{I}$$

- Example:  $\mathbf{IIIIII}$  is six
- Structural definition of the set  $\mathbb{O}$  of odd positive integers:

- axiom  $\frac{}{\mathbf{I} \in \mathbb{O}}$

- inference rule  $\frac{n \in \mathbb{O}}{n\mathbf{II} \in \mathbb{O}}$

- Set  $s(n)$  of numbers smaller than or equal to  $n$ :

$$\frac{}{n \in s(n)} \qquad \frac{m\mathbf{I} \in s(n)}{m \in s(n)}$$

Example:  $\mathbf{III} \in s(\mathbf{III})$  by the axiom so  $\mathbf{II} \in s(\mathbf{III})$  by the inference rule so  $\mathbf{I} \in s(\mathbf{III})$  by the inference rule proving that  $s(\mathbf{III}) = \{\mathbf{III}, \mathbf{II}, \mathbf{I}\}$ .

# Structural prefix trace semantics

## Prefix trace semantics $\hat{\mathcal{S}}^* \llbracket S \rrbracket$ of a program component $S$

$$\pi_2 \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1)$$

- the prologue trace  $\pi_1$  terminates at  $\text{at} \llbracket S \rrbracket$
- the continuation trace  $\pi_2$  starts at  $\text{at} \llbracket S \rrbracket$

(will be proved by structural induction on  $S$ )

# Axioms

## Structural prefix trace semantics at a program component

Prefix trace at a program component  $S$

$$\bullet \quad \frac{}{\text{at}[\![S]\!] \in \hat{\mathcal{S}}^*[\![S]\!](\pi_1 \text{at}[\![S]\!])} \quad (6.11)$$

A prefix continuation of the traces  $\pi_1 \text{at}[\![S]\!]$  arriving at a program, statement or statement list  $S$  can be reduced to the program point  $\text{at}[\![S]\!]$  at this program, statement or statement list  $S$ .

## Structural prefix trace semantics of an empty statement list

Prefix traces of an empty statement list  $S\ell ::= \epsilon$

$$\bullet \quad \frac{}{\text{at}[\![S\ell]\!] \in \widehat{\mathcal{S}}^*[\![S\ell]\!](\pi \text{at}[\![S\ell]\!])} \quad (6.15)$$

- A prefix/maximal trace  $\pi$  of the empty statement list  $\epsilon$  continuing some trace is reduced to the program label  $\text{at}[\![S\ell]\!]$  at that empty statement.
- This case is redundant and already covered by (6.11).

## Structural prefix trace semantics of an assignment statement

Prefix traces of an assignment statement  $S ::= \ell \ x = A ;$

$$\bullet \quad \frac{v = \mathcal{A} \llbracket A \rrbracket \varrho(\pi^\ell)}{\ell \xrightarrow{x = A = v} \text{after} \llbracket S \rrbracket \in \widehat{\mathcal{S}}^* \llbracket S \rrbracket (\pi^\ell)} \quad (6.16)$$

A prefix/maximal finite trace of an assignment  $\ell \ x = E ;$  continuing some trace  $\pi^\ell$  is  $\ell$  followed by the event  $x = v$  where  $v$  is the last value of  $x$  previously assigned to  $x$  on  $\pi^\ell$  (otherwise initialized to 0) and finishing at the label  $\text{after} \llbracket S \rrbracket$  after the assignment.



## Structural prefix trace semantics of a skip statement

*Prefix traces of a skip statement*  $S ::= \ell;$

$$\bullet \quad \frac{}{\ell \xrightarrow{\text{skip}} \text{after}[[S]] \in \hat{\mathcal{S}}^*[[S]](\pi^\ell)} \quad (6.17)$$

A prefix/maximal finite trace of a skip statement  $\ell;$  continuing an initial trace  $\pi^\ell$  arriving at  $\ell$  is just continuing after the skip statement.

## Structural prefix trace semantics of a break statement

Prefix traces of a break statement  $S ::= \ell \text{ break ;}$

$$\bullet \quad \frac{}{\ell \xrightarrow{\text{break}} \text{break-to}[\![S]\!] \in \widehat{\mathcal{S}}^*[\![S]\!](\pi^\ell)} \quad (6.29)$$

A prefix/maximal finite trace of a break  $\ell \text{ break ;}$  continuing some initial trace  $\pi^\ell$  is the trace  $\ell$  followed by the  $\text{break ;}$  event and ending at the break label  $\text{break-to}[\![S]\!]$  (which is the exit label of the closest enclosing iteration loop or else the program exit).

# Structural inference rules

## Structural prefix trace semantics of a program

Prefix traces of a program  $P ::= S \ell$

$$\bullet \frac{\pi_2 \in \hat{\mathcal{S}}^* \llbracket S \ell \rrbracket (\pi_1 \text{at} \llbracket S \ell \rrbracket)}{\pi_2 \in \hat{\mathcal{S}}^* \llbracket P \rrbracket (\pi_1 \text{at} \llbracket P \rrbracket)} \quad (6.12)$$

If  $P ::= S \ell$  then the prefix continuations of the traces  $\pi_1 \text{at} \llbracket S \ell \rrbracket$  arriving at program entry  $\text{at} \llbracket P \rrbracket = \text{at} \llbracket S \ell \rrbracket$  are the continuations of the statement list  $S \ell$ .

## Structural prefix trace semantics of a compound statement

*Prefix traces of a compound statement*  $S ::= \{ S \ell \}$

$$\bullet \frac{\pi_2 \in \hat{\mathcal{S}}^* \llbracket S \ell \rrbracket (\pi_1)}{\pi_2 \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1)} \quad (6.30)$$

A prefix trace of a compound statement  $\{ S \ell \}$  is that of its statement list  $S \ell$ .

# Structural prefix trace semantics of a conditional statement

Prefix traces of a conditional statement  $S ::= \text{if } \ell(B) S_t$

$$\bullet \frac{\mathcal{B}[[B]]\varrho(\pi_1^\ell) = \text{ff}}{\ell \xrightarrow{\neg(B)} \text{after}[[S]] \in \hat{\mathcal{S}}^*[[S]](\pi_1^\ell)} \quad (6.18)$$

$$\bullet \frac{\mathcal{B}[[B]]\varrho(\pi_1^\ell) = \text{tt}, \quad \pi_2 \in \hat{\mathcal{S}}^*[[S_t]](\pi_1^\ell \xrightarrow{B} \text{at}[[S_t]])}{\ell \xrightarrow{B} \text{at}[[S_t]] \frown \pi_2 \in \hat{\mathcal{S}}^*[[S]](\pi_1^\ell)} \quad (6.19)$$

## Structural prefix trace semantics of a conditional statement

- A prefix trace of a conditional statement  $\text{if } \ell \ (B) \ S_t$  continuing some initial trace  $\pi_1^\ell$  is
  - either  $\ell$  (a case already covered by (6.11));
  - or, in case (6.18),  $\ell$  followed by the event  $\neg(B)$  when the value of this boolean expression on  $\pi_1^\ell$  is  $\text{ff}$  and finishing at the label after  $\llbracket S \rrbracket$  after the conditional statement;
  - or, in case (6.19), when the value of the boolean expression  $B$  on  $\pi_1^\ell$  is  $\text{tt}$ ,  $\ell$  followed by the test event  $B$  followed by a prefix trace of  $S_t$  continuing  $\pi_1^\ell \xrightarrow{B}$  at  $\llbracket S_t \rrbracket$ .

# Structural prefix trace semantics of a conditional statement

Prefix traces of a conditional statement  $S ::= \text{if } \ell(B) S_t \text{ else } S_f$

$$\bullet \frac{\mathcal{B}[\![B]\!]q(\pi_1^\ell) = \text{tt}, \quad \pi_2 \in \hat{\mathcal{S}}^*[\![S_t]\!](\pi_1^\ell \xrightarrow{B} \text{at}[\![S_t]\!])}{\ell \xrightarrow{B} \text{at}[\![S_t]\!] \frown \pi_2 \in \hat{\mathcal{S}}^*[\![S]\!](\pi_1^\ell)} \quad (6.22)$$

$$\bullet \frac{\mathcal{B}[\![B]\!]q(\pi_1^\ell) = \text{ff}, \quad \pi_2 \in \hat{\mathcal{S}}^*[\![S_f]\!](\pi_1^\ell \xrightarrow{\neg(B)} \text{at}[\![S_f]\!])}{\ell \xrightarrow{\neg(B)} \text{at}[\![S_f]\!] \frown \pi_2 \in \hat{\mathcal{S}}^*[\![S]\!](\pi_1^\ell)} \quad (6.23)$$

A prefix finite trace of a conditional statement  $\text{if } \ell(B) S_t \text{ else } S_f$  continuing an initial trace  $\pi_1^\ell$  is the test event  $B$  (respectively  $\neg(B)$ ) at  $\ell$  followed by a prefix trace of  $S_t$  (respectively  $S_f$ ) when boolean expression  $B$  is  $\text{tt}$  (respectively  $\text{ff}$ ) on  $\pi_1^\ell$  in case (6.22) (respectively (6.23)).



## Structural prefix trace semantics of a statement list

Prefix traces of a statement list  $sl ::= sl' S$

$$\bullet \frac{\pi_2 \in \hat{\mathcal{S}}^* \llbracket sl' \rrbracket (\pi_1)}{\pi_2 \in \hat{\mathcal{S}}^* \llbracket sl \rrbracket (\pi_1)} \quad (6.13)$$

$$\bullet \frac{\pi_2 \in \hat{\mathcal{S}}^+ \llbracket sl' \rrbracket (\pi_1), \quad \pi_3 \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1 \frown \pi_2)}{\pi_2 \frown \pi_3 \in \hat{\mathcal{S}}^* \llbracket sl \rrbracket (\pi_1)} \quad (6.14)$$

In case (6.14),

$$\begin{array}{c} \xrightarrow{\pi_1} \quad \begin{array}{c} \text{at} \llbracket sl \rrbracket \\ \text{at} \llbracket sl' \rrbracket \end{array} \xrightarrow{\pi_2} \quad \begin{array}{c} \text{after} \llbracket sl' \rrbracket \\ \text{at} \llbracket S \rrbracket \end{array} \xrightarrow{\pi_3} \ell \\ \hline \underbrace{\begin{array}{c} \in \hat{\mathcal{S}}^+ \llbracket sl' \rrbracket (\pi_1 \text{at} \llbracket sl' \rrbracket) \\ \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1 \text{at} \llbracket sl' \rrbracket \pi_2 \text{at} \llbracket S \rrbracket) \end{array}}_{\in \hat{\mathcal{S}}^* \llbracket sl \rrbracket (\pi_1 \text{at} \llbracket sl \rrbracket)} \end{array}$$

A prefix trace of  $sl' S$  continuing an initial trace  $\pi_1$  can be a prefix trace of  $sl'$  or a finite maximal trace of  $sl'$  followed by a prefix trace of  $S$ .

# Structural prefix trace semantics of an iteration statement

Prefix traces of an iteration statement  $S ::= \text{while } \ell(B) S_b$

$$\bullet \frac{}{\ell \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell)} \quad (6.24)$$

$$\bullet \frac{\ell \pi_2^\ell \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell), \quad \mathcal{B} \llbracket B \rrbracket \mathbf{q}(\pi_1^\ell \pi_2^\ell) = \text{ff}}{\ell \pi_2^\ell \xrightarrow{\neg(B)} \text{after} \llbracket S \rrbracket \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell)} \quad (6.25)$$

$$\bullet \frac{\begin{array}{l} \ell \pi_2^\ell \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell), \quad \mathcal{B} \llbracket B \rrbracket \mathbf{q}(\pi_1^\ell \pi_2^\ell) = \text{tt}, \\ \pi_3 \in \hat{\mathcal{S}}^* \llbracket S_b \rrbracket (\pi_1^\ell \pi_2^\ell \xrightarrow{B} \text{at} \llbracket S_b \rrbracket) \end{array}}{\ell \pi_2^\ell \xrightarrow{B} \text{at} \llbracket S_b \rrbracket \frown \pi_3 \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell)} \quad (6.26)$$

This is a forward, left recursive definition where  $n + 1$  iterations are  $n$  iterations followed by one more iteration.

# Structural prefix trace semantics of an iteration statement: break statements

*Remark 6.27* The inference rule (6.26) includes the case of an iteration ending with an **exits** by a **break statement** that would have the form

$$\begin{array}{c}
 \ell\pi_2^\ell \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell), \quad \mathcal{B} \llbracket B \rrbracket \varrho(\pi_1^\ell \pi_2^\ell) = \mathbf{tt}, \\
 \pi_3 \xrightarrow{\text{break}} \text{break-to} \llbracket S \rrbracket \in \hat{\mathcal{S}}^* \llbracket S_b \rrbracket (\pi_1^\ell \pi_2^\ell \xrightarrow{B} \text{at} \llbracket S_b \rrbracket) \\
 \hline
 \bullet \quad \ell\pi_2^\ell \xrightarrow{B} \text{at} \llbracket S_b \rrbracket \frown \pi_3 \xrightarrow{\text{break}} \text{break-to} \llbracket S \rrbracket \in \hat{\mathcal{S}}^* \llbracket S \rrbracket (\pi_1^\ell)
 \end{array} \tag{6.28}$$

## Structural prefix trace semantics of an iteration statement

- A prefix finite trace of an iteration statement  $\text{while } \ell \ (B) \ S_b$  continuing some initial trace  $\pi_1^\ell$  is
  - either  $\ell$  (case (6.24), already covered by (6.11));
  - or, in case (6.25), the trace starting at  $\ell$  followed by the event  $\neg(B)$  when the value of this boolean expression on  $\pi_1^\ell$  is  $\text{ff}$  and finishing at the label after  $\llbracket S \rrbracket$  after the iteration statement;
  - or, in case (6.28), the trace starting at  $\ell$  followed by the event  $B$  when the value of this boolean expression on  $\pi_1^\ell$  is  $\text{tt}$  and finishing at the label at  $\llbracket S_b \rrbracket$  followed by a prefix (indeed maximal) trace of the loop body  $S_b$  ending up in a break;
  - or, in case (6.26), the trace starting at  $\ell$ , followed by a prefix trace of the iteration statement  $\text{while } \ell \ (B) \ S_b$  representing 0 or more of iterations ending at  $\ell$ , followed by the test event  $B$  (where the expression  $B$  is  $\text{tt}$ ), followed by a prefix finite trace of the body  $S_t$ .

## Prefix trace semantics

- The prefix trace semantics is defined structurally:

$$\mathcal{S}^*[[S]] \triangleq \widehat{\mathcal{S}}^*[[S]]$$

- The prefix traces starting from a set  $\mathcal{P}_0$  of initial traces are

$$\mathcal{S}^*[[S]] \mathcal{P}_0 \triangleq \bigcup \{ \mathcal{S}^*[[S]](\pi^\ell) \mid \pi^\ell \in \mathcal{P}_0 \}.$$

- The prefix traces starting from a set  $\mathcal{P}_0$  of initial traces and arriving at program label  $\ell$  are

$$\begin{aligned} \mathcal{S}^*[[S]] &\in \wp(\mathbb{T}^+) \xrightarrow{\quad} (\mathcal{L} \rightarrow \wp(\mathbb{T}^+)) \\ \mathcal{S}^*[[S]] \mathcal{P}_0^\ell &\triangleq \{ \pi_0^{\ell_0} \pi_1^{\ell_1} \mid \pi_0^{\ell_0} \in \mathcal{P}_0 \wedge \ell_0 \pi_1^{\ell_1} \in \mathcal{S}^*[[S]](\pi_0^{\ell_0}) \wedge \ell_1 = \ell \} \end{aligned} \tag{6.48}$$

## Example of prefix trace semantics

- $S = \text{while } \ell_1 \text{ (tt)} \ell_2 \ x = x + 1 ; \ell_3.$
- $\hat{\mathcal{S}}^* \llbracket S \rrbracket (\ell_1) = \left\{ \left( \ell_1 \xrightarrow{\text{tt}} \ell_2 \xrightarrow{x=i} \ell_1 \right)_{i=1}^n, \left( \ell_1 \xrightarrow{\text{tt}} \ell_2 \xrightarrow{x=i} \ell_1 \right)_{i=1}^n \xrightarrow{\text{tt}} \ell_2 \mid n \in \mathbb{N} \right\}$  (reduced to  $\ell_1$  for  $n = 0$ ).
- Notation:
  - $\left( \ell \pi(i) \ell \right)_{i=1}^n$  denotes the finite trace  $\ell \pi(1) \ell \pi(2) \ell \dots \pi(n) \ell$ . This is the trace  $\ell$  for  $n = 0$ .
  - $\left( \ell \pi(i) \ell \right)_{i=1}^{\infty}$  denotes the infinite trace  $\ell \pi(1) \ell \pi(2) \ell \dots \pi(n) \ell \pi(n+1) \ell \dots$ .

# Conclusion

# Conclusion

- We have defined the **structural deductive stateless prefix trace semantics** of a subset of C to observe partial computations of programs, where this observation can stop at any time.
- By passing to the limit, we will define the **maximal trace semantics** where observations terminate with the execution of the program or last for ever in case of non-termination.



# The End, Thank you