

LAPORAN PRAKTIKUM
PEMROGRAMAN BERBASIS FRAMEWORK

Pertemuan Minggu-13

Modul 13 – Laravel dan ReactJS (CRUD 1)

“Backend Laravel dan Frontend ReactJS”




NAMA : DINA RISKY ALIN SAPUTRI
NIM : 1841720016
KELAS : 3F

PROGRAM STUDI TEKNIK INFORMATIKA
JURUSAN TEKNOLOGI INFORMASI
POLITEKNIK NEGERI MALANG

2021



Praktikum Bagian 1 – Install Laravel 7



Langkah	Keterangan
1	<p>Ketikkan syntax seperti dibawah ini untuk melakukn instalasi Laravel 7.</p> <p>composer create-project --prefer-dist laravel/laravel:^7.0 laravelreactcrud-dina</p>  <pre>C:\Windows\System32\cmd.exe Microsoft Windows [Version 10.0.19042.985] (c) Microsoft Corporation. All rights reserved. C:\Users\ASUS\Pemrograman-Framework\minggui3>composer create-project --prefer-dist laravel/laravel:^7.0 laravelreactcrud-dina Creating a "laravel/laravel:7.0" project at "./laravelreactcrud-dina" Installing laravel/laravel (v7.0.0) - Installing laravel/laravel (v7.0.0): Extracting archive Created project in C:\Users\ASUS\Pemrograman-Framework\minggui3\laravelreactcrud-dina > @php -r "file_exists('.env') copy('.env.example', '.env');" Loading composer repositories with package information Updating dependencies Lock file operations: 97 installs, 0 updates, 0 removals - Locking asm89/stack-cors (1.3.0) - Locking brick/math (0.9.2) - Locking doctrine/inflector (2.0.3) - Locking doctrine/instantiator (1.4.0) - Locking doctrine/lexer (1.2.1) - Locking dragonmantank/cron-expression (v2.3.1) - Locking egulias/email-validator (2.1.25) - Locking facade/flare-client-php (1.8.0) - Locking facade/ignition (2.9.0) - Locking facade/ignition-contracts (1.0.2) - Locking fideloper/proxy (4.4.1) - Locking filp/whoops (2.12.1) - Locking fruitcake/laravel-cors (v1.0.6) - Locking fzaminotto/faker (v1.9.2) - Locking guzzlehttp/guzzle (6.5.5) - Locking tijsverkoyen/css-to-inline-styles (2.2.3) - Locking vlucas/phpdotenv (v4.2.0) - Locking voku/portable-ascii (1.5.6) - Locking webmozart/assert (1.10.0) Writing lock file Installing dependencies from lock file (including require-dev) Package operations: 97 installs, 0 updates, 0 removals - Downloading symfony/var-dumper (v5.2.8) - Downloading symfony/string (v5.2.8) - Downloading symfony/console (v5.2.8) - Downloading symfony/css-selector (v5.2.9) - Downloading symfony/routing (v5.2.9) - Downloading symfony/mime (v5.2.9) - Downloading symfony/http-foundation (v5.2.8) - Downloading symfony/error-handler (v5.2.8) - Downloading symfony/http-kernel (v5.2.9) - Downloading symfony/finder (v5.2.9) - Downloading symfony/translation (v5.2.9) - Downloading nesbot/carbon (2.48.0) - Downloading league/commonmark (1.6.2) - Downloading facade/ignition (2.9.0)</pre>

	<pre> - Installing sebastian/comparator (3.0.2): Extracting archive - Installing phpunit/php-timer (2.1.3): Extracting archive - Installing phpunit/php-text-template (1.2.1): Extracting archive - Installing phpunit/php-file-iterator (2.0.3): Extracting archive - Installing theseer/tokenizer (1.2.0): Extracting archive - Installing sebastian/code-unit-reverse-lookup (1.0.2): Extracting archive - Installing phpunit/php-code-coverage (7.0.14): Extracting archive - Installing doctrine/instantiator (1.4.0): Extracting archive - Installing phpspec/prophecy (1.13.0): Extracting archive - Installing phar-io/version (3.1.0): Extracting archive - Installing phar-io/manifest (2.0.1): Extracting archive - Installing myclabs/deep-copy (1.10.2): Extracting archive - Installing phpunit/phpunit (8.5.15): Extracting archive 77 package suggestions were added by new dependencies, use `composer suggest` to see details. Package fzaninotto/faker is abandoned, you should avoid using it. No replacement was suggested. Package phpunit/php-token-stream is abandoned, you should avoid using it. No replacement was suggested. Generating optimized autoload files > Illuminate\Foundation\ComposerScripts::postAutoloadDump > @php artisan package:discover --ansi Discovered Package: facade/ignition Discovered Package: fideloper/proxy Discovered Package: fruitcake/laravel-cors Discovered Package: laravel/tinker Discovered Package: nesbot/carbon Discovered Package: nunomaduro/collision Package manifest generated successfully. 66 packages you are using are looking for funding. Use the `composer fund` command to find out more! > @php artisan key:generate --ansi Application key set successfully. C:\Users\ASUS\Pemrograman-Framework\minggu13> </pre>
2	<p>Silahkan buat database baru bernama db_laravelreactcrud_dina.</p> 
3	<p>Kemudian buka file .env yang ada di direktori laravelreactcrud-dina/.env:</p> <p>Cari kode berikut ini di file .env:</p> <pre> laravelreactcrud-dina > .env 9 DB_CONNECTION=mysql 10 DB_HOST=127.0.0.1 11 DB_PORT=3306 12 DB_DATABASE=laravel 13 DB_USERNAME=root 14 DB_PASSWORD= 15 </pre> <p>Dan ubah menjadi menjadi</p> <pre> laravelreactcrud-dina > .env 9 DB_CONNECTION=mysql 10 DB_HOST=127.0.0.1 11 DB_PORT=3306 12 DB_DATABASE=db_laravelreactcrud_dina 13 DB_USERNAME=root 14 DB_PASSWORD= 15 </pre>

4	<p>Masih di direktori project, ketik command berikut untuk membuat Model Article dan Migration-nya:</p> <p>php artisan make:model Article --migration</p> <pre> C:\Users\ASUS\Pemrograman-Framework\minggu13>cd C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>php artisan make:model Article --migration Model created successfully. Created Migration: 2021_05_25_225007_create_articles_table C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina> </pre>
5	<p>Sekarang buka file Article.php yang ada di dalam direktori app/Article.php dan modifikasi:</p> <pre> Article.php X laravelreactcrud-dina > app > Article.php > ... 1 <?php 2 3 namespace App; 4 5 use Illuminate\Database\Eloquent\Model; 6 7 class Article extends Model 8 { 9 protected \$table = "articles"; 10 protected \$fillable = ['title', 'content']; 11 } 12 </pre>
6	<p>Kemudian, buka file *****create_articles_table.php yang tersimpan di direktori database/migrations dan modifikasi seperti kode di bawah ini:</p>

	 <pre> 2021_05_25_225007_create_articles_table.php U X laravelreactcrud-dina > database > migrations > 2021_05_25_225007_create_articles_table.php > PHP Intelephense > 1 <?php 2 3 use Illuminate\Database\Migrations\Migration; 4 use Illuminate\Database\Schema\Blueprint; 5 use Illuminate\Support\Facades\Schema; 6 7 class CreateArticlesTable extends Migration 8 { 9 /** 10 * Run the migrations. 11 * 12 * @return void 13 */ 14 public function up() 15 { 16 Schema::create('articles', function (Blueprint \$table) { 17 \$table->bigIncrements('id'); 18 \$table->string('title'); 19 \$table->string('content'); 20 \$table->timestamps(); 21 }); 22 } 23 24 /** 25 * Reverse the migrations. 26 * 27 * @return void 28 */ 29 public function down() 30 { 31 Schema::dropIfExists('articles'); 32 } 33 } </pre>
7	<p>Kemudian jalankan command berikut ini agar table yang kita buat migrate ke database:</p> <p>php artisan migrate</p>  <pre> C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>php artisan migrate Migration table created successfully. Migrating: 2014_10_12_000000_create_users_table Migrated: 2014_10_12_000000_create_users_table (0.41 seconds) Migrating: 2019_08_19_000000_create_failed_jobs_table Migrated: 2019_08_19_000000_create_failed_jobs_table (0.19 seconds) Migrating: 2021_05_25_225007_create_articles_table Migrated: 2021_05_25_225007_create_articles_table (0.28 seconds) C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina> </pre>
8	<p>Jika berhasil dengan baik, maka di database db_laravelreactcrud_dina akan muncul table seperti gambar di bawah ini:</p>

	
9	<p>Buka file routes/web.php dan silahkan modifikasi:</p>  <pre> 1 <?php 2 3 use Illuminate\Support\Facades\Route; 4 5 /* 6 ----- 7 Web Routes 8 ----- 9 10 Here is where you can register web routes for your application. These 11 routes are loaded by the RouteServiceProvider within a group which 12 contains the "web" middleware group. Now create something great! 13 14 */ 15 16 Route::view('/articles', 'app'); 17 Route::view('/article/edit/{id}', 'app'); 18 Route::view('/article/{id}', 'app'); 19 Route::view('/', 'app'); 20 Route::view('/{path}', 'app'); 21 </pre>
10	<p>Kemudian buka file routes/api.php dan modifikasi menjadi:</p>

	 <pre> api.php U X laravelreactcrud-dina > routes > api.php 1 <?php 2 3 use Illuminate\Http\Request; 4 use Illuminate\Support\Facades\Route; 5 6 /* 7 ----- 8 API Routes 9 ----- 10 11 Here is where you can register API routes for your application. These 12 routes are loaded by the RouteServiceProvider within a group which 13 is assigned the "api" middleware group. Enjoy building your API! 14 15 */ 16 17 Route::get('/articles', 'ArticleController@index'); 18 Route::post('/article/store', 'ArticleController@store'); 19 Route::get('/article/edit/{id}', 'ArticleController@getArticle'); 20 Route::get('/article/{id}', 'ArticleController@getArticle'); 21 Route::put('/article/{id}', 'ArticleController@update'); 22 Route::delete('/article/delete/{id}', 'ArticleController@delete'); </pre>
11	<p>Ketik command di bawah ini untuk membuat controller baru bernama ArticleController</p> <p>php artisan make:controller ArticleController</p>  <pre> C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>php artisan make:controller ArticleController Controller created successfully. C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina> </pre>
12	<p>Sekarang buka file ArticleController.php yang terdapat di app/Http/Controllers.</p> <p>Kemudian ketik kode berikut ini:</p>

ArticleController.php U X

laravelreactcrud-dina > app > Http > Controllers > ArticleController.php > PHP Intelephense >

```
1  <?php
2
3  namespace App\Http\Controllers;
4
5  use Illuminate\Http\Request;
6
7  class ArticleController extends Controller
8  {
9      public function index()
10     {
11         $articles = \App\Article::all();
12
13         return $articles->toJson();
14     }
15
16     public function store(Request $request)
17     {
18         $validatedData = $request->validate([
19             'title' => 'required',
20             'content' => 'required',
21         ]);
22
23         $project = \App\Article::create([
24             'title' => $validatedData['title'],
25             'content' => $validatedData['content'],
26             'content' => $validatedData['content'],
27         ]);
28
29         $msg = [
30             'success' => true,
31             'message' => 'Article created successfully!'
32         ];
33
34         return response()->json($msg);
35     }
36
37     public function getArticle($id) // for edit and show
38     {
39         $article = \App\Article::find($id);
40
41         return $article->toJson();
42     }
43
44     public function update(Request $request, $id)
45     {
46         $validatedData = $request->validate([
47             'title' => 'required',
48             'content' => 'required',
49         ]);
50
51         $article = \App\Article::find($id);
```



```

51         $article->title = $validatedData['title'];
52         $article->content = $validatedData['content'];
53         $article->save();
54
55         $msg = [
56             'success' => true,
57             'message' => 'Article updated successfully'
58         ];
59
60         return response()->json($msg);
61     }
62
63     public function delete($id)
64     {
65         $article = \App\Article::find($id);
66         if (!empty($article)) {
67             $article->delete();
68             $msg = [
69                 'success' => true,
70                 'message' => 'Article deleted successfully!'
71             ];
72             return response()->json($msg);
73         } else {
74             $msg = [
75                 'success' => false,
76                 'message' => 'Article deleted failed!'
77             ];
78             return response()->json($msg);
79         }
80     }
81 }
82

```

Jika Anda ingin menginstall package React Js, React Router Dom dan Sweet Alert, silahkan dimulai dari install package **laravel ui** dan **laravel ui react** berikut ini:

composer require laravel/ui “^2.0”

```

C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>composer require laravel/ui "^2.0"
./composer.json has been updated
Running composer update laravel/ui
Loading composer repositories with package information
Updating dependencies
Lock file operations: 1 install, 0 updates, 0 removals
  - Locking laravel/ui (v2.5.0)
Writing lock file
Installing dependencies from lock file (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
  - Downloading laravel/ui (v2.5.0)
  - Installing laravel/ui (v2.5.0): Extracting archive
Package fzaninotto/faker is abandoned, you should avoid using it. No replacement was suggested.
Package phpunit/php-token-stream is abandoned, you should avoid using it. No replacement was suggested.
Generating optimized autoload files
> Illuminate\Foundation\ComposerScripts::postAutoloadDump
> @php artisan package:discover --ansi
Discovered Package: facade/ignition
Discovered Package: fideloper/proxy
Discovered Package: fruitcake/laravel-cors
Discovered Package: laravel/tinker
Discovered Package: laravel/ui
Discovered Package: nesbot/carbon
Discovered Package: nunomaduro/collision
Package manifest generated successfully.
66 packages you are using are looking for funding.
Use the 'composer fund' command to find out more!

C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>

```

Kemudian install react js:

php artisan ui react

```
C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>php artisan ui react
React scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.
```

Lalu install NodeJsnya:

npm install && npm run dev

```
C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>npm install && npm run dev
npm WARN deprecated axios@0.19.2: Critical security vulnerability fixed in v0.21.1. For more information, see https://github.com/axios/axios/pull/3410
npm WARN deprecated popper.js@1.16.1: You can find the new Popper v2 at @popperjs/core, this package is dedicated to the legacy v1
npm WARN deprecated chokidar@2.1.8: Chokidar 2 will break on node v14+. Upgrade to chokidar 3 with 15x less dependencies.
npm WARN deprecated fsevents@1.2.13: fsevents 1 will break on node v14+ and could be using insecure binaries. Upgrade to fsevents 2.
npm WARN deprecated urix@0.1.0: Please see https://github.com/lydell/urix#deprecated
npm WARN deprecated resolve-url@0.2.1: https://github.com/lydell/resolve-url#deprecated
npm notice created a lockfile as package-lock.json. You should commit this file.
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.7 (node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~2.3.1 (node_modules\watchpack\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~2.3.1 (node_modules\sass\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

added 1129 packages from 500 contributors and audited 1133 packages in 127.582s

59 packages are looking for funding
```

```
98% after emitting SizeLimitsPlugin
DONE Compiled successfully in 12547ms 6:38:55 AM

   Asset      Size  Chunks             Chunk Names
  /css/app.css 179 KiB  /js/app  [emitted]  /js/app
  /js/app.js    2 MiB  /js/app  [emitted]  /js/app
Installing shortcut: "C:\\Users\\ASUS\\AppData\\Roaming\\Microsoft\\Windows\\Start Menu\\Programs\\SnoreToast\\0.7.0\\SnoreToast.lnk" "C:\\Users\\ASUS\\Pemrograman-Framework\\minggu13\\laravelreactcrud-dina\\node_modules\\node-notifier\\vendor\\snoretoast\\snoretoast-x64.exe" Snore.DesktopToasts.0.7.0

C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>
```

Kemudian install react router dom nya:

npm install react-router-dom

```
C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>npm install react-router-dom
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\watchpack\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})



+ react-router-dom@5.2.0
added 11 packages from 6 contributors and audited 1144 packages in 22.026s

59 packages are looking for funding
  run `npm fund` for details

found 38 vulnerabilities (36 moderate, 2 high)
  run `npm audit fix` to fix them, or `npm audit` for details

C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>
```

	<p>dan terakhir sweat alertnya:</p> <p>npm i react-bootstrap-sweetalert</p> <pre> C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>npm i react-bootstrap-sweetalert npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@1.2.13 (node_modules\fsevents): npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"}) npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\watchpack\node_modules\fsevents): npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"}) npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@2.3.2 (node_modules\sass\node_modules\fsevents): npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.3.2: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"}) + react-bootstrap-sweetalert@5.2.0 added 1 package from 1 contributor and audited 1145 packages in 59.993s 59 packages are looking for funding run `npm fund` for details found 38 vulnerabilities (36 moderate, 2 high) run `npm audit fix` to fix them, or `npm audit` for details C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina> </pre>
14	<p>Buat file baru bernama App.js dan simpan di direktori resources/js/components.</p> <p>Ketik kode berikut ini:</p> <pre> JS App.js U X laravelreactcrud-dina > resources > js > components > JS App.js > ... 1 import React, { Component } from 'react' 2 import ReactDOM from 'react-dom' 3 import { BrowserRouter, Route, Switch } from 'react-router-dom' 4 import Header from './Header' 5 import ArticleIndex from './ArticleIndex' 6 import ArticleCreate from './ArticleCreate' 7 import ArticleShow from './ArticleShow' 8 import ArticleEdit from './ArticleEdit' 9 10 class App extends Component { 11 render() { 12 return (13 <BrowserRouter> 14 <div> 15 <Header /> 16 <Switch> 17 <Route exact path="/" component={ArticleIndex} /> 18 <Route exact path="/create" component={ArticleCreate} /> 19 <Route path="/article/edit/:id" component={ArticleEdit} /> 20 <Route path="/article/:id" component={ArticleShow} /> 21 </Switch> 22 </div> 23 </BrowserRouter> 24) 25 } 26 } 27 28 ReactDOM.render(<App />, document.getElementById('app')) </pre>
15	<p>Buat lagi file baru bernama Header.js dan simpan di direktori resources/js/components.</p>

	 <pre> JS App.js U JS Header.js U X laravelreactcrud-dina > resources > js > components > JS Header.js > Header 1 import React from 'react' 2 import { Link } from 'react-router-dom' 3 4 const Header = () => (5 <nav className='navbar navbar-dark bg-dark'> 6 <div className='container'> 7 <Link className='navbar-brand' to='/'>Ilmu Coding</Link> 8 </div> 9 </nav> 10) 11 12 export default Header </pre>
16	<p>Buat lagi file baru bernama ArticleIndex.js dan simpan di direktori resources/js/components.</p> <p>Ketik kode berikut ini:</p>  <pre> JS App.js U JS Header.js U JS ArticleIndex.js U X laravelreactcrud-dina > resources > js > components > JS ArticleIndex.js > ArticleIndex > render > articles.map() callback 1 import axios from 'axios' 2 import React, { Component } from 'react' 3 import { Link } from 'react-router-dom' 4 import SweetAlert from 'react-bootstrap-sweetalert'; 5 6 class ArticleIndex extends Component { 7 8 constructor() { 9 super() 10 this.state = { 11 articles: [], 12 msg: null, 13 type: null, 14 flash: false, 15 alert: null, 16 } 17 } 18 19 hideAlert() { 20 this.setState({ 21 alert: null 22 }); 23 } 24 25 componentDidMount() { </pre>

```

26     axios.get('/api/articles').then(response => {
27         this.setState({
28             articles: response.data
29         })
30     })
31 }
32
33 confirmDelete(id) {
34     const getAlert = () => (
35         <SweetAlert
36             warning
37             showCancel
38             confirmBtnText="Hapus Deh"
39             cancelBtnText="Nggak Jadi"
40             confirmBtnBsStyle="default"
41             cancelBtnBsStyle="danger"
42             title="Tunggu ..."
43             onConfirm={() => this.deleteItem(id)}
44             onCancel={() => this.hideAlert()}
45             focusCancelBtn
46         >
47         Kalau udah dihapus, nggak bakal balik lagi.
48     </SweetAlert>
49 );
50     this.setState({
51         alert: getAlert()
52     });
53 }
54
55 deleteItem(id) {
56     axios.delete(`/api/article/delete/${id}`).then(response => {
57         var msg = response.data.success;
58         if (msg == true) {
59             this.hideAlert();
60             this.goToHome();
61         }
62     })
63 }
64
65 goToHome() {
66     const getAlert = () => (
67         <SweetAlert
68             success
69             title="Success!"
70             onConfirm={() => this.onSuccess()}
71             onCancel={this.hideAlert()}
72             timeout={2000}
73             confirmBtnText="Oke Siap"
74         >
75         Deleted article successfully
76     </SweetAlert>
77 );
78     this.setState({
79         alert: getAlert()
80     });
81 }
82
83 onSuccess() {
84     this.componentDidMount();
85     this.hideAlert();
86 }
87
88 render() {
89     const { articles } = this.state
90     return (
91         <div className='container py-4'>
92             <div className='row justify-content-center'>
93                 <div className='col-md-8'>
94                     <div className='card'>
95                         <div className='card-header'>All Article</div>
96                         <div className='card-body'>
97                             <Link className='btn btn-primary btn-sm mb-3' to='/create'>
98                                 Create new article
99                             </Link>
100                     </div>

```

```

101 <table className="table table-bordered table-hover">
102 <thead>
103 <tr>
104 <th width="50" className="text-center">No</th>
105 <th>Title</th>
106 <th width="200" className="text-center">Action</th>
107 </tr>
108 </thead>
109 <tbody>
110 {articles.map((article, i) => (
111 <tr key={i}>
112 <td width="50" className="text-center">{i + 1}</td>
113 <td>{article.title}</td>
114 <td width="200" className="text-center">
115 <div className="btn-group">
116 <Link
117   className='btn btn-primary'
118   to={` /article/${article.id}`}
119 >Detail
120 </Link>
121
122 <Link
123   className='btn btn-success'
124   to={` /article/edit/${article.id}`}
125 >Edit
126 </Link>
127
128 <button
129   className='btn btn-danger'
130   onClick={() => this.confirmDelete(article.id)}
131 >Delete
132 </button>
133 </div>
134 </td>
135 </tr>
136 )))
137 </tbody>
138 </table>
139 {this.state.alert}
140 </div>
141 </div>
142 </div>
143 </div>
144 </div>
145 </div>
146 )
147 }
148 }
149
150 export default ArticleIndex

```

17

Buat lagi file baru bernama **ArticleCreate.js** dan simpan di direktori **resources/js/components**.

Ketik kode berikut ini:

```

JS App.js U JS Header.js U JS ArticleIndex.js U JS ArticleCreate.js U X
laravelreactcrud-dina > resources > js > components > JS ArticleCreate.js > ArticleCreate > render
1 import axios from 'axios'
2 import React, { Component } from 'react'
3 import { Link } from 'react-router-dom'
4 import SweetAlert from 'react-bootstrap-sweetalert';
5
6 class ArticleCreate extends Component {
7
8   constructor(props) {
9     super(props)
10    this.state = {
11      title: '',
12      content: '',
13      alert: null,
14      errors: []
15    }
16    this.handleFieldChange = this.handleFieldChange.bind(this)
17    this.handleCreateNewArticle = this.handleCreateNewArticle.bind(this)
18    this.hasErrorFor = this.hasErrorFor.bind(this)
19    this.renderErrorFor = this.renderErrorFor.bind(this)
20  }
21
22  handleFieldChange(event) {
23    this.setState({
24      [event.target.name]: event.target.value
25    })
26  }
27
28  goToHome() {
29    const getAlert = () => (
30      <SweetAlert
31        success
32        title="Success!"
33        onConfirm={() => this.onSuccess()}
34        onCancel={this.hideAlert()}
35        timeout={2000}
36        confirmBtnText="Oke Siap"
37      >
38        Created article successfully
39      </SweetAlert>
40    );
41    this.setState({
42      alert: getAlert()
43    });
44  }
45
46  onSuccess() {
47    this.props.history.push('/');
48  }
49
50  hideAlert() {
51    this.setState({
52      alert: null
53    });
54  }
55
56  handleCreateNewArticle(event) {
57    event.preventDefault()
58    const article = {
59      title: this.state.title,
60      content: this.state.content
61    }
62    axios.post('/api/article/store', article).then(response => {
63      var msg = response.data.success;
64      if (msg == true) {
65        return this.goToHome();
66      }
67    })
68  }
69
70  hasErrorFor(field) {
71    return !!this.state.errors[field]
72  }
73
74  renderErrorFor(field) {
75    if (this.hasErrorFor(field)) {
76      return (
77        <span className='invalid-feedback'>
78          <strong>{this.state.errors[field][0]}</strong>
79        </span>
80      )

```

```

81     }
82   }
83
84   render() {
85     return (
86       <div className='container py-4'>
87         <div className='row justify-content-center'>
88           <div className='col-md-6'>
89             <div className='card'>
90               <div className='card-header'>Create new project</div>
91               <div className='card-body'>
92                 <form onSubmit={this.handleClickNewArticle}>
93                   <div className='form-group'>
94                     <label htmlFor='title'>Title</label>
95                     <input
96                       id='title'
97                       type='text'
98                       className={`form-control ${this.hasErrorFor('title') ? 'is-invalid' : ''}`}
99                       name='title'
100                       value={this.state.title}
101                       onChange={this.handleChange}
102                     />
103                     {this.renderErrorFor('title')}
104                   </div>
105                   <div className='form-group'>
106                     <label htmlFor='content'>Project content</label>
107                     <textarea
108                       id='content'
109                       className={`form-control ${this.hasErrorFor('content') ? 'is-invalid' : ''}`}
110                       name='content'
111                       rows='10'
112                       value={this.state.content}
113                       onChange={this.handleChange}
114                     />
115                     {this.renderErrorFor('content')}
116                   </div>
117                   <Link
118                     className='btn btn-secondary'
119                     to={'/' }
120                   >Back
121                   </Link>
122                   <button className='btn btn-primary'>Create</button>
123                   {this.state.alert}
124                 </form>
125               </div>
126             </div>
127           </div>
128         </div>
129       </div>
130     )
131   }
132 }
133 export default ArticleCreate

```

18

Buat lagi file baru bernama **ArticleEdit.js** dan simpan di direktori **resources/js/components**.

Ketik kode berikut ini:

JS App.js U JS Header.js U JS ArticleIndex.js U JS ArticleCreate.js U JS ArticleEdit.js U X

laravelreactcrud-dina > resources > js > components > JS ArticleEdit.js > ArticleEdit > render

```
1 import axios from 'axios'
2 import React, { Component } from 'react'
3 import { Link } from 'react-router-dom'
4 import SweetAlert from 'react-bootstrap-sweetalert';
5
6 class ArticleEdit extends Component {
7   constructor(props) {
8     super(props)
9     this.state = {
10       title: '',
11       content: '',
12       alert: null,
13       message: '',
14       errors: []
15     }
16     this.handleFieldChange = this.handleFieldChange.bind(this)
17     this.handleUpdateArticle = this.handleUpdateArticle.bind(this)
18     this.hasErrorFor = this.hasErrorFor.bind(this)
19     this.renderErrorFor = this.renderErrorFor.bind(this)
20   }
21
22   handleFieldChange(event) {
23     this.setState({
24       [event.target.name]: event.target.value
25     })
26   }
27
28   componentDidMount() {
29
30     const articleId = this.props.match.params.id
31
32     axios.get(`/api/article/edit/${articleId}`).then(response => {
33       this.setState({
34         title: response.data.title,
35         content: response.data.content,
36       })
37     })
38   }
39
40   goToHome() {
41
42     const getAlert = () => (
43       <SweetAlert
44         success
45         title="Success!"
46         onConfirm={() => this.onSuccess()}
47         onCancel={this.hideAlert()}
48         timeout={2000}
49         confirmBtnText="Oke Siap"
50       >
51         {this.state.message}
52       </SweetAlert>
53     );
54     this.setState({
55       alert: getAlert()
56     });
57
58     onSuccess() {
59       this.props.history.push('/');
60     }
61
62     hideAlert() {
63       this.setState({
64         alert: null
65       });
66     }
67
68     handleUpdateArticle(event) {
69       event.preventDefault()
70
71       const article = {
72         title: this.state.title,
73         content: this.state.content
74       }
75
76       const articleId = this.props.match.params.id
77
78       axios.put(`/api/article/${articleId}`, article)
79         .then(response => {
80           // redirect to the homepage
```

```

81         var msg = response.data.success;
82         if (msg == true) {
83             this.setState({
84                 message: response.data.message
85             })
86             return this.goToHome();
87         }
88     });
89 }
90
91
92 hasErrorFor(field) {
93     return !!this.state.errors[field]
94 }
95
96 renderErrorFor(field) {
97     if (this.hasErrorFor(field)) {
98         return (
99             <span className='invalid-feedback'>
100                 <strong>{this.state.errors[field][0]}</strong>
101             </span>
102         )
103     }
104 }
105
106 render() {
107     const { article } = this.state
108     return (
109         <div className='container py-4'>
110             <div className='row justify-content-center'>
111                 <div className='col-md-6'>
112                     <div className='card'>
113                         <div className='card-header'>Create new project</div>
114                         <div className='card-body'>
115                             <form onSubmit={this.handleUpdateArticle}>
116                                 <div className='form-group'>
117                                     <label htmlFor='title'>Title</label>
118                                     <input
119                                         id='title'
120                                         type='text'
121                                         className={`form-control ${this.hasErrorFor('title') ? 'is-invalid' : ''}`
122                                         name='title'
123                                         value={this.state.title}
124                                         onChange={this.handleFieldChange}
125                                     />
126                                     {this.renderErrorFor('title')}
127                                 </div>
128                                 <div className='form-group'>
129                                     <label htmlFor='content'>Project content</label>
130                                     <textarea
131                                         id='content'
132                                         className={`form-control ${this.hasErrorFor('content') ? 'is-invalid' : ''}`
133                                         name='content'
134                                         rows='10'
135                                         value={this.state.content}
136                                         onChange={this.handleFieldChange}
137                                     />
138                                     {this.renderErrorFor('content')}
139                                 </div>
140                                 <Link
141                                     className='btn btn-secondary'
142                                     to={`/${`}`
143                                 >Back
144                                </Link>
145                                <button className='btn btn-primary'>Update</button>
146                                {this.state.alert}
147                            </form>
148                        </div>
149                    </div>
150                </div>
151            </div>
152        </div>
153    )
154 }
155 }
156 export default ArticleEdit

```

19

Buat lagi file baru bernama **ArticleShow.js** dan simpan di direktori **resources/js/components**.

Ketik kode berikut ini:

```
JS App.js U JS Header.js U JS ArticleIndex.js U JS ArticleCreate.js U JS ArticleEdit.js U JS ArticleShow.js U X
laravelreactcrud-dina > resources > js > components > JS ArticleShow.js > ArticleShow > constructor > article
1 import axios from 'axios'
2 import React, { Component } from 'react'
3 import { Link } from 'react-router-dom'
4
5 class ArticleShow extends Component {
6   constructor(props) {
7     super(props)
8     this.state = {
9       article: {}
10    }
11  }
12
13  componentDidMount() {
14    const articleId = this.props.match.params.id
15
16    axios.get(`/api/article/${articleId}`).then(response => {
17      this.setState({
18        article: response.data
19      })
20    })
21  }
22
23  render() {
24    const { article } = this.state
25
26    return (
27      <div className='container py-4'>
28        <div className='row justify-content-center'>
29          <div className='col-md-8'>
30            <div className='card'>
31              <div className='card-header'>Judul Artikel: {article.title}</div>
32              <div className='card-body'>
33                <p>{article.content}</p>
34                <Link
35                  className='btn btn-primary'
36                  to={`/${articleId}`}
37                >Back
38              </Link>
39            </div>
40          </div>
41        </div>
42      </div>
43    )
44  }
45
46  }
47
48  export default ArticleShow
```

20

Buat file baru bernama **app.blade.php** dan simpan di direktori **resource/views**.

Sekarang ketik kode berikut:

	<div data-bbox="406 210 1485 1029"> <pre> app.blade.php U X laravelreactcrud-dina > resources > views > app.blade.php > html 1 <!DOCTYPE html> 2 <html lang="{{ app()->getLocale() }}"> 3 4 <head> 5 <meta charset="utf-8"> 6 <meta http-equiv="X-UA-Compatible" content="IE=edge"> 7 <meta name="viewport" content="width=device-width, initial-scale=1"> 8 9 <!-- CSRF Token --> 10 <meta name="csrf-token" content="{{ csrf_token() }}"> 11 12 <title>React Laravel</title> 13 14 <!-- Styles --> 15 <link href="{{ asset('css/app.css') }}" rel="stylesheet"> 16 </head> 17 18 <body> 19 <div id="app"></div> 20 21 <script src="{{ asset('js/app.js') }}"></script> 22 </body> 23 24 </html> </pre> </div>
21	<p>Silahkan buka file resources/js/app.js kemudian cari kode berikut:</p> <pre>require('./components/Example');</pre> <div data-bbox="406 1218 1485 1774"> <pre> JS app.js U X laravelreactcrud-dina > resources > js > JS app.js 1 /** 2 * First we will load all of this project's JavaScript dependencies which 3 * includes React and other helpers. It's a great starting point while 4 * building robust, powerful web applications using React + Laravel. 5 */ 6 7 require('./bootstrap'); 8 9 /** 10 * Next, we will create a fresh React component instance and attach it to 11 * the page. Then, you may begin adding components to this application 12 * or customize the JavaScript scaffolding to fit your unique needs. 13 */ 14 15 require('./components/Example'); 16 </pre> </div> <p>Ubah menjadi kode berikut:</p>

```
require('./components/App');
```

```
JS app.js U X
laravelreactcrud-dina > resources > js > JS app.js
1  /**
2   * First we will load all of this project's JavaScript dependencies which
3   * includes React and other helpers. It's a great starting point while
4   * building robust, powerful web applications using React + Laravel.
5   */
6
7   require('./bootstrap');
8
9   /**
10    * Next, we will create a fresh React component instance and attach it to
11    * the page. Then, you may begin adding components to this application
12    * or customize the JavaScript scaffolding to fit your unique needs.
13    */
14
15   require('./components/App');
16
```

Fungsinya agar antara file **resources/js/app. js** dan **resources/js/components/App. js** terhubung.

Ketik command berikut untuk menginstall perubahan yang terjadi:

npm run dev

```
C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>npm run dev
> @ dev C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina
> npm run development

> @ development C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina
> cross-env NODE_ENV=development node_modules\webpack\bin\webpack.js --progress --hide-modules --config=node_modules\laravel-mix\setup\webpack.config.js

12% building 19/21 modules 2 active ...laravelreactcrud-dina\node_modules\react-router-dom\esm\react-router-dom.jsD
DEPRECATION WARNING: Using / for division is deprecated and will be removed in Dart Sass 2.0.0.

Recommendation: math.div($spacer, 2)

More info and automated migrator: https://sass-lang.com/d/slash-div

302 | $headings-margin-bottom:          $spacer / 2 !default;
    |                                ^^^^^^^^^^^^^
    |                                |
    |                                node_modules\bootstrap\scss\_variables.scss 302:31 @import
    |                                node_modules\bootstrap\scss\bootstrap.scss 9:9      @import
    |                                stdin 8:9      root stylesheet

DEPRECATION WARNING: Using / for division is deprecated and will be removed in Dart Sass 2.0.0.

WARNING: 64 repetitive deprecation warnings omitted.

98% after emitting SizeLimitsPlugin

DONE Compiled successfully in 23114ms 7:18:24 AM


Asset      Size  Chunks  Chunk Names
/css/app.css 179 KiB  /js/app  [emitted]  /js/app
/js/app.js  2.26 MiB  /js/app  [emitted]  /js/app
```

Kemudian ketik command berikut:

php artisan serve


```
C:\Users\ASUS\Pemrograman-Framework\minggu13\laravelreactcrud-dina>php artisan serve
Laravel development server started: http://127.0.0.1:8000
[Wed May 26 07:22:38 2021] 127.0.0.1:56041 [200]: /css/app.css
[Wed May 26 07:22:38 2021] 127.0.0.1:56042 [200]: /js/app.js
[Wed May 26 07:22:40 2021] 127.0.0.1:56048 [200]: /favicon.ico
[Wed May 26 07:22:52 2021] 127.0.0.1:56049 [200]: /favicon.ico
[Wed May 26 07:23:11 2021] 127.0.0.1:56058 [200]: /favicon.ico
[Wed May 26 07:23:13 2021] 127.0.0.1:56063 [200]: /favicon.ico
[Wed May 26 07:23:15 2021] 127.0.0.1:56068 [200]: /favicon.ico
[Wed May 26 07:23:16 2021] 127.0.0.1:56073 [200]: /favicon.ico
[Wed May 26 07:23:27 2021] 127.0.0.1:56082 [200]: /favicon.ico
```

Ketikkan URL Halaman Index **localhost:8000** maka project akan running dan hasilnya:




23


Tampilan untuk melakukan aksi Create New Article




Tampilan aksi setelah melakukan Create New Article




Tampilan untuk melakukan aksi Edit




Tampilan untuk melihat aksi Detail



Tampilan aksi setelah melakukan Edit



Tampilan aksi setelah melakukan Delete



Link Github:

<https://github.com/dinariskyas/PemrogramanFramework2021/tree/master/minggu13>

Link Youtube :

<https://youtu.be/FTsx19ky9og>