

“A Wait-free Queue as Fast as Fetch-and-Add”

Chaoran Yang, John Mellor-Crummey

Loris Lucido

17 mars 2017

Blocking queue → unexpected delays from the Operating System can block every threads.

Progress Guarantee

An operation is guaranteed to end in a finite number of steps for. . .

- | | |
|---------------------------|-------------------------------------|
| • <i>Obstruction-free</i> | <i>1 thread only (in isolation)</i> |
| • <i>Lock-free</i> | <i>at least 2 threads</i> |
| • <i>Wait-free</i> | <i>any number of threads</i> |

Fetch-and-Add

FAA(x, v) returns the value of x and increments it by v

Compare-and-Swap

CAS(x, t, v) replaces x by v if x equals t

Can an **obstruction-free/lock-free** queue using **fetch-and-add** can be transformed to a **wait-free** queue using the **fast-path-slow-path** methodology ?

An obstruction-free queue using an infinite array.


```
⊤: invalid cell
⊥: empty cell
enqueue(x: var) {
    do t := FAA(&Tail, 1);
    while (!CAS(&Queue[t], ⊥,
               x));
}
```

```
dequeue(x: var) {
    do h := FAA(&Head, 1);
    while (CAS(&Queue[h], ⊥, ⊤) and
          Tail > h);
    return (Queue[h] == ⊤ ? EMPTY :
           Queue[h]);
}
```

An obstruction-free queue using an infinite array.

```
T: invalid cell
⊥: empty cell
enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
```

```
dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
```




An obstruction-free queue using an infinite array.

```
T: invalid cell
⊥: empty cell

enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
```

```
dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
```




An obstruction-free queue using an infinite array.

```
T: invalid cell
⊥: empty cell

enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
```


```
dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
```



An obstruction-free queue using an infinite array.

```
T: invalid cell
⊥: empty cell
enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
```


```
dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
```



An obstruction-free queue using an infinite array.

```
T: invalid cell
⊥: empty cell
enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
```

```
dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
```




An obstruction-free queue using an infinite array.

```

T: invalid cell
⊥: empty cell
enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
    
```

```

dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
    
```




An obstruction-free queue using an infinite array.

```
T: invalid cell
⊥: empty cell

enqueue(x: var) {
  do t := FAA(&Tail, 1);
  while (!CAS(&Queue[t], ⊥,
             x));
}
```


```
dequeue(x: var) {
  do h := FAA(&Head, 1);
  while (CAS(&Queue[h], ⊥, T) and
         Tail > h);
  return (Queue[h] == T ? EMPTY :
         Queue[h]);
}
```




<pre> T: invalid cell ⊥: empty cell enqueue(x: var) { do t := FAA(&Tail, 1); while (!CAS(&Queue[t], ⊥, x)); } </pre>	<pre> dequeue(x: var) { do h := FAA(&Head, 1); while (CAS(&Queue[h], ⊥, T) and Tail > h); return (Queue[h] == T ? EMPTY : Queue[h]); } </pre>
-----------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Transform lock-free/obstruction-free queue into wait-free queue





Some lock-free/blocking objects are *practically* wait-free.

- 99.97% enqueue done in one try on fast-path
- 95.95% dequeue done in one try on fast-path

Low probability of the worst-case scenario (slow-path)

- First wait-free queue with performance as good as Lock-free queue
- Design complexity increased for wait-free queue

Thanks for your attention !



Dan ALISTARH, Keren CENSOR-HILLEL et Nir SHAVIT. “Are Lock-Free Concurrent Algorithms Practically Wait-Free?” In : *J. ACM* 63.4 (sept. 2016), 31 :1–31 :20. ISSN : 0004-5411. DOI : 10.1145/2903136.



Tudor DAVID et Rachid GUERRAOU. “Concurrent Search Data Structures Can Be Blocking and Practically Wait-Free”. In : *Proceedings of the 28th ACM Symposium on Parallelism in Algorithms and Architectures*. SPAA '16. New York, NY, USA : ACM, 2016, p. 337–348. ISBN : 978-1-4503-4210-0. DOI : 10.1145/2935764.2935774.



Chaoran YANG et John MELLOR-CRUMMEY. “A Wait-free Queue As Fast As Fetch-and-add”. In : *SIGPLAN Not.* 51.8 (fév. 2016), 16 :1–16 :13. ISSN : 0362-1340. DOI : 10.1145/3016078.2851168.



Adam MORRISON et Yehuda AFEK. “Fast Concurrent Queues for x86 Processors”. In : *SIGPLAN Not.* 48.8 (fév. 2013), p. 103–112. ISSN : 0362-1340. DOI : 10.1145/2517327.2442527.



Panagiota FATOUROU et Nikolaos D. KALLIMANIS. “Revisiting the Combining Synchronization Technique”. In : *SIGPLAN Not.* 47.8 (fév. 2012), p. 257–266. ISSN : 0362-1340. DOI : 10.1145/2370036.2145849.



Alex KOGAN et Erez PETRANK. “A Methodology for Creating Fast Wait-free Data Structures”. In : *SIGPLAN Not.* 47.8 (fév. 2012), p. 141–150. ISSN : 0362-1340. DOI : 10.1145/2370036.2145835.



Maged M. MICHAEL et Michael L. SCOTT. “Simple, Fast, and Practical Non-Blocking and Blocking Concurrent Queue Algorithms”. In : *Proc. 15th ACM Symp. on Principles of Distributed Computing*. 1996, p. 267–275.