Careers | Investors

Enter search term

Company Products Markets Sales Support Vision Campus News / Press

Product Highlights Cameras Accessories Software Embedded Vision Portfolio

Products Cameras Area Scan Cameras Basler ace

Camera Quick Finder

acA780-75gc

ace Series



Find Product







The Basler acA780-75gc GigE camera with the Sony ICX415 CCD sensor delivers 75 frames per second at CCIR resolution.

Quantity: 1 Add to Request Cart

Specifications	Features	Dimensions	Downloads	Software	Accessories	
Resolution (H x V pixels)			780 px x 580 px			
Pixel Size horizontal/vertical			8.3 µm x 8.3 µm			
Frame Rate			75 fps			
Mono/Color			Color			
Interface			GigE			
Video Output Format			Mono 8, Bayer BG 8, Bayer BG 12, Bayer BG 12 Packed, YUV 4:2:2 Packed, YUV 4:2:2 (YUYV) Packed			
Pixel Bit Depth			12 bits			
Exposure Control			programmable via the camera APIexternal trigger signal			
Synchronization			external triggerfree-runEthernet connection			
Housing			box			
Quantum Efficiency (typical)			41,29 % (at 545 nm)			
Dark Noise (typical)			19,4 e ⁻			
Saturation Capacity (typical)			19 ke			
Dynamic Range (typical)			59,8 dB			
Signal to Noise Ratio			42,8 dB			
Housing Size (L x W x H) in mm			42.0 x 29.0 x 29.0			
Housing Temperature			0 °C - 50 °C			
Lens Mount			■ C-mount ■ CS-mount			
Digital Input			1	1		
Digital Output			1			
Power Requirements			PoE or 12 VDC			

The new ace models:



More ace videos

Further Information

ace USB 3.0 models from VGA to 14 MP ace CMOSIS – now also with USB 3.0 Basler ace 10 and 14 MP models ace models with new CMOS sensors

News



2016-11-09
The Right Solution for Many
Applications: Benefits of a
Broad CMOS Portfolio
more



2016-10-26 pylon Camera Software Suite and Basler Cameras in Robotics Applications more



2016-10-26
Basler to Make the First
Appearance at China
International Medical
Equipment Fair 2016

All news for these topics

We'd Be Glad to Help You

Sales Inquiry Basler Support

Power Consumption (typical)	3.3 W			
Power Consumption PoE	3.6 W			
Weight (typical)	90 g			
Conformity	 CE RoHS GenICam GigE Vision IP30 UL FCC IEEE 802.3af (PoE) 			
Sensor Vendor	Sony			
Sensor	ICX415			
Shutter	global shutter			
Max. Image Circle	1/2 inch			
Sensor Type	CCD			
Sensor Size (mm)	6.49 mm x 4.83 mm			
Order Number	105982			

F Like

≫ Tweet







eNewsletter

Regular updates on events and product innovations:

Basler on the social networks

Keep in touch with us via the social networks:

Subscribe

© 2016 Basler AG Glossary Sitemap Legal Info Privacy Statement Legal Notice Terms and Conditions Contact