

List

- A list is a record of short pieces of related information or used to display the data or any information on web pages in the ordered or unordered form.
- For instance, to purchase the items, we need to prepare a list that can either be ordered or unordered list which helps us to organize the data & easy to find the item.

❖ Types of lists

HTML Lists are used to specify lists of information. All lists may contain one or more list elements. There are three different types of HTML lists:

- **Ordered List or Numbered List (ol)**
- **Unordered List or Bulleted List (ul)**
- **Description List or Definition List (dl)**

❖ HTML Ordered List

HTML Ordered List or Numbered List displays elements in numbered format. The HTML ol tag is used for ordered list.

We can use ordered list to represent items either in numerical order format or alphabetical order format, or any format where an order is emphasized.

There can be different types of numbered list:

- Numeric Number (1, 2, 3)
- Capital Roman Number (I II III)
- Small Roman Number (i ii iii)

- Capital Alphabet (A B C)
- Small Alphabet (a b c)

To represent different ordered lists, there are 5 types of attributes in tag.

Type	Description
Type "1"	This is the default type. In this type, the list items are numbered with numbers.
Type "I"	In this type, the list items are numbered with upper case roman numbers.
Type "i"	In this type, the list items are numbered with lower case roman numbers.
Type "A"	In this type, the list items are numbered with upper case letters.
Type "a"	In this type, the list items are numbered with lower case letters.

Syntax:

```
<ol>
  <li>Item1</li>
  <li>Item2</li>
  <li>Item3</li>
</ol>
```

Attributes:

- **compact:** It defines the list should be compacted (compact attribute is not supported in HTML5. Use CSS instead.).


➤ **reversed:** It defines that the order will be descending.

✚ This is a Boolean attribute of HTML tag, and it is new in HTML5 version. If you use the reversed attribute with tag then it will numbered the list in descending order (7, 6, 5, 4.....1).

Example:

```
<ol reversed>
<li>HTML</li>
<li>Java</li>
<li>JavaScript</li>
<li>SQL</li>
</ol>
```

Output:



The reversed attribute

4. HTML
3. Java
2. JavaScript
1. SQL



➤ **start:** It defines from which number or alphabet the order will start.

The start attribute is used with ol tag to specify from where to start the list items.

<ol type="1" start="5"> : It will show numeric values starting with "5".

<ol type="A" start="5"> : It will show capital alphabets starting with "E".

<ol type="a" start="5"> : It will show lower case alphabets starting with "e".

<ol type="I" start="5"> : It will show Roman upper case value starting with "V".

<ol type="i" start="5"> : It will show Roman lower case value starting with "v".

Example:

```
<ol type="i" start="5">  
  <li>HTML</li>  
  <li>Java</li>  
  <li>JavaScript</li>  
  <li>SQL</li>  
</ol>
```

- **type:** It defines which type(1, A, a, I, and i) of the order you want in your list of numeric, alphabetic, or roman numbers.

Example:

```
<ol>  
  <li>Aries</li>  
  <li>Bingo</li>  
  <li>Leo</li>  
  <li>Oracle</li>  
</ol>
```

Output:

1. Aries
2. Bingo
3. Leo
4. Oracle

❖ The HTML Unordered List

An unordered list starts with the “ul” tag. Each list item starts with the “li” tag. The list items are marked with bullets i.e small black circles by default.

HTML Unordered List or Bulleted List displays elements in bulleted format . We can use unordered list where we do not need to display items in any particular order. The HTML ul tag is used for the unordered list. There can be 4 types of bulleted list:

- disc
- circle
- square
- none

To represent different ordered lists, there are 4 types of attributes in tag.

Type	Description
Type "disc"	This is the default style. In this style, the list items are marked with bullets.
Type "circle"	In this style, the list items are marked with circles.
Type "square"	In this style, the list items are marked with squares.
Type "none"	In this style, the list items are not marked .

Syntax:

```
<ul> list of items </ul>
```

Attribute: This tag contains two attributes which are listed below:

- **compact:** It will render the list smaller.
- **type:** It specifies which kind of marker is used in the list.

Note: The attributes are not supported by HTML5.

Example:

```
<ul>
<li>Aries</li>
<li>Bingo</li>
<li>Leo</li>
<li>Oracle</li>
</ul>
```

Output:

- Aries
- Bingo
- Leo
- Oracle

❖ HTML Description List

HTML Description list is also a list style which is supported by HTML and XHTML. It is also known as definition list where entries are listed like a dictionary or encyclopedia.

The definition list is very appropriate when you want to present glossary, list of terms or other name-value list.

The HTML definition list contains following three tags:

- 1) **<dl> tag** defines the start of the list.

- 2) **<dt>** tag defines a term.
- 3) **<dd>** tag defines the term definition (description).

Syntax:

```
<dl> Contents... </dl>
```

Example:

```
<dl>
<dt>Aries</dt>
<dd>-One of the 12 horoscope sign.</dd>
<dt>Bingo</dt>
<dd>-One of my evening snacks</dd>
<dt>Leo</dt>
<dd>-It is also an one of the 12 horoscope sign.</dd>
<dt>Oracle</dt>
<dd>-It is a multinational technology corporation.</dd>
</dl>
```

❖ HTML Nested List

A list within another list is termed as nested list. If you want a bullet list inside a numbered list then such type of list will called as nested list.

Example:

```
<!DOCTYPE html>
<html>
<head>
  <title>Nested list</title>
</head>
<body>
  <p>List of Indian States with thier capital</p>
```

```
<ol>
  <li>Delhi
    <ul>
      <li>NewDelhi</li>
    </ul>
  </li>
  <li>Haryana
    <ul>
      <li>Chandigarh</li>
    </ul>
  </li>
  <li>Gujarat
    <ul>
      <li>Gandhinagar</li>
    </ul>
  </li>
  <li>Rajasthan  <ul>
    <li>Jaipur</li>
  </ul>
  </li>
  <li>Maharashtra
    <ul>
      <li>Mumbai</li>
    </ul>
  </li>
  <li>Uttarpradesh
    <ul>
      <li>Lucknow</li> </ul>
  </li>
```

```
</ol>  
</body>  
</html>
```

Output:

