

1) Generic :

using system;

using system, Collections, Generic;

class program

{

static void main()

{

List<int> num = new List<int> ();

~~num~~ num.Add(10);

num.Add(20);

num.Add(30);

for each (int number in num)

{

console.WriteLine(num);

}

Dictionary<int, string> student = new Dictionary<int, string> ();

student.Add(101, "John");

student.Add(102, "David");

student.Add(103, "Mary");

for each (~~int~~ ^{item} int, string in student)

{ console.WriteLine(item.key + ":" + item.value);

}


```
HashSet<int> set = new HashSet<int>();
```

```
set.Add(10);
```

```
set.Add(20);
```

```
set.Add(30);
```

```
set.Add(10);
```

```
for each (int item in set)
```

```
{  
    console.WriteLine(item);  
}
```

```
}  
Stack<string> s1 = new Stack<string>();
```

```
s1.Push("A");
```

```
s1.Push("B");
```

```
s1.Push("C");
```

```
console.WriteLine("Removed: " + s1.Pop());
```

```
}
```

```
Queue<string> q1 = new Queue<string>();
```

```
q1.Enqueue("A");
```

```
q1.Enqueue("B");
```

```
q1.Enqueue("C");
```

```
console.WriteLine("Removed: " + q1.Dequeue());
```

```
}
```

```
LinkedList<int> list = new LinkedList<int>();
```

```
list.AddLast(10);
```



```
list.AddLast(20);
```

```
list.AddLast(30);
```

```
for each (int item in list)
```

```
{
```

```
    console.WriteLine(item);
```

```
}
```

```
sortedset<int> numbers = new sortedset<int>()
```

```
{
```

```
    50, 10, 30, 20
```

```
};
```

```
for each (int item in numbers)
```

```
{
```

```
    console.WriteLine(item);
```

```
}
```

```
}
```

```
}
```

non-generic

```
using system;
```

```
using system.collections;
```

```
class Program
```

```
{
```

```
    static void main()
```



```
{  
ArrayList arr arrList = new ArrayList();
```

```
arrList.Add(1);
```

```
arrList.Add("Hello");
```

```
for each (object item in arr)
```

```
{
```

```
    console.WriteLine(item);
```

```
}
```

```
}
```

```
Hashtable ht = new Hashtable();
```

```
ht.Add(1, 1000)
```

```
ht.Add(2, 2000)
```

```
for each (object item in ht)
```

```
{
```

```
    console.WriteLine(ht);
```

```
}
```

```
}
```

```
}
```

2)

using dictionary

using system;

using system, collection, generic;

class program

{

console, write ("Enter a sentence : ");

string sentence = console, ReadLine ();

string [] words = sentence, split (' ');

Dictionary <string, int> wordCount = new Dictionary
<string, int> ();

for each (string word in words)

{
if (word count, contains key (word))

word count [word] ++;

else.

word count [word] = 1;

}

console, write Line ("word :");

for each (string item in word count)

{

console.WriteLine (item.Key + ":" + item.Value)

}

}

}

without using dictionary

using system;

class Program

{

static void main ()

{

console.WriteLine ("Enter a sentence:");

string sentence = console.ReadLine();

string word = sentence.Split(' ');

console.WriteLine ("word:");

for (int i = 0; i < word.Length; i++)

int count = 1;

bool alreadyCount = true;

}

}

is (already count)

continue;

for (int k=i+1; k < word.length; k++).

{

if (word[i] == words[k])

count++;

}

console.WriteLine (word[i] + ":" + count);

}

}

}