



DineshTrade

Operations & Deployment Cheatsheet

EC2 Mumbai · 3.111.255.172 · dineshtrade.online · May 2026

Private & Confidential · Dinesh Wadhwani · dinesh.k.wadhwani@gmail.com

Quick Reference

Server IP	3.111.255.172
Domain	https://dineshtrade.online
SSH User	ubuntu
PEM Key	~/Downloads/dineshtrade-server.pem
App Folder	~/dineshtrade
Env File	~/dineshtrade/.env.local
Instance ID	i-0261e0d98f83e1458
Region	Mumbai — ap-south-1

01

Connect to Server

```
ssh -i ~/Downloads/dineshtrade-server.pem ubuntu@3.111.255.172

# Type "yes" if asked about fingerprint (first time only)
# You will see: ubuntu@ip-172-31-46-156:~$

# To disconnect from server:
exit
```

SHORTCUT: Add to ~/.zshrc on Mac: alias dineshtrade="ssh -i ~/Downloads/dineshtrade-server.pem ubuntu@3.111.255.172" Then just type: dineshtrade

02

Edit Environment Variables (.env.local)

The `.env.local` file lives on the server permanently. It is NEVER overwritten by deployments. This is where all your API keys and secrets live.

Open and edit the file:

```
# SSH into server first, then:

cd ~/dineshtrade
nano .env.local

# Make your changes inside nano

# Save: Ctrl+X → Y → Enter

# ALWAYS restart after changing env vars:

pm2 restart dineshtrade
```

Full .env.local contents reference:

[illegible]

NEVER commit `.env.local` to GitHub. It is in `.gitignore` — verify before every push. If API keys are ever accidentally pushed, rotate them immediately at console.anthropic.com and developers.kite.trade.

View current values (without editing):

```
cat ~/dineshtrade/.env.local
```

03 Deploy Latest Code

Step 1 — Push from Mac (GitHub Desktop or terminal):

```
# In GitHub Desktop: commit changes → Push origin

# OR via VS Code terminal:
cd ~/Downloads/dineshtrade
git add .
git commit -m "describe your change"
git push
```

Step 2 — Deploy on server:

```
cd ~/dineshtrade
git pull
npm install
npm run build
pm2 restart dineshtrade

# Done! Live at https://dineshtrade.online
```

If only changing existing code (no new packages): skip "npm install" git pull → npm run build → pm2 restart dineshtrade

04 PM2 — App Management

```
# Check if app is running
pm2 status

# View live logs (Ctrl+C to exit)
pm2 logs dineshtrade

# Restart app
pm2 restart dineshtrade

# Stop app
pm2 stop dineshtrade

# Start app (if stopped)
pm2 start npm --name "dineshtrade" -- start
pm2 save

# Live CPU/memory dashboard
pm2 monit
```

05 Nginx — Web Server

```
# Check status
```

```
sudo systemctl status nginx

# Restart
sudo systemctl restart nginx

# Test config syntax before restarting
sudo nginx -t

# View error logs
sudo tail -f /var/log/nginx/error.log
```

06 Server Health Checks

```
# Disk space (keep under 80%)
df -h

# Memory
free -h

# Reboot server
sudo reboot

# Wait 30 seconds then reconnect via SSH

# Install better process monitor
sudo apt install -y htop && htop
```

07 SSL Certificate

```
# Check expiry date
sudo certbot certificates

# Test auto-renewal
sudo certbot renew --dry-run

# Current cert expires: 2026-08-16
# Renews automatically every 90 days – no action needed
```

08 Lost PEM File — How to Recover Access

AWS does NOT let you re-download the original .pem key. If lost, use one of these two methods to regain access.

Method 1 — AWS Session Manager (Easiest — no PEM needed)

1. AWS Console → Systems Manager → Session Manager
2. Click "Start session" → select your EC2 instance

3. Click "Start session" — browser terminal opens without any key
4. Generate a new key pair on your Mac:

```
# On your Mac terminal:
ssh-keygen -t rsa -b 4096 -f ~/Downloads/dineshtrade-new
# This creates dineshtrade-new (private) and dineshtrade-new.pub (public)
# Copy the contents of dineshtrade-new.pub
cat ~/Downloads/dineshtrade-new.pub
```

5. In the Session Manager browser terminal, paste the public key:

```
# In Session Manager terminal on server:
echo "paste-your-public-key-here" >> ~/.ssh/authorized_keys
chmod 600 ~/.ssh/authorized_keys
```

6. Now SSH in normally using the new private key:

```
ssh -i ~/Downloads/dineshtrade-new ubuntu@3.111.255.172
```

Method 2 — Stop Instance + User Data Script

1. AWS Console → EC2 → Instances → select instance
2. Instance State → Stop (wait to stop fully)
3. Actions → Instance Settings → Edit User Data
4. Paste this (replace with your new public key):

```
#!/bin/bash
echo "ssh-rsa YOUR_NEW_PUBLIC_KEY ubuntu@dineshtrade" \
>> /home/ubuntu/.ssh/authorized_keys
```

5. Start the instance → SSH in with new key

PREVENTION — Back up dineshtrade-server.pem to: • iCloud Drive / Google Drive • Email to yourself as attachment • USB drive stored separately Recovery takes 20-40 mins. Prevention takes 2 minutes.

App runs 24/7 automatically. No server commands needed on a normal trading day.

Time	Action	Where
Before 9:15 AM	Open dineshtrade.online	Browser / Phone
Before 9:15 AM	Login with ddmmyyyyhh password	Login screen
Before 9:15 AM	Settings → paste Zerodha token → Connect	Settings page
9:00–9:15 AM	Dashboard — market brief, GIFT Nifty, outlook	Dashboard
9:15 AM	Trading Engine → Refresh & Scan for signals	Engine page
9:15–3:30 PM	Execute signals manually via Kite app	Zerodha Kite
3:30 PM	Check Today's Trades for P&L summary	Trades page
Midnight	Session auto-expires. Token cleared automatically.	Automatic

Site not loading

```
pm2 status # is app running?
pm2 restart dineshtrade # restart if needed
sudo systemctl restart nginx # restart nginx
```

App crashed / errors

```
pm2 logs dineshtrade --lines 50 # view last 50 lines
# Fix code locally → push → deploy
```

Cannot SSH — your home IP changed

```
# AWS Console → EC2 → Security Groups → dineshtrade-sg
# Edit inbound rules → SSH rule → update Source to new IP
# Find your current IP: curl ifconfig.me
```

Changes not showing after deploy

```
pm2 logs dineshtrade # check for build errors
# Make sure you ran: npm run build && pm2 restart
```

```
# Hard refresh browser: Cmd+Shift+R
```

SSL expired or not working

```
sudo certbot renew # manual renew  
sudo systemctl restart nginx # apply new cert
```