

# Newton's method for FastICA algorithm

Tomas Zeman\*

May 2000

## Abstract

Here we present in more details the Newton's method modified for performing ICA - so called FastICA algorithm introduced by Aapo Hyvarinen in [1, 2, 3, 4], overview of the methods in [5]. It is a batch algorithm which optimizes some nonlinear function used as a measure of statistical independence. Commonly used are e.g. cummulants (but these are sensitive to outliers), approximation of negentropy (tanh, pow3) or sigmoidal function in infomax principle (Bell & Sejnowski [6, 7]). The optimization by means of Newton's method is very effective and a slight modification makes the approach more robust.

## FastICA algorithm derivation

Maxima of approximation of negentropy are reached at certain optima of  $E\{G(\mathbf{w}^T \mathbf{x})\}$ . According to Kuhn-Tucker conditions, the optima of  $E\{G(\mathbf{w}^T \mathbf{x})\}$  under the constraint  $\|\mathbf{w}\| = 1$  are obtained at points where

$$E\{\mathbf{x}g(\mathbf{w}^T \mathbf{x})\} - \beta \mathbf{w} = 0, \quad (1)$$

where  $g = G'$  and  $\beta = E\{\mathbf{w}_{opt}^T \mathbf{x}g(\mathbf{w}_{opt}^T \mathbf{x})\}$ .

We will use the Newton's method for iteration, i.e.

$$\mathbf{w}^+ = \mathbf{w} - (\mathbf{J}(\mathbf{w}))^{-1} f(\mathbf{w}),$$

where  $\mathbf{J}(\mathbf{w})$  is the Jacobian of the eq. (1). Now we derive the Jacobian:

$$\mathbf{J}(\mathbf{w}) = \frac{\partial}{\partial \mathbf{w}} [E\{\mathbf{x}g(\mathbf{w}^T \mathbf{x})\} - \beta \mathbf{w}] = E\{\mathbf{x}g'(\mathbf{w}^T \mathbf{x})\mathbf{x}^T\} - \beta \mathbf{I} = E\{\mathbf{x}\mathbf{x}^T g'(\mathbf{w}^T \mathbf{x})\} - \beta \mathbf{I}$$

Since the data is whitened,  $E\{\mathbf{x}\mathbf{x}\}^T = \mathbf{I}$ . We make some approximation  $E\{\mathbf{x}\mathbf{x}^T g'(\mathbf{w}^T \mathbf{x})\} \approx E\{\mathbf{x}\mathbf{x}^T\} E\{g'(\mathbf{w}^T \mathbf{x})\} = E\{g'(\mathbf{w}^T \mathbf{x})\}$ . Then the Jacobian has final form:

$$\mathbf{J}(\mathbf{w}) = E\{g'(\mathbf{w}^T \mathbf{x})\} \mathbf{I} - \beta \mathbf{I} \quad (2)$$

---

\*CTU FEE, Dept. of Circuit Theory, e-mail: xzeman@feld.cvut.cz

So the inversion of  $\mathbf{J}(\mathbf{w})$  is simple and iteration formula is as follows:

$$\mathbf{w}^+ = \mathbf{w} - (\mathbf{J}(\mathbf{w}))^{-1}f(\mathbf{w}) = \mathbf{w} - \frac{\mathbb{E}\{\mathbf{x}g(\mathbf{w}^T\mathbf{x})\} - \beta\mathbf{w}}{\mathbb{E}\{g'(\mathbf{w}^T\mathbf{x})\} - \beta} \quad (3)$$

Now let's multiply both sides by the denominator and we obtain:

$$\begin{aligned} \mathbf{w}^+(\beta - \mathbb{E}\{g'(\mathbf{w}^T\mathbf{x})\}) &= \mathbf{w}(\beta - \mathbb{E}\{g'(\mathbf{w}^T\mathbf{x})\}) + \mathbb{E}\{\mathbf{x}g(\mathbf{w}^T\mathbf{x})\} - \beta\mathbf{w} \\ &= \mathbb{E}\{\mathbf{x}g(\mathbf{w}^T\mathbf{x})\} - \mathbb{E}\{g'(\mathbf{w}^T\mathbf{x})\}\mathbf{w} \end{aligned}$$

Since the new update is normalized after every iteration, the final form of the FastICA algorithm is:

$$\begin{aligned} \mathbf{w}^+ &= \mathbb{E}\{\mathbf{x}g(\mathbf{w}^T\mathbf{x})\} - \mathbb{E}\{g'(\mathbf{w}^T\mathbf{x})\}\mathbf{w} \\ \mathbf{w}_{new} &= \frac{\mathbf{w}^+}{\|\mathbf{w}^+\|} \end{aligned} \quad (4)$$

Sometimes, however, the convergence of the Newton's method may be uncertain. So after slight modification we can make the above algorithm more robust by adding a step size in (3):

$$\begin{aligned} \mathbf{w}^+ &= \mathbf{w} - \mu \frac{\mathbb{E}\{\mathbf{x}g(\mathbf{w}^T\mathbf{x})\} - \beta\mathbf{w}}{\mathbb{E}\{g'(\mathbf{w}^T\mathbf{x})\} - \beta} \\ \mathbf{w}_{new} &= \frac{\mathbf{w}^+}{\|\mathbf{w}^+\|} \end{aligned} \quad (5)$$

thus obtaining the *stabilized fastICA algorithm*.

## References

- [1] A. Hyvärinen. A family of fixed-point algorithms for independent component analysis. *In Proc. IEEE Int. Conf. on Acoustics, Speech and Signal Processing (ICASSP'97), Munich, Germany, 1997.*
- [2] R. Vigario J. Karhunen, A. Hyvärinen, J. Hurri, and E. Oja. Applications of neural blind separation to image and signal processing. *In Proc. IEEE Int. Conf. on Acoustics, Speech and Signal Processing (ICASSP'97), Munich, Germany, pages 131–134, 1997.*
- [3] A. Hyvärinen and E. Oja. Independent component analysis by general non-linear hebbian-like learning rules. *Signal Processing*, 64(3):301–313, 1998.
- [4] A. Hyvärinen. Survey on independent component analysis. *Neural Computing Surveys*, 2:94–128, 1999.
- [5] E.Oja A.Hyvärinen. Independent component analysis: A tutorial, 1999.
- [6] Sejnowski T.J. Bell A.J. An information-maximization approach to blind separation and blind deconvolution. *Neural Computation*, 7:1129–1159, 1995.
- [7] Bell A.J. Information theory, ICA & Applications, 1996.