


iOS Foundations II

Day 4

- Homework Review
- Navigation Controller
- Segues
- 'Passing' objects through segues

NavigationControllers



- “A navigation controller manages a stack of view controllers to provide a drill-down interface for hierarchical content.”

NavigationControllers


- “The navigation controller’s primary responsibility is to respond to user actions by pushing new content view controllers onto the stack or popping content view controllers off of the stack”
- The first ViewController you push onto the stack becomes the rootViewController and is never popped off because then no view would be on screen
- Nav Controllers have a property to the topViewController and an array property for all its viewControllers currently on the stack.
- The Nav bar up top can be customized or hidden.

NavigationControllers

- Storyboards make navigation controllers extremely easy to install into your app. Here's all the methods you need to do it in code without the storyboard:
- `init(rootViewController:)` UINavigationController is initialized with a rootViewController.
- `pushViewController(animated:)` To add or 'push' a view controller onto the stack.
- `popViewController(animated:)` To remove or 'pop' a view controller from the stack.

Stack Data Structure

- “A stack is particular kind of abstract data type or collection in which the only operations on the collection is adding (push) or removal (pop).” - Wikipedia
- LIFO : Last-In-First-Out. The last item added is the first to be removed.



Demo

Segues

- Segues are provided by the storyboard to help you easily transition from one view controller to another.
- There are 2 primary segues that are used : Show and Present
- Show refers to pushing a view controller onto the navigation stack, it usually will slide in from the right or left.
- Present refers to modally presenting a view controller, it usually slides up from the bottom.
- You can create your own custom segue to customize the behavior to match your needs.

Segues

- 2 primary methods for dealing with segues in code:
 1. `performSegueWithIdentifier:`
 2. `prepareForSegue:sender:`

performSegueWithIdentifier

- Call this method in your View Controller to trigger a segue in code.
- If you your segue isn't hooked up to be triggered by an action in your interface, you will need to call this method to trigger the segue.

prepareForSegue:sender:

- This method is called on the source view controller of the segue, right before the segue is actually performed.
- The first parameter is the segue itself, which is an instance of the UIStoryboardSegue class.
- The most important property of a UIStoryboardSegue instance is the destinationViewController property, which gives you a reference to the view controller you are about to segue to.
- This is a great spot to pass information to the next screen.

Demo

Passing data to View Controllers

- There are many patterns we can use to pass data around our app:
 - Delegation
 - Notification Center
 - Singletons
- But for now, we can do something as simple as passing a reference directly to the new view controller.

Passing data to View Controllers

ListViewController




ListViewController creates an array of Person objects and sets its people property's value to that array

ListViewController



Self.people




ListViewController, as the datasource of the tableview, uses the self.people array as the backing array for the tableview

ListViewController

brad
elvis
santa
Russell
Sherman
Clem

Self.people




The User clicks on a cell, triggering our ShowPerson Segue. The PersonDetailViewController is initialized.

ListViewController

brad
elvis
santa
Russell
Sherman
Clem

Self.people



PersonDetailViewController



Self.selectedPerson

Show Person



In Prepare for Segue, the ListViewController intercepts the segue and grabs a reference to the destination view controller, which is the PersonDetailViewController.

```
override func prepareForSegue(segue: UIStoryboardSegue!, sender: AnyObject!) {  
    if segue.identifier == "ShowPerson" {  
        var personDetailViewController = segue.destinationViewController as  
        PersonDetailViewController  
        //now we can prepare this view controller to be displayed with what  
        ever data we need to pass to it.  
    }  
}
```

ListViewController sets PersonDetailViewController's selectedPerson property to reference the person that was clicked from the list.

ListViewController

PersonDetailViewController

brad
elvis
santa
Russell
Sherman
Clem

Show Person



Self.people

Self.selectedPerson



brad
santa
elvis

ListViewController sets PersonDetailViewController's selectedPerson property to reference the person that was clicked from the list.

```
if segue.identifier == "ShowPerson" {  
  
    var personDetailViewController = segue.destinationViewController as  
    PersonDetailViewController  
  
    //now we can prepare this view controller to be displayed with what  
    ever data we need to pass to it.  
  
    //grab the selected index path from our tableview  
    var selectedIndexPath = self.tableView.indexPathForSelectedRow()  
  
    //grab the selected person using the indexPath as the index in our  
    people array  
    var selectedPerson = self.people[selectedIndexPath.row]  
  
    //set destinationViewController's person property to reference the  
    selectedPerson  
    personDetailViewController.person = selectedPerson  
  
}
```

Now `PersonDetailViewController` can use its `selectedPerson` property to fill out his interface with that `Person`'s name properties. Any changes he makes to this `Person` object apply to the person object inside the original array!

`ListViewController`

brad
elvis
santa
Russell
Sherman
Clem

`Self.people`

`PersonDetailViewController`

elvis
presley

`Self.selectedPerson`

