



PRE-RELEASE - NOT FOR DISTRIBUTION

LED BULLET FLOOD, BEAM ADJUSTABLE

BULLET FLOOD SERIES

>=120 LM/W

DRAFT - PLACEHOLDER FAMILY NAME - REQUIRES DINO'S APPROVAL

WATTAGE	VOLTAGE	LIFESPAN	WARRANTY	CRI	CCT
15/20/25W	120-277V	50,000 h	5 years	>70	3000/4000/5000K

SELECTABLE POWER. SELECTABLE CCT. ADJUSTABLE BEAM.

A compact die-cast bullet flood for landscape, facade and sign lighting. Power, colour temperature and beam spread are all set in the field, so one fixture covers accent spots and wide floods. For custom solutions please contact our sales representative.

For custom solutions please contact our sales representative.

PHONE: 702.847.7680 WEB: www.ledconnection.com EMAIL: bids@ledconnection.com 915 E Dale Ave Ste 110 Henderson, NV 89044

LED BULLET FLOOD, BEAM ADJUSTABLE

BULLET FLOOD SERIES



LC-BFL

3 WATTAGES | 3 CCTS | 3 BEAMS | 5 YEARS WARRANTY

QUALITY DEFENDER

Die-cast aluminium housing, wet-location rated, 5-year warranty.

PRODUCT DESCRIPTION

The Bullet Flood Series is a compact die-cast aluminium bullet flood for landscape, facade and sign lighting. Power (15, 20 or 25W), colour temperature (3000, 4000 or 5000K) and beam spread (NEMA 4x4, 5x5 or 6x6) are all set in the field, so one fixture covers narrow accents and wide floods. It runs on 120-277VAC with a dusk-to-dawn photocell, mounts on a standard 1/2 in NPS knuckle, ground spike or wall plate, and is suitable for wet locations.

OVERVIEW

- Wattage options: 15W / 20W / 25W
- Input voltage: 120-277VAC
- Efficacy: >=120 lm/W
- Colour temperature: 3000K / 4000K / 5000K
- Colour rendering: Ra >70
- Rated life: >=50,000 h
- Warranty: 5 years
- Beam: 47-70 deg (NEMA 4x4) / 71-100 deg (NEMA 5x5) / 101-130 deg (NEMA 6x6)
- Mounting: 1/2" NPS knuckle (standard) / ground spike / wall mount plate
- Housing: Die-cast aluminium housing, PC lens

DIMENSIONS

WEIGHT	MOUNTING	DRAWING
approx. 0.6 kg / 1.3 lb	1/2 in NPS knuckle	to follow

ORDER LOGIC

Build a Bullet Flood Series SKU by selecting one option from each segment.

LC – BFL – 25 – BA – 3C – PC – KN – GB

[BRAND] [02] [03] [04] [05] [06] [07] [08]

02 SERIES	03 WATTAGE	04 BEAM	05 CCT	06 CONTROL	07 MOUNTING	08 FINISH
BFL Bullet Flood	**25** 15/20/25W selectable	**BA** 4x4/5x5/6x6 beam	**3C** 3/4/5K selectable	**PC** Photocell	**KN** 1/2" NPS knuckle **SP** Ground spike **WP** Wall plate	**GB** Grey brown (RAL 8019) **VG** Verde green

For custom solutions please contact our sales representative.

NOTE:

VALUES TAKEN FROM SUPPLIER DOCUMENTATION. AVAILABILITY VARIES BY CONFIGURATION.

ELECTRICAL DATA

SPECIFICATION	VALUE
Wattage options	15W / 20W / 25W
Input voltage	120-277VAC
Efficacy	>=120 lm/W
CCT	3000K / 4000K / 5000K
Colour rendering	Ra >70
Rated life	>=50,000 h
Warranty	5 years
Beam	47-70 deg (NEMA 4x4) / 71-100 deg (NEMA 5x5) / 101-130 deg (NEMA 6x6)
Mounting	1/2" NPS knuckle (standard) / ground spike / wall mount plate
Housing	Die-cast aluminium housing, PC lens
Finishes	Grey brown (RAL 8019) / Verde green (custom order)
Operating temperature	-40 F to +113 F
Controls	Button photocell (dusk to dawn)
Power Factor	>=0.9

LUMEN MAINTENANCE

Lumen maintenance data pending. Must be backed by an LM-80 report and projected per IES TM-21 before publication.