

Parksphere Mobile App

iOS Local Build Guide (Mac Only)

Phase 1: Environment Setup (One-Time)

Before building, your Mac must be configured to handle modern Ruby and CocoaPods.

1. Install Modern Ruby via Homebrew

The default Mac Ruby is too old. Use Homebrew to install Ruby 3.x:

```
brew install ruby
```

Add Ruby to your Path (for Intel Macs):

```
echo 'export PATH="/usr/local/opt/ruby/bin:$PATH"' >> ~/.zshrc
echo 'export PATH="/usr/local/lib/ruby/gems/4.0.0/bin:$PATH"' >>
~/.zshrc
source ~/.zshrc
```

Verify with `ruby -v`. It should be 3.x+.

2. Install & Link CocoaPods

Install CocoaPods and ensure the symlinks are correct:

```
brew install cocoapods  
brew link --overwrite cocoapods
```

Verify with `pod --version`.

Phase 2: Project Build Workflow

Follow these steps whenever you want to create a fresh build on your phone.

1. Clean & Prebuild

In your project root (ensure no spaces in folder names, e.g., `Software_Development`):

```
rm -rf ios  
npx expo prebuild
```

2. Native Installation

```
cd ios  
pod install  
cd ..
```

3. Xcode Configuration (Signing)

- Run `open ios/*.xcworkspace`
- Go to **Signing & Capabilities**.
- Select your **Team** (Apple ID).

- **CRITICAL:** Click the "X" to remove **Push Notifications** and **Background Modes** (required for free accounts).

4. Deploy to iPhone

Plug in your iPhone, unlock it, and run:

```
npx expo run:ios --configuration Release --device
```

The 7-Day Expiration

Because you are using a Free Apple Developer account, the app will expire every 7 days. To fix this, simply plug your phone in and repeat **Step 4**.

Post-Installation

On your iPhone: Go to **Settings > General > VPN & Device Management** and "Trust" your Apple ID. If on iOS 16+, also enable **Developer Mode** in Privacy settings.