

SQL – Views

Carla Teixeira Lopes

Bases de Dados

Mestrado Integrado em Engenharia Informática e Computação, FEUP

Based on Jennifer Widom slides

Agenda

~~Defining and Using Views~~

~~Views Modifications Introduction~~

Views Modification Using Triggers

View CSaccept

Create View CSaccept As

Select sID, cName

From Apply

Where major = 'CS' and dec = 'Y';

Select *

From CSaccept



sID	cName
123	Stanford
123	Berkeley
345	Cornell
987	Stanford
987	Berkeley

Delete from CSaccept

Delete from CSaccept

Where sID = 123;



Error: SQLite does not
allow to modify views

Create trigger CSacceptDelete

instead of delete on Csaccept

For each row

Begin

Delete from Apply

Where sID = Old.sID and cName = Old.cName and
major = 'CS' and dec = 'Y';

End;

sID	cName
123	Stanford
123	Berkeley
345	Cornell
987	Stanford
987	Berkeley

Delete from CSaccept

CSaccept

sID	cName
123	Stanford
123	Berkeley
345	Cornell
987	Stanford
987	Berkeley

Create trigger CSacceptDelete

instead of delete on CSaccept

For each row

Begin

Delete from Apply

Where sID = Old.sID and

cName = Old.cName and

major = 'CS' and dec = 'Y';

End;

Apply

sID	cName	major	dec
123	Stanford	CS	Y
123	Stanford	EE	N
123	Berkeley	CS	Y
123	Cornell	EE	Y
234	Berkeley	biology	N
345	MIT	bioengineering	Y
345	Cornell	bioengineering	N
345	Cornell	CS	Y
345	Cornell	EE	N
678	Stanford	history	Y
987	Stanford	CS	Y
987	Berkeley	CS	Y
876	Stanford	CS	Y
876	MIT	biology	Y
876	MIT	marine biology	N
765	Stanford	history	Y
765	Cornell	history	N

Delete from CSaccept

Delete from CSaccept

Where sID = 123;



sID	cName
345	Cornell
987	Stanford
987	Berkeley



Apply

<u>sID</u>	<u>cName</u>	<u>major</u>	<u>dec</u>
123	Stanford	EE	N
123	Cornell	EE	Y
234	Berkeley	biology	N
345	MIT	bioengineering	Y
345	Cornell	bioengineering	N
345	Cornell	CS	Y
345	Cornell	EE	N
678	Stanford	history	Y
987	Stanford	CS	Y

Update CSaccept

sID	cName
345	Cornell
987	Stanford
987	Berkeley



Change this acceptance to
Carnegie Melon

Update CSaccept

Set cName = 'CMU'

Where sID = 345;



Error: SQLite does not
allow to modify views

Update CSaccept

Create trigger CSacceptUpdate

instead of update of cName on Csaccept

For each row

Begin

Update Apply

Set cName = New.cName

Where sID = Old.sID and cName = Old.cName and

major = 'EE' and dec = 'N';

End;

Update CSaccept

CSaccept

sID	cName
345	Cornell
987	Stanford
987	Berkeley

Create trigger CSacceptUpdate
instead of update of cName on CSaccept
For each row
Begin
 Update Apply
 Set cName = New.cName
 Where sID = Old.sID and cName = Old.cName
 and major = 'EE' and dec = 'N';
End;

Apply

sID	cName	major	dec
123	Stanford	CS	Y
123	Stanford	EE	N
123	Berkeley	CS	Y
123	Cornell	EE	Y
234	Berkeley	biology	N
345	MIT	bioengineering	Y
345	Cornell	bioengineering	N
345	Cornell	CS	Y
345	Cornell	EE	N
678	Stanford	history	Y
987	Stanford	CS	Y
987	Berkeley	CS	Y
876	Stanford	CS	Y
876	MIT	biology	Y
876	MIT	marine biology	N
765	Stanford	history	Y
765	Cornell	history	N

Update CSaccept

Update CSaccept

Set cName = 'CMU'

Where sID = 345;

Nothing in the system is checking the correctness of the translation

CSaccept

sID	cName
345	Cornell
987	Stanford
987	Berkeley

Apply

<u>sID</u>	<u>cName</u>	<u>major</u>	<u>dec</u>
123	Stanford	EE	N
123	Cornell	EE	Y
234	Berkeley	biology	N
345	MIT	bioengineering	Y
345	Cornell	bioengineering	N
345	Cornell	CS	Y
345	CMU	EE	N
678	Stanford	history	Y
987	Stanford	CS	Y

Update CSaccept

Create trigger CSacceptUpdate

instead of update of cName on Csaccept

For each row

Begin

Update Apply

Set cName = New.cName

Where sID = Old.sID and cName = Old.cName and

major = 'CS' and dec = 'Y';

End;

View CSEE

Create View CSEE As

Select sID, cName, major

From Apply

Where major = 'CS' or major = 'EE';

Select *
From CSEE



sID	cName	major
123	Stanford	EE
123	Berkeley	EE
345	Cornell	CS
345	CMU	EE
987	Stanford	CS
987	Berkeley	CS
876	Stanford	CS
543	MIT	CS

Insert on CSEE

Insert into CSEE values (111, 'Berkeley', 'CS'); → Error: SQLite does not allow to modify views

Create trigger CSEEinsert

Instead of insert on CSEE

For each row

Begin

Insert into Apply values (New.sID, New.cName, New.major, null);

End;

Insert on CSEE

Insert into CSEE values
(111, 'Berkeley', 'CS');

CSEE

sID	cName	major
123	Stanford	EE
123	Berkeley	EE
345	Cornell	CS
345	CMU	EE
987	Stanford	CS
987	Berkeley	CS
876	Stanford	CS
543	MIT	CS
111	Berkeley	CS

Apply

<u>sID</u>	<u>cName</u>	<u>major</u>	<u>dec</u>
123	Stanford	EE	N
...
543	MIT	CS	N
111	Berkeley	CS	Null

Insert on CSEE

Insert into CSEE values
(222, 'Berkeley', 'biology');

CSEE

sID	cName	major
123	Stanford	EE
123	Berkeley	EE
345	Cornell	CS
345	CMU	EE
987	Stanford	CS
987	Berkeley	CS
876	Stanford	CS
543	MIT	CS
111	Berkeley	CS

Apply

<u>sID</u>	<u>cName</u>	<u>major</u>	<u>dec</u>
123	Stanford	EE	N
...
111	Berkeley	CS	Null
222	Berkeley	biology	Null

Don't want insertions
on a view that affect
the base tables and
not the view

Insert on CSEE

Drop trigger CSEEinsert;

Create trigger CSEEinsert

Instead of insert on CSEE

For each row

When New.major = 'CS' or New.major = 'EE'

Begin

 Insert into Apply values (New.sID, New.cName, New.major, null);

End;

Insert on CSEE

Insert into CSEE values
(333, 'Berkeley', 'biology');

CSEE

sID	cName	major
123	Stanford	EE
123	Berkeley	EE
345	Cornell	CS
345	CMU	EE
987	Stanford	CS
987	Berkeley	CS
876	Stanford	CS
543	MIT	CS
111	Berkeley	CS

Apply

<u>sID</u>	<u>cName</u>	<u>major</u>	<u>dec</u>
123	Stanford	EE	N
...
111	Berkeley	CS	Null
222	Berkeley	biology	Null

Insert on CSEE

Insert into CSEE values
(333, 'Berkeley', 'EE');

CSEE

sID	cName	major
123	Stanford	EE
123	Berkeley	EE
345	Cornell	CS
345	CMU	EE
987	Stanford	CS
987	Berkeley	CS
876	Stanford	CS
543	MIT	CS
111	Berkeley	CS
333	Berkeley	EE

Apply

<u>sID</u>	<u>cName</u>	<u>major</u>	<u>dec</u>
123	Stanford	EE	N
...
222	Berkeley	biology	Null
333	Berkeley	EE	Null

Kahoot time!

Any doubts?

Readings

Jeffrey Ullman, Jennifer Widom, A first course in
Database Systems 3rd Edition

Section 8.1 – Virtual Views

Section 8.2 – Modifying Views