

How to declare an imperative

Bibliography

“*How to declare an imperative*”, Philip Wadler. ACM Computing Surveys, 29(3):240–263, September 1997.

“Monads for functional programming”, Philip Wadler, 2001. PDF

Commands

Modeling commands

How can we express **imperative input/output** in a purely-functional language?

Let’s use an **embedded domain specific language**:

- a data type for *commands*
- *some constants* of this type (for primitive commands)
- *combinators* (for putting together complex commands from simpler ones)

A type for commands

Our initial type of commands is:

IO ()

For now: ignore the ()-parameter and think of this as an “opaque” type.

Print a character

Let us consider a function **putChar** of the following type.

putChar :: **Char** -> **IO** ()

For example,

putChar '?'

denotes a command that, *if it is ever performed*, prints a single question-mark character.

Combining two commands

We can build more complex commands from two simpler ones by combining them sequentially.

```
(>>) :: IO () -> IO () -> IO ()
```

For example,

```
putChar '?' >> putChar '!'
```

denotes a command that, *if it is ever performed*, prints a question-mark followed by an exclamation mark.

Doing nothing

It is useful to have a “null” command that doesn’t do anything.

```
done :: IO ()
```

Note that **done** doesn’t actually do nothing; it just denotes the command that, *if it is ever performed*, won’t do anything.

Compare *thinking* about doing nothing with *actually* doing nothing — they’re not the same thing!

Printing a string

We can build complex commands from simple ones.

Example: print a string, one character at a time.

```
putStr :: String -> IO ()
putStr []      = done
putStr (x:xs) = putChar x >> putStr xs
```

For example, `putStr "?!"` is equivalent to

```
putChar '?' >> (putChar '!' >> done)
```

Using higher-order functions

We could also express `putStr` using higher-order functions over lists.

```
putStr :: String -> IO ()
putStr = foldr (>>) done . map putChar
```

E.g.:

```

    putStr "?!"
= foldr (>>) done (map putChar ['?', '!'])
= foldr (>>) done [putChar '?', putChar '!']
= putChar '?' >> (putChar '!' >> done)

```

Main

How are commands ever performed?

Answer: the runtime system executes a “special” command named `main`.

```

-- file Hello.hs
main :: IO ()
main = putStr "Hello!"

```

Note that only `main` is executed even though there may be other values of type `IO ()` in our program.

Equational reasoning

Replacing equals by equals

In both Haskell and OCaml, the terms

```
(1+2)*(1+2)
```

and

```
let x = 1+2 in x*x
```

are equivalent (both evaluate to 9).

Equational reasoning lost

In OCaml `print_string : string -> ()` performs output as a *side-effect*.

We lose *referential transparency*, i.e. the ability to exchange identical sub-expressions.

```

print_string "ah"; print_string "ah"
(* prints "ahah" *)

let x = print_string "ah" in x; x end
(* prints a single "ah" *)

let f () = print_string "ah"
in f (); f () end
(* prints "ahah" *)

```

Equational reasoning regained

In Haskell (unlike OCaml), the terms

```
putStr "ah" >> putStr "ah"
```

and

```
let m = putStr "ah"
in m >> m
```

are also equivalent (both denote a command that prints “ahah”).

Commands with values

Return values

`IO ()` is the type of commands that *return no useful value*.

Recall that `()` is the *unit type* with a single inhabitant also written `()`.

More generally, `IO a` is the type of commands that *return a value of type a*.

```
IO Char      -- returns a single character
IO (Char,Char) -- ... a pair of characters
IO Int       -- ... a single integer
IO [Char]    -- ... a list of characters
```

Reading a character

A command for reading the next input character:

```
getChar :: IO Char
```

E.g., if the available input is "abc" then `getChar` will yield the value 'a' and the input remaining will be "bc".

Doing nothing and returning a value

The command

```
return :: a -> IO a
```

does nothing and but returns the given value.

E.g. performing

```
return 42 :: IO Int
```

yields the value 42 and leaves the input unchanged.

Combining commands with values

The operator `>>=` (pronounced “bind”) combines two commands and passes a value from the first to the second.

```
(>>=) :: IO a -> (a -> IO b) -> IO b
```

For example, performing the command

```
getChar >>= \x -> putChar (toUpper x)
```

when the input is "abc" produces the output "A" and the remaining input is "bc".

Bind in detail

If

```
m :: IO a
k :: a -> IO b
```

then

```
m >>= k
```

is a command that acts as follows:

1. perform command `m` yielding `x` of type `a`
2. perform command `k x` yielding `y` of type `b`
3. yield the final value `y`

Reading a line

A program to read input until a newline and yield the list of characters read.

```
getLine :: IO [Char]
getLine = getChar >>= \x ->
  if x == '\n' then
    return []
  else
    getLine >>= \xs ->
      return (x:xs)
```

Commands as special cases

The general combinators for commands are:

```
return :: a -> IO a
(>>=) :: IO a -> (a -> IO b) -> IO b
```

The command `done` is a special case of `return` and `>>` is a special case of `>>=`:

```

done :: IO ()
done = return ()

(>>) :: IO () -> IO () -> IO ()
m >> n = m >>= \_ -> n

```

An analogy with *let*

The operator `>>=` behaves similarly to `let` when the continuation is a lambda expression.

Compare two type rules for `let` and `>>=`:

$$\frac{\Gamma \vdash m :: a \quad \Gamma, x :: a \vdash n :: b}{\Gamma \vdash \text{let } x = m \text{ in } n :: b} \quad \frac{\Gamma \vdash m :: \text{IO } a \quad \Gamma, x :: a \vdash n :: \text{IO } b}{\Gamma \vdash m \gg= \lambda x \rightarrow n :: \text{IO } b}$$

“Do” notation

Echoing input to output

A program that echoes each input line in upper-case.

```

echo :: IO ()
echo = getLine >>= \line ->
  if line == "" then
    return ()
  else
    putStrLn (map toUpper line) >>
    echo

```

“Do” notation

Here’s the same program using “do” notation.

```

echo :: IO ()
echo = do {
  line <- getLine;
  if line == "" then
    return ()
  else do {
    putStrLn (map toUpper line);
    echo
  }
}

```

Translating “do” notation

Each line “`x <- e; ...`” becomes “`e >>= \x -> ...`”.

Each line “`e; ...`” becomes “`e >> ...`”.

Example

```
do { x1 <- e1;
     x2 <- e2;
     e3;
     x4 <- e4;
     e5;
     e6 }
```

is equivalent to

```
e1 >>= \x1 ->
e2 >>= \x2 ->
e3 >>
e4 >>= \x4 ->
e5 >>
e6
```

Monads

Monoids

A *monoid* is a pair (\star, u) of an *associative operator* \star with an *identity value* u that satisfy the following laws:

Left-identity $u \star x = x$

Right-identity $x \star u = x$

Associativity $(x \star y) \star z = x \star (y \star z)$

Examples

`(+)` and `0`

`(*)` and `1`

`(||)` and `False`

`(&&)` and `True`

`(++)` and `[]`

`(>>)` and `done`

Monads

A *monad* is a pair of functions (`>>=`, `return`) that satisfy the following laws:

Left-identity `return a >>= f = f a`

Right-identity `m >>= return = m`

Associativity `(m >>= f) >>= g = m >>= (\x -> f x >>= g)`

Monad laws in “do” notation

```
-- (1) Left identity
do { x' <- return x ; f x' } = do { f x }

-- (2) Right identity
do { x <- m ; return x } = do { m }
```

Monad laws in “do” notation

```
-- (3) Associativity
do { y <- do { x <- m ; f x }
    g y
}
=
do { x <- m ;
    do { y <- f x ; g y }
}
=
do { x <- m ;
    y <- f x ;
    g y
}
```

The monad type class

Monad operations in Haskell are overloaded in a *type class*.

```
-- in the Prelude
class Monad m where
    return :: a -> m a
    (>>=)  :: m a -> (a -> m b) -> m b

instance Monad IO where
    return = ... -- primitive ops
    (>>=) = ...

-- other Monad instances
```


The partiality monad

The Maybe type

```
data Maybe a = Nothing | Just a
```

A value of type `Maybe a` is either:

`Nothing` representing the absence of further information;

`Just x` with a further value `x :: a`

Examples

```
Just 42 :: Maybe Int
```

```
Nothing :: Maybe Int
```

```
Just "hello" :: Maybe String
```

```
Nothing      :: Maybe String
```

```
Just (42, "hello") :: Maybe (Int,String)
```

```
Nothing           :: Maybe (Int,String)
```

Representing failure

Partial functions can return a `Maybe` value:

- `Nothing` if the result is undefined;
- `Just r` when the result is `r`.

```
-- Example: lookup a key in key-value list
-- (from the Prelude)
lookup :: Eq a => a -> [(a,b)] -> Maybe b
lookup k ((x,v):assocs)
  | k == x    = Just v    -- key found
  | otherwise = lookup k assocs
lookup k []   = Nothing  -- key not found
```

Representing failure (2)

```
phonebook :: [(String, String)]
phonebook = [ ("Bob",   "01788 665242"),
              ("Fred",  "01624 556442"),
              ("Alice", "01889 985333"),
              ("Jane",  "01732 187565") ]
```

E.g.:

```
> lookup "Bob" phonebook
Just "01788 665242"
```

```
> lookup "Alice" phonebook
Just "01889 985333"
> lookup "Zoe" phonebook
Nothing
```

Combining lookups

Lookup up a name...

1. first in the phonebook
2. then in an email list

Return the pair of *phone*, *email* and fail if *either* lookup fails.

Combining lookups (2)

```
getPhoneEmail :: String -> Maybe (String,String)
getPhoneEmail name =
  case lookup name phonebook of
    Nothing -> Nothing
    Just phone -> case lookup name emails of
      Nothing -> Nothing
      Just email -> Just (phone,email)
```

This works but gets very verbose quickly!

Monads to the rescue

We can simplify this pattern because `Maybe` is a monad.

```
-- define in the Prelude
instance Monad Maybe where
  return x      = Just x
  Nothing >>= k = Nothing
  Just x  >>= k = k x
```

Specific types of the monad operations:

```
return :: a -> Maybe a
(>>=) :: Maybe a -> (a -> Maybe b) -> Maybe b
```

Re-writing the combined lookup

The code gets much shorter with `>>=` handling the failure cases.

```
getPhoneEmail :: String -> Maybe (String,String)
getPhoneEmail name =
```

```
lookup name phonebook >=> \phone ->
lookup name emails >=> \email ->
return (phone,email)
```

Re-writing the combined lookup

Gets even simpler by using “do” notation.

```
getPhoneEmail :: String -> Maybe (String,String)
getPhoneEmail name
  = do phone <- lookup name phonebook
      email <- lookup name emails
      return (phone,email)
```

The error monad

Representing errors

If we need represent computations that may result in *distinct errors* we can use an **Either** result value:

```
-- from the Prelude
data Either a b = Left a | Right b
```

We can use:

- **Left** to tag errors;
- **Right** to tag valid results.

Example

Write an integer division function that may fail because:

- the divisor is zero; *or*
- the result is not exact.

Example (cont.)

```
myDiv :: Int -> Int -> Either String Int
myDiv x y
  | y == 0          = Left "zero division"
  | x`mod`y /= 0    = Left "not exact"
  | otherwise       = Right (x`div`y)
```

```
> myDiv 42 2
Right 21
```

```
> myDiv 42 0
Left "zero division"
> myDiv 42 5
Left "not exact"
```

Monad instance for Either

As with `Maybe`, there is a monad instance in the Prelude for `Either`.

```
-- in the Prelude
instance Monad (Either e) where
  return x      = Right x
  Left e >>= k  = Left e
  Right x >>= k = k x
```

Idea: `Left` values behave similarly to *exceptions*.

Note that `Either e` is a monad but `Either` itself is *not* a monad (wrong kind).

Examples

```
> Right 41 >>= \x -> return (x+1)
Right 42

> Left "boom" >>= \x -> return (x+1)
Left "boom"

> Right 100 >>= \x -> Left "no way!"
Left "no way!"
```

Exercise: prove the monad laws for the `Either` instance.

The state monad

Representing stateful computations

Recall that we can view stateful computations as functions:

$$\text{state} \longrightarrow (\text{result}, \text{new state})$$

The state monad

```
--- from Control.Monad.State

newtype State s a = State (s -> (a, s))
    -- type for state computations

run :: State s a -> s -> (a, s)
run (State f) s = f s

instance Monad (State s) where
    return a = State (\s -> (a, s))
    m >>= k  = State (\s ->
        let (x, s') = run m s
        in run (k x) s')
```

NB: for something to be a monad it should also satisfy the three monad laws — these are *not* checked by the compiler!