Index

| A | Bellman's equation, 399 | Codex networks, 141 |
|---|---|---|
| | Bellman-Ford algorithm, 396–400, | data link control, 518 |
| ABM, See Asynchronous balanced mode | 404-410, 424, 481, 492 | flow control, 518 |
| ADCPP, 72, 97-103 AD. See Amplitude modulation | Binary exponential backoff, 286–87, 352 | routing, 378, 417, 476, 77 |
| ANSL See American National Standards | Binary synchronous communication, 87 | session identification, 113 =15 |
| Institute | Birth-death processes, 184, 215, 261 Bisynch, 87 | Coding. See Data compression. |
| AM, See Amplitude modulation | Bit pipes, 20-23, 38, 65, 86 | Encryption, Error detection, or Error correction |
| ARM, See Asynchronous response mode | intermittent synchronous, 38 | Collision resolution, 276–77 |
| ARPANET, 2, 4, 19-20 | synchronous, 38 | packet radio, 347-49 |
| ARQ. 84-86 | Bit stuffing, 88-90, 145, 320 | Collision resolution period, 291, 295-300 |
| flow control, 515 | Bits, 10 | Collision-free set, 345 |
| framing, 87 routing, 374–76, 404–6, 412 | Black box, 17 | Communication channels, 20, 38, 40–57 |
| ARQ. See Automatic repeat request | Blocking probability, 180, 185 Bottlewed, Ind., 526 | analog, 40 |
| ASCII code, 21, 31, 58, 86 | Bottleneck link, 526 Branch exchange heuristic, 444, 448 | bandpass, 47 52 digital, 40, 53-54 |
| ATM, See Asynchronous transfer mode | Bridge learning, 384 | voice-grade, 49–50, 52 |
| Abort capability for frames, 89 | Bridged local area networks, 382-87 | Concentrator location problem, 448 |
| Access rights, 31 | Bridges, 4, 29, 380 | Concentrators, 1 |
| Acks, 66, 500 | Broadband ISDN, 5, 11-12, 32, 55, | Congestion control, 27, 116-17 |
| end-to-end, 115-16 | 128 32 | in ATM, 138-39 See also Flow contro |
| Adaptive equalizers, 45, 49, 140 | Broadcasting, 369, 375–76, 433, 485 | Connected graph, 387, 394 |
| Addressing, 40, 111–14 in TCP, 124–25 | Buffer management, 496–98 | Connectionless service, 26 |
| Age field, 422, 425 | Buffer overflow, 496-99 Burke's theorem, 218, 255 | in ATM, 137–39 |
| Aggregation of queues, 254 | Burst detection, 60-61 | Connectivity, 445 Constrained MST problem, 447 |
| Airline reservation systems, 7, 9, 10 | Bursty sessions, 14-15 | Convergence sublayer in ATM, 136–39 |
| Allocate message, 500 | Bus systems, 271, 274, 331-33 | Convex set or function, 453, 486 |
| Aloha, 275-89, 352 | undirectional, 334-41 | Convolution, 43 |
| slotted, 277–87 | Busy tones, 350–51 | Convolutional codes, 61 |
| stabilized, 282-86 | | Correctness, stop-and-wait, 69-70 |
| unslotted, 287-89 American National Standards Institute, 97 | C | Cut-through routing, 373 |
| Amplitude modulation, 48 | C | Cycle, 387 |
| Application layer, 31–32 | CCIFT, 97 | Cyclic redundancy check, 61-64, 140 on ATM header, 133-34 |
| Arc. 387, 394 | CRC. See cyclic redundancy checks | end to-end, 116 |
| Arrival rate, 12, 152 | CRC-16 polynomial, 64 | |
| Arrival theorem, 239, 256 | CRC-32 IEEE polynomial, 64 | |
| Asynchronous balanced mode, 98-103 | CRC-CCTTT polynomial, 64, 98 | D |
| Asynchronous character pipes, 38 | CRP. See Collision resolution period | 11 C 15 M 1 |
| Asynchronous response mode, 98 Asynchronous transfer mode, 32, 40, 55, | CSMA, See Carrier sense multiple access | db. See Decibets |
| 97, 128–39, 141 | CSMA/CD. See Carrier sense multiple access/collision detection | DC component, 47, 48 DCE. See Data communication equipment |
| adaptation layer, 135-39 | Cable TV, 56, 341–42 | DECNET. 2, 19–20, 91, 93, 404 |
| call size, 132 | Call blocking, 494 | DLC. See Data link control |
| congestion, 138-39 | Call-request packet X.25, 119 | DLE (data link escape), 87 |
| CRC on header, 133-34 | Capacity assignment, 439-44 | DNA. See Digital network architecture |
| flow control, 138, 39 | Capacity, 51, 150 | DQDB. See Distributed queue dual bus |
| use of SONET, 134–35 | Capture effects, slotted Aloha, 355 | DTE. See Data terminal equipment |
| virtual channel and path ID, 133 Attenuation, 56 | Carrier offset, 53 | Data bases, remote access, 7-8 |
| Automatic repeat request, 39, 64–80, 272 | Carrier sense multiple access, 272, 304–12, 352 | Data communication equipment, 21, 118 Data compression, 10, 31 |
| ARPANET, 84-86 | collision avoidance, 333 | Data link control, 20, 23, 24, 37–40. |
| delay analysis, 190 | collision detection, slotted, 317-18 | 57-110, 271 |
| go back n. 72/81, 190 | collision detection, unslotted, 318-20 | correctness, 76–79, 140 |
| packet radio, 347–48 | FCFS splitting, 310-12 | standards, 97-103, 141 |
| ring networks, 323 | nonpersistent, 305 | Data terminal equipment, 21, 118 |
| selective repeat, 81–84 | packet radio, 350-51 | Datagram: |
| stop and wait, 66-71 | persistent, 305 P-Persistent, 305, 307 | networks, 115 routing, 16 |
| | pseudo-Bayesian stabilization, 307–9 | service, 26 |
| B | slotted Aloha, 305-9 | Datagram routing, 363 |
| | unslotted Aloha, 309-10 | Deadlock, 497-99 |
| BRAM, 333 | variable delay, 358 | Decibels, 51 |
| BSC. See Binary synchronous | Cellular radio system, 247 | Decomposition of gueues, 254 |
| communication Part Law 276 270 | Character based framing, 86-88 | Deflection routing, 372 |
| Backlog, 276, 279 Backlog estimation, 283, 286 | Choke packet, 510 Circuit switchmar, 14, 12, 180, 185, 379 | Delay, 13 CSMA, 308-9 |
| Backrog estimation, 285, 280 Backpressure, 507 | Circuit switching, 14–17, 180, 185, 379 Coaxial cuble, 7, 56 | CSMA/CD, 318, 360 |
| Bandwidth, 50-51 | Code conversion, 31 | FCFS splitting algorithm, 300–304 |

Delay cont.

Fiber distributed processing 15 propagation 5 queueing 15 satellite systems 3 1 dotted Aloha 15 dotted Aloha 16 dotted Aloha 16 dotted dotted Aloha 16 dotted dotte

E

EXT (end of the fill like the

F

FDDI. See Fiber in son = 1. FDM. See Frequent multiples of Facsimile, 8 Feasible direction, =59

| Delay cont. | Feedback, multiaccess; | Graphics, 8, 13 |
|--|---|---|
| Fiber distributed data interface, 329–30 | delayed, 303-4 | Guaranteed data rate, 494 |
| processing, 150 | _ mmediate, 276 | |
| propagation, 150 | Feedback shift register, 62 | |
| queueing, 15() | Fiber distributed data interface, 326-30, | Н |
| satellite systems, 314–45 slotted Aloha, 284–86 | 334, 339, 353 | HEN C 20 22 07 102 |
| token buses and polling systems, | delay, 329=30 | HDLC, 39, 72, 97-103 |
| 331 32 | throughput, 330 | faulty initialization, 106 |
| token ring, 324-25 | File transfer, 13 | Header: |
| transmission, 150 | Filtering, 41–53 | frame, 23, 39, 65 |
| Demand sharing, 274 | First derivative length, 452 | packet, 25 |
| Descent direction, 456 | First-come first-serve splitting, 293=304 | Hessian matrix, 465 |
| Designated port, 383 | CSMA, 310-12 Flags, 88-90, 320 | Hierarchy of modules, 17 |
| Detailed balance equations, 182, 214, | Flooding, 369, 419–25, 432, 490 | Homenets, 341–42 |
| 216, 218, 261, 263 | Flooding with sequence numbers, 420 | Horizontal and vertical parity checks, 58-59 |
| Digital network architecture, 404 | Flow control, 25-29, 30, 116-17, 158 | Hot potato routing, 372 |
| Digraph, 394 | combined with optimal routing. | Hybrids, 56 |
| Dijkstra's algorithm, 401-3, 481 | 519-24 | rigeria e po |
| Directed are, 394 | fairness, 498-99, 505, 507, 524-29 | |
| Directed cycle, 394 | in ARPANET, 515 | I |
| Directed graph, 394 | in ATM, 138-39 | |
| Directed walk, 394 | in Codex network, 518 | IEEE 802 standards, 48, 320, 323-24, |
| Directory assistance, 30 | in PARIS network, 518 | 332-33, 335 |
| Disconnect command, 100 | in SNA, 517 | IMP. See Interface message processor |
| Disconnect protocols, 103=10 | in TCP, 127-28 | IP. See Internet protocol |
| Distributed algorithms, 28, 32-34, 39, | m TYMNET, 517 | ISDN, See Integrated services digital |
| 1.39 | in X.25, 519 | network |
| Distributed queue dual bus, 335-39, 353 | input rate adjustment, 519-29 | ISO, See International Standards |
| Distributed shortest path construction, | max-min, 524-29, 534 | Organization |
| 404-10 | means, 494–95 | Idle fill, 38, 90, 321 |
| Distributed spanning tree construction. | objectives, 496–99 | Image transmission systems, 9 |
| .392 | optimal, 519-24 | Implicit tokens, 333 |
| Drift, 264 | satellite links, 506-8, 517 | Impulse response, 42 |
| Drift analysis: | transport layer, 509 | Incident are, 387 |
| CSMA, 306 | window, 500-510 | Infinite node assumption, 276 |
| FCFS splitting algorithm, 300 | Flow deviation method, 458-64 | Initialization protocols, 147 |
| slotted Aloha, 280 | Flow models, 433-37 | ARQ, 103–10 balanced, 107, 0 |
| Dynamic programming, 395 | Floyd-Warshall algorithm, 403-4 | balanced, 107–9 |
| Dynamic routing, 16–17, 436–38, 491 | Forwarding database, 383 | fault in HDLC, 106 |
| Dynamic window adjustment, 510 | Fourier transforms, 44, 45 Fragment, 389 | with link failures, 103 9 |
| | | master-slave, 104–7 with node failures, 109–10 |
| E | Fragmentation, internet protocol, 122 Frames, 23, 52, 65 | in TCP, 126 |
| L | internet protocol, 122 | use of stop-and-wait, 104 |
| EXT (end of text), 87 | maximum fixed length, 97 | Integrated services digital network, 5, |
| Electronic mail, 8, 9 | maximum length, 140-41 | 11 12, 54–56 |
| Embedded chain, 262 | maximum variable length, 93-97 | basic service, 55 |
| Encryption, 31 | Framing, 39, 86-97 | primary service, 55 |
| End-to-end CRC, 116 | bit-oriented, 88-90 | Interactive sessions, 13, 15 |
| End-to-end acks, 115-16, 119 | characted based, 86-88 | Interface message processor, 2 |
| End-to-end windows, 506-8, 515-17 | length fields, 90-92 | Internal signaling network, 55 |
| Entropy, 91, 140 | overhead, 87, 89, 90, 90, 92 | International Consultative Committee on |
| Ergodic system, 156 | with errors, 92-93 | Telegraphy and Telephony. See |
| Erlang B formula, 179, 167 | Frank Wolfe method, 458-64, 471, 488 | CCITT |
| Erlang C formula, 175, 267 | Free-for-all multiaccess, 272 | International Standards Organization, 19. |
| Error correction, 52, 61, 140 | Prequency division multiplexing, 52, 151. | 97 |
| Error detection, 39, 53, 57-64, 140 | 170, 177, 194 | terminology, 30 |
| bursts, 60-61 | in satellite channels, 273 | Internet protocol, 40, 120-23, 141 |
| random strings, 60–61 | Frequency response, 43–46 | addressing, 121–22 |
| Error recovery, 23, 32, 115-16 | Front end, 1 | datagrams, 120 |
| in TCP, 125–27 | | fragmentation, 122 |
| transport vs. network layer, 117-18 | G | time to live, 123 |
| Essau-Williams algorithm, 448 | | Internet sublayer, 28, 29 |
| Etheriet, 4, 48, 52, 274, 286, 317–20 | G/G/1 queue. See Queueing System | Internetworking, 28–29 |
| degradation with size and speed, 334 | Gateways, 4, 28-29, 120, 380 | Intersymbol interference, 42, 45–47, 49 Isarithmic method, 508 |
| Exponential distribution, 164, 266 | Generator polynomials, 62-64, 142 | rsamming memod, 508 |
| Expressnet, 339-41 | Global balance equations, 168, 260, 263 | |
| External site, 19 | Go back n ARQ, 72-81, 113, 143-44, | I |
| | 501 | , |
| F | correctness proof, 76-79 | Jackson's theorem: |
| 1 | efficiency, 80–81, 144 | closed networks, 234 |
| FIDDL Con Library House of the Control of | ideal, 82 | heuristic explanation, 227 |
| FDDI. See Fiber distributed data interface | rules, 74–76 | with limit on the number of customers |
| FDM. See Frequency division | rules with mod m, 80 | 256 |
| multiplexing Facsimile, 8 | Gradient project method, 459, 467-77, | multiple classes of customers, 231 |
| Feasible direction, 456 | 486-87, 489 | open networks, 223 |
| · ···································· | Graph 387 | tate depend on the 200 |

| K | Min-hop path, 370 | Packets, 10, 39 |
|--|--|--|
| Kleitman's algorithm, 445-47 | Minimum distance, 60 | ordering, 13, 86 |
| Kruskal algorithm, 390, 448 | Minimum weight spanning tree, 389, 484 Modems, 21, 38, 40, 48–52 | Parity check codes, 59–64, 140 Parity checks, 58 |
| | Modularity, 17 | Partial balance equations, 262 |
| L | Modulation, 140 | Path in a graph, 387 |
| L | amplitude, 48–49 | Peer process (modules), 18, 23, 25, 28, |
| LAN, See Local area network | phase-shift keying, 50 quadrature amplitude, 49-52 | 39 Periodic routing updates, 422 |
| LAPB, 72, 97–103, 118 | Module, 17 | Permit, 117, 500 |
| Last-come first-serve splitting algorithm. 302-3 | Modulo arithmetic, 58 | Permit (window) in TCP, 127 |
| Layering, 17-32, 35 | Multiaccess communication, 24, 195, 271-362 | Phase jitter, 53 |
| Leaky bucket, 245, 511–15, 535 | canonic reservation system, 312 | Phase shift keying, 50 Physical layer, 20–23, 37–38, 40–57 |
| Linear codes, 59 Linear systems, 41–46, 140 | Multidrop telephone lines, 271, 274, 331, | Piggybacked requests, 67 |
| Little's theorem, 152 62, 250–51 | 342 | Pipelining, 94-96 |
| slotted Aloha, 280 | Multiplexers, 1 Multiplexing, in TCP, 124–25 | Point to point protocols, 37 Poisson distributing, 164, 266 |
| Liveness; | Multicap bus systems, 271, 274 | Poisson process, 11, 164–65, 172–73, |
| go back n. 77–78 stop-and-wait, 69–70 | · - | 275 |
| Load sharing, 8 | N | combined, 244 |
| Local access network, 438 | N | merged, 165 properties, 243 |
| Local access network design, 448-51 | NRM. See Normal response mode | split, 165, 245 |
| Local area networks, 4, 7, 29, 56, 271-72, 317-42, 352-53 | NRZ code, 42, 48 | Poll final bit, 99 |
| Local loop, telephone network, 54, 56 | Nak, 66 | Pollaczek-Khinchin formula, 186 |
| | Network layer, 25–29 point to point protocols, 110–20 | Polling, 274, 331–32, 342–44 generalized, 342–44 |
| M | Networks of queues; | hub, 331 |
| *** | acyclic, 221 | queueing analysis, 195-203 |
| M/D/1 queue. See Queueing system | closed, 233 | Polynomial division, 62 Port, 382 |
| M/G/1 queue. See Queueing system M/G/∞ queue. See Queueing system | Jackson's theorem, 212, 221, 434 Kleinrock independence approximation, | in TCP, 124 |
| M/M/1 approximation. See Networks of | 212, 221, 434, 440 | Positive definite matrix, 465 |
| queues | M/M/1 approximation, 213, 221, 434, | Positive semidefinite matrix, 465 |
| M/M/I queue. See Queueing system | 440, 453, 476 | Presentation layer, 31 Prim-Dijkstra algorithm, 390, 448, 484 |
| M/M/1/m queue. See Queueing system M/M/∞ queue. See Queueing system | multiple classes of customers, 230 state dependent service rates, 229 | Primitive polynomials, 64 |
| M/M/m queue. See Queueing system | tandem queues, 209, 220 | Priorities, FDDI, 326–27 |
| M/M/m/m queue. See Queueing system | with multiple classes of customers, 222 | Priority queueing system. See Queueing |
| MAC. See Medium access control | Newton's method, 467 Node of a graph, 387 | system Product form, 182 |
| MAN. See Metropolitan area network MSAP, 333 | Node-by-node windows, 501-6, 517 | Product form solution, 220, 223-25 |
| Manchester coding, 48 | Noise, 45, 51 | Promiscuous mode, 382 |
| Markov chain: | Nonlinear distortion, 53 | Protocols, See Automatic regeat request. |
| aperiodic, 260 continuous-time, 262–63 | Normal response mode, 98–101 Nyquist criterion, 47 | Distributed algorithms, HDLC, X.25, X.21 |
| discrete-time, 259-62 | , | Pseudo-Bayesian algorithm, 283-86, 352 |
| FCFS splitting algorithm, 297 | 0 | CSMA slotted Aloha, 307–9 CSMA producted Aloha, 250 |
| instability, 265 | O | CSMA unslotted Aloha, 359 Pure Aloha, 287–89 |
| irreducible, 260 M/M/1 system, 166 | OD pair. See Origin-destination pair | |
| M/M/∞ system, 177 | OSI, See Open systems interconnection | O |
| M/M/m system, 174 | On-off flow, 11 | × |
| M/M/m/m system, 179 multidimensional, 180-86 | Open systems interconnection, 19-20, 35 Optical fibers, 6-7, 15, 56, 326, 333 | QAM. See Quadrature amplitude |
| queueing networks, 223 | Optimal routing: | modulation Quasistatic assumption, 177 |
| reversible, 182 | algorithms, 455-75 | Quencing system: |
| slotted Aloha, 279, 353 stability, 264 | dynamic, 436–38, 491 formulation, 433–36 | closed, 158, 233, 256, 58 |
| time reversible, 215 | Origin-destination pair, 434 | discrete-time M/M/1, 246 G/G/1, 206-9, 253, 269 |
| Max-min fairness, 328 | | last-come first-serve, 232 |
| Max-min flow control, 524-29, 534 | P | last-come first-serve M/G/1 system, |
| Mean residual service time, 187 Mean value analysis, 238–40 | Г | 253 M/C/L matrix 247 |
| Media access control, 24, 27, 29, 271 | PARIS network, 392, 518 | M/G/1 system, 267 with arbitrary order of service, 248 |
| Memoryless property, 165 | PERT networks, 395 | with batch arrivals, 251 |
| Message switching, 16 Messages, 10 | PSK, See Phase-shift keying Packet blocking 195 | with busy period overhead, 251 |
| arrival rate, 12 | Packet blocking, 495 Packet discarding, 495 | with delay for new busy period, 251 with vacations, 192–95, 252, 268 |
| delay, 13 | Packet radio nets, 57, 273, 275, 286, | M/G/m/m, 179 |
| length, 12–13 | 344–51 | M/G/∞. 252 |
| ordering, 13 Metering, 214, 436 | collision resolution, 347–49 TDM, 346–47 | M/M/1, 162-73, 175, 216, 266 |
| Metropolitan area networks, 271-72, | transmission radii. 349-50, 353 | shared service, 247 with multiple classes of customers |
| 326–30. 333–42 | Packet scheduling, 495 | 258 |
| Micro-processors, 5 Microwave channels, 56 | Packet switching, 131 why used in ATM, 16 | with state-dependent rates, 246 |
| | way over in ALM, 10 | M/M/I/m, 247, 255 |

RN. See Real.

RS-232 content of the Radio Chamber of the Ladi
Randomizer of the Real time of Re

Regular chain [12]
Reject super.
Reject X.25 [12]
Repeaters: 53=5=
Request nummer 7
Reservation [12]
exhaustive, [3]
gated, [36]
limited serval [2]
multiaccess [27] [3]
multiaccess [27] [3]
partially gates [3]
satelares [3]
single-user

saletines single-user single-user services. Reset community. 2 = 2 Ring networks. Single services and services are services. Ringing, 48 Round services.

Runging, 48
Round robing in
Round robing in
Round robing, 25–2 - 10 - 2 - 2
adaptive, 55–2 - adaptive, 57–5 - 2
broadcast, 257
controller

asynchron 173 and broadcast, 257 centralized 174 and distributed, 375 in the ARP NET of in Codey near 175 in circuit switch as Taylor normalisms of the TYMNET 175 interaction as Taylor nonlineration of the TYMNET 175 oscillations, 175 and 175 shortest pain 175 and 175 shortest pain 175 and 175 static, 368

static, 368

R

| M/M/2 with heterogeneous servers, | Routing cont | Stack algorithms, 291 (See also Tree |
|---|---|---|
| 247 M/M/∝. 177–78, 216, 247 | tables, 365, 375, 76, 377, 382 | algorithms) |
| M/M/m, 174-77, 216, 266 | with frequently changing topology, 491 | unblocked stack, 293 |
| M/M/m/m, 175, 179, 216, 267 | | Standardization, 19–20, 32 |
| networks. See Networks of queues | S | Star configuration for rings, 324 |
| nonpreemptive priority, 203-5. | | Stationary distribution, 260, 263 |
| 249 50, 269 | SDLC, 72, 97-103 | Statistical multiplexing, 113, 150, 170 176, 214 |
| with phase-type distributions, 232 polling, 160, 195, 268 | SN. See Sequence number | Steepest descent method, 465 |
| preemptive resume priority, 205-6, | SNA. Sec System network architecture | Stop-and-wait, 142-43 |
| 249, 269 | SONET, 54, 141 | ARQ, 66-69 |
| priority with multiple servers, 249 | use in ATM, 134-35 SPTA. Sec Shortest path topology | correctness proof, 69-70 |
| processor sharing, 232 | algorithm | in initialization protocols, 104 |
| reservation, 195 204, 268 | STX (start of text), 87 | Store and-forward switching, 14-17 Strongly connected graph, 394 |
| time reversible, 214 | SYN (synchronous idle), 86 | Subgraph, 388 |
| . | Sampling theorem, 46, 47, 51 | Sublinear convergence rate, 461 |
| R | Satellite channels, 56, 57, 271, 273-74. | Subnet, 2=3, 10 |
| RN. See Request number | 313 17, 352–53 Saturated cut method, 81 84, 14(1–41, | Subnet design, 439-48 |
| RS-232-c interface, 21–22 | 444 | Supercomputers, 8 |
| Radio channels, 56, 271 See also Packet | Scheduling for multiaccess, 272 (See also | Supervisory frames, 99 100 |
| radio nets) | Reservations) | System network architecture (SNA), 19-20 |
| Randomization, 214, 222, 436 | Segmentation and reassembly, in ATM. | explicit route control, 378 |
| Rate control schemes, 510-15 | 136-39 | flow control, 501, 517 |
| Real time computation, 8 | Selective repeat ARQ, 144 | path control layer, 378 |
| Real time control, 13 Reassembly, 29 | ideal, 82 | routing, 378 |
| Receive-not-ready: | Selective-reject supervisory frame, 99-100 | SDLC, 72, 97-103 |
| supervisory frame, 99 100 | Sequence number, 66 | session level pacing, 517 |
| X.25 packet, 119 | Service rate, 152 | transmission control layer, 378 |
| Receive-ready: | Session holding time, 12 | transmission group control, 378 virtual route control, 378, 517 |
| supervisory frame, 99=100 | Session identification, 111-14 | virtual route pacing scheme, 501, 51 |
| X.25 packet, 119 | Session initiation, 31 | |
| Register insertion rings, 330–31 Regular chain, 262 | Session layer, 3() 31 | _ |
| Reject supervisory frame, 99-100 | Sessions, 11-14 Sharmon tangents thrown 50 51 52 | Τ |
| Reject X.25 packet, 119 | Shannon capacity theorem, 50-51, 53, 140 | TWID C T |
| Reliability, 9, 13, 29, 443-48 | Shortest path problem, 394 | TCP. See Transport control protocol TCP/IP. See Internet protocol. Transpor |
| Repeaters, 53-54 | Shortest path routing, 370 | control protocol |
| Request number, 67 | Shortest path spanning tree 400 | TDM. See Time-division multiplexing |
| Reservation system: | Shortest path topology algorithm, | 1P4 (ISO transport protocol), 128 |
| canonic multiaccess system, 312 exhaustive, 195 | 425 33, 483 Signal approximation 50 51 | 11 carrier, 53–54 |
| gated, 195 | Signal constellations, 50-51 Signal power, 51 | T3 carrier, 54 |
| limited service, 201, 249 | Simulated annealing, 443 | TYMNET, 2, 4, 19–20, 141 |
| multiaccess, 272, 312-44 | Sliding window, 72 (See also Go back n | flow control, 517 routing, 376–78 |
| multiuser, 198 | ARQ) | session identification, 112–13 |
| partially gated, 195 | Slotted Aloha: | Technology: |
| satellites 343-47 | capture, 355 | communication, 6-7 |
| single user 196 Reset command, 103 | delay, 354 | computer, 5/6 |
| Reversibility, 214-21 | stability, 353 Slotted frequency-division multiplexing, | Three army problem, 33-34, 71 |
| Ring networks, 320-31 | 194 | Throughput: |
| Ringing, 48 | Slotted multiaccess sytems, 275-88 | CSMA FCFS splitting, 311 CSMA slotted Aloha, 306 |
| Round-robin scheduling, 495 | Slotted ring, 330 | CSMA unslotted Aloha, 310 |
| Router, 380 Routing, 25 - 29, 363–491 | Socket in TCP, 124 | CSMA/CD: |
| adaptive, 368, 410-17, 455 | Solid state technology, 5 | slotted, 318 |
| asynchronous, 375, 404-10, 425 | Source coding theorem, 91–92, 140 Source routing, 385–87 | unslotted, 319 |
| broadcast, 487 | Spanning tree, 369, 388 | FCFS splitting algorithm, 300-301 |
| centralized, 367, 418 | Spanning tree routing, 383-85 | slotted Aloha, 282–83 |
| distributed, 367 | Spanning tree topoligy design, 447-48 | token buses and polling systems, 331-32 |
| hierarchical, 379–82 | Spitting algorithms, 289–304 | unslotted Aloha, 288 |
| in the ARPANET, 374 in Codex network, 476–77 | first-come first-serve, 293-304, 352 | Time invariance, 41 |
| in circuit switching networks, 379 | LCFS, 302-3 | Time sharing system, 160, 236 |
| in SNA, 378 | round robin, 304 with delayed feedback, 303-4 | Time to live, internet protocol, 123 |
| in the TYMNET, 376 | zero or positive feedback, 342-44 | Time window flow control, 511 |
| interaction with flow control, 365 | Stability: | Time-division multiplexing, 52, 151, 170 |
| interconnected network, 379-87 | CSMA, 307-12 | 177, 194, 214, 273, 277 for packet radio, 346–47 |
| main issues, 365–68 | datagram networks, 410–14 | Time-outs, 67-70, 73 |
| nonhierarchical, 380-82 optimal, 372, 433, 451-75 | PCFS splitting algorithm, 300 | Token buses, 331–33 |
| oscillations, 371, 374, 410–17 | shortest path routing algorithm, | degradation with size and speed, 334 |
| shortest path. 374-76, 387-417 | 410-417 | implicit tokens, 333 |
| shortest path first, 375, 382 | slotted Aloha, 281–86, 352 unslotted Aloha, 288, 359 | Token rings, 4, 320-30 |
| static, 368 | virtual circuit networks, 414-17 | Topological design, 437–51, 464 |
| | sac eneur networks, +14-1/ | Topology, 418 |

Trailer frame, 23, 39, 65
Transition rate, 262
Transmission delay, See Delay
Transparent mode, 87
Transport control protocol, 40, 124–28, 141
addressing, 124–25
error recovery, 117–18, 125–27
flow control, 127–28
initialization, 126
multilexing, 124–25
Transport layer, 29–30, 123–28
standards, 123–24
Transport layer flow control, 509
Tree, 388
Tree algorithms, 290–93, 352
Truncation of Markov chains, 182, 254
Twisted pair, 7, 56

T

Unary-binary encoding, 91, 114

Undetectable errors, 60, 64, 114–15 Unnumbered acks, 100 Unnumbered frames, 100 Unslotted Atoha, 287–89 precise feedback, 356 throughput, 357 Unstable equilibrium for Aloha, 281 Utilization factor, 157, 169

V

VLSI. See Very large scale integration Vacation Queueing system. See Queueing system Very large scale integration, 5 Video conferencing, 12 Virtual channel number, X.25, 118 Virtual channels, 111 Virtual circuit routing, 16, 26, 111, 116, 363, 476-77, 490 Voice: digitized, 11 packetized, 13-14 Voice mail, 8 Voice network, 5, 8 Voice-grade, See Communication channels

W

WAN, See Wide area network Walk in a graph, 387 Wide area network, 4, 6 Window tpermit) in TCP, 127 Window flow control, 117, 158, 500-10

X

X.21 interface, 21–22, 118 X.25 standard, 40, 118–20, 500-10 LAPB, 97–103