FEUP – Redes de Computadores 2021/2022

1.º Trabalho Laboratorial

Diogo Costa
up201906731@edu.fe.up.pt

Francisco Colino
up201905405@edu.fe.up.pt

9 de dezembro de 2021

Sumário

1 Introdução

O objetivo deste trabalho é implementar um protocolo de ligação de dados, de acordo com o guião fornecido, que permite fazer a transmissão de ficheiros de forma assíncrona através de portas série assegurando a integridade dos ficheiros. Esta integridade deve ser assegurada mesmo com interrupções e interferências. Este relatório procura expor a teoria por de trás deste projeto, como é que os objetivos foram alcançados e os testes efetuados à eficiência do protocolo.

Este relatório está estruturado da seguinte forma:

- **Arquitetura** – Blocos funcionais e interfaces.
- **Estrutura do Código** – Demonstração das APIs, principais estruturas de dados, principais funções e a sua relação com a arquitetura.
- **Casos de uso principais** – Identificação dos casos de uso e representação das sequências de chamada de funções.
- **Protocolo de ligação lógica** – Identificação dos principais aspetos funcionais da ligação lógica e descrição das estratégias usadas na implementação destes aspetos com extratos de código.
- **Protocolo de aplicação** – Identificação dos principais aspetos funcionais da aplicação e descrição das estratégias usadas na implementação destes aspetos com extratos de código.
- **Validação** – Descrição dos testes efetuados com apresentação quantificada dos resultados.
- **Eficiência do protocolo de dados** – Caraterização estatística da eficiência do protocolo, efetuada recorrendo a medidas sobre o código desenvolvido.

- **Conclusão** – Síntese da informação apresentada nas secções anteriores e reflexão sobre os objetivos de aprendizagem alcançados.

2 Arquitetura

3 Estrutura do código

4 Casos de uso principais

5 Protocolo de ligação lógica

6 Protocolo de aplicação

7 Validação

8 Eficiência do protocolo de ligação de dados

9 Conclusões

10 Anexos

10.1 Código Fonte

```c
#include <stdio.h>
#include <string.h>
#include <stdlib.h>

#include "aplic.h"


int main(int argc, char** argv) {
    if (argc != 4) {
        printf("Usage:\tsender SerialPort Path NameToGive\n\tex: nserial <i> <path> <name>\n");
        return -1;
    }

    int porta = atoi(argv[1]);

    if (send_file(porta, argv[2], strlen(argv[2]), argv[3]) < 0) {
        return -1;
    }

    return 0;
}
```

Listing 1: sender.c

```c
#include <stdio.h>
#include <stdlib.h>

#include "aplic.h"


int main(int argc, char** argv) {
    if (argc != 2) {
        printf("Usage:\treceiver SerialPort\n\tex: nserial <i>\n");
        return -1;
    }

    int porta = atoi(argv[1]);

    if (receive_file(porta) < 0 ) {
        return -1;
    }

    return 0;
}
```

Listing 2: receiver.c

```c
int send_file(int porta, char *path, int path_size, char *
    file_name);

int receive_file(int porta);
```

Listing 3: aplic.h

```c
#include <stdint.h>

#define BAUDRATE B38400
#define _POSIX_SOURCE 1 /* POSIX compliant source */
#define FALSE 0
#define TRUE 1

#define DATA_PACKET_MAX_SIZE 1000

typedef enum type {
    TRANSMITTER,
    RECEIVER
} type_t;

int llopen(int porta, type_t type);

int llclose(int fd, type_t type);

int llwrite(int fd, uint8_t *buffer, int length);

int llread(int fd, uint8_t *buffer);
```

Listing 4: linklayer.h

```c
#include "aplic.h"
#include "linklayer.h"
#include <sys/types.h>
#include <sys/stat.h>
#include <fcntl.h>
#include <termios.h>
#include <stdio.h>
#include <string.h>
#include <strings.h>
#include <stdlib.h>
#include <unistd.h>
#include <stdint.h>

#define CONTROL_PACKET_MAX_SIZE 500
#define PACKET_MAX_SIZE (CONTROL_PACKET_MAX_SIZE >
    DATA_PACKET_MAX_SIZE ? CONTROL_PACKET_MAX_SIZE :
    DATA_PACKET_MAX_SIZE)
#define FILE_NAME_MAX_SIZE 255

#define C_DATA 0x1
#define C_START 0x2
#define C_END 0x3

```

```c
#define N(seq) ((seq) % 255)

#define L1(K) ((K) & 0b11111111)
#define L2(K) (((K) >> 8) & 0b11111111)
#define K(L1,L2) (256*(L2)+(L1))

#define T_FILE_SIZE 0x0
#define T_FILE_NAME 0x1


static off_t get_file_size(int fd) {
    struct stat s;
    if (fstat(fd, &s) == -1) {
        return -1;
    }

    return s.st_size;
}

static uint8_t* get_control_packet(off_t file_size, char *
    file_name, int file_name_size, int *length) {
    uint8_t* control_packet = malloc(CONTROL_PACKET_MAX_SIZE);
    if (control_packet == NULL) {
        return NULL;
    }

    size_t i = 0;

    control_packet[i++]  = C_START;
    control_packet[i++]  = T_FILE_SIZE; // T1
    control_packet[i++]  = sizeof(off_t); // L1

    memcpy(&control_packet[i], &file_size, sizeof(off_t)); //
    V1
    i += sizeof(off_t);

    control_packet[i++] = T_FILE_NAME; // T2

    control_packet[i++] = (uint8_t)file_name_size; // L2

    memcpy(&control_packet[i], file_name, file_name_size); //
    V2

    *length = i + file_name_size;
    return control_packet;
}

static int send_packaged_file(int fd_serial_port, int fd_file)
    {
    uint8_t *data_packet = malloc(DATA_PACKET_MAX_SIZE);
    if (data_packet == NULL) {
        return -1;
    }

```

```
72      uint8_t sequence_number = 0;
73      data_packet[0] = C_DATA;
74
75      while (1) {
76          data_packet[1] = sequence_number;
77          sequence_number = (sequence_number+1) % 255;
78
79          ssize_t num = read(fd_file, &data_packet[4],
        DATA_PACKET_MAX_SIZE-4);
80
81          if (num == -1) {
82              free(data_packet);
83              return -1;
84          } else if (num == 0) {
85              break;
86          } else {
87              data_packet[2] = L2(num);
88              data_packet[3] = L1(num);
89
90              if (llwrite(fd_serial_port, data_packet, num+4) <
        0) {
91                  free(data_packet);
92                  return -1;
93              }
94          }
95      }
96
97      free(data_packet);
98      return 0;
99  }
100
101 int send_file(int porta, char *path, int path_size, char *
        file_name) {
102     int file_name_size = strlen(file_name);
103     if (file_name_size > FILE_NAME_MAX_SIZE) {
104         printf("File name to big.\n");
105         return -1;
106     }
107
108     int fd_file;
109     if ((fd_file = open(path, O_RDONLY)) < 0) {
110         printf("File not found.\n");
111         return -1;
112     }
113
114     off_t file_size = 0;
115     if ((file_size = get_file_size(fd_file)) < 0) {
116         close(fd_file);
117         return -1;
118     }
119
120     int fd_serial_port;
121     if ((fd_serial_port = llopen(porta, TRANSMITTER)) < 0) {
122         close(fd_file);
```

```
123         return -1;
124     }
125 
126     uint8_t* control_packet = NULL;
127     int control_packet_size = 0;
128     if ((control_packet = get_control_packet(file_size,
    file_name, file_name_size, &control_packet_size)) == NULL)
    {
129         close(fd_file);
130         llclose(fd_serial_port, TRANSMITTER);
131         return -1;
132     }
133 
134     // Control packet start
135     if (llwrite(fd_serial_port, control_packet,
    control_packet_size) < 0) {
136         free(control_packet);
137         close(fd_file);
138         llclose(fd_serial_port, TRANSMITTER);
139         return -1;
140     }
141 
142     if (send_packaged_file(fd_serial_port, fd_file) != 0) {
143         free(control_packet);
144         close(fd_file);
145         llclose(fd_serial_port, TRANSMITTER);
146         return -1;
147     }
148 
149     // Control packet end
150     control_packet[0] = C_END;
151     if (llwrite(fd_serial_port, control_packet,
    control_packet_size) < 0) {
152         free(control_packet);
153         close(fd_file);
154         llclose(fd_serial_port, TRANSMITTER);
155         return -1;
156     }
157 
158     free(control_packet);
159     close(fd_file);
160     llclose(fd_serial_port, TRANSMITTER);
161     return 0;
162 }
163 
164 int receive_file(int porta) {
165     int fd_serial_port;
166     if ((fd_serial_port = llopen(porta, RECEIVER)) < 0) {
167         return -1;
168     }
169 
170     uint8_t *packet = malloc(PACKET_MAX_SIZE);
171     if (packet == NULL) {
172         llclose(fd_serial_port, RECEIVER);
```

```
173         return -1;
174     }
175 
176     int fd_file_to_write = -1;
177     int sequence_number = 0;
178     off_t file_size = 0;
179 
180     int not_end_packet = TRUE;
181     while (not_end_packet) {
182         int packet_size = 0;
183         if ((packet_size = llread(fd_serial_port, packet)) < 0)
     {
184             free(packet);
185             llclose(fd_serial_port, RECEIVER);
186             return -1;
187         }
188 
189         uint8_t control_field = packet[0];
190         switch (control_field) {
191         case C_DATA:
192             if (fd_file_to_write == -1) { // Control start
    packet didn't arrive yet
193                 break;
194             }
195 
196             int N = packet[1];
197 
198             if (N == sequence_number) {
199                 int num_octets = K(packet[3], packet[2]);
200                 if (write(fd_file_to_write, &packet[4],
    num_octets) == -1) {
201                     free(packet);
202                     llclose(fd_serial_port, RECEIVER);
203                     return -1;
204                 }
205                 sequence_number = (sequence_number + 1) % 255;
206             } else {
207                 // wrong sequence number
208                 printf("Wrong packet sequence number. Expected:
     %d ; Got: %d\n", sequence_number, N);
209                 free(packet);
210                 llclose(fd_serial_port, RECEIVER);
211                 return -1;
212             }
213 
214             break;
215 
216         case C_START:;
217             int i = 1;
218             while (i < packet_size) {
219                 uint8_t T = packet[i++];
220                 uint8_t L = packet[i++];
221 
222                 if (T == T_FILE_SIZE) {
```

```
223                     memcpy(&file_size, &packet[i], L);
224
225                 } else if (T == T_FILE_NAME) {
226                     char file_name[FILE_NAME_MAX_SIZE];
227                     memcpy(file_name, &packet[i], L);
228
229                     fd_file_to_write = open(file_name, O_WRONLY
    | O_APPEND | O_CREAT, 0644);
230                     if (fd_file_to_write == -1) {
231                         free(packet);
232                         llclose(fd_serial_port, RECEIVER);
233                         return -1;
234                     }
235
236                 } else {
237                     printf("ERROR: not supposed to reach this\n
    ");
238                 }
239
240                 i += L;
241             }
242
243             break;
244
245         case C_END:
246             if (fd_file_to_write != -1) {
247                 close(fd_file_to_write);
248                 not_end_packet = FALSE;
249             }
250             // else Control start packet didn't arrive yet, so
    wait for it
251
252             break;
253
254         default:
255             break; // invalid control field (ignore packet)
256         }
257     }
258
259     if (llclose(fd_serial_port, RECEIVER) < 0) {
260         free(packet);
261         return -1;
262     }
263
264     free(packet);
265     return 0;
266 }
```

Listing 5: aplic.c

```
1 #include "linklayer.h"
2 #include <sys/types.h>
3 #include <sys/stat.h>
4 #include <fcntl.h>
```

```c
#include <termios.h>
#include <stdio.h>
#include <string.h>
#include <strings.h>
#include <stdlib.h>
#include <unistd.h>
#include <signal.h>
#include <stdint.h>

#define FLAG 0x7E
#define ESC 0x7D
#define A 0x03
#define C_SET 0x03
#define C_DISC 0x0B
#define C_UA 0X07

#define C_RR(r) (0x05 | (((r) << 7) & 0x80))
#define C_REJ(r) (0x01 | (((r) << 7) & 0x80))
#define C_I(s) ((s) << 6)

#define CONTROL_SIZE 5

#define STUFFER 0x20

#define TIME_OUT_TIME 3
#define MAX_NO_TIMEOUT 3

#define HEADER_AND_TAIL_SIZE 10 // more than enough

typedef enum control_frame_type {
    SET,
    DISC,
    UA,
    RR,
    REJ
}  control_frame_type_t;

typedef enum state_sv_frame {
    START,
    FLAG_RCV,
    A_RCV,
    C_RCV,
    RR_RCV,
    REJ_RCV,
    BCC_OK,
    STOP
} state_sv_frame_t;

typedef enum state_info_rcv {
    I_START,
    I_GOT_FLAG,
    I_IGNORE,
    I_GOT_A,
    I_GOT_C,
```

```
    I_GOT_BCC1,
    I_DATA_COLLECTION,
    I_GOT_ESC,
    I_GOT_END_FLAG,
    I_TEST_DUP_RR,
    I_TEST_DUP_REJ,
    I_RR_DONT_STORE,
    I_RR_STORE,
    I_REJ,
    I_STOP
} state_info_rcv_t;

static struct termios oldtio;
static volatile int g_count = 0;

static uint8_t S = 0;
static uint8_t next_S = 0;
static uint8_t R = 0;

static void control_frame_builder(control_frame_type_t cft,
    uint8_t msg[]){
    msg[0] = FLAG;
    msg[1] = A;

    switch (cft) {
    case SET:
        msg[2] = C_SET;
        break;

    case DISC:
        msg[2] = C_DISC;
        break;

    case UA:
        msg[2] = C_UA;
        break;

    case RR:
        msg[2] = C_RR(R);
        break;

    case REJ:
        msg[2] = C_REJ(R);
        break;

    default:
        break;
    }

    msg[3] = msg[1] ^ msg[2];
    msg[4] = FLAG;
}

static int update_state_rr_rej(state_sv_frame_t *state, uint8_t
```

```
    byte) {
112
113     if (state == NULL) {
114         return 1;
115     }
116     switch (*state) {
117
118         case START:
119             if (byte == FLAG) *state = FLAG_RCV;
120             else *state = START;
121             break;
122
123         case FLAG_RCV:
124             if (byte == A) *state = A_RCV;
125             else *state = START;
126             break;
127
128         case A_RCV:
129             if ((byte & 0x0F) == 0x05) *state = RR_RCV;
130             else if ((byte & 0x0F) == 0x01) *state = REJ_RCV;
131             else *state = START;
132             next_S = (byte >> 7) & 0x01;
133             break;
134
135         case RR_RCV:
136             if (byte == (A^C_RR(next_S))) *state = BCC_OK;
137             else if (byte == FLAG) *state = FLAG_RCV;
138             else *state = START;
139             break;
140
141         case REJ_RCV:
142             if (byte == (A^C_REJ(next_S))) *state = BCC_OK;
143             else if (byte == FLAG) *state = FLAG_RCV;
144             else *state = START;
145             break;
146
147         case BCC_OK:
148             if (byte == FLAG) *state = STOP;
149             else *state = START;
150             break;
151
152         case STOP:
153             break;
154
155         default:
156             printf("ERROR: not supposed to reach this\n");
157             break;
158     }
159
160     return 0;
161 }
162
163 static int update_state_set_ua(uint8_t c, state_sv_frame_t *
    state, uint8_t byte) {
```

```
164     if (state == NULL) {
165         return 1;
166     }
167 
168     switch (*state) {
169         case START:
170             if (byte == FLAG) {
171                 *state = FLAG_RCV;
172             }
173             break;
174 
175         case FLAG_RCV:
176             if (byte == A) {
177                 *state = A_RCV;
178             } else if (byte != FLAG) {
179                 *state = START;
180             }
181             break;
182 
183         case A_RCV:
184             if (byte == c) {
185                 *state = C_RCV;
186             } else if (byte == FLAG) {
187                 *state = FLAG_RCV;
188             } else {
189                 *state = START;
190             }
191             break;
192 
193         case C_RCV:
194             if (byte == (A^c)) {
195                 *state = BCC_OK;
196             } else if (byte == FLAG) {
197                 *state = FLAG_RCV;
198             } else {
199                 *state = START;
200             }
201             break;
202 
203         case BCC_OK:
204             if (byte == FLAG) {
205                 *state = STOP;
206             } else {
207                 *state = START;
208             }
209             break;
210 
211         case STOP:
212             break;
213 
214         default:
215             printf("ERROR: not supposed to reach this\n");
216             break;
217     }
```

```
218
219
220     return 0;
221 }
222
223 static int update_state_info_rcv(state_info_rcv_t *state,
        uint8_t byte){
224
225     switch (*state){
226         case (I_START):
227             if (byte == FLAG) *state = I_GOT_FLAG;
228             else *state = I_IGNORE;
229             break;
230
231         case (I_GOT_FLAG):
232             if (byte == FLAG) *state = I_GOT_FLAG;
233             else if (byte == A) *state = I_GOT_A;
234             else *state = I_IGNORE;
235             break;
236
237         case (I_IGNORE):
238             if (byte == FLAG) *state = I_GOT_FLAG;
239             else *state = I_IGNORE;
240             break;
241
242         case (I_GOT_A):
243             if (byte == C_I(R)) * state = I_GOT_C;
244             else *state = I_IGNORE;
245             break;
246
247         case (I_GOT_C):
248             if (byte == (C_I(R)^A)) *state = I_GOT_BCC1;
249             else *state = I_IGNORE;
250             break;
251
252         case (I_GOT_BCC1):
253             if (byte == ESC) *state = I_GOT_ESC;
254             else *state = I_DATA_COLLECTION;
255             break;
256
257         case (I_DATA_COLLECTION):
258             if (byte == FLAG) *state = I_GOT_END_FLAG;
259             else if (byte == ESC) *state = I_GOT_ESC;
260             else *state = I_DATA_COLLECTION;
261             break;
262
263         case (I_GOT_ESC):
264             *state = I_DATA_COLLECTION;
265             break;
266
267         case (I_GOT_END_FLAG):
268             if (byte) *state = I_TEST_DUP_RR; // byte = is bcc2
        valid ?
269             else *state = I_TEST_DUP_REJ;
```

```
270             break;
271
272         case (I_TEST_DUP_RR):
273             if (byte) *state = I_RR_DONT_STORE; // byte = is
    dup ?
274             else *state = I_RR_STORE;
275             break;
276
277         case (I_TEST_DUP_REJ):
278             if (byte) *state = I_RR_DONT_STORE; // byte = is
    dup ?
279             else *state = I_REJ;
280             break;
281
282         case (I_RR_DONT_STORE):
283             *state = I_START;
284             break;
285
286         case (I_RR_STORE):
287             *state = I_STOP;
288             break;
289
290         case (I_REJ):
291             *state = I_START;
292             break;
293
294         case (I_STOP):
295             break;
296
297         default:
298             break;
299     }
300
301     return 0;
302 }
303
304 static void time_out() {
305     printf("alarme # %d\n", g_count);
306     g_count++;
307 }
308
309 static int setup_alarm() {
310     struct sigaction new;
311     sigset_t smask;
312
313     if (sigemptyset(&smask)==-1) {
314         perror ("sigsetfunctions");
315         return 1;
316     }
317
318     new.sa_handler = time_out;
319     new.sa_mask = smask;
320     new.sa_flags = 0;
321
```

```
322     if (sigaction(SIGALRM, &new, NULL) == -1) {
323         perror ("sigaction");
324         return 1;
325     }
326 
327     return 0;
328 }
329 
330 static int common_open(int porta) {
331     int fd = -1;
332     struct termios newtio;
333 
334     /*
335     Open serial port device for reading and writing and not as
    controlling tty
336     because we don't want to get killed if linenoise sends CTRL
    -C.
337     */
338 
339     char buffer[20];
340     if (sprintf(buffer, "/dev/ttyS%d", porta) < 0) {
341         perror("");
342         return -1;
343     }
344 
345 
346     fd = open(buffer, O_RDWR | O_NOCTTY );
347     if (fd < 0) {
348         perror(buffer);
349         return -1;
350     }
351 
352     if (tcgetattr(fd, &oldtio) == -1) { /* save current port
    settings */
353         perror("tcgetattr");
354         return -1;
355     }
356 
357     bzero(&newtio, sizeof(newtio));
358     newtio.c_cflag = BAUDRATE | CS8 | CLOCAL | CREAD;
359     newtio.c_iflag = IGNPAR;
360     newtio.c_oflag = 0;
361 
362     /* set input mode (non-canonical, no echo,...) */
363     newtio.c_lflag = 0;
364 
365     newtio.c_cc[VTIME]    = 0;   /* inter-character timer
    unused */
366     newtio.c_cc[VMIN]     = 1;   /* blocking read until 1 char
    received */
367 
368     tcflush(fd, TCIOFLUSH);
369 
370     if (tcsetattr(fd,TCSANOW,&newtio) == -1) {
```

```
371         perror("tcsetattr");
372         return -1;
373     }
374 
375     printf("New termios structure set\n");
376 
377     return fd;
378 }
379 
380 static int common_close(int fd) {
381     if (tcsetattr(fd, TCSANOW, &oldtio) == -1) {
382         perror("tcsetattr");
383         close(fd);
384         return -1;
385     }
386 
387     return close(fd);
388 }
389 
390 static void R_invert(){
391     R = ((!R) << 7) >> 7;
392 }
393 
394 int llopen(int porta, type_t type) {
395     state_sv_frame_t state;
396     int fd = common_open(porta);
397     if (fd < 0) {
398         printf("Failed to open serial port.\n");
399         return -1;
400     }
401 
402     printf("%d opened fd\n", fd);
403 
404     uint8_t set[CONTROL_SIZE];
405     control_frame_builder(SET, set);
406 
407     uint8_t ua[CONTROL_SIZE];
408     control_frame_builder(UA, ua);
409 
410     if (setup_alarm() != 0) {
411         common_close(fd);
412         return -1;
413     }
414     g_count = 0;
415 
416     switch (type) {
417     case TRANSMITTER:;
418         int ua_received = FALSE;
419         int res;
420         while (g_count < MAX_NO_TIMEOUT && !ua_received) {
421             state = START;
422 
423             res = write(fd, set, CONTROL_SIZE * sizeof(uint8_t)
    );
```

```
424             if (res == -1) {
425                 printf("llopen() -> write() TRANSMITTER error\n
    ");
426                 common_close(fd);
427                 return -1;
428             }
429             printf("SET sent.\n");
430             printf("%d bytes written\n", res);
431 
432             alarm(TIME_OUT_TIME);
433 
434             int timed_out = FALSE;
435             while (!timed_out && state != STOP) {
436                 uint8_t byte_read = 0;
437 
438                 res = read(fd, &byte_read, 1);
439                 if (res == 1) {
440                     if (update_state_set_ua(C_UA, &state,
    byte_read) != 0) {
441                         common_close(fd);
442                         alarm(0);
443                         return -1;
444                     }
445                     ua_received = (state==STOP);
446 
447                 } else if (res == -1) {
448                     timed_out = TRUE;
449 
450                 } else {
451                     printf("DEBUG: not supposed to happen\n");
452                 }
453             }
454 
455             alarm(0);
456         }
457 
458         if (ua_received) {
459             printf("UA received.\n");
460             printf("ACK\n");
461         } else {
462             common_close(fd);
463             return -1;
464         }
465 
466         break;
467 
468     case RECEIVER:
469         alarm(TIME_OUT_TIME * MAX_NO_TIMEOUT);
470         state = START;
471         while (state != STOP) {
472             uint8_t byte_read = 0;
473             res = read(fd, &byte_read, 1);
474 
475             if (res == 1) {
```

```
476                 if (update_state_set_ua(C_SET, &state,
    byte_read) != 0) {
477                     common_close(fd);
478                     alarm(0);
479                     return -1;
480                 }
481             } else if (res == -1) {
482                 if (g_count > 0) {
483                     printf("llopen timedout\n");
484                 } else {
485                     printf("llopen() -> read() RECEIVER error\n
    ");
486                 }
487                 common_close(fd);
488                 alarm(0);
489                 return -1;
490             } else {
491                 printf("DEBUG: not supposed to happen\n");
492             }
493         }
494 
495         printf("SET received.\n");
496         if (write(fd, ua, CONTROL_SIZE) < 0) {
497             printf("llopen() -> write() RECEIVER error\n");
498             common_close(fd);
499             alarm(0);
500             return -1;
501         }
502 
503         printf("UA sent.\n");
504         printf("ACK\n");
505         alarm(0);
506         break;
507     }
508 
509     return fd;
510 }
511 
512 int llclose(int fd, type_t type) {
513     state_sv_frame_t state;
514     uint8_t disc[CONTROL_SIZE];
515     control_frame_builder(DISC, disc);
516 
517     uint8_t ua[CONTROL_SIZE];
518     control_frame_builder(UA, ua);
519 
520     int res = 0;
521     int disc_received = FALSE;
522     g_count = 0;
523 
524     switch (type) {
525     case TRANSMITTER:
526         while (g_count < MAX_NO_TIMEOUT && !disc_received) {
527             state = START;
```

```
528
529             res = write(fd, disc, CONTROL_SIZE * sizeof(uint8_t
    ));
530             if (res == -1) {
531                 printf("llclose() -> write() TRANSMITTER error\
    n");
532                 return -1;
533             }
534             printf("DISC sent.\n");
535             printf("%d bytes written\n", res);
536
537             alarm(TIME_OUT_TIME);
538
539             int timed_out = FALSE;
540             while (!timed_out && state != STOP) {
541                 uint8_t byte_read = 0;
542
543                 res = read(fd, &byte_read, 1);
544                 if (res == 1) {
545                     if (update_state_set_ua(C_DISC, &state,
    byte_read) != 0) {
546                         common_close(fd);
547                         alarm(0);
548                         return -1;
549                     }
550                     disc_received = (state==STOP);
551
552                 } else if (res == -1) {
553                     timed_out = TRUE;
554
555                 } else {
556                     printf("DEBUG: not supposed to happen\n");
557                 }
558             }
559
560             alarm(0);
561         }
562
563         if (disc_received) {
564             printf("DISC received.\n");
565             res = write(fd, ua, CONTROL_SIZE * sizeof(uint8_t))
    ;
566             printf("UA sent.\n");
567         } else {
568             printf("DISC not received.\n");
569         }
570
571         break;
572
573     case RECEIVER:
574         alarm(TIME_OUT_TIME * MAX_NO_TIMEOUT);
575         state = START;
576         while (state != STOP) {
577             uint8_t byte_read = 0;
```

```
578
579             res = read(fd, &byte_read, 1);
580             if (res == 1) {
581                 if (update_state_set_ua(C_DISC, &state,
    byte_read) != 0) {
582                     common_close(fd);
583                     alarm(0);
584                     return -1;
585                 }
586                 disc_received = (state==STOP);
587             } else if (res == -1) {
588                 if (g_count > 0) {
589                     printf("llclose timedout\n");
590                 } else {
591                     printf("llclose() -> read() RECEIVER error\
    n");
592                 }
593                 alarm(0);
594                 common_close(fd);
595                 return -1;
596                 break;
597             } else {
598                 printf("DEBUG: not supposed to happen\n");
599             }
600         }
601
602         alarm(0);
603
604         if (res != -1) {
605             printf("DISC received.\n");
606             int ua_received = FALSE;
607             g_count = 0;
608             while (g_count < MAX_NO_TIMEOUT && !ua_received) {
609                 state = START;
610
611                 res = write(fd, disc, CONTROL_SIZE * sizeof(
    uint8_t));
612                 if (res == -1) {
613                     printf("llclose() -> write() RECEIVER error
    \n");
614                     alarm(0);
615                     return -1;
616                 }
617                 printf("DISC sent.\n");
618                 printf("%d bytes written\n", res);
619
620                 alarm(TIME_OUT_TIME);
621
622                 int timed_out = FALSE;
623                 while (!timed_out && state != STOP) {
624                     uint8_t byte_read = 0;
625
626                     res = read(fd, &byte_read, 1);
627                     if (res == 1) {
```

```
628                         if (update_state_set_ua(C_UA, &state,
    byte_read) != 0) {
629                             common_close(fd);
630                             alarm(0);
631                             return -1;
632                         }
633                         ua_received = (state==STOP);
634 
635                     } else if (res == -1) {
636                         timed_out = TRUE;
637 
638                     } else {
639                         printf("DEBUG: not supposed to happen\n
    ");
640                     }
641                 }
642 
643                 alarm(0);
644             }
645 
646             if (ua_received) {
647                 printf("UA received.\n");
648             }
649         }
650 
651         break;
652     }
653 
654     res = common_close(fd);
655 
656     return res;
657 }
658 
659 int message_stuffing(uint8_t in_msg[], unsigned int in_msg_size
    , uint8_t ** out_msg){
660 
661     int size_counter = 0;
662     *out_msg = malloc(in_msg_size*2);
663 
664    uint8_t * out_message = * out_msg;
665 
666     for (int i = 0; i < in_msg_size; i++){
667         switch (in_msg[i]){
668         case FLAG:
669             out_message[size_counter++] = ESC;
670             out_message[size_counter++] = FLAG ^ STUFFER;
671             break;
672         case ESC:
673             out_message[size_counter++] = ESC;
674             out_message[size_counter++] = ESC ^ STUFFER;
675             break;
676         default:
677             out_message[size_counter++] = in_msg[i];
678             break;
```

```
679         }
680     }
681     return size_counter;
682 }
683 
684 int message_destuffer(uint8_t in_msg[], unsigned int
    in_msg_size, uint8_t ** out_msg){
685 
686     int size_counter = 0;
687     *out_msg = malloc(in_msg_size);
688 
689     uint8_t * out_message = * out_msg;
690 
691     for (int i = 0; i < in_msg_size; i++){
692         if (in_msg[i] == ESC){
693             out_message[size_counter] = (in_msg[++i] ^ STUFFER)
    ;
694         } else {
695             out_message[size_counter] = in_msg[i];
696         }
697         size_counter++;
698     }
699 
700     return size_counter;
701 }
702 
703 uint8_t bcc2_builder(uint8_t msg[], unsigned int msg_size){
704 
705     if (msg_size == 1) {
706         return msg[0];
707     } else if ( msg_size < 0) {
708         return 0;
709     }
710 
711     uint8_t ret = msg[0];
712 
713     for (int i = 1; i < msg_size; i++){
714         ret ^= msg[i];
715     }
716 
717     return ret;
718 }
719 
720 int llwrite(int fd, uint8_t * buffer, int length){
721 
722     int write_successful = 0;
723     int ret = 0;
724     uint8_t bcc2 = bcc2_builder(buffer, length);
725     uint8_t *unstuffed_msg = malloc((length+1) * sizeof(uint8_t
    ));
726     memcpy(unstuffed_msg, buffer, length);
727     unstuffed_msg[length] = bcc2;
728     uint8_t *stuffed_msg = NULL;
729     int stuffed_msg_len = message_stuffing(unstuffed_msg,
```

```
    length+1, &stuffed_msg);
730     free(unstuffed_msg);
731     int total_msg_len = stuffed_msg_len + CONTROL_SIZE;
732     uint8_t *info_msg = malloc(total_msg_len);
733 
734     info_msg[0] = FLAG;
735     info_msg[1] = A;
736     info_msg[2] = C_I(S);
737     info_msg[3] = A ^ C_I(S);
738     memcpy(&(info_msg[4]), stuffed_msg, stuffed_msg_len);
739     info_msg[total_msg_len-1] = FLAG;
740 
741     setup_alarm();
742     g_count = 0;
743 
744     while(!write_successful && g_count < MAX_NO_TIMEOUT) {
745 
746         printf("----- TASK: WRITING MESSAGE\n");
747 
748         if (write(fd, info_msg, total_msg_len * sizeof(uint8_t)
    ) == -1) {
749             printf("llwrite() -> write() error\n");
750             free(info_msg);
751             free(stuffed_msg);
752             return -1;
753         }
754 
755         printf("----- TASK: DONE\n");
756 
757         uint8_t byte_read = 0;
758         int res = 0;
759         state_sv_frame_t state = START;
760 
761         printf("----- TASK: READING REPLY\n");
762 
763         alarm(TIME_OUT_TIME);
764 
765         while(state != STOP){
766             res = read(fd, &byte_read, 1);
767 
768             if (res == -1) {
769                 write_successful = 0;
770                 break;
771             }
772 
773             update_state_rr_rej(&state, byte_read);
774             printf("BYTE: 0x%x; STATE: %d\n", byte_read, state)
    ;
775 
776             if (state == RR_RCV) {
777                 write_successful = 1;
778             } else if (state == REJ_RCV) {
779                 write_successful = 0;
780             }
```

```
781         }
782 
783         printf("----- TASK: DONE\n");
784     }
785 
786     alarm(0);
787 
788     S = next_S;
789 
790     free(info_msg);
791     free(stuffed_msg);
792 
793     if (g_count >= MAX_NO_TIMEOUT) {
794         ret = -1;
795     } else {
796         ret = total_msg_len;
797     }
798 
799     return ret;
800 }
801 
802 int llread(int fd, uint8_t *buffer) {
803 
804     state_info_rcv_t state;
805     uint8_t byte_read = 0;
806     uint8_t data_read[DATA_PACKET_MAX_SIZE * 2 +
    HEADER_AND_TAIL_SIZE];
807     int msg_size = 0;
808 
809     uint8_t *unstuffed_msg = NULL;
810     int unstuffed_size = 0;
811 
812     setup_alarm();
813     g_count = 0;
814 
815     state = I_START;
816 
817     printf("--- NEW READ ---\n");
818 
819     while (state != I_STOP){
820 
821         printf("--- TRY READ ---\n");
822 
823         alarm(TIME_OUT_TIME * MAX_NO_TIMEOUT);
824 
825         msg_size = 0;
826         int rcv_s = -1;
827 
828         while (state != I_GOT_BCC1){
829             printf("PHASE 1 ; START_STATE : %d ; ", state);
830             if (read(fd, &byte_read, 1) == -1) {
831                 printf("llread() -> read() 1. error.\n");
832                 alarm(0);
833                 free(unstuffed_msg);
```

```
834                 return -1;
835             }
836 
837             if (g_count) {
838                 alarm(0);
839                 free(unstuffed_msg);
840                 return -1;
841             }
842             if (state == I_GOT_C) rcv_s = byte_read >> 6;
843             update_state_info_rcv(&state, byte_read);
844             printf("END_STATE : %d\n", state);
845         }
846 
847         while(state != I_GOT_END_FLAG) {
848             printf("PHASE 2 ; START_STATE : %d ; ", state);
849             if (read(fd, &byte_read, 1) == -1) {
850                 printf("llread() -> read() 2. error.\n");
851                 alarm(0);
852                 free(unstuffed_msg);
853                 return -1;
854             }
855 
856             if (g_count) {
857                 alarm(0);
858                 free(unstuffed_msg);
859                 return -1;
860             }
861             update_state_info_rcv(&state, byte_read);
862             data_read[msg_size] = byte_read;
863             msg_size++;
864             printf("BYTE : 0x%x ; END_STATE : %d\n", byte_read,
     state);
865         }
866 
867         unstuffed_size = 0;
868         uint8_t rej_msg[CONTROL_SIZE];
869         uint8_t rr_msg[CONTROL_SIZE];
870 
871         free(unstuffed_msg);
872         unstuffed_size = message_destuffer(data_read, msg_size
    -1, &unstuffed_msg);
873 
874         while (state != I_STOP && state != I_START){
875 
876             printf("PHASE 3 ; START_STATE : %d ; ", state);
877 
878             uint8_t res = 0;
879 
880             switch(state){
881                 case (I_GOT_END_FLAG):
882                     res = unstuffed_msg[unstuffed_size-1] ==
    bcc2_builder(unstuffed_msg, unstuffed_size-1);
883                     break;
884 
```

```
885                 case (I_TEST_DUP_REJ):
886                     res = rcv_s != R;
887                     break;
888 
889                 case (I_TEST_DUP_RR):
890                     res = rcv_s != R;
891                     break;
892 
893                 case (I_RR_DONT_STORE):
894                     R_invert();
895                     control_frame_builder(RR, rr_msg);
896                     if (write(fd, rr_msg, CONTROL_SIZE) == -1)
    {
897                         printf("llread() -> write() 1. error.\n
    ");
898                         alarm(0);
899                         free(unstuffed_msg);
900                         return -1;
901                     }
902                     break;
903 
904                 case (I_RR_STORE):
905                     R_invert();
906                     control_frame_builder(RR, rr_msg);
907                     memcpy(buffer, unstuffed_msg,
    unstuffed_size-1);
908                     if (write(fd, rr_msg, CONTROL_SIZE) == -1)
    {
909                         printf("llread() -> write() 2. error.\n
    ");
910                         alarm(0);
911                         free(unstuffed_msg);
912                         return -1;
913                     }
914                     break;
915 
916                 case (I_REJ):
917                     control_frame_builder(REJ, rej_msg);
918                     if (write(fd, rej_msg, CONTROL_SIZE) == -1)
     {
919                         printf("llread() -> write() 3. error.\n
    ");
920                         alarm(0);
921                         free(unstuffed_msg);
922                         return -1;
923                     }
924                     break;
925 
926                 case (I_STOP):
927                     break;
928 
929                 case (I_START):
930                     break;
931 
```

```
932                 default:
933                     printf("NOT SUPPOSED TO REACH THIS\n");
934                     break;
935             }
936             update_state_info_rcv(&state, res);
937             printf("RES : %d ; END_STATE : %d\n", res, state);
938         }
939     }
940 
941     alarm(0);
942 
943     free(unstuffed_msg);
944 
945     return msg_size;
946 }
```

Listing 6: linklayer.c