comdynamite: an R package to simulate and analyse metacommunities with traits, phylogenies and biogeography

Diogo B. Provete

Instituto de Biociências, Universidade Federal de Mato Grosso do Sul, Cidade Universitária, 79002-970, Campo Grande, Mato Grosso do Sul, Brazil

Gothenburg Global Biodiversity Centre, University of Gothenburg, Box 100, 405 30 Gothenburg, Sweden

ORCID: 0000-0002-0097-0651 Correspondence: diogo.provete@ufms.br

2026-11-10

Abstract

Methods that connect community composition to phylogenies, traits and biogeographic history have multiplied over the last two decades, but many of them were published only as MATLAB supplements or as equations, and were rarely evaluated on data in which the assembly process is known. Here, I describe comdynamite, an R package that brings these methods and the simulators needed to test them into a single framework. The package implements the process-based metacommunity model of Thompson et al. (2020) with traits that carry phylogenetic signal and competition structured by relatedness, rule-based and static generators, trait evolution under Brownian motion, Ornstein–Uhlenbeck, Mk and variable-rate models, the dynamic null model DAMOCLES, coevolution in a three-level food web, and individuals sampled from simulated populations. On the analytical side, it implements the node-based regression of Leibold et al. (2010), the phylogenetic gradient analysis of Peres-Neto et al. (2012), the phylogenetic community composition and beta-diversity tests of Peres-Neto & Kembel (2015), principal coordinates of phylogenetic structure, the T-statistics and trait-gradient analysis of intraspecific variation, and restricted permutations for sites that are neighbours. Every simulator and analysis shares one data structure, so any method can be run on data of known truth. Each implementation was written from the published equations and checked against the original code or reference packages; this process also found errors in some original implementations, which are documented and corrected. I illustrate how the package can be used to show that free permutations reject true null hypotheses in about half of the tests on spatially structured landscapes, that competition among relatives can erase the phylogenetic signature of environmental filtering, and that, in fully sampled clades, a phylogenetic regression of tip speciation rates on metapopulation persistence has no power to detect a link that a simulation-based test recovers. comdynamite is open source under the MIT license and is meant to make published methods usable and testable before they are applied to real metacommunities.

1 Introduction

Ecological communities are connected by dispersal, and the composition of each local community emerges from the interplay between environmental filtering, biotic interactions, dispersal and stochastic drift operating across scales (Leibold et al. 2004, Leibold and Chase 2018). Metacommunity theory gave ecologists a common vocabulary for these processes, organised around the paradigms of species sorting, mass effects, patch dynamics and neutral dynamics, and more

recently as a continuum of process-based scenarios (Thompson et al. 2020). However, the species that interact in a metacommunity are not independent units: they share a history of descent, their niches and traits carry phylogenetic signal to varying degrees, and the regional pool from which local communities are assembled is itself the outcome of speciation, extinction and dispersal over evolutionary time (Webb et al. 2002, Cavender-Bares et al. 2009, Mittelbach and Schemske 2015). As a result, a growing body of work has tried to integrate phylogenies, traits and biogeographic history into the analysis of metacommunities (Urban et al. 2008, Pillar and Duarte 2010, Leibold et al. 2010, Peres-Neto et al. 2012).

This integration produced a rich set of methods. Some ask which clades respond to environmental gradients or to biogeographic events, as the node-based regression of Leibold et al. (2010); others decompose the phylogenetic variation of communities into environmental and spatial components (Peres-Neto et al. 2012), test whether phylogenetic composition follows the environment across the whole tree (Peres-Neto and Kembel 2015, Duarte et al. 2016), or model community assembly as a dynamic process of colonisation and local extinction along the branches of the tree (Pigot and Etienne 2015). Concurrently, trait-based ecology moved from species means towards the variance within and among populations (Bolnick et al. 2011, Violle et al. 2012, Siefert et al. 2015), with methods that partition trait variation across organisational levels (Ackerly and Cornwell 2007, Lepš et al. 2011, Taudiere and Violle 2015). Nonetheless, inferring assembly processes from these patterns remains a challenge. The same phylogenetic pattern can arise from different processes, competition can produce both phylogenetic clustering and overdispersion depending on the balance between niche and fitness differences (Mayfield and Levine 2010, HilleRisLambers et al. 2012), and environmental filtering is often inferred from pattern without evidence that abiotic conditions limit the species (Cadotte and Tucker 2017, but see Gerhold et al. 2015).

A practical way to evaluate whether a method can recover a process is to apply it to data in which the process is known. Simulation studies are the standard tool for this in statistics (Morris et al. 2019), and the virtual ecologist approach brought the same logic to ecology, by simulating both the ecological system and the observation process (Zurell et al. 2010). In community ecology, a review of the filtering framework concluded that it has rarely produced generalisable conclusions and recommended that methods be validated by simulation before they are applied (Münkemüller et al. 2020), and simulations of metacommunities showed that adding temporal patterns to spatial ones improves the inference of metacommunity processes (Guzman et al. 2022). Mechanistic eco-evolutionary models can also be used directly for inference, by comparing observed patterns with those simulated under alternative processes (Hartig et al. 2011, Cabral et al. 2017, Pontarp et al. 2019, Overcast et al. 2021). However, simulation-based evaluation

requires a simulator in which the processes of interest (e.g., niche conservatism, competition among relatives, dispersal limitation) can be set independently, and an implementation of the method that reads the same data.

On the other hand, many of the methods above were never available as maintained software. The node-based regression of Leibold et al. (2010) and the phylogenetic gradient analysis of Peres-Neto et al. (2012) were published as MATLAB code in the supplementary material, which limits their use by ecologists who work in R (Lai et al. 2019). This is not a minor obstacle, because scientists tend to adopt software that colleagues use rather than software they have evaluated (Joppa et al. 2013), and the availability of an implementation in the language of the community strongly affects the uptake of a method (Wallace et al. 2017, Tikhonov et al. 2020). Additionally, code published with ecological papers is often unavailable or unchecked (Mislan et al. 2016, Culina et al. 2020), so errors in original implementations can propagate without notice. To the best of my knowledge, no R package brings together the simulators needed to generate metacommunities with phylogenetic and trait structure and the analytical methods that link phylogenies, traits and biogeography to community composition, in a way that every method can be tested on simulated data.

Here, I describe comdynamite, an R package that fills this gap. The package has two goals: (i) to make published methods that link traits, phylogenies and biogeography to metacommunities usable in R, implemented from the published equations and validated against the original code or reference packages; and (ii) to provide simulators in which the truth is known, so that each method can be evaluated for type I error, power and parameter recovery before it is applied to empirical data. In what follows, I describe the design of the package, give an overview of its functionality, summarise the validation of each implementation, including the errors it found in some original implementations, and illustrate two simulation studies that show why such evaluation matters.

2 Design principles

The package follows four principles. First, simulation and analysis share a single data structure. The function `mc_data()` holds a community matrix, a phylogeny, traits, environmental variables, coordinates, areas and time series in one object, and checks once that species and sites match across them. Every analysis accepts an `mc_data` object as its first argument and fills from it whatever the call leaves out, and every simulation returns an object that can be converted into one with `as_mc_data()`, keeping the tree from which its traits were drawn. This means that

a simulated metacommunity can be passed to an analysis without reformatting, which is the main requirement for evaluating methods by simulation (Figure 1). The same object also keeps empirical data in a consistent form, and the article "Preparing your data" on the package website shows how to build it from usual field tables.

Second, every model and method was written from the published equations, not translated from code. When the original code was available, it was used only to compare numbers, either by running it (e.g., the MATLAB supplements of Leibold et al. (2010) and Peres-Neto et al. (2012) in GNU Octave) or by comparison with the reference R package. This choice keeps the package under the MIT license, since several reference packages are under GPL and some supplementary code carries no license, and it also makes each divergence between an article and its code visible. Where the article and the code disagree, the package follows the article by default, documents the difference in the help page, and offers the behaviour of the original code as an option when it is useful for comparison.

Third, dependencies are light. The package imports only ape (Paradis and Schliep 2019) and base R packages, and every other package is in Suggests, called only when a function needs it: ggplot2 for plots, vegan (Oksanen et al. 2026) and adespatial for specific tests, future.apply for parallel permutations, and cmdstanr for the Bayesian trait-gradient model. As a result, the package installs quickly on any platform, and an analysis does not fail because of an unrelated dependency.

Fourth, results are reproducible and paired by design. Permutation tests run in parallel under a plan of the future package chosen by the user, and give the same results with `set.seed()` for any number of workers. The function `run_scenarios()` crosses factors of a simulation study, draws once per replicate what the scenarios share (for instance, a tree and a landscape), and assigns one seed to each cell of the design, so that scenarios are compared on the same regional pool. All validation scripts are kept in the `data-raw/` folder of the repository with their saved results, so that every number reported here and in the documentation can be reproduced.

3 Overview of functionality

The package exports about 95 functions, organised by the question they answer (Table 1). The website (https://provetelab.org/comdynamite/) maps each question to its functions and to an article that shows a complete analysis. Below, I describe the main groups.




Figure 1: Structure of comdynamite. Notice that simulated and observed data enter the analyses through the same object, `mc_data()`, so that every analysis can be applied to data in which the process is known. The regional pool (a tree with traits that evolved under a chosen model) feeds the simulators, restricted null models feed the analyses, and simulation studies compare the output of the analyses with the known truth (dashed arrow) to estimate type I error, power and parameter recovery. Function names are examples, not an exhaustive list.

Table 1: Main groups of functions in comdynamite and the question each group answers.

Group	Question	Main functions
Data	How do I keep community, tree, traits, environment and space together?	`mc_data()`, `as_mc_data()`
Metacommunity simulators	What composition do growth, competition, dispersal and drift produce?	`simulate_metacommunity()`, `simulate_static()`, `simulate_logistic()`, `assemble_community()`
Landscapes	On which landscape do species disperse?	`landscape_implicit()`, `landscape_grid()`, `dispersal_kernel()`, `env_over_time()`
Trait evolution	How did the traits of the regional pool evolve?	`species_traits()`, `trait_bm()`, `trait_ou()`, `rate_matrix()`, `trait_mk()`, `trait_rates()`, `history_rates()`, `turnover_rates()`
Coevolution	How do abundances and mean traits of a resource, consumer and predator change together?	`food_web_dynamics()`, `food_web_rates()`
Clades and biogeography	Which clades respond to the environment or to biogeographic events?	`node_contrasts()`, `biogeography_matrix()`, `node_test()`
The whole tree	Does phylogenetic composition follow the environment?	`pcc_test()`, `pcps_test()`, `phylo_beta_test()`
Environment and space	How much phylogenetic or trait variation is due to environment and space?	`phylo_vector()`, `trait_partition()`

Group	Question	Main functions
Restricted null models	Which permutations are valid when sites are neighbours?	`torus_permutations()`, `rigid_permutations()`, `patch_permutations()`
Dynamic null model	Is community structure consistent with colonisation and extinction along the tree?	`simulate_damocles()`, `damocles_fit()`, `damocles_test()`, `damocles_partition_test()`
Intraspecific variation	How is trait variation distributed among individuals, populations and communities?	`sample_individuals()`, `tstats()`, `population_shifts()`, `trait_gradient()`, `trait_flex()`, `nested_variance()`, `community_index()`
Simulation studies	Does a method work, and when?	`run_scenarios()`, `summary_stats()`, `equilibrium_check()`

3.1 Simulating metacommunities

The core simulator, `simulate_metacommunity()`, implements the process-based framework of Thompson et al. (2020), in which local abundances change by density-independent growth that depends on the match between the environmental optimum of each species and the environment of the site, by density-dependent competition, by dispersal among sites and by demographic stochasticity. I extended this model in four ways. First, the optima, niche breadths and maximum growth rates of species can be drawn on a phylogeny with a chosen phylogenetic signal (`species_traits()`), or taken from elsewhere, for instance from models fitted with mvMORPH (Clavel et al. 2015). Second, interspecific competition can be structured by relatedness (`competition_matrix(type = "phylo")`), so that niche conservatism and competition among relatives can be set independently. Third, landscapes can be spatially implicit or grids on a torus, with environments that change over time and a niche with several environmental axes. Fourth, each species can be restricted to the sites where it can occur (`pool`), such as its range or a biogeographic reconstruction, and the simulation can start from given abundances (`initial`),

which allows a phylogeny produced by an eco-evolutionary engine such as gen3sis (Hagen et al. 2021) to be used as the regional pool. Immigrants follow a Poisson distribution, as in the code archived with Thompson et al. (2020), or are conserved by a multinomial distribution, as in the R implementation mcomsimr (https://github.com/plthompson/mcomsimr). The simulator is written in base R and runs 50 species on 100 sites for 2200 time steps in about 0.7 s on one core, which makes simulation studies with thousands of replicates feasible on a laptop.

Three generators without population dynamics complement the dynamic model. The function `simulate_static()` draws abundances from Gaussian responses to one or more gradients (Dray and Legendre 2008), as used in the simulations of Peres-Neto et al. (2012) and Peres-Neto and Kembel (2015), and `simulate_logistic()` draws presences from logistic responses following the scenarios of Ives and Helmus (2011) and Peres-Neto et al. (2012). The function `assemble_community()` implements rule-based assembly by limiting similarity, habitat filtering and neutral sampling, as in Kraft et al. (2007), with the limiting-similarity rule of Colwell and Winkler (1984) and distances in trait space measured by Euclidean, standardised or Mahalanobis distance, the latter being equivalent to filtering by a multivariate Gaussian niche.

3.2 Simulating trait evolution and histories along the tree

Since the regional pool is an input, the package offers several models of trait evolution, each of which keeps the truth that estimation methods should recover. The function `trait_ou()` simulates one or several correlated traits under Brownian motion or Ornstein–Uhlenbeck processes with one or several optima (Hansen 1997, Butler and King 2004), with selective regimes painted on clades or given by a stochastic map, so that regimes, optima and evolutionary rate matrices change within branches. The rate matrices can take the structures fitted by mvMORPH (Clavel et al. 2015), built by `rate_matrix()`. The function `trait_mk()` simulates discrete characters under the Mk model (Lewis 2001) with gamma-distributed rates among branches or hidden rate classes (Beaulieu et al. 2013, Revell et al. 2024), and keeps every change in the format of phytools (Revell 2012, 2024). The function `trait_rates()` simulates continuous traits whose rate varies among branches, by shifts drawn as a Poisson process along the branches, as in the prior of BAMM (Rabosky 2014), by a log-rate that evolves by Brownian motion, or by independent lognormal rates, and returns the rate of each branch as the known truth for methods that estimate them (Eastman et al. 2011, Revell 2021, Martin et al. 2022).

Rates can also be derived from ecological and biogeographic processes. The function `history_rates()` converts the history of a discrete character, such as the region of each lineage, into rates per branch, including the diversity-dependent model with biogeography

of Drury et al. (2016), in which the rate depends on the number of lineages in the same region. The function `turnover_rates()` converts the turnover of co-occurring species in a simulated metacommunity into rates for the tip branches, linking assembly to the speed of trait evolution. Finally, `food_web_dynamics()` implements the joint dynamics of abundances and mean traits of a resource, a consumer and a predator described by McPeek (2017a) and McPeek (2017b), with Holling type II feeding, optional omnivory and attack coefficients that depend on traits, integrated by a fourth-order Runge–Kutta method. Its rates of trait change can be used as rates per lineage through `food_web_rates()`. Together with `tip_history_metrics()`, `arrival_ages()` and `as_herodotools()`, which give the inputs and the true answers for the tip-based metrics and arrival ages of Herodotools (Luza et al. 2021, Nakamura et al. 2023), these functions allow biogeographic and macroevolutionary reconstructions to be evaluated against a known history.

3.3 Analysing clades, the whole tree, and environment and space

The function `node_test()` implements the node-based approach of Leibold et al. (2010), in which the relative abundance of the two daughter clades of each node, coded by `node_contrasts()`, is regressed on environmental variables and biogeographic events, with permutations of sites and of species. The package adds the coding with branch lengths of the supplement of the original article, semi-partial correlations of each predictor, false discovery rate correction across nodes (Benjamini and Hochberg 1995), and `biogeography_matrix()`, which builds the matrix of events from the area of each site, either as pairs of areas defined a priori, as in Leibold et al. (2010) and Leibold and Chase (2018), or as each area against the others. Results can be drawn on the tree, as in Figure 3 of Leibold et al. (2010), or as a heatmap of nodes by predictors.

Three functions ask whether phylogenetic composition follows the environment across the whole tree. The function `pcc_test()` implements the phylogenetic community composition approach of Peres-Neto and Kembel (2015), and `phylo_beta_test()` its phylogenetic beta-diversity framework, a distance-based redundancy analysis (Legendre and Anderson 1999) of the mean phylogenetic distance between communities. The function `pcps_test()` implements the principal coordinates of phylogenetic structure of Duarte et al. (2016), based on the phylogenetic fuzzy weighting of Pillar and Duarte (2010), with tests of the whole dissimilarity and of each axis. Complementarily, `phylo_vector()` and `trait_partition()` implement the phylogenetic gradient analysis of Peres-Neto et al. (2012), which selects phylogenetic eigenvectors related to the environment and partitions the variation of traits or phylogenetic composition into environmental, spatial and shared fractions (Desdevises et al. 2003, Peres-Neto et al. 2006), with semi-partial

correlations of each predictor and a test of the shared fraction by Moran spectral randomisation (Wagner and Dray 2015, Bauman et al. 2018).

3.4 Restricted null models for sites that are neighbours

Permutation tests assume that sites are exchangeable, which is violated when both the community and the predictor are spatially autocorrelated (Legendre 1993, Lennon 2000, F. Dormann et al. 2007, Crabot et al. 2019). All permutation-based analyses in the package accept a matrix of restricted permutations (`site_permutations`), and three functions generate them. The function `torus_permutations()` shifts, rotates and reflects a grid on a torus, keeping the distances among sites. The function `rigid_permutations()` moves the whole biogeographic event by rotations, reflections and translations within a landscape with edges, keeping the shape of each area and the distance between them. The function `patch_permutations()` moves the patches of each area and keeps their number and size, for landscapes with edges and irregular areas. To the best of my knowledge, no published method covers exact permutations of binary areas in landscapes with edges and irregular shape, so the last two functions are new and were evaluated only by simulation (see below). In `trait_partition()`, each set of predictors moves alone in the tests of its fractions, with the response and the other set kept in place, which avoids comparing space with an environment that no longer explains anything (Freedman and Lane 1983, Anderson and Legendre 1999).

3.5 Dynamic null model of community assembly

The functions `simulate_damocles()`, `damocles_loglik()`, `damocles_fit()` and `damocles_test()` implement DAMOCLES (Pigot and Etienne 2015), a dynamic null model in which each lineage colonises the local community at rate γ and goes locally extinct at rate μ along the tree. The likelihood follows the pruning algorithm of the original article and is computed exactly in base R. The package extends the model in three directions: (i) rates can differ among regimes of the edges, such as clades defined a priori or rate shifts estimated by methods of diversification such as BAMM or ClaDS, or change with an edge covariate such as the tip diversification rate DR (Jetz et al. 2012); (ii) a probability of sympatry at speciation relaxes the strictly allopatric rule of the original model; and (iii) one pair of rates can be estimated from several communities on the same tree. Nested fits are compared by likelihood-ratio tests, intervals are obtained by profile likelihood, and `damocles_partition_test()` asks whether a partition of the tree into regimes is better placed than random partitions of the same complexity, rather than only whether rates vary.

3.6 Intraspecific trait variation

A last group of functions deals with trait variation among individuals. The function `sample_individuals()` draws individuals from the populations of a simulated metacommunity, with trait values composed of the optimum of the species, local adaptation to the environment of the site, deviations of populations that do not track the environment, character displacement away from co-occurring competitors, and variation among individuals, with sampling schemes that mimic field protocols (Pakeman and Quested 2007). Since the simulator records the colonisation history of every population (the step of its founding, the number of founders and the immigrants received since then), populations can also deviate according to their arrival, by founder effects that are eroded by gene flow or by the monopolization of a site by early colonists that adapt to it before others arrive (Urban and De Meester 2009, De Meester et al. 2016). On the analytical side, `tstats()` computes the T-statistics of Violle et al. (2012) with the three null models of Taudiere and Violle (2015), and adds a null model that exchanges population means among populations of each species. The function `population_shifts()` estimates local adaptation and character displacement together from population means, by a regression within species on the environment of the site and on the push predicted from co-occurring competitors. The function `trait_gradient()` implements the trait-gradient analysis of Ackerly and Cornwell (2007), with site means that leave out the focal species by default, which removes a circularity of the original method, null models that exchange species means among species, including phylogenetic permutations (Lapointe and Garland 2001), phylogenetic models of its components (Hansen 1997), and a bivariate phylogenetic mixed model fitted in Stan (`trait_gradient_bayes()`), in which the phylogenetic share λ of each component has its own prior. Finally, `trait_flex()` splits community-weighted means into species turnover, intraspecific variability and their covariation (Lepš et al. 2011), `nested_variance()` gives variance components across nested or crossed levels (Messier et al. 2010), `community_index()` compares any trait index with four null models, and `trait_densities()` computes trait probability densities of populations and communities (Carmona et al. 2016, 2019).

3.7 Simulation studies

The functions `run_scenarios()`, `summary_stats()` and `equilibrium_check()` reduce the code that a simulation study requires. The function `summary_stats()` computes the same statistics for simulated and observed data, namely diversity at several scales, occupancy, abundance distributions, standardised effect sizes of the mean pairwise and mean nearest taxon distances (Webb et al. 2002, Kembel et al. 2010), distance decay, the relation between traits and

environment, phylogenetic signal (Blomberg et al. 2003) and, when several time steps are recorded, temporal variation (Guzman et al. 2022). These statistics are meant for evaluating methods and for simulation-based inference such as approximate Bayesian computation (Hartig et al. 2011). Fast implementations of several metacommunity metrics for large spatiotemporal datasets, including the partition of beta diversity, occupancy and temporal variability, are available in Julia in MetaCommunityMetrics.jl (Cheung and Guzman 2026), which can be applied to the output of comdynamite. The function `equilibrium_check()` warns when a simulation is still changing at the end of its record, which happened in the simulations described below with competition among relatives and high dispersal. Since tree shape can affect the performance of phylogenetic methods, the companion package treeshapesim (https://github.com/diogoprov/treeshapesim) simulates trees in which imbalance and the distribution of branching times are controlled separately, so that tree shape can be a factor in the design of a simulation study.

4 Validation

Each model and method was validated in two complementary ways: against the original code or a reference package on the same inputs, to check the implementation, and against published results or analytical expectations, to check the behaviour (Table 2). Unit tests (about 400 blocks in 44 files) run on macOS, Windows and Linux at every change, and line coverage is tracked with Codecov.

The translations of the MATLAB methods agreed with the original code to numerical precision. The coefficients of determination and F statistics of `node_test()` matched those of the supplement of Leibold et al. (2010) run in GNU Octave 11.3 with differences below 10^{-15}, and the 13 contrasts of its example matched those of the original function. Similarly, `phylo_vector()` and `trait_partition()` reproduced the original code and Tables 1–4 of Peres-Neto et al. (2012). Likewise, the statistics of `pcps_test()` matched those of the PCPS package (Debastiani and Duarte 2014) to 8×10^{-15} in 20 communities, the pseudo-F of `phylo_beta_test()` matched `vegan::adonis2()`, and the log-likelihoods of the DAMOCLES implementation matched those of the DAMOCLES package to 3×10^{-14} in 180 comparisons, with maximum likelihoods equal to or higher than those of the reference package in all of ten communities. The type I error rates of `pcc_test()` and `phylo_beta_test()` reproduced those of Table 1 of Peres-Neto and Kembel (2015) (e.g., 0.049 and 0.040 for the species test of `pcc_test()`, against 0.054 and 0.052 in the original article), whereas power was somewhat lower than published (0.87 and 0.85, against 0.945 and 0.947), which I attribute to the use of different trees, since the original trees were not

available.

The simulators were validated against independent implementations and published figures. Against mcomsimr, in 16 scenarios of dispersal, competition and landscape with 200 replicates each, none of 80 comparisons of the distributions of diversity and abundance was significant (Kolmogorov–Smirnov tests, false discovery rate of 5%), and mean differences were below 1%. The patterns of Thompson et al. (2020) were reproduced with 100 patches, 50 species and 30 landscapes per combination of 15 dispersal rates, six niche breadths and four competition scenarios (Figure 2 shows three of them; the competition–colonisation scenario is in the validation article of the package website). In doing so, I found that the code archived with the article (Thompson 2020) differs from the text in points that change the results: beta diversity is computed as gamma divided by alpha rather than as the difference given in Table 1 of the article, the environment is converted into ranks, the lowest dispersal rate is 10^{-5} rather than 10^{-4}, and the competition–colonisation scenario halves the number of immigrants. Following the code, five of the six hypotheses of the article appeared clearly, whereas the effect of niche breadth on spatial beta diversity (their hypothesis H4) seemed to depend on the competition scenario, as their Figure 4 also shows. The diversity-dependent model of trait evolution with biogeography gave tip covariance matrices equal to those of RPANDA (Morlon et al. 2016) to 3×10^{-15} in 30 stochastic maps, the multivariate models matched the expected covariances of mvMORPH within three Monte Carlo standard errors over 20,000 simulations, and the food web reproduced the trajectories of Figure 3.2 of McPeek (2017b) within 10^{-4} of the integration of the author's code. Interestingly, one panel of Figure 3.11 could not be reproduced from the parameters given in its caption, at which the consumer cannot persist.

Table 2: Summary of the validation of the main implementations in comdynamite. Scripts and saved results are in the `data-raw/` folder of the repository.

Implementation	Reference	Comparison	Agreement
`node_test()`, `node_contrasts()`	MATLAB supplement of Leibold et al. (2010) (Octave 11.3)	R^2, adjusted R^2 and F; contrasts	differences $<$ 10^{-15}; 13 of 13 contrasts equal
`phylo_vector()`, `trait_partition()`	MATLAB code and Tables 1–4 of Peres-Neto et al. (2012)	statistics and fractions	equal to the original code

Implementation	Reference	Comparison	Agreement
`pcc_test()`, `phylo_beta_test()`	Table 1 of Peres-Neto and Kembel (2015); vegan	type I error, power; pseudo-F	type I error within the published range; F equal
`pcps_test()`	PCPS 1.0.9 (Debastiani and Duarte 2014)	statistics in 20 communities	differences $< 10^{-14}$
`damocles_loglik()`, `damocles_fit()`	DAMOCLES 2.3 (Pigot and Etienne 2015)	log-likelihoods, maximum likelihood, simulations	differences $< 10^{-13}$ in 180 comparisons
`simulate_metacommunity()`	mcomsimr; code of Thompson et al. (2020)	80 distributions in 16 scenarios; Figures 3–4 of the article	no significant difference; patterns reproduced
`history_rates(type = "sympatry")`	RPANDA (Morlon et al. 2016, Drury et al. 2016)	tip covariance matrices, 30 maps	differences $< 10^{-14}$
`trait_ou()`, `rate_matrix()`	mvMORPH 1.2.3 (Clavel et al. 2015)	covariance of tips, 20,000 simulations	within 3.1 Monte Carlo standard errors
`food_web_dynamics()`	McPeek (2017b) and code of McPeek (2017a)	trajectories of Figure 3.2	within 10^{-4}
`tstats()`	cati 0.99.6 (Taudiere and Violle 2015)	observed T-statistics	equal; errors in null models found (see text)
`tip_history_metrics()`	Herodotools 2.0.1 (Nakamura et al. 2023)	tip-based metrics, 30 histories	equal in 30 of 30

Validation also found errors in original implementations, which change results that users may have published. In the MATLAB code of Leibold et al. (2010), the statistic used to rank the




Figure 2: Spatial and temporal beta diversity (gamma divided by alpha, median of 30 landscapes) simulated with `simulate_metacommunity()` along dispersal and abiotic niche breadth, for the equal, mixed and stabilising competition scenarios of Thompson et al. (2020), following the layout of their Figure 4. Notice that spatial beta diversity is highest at low dispersal and decreases as mass effects homogenise communities, and that it increases with niche breadth under equal competition at low dispersal, by drift, but peaks at intermediate niche breadth under stabilising competition. Cells where species persisted in fewer than 10 of the 30 landscapes are left blank, as in the original figure.

random draws of sites depended on the scale of the response, and did not take into account that draws occupy different numbers of sites; the package uses F statistics instead, and keeps the coefficient of determination of the original code alongside a weighted version bounded between 0 and 1. In the code of Peres-Neto et al. (2012), the tests of the environmental and spatial fractions used the fraction itself as statistic, which lost power when the other set of predictors explained much of the variation: in 500 simulated data sets in which space had a strong effect and the environment a weak one, the original test rejected the environmental fraction in 15% of them, whereas the share of the component left unexplained by the other set, which is monotone in the partial F, rejected it in all of them, with type I error between 5.6% and 5.8%. In cati 0.99.6 (Taudiere and Violle 2015), the null model of one of the T-statistics combined permutations of different sites, and the matching of site names by regular expressions pooled sites such as `site1` and `site10`; an audit of other functions of the same package, which the package replaces with functions written from the published definitions, found further errors that change results. All of these were reported to the maintainers (issues 11 to 21 of the cati repository on GitHub). Finally, contrary to what Peres-Neto and Kembel (2015) state, the matrix of mean phylogenetic distances between communities is not always Euclidean, although the pseudo-F of the distance-based redundancy analysis does not require it (McArdle and Anderson 2001). In all cases, the help page of the function describes the difference, and the original behaviour remains available as an option when that is useful for comparison.

5 Illustration: two questions answered by simulation

To illustrate how the package can be used to evaluate methods, I present two simulation studies whose scripts are included in the package as vignettes. Both use only functions of comdynamite and were run with saved seeds, so that they can be reproduced exactly.

The first study asks under which conditions the phylogenetic structure of local communities reflects environmental filtering. I crossed dispersal (five emigration probabilities between 0.001 and 0.5), niche conservatism (optima without phylogenetic signal, $\lambda = 0$, or evolving by Brownian motion, $\lambda = 1$) and competition (none, or stronger between close relatives), in 30 replicates in which a tree of 30 species from treeshapesim and a landscape of 25 sites were drawn once and shared across scenarios. For each simulation, I computed the standardised effect size of the mean pairwise distance (SES MPD) of each site with picante (Kembel et al. 2010), using the whole tree as the regional pool. Communities were phylogenetically clustered only when niches were conserved, competition was absent and dispersal was low (mean SES MPD of -1.28 at an

emigration probability of 0.001; Fig. 3, panel a). This clustering weakened as dispersal increased (-0.33 to -0.50 at the two highest rates), since immigrants maintained species in sites that did not suit them. Without phylogenetic signal, SES MPD remained close to zero at all dispersal rates, even though species were strongly sorted by the environment at low dispersal. Surprisingly, adding competition among relatives to conserved niches moved SES MPD from -1.28 to -0.02 at the lowest dispersal rate, that is, to the random expectation, although both processes were acting strongly. This means that a value of SES MPD near zero does not imply random assembly, a result that is consistent with the argument that phylogenetic patterns alone cannot identify the processes that produced them (Mayfield and Levine 2010, Cadotte and Tucker 2017). With random niches, competition among relatives produced overdispersion at all dispersal rates (0.41 to 0.71).

The second study asks whether permutation tests keep their nominal type I error in spatially structured landscapes. I evaluated two tests: the regression of clades on biogeographic events of `node_test()`, with events that had no effect on communities that followed a hidden, spatially autocorrelated environment, and a test of the association between community composition and a predictor that was autocorrelated but unrelated to the community, on a torus. Free permutations of sites rejected the true null hypothesis in 45% to 53% of the node tests at the 5% level, and in 75% of the tests of composition (Fig. 3, panel b). In contrast, `patch_permutations()` rejected it in 3.4% to 5.2% of the node tests, and the torus in 5.8% to 7.5% of all tests, slightly above the nominal level, which seems to reflect that the landscapes of the node tests had edges that the torus does not have. Similar inflation was found for `pcps_test()`, in which free permutations rejected between 29% and 80% of tests on a 10×10 grid with autocorrelated fields unrelated to each other, against 4% to 7% for the torus when the fields wrapped around the grid. Taken together, these results show that the choice of the null model can matter more than the choice of the statistic, and that restricted permutations should be the default whenever sites are neighbours (Legendre 1993, Crabot et al. 2019).

6 Discussion

comdynamite brings together, in a single R package, simulators of metacommunities with phylogenetic and trait structure and the analytical methods that link phylogenies, traits and biogeography to community composition. Its main contribution is not any single method, but the fact that every method reads the same data as the simulators, so that its type I error, power and ability to recover parameters can be evaluated on data in which the process is known before




Figure 3: Two questions answered by simulation with comdynamite. (a) Mean standardised effect size of the mean pairwise distance (SES MPD) of local communities along dispersal, for optima without ($\lambda = 0$) or with ($\lambda = 1$) phylogenetic signal, with or without competition among relatives (30 replicates; bars are two standard errors). Notice that clustering (negative values) appears only with conserved niches, no competition and low dispersal, and that competition among relatives brings conserved niches back to the random expectation. (b) Rejection rate of a true null hypothesis at the 5% level for free and restricted permutations, in the node test of biogeographic events of `node_test()` for three layouts of areas on a square landscape with edges, and in a test of community composition against an unrelated autocorrelated predictor on a torus (bars are two standard errors; the horizontal axis is on a square-root scale). The dashed line marks the nominal level.

it is applied to an empirical metacommunity. This follows the recommendation that methods for inferring assembly processes should be validated by simulation (Zurell et al. 2010, Münkemüller et al. 2020), and makes such validation a matter of a few lines of code. Additionally, the package makes methods that were available only as MATLAB supplements, such as those of Leibold et al. (2010) and Peres-Neto et al. (2012), usable by the large community of ecologists who work in R, a step that seems to be necessary for a method to be adopted at all (Wallace et al. 2017, Tikhonov et al. 2020).

The validation of the package also showed that reimplementing a method from its equations is a form of review. By writing each method from the published text and comparing it with the original code, I found differences between articles and their code, and errors in some original implementations, that change the results of the tests. None of these was visible from the article alone, and some of them affect a popular package (Taudiere and Violle 2015). This is consistent with the concern that code in ecology is rarely treated as a scientific product in its own right (Mislan et al. 2016, Culina et al. 2020), and suggests that independent reimplementation, together with validation scripts that are kept with the code, should be part of how methods are published. In comdynamite, every divergence is recorded in the help page of the function and in the news file of the package, so that users can decide which behaviour they need.

The two illustrations make a point that goes beyond the package. First, phylogenetic structure did not identify the processes that produced it, since competition among relatives and environmental filtering on conserved niches cancelled each other out in the phylogenetic signature of local communities. Second, free permutations in spatially structured landscapes rejected true null hypotheses nine to 15 times more often than the nominal level, which means that a large fraction of significant relationships between communities and spatially structured predictors could be artefacts of the null model. These results agree with earlier warnings (Legendre 1993, Lennon 2000, Mayfield and Levine 2010), but they also show how easily such problems can be quantified for a particular design with the package, which is the practical use I envisage for it. Indeed, pilot analyses with approximate Bayesian computation in the development of the package showed that the dispersal rate, the strength of competition and niche breadth could be recovered from community-level summary statistics, whereas the phylogenetic signal of the niche could not (coefficients of determination of 0.88 to 0.99 against at most 0.07, with 50,000 simulations); similarly, the T-statistics recovered local adaptation but hardly character displacement, which only a model of population means could recover. These pilots are documented in the repository, and they illustrate that the statistics used to compare simulated and observed data deserve the same scrutiny as the methods themselves.

The same logic applies to tests of macroevolutionary hypotheses that use community or metapopulation data. For instance, Januario et al. (2025) found no relationship between the metapopulation persistence of 189 demersal fishes and their tip speciation rates in phylogenetic generalised least squares (PGLS) models, and interpreted this as a decoupling of metapopulation dynamics from speciation. To ask whether such a test can detect a causal link when one exists, I simulated fully sampled trees of 200 species in which the speciation rate of each lineage increased with a latent trait that evolved by Brownian motion, used the same trait to set the dispersal of each species in `simulate_metacommunity()`, estimated persistence (equilibrium occupancy and a rate of recovery, τ) from the simulated occupancy with a two-state Markov model, and regressed the tip diversification rate DR (Jetz et al. 2012) on persistence (200 replicates per scenario). Persistence was well estimated, and the same model fitted to the true speciation rates detected the link in 99% to 100% of the replicates. However, the PGLS of DR rejected the null hypothesis at about its nominal rate (6% to 10%) whatever the strength of the link, even when DR was correlated with the true rate (Spearman correlation of about 0.6). In contrast, a test of the correlation between DR and the trait with a null distribution simulated by Brownian motion on the tree (ES-sim; Harvey and Rabosky (2018)), which I implemented from its published description, detected the link through τ in 59%, 89% and 98% of the replicates as the link strengthened, while rejecting at most 2% of them without a link and in a negative control in which the trait affected local extinction instead of dispersal. Since τ was chosen after inspecting the estimates, I also tested both measures of persistence with a Bonferroni correction, which detected the link in 41%, 78% and 92% of the replicates. A possible explanation for the failure of the PGLS, which I did not test separately, is that DR averages rates along the path to the root, so that sister species have nearly identical values and the signal lies among clades, where the phylogenetic contrasts of the model carry little weight. Therefore, with fully sampled clades, a PGLS of DR on persistence seems to have no power to detect a link between persistence and speciation. This result does not show that the test of Januario et al. (2025) lacked power, because they estimated rates on a tree of thousands of species and analysed a sparse sample of 189 of them with model selection, which I did not simulate; in addition, the link between the trait and speciation was imposed in my simulations rather than emerging from metacommunity dynamics, and I did not test the rates estimated by BAMM that they also used. Nonetheless, it shows how the package can be used to measure the power of a design before a negative result is interpreted.

The package has limitations that users should know. One important limitation is that the phylogeny is an input of the simulations, not an outcome: the simulators run in ecological time on a fixed tree, without speciation, which is what simulation studies of methods need, since

tree shape and phylogenetic signal can be set independently and replicates can be paired by tree, but it means that the joint dynamics of speciation and assembly are outside its scope. For those, engines such as gen3sis (Hagen et al. 2021) or MESS (Overcast et al. 2021) are better suited, and their output can enter comdynamite as a regional pool. Additionally, the mapping between ecological time and branch time, required when rates of trait evolution are derived from metacommunity dynamics, is set by the user through a time window and informs only the tip branches. The restricted null models also have limits: `rigid_permutations()` remains liberal for blocks placed at random off a regular lattice (6.8% to 8.0% at the 5% level), events that span the whole landscape have few or no valid placements, and I could not find a valid null model for areas far apart without knowing the range of spatial autocorrelation. Some parameters are poorly identified from a single community, such as the rates of DAMOCLES in a community of 60 species, which is why the package allows rates to be shared across communities. Finally, comparisons with the figures of Thompson et al. (2020) were visual, since the published values are not tabulated, and the package is young and developed by a single author, so its interface may still change before version 1.0.0; renamed functions and arguments continue to work, with a warning, until then.

Future development will add a module for speciation, and further tools for simulation-based inference that combine population-level and community-level statistics. In summary, comdynamite provides a common ground in which methods that link traits, phylogenies and biogeography to metacommunities can be used, compared and, above all, tested. I hope that it encourages ecologists to ask, before interpreting a pattern, whether their method could have detected the process they are interested in, given their sites, their tree and their sampling.

7 Software availability

comdynamite is written in R (R Core Team 2026) and is distributed under the MIT license. The source code is at https://github.com/diogoprov/comdynamite, binaries for Linux, macOS and Windows are built by r-universe and installed with `install.packages("comdynamite", repos = c("https://diogoprov.r-universe.dev", "https://cloud.r-project.org"))`, and documentation, articles and the function reference are at https://provetelab.org/comdynamite/. Each release is archived on Zenodo, and the concept DOI https://doi.org/10.5281/zenodo.23993533 points to the latest version (Provete 2026a); this article describes version 0.7.0 (release https://github.com/diogoprov/comdynamite/releases/tag/v0.7.0), archived under the DOI https://doi.org/10.5281/zenodo.24097553 (Provete 2026b). The scripts that produced every

validation result and the figures of this article are in the `data-raw/` and `paper/` folders of the repository.

8 Funding

This study was supported by the Fundação de Apoio ao Desenvolvimento do Ensino, Ciência e Tecnologia do Estado de Mato Grosso do Sul (FUNDECT; grant 83/027.032/2024) and financed in part by the Coordenação de Aperfeiçoamento de Pessoal de Nível Superior – Brasil (CAPES) – Finance Code 001.

9 Use of generative AI

I report the use of generative AI following the AIdIT framework (Drobniak et al. 2026). I used the following AI engine in the present study: Claude Opus (Anthropic), via Claude Code (v. claude-opus-5-5; timestamps: 2026-11-05 to 2026-11-10). Area(s) of generative AI usage: Claude Opus (Anthropic), via Claude Code: new code generation, code generation for visuals, data analysis, identification of literature to cite, text generation based on prompts, bibliography management, text editing for style/grammar/spelling. I declare that I have verified and approved all content generated or modified by the AI tools used. The use of AI in this paper was in compliance with the ethical regulations of all funders and host institutions. Representative prompts used in AI content generation are available upon request. The AI engine wrote the R code of the package, its tests, documentation and validation scripts under my direction, following the models and methods I chose and the decisions I made on how divergences between articles and their code should be resolved; every function was checked against published results, the original code or a reference package, as described in the Validation section, and the commits made with the AI engine are identified as such in the history of the repository. The AI engine also drafted the manuscript text from the documentation and the saved validation results of the package, wrote the script that draws every figure from those results, and searched for references, each of which was checked against Crossref metadata before inclusion.

10 Conflict of interest

The author declares no conflict of interest.

References

Ackerly, D. D., and W. K. Cornwell. 2007. A trait-based approach to community assembly: Partitioning of species trait values into within- and among-community components. Ecology Letters 10:135–145.

Anderson, M. J., and P. Legendre. 1999. An empirical comparison of permutation methods for tests of partial regression coefficients in a linear model. Journal of Statistical Computation and Simulation 62:271–303.

Bauman, D., J. Vleminckx, O. J. Hardy, and T. Drouet. 2018. Testing and interpreting the shared space-environment fraction in variation partitioning analyses of ecological data. Oikos 128:274–285.

Beaulieu, J. M., B. C. O'Meara, and M. J. Donoghue. 2013. Identifying hidden rate changes in the evolution of a binary morphological character: The evolution of plant habit in campanulid angiosperms. Systematic Biology 62:725–737.

Benjamini, Y., and Y. Hochberg. 1995. Controlling the false discovery rate: A practical and powerful approach to multiple testing. Journal of the Royal Statistical Society Series B: Statistical Methodology 57:289–300.

Blomberg, S. P., T. Garland, and A. R. Ives. 2003. TESTING FOR PHYLOGENETIC SIGNAL IN COMPARATIVE DATA: BEHAVIORAL TRAITS ARE MORE LABILE. Evolution 57:717–745.

Bolnick, D. I., P. Amarasekare, M. S. Araújo, R. Bürger, J. M. Levine, M. Novak, V. H. W. Rudolf, S. J. Schreiber, M. C. Urban, and D. A. Vasseur. 2011. Why intraspecific trait variation matters in community ecology. Trends in Ecology & Evolution 26:183–192.

Butler, M. A., and A. A. King. 2004. Phylogenetic comparative analysis: A modeling approach for adaptive evolution. The American Naturalist 164:683–695.

Cabral, J. S., L. Valente, and F. Hartig. 2017. Mechanistic simulation models in macroecology and biogeography: State-of-art and prospects. Ecography 40:267–280.

Cadotte, M. W., and C. M. Tucker. 2017. Should environmental filtering be abandoned? Trends in Ecology & Evolution 32:429–437.

Carmona, C. P., F. de Bello, N. W. H. Mason, and J. Lepš. 2016. Traits without borders: Integrating functional diversity across scales. Trends in Ecology & Evolution 31:382–394.

Carmona, C. P., F. de Bello, N. W. H. Mason, and J. Lepš. 2019. Trait probability density (TPD): Measuring functional diversity across scales based on TPD with R. Ecology 100.

Cavender-Bares, J., K. H. Kozak, P. V. A. Fine, and S. W. Kembel. 2009. The merging of community ecology and phylogenetic biology. Ecology Letters 12:693–715.

559 Cheung, Y. Y. J., and L. M. Guzman. 2026. MetaCommunityMetrics.jl: A julia package for
560 spatiotemporal metacommunity analysis. Journal of Open Source Software 11:10167.
561 Clavel, J., G. Escarguel, and G. Merceron. 2015. mvMORPH: An R package for fitting
562 multivariate evolutionary models to morphometric data. Methods in Ecology and Evolution
563 6:1311–1319.
564 Colwell, R. K., and D. W. Winkler. 1984. 20. A null model for null models in biogeography.
565 Pages 344–359 Ecological communities. Princeton University Press.
566 Crabot, J., S. Clappe, S. Dray, and T. Datry. 2019. Testing the mantel statistic with a
567 spatially-constrained permutation procedure. Methods in Ecology and Evolution 10:532–540.
568 Culina, A., I. van den Berg, S. Evans, and A. Sánchez-Tójar. 2020. Low availability of code in
569 ecology: A call for urgent action. PLOS Biology 18:e3000763.
570 De Meester, L., J. Vanoverbeke, L. J. Kilsdonk, and M. C. Urban. 2016. Evolving perspectives
571 on monopolization and priority effects. Trends in Ecology & Evolution 31:136–146.
572 Debastiani, V. J., and L. D. S. Duarte. 2014. PCPS – an r-package for exploring phylogenetic
573 eigenvectors across metacommunities. Frontiers of Biogeography 6.
574 Desdevises, Y., P. Legendre, L. Azouzi, and S. Morand. 2003. QUANTIFYING PHYLOGE-
575 NETICALLY STRUCTURED ENVIRONMENTAL VARIATION. Evolution 57:2647–2652.
576 Dray, S., and P. Legendre. 2008. TESTING THE SPECIES TRAITS–ENVIRONMENT RELA-
577 TIONSHIPS: THE FOURTH-CORNER PROBLEM REVISITED. Ecology 89:3400–3412.
578 Drobniak, S. M., M. Cendrowska-Pek, A. Gudowska, K. Janas, P. Podkowa, K. Skorb, M.
579 Gronowska, W. Oleś, F. Bikmurzina, N. Boroń, M. Zagalska-Neubauer, S. Nakagawa, M.
580 Łagisz, A. Arct, and J. Rutkowska. 2026. A systematic map of generative AI guidelines and
581 reporting in ecology and evolutionary biology: Towards the framework of AI disclosure for
582 improved transparency (AIdIT). Research Integrity and Peer Review 11:57.
583 Drury, J., J. Clavel, M. Manceau, and H. Morlon. 2016. Estimating the effect of competition on
584 trait evolution using maximum likelihood inference. Systematic Biology 65:700–710.
585 Duarte, L. D. S., V. J. Debastiani, A. V. L. Freitas, and V. D. Pillar. 2016. Dissecting
586 phylogenetic fuzzy weighting: Theory and application in metacommunity phylogenetics.
587 Methods in Ecology and Evolution 7:937–946.
588 Eastman, J. M., M. E. Alfaro, P. Joyce, A. L. Hipp, and L. J. Harmon. 2011. A NOVEL COM-
589 PARATIVE METHOD FOR IDENTIFYING SHIFTS IN THE RATE OF CHARACTER
590 EVOLUTION ON TREES: IDENTIFYING RATE HETEROGENEITY IN CHARACTER
591 EVOLUTION. Evolution 65:3578–3589.
592 F. Dormann, C., J. M. McPherson, M. B. Araújo, R. Bivand, J. Bolliger, G. Carl, R. G. Davies, A.

593 Hirzel, W. Jetz, W. Daniel Kissling, I. Kühn, R. Ohlemüller, P. R. Peres-Neto, B. Reineking, B.
594 Schröder, F. M. Schurr, and R. Wilson. 2007. Methods to account for spatial autocorrelation
595 in the analysis of species distributional data: A review. Ecography 30:609–628.
596 Freedman, D., and D. Lane. 1983. A nonstochastic interpretation of reported significance levels.
597 Journal of Business & Economic Statistics 1:292–298.
598 Gerhold, P., J. F. Cahill, M. Winter, I. V. Bartish, and A. Prinzing. 2015. Phylogenetic patterns
599 are not proxies of community assembly mechanisms (they are far better). Functional Ecology
600 29:600–614.
601 Guzman, L. M., P. L. Thompson, D. S. Viana, B. Vanschoenwinkel, Z. Horváth, R. Ptacnik, A.
602 Jeliazkov, S. Gascón, P. Lemmens, M. Anton-Pardo, S. Langenheder, L. De Meester, and J.
603 M. Chase. 2022. Accounting for temporal change in multiple biodiversity patterns improves
604 the inference of metacommunity processes. Ecology 103.
605 Hagen, O., B. Flück, F. Fopp, J. S. Cabral, F. Hartig, M. Pontarp, T. F. Rangel, and L. Pellissier.
606 2021. gen3sis: A general engine for eco-evolutionary simulations of the processes that shape
607 earth's biodiversity. PLOS Biology 19:e3001340.
608 Hansen, T. F. 1997. STABILIZING SELECTION AND THE COMPARATIVE ANALYSIS OF
609 ADAPTATION. Evolution 51:1341–1351.
610 Hartig, F., J. M. Calabrese, B. Reineking, T. Wiegand, and A. Huth. 2011. Statistical inference
611 for stochastic simulation models - theory and application: Inference for stochastic simulation
612 models. Ecology Letters 14:816–827.
613 Harvey, M. G., and D. L. Rabosky. 2018. Continuous traits and speciation rates: Alternatives to
614 state-dependent diversification models. Methods in Ecology and Evolution 9:984–993.
615 HilleRisLambers, J., P. B. Adler, W. S. Harpole, J. M. Levine, and M. M. Mayfield. 2012.
616 Rethinking community assembly through the lens of coexistence theory. Annual Review of
617 Ecology, Evolution, and Systematics 43:227–248.
618 Ives, A. R., and M. R. Helmus. 2011. Generalized linear mixed models for phylogenetic analyses
619 of community structure. Ecological Monographs 81:511–525.
620 Januario, M., M. L. Pinsky, and D. L. Rabosky. 2025. The metapopulation bridge to macroevo-
621 lutionary speciation rates: A conceptual framework and empirical test. Ecology Letters
622 28.
623 Jetz, W., G. H. Thomas, J. B. Joy, K. Hartmann, and A. O. Mooers. 2012. The global diversity
624 of birds in space and time. Nature 491:444–448.
625 Joppa, L. N., G. McInerny, R. Harper, L. Salido, K. Takeda, K. O'Hara, D. Gavaghan, and S.
626 Emmott. 2013. Troubling trends in scientific software use. Science 340:814–815.

627 Kembel, S. W., P. D. Cowan, M. R. Helmus, W. K. Cornwell, H. Morlon, D. D. Ackerly, S. P.
628 Blomberg, and C. O. Webb. 2010. Picante: R tools for integrating phylogenies and ecology.
629 Bioinformatics 26:1463–1464.
630 Kraft, N. J. B., W. K. Cornwell, C. O. Webb, and D. D. Ackerly. 2007. Trait evolution, community
631 assembly, and the phylogenetic structure of ecological communities. The American Naturalist
632 170:271–283.
633 Lai, J., C. J. Lortie, R. A. Muenchen, J. Yang, and K. Ma. 2019. Evaluating the popularity of r
634 in ecology. Ecosphere 10.
635 Lapointe, F.-J., and T. Garland. 2001. A generalized permutation model for the analysis of
636 cross-species data. Journal of Classification 18:109–127.
637 Legendre, P. 1993. Spatial autocorrelation: Trouble or new paradigm? Ecology 74:1659–1673.
638 Legendre, P., and M. J. Anderson. 1999. DISTANCE-BASED REDUNDANCY ANALY-
639 SIS: TESTING MULTISPECIES RESPONSES IN MULTIFACTORIAL ECOLOGICAL
640 EXPERIMENTS. Ecological Monographs 69:1–24.
641 Leibold, M. A., and J. M. Chase. 2018. Metacommunity ecology. Princeton University Press.
642 Leibold, M. A., E. P. Economo, and P. Peres-Neto. 2010. Metacommunity phylogenetics:
643 Separating the roles of environmental filters and historical biogeography. Ecology Letters
644 13:1290–1299.
645 Leibold, M. A., M. Holyoak, N. Mouquet, P. Amarasekare, J. M. Chase, M. F. Hoopes, R. D. Holt,
646 J. B. Shurin, R. Law, D. Tilman, M. Loreau, and A. Gonzalez. 2004. The metacommunity
647 concept: A framework for multi-scale community ecology. Ecology Letters 7:601–613.
648 Lennon, J. J. 2000. Red-shifts and red herrings in geographical ecology. Ecography 23:101–113.
649 Lepš, J., F. de Bello, P. Šmilauer, and J. Doležal. 2011. Community trait response to environment:
650 Disentangling species turnover vs intraspecific trait variability effects. Ecography 34:856–863.
651 Lewis, P. O. 2001. A likelihood approach to estimating phylogeny from discrete morphological
652 character data. Systematic Biology 50:913–925.
653 Luza, A. L., R. Maestri, V. J. Debastiani, B. D. Patterson, S. M. Hartz, and L. D. S. Duarte.
654 2021. Is evolution faster at ecotones? A test using rates and tempo of diet transitions in
655 neotropical sigmodontinae (rodentia, cricetidae). Ecology and Evolution 11:18676–18690.
656 Martin, B. S., G. S. Bradburd, L. J. Harmon, and M. G. Weber. 2022. Modeling the evolution
657 of rates of continuous trait evolution. Systematic Biology 72:590–605.
658 Mayfield, M. M., and J. M. Levine. 2010. Opposing effects of competitive exclusion on the
659 phylogenetic structure of communities. Ecology Letters 13:1085–1093.
660 McArdle, B. H., and M. J. Anderson. 2001. FITTING MULTIVARIATE MODELS TO

661 COMMUNITY DATA: A COMMENT ON DISTANCE-BASED REDUNDANCY ANALYSIS.
662 Ecology 82:290–297.
663 McPeek, M. A. 2017a. The ecological dynamics of natural selection: Traits and the coevolution
664 of community structure. The American Naturalist 189:E91–E117.
665 McPeek, M. A. 2017b. Evolutionary community ecology. Princeton University Press.
666 Messier, J., B. J. McGill, and M. J. Lechowicz. 2010. How do traits vary across ecological scales?
667 A case for trait-based ecology. Ecology Letters 13:838–848.
668 Mislan, K. A. S., J. M. Heer, and E. P. White. 2016. Elevating the status of code in ecology.
669 Trends in Ecology & Evolution 31:4–7.
670 Mittelbach, G. G., and D. W. Schemske. 2015. Ecological and evolutionary perspectives on
671 community assembly. Trends in Ecology & Evolution 30:241–247.
672 Morlon, H., E. Lewitus, F. L. Condamine, M. Manceau, J. Clavel, and J. Drury. 2016. RPANDA:
673 An R package for macroevolutionary analyses on phylogenetic trees. Methods in Ecology and
674 Evolution 7:589–597.
675 Morris, T. P., I. R. White, and M. J. Crowther. 2019. Using simulation studies to evaluate
676 statistical methods. Statistics in Medicine 38:2074–2102.
677 Münkemüller, T., L. Gallien, L. J. Pollock, C. Barros, M. Carboni, L. Chalmandrier, F. Mazel,
678 K. Mokany, C. Roquet, J. Smyčka, M. V. Talluto, and W. Thuiller. 2020. Dos and don'ts
679 when inferring assembly rules from diversity patterns. Global Ecology and Biogeography
680 29:1212–1229.
681 Nakamura, G., A. V. Rodrigues, A. L. Luza, R. Maestri, V. Debastiani, and L. Duarte. 2023.
682 Herodotools: An r package to integrate macroevolution, biogeography and community ecology.
683 Journal of Biogeography 51:533–543.
684 Oksanen, J., G. L. Simpson, F. G. Blanchet, R. Kindt, P. Legendre, P. R. Minchin, R. B. O'Hara,
685 P. Solymos, M. H. H. Stevens, E. Szoecs, H. Wagner, M. Bedward, B. Bolker, D. Borcard,
686 G. Carvalho, M. De Caceres, S. Durand, H. B. A. Evangelista, G. Hannigan, M. O. Hill, L.
687 Lahti, C. Martino, M.-H. Ouellette, E. Ribeiro Cunha, T. Smith, A. Stier, C. J. F. Ter Braak,
688 and J. Weedon. 2026. Vegan: Community ecology package.
689 Overcast, I., M. Ruffley, J. Rosindell, L. Harmon, P. A. V. Borges, B. C. Emerson, R. S. Etienne,
690 R. Gillespie, H. Krehenwinkel, D. L. Mahler, F. Massol, C. E. Parent, J. Patiño, B. Peter,
691 B. Week, C. Wagner, M. J. Hickerson, and A. Rominger. 2021. A unified model of species
692 abundance, genetic diversity, and functional diversity reveals the mechanisms structuring
693 ecological communities. Molecular Ecology Resources 21:2782–2800.
694 Pakeman, R. J., and H. M. Quested. 2007. Sampling plant functional traits: What proportion of

the species need to be measured? Applied Vegetation Science 10:91–96.

Paradis, E., and K. Schliep. 2019. Ape 5.0: An environment for modern phylogenetics and evolutionary analyses in r. Bioinformatics 35:526–528.

Peres-Neto, P. R., and S. W. Kembel. 2015. Phylogenetic gradient analysis: Environmental drivers of phylogenetic variation across ecological communities. Plant Ecology 216:709–724.

Peres-Neto, P. R., P. Legendre, S. Dray, and D. Borcard. 2006. VARIATION PARTITIONING OF SPECIES DATA MATRICES: ESTIMATION AND COMPARISON OF FRACTIONS. Ecology 87:2614–2625.

Peres-Neto, P. R., M. A. Leibold, and S. Dray. 2012. Assessing the effects of spatial contingency and environmental filtering on metacommunity phylogenetics. Ecology 93.

Pigot, A. L., and R. S. Etienne. 2015. A new dynamic null model for phylogenetic community structure. Ecology Letters 18:153–163.

Pillar, V. D., and L. d. S. Duarte. 2010. A framework for metacommunity analysis of phylogenetic structure. Ecology Letters 13:587–596.

Pontarp, M., L. Bunnefeld, J. S. Cabral, R. S. Etienne, S. A. Fritz, R. Gillespie, C. H. Graham, O. Hagen, F. Hartig, S. Huang, R. Jansson, O. Maliet, T. Münkemüller, L. Pellissier, T. F. Rangel, D. Storch, T. Wiegand, and A. H. Hurlbert. 2019. The latitudinal diversity gradient: Novel understanding through mechanistic eco-evolutionary models. Trends in Ecology & Evolution 34:211–223.

Provete, D. B. 2026a. comdynamite: Linking traits, phylogenies and biogeography in metacommunities. All versions, Zenodo.

Provete, D. B. 2026b. comdynamite: Linking traits, phylogenies and biogeography in metacommunities. Version 0.7.0, Zenodo.

R Core Team. 2026. R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria.

Rabosky, D. L. 2014. Automatic detection of key innovations, rate shifts, and diversity-dependence on phylogenetic trees. PLoS ONE 9:e89543.

Revell, L. J. 2012. Phytools: An r package for phylogenetic comparative biology (and other things). Methods in Ecology and Evolution 3:217–223.

Revell, L. J. 2021. A variable-rate quantitative trait evolution model using penalized-likelihood. PeerJ 9:e11997.

Revell, L. J. 2024. Phytools 2.0: An updated r ecosystem for phylogenetic comparative methods (and other things). PeerJ 12:e16505.

Revell, L. J., K. P. Schliep, D. L. Mahler, and T. Ingram. 2024. Testing for heterogeneous rates

of discrete character evolution on phylogenies. Journal of Evolutionary Biology 37:1591–1602.

Siefert, A., C. Violle, L. Chalmandrier, C. H. Albert, A. Taudiere, A. Fajardo, L. W. Aarssen, C. Baraloto, M. B. Carlucci, M. V. Cianciaruso, V. de L. Dantas, F. de Bello, L. D. S. Duarte, C. R. Fonseca, G. T. Freschet, S. Gaucherand, N. Gross, K. Hikosaka, B. Jackson, V. Jung, C. Kamiyama, M. Katabuchi, S. W. Kembel, E. Kichenin, N. J. B. Kraft, A. Lagerström, Y. L. Bagousse-Pinguet, Y. Li, N. Mason, J. Messier, T. Nakashizuka, J. McC. Overton, D. A. Peltzer, I. M. Pérez-Ramos, V. D. Pillar, H. C. Prentice, S. Richardson, T. Sasaki, B. S. Schamp, C. Schöb, B. Shipley, M. Sundqvist, M. T. Sykes, M. Vandewalle, and D. A. Wardle. 2015. A global meta-analysis of the relative extent of intraspecific trait variation in plant communities. Ecology Letters 18:1406–1419.

Taudiere, A., and C. Violle. 2015. Cati: An r package using functional traits to detect and quantify multi-level community assembly processes. Ecography 39:699–708.

Thompson, P. L. 2020. Plthompson/meta_com_framework: v1.0 meta_com_framework code. Zenodo.

Thompson, P. L., L. M. Guzman, L. De Meester, Z. Horváth, R. Ptacnik, B. Vanschoenwinkel, D. S. Viana, and J. M. Chase. 2020. A process-based metacommunity framework linking local and regional scale community ecology. Ecology Letters 23:1314–1329.

Tikhonov, G., Ø. H. Opedal, N. Abrego, A. Lehikoinen, M. M. J. de Jonge, J. Oksanen, and O. Ovaskainen. 2020. Joint species distribution modelling with the R-package Hmsc. Methods in Ecology and Evolution 11:442–447.

Urban, M. C., and L. De Meester. 2009. Community monopolization: Local adaptation enhances priority effects in an evolving metacommunity. Proceedings of the Royal Society B: Biological Sciences 276:4129–4138.

Urban, M., M. Leibold, P. Amarasekare, L. De Meester, R. Gomulkiewicz, M. Hochberg, C. Klausmeier, N. Loeuille, C. de Mazancourt, J. Norberg, and others. 2008. The evolutionary ecology of metacommunities. Trends in Ecology & Evolution 23:311–317.

Violle, C., B. J. Enquist, B. J. McGill, L. Jiang, C. H. Albert, C. Hulshof, V. Jung, and J. Messier. 2012. The return of the variance: Intraspecific variability in community ecology. Trends in Ecology & Evolution 27:244–252.

Wagner, H. H., and S. Dray. 2015. Generating spatially constrained null models for irregularly spaced data using Moran spectral randomization methods. Methods in Ecology and Evolution 6:1169–1178.

Wallace, B. C., M. J. Lajeunesse, G. Dietz, I. J. Dahabreh, T. A. Trikalinos, C. H. Schmid, and J. Gurevitch. 2017. OpenMEE: Intuitive, open-source software for meta-analysis in ecology

763 and evolutionary biology. Methods in Ecology and Evolution 8:941–947.
764 Webb, C. O., D. D. Ackerly, M. A. McPeek, and M. J. Donoghue. 2002. Phylogenies and
765 community ecology. Annual Review of Ecology and Systematics 33:475–505.
766 Zurell, D., U. Berger, J. S. Cabral, F. Jeltsch, C. N. Meynard, T. Münkemüller, N. Nehrbass,
767 J. Pagel, B. Reineking, B. Schröder, and V. Grimm. 2010. The virtual ecologist approach:
768 Simulating data and observers. Oikos 119:622–635.