

a1

December 8, 2022

1 Task A1 - Initial access - (Log analysis) Points: 10

1.1 Problem Statement

We believe that the attacker may have gained access to the victim's network by phishing a legitimate users credentials and connecting over the company's VPN. The FBI has obtained a copy of the company's VPN server log for the week in which the attack took place. Do any of the user accounts show unusual behavior which might indicate their credentials have been compromised? Note that all IP addresses have been anonymized. Enter the username which shows signs of a possible compromise.

Given VPN logs, we need to return a username who is seemingly malicious. First, use Python to analyze the given file `data/vpn.log`.

```
[1]: import pandas as pd
      from datetime import datetime, timedelta
      import warnings
      warnings.filterwarnings('ignore')
```

```
[2]: df = pd.read_csv("data/a1/vpn.log")
      df.head()
```

```
[2]:
```

	Node	Username	Start Time	Duration	Service	\
0	openvpn-server	Doris.X	2022.06.27 07:48:08 EDT	37494.0	VPN	
1	openvpn-server	Kelly.G	2022.06.27 08:15:32 EDT	32314.0	VPN	
2	openvpn-server	Dorothy.D	2022.06.27 08:43:39 EDT	18184.0	VPN	
3	openvpn-server	James.V	2022.06.27 08:54:02 EDT	2266.0	VPN	
4	openvpn-server	Joan.P	2022.06.27 09:28:35 EDT	20074.0	VPN	

	Active	Auth	Real Ip	Vpn Ip	Proto	Port	Bytes	Total	Error
0	0	1	172.28.168.133	10.128.20.108	UDP	1194	2.030863e+09		NaN
1	0	1	172.19.185.189	10.128.20.194	UDP	1194	2.363123e+09		NaN
2	0	1	172.22.90.19	10.128.20.43	UDP	1194	2.009805e+09		NaN
3	0	1	172.25.206.19	10.128.20.78	UDP	1194	1.379042e+08		NaN
4	0	1	172.23.234.95	10.128.20.106	UDP	1194	1.318902e+09		NaN

This result shows `data/vpn.log`'s columns. Some of the tables seem useless in terms of analysis, so let's remove them.

```
[3]: df = df.drop(columns=["Node", "Service", "Active", "Proto", "Port", "Error"])
```

After this procedure, use Start Time and Duration to create a new column. This column name should be End Time opposition to Start Time.

```
[4]: from dateutil import parser
df[["Duration"]] = df[["Duration"]].fillna(value=0)
df['Start Time'] = pd.to_datetime(df['Start Time'])
df["Duration"] = df["Duration"].apply(lambda x: timedelta(0, x))
end_time = df["Start Time"] + df["Duration"]
df.insert(2, "End Time", end_time)
```

Let's check Start Time and End Time. Assume you were an attacker, what do you do to deceive data? You may want to use VPN from multiple computers. See if there is an overlap between them.

```
[5]: df = df.sort_values("Username")
usernames = df["Username"].unique()
suspect = []
for user in usernames:
    user_rows = df[df["Username"] == user]
    intervals = []
    for i, row in user_rows.iterrows():
        start_time = row["Start Time"]
        end_time = row["End Time"]
        real_ip = row["Real Ip"]
        intervals.append((start_time, end_time, real_ip))
    intervals.sort()
    # see if there is an overlap in intervals
    is_suspicious = False
    for i in range(1, len(intervals)):
        prev_left, prev_right, prev_ip = intervals[i - 1]
        cur_left, cur_right, cur_ip = intervals[i]
        if prev_left <= cur_left <= prev_right and prev_ip != cur_ip:
            is_suspicious = True
    if is_suspicious:
        suspect.append((user, prev_ip, cur_ip))
        break
print(suspect)
```

```
[('Moses.K', '172.30.122.56', '172.27.26.101')]
```

Yes! We've found a suspicious user that has an overlap in accessing. He seems to have enter VPN using two different IPs at the same time.

