



Authentication **Auth**orization

Eirini Degkleri

Authentication - Authorization



Authentication: Who is the user?

- Allows the user to access a service.

Authorization: What is the role of the user?

- Determines what the user is allowed to do in that service.

Traditional login



Please login:

How SSO works

User logs in with a single set of credentials to all **connected** applications and services.



Known SSO login examples



You can use your institutional credentials to access:

- Eudoxus
- Eduroam
- ~okeanos
- ATLAS (Internship for Greek higher education students)
- ...

Components of a SSO system




- The **Identity Provider (IdP)** is responsible for user authentication and providing user information to the Service Provider (SP).
- The **Service Provider (SP)** is responsible for protecting an online resource and consuming information from the Identity Provider (IdP).
- The **Discovery Service (DS)** helps the Service Provider (SP) discover the user's Identity Provider (IdP).

Architecture of a SSO system

Security Assertion Markup Language (SAML) is SSO login standard.

Img location: <https://hungreyweasel.wordpress.com/saml-ssos-shibboleth-sp-reverse-proxy/>



Architecture of a SSO system

oceanos dashboard

In practice:

Step 1:

User tries to access:
~oceanos



LOGIN

[Sign up](#)

If you are a student, professor or researcher you can login using your academic account.

ACADEMIC LOGIN



LOGIN using

ACADEMIC
ACCOUNT

CLASSIC
ACCOUNT

Architecture of a SSO system



AAI Federation for the Ministry of Education
Authentication & Authorization Infrastructure

In practice:

You were redirected to this page because you tried to access a service that participates in DELOS Federation. In order to proceed, you have to select your Home Organization from the list below. You may save your selection, in order to avoid this question during future access attempts.

Step 2:

User chooses his
home institution

National and Kapodistrian University of Athens

Universities

International Hellenic University

National Technical University of Athens

National and Kapodistrian University of Athens

University of Ioannina

Technological educational institutes

Alexander Technological Educational Institute of Thessaloniki

Confirm

Architecture of a SSO system

In practice:

Step 3:

User is redirected
to his home
institution to login



Architecture of a SSO system

In practice:

Step 4:

User is logged in to
~okeanos, with his
home institution
credentials.

Success!

Logged in successfully, using Academic login.

X

Overview

Profile


API access

Usage


Projects

Contact

Pithos is the File Storage service. Click to start uploading and managing your files on the cloud.



Cyclades is the Compute and Network Service. Click to start creating Virtual Machines and connect them to arbitrary Networks.



Access the dashboard from the top right corner of your screen. Here you can manage your profile, see the usage of your resources and manage projects to share virtual resources with colleagues.

username@synnefo.org

What about my role? | Authorization



After login visit: <https://accounts.oceanos.grnet.gr/Shibboleth.sso/Session>

Miscellaneous

Session Expiration (barring inactivity): 473 minute(s)

SSO Protocol: urn:oasis:names:tc:SAML:2.0:protocol

Identity Provider: <https://login.uoc.gr/idp/shibboleth>

Authentication Time: 2018-05-23T08:43:11.403Z

Attributes

Shib-EP-Affiliation: Student@uoc.gr

Shib-EP-Entitlement:

Shib-EP-PrimaryAffiliation: Student

Shib-Person-commonName: EIRINI-AIKATERINI DEGKLERI

eppn: <username>@csd.uoc.gr

mail: <username>@csd.uoc.gr

Questions?



Internal Pentesting @ GRNET

Linos Giannopoulos

Some bits of theory



Whitebox Testing:

- Access to internal information about the application (e.g. source code, network architecture)
- Deep and thorough
- Time can be wasted if you don't know what you're looking for during code review

Blackbox Testing:

- Performed without any additional information
- Certain scenarios might not be tested
- Simulates a realistic scenario

What should I choose?

- Depends on the scenario we want to test

Some bits of theory



→ What defines a hacker?

Some bits of theory



Some bits of theory



→ What is/defines a hacker?

- ◆ *A computer hacker is any skilled computer expert that uses their technical knowledge to overcome a problem.*
....someone who, with their technical knowledge, uses bugs or exploits to break into computer systems ~ Wikipedia
- ◆ *Anyone with enough interest and curiosity in learning how things work, how they can break and helping others fix them*
- ◆ **Ethics**

Internal Penetration Tests



- Tested applications:
 - ◆ X: Social media App
 - ◆ Y: E-shop
- Whitebox testing
- Lots of interesting findings

Interesting findings - X



- Exposed password hashes and personal data
 - ◆ Friends' information is available when two people like the same "group"
 - ◆ The API returned too much information while the UI displayed a fraction of it
- Field injection during User registration
 - ◆ The typical User model has several fields (e.g. first_name, age)
 - ◆ The backend would take all user-inserted fields and put them in a User object
 - ◆ A malicious user could inject fields (e.g. is_verified, user_type) into the final User object
- CSV Injection
 - ◆ Administrators can export all users' data into a CSV file
 - ◆ A malicious user can inject CSV formulas instead of valid user data
 - ◆ Lack of sanitization leads to exposure to Phishing, Remote Code Execution, Local File Inclusion etc.
 - Depends on the client software and version (e.g. Microsoft Excel, LibreOffice)

Interesting findings - Y



- Stored XSS @ unreachable view
 - ◆ A user with low privileges can create a new product with an arbitrary name
 - ◆ An XSS payload can also be inserted as the product's name
 - ◆ All of the views that were reachable through the UI were safe due to proper sanitization
 - ◆ After reviewing the source code, an unreachable view was found that was vulnerable to XSS
- IP-based rate limiting bypass @ Demo account registration
 - ◆ A user can register for a demo account for testing purposes
 - ◆ That endpoint must be rate limited, otherwise an Application-level DDoS would be possible
 - ◆ Due to improper use of X-Forwarded-For Header, a bypass was found
- CSRF @ Demo account registration
 - ◆ Cross-site Request Forgery due to lack of use of CSRF tokens
 - ◆ Combined with the above vulnerability, an Application-level DDoS is possible

Questions?
